

17

2.

No. 659

BOOK 659

4-671

659

FIELD NOTES
GENERAL LAND OFFICE.

Subdivision
of
T.6 S. R. 26 E.

Indexed, Book 658

Township 65 R. 26 E

61

6	5	4	123	3	101	2	80	1
7	8	9	118	10	97	11	75	12
18	17	16	114	15	94	14	71	13
19	20	21	111	22	89	23	66	24
30	29	28	106	27	85	26	62	25
31	32	126	33	104	34	83	35	36

Subdivisions, R. 6. S. R 26. E.

- Chain pits 18X18X12 ins. N.^{4th} S. of Stone
3 ft. dist, and raise a mound
of earth, 3 1/2 ft. base, 1 1/2 ft. High
W. of Cor.
- 42.00 Entire tesota undergrowth, beans. E. & W.
- 45.63 Dry wash, 8 lks. wide, flows S.W.
- 62.43 Trail, beans N.E. & S.W.
- 73.27 Dry wash, 8 lks. wide flows S.S.W.
- 79.90 The Cor. of Secs. 25, 26, 35^{4th} & 36.
Land, level and rolling
Soil, gravelly loam, 2^d rate
Greasewood^{4th} and tesota undergrowth
No timber.

N 0° 1' W. bet. Secs. 25.^{4th} and 26.
over level land. through
scattering undergrowth

- 19.77 Road, beans. N.E. & S.W.
- 28.02 Trail, beans. N.E. & S.W.

Subdivisions.

- | chs. | |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 40.00 | Set a Malpais Stone 14x10x8 ins., 9 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on w. face; and raise a mound of Stone, 2 ft. base, $1\frac{1}{2}$ ft. high, w. of Cor. Pits impracticable. |
| 44.53 | Ascend vertical 6 ft., bears N.E. & S.W. |
| 44.53 | Top. |
| 50.20 | Road from Salomonville to San Juan Mine, bears N.W. & S.E. |
| 55.35 | Old Road, bears E. N.E. & W. S.W. |
| 56.17 | Dry Wash, 12 lks. wide, flows S.W. |
| 59.97 | Old Road, bears E. & W. |
| 78.10 | Trail, bears N.E. & S.W. |
| 79.90 | Trail, bears N.E. & S.W. |
| 80.00 | Set a Malpais Stone 16x12x6 ins. 11 ins. in the ground, for Cor. of Secs. 23. 24. 25 ^{and} 26, marked, |

T. C. S. R. 26. E.

Chains T. C. S. on N.E., and
 R. 26. E. on S.E. faces; with 2 matches
 on S. and 1 match on E. edges, and
 raise a mound of Stone, 2 ft. base,
 1 1/2 ft. high, W. of Cor.
 Pits impracticable. -
 Land, rolling.
 Soil, gravelly loam; 2^d rate
 Mesquite, Greasewood and *Lesota*
 undergrowth. - No timber. -

S 89° 57' E on a random line
 bet. Secs. 24th & 25.

40.00 Set. temp 1/4 Sec. Cor.
 80.06 Intersect E. bdy of Sp. at 7. lks.
 N. of Cor. of Secs. 19, 24, 25 & 30.
 as recently established by me
 and heretofore described,
 Thence I run,

Subdivisions.

- Chains West. on a true line
bet. Secs. 24. ^{and} 25.
over rolling land.
- 12.15 Old Road, bears N.E. & S.W.
- 37.55 Dry Wash, 10 lks. wide, flows S.
- 38.61 Trail, bears N.N.E. & S.S.W.
- 40.03 Set a Malpais Stone, 18x8x6 ins.
12 ins. in the ground, for $\frac{1}{4}$ Sec.
Cor., marked $\frac{1}{4}$ on N. face; and
raise a mound of Stone, 2 ft.
base, $1\frac{1}{2}$ ft. high, N. of Cor.
Pits impracticable; whence
A mesquite 5 ins. diam., bears
S $80\frac{1}{2}^{\circ}$ W 359 lks. dist.
marked $\frac{1}{4}$ S. B.T.
A mesquite 4 ins. diam., bears
S $27\frac{1}{2}^{\circ}$ E 208 lks. dist.;
marked $\frac{1}{4}$ S. B.T. -
- 41.13 Dry Wash, 10 lks. wide flows S.

T. C. S. R. 26. E.

- | | |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| chs.
43.03 | Dry wash, 7 lks. wide, flows S. |
| 46.53 | Dry wash, 7 lks. wide, flows S.W. |
| 48.62 | Dry wash, 8 lks. wide, flows S. |
| 51.88 | Dry wash, 15 lks. wide, flows S.S. E. |
| 55.68 | Dry wash, 10 lks. wide, flows S.S.W. |
| 59.85 | Dry wash, 20 lks. wide, flows S.W. |
| 63.42 | Dry wash, 7 lks. wide, flows S.S.E. |
| 73.06 | Dry wash, 10 lks. wide, flows S. |
| 77.22 | Dry wash, 8 lks. wide, flows S.W. |
| 79.92 | Trail, trans. N.E. & S.W. |
| 80.06 | The Cor. of Secs. 23, 24, 25, and 26.
Land, gently rolling
Soil, sandy; 2 ^d and 3 ^d rate
Scattering mesquite and tesota
undergrowth. No timber. |
| <hr/> | |
| | N ^o 1' W. bet. Secs. 23, and 24,
over rolling land. |
| .65 | Trail, trans. N.E. & S.W. |

Subdivisions.

- | chs. | |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 8.62 | Trail, trans. N.E. $\frac{1}{4}$ S.W. |
| 19.79 | Dry wash, 20 lks. wide, flows S.W. |
| 21.11 | Dry wash, 18 lks. wide, flows S.W. |
| 23.96 | Dry wash, 12 lks. wide, flows S.W. |
| 24.67 | Dry wash, 15 lks. wide, flows S.S.W. |
| 39.23 | A Malpais rock in place 18x18 ins.
12 ins. above ground, for Witness
to $\frac{1}{4}$ Sec. Cor., marked W.C. $\frac{1}{4}$
on W. face; and raise a mound
of stone 2 ft. base. $1\frac{1}{2}$ ft. high,
W. of Cor. Pits impracticable |
| 39.92 | Dry wash, 25 lks. wide, flows S.W. |
| 40.00 | Cor. point falls in wash |
| 41.27 | Dry wash, 18 lks. wide, flows S.S.W. |
| 59.75 | Dry wash, 15 lks. wide, flows S.W. |
| 73.32 | Dry wash, 18 lks. wide, flows S.S.W. |
| 80.00 | A Malpais rock in place 12x12
ins., 4 ins. above ground, for Cor. of
Secs. 13, 14, 23, and 24, marked |

T. 6. S. R. 26. E.

Chains with a cross at exact Cor. point
 and T. 6. S. on N. E. and
 R. 26 E on S. E. ^{faces} with 3 grooves
 S. and 1 groove E. of Cross;
 and raise a mound of stone, 2
 ft. base, 1 1/2 ft. high, W. of Cor.
 Pits impracticable.
 Land, rolling
 Soil, sandy; 2^d and 3^d rate.
 Greasewood, Mesquite, Palo Verde
 and tesota undugrowth.
 No timber.

East on a random line.

bet. Secs. 13. and 24.

40.00 Set. temp 1/4 Sec. Cor.

80.00 Intersect. E. bdy of Tp. 5. Ns.
 N. of Cor. of Secs. 13, 18, 19, & 24
 as recently established by me

Subdivisions.

Chains	and heretofore described, thence I run N 89° 58' W. on a true line bet. Secs. 13. and 24. over rolling mesa land
.95	Dry wash, 15 lks. wide, flows S.S.W.
5.60	Dry wash, 20 lks. wide, flows S. -
7.70	Dry wash, 30 lks. wide, flows S. -
9.15	Dry wash, 30 lks. wide, flows S.
16.20	Dry wash, 40 lks. wide, flows S.
25.60	Dry wash, 10 lks. wide, flows S.
27.23	Dry wash, 15 lks. wide, flows S.
32.97	Dry wash, 8 lks. wide, flows S.
34.00	Dry wash, 10 lks. wide, flows S.
34.72	Dry wash, 15 lks. wide, flows S.
37.40	Dry wash, 8 lks. wide, flows S.
38.35	Dry wash, 8 lks. wide, flows S.
39.63	Dry wash, 10 lks. wide, flows S.S.E.
40.00	Set a Malpais Stone 15 x 10 x 8 ins.

T. 6. S. R. 26. E.

- | | |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chains | 10 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, and raise a mound of Stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of Cor.
Cpito impracticable |
| 40.55 | Dry wash, 10 lks. wide, flows. S. |
| 42.78 | Dry wash, 30 lks. wide, flows. S. |
| 55.74 | Dry wash, 10 lks. wide, flows. S. |
| 59.44 | Dry wash, 9 lks. wide, flows. S. |
| 63.45 | Dry wash, 60 lks. wide, flows. S. |
| 64.00 | Enta mesquite underground,
trans. N. & S. |
| 67.53 | Dry wash, 7 lks. wide, flows. S. S. E. |
| 68.00 | Enta Palo Verde underground
trans. N. & S. |
| 73.90 | Dry wash, 6 lks. wide, flows S. W. |
| 75.80 | Dry wash, 18 lks wide, flows S. S. W. |
| 76.25 | Dry wash, 10 lks. wide, flows. S. |
| 80.00 | The Cor. of Secs. 13. 14. 23 and 24. |

Subdivisions.

- Chains Land, rolling.
Soil, Stony; 2^d and 3^d rate.
Greasewood, Mesquite, tisota
and Acotillo sundugrowth.
No. timber.
-
- No^o 1' W. bet. Secs. 13 & 14.
over rolling land, descend.
.49 Gulch, 100. lks. wide, flows S.W.
17.77 Road, bears N.E. to S.W.
37.00 Descend, bears N.E. to S.W.
40.00 Set a Malpais Stone 20x14x12 ins
15 ins, in the ground. for $\frac{1}{4}$ Sec.
Cor., marked $\frac{1}{4}$ on W. face, and
raise a mound of stone 2 ft
base, $1\frac{1}{2}$ ft high, W. of Cor.
Pits impracticable.
43.00 Enter bottom, bears N.E. to S.W.
43.75 Dry wash, 15 lks. wide, flows S.W.

T. C. S. R. 26. E.

chs.	
43.90	Begin ascent
46.00	Top, trans. N.E. & S.W.
55.00	ascend S. Slope of ridge trans. N.N.E. & S.S.W.
74.00	Top, and along W. Slope. 4 chs. from top of ridge
80.00	A Malpais rock in place 24x20 ins. 12 ins., above ground, for Cor of Secs. 11, 12, 13 & 14 marked a cross at exact Cor. point T. C. S. on N.E. and R 26 E. on S.E., of Cross, with 4 grooves on S. and 1 groove E. Sides of Cross, and raise a mound of Stone, 2 ft. base, 1 1/2 ft. high, W. of Cor. Pits impracticable Land, rolling and mountainous Soil, stony; 3 ^d and 4 th rate

Subdivisions.

Chains Grease wood & Ocotillo undergrowth
 No timber
 Mountainous land 25. chs.

$189^{\circ}58'E.$ on a random line
 bet. Secs. 12nd & 13,

40.00 Set. temp. $\frac{1}{4}$ Sec. Cor.

80.04 Intersect E. bdy. of Tp. 7th
 S. of Cor. of Secs. 7, 12, 13 & 18,
 as recently established by me
 and heretofore described.

Thence I run

$189^{\circ}59'W.$ on a true line
 bet. Secs. 12nd & 13,

Over Mountainous land

5.80 Begin descent, bears N. & S.

6.00 Gulch, 30 lbs. wide, flows S.

6.50 Begin ascent

7.50 Top, bears N. & S.

T. 6. S. R. 26. E.

chs.	
8.20	Old Road, bears N.E. and S.W.
11.12	Road, bears N.E. & S.W.
36.00	Begin descent, bears N.E. & S.W.
38.50	Enter bottom
39.00	Dry Wash, 100 lks. wide, flows S.W.
40.02	Set a malpais Stone 24x7x7 in., 18 in. in the ground, for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face, & raise a mound of Stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of Cor. Pits impracticable.
43.80	Gulch, flows S.
45.50	Gulch, flows S.
53.90	Gulch, flows S.E.
60.00	Begin ascent, bears N.W. & S.S.W.
76.00	Ridge, bears N.W. & S.S.W. descend
80.04	The Cor. of Secs. 11, 12, 13, & 14 Land, Mountainous. Soil, Stony, 4 th rate.

Subdivisions.

Chains Scattering Greasewood & mesquite
No timber.

Mountainous land 20. chs.

February 3, 1896

February 4. at 7.30^{h} $^{\text{m}}$ a.m. l.m.t
I set off $32^{\circ}55'$ on the lat. arc,
 $16^{\circ}12'$ s. on the decl. arc, and
determine a true meridian
with the Solar, at the Cor.
of Secs. 11, 12, 13. ^{and} 14.

Thence I run

$N0^{\circ}1'W$, bet. Secs. 11. ^{and} 12.

over Mountainous land, descend

- 25.00 Enter bottom, Drains NNE. & S.S.W.
25.18 Dry Wash, 25 lks. wide, flows. S.S.W.
35.55 Road, Drains, NE. & S.W.
40.00 A Malpais rock, in place
24x16 ins, 6 ins above ground,

T. C. S. R. 26. E.

- chain for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, and raise a mound of Stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of Cor. It's impracticable.
- 41.00 Dry Wash, 12 lks. wide, flows. S.W.
- 56.95 Gulch, 50 lks. wide, flows. S.W.
- 63.00 Dry Wash, 12 lks. wide, flows. S.W.
- 63.50 Old Road, trans. N.E. & S.W.
- 64.65 Dry Wash, 10 lks. wide, flows. S.W.
- 78.40 Gulch, 25 lks. wide, flows. S.W. by W. and ascend,
- 80.00 Set a Malpais Stone 16x7x7 in. 11 in. in the ground, for Cor. of Secs. 1, 2, 11 and 12., marked T. C. S. on N.E.
- R. 26. E. on S.E. face, with 5 notches on S. and 1 notch on E. edges; and raise a mound of Stone 2 ft. base, $1\frac{1}{2}$ ft. high

Subdivisions.

Chains N. of Cor. Spits impracticable
 Land Mountainous
 Soil, Stony, 3^d & 4th rate.
 Ocotillo, undergrowth.
 No timber.
 Mountainous land 80. chs.

N 89° 59' E on a random line
 bet. Secs. 1st & 12.

40.00 Set temp. 1/4 Sec. Cor.

80.02 Intersect E. body of Sp. 5 lks.

N. of Cor. of Secs. 1, 6, 7th & 12.

as recently established by me
 and heretofore described,

Thence I run

N 89° 59' W on a true line
 bet. Secs. 1st & 12.

Over Mountainous land; about
 S. Slope of mountain.

T. 6. S. R. 26. E.

chs.	
8.00	Top, bears N. & S.
8.26	Descend
8.54	Enter bottom, bears N. & S.
9.00	Dry wash, 25 lbs. wide, flows S.
9.45	Begin ascent.
10.50	Top, bears N. & S.
20.50	Begin descent
23.50	Enter bottom, bears N. & S.
24.50	Begin ascent.
30.00	Top, bears N. & S.
30.50	Descend
36.60	Enter bottom, bears N. & S.
38.00	Begin ascent, bears N. & S.
40.01	Set a mark pair 20 x 8 x 5 ins, 15 ins, in the ground, for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face, and raise a mound of stone 2 ft, base, $1\frac{1}{2}$ ft. high, N. of Cor. Pit is impracticable.
45.41	Mining shaft, bears N $31\frac{1}{2}$ W. 10 chs. dist

Subdivisions.

chs. 45.50	Top, trans. N.T.S. 5 prospect holes, bear S 54° W. about 10 chs. dist.
46.00	Begin descent, trans, N.T.S.
48.03	Trail, trans N.T.S.
48.50	Shaft, trans. S. 150 lbs. dist.
55.00	Enter bottom, trans. N.T.S. ² / ₃ gold Furnace, trans S. 1 ch. dist, ascend
59.00	Top, trans. N.T.S. and descend
66.00	Enter bottom, trans. N.T.S.
67.50	Begin ascent.
73.00	ascend, abruptly
77.00	Top, trans. N.T.S. and descend
80.02	The Cor. of Secs. 1, 2, 11 & 12 Land, Mountainous Soil, Stony 4 th rate. Ocotillo & Palo Verde undergrowth No timber. Mountainous land. 80.02 chs.

P. C. S. R. 26. E.

- Chains N 0° 1' W. bet. Recs. 1st & 2.
- Over mountainous land, descend
- 2.87 Enter bottom, dry wash 8 lks.
wide flows, W. and ascend
- 6.42 Tap, bears. E. N. E. + W. S. W., descend
- 13.02 Enter bottom, dry wash 10 lks,
wide, flows S. S. W. & ascend
- 13.42 Tap, bears, N. N. E. + S. S. W., descend
- 15.20 Enter bottom, dry wash 8 lks.
wide, flows. S. W., ascend
- 20.72 Tap, bears. N. E. + S. W., descend
- 37.72 Set a malpais stone 20 x 10 x 6 ins.
15 ins. in the ground, for witness
to 1/4 Sec. Cor., marked ^{W.C.} 1/4 on
W. face; and raise a mound
of stone, 2 ft. base, 1 1/2 ft. high,
W. of Cor. pits impracticable.
Whence A mesquite 5 ins. diam, bears
N 84 3/4° W 206 lks. dist.

Subdivisions.

- | | |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| chains | Marked $\frac{1}{4}$ S. W. C. B. I.
A Mesquite 5 ins. diam., bears
N 24° E. 109 lks., dist.
Marked $\frac{1}{4}$ S. W. C. B. I. - |
| 38.22 | Entire dry wash. |
| 40.00 | Cor. point in wash |
| 41.87 | leave dry wash, flows. S. S. W. |
| 45.96 | Initial Monument of the
Granger Mining Claim, bears.
W. 1. chs. dist.; Shaft. bears.
W. 2. chs. dist. |
| 50.77 | Dry wash, 10 lks. wide, flows. S. S. W. |
| 51.20 | Begin ascent, bears. N. N. E. & S. S. W. |
| 64.77 | Top, bears. N. N. E. & S. S. W. |
| 66.20 | Descend |
| 75.20 | Bottom, bears. N. E. & S. W. ascend, |
| 78.22 | Intersect First Standard
parallel. S., at 2.90 chs. E.
of Standard $\frac{1}{4}$ Sec. Cor. Sec. |

T. C. S. R. 26. E.

chains 35. as recently established by me, and heretofore described
 Set a Malpais Stone 20x10x8 in
 15 in. in the ground, for Closing
 Cor. of Secs. 1 and 2, marked
 C.C. on S., with 1 groove
 on E. and 5 grooves on W.
 faces, and raise a mound of
 Stone, 2 ft. base, 1 1/2 ft. high
 S. of Cor. ^{pts} impracticable
 Land, mountainous
 Soil, stony, 4th rate.
 Scattering Greasewood and
 ocotillo and dogwood.
 No timber.—
 Mountainous land 78.22 chs.

Subdivisions.

Chains From the Cor. of Secs. 26, 27, 34
and 35. Hereinafore described
I run

S $0^{\circ} 20' E$ on a random line
bet Secs. 34^{and} 35.

40.00 Set temp $\frac{1}{4}$ Sec. Cor.

79.02 Intersect S. body of Sp. 49 lks.
W. of Cor. of Secs. 2, 3, 34, & 35,
as recently re-established by
me, and hereinafore described
Thence I run

N $0^{\circ} 41' W$. on a true line.
bet. Secs. 34^{and} 35.

over level land, and through
undergrowth.

12.40 Begin descent, bears E. & W.

13.00 Enter bottom, and dense
undergrowth; bears E. & W.

13.14 Dry wash, 18 lks wide, flows W.

J. G. S. R. 26. E.

Chs. 16.30	Road, trans E. & W.
16.50	ascend
18.00	Top, Enter mesa, trans E. & W.
20.80	descend
22.00	Enter bottom
26.50	Dry wash, 12 lks. wide, flows. S.W.
37.30	Set a malpais Stone 20x12x7 ins. 15 ins. in the ground for Witness Cor. to 1/4 Sec. Cor., marked W.C. 1/4 on W. face, and raise a mound of Stone, 2 ft. base, 1 1/2 ft. high, W. of Cor. It's impracticable
39.00	Dry wash, 100 lks. wide, flows. S.W.
39.02	Cor. point in wash.
39.55	Road, trans N.E. & S.W.
41.60	leave dense undergrowth, trans. N.E. & S.W.; ascend
44.00	Top, trans. N.E. & S.W.; descend
51.03	Trail, trans. N.E. & S.W.

Subdivisions.

Chs.	
58.58	Entire bottom, dry wash, 10 lks. wide, flows S.W.
66.83	Old Road, bears N.E. & S.W.
75.33	Trail, bears N.E. & S.W.
79.02	The Cor. of Secs. 26, 27, 34 & 35 Land, level & rolling Soil, gravelly loam; 2 ^d rate. Greasewood, tesota & mesquite mudgy growth. No timber. Land covered with dense under- growth 28.60 chains.

N 0° 1' W. bet. Secs. 26. ^{and} 27.
over rolling land

6.58	Trail, bears N.E. & S.W.
17.98	Dry wash, 10 lks. wide, flows S.W.
31.00	Dry wash, 6. lks. wide, flows W.
39.24	Road from Safford to mines, bears N 80° E & S 80° W.

J. G. S. R. 26. E.

- | | |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chs.
40.00 | Set a Malpais Stone 12x12x9 ins.
8 ins. in the ground, for $\frac{1}{4}$ Sec.
Cor., marked $\frac{1}{4}$ on W. face, and
raise a mound of stone, 2 ft. base,
$1\frac{1}{2}$ ft. high W. of Cor. -
Pits impracticable |
| 43.36 | Dry Wash, 45 lks. wide, flows. S.W. |
| 48.80 | Trail, bears N.W. + S.E. |
| 53.87 | Dry Wash, 7 lks. wide, flows. W. |
| 56.10 | Dry Wash, 8 lks. wide, flows. S.W. |
| 72.20 | Dry Wash, 30 lks. wide, flows. S.W. |
| 76.53 | Dry Wash, 10 lks. wide, flows. S.W. |
| 80.00 | Set a Malpais Stone 15x12x8 ins.
10 ins. in the ground, for Cor. of
Secs. 22, 23, 26 and 27, marked
J. G. S. on N.E. and
R. 26 E on S.E. faces, with 2 notches
on S. and E. edges, and raise a
mound of stone, 2 ft. base, $1\frac{1}{2}$ |

Subdivisions.

Chain ft. high, W. of Cor. Pits
 impracticable, whence
 A Tesota 6 ins. diam, bears
 $S 84\frac{1}{4}^{\circ} W$ 295 lks. dist, marked
 T. 6. S. R. 26. E. S. 27. B. S.
 No other trees within limits
 of land rolling.
 Soil, gravelly loam, 2^d rate.
 Mesquite, tesota and Greasewood;
 undergrowth. No timber. -
 February 4. 1896.

February 5. at ^{L m} 7 30. a.m. L.M.T.
 I set off $32^{\circ} 54'$ on the lat. arc.
 $15^{\circ} 54'$ S on the decl. arc, and
 determine a true meridian,
 with the Solar. at. the Cor. of
 Secs. 22. 23. 26 & 27.
 Thence I run
 $S 89^{\circ} 57' E$ on a random line

T. 6 S. R. 26 E.

Chains	bet. Secs. 23 rd & 26.
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.
79.82	Intersect N.T.S. line 14 lks. S. of Cor. of Secs. 23, 24, 25. & 26. Thence I run $S 89^{\circ} 57' W.$ on a true line bet. Secs. 23. ^{4th} & 26.
1.28	Over rolling land, in mudgrowth Dry wash, 10 lks. wide, flows. S.S.W.
4.82	Dry Wash, 10 lks. wide, flows. S.S.W.
10.00	Dry Wash, 10 lks. wide, flows. S.W.
17.60	Dry Wash, 8 lks. wide, flows. S.W.
21.90	Road from Salomonsville to Cotton wood Springs, from. N.W. & S.E.
23.99	Dry wash, 10 lks. wide, flows. S.W.
33.46	Dry Wash, 18 lks. wide, flows. S.S.W.
38.00	Dry Wash, 15 lks. wide, flows. S.S.W.
39.91	Set a Malpais Stone $12 \times 7 \times 7$ ins. 8 ins. in the ground, for $\frac{1}{4}$ Sec.

Subdivisions.

Chains Cor. marked $\frac{1}{4}$ on N. face, and
raise a mound of Stone 2 ft. base,
 $1\frac{1}{2}$ ft. high, N. of Cor.

Pits impracticable

46.32 Dry wash, 10 lks. wide flows, S.S.W. 2

59.90 Dry wash, 20 lks wide, flows S.W. 2

63.82 Dry wash, 14 lks. wide, flows S.S.W., 2

73.34 Dry wash, 8 lks wide, flows S.S.W., 3

75.82 Dry wash, 6 lks. wide, flows. S.W. 3

76.56 Dry wash, 16 lks wide, flows. S.S.W., 3

79.82 The Cor. of Recs. 22. 23. 26. & 27. 4

Land, rolling

Soil, gravelly loam, 2^d rate

Greasewood, mesquite and tesota

undergrowth. No timber. -

N^o 1' W. bet. Recs. 22 and 23. 4

Over rolling land 4

1.66 Dry wash, 16 lks. wide, flows. S.S.W. 5

T. 6. S. R. 26. E.

8.54	Dry wash, 10 lks. wide, flows. S.W.
9.90	Dry wash, 10 lks. wide, flows. S.W.
15.04	Dry Wash, 8 lks. wide, flows. S.W.
19.04	Dry wash, 8 lks. wide, flows. S.W.
3.88	Dry wash, 7 lks wide, flows. S.W.
27.70	Dry wash, 10 lks wide, flows. S.W.
29.78	Trail, trans. N.E. to S.W.
0.87	Dry wash, 8 lks. wide, flows. S.W.
5.30	Dry wash, 9 lks wide, flows. S.W.
8.30	Dry wash, 12 lks. wide, flows. S.W.
40.00	Set a Mulpain Stone 15x13x4 ins. 10 ins, in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; and raise a mound of Stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of Cor. Pits impracticable.
44.75	Dry wash, 8 lks wide, flows. S.W.
49.20	Dry wash, 17 lks. wide, flows. S.W.
54.76	Dry wash, 15 lks. wide, flows. S.W.

Subdivisions.

- ch.
- 60.54 Dry wash, 12 lks. wide, flows. S.W.
- 68.33 Euta Road, from S.W.
- 72.08 Leave Road, bears N.N.E.
- 74.82 Dry wash, 8 lks. wide, flows. S.E.
- 80.00 Set a Mulpain Stone $24 \times 8 \times 8$ ins.
18 ins. in the ground, for Cor. of
Secs. 14, 15, 22 & 23, marked
T. 6. S. on N.E. and
R. 26. E. on S.E. faces, with 3 notches
on the S. and 2 notches on E. edges,
and raise a mound of stone 2 ft.
base, $1\frac{1}{2}$ ft. high, W. of Cor.
Pits impracticable, whence
A Mesquite 6 ins. diam. bears
N $4\frac{3}{4}^{\circ}$ E 371 lks. dist. marked
T. 6. S. R. 26. E. S. 14. B. I.
A Mesquite 7 ins. diam. bears
S $10\frac{3}{4}^{\circ}$ W 141 lks. dist. marked
T. 6. S. R. 26. E. S. 22. B. I.

T. C. S. R. 26. E.

Chains Land, rolling.
Soil, gravelly loam; 2^d rate.
Greasewood, Mesquite and Sesota
undugrowth. No timber.

N 89° 57' E. on a random line
bet. Secs. 14th & 23.

40.00 Ret. temp 1/4 Sec. Cor.

79.94 Intersect N. and S. line 9 lks.
N. of Cor. of Secs. 13, 14, 23, & 24.
Thence I run.

N 89° 59' W on a true line
bet. Secs. 14th & 23.

Over rolling land

1.20 Dry wash, 100 lks. wide, flows S.W.
8.49 Dry wash, 40 lks wide, flows. S.W.
22.60 Dry wash, 18 lks. wide, flows. S.W.
30.33 Road from Solomonville to Carr
Juan mine; bears. N.T.S.

Subdivisions.

- | Chs. | |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 32.80 | Dry wash, 80 lks. wide, flows S.W. |
| 35.85 | Dry wash, 8 lks. wide, flows S.W. |
| 38.00 | Dry Wash, 10 lks. wide, flows S.S.W. |
| 39.97 | Set a malpais Stone 15x12x6 ins.
10 ins. in the ground, for $\frac{1}{4}$ Sec.
Cor. marked $\frac{1}{4}$ on N. face, and
raise a mound of Stone, 2 ft.
base, $1\frac{1}{2}$ ft. high, N. of Cor.
Pito impracticable |
| 44.83 | Dry wash, 12 lks. wide, flows S. |
| 51.97 | Dry wash, 8 lks. wide, flows S.W. |
| 54.41 | Dry wash, 15 lks. wide, flows S.S.W. |
| 67.23 | Dry wash, 25 lks. wide, flows S. |
| 76.25 | Dry wash, 30 lks. wide, flows S. |
| 78.67 | Road from Safford to Minis,
trans N.N.E. + S.S.W. |
| 79.94 | The Cor. of Secs. 14, 15, 22, & 23.
Land ralling
Soil, gravelly loam, 2 ^d rate |

T. C. S. R. 26. E.

Chains Greasewood, Mesquite and Palo Verde
 undugrowth. No. timber.

N^o 1' W bet. Secs. 14th and 15.

Ascending gradually

- 15.60 Dry wash, 15 lks wide, flows S.W.
 32.10 Dry wash, 10 lks wide, flows S.S.W.
 40.00 Set a Malpais Stone 20x12x9 ins.
 - 15 ins. in the ground for $\frac{1}{4}$ Sec.
 Cor., marked $\frac{1}{4}$ on W. face, and
 raise a mound of stone 2 ft.
 base, $1\frac{1}{2}$ ft. high, W. of Cor.
 Pits impracticable
- 44.22 Dry wash, 10 lks. wide, flows S.S.W.
 49.52 Dry wash, 30 lks. wide, flows S.S.W.
 54.00 Same wash, 50 lks. wide, flows S.E.
 59.00 Same wash, 40 lks. wide, flows S.S.W.
 80.00 Set a Malpais Stone 15x12x8 ins.,
 10 ins. in the ground, for Cor. of

Subdivisions.

Chains Secs. 10, 11, 14 & 15, marked
 T. 6. S. on N.E. and
 R. 26. E. on S.E. face, with 4 notches
 on S. and 2 notches on E. edges,
 and raise a mound of Stone 2
 ft. base $1\frac{1}{2}$ ft high W. of Cor.
 Pits impracticable
 Land, rolling
 Soil, gravelly, 3^d & 4th rate
 Greasewood & Ocotillo undergrowth
 No timber.

S $89^{\circ}59'E$. on a random line
 bet. Secs. 11. ^{and} 14.

40.00 Set temp. $\frac{1}{4}$ Sec. Cor.

80.08 Intersect N² of S line. 2 lks.
 S. of Cor. of Secs. 11, 12, 13 & 14.
 Thence I run
 West, on a true line

BOOK 659 96.

T. C. S. R. 26 E.

Chains	Lat. Secs. 11, ^{4th} 14.
	over Mountainous land, descend
9.80	Enter bottom, trans. N. & S.
15.40	Dry wash, 50 lks. wide, flows. S.
34.29	Begin descent
35.70	Enter bottom
35.90	Dry wash, 15 lks. wide, flows. S. & W.
36.74	Begin ascent
37.60	Tap, trans N. N. E. & S. S. W.
38.58	Road from Solomonville to mines, trans. N. & S.
40.04	Set a malpais Stone 18x15x12 ins. 12 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of Cor. Pit's impracticable
43.05	Dry wash, 10 lks wide, flows. S.
44.06	Dry wash, 8 lks wide, flows S.

Subdivisions.

chs.	
47.78	Road, bears N.E. & S.S.W.
57.00	Dry wash, 75 lks. wide, flows S.S.W.
74.85	Dry wash, 15 lks wide, flows. S.S.W.
80.08	The Cor. of Secs. 10. 11. 14 & 15. Land, Mountainous and rolling Soil, gravelly; 3 ^d & 4 th rate Greasewood, Ocotillo & Palo Verde undergrowth. No timber Mountainous land 9.80 chs.

N^o 1' W. bet. Secs. 10. and 11.

Over Mountainous land

26.00	Begin ascent, bears. N.E. & S.W.
36.00	Ridge, bears. N.E. & S.W.
36.40	Begin descent.
40.00	Set a malpais Stone 20x12x6 ins 15 ins. in the ground, for 1/4 Sec Cor., marked 1/4 on W. face, and raise a mound of Stone 2 ft.

T. C. S. R. 26. E.

Chains	base, $1\frac{1}{2}$ ft. high, W. of Cor. Pits impracticable.
42.90	Enter bottom, dry wash 10 lks wide, flows S.W., and ascend
54.00	Ridge, trans. N.E. and S.W., descend
63.80	Enter bottom, dry wash 10 lks wide, flows S.W.
64.00	Begin ascent, trans. N.E. & S.W.
77.00	Ridge, trans. N.E. & S.W., descend
80.00	Set a Malpais Stone $18 \times 12 \times 6$ ins. 12 ins. in the ground, for Cor. of secs. 2, 3, 10 and 11, marked T. C. S. on N.E. and R. 26. E. on S.E. faces, with 5 notches on N. and 2 notches on E. edges, and raise a mound of Stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of Cor. Pits impracticable Land, mountainous

Subdivisions.

Chains Soil, Stony, $1\frac{1}{2}$ rate
 Greasewood and Ocotillo scrub growth
 No. timber
 Mountainous land 54. chs.

East. on a random line
 bet. Secs. 2, ⁹ and 11.

40.00 Set. temp. $\frac{1}{4}$ Sec. Cor.

80.04 Intersect N. and S. line 2 lks. S.
 of Cor. of Secs. 1, 2, 11, & 12
 Thence I run

S 89° 59' W. on a true line
 bet. Secs. 2 and 11.

over mountainous land, descend

3.95 Enter bottom, dry wash 9 lks wide,
 flows. S. and ascend.

7.50 Top, bears N. & S., descend

12.30 Enter bottom, dry wash 10 lks.
 wide, flows. S., and ascend.

T. C. S. R. 26. E.

chs.	
18.20	Tap, bears. N.T.S.; descend
30.00	Entire bottom, dry wash 10 lks. wide, flows. S.
36.62	Road from Salomonville to Manis, bears N.T.S.
39.00	Dry wash, 10 lks. wide flows, S.; ascend
40.02	Set a malpais Stone 24x14x4 ins. 18 ins. in the ground for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face, and raise a mound of Stone, 2 ft. base, $\frac{1}{2}$ ft. high, N. of Cor. Pits impracticable
43.00	Tap, bears. N.T.S.; descend
46.30	Entire bottom, dry wash, 8 lks wide, flows. S.W. and ascend
54.00	Tap, bears. N.E. + S.W.; descend
59.15	Entire bottom, bears. N.E. + S.W.; ascend
62.50	Tap, bears. N.T.S.; descend
69.20	Entire bottom, dry wash 10 lks.

Subdivisions.

chains wide, flows S, and ascend
 77.00 Tap, bears N.E. & S.W., descend
 80.04 The Cor of Recs. 2, 3, 10, & 11.
 Land, Mountainous
 Soil, gravelly, 2^d & 3^d rate
 No timber
 Mountainous land 8p. of chs.

N^o 1' W. bet. Recs. 2. ^{and} 3.

Overs Mountainous land descend
 15.50 Entire bottom, dry wash, 10 lks.
 wide, flows S.W. & ascend
 20.50 Tap, bears N.E. & S.W.
 22.00 Begin descent of N.W. Slope to
 Cottonwood Cañon, from N.E. & S.W.
 40.00 Set a malpais Stone 18x7x5 ins.
 12 ins., in the ground, for 1/4 Sec.
 Cor., marked 1/4 on W. face, and
 raise a mound of Stone 2 ft.

T. C. S. R. 26. E.

- | | |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chains | base, $1\frac{1}{2}$ ft. high, W. of cor.
Pits impracticable, whence
A Mesquite 4 ins. diam., bears
N $81\frac{1}{4}^{\circ}$ E 230. lks. dist.,
marked $\frac{1}{4}$ S. B. I. -
A Mesquite 6 ins. diam., bears.
N $82\frac{1}{4}^{\circ}$ W 52 $\frac{1}{2}$ lks. dist.,
marked $\frac{1}{4}$ S. B. I. - |
| 40.25 | Enter bottom, bears. N.E. & S.W. |
| 42.10 | Cottonwood Wash, 50 lks. wide
flows. S.W. |
| 45.37 | Road to Cottonwood Springs, bears.
E.N.E. and W.S.W. |
| 45.50 | Begin ascent. |
| 59.00 | Ridge, bears. N.E. and S.W., descend |
| 65.55 | Enter bottom, dry wash 8 lks. wide
flows. W. and ascend |
| 69.85 | Tap, bears. E. & W., descend |
| 74.25 | Enter bottom, dry wash 8 lks. wide, |

Subdivisions.

chains flows. W., and ascend
 77.50 Top, bears E. & W.
 78.30 Intersect First Standard
 parallel S. at 3.00 chs. E. of
 Standard $\frac{1}{4}$ Sec. Cor. Sec. 34.
 as recently established by me
 and heretofore described
 Set a malpais Stone 18x12x6 ins.
 12 ins. in the ground, for closing
 Cor. of Secs. 2nd & 3rd, marked,
 C.C. on the S., with 2 grooves
 on the E. and 4 grooves on
 W. faces, and raise a mound
 of Stone 2 ft., base $1\frac{1}{2}$ ft., high
 S. of Cor. pits impracticable
 Land, maintains
 Soil, Stony; 3rd and 4th rate
 Greasewood & Ocotillo undergrowth
 No timber.

T. C. S. R. 26. E.

chains Mountainous, land 78.30 chains
February 5, 1896.

February 6 at 7.30^h a.m. l, m, t,
I set off $32^{\circ}53'$ on the lat. arc
 $15^{\circ}38'S$, on the decl. arc, and
determine a true meridian
with the Solar. at the Cor.
of Secs. 27, 28, 33, and 34.
Thence I run

$S 0^{\circ}41'E$ on a random line
bet. Secs. 33, and 34

40.00 Set temp $1/4$ Sec. Cor.

79.17 Intersect S. bdy of Sp. 49 lks.
W. of Cor. of Secs. 3, 4, 33, & 34,
as recently re-established by
me, and heretofore described
Thence I run

$N 1^{\circ}2'W$, on a true line

Subdivisions.

Chain	Lat. Secs. 33. ^{2d} 34.
	Over level land.
4.00	Ascend, bears N.E. & S.W.
10.00	Top, bears N.E. & S.W.
17.50	Trail, bears N.E. & S.W.
20.48	Trail, bears N.E. & S.W.
28.44	Trail, bears N.E. & S.W.
39.17	Set a malpais Stone, 16x8x6 ins. 11 ins. in the ground, for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on W. face, and raise a mound of Stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of Cor. Pits impracticable, Whence a Mesquite 4 ins. diam., bears N6°W 326 lks. dist., marked $\frac{1}{4}$ S. B.S. -
47.17	Gulch, 50 lks. wide, flows N.W. & E.
58.00	Begin descent, bears N.E. & S.W.
63.00	Enter bottom, bears N.E. & S.W.

T. C. S. R. 26. E.

- | | |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| chs. | |
| 64.17 | Dry wash, 10 lks. wide. flows S.W. |
| 64.67 | Begin ascent |
| 64.87 | Top, bears N.E. & S.W.; descend |
| 66.17 | Enter bottom. |
| 66.37 | Dry wash, 40 lks. wide, flows S.W. |
| 76.17 | Dry wash, 200 lks. wide, flows S.S.W. |
| 78.74 | Road, bears E. N.E. ^{and} W. S.W. |
| 79.17 | The Cor of Secs. 27, 28, 33 & 34.
Land, rolling
Soil, gravelly loam; 2 ^d rate
Greewood, mesquite and tesota
Mudngrowth. No timber. |
| | <hr/> |
| | N ^o 2' W. bet. Secs. 27. ^{and} 28. |
| | Over level, and rolling land |
| .20 | Road from Safford to mines,
bears N.E. & S.W. |
| 1.50 | Trail, bears N.E. & S.W. |
| 2.90 | Trail, bears N.E. & S.W. |

Subdivisions.

- | | |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| chs. | |
| 3.80 | Begin ascent, trans. N.E. & S.W. |
| 5.00 | Top, trans. N.E. & S.W. |
| 22.59 | Trail, trans. N.E. & S.W. |
| 33.61 | Dry wash, 10 lks. wide, flows S.W. |
| 35.63 | Trail, trans. N.N.E. & S.S.W. |
| 40.00 | Set a Malpais Stone 14x8x7 ins.
9 ins. in the ground for $\frac{1}{4}$ Sec.
Cor., marked $\frac{1}{4}$ on W. face, and
raise a mound of stone 2
ft. base, $1\frac{1}{2}$ ft. high, W. of Cor.
Pits impracticable. |
| 42.87 | Trail, trans. N.N.E. & S.S.W. |
| 43.85 | Road from Safford to mines,
trans. N.E. & S.W. |
| 44.02 | Dry wash, 15 lks wide, flows W.
then S.W. |
| 46.85 | Dry wash, 10 lks. wide, flows S.W. |
| 55.33 | Dry wash, 10 lks wide, flows S.W. |
| 79.00 | Dry wash, 10 lks. wide, flows S.W. |

T. C. S. R. 26. E.

chs.

- 80.00 Set a Malpais Stone, 15x12x10 ins
10 ins, in the ground for Cor. of
Secs. 21, 22, 27 & 28, marked
T. C. S. on N.E. and
R. 26. E. on S.E. faces, with 2 notches
on S. and 3 notches on E. edges;
and raise a mound of Stone, 2
ft. base, 1 1/2 ft. high, W. of Cor.
Pits impracticable.
Land, level. ^{and} rolling
Soil, gravelly loam, 2^d rate
Greaserwood mesquite and
Desota mudu growth.
No. timber. -

189° 57' E on a random line
bet. secs. 22nd & 27

40.00 Set. temp. 1/4 Sec. Cor.

80.04 Intersect N. ^{2d} & S line of Sec. S.

Subdivisions.

chains of Cor. of Secs. 22, 23, 26 & 27,
Thence I run

189°59'W on a true line
bet. Secs. 22nd & 27.

Over level land

- 2.96 Dry wash, 15 lks wide, flows S.S.W.,
 9.08 Dry wash, 8 lks. wide, flows S.W.,
 11.00 Dry wash, 10 lks. wide, flows S.S.W.,
 17.90 Dry wash, 9 lks. wide, flows. S.W.,
 20.17 Trail, bears N.E. & S.W.,
 24.11 Dry wash, 12 lks. wide, flows. S.W.,
 26.14 Dry wash, 20 lks. wide, flows S.S.E.,
 27.25 Trail, bears. N.E. & S.W.,
 39.63 Dry wash, 10 lks. wide, flows. S.W.,
 40.02 Set a Malpais Stone 15x10x9 ins
 10 ins. in the ground, for $\frac{1}{4}$ Sec.
 Cor., marked $\frac{1}{4}$ on N. face, and
 raise a mound of stone, 2 ft.
 base, $1\frac{1}{2}$ ft high, N. of Cor.

T. G. S. R. 26. E.

Chains	Pits impracticable, whence A Mesquite 5 ins. diam., bears N 38 1/2° W 147 lks. dist., marked, 1/4 S. B. J. A Mesquite, 6 ins. diam., bears S 48° W 135. lks. dist., marked 1/4 S. B. J. -
41.50	Dry wash, 25 lks. wide, flows. S. W.
49.68	Dry wash, 20 lks. wide, flows. S. S. W.
52.77	Trail, bears. N. N. E. & S. S. W.
53.62	Road, bears. N. E. and S. W.
57.33	Dry wash, 9 lks. wide, flows. S.
60.47	Dry wash, 8 lks. wide, flows. S.
63.48	Dry wash, 10 lks. wide, flows S. S. W.
65.68	Dry wash, 10 lks. wide, flows. S.
68.70	Trail, bears. N. N. E. and S. S. W.
69.75	Dry wash, 10 lks. wide, flows. S. W.
80.04	The Cor. of Recs. 21. 22. 27 & 28. Land, level.

Subdivisions.

Chains Soil, gravelly loam; 2^d rate.
Greasewood & Mesquite undergrowth
No. timber. -

N 0° 2' W. bet. Secs. 21. & 22.

Over rolling land

- 8.55 Dry wash, 15 lks. wide, flows S.W.
16.52 Dry wash, 10 lks. wide, flows S.W.
26.18 Dry wash, 12 lks. wide, flows S.S.W.
29.10 Dry wash, 15 lks. wide, flows S.W.
40.00 Set a Malpais Stone 18x8x6 ins.
12 ins. in the ground, for $\frac{1}{4}$ Sec.
Cor., marked $\frac{1}{4}$ on W. face, and
raise a mound of stone, 2 ft.
base, $1\frac{1}{2}$ ft. high, W. of Cor.
Pits impracticable.
46.18 Dry wash, 12 lks. wide, flows S.W.
52.27 Trail, bears N.E. and S.W.
59.48 Dry wash, 20 lks. wide, flows S.W.

T. 6. S. R. 26. E.

- chs.
80.00 Set a marpais Stone, 14x14x5 ins.
9 ins. in the ground, for Cor. of
Secs. 15, 16, 21. ^{and} 22, marked
T. 6. S. on N.E. and
R. 26. E. on S.E. faces, with 3 notches
on S. and E. edges, and raise a
mound of Stone 2 ft. base, 1 1/2
ft. high. W. of Cor. ^{is} impracticable
Land level & rolling. - Soil gravelly
^{2nd rate. Greasewood & mesquite undergrowth}
~~no timber~~
N 89° 59' E on a random line
bet. Secs. 15. ^{and} 22.
- 40.00 Set. temp. 1/4 Sec. Cor.
- 80.02 I returned N. and S. line 4 lks. S.
of Cor. of Secs. 14, 15, 22. & 23.
Thence I run
S 89° 57' W on a true line
bet. Secs. 15. ^{and} 22.
Over rolling land.
- 4.55 Dry wash, 10 lks. wide, flows. S.W.

Subdivisions.

- chs.
- 7.95 Dry wash, 12 lks. wide, flows. S.S.W.
- 12.45 Dry wash, 8 lks. wide, flows. S.W.
- 14.18 Dry wash, 9 lks. wide, flows S.S.W.
- 20.40 Dry wash, 10 lks. wide, flows. S.W.
- 23.82 Dry wash, 12 lks. wide, flows. S.
- 31.50 Dry wash, 10 lks. wide, flows S.
- 31.90 Dry wash, 12 lks. wide, flows. S.E.
- 34.24 Dry wash, 30 lks. wide, flows. S.
- 40.01 Set a malpais stone $18 \times 18 \times 10$ ins,
 12 ins. in the ground, for $\frac{1}{4}$ Sec,
 Cor. marked $\frac{1}{4}$ on N. face, and
 raise a mound of stone 2 ft.
 base, $1\frac{1}{2}$ ft. high, N. of Cor.
 Pit's impracticable, whence
 A mesquite 4 ins. diam, bears
 $N 65\frac{1}{2}^{\circ} W 340$ lks. dist.
 marked $\frac{1}{4}$ S. B. J.
 A mesquite 4 ins. diam, bears
 $S 31\frac{1}{2}^{\circ} W 226$ lks. dist.,

T. C. S. R. 26. E.

- Chain marked, $\frac{1}{4}$ S. B. T. -
- 41.64 Dry wash, 12 lks. wide, flows. S.
- 47.08 Dry wash, 8 lks. wide, flows. S.S.W.
- 51.64 Dry wash, 12 lks. wide, flows. S.S.W.
- 53.68 Dry wash, 15 lks. wide, flows. S.
- 60.70 Dry wash, 12 lks. wide, flows. S.
- 63.05 Dry wash, 10 lks. wide, flows. S.S.E.
- 68.13 Dry wash, 12 lks. wide, flows. S.E.
- 72.09 Trail, cross. N.N.W. and S.S.E.
- 73.80 Dry wash, 20 lks. wide, flows. S.S.W.
- 80.02 The Cor. of Secs. 15. 16. 21. & 22.

Land rolling.

Soil, gravelly, 2^d and 3^d rate.

Greenwood & Mesquite undergrowth.

No. timber. -

N 0° 2' W. bet. Secs. 15. and 16.

Even level, land. ascend gently.

- 2.30 Dry wash, 10 lks wide, flows. S.W.

Subdivisions.

- chs.
 4.03 Dry wash, 16 lks. wide, flows S.S.W.
 39.53 Descend, trans. N.N.E. & S.S.W.
 40.00 Set a malpais, ^{stone} 18 x 12 x 5 ins,
 12 ins. in the ground for $\frac{1}{4}$ Sec
 Cor. marked $\frac{1}{4}$ on W. face, and
 raise a mound of Stone 2
 ft. base, $1\frac{1}{2}$ ft. high, W. of Cor.
 Pits impracticable
 41.00 Enter bottom.
 41.25 Dry wash, 12 lks. wide, flows S.S.W.
 42.80 Same wash, 12 lks. wide, flows S.S.E.
 43.00 ascend
 44.00 Top of bank & descend
 46.00 Enter bottom, trans. N.N.E. & S.S.W.
 49.32 Same wash, 12 lks. wide, flows S.S.W.
 51.24 Same wash, 12 lks. wide, flows S.S.E.
 53.51 Same wash, 12 lks. wide, flows S.S.W.
 54.00 Begin ascent.
 59.50 Top, trans. N.W. and S.E.

T. C. S. R. 26. E.

- chs.
63.00 Gulch, 20 lks. wide, 25 ft. deep,
flows S.E.
- 80.00 Set a Malpais Stone 15x8x6 ins.
10 ins. in the ground, for Cor. of
Secs. 9, 10, 15, and 16, marked
T. C. S. on N.E. and
R. 26. E. on S.E. faces, with 4 notches
on S. and 3 notches on E. edges,
and raise a mound of Stone 2
ft. base, 1 1/2 ft. high W. of Cor.
Pits impracticable.
Land, nearly level.
Soil gravelly 2^d and 3^d rate.
Greasewood & Palo Verde undergrowth
No. timber. -

N 89° 57' E. on a random line
bet. Secs. 10. and 15.

40.00 Set. temp. 1/4 Sec. Cor.

Subdivisions.

- chs.
 80.10 Intersect N. and S. line at
 Cor. of Secs. 10, 11, 14 and 15.
 Thence I run
 S $89^{\circ} 57'$ W. on a true line
 bet. Secs. 10. and 15.
 Over rolling land.
- 24.50 Dry wash, 15 lbs. wide, flows S.
- 40.05 A Malpais rock in place
 14 x 12 ins. 8 ins., above ground
 for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on
 N. face, and raise a mound
 of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
 N. of Cor. pits impracticable
- 47.82 Dry wash, 15 lbs. wide, flows S.
- 59.88 Dry wash, 20 lbs wide, flows S.
- 69.00 descend, bears N. & S.
- 69.48 Enter bottom, dry wash 10 lbs,
 wide, flows S.
- 70.00 ascend, bears N. & S.

T. C. S. R. 26. E.

- chs.
71.00 Sap, beams. N.T.S.
75.39 Dry wash, 10 fms. wide, flows. S.
80.10 The Cor. of Secs. 9, 10, 15, ^{2nd} 16.
Land, rolling.
Soil, gravelly; 3^d rate.
Greasewood & Palo Verde mesquite growth
No timber. —

February 6, 1896.

February 7 at 7.^h 30.^m a.m., l.m.t.,
I set off $32^{\circ} 55'$ on the lat. arc.
 $15^{\circ} 19'$ S. on the decl. arc and
determine a true meridian
with the Solar. at the Cor.
of Secs. 9, 10, 15, & 16.
Thence I run
 $N 0^{\circ} 2' W.$ bet. Secs. 9th and 10.
Over rolling mesa land
19.55 Road from Safford to Cottonwood.

Subdivisions.

- | | |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chains | Springs, bears N.E. and S.W. |
| 35.50 | Descend, bears N.E. & S.W. |
| 36.40 | Enter bottom |
| 36.50 | Dry Wash, 10 lks. wide, flows S.W. |
| 36.65 | Ascend |
| 37.20 | Tap, bears N.E. & S.W. |
| 40.00 | Set a Malpais Stone 18x10x10 ins
12 ins, in the ground. for $\frac{1}{4}$ Sec.
Cor., marked $\frac{1}{4}$ on W. face, &
raise a mound of stone 2 ft.
base. $1\frac{1}{2}$ ft. high W. of Cor.
Pits impracticable |
| 59.00 | Descend, bears N.E. & S.W. |
| 59.80 | Enter bottom, dry wash 10 lks.
wide, flows S.W. |
| 60.00 | ascend |
| 61.05 | Tap, bears N.E. & S.W. |
| 70.53 | Descend, bears N.E. & S.W. |
| 71.30 | Enter bottom. |

T. C. S. R. 26 E.

- chs.
71.35 Dry wash, 9 lks. wide, flows. S.W.
71.60 ascend
72.30 Top, trans N.E. + S.W.
73.53 Descend, trans. N.E. + S.W.
74.28 Enter bottom, dry wash 8 lks wide,
flows. S.W.
74.35 ascend.
76.00 Top, trans N.E. + S.W.
80.00 Set a Malpais Stone 12 x 7 x 6 ins.
8 ins. in the ground. for Cor. of
Secs. 3, 4, 9 and 10, marked
T. C. S. on N.E. and
R. 26. E on S.E. faces, with 5 matches
on N. and 3 matches on E. edges;
and raise a mound of Stone 2
ft. base 1 1/2 ft. high W. of Cor.
Pits impracticable, whence
A Palo Verde 6 ins. diam. trans
N 9 3/4° W 330. lks. dist. marked

Subdivisions.

Chains	T. 6. S. R. 26. E. S. 4. B. 1. - Land, rolling mesa. Soil, gravelly; 2 ^d & 3 ^d rate Palo Verde undergrowth. No timber. -
	<hr/>
	N 89° 57' E on a random line bet. Secs. 3. and 10.
40.00	Set. temp. 1/4 Sec. Cor.
80.12	Intersect N. and S. line 2 lks. S. of Cor. of Secs. 2, 3, 10 and 11. Thence I run S 89° 56' W. on a true line bet. Secs. 3. and 10.
	Over Mountainous land, descend
3.00	Enter bottom
3.20	Dry wash, 20 lks. wide, flow. S.S.W.
5.00	Dry wash, 20 lks. wide, flow. S.S.W. and ascend

D. C. S. R. 26. E.

18.00	Top, trans. N. & S.
24.40	Begin descent, trans. N. & S.
40.06	Set a Malpais Stone 13 x 8 x 8 ins. 9 ins. in the ground. for $\frac{1}{4}$ Sec. Cor, marked $\frac{1}{4}$ on N. face, and raise a mound of stone 2 ft. base. $1\frac{1}{2}$ ft. high, N. of Cor. Pits impracticable.
40.80	Enter bottom, trans. N. & S.
42.50	Dry wash, 80 lbs. wide, flows. S.W.
48.04	Ascend
48.55	Top, trans. N.E. & S.W.
53.03	Road, from Safford to Cottonwood Springs, trans. N.E. & S.W.
67.00	Descend, trans. N.E. & S.W.
72.00	Enter bottom, dry wash. 8 lbs wide, flows. S.W., and ascend
73.20	Top, trans. N.E. & S.W.
80.12	The Cor. of Secs. 3, 4, 9 and 10.

Subdivisions.

Chains Land, mountainous and rolling
 Soil, stony; 3^d and 4th rate.
 Greasewood & Sotillo undergrowth
 No timber.
 Mountainous land 40.80 chs.

N 0° 2' W. bet. Secs. 3^d & 4th.

Over Mountainous land, ascend
 6.23 Road to Cottonwood Springs,
 bears N.E. + S.W.
 9.00 Begin descent, bears N.E. & S.W.
 11.30 Enter bottom
 11.51 Dry wash, 20 lks. wide, flows S.W.
 12.00 Ascend, bears N.E. + S.W.
 13.10 Top, bears N.E. + S.W., descend
 18.40 Dry wash, 10 lks. wide, flows S.W.
 20.34 Begin descent, bears N.E. + S.W.
 21.00 Enter bottom.
 24.80 Dry wash, 50 lks. wide, flows S.W.

BOOK 659 124.

T. 6. S. R. 26. E.

chs.	
25.45	Ascend
26.00	Tap, trans. N.E. & S.W.
28.30	Begin, descent, trans. N.E. & S.W.
28.75	Enter bottom
28.80	Dry wash, 10 Mts. wide, flows. S.W.
30.82	Same wash, 10 Mts. wide, flows. S.E.
32.80	Same wash, 10 Mts. wide, flows. S.W.
33.00	Ascend
37.58	Tap, trans. W.S.W. ^{and} E. N.E. descend
40.00	Set a walpais Stone 15x9x5 ins. 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, and raise a mound of Stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of Cor. Pits impracticable.
44.05	bottom, dry wash 6 Mts. wide, flows W. S.W., and ascend
47.10	Tap, trans N.E. & S.W.
47.50	descend, trans. N.E. & S.W.

Subdivisions, T. C. S. R. 26, E.

chs.	
52.56	Bottom, dry wash, 9 lbs. wide, flows S.W., ascend
58.00	Top, trans. N.E. + S.W., descend
61.40	Bottom, dry wash, 8 lbs. wide, flows W.S.W., ascend
66.50	Top, trans. E. + W.
67.00	Descend
77.42	Dry wash, 6 lbs. wide, flows W.
78.46	Intersect First Standard parallel S. at 2.63 chs. E. of Standard 1/4 Sec. Cor. Sec. 33. as recently established by me, and heretofore described. Set a Malpais Stone 26x12x8 in 19 in, in the ground for closing Cor. of Secs. 3 rd and 4 th , Marked, C.C. on S. with 3 grooves on E. and W. faces, and raise a mound of Stone