

701
701
701

Indexed

No. 701

BOOK 701

Field Notes

BOOK 701

OF THE SURVEY OF THE

Subdivision

-OF- *No. 701*

Township *8 South* Range *25 East*

Gila and Salt River Base and Meridian

ARIZONA.

By *C. H. Wallace* D.S.

Under contract dated *April 26th* 1886.

Survey commenced *Nov. 5th* 1886.

Survey completed *Nov. 11th* 1886.

Book No. 9

701

No. 701

Field Notes,

BOOK 701

of the survey of subdivision of
Township, No. 8 S., Range No. 25 E.
of the
Gila and Salt River, Base and
Meridian,
of
Arizona Territory.

Assurveyed by,

C. H. Wallace,
U.S. Deputy Surveyor.

Under his Contract,

No. 3,

Dated, April 26, 1886.

Survey Commenced, Nov. 5th 1886.

Survey Completed, Nov. 11th, 1886.

Titles And names of Assistants

Frank L. Lewis	Chairman
G. E. Norton	Chairman
A. B. Ford	Axeman
H. H. Hallahan	Axeman
N. E. Mc Bride	Flagman

For Preliminary and Final Oaths,
See Books Nos. 1, 6, 7, 9, 10 and 15.

BOOK 701

Frank L. Lewis, A. B. Ford, Charles E. Norton
 and William E. McBride each bring duly sworn
 for himself and not one for the other depose
 and say that he has assisted C. H. Wallace
 U.S. Deputy Surveyor in surveying a portion
 of T₄ S R 25 E and he knows from personal
 observation that the southwestern portion of the
 same is unurveyable on account of the rough
 nature of the surface

x Frank L. Lewis
 x A B Ford
 C E Norton
 Wm. E. McBride

Subscribed and Sworn to before me
 This 29 day of November A. D 1886 at
 Pileox Arizona Territory

George P. King
 Notary Public



BOOK 701

Index

of Subdivisions of

Township 8 South R. 25 East

Sila and Salt River Base and Meridian

6	57	5	49	4	43	3	32	2	18	1
56		55		47		41		31		16
7	53	8	45	9	40	10	30	11	15	12
52		50		44		39		28		13
18		17		16	37	15	27	14	12	13
					36		26		11	
19		20		21	35	22	25	23	9	24
					33		23		8	
30		29		28		27	22	26	6	25
								21		5
31		32		33		34	19	35	3	36

Subdivision F. S. R. 25 E.

G. & S. R. B & M.

Preliminary to commencing this survey I run North on the East boundary of sec. 36 and at 79.93 chs. I find the cor. to sec. 25, 30, 31 and 36. 8 chs. to the west of my line.

As I had established the south boundary I did not retrace it.

By observation I find ~~here~~ ^{here} the latitude to be $32^{\circ}43'46''$ N.

Survey commenced Nov. 5th 1886.

With a Gurley solar transit.

I begin at the cor. to sec. 1, 2, 35, and 36 which is a stone marked, with 1 notch on E, and 5 notches on W. edges. with mound of stone alongside.

Thence I run,

Subdivision T. 8 S. R. 25 E.

N. T. S. R. B. & M.

North, bet. secs. 35 and 36.

Ta. 13° E.

Over rocky rough ground.

2.20 Small stream of water 5 ^{1/2} wide cross N. E.8.10 Stream of water 10 ^{1/2} wide bears. N. E.

11.60 Wash with sycamores along it to N. E.

40.00 Set a granite stone 18x8x6 ins. 12 ins
in the ground for 1/4 sec. Cor. Marked
1/4 on N. face Raised a Mound of
stone alongside. Rts impracticable
ascending slope.

80.00 Set a granite stone 10x9x4 ins. 7 1/2 ins
in the ground for Cor. to sec.

25, 26, 35 and 36, Marked with 1
Notch on S. and E. edges; raised
a mound of stone alongside
Ground rolling. and rough.

Subdivision F. S. R. 25, E.

Soil, covered with rock, 4th rate,
Cottonwood and sycamore timber along
ravines. Some grass.

East on a random line bet. sec. 25 and 36.
Var. 13° E.

Receding over a gentle slope.

40.00 Set temporary $1/4$ sec. cor.

79.73 Intersect E. boundary line 31^{1/2} lks. S. of
cor. to sec. 25, 30, 31 and 36. which is a
post properly marked, in a mound
of earth with bearing tree.

Armesquite bro. S. 20° W. 50 lks. dist
marked T 88 R 25 E S 36, 13.5.

A Hackberry bro. N. 33° E. 168 lks. dist.
marked T 88 R 26 E S 30 13.5.

A Hackberry bro. N. 66° E. 100 lks. dist.
marked T 88 R 25 E S 30, 13.5.

Antish bro. N. 71° W. 103 lks.
marked S. 88. R 25 E S 25 13.5.

Thence Drive

Subdivision F, S, R, 25 E,

S. $89^{\circ}47'$ N. on a true line bet. sec. 25 and 36.

Var. the same.

39.86

Set a stone $12 \times 9 \times 9$ ins. ^{6 in} $\frac{2}{3}$ in the ground
for $\frac{1}{4}$ sec., cor. Marked $\frac{1}{4}$ on N. face;
raised a mound of stone alongside.

79.73

The cor. to sec. 25, 26, 35 and 36.

Soand, rolling.

Soil, 4th rate.

No timber. Mesquite bushes.

North, bet. sec. 25 and 26.

Var. 130° E.

Over broken land.

9.30

Ascend,

10.30

Ravine. 60 yds. wide cross E.

14.00

Ascend,

15.00

Top of mesa, 100 ft. high.

Superior in F. S. R. 25 E.

- 39.00 Work 10 Mts. wide course N.E.
- 40.00 Set a granite stone. 20x12x7 ins.
 15 in. ~~3/4~~ in the ground. for 14 sec. cor.
 Marked 1/4 in N. face; raised a mound of stone alongside.
- 46.00 Top of hill, 200 ft. high.
- 56.00 Ravine, 8 Mts. wide, course N.E.
- 62.50 Ravine, ^{20' wider} " course N.E.
- 80.00 Set a stone 18x6x5 ins. ^{12 in.} ~~3/4~~ in the ground for con to seas. 23, 24, 25, and 26. Marked with 2 notches on S. and 1 notch on E. edges ^{any pits 18x14x12 in. in cor.} and raised a mound of stone alongside.
- Land, rolling and hilly, surface rocky.
 Soil, 4th rate. Worthless
 No timber.

Subdivision T. 8 S. R. 25 E.

East, on abandoned line bet. sec. 25 & 24,
T. 13° E.

30.00 Over rolling land, granite boulders; brushy
Ravine 110 lks. wide, Course N. E.

40.00 Set temporary 1/4 sec. Cor.

79.90 Intersect E. boundary line 19 lks. S.
of Cor. to sec. 19, 24, 25 and 30,
which is a post properly marked
in a mound of earth, with pits
from which there are coming trees.

At Mesquite tree N. 20° E. 17 lks. dist.
marked T. 8 S. R. 26 E. B. P.

At Mesquite tree N. 70° W. 85 lks. dist.
marked T. 8 S. R. 25 E. B. P. 324
Thence South.

S. 89° 52' N. on a true line bet. sec. 24 & 25
T. 13° E.

Over uneven ground covered with boulders

Subdivision F. & S. R. 25 E.

39.95 Set a granite stone $15 \times 6 \times 6$ ins, ^{10 ins} ~~2 1/2~~
in the ground for $1/4$ sec. Cor. Marked
 $1/4$ on N. face; raised a mound
of stone alongside. It's impracticable

79.90 The Cor. to secs. 23, 24, 25 and 26
land, rolling. Surface covered with rocks.
Soil, worthless.

No timber. Mesquite brush. Some grass.

North, bet. secs. 23 and 24,
Va. 13° E.

Over rough broken land covered
with granite boulders and brush.

15.30 Ravine, ²⁷ Course N. E.

18.00 Wey Creek, 20 ft. wide, Course N. E.

27.00 Ravine, Course N. E.

33.00 Ravine, Course N. E.

Subdivisions T. 8 S. R. 25 E.

- 35.10 Ravine, Course N. E.
- 40.00 Marked a rock in place ^{with a x a exact cor.} ~~at~~
^{and on} W. face $\frac{1}{4}$ for $\frac{1}{4}$ sec. cor size
 18x18 ins. and 18 ins high; raised
 a mound of stone alongside.
- 41.00 Ravine, Course N. E.
- 47.50 Ravine, Course N. E.
- 62.00 Ravine, 25 Ms. wide Course N. E.
- 80.00 Set granite stone 18x6x6 ins. ^{12x12 ins}
 in the ground for Cor. to secs. 13, 14
 23, and 24. Marked with 3 notches
 on S. and 1 notch on E. edges;
 raised a mound of stone alongside.
 At this place ^{at 12 M.} I take
 observation by solar apparatus
 and find the latitude to be, $32^{\circ}47'49''$ N.
 Ground, rough; large boulders over surface.

Subdivision F. S. R. 25 E.

Soil, worthless, Mesquite brush,
 & Few Cottonwoods along ravines.

Eastward random line bet. secs. 13 and 24.
 Val. $123\frac{1}{2}^{\circ}$ E.

Over flat land, heavy Mesquite brush.

40.00 Set temporary $\frac{1}{4}$ sec. Cor.

79.40 Intersect E. boundary line 26 N. S.

of Cor. to secs. 13, 18, 19, and 24, which is
 a post in mound of stone. From
 which.

A Cottonwood bro. N. 21° W. 57 lks, dist.
 marked 598 R 25 E S 13 13.5

A Cottonwood bro. N. 5° W. 76 lks, dist.

B Cottonwood bro. N. 22° E. 40 lks, dist.
 marked 785 R 26 E S 18 13.5

Shiner's run

Set in copy and pass

S. $89^{\circ}49'$ W. water line bet. secs 13 & 24.

Subdivision F.S. P 258

Val. $12\frac{3}{4}^{\circ}$ E.

39.70 Set a stone $14 \times 12 \times 3$ ins, $\frac{2}{3}$ ^{9 ins} in the ground for $\frac{1}{4}$ sec. Cor. Marked $\frac{1}{4}$ in N. face. Raised a mound of stone alongside.

79.40 The Cor. to sees, 13, 14, 23 and 24.
Sand, rolling.
Soil, poor. Covered with boulders.
Use Mesquite brush.

North, bet. sees. 13 and 14,
Val $12\frac{3}{4}$ E.

Over flat rocky ground.

90.00 Ravine Course N.E.

40.00 Marked a rock in place 18 ins. high
 10×24 ins. on N. face $\frac{1}{4}$ for $\frac{1}{4}$ sec.
and made a \times as exact corners
Cor., raised a mound of stone alongside

Subelvisim, F. & S. R. 25 E.

- 49.80 Mesa 400 ft. high.
 52.00 Descend from Mesa.
 63.00 Bottom of Mesa.
 65.00 Ravine, Course N.E.
 80.00 Set a granite stone $18 \times 9 \times 6$ ins. ^{12 ins.}
 in the ground for Cor. to secs. 11, 12
 13, and 14. Marked with 4 notches
 on S. and 1 notch on E. edges.
 dug pits $18 \times 18 \times 12$ ins. in each
 sec. $5\frac{1}{2}$ ft. dia.; raised a mound
 of earth 2 ft. high. $4\frac{1}{2}$ ft. base
 all around.

Land rolling and hilly,

Soil, worthless

No timber, Mesquite brush.

Nov 5th 1886

East, on a round line bet. secs. 12 and 13.

Subdivision T. 8 S. R. 25 E.

Var. 12 $\frac{1}{4}$ ° E

Over. flat brushy ground.

3,00 Ravine, 25 lks. wide, corner N.

17,50 Ravine 20 lks. wide corner N.E.

40,00 Set temporary $\frac{1}{4}$ sec. cor.

79,56 Intersect E. boundary line 33 lks.

S. of Cor. to sec. 7, 12, 13 and 18.

which is a post in mound of earth
with pits. From which

A mesquite tree S. 22° W. 156 lks. dist.

A Mesquite tree S. 87° E. 196 lks. dist.

marked T 8 S R 25 E S 13 13.7
marked T 8 S R 26 E S 18 13.7
Fence Run.

S. 89° 46' W. water line bet. sec. 12 & 13

With the same var.

39.78 Marked a rock in place 18 ins. high 36 x 24

with an exact cor. point and
ins. $\frac{1}{4}$ on N. face for $\frac{1}{4}$ sec. cor.;

Subdivision F. S. R. 25 E.

- 79.56 raised a mound of stone alongside,
 The cont. seed, 11, 12, 13 and 14.
 Good, rolling, Brushy.
 Soil, 4th rate.
 No timber. Some grass.
-
- North, bet. seed, 11 and 12,
 γ a. $12\frac{3}{4}^{\circ}$ E.
 Over low ridges.
- 40.00 Rock in place 24×24 ; 18 ins. high
and x are approx. points
 Marked $\frac{1}{4}$ on N. face, for $\frac{1}{4}$ sec. Cor.
 raised a mound of stone alongside.
- 69.60 Mark 1 Ch. wide, course N.E.
- 77.00 Key creek, with cottonwood, 50 ft wide ^{course} E.
- 80.00 Set a post 4 ft long 4 ins square
 with a marked stone 12 ins. in the ground
 for Cor. to secs. 1, 2, 11, and 12. Aug.

Subdivision F, S, R. 5 E.

pits 18x18x12 ins. in each sec. 5 1/2
 ft. dist. and raised a mound of
 earth around post. 2 ft. high
 4 1/2 ft. base. Post marked,
 F, S, S. 1 on N.E.

R. 25 E. S. 12 on S. E.

S. 11 on S. W. and

S. 2 on N. W. faced with 5 notches
 on S. and 1 notch on E. edges.

Land rolling.

Soil 4th rate.

Timber Cottonwood and ash along ravines.

East on a random line bet. secs. 1 and 12.

Var. 12° E. Over rolling ground.

780 Key Creek, ^{then} down bed of stream

900 Near Creek, Course N. E.

Subdivision T. 8 S. R. 25 E.

- 15.90 Wagon road down ravine bet. N.E. & S.W.
 40.00 Set temporary $\frac{1}{4}$ sec. Cor.
 79.32 Intersect E. boundary line 7th 1/2 N. of
 Cor. to secs. 1, 6, 7, and 12. which is a
 post in mound of earth with pits.
 properly established
 Thurstman,

N. 89° 57' N. on a true line bet. secs. 1 & 12
 at the corner

- 39.86 Set a granite stone 14x8x6 ins. 9 in.
 in the ground for $\frac{1}{4}$ sec. Cor.
 Marked $\frac{1}{4}$ on N. face and
 raised a mound of stone
 alongside.
 79.32 F.W. Cor. to secs. 1, 2, 11 and 12.
 Do and rolling mesa.

Subdivision F.S.R. 24 E.

Soil, 4th rate.

No timber, rocky.

North, on a random line bet. secs. 1 and 2.

Va. 12° E.

Over rolling mesa.

40.00 Set temporary $\frac{1}{4}$ sec. cor.

79.70 Intersect N. boundary line 38 lks.

E. of cor. sec. 1, 2, 35 and 36

which is a post in mound of stone
properly established.

Thence I run,

S. $0^{\circ} 16' E$ on a true line bet. secs. 1 and 2.

Va. the same.

39.70 Set a granite stone $16 \times 16 \times 6$ ins. in
in the ground for $\frac{1}{4}$ sec. cor.

Subdivision F, S. R. 25 E.

79.70

Marked $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 1
a mound of stone alongside

The Cor. to sec. 1, 2, 11 and 12.

Sound, rolling mesa,

Soil, 4th rate.

No timber. Fair grass.

From the cor. to sec. 2, 3, 34 and
35, at S. boundary, which is a large
rock in place. Marked with a X^{at}

and 2 notches E. and 4 notches

N. of cross. Mound of stone alongside
I run,

North, bet. sec. 34 and 35.

Var. 13° E.

Over rough broken hills. surface
covered with large granite boulders.

Subdivision F.S., P 25-E.

- 10.00 Descend steep hill.
- 12.50 Bottom Cañon 200 ft. deep bro. N.E.
ascend.
- 40.00 Set a stone 22 x 7 x 6 ins. ^{16 ins.} ~~3/4~~ in the
ground for $\frac{1}{4}$ sec. Cor. Marked $\frac{1}{4}$
in N. face. Raised a mound of
stone alongside.
- 57.10 Top of hill. Descending into ravine
- 60.50 Ravine, Course E.
- 77.50 Ravine, Course N.E.
- 80.00 Set a stone 18 x 6 x 5 ins. ^{12 ins.} ~~2/3~~ in the
ground for Cor. to sec. 26, 27, 34 and
35. Marked with 1 notch on S.
and 2 notches on E. edges; and
raised a mound of stone alongside.
Soand, rough and hilly; Covered
with large boulders.

No. 701

BOOK 701

Subdivision F, S, R, 25 E 11

Soil, worthless.

No timber. Poor grass.

Eastward round line bet. sec. 26 and 35.

Va. 13° E.

Descending over rocky land.

40.00 Set temporary $\frac{1}{4}$ sec. Cor.

41.40 Ravine 30 Mts. wide bet. N.E.

80.18 Intersect N. and S. line 23 Mts. N. of cor.

to sec. 25, 26, 35, and 36.

Then on run,

N. $89^{\circ}58'$ W. on a true line bet. sec. 26 and 35.

Va. the same.

40.81 Marked a rock in place $36 \times 18 \times 18$

with a xaxexax cor. to hand
in $\frac{1}{4}$ sec. N. face for $\frac{1}{4}$ sec.

Cor; raised a mound of stone

Subdivision F. S. R. 25 E.

alongside.

- 80.18 The Cor. to sec. 26, 27, 34 and 35.
 Good, rolling and rocky.
 Soil, worthless.
 No timber.

North, bet. sec. 26 and 27.
 Va. 13⁰⁰ E.

- 18 Over rough land covered with boulders.
 18.30 Ravine, course N.E.
 40.00 Set a granite stone 18x6x6 ins. ^{12 1/2} in
 in the ground for 1/4 sec. Cor.
 Marked 14 on N. face; raised a
 mound of stone alongside.
 64.50 Creek, water 3 lbs. wide bro. E.
 67.80 Creek, water 5 lbs. wide bro. E.
 80.00 Set a granite stone 18x10x8 ins.

Subdivision T & S, R. 25 E.

12 mi -

~~23~~ mths ground for cr. & seeds,
22, 23, 26, and 27. Marked with
2 notches on S. and E. edges, and
raised a mound of straw along side
to and rough and broken, surface
covered with large boulders
Soil rocky 14th rate

Timber Cottonwood ash, oak and
Sycamores along creek; brushy.

Nov. 6th 1882

East, on a random line bet. sec. 23 and 26.

Va. $12\frac{3}{4}^{\circ}$ E.

Through dense brush. Cut claws and
mesquite, over granite boulders

16.00 Creek 1 ch. wide course N.E.

21.80 Creek 1 ch. wide course N.E. rocky,

31.00 Ravine 60 lbs. wide course N.E.

Subdivision F. & S. R. 25-8

- 40,00 Set temporary $\frac{1}{4}$ sec. cor.
 46,70 Dry wash 20 lbs. wide br. N.E.
 80,15 Intersect N. and S. line 30 lbs. N.
 of Cor. to secs. 23, 24, 25 and 26.
 Fence I run.

N. $89^{\circ}47'$ W. on a true line bet. sec. 23 and 26
 Val. $13^{\circ}E$.

- 40,07 Set a stone $15 \times 10 \times 5$ ins. ^{10 ins.} $\frac{1}{8}$ in the
 ground for $\frac{1}{4}$ sec. cor. Marked
 $\frac{1}{4}$ on N. face. raised a mound of
 stone alongside.

- 80,15 The Cor. to secs. 22, 23, 26 and 27.
 Land, rough and rocky.
 Soil, worthless.
 Cottonwood and Sycamore, along ravine.
 Acacia, Mesquite and Cat. Chew brush.

Subdivision T, 8 S, R, 25-E.

North, bet. sec. 22, and 23.

Va. $12\frac{3}{4}$ E.

Overrolling, rocky ground through brush.

40.00 Set a granite stone $16 \times 11 \times 6$ ins, ^{11 ins.} ~~12~~
in the ground for $\frac{1}{4}$ sec. Cor.Marked $\frac{1}{4}$ on N. face raised a mound of stone alongside.

52.00 Ravine, Course N, E.

77.00 Ravine, 40 lks. wide, Course N, E.

80.00 Marked a rock in place 12 ins. high
 14×14 ins. with a cross (X) ^{at each cor. point} and 3
notches on S. and 2 notches on E
edges. for Cor to sec 14, 15, 22 and
23., and raised a mound of
stone alongside.Land, rolling, dense Mesquite brush.
Soil, rocky, worthless.

Subdivision T.S.D. R 25 E.

East, wa random line bet. secs. 14 and 23,
 Var. $12^{\circ} 3/4^{\circ}$ E.

Over rough broken land.

- 1.00 Ravine, 22 lks. wide 15 ft. deep thro. N.E.
- 12.80 Ravine, 50 lks. wide, course N.
- 27.80 Top of Mesa 20 ft. high.
- 38.90 Descend from Mesa.
- 40.00 Set temporary $1/4$ sec. Cor.
- 43.90 Ravine at foot of slope, course N.E.
- 73.00 Ravine, course N.E.
- 74.70 Ravine, course N.E.
- 80.27 Interest N. and S. line 17 lks. S.
 of Cor. to secs. 13, 14, 23, and 24,
 Thence I run,
 S. $89^{\circ} 53'$ N. w. a true line bet. secs. 14 and 23.
 Var. the same.
- 40.14 Set a stone 18x2x6 ins, $1/2$ in

Subdivision F, S, R, 25 E.

the ground for $\frac{1}{4}$ sec. cor. Marked
 $\frac{1}{4}$ on N. face; raised a mound
 of stone along side.

80.27

The cor. to secs. 14, 15, 22 and 23.

Land. rough and broken.

Soil, rocky and poor.

No timber. Some grass.

North, bet. secs. 15, and 14,
 Va. $12\frac{3}{4}^{\circ}$ E.

Over rocky ground.

1.60

Ravin, to the south 10 ft deep bet. N. 3.

7.45

Ravin, Course N. E.

40.00

Set a granite stone $2.0 \times 8 \times 4$ ins. ^{15 in.} ~~H~~
 in the ground. for $\frac{1}{4}$ sec. cor.

Marked $\frac{1}{4}$ on N. face; raised a
 mound of stone along side.

Subdivision F. S. R. 25-E

- 53.30 Ravine, Course N. E.
 58.70 Ravine, Course N. E.
 59.00 Ravine, Course N. E.
 65.80 Ravine, Course, E.
 80.00 Set a stone $24 \times 8 \times 4$ ins. ^{19 in} $\frac{3}{4}$ in
 the ground for Cont. sec. 10, 11, 14,
 and 15. Marked with 4 notches on
 sand 2 notches on E. edge; raised
 a mound of stone alongside.
 Gravel rolling.
 Soil, rocky and worthless.
 No timber. Mesquite brush.
-

East, on a random line bet. sec. 11 and 14.
 Va. $12\frac{1}{2}^{\circ}$ E.
 Over rolling land.

33.00 Ravine, Course N.

Subdivision F. S. R. 25-E.

- 34.00 Ravine, 65 lks. with course N.
- 40.00 Set temporary $\frac{1}{4}$ sec. cor.
- 80.35 Intersect N. and S. line 10 lks. N.
 of Cor. to sec. 11, 12, 13 and 14.
 Fence 3 run.
 N. $89^{\circ} 56'$ N. on a true line bet. sec. 11 and 14.
 Val. ~~100.00~~
- 40.17 Set a granite stone $10 \times 8 \times 8$ ins. ^{10 in.} ~~7/8~~ in
 the ground for $\frac{1}{4}$ sec. cor. Marked $\frac{1}{4}$
 on N. face; raised a mound of stone
 alongside.
- 80.35 This cor. to sec. 10, 11, 14 and 15.
 Road, rolling surface covered with rocks.
 Soil, 4th rate.
 No timber. Some grass.

Supervisor F. S. R. 25 Co.

North, bet. sees. 10 and 11.

No. 12 $\frac{1}{2}$ E.

Over broken, land covered with boulders.

- 8.00 Ravine, Course E.
- 19.00 Ravine, Course E.
- 40.00 Set a granite stone 15x10x4 ins. ^{10 ins.} ~~7 1/2~~
in the ground for $\frac{1}{4}$ sec. Cor. Marked
 $\frac{1}{4}$ on N. face raised a mound of
stone alongside.
- 63.30 Ravine, 10 kts. wide, Course E.
- 64.70 Ravine 30 kts. wide, Course E.
- 80.00 Set an eggshaped stone 30 ins. long
20 ins. diam. ^{2 2 ins.} $\frac{3}{4}$ in the ground
for. Cor. sees. 2, 3, 10 and 11 Marked
with 5 notches on S. and 2 notches
on E. sides; raised a mound of
stone alongside.

Subdivision T. 8 S. R. 25 E.

Ground rolling,

Soil, 4th rate rocky.

Timber, Cottonwood along ravine.

East, on a random line bet. sec. 2 and 11 ⁺

Va. 12° E.

Ascending slope

40.00 Set temporary 1/4 sec. cor.

80.31 Intersect N. and S. line 15. Sta. N.
of cor. to sec. 1, 2, 11, and 12.

Thence I run

N. 89° 54' W. waste line bet. sec. 2 & 11

Va. the same.

40.15 Set a granite stone 16 x 15 x 3 ins. ~~to~~ ¹¹ ins.
in the ground, marked 1/4 on
N. face; raised a mound of stone
alongside.

Subdivision T. 8 S. R. 25 E.

80,31 The Cor. to secs. 2, 3, 10, and 11.
 Land, Rolling and rocky,
 Soil, worthless
 No timber. Fair grass.
 Nov. 8th 1886.

North, on a random line bet. secs. 2 and 3,
 Va. 12° E.

Over rolling, high mesa, rocky,

40,00 Set temporary 1/4 sec. Cor.

79,44 Intersect N. boundary line 18 N. & E.
 of Cor. to secs. 2, 3, 34 and 35. Which
 is a post in Mineral of stone,
 properly established.

Fence I run,
 S. 0° 8' E. on a true line bet. secs. 2 and 3,
 Va. the same.

39,44 Set a granite stone 16 1/2 x 5 ins. ^{10 in} 2/3

Subdivision T, S, R 25 E.

in the ground for $1/4$ sec. Cor. Marked
 $1/4$ on N. face; raised a mound
 of stones alongside.

79.44 The Cor. to secs. 2, 3, 10, and 11.
 Good, rolling Mesa.

Soil, worthless; Covered with boulders.
 No timber, Fair grass.

The lines from the S. boundary
 bet. secs. 33 and 34, 27 and 28 are
 over precipitous, worthless, rough
 mountains, and impracticable
 to survey. Whence I begin
 at the Cor. to secs. 22, 23, 26,
 and 27, and run.

West, on a true line bet. secs. 22 and 27.

Var. $12\frac{3}{4}^{\circ}$ E.

Subdivision F 88 R 25 E.

Ascending over rocky slope.

40.00 Set a granite stone $24 \times 6 \times 6$ ins. ^{1 1/4} in the ground for $\frac{1}{4}$ sec. Cor. Marked $\frac{1}{4}$ m N. face; raised a mound of stone alongside.

45.40 Ravine 20 lks. wide bro N.E.

80.00 Set a granite stone $19 \times 9 \times 5$ ins. ^{3/4} in the ground for Cor. to secs. 21, 22, 27 and 28. Marked with 2 notches on S. and 3 notches on E. edges, and raised a mound of stone ~~of stone~~ alongside.

Land, rough and surface covered with boulders.

Soil, worthless.

No timber. Fair grass.

Subdivision F.S.R. 25-E

North, bet. sec. 21 and 22.

Va 13° E.

Over rough ridges, and across cotons.

0.00 Top of ridge 300 ft high. br. E. descend

10.00 Marked a rock in place 6' x 6', 5 ft.
with X at each corner ^{1/4} and 1/4
high, on N. face with X and #4 for

1/4 sec. Cor. Raised a mound of
stone alongside

42.20 Ravine 20 lbs wide. br. E.

50.80 Ravine 15 lbs. wide course E.

52.30 Top of ridge 200 ft. high br. E.

57.30 Descend from ridge.

70.00 Top of ridge 800 ft. high, br. E.

Descend.

80.00 Set a granite stone 2.4 x 8 x 5 ins.

19 in. ~~4~~ in the ground. for Cor. to sec. 15.

16, 21 and 22. Marked with 3

Subdivision F.P.S. R. 25 E.

notches on S. and E. edges, and
raised a mound of stone alongside
L. and rough broken hills.

Soil, very rocky. worthless.

No timber. Some grass.

East, on a random line bet. sec. 15 and 22
Va. 13° E.

Over ~~rather~~ slope descending over rocks

- 40.00 Set temporary 1/4 sec. cor.
56.00 Ravine, 30 ft. wide Course N. E.
77.00 Ravine, 30 ft. wide Course N. E.
80.15 Intersect. N. and S. line. 20 ft. S.

of Cor. to sec. 14, 15, 22 and 23.

Thence I run,

S. 89° 51' W. wa. true line bet. sec. 15 and 22

Va. the same.

Subdivision T8S, R. 25E.

40.07 Set a stone $36 \times 24 \times 18$ ^{27 in} ~~14~~ in the ground for. 70 sec. cor. Marked $\frac{1}{4}$ on N. face; raised a mound of stone alongside

80.15 The cor. to sec. 15, 16, 21 and 22. Land rough, hilly, surface covered with piles of huge boulders. Soil, worthless.

No timber, some grass.

North, bet. sec. 15 and 16.

Val 13° E.

Over rough hills.

6.60 Ravine, 60 ft. deep 20 ft. wide bet. E

10.00 Ridge 200 ft. high bet. E.

14.80 Cañon, 100 ft. deep bet. S.E.

16.80 Cañon, Course E.

Subdivision F. & S. R. 25 E.

- 32.00 Ravine, Course E.
- 36.80 Ravine, Course E.
- 40.00 Set a stone $18 \times 8 \times 3$ ins. ^{12 in.} ~~2 1/2~~ in
the ground for $\frac{1}{4}$ sec. \odot Cor. Marked
 $\frac{1}{4}$ on W. face Raised a mound
of stone alongside.
- 62.50 Ravine, Course E.
- 80.00 Set a granite stone $19 \times 9 \times 5$ ins. ^{13 in.} ~~8 1/4~~
in the ground for Cor. to secs. 9,
10, 15, and 16. Marked with 4 notches
on S. and 3 notches on E. edges.
and raised a mound of stone
alongside.

Soil, rough hills, covered with rocks
Soil, Worthless.
No timber. Some grass.

Subdivision F. S. R. 25 E.

East on a random line bet. secs. 10 and 15.

Var. $12\frac{1}{2}^{\circ}$ E.

Ascend over rocky flat.

13.24 Ravine; course N. E. 20 fms. wide.

40.00 Set temporary $\frac{1}{4}$ sec. cor.

79.77 Intersect N. and S. line 24 fms. S.

of Cor. to secs. 10, 14, and 15

Thence I run,

S. $89^{\circ} 50' W$ over true line bet. secs. 10 & 15.

Var. the same

39.88 Set a stone $16 \times 8 \times 4$ ins. ^{11 ins.} ~~2 1/2~~ in

the ground for $\frac{1}{4}$ sec. cor. Marked
"low N. face"; raised a mound
of stone alongside.

79.77 Thence to secs. 9, 10, 15 and 16.

Gravel, rolling,

Soil, worthless. No timber.

Subdivision F.S.R. 25 E

North, bet. secen 9 and 10.

Var. $12\frac{1}{2}^{\circ}$ E.

Over very rough hills, much broken.

21.00 Dry Creek. Cottonwoods along it, 300 yds. wide.
Course N.E.

32.00 Ruins, Course N.E.

40.00 Set a granite stone $16 \times 12 \times 6$ ins.

45.80 Hit the ground for $\frac{1}{4}$ sec. Cor.

57.00 Marked $\frac{1}{4}$ on N. face. Raised
a mound of stone alongside.

40.80 Top of Mesa 200 ft. high.

48.80 Descend from mesa.

59.00 Bottom of Cañon bet. N.E. ascends.

62.00 Top of Mesa 250 ft. high, descend

66.00 Bottom of Cañon, bet. N.E.

69.00 Top of Mesa 200 ft. high.

76.70 Descend from mesa.

Subdivision F.S.R. 25-E.

80.00 Set as granite stave 2.4 X 10 X 6 ins.
 19 in² in the ground for cor. to secs.
 3, 4, 9 and 10. Marked with 5
 notches on S and 3 notches on
 E. edged and raised a mound
 of stone alongside.
 Land, rough broken mesa:
 Covered with rock.
 Soil, worthless.
 Timber, Cottonwood along
 ravines. Fair grass on mesa.
 Nov. 9th 1886

East, on a random line bet. secs. 3 and 10
 Var. 12° E.

2.00 Rescinding over broken hills and ridges
 22.20 Top of mesa 200 ft. high.
 Rescued from mesa.
 34.00 Bottom of Cañon 300 ft. deep, bn. S. E.

Subdivision F. S. R. E. 5 E.

- 40.00 Set temporary 1/4 sec. cor.
- 43.00 Cross same Canon bet. N. E.
- 49.80 Top of ridge 150 ft. high bet. N. and S.
- 62.00 Bottom of hill.
- 64.50 Bottom Canon course N. E.
- 79.87 Intersect N. and S. line 30 N. S. of
cor. to sec. 2, 3, 10, and 11.
Fence Run.
S. 89° 47' N. watch line bet. sec. 3 and 10.
V. the same.
- 39.93 Marked rock in place 15 ins. high
with a cross at each corner ^{point} and
18x18 ins. 1/4 in N. face for 1/4 sec.
Cor. and raised a mound of
stone alongside.
- 79.87 The cor. to sec. 3, 4, 9 and 10.
Grand, rough hills
Soil, rocky, and without timber

Subdivision F. S. R. 5 E

North, on a random line bet. secs. 3 and 4
 Val. 12° E.

Over rough broken ground

470 Bottom, Canon 100 ft. deep bet. N. E.

1680 Top of ridge 100 ft. high, bet. N. E.

26.10 Bottom, of ridge.

27.50 Ravine, Course N. E.

40.00 Set temporary 1/4 sec. Cor.

43.00 Key Mark 24 lbs. with Course N. E.

69.75 Old road bet. E. and N.

79.26 Intersect N. boundary line 22 lbs. E. of
 Cor. to secs. 3, 4, 33 and 34, which
 is a post properly marked with
 a mound of stone around it.

Then I run,

S. 0° 9' E on a true line bet. secs. 3 and 4

39.26 Marked a rock in place 16 in. high

Subdivision T. 8 S, R. 25 E.

with a x at exact corner point and

18x18 ins. $\frac{1}{4}$ in W. face for $\frac{1}{4}$ sec.

Cor. and raised a mound of stone
alongside.

79.26 The Cor. to sec. 3, 4, 9 and 10.

Soil, hard, rough and broken.

Soil, worthless covered with boulders

No timber, scrub oak brush.

Begin at the Cor. to sec. 9, 10, 15 and 16
and thence run,

West on a true line bet. sec. 9 and 16.

Val. $12\frac{1}{2}^{\circ}$ E.

To the south of this line the country
~~is~~ impracticable to survey.

Ascending over piles of granite boulders

40.00 Set a granite stone 14x12x6 ins.

$\frac{2}{3}$ in. the ground for $\frac{1}{4}$ sec. Cor. raised

Subdivision 7, S. R. 25 E.

a mound of stone alongside.

65.00 Creek of water 10 Mo. mile Course N. E.

As creek along North side of creek.

80.00 Set a granite stone $18 \times 8 \times 8$ ins. ^{12 ins} ~~7~~ in
the ground. on S. side of steep hill.

for Cont. sees. 8, 9, 16 and 17. Marked
with 4 notches on S. and E. edges
and raised a mound of stone
alongside.

Land, rough, rolling, covered with
granite boulders.

Soil, Worthless.

Cottonwood, Ash and sycamores along creek.

North. bet. sees. 8 and 9.

Var. 13° E.

Ascending steep hill.

Superiorism, T. S. R. 25, E.

- 3,30 Hitch, Course N.E.
- 4,10 Top of Mesa.
- 24,10 Descend from Mesa into Cañon.
- 32,60 Bottom of Cañon, 200 ft. deep here, N.E.
- 39,70 Top of ridge 150 ft. high here, E.
- 40,00 [✓] Marked a rock in place. 7 ins. high
with a x at exact center point and
10x6 ins. on N. face $\frac{1}{4}$ in. for $\frac{1}{4}$ sec.
over and raised a mound of
stone along side.
- 60,00 Descend from Mesa.
- 76,00 Ravine, Course N.E.
- 80,00 Set a granite stone 24x10x3 ins.
18 ins $\frac{3}{4}$ in the ground for Cor. to Secs.
4, 5, 8, and 9. Marked with 5
notches on S. and 4 notches on
E. edges. Raised a mound of
stone along side.

Subdivision F, S. R. 25 E.

Soil, broken hills.
Soil, rocky and worthless,
Mesquite and Cat claw brush.

East, on a random line bet. sec. 4 and 9
Var. 13° E.

Over rolling, rocky hills.

- | | |
|-------|---|
| 1,30 | Rainy Course N.E., ascend. |
| 8,50 | Top of ridge, course N.E. |
| 18,50 | Rainy, 20 kts. wide course N.E. |
| 19,50 | Ascend. |
| 37,40 | Top Ridge 300 ft. high hrs. N.E., descend |
| 40,00 | Set temporary $\frac{1}{4}$ sec. on bottom of Cañon |
| 40,20 | Cross Rainy, course N.E., and ascend. |
| 46,30 | Top of mesa. |
| 62,20 | Descend from Mesa into Cañon |
| 71,00 | Bottom of Cañon 300 ft. deep and follow. |

Subdivision T. 8 S., R. 25 E.

down the Cañon,

76.00 leave Cañon and ascend to S. E. side.

80.18 Intersect N. and S. line 24 lks.
S. of Cor. to sec. 3, 4, 9 and 10.

Thenew I run.

S. $89^{\circ}50'$ N. on true line bet. sec. 4 and 9.

V. 12° E.

Over rough broken land.

40.09 Set a granite stone $15 \times 12 \times 8$ ins. ^{10 in} ~~7 1/2~~
in the ground for $\frac{1}{4}$ sec. Cor. Marked
14 on N. face; raised a mound of
stone alongside.

80.18 The Cor. to sec. 4, 5, 8 and 9.

Ground, rough, broken places.

Soil, with less spoulders over surface

No timber. Poor grasses.

Subdivision T. 8 S. R. 25 E.

North, wa random line bet. sec. 4 and 5
 Var. 13° E.

Over broken, rough ground.

1.20 Top of mesa, 20 ft. high.

11.80 Cross stream running water, 20 ft. wide.

Course N. E.

15.70 Road from Fry's sawmill to N. E. + S. W.

31.00 Top of ridge 100 ft. high descend.

40.00 Set, temporary 1/4 sec, cor.

79.60 S. corner, N. boundary line, 30 ft. N. of cor. to sec. 4, 5, 32 and 33 which is a granite stone firmly set in the ground marked with 4 notches on East and 2 notches on West edges with word of stone alongside.

Fence Iron.

Subsidiaries F. 88, P. 25 &

S. 0° - 13' N. on a true line bet. sees. 4 and 5.

Var. the same.

39.60 Set a granite stone 18x8x6 ins. ^{12) ins.} ~~78~~ in
the ground for 1/4 cor. Marked
1/4 on N. face and raised a mound
of stone alongside.

79.60 The Cor. to sees. 4, 5, 8 and 9.

Land rough and hilly
Soil, rocky and worthless.
Cottonwood, Ash and sycamore timber -
along creek. Nov. 10th 1886.

From the Cor. to sees. 8, 9, 16 and 17.

Runs

West, on a true line bet. sees. 8 and 17.

Var. 13° E.

To the south of this line the country

Subdivision F. S. R. 25 E.

is high precipitous Mountains
and impracticable to survey.

Ascending, along N. of Creek gaining
water, ^{along} the sides hill,

- 19.57 Hitch leading from Creek Course N. E.
- 25.00 Poppy Mesa, 200 ft. high.
- 40.00 Set a granite stone $18 \times 12 \times 3$ ins. ~~4~~¹²
in the ground for 14 sec. cor.
Marked $\frac{1}{4}$ on N. face; raised a
ring of stone alongside.
- 43.00 Ravine, 100 ft. deep course N. E.
- 45.00 Ravine, 200 ft. deep, course N. E.
and ascend a steep rocky Mountain.
- 80.00 Set a granite stone $30 \times 12 \times 3$ ins.
²³~~34~~ in the ground for Cor. to sec. 1,
7, 8, 17, and 18. Marked with
4 notches on S. and 5 notches on E. edges

Subdivision F.S. R. 5. E.

and raised a mound of stone alongside.
 This cor. is on top of high ridge course N. E.
 and about 800 ft. above last ad. Cor. at
 Grand Mountains.
 Soil, rocky and worthless.
 No timber. Fair grass.

Nest on a random line bet. sec. 7 and 18.
 Va. 13° E.

Over mountainous country,
 descending into Cañon.

22.00 Bottom of Cañon 600 ft. deep bet. N. E.
 ascend up a rocky slope.

40.00 Top of ridge 300 ft. above sec. cor. at last.
 is temporary 1/4 sec. Cor.

79.11 Intersect. N. boundary line. 3 7/8 m.

N. of Cor. to sec. 7, 12, 13 and 18,
 which is a stone Market. 2 rocks are found 4 and 8 edges
 firmly set in the ground with

Subdivision F. S. R. 25 E

Mound of stone along side,
 Thence I run,

N. 89° 44' E. over true line bet. sec. 7 and 18.

Var. the same.

39, 11

Marked a rock in place 7 ft. high 8 x 6 ft.
 with \times and $\frac{1}{4}$ on N. face for $\frac{1}{4}$ sec.
 as exact cor. point
 Cor. and raised a mound of stone
 on top of rock along side corner point.

79, 11

The Cont. sec. 7, 8, 17, and 18.

Land, Mountainous.

Soil, Worthless.

No timber, some grass.

North, bet. sec. 7 and 8.

Var. 13° E.

Ascending steep hill.

28, 40

Bottom of rocky Cañon 500 ft. deep N. & E.

ascending, rocky slope.

Subdivision T. 8 S., R. 25 E.

- 44000 Mark a granite rock in place
^{with an X at exact corner and}
 1 1/2 ft. high 4 x 3 ft., 1/4 on N. face
 for 1/4 sec. Cr. and raised a
 mound of stone alongside.
- 54000 Top of ridge 400 ft. high pros. E. descend.
- 65000 Creek of pure running water 10 fks.
 wide in deep Cañon, timber along creek.
- 66000 Ascend, steep hill.
- 76000 Top of Mesa, 300 ft. high,
- 7944 Old road, pros N.E. and S.W.
- 7990 New road, from Fryed summit to N.E.
- 80000 Set a granite stone 2 1/4 x 6 x 6 ins. 3/8 in.
 in the ground for Cor to sec. 5, 6, 7 and 8.
 Marked with 5 notches, on E and S
 S. Edges, and raised a mound of
 stone alongside.
- Lowland, rough and Mountainous.

Subdivision T. 8 S. R. 25 E.

Soil, poor. Covered with rock,
 Winter Cottonwood Ash and sycamore,
 along creek.

East, on abandoned line bet. sec. 5 and 8,
 Va) 13° E.

Ascending over broken Mesa.

- .30 Road, course N. E.
- 1.45 Road from Frye's Mill, hrs. N. E. + S. W.
- 26.60 Cross same ^{graded} road on side of hill hrs. N. E. +
 S. W. grade up hill.
- 40.60 Bottom of hill set temporary 1/4 sec. cor.
- 48.50 Frye's road bears N. E. down some
- 58.10 Cross running stream 20 ft. wide.
 Course N. E.
- 79.74 Intersect - 1/4 and S. line 15. ft. N. of
 Cor. to sec. 4, 5, 8 and 9, thence

Subdivision F.S.P. 15 &

I run.

N. $89^{\circ} 54' W.$ on true line bet. sec. 5 and 8.

Var the same.

3987 Set a granite stone $18 \times 12 \times 4$ ins, ~~12~~ ¹² ins
 the ground for $\frac{1}{4}$ sec. cor. on steep
 side of hill, and raised a mound of
 stone at top side.

7974 The cor. to sec. 5, 6, 7, and 8.

Ground, hilly and rough.

Soil, worthless.

Cottonwood Ash and sycamore along creek.

West, on a random line bet. sec. 6 and 7.

Var. $13^{\circ} E.$

Ascending over high rocky mesa.

40,00 Set temporary $\frac{1}{4}$ sec. cor.

5185 Bottom of Carrow 60 ft deep bet. N.P.

Subdivision F S R 25 E,

- 78.80 Intersect W. boundary line 500 ft.,
 N. of cor. to sec. 1, 6, 7 and 12,
 which is a stone properly marked
 and, marked of stone alongside.
 Thence I run
 N. 89° 39' E. on a true line bet. sec. 6 and 7,
 Va. 13° E.
- 38.80 Set a granite stone 15 x 8 x 6 ins. ^{2 1/2} 10 in
 in the ground for 1/4 sec. cor.
 Marked 1/4 on N. face, raised
 around of stone alongside.
- 78.80 The cor. to sec. 5, 6, 7, and 8,
 Grand, high, rolling mesa.
 Soil, rocky, worthless
 No timber, good grass.

North on a random line bet. sec. 5 and 6.

Subdivision F.S. R 25 E.

Va, 13° E.

Over rough Mesa.

8,00 Descend from Mesa.

12,50 Bottom of Cañon 200 ft. deep br. N.E.
Ascend.

18,00 Top of ridge 100 ft. high. descend

24,00 Bottom Cañon 200 ft. deep. N.E.

46,00 Top of Mesa set temporary 1/4 sec, Cor.
Descend from Mesa.

79,70 Intersect N. boundary 40' N.E. of
Cor. to sees. 5, 6, 31 and 32, which
is a stone and mound of stone
properly established and marked
Fence Row.

S. 17' E. over true line bet. sees. 5 and 6
Va. the same.

Ascending over very rough land.

Subdivision T. 8 S. R. 25 E.

39.70 Set a granite stone $14 \times 8 \times 8$ ins. ^{9 in.} in the ground for 14 sec. Cor. Marked $1/4$ on N. face and raised a mound of stone alongside.

79.70 The Cor. to sec. 5, 6, 7 and 8. Ground, high rough Mesa. Soil, rocky and worthless. No timber. Fair grass. Nov. 11th, 1886.

General Description

This township is located along the northeast side of the Graham Mountains and extends high up on its precipitous spurs, in some parts wholly inaccessible to survey.

The soil is quite generally poor, and the surface is mostly covered with granite rocks. There are several streams of mountain water running into it and portions are covered with a good growth of grass. Some cottonwood, sycamore, and ash timber along ravines. There are no settlers in the township.

Clarence H. Waller
U.S. Dep. Surveyor

Final Oaths for Surveys.

LIST OF NAMES.

A List of the Names of Individuals employed by
Clarence H. Wallace U. S. Deputy Surveyor to
assist in running, measuring and marking the lines and
corners described in the foregoing Field Notes of the survey of
the Extensio and subdivisions of
T. 7 S. R. 24 E. and T. 8 S. R. 25 E.

of the principal base and meridian in the Territory of Arizona,
showing the respective capacities in which they acted.

Frank L. Lewis, Chairman

C. E. Norton, Chairman

A. B. Ford, Assessor

H. A. Callahan, Assessor

W. B. Mc Bride, Flagman



62

Final Oaths of Assistants.

We hereby certify that we assisted Clarence H.
Wallace U. S. Deputy Surveyor, in surveying
the lines necessary to complete the
survey of the exterior and sub-
divisions of T7S R24E and T8S
R25E.

of the principal base and meridian in the Territory of Arizona,
as are represented in the foregoing field notes as having been
surveyed by him and under his direction; and that said Survey
has been in all respects, to the best of our knowledge and belief,
well and faithfully surveyed, and the corner monuments es-
tablished according to the instructions furnished by the U. S.
Surveyor-General for Arizona.

Wm. C. Mc Bride

Subscribed and sworn to before me this 29th

day of November 1886

George R. King
Notary Public.



Final Oath of U. S. Deputy Surveyor.

I.....

*United States Deputy Surveyor, do solemnly swear that in
pursuance of instructions received from.....*

*..... U. S. Surveyor General for Ari-
zona bearing date of the..... day of.....*

*188..... I have well, faithfully, and truly, in my own proper
person and in strict conformity, with the instructions furnish-
ed by the U. S. Surveyor General for Arizona, the surveying
manual and the laws of the United States surveyed the.....*

.....

.....

.....

*of the principal base and meridian in the Territory of Ari-
zona, as are represented in the foregoing fields notes as having
been surveyed by me and under my direction; and I do further
solemnly swear that all the corners of the said survey have been
established and perpetuated in strict accordance with the survey-
ing manual, printed instructions, the special written instruc-
tions of the U. S. Surveyor General for Arizona, and in the*

64

specific manner described in the field notes, and that the foregoing are the true field notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

.....
U. S. Deputy Surveyor.

Subscribed and sworn to before me, this.....
day of.....188.....

.....
Notary Public.

BOOK 701

Final Oaths for Surveys **BOOK 701**

LIST OF NAMES.

*A List of the Names of Individuals employed by
U. S. Deputy Surveyor to
assist in running, measuring and marking the lines and
corners described in the foregoing Field Notes of the survey of
the*

*of the principal base and meridian in the Territory of Arizona,
showing the respective capacities in which they acted.*



66

Final Oaths of Assistants.

We hereby certify that we assisted Clarence
H. Wallace U. S. Deputy Surveyor, in surveying
 the lines necessary to complete the survey
 of the exterior and subdivisions of
 T 7 S R 24 E and T 8 S R 25 E.

of the principal base and meridian in the Territory of Arizona,
 as are represented in the foregoing field notes as having been
 surveyed by him and under his direction; and that said Survey
 has been in all respects, to the best of our knowledge and belief,
 well and faithfully surveyed, and the corner monuments es-
 tablished according to the instructions furnished by the U. S.
 Surveyor-General for Arizona.

J. A. McBride *township*
was not present at the field

Subscribed and sworn to before me this 29th

day of November 1886

George R. King
 Notary Public.



Final Oath of U. S. Deputy Surveyor.

I.....
 United States Deputy Surveyor, do solemnly swear that in
 pursuance of instructions received from.....

..... U. S. Surveyor General for Ari-
 zona bearing date of the..... day of
 188..... I have well, faithfully, and truly, in my own proper
 person and in strict conformity, with the instructions furnish-
 ed by the U. S. Surveyor General for Arizona, the surveying
 manual and the laws of the United States surveyed the.....

.....

.....

.....

of the principal base and meridian in the Territory of Ari-
 zona, as are represented in the foregoing fields notes as having
 been surveyed by me and under my direction; and I do further
 solemnly swear that all the corners of the said survey have been
 established and perpetuated in strict accordance with the survey-
 ing manual, printed instructions, the special written instruc-
 tions of the U. S. Surveyor General for Arizona, and in the

68

BOOK 701

specific manner described in the field notes, and that the foregoing are the true field notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

.....
U. S. Deputy Surveyor.

Subscribed and sworn to before me, this.....
day of.....*188*.....

.....
Notary Public.

U. S. Surveyor-General's Office,

TUCSON, A. T., June 13, 1888

The foregoing Field Notes of the Surveys of
the subdivisions of lines
T. 8 S. - R. 25 E.

Gila and Salt River Meridian
in Arizona executed by
Clarence H. Wallace,

U. S. Deputy Surveyor, under his contract dated
April 26th 1886
having been critically examined, the necessary correc-
tions and explanations made, the said Field Notes and
the surveys they describe are hereby approved.

John Hise
U. S. Surveyor-General
for the Territory of Arizona.