

SUBDIVISIONS.

Township N° 12 S. Range N° 14 E.

BOOK 759

759

No. 759  
4-671

FIELD NOTES  
GENERAL LAND OFFICE.

No. 759

BOOK 759

Field Notes  
of the Survey of the  
Subdivision lines  
of  
Township N 12 S. —  
Range No 14 E.  
of the  
Sila and Salt River  
Base and Meridian  
in the  
Territory of Arizona  
as surveyed by  
Francis B. Jacobs  
U.S. Deputy Surveyor  
under his contract no 81  
dated May 22<sup>d</sup> 1901

Survey commenced January 1<sup>st</sup> 1902  
Survey completed January 6<sup>th</sup> 1902

Subdivision of  
 Names and duties of Assistants  
 Harry R. Elder Chairman  
 Everett L. Beulden Chairman  
 James S. Henderson Moundman  
 " " " " Apexman  
 Jay Jacobs Flagman

BOOK 759

INDEX.

Township 12 S. Range 14 E.

6	46	5	29	4	23	3
43		41		27		
7	38	8	25	9	21	10
36		34		19		
18	31	17	17	16		15
13		15				
19		20				
30		29				
11		9				
31	3	32	6	33		5



T. 12 S. - R. 14 E.

Survey commenced  
January 1<sup>st</sup> 1902 and  
executed with the Gurley  
Transit described in  
the field notes of the  
boundaries hereof.

Before beginning the  
subdivision of the Sp.

I test the instrument on  
the true meridian established  
by observation on Polaris.  
On December 27<sup>th</sup> - and  
correct all of its adjustments  
so that the Solar by a.m. and  
P.M. observations indicates  
a true meridian that agrees  
with the True Meridian  
established by observation on  
Polaris

4

January 1<sup>st</sup> at the  
cor. of Sues. 3-4-33 and  
34 on the South. Edg.  
of the Sp. -

I set off  $32^{\circ} 19'$  on the  
lat. arc:  $23^{\circ} 01' S.$  on  
the decl. arc. and at  
 $1^{h} 00^{m}$  P.M. A.M.T.  
determine with the  
Solar a true meridian  
and run thence

Subdivision of T. 12 S. R. 14. E.

North  $8^{\circ} 2'$  W. bet secs. 33 and 34.  
Ascend over Granite boulders.  
and through dense undergrowth  
of Palo Verde Mesquite cacti and  
Catclaw

35.00 Ascend very steep high rocky  
mountain

48.00 Set a Granite stone  $18 \times 16 \times 10$  ins.  
12 ins. in the ground for  $\frac{1}{4}$  sec.  
cov. marked  $\frac{1}{4}$  on W. face.  
and raise a mound of stone  
3 ft base 2 ft high W of cov.

Pits impracticable.  
Impracticable and unnecessary  
to extend line further.

---

Land mountainous

Soil at  $\frac{1}{2}$  rate

Timber Palo Verde and Mesquite  
mountainous land 40.00 chs.



6

BOOK 759

## Subdivisions of T. 12 S. R. 14 E.

- North's 2' N. bit sec. 32 and 33.  
Ascend
- 5.25 Gulch course S.W.
- 12.00 Ascend.
- 12.00 Ridge bears N. E. and S. W.
- 32.00 Descend
- 39.00 Deep Gulch course S. 60° W.
- 40.00 Set a Granite Stone 20x16x10 ins  
12 ins in the ground for  $\frac{1}{4}$  sec  
cov. marked  $\frac{1}{4}$  on N. face  
and raise a mound of stone  
3 ft base 2 ft high N of cov.  
Pits impracticable  
Ascend steep mountain
- 58.50 Ridge slopes S.W. 800 ft above  
 $\frac{1}{4}$  sec. cov.  
Descend
- 64.00 Gulch course S.W.
- Ascend very steep bluffs.

Subdivisions of T. 12 S. R. 14 E.

80 00

The point for sec. cov. falls  
on a Granite stone in place  
24 x 34 x 20 ins above ground  
on which I.

cut a (x) at the exact cov. point  
for cor of Secs. 28-29-32 and 33.

Marked with 1 groove on S.  
and 4 grooves on E. edges.

And raise a mound of stone  
3 ft base 2 ft high N of cov.

Pits impracticable.

This sec cov is 1000 ft above  
 $\frac{1}{4}$  sec. cov.

Land mountainous and rocky

Thick underbrush of Catclaw.

& cacti

Soil 4 rali-

No timber

Mountainous land 8000 chs,

January 1<sup>st</sup> 1903



## 8. Subdivisions of T. 2 S. R. 14 E.

- North  $83^{\circ}$  W. bet. secs 31 and 32.
- 19.50 Wash course S. W.
- 37.00 Wash course S. W.
- 40.00 Set a Granite stone  $24 \times 10 \times 8$  ins  
18 ins in the ground for  $\frac{1}{4}$  sec.  
cov. marked  $\frac{1}{4}$  on W face  
From Which
- A Palovide 4 ins in diam  
bears N.  $52^{\circ} \frac{1}{4}$  E. 40 lbs dist  
marked  $\frac{1}{4}$  S 32 B. 9.
- A Palovide 6 ins in diam  
bears N.  $68^{\circ}$  W. 65 lbs dist  
marked  $\frac{1}{4}$  S. 31 B. 9.
- 70.00 Wash course S. W.
- 73.00 Ascend.
- 80.00 Set a Granite stone  $24 \times 12 \times 10$   
ins. 18 ins in the ground for  
cov of Secs. 29-30-31 and 32  
Marked with 1 notch on S and

Subdivisions of T. 2 S. R. 14. E.

5 notches on the E. edges.  
and raise a mound of stone  
3 ft. base 2 ft. high N. of cov.

Pits impracticable  
land mountainous & rocky  
Soil 4 cali-

Not timber 80.00 chs.

Mountainous land 80.00 chs.

East on a random line

East on a random line  
bet. Secs. 29 and 32.

40.00 Set Temp.  $\frac{1}{4}$  sec cov.

80.00 Intersect N. and S. line at  
cov. of secs. 28-29-32 and 33.

Thence down

West on a true line bet. Secs.  
29 and 32

Over rough and broken land

## Subdivisions of T. N. S. R 14 E.

- 1.50 Descend
- 2.25 Descend very abrupt
- 9.60 Gulch course S.
- ~~23.00~~ Ascend
- 23.00 Ridge slopes S. E.
- Descend very abrupt
- 33.00 To bottom of mountain
- 38.00 Descend very steep hill
- 40.00 Set a Granite stone 24x12x8  
 ins 8 ins to bedrock  
 surrounded by a mound of  
 stone for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  on N. face  
 And raise a mound of stone  
 3 ft base 2 ft high N of cor.  
 This is impracticable
- 41.40 Road bears S. E. and N. W. and  
 Gulch course S.  
 Thence over huge boulders.



## Subdivisions of T. 12 S. R. 14 E. //

80.00 The cor. of secs. 29-30-31 and 32.  
 Land rough rocky and  
 mountainous  
 No timber  
 Soil 4 rate  
 Mountainous land 80.00 chs.

West

West on a random line  
 bet. secs. 30 and 31.

40 00

Set temp  $\frac{1}{4}$  sec. Corn

79.91

Intersect the N. bdy. of the  
 Tp. at the cor. of secs. 25-30-31  
 and 36.

+

Thence Down

East on a true line bet. secs.  
 30 and 31.

Over rough rolling land

5.00

Gulch course S. W.

## Subdivisions of T. 2 S. R. 14 E.

- 35.50 Mark corner S. W.
- 39.91 Set a Granite stone 16 x 12 x 8.  
 ins 10 ins in the ground for  
 $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on N.  
 face  
 From which  
 A Palovide 12 ins in diam  
 bears S.  $26\frac{1}{2}^{\circ}$  E. 170 lbs dist.  
 marked  $\frac{1}{4}$  S. 31 B. 7.
- A Mesquite 6 ins. in diam.  
 bears N.  $50^{\circ}$  W. 26 lbs dist  
 marked  $\frac{1}{4}$  S 30 B. 9.
- 55.50 Gulch corner S
- 72.35 Gulch corner S. W.
- 79.90 The cor of secs. 29-30-31<sup>2</sup> & 32.  
 Soil 4 rats  
 Mountainous & rocky land  
 Scrubby timber of Palovide  
 and Mesquite  
 Mountainous land 79.91 lbs  
 January 2<sup>nd</sup> 1902.

## Subdivisions of T. 2 S. R. 14. E. 13

From the cor of secs. 18-18-  
19 and 24 on the N. bdy.

Run East <sup>on a true line</sup> bet. Secs. 18 and 19  
ascending along N. slope  
of Catalina Mts.

40.00 Set a Granite stone 18' x 12' x 10'  
ins 12 ins in the ground  
In  $\frac{1}{4}$  sec. cor marked  
 $\frac{1}{4}$  on N. face  
From which

A Palovide 6 ins in diam  
bears N.  $23\frac{1}{4}^{\circ}$  E. 108 lbs dist.  
marked  $\frac{1}{4}$  S. 18. B.Y.

A Palovide 4 ins in diam.  
bears S  $54\frac{1}{4}^{\circ}$  N. 115 lbs dist.  
marked  $\frac{1}{4}$  S. 19 B.Y.

80.00 Set a Granite stone 20' x 12' x 8'  
ins 15 ins in the ground  
In the cor of secs. 17-18-19 and 20.



74 Subdivisions of T. 2 S. R. 14. E.

marked with 3 notches on  
S. and 5 notches on the E  
edges.

From Which

A Palovode 5 ins in diam.

bears N.  $61\frac{1}{2}^{\circ}$  W. 27 lbs dist

marked T. 12 S. R. 14 E. S. 18 B. 7.

<sup>No other trees within sight.</sup>  
And raise a mound of stone

3 ft base 2 ft high N of cov.

Pits impracticable

land rough

Soil 4 rats

Timber scattering Palovode  
and Mesquite

Mountainous land

80.00 chs.

## Subdivisions of T. 12 S. R. 14. E. 15-

~~West on a random line  
bet. sec. 17 and 20  
Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect N. and S. line  
of the cor of 16-17-20 and 21  
Thence Drive~~

East on a true line bet.  
sec. 17 and 20

Along N. slope of mountain  
Gulch course N. W.

31.00

40.00

A Granite rock in place  
12 x 14 x 10 ins above ground  
for  $\frac{1}{4}$  sec. cor.

Marked  $\frac{1}{4}$  on N. face  
and raise a mound of  
stone 3 ft base 2 ft high  
N. of cor.

44.00

Gulch course S. W.  
As end very steep slope

## 16 Subdivisions of T. 12. S. R. 14. E.

71.00 Ridge bears S. E. and N. W.  
Mountain Ridge. 1000 ft above  
1/4 sec. cor.

Descend

80.00 The point for sec. cor. falls on  
top of a Granite bluff 60 ft high  
on which I cut a cross (X)  
at the exact cor. point for  
cor. of secs 16-17-20 and 21  
marked with 3 grooves on  
S and 4 grooves on E. sides  
With a mound of stone  
3 ft base 2 ft high N. of cor.  
Loud mountains and  
rocky

Soil of rali-

No timber

Mountainous land 80.00 chs.



## Subdivisions of T. 12 S. R. 14 E. '17

- ✓ North <sup>0° 2' W.</sup> bet secs 16 and 17.
- 1.25 Granite Bluff 50 ft high bears E. and W.
- 16.50 Descend very steep mountain
- 40.00 Set a Granite stone 24 X 12 X 10 ins 12 ins in the ground for  $\frac{1}{4}$  sec. Cor.
- Marked  $\frac{1}{4}$  on N. face from which
- A Palovide 4 ins in diam bears S 68  $\frac{1}{2}$ ° E. 40 lbs dist marked  $\frac{1}{4}$  S 16. B.Y.
- A Palovide 8 ins in diam. bears S 60° W. 79 lbs dist marked  $\frac{1}{4}$  S 17. B.Y.
- 49.00 Descend
- 52.70 Ascend bluff 30 ft
- 53.50 Ridge slopes N. W.
- 65.00 Descend steep mountains
- 66.50 Gulch course W.

18 Subdivisions of T<sub>12</sub>S. R 14 E.

80.00. Set a Granite stone 24 x 12 x 8 ins  
 10 ins W bedrock for cov of  
 sec 8-9-16 and 17  
 marked with 4 notches on S and  
 E edges

And raise a Mound of stone  
 3 ft base 2 ft high N. of cov  
 Pts impracticable

Land Mountainous & Rocky  
 Soil 4<sup>th</sup> class -

Timber Paloverde  
 Mountainous land 8000 chs,

## Subdivisions of T. 25. R. 14 E. 19

- East on a true line bet. sec. 9 and 16.  
 Ascending very steep hill  
 ✓ 4000 The corner falls on a Granite Stone  
 in place 16 X 48 X 10 ins above  
 ground.  
 On which I cut a cross (X) at  
 the exact cor. point for  $\frac{1}{4}$  sec.  
 cor. marked  $\frac{1}{4}$  S. N. of point  
 and raise a mound of stone  
 3 ft base  $\frac{1}{2}$  ft high N. of cor.  
 Pit's. Impracticable
- 4100 Top of high Granite ridge corner  
 Descend
- 54.00 Ascend
- 78.00 Granite reef 50 ft. high corner  
 Descend
- 80.00 Set a Granite stone 30 X 10 X 8 ins  
 27 ins in the ground for  
 cor of sec. 9-10-15 and 16



## Subdivisions of T. 12 S. R. 14 E.

marked 4 notches on S. and  
3 notches on E. edges

From Which

✓ An Oak 10 ins. in diam.

bears N.  $21\frac{1}{4}^{\circ}$  E. 81 lbs. dist.

marked T. 12 S. R. 14 E. S. 10 B. 4.

An Oak 7 ins. in diam.

bears S.  $48\frac{1}{2}^{\circ}$  E. 128 lbs. dist.

marked T. 12 S. R. 14 E. S. 15 B. 4.

An Oak 8 ins. in diam. bears.

N.  $15\frac{1}{4}^{\circ}$  W. 67 lbs. dist.

marked T. 12 S. R. 14 E. S. 9 B. 4.

no other tree within limit, and base ground of some 2 1/2 ft. N. of base

and Mountainous & rocky

Soil 4<sup>th</sup> soil -

Timber scrubby Oak.

Mountainous land 80,000 acs.

January 3<sup>d</sup> 1902

## Subdivisions of T. 12 S. R. 14 E. 21

- N.  $8^{\circ}$  2' N bet. secs. 9 and 10.
- 9.00 Descent very abrupt.  
Descent
- 14.00 Gulch 800 ft. below ridge  
course N. W.  
Ascend
- 32.00 Ridge of Mountain bears S. E. <sup>away</sup>  
N. W.  
Descend
- 40.00 The point for  $\frac{1}{4}$  sec. cor.  
400 ft below top of Ridge  
falls on a Granite reef in  
place 12 x 24 x 18 ins above  
ground & cut a cross.  
(x) at the exact cor. point  
for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$   
S. on N. side  
From which  
An Oak 14 ins in diam

## Subdivisions of T. 12 S. R. 14 E.

- bears S.  $53\frac{3}{4}^{\circ}$  E. 61 lbs dist  
 Marked  $\frac{1}{4}$  S. 10. B.T.
- An Oak 20 ins in diam.  
 bears N  $35\frac{3}{4}^{\circ}$  W 57 lbs dist  
 marked  $\frac{1}{4}$  S. 9. B.T.
- 58.00 Foot of steep Mountain descend  
 more gentle
- 70.00 Gulch course N. W.
- 72.00 Descend over huge Granite  
 boulders
- 80.00 Set a Granite stone  $24 \times 14 \times 10$  ins  
 16 ins in the ground for the  
 cor. of recs.  $3 \times 4 \times 9$  and 10.  
 Marked 5 notches on S. and  
 3 notches on E. edges  
 From which
- A Mesquite 17 ins in diam.  
 bears S.  $47\frac{3}{4}^{\circ}$  E. 744 lbs. dist.  
 Marked T. 12 S. R. 14 E. S. 10. B. Y.



Subdivisions of T. 12 S. R. 14 E. 23

A Mesquite 12 ins in diam.  
 bears S.  $33\frac{3}{4}^{\circ}$  N. 46 lbs dist  
 marked T. 12 S. R. 14 E. S. 9 B. T.  
<sup>no other trees within limit</sup>  
 And raise a mound of stone  
 3 ft base 2 ft high N. of cor  
 Land <sup>Practically</sup> mountainous & rocky  
 Soil 4<sup>th</sup> class.  $\downarrow$   
 Timber Mesquite and oak  
 Mountainous land 80.00 acs.

N.  $0^{\circ} 2'$  N. on a random line  
 bet. sec. 3 and 4.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.42 Intersect N. bdy. of the  $\frac{1}{4}$  sec.  
 36 lbs. N. of cor of sec.  
 3-4-33 and 34.

Thence  $\downarrow$  new.

S.  $0^{\circ} 13'$  N. on a true line

## 24 Subdivisions of T. S. R. 14. E.

bet. sec. 3 and 4.

7.40 Leave Canada Del Rio wash  
Course West

11 00 Ascend bank.

~~40.42~~  
40.42 Set a Granite Stone  $24 \times 10 \times 8$  ins  
18 ins in the ground In  $\frac{1}{4}$   
sec. cor. marked  $\frac{1}{4}$  S. on N face  
From Which

A Mesquite 5 ins in diam  
bears. N  $43 \frac{3}{4}^{\circ}$  E. 47 lbs dist  
marked  $\frac{1}{4}$  S. 3. B. T.

A Mesquite 5 ins. in diam.  
bears. S.  $60^{\circ}$  W. 47 lbs dist.  
marked  $\frac{1}{4}$  S. 4. B. T.

80.42 The cor of sec. 3-4-9 and 10

Land mountainous

Soil stony 4<sup>th</sup> rate

Timber Mesquite and Palo verde

Mountainous land 80.42 Chs.

Subdivisions T. 12 S. R. 14 E. 25 29

N. 0° 7' W bet sec. 8 and 9.  
Descend over Granite boulders.  
Through dense undergrowth

31.00 Gulch course N. W.

Ascend

35.00 Ridge bears S. E. and N. W.

Descend

40.00 Set a Granite stone 18 X 18 X 6 ins.  
12 ins. in the ground for cor.  
¼ sec cor marked ¼ S. M  
N. face

From which

A Palovide 6 ins in diam.  
bears N 70° E. 115 lbs dist  
marked ¼ S. 9 B.T.

A Palovide 8 ins in diam.  
bears N. 81° W 61 lbs dist.

Marked ¼ S. 8. B.Y.

4560 Gulch course N. W.



## Subdivisions of T. 12 S. R. 14 E.

- 46.00 Ascend steep rocky hill.
- 51.00 Ridge bears S.E. and N.W.  
Descend
- 56.85 Gulch course W.  
Ascend
- 65.00 Ridge bears S.E. and N.W.  
Descend
- 70.00 Gulch course W.  
Ascend
- 77.00 Ridge bears S.E. and N.W.
- 80.00 Set a Granite Stone  $24 \times 12 \times 8$  ins  
16 ins in the ground for the  
cor. of sec. 4-5-8 and 9  
marked 5 notches on S. and  
4 notches on E. edges.  
And raise a md. of stone  
3 ft. base 2 ft. high. N. of cor.  
Pits impracticable  
Land Mountainous & rocky

Subdivisions of T. 12 S. R. 14. E. <sup>27</sup>

29

Soil <sup>th</sup> 4 rate

Lumber Palouse.

Mountainous land 80.00 chs.

East on a random line  
bet. sec. 4 and 9.40.00 Set 4 emp.  $\frac{1}{4}$  sec. cor.80.00 Intersect N and S. line  
at the cor of sec. 3-4-9 and 10.

Thence S run

West on a true line bet. sec.  
4 and 9.

300 Footing Bank

5.00 Descend very steep bluff

6.20 Big Gulch course N.W.

9.00 Ascend

16.20 Gulch course N 30° W.

## Subdivisions of T. 12 S. R. 14. E.

- 25.80 Top of Peak.  
Descend
- 29.80 Dup gulch course N.W.  
Ascend
- 35.00 Ridge bears S.E. & N.W.
- 40.00 Set a Granite stone 20 X 14 X 8 ins  
14 ins in the ground for  $\frac{1}{4}$   
see cor marked  $\frac{1}{4}$  on N. face  
From which  
A Palovide 8 ins in diam.  
bears N.  $2\frac{1}{2}^{\circ}$  E 15 lbs dist  
marked  $\frac{1}{4}$  S. 9. B. Y.  
A Palovide 8 ins in diam  
bears S  $27^{\circ}$  W 27 lbs dist  
marked  $\frac{1}{4}$  S. 9 B. T.  
Descend
- 41.80 Gulch course N.W.  
Ascend
- 52.00 Ridge bears S.E. and N.W.



## Subdivisions of T. 12 S. R. 14. E. 29

Descend

58.75 Gulch course N.W.

Ascend

65.00 Ridge bases S.E. and N.W.

Descend

72.50 Gulch course N.W.

88.00 The cov. of secs. 4-5-8 and 9.  
150 ft. above bottom of Gulch  
and mountainous

Soil Rocky &amp; calc.

Timber Palmetto and Mesquite  
mountainous land 8000 chsJanuary 4<sup>th</sup> 1902N. 0° 2' W. or a random line  
bet. secs. 4 and 5.40.00 Set temp.  $\frac{1}{4}$  sec cov.8030 Intersect N. bdy. 44 chs.  
N. of cov.

30

## Subdivisions of T. 12 S. R. 14 E.

of secs. 4-5-32 and 33.  
Thence & run.

S.  $5^{\circ} 16' N.$  on a true line  
bet. Secs. 4 and 5.

- 3240 Wire fence bears N.E. and S.W.  
3424 Road bears N.E. and S.W.  
3530 Enter wash course S.W.  
3810 Leave mark.

Ascend

- 4030 Set a Granite Stone  $20 \times 16 \times 10$   
ins 12 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  on N face

From which

A Palovide 5 ins in diam  
bears S  $84^{\circ} \frac{3}{4} E.$  130 lbs dist  
marked  $\frac{1}{4}$  S 4 B.T.

A Mesquite 4 ins in diam  
bears S.  $59^{\circ} \frac{1}{2} N.$  126 lbs dist.  
Marked  $\frac{1}{4}$  S 5 B.T.

## Subdivisions of Tn. S. R. 14. E. 31

- 48.20 Ascend  
 49.20 Descend along E. slope of Knoll.  
 49.75 Enter Bottom  
 67.50 Gulch course N.W.  
 Ascend Steep rocky hill  
 80.30 The cor. of sec 4-5-8-9  
 100 ft above Gulch  
 Land mountainous  
 Soil rocky 4<sup>th</sup> rate  
 Timber Mesquite & Palmetto  
 Mountainous land 8000 chs  
 80.30
- 
- N. 0° 3' W. bet. secs. 17. and 18  
 Descend over Granite boulders  
 90.00 Gulch course N.W.  
 Ascend  
 93.00 Ridge slopes N.W.  
 Descend



Subdivisions of T<sub>12</sub> S R. 14 E.

- 40.00 Set a Granite stone 20 x 12 x 8  
 ins. 15-ins in the ground  
 for  $\frac{1}{4}$  sec. cov. marked  $\frac{1}{4}$  S.  
 on N. face.  
 And raise a md. of stone  
 3 ft base 2 ft high N. of cov.  
 Pls impracticable
- 42.50 Bottom of ridge
- 46.15 Gulch course N.  
 Ascend
- 46.60 perpendicular wall of  
 concrete 30 ft high
- 50.00 Ridge bars E & W  
 Descend
- 57.60 Gulch course N. 60' W.  
 Ascend
- 66.50 Ridge bars S.E. and N.W.  
 Descend
- 73.00 Enter Gulch course N.

## Subdivisions of T. 12. S. R. 14 E. 33

- 79.00 Leave Gulch corner N.W.
- 80.00 Set a Granite stone  $18 \times 12 \times 12$  ins  
 12 ins in the ground in case of  
 sees 7-8-17 and 18  
 marked with 4 notches on S. and  
 5 notches on E edges.  
 and raise a mound of stone  
 3 ft base 2 ft high N of cor  
 Pits impracticable.
- Land Rocky & Mountainous  
 Covered with dense underbrush  
 of Cat claw & Cacti  
 Soil 3rd and 4th rate  
 Mountainous land 80.00 chs

34 BOOK 759  
Subdivisions of T. 12 S. R. 14 E.

East on a random line bet.  
secs 8 and 17.

40.00 Set temp.  $\frac{1}{4}$  Sec. cov.

80.00 Intersect N. and S. line  
at the cov. of secs. 8-9-16 and 17.

Thence S run.

West on a true line  
bet. secs. 8 and 17.

Descend

1.58 Gulch course N.

Ascend

3.48 Granite Knoll

31.00 Descend

32.70 Gulch course N.W.

34.70 Ascend rocky bluff.

45.00 The point on  $\frac{1}{4}$  Sec. cov. falls  
on a Granite stone in place  
18 x 36 x 13 ins. above ground  
on which I cut a cross (X)



No. 759 BOOK 759  
Subdivisions of T. 12 S. R. 4. E. 35

at the exact cor. point for  $\frac{1}{4}$   
sw. cor. marked  $\frac{1}{4}$  S. on N. side  
from which.

A mesquite 10 ins in diam  
bears N.  $40\frac{1}{2}^{\circ}$  E. 133 lbs dist  
marked  $\frac{1}{4}$  S. 8. B.T.

A Paloude 6 ins in diam  
bears S  $57\frac{1}{4}^{\circ}$  E. 226 lbs dist  
marked  $\frac{1}{4}$  S. 17. B.T.

And raise a mound of stone  
3 ft base 2 ft high N. of cor  
Rits impracticable

46.50 Descend. -

80.00

The cor of sec. 7-8-17 and 18.  
Land Mountainous and Rocky  
Soil Rocky 4<sup>th</sup> soil -  
Timber Paloude <sup>and</sup> Mesquite  
Land Mountainous 8000 chs.

---

## 36 Subdivisions of T. 12. S. R. 14. E.

From the cor. of secs. 7-8-17  
and 18 & run N. on a random  
line bet. secs. 7-18.

40.00 Set Temp  $\frac{1}{2}$  sec. cor.

79.72 Intersect N bdy of the  $\frac{1}{4}$ s.  
28 lbs S. of sec. 7-12-13 and 18  
Thence to run

S  $89^{\circ}48'E$  on a true line bet.  
secs. 7 and 18.

2.70 Road from Tucson to Mammoth

1200 Leave Bottom

Ascend

1682 Telephone line bears N and S.

22.50 Ridge bears N and S.

Descend

25.50 Gulch course N.

Ascend

Ridge bears S.E. and N.W.

39.72 Set a Granite stone 16 x 12 x 10

## Subdivisions of T. 12. S. R. 14. E. 37

10 ins. in the ground for  $\frac{1}{4}$  sec.  
 cor marked  $\frac{1}{4}$  on N face  
 dig pits 18x18x12 ins E. and W.  
 of the stone 3 ft dist and raise  
 a mound of earth  $3\frac{1}{2}$  ft base  
 $1\frac{1}{2}$  ft high N of cor.

Descend

45.50 Gulch course N 30° W.

Ascend

49.00 Ridge bears S.E. and N.W.

Descend

62.00 Gulch course N.W.

70.00 Top of ascent

Descend

74.80 Enter Wash course N 70° W.

78.50 Leave Wash course W.

Ascend

79.72 The cor of sec. 7-8-12 and 18  
 Timber Mesquite &  
 Paloveds



Subdivisions of T. R. S. R. 14. E.

Land Valley & Level.

Soil / and 2<sup>nd</sup> rate -

mountainous land \$0.79.72<sup>0</sup>.

January 5<sup>th</sup> 1902

N. 0° 3' N. bet. nos 7 and 8  
Ascend

.50 Top of bank bet. S.E. and N.W.

4.50 Gulch course N.

Ascend very rocky ridge

14.00 Ridge slopes N.

Descend

30.80 Enter wash course N.W.

34.00 Leave wash ascend steep ridge

39.75 Ridge bears S.E.

Descend

40.00 Set a Granite stone 20x18x10  
ins. 15 ins in the ground

Submissions of T. 12 S. R. 14. E. 39

In  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on  
W. face

From Which

A Mesquite 8 ins in diam.  
bears S  $85^{\circ}\frac{1}{4}$  E. 45 lbs dist.  
marked  $\frac{1}{4}$  S. 8 B.T.

A Paloude 6 ins in diam.  
bears S  $36^{\circ}\frac{1}{2}$  W. 101 lbs. dist.  
Marked  $\frac{1}{4}$  S. 7. B.T.

Steam Pump Station bears.  
N.  $40^{\circ}$  W. about 40 chs.

45.00 Onlie Bottom

53.20 Pitches Wire fence. brs. N.  $60^{\circ}$  <sup>and</sup> S. W.

71.66 Pitches Wire fence brs. N.  $55^{\circ}$  E.

71.70 Telephone line brs. N.  $65^{\circ}$  E. and  
S.  $55^{\circ}$  W.

75.00 Road to Gueson & Mammoth  
brs. N.  $60^{\circ}$  E.

80.00 Set a Granite stone  $18 \times 10 \times 6$  ins.

## Subdivisions of T. 12 S. R. 14 E.

12 ins in the ground. In cov. of  
secs. 6-7 and 8

Marked with 5 notches on  
S. and E. edges

From Which.

An Iron wood 6 ins. in  
diam. bears N. 66 $\frac{1}{2}$ ° E. 90 lbs. dist.  
Marked T. 12 S. R. 14 E. S. 5. B. T.

A Mesquite 12 ins in diam  
br. N. 13° W 272 lbs. dist.

Marked T. 12 S. R. 14 E. S. 6. B. T.

dig pits 18 x 18 x 12 ins. in  
each sec 5 $\frac{1}{2}$  ft dist. and  
raise a mound of earth 4 ft  
bar 2 ft high N of cov.

Land Mountainous and level.

Soil 4<sup>th</sup> and 1<sup>st</sup> rate -

Timber Mesquite & Iron wood

Dense undergrowth of  
Catclaw & Cactus



## Subdivisions of T. 12 S. R. 14 E. 41

Mountainous 8000 chs.

Post on a random line  
bet. secs. 5 and 8.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.14 Intersect N and S. line at the  
cor. of secs. 4-5-8 and 9.

Thence S. and W.

West on a true line  
bet. secs. 5 and 8.

Ascend

150 Ridge bears S.E. and N.W.

Descend

16.00 Gulch course N.

17.25 Ridge bears S.E. and N.W.

Descend very abrupt hill

22.00 Enter Wash course N.

30.00 ~~Leave~~ wash course N.W.

## 42. Subdivisions of T. 12. S. R. 14. E.

40.07 Set a Granite stone  $24 \times 12 \times 8$  ins  
 $12$  ins in the ground  
 in ~~the~~ ~~ground~~

marked  $\frac{1}{4}$  on N face  
 From Which

A Mesquite 8 ins in diam.  
 br. N.  $61\frac{1}{4}^{\circ}$  E. 46 lbs. dirt.

marked  $\frac{1}{4}$  S. 5 B.T.

A Mesquite 6 ins. in diam.  
 bears S.  $57\frac{1}{4}^{\circ}$  W. 6 lbs. dirt.

marked  $\frac{1}{4}$  S. 8 B.T.

Ascend

42.50 Ridge 75 ft above cor bears.  
 S.E. and N.W.

Descend

45.00 Bottom of Ridge

Enter Canada Del Rio Bottom

54.76 Paches wire fence bears N and S.

69.70 Paches wire fence bears N  $60^{\circ}$  E.  
 and S.  $60^{\circ}$  W.

## Subdivisions of T. 12 S. R. 14 E. 43

- 64.26 Telephone line bears N. 60° E.  
and S. 60° W.
- 72.00 Road to Tucson and Mammoth  
bears N. 60° E. and S. 60° W.
- 80.14 The cor of secs. 5-6-7 and 8.  
Land Mountainous and level  
Soil 4<sup>th</sup> and 1<sup>st</sup> rate.  
Timber Mesquite & Paloverde  
Dense undergrowth of  
Catalpa & Cacti  
Mountains covered with  
dense undergrowth 88.14 chs.

N. 89° 48' W. on a random line  
bet. secs 6 and 7.

40.00 Set temp  $\frac{1}{4}$  sec cor.

80.00 Intersect N bdy of the T<sub>12</sub> S<sub>20</sub>



## 44 Subdivisions of T. 12 S. R. 14. E.

lbs. South of the cor. of sec.

1-6-7 and 12.

Thence down

S.  $89^{\circ} 39' E.$  on a true line  
bet. sec. 6 and 7.

1.00 Ascend

5.00 Ridge bears S. E. and N. W.

Descend

20.00 Gulch course S. E.

22.00 Ascend

26.25 Ridge bears S. E. and N. W.

Descend

28.50 Bottom

34.50 Road bears S. E. and N. W.

39.00 Ascend

40.00 Set a Granite stone  $8 \times 10 \times 8$

ins  $12$  ins. in the ground

In  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on

N. face

From which

Subdivisions of T. 12 S. R. 14. E. 43

A Paloude 5 ins. in diam.  
 hrs. S. 29  $\frac{1}{2}$  E. 192 lbs dist.  
 marked # S. 4 B. 4.

A Paloude 6 ins. in diam  
 hrs. N 30  $\frac{3}{4}$  W. 163 lbs dist.  
 marked # S. 6 B. 4.

42.50 Ridge

45.00 Descend

48.80 Bottom

Ascend

57.20 Ridge bears N & S.

Descend

61.35 Enter Canada Del Cr. wash  
 course S. W.

66.00 Leave Canada Del Cr wash  
 across level bottom

through dense undergrowth  
 of Catclaw Mesquite and Cacti

70.00 The corner of sec. 5-6-7 and 8.  
 Land Hilby

46

## Subdivisions of T. 12 S. R. 14 E.

Soil sandy / sand shale -  
 Timber Redwood & Mesquite  
 Mountainous land 80,000 obs.

N. 8° 3' W. on a random line  
 bet. sec. 5 and 6.

40.00 Set temp  $\frac{1}{4}$  sec. cor.

80.36 Enter out N. 8° 3' W. of sec of  
 sec. 5 - 6 - 31 and 32.

Thence to run

South on a true line bet. sec. 5 <sup>1/4</sup> & 6

17.00 Canada del. br. Wash course ~~W~~

20.00 Ascend W

25.50 Ridge bears E and W.

28.00 Descend

32.00 Bottom of Ridge

Ascend

35.00 Ridge bears E and W.

Descend

40.36 Set a granite stone 18x10x8 ins.



## Subdivisions of T. 12 S. R. 14. E. 47

2 ins in the ground for  $\frac{1}{4}$  sec  
 cor. marked  $\frac{1}{4}$  S on N face  
 from which

A Palovide 5 ins. in diam.  
 bears  $S 84^{\circ} \frac{3}{4} E$ . 130 lbs dist  
 marked  $\frac{1}{4}$  S. 5-B.T.

A Mesquite 14 ins. in diam.  
 bears  $S 59^{\circ} \frac{1}{2} W$ . 126 lbs dist  
 marked  $\frac{1}{4}$  S. 6 B.Y.

41.00 Ascend

42.15 Ridge bears S.E. & N.W.

Descend

44.00 Gulch course S.E.

Ascend

46.60 Ridge bears S.E. and N.W.

Descend

52.00 Gulch course S.E.

Ascend

55.50 Ridge bears S.E. and N.W.

## Subdivisions of T. 12 S. R. 14. E.

- 6340 Descend Rocky hill  
 6350 Enter Canada Del Oro Wash  
 6990 Near Canada del Oro wash coun S. N.  
 8036 The cor of secs. 5-6-7 and 8.

Land hilly

Soil 3<sup>rd</sup> and 1<sup>st</sup> rate -

Timber Mesquite

dense undergrowth 8036 chs.

January 6<sup>th</sup> 1902

### General Description

There was only a small fraction of this sp that could be surveyed most of it lays in the Catalina mountains which is too rough to survey. -

The only surface water on the sp. is on Sec 33. There is a deep well and considerable improvements on Sec 7 and another settler on Sec 5.

The only agricultural land on the sp is along the Canada del Oro Wash. -


Francis B. Jacobs U.S. Deputy Surveyor

## OFFICE OF THE U.S. SURVEYOR GENERAL.

Phoenix, Arizona.

Dec. 10-1902.

The foregoing field notes of the survey of Subdivisions of  
Sp. 12 South Range 14 East  
 executed by A. D. Jacobs, D. I.  
 under his contract No. 81 dated May 23-  
1901. having critically examined, and the necessary corrections, and explanations made, the said field notes, and the surveys they describe, are hereby approved.



U.S. Sur. Gen. for Arizona.