

829

No. 829

BOOK 829

4-671

FIELD NOTES  
GENERAL LAND OFFICE.

Subdivision

of

T. 16 S. R. 15 E.

56

ARIZONA

Indexed, Book 828

Township 16 S R. 15 E

6	5	4	16 63	852	65	1
			105	84	64	
7	8	9	10310	8211	62	12
			101	80	60	
18	17	16	9915	7814	58	13
			98	77	57	
19	20	21	9622	7523		24
			115	94	73	
30	29	11	328	9227	71	26
			111	90	70	
31	32	109	33	8834	6735	36

No. 829

BOOK 829 57

Subdivision of T. 16. S. R. 15E

chains

40.00 Set temp.  $\frac{1}{4}$  sec. cor  
80.25 Intersect E. bdy. of  
Tp. 30 lks N. of cor. of  
secs. 13, 18, 19 and 24, which  
I reestablished June 7  
1895.

Thence I run

N  $89^{\circ} 22' W$ , on a true line  
bet secs 13 and 24

Over level land, through  
scattering timber

29.72 Trail bears N.E. and S.W.

40.12 $\frac{1}{2}$  Set a sand stone  
12 x 10 x 6 ins, 8 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N. face;  
dig pits 18 x 18 x 12 ins.

# Subdivision of

Chains

E. and W. of stone, 3 ft  
dist; and raise a  
mound of earth  $3\frac{1}{2}$  ft  
base,  $1\frac{1}{2}$  ft. high, N. of  
cor.

80.25 The cor. of sees 13, 14, 23 and 24  
Land, level  
Soil, loam; 1<sup>st</sup> rate  
Timber, mesquite

N<sup>o</sup> 6'E, bet sees 13 and 14  
Over level land, through  
scattering timber and  
undergrowth

40.00 Set a mesquite post,  
3 ft. long, 3 ins. sq.  
with marked stone,  
24 ins. in the ground,  
for  $\frac{1}{4}$  sec. cor. marked

T. 16. S. R. 15. E. - Continued  
 chains

$\frac{1}{4}$  S on W. face; from which  
 A mesquite 6 ins. diam  
 bears  $N 75^{\circ} E$ , 127 lks  
 dist, marked  $\frac{1}{4}$  S. B. T.  
 A mesquite 6 ins. diam  
 bears  $S 30\frac{1}{2}^{\circ} W$ , 89 lks.  
 dist, marked  $\frac{1}{4}$  S. B. T.

49.50 Road, bears N. W. and S. E

80.00 Set a granite stone  
 15 x 14 x 6 ins., 10 ins. in  
 the ground, for cor. of  
 sees 11, 12, 13 and 14,  
 marked with 4 notches  
 on S and 1 notch on E.  
 edges; from which  
 A mesquite 4 ins. diam  
 bears  $S 82^{\circ} E$ , 178 lks. dist,  
 marked T. 16. S. R. 15 E.  
 S. 13. B. T.; no other trees  
 within limits; dig

Subdivision of  
Chains

pits 18x18x12 ins. in  
secs 11, 12 and 14, 5 1/2 ft  
dist. and raise a mound  
of earth 4 ft. base, 2  
ft. high W. of cor.

Land, level

Soil, loam; 2<sup>nd</sup> rate

Timber, mesquite;

undergrowth mesquite.

June 11. 1895

S89°22'E, on a random  
line, bet sees 12 and 13

40.00 Set temp. 1/4 sec. cor.

79.90 Intersect E. bdy. of Tp.

31 lks N. of cor. of sees  
7, 12, 13 and 18, which I  
reestablished June 7.  
1895.

Thence I run

## T. 16. S. R. 15. E. - Continued

Chains

N 89° 9' W, on a true line  
bet. sees. 12 and 13

Over level and rolling land  
through scattering  
under growth

39.95 Set a sand stone 15x10x6  
ins. 10 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  on N. face; dig pits  
18x18x12 ins, E and W.  
of stone, 3 ft. dist, and  
raise a mound of  
earth 3 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$   
ft. high, N. of cor.

53.14 Road from Tucson to  
David<sup>son</sup> Spring bears N W  $\frac{1}{2}$  S E

79.90 The cor. of sees 7, 12, 13 and 18  
Land, level and rolling.  
Soil, loam; 1<sup>st</sup> rate

## Subdivision of

No timber; undergrowth  
mesquite and greasewood

No  $6^{\circ} E$ , bet. secs. 11 and 12  
Over level and rolling  
land, through under-  
growth

- 22.30 Road from Tucson to  
David <sup>Spring</sup> bears N.  $W \frac{3}{4}$ ,  $1 \frac{1}{2} E$
- 40.00 Set a granite stone  
14 x 10 x 4 ins, 9 ins. in  
the ground for  $\frac{1}{4}$  sec.  
cor., marked  $\frac{1}{4}$  on  
N. face; dig pits 18 x 18 x 12  
ins. N and S. of stone,  
3 ft. dist., and raise a  
mound of earth  $3 \frac{1}{2}$  ft  
base,  $1 \frac{1}{2}$  ft. high, N. of cor.
- 80.00 Set a granite stone



## T. 16. S. R. 15 E. - Continued

17 x 8 x 5 ins., 12 ins. in  
the ground for cor. of  
secs 1, 2, 11 and 12, marked  
with 5 notches on S.  
and 1 notch on E. edges;  
from which

A mesquite 10 ins. diam.  
bears S 74° E, 174 ft. dist,  
marked T. 16. S. R. 15. E. S.

12. B. T. no other trees  
within limits; dig  
pits 18 x 18 x 12 ins., in  
secs. 1, 2 and 11, 5½ ft  
dist. and raise a mound  
4 ft. base, 2 ft. high, W  
of cor.

Land level and rolling  
Soil, loam, 2<sup>nd</sup> rate  
No timber; undergrowth

## Subdivisions of

Chains

mesquite, greasewood  
and chollas.

S $89^{\circ}9'E$ , on a random  
line bet. secs. 1 and 12

40.00 Set temp.  $\frac{1}{4}$  sec. cor.79.98 Intersect E. bdy of Tp.  
40 lks. N. of cor. of secs  
1, 6, 7 and 12, which I re-  
established June 7, 1895.

Thence I run

N $88^{\circ}52'W$ , on a true line  
bet. secs 1 and 12Over rolling land, through  
undergrowth39.99 Set a sand stone  $12 \times 8 \times 8$   
ins., 8 ins in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; dig pits

## T. 16. S. R. 15. E. - Continued

Chains

18 x 18 x 12 ins. E. and W. of  
stone, 3 ft. dist, and  
raise a mound of  
earth, 3½ ft. base, 1½ ft  
high, N. of cor.

60.90 Trail bears N.E. and S.W.

74.80 Trail bears N.E. and S.W.

79.98 The cor. of sees 1, 2, 11 and 12

Land, rolling

Soil, loam; 2<sup>nd</sup> rate

No timber; undergrowth  
mesquite and oertillos

N<sup>o</sup> 6 E. bet sees 1 and 2

Over rolling land,  
through scattering  
undergrowth

40.00 Set a lime stone 14 x 12 x 4  
ins., 8 ins. in the ground

# Subdivisions of chains

for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face, dig pits  
 $18 \times 18 \times 12$  ins., N. and S.  
of stone, 3 ft. dist., and  
raise a mound of earth  
 $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

68.53 Intersect the "Third  
Standard Parallel South"  
at a point 4.87 chs. W.  
of the standard cor. to  
secs. 35 and 36, T. 15. S. R. 15 E,  
at which point I set  
a granite stone  $14 \times 12 \times 6$ ,  
8 ins. in the ground for  
closing cor. of secs. 1 and 2,  
marked C.C., on S., with  
1 groove on E., and 5  
grooves on W. faces, dig

## T. 16 S. R. 15. E. - Continued

Chains

posts,  $24 \times 18 \times 12$  ins. cross-wise on each line, E. and W., 3 ft., and S. of stone, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, S. of cor.

Land, rolling

Soil, gravelly loam, 3<sup>rd</sup> rate

No timber; undergrowth, mesquite, greasewood and acotillos.

June 12. 1895

June 13: At 7<sup>h</sup> 40<sup>m</sup> a. m., l. m. t., I set off  $32^\circ$  on the lat. arc,  $23^\circ 14' N.$  on decl. arc, and determine a true meridian with the

Subdivisions of  
 Chains the solar at the cor. of  
 secs. 2, 3, 34 and 35, on the  
 S. bdy. of the Twp. which  
 I established June 10. 1895.  
 Thence I run  
 No<sup>o</sup> 6' E., bet secs 34 and 35  
 Over level and rolling land  
 through scattering timber  
 12.00 Dry wash, 12 lks wide, course N.W.  
 40.00 Set a sand stone 15 x 8 x 6  
 ins, 10 ins. in the ground  
 for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  on N. face; from which  
 A mesquite 4 ins. diam.  
 bears N. 17 $\frac{1}{2}$  E., 40 lks dist,  
 marked  $\frac{1}{4}$  S. B. T.  
 no other tree within limits.  
 80.00 Set a sandstone 17 x 10 x 7  
 ins, 11 ins. in the ground  
 for cor. of secs. 26, 27, 34 $\frac{3}{4}$ , 35,

## T. 16. S. R. 15 E. - Continued

Chairs

marked with 1 notch on  
S. and 2 notches on E.  
edges, from which:

A mesquite 6 ins. diam.  
bears  $N 28^{\circ} E$ , 300 lks. dist.,  
marked T. 16. S. R. 15 E. S. 26. B. T.

A mesquite 4 ins. diam. bears  
 $S 17 \frac{1}{2}^{\circ} E$ , 159 lks. dist. marked  
T. 16. S. R. 15 E. S. 35. B. T.

A mesquite 6 ins. diam. bears  
 $S 25^{\circ} W$ , 204 lks. dist. marked  
T. 16. S. R. 15 E. S. 34. B. T.

A mesquite 4 ins. diam. bears  
 $N 32 \frac{1}{2}^{\circ} W$ , 94 lks. dist., marked  
T. 16. S. R. 15 E. S. 27. B. T.

Land, level and rolling  
Soil, gravelly loam; 2<sup>nd</sup> rate  
Timber, mesquite

Subdivision of  
chains.

East, on a random line  
bet. secs. 26 and 35

40.00 Set temp.  $\frac{1}{4}$  sec. cor

80.07 Intersect N. and S. line  
3 lks. S. of cor. of secs.  
25, 26, 35 and 36.

Thence, I run

$S 89^{\circ} 59' N$ , on a true line  
bet. secs. 26 and 35

over level land, through  
scattering timber and  
undergrowth

40.03 $\frac{1}{2}$  Set a mesquite post  
3 ft. long, 3 ins. sq. with  
marked stone, 24 ins.  
in the ground for  $\frac{1}{4}$  sec.  
cor. marked  $\frac{1}{4}$  S. on N.  
face; from which  
a mesquite, 6 ins. diam.



T. 16. S. R. 15 E. - Continued  
chain

bears  $N 48^{\circ} E$ , 67 lks. dist,  
marked  $\frac{1}{4}$  S. B. T.

A mesquite 7 ins. diam  
bears  $S 76 \frac{3}{4}^{\circ} W$ . 99 lks. dist,  
marked  $\frac{1}{4}$  S. B. T.

72.28 Road bears N. W. and S. E

00.07 The cor. of sees 26, 27, 34 and 35

Land, level

Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rate

Timber, scattering mes-  
quite and undergrowth

$N 0^{\circ} 6' E$ , bet. sees 26 and 27

Over level, and rolling land  
through scattering timber  
and undergrowth

15.90 Road, bears N. W. and S. E.

40.00 Set a mesquite post  
3 ft. long. 3 ins. sq, with  
marked stone 24 ins

Subdivision of  
chains

in the ground for  $\frac{1}{4}$  sec.  
cor., marked  $\frac{1}{4}$  on W.  
face, from which  
a mesquite 4 ins. diam.  
bears  $N 3\frac{3}{4}^{\circ} E$ , 63 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

A mesquite 4 ins. diam.  
bears  $S. 66^{\circ} W$ , 59 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

80.00 Set a granite stone  
14 x 8 x 8 ins., 9 ins. in  
ground for cor. of secs.  
22, 23, 26 and 27, marked  
with 2 notches on S. and  
E. edges; dig pits 18 x 18 x 12  
ins. in each sec.  $5\frac{1}{2}$  ft.  
dist., and raise a mound  
of earth 4 ft. base, 2 ft.  
high, W. of cor. (a mesquite

T. 16 S. R. 15 E - Continued

chains

8 ins. diam. bears  $N77^{\circ}E$ ,  
 7.04 chs. dist, marked  
 T. 16. S. R. 15 E. S. 23. B. T.)  
 Land level and rolling  
 Soil loam; 2<sup>nd</sup> and 3<sup>rd</sup> rate  
 Timber, mesquite; under  
 growth mesquite and  
 greasewood

$N89^{\circ}59'E$ , on a random  
 line, bet secs. 23 and 26

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.04 Intersect N. and S. line  
 11 lks. N. of cor. of secs. 23  
 24, 25 and 26.

Thence, I run

$N89^{\circ}56'W$ , on a true  
 line bet. secs. 23 and 26

Over gently rolling land

Subdivision of  
 through scattering timber  
 and undergrowth

- 1.53 Dry Wash 4 lks wide, course N.W.
- 6.40 Road bears N. N.W. and S. S. E
- 40.02 Set a mesquite post  
 3 ft. long, 3 ins. sq. with  
 marked stone, 24 ins.  
 in the ground for  $\frac{1}{4}$  sec.  
 cor. marked  $\frac{1}{4}$  S on N.  
 face; from which,  
 A mesquite 6 ins. diam.  
 bears N  $72\frac{3}{4}^{\circ}$  E, 121 lks. dist,  
 marked  $\frac{1}{4}$  S. B. T.
- A mesquite <sup>5 ins diam. bears</sup> S.  $34^{\circ}$  W, 124 lks,  
 dist. marked  $\frac{1}{4}$  S. B. T.
- 48.00 Dry Wash, 8 lks wide, course N.W.
- 80.04 The cor. of secs. 22, 23, 26  
 and 27.  
 Land, gently rolling.

## T. 16. S. R. 15 E. - Continued

Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rate  
 Timber, mesquite; under-  
 growth mesquite and  
 greasewood; some  
 giant cactus.

N 86° E, bet sees 22 and 23  
 Over level land, through  
 scattering timber

40.00 Set a mesquite post  
 3 ft. long, 3 ins. sq. with  
 marked stone 24 ins. in  
 the ground, for  $\frac{1}{4}$  sec.  
 cor., marked  $\frac{1}{4}$  S. on  
 W. face; from which  
 a mesquite 4 ins. diam.  
 bears N 86° E, 43 lks. dist.,  
 marked  $\frac{1}{4}$  S. B. T.  
 A mesquite 6 ins. diam

## Subdivision of

bears  $N56\frac{1}{2}^{\circ}W$ , 102 lks. dist,  
marked  $\frac{1}{4}$  S. B. T.

71.59 Trail bears N.W. and S. E

72.39 Dry Wash 6 lks wide course N.W.

73.00 Round, bears N.W. and S.E.

80.00 Set a sand stone  $16 \times 8 \times 8$

ins, 11 in the ground for  
cor. of secs 14, 15, 22 and 23,

marked with 3 notches

on S. and 2 notches on

E. edges; from which,

A mesquite 8 ins. diam.

bears  $S39\frac{1}{4}^{\circ}W$ , 213 lks

dist, marked T. 16. S.

R. 15. E. S. 27. B. T.; no

other trees within limits,

dig pits  <sup>$18 \times 18 \times 12$  ins</sup> in secs 22, 23

and 26,  $5\frac{1}{2}$  ft dist; and

raise a mound of earth

4 ft. base, 2 ft high, W. of cor.

## T. 16. S. R. 15 E - Continued

Land, level

Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rate

Timber, mesquite

S89°56'E, on a random  
line, bet. secs 14 and 23

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.09 Intersect N. and S. line  
2 lks N. of cor. of secs. 13,  
14, 23 and 24

Thence, I run

N89°55'W, on a true line  
bet. secs. 14 and 23.

Over level land, through  
scattering undergrowth

39.60 Trail bears N.E. and S.W.

40.04 $\frac{1}{2}$  Set a sand stone 15x10x6,  
10 ins. in the ground for  
 $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$

# Subdivision of

Chains

on N. face; dig pits 18x18x12  
ins., N and S. of stone,  
3 ft. dist.; and raise a  
mound of earth 3½ ft.  
base, 1½ ft. high, N. of cor.

71.00 Trail bears N.W. and S.E

80.09 The cor. of secs. 14, 15, 22<sup>or</sup> 23

Land, level

Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rate

Timber, a few mesquite;  
undergrowth, mesquite

June 13. 1895.

N<sup>o</sup> 6 'E, bet. secs. 14 and 15

Over rolling land, through  
scattering mesquite

40.00 Set a mesquite post,  
3 ft long, 3 ins. sq. with  
marked stone, 24 ins.  
in the ground, for ¼ sec



## T. 16 S. R. 15 E. - Continued

Chains

cor. marked  $\frac{1}{4}$  S. on W  
face; from which,  
A mesquite 6 ins. diam.  
bears  $N 15 \frac{1}{4}^{\circ} E$ , 44 lks. dist.  
marked  $\frac{1}{4}$  S. B. T.

A mesquite 5 ins. diam  
bears  $S 32 \frac{1}{2}^{\circ} W$ , 93 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

48.90 Dry Wash 5 lks. wide, course N.W.

49.05 Road bears E. and W.

74.45 Trail bears E. and W.

78.20 Trail bears E. and W.

78.80 Trail bears E. and W.

80.00 Set a sand stone  $16 \times 10 \times 6$   
ins. 11 ins. in the ground  
for cor. of secs. 10, 11, 14 and  
15; marked with 4 notches  
on S. and 2 notches on  
E. edges; from which

## Subdivision of chains

A mesquite 6 ins. diam,  
bears S 15½° E, 161 lks. dist,  
marked T. 16. S. R. 15. E.  
S. 14. B. T.; no other  
trees within limits,  
dig pits 18 x 18 x 12 ins. in  
secs 10, 11 and 15, 5½ ft. dist,  
and raise a mound of  
earth 4 ft. base, 2 ft. high,  
W. of cor.

### Land rolling

Soil, gravelly loam; 3<sup>rd</sup> rate  
Timber, mesquite

Bsg 55° E, on a random  
line, bet. secs 11 and 14

40.00 Set temp. ¼ sec. cor.

80.02 Intersect N. and S. line,  
5 lks. S. of cor. of secs.

## T. 16. S. R. 15 E. - Continued

chains

11, 12, 13 and 14.

Thence, I run

N89°57'W, on a true line  
bet sees. 11 and 14Over gently rolling land,  
through scattering grease  
wood

40.01 Set a sandstone 15x12x8  
ins, 10 ins in the ground  
for  $\frac{1}{4}$  sec. cor, marked  
 $\frac{1}{4}$  on N. face; dig pits  
18x18x12 ins. East W.  
of stone, 3 ft. dist., and  
raise a mound of earth  
3 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft high  
N. of cor.

41.66 Trail bears N.E. and S.W.

80.02 The cor of sees. 10, 11, 14 and 15  
Land gently rolling.

Subdivisions of  
 Chains Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rate  
 No timber; undergrowth,  
 greasewood

No 6'E, bet. sees 10 and 11  
 over rolling land, through  
 scattering timber and  
 undergrowth

40.00 Set a sand stone 16x8x8 ins.  
 11 ins. in the ground for  
 1/4 sec. cor., marked 1/4  
 on W. face; dig pits 18x18x12  
 ins., N. and S. of stone,  
 3 ft. dist. and raise a  
 mound of earth 3 1/2 ft.  
 base 1 1/2 ft. high, W. of

66.90 <sup>copy</sup> Old road, bears N.E. and S.W.

80.00 Set a basalt stone  
 18x12x10 ins, 12 ins. in the

## T. 16 S. R. 15 E - Continued

Chains

ground, for cor. of secs.  
2, 3, 10 and 11, marked with  
5 notches on S. and 2  
notches on E. edges; from  
which

A mesquite 4 ins. diam.  
bears  $S 35\frac{1}{2}^{\circ} W$ , 203 lks. dist,  
marked T. 16. S. R. 15 E.

S. 10. B. T. no other trees  
within limits. dig pits  
<sup>in secs. 2, 3 and 11</sup>  
18x18x12 ins.  $\times$  5 $\frac{1}{2}$  ft. dist;  
and raise a mound of  
earth 4 ft. base, 2 ft.  
high, W. of cor.

Land, rolling

Soil, loam; 3<sup>rd</sup> rate

Timber, mesquite; under-  
growth mesquite

# Subdivision of

Chains

S89°07'E, on a random  
line, bet. secs. 2 and 11  
40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
80.08 Intersect N. and S. line  
12 $\frac{1}{2}$  lks S. of cor. of secs. 1, 2  
11 and 14.

Thence, I run

S89°07'W, on a true line  
bet. secs. 2 and 11

Over rolling land, through  
scattering timber and  
undergrowth.

33.00 Dry wash, 10 lks. wide, course N.W.

40.04 Set a sand stone  
12 x 10 x 8 ins. 8 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor.,  
marked  $\frac{1}{4}$  on N. face;  
from which  
A mesquite 4 ins. diam

## T. 16 S. R. 15 E. - Continued

Chains

bears  $N 61^{\circ} E$ ,  $7\frac{1}{2}$  lks.,  
marked  $\frac{1}{4}$  S. B. T.

A. mesquite 5 ins. diamo  
bears  $S 4^{\circ} W$ . 81 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

53.90 Road from Tucson to  
David Spring bears  $N W \frac{2}{3} \frac{1}{2} E$

74.75 Road bears  $N. E.$  and  $S. W$

80.08 The cor. of secs. 2, 3, 10 and 11  
Land, rolling  
Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rate  
Timber, mesquite; under-  
growth, mesquite, grease-  
wood and ocotillos.

$N 0^{\circ} 6' E$ , bet secs. 2 and 3  
Over rolling land, through  
scattering undergrowth

36.20 Road from Tucson to

## Subdivision of

Chains

- David's <sup>son's</sup> Spring bears N.W.  $\frac{3}{4}$  S.E.
- 40.00 Set a mesquite post 3 ft long, 3 ins. sq. with marked stone 24 ins. in the ground, marked  $\frac{1}{4}$  S. on W. face; dig pits 18x18x12 ins, N. and S. of post. 3 ft. dist, and raise a mound of earth  $3\frac{1}{2}$  ft base,  $1\frac{1}{2}$  ft. high, W. of cor.
- 52.75 Road bears N.W. and S.E.
- 59.37 Mesquite post 2 ft above ground 2 ins. sq. marked "4" on W. face bears E. 10 Wks.
- 61.85 Trail bears N.W. and S.E.
- 68.50 Intersect. the "Third Standard Parallel South" at a point 5.05 chs W. of standard cor. of



## T. 16. S. R. 15 E. - Continued

Chains

secs 34 and 35, T. 15 N.  
R. 15. E., at which point  
I set a malpais stone  
16 x 12 x 4 ins, 11 ins in  
the ground for closing  
cor. of secs. 2 and 3, marked  
C.C. on S., with 2 grooves  
on E and 4 grooves on  
W. faces; dig pits,  
24 x 18 x 12 ins. crosswise  
on each line, E. and W.,  
3 ft., and S. of stone,  
7 ft. dist., and raise  
a mound of earth  
4 ft. base, 2 ft. high,  
S. of cor.

Land, rolling

Soil, loam; 2<sup>nd</sup> and 3<sup>rd</sup> rate

No timber; undergrowth

# Subdivision of

Chains

mesquite and palo verde

June 14, 1895

From the cor. of secs.  
3, 4, 33 and 34, on S. bdy  
of the Tp., which I  
established June 10, 1895,  
I run

$N 0^{\circ} 5' E$ , bet. secs. 33 and 34  
Over level land through  
scattering timber and  
undergrowth

40.00 Set a granite stone  
 $12 \times 10 \times 5$  ins., 8 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor.,  
marked  $\frac{1}{4}$  on W. face;  
from which  
A mesquite 6 ins. diam  
bears  $N 69^{\circ} \frac{1}{4}' E$ , 125 lks. dist  
marked  $\frac{1}{4}$  S. B. T.

## T. 16 S. R. 15 E. - Continued

Chains

A mesquite 4 ins. diam.  
bears  $S 33^{\circ} W$ , 87 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

80.00 Set a sand stone  $16 \times 8 \times 8$   
ins., 11 ins. in the ground,  
for cor. of secs. 27, 28, 33  
and 34, marked with  
1 notch on S, and 3 notches  
on E. edges; from which  
A mesquite 6 ins. diam.  
bears  $S 19^{\frac{3}{4}}^{\circ} E$ , 117 lks. dist.,  
marked T. 16. S. R. 15 E.  
S. 34. B. T.

A mesquite 6 ins. diam.  
bears  $N 11^{\frac{3}{4}}^{\circ} W$ , 254 lks.  
dist., marked T. 16. S.  
R. 15 E. S. 28. B. T., no  
other trees within limits,  
<sup>18x18x12 ins</sup>  
dig pits, in secs 27 and 33

Subdivision of  
Chains

5½ ft. dist; and raise  
a mound of earth 3½ ft.  
base, 1½ ft. high, N. of cor.

Land, level

Soil, loam; 1<sup>st</sup> rate

Timber, mesquite; under-  
growth mesquite.

East on a random line  
bet. sees. 27 and 34

40.00 Set temp. ¼ sec. cor.

80.06 Intersect N. and S. line  
5 lks S. of cor. of sees. 26,  
27, 33 and 34

Thence, I run

S 89° 58' W. on a true  
line bet. sees. 27 and 34

Over level land through  
scattering timber and

## T. 16. S. R. 15. E. - Continued

chains

under growth

40.03 Set a mesquite post 3 ft. long, 3 ins. sq. with marked stone 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on N. face; from which a mesquite 4 ins. diam. bears  $N 1\frac{3}{4}^{\circ} W$ , 187 lks. dist. marked  $\frac{1}{4}$  S. B. T.

A mesquite 5 ins. diam. bears  $S 30^{\circ} W$ , 240 lks. dist. marked  $\frac{1}{4}$  S. B. T.

80.06 The cor. of secs. 27, 28  
33 and 34

Land, level

Oil, boom; 1<sup>st</sup> and 2<sup>nd</sup> rate

Timber, mesquite; under growth, mesquite and

Subdivision of  
Chains greasewood.

No<sup>o</sup> 5<sup>e</sup>, bet. secs. 27 and 28  
Over level land, through  
scattering timber and  
undergrowth.

40.00 Set a mesquite post,  
3 ft. long. 3 ins. sq.  
with marked stone,  
24 ins. in the ground,  
marked  $\frac{1}{4}$  S. on W. face,  
from which

A mesquite 8 ins. diam.

bears  $N 12 \frac{1}{2}^{\circ} W$ , 19 lks. dist,  
marked  $\frac{1}{4}$  S. B. F.

A mesquite 8 ins. diam.

bears  $S 31 \frac{1}{4}^{\circ} E$ , 89 lks. dist,  
marked  $\frac{1}{4}$  S. B. F.

44.25 Dry wash, 4 lks wide course W.

45.57 Dry wash, 6 lks wide, course W.

## T. 16. S. R. 15 E - Continued.

Chains

- 53.30 Dry wash, 7 lks wide, course W.  
 60.00 Dry wash 5 lks wide, course W.  
 60.90 Dry wash 4 lks wide, course W.  
 61.80 Dry wash 5 lks wide, course W.  
 80.00 Set a sand stone 18x12x8

ins.; 12 ins. in the ground,  
 for 'cor. of secs. 21, 22, 27  
 and 28, marked with  
 2 notches on S. and  
 3 notches on E. edges;  
 from which

A mesquite 6 ins. diam  
 bears N 80  $\frac{3}{4}$ ° E, 115 lks  
 dist, marked T. 16. S.  
 R. 15. E. S. 22. B. T. no  
 other trees within limits.  
 dig pits <sup>18x18x12 ins</sup> in secs. 22, 26  
 and 27, and raise a  
 mound of earth 4 ft

## Subdivision of

Chains

base, 2 ft. high, W. of cor.  
 Land level  
 Soil, loam; 2<sup>nd</sup> rate  
 Timber, mesquite, under-  
 growth mesquite

N89°58'E, on a random  
 line bet. secs 22 and 27  
 Over level land through  
 scattering undergrowth.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.05 Intersect N. and S. line  
 4 lbs. N. of cor. of secs.  
 22, 23, 26 and 27

Thence, I run  
 West, on a true line  
 bet. secs 22 and 27

1.85 Dry Wash, 4 lbs wide, course  $\frac{1}{4}$  sec.

5.00 Dry Wash 5 lbs wide, course  $\frac{1}{4}$  sec.



## T. 16. S. R. 15 E - Continued

Chains

40.02 1/2

Set a mesquite post  
3 ft. long, 3 ins. sq. with  
marked stone 24 ins.  
in the ground for 1/4  
sec. cor., marked 1/4<sup>S</sup> on  
N. face; dig pits 18x18x12  
ins. E and W. of post,  
3 ft. dist.; and raise a  
mound of earth 3 1/2 ft.  
base, 1 1/2 ft. high, N. of cor.

60.00

Road bears N. W. and S. E

63.00

Dry Wash 4 lks. wide, course N. W.

64.00

Dry Wash 5 lks. wide, course N. W.

75.00

Road bears N. W. and S. E

80.05

The cor. of secs 21, 22, 27 and 28

Land level

Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rate  
No timber; undergrowth  
mesquite and greasewood.

## Subdivision of

Chains

- No<sup>o</sup> 5 E, bet secs. 21 and 22  
 Over level land, through  
 scattering undergrowth
- 8.10 Dry wash, 6 lks wide, course N.W.
- 17.35 Dry wash, 6 lks wide, course N.W.
- 18.40 Road bears E. and W.
- 20.20 Dry wash 7 lks. wide, course N.W.
- 32.90 Road bears N.W. and S.E.
- 40.00 Set a sand stone 15x12x10  
 ins., 10 ins. in the ground,  
 for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  on W. face; dig pits  
 18x18x12 ins. N and S. of  
 stone, 3 ft. dist; and  
 raise a mound of earth  
 3 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high,  
 W. of cor.
- 80.00 Set a basalt stone  
 18x14x10 ins., 12 ins in

## T. 16. S. R. 15 E - Continued

Chains

the ground, for cor. of  
secs. 15, 16, 21, <sup>and</sup> 22, marked  
with 3 notches on S. and  
E. edges; from which  
A mesquite 4 ins. diam.  
bears S 4° E, 166 lks. dist.,  
marked T. 16. S. R. 15 E.

S. 22. B. T.

A mesquite 6 ins. diam.  
bears N 10° E, 197 lks. dist.,  
marked T. 16. S. R. 15 E. S. 15 B. T.

No other trees within  
limits; dig pits 18x18x12  
ins. in secs. 16 and 21  
5½ ft. dist, and raise  
a mound of earth 4 ft  
base, 2 ft high, W. of cor.  
Land, level  
Soil, loam; 2<sup>nd</sup> rate

Subdivision of  
Chains  
Timber, a few mesquite,  
undergrowth, greasewood

East, on a random line,  
bet. secs. 15 and 22

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.04 Intersect N. and S. line  
3 lks. S. of cor. of secs  
14, 15, 22 and 23

Thence, I run

S  $89^{\circ}59'$  W. on a true  
line bet. secs 15 and 22

Over level land, through  
scattering undergrowth

10.00 Dry wash 5 lks wide course N.W.

11.00 Road, bears N.W. and S.E.

40.00 Set a sandstone  $14 \times 14 \times 6$   
ins., 8 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; from which

## T. 16. S. R. 15. E. - Continued

Chains

A mesquite 7 ins. diam.

bears N 25° W, 69 lks. dist,  
marked  $\frac{1}{4}$  S. B. T.

A mesquite 10 ins. diam

bears S 77° W, 91 lks. dist,  
marked  $\frac{1}{4}$  S. B. T.

80.04 The cor. of secs 15, 16, 21 and 22

Land, rolling

Soil, loam; 1<sup>st</sup> and 2<sup>nd</sup> rateTimber, a few mesquite;  
undergrowth mesquite.

June 15, 1895

N 0° 5' E, bet secs 15 and 16

Over rolling land, through  
scattering undergrowth

14.16 Dry wash, 4 lks wide, course W.

22.45 Road bears N. E. and S. W.

40.00 Set a mesquite post  
3 ft long, 3 ins. sq. with

# Subdivision of Chains

marked stone, 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on W. face; from which a mesquite 5 ins. diam. bears  $N29\frac{1}{2}^{\circ}E$ , 177 lks. dist; marked  $\frac{1}{4}$  S. B. T.

A mesquite 4 ins. diam. bears  $S18\frac{1}{2}^{\circ}W$ , 112 lks. dist; marked  $\frac{1}{4}$  S. B. T.

- 63.90 Dry wash 6 lks wide, course N.W.
- 64.35 Dry Wash 5 lks wide, course N.W.
- 64.88 Dry Wash 8 lks wide, course N.W.
- 65.00 Road, bears N.W. and S.E.
- 80.00 Set a sand stone  $17 \times 12 \times 10$  ins., 11 ins in the ground for. cor. of secs 9, 10, 15 and 16, marked with 4 notches on S. and 3 notches on E. edges;

## T. 16. S. R. 15. E - Continued

Chains

dig pits 18 x 18 x 12 ins. in  
each sec.  $5\frac{1}{2}$  ft. dist;  
and raise a mound  
of earth 4 ft. base, 2  
ft. high. W. of cor.

Land, rolling  
Soil, loam; 3<sup>rd</sup> rate  
Timber, a few mesquite;  
undergrowth, grease-  
wood.

$N89^{\circ}59'E$ , on a random  
line, bet. sees. 10 and 15

40.00 Set. temp.  $\frac{1}{4}$  sec. cor

80.00 Intersect N. and S. line  
at cor. of sees. 10, 11, 14 and 15.

Thence, I run  
 $S89^{\circ}59'W$ , on a true line  
bet. sees. 10 and 15.

# Subdivision of Chains.

- Over level, land, through  
scattering timber
- 2.70 Trail  $N 88^{\circ} W$  and  $S 88^{\circ} E$
- 5.00 Trail bears  $N. E.$  and  $S. W.$
- 39.05 Road bears  $N. E.$  and  $S. W.$
- 40.00 Set a sand stone  $14 \times 10 \times 8$   
ins., 8 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  on N. face; from which  
A mesquite 4 ins. diam.  
bears  $N 2^{\circ} E$ , 65 lks. dist,  
marked  $\frac{1}{4}$  S. B. T.
- A mesquite 4 ins. diam.  
bears  $S 56 \frac{1}{4}^{\circ} W$ , 100 lks. dist,  
marked  $\frac{1}{4}$  S. B. T.
- 80.00 The cor. of secs 9, 10, 15 and 16  
Land, level  
Soil, loam; 1<sup>st</sup> rate  
Timber, mesquite



## T. 16. S. R. 15 E. - Continued

Chains

N $5^{\circ}$ E, bet sees. 9 and 10  
over rolling land,  
through scattering  
timber.

40.00 Set a mesquite post  
3 ft. long, 3 ins. sq.,  
with marked stone 24  
ins. in the ground,  
for  $\frac{1}{4}$  sec. cor,  
marked  $\frac{1}{4}$  S. on W.  
face; from which  
a pole verde 6 ins. diam.  
bears N $44\frac{1}{2}^{\circ}$ E, 240 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

A mesquite 4 ins. diam.  
bears S $47\frac{3}{4}^{\circ}$ W, 60 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

80.00 Set a granite stone  
18 x 10 x 10 ins., 12 ins. in  
the ground, for cor of  
sees. 3, 4, 9 and 10, marked

## Subdivision of

with 5 notches on S.  
and 3 notches on E.  
edges; from which  
A mesquite 4 ins. diam.  
bears  $S 52^{\circ} E$ , 143 lks dist.  
marked T. 16. S. R. 15 E.  
S. 10. B. T.

A mesquite 4 ins. diam.  
bears  $N 67\frac{1}{4}^{\circ} W$ , 154 lks  
dist., marked. T. 16. S.  
R. 15. E. S. 4. B. T., no  
other trees within limits,  
dig pits  $18 \times 18 \times 12$  ins., in  
sees 3 and 9,  $5\frac{1}{2}$  ft. dist.,  
and raise a mound  
of earth 4 ft. base, 2 ft.  
high W. of cor.

Land, rolling.

Soil, gravelly loam, 3<sup>rd</sup> rate

## T-16. S. R. 15 E. - Continued

Timber, mesquite and  
palo verde

N 89° 59' E, on a random  
line bet. secs 3 and 10.

40.00 Set temp.  $\frac{1}{4}$  sec. cor

80.03 Intersect N and S. line  
3 lks. S. of cor. of secs.  
2, 3, 10 and 11.

Thence, I run

S 89° 58' W, on a true line  
bet. secs. 3 and 10

Over level and rolling  
land, through scattering  
timber

15.00 Old road bears N.E. and S.W.

40.01 $\frac{1}{2}$  Set a sand stone  
18 x 8 x 4 ins., 12 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.

Subdivision of  
Chains  
marked  $\frac{1}{4}$  on N. face;  
from which  
A palo verde 5 ins. diam.  
bears  $N 66 \frac{1}{4}^{\circ} W$ , 144 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.  
A palo verde 12 ins. diam.  
bears  $S 59 \frac{1}{2}^{\circ} E$ , 157 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

80.03 The cor of secs. 3, 4, 9<sup>2</sup>/<sub>10</sub>  
Land, level and rolling  
Soil, loam; 1<sup>st</sup> and 3<sup>rd</sup> <sup>drate</sup>  
Timber, mesquite and  
palo verde

$N 0^{\circ} 5' E$ , bet secs 3 and 4  
Over rolling land,  
through scattering  
timber

40.00 Set a sand stone

T. 16. S. R. 15 E - Continued  
Chains

15 x 12 x 6 ins., 10 ins. in  
the ground for  $\frac{1}{4}$  sec. cor.,  
marked  $\frac{1}{4}$  on W. face,  
from which

A mesquite 7 ins. diam.  
bears  $S 27 \frac{3}{4}^{\circ} E$ , 185 lbs.  
dist., marked  $\frac{1}{4}$  S. B. T.

A mesquite 6 ins. diam.  
bears  $S 23^{\circ} W$ , 296 lbs.  
dist., marked  $\frac{1}{4}$  S. B. T.

68.52 Intersect the "Third  
Standard Parallel  
South" at a point  
4.98 lb. W. of the  
standard cor. of secs.  
33 and 34, T. 15. S. R. 15 E.,  
at which point I set  
a mesquite post 3 ft  
long, 4 ins sq. with

# Subdivision of Chains

marked stone, 24 ins.  
in the ground, for  
closing cor. of secs 3 and 4,  
marked

C.C. T. 16. S. R. 15 E. on S.,  
S. 3 on E., and

S. 4. on W. faces, with  
3 grooves on E. and W.  
faces; from which

A mesquite 6 ins. diam  
bears  $S 36\frac{1}{2}^{\circ} E$ , 254 lks. dist,  
marked T. 16. S. R. 15 E. S. 3. B. T.

A mesquite 5 ins. diam bears  
 $S 47\frac{1}{4}^{\circ} W$ , 333 lks. dist, marked  
T. 16 S. R. 15. E. S. 4. B. T.

Land, rolling

Soil, gravelly loam, 3<sup>rd</sup> rate  
Timber, palo verde and  
mesquite. June 17. 1895.

## T. 16. S. R. 15 E - Continued

Chains

June 18. 1895: At 7<sup>h</sup>. 15<sup>m</sup>  
 a. m. l. m. t., I set off  
 32° on the lat. arc, 23° 24'  
 N. on the decl. arc, and  
 determine a true meridian  
 with the solar, at the  
 cor. of secs. 4, 5, 32 and 33,  
 on the S. bdy of the Tp.,  
 which I established

June 10. 1895.

Thence, I run

N 0° 5' E, bet secs 32 and 33

Over level land, through  
 scattering timber

40.00 Set a mesquite post  
 3 ft. long. 3 ins. sq. with  
 marked stone 24 ins.  
 in the ground, marked  
 1/4 S. on N. face, from which

# Subdivision of

Chains

A mesquite 10 ins. diam  
bears  $N45\frac{1}{2}W$ , 226 lbs. dist,  
marked  $\frac{1}{4}$  S. B. T.

A mesquite 9 ins. diam.  
bears  $S35^{\circ}E$ , 122 lbs. dist,  
marked  $\frac{1}{4}$  S. B. T.

80.00 Set a sand stone  
15x10x8 ins, 10 ins. in  
the ground, for cor. of  
secs. 28, 29, 32 and 33,  
marked with 1 notch  
on S, and 4 notches  
on E. edges; from which  
A mesquite 8 ins. diam  
bears  $N83^{\circ}E$ , 195 lbs. dist,  
marked T. 16. S. Q. 15 E.  
S. 28. B. T.

A mesquite 4 ins. diam.  
bears  $S66\frac{1}{2}^{\circ}E$ , 160 lbs. dist,



## T. 16. S. R. 15 E - Continued

Chains

marked T. 16. S. R. 15 E.

S. 33. B. T.

A mesquite 7 ins. diam.  
bears  $S 15^{\circ} 34' W$ , 167 lks  
marked T. 16. S. R. 15 E.

S. 32. B. T.

A mesquite 4 ins. diam.  
bears  $N 46^{\circ} W$ , 141 lks. dist.,  
marked T. 16. S. R. 15 E.

S. 29. B. T.

Land, level

Soil, loam<sup>2</sup> clay; 1<sup>st</sup> 2<sup>nd</sup>, 3<sup>rd</sup> hate

Timber, mesquite;  
undergrowth, mesquite  
and greasewood.

East, on a random  
line bet. secs 28 and 33

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

# Subdivision of

Chains

80.03 Intersect N. and S. line  
5 lks S. of cor. of sees.

27, 28, 33 and 34

Thence, I run

$S 89^{\circ} 58' W$ , on a true line  
bet. sees. 28 and 33

Over level land, through  
scattering undergrowth

40.01½ Set a mesquite post  
3 ft. long, 3 ins. sq.  
with marked stone  
24 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  S. on N. face; from which  
a mesquite 6 ins. diam.  
bears  $N 26\frac{3}{4}^{\circ} E$ , 145 lks.  
dist, marked  $\frac{1}{4}$  S. B. T.  
a mesquite 7 ins. diam.  
bears  $S 74\frac{3}{4}^{\circ} W$ , 150 lks

## T. 16 S. R. 15 E. - Continued

chains  
dist., marked  $\frac{1}{4}$  S. B. T.

80.03 The cor. of secs. 28, 29, 32  
and 33

Land, level; Soil loam; 1<sup>st</sup> rate  
Timber, a few mesquite,  
undergrowth mesquite

N $0^{\circ}$  5' E., bet. secs 28 and 29

Over level land, through  
scattering timber and  
undergrowth

40.00 Set a mesquite post 3  
ft. long, 3 ins. sq. with  
marked stone 24 ins.  
in the ground for  $\frac{1}{4}$  sec.  
cor. marked  $\frac{1}{4}$  S. on W.  
face; from which,  
A mesquite 7 ins. diam.,  
bears N $76^{\circ}$  E., 215 lbs. dist.,

Subdivision of  
Chains

marked  $\frac{1}{4}$  S. B. T.

A mesquite 6 ins. diam.  
bears  $N 81\frac{1}{4}^{\circ} W$ , 212 lks. dist.,  
marked  $\frac{1}{4}$  S. B. T.

42.00 Road bears N.W. and S.E

59.30 Road bears N.W. and S.E

80.00 Set a sand stone  $18 \times 8 \times 8$   
ins. 12 ins. in the ground  
for cor. of secs. 20, 21, 28<sup>2</sup> & 29,  
marked with 2 notches  
on S. and 4 notches on E.  
edges; from which

A mesquite 6 ins. diam  
bears  $N 4^{\circ} E$ , 91 lks. dist.,  
marked T. 16 S. R. 15 E.  
S. 21. B. T.

A mesquite 6 ins. diam.  
bears  $N 58\frac{1}{4}^{\circ} W$ , 67 lks.  
dist., marked T. 16. S. R. 15 E

## T. 16. S. R. 15 E - Continued

Pines

S. 20. B. T., no other trees  
within limits. dig pits  
<sup>in secs. 28 and 29</sup>  
18x18x12 ins., 5½ ft. dist.,  
and raise a mound of  
earth 4 ft. base, 2 ft. high,  
W. of cor.

Land, level

Soil, loam, 2<sup>nd</sup> rateTimber, mesquite, under-  
growth mesquite.

N89°58'E, on a random  
line, bet. secs. 21 and 28

40.00 Set. temp. ¼ sec. cor.

80.09 Intersect N. and S. line  
3 lks S. of. cor. of secs.

21, 22, 27 and 28

Thence, Run

S89°57'N, on a true line

## Subdivision T. 16 S. R. 15 E. - Continued

Chains

bet. secs 21 and 28

Over level land, through  
scattering timber and  
undergrowth

8.50 Dry Wash, 6 lks wide, course N. W.

40.04½ Set a granite stone  
15 x 10 x 10 ins., 10 ins. in  
the ground for ¼ sec. cor.,  
marked ¼ on N. face,  
from whichA mesquite 10 ins. diam. bears  
N 3½° E, 68 lks. dist. marked  
¼ S. B. T.A mesquite, 12 ins. diam.  
bears S 40¼° W, 235 lks. dist.  
marked ¼ S. B. T.

43.85 Dry Wash, 6 lks wide, course N. W.

80.09 The cor. of secs. 20, 21, 28, and 29  
Land, level

Concluded, Book 830