

Book No. 1.

Sub's. of T. 12 S. R. 24 E.

Rockfellow Cont. No. 82.

BOOK 854

854

No. 854.

4-671,

FIELD NOTES
GENERAL LAND OFFICE.

We, F. E. Simpson and
G. E. Austin, do solemnly
swear that we will well and
faithfully execute the duties
of chain carriers; that we
will level the chain upon even
and uneven ground, and plumb
the tally pins, either by sticking
or dropping the same; that we
will report the true distance to
all notable objects, and the true
lengths of all lines that we assist
in measuring, to the best of
our skill and ability, and in
accordance with instructions
given us, in the survey of the
subdivision lines of Twp. 19 S., R. 24 E.
of the Gila and Salt River Basins
and Meridian in the Territory
of Arizona.

F. E. Simpson Chairman
G. E. Austin Chairman

BOOK 854

Given and subscribed to before
me this 27 day of Jan
A. D. 1902
John A. Rockwell
Notary Public

MY COMMISSION EXPIRES APR. 10, 1909

We, Wm. McRay, James ^{IA} Hardin, and W. F. Sweeney, do solemnly swear that we will well and truly perform the duties of ^{Plateman} Measuror and Assessor in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the subdivisions of T. 17 S. R. 24 E. of the Gila and Salt River Basins and Meridian in the Territory of Arizona.

William McRay. ^{Plateman}
 James Hardin ^{Measuror}
 William Sweeney ^{Assessor}

Sworn and subscribed before me this 27 day of Jan A. D. 1902
 John A. Rockwell 901
 Notary Public

MY COMMISSION EXPIRES APR. 10, 1905

No. 854

BOOK 854

1B

Field Notes
of the survey of the
Subdivisions
of
Twp. 17 S., Range 24 E
of the
Gila and Salt River
Base and Meridian
in the
Territory of Arizona
as surveyed by
John A. Rockfellow
U. S. Deputy Surveyor
Under his contract
No. 82, dated May 23, 1901

Survey commenced Jan 27, 1902
Survey completed Feb. 8, 1902

2

Survey of the Subdivisions

Names of Assistants

T. E. Simpson Chairman

G. E. Austin Chairman

Wm. McKay Flagman

James Hardin Woundman

Wm. Sweeney Axeman.

BOOK 854

Twp 17 S R 24 E

4-674.

Township 17 S., R. 24 E., S. 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36

Index for { BOOK 854
BOOK 855

6	94	5	67	4	57	3	36	2	21	1
93		91		65		50		35		19
7	90	8	64	9	48	10	34	11	17	12
88		87		63		47		33		15
18	86	17	62	16	46	15	31	14	14	13
84		83		60		45		30		13
19	81	20	59	21	43	22	29	23	11	24
78		76		57		42		27		10
30	74	29	56	28	40	27	26	26	9	25
73		71		54		39		24		7
31	68	32	52	33	37	34	23	35	6	36

Survey of Subdivisions

Survey commenced Jan. 27, 1902 and executed with a Young and Sons Light Mountain Transit No. 6855 with Smith Solar attachment. The horizontal limb is provided with two double verniers placed opposite to each other, reading to single minutes of arc, which is also the least count of the verniers of the latitude and declination arcs. The instrument was examined, tested on the true meridian at Tucson, found correct and was approved.

Tp 17 S R 24 E
cls

by the Surveyor General
for Arizona, May 10, 1901
The instrument was
tested on the true
meridian Jan 18, 1902
as shown in notes
of survey of secs 21 +
28, Tp 18 S. R. 24 E, made
under special instru-
tions in connection
with this contract,
also at the S.E. cor of
this Township, as
shown in the notes
of Boundaries of this
survey.

Jan 31, 1902
I commence at the
cor of secs 1, 2, 35 + 36
on S. Bdy of Tp, which

6

BOOK 854

Survey of Subdivisions
chs

- is a granite rock firmly set & marked and intressed as described by the Surveyor General. Thence I run N. $0^{\circ} 06' W$ bet secs 35 & 36 over level prairie land. Road bear $8^{\circ} W$. Var $12^{\circ} 35' E$.
- 24.00
40.00 Set a granite rock 16 x 8 x 8 ins, 12 ins in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face. Dig pits 18 x 18 x 12 ins N. & S. 3 ft. dist. Raise a mound of earth $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high W. of cor.
- 5-9-85 Grapevine Canyon road
bet N. W. & S. E.
- 80.00 Set a granite rock

Tfr. 17 S. R. 24 E.
chs

14x10x8 ins 10 ins in
ground for cor sees.
25, 26, 35 and 36.
marked with 1 notch
on S. and 1 on E edges.
Dig pits 18x18x12 ins
in each sec. 5 1/2 ft dist
Raise mound of earth
4 ft base 2 ft high
W. of cor.

Land level.
Soil 2^d rate
No timber

E. on random line
bet sees 25 and 36

40.00 Set temp 1/4 sec. cor.
79.97 Intersect E. Bdy of Tfr
3 lks S. of cor sees

8

BOOK 854

Survey of Subdivisions
cls

25-30, 31 and 36

Which is a post
4x4 ins, marked &
intressed as described
by the Surveyor General.

Thence I run

S. 89° 59' W on true
line bet secs 25 & 36
over level prairie land.39.98 1/2 Set a granite rock 18x10x
5 ins, 12 ins in ground
for 1/4 sec. cor, marked
1/4 on N. face; dig pits
18x18x12 ins, 3 ft E & W
of cor. raise mound
of earth 3 1/2 ft base
1 1/2 ft high N. of cor

79.97 cor secs 23, 26, 33 & 36

Land level
soil 2¢ rate

The 17 S R 24 E.
 chs

No timber.

40.00 N. 0° 06' W. bit sec; 25 + 26
 over level land.

Set a granite rock 18x10x
 8 ins, 12 ins in ground
 for $\frac{1}{4}$ sec. cor. marked
 $\frac{1}{4}$ on W. face; dig pits
 18x18x12 ins N. + S. of cor.
 3 ft dist; raise mound
 of earth $3\frac{1}{2}$ ft - base
 $1\frac{1}{2}$ ft high W. of cor.

80.00

Set a granite rock
 15x10x8 ins, 10 ins in
 the ground, for cor
 sec 23, 24, 25 + 26
 marked with 2 notches
 on S. and 1 notch on
 E. edges; dig pits
 18x18x12 ins in each sec

Survey of Subdivisions
cls

$5\frac{1}{2}$ ft dist; raise a
 mound of earth 4 ft
 base, 2 ft high W of cor.
 Land level
 Soil 2^d rate
 No timber

$N. 89^{\circ} 59' E$ on random
 line bet secs 24 and 25.

40.00 Set temp $\frac{1}{4}$ sec. cor.

79.97 The cor sec 19, 24, 25 + 30
 On E. Body of R^{r}
 which is a post marked
 and witnessed as
 described by the Sur-
 veyor General.

Thence I run
 $S. 89^{\circ} 59' W$ on true
 line bet secs 24 + 25.
 Over level land.

The 17 S. R. 24 E

39.98 1/2 ^{Set} a granite rock
18 x 8 x 4 ins, 12 ins in
the ground for 1/4 sec. cor.
marked 1/4 on N. face; dig
pits 18 x 18 x 12 ins E + W.
of stone 3 ft dist; raise
a mound of earth 3 1/2 ft
base, 1 1/2 ft high N. of cor.

79.97 The cor of secs 23, 24,
25 and 26

Land level
Soil 2^d rate
No timber

40.00 N. 0° 06' W bet secs 23 + 24
Set a granite rock
12 x 10 x 6 ins, 8 ins in the
ground for 1/4 sec. cor.
marked 1/4 on W. face

Survey of Subdivisions

the

80.00

dig pits 18X18X12 ins
 N + S. of stone, 3 ft dist
 and raise a mound
 of earth 3 1/2 ft base
 4 1/2 ft high W. of cor.
 Set a granite rock
 17X10X7 ins, 12 ins in
 the ground, for cor of
 sec. 13, 14, 23 and 24.
 marked with 3 notches
 on S. and 1 notch on
 E. edges; dig pits
 18X18X12 ins in each sec
 3 1/2 ft dist; and raise
 a mound of earth
 4 ft base, 2 ft high
 W. of cor.

Land level

Soil 2nd rate Not under

Tfr. 17 S. R 24 E.
 chs

N. $89^{\circ}59'E$ on a random
 line bet secs 13 and 24

40.00 Set temp $\frac{1}{4}$ sec. cor.

79.97 The cor of secs 13, 18, 19 + 24
 on E. Body of Tfr
 which is a post 4x4 ins
 marked and witnessed
 as described by the
 Surveyor General.

Thence I run

S. $89^{\circ}59'W$ on a true
 line bet secs 13 and 24
 overlol plain land.

39.98 $\frac{1}{2}$ Set a granite rock 18x
 10x10 ins, 12 ins in the
 ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4}$ on N. face;
 dig pits 18x18x12 ins
 E + W. of stone 3ft dist
 and raise a mound
 of earth 3 $\frac{1}{2}$ ft base.

Survey of Subdivisions
cls

79.97 $1\frac{1}{2}$ ft high N. of cor.
The cor of secs 13, 14,
23 and 24.

Land level.

Soil 2^d rate

No timber

N. $0^{\circ}06'$ W. bet secs 13 & 14

Over level land.

40.00 Set a granite rock
" 12x8x6 ins, 8 ins in the
ground for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}$ on W. face.

dig pits 18x18x12 ins
N. + S. of stone 3 ft dist
and raise a mound
of earth $3\frac{1}{2}$ ft base
 $1\frac{1}{2}$ ft high W. of cor.

80.00 Set a granite rock

Tr 17 S. R. 24 E
 ch

18x12x8 ins, 12 ins in the
 ground for cor secs
 11, 12, 13 and 14, marked
 with 4 notches on S. and
 1 notch on E. edges.

Dig pits 18x18x12 ins in
 each sec, 5 1/2 ft dist,
 and raise a mound
 of earth 4 ft base, 2 ft
 high W. of cor.

Land level
 Soil 2nd rate
 No timber

N. 89° 59' E on a random
 line bet secs 12 & 13

40.00 Set temp 1/4 sec. cor.

79.95 Intersect E. byd of
 Tr. 3 lks N. of cor.

Survey of Subdivisions
chs

of secs 7, 12, 13 + 18
which is a frost
4x4 ins, marked
and witnessed
as described by the
Surveyor General.

Thence I run
It. on true line
bet. secs 12 and 13:

11.85' ^{Old line laid} Freight Road Cochise
to Pearce brs N.N.W
and S.S.E.

14.27' Telegraph line Cochise
to Pearce brs S.S.E + N.N.W.

14.42' Telegraph Road same
course

25.00' Upper road, same course

39.97 1/2' Set a granite rock
18x10x8 ins 12 ins in
the ground for

Tr 17 S. R 24 E
 chs

$\frac{1}{4}$ sec. cor; marked
 $\frac{1}{4}$ on N. face; dig
 pits $18 \times 18 \times 12$ ins, E + W
 of cor, 3 ft. dist, and
 raise a mound of
 earth $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft
 high N. of cor.

79.95 cor. secs. 11, 12, 13 + 14.
 Land level,
 Soil 2nd rate
 No. timber

40.00 N. $0^{\circ} 06'$ W. bet secs 11 + 12
 Over level land
 Set a granite rock
 $18 \times 8 \times 8$ ins, 12 ins in
 ground for $\frac{1}{4}$ sec cor
 marked $\frac{1}{4}$ on N. face
 dig pits $18 \times 18 \times 12$ ins
 N. + S of stone 3 ft dist.

Survey of subdivisions
chs

raise a mound of earth $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high W. of cor.

80,00 Set a granite rock $20 \times 8 \times 8$ ins 15 ins in ground for cor secs 1, 2, 11 and 12, marked with 5 notches on S. and 1 on E edges. dig pits $18 \times 18 \times 12$ ins in each sec $5\frac{1}{2}$ ft dist, raise a mound of earth 4 ft base 2 ft high W. of cor.

Land level
Soil 2nd rate.
No timber

Twp 17 S. R 24 E.

chs

East on a random
line bet. secs 1 and 12

40.00 Sit temp 1/4 sec. cor.

79.95 Intersect E. body line
3 lks S. of cor secs

1, 6, 7 and 12, which is
a 4x4 post marked
and witnessed as
described by the
Surveyor General

Thence I run
S. 89° 59' W on true
line bet secs 1 and 12

Over level land.

39.97 1/2 Sit a granite rock

14x10x8 ins, 10 ins in
the ground for

1/4 sec. cor, marked
1/4 on N. face, dig
fits 15x18x12 ins

Survey of Subdivisions
 chs of

- E and W of stone
 3 ft dist; raise a
 mound of earth
 3 1/2 ft base 1 1/2 ft high
 N. of cov.
- 44.65 Freight road Cochise
 to Pearce brs S.S.E. +
 N.N.W.
- 48.80 Telegraph line bet
 same points the
 same course
- 48.95 Telegraph road brs
 S.S.E. and N.N.W.
- 62.20 Upper road bet Cochise
 and Pearce brs S.S.E. +
 N.N.W.
- 79.95 Cov secs 1, 2, 11 and 12
 Land level. Soil 2^d rate.
 No timber
-

Tfr 17 S R 24 E.

chs

N $0^{\circ}06'W$ on a random
line bet secs 1 and 2

40.00 Set temp $\frac{1}{4}$ sec. cor

80.03 Intersect N. bdy of Tfr
18 lks E of cor secs

1, 2, 35 and 36. A rock
as described in notes
of resurvey of N.
bdy by me

Thence I run,

S $0^{\circ}14'E$. on true line
bet secs 1 and 2
over level land.

1.50 Freight-road Cochise
to Pearce br S.S.E. +
N. N. W.

13.10 Telegraph line Cochise
to Pearce br S.S.E. + N. N. W.

13.20 Telegraph road br
S.S.E. and N. N. W.

Survey of Subdivisions

chs

40.03

Set a granite rock
 14x7x6 ins, 10 ins in
 ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4}$ on W. face.
 dig pits 18x18x12 ins
 N & S. of stone 3 ft dist.
 raise a mound of
 earth $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high
 W. of cor.

41.35

Upper road Cochise
 to Pearce brs S.S.E. + N.N.W.

80.03

Coverces 1, 2, 11 and 12
 Land level.
 Soil 2nd rate
 No timber.

Jan 31, 1902

The 17 S. R 24 E.
 chs

Feb 1st
 at the cor of secs
 2, 3, 34 and 35 on S. bdy
 which is a granite
 rock, marked and
 witnessed as described
 by the Surveyor General.

Thence I run
 N. 0° 06' W. bet secs 34 +
 35, over level ground.

18.95 Gulch 30 lks wide,
 course N. E.

24.10 Road to Grapevine can-
 you brs. N. and E.

40.00 Set a granite rock
 20x10x8 ins, 15 ins in
 ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4}$ on W. face,
 dig pits 18x18x12 ins
 N. and S. of stone, 3 ft
 dist; and raise a

Survey of Subdivisions
chs of

80.00 mound of earth $3\frac{1}{2}$ ft.
base, $1\frac{1}{2}$ ft high, St. of cor
Set a granite rock $18 \times$
 10×4 ins, 12 ins in the
ground, for cor of secs
26, 27, 34 and 35, marked
with 1 notch on S. and
2 notches on E. edges.
dig pits $18 \times 18 \times 12$ ins
in each sec. $5\frac{1}{2}$ ft dist.
and raise a mound
of earth, 4 ft base, 2 ft
high, St. of cor.
Land level
Soil 2nd rate
no timber

E. on a random line
bet. secs. 26 and 35.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

The 17 S. R. 24 E.

chis

80.00

Intersect N. & S. line
10 lks S. of cor of secs
25, 26, 35 and 36.

thence I run

S. $89^{\circ}56'W$ on a true
line bet secs 26 and 35-

Over level ground.

40.00

Set a granite rock $20 \times 6 \times$
 5 ins, 15 ins in ground,
for $\frac{1}{4}$ sec. cor, marked
with $\frac{1}{4}$ on the N. face
dig pits $18 \times 18 \times 12$ ins
E & W. of stone, 3 ft dist.
and raise a mound
of earth, $3\frac{1}{2}$ ft base
 $1\frac{1}{2}$ ft high N. of cor.

47.25

Road from Pearce
to Cochise Stronghold
course N. W. and S. E.

80.00

The cor of secs 26, 27, 34 & 35

Survey of subdivisions
etc

Land level.
Soil 2^d rate.
No timber.

- 10.35 ^{per acre land} N. 0° 06' W. betwees 26 + 27
Road from Pearce to
Cochise Stronghold
course N. W. and S. E.
- 40.00 Set a limestone 18x6x
5 ins, 12 ins in the
ground, for 1/4 sec. cor.
Marked 1/4 on W. face;
dig pits 18x18x12 ins
N. & S. of cor, 3 ft dist,
and raise a mound
of earth 3 1/2 ft base
1 1/2 ft high N. of cor
- 80.00 Set a granite rock
18x8x6 ins, 12 ins in the
ground for cor secs

Tfr 17 S. R. 24 E

chs

22, 23, 26 and 27, marked
with 2 notches on S
and 2 on E. edges,
and dig pits $18 \times 18 \times 2$ ins
in each sec $5\frac{1}{2}$ ft dist
raise a mound of
earth 4 ft base, 2 ft high
W. of cor.

Land level.

Soil 2nd rate.

No timber

N. $89^{\circ}56'E$ on a random
line bet secs 23 + 26

40.00 Set temp $\frac{1}{4}$ sec. cor.

80.06 Intersect N. + S. line

2 lks S. of cor sec

23, 24, 25 and 26

Thence Iron

Survey of Subdivisions
chs

- S. $89^{\circ}55'$ on a true line bet secs 23 + 26.
 One level ground.
- 40.03 Set a granite rock
 $18 \times 9 \times 5$ ins, 12 ins in
 ground for $\frac{1}{4}$ sec. cor.
 marked with $\frac{1}{4}$ on N.
 face; dig pits $18 \times 18 \times$
 12 ins E & W of stone
 3 ft dist; raise a mound
 of earth $3\frac{1}{2}$ ft base
 $4\frac{1}{2}$ ft high N. of cor
- 80.06 The cor of secs 22, 23, 26 +
 27.
 Land level.
 Soil 2nd rate
 no timber
-

The 17 S. R. 24 E
 chs

N 0° 06' W. bet secs 22 + 23
 Over level land

40.00

Set a granite rock
 14 x 9 x 5 ins 10 ins in the
 ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4}$ on W. face
 dig pits 18 x 18 x 12 ins
 N. and S. of stone 3 ft
 dist, and raise a
 mound of earth
 3 $\frac{1}{2}$ ft base 1 $\frac{1}{2}$ ft high
 W. of cor.

80.00

Set a limestone 20 x
 9 x 5 ins, 13 ins in the
 ground for cor. of
 secs 14, 15, 22 + 23
 marked with 3 notches
 on S. and 2 on E. edges
 dig pits 18 x 18 x 12 ins
 in each sec 3 $\frac{1}{2}$ ft dist.

Survey of Subdivisions
che

raise a mound of
earth 4 ft base, 2 ft high
N. of cor.

Soil 2nd rate

Land level.

No timber

N. $89^{\circ} 55' E$ on a random
line bet sec 14 and 23.

40.00 Set temp 1/4 sec, cor.

80.04 Intersect N. + S. line 5 lks
N. of cor of sec 13, 14, 23 + 24

Thence I run

S. $89^{\circ} 57' W$ on a true
line bet sec 14 + 23

Over level land.

40.02 Set a granite rock
14 X 10 X 6 ins, 10 ins in
the ground for 1/4 sec. cor.

31
The 17 S. R. 24 ^{BOOK} 854 No. 854
che

marked $\frac{1}{4}$ on N. face
dig pits 18x12x12 ins
E and W. of stone 3 ft-
dist, and raise a
mound of earth
 $3\frac{1}{2}$ ft base, $1\frac{1}{2}$ ft high
N. of cor.

80.04 The cor of secs 14, 15-
22 and 23.

Land level
Soil 2nd rate
No timber

N 0° 06' W. bet. secs 14 + 15.

Over level ground

40.00 Set a granite rock
17x8x6 ins, 12 ins in the
ground for $\frac{1}{4}$ sec. cor
marked $\frac{1}{4}$ on W. face;
dig pits 18x18x12 ins

Survey of Subdivisions
che

N. and S. of cor. 3 ft dist.
and raise a mound
of earth $3\frac{1}{2}$ ft base
 $1\frac{1}{2}$ ft high W. of cor.
80.00 Set a granite $14 \times 8 \times 7$ ins
10 ins in the ground
for cor sees 10, 11, 14 + 15
marked with 4 notches
on S. and 2 on E. edges.
Dig pits $18 \times 18 \times 12$ ins,
in each sec. $5\frac{1}{2}$ ft
dist, and raise a
mound of earth 4 ft
base, 2 ft high W. of cor
Land level.
Soil 2^d rate
No timber

The 17 S. R 24 E.

chs

N. $89^{\circ} 57' E$ on a random
line bet secs 11 and 14

40.00 Set. temp $\frac{1}{4}$ sec. cor.

80.02 Intersect N. + S. line 2 lks

S. of cor secs 11, 12, 13 + 14

Thence I run on
true line.

S. $89^{\circ} 56' W$ bet secs 11 + 14

Over level ground

40.01 Set a granite rock $16 \times 7 \times 6 \frac{2}{3}$

11 ins in ground, for $\frac{1}{4}$ sec. cor

marked $\frac{1}{4}$ on N. face

dig pits $18 \times 18 \times 12$ ins

E + W of stone 3 ft. dist.

raise a rnd of earth

$3 \frac{1}{2}$ ft base, $1 \frac{1}{2}$ ft high

N. of cor.

80.02 Cor of secs 10, 11, 14 + 15.

Land level, soil 2^d rate.

No timber

Survey of Subdivisions
etc

- 40.00 N. $0^{\circ}06'$ W. bet secs 10 & 11
 Set a granite rock
 16x10x8 ins, 11 ins in ground
 for $\frac{1}{4}$ sec. cor. marked
 $\frac{1}{4}$ on W. face; dig pits
 18x18x12 ins N. & S. of cor
 3 ft dist. and raise
 mound of earth $3\frac{1}{2}$ ft
 base $1\frac{1}{2}$ ft high W. of cor.
- 80.00 Set a granite rock
 24x10x4 ins, 18 ins in
 ground for cor secs
 2, 3, 10 & 11, marked with
 5 notches on S, and 2
 notches on E. edges.
 dig pits 18x18x12 ins
 in each sec. $5\frac{1}{2}$ ft
 dist. raise a mound
 of earth 4 ft base
 2 ft high W. of cor

Tfr 17 S. R. 24 E
 chs

Land level.
 Soil 2nd rate
 No timber

N. $89^{\circ} 36' E$ on a random
 line bet secs 2 and 11

40.00 Set temp $\frac{1}{4}$ sec. cor.

80.03 Intersect N. and S. line
 3 lks N. of cor sec 1, 2, 11 & 12

Thence I run

S. $89^{\circ} 37' W$ on a true
 line bet secs 2 and 11

40.01 $\frac{1}{2}$ Our level ground
 Set a granite rock
 20x10x8 ins, 15 ins in ground

for $\frac{1}{4}$ sec cor, marked
 $\frac{1}{4}$ on N. face; dig

pit to 18x18x12 ins, E & W
 of stone 3 ft dist.

raise a mound
 of earth $3\frac{1}{2}$ ft base,

Survey of subdivisions
the

1 1/2 ft high N. of cor.
80.03 Cov secs 2, 3, 10 and 11
Land level.
Soil 2nd rate.
No timber

^{200 8:10}
N. 0° 6' W on a random
line bet secs 2 and 3.

40.00 Set temp 1/4 sec cor.

80.04 Intersect N. bdy of Tfr.
³⁰
30 lks E. of cor secs 2, 3,
34 and 35; which is
a post marked and
witnessed as described
by the Surveyor General.
Thence I run
S. 0° 19' E on a true line
bet secs 2 and 3.
Over level ground.

40.04 Set a limestone

Tp 17 S. R 24 E
 dis

18 X 10 X 6 ins, 12 ins in the
 ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4}$ on W. face;
 dig pits 18 X 18 X 12 ins
 N. and S. of stone 3 ft dist.
 raise a mud of earth
 $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high
 W. of cor.

8004 Cor. secs. 2, 3, 10 and 11

Land level
 Soil 2^d rate.

No timber

Feb. 1st 1902

Feb 3rd

From cor. secs. 3, 4, 33 & 34
 on S. bdy of Tp, which
 is a granite rock
 marked and witnessed
 as described by the

Survey of Subdivisions
cls

- Surveyor General
Drum
- 110° 07' N bet sec 33 + 34
Over level ground
- 12.75- Road from Pearce to
Noonan Ranch course N. of E.
- 38.50 Road Pearce to Grapevine
Canyon, course N. W. + S. E.
- 40.00 Set a granite rock
14x10x8 ins, 10 ins in the
ground, for 1/4 sec cor
marked 1/4 on N. face;
dig pits 18x18x12 ins
N. and S. of stone, 3 ft dist
and raise a mound
of earth 3 1/2 ft base
1 1/2 ft high, W. of cor.
- 80.00 Set a granite rock
18x6x5 ins, 12 ins in the
ground for cor. sec

The 17 S. R 24 E

chs.

27, 28, 33 and 34, marked
with 1 notch on S, and
3 notches on E. edges;
dig pits 18x18x12 ins
in each sec, $5\frac{1}{2}$ ft-
dist, and raise a
mound of earth
4 ft base, 2 ft high N.
of cor.

Land level.

soil 2^d rate,

no timber

East on a random
line but sec 27 + 34

40.00 Set temp $\frac{1}{4}$ sec, cor.

80.01 Intersect N. + S. line

9 like N. of cor of sec
26, 27, 34 and 35. Thence

I run

40

BOOK 854

Survey of subdivisions
chs

N. $89^{\circ}56'W$. on a true line
bet. secs 27 and 34.

Over level ground
40.00 $\frac{1}{2}$ Set a granite rock
16x8x4 ins, 11 ins in the
ground, for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}$ on N. face.
dig pits 18x18x12 ins
E. and W. of stone
3 ft dist, and raise
a mound of earth
3 $\frac{1}{2}$ ft base, 1 $\frac{1}{2}$ ft high
N. of cor.

80.01 The cor of secs 27, 28, 33 + 34.
Land level
Soil 2 $\frac{1}{2}$ rate
no timber

N. $0^{\circ}07'W$ bet secs 27 + 28
Over level land.

Twp 17, S. R. 24 E.

the

40.00

Set a granite rock
 15 x 8 x 6 ins, 10 ins in the
 ground, for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4}$ on W. face.
 dig pits 18 x 18 x 12 ins
 N. and S. of stone 3 ft dist
 and raise a mound of
 earth $3\frac{1}{2}$ ft base, $1\frac{1}{2}$ ft
 high W. of cor.

5-3. 80

Road Pearce to Stronghold
 brs N. W. + S. E.

80.00

Set a granite rock 16 x 12 x 8
 ins, 11 ins in the ground
 for cor secs 21, 22, 27 + 28.
 marked with 2 notches
 on S. + 3 on E. edges;
 dig pits 18 x 18 x 12 ins in
 each sec. $5\frac{1}{2}$ ft dist;
 raise a mound of
 earth 4 ft base, 2 ft high

Survey of Subdivisions
chs

W. of cor.

Land level

Soil 2^d rate

No timber

S. $89^{\circ}56'E$ on a random
line bet secs 22 + 2740.00 Set temp $\frac{1}{4}$ sec. cor

80.00 Cor. secs. 22, 23, 26 + 27.

Thence I run

N. $89^{\circ}56'W$ on a true line
bet secs 22 and 27

One level land.

40.00 Set a granite rock
16X10X8 ins, 11 ins in the
ground for $\frac{1}{4}$ sec. mark-
ed. $\frac{1}{4}$ on N. face; dig
pits 18X18X12 ins. E & W
of stone 3 ft dist; and
raise a mound of

Twp. 17 S. R. 24 E.

chs

earth, $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft
high N. of cor.

80.00 The cor secs 21, 22, 27 + 28
Land level
Soil 2nd rate
No timber

40.00 N. $0^{\circ}07'$ W. bet secs 21 + 22
Own land land
Set a granite rock $18 \times 6 \times$
 5 ins, 12 ins in ground
for $\frac{1}{4}$ sec cor, marked
 $\frac{1}{4}$ on W. face; dig pits
 $18 \times 18 \times 12$ ins N. + S. of stone
 3 ft dist; and raise
a mound of earth
 $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high
W. of cor.

80.00 Set a granite rock
 $18 \times 10 \times 6$ ins, 12 ins in
ground for cor.

Survey of subdivisions

secs 15, 16, 21 and 22.
 marked with 3 notches
 on S. and 3 notches
 on E. edges, also T. 17 S
 on N.E. and R. 24 E, on
 S.E. faces; dig pits
 18x18x12 ins in each sec
 5-1/2 ft dist; and raise
 a mound of earth 4 ft base
 2 ft high N. of cor.
 Whence Dos Cabezas
 Peak brs N $41^{\circ} 37' E$
 Old house at Sulphur
 Springs brs N. $59^{\circ} 30' E$
 dist. about 7. miles
 U.S. location monument
 N. 1249, Pearce brs S. $54^{\circ} 57' E$
 Eagle Butte Cochise
 Stronghold brs S. $71^{\circ} 55' E$
 Land level

Tfr 17 S R 24 E.

chs

Soil 2^d rate
No timber

S. $89^{\circ} 56' E$ on a random
line bet secs 15 + 22.

40.00

Set temp $\frac{1}{4}$ sec. cor.

80.01

Intersect N. + S. line

7 lks S of cor sec

14, 15, 22, + 23, thence run

N. $89^{\circ} 59' W$ on true line

bet secs 15 + 22

One level land.

40.00 $\frac{1}{2}$

Set a granite rock
16 X 10 X 8 ins, 11 ins in the
ground for $\frac{1}{4}$ sec cor

marked $\frac{1}{4}$ on N. face

dig pits 18 X 18 X 12 ins

E. and W. of stone

3 ft dist; raise a

mound of earth

Survey of Subdivisions
chc

3½ ft base, 1½ ft high
N. of cor.

80.01 The cor secs 15, 16, 21 + 22
Land level
soil 2¢ rate
No timber

40.00 N. 0°07' W. bet. secs 15 + 16
^{over level land}
 set a granite rock
 13 x 7 x 5 ins, 10 ins in the
 ground, for ¼ sec cor
 marked ¼ on N. face;
 dig pits 18 x 18 x 12 ins
 N. and S. of stone 3 ft
 dist, and raise a
 mound of earth 3½ ft-
 base, 1½ ft high N. of cor.

80.00 set a granite rock
 18 x 8 x 5 ins, 12 ins in
 the ground for cor.

The 17 S. R. 24 E.

the

of secs 9, 10, 15 + 16, marked
with 4 notches on S. and
3 on E. edges; dig pits
18x18x12 ins in each sec
3-1/2 ft dist; and raise
a mound of earth
3 1/2 ft base, 1 1/2 ft high
N. of cor.

Land level

Soil 2^d rate

No timber

S. $89^{\circ}59'E$ on a random
line bet secs 10 + 15-

40.00 set temp 1/4 sec. cor.

80.03 Intersect N. + S. line, 9 lbs
S of cor secs 10, 11, 14 + 15-

Thence I run

S $89^{\circ}37'W$ on true line
bet secs 10 + 15; over

Survey of subdivisions
chs

level ground

40.01 1/2 Set a granite rock
16x8x6 ins, 11 ins in the
ground, for 1/4 sec cor
marked 1/4 on N. face;
dig pits 18x18x12 ins E+W.
of stone 3 ft dist
and raise a mound
of earth 3 1/2 ft base, 1 1/2 ft
high N. of cor.

80.03 Corsecs 9, 10, 15 + 16
Land level,
soil 2^d rate
no timber

N. 0° 07' W bet sees 9 + 10
Once level land

40.00 Set a granite rock
14x8x6 ins 10 ins in
ground for 1/4 sec cor

Tr. 17 S. R. 24 E.

chs

marked $\frac{1}{4}$ on N. face
dig pits $18 \times 18 \times 12$ ins
N. + S. of stone 3 ft dist.
and raise a mound
of earth $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft
high N. of cor.

80.00

Set a granite rock
 $24 \times 10 \times 4$ ins, 18 ins in the
ground for cor sec
3, 4, 9 and 10, marked
with S notches on S, and
3 on E. edges, dig pits
 $18 \times 18 \times 12$ ins in each sec
 $5\frac{1}{2}$ ft dist, and raise
a mound of earth
4 ft base $1\frac{1}{2}$ ft high
N. of cor.

Land level. soil 2^d rate
No timber

50

BOOK 854

Survey of subdivisions
cls

- N. $89^{\circ} 58' E$ on a random
line bet secs 3 + 10
- 40.00 Set temp $\frac{1}{4}$ sec. cor.
- 80.06 Intersect N. + S. line 2 lks
S. of cor secs 2, 3, 10 + 11
Thence run
S. $89^{\circ} 56' W$ on true line
bet. secs. 3 and 10
On level land
40.03 Set a limestone $6 \times 19 \times 6$ ins
11 ins in the ground
for $\frac{1}{4}$ sec cor. marked
 $\frac{1}{4}$ on N. face; dig pits
 $18 \times 18 \times 12$ ins, E + W of stone
3 ft dist; and raise
a mound of earth
 $3\frac{1}{2}$ ft base, $1\frac{1}{2}$ ft high
N. of cor.
- 80.06 The cor of secs 3, 4, 9 + 10
Land level
Soil 2^d rate

Tfr. 17 S. R 24 E

chs

no timber

$210^{\circ} 7'$ W. on a random
line bet secs 3 and 4

46.00 Set temp $\frac{1}{4}$ sec. cor.

80.04 Intersect N. bdy of Tfr

$288^{\circ} 25'$ E of cor secs 3, 4, 33+34

which is a frost, marked
and witnessed as described
by the Surveyor General
Thence I run

$50^{\circ} 19'$ E, on a true line
bet secs. 3 and 4

Over level land.

40.04 Set a limestone $17 \times 10 \times$

5 ins, 12 ins in ground
for $\frac{1}{4}$ sec. cor. marked
 $\frac{1}{4}$ on N. face; dig pits
 $18 \times 18 \times 12$ ins N. & S. of stone
3 ft dist; and raise

Survey of subdivisions
ch 2

a mound of earth
3 1/2 ft base, 1 1/2 ft high
W. of cor.

77.20 Road N.Y. Ranch to
Cochise Stronghold
course S.W. + N.E.

80.04 The cor secs. 3, 4, 9 + 10
Land level
Soil 2^d rate.
No timber

Feb. 3, 1902

Feb 4, 1902

From the cor of secs
4, 5, 32 and 33 on S. body
of Tp, which is a
granite stone set firmly
in the ground, marked
and witnessed as
described by the

Twp. 17 S. R. 24 E.

chr

Surveyor General
I runN. $0^{\circ}07'$ W bet sec 32 + 33

One level + rolling land.

40.00 Set a granite rock
16x6x6 ins, 11 ins in ground
for $\frac{1}{4}$ sec. cor. marked
 $\frac{1}{4}$ on W. face; dig pits
18x18x12 ins N. + S. of stone
3 ft dist; and raise
a mound of earth
 $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high
W. of cor.

44.50 Road to Grapevine
canyon bet N. W + S E.

80.00 Set a granite rock
18x8x6 ins, 12 ins in
ground for cor secs
28, 29, 32 and 33 marked
with 1 notch on S.

Survey of Subdivisions
cho

and 4 on E. edges.
dig pits 18x18x12 ins
in each sec. 5-1/2 ft
dist; and raise
a mound of earth
4 ft base, 2 ft high
W. of cor.

Land level + rolling
Soil 1st + 2nd rate

Few scattering stumps
No timber standing

E. on a random line
bet secs. 28 and 33.

40.00 set temp 1/4 sec. cor.

79.96 Intersect N. + S. line
2 lks S. of cor secs 27, 28,
33 + 34. Thence I run
S 89° 39' W on a true line

The 17 S R 24 E
the

bet secs 28 + 33

One level + hilly land

25.30 Road Cochise To Middle
march, bet N. and S.

39.98 Set a limestone $16 \times 8 \times 8$ ins
11 ins in the ground
for $\frac{1}{4}$ sec. cor. marked
 $\frac{1}{4}$ on N. face; dig pits
 $18 \times 18 \times 12$ ins E + W. of stone
3 ft dist; and raise
a mound of earth
 $3\frac{1}{2}$ ft base, $1\frac{1}{2}$ ft high
N. of cor

45.00 Ascend low hill

64.00 Leave low hill. enter flat.

79.96 Cor secs 28, 29, 32 + 33

Land level + hilly
Soil 2nd + 3rd rate.

No timber

5-6

BOOK 854

Survey of Subdivisions
chs

- 6.00 N. $0^{\circ} 07' W.$ bet secs 28 + 29.
Land level + mountainous
Land broken + mountainous
along W. slope of low
conical mountain
- 31.00 Slope of mountain -
descend
- 40.00 Set a granite rock $17 \times 12 \times$
 10 ins, 12 ins in ground
for $\frac{1}{4}$ sec. cor. marked
 $\frac{1}{4}$ on W. face dig pits
 $18 \times 18 \times 12$ ins N. + S. of stone
 3 ft dist, and raise
a mound of earth
 $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high
W. of cor.
Leave mountainous
Entire flat,
- 49.85. Wash of Grapevine
Canyon 1.25 chs wide
course N. E.

Tfr. 17 S. R 24 E

80.00

Set a granite rock
 18x10x10 ins, 12 ins in the
 ground for cor. secs.
 20, 21, 28 + 29, marked
 with 2 notches on S. and
 4 on E. edges; dig pits
 18x18x12 ins in each sec.
 5 1/2 ft dist, raise a mid
 of earth 4 ft base, 2 ft-
 high N. of cor.

Land level and moun-
 tainous.

Soil 2^d + 3^d rate

No timber.

Mountainous land

34 chains

N. 89.5° E on a random
 line bet secs, 21 + 28

5-8

BOOK 854

Survey of subdivisions
chs40.00 Set temp $\frac{1}{4}$ sec. cor.

79.95 Intersect N. & S. line 2 lks

N. of cor sec 21, 22, 27+28

Thence I run

W. on true line bet

secs. 21 and 28

Over level land

39.97 $\frac{1}{2}$ Set a granite rock

17x8x6 ins, 12 ins in

the ground for $\frac{1}{4}$ sec. cor.marked $\frac{1}{4}$ on N. face;

dig pits 18x18x12 ins

E & W. of cor, 3ft dist

and raise a mound

of earth $3\frac{1}{2}$ ft base $1\frac{1}{2}$ ft high N. of cor.

47.40 Road Cochise to Middle

march brs. S. & N.

5-1.20 Road Pearce to Cochise

stronghold brs N. & S, E.

Tr 17 S. R. 24 E.

dis

- 66.60 Wash of Grapevine Canyon
3 chs wide, course N. E.
- 79.95 The cor. secs. 20, 21, 28 + 29.
Land level.
Soil 2^d rate
No timber

N 0° 07' W. bet secs 20 + 21
Over level land.

- 130.5 Road Pearce to Cochise
Stronghold bet N. W. + S. E.
- 37.00 Road to Goodhope bet N. W. + S. E.
- 40.00 Set a granite rock
16 x 7 x 6 ins, 11 ins in the
ground, for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}$ on N. face;
dig pits 18 x 18 x 12 ins
N. + S. of stone 3 ft dist.
and raise a mound
of earth $3\frac{1}{2}$ ft base

Subdivisions Tfr. 17 S. R 24 E
che

80.00

1 1/2 ft high W. of cor.
Set a granite rock
18x10x8 ins, 12 ins in
ground for cor. sec
16, 17, 20 + 21, marked
with 3 notches on
S. and 4 on E. edges.
dig pits 18x18x12 ins
in each sec 5 1/2 ft-
dist. and raise a
mound of earth
4 ft base 2 ft high
W. of cor.
Land level.
Soil 2^d rate.
No. timber.

E. on a random line
bet sec 16 and 21

Concluded, Book 855.