

862

4  
No. 862

2.

BOOK 862

*Fractional*

4-671

FIELD NOTES  
GENERAL LAND OFFICE.

*Subdivision*

*— of —*

*T.16S. R.23E.*

*Indexed, Book 861*

Township 165 R. 23E 60

6	5	110	4	87	3	67	2	1
			108		85			
7	8	106	9	82	10	63	11	12
			104		79		61	
18	17	101	16	77	15		14	13
19	112	20	90	21	69	22	23	24
116		114		92				
30	118	29	94	28	74	27	26	25
		119		96				
31	32	98	33	34		35		36

Subdivision of T. 16 S. R. 23 E. - Continued

chains

and 2 notches on E. edges;  
dig pits 18 x 18 x 12 ins.,  
in each sec. 5 1/2 ft. dist.,  
and raise a mound of  
earth 4 ft. base, 2 ft. high,  
W. of cor.

Land rolling <sup>to</sup> mountainous  
Soil, gravelly loam; 3<sup>rd</sup> rate  
No timber; under growth  
sage.

Mountainous or land  
covered with dense under-  
growth 44.50 chs.

S 89° 50' E, on a random  
line bet. sees. 11 and 14

40.00 Set. temp. 1/4 sec. cor.

79.94 Intersect N. an S. line, 5 lks  
N. of cor. of sees. 11, 12, 13 <sup>and</sup> 14



# Subdivision of chains

Thence I run

- N 89° 48' W., bet. secs. 11 <sup>2nd</sup> / 14  
 Over level <sup>2nd</sup> gently rolling land
- 4.96 Trail, bears N. W. E <sup>2nd</sup> of S. S. W.
- 18.25 Road from Dagoon Summit  
 to Wilcox, bears N 29° 56' E <sup>2nd</sup> of S 29° 56' W.
- 18.43 Telegraph line, bears N 29° 56' E  
 and S 29° 56' W
- 19.29 Middle of single track  
 of the Southern Pacific  
 Railroad, bears N 29° 56' E <sup>2nd</sup> of  
 S 29° 56' W.
- 20.40 Telegraph line, bears N 29° 56' E  
 and S 29° 56' W.
- 20.78 Road from Dagoon Summit  
 to Wilcox, bears N 29° 56' E <sup>2nd</sup> of S 29° 56' W.
- 39.97 Set a pine post, 3 ft. long  
 4 ins. sq. with marked  
 stone, 24 ins. in the ground

## T. 16 S. R. 23 E. - Continued

Chains

for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  S. on N. face; dig pits  
 $18 \times 18 \times 12$  ins. E. and W. of  
 post, 3 ft. dist.; and raise  
 a mound of earth,  $3\frac{1}{2}$  ft.  
 base,  $1\frac{1}{2}$  ft. high, N. of cor.

68.00 Enter dense sage under-  
 growth, bears N. N. W.  $2^{\text{nd}}$  of S. S. E.

79.94 The cor. of sees. 10, 11, 14  $2^{\text{nd}}$  of 15  
 Land level  $2^{\text{nd}}$  gently rolling  
 Soil, sandy loam;  $2^{\text{nd}}$  rate  
 No timber; undergrowth  
 sage.

Land covered with dense  
 undergrowth, 12 chs.

N $0^{\circ}$  1' W., bet. sees. 10  $2^{\text{nd}}$  of 11  
 Along E. slope of ridge,  
 through sage undergrowth

## Subdivision of

Chains

- 3.14 Trail, bears N.E. <sup>2nd</sup> S.W.
- 20.00 Descend
- 20.65 Trail, bears N.W. <sup>2nd</sup> S.E.
- 22.40 Trail, bears N.N.W. <sup>2nd</sup> S.S.E.
- 25.12 Trail, bears N.N.W. <sup>2nd</sup> S.S.E.
- 27.00 Enter bottom, bears Easterly  
and Westerly
- 30.00 Leave dense sage undergrowth  
bears E. and W.
- 40.00 Set a limestone, 16x16x4  
ins., 11 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face; dig pits  
18x18x12 ins., N. and S.  
of stone, 3 ft. dist. and  
raise a mound of earth  
3 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high  
W. of cor.
- 80.00 Set a limestone 14x12x6



## T. 16 S. R. 23 E. - Continued

Chains

ins., 9 ins. in the ground  
for cor. of secs. 2, 3, 10<sup>3rd</sup> & 11,  
marked

T. 16 S. on N. E. and  
R. 23 E. on S. E. with  
5 notches on S. and 2  
notches on E. edges; dig  
pits 18 x 18 x 12 ins. in  
each sec. 5 1/2 ft. dist.;  
and raise a mound of  
earth 4 ft. base, 2 ft.  
high, W. of cor.

Land rolling<sup>2nd</sup> & mountainous  
Soil, gravelly loam; 2<sup>nd</sup> rate  
No timber; undergrowth  
sage and mesquite.

Mountainous or land covered  
with dense undergrowth  
30 chs.

## Subdivision of

Chains

- S 89° 48' E, on a random  
 line bet. secs. 2 and 11  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.92 Intersect N. and S. line  
 at cor. of secs. 1, 2, 11<sup>2nd</sup> & 12  
 Thence I run  
 N 89° 48' W, on a true line  
 bet. secs. 2 and 11  
 18.28 Trail, bears N. N. E.  $\frac{3}{4}$  of S. S. W.  
 18.55 Trail, bears N. W.  $\frac{3}{4}$  of S. E.  
 22.82 Trail, bears N. W.  $\frac{3}{4}$  of S. E.  
 39.96 Set a lime stone, 12 x 7 x 7  
 ins., 8 ins. in the ground  
 for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; dig pits  
 18 x 18 x 12 ins., E. and W. of  
 stone, 3 ft. dist.; and raise  
 a mound of earth, 3  $\frac{1}{2}$  ft  
 base, 1  $\frac{1}{2}$  ft. high, N. of cor.



## T. 16 S. R. 23 E. - Continued

Chains

Enclosure, bears  $N 9^{\circ} W$ .  
10 chs. dist.

45.71 Trail, bears Easterly <sup>2<sup>nd</sup></sup> and Westerly

79.92 The cor. of secs. 2, 3, 10 and 11  
Land level

Soil, loam; 2<sup>nd</sup> rate

No timber; undergrowth  
scattering sage.

$N 0^{\circ} 1' W$ , bet. secs. 2 and 3

Over gently rolling land;

1.00 Enter dense sage undergrowth,  
bears E. and W.

40.00 Set a lime stone  $18 \times 8 \times 4$  ins.  
12 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  
17.00 on W. face of 9' plat. 18 x 12 ins. ft.  
N. and S. of stone, 3 ft.

dist. and raise a mound  
of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.  
high, W. of cor.

49.85 Soil, bears E. and W.

50.00 Leave dense sage undergrowth.

Subdivision of  
Chains

bears E. and W.

61.07 Trail, bears N. Easterly and  
S. Westerly

78.57 Intersect the "Third  
Standard Parallel South"  
at a point 5.92 chs. —

$N 89^{\circ} 41' W.$  of the standard  
cor. of secs. 34 and 35,  
T. 15 S. R. 23 E., at which  
point I set a lime  
stone  $15 \times 7 \times 5$  ins., 10 ins.  
in the ground for closing  
cor. of secs. 2 and 3, marked  
C.C., on S., with 2 grooves  
on E. and 4 grooves on  
W. faces; dig pits  $24 \times 18 \times 12$   
ins., crosswise on each  
line E. and W., 3 ft., and  
S. of stone, 7 ft. dist., and

## T. 16 S. R. 23 E. - Continued

Chains

raise a mound of earth,  
4 ft. base, 2 ft. high, S. of cor.  
Land level and rolling  
Soil, gravelly loam; 2<sup>nd</sup> rate  
No timber; undergrowth  
sage.

Land covered with dense  
undergrowth 49 chs.

From cor. of secs. 15, 16, 21  
and 22, as heretofore described  
I run

S 0° 2' E, bet. secs. 21 and 22  
Over rolling land, with  
gradual ascent.

. 60 Dry wash, 15 lbs. wide, course N. E.

1. 40 Old road, bears N. E <sup>2</sup>/<sub>3</sub> and S. W.

21. 60 Old road, bears N. E <sup>2</sup>/<sub>3</sub> and S. W.

40. 00 Set a lime stone 14 x 8 x 7

ins., 8 ins. in the ground



Chains Subdivision of

- for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face; and raise  
 a mound of stone 2  $\frac{1}{2}$  ft.  
 base  $1\frac{1}{2}$  ft. high, W. of cor.  
 Pits impracticable
- 43.50 Junction of 2 draws;  
 one flows N.E. and the other  
 N.W.; average width 60 fms.
- 76.75 Dry wash, 10 fms. wide, course N.E.
- 80.00 Set a lime stone 20 x 8 x 6  
 ins., 15 ins. in the ground  
 for cor. of secs. 21, 22, 27 <sup>and</sup> 28,  
 marked  
 T. 16 S., on N.E., and  
 R. 23 E., on S.E.; with  
 2 notches on S. and 3 notches  
 on E. edges; and raise  
 a mound of stone 2 ft  
 base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Pits impracticable.

## T. 16 S. R. 23 E. - Continued

Chains.

Land rolling

Soil, gravelly loam; 2<sup>nd</sup> rate

No timber

S 89° 50' E. on a random  
line, bet. secs. 22 and 27

40.00 Set temp 1/4 sec. cor.

80.08 Intersect N. and S. line  
8 lks. N. of cor. of secs.

22, 23, 26 and 27

Thence I run

N 89° 47' W., on a true line  
bet. secs. 22 and 27Along N. Slope of  
Dragoon Mts.

.90 Gulch, 30 lks. wide, course N.N.W.

2.00 Gulch, 30 lks. wide, course N.

3.00 Descend

8.50 Bottom and dry wash, 10 lks. wide

## Sub-division of

Chains

course N.W.

- 8.60 Ascend
- 9.40 Top, bears N.W. and S.E., descend
- 13.80 Bottom
- 14.00 Dry wash, 10 lks. wide, course N.W.
- 15.50 Dry wash, 20 lks. wide, course N.W.
- 17.90 Dry wash, 20 lks. wide, course N.
- 18.00 Ascend.
- 28.00 Top, bears N.W. and S.E., descend
- 30.16 Bottom, dry wash, 30 lks. wide,  
course N.W.
- 30.90 Ascend
- 32.43 Top, bears N.W. and S.E.
- 40.04 Set a lime stone  $18 \times 11 \times 5$  ins,  
12 ins, in the ground for  
 $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$   
on N. face; and raise a  
mound of stone 2 ft.  
base,  $1\frac{1}{2}$  ft. high, N. of cor.  
Pits impracticable



## T. 16 S. R. 23 E. - Continued

Chains	
48.00	Descend
49.40	Bottom, bears N. N. W. <sup>2nd</sup> of S. S. E.
49.72	Dry wash, 17 lks. wide, course N. N. W.
50.00	Ascend
51.17	Top, bears N. and S.
51.37	Descend
52.31	Bottom and wash, 8 lks. wide, course N.
52.33	Ascend
52.73	Top, bears N. W. and S. E.
61.19	Dry wash, 7 lks. wide, course N. W.
65.04	Dry wash, 6 lks. wide, course N. W.
66.07	Ascend spur of Mountain
70.00	Top, bears N. and S.
71.10	Descend
73.33	Trail, bears N. E. <sup>2nd</sup> of S. W.
73.53	Bottom and dry wash, 17 lks. wide, course N. E.
73.60	Ascend

## Subdivision of

chains

76.80 Top. bears N. and S.

77.60 Descend

80.08 The cor. of secs. 21, 22, 27 <sup>and</sup> 28

Land mountainous

Soil, stony; 4<sup>th</sup> rate  
Timber, scattering cedar  
and pinion.

Mountainous land 80.00 ch.

Jan. 5. 1896

---

Jan. 6. 1896: At 8<sup>h</sup> 40<sup>m</sup>  
a. m., l. m. t., I set  
off 32° 2' on the lat. arc;  
22° 29' S. on the decl. arc;  
and determine a true meri-  
dian with the solar at  
the cor. of secs. 21, 22, 27 <sup>and</sup> 28  
Thence, I run  
S 0° 2' E. bet. secs. 27 and 28  
Ascending

T. 16 S. R. 23 E. - Continued

Chains.	
17.80	Descend
18.10	Bottom of gulch, 12 lks. wide,
	course N. Westerly
19.70	Recross gulch, 10 lks. wide,
	course N. Easterly
20.20	Ascend
20.60	Top, bears N. E. and S. W.
27.30	Gulch, 10 lks. wide, course N. E.
28.00	Ascend steep slope of
	Dragon mts.
40.00	Set a lime stone 18x12x8
	ins., 12 ins. in the ground
	for $\frac{1}{4}$ sec. cor., marked
	$\frac{1}{4}$ on W. face; and raise
	a mound of stone 2 ft.
	base $1\frac{1}{2}$ ft. high, W. of cor.
	<i>Pits impracticable</i>
41.50	Top. and descend
60.00	Bottom, bears E and W.
61.00	Gulch, 25 lks. wide, course N. W.



## Subdivision of

Chains

- 64.00 Gulch, 30 lks. wide, course N.W.  
 65.00 Ascend steep Mountain  
 80.00 Set a line stone, 18x12x6  
 ins., 12 ins. in the ground  
 for cor. of secs. 27, 28, 33<sup>2d</sup> & 34,  
 marked,

T. 16 S. on N.E. and  
 R. 23 E. on S.E., with  
 1 notch on S. and 3 notches  
 on E. edges; and raise  
 a mound of stone, 2 ft.  
 base, 1½ ft. high, W. of cor.  
 Pits impracticable.

Land mountainous  
 Soil, stony, 4<sup>th</sup> rate  
 Timber, scattering cedar

— At this cor. I discontinue  
 on account of high mountains

## T. 16 S. R. 23 E. - Continued

Chains

From cor. of secs. 15, 16, 21 <sup>2</sup>/<sub>2</sub>,  
as heretofore described

I run

No. 2' W., bet. secs. 15 <sup>2</sup>/<sub>2</sub> and 16  
Descending

- 1.20 Old road, bears E. and W.
- 1.50 Bottom and enter valley,  
course Easterly
- 6.15 Road from Dragoon  
Summit to Willcox, bears  
E. and W.
- 7.53 Telegraph line, bears E. <sup>2</sup>/<sub>2</sub> of W.
- 8.00 Ditch, course Easterly
- 8.25 Middle of single track of  
the Southern Pacific  
Railroad bears Easterly  
and Westerly
- 8.93 Telegraph line, bears E. <sup>2</sup>/<sub>2</sub> of W.
- 9.00 Old road, bears E. and W.
- 11.50 Leave valley <sup>2</sup>/<sub>2</sub> and ascend

## Subdivision of

Chains

- 13.60 Dry wash, 5 lks. wide, course S.W.
- 18.55 Dry wash, 4 lks. wide, course S.E.
- 31.30 Dry wash, 10 lks. wide, course S.W.
- 40.00 Set a lime stone  $16 \times 12 \times 8$  ins., 11 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N. face, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. Pits impracticable, ascend
- 70.00 Top, <sup>bears E. and W.</sup> and descend
- 72.00 Gulch, 20 lks. wide, course W. and ascend
- 74.50 Top, bears E. and W. <sup>and descend</sup>
- 76.60 Trail, bears N.W. and S.E.
- 77.40 Bottom and gulch, 20 lks. wide, course N.W.
- 78.20 Gulch, 20 lks. wide, course W.
- 80.00 Set a lime stone,  $16 \times 12 \times 8$



## T. 16 S. R. 23 E. - Continued

Chains

ins., 11 ins. in the ground  
for cor. of sec. 9, 10, 15<sup>2nd</sup> of 16,  
marked

T. 16 S., on N.E. and  
R. 23 E., on S.E., faces;  
with 4 notches on S.,  
and 3 notches on E. edges,  
and raise mound of  
stone 2 ft. base, 1½ ft. high  
W. of cor. Pits impracticable  
Land rolling<sup>2nd</sup> and mountainous  
Soil, loam and stony;  
2<sup>nd</sup> and 4<sup>th</sup> rate

No timber; undergrowth  
scattering ocotillo

Mountainous land, 68.50 chs.

S 89° 50' E., on a random  
line, bet. secs. 10 and 15

# Subdivision of

Chains

40.00 Set temp. 4 sec. cor.,

80.04 Intersect N. and S. line  
10 lks. S. of cor. of secs.  
10, 11, 14 and 15

Thence, I run

$N89^{\circ}54'W$ , on a true line  
bet. secs. 10 and 15

Ascend through sage  
undergrowth along  
south slope of ridge

10.00 Leave dense sage under-  
growth bears N and S.

16.40 Top of ascent

18.10 Descend

18.30 Bottom, and dry wash, 20 lks.  
wide, course S. E.

20.00 Ascend

35.00 Ascend steeper

40.02 Set a lime stone,  $14 \times 14 \times 8$

## T. 16 S. R. 23 E. - Continued

chains

- ins., 8 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; and raise  
a mound of stone 2 ft.  
base  $1\frac{1}{2}$  ft. high, N. of cor.  
Pits impracticable.  
47.75 Top of ridge, bears N. E. <sup>2nd</sup> and S. W.  
and descend
- 62.85 Bottom, bears N. and S.  
and ascend
- 69.50 Top, bears N. and S.; descend
- 80.04 The cor. of secs. 9, 10, 15 <sup>2nd</sup> and 16  
Land mountainous  
Soil, stony; 4<sup>th</sup> rate  
No timber; under growth  
sage and acotillo  
Mountainous or land  
covered with dense under  
growth 80.04 chs.



Subdivision of  
Chains

January 6: At cor. of  
secs. 9, 10, 15 and 16, I set  
off  $22^{\circ} 29' S.$  on the decl.  
arc, and at  $0^{\text{h}} 6^{\text{m}}$  p. m.,  
l. m. t., observe the sun  
on the meridian; the re-  
sulting lat. is  $32^{\circ} 3' N.$

$N 0^{\circ} 2' N.$ , bet. secs. 9 and 10  
Along E. Slope of  
mountains

- 1.50 Gulch, 25 lks. wide, course  
Westerly
- 3.00 Gulch, 30 lks. wide, course Westerly
- 10.00 Gulch, 40 lks. wide, course Westerly
- 14.90 Gulch 25 lks. wide, course Westerly  
and ascend steep ridge
- 28.40 Top of ridge, bears  $N. W. \frac{3}{4} S. E.$
- 35.00 Ravine, 30 lks. wide, course  $N. E.$

## T. 16 S. R. 23 E. - Continued

Chains	
39.00	Descend
40.00	The point for $\frac{1}{4}$ sec. cor falls on rock in place, $20 \times 10 \times 3$ ft above ground, on which I mark a cross (x) at the exact cor. point, for $\frac{1}{4}$ sec. cor. and $\frac{1}{4}$ W. of cross, and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Pits impracticable
59.00	Bottom, bears N.W. <sup>2nd</sup> S.E.
59.90	Dry wash, 6 lks. wide, course S.E.
60.00	Ascend
61.50	Top, bears N.W. <sup>2nd</sup> S.E.
62.00	Descend
62.50	Dry wash, 30 lks. wide, course S.E.
63.00	Ascend
64.50	Top, bears N.W. <sup>2nd</sup> S.E.;

## Subdivision of

Chains

descend

65.00 Bottom

65.45 Dry wash, 8 lks. wide, course S.E.

65.50 Ascend

69.00 Top, bears N.W. and S.E. <sup>2nd of ascending</sup>

69.40 Bottom, and dry wash, 25 lks. wide, course S.E.

69.50 Ascend

70.70 Trail, bears N.N.W. <sup>2nd of S.S.E.</sup>

72.00 Dry wash, 10 lks. wide, course S.W.

74.50 Top, and descend

77.90 Dry wash, 15 lks. wide, course E.

79.50 Trail, bears N.E. <sup>2nd of S.W.</sup>80.00 Set a lime stone 16x12x6 ins., 11 ins. in the ground for cor. of secs. 3, 4, 9 <sup>2nd of</sup> 10, marked

T. 16 S, on N.E., and R. 23 E, on S.E. faces;



## T. 16 S. R. 23 E. - Continued

Chains

with 5 notches on S.  
and 3 notches on E. edges,  
and raise a mound of  
stone 2 ft. base,  $1\frac{1}{2}$  ft  
high, W. of cor. Pits impractical  
Land mountainous  
Soil, stony; 4<sup>th</sup> rate  
No timber.

Mountainous land 80chs.

S  $89^{\circ} 54' E$ , on a random  
line, bet. secs. 3 and 10

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 Intersect N. and S. line  
5 lks. S. of cor. of secs.  
2, 3, 10 and 11

Thence, I run

N  $89^{\circ} 52' W$ , on a true line  
bet. secs. 3 and 10

Ascending, through

## Subdivision of

Chains

- sage under growth
- 15.80 Dry wash, 8 lks. wide,  
course N.E.
- 39.88 Trail, bears N. and S.
- 39.98 Set a lime stone  $12 \times 10 \times 5$   
ins., 8 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; dig pits  
 $18 \times 18 \times 12$  ins. E. and W.  
of stone, 3 ft. dist; and  
raise a mound of earth  
 $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor. Leave under growth, bears N. & S.
- 41.00 Ascend ridge
- 58.00 Top, crest, bears E<sup>2d</sup> & W.
- 58.50 Descend
- 67.50 Bottom
- 67.90 Dry wash, 25 lks. wide, course N.
- 68.00 Ascend

## T. 16 S. R. 23 E. - Continued

Chains

- 71.50 Top, bears N. E. <sup>2nd</sup> of S. W.
- 72.00 Descend
- 76.20 Bottom
- 76.30 Dry wash, 20 lks. wide, course N. E.
- 76.40 Ascend
- 78.25 Dry wash, 6 lks. wide, course N. E.
- 79.62 Trail, bears N. E. <sup>2nd</sup> of S. W.
- 79.96 The cor. of secs. 3, 4, 9 <sup>2nd</sup> of 10  
 Land rolling and mountainous  
 Soil gravelly loam, and  
 stony; 2<sup>nd</sup> and 4<sup>th</sup> rate  
 No timber; undergrowth  
 scattering sage.  
 Mountainous land 38.98 chs.
- 
- No. 2 W. bet. secs. 3 and 4  
 Along east slope of  
 mountains
- 29.00 Gulch, 30 lks. wide, course N. E.



- Subdivision of
- | Chains |   |
|--------|---|
|        | and ascend  |
| 34.20  | Top of ridge, bears N. E $\frac{2}{4}$ of S. W.<br>and descend  |
| 36.80  | Gulch 35 lks. wide, course N. E   |
| 38.80  | Gulch 30 lks. wide, course N. E<br>and ascend   |
| 40.00  | The point for $\frac{1}{4}$ sec.<br>cor. falls on rock in<br>place 20 x 15 x 1 ft. above<br>ground, on which<br>Cut a cross (x) at the<br>exact corner point, for<br>$\frac{1}{4}$ sec. cor., marked<br>$\frac{1}{4}$ , on W. side of cross;<br>and raise a mound of<br>stone 2 ft. base, $1\frac{1}{2}$ ft.<br>high W. of cor. <small>It is impractical<br/>to descend gradually</small> |
| 50.60  | Top, bears E. and W.  |
| 50.80  | Dry wash, 40 lks. wide, course E.   |

## T. 16 S. R. 23 E. - Continued

Chains

- 53.30 Dry wash, 15 lks. wide, course N.E.
- 54.06 Dry wash, 15 lks. wide, course E.
- 60.70 Dry wash, 20 lks. wide, course E.
- 62.40 Dry wash, 15 lks. wide, course N.E.
- 76.40 Dry wash, 20 lks. wide, course E.
- 78.60 Dry wash, 25 lks. wide, course E.
- 79.20 Intersect the "Third Standard Parallel South" at a point 7.30 chs  $N89^{\circ}30'W$ . of the standard cor. of secs. 33 and 34, T. 15 S. R. 23 E., at which point I set a quartz stone  $18 \times 12 \times 10$  ins., 12 ins in the ground for closing cor. of secs. 3 and 4, marked C.C. on S. with 3 grooves on E. and W. faces; and raise a mound of stone

Subdivisions of  
 Chains 2 ft. base,  $1\frac{1}{2}$  ft. high, S.  
 of cor.

Land mountainous  
 Soil, stony; 4<sup>th</sup> rate

No timber

Mountainous land of 79.20 cho.  
 January 6. 1896

January 13. 1896: At 8<sup>h</sup> 45<sup>m</sup>  
 a. m., l. m. t., I set off  
 $32^{\circ} 3'$  on the lat. arc;  $21^{\circ} 27'$   
 on the decl. arc; and de-  
 termine a true meridian  
 with the solar at the  
 cor. of secs. 16, 17, 20 and 21,  
 as heretofore described.

Thence, I run

$S 0^{\circ} 2' E$  bet. secs. 20 and 21

Over rolling land

18.20 Trail, bears N. E. and S. W.

18.50 Road from Tombstone



## T. 16 S. R. 23 E. - Continued

Chains	
	to Wilcox, bears N.E. <sup>2nd</sup> S.W.
26.50	Trail, bears N.W. and S.E.
40.00	Set a lime stone 18 x 9 x 7 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face; and raised a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor. Pits impracticable
41.20	Dry wash, 50 lks. wide, course N.W.E.
51.00	Recross dry wash, 40 lks. wide, course N.W.
80.00	Set a sand stone 15 x 10 x 8 ins., 10 ins. in the ground for cor. of secs. 20, 21, 28 <sup>2d</sup> 29, marked
	T. 16 S. on N.E., and R. 23 E. on S.E., <sup>faces</sup> with 2 notches on S. and 4 notches on E. edges, dig

# Subdivision of Chains

pits 18 x 18 x 12 ins. in each  
sec. 5 1/2 ft. dist.; and raise  
a mound of earth 4 ft.  
base, 2 ft. high W. of cor.  
A cedar 12 ins. diam. bears  
N 16 3/4° E, 6.58 chs. dist.; marked  
T. 16 S. R. 23. E., S. 21. B. T.  
Land rolling  
Soil, gravelly loam; 3<sup>rd</sup> rate  
No timber

---

S 89° 50' E, on a random  
line bet. secs. 21 and 28  
40.00 Set temp. 1/4 sec. cor.  
80.00 Intersect N. and S. line  
at cor. of secs. 21, 22, 27<sup>2nd</sup>/28  
Thence, Run  
N 89° 50' W., on a true line  
bet. secs. 21 and 28

## T. 16 S. R. 23 E. - Continued

Chains	
	Over rolling land
5.65	Gulch, 30 lks. <sup>wide</sup> course N. W.
7.70	Dry wash, 30 lks. <sup>wide</sup> course N.
16.00	Dry wash, 50 lks. <sup>wide</sup> course N.
24.90	Dry wash, 40 lks. wide, course N.
36.00	Dry wash, 25 lks. wide, course N.E.
37.89	Old road, bears N. E. <sup>2nd</sup> S. W.
40.00	Set a lime stone, 18 x 14 x 4 ins., for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; dig pits 18 x 18 x 12 ins. E. and W. of stone, 3 ft. dist.; and raise a mound of earth 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
52.00	Old road, bears N. E. <sup>2nd</sup> S. W.
60.35	Draw, 20 lks. wide, course N.
63.20	Draw, 20 lks. wide, course N. E.
75.30	Dry wash, 20 lks. wide, course N. W.
76.00	Dry wash, 30 lks. wide, course N. W.



## Subdivision of

Chains

80.00

The cor. of secs. 20, 21, 28<sup>2nd/29</sup>

Land rolling

Soil, gravelly loam; 3<sup>rd</sup> rate

No timber

S<sup>o</sup> 2' E. bet secs. 28<sup>2nd/29</sup>

Over rolling land; ascend

gradually

39.00

40.00

Road bears N. E. and S. W.

Set a quartz stone 20x12x8

ins., 15 ins. in the ground

for  $\frac{1}{4}$  sec. cor. marked $\frac{1}{4}$  on W. face; dig pits

18x18x12 ins. N. and S. of

stone, 3 ft. dist.; and raise

a mound of earth 3 $\frac{1}{2}$  ft.base, 1 $\frac{1}{2}$  ft. high, W. of cor.

48.30

Trail, bears N. W. and S. E.

75.50

Descend

77.00

Bottom,

## T. 16 S. R. 23 E. - Continued

Chains.

- 78.50 Dragoon Creek (dry) 40 lks  
wide, course N 80° W.
- 79.00 Trail, bears N. W.  $\frac{2}{3}$  of S. E.;  
ascend
- 79.50 Top, bears N. Westerly  $\frac{2}{3}$  of S. Easterly
- 80.00 Set a quartz stone, 18 x 7 x 6  
ins., 12 ins. in the ground  
for cor. of secs. 28, 29, 32  $\frac{2}{3}$  of 33,  
marked

T. 16 S., on N. E., and  
R. 23 E., on S. E. faces; with  
1 notch on S. and 4 notches  
on E. edges; and raise  
a mound of stone 2 ft.  
base, 1  $\frac{1}{2}$  ft. high, W. of cor.  
(It is impracticable  
and rolling)

Soil, hard and gravelly; 3<sup>rd</sup> rate  
No timber

Subdivision of

Chains	
	S $89^{\circ} 50' E$ , on a random line bet. secs. 28 and 33
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect N. and S. line 5 lks. N. of cor. of sec's 27, 28, 33 and 34
	Thence, I run N $89^{\circ} 48' W$ , on a true line bet. secs. 28 and 33
	Ascending
9.00	Top, bears N. and S. and descend
28.00	Cliff, 60 ft high
28.50	Enter bottom
29.00	Dry wash, 100 lks. wide, course N.
31.90	Ascend
32.60	Top, bears N. and S.
34.20	Bottom, and dry wash, 15 lks. wide, course N., ascend



## T. 16 S. R. 23 E. - Continued

- Chains
- 37.00 Top, bears N. and S.; descend
- 40.04 Set a lime stone  $16 \times 8 \times 3$  ins., 11 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N. face; and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.   
 *Pit impracticable*
- 40.10 Bottom and dry wash, 6 lks. wide, course N.
- 41.90 Ascend
- 46.50 Top of ridge, bears N. and S.
- 46.60 A mon. of stone, 3 ft. high containing a location notice of the Cristal Mine, by J. N. Holiday, dated Feb. 20. 1882, bears North 160 lks.
- 50.90 Descend
- 51.00 Bottom; dry wash, 15 lks. wide

# Subdivision of

Chains

course N.

- 52.10 Dry wash, 12 lks. wide, course N.  
 55.10 Dry wash, 30 lks. wide, course N.  
 76.00 Dry wash, 30 lks. wide, course N.W.  
 77.05 Trail, bears N.W. and S.E.  
 78.50 Bottom, bears N.W. and S.E.  
 79.50 Ascend  
 80.08 The cor. of sees. 28, 29, 32<sup>2</sup>/<sub>4</sub> 33  
 Land broken <sup>2</sup>/<sub>3</sub> of mountainous  
 Soil, stony, 4<sup>th</sup> rate  
 Timber, scattering cedar  
 Mountainous land 80.08 chs.

S 0° 2' E, on a random  
 line bet. sees. 32 and 33

- 40.00 Set temp. <sup>1</sup>/<sub>4</sub> sec. cor.  
 80.57 Intersect S. bdy. of Tp.  
 5 lks. E. of cor. of sees.  
 4, 5, 32 and 33  
 Thence, I run

## T. 16 S. R. 23 E. - Continued

Chains

North, bet. sees. 32 and 33

Over mountainous land,  
Ascend1.00 Top bears N. and S. and  
descend9.80 Bottom of gulch, 20 lks. wide  
course W.; ascend

11.00 Top, bears E. and W.; descend

17.50 Trail, bears E. and W.

18.00 Bottom of gulch, 50 lks. wide,  
course W.; ascend

26.60 Top of ridge, bears E. and W.

30.50 Descend

39.00 Ravine, 15 lks. wide, course N.W.

40.57 Set a sand stone 16x12x6  
ins., 11 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face; from which  
An oak 14 ins. diam, bears



## Subdivision of

Chains

- $S 39 \frac{1}{2}^{\circ} E$ , 205 lks. dist.;  
 marked  $\frac{1}{4}$  S. B. T.  
 An oak 12 ins. diam. bears  
 $S 18 \frac{1}{2}^{\circ} W$ , 120 lks. dist.;  
 marked  $\frac{1}{4}$  S. B. T.  
 42.50 Dry wash, 12 lks. wide, course  
 Westerly  
 44.30 Dry wash, 20 lks. wide, course  
 N. Westerly  
 46.30 Dry wash, 8 lks. wide, course  
 West.  
 47.90 Dry wash, 20 lks. wide, course  
 N. W.  
 48.10 Bottom, and ascend  
 50.00 Top, bears E. and W.  
 51.00 Descend  
 54.30 Bottom, bears N. W. and S. E.  
 57.00 Ascend  
 59.50 Top, bears N. W. and S. E.

## T. 16 S. R. 23 E. — Continued

Chains	
60.00	Descend
62.00	Bottom, bears E. and W.
67.50	Ascend
76.70	Shaft 4' x 6' x 10'
76.80	Top, bears E. and W.
77.50	Descend
80.57	The cor. of secs. 28, 29, 32 <sup>2</sup> / <sub>3</sub> 33
	Land mountainous
	Soil, stony, 4 <sup>th</sup> rate
	Timber, scattering
	cedar and oak.
	Mountainous land 80.57 chs.
	January 13, 1896

From cor. of secs. 16, 17,  
20 and 21, as heretofore  
described, I run  
No. 2' W., bet. secs. 16 and 17  
Over rolling land, descend  
9.00 Enter Valley, course Easterly  
9.78 Road, from Dragoon Summit

- Subdivision of  
Chains
- to Willcox, bears E. and W.
- 10.09 Wire fence, bears E. and W.
- 10.90 Telegraph line, bears Easterly  
and westerly
- 11.40 Ditch, course Easterly
- 11.58 Middle of single track  
of the Southern Pacific  
Railroad, bears Easterly  
and Westerly
- 11.80 Ditch, course Easterly;  
Bridge No 1054 A. bears  
40 lks. E.
- 12.26 Telegraph line, bears Easterly  
and Westerly
- 12.30 Wire fence, bears Easterly  
and Westerly
- 16.00 Leave Valley and  
enter rolling land
- 40.00 Set a quartz stone 16x8x6



## T. 16 S. R. 23 E. - Continued

Chains

ins., 11 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; dig pits  
pits 18 x 18 x 12 ins. N. and S.  
of stone, 3 ft. dist., and  
raise a mound of earth  
 $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.

61.96 Trail, bears N.W. and S.E.

62.02 Trail, bears N.W. and S.E.

76.04 Trail, bears N.W. and S.E.

76.48 Old road, bears N.W. and S.E.

80.00 Set a quartz stone 16 x 8 x 6  
ins., 11 ins. in the ground  
for cor. of secs. 8, 9, 16 and 17,  
marked

T. 16 S. on N.E., and  
R. 23 E. on S.E. faces;  
with 4 notches on S.

Subdivision of  
 Chains and E. edges; dig pits  
 18x18x12 ins. in each see  
 5½ ft. dist; and raise  
 a mound of earth 4 ft  
 base, 2½ ft. high, N. of cor.  
 Land rolling  
 Soil, gravelly loam; 2<sup>nd</sup> rate  
 No timber

---

S 89° 50' E., on a random  
 line bet sees. 9 and 16  
 40.00 Det temp ¼ sec. cor.  
 79.90 Intersect N. and S. line  
 3 lks. S. of cor. of sees.  
 9, 10, 15 and 16  
 Thence, Run  
 N 89° 51' W., on a true line  
 bet. sees. 9 and 16  
 Descending

## T. 16 S. R. 23 E. - Continued

- | Chains |   |
|--------|---|
| 2.50   | Bottom; dry wash, 20 lks. wide, course N.W.; ascend   |
| 12.50  | Top of N. Slope of ridge, crest bears E. and W.; descend  |
| 24.00  | Bottom  |
| 24.40  | Dry wash, 10 lks. wide, course S.S.W.   |
| 39.95  | Set a lime stone 14 x 8 x 6 ins., 9 ins. in the ground for $\frac{1}{4}$ sec. cor.; marked $\frac{1}{4}$ on N. face; dig pits 18 x 18 x 12 ins. E. and W. of stone, 3 ft. dist.; and raise a mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high, N. of cor. |
| 70.70  | Trail, bears N. and S.  |
| 79.90  | The cor. of secs. 8, 9, 16 <sup>and</sup> 17<br>Land rolling 2 <sup>nd</sup> mountains.<br>Soil, gravelly loam, and stony,<br>2 <sup>nd</sup> and 3 <sup>rd</sup> rate  |



## Subdivision of

Chains

No timber; undergrowth,  
scattering mesquite.

Mountainous land 24 chs.

No 2' W. bet. sec's. 8 and 9

Over rolling land

40.00 Set a lime stone 18x8x6  
ins., 12 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face; dig pits  
18x18x12 ins. N. and S.  
of stone, 3 ft. dist,  
and raise a mound  
of earth 3 $\frac{1}{2}$  ft. base,  
1 $\frac{1}{2}$  ft. high, W. of cor.

55.50 Descend

57.30 Bottom, and dig wash 5 lks.  
wide, course S. W

58.30 Ascend

## T. 16 S. R. 23 E. - Continued

chains

- 61.00 Top, bears N.E. and S.W.  
 80.00 Set a quartz stone, 18x10x7  
 ins., 12 ins. in the ground  
 for cor. of secs. 4, 5, 8 and 9,  
 marked

T. 16 S., on N.E., and  
 R. 23 E., on S.E., faces;  
 with 5 notches on S.  
 and 4 notches on E. edges;  
 dig pits 18x18x12 ins. in  
 each sec. 5½ ft. dist.,  
 and raise a mound of  
 earth 4 ft. base, 2 ft  
 high, W. of cor.

Land rolling

Soil, gravelly loam; 2<sup>nd</sup> rate  
 No timber, undergrowth  
 mesquite.

- Subdivision of
- Chains
- $S 89^{\circ} 51' E$ , on a random line, bet. secs. 4 and 9
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.93 Intersect N. and S. line 5 lks. S. of cor. of secs. 3, 4, 9 and 10
- Thence I run
- $N 89^{\circ} 53' W$ , on a true line bet. secs. 4 and 9
- Ascend ridge
- 21.00 Top, bears N. and S.; descend
- 37.16 Foot of ridge
- 37.22 Dry wash, 20 lks. wide, crossed
- 37.32 Ascend
- 39.96 $\frac{1}{2}$  Set a limestone, 18 x 10 x 8 ins., 12 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N. face, and raise a mound of stone 2 ft. base



## T. 16 S. - R. 23 E. - Continued

Chains

- $1\frac{1}{2}$  ft. high N. of cor.  
~~Practically~~ impracticable  
 44.00 Top of ridge, bears N. and S.  
 44.50 Descend  
 47.57 Dry wash, 15 lks. wide, course S.W.  
 50.92 Dry wash, 15 lks. wide, course S.W.  
 61.32 Foot of ridge, bears N. <sup>2</sup>/<sub>3</sub> of S.  
 61.70 Trail, bears N. <sup>2</sup>/<sub>3</sub> of S.  
 62.80 Descend  
 63.80 Enter bottom  
 64.12 Dry wash, 10 lks. <sup>wide</sup>, course S.  
 64.20 Ascend  
 64.65 Top, bears N. and S.  
 79.93 The cor. of secs. 4, 5, 8 and 9  
 Land rolling <sup>2</sup>/<sub>3</sub> of mountainous  
 Soil, loam; gravel and stones  
 2<sup>nd</sup>, 3<sup>rd</sup> and 4<sup>th</sup> rate  
 No timber.  
 Mountainous land of 6132 chs.

- Subdivision of  
Chains
- No. 2' N., bet. secs. 4<sup>nd</sup> & 5  
along W. slope of mountains
- 40.00 Set a lime stone 15 x 14 x 5  
ins., 10 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face; dig pits  
18 x 18 x 12 ins., N. and S.  
of stone, 3 ft. dist., and  
raise a mound of earth  
4 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.
- 42.70 Dry wash, 6 lks. wide, course W.
- 52.95 Dry wash, 12 lks. wide, course W.
- 58.06 Dry wash, 20 lks. wide, course S. W.
- 64.50 A shaft, bears S 44 $\frac{1}{2}$  E.  
about 10 chs.
- 72.70 Dry wash, 6 lks. wide, course S. S. W.
- 79.75 Intersect the "Third  
Standard Parallel South  
at a point 9.08 chs.  $109^{\circ}50'$  W.

## T. 16 S. R. 23 E. - Continued

Chains

of cor. of secs. 32 and 33,  
T. 15 S. R. 23 E., at which  
point I set a lime stone  
14 x 10 x 6 ins., 9 ins. in the  
ground for closing cor.  
of secs. 4 and 5, marked  
C.C., on S., with 4 grooves  
on E. and 2 grooves on  
W. faces; and raise a  
mound of stone, 2 ft.  
base  $1\frac{1}{2}$  ft. high, S. of cor.  
~~City impracticable~~  
Land mountainous.

Soil, hard and gravelly; <sup>4<sup>th</sup> note</sup>

No timber.

Mountainous land 79.75 chs

Jan. 14, 1896

Jan. 15, 1896: At 8. <sup>h</sup> 00 <sup>m</sup>,  
<sup>u. m</sup>  
l. m. t., I set off 32° 3' on  
the lat. arc, 21° 1' S. on the



Subdivision of  
 Chains decl. arc, and determine  
 a true meridian, at the  
 cor. of secs. 17, 18, 19 and 20,  
 as heretofore described  
 Thence, I run  
 $S 0^{\circ} 3' E$ , bet. secs. 19 and 20  
 Over rolling land  
 6.70 Road, bears  $N. E.$  and  $S. W.$   
 7.12 Wire fence, bears  $N 56^{\circ} E$  <sup>2d</sup>  $S 56^{\circ} W$   
 7.94 Telegraph line, bears  $N 56^{\circ} E$  <sup>2d</sup>  $S 56^{\circ} W$   
 8.50 Dry wash, 20 lks. wide, course  $N. E.$   
 8.90 Middle of single track of  
 the Southern Pacific Rail-  
 road bears  $N 56^{\circ} E$  <sup>2d</sup>  $S 56^{\circ} W$   
 9.20 Ditch 20 lks. wide, course  $N. E.$   
 9.86 Telegraph line, bears  $N 56^{\circ} E.$   
 and  $S 56^{\circ} W.$   
 10.69 Wire fence, bears  $N 56^{\circ} E$  <sup>2d</sup>  $S 56^{\circ} W.$   
 10.90 Road from Dragon Summit

## T. 16 S. R. 23 E. - Continued

Chains

to Willcox, bears N.E. and S.W.

34.85 Road from Tombstone to  
Willcox, bears N.E. and S.W.40.00 Set a lime stone  $15 \times 12 \times 4$   
ins., 10 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  
 $\frac{1}{4}$  on W. face; dig pits  
 $18 \times 18 \times 12$  ins. N. and S. of  
stone 3 ft. dist.; and raise  
a mound of earth  $3\frac{1}{2}$  ft.  
base,  $1\frac{1}{2}$  ft. high, W. of cor.

46.50 Trail, bears E. and W.

80.00 Set a lime stone  $15 \times 10 \times 10$   
ins., 10 ins. in the ground  
for cor. of secs. 19, 20, 29  $\frac{2}{3}$ /<sub>30</sub>,  
markedT. 16 S. on N.E., and  
R. 23 E. on S.E. faces; with  
2 notches on S. and 5 notches

Subdivision of  
 Chains on E. edges; dig pits  
 18x18x12 ins. in each sec  
 5½ ft. dist. and raise  
 a mound of earth 4 ft  
 base, 2 ft. high, W. of cor.  
 From this cor. Section  
 house of Dragoon Summit  
 bears N 42° W. —  
 Section house and telegraph  
 office, bears N 37½° W.  
 A house bears N 35° W  
 A house bears N 32° W  
 Turntable bears N 26¾° W.  
 Sand rolling  
 Soil, loam; 2<sup>nd</sup> rate  
 No timber

---

S 89° 50' E, on a random  
 line bet. secs. 20 and 29



## T. 16 S. R. 23 E. - Continued

Chains

40.00

Set temp.  $\frac{1}{4}$  sec. cor.

79.90

Intersect N. and S. line

3 lks. N. of cor. of secs.

20, 21, 28 and 29

Thence, I run

N 89° 49' W, on a true line  
bet. secs. 20 and 29

Over rolling land

39.95

Set a sand stone 16x8x8  
ins., 11 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked $\frac{1}{4}$  on N. face; dig pits  
18x18x12 ins. E. and W. of  
stone, 3 ft. dist; and raise  
a mound of earth 3 $\frac{1}{2}$  ft.  
base, 1 $\frac{1}{2}$  ft. high, N. of cor.

79.90

The cor. of secs. 19, 20, 29 $\frac{2}{3}$ /30

Land rolling

Soil, loam; 2<sup>nd</sup> rate

Subdivision of  
Chains No timber

- N 89° 50' W. on a random  
line, bet. secs. 19 and 30
- 40.00 Set temp. 1/4 sec. cor.
- 60.00 Intersect W. bdy. of Tps.  
18 lks. N. of cor. of secs.  
19, 24, 25 and 30, which  
is granite stone; marked  
and witnessed as described  
by the Surveyor General  
Thence, I run  
East, on a true line bet.  
secs. 19 and 30  
Over rolling land
- 13.03 Road from Tombstone  
to Wilcox, bears N. E. <sup>94</sup> and  
S. S. W.
- 20.00 Set a granite stone

## T. 16 S. R. 23 E. - Continued

Chains

18x10x6 ins; 12 ins. in the  
ground for  $\frac{1}{4}$  sec. cor;  
marked  $\frac{1}{4}$  on N. face;  
and raise a mound of  
stone, 2 ft. base,  $1\frac{1}{2}$  ft.  
high, N. of cor. *Pits impracticable*

60.00

The cor. of secs. 19, 20, 29<sup>nd</sup> & 30

Land rolling

Soil, gravelly loam; 2<sup>nd</sup> rate

No timber

Note - From  $\frac{1}{4}$  sec. cor. bet.  
secs. 19 and 30: Section

House at Dragoon Summit,  
bears N  $8\frac{1}{2}^{\circ}$  E.

Section House <sup>2<sup>nd</sup></sup> telegraph  
office, bears N  $12^{\circ}$  E.

House, bears N  $13\frac{1}{2}^{\circ}$  E.

House, bears N  $15^{\circ}$  E.

Turntable, bears N  $16\frac{3}{4}^{\circ}$  E.



- Subdivision of  
Chains
- S<sup>0</sup>3'E bet. secs. 29<sup>2nd</sup> & 30  
Over rolling land
- 14.24 Trail, bears N.W. <sup>2nd</sup> S.E.
- 30.75 Trail, bears N.W. <sup>2nd</sup> S.E.
- 40.00 Set a lime stone, 15x10x4  
ins., 10 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face; and raise  
a mound of stone, 3 $\frac{1}{2}$  ft.  
base, 1 $\frac{1}{2}$  ft. high W. of cor.  
*its impracticable*
- 68.40 Descend
- 69.00 Enter bottom; trail, bears N.W. <sup>2nd</sup> S.E.
- 69.30 Dragoon Creek, (dry) 25 Mts. wide,  
course N.W.
- 74.00 Leave bottom and ascend
- 77.00 Top, bears N.W. and S.E.
- 80.00 Set a granite stone, 16x12x8  
ins., 11 ins. in the ground  
for cor. of secs. 29, 30, 31<sup>2nd</sup> & 32,

## T. 16 S. R. 23 E. - Continued

Chains

marked

T. 16 S. on N.E., and  
 R. 23 E. on S.E. faces; with  
 1 notch on S. and 5 notches  
 on E. edges; and raise  
 a mound of stone, 2 ft.  
 base  $1\frac{1}{2}$  ft. high N. of cor.

City 'impracticable'  
 Sand rolling

Soil, gravelly loam; 2<sup>nd</sup> rate  
 No timber; some under-  
 growth along Dragoon Creek

S  $89^{\circ}49'E$ , on a random  
 line, bet. secs. 29 and 32

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.92 Intersect N. and S. line  
 8 lks. N. of cor. of secs. 28, 29  
 32 and 33.

Thence, I run

Subdivision of T. 16 S. R. 23 E. - Continued  
Chains

- N 89° 46' W, on a true line  
bet. secs. 29 and 32
- Over rolling land; descend
- 20.57 Dry wash, 15 lks. wide, course S.W.
- 26.95 Old road, bears N. and S.
- 39.65 Trail, bears N.W. and S.E.
- 39.96 Set a lime stone 14 x 9 x 5  
ins., 8 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; dig pits  
18 x 18 x 12 ins., E. and W. of  
stone, 3 ft. dist. and raise  
a mound of earth, 3  $\frac{1}{2}$  ft  
base, 1  $\frac{1}{2}$  ft. high, N. of cor.
- 40.80 Trail, bears N.W. and S.E.
- 41.00 Trail, bears N.W. and S.E.
- 42.30 Bottom
- 42.60 Dry wash, 10 lks. wide, course S.W.
- 43.00 Enter scattering undergrowth



Concluded, Book 863.