

3.

863

BOOK 863

No. 863

*Fractional*

4-671

FIELD NOTES  
GENERAL LAND OFFICE.

*Subdivision*

*of*

*T. 16 S. R. 23 E.*

Indexed, Book #61.  
120

Township 16S R. 23E

			137			
6	135	5	4	3	2	1
134		132				
7	130	8	9	10	11	12
128		127				
18	125	17	16	15	14	13
19		20	21	22	23	24
30		29	28	27	26	25
31	123	32	33	34	35	36

No. 863

BOOK 863 121

## Subdivision of T. 16 S. R. 23 E. - (Continued)

Chains

- bears N. and S.
- 63.00 Leave scattering undergrowth  
bears N. and S.
- 67.00 Descend
- 70.20 Bottom, bears N.W. and S.E.
- 73.90 Dagoon Creek (dry), <sup>30 lks wide</sup> course N.W.
- 74.00 Ascend
- 75.00 Top, bears N.W. and S.E.
- 79.92 The cor. of secs. 29, 30, 31 <sup>2nd</sup> of 32
- Land rolling
- Soil, hard <sup>2nd</sup> gravelly, 2<sup>nd</sup> rate
- No timber, scattering mesquite  
under growth
- 
- West, on a random line  
bet. secs. 30 and 31
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 60.17 Intersect the W. bdy of T. 16  
16 lks. N. of cor. of secs.



- Subdivision of
- Chains 25, 30, 31 and 36, which is a granite stone, marked and witnessed as described by the surveyor general. Thence, I run N 89° 51' E, on a true line bet. sees. 30 and 31
- Over rolling land
- 9.77 Road from Tombstone to Willcox, bears N. <sup>3</sup>/<sub>4</sub> S.
- 20.17 Set a sand stone 16 x 12 x 6 ins., 11 ins. in the ground for <sup>1</sup>/<sub>4</sub> sec. cor., marked <sup>1</sup>/<sub>4</sub> on N. face; and raise a mound of stone, 2 ft. base 1 <sup>1</sup>/<sub>2</sub> ft. high, N. of cor. <sup>It's impracticable</sup>
- 27.67 Draw, 150 lbs. wide, course N. W.
- 45.67 Draw, 150 lbs. wide, course N.
- 52.20 Draw, 100 lbs. wide, course N. W.

## T. 16 S. R. 23 E. - Continued

Chains

52.50

Old road, bears N.W. <sup>and</sup> S.E.

60.17

The cor. of secs. 29, 30, 31 <sup>and</sup> 32

Land rolling

Soil, gravelly loam; 2<sup>nd</sup> rate

No timber

The cor. of secs. 5, 6, 31 and 32  
on S. bdy, being plainly  
visible, therefore

Run S 0° 3' E. on a true  
line, bet. secs 31. <sup>and</sup> 32

Over rolling land

35.60

Trail bears E. and W.

40.00

Set a quartz stone, 16x12x8 ins,  
11 ins. in the ground for  $\frac{1}{4}$ sec. cor., marked  $\frac{1}{4}$  onN. face; and raise a mound  
of stone 2½ ft. base, 1½ ft.

high, W. of cor. (It's impracticable)

## Subdivision of

Chains

- 56.03 Trail, bears E. and W.  
 56.47 Trail, bears E. and W.  
 56.66 Trail, bears E. and W.  
 57.10 Old road, bears E. and W.  
 57.25 Dry wash, 5 lks. wide, course W.  
 60.00 Descend  
 63.90 Bottom, bears E. and W.  
 64.40 Dry wash, 40 lks. wide, course W.  
 64.80 Ascend  
 80.64 The cor. of secs. 5, 6, 31<sup>and</sup> 32  
 as heretofore described.

Land rolling

Soil, gravelly loam; 2<sup>nd</sup>/<sub>3</sub>/<sub>3</sub> notes

Timber, scattering oak.

Jan. 15. 1896

January 16, 1896: At  
 8 h 15<sup>a.m.</sup> <sup>p.l.</sup> m. t., I set  
 off 32° 3' on the lat. arc.



## T. 16 S. R. 23 E. - Continued

chains

20°55' S. on the decl. arc;  
and determine a true  
meridian, at the cor. of  
secs. 17, 18, 19 and 20, as here-  
tofore described

Thence, I run

N 0°3' W, bet. secs. 17 <sup>and</sup> 18

Over rolling land

2.05 Trail, bears E. and W.

21.20 Dry wash, <sup>12 lks. wide</sup> course E.

35.60 Road from Dragoon  
Summit bears N. N. E.  
and S. S. W.

40.00 Set a quartz stone  
15 x 10 x 6 ins., 10 ins. in the  
ground for  $\frac{1}{4}$  sec. cor  
marked  $\frac{1}{4}$  on W. face;  
dig pits 18 x 18 x 12 ins.  
N. and S. of stone, 3 ft. dist.

## Subdivision of

Chains

- and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- 65.00 Center of dry wash, 200 lks. wide, course S.E.
- 66.53 Trail, bears N.W. <sup>2nd</sup> of S.E.
- 79.43 Dry wash, 30 lks. wide, course S.
- 80.00 Set a quartz stone  $12 \times 9 \times 9$  ins., 8 ins. in the ground for cor. of secs. 7, 8, 17 <sup>2nd</sup> of 18, with 4 notches on S. and 5 notches on E. edges; dig pits  $18 \times 18 \times 12$  ins. in each sec.  $5\frac{1}{2}$  ft. dist; and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.
- Land rolling  
Soil, gravelly loam; 2<sup>nd</sup> rate  
No timber



## T. 16 S. R. 23 E. - Continued

Chains

- S  $89^{\circ}50'E$ , on a random line, bet. secs. 8 and 17
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.36 Intersect N. and S. line 8 lks. S. of cor. of secs. 8, 9, 16 and 17
- Thence, I run
- N  $89^{\circ}53'W$ , on a true line, bet. secs. 8 and 17
- Over rolling land
- 1.97 Old road, bears N.W.  $\frac{2}{4}$  of S.E.
- 2.50 Trail, bears N.W.  $\frac{2}{4}$  of S.E.
- 12.98 Trail, bears N.W.  $\frac{2}{4}$  of S.E.
- 20.20 Trail, bears N.W.  $\frac{2}{4}$  of S.E.
- 40.18 Set a quartz stone,  $12 \times 8 \times 7$  ins., 8 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N. face; dig pits  $18 \times 18 \times 12$  ins. E. and W. of stone

## Subdivision of

Chains

- 3 ft. dist, and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.
- 55.58 Trail, bears N.W. and S.E.
- 64.00 Old road, bears N.W.  $\frac{3}{4}$  S.E.
- 69.50 Trail, bears N.W.  $\frac{1}{2}$  S.E.
- 80.36 The cor. of secs. 7, 8, 17 and 18
- Land rolling
- Soil, gravelly loam; 2<sup>nd</sup> rate
- No timber

N  $89^{\circ}50'$  W. on a random line, bet. secs. 7 and 18

- 40.00 Set temp  $\frac{1}{4}$  sec. cor
- 59.58 Intersect W. bdy. of Twp. 18 lks. S. of cor. of secs. 7, 12, 13 and 18, which is a charred stake with mound of earth, witnessed

## T. 16 S. R. 23 E. - Continued

Chains

as described by the  
Surveyor General  
Thence, I run  
S  $89^{\circ} 40' E$ , on a true line  
bet. secs. 7 and 18

Over rolling land

.03 Trail, bears N. and S.

7.04 Old road, bears N.  $\frac{2}{3}$  of S.

7.24 Dry wash, 6 lks. wide, course N.

19.58 Set a quartz stone  $12 \times 8 \times 8$   
ins., 8 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; dig pits  
 $18 \times 18 \times 12$  ins., E. and W. of  
stone, 3 ft. dist.; and raise  
a mound of earth,  $3\frac{1}{2}$  ft.  
base,  $1\frac{1}{2}$  ft. high, N. of cor.

42.02 Trail, bears N. N. E.  $\frac{2}{3}$  and S. S. W.

43.30 Trail, bears N. E.  $\frac{2}{3}$  and S. W.



## Subdivision of

Chains

- 44.60 Dry wash, 30 lks. wide, course N.W.
- 45.44 Trail, bears N.E. and S.W.
- 58.05 Dry wash, 30 lks. wide, course  
S80°E.
- 59.58 The cor. of secs. 7, 8, 17<sup>2nd</sup> & 18  
Land rolling  
Soil, gravelly loam; 2<sup>nd</sup> rate  
No timber

N<sup>o</sup> 3' N. bet. secs. 7 and 8  
Over rolling land

- 14.62 Trail, bears N.N.E <sup>2nd</sup> & S.S.W.
- 25.80 Trail, bears N.W. and S.E.
- 26.00 Trail, bears N.W. and S.E.
- 34.90 Old road, bears E. and W.
- 36.00 Trail, bears N.W. and S.E.
- 36.15 Trail, bears N.W. and S.E.
- 36.60 Trail, bears N.W. and S.E.
- 40.00 Set a quartz stone, 14x10x8

## T. 16 S. R. 23 E. - Continued

Chains

ins., 9 ins. in the ground  
for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on W. face; dig pits  
18x18x12 ins. N. and S. of  
stone, 3 ft. dist., and raise  
a mound of earth  $3\frac{1}{2}$  ft  
base,  $1\frac{1}{2}$  ft. high W. of cor.

- 40.66 Trail, bears E. and W.  
46.55 Trail, bears E. and W.  
47.64 Dry wash, 10 lks. wide, course E.  
47.90 Trail, bears E. and W.  
48.10 Trail, bears E. and W.  
48.40 Trail, bears E. and W.  
52.50 Trail, bears N.E. and S.W.  
52.67 Dry wash, 5 lks. wide, course S.W.  
79.50 Dry wash, 3 lks. wide, course E.  
80.00 Set a quartz stone 16x12x8  
ins., 12 ins. in the ground  
for cor. of secs. 5, 6, 7  $\frac{2}{4}$  / 8  
marked

Subdivision of  
Chains

with 5 notches on S. <sup>2nd</sup> of  
E. edges; dig pits 18x18x12  
ins. in each sec. 5 1/2 ft. dist  
and raise a mound of  
earth 4 ft. base, 2 ft. high  
N. of cor.

Sand rolling

Soil, gravelly loam; 2<sup>nd</sup> rate  
No timber

S 89° 53' E, on a random  
line, bet. secs. 5 and 8

40.00 Set temp. 1/4 sec. cor.

80.36 Intersect N. and S. line  
5 lks. S. of cor. of secs.  
4, 5, 8 and 9

Thence, I run

N 89° 55' W, on a true line  
bet. secs. 5 and 8



## T. 16 S. R. 23 E. - Continued

Chains

40.18

Set a lime stone  $12 \times 8 \times 7$  ins.,  
 8 ins. in the ground for  
 $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$   
 on N. face; dig pits  
 $18 \times 18 \times 12$  ins., E. and W.  
 of stone, 3 ft. dist.; and  
 raise a mound of earth  
 $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.

49.24 Old road bears N. E.  $2^{\text{nd}}$  of S.W.58.95 Old road bears N. E.  $2^{\text{nd}}$  of S.W.60.27 Old road bears N. W.  $2^{\text{nd}}$  of S. E.73.25 Trail, bears  $N 75^{\circ} W$   $2^{\text{nd}}$  of  $S 75^{\circ} E$ .

78.50 Trail bears N. W. and S. E.

79.50 Dry Wash 3 links wide Course N. E.

80.36 The cor. of secs. 5, 6, 7 and 8

Land rolling

Soil, gravelly loam;  $2^{\text{nd}}$  rate

No timber

# Subdivision of Chains

- $N 89^{\circ} 40' W.$ , on a random  
 line, bet. secs. 6 and 7  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 59.21 Intersect the W. bdy.  
 of Twp.  $16\frac{1}{2}$  lks. S. of  
 cor. of secs. 1, 6, 7 and 12  
 Thence, I run  
 $S 89^{\circ} 31' E.$ , on a true line  
 bet. secs. 6 and 7  
 Over rolling land  
 4.13 Road, from Dragoon  
 Summit, bears N. W.  $2^{\text{nd}}$  of S. E  
 8.69 Trail, bears N. W.  $2^{\text{nd}}$  of S. E  
 19.21 Set a quartz stone  $12 \times 8 \times 6$   
 ins., 8 ins., in the ground  
 for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  on N. face; dig pits  
 $18 \times 18 \times 12$  ins. E. and W.  
 of stone, 3 ft. dist; and

## T. 16 S. R. 23 E. - Continued

Chains

- raise a mound of earth  
3½ ft. base, 1½ ft. high,  
N. of cor.
- 20.12 Trail, bears N.W. and S.E.
- 21.28 Trail, bears N.W. and S.E.
- 22.23 Dry wash, 10 lks. wide, course S.E.
- 23.65 Dry wash, 15 lks. wide, course S.E.
- 23.98 Trail, bears N.W. and S.E.
- 59.21 The cor. of secs. 5, 6, 7<sup>nd</sup> & 8<sup>th</sup>  
Land rolling  
Soil, loam; 2<sup>nd</sup> rate  
No timber
- 
- No<sup>o</sup> 3' W., bet. secs. 5 and 6  
Over rolling land
- 1.00 Trail, bears N.W. <sup>nd</sup> S.E.
- 2.90 Trail, bears E. and W.
- 10.20 Road, bears E. and W.
- 31.30 Dry wash, 20 lks. wide, course E.



## Subdivisions of

Chains

40.00

Set a granite stone  
 15 x 8 x 8 ins., 10 ins. in the  
 ground for  $\frac{1}{4}$  sec. cor.,  
 marked  $\frac{1}{4}$  on W. face;  
 dig pits 18 x 18 x 12 ins.,  
 N. and S. of stone, 3 ft.  
 dist.; and raise a mound  
 of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.  
 high, W. of cor.

43.15

Trail, bears E. and W.

46.90

Trail, bears E. and W.

47.30

Trail, bears E. and W.

68.90

Dry wash, 20 lks. wide, course E.

79.88

Intersect the "Third  
 Standard Parallel South"  
 at a point 9.78 chs.  $N 89^{\circ} 50' W$   
 of the standard cor.  
 of secs. 31 and 32, T. 15 S.  
 R. 23 E, at which point,

## T. 16 S. R. 23 E. - Continued

Chains

I set a lime stone, 18x14x14 ins., 12 ins. in the ground for closing cor. of secs. 5 and 6, marked C.C. on S. with 5 grooves on E. and 1 groove on W. faces; and raise a mound of stone, 2 ft. base, 1½ ft high, S. of cor. - Pits impracticable

Land rolling

Soil, gravelly loam; 2<sup>nd</sup> rate  
No timber.

January 16. 1896.

Note: - Owing to the closings of lines bet. secs. 3 and 4 and 4 and 5, I retrace the S. bdy of sec. 33, T.

Retracement of S. bdy of  
Chains.

- 15 S. R. 23 E; I begin  
at standard cor. of secs  
32 and 33, which is a  
lime stone, marked and  
witnessed, as described  
by the Surveyor general  
Thence, I run  
E. on S. bdy of sec. 33  
Ascending
- 21.00 Top and descend along  
S. Slope of Mt.
- 31.10 Dry wash, 10 lks. wide, course N.E.
- 38.75 Standard  $\frac{1}{4}$  sec. cor. which  
is a lime stone, marked  
and witnessed as described  
by the surveyor general,  
bears  $34\frac{1}{2}$  lks. S.
- 49.56 Dry wash, 10 lks. wide course N.E.
- 52.66 Dry wash, 9 lks. wide, course N.E.



## Sec. 33 - T 15 S. R. 23 E.

Chains

- 54.20 Foot of descent  
 60.00 Ascend ridge  
 61.90 Top, bears N. and S.  
 62.00 Descend  
 78.27 Standard cor. of secs. 33  
 and 34, which is a lime-  
 stone, marked and  
 witnessed, as described  
 by the Surveyor General  
 bears 70 lks S.

— The true course of this  
 line is  $N 89^{\circ} 30' W.$  and  $S 89^{\circ} 30' E.$

Land mountainous  
 Soil, stony; 4<sup>th</sup> rate  
 No timber

Mountainous land 78.27 chs.

January 16. 1896

Note: The course of the S. boundaries  
 of secs. 31 and 32. T. 15 S. R. 23 E. is

Subdivision of  
N 89° 50' W. and S 89° 50' E.

Note: In the execution of the survey of this township I destroyed all corners previously set by U. S. Deputy Surveyor A. L. Trippel, in compliance with my Special Instructions dated Sept. 23. 1895

General Description  
This township is level, rolling and mountainous. The soil is mostly gravelly loam, almost the <sup>entire</sup> township is covered with an abundant growth of rich and nutritious grasses.

## T. 16 S. R. 23 E. — Concluded

cedar and oak timber is found in small quantities in the mountains. —

There is no permanent water in this township.

The Golden Rule, Apache Chief, Dexter, Blue Top, Bell, Wellington and Golden Sight Mining claims are situated in sec. 23, and the Emma Mining claim, also portions of the Apache Chief and Dexter mining claims are situated in Sec. 24. There <sup>are</sup> mineral indications in the N.E.  $\frac{1}{4}$  of sec. 6; also bet. secs. 32 and 33 and



along the S. bdy of Sec.  
28. — The Southern  
Pacific Railroad runs  
through this township.  
Dragoon Summit,  
a railroad station  
is situated in the center  
of sec. 19. There are  
no settlers in this  
township.

Philip Contzen  
Compassman

U. S. Surveyor-General's Office.

Tucson, A. T. January 22, 1897.

The foregoing field notes of the Resurvey of the South Boundaries of secs. 34, 35, and 36, and the retracement of the South Bdy. of Sec. 33 of Tp. 15 S. R. 23 E.; and the survey of the Subdivision lines of Tp. 16 S., R. 23 E., Gila and Salt River Meridian in Arizona, executed by Philip Contzen, Compassman and U. S. Deputy Surveyor, under his Contract No. 29, with A. L. Trippel, dated June 17, 1895, having been critically examined, the necessary corrections and explanations made, the said field notes and the surveys they describe are hereby approved.

*George J. Roskrug*  
U. S. Sur. Gen. for Ariz.