

BOOK 929

No. 929

626

Subdivisions

Book I

4-671

FIELD NOTES  
GENERAL LAND OFFICE.

*Tr 226R 11E*

Township No. 20 S Range No. 11 E, Q & R M Meridian

from over Blomson  
to Mansfield bench  
and McLesore



Township Plot.  
 Meridian Line,  
 Base Line,  
 Standard Line,  
 Township Lines,

BOOK 929

1A



16

Index for { BOOK 929  
BOOK 930

# INDEX

Township 22 S R. 11 E

6	84	5	63	4	47	3	31	2	15	1
83		82		62		46		30		14
7	81	8	61	9	44	10	28	11	13	12
79		78		59		42		27		11
18	77	17	58	16	41	15	26	14	10	13
75		74		57		40		24		9
19	73	20	55	21	39	22	23	23	7	24
71		70		54		37		22		6
30	69	29	52	28	36	27	20	26	5	25
67		66		50		34		19		3
31	65	32	49	33	33	34	17	35	2	36

For preliminary oaths see books No. 1.

No. 929

BOOK 929 C

Field Notes

of the Survey of the

Subdivision line of

Township 22 South Range 11 East  
of the

Gila and Salt River Meridian  
of Arizona

as surveyed by

Geo. J. Roskrutz

U. S. Dep. Surv<sup>r</sup>

Under his contract No 2

Dated June 16<sup>th</sup> 1886

Survey commenced Jan 10<sup>th</sup> 1887.

Survey completed Jan 15<sup>th</sup> 1887.

T<sup>w</sup> 22 S. R. 11 E.

chains

Before commencing the survey of the subdivisions lines of this Township I take an observation using a Young & Sons Solar Transit and find the magnetic Var. to be  $12^{\circ} 35' E$ . I ran N. on a blank line on the E. boundary of Sec 36 and at 40 chs. from the cor. found the  $\frac{1}{4}$  Sec cor. and at 80 chs. found the Sec. cor. I then ran West on a blank line on the S. boundary of Sec 36 and at 40 chs found the  $\frac{1}{4}$  Sec. cor. and at 80 chs found the Sec. cor. My Compass will therefore run the same line as the exterior boundaries and the chaining agrees.

Survey commenced January 10<sup>th</sup> 1887

I commenced at the cor. to Secs. 1. 2. 35 & 36 on the South boundary of T<sup>w</sup>. previously established and described by me. Thence I ran

Subdivisions T<sub>p.</sub> 22 S. R. 11 E. - Continued

Chains.

North bet Secs 35 &amp; 36

Var.  $12^{\circ} 35' E.$ 

Over rough hilly country

4.00 Gulch 20 lbs wide, Course E.

9.00 Gulch 15 lbs wide, Course E & E, and  
line runs along East slope of rocky hill40.00. Set a granite stone  $24 \times 10 \times 10$  ins 18 ins  
in the ground, for  $\frac{1}{4}$  Sec Cor. marked  $\frac{1}{4}$   
on N. face and raised a mound of  
stone,  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft base, alongside,  
pile impracticable. From which  
An oak 8 ins. diam bears West 8 lbs  
dist marked  $\frac{1}{4}$  S. B. F.An oak 16 ins. diam bears  $N 42^{\circ} E$  15 lbs  
dist. marked  $\frac{1}{4}$  S. B. F.60.00 Leave hill and enter rocky rolling  
land80.00 Set a Granite stone  $24 \times 12 \times 10$  ins  
18 ins in the ground for cor. to sec



Subdivisions T. 22 S. R. 11 E. - Continued

Chamo

25, 26, 35 & 36 marked with 1 notch on S. and 1 notch on E edges and raised a mound of stone alongside. Site impracticable. From which

The oak 24 ins diam. bears S.  $55^{\circ}$  W. 58 lbs dist, marked T. 22 S. R. 11 E. Sec 35 B. T.

The oak 12 ins. diam bears N  $79^{\circ}$  W. 95 lbs dist, marked T. 22 S. R. 11 E. S. 26 B. T.

The oak 6 ins. diam bears N  $17^{\circ}$  W. 86 lbs dist, marked T. 22 S. R. 11 E. S. 26 B. T.

The oak 20 ins diam. bears S.  $85^{\circ}$  E. 83 lbs dist, marked T. 22 S. R. 11 E. S. 36 B. T.

Land, rough, hilly and rocky

Soil, 4<sup>th</sup> rate and worthless

Timber, scattering Oak. Good grass.

East on a random line bet Secs 25 & 36

Var.  $12^{\circ} 35' E$ .

Over rough hilly land.

Subdivisions of T. 22 S. R. 11 E. - Continued

Chains.

- 12.00 Wash 1 ch. wide course S.  $20^{\circ}$  E. and line runs over low rocky hills
- 40.00 Set temp.  $\frac{1}{4}$  Sec. cor.
- 43.00 Ravine 10 feet deep course N  $50^{\circ}$  E.
- 58.00 Ravine 10 feet deep course North
- 80.08 Intersect East bdy of Township at 14 lks North of the cor. to Secs 25, 30, 31 & 36 previously established and described by me
- Thence run N.  $89^{\circ} 54'$  W on a true line betw. Secs 25 & 36 with same Var.
- 40.04. Set a Granite stone 16 x 12 x 8 ins 11 ins in the ground for  $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$  on N. face, and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside pits impracticable. From which an Oak 8 ins. diam bears N.  $40^{\circ}$  W  $25$  lks dist marked  $\frac{1}{4}$  S. B. T.
- An oak 8 ins. diam bears S.  $52^{\circ}$  E  $26$  lks dist. marked  $\frac{1}{4}$  S. B. T.



Subdivision T. 22. R. 11 E. - Continued

name

80.08 The cor to Secs 25, 26, 35 & 36

Land, rough, rocky and hilly.  
Soil, worthless. Good grass.  
Timber, scattering oak.

North bet. Secs 25 & 26

Var. 12° 35' E.

Over rolling land.

1.50. Wash 60 lks wide, Course, East.

20.00 Wash 50 lks wide, Course S. 50° E.

29.00 Wash 40 lks wide, Course S 45° E.

40.00 Set a Limestone 15 x 10 x 8 ins. 10 ins. in  
the ground for 1/4 Sec. cor. marked 1/4 on  
along side.

Its face with mound of stone from which  
was impracticable.

An oak 6 ins diam bears S 65° W 18 1/2 dia marked 1/4 SBT.

An oak 6 ins diam bears N 22° E 46 lks dia marked 1/4 SBT

73.00 Wash 50 lks wide, course S 50° E

80.00 Set a Granite stone 18 x 18 x 18 ins 12 ins

## Subdivisions T. 22. S. R. 11E. - continued

Crown.

in the ground for cor to Secs 23, 24, 25  
& 26 marked with 2 notches on S. and  
1 notch on E edges and raised a  
mound of stone alongside. Pits  
unpracticable. From which  
An oak 16 ins. diam bears S.  $82\frac{1}{2}^{\circ}$  E. 150 lks  
diat marked T. 22. S. R. 11E. S. 25 B. S.  
An oak 10 ins. diam bears N  $28^{\circ}$  E. 155 lks  
diat marked T. 22 S. R. 11E. S. 24 B. S.  
An oak 24 ins. diam bears N  $27^{\circ}$  W. 242 lks  
diat. marked T. 22 S. R. 11E. Sec 23 B. S.  
No other trees within limits.  
Land rolling and rocky.  
Soil, 4<sup>th</sup> rate. Good Grass.  
Timber, scattering oak.

East on a random line bet Secs 24 & 25  
Var  $12^{\circ} 35' E$ .

## Subdivisions T. 22 S. R. 11 E. - continued

name	
	Over rough rolling land
70.00	Set temporary $\frac{1}{4}$ Sec cor.
54.60	Mark 1 ch wide course $\S 30^{\circ} E$
79.90	Intersect E boundary of Tp. 21 bk S of the cor to secs 19. 24. 25 & 30 previously established and described by me Thence run $\S 89^{\circ} 51' W.$ on a true line bet Secs 24 & 25 with same Var.
39.95	Set a volcanic stone 24 X 10 X 8 ins 18 ins in the ground for $\frac{1}{4}$ Sec cor. marked $\frac{1}{4}$ on N face and raised a mound of stone alongside pits impracticable From which An oak bin diam bears $\S. 15$ lks dist marked $\frac{1}{4}$ SBT
79.90	The cor to secs 23. 24. 25 & 26 Land rolling and rocky Soil 3 <sup>d</sup> and 4 <sup>th</sup> rate Good grass Timber scattering oak.
	North bet Secs 23 & 24 Var $12^{\circ} 35' E$



## Subdivisions T. 22 S. R. 11 E - continued

Chains

Over rolling land rough and rocky.

37.00 Wash 20 lks wide course S 40° E.

40.00 Set a granite stone 30 x 20 x 20 ins 22 ins in the ground for  $\frac{1}{4}$  Sec cor. marked  $\frac{1}{4}$  on W. face, and raised a mound of stone alongside pits impracticable  
From which

An oak 6 ins diam bears S 70° E 20 lks dist marked  $\frac{1}{4}$  S.B.T.

An oak 10 ins diam bears S 78° E 32 lks dist marked  $\frac{1}{4}$  S.B.T.

45.00 Same Wash as above 20 lks wide course S 50° E.

52.00 Wash 20 lks wide course S 45° W.

80.00 Set a granite stone 30 x 18 x 18 ins 22 ins in the ground for cor to sec 13, 14, 23 & 24 marked with 3 notches on S and 1 notch on E edges and raised a mound of stone alongside. Pits impracticable  
From which

An oak 4 ins diam bears N 86° E 27 lks dist marked T. 22 S. R. 11 E. S. 13 B.T.

A piñon pine 6 ins diam bears N 50° E 36 lks dist. marked T. 22 S. R. 11 E. S. 13 B.T.

Subdivisions T<sub>22</sub> S. R. 11 E. - Continued

Chains.

No other trees within limits.

Land, rough and rocky.

Soil, worthless.

Timber, scattering oak and prairie pine.

East on a random line bet Secs 13 &amp; 24

Var.  $12^{\circ} 53' E$ .

Over rough and broken ridges.

28.00 Ravine 15 ft deep, course  $S. 30^{\circ} E$ 

35.00 Line passes at foot of rocky bluff 70 ft high on the North.

40.00 Set temporary to Sec. cor.

58.00 Ravine 10 ft deep course South

72.00 Ravine 15 ft deep course  $S 30^{\circ} E$ .80.43. Intersect E. bdy of Township on summit of ridge bearing  $N \frac{1}{2} S$  at 33 lks N. of the cor. to Secs 13, 18, 19, & 24 previously established and described by me. Thence I run  $N 89^{\circ} 46' W$ . on a true line bet Secs 13 &

## Subdivisions T. 22 S. R. 11 E. - Continued

Chains.

24 with same Var.

40.22. Set a Granite stone  $30 \times 18 \times 12$  ins 22 ins in the ground for  $\frac{1}{4}$  Sec cor marked  $\frac{1}{4}$  on N. face, and raised a mound of stone,  $1\frac{1}{2}$  ft high 3  $\frac{1}{2}$  ft base along side, pits impracticable.

80.43. The cor to secs 13, 14, 23 & 24.

Land rough, and rocky.

Soil, worthless. Good grass.

Timber a few oak.

North bet. Secs. 13 & 14

Var.  $12^{\circ} 35' E$

Over rocky hills

2.00 Wash 50 lks wide course S.  $30^{\circ} W$  and commence descent of rough rocky hills

40.00 Set a Granite  $20 \times 8 \times 6$  ins 15 ins in the ground for  $\frac{1}{4}$  Sec Cor. marked  $\frac{1}{4}$  on W.



## Subdivision T. 22 S. R. 11 E. - Continued

chains

face, and raised a mound of Stone  
 $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft base alongside, pits  
 impracticable

62.00 Summit 800 ft high and commence  
 descent

80.00 Set a Granite stone  $20 \times 6 \times 4$  ins  $15$  ins  
 in the ground for cor to secs 11. 12. 13 & 14  
 marked with 4 notches on S and 1 notch  
 on E edges, and raised a mound of  
 stone alongside. Pits impracticable  
 Land mountainous & rocky  
 Soil worthless  
 Timber a few oak and pinon.

East on a random line bet Secs 12 & 13.

Var  $12^{\circ}35'$  E.

Over mountainous land, line runs  
 along North side of Mountain.

## Subdivisions T. 22 S. R. 11 E - Continued

Chains

40.00 Set temporary  $\frac{1}{4}$  Sec. Cor. and commenced descent of East slope.

52.00 Foot and enter rough rocky hills.

80.36. Intersects the E. boundary of Twp. 16 Nks South of the Cor to 7.12.13 & 18. previously established and described by me.

Thence I run S.  $89^{\circ}53'$  W. on a true line bet. Secs 12 & 13 with same Var.

40.18 Set a Granite stone  $18 \times 6 \times 6$  ins  $12$  ins in the ground for  $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$  on N. face, and raised a mound of stone,  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along side, pits impracticable.

80.36 The cor to Secs 11.12.13 & 14

Land, mountainous

Soil, worthless.

Timber, some oak and pinon pine

## Subdivisions T. 22 S. R. 11 E. Continued

hans

North bet Secs 11 &amp; 12

Var.  $12^{\circ}35'E$ .Commence descent from corner line  
running down North slope of mountain

12.00 Foot and enter rolling hills

40.00 Set a volcanic stone  $16 \times 8 \times 8$  ins  $11$  ins  
in the ground for  $\frac{1}{4}$  Sec Cor. marked  $\frac{1}{4}$   
on W. face, dig pits  $18 \times 18 \times 12$  ins N & S  
of stone  $5\frac{1}{2}$  ft dist and raised a mound  
of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  feet base alongside78.00 Wash 15 lks wide, course  $N 20^{\circ} W$ .80.00 Set a Granite stone  $16 \times 14 \times 4$  ins.  $11$  ins  
in the ground for Cor to Secs 1. 2. 11 & 12  
marked with 5 notches on S and 1 notch  
on E edges, and raised a mound of  
stone alongside, pits impracticable  
Land, for first 12 chs mountainous  
balance rolling hills.Soil, 3<sup>d</sup> and 4<sup>th</sup> rate, good grass



## Subdivisions T. 22. S. R. 11 E. Continued

Chains

in rolling hills

Timber, a few oaks on mountain slope.

Survey 10<sup>th</sup> 1887.

East on a random line bet Secs 1 &amp; 12.

Var.  $12^{\circ} 35' E$ .

Over rolling land

27.00 Wash 20 lks wide, course  $N 30^{\circ} W$ .38.60 Wash 20 lks wide, course  $N 30^{\circ} W$ .40.00 Set temp  $\frac{1}{4}$  Sec. Cor.50.00 Wash 10 lks wide course  $N 20^{\circ} W$ .67.00 Wash 20 lks wide course  $N 20^{\circ} W$ .71.00 Wash 20 lks wide course  $N 30^{\circ} W$ .79.00 Wash 15 lks wide course  $N 30^{\circ} W$ .80.11 Intersect E. bdy of Tp. at 28 lks N. of the cor to Secs 1, 6, 7 & 12 previously established and described by me. Thence I run  $N 89^{\circ} 48' W$  on a true line bet. secs 1 & 12 with same

## Subdivisions T. 22. S. R. 116. - Continued

ans

Var.

40.06 Set a Granite stone  $18 \times 14 \times 4$  ins  $12$  ins  
in the ground for  $\frac{1}{4}$  Sec. Cor. marked  
 $\frac{1}{4}$  on N. face, and raised a mound  
of stone,  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along-  
side, pits impracticable. From which  
An oak  $14$  ins diam <sup>long</sup> N.  $36^\circ$  W.  $72$  lks  
dist. marked  $\frac{1}{4}$  S. B. T.

An oak  $10$  ins. diam bears S.  $40^\circ$  E  $104$   
lks dist. marked  $\frac{1}{4}$  S. B. T.

50.11 The cor to secs 1. 2. 11 & 12.

Land rolling.

Soil 3<sup>d</sup> rate. Good grass.

No Timber.

North on a random line bet Secs 1 & 2

Var.  $12^\circ 35'$  E.

Over rolling land.

## Subdivisions T. 22. S. R. 11 E. Continued

Chains

- 40.00 Set temporary  $\frac{1}{4}$  Sec cor.
- 62.00 Wash 20 lks wide, course West.
- 80.11 Intersect N. boundary of Tp. at 24 lks  
W. of the cor. to Secs 1, 2, 35 & 36 previously  
established and described by me. Thence  
run S.  $0^{\circ} 10' W.$  on a true line  
bet Secs 1 & 2 with same Var.
- 40.11 Set a volcanic stone 12x10x10 ins  
8 ins in the ground for  $\frac{1}{4}$  Sec Cor.  
marked  $\frac{1}{4}$  on W. face, dug pits 18x  
18x12 ins N & S of Stone  $5\frac{1}{2}$  ft  
dist, and raised a mound of  
earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside.
- 80.11 The cor. to secs 1, 2, 11 & 12  
Land rolling  
Soil. 3<sup>d</sup> and 4<sup>th</sup> rate. Good grass.  
No Timber.



## Subdivisions T. 22 S. R. 11 E. - Continued

Chains

From the cor. to secs 2, 3, 34 & 35 on the  
South boundary of Township which  
is a granite stone previously established  
and described by me I run

North bet. Secs 34 & 35  
Var  $12^{\circ}35'E$ .

Over rough rocky hills.

21.00 Wash 30 lks wide course East

32.00 Wash 20 lks wide course  $S. 80^{\circ}E$ .

40.00 Set a Volcanic stone  $14 \times 12 \times 8$  ins 10 ins  
in the ground for  $\frac{1}{4}$  Sec Cor. marked  
 $\frac{1}{4}$  on W. face, and raised a mound  
of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along  
side, pits impracticable From which  
An oak 6 ins. diam bears  $S. 75^{\circ}E$  35 lks  
dist marked  $\frac{1}{4}$  S. B. T.

An oak 12 ins. diam bears  $N. 61^{\circ}W$   
40 lks dist. marked  $\frac{1}{4}$  S. B. T.

60.50 Wash 60 lks wide, course  $S. 40^{\circ}E$ .

## Subdivisions T. 22 S. R. 11 E. - Continued

Chains

- 78.00. Wash 70 lks wide course S. 35° E.
- 80.00 Set a Volcanic stone 18 x 12 x 8 ins 12 ins  
in the ground for cor to sec 26. 27.  
34 & 35. marked with one notch on  
S and 2 notches on E edges, and  
raised a mound of stone along side,  
pits impracticable. From which  
An oak 3 ins. diam. bears N 32½ E 25 lks  
dist. marked T. 22 S. R. 11 E. S. 26 B.T.
- An oak 8 ins. diam bears S. 86° E 103 lks  
dist. marked T. 22 S. R. 11 E. Sec 35 B.T.
- An oak 12 ins diam. bears S. 43° E. 126 lks  
dist. marked T. 22 S. R. 11 E. Sec 35 B.T.
- An oak 6 ins. diam bears N. 65° E 152 lks  
dist. marked T. 22 S. R. 11 E. S. 26 B.T.
- Land rough and rocky hills.  
Soil, worthless. Good grass  
Timber scattering oak

## Subdivisions T. 22 S. R. 11 E. - Continued

Chain

East on a random line bet. Secs 26 & 35  
Var.  $12^{\circ}35' E$ .

Over rolling land.

- 40.00 Set temp.  $\frac{1}{4}$  Sec. Cor.
- 68.00 Wash 50 lks wide, course  $S. 65^{\circ} E$ .
- 74.00 Same wash 75 lks wide course  $N 70^{\circ} E$
- 80.20 Intersect N and S line 13 lks S of the  
cor to secs 26, 27, 34 & 35. Thence I run  
 $S. 89^{\circ} 55' W$ . on a true line bet Secs  
26 & 35 with same Var.
- 40.10 Set a volcanic stone  $24 \times 18 \times 10$  ins  
18 ins in the ground for  $\frac{1}{4}$  Sec. Cor.  
marked  $\frac{1}{4}$  on N. face and raised a  
mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft  
base along side, pits impracticable  
from which
- An oak 8 ins. diam bears  $S. 1^{\circ} E$ . 15 lks  
distant marked  $\frac{1}{4}$  S. B. T.
- An oak 8 ins. diam bears  $S. 82^{\circ} W$ . 28 lks



## Subdivisions T. 22 S. R. 11 E. - Continued

Chains

- dist marked  $\frac{1}{4}$  S. B. T.
- 80.20 The cor to secs 26. 27. 34 & 35.  
Land rolling.  
Soil 3<sup>rd</sup> and 4<sup>th</sup> rate Good grass.  
Timber scattering oak.
- 
- North bet. Secs 26 & 27.  
Var.  $12^{\circ} 35' E$ .
- Over rough and rocky land
- 40.00 Set a Granite stone  $20 \times 6 \times 6$  ins 15 ins  
in the ground for  $\frac{1}{4}$  Sec cor. marked  
 $\frac{1}{2}$  on N. face and raised a mound  
of stone  $1\frac{1}{2}$  ft  $3\frac{1}{2}$  ft base alongside,  
pits impracticable
- 78.00 Line passes over rocky bluff 50 ft high  
bearing N & S.
- 80.00 Set a Granite stone  $30 \times 20 \times 12$  ins  
22 ins. in the ground for cor to secs

## Subdivisions T. 22 S. R. 11 E. - Continued

Chains

22. 23. 26. & 27 marked with 2 notches  
on S and E edges, and raised a  
mound of stone alongside, pits im-  
practicable. From which

An oak 8 ins. diam. bears S. 78 W. 50 lks  
dist. marked T. 22 S. R. 11 E. S. 34 B. T.

An oak 14 ins. diam bears N 65° W 125 lks  
dist. marked T. 22 S. R. 11 E. S. 22 B. T.

No other trees within limits.

Land rough and broken  
soil, worthless

Timber a few scattering oak and  
piñon pine.

By observation taken this day I  
find the magnetic Variation  
to be  $12^{\circ} 35' E$ .

## Subdivisions T. 22 S. R. 11 E. Continued

Chains

- 44.00 Wash 30 lbs wide course  $N 80^{\circ} E$ .
- 80.00. Set a granite stone  $24 \times 18 \times 6$  ins  
18 ins in the ground for cor to sec  
14. 15. 22 & 23 marked with 3 notches  
on S and 2 notches on E edges and  
raised a mound of stone along side,  
pits impracticable.
- Land mountainous  
Soil worthless.  
Timber a few oaks and pinow pine

East on a random line bet Secs 14 &amp; 23

Var.  $12^{\circ} 35' E$ .

Descending from corner.

- 8.00 Gulch 10 ft deep. course  $N 10^{\circ} E$ . and  
line runs up over little hill
- 33.00. Summit 150 ft high and descend.
- 40.00 Set temp.  $\frac{1}{4}$  Sec. cor.



Subdivisions T. 22 S. R. 11 E. - Continued

Chains

- 57.00 Gulch 15 ft deep crosses S. 15° E and enters rolling land.
- 78.70. Wash 50 lks wide course S. 40° W.
- 80.08 Intersect N & S line at 27 lks N. of the cor. to secs. 13, 14, 23 & 24. Thence I run N. 89° 49' W. on a true line bet sec. 14 & 23 with same var.
- 40.04. Set a granite stone 36 x 18 x 12 ins 27 ins in the ground for  $\frac{1}{4}$  Sec cor. marked  $\frac{1}{4}$  on N. face and raised a mound of stone 1 $\frac{1}{2}$  ft high 3 $\frac{1}{2}$  ft base alongside, pits impracticable
- 80.08 The cor. to secs 14, 15, 22, & 23.  
Land rough, rocky & hilly.  
Soil worthless  
Timber a few oaks.

Subdivisions T<sub>p.</sub> 22 S. R. 11 E. Continued  
 Chains.

North bet Secs 14 & 15.

Var.  $12^{\circ}35' E$ .

Descending from cor over rough hillside.

12.00 Gulch 20 ft deep course N.  $50^{\circ} W$ . and ascend along West slope of high hill

40.00. Set a granite stone  $16 \times 8 \times 6$  ins 11 ins in the ground for  $\frac{1}{4}$  Sec cor. marked  $\frac{1}{4}$  on W. face, and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along side pits impracticable

45.50 Summit of ridge 600 ft high bearing West from hill on East and commence descent of North slope of hill

73.00 Foot of slope and gulch 18 ft deep course N  $10^{\circ} E$

80.00 Set a Granite stone  $20 \times 8 \times 8$  ins 15 ins in the ground for cor to secs 10, 11, 14 & 15 marked with 4 notches on S and 2 notches on E edges, and raised a mound of

Subdivision T. 22 S. R. 11 E. - Continued  
chains

stone alongside, pits impracticable

Land rough and hilly

Soil, worthless.

Timber a few scattering oak and piñon pine

January 11<sup>th</sup> 1887.

Secs

East on a random line bet 11 & 14

Var  $12^{\circ} 35' E$

Over rough broken mountain side

300 Ravine 30 ft deep course  $N 30^{\circ} E$  and  
line runs along North slope of Mountain

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

59.50 Ravine 20 ft deep course N.

80.29 Intersect N. and S. line 19 lks E. of the  
cor to secs. 11, 12, 13 & 14. Thence I run  
 $S. 89^{\circ} 52' W.$  on a true line bet secs.  
11 & 14. with same Var.

40.15 Set a granite stone  $18 \times 10 \times 8$  ins.  
12 ins in the ground for  $\frac{1}{4}$  Sec. cor.



## Subdivision T. 22 S. R. 11 E - Continued

Chains

marked  $\frac{1}{4}$  on N. face, and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside, pits impracticable

80.29 The cor to secs 10. 11. 14 & 15.

Land rough and mountainous.

Soil worthless

Timber some few oak and piñon pine

North bet Secs. 10 & 11

Var.  $12^{\circ}35'E$ .

Commence ascent from cor. over East slope of rocky hill

15.00 Summit of ridge and descend

32.00 Foot, Wash 20 lks wide course N.  $70^{\circ}E$  and enter rolling land.

40.00 Set a Granite stone  $16 \times 10 \times 8$  ins  $11$  ins. in the ground for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  on W. face, and raised

Subdivisions T. 22 S. R. 11 E. - Continued  
 Chamo

a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft  
 base alongside, pits impracticable  
 From which

An oak 10 ins. diam bears S. 40° E 20 lbs  
 dist. marked  $\frac{1}{4}$  S. B. T.

No other trees in limits

41.00. Wash 10 lbs wide course N 45° E.

71.00 Wash 70 lbs wide course N 80° E

77.00 Wash 30 lbs wide course S. 80° E.

80.00 Set a volcanic stone  $12 \times 12 \times 8$  ins

8 ins in the ground for cor-to-secs  
 2, 3, 10 & 11 marked with 5 notches  
 on S and 2 notches on E edges

and raised a mound of stone along-  
 side pits impracticable

Land, rough and hilly for 32 chs,  
 balance rolling

Soil, 3<sup>d</sup> and 4<sup>th</sup> rate. Good grass in  
 rolling land.

Subdivisions T. 22 S. R. 11 E. - Continued

Chains

Timber a few oaks.

East on a random line bet Secs 2 & 11  
Var  $12^{\circ} 35' E$ .

Over rolling land.

- 10.00 Wash 10 lks wide, course  $S 80^{\circ} W$
- 16.00 Same wash 15 lks wide course  $N 60^{\circ} W$
- 21.00 Same wash 15 lks wide course  $S. 70^{\circ} W$ .
- 40.00 Set temp.  $\frac{1}{4}$  Sec. Cor.
- 40.30 Wash 10 lks wide course South
- 52.00 Wash 10 lks wide course  $S. 45^{\circ} W$
- 68.00 Same wash 15 lks wide course  $N 30^{\circ} W$
- 79.80 Wash 15 lks wide course  $N. 10^{\circ} W$ .
- 80.15 Intersect N and S. line at 31 lks S.  
of the cor. to Secs 1. 2. 11 & 12. Thence  
I run  $S 89^{\circ} 47' W$ . on a true line  
bet Secs. 2 & 11 with same Var.
- 40.08. Set a volcanic stone  $14 \times 8 \times 6$  ins 10 ins

Subdivisions T. 22 S. R. 11 E. - Continued

Chains

in the ground for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  on N. face and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside, pits impracticable. From which

A mesquite 8 ins. diam bears S.  $83\frac{1}{2}^{\circ}$  W  
200 lks dist. marked  $\frac{1}{4}$  S. B. T.

A mesquite 4 ins. diam bears S.  $31^{\circ}$  E.  
133 lks dist. marked  $\frac{1}{4}$  S. B. T.

80.15 The cor to secs 2, 3, 10 & 11.

Land, rolling.

Soil, 3<sup>d</sup> and 4<sup>th</sup> rate. Good grass.

Timber, a few mesquite.

North on a random line bet Secs 2 & 3.

Var.  $12^{\circ}35'$  E.

Over rolling land

40.00 Set temp.  $\frac{1}{4}$  Sec. cor.

40.30 Wash 15 lks wide, course S.  $45^{\circ}$  W.



BOOK 929

## Subdivisions T. 22 S. R. 11 E - Continued

Chains

- 80.30 Intersect North boundary of Township  
16 lks W. of the cor to Secs 2, 3, 34 & 35 pre-  
viously established and described by me  
Thence Drive S  $0^{\circ} 07''$  W on a true  
line bet Secs 2 & 3 with same Var.
- 40.30 Set a Granite stone  $14 \times 8 \times 6$  ins 10 ins  
in the ground for  $\frac{1}{2}$  Sec cor. marked  
 $\frac{1}{2}$  on W. face, and raised a mound  
of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside  
It is impracticable
- 80.30. The cor to secs 2, 3, 10 & 11.  
Land, rolling  
Soil, 3<sup>d</sup> and 4<sup>th</sup> rate. Good grass  
No timber.

From the cor. to Secs 3, 4, 33 & 34 on  
the South boundary of Township  
previously established and described

## Subdivisions T. 22 S. R. 11 E. Continued

chains

by me &amp; run

North bet Secs. 33 &amp; 34

Var.  $12^{\circ}35' E$ 

Over rolling land

1.00 Wash 30 lks wide course  $N 45^{\circ} E$ .

40.00 Set a volcanic stone  $14 \times 10 \times 8$  ins 10 ins  
in the ground for  $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$   
on W. face and raised a mound of  
stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside  
Pits impracticable. From which  
An oak 12 ins. diam bears  $N. 14^{\circ} E$  43 lks  
dist. marked  $\frac{1}{4}$  S. B. T.  
An oak 8 ins. diam bears  $S. 71^{\circ} E$  38 lks  
dist. marked  $\frac{1}{4}$  S. B. T.

41.50 Wash 15 lks wide, course  $S. 85^{\circ} E$ .

80.00 Set a volcanic stone  $16 \times 10 \times 8$  ins 12 ins  
in the ground for cor to secs 27. 28. 33  
& 34 marked with 1 notch on S and  
3 notches on E edges, and raised a

Subdivisions T. 22 S. R. 11 E. Continued  
 names

mound of stone alongside, pits imprac-  
 ticable. From which

An oak 8 ins. diam bears  $N 46^{\circ} E$  27 lks dist  
 marked T. 22 S. R. 11 E S. 27 B.T.

An oak 6 ins. diam bears East 20 lks dist  
 marked T. 22 S. R. 11 E. B.T. on line

An oak 10 ins diam bears  $S. 48^{\circ} W.$  65 lks  
 dist. marked T. 22 S. R. 11 E. S. 33 B.T.

No other trees within limits

Land, rolling and rocky

Soil, 4<sup>th</sup> rate

Timber, a few oaks.

East on a random line bet Secs 27 & 34

Var.  $12^{\circ} 35' E.$

Over rolling and broken land.

00.20 Oak Tree on line, 6 ins. diam

12.00 Wash 30 lks wide course  $N 45^{\circ} E.$

30.00 Wash 30 lks wide course  $N 45^{\circ} W.$

## Subdivisions T. 22 S. R. 11 E - Continued

- Chains
- and line runs over little rocky hill
- 36.00 Summit 200 ft high and commence descent.
- 40.00 Set temp  $\frac{1}{4}$  Sec. Cor.
- 46.00 Foot of little rocky hill and wash 30 lks wide, course  $N 45^{\circ} W$ .
- 79.00 Wash 60 lks wide course  $S. 10^{\circ} E$ .
- 80.16 Intersect N & S line at 14 lks N. of the cor. to Secs 26. 27. 34 & 35. Thence I run  $N 89^{\circ} 54' W$ . on a true line bet sec. 27 & 34 with same var.
- 40.08 Set a volcanic stone  $24 \times 18 \times 18$  ins 18 ins in the ground for  $\frac{1}{4}$  Sec cor. marked  $\frac{1}{2}$  on N. face and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside, pits impracticable
- 80.16. The cor to sec. 27. 28. 33 & 34  
Land rolling and hilly  
Soil  $\frac{1}{4}$  the rate, good grass.



## Subdivisions T. 22. S. R. 11 E. Continued

Chains

Timber a few oaks.

North bet. Secs 27 &amp; 28

Var  $12^{\circ} 35' E$ 

Over rough rolling land.

20.50 Ravine 20 ft deep, course  $N 30^{\circ} E$ .

40.00 Set a granite stone  $18 \times 12 \times 6$  ins. 12 ins  
in the ground for  $\frac{1}{4}$  Sec. Cor. marked  
 $\frac{1}{4}$  on W. face, and raised a mound of  
stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along side  
pit impracticable

48.00 Commence ascent of rocky hill

62.00 Summit 300 ft high and descend.

73.00 Foot and ravine 10 ft deep course West.

80.00 Set a granite stone  $18 \times 12 \times 6$  ins 12 ins  
in the ground for cor to secs 21. 22. 27  
& 28 marked with 2 notches on S and  
3 notches on E edges and raised

## Subdivisions T. 22 S. R. 11 E. Continued

Chains

a mound of stone along side. Pits  
 impracticable. From which  
 An oak 6 ins. diam. bears N. 88° E. 30 lks  
 dist. marked T. 22 S. R. 11 E. S. 22 B.T.  
 An oak 4 ins. diam. bears S. 86° E. 33 lks  
 dist. marked T. 22 S. R. 11 E. S. 27 B.T.  
 An oak 4 ins diam. bears S 8° W. 40 lks  
 dist. marked T. 22 S. R. 11 E. S. 28 B.T.  
 An oak 4 ins. diam bears S. 42° W. 85 lks  
 dist. marked T. 22 S. R. 11 E. S. 28 B.T.  
 Land, rough, broken and hilly  
 Soil 4<sup>th</sup> rate and worthless.  
 Timber, scattering oak.

East on a random line bet Secs 22 & 27  
 Var. 12° 35' E.

Over rough rocky ground

6.00 Ravine 10 ft deep course S. 40° E.

## Subdivisions T. 22 S. R. 11 E. - Continued

Chains

- 40.00 Set temp  $\frac{1}{4}$  Sec Cor.
- 66.00. Gulch 18 ft deep course South.
- 80.10 Intersect N & S. line 16 lks N. of the cor. to secs 22. 23. 26 & 27. Thence I run N.  $89^{\circ} 53' W.$  on a true line bet. Secs. 22 & 27 with same Var.
- 40.05 Set a granite stone  $40 \times 30 \times 30$  ins 30 ins in the ground for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  on N. face, and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along side. Pits impracticable. From which  
 A piñon pine 8 ins. diam. bears N  $8^{\circ} W$  25 lks dist marked  $\frac{1}{4}$  S. B. F.  
 A piñon pine 4 ins diam. bears S.  $17^{\circ} E$ . 40 lks dist, marked  $\frac{1}{4}$  S. B. F.
- 80.10. The cor to secs 21. 22. 27 & 28  
 Land, rough and rocky.  
 Soil worthless.  
 Timber a few piñons and oaks

## Subdivisions T. 22 S. R. 11 E. - Continued

- Chamo
- North bet Secs 21 & 22  
Var  $12^{\circ} 35' E$ .
- 1.50. Line runs along West slope of rocky hill  
Gulch 15 ft deep course West.
- 40.00 On steep West slope of rocky hill set a  
granite stone  $20 \times 10 \times 6$  ins 15 ins in the  
ground for  $\frac{1}{4}$  Sec Cor. marked  $\frac{1}{4}$  on  
W. face and raised a mound of stone  
 $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside, pits  
impracticable
- 43.00 Ravine 15 ft deep, course West and descend
- 73.00 Foot of hill and wash 20 lbs wide course  
 $S. 75^{\circ} W.$  and commence ascent of another  
hill.
- 80.00 Set a granite stone  $18 \times 12 \times 12$  ins. 12 ins  
in the ground for cor to secs 15. 16. 21 & 22  
marked with 3 notches on S and E  
edges and raised a mound of stone  
alongside  
pits impracticable.



Subdivision T. 22 S. R. 11 E. - Contained  
 Chain

Land, rough, rocky and mountainous.

Soil, worthless.

Timber a few oaks.

12<sup>th</sup> Jan'y 1887.

East on a random line bet Secs 15 & 22

Var.  $12^{\circ}35' E$

Commence descent from cor; line runs  
 over rough North slope of Mountain from South

10.00 Wash 30 lks wide, course  $S. 60^{\circ} W.$

28.00 Wash 20 lks wide, course  $N 30^{\circ} W.$

40.00 Set temp  $\frac{1}{2}$  Sec. cor.

61.00 Ravine 15 lks deep course  $N 20^{\circ} E.$

79.96 Intersect N and S line at 27 lks S of the  
 cor. to secs 14, 15, 22 & 23. Thence I run  
 $S. 89^{\circ}49' W.$  on a true line bet. secs 15  
 & 22 with same var.

39.98 Set a granite stone  $18 \times 8 \times 6$  ins  $12$  ins  
 in the ground for  $\frac{1}{4}$  Sec Cor. marked

Subdivisions T. 22 S. R. 11 E. - Continued  
 name

$\frac{1}{4}$  on N. face, and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside pits impracticable.

79.96 The cor to secs 15.16. 21 & 22

Land, rough and hilly  
 Soil, worthless.

Timber scattering oaks.

North bet. Secs 15 & 16

Var.  $12^{\circ} 35' E.$

Ascending from cor. and line runs up SE slope of mountain.

20.00 Summit of mountain 700 ft high bearing  $N 20^{\circ} E$  and  $S 30^{\circ} W$  and commence descent

40.00 Set a granite stone  $18 \times 10 \times 8$  ins  $12$  ins in the ground for  $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$  on W. face and raised a mound

## Subdivision T. 22 S. R. 11 E. - Continued

Chain

of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside,  
Pits impracticable.

61.00 Gulch 20 ft deep course  $N 45^{\circ} E$ .

78.00 Foot of hill and wash 1 ch. wide course  
 $N. 50^{\circ} E$ .

80.00. Set a volcanic stone  $30 \times 12 \times 6$  ins  $22$  ins  
in the ground for cor to secs 2, 3, 10 & 11  
marked with 4 notches on S and  
3 notches on E edges, and raised a  
mound of stone alongside, Pits  
impracticable

Land mountainous and broken.

Soil, worthless

Timber a few oaks and pines

East on a random line bet Secs 10 & 15

Var  $12^{\circ} 35' E$ .

Over rough north slope of hill

## Subdivisions T. 22 S. R. 11 E. Continued

Chains

- 3.00 Wash 80 lks wide course  $N 45^{\circ} E$ .
- 18.00 Gulch 15 ft deep course  $N. 20^{\circ} E$ .
- 38.00 Foot of slope and gulch 15 ft deep course  $N 10^{\circ} W$ . and commence ascent of South slope of rocky hill on the North
- 40.00 Set temp  $\frac{1}{2}$  sec. cor.
- 57.00 Summit of slope and descend.
- 80.30 Intersect N. and S. line 10 lks N. of the cor. to secs 10. 11. 14 & 15. Thence I run  $N 89^{\circ} 56' W$  on a true line bet secs 10 & 15 with same Var.
- 40.15. Set a granite stone  $18 \times 18 \times 12$  ins 12 ins in the ground for  $\frac{1}{2}$  Sec. cor. marked  $\frac{1}{4}$  on N. face, and raised a mound of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along side. Pits impracticable
- 80.30. The cor. to secs. 9. 10. 15 & 16. Land rough and mountainous Soil, worthless.



Subdivisions T. 22. R. 11 E. Continued  
 chains

Timber, few oaks.

By observation taken this day I find  
 the magnetic variation to be  $12^{\circ}35'E$ .

North bet. Secs 9 and 10

Var.  $12^{\circ}35'E$ .

Over rough rocky hills.

- 4.50 Wash 50 lks wide course  $N70^{\circ}E$ . and  
 line runs up steep hill side.
- 30.00 Summit 800 ft high bearing NW  
 and SE, and descend
- 40.00 Set a granite stone  $18 \times 6 \times 6$  ins  $12$  ins  
 in the ground for  $\frac{1}{4}$  Sec. cor. marked  
 $\frac{1}{4}$  on W. face, and raised a mound  
 of stone  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base along  
 side, Pits impracticable
- 66.00 Foot and wash 30 lks wide course

## Subdivisions T. 22 R. 11 E. Continued

Chamo

at 45° W. and enter rolling land.

78.00 Wash 20 lks wide, course S. 60° W.

80.00 Set a quartz stone 14 x 12 x 10 ins 10 ins  
in the ground for cor to secs 3, 4, 9 & 10  
marked with 5 notches on S and  
3 notches on E edges, and raised a  
mound of stone alongside, Pits im-  
practicable.

From which

An oak 8 ins. diam bears N. 57° E. 18 lks  
dist. marked T. 22 S. R. 11 E. S. 3 B. T.

An oak 6 ins. diam. bears N. 86° E. 70 lks  
dist. marked T. 22 S. R. 11 E. S. 3 B. T.

An oak 8 ins. diam bears N 61° W. 17 lks  
dist. marked T. 22 S. R. 11 E. S. 4 B. T.

An oak 4 ins diam bears S. 1° W. 48 lks  
dist. marked T. 22 S. R. 11 E. S. 10 B. T.

Land rocky mountainous for 66 chs  
then rolling.

Soil 3<sup>d</sup> and 4<sup>th</sup> rate. Good grass

Subdivisions T. 22 S. R. 116. Continued  
 Chains

Timber some scattering oak.

East on a random line bet Secs 3 & 10.

Var.  $12^{\circ} 35' E$ .

Over rolling land.

- 2.00. Wash 15 lks wide, course S.  $70^{\circ} W$ .
- 12.00 Wash 20 lks wide, course S.  $45^{\circ} W$ .
- 40.00 Set temp  $\frac{1}{4}$  Sec. cor.
- 57.00 Wash 70 lks wide, course N  $45^{\circ} W$ .
- 56.00 Wash 100 lks wide, course N  $70^{\circ} W$ .
- 76.00 Wash 15 lks wide, course S.  $45^{\circ} W$ .
- 79.92. Intersect N & S. line at 17 lks N of the cor. to secs 2, 3, 10 & 11. Thence I run N.  $89^{\circ} 53' W$ . on a true line bet Secs 3 & 10 with same Var.
- 79.96. Set a volcanic stone 36 x 18 x 8 ins 27 ins in the ground for  $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$  on N. face, and raised

Subdivision T. 22 S. R. 11 E. Continued  
 Chams

a mound of stone  $1\frac{1}{2}$  ft <sup>high</sup>,  $3\frac{1}{2}$  ft base  
 alongside, pits impracticable.

From which

An oak 6 in. diam bears S.  $88^{\circ}$  W. 190 lks  
 dist, marked  $\frac{1}{4}$  S.B.T.

No other trees within limits

79.92 The cor to secs 3, 4, 9 & 10

Land rolling.

Soil 3<sup>d</sup> and 4<sup>th</sup> rate Good grass

Timber, scattering oak.

North on a random line bet Secs 3 & 4

Var.  $12^{\circ} 35' E$ .

Over rolling land

0.75 Wash 50 lks wide course S.  $45^{\circ}$  W.

15.00 Wash 30 lks wide course S.  $80^{\circ}$  W.

29.00 Wash 20 lks wide course S.  $50^{\circ}$  W.

40.00 Set a temp  $\frac{1}{4}$  sec. cor.



Subdivisions T. 22 S. R. 11 E. - Continued

Chains

- 80.42. Intersect N. boundary of Township at 21 lks W. of the cor to secs 3. 4. 33. & 34. previously established and described by me. Thence I run  $\S 0^{\circ}09' W.$  on a true line bet. Secs 3 & 4 with same Var.
- 40.42. Set a granite stone  $18 \times 15 \times 6$  ins  $12$  ins in the ground for  $\frac{1}{4}$  Sec cor marked  $\frac{1}{4}$  on W. face, and raised a mound of stone  $1\frac{1}{2}$  ft high and  $3\frac{1}{2}$  ft base along side, Pits impracticable.
- 80.42. The cor to secs 3. 4. 9 & 10.  
Land. rolling  
Soil 3<sup>d</sup> and 4<sup>th</sup> rate. Good grass.  
Timber, few scattering oaks.

From the cor to secs 4. 5. 32 & 33 on South boundary of Township previously

Subdivision P. 22 S. R. 4 E - Continued

established and described by me.

I run

North bet Secs 32 & 33

Var  $12^{\circ} 35' E$

Over rough rocky land.

2.00 Ascend, and line runs along SW slope  
of little rocky butte.

3.00 Summit of slope and descend.

4.00 On NW slope of little rocky butte.

Set a volcanic stone  $18 \times 10 \times 6$  ins  $12$  ins  
in the ground for  $\frac{1}{4}$  Sec. cor. marked  
 $\frac{1}{4}$  on W. face and raised a mound  
of stone alongside. Pits impracticable

From which

An oak 8 ins diam bears N.  $25^{\circ}$  W. dist.  
marked  $\frac{1}{4}$  S. K. T.

An oak 6 ins diam bears S.  $43^{\circ}$  W. 18 lbs  
dist. marked  $\frac{1}{4}$  S. K. T.

5.00 Set a volcanic stone  $18 \times 12 \times 10$  ins  $12$  ins

## Subdivisions F. 22 S. R. 11 E. continued

in the ground for cor to sec 28.29  
32833 marked with 1 notch on S  
and 4 notches on E edges and raised  
a mound of stone alongside. Pits  
unpracticable. From which

An oak 6 ins diam bears N 30° W. 40 lbs.  
dist. marked F. 22 S. R. 11 E. S. 29 B. 5.

No other trees within limits

Land, rough broken and hilly

Soil mineral

Timber scattering oak

East on a random line bet Secs 28 & 33

Var 12° 35' E.

Ascending from corner line runs  
over North slope of rocky butte.

16.00 Summit of ridge between two  
rocky buttes 600 ft high and descend

## Subdivisions T. 22 S. R. 11 E. Continued

- Chains
- 21.00 Ravine 15 deep, course  $N 30^{\circ} E$ .
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 52.00 Foot of rocky Butte wash 30 lks wide, course North.
- 66.00 Wash 30 lks wide course  $N 30^{\circ} E$  and line ascends West slope of little rocky hill.
- 72.00 Summit about 150 ft high and descend.
- 80.17 Foot and intersect N and S line 11 links N. of the cor. to secs 27. 28. 33 & 34. Thence I run  $N 89^{\circ} 55' W$  on a true line bet secs 28 & 33 with same Var.
- 40.09 Set a volcanic stone  $20 \times 18 \times 10$  ins  $15$  ins in the ground for  $\frac{1}{4}$  Sec cor marked  $\frac{1}{4}$  on N. face and raised a mound of stone alongside. Its impracticable to form which.
- An oak 8 ins. diam. bears  $N. 87^{\circ} W$  30 lks dist marked  $\frac{1}{4}$  S. B. T.



Subdivision T. 22 S. R. 11 E. Continued  
 Chain

An oak 4 ins diam. bears S. 87° E. 28 lbs  
 dist marked  $\frac{1}{4}$  S B T.

80.17. The cor to Secs 28. 29. 32 & 33

Land rough, rocky and hilly

Soil worthless.

Timber, scattering oak.

North bet. Secs 28 & 29.

Var. 12° 35' E.

Line runs along West side of rocky Butte  
 descending from cor.

18.00 Gulch 10 ft deep, course N. 75° W.

40.00 Set a Granite stone 16 x 10 x 8 ins 11 ins  
 in the ground for  $\frac{1}{4}$  Sec. cor. marked  
 $\frac{1}{4}$  on W. face and raised a mound  
 of stone  $1\frac{1}{2}$  ft high 3 $\frac{1}{2}$  ft base alongside

46.00 Foot of rocky Butte and gulch 10 ft deep  
 course N. 50° E and line runs over broken ground

## Subdivisions T. 22 S. R. 11 E. - Continued

- 57.00 Wash 15 lks wide course N. 80° E
- 66.00 Ravine 10 ft deep course East.
- 75.50 Wash 30 lks wide course N. 70° W.
- 80.00 Set a granite stone 15x12x10 ins. 10 ins  
in the ground for cor to secos 20, 21, 28 & 29  
marked with 2 notches on S and 4 notches  
on E edges, and raised a mound of  
earth 2 ft high 4½ ft base, alongside.  
From which
- An oak 12 ins. diam. bears N. 15½ W. 63 lks  
dist. marked T. 22 S. R. 11 E. S. 20 B F.
- An oak 16 ins. diam. bears N. 49° W. 87 lks  
dist. marked T. 22 S. R. 11 E. S. 20 B F.
- An oak 12 ins diam bears S. 68° W. 70 lks  
dist marked T. 22 S. R. 11 E. S. 29 B F.
- An oak 10 ins. diam bears S. 4½ W. 124 lks  
dist marked T. 22 S. R. 11 E. S. 29 B F.
- Land, rough, rocky and hilly.  
Soil, worthless. Indications of unmined

Subdivision T. 22 S. R. 11 E. - Continued  
 Chas.

along North end of line.  
 Timber, scattering oak.

East on a random line bet Secs 21 & 28.  
 Var.  $12^{\circ}35'$  'E.

- Line runs over rough hills ascending from S. to  
 32.00 Summit of hill 300 ft high and descend  
 40.00 Set temporary  $\frac{1}{4}$  Sec cor.  
 53.00 Cedar creek 1 ch wide, course North  
 and line runs up gulch coming  
 from the East  
 73.00 Leave gulch coming from the NE.  
 80.18. Intersect N & S line at 31 lks S of  
 cor to secs 21, 22, 27 & 28. Thence  
 run S.  $89^{\circ}47'$  W. on a true line  
 bet secs 28 & 33. with a true Var.  
 40.09 Set a sandstone  $18 \times 12 \times 8$  ins  $12$  ins  
 in the ground for  $\frac{1}{4}$  sec. cor. marked

Subdivisions T. 22 S. R. 11 E. Continued

chains

from N. face, and raised a mound of stone  $1\frac{1}{2}$  ft high &  $3\frac{1}{2}$  ft base along side  
to impracticable.

80.18 The cor. to secs 20, 21, 28 & 29.

Land rough rocky hills.

Soil 4<sup>th</sup> rate, indications of mineral  
West end of line.

Timber, scattering oak.

North bet secs 20 & 21.

Var.  $12^{\circ}35'E$ .

Line runs over East slope of little hill

18.00 Leave little hill and enter rolling  
broken land

40.00 Set a volcanic stone  $24 \times 12 \times 10$  ins  
18 ins in the ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on W. face, and raised  
a mound of stone along side



Subdivision T. 22 S. R. 11 E. Continued  
Chains.

Pits impracticable. From which  
An oak 10 ins. diam. bears S. 40° E 30 lks  
dist. marked  $\frac{1}{4}$  S. B. T.  
The other trees within limits.

78.00 Wash 50 lks wide course N 80° W.

50.00 Set a volcanic stone 18x12x10 ins  
12 ins in the ground for cor to sec  
16. 17. 20 & 21 marked with 3 notches  
on S. and 4 notches on E edges  
and raised a mound of stone along  
side. Pits impracticable.  
Land rough & rocky.

Soil 4<sup>th</sup> rate and worthless.

Indication of mineral South  
end of line.

Timber scattering oak.

13<sup>th</sup> Jan 1887.

Concluded, Book 930