

No. 1057

# Field Notes

OF THE SURVEY OF THE

*SUBDIVISION LINES*

-OF- BOOK 1057

Township 19N. Range 3W.*Gila and Salt River Base and Meridian***ARIZONA.** No. 1057By L. Burton Foster, D. S.under contract dated Oct. 11, 1876.Survey commenced March 30, 1877.Survey completed April 2, 1877.

1057

**PRELIMINARY OATHS OF ASSISTANTS.**

WE, Almerin S Skinkle

and Richard Shrope

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain upon uneven ground, and plumb the tally pins, whether by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability.

Almerin S Skinkle  
Richard Shrope

Sworn to and subscribed before me, this 17<sup>th</sup>  
day of March, 1877



William Chester  
Notary Public

a.

H.E. I Paul Brutschke

do solemnly swear that ~~we~~ <sup>I</sup> will well and truly perform the duties of Axeman

according to instructions given ~~us~~ <sup>me</sup>, and to the best of ~~our~~ <sup>my</sup> skill and ability.

Paul Brutschke

Sworn to and subscribed before me this 19<sup>th</sup> day of March 1877

William C. Foster  
Notary Public



106

7  
7

BOOK 1057

Fractional

Township 19. North R. 3 West.

Gila and Salt River Meridian.

6	<del>21</del>	5		4		3		2		1
7	21	8		9		10		11		12
18	20	19		16		15		14		13
18	18	17	11	16		15		14		13
19	18	17	11							
19	16	20	10	21	6	22		23		24
16	16	15	9	6						
30	14	29	9	28	5	27	3	26		25
13	13	13	8	4				2		
31	12	32	7	33	3	34	1	35	1	36



X.  
Field Notes

of the No. 1057

Subdivision lines  
of  
Fractional Township 19 North  
Range 8 West

Gila Salt River Meridian  
Territory of Arizona

Surveyed by  
Chas. B. Foster  
US Dep Surveyor

Under Contract of October 11<sup>th</sup> 1876

Survey commenced March 30<sup>th</sup> 1877  
" completed April 2<sup>nd</sup> 1877

Fractional Twp. 19. N. Range 3. W.  
Gila and Salt River Meridian

From the Cor to Secs 35<sup>th</sup> and 36. 1<sup>st</sup> and 2<sup>nd</sup> on the  
S. boundary of the Twp. Iron  
North between Secs 35<sup>th</sup> and 36.  
wa 140 38' East.

as per Dunks Improved Solar Compass.

40.00 Set a post marked 448. 4 ft long. flattened  
3 in wide. 1 ft in the ground. deposit stone marked  
x and build mound of earth 2 ft high. with pipe  
2 x 1 x 1 ft for 1/4 sec. Cor. No trees near

41.10 Road bears N E. and S W.

80.00 Set a volcanic stone 16 x 10 x 4 in properly notched  
set 7/8 in the ground. and on 7/8 in build mound of stone  
2 ft high for Cor to Secs 35. 36. 35<sup>th</sup> and 36. No trees near  
Land sloping S W. Soil 2<sup>nd</sup> rate. Timber Somb cedar.  
The Land N. of this Cor. coming under the head  
of waste and useless land. I extend this line no farther

---

North between Secs 34<sup>th</sup> and 35  
wa 140 38' East

40.00 Set a post marked 448. 4 ft long. flattened 3 in

Fractional Twp. 19. N. Range 3. W.  
 Gila and Salt River Meridian

- 0000 Set a limestone 16. X 10 X 10 ins. Properly notched, set  $\frac{2}{3}$  in the ground, and on N side build mound of stone 2 ft high for cor. to sees 26 27 34 and 35. No trees near. Land mostly level. Soil 1st and 2d rate timber, scattering. Semib cedar.
- East on random line between sees 26 and 35.  
 Va 14038' East
- 29.00 Gulch 74 lks wide flows S.
- 40.00 Set a stone for temporary  $\frac{1}{4}$  sec Cor
- 57.50 Gulch 30 lks wide. flows SW.
- 80.78 Intersect N. and S. line 74 lks N. of Cor to sees 25 26 35 and 36. From which Cor. run N. 89° 30' W. on true line between sees 26 and 35.  
 Va 14038' East
- 40.11 Set a volcanic stone 14 X 12 X 12 ins. marked  $\frac{1}{4}$ . set  $\frac{2}{3}$  in the ground, and build of stone 2 ft high for  $\frac{1}{4}$ .



Fractenal Tp. 19. N. Range 3 W.

Gila and Salt River Meridian  
Chs

Sec 27 No trees near

So. W The lot to Secs 26, 27, 34, and 35.

Land rolling and sloping SW. Soil 2<sup>d</sup> and 3<sup>d</sup> rate  
Timber Sembedat.

North between Secs 26 and 27

or 110° 38' East

40.00 Set a limestone 16 x 10 x 6 ins marked 1/4" set  
2/3 in the ground, and build mound of stone 2 ft  
high for 1/4 sec. lot. No trees near.

80.00 Set a limestone 14 x 10 x 10 ins properly notched set  
2/3 in the ground, and on N side build mound of stone  
2 ft high for lot to Secs. 22, 23, 26 and 27. No trees near  
Land rolling and sloping SW. Soil 1<sup>st</sup> 2<sup>d</sup> and 3<sup>d</sup> rate,  
Timber Sembedat

The land N. of this lot coming under the head  
of waste and useless land. Beyond this line no  
further North

North between Secs 33 and 34



Fractional Twp. 19. N. Range 3 W.  
Gila and Salt River Meridian  
Chs

Va 14038' East

40.00 Set a limestone 18x14x8 ins marked 1/4 set 3/4 in the  
ground and build mound of earth 2 ft high with  
pits 2x1 ft. for 1/4 sec cor. from which  
A Cedar 10 in dia bears N. 21° E. 112 lks dist.  
No other tree near

63.50 Wood road. bears NNE. and SSW.

80.00 Set a post marked and notched. 4 ft long 3 ins  
square, 1 ft in the ground. deposit stone marked  
and build mound of earth 2 ft high with pits 2x1  
x1 ft. for cor to secs 27. 28. 33<sup>rd</sup> & 34. No trees near  
Land level, Soil 1st and 2d rate  
Timber Scattering Cedars.

Cast on random line between secs 27<sup>th</sup> & 34<sup>th</sup>  
Va 14038' East

13.90 Wood road bears NE. and SW.

40.00 Set a post for temporary 1/4 sec cor

80.70 Intersect N. and S. line 26 lks N. of cor. to  
secs 26. 27. 34<sup>th</sup> & 35. from which cor. run

Fractional Twp. 19. N. Range 3. W.

Gila and Salt River Meridian

Ch<sup>o</sup> N. 89° 49' W. on town line between Secs 27<sup>th</sup> & 34<sup>th</sup>  
Va 140° 38' East

40.10 Set a post marked 1/4 sec 1/4 along flat mul 3 ins wide  
1 ft in the ground. deposit stone marked + and build  
mound of earth 2 ft high, with pits 2 x 1 x 1 ft. for 1/4  
sec cor. No trees near

80.20 The Cor to Secs 27, 28, 33 and 34.  
Land gently rolling Soil 2d rate  
Timber scattering Cedars

North between Secs 27<sup>th</sup> and 28<sup>th</sup>  
Va 140° 38' East.

40.00 Set a limestone 16 x 8 x 6 ins marked 1/4 sec 1/4 in  
the ground, and build mound of stone 2 ft  
high for 1/4 sec cor. No trees near

57.00 Gulch 60 lks wide flows SW.

80.00 Set a limestone 16 x 10 x 10 ins properly notched, set 1/4 sec  
the ground, and on N. side build Mound of stone 2 ft  
high for cor to Secs 27, 27<sup>th</sup>, and 28<sup>th</sup>. No trees near  
Land rolling and sloping SW. Soil 1, 2, 3<sup>rd</sup> rate



Fractional Twp. 19. N. Range 3. W.  
Gila and Salt River Meridian

Timber scattering clear.

East on random line, between Secs 22, 23, 26, and 27.  
Twp 140 38' East

40.00 Set a post for temporary 1/4 sec Cor.  
80.08 Intersect N. & S. line 12 1/2 N. of Cor. to Secs  
22, 23, 26, and 27. From which Cor. Iron  
N. 89° 55' W. on true line between Secs 22, 23, 26, and 27  
Twp 140 38' East

40.04 Set a post marked 1/4 S. 4 ft long flattened 3 in with  
1 ft in the ground, and build mound of earth 2 ft high  
with 2x1x1 ft. for 1/4 sec Cor. No true near  
80.08 The Cor. to Secs 21, 22, 27, and 28.  
Land rolling and sloping SW. Soil good 3<sup>rd</sup> rate  
Timber scrub clear.

North between Secs 21 and 27  
Twp 140 38' East

40.00 Set a post marked 1/4 S. 4 ft long flattened 3 in with 1 ft  
in the ground. deposit stone marked 1<sup>st</sup> and build mound of earth



7  
 Fractional Twp. 19. N. Range 3. W.  
 Gila and Salt River Meridian

- cho
- 68.00 2 ft high with pits 2X1 ft. for 1/4 sec lot. No trees near  
 Begins ascent to high Mtn. slope bears NW. & SE.
- 73.00 Gulch 100 yds wide flows SW.
- 80.00 Set a volcanic stone 18X12X12 ins properly notched at  
 3/4 in the ground. 2 on N side build mound of stone 7  
 ft high for Cor to Sec 15 16. 21. 22. No trees near  
 Land sloping SW. Soil 2d and 3d rate  
 Timber scrub cedar  
 On account of the worthless character of the  
 soil N. of this Cor. I extend this line as follows:  
 North

March 30. 1877.

North between Secs 32 and 33  
 on 140 38' East.

- 40.00 Remote from stone or timber, drive chaul stake 12  
 ins down, and build mound of earth 7 ft high with  
 pits 2X1 ft for 1/4 sec lot. No trees near
- 47.10 Wash 50 yds wide flows SE.
- 47.30 Road bears W. and SE.
- 80.00 Set a limestone 18X14X12 ins properly notched, set

Fractional T<sub>19</sub> N. Range 3 W  
Gila and Salt River Meridian

cho

$\frac{3}{4}$  in the ground. and on N side build mound of straw  
2 ft high. for corner Secs 28<sup>th</sup> 29<sup>th</sup> 32<sup>nd</sup> 33. No trees near  
Land level. Soil 1<sup>st</sup> rate  
No timber or undergrowth

East on random line between Secs 28<sup>th</sup> 33.

Or 140.38' East

40.00

Set a stone for temporary  $\frac{1}{4}$  sec cor

48.00

Gulch 75 lks wide flows SSW.

79.94

Intersect N. <sup>2nd</sup> of line. 10 lks S. of corner Secs.

27.28. 33<sup>rd</sup> 34 from which cor Iron

S. 89° 56' W. on true line between Secs 28<sup>th</sup> 33.

Or 140.38' East

39.97

Set a limestone 14x10x4 in marked  $\frac{1}{4}$  sec  $\frac{2}{3}$  in the  
ground. and build mound of earth 2 ft high

with pile 2x1x1 ft for  $\frac{1}{4}$  sec cor. No trees near

79.94

The cor to Secs 28. 29. 32<sup>nd</sup> 33.

Land mostly level. Soil 1<sup>st</sup> and 2<sup>d</sup> rate

Timber scrub cedars.



Fractional T<sup>h</sup> 19<sup>th</sup> Range 3. W.  
Tila and Salt River Meridian

- Chs
- North between Secs 28<sup>th</sup> and 29.  
No 140 38' East
- 40.00 Set a post marked 1/4 ch 4 ft long. Flattened 3 in wide  
1 ft in the ground. deposit stone marked + and build  
mound of earth 2 ft high with pits 2 x 1 ft. for  
1/4 sec cor. from which  
a cedar 6 in dia. bears N 51° E. 118 cks dist.  
No other trees near
- 80.00 Set a post marked 1/4 notch 4 ft long 3 in square 1 ft  
in the ground. deposit stone marked + and build mound  
of earth 2 ft high with pits 2 x 1 ft. for cor to Secs  
20, 21, 28<sup>th</sup> and 29. No trees near.  
Land mostly level. Soil 1<sup>st</sup> and 2<sup>d</sup> rate  
Timber Scattering Cedars.
- East on random line between Secs 21<sup>st</sup> and 28<sup>th</sup>.  
No 140 38' East.
- 40.00 Set a stone for temporary 1/4 sec cor
- 80.00 Intersect N. of S. line at cor to Secs. 21, 22,  
27<sup>th</sup> and 28. from which Cor. I run



Fractional T<sup>197</sup> Range 3<sup>W</sup>,  
T<sup>197</sup> and Salt River Meridian

Chs

West on line between Secs 21<sup>and</sup> 28  
T<sup>197</sup> 38' East

40.00 Set a volcanic stone 6x16x6 ins. marked 1/4 set 2/3  
in the ground and build mound of stone 2 ft high for  
1/4 sec lot. No trees near

80.00

The Cor to Secs 20, 21, 28, and 29.  
Land rolling and sloping SW. Soil 2<sup>nd</sup> and 3<sup>rd</sup> rate  
Timber Samba cedar.

North between Secs 20<sup>and</sup> 21  
T<sup>197</sup> 38' East.

40.00 Set a limestone 14x10x5 ins. marked 1/4 set 2/3 in the  
ground, and build mound of stone 2 ft high for  
1/4 sec lot. No trees near.

80.00

Set a post marked and notched 4 ft long 3 ins.  
square, 1 ft in the ground deposit stone marked +  
and build mound of earth 2 ft high with pits 2x1x1  
ft for Cor to Secs 16, 17, 20<sup>and</sup> 21. No trees near.  
Land gently rolling. Soil 1<sup>st</sup> and 2<sup>nd</sup> rate  
Timber scattering cedars.

Fractional T. 19 N. Range 3 W.  
 Gila Salt River Meridian

80 East random line between Secs 16<sup>th</sup> & 21  
 Va 140° 38' East

40.00 Set a stone for temporary 1/4 sec Cor

67.00 Begin ascent to Mtn. slope bears NW<sup>th</sup> & S.E.

80.16 Set a net N. <sup>th</sup> & S. line 1/4 sec N. of Cor. to Secs  
 15, 16, 21<sup>st</sup> & 21. From which Cor. I run  
 71.89° 55' W. on true line between Secs 16<sup>th</sup> & 21.  
 Va 140° 38' East.

40.08 Set a volcanic stone 19x12x4 ins marked 1/4 sec 2/3 in  
 the ground. <sup>nd</sup> build mound of stone 2 ft high. for  
 1/4 sec Cor. No trees near

80.16 The Cor to Secs 16, 17, 20<sup>th</sup> & 21.  
 Land rolling <sup>nd</sup> sloping SW. Soil & sh<sup>al</sup> & 3<sup>rd</sup> rate  
 timber scattering some Cedars

North between Secs 16<sup>th</sup> & 17.  
 Va 140° 38' East.

40.00 Set a post marked 1/4 S. 4 ft long. flattened 3 ins  
 wide 1/2 in the ground. deposit stone marked + <sup>and</sup>  
 build mound of earth 1 ft high with pipe 2x1 1/2 ft for 1/4 sec Cor. No trees near



Fractional T<sup>19</sup>. N. Range 3 W  
Gila and Salt River Meridian.

chs

77.00 Begin ascent of bluff of Black Mesa, bears N.W. & S.E.  
80.00 Set a volcanic stone 18x16x10 ins properly notched each  
2/4 in the ground, and on N. side build mound of stone 2 ft  
high for Cor. to Secs 8, 9, 16 & 17. No trees near  
Land rolling and sloping W. Soil 2d & 3d rate  
Timber scattering red oak. The land 1/2 of this  
Cor. being worthless. Extend this line no further North.

North between Secs 31. and 32.  
Va 14038 East.

10.70 Walnut creek wash 40 lks wide flows E  
40.00 Set a granite stone 12x10x6 ins marked 14. set 1/3  
in the ground and build mound of earth 2 ft high, with  
pits 2x1x1 ft for 1/4 sec of. No trees near  
49.40 Road bears E. and W.  
80.00 Remote from stone or timber. Drive charred stake 12 ins  
down, and build mound of earth 2 ft high with pits 2  
x1x1 ft, and in center of pit S.E. of Cor drive stake marked  
& notched 2 ft long 7 ins square, 1 ft in the ground, for Cor  
to Secs 29, 30, 31. and 32. No trees near  
Land level and gently rolling. Soil 1st & 2d rate



Fractional T. 19. N. Range 3 W  
Gila and Salt River Meridian

No timber or undergrowth.

East on random line between Secs 29<sup>nd</sup> & 31<sup>st</sup>  
Va 110° 38' East

7.90 Wash 40 lks wide flows S E.  
40.00 Set a stone for temporary 1/4 Sec Cor.  
80.00 Intersect N. W. S. line 16 lks N of Cor to Secs  
28, 29, 31, & 32. From which Cor. I run  
N. 89° 53' W. on town line between Secs 29<sup>nd</sup> & 31<sup>st</sup>.  
Va 110° 38' East.

40.10 Set a limestone 12x12x12 ins marked 1/4 at 1/2 in  
the ground. and build a mound of earth 2 ft high, with  
pile 2x12x12 ft. for 1/4 Sec Cor. No trees near.

80.00 The Cor to Secs 29, 30, 31, & 32.  
Lowest level, soil 1<sup>st</sup> rate  
No timber or undergrowth

West on random line, between Secs 30<sup>th</sup> & 31<sup>st</sup>  
Va 110° 38' East.

40.00 Set a stake for temporary 1/4 Sec Cor.

Fractional T<sup>19</sup> N. Range 3 W.  
 1<sup>st</sup> 2<sup>nd</sup> Salt River Meridian

- chs  
 79.05 Intersect W. boundary of T<sup>19</sup>: 16 lks. S. of Cor. to  
 Secs 30. <sup>4</sup> & 31. from which Cor. I run  
 S. 89° 53' E. on true line. between Secs 30. <sup>4</sup> & 31.  
 Va 140 38' East.
- 39.05 Remote from stone or timber. drive charred stake  
 18 ins down. and build mound of earth 2 ft high  
 with pike 2x1x1 ft. for 1/4 sec lot. No trees near.
- 79.05 The Cor to Secs 29, 30, 31. <sup>4</sup> & 32.  
 Land level soil 1<sup>st</sup> rate.  
 No timber or undergrowth

North between Secs 29 <sup>4</sup> & 30  
 Va 140 38' East

- 19.25 Wash 40. lks wide flows S E.
- 40.00 Remote from stone or timber. drive charred stake  
 18 ins down. and build mound of earth 2 ft high  
 with pike 2x1x1 ft. for 1/4 sec lot. No trees near.
- 80.00 Remote from stone or timber. drive charred stake  
 18 ins down. build mound of earth 2 ft high with  
 pike 2x1x1 ft. and in center of pit S E. of Cor. drive



Fractional T<sup>19</sup>.N. Range 3.W.  
Cila and Salt River Meridian

Chs

stake marked and notched. 2 ft long. 2 ins square.  
1 ft in the ground. For Cor. to Secs 19. 20. 29. and 30.

No trees near.

Land level. Soil 1<sup>st</sup> rate

No timber or undergrowth

March 31. 1877

Caution random line between Secs 20<sup>th</sup> & 29<sup>th</sup>  
Va 14038' East.

40.00 Set a stone for temporary 1/4 sec Cor.

80.00 Intersect N. & S. line 10 kts. S. of Cor. to Secs  
20. 21. 28. and 29. from which Cor. is run  
S. 89° 56' W. on true line. between Secs 20. and 29.

Va 14038' East.

40.00 Set a limestone 16 x 12 x 4 ins. marked 1/4. set 1/3 in the  
ground, and build mound of earth 2 ft high, with  
pile 2 x 1 ft. for 1/4 sec Cor. No trees near

80.00 The Cor. to Secs 19. 20. 29. and 30.

Land gently rolling. Soil 1<sup>st</sup> rate

No timber or undergrowth



Fractional T<sub>19</sub> N. Range 3 W.  
Gila and Salt River Meridian

chs

Weston random line between Secs 19<sup>th</sup> & 20.  
Va 140 38' East.

40.00 Set a stake for temporary 1/4 sec Cor.  
49.20 Indirect W. boundary of Op. 10 W. S. of Cor to  
Secs 19<sup>th</sup> & 20. From which Cor Iron  
S. 89° 56' E. on town line  
between Secs 19<sup>th</sup> & 20.

Va 140 38' East

39.20 Remote from stone or timber. drive charred stake  
12 ins down. 2<sup>nd</sup> build mound of earth 2 ft high, with  
pits 2 x 1 x 1 ft for 1/4 sec Cor No trees near

47.20 The cor to Secs 19, 20, 29<sup>th</sup> & 30.  
Land level soil 1<sup>st</sup> rate.  
No timber or undergrowth

North between Secs. 19<sup>th</sup> & 20

Va 140 38' East

40.00 Remote from stone or timber. drive charred stake  
12 ins down and build mound of earth 2 ft high  
with pits 2 x 1 x 1 ft. for 1/4 sec Cor No trees near

Fractional T<sub>19</sub> N. Range 3 W.  
Gila and Salt River Meridian.

Chs.  
80.00 Remote from shore on timber drive charred stake  
17 in down. build mound of earth 2 ft high, with pits  
2x1 ft. 4 in center of pit SE. of cor. drive stake marked  
and notched. 2 ft long. 2 in square. 1 ft in the ground for  
cor to Secs 17, 18, 19, and 20. No trees near  
Land slopes S. Soil 1st and 2d rate.  
No timber or undergrowth.

East on random line between Secs 17 and 20.  
Va 140 38' East.

40.00 Set a post for temporary 1/4 sec cor  
80.12 Intersect 7<sup>th</sup> line at cor to Secs 16, 17, 20 and  
21. From which cor Iron.  
West on true line between Secs 17 and 20.  
Va 140 38' East.

40.06 Set a post, marked 1/4 S. 4 ft long. 3/4 in  
wide 1 ft in the ground. deposit stone marked X and  
build mound of earth 2 ft high, with pits 2x1  
x 1 ft for 1/4 sec cor. No trees near  
80.12 The cor to Secs 17, 18, 19, and 20.

Fractional T. 19. N. Range 3. W.  
 Tila and Salt River Meridian

also

Land slopes W. Soil 1<sup>st</sup> and 2<sup>d</sup> rate  
 Timber, a few Cedars, on E. end of line.

West on random line between Secs. 18<sup>th</sup> and 19<sup>th</sup>,  
 Va 140° 38' East.

40.00 Set a stake for temporary 1/4 sec Cor

79.10 Intersect W. boundary of T. 19. N. Range 3. W. Sec.  
 to Secs 18<sup>th</sup> and 19<sup>th</sup>. From which Cor Iron  
 71.89° 57' E. on true line between Secs 18<sup>th</sup> and 19<sup>th</sup>  
 Va 140° 38' East.

39.10 Remove from stone or timber, drive charred stake  
 12 in down, and build mound of earth 2 ft high  
 with pits 2 x 1 x 1 ft. for 1/4 sec Cor No trees near.

79.10 The Cor to Secs 17, 18, 19, and 20.  
 Land gently rolling. Soil 1<sup>st</sup> and 2<sup>d</sup> rate  
 No timber or undergrowth

North between Secs 17<sup>th</sup> and 18<sup>th</sup>.  
 Va 140° 38' East.

40.00 Set a post marked 1/4 S. 4 ft long. flattened 3 in wide



Fractional T. 19. N. Range 3. W.  
Gila and Salt River Meridian  
cho

1 ft in the ground. deposit stone marked + and build mound of earth 2 ft high, with pits 2 x 1 x 1 ft. for 1/4 Sec Cor. No house near

80.00 Set a post marked and notched. 4 ft long 3 ins squared 1 ft in the ground. deposit stone marked + and build mound of earth 2 ft high with pits 2 x 1 x 1 ft. for Cor to Secs 7, 8, 17, and 18. No house near  
Land rolling and sloping. Soil 2nd rate  
Timber, a few Cedars in N. part of Sec 17

East on random line between Secs 8<sup>th</sup> and 17.  
N. 71° 40' 38" East.

40.00 Set a post for temporary 1/4 sec Cor  
78.00 Begin ascent of bluff. bears S. E. and N. W.  
79.90 Intersect N. and S. line 44 kts. S. of Cor to Secs 8, 9, 16 and 17. From which Cor down  
S. 89° 54' W. on true line between Secs 8<sup>th</sup> and 17.  
N. 71° 40' 38" East.

39.95 Set a post marked 1/4 S. 4 ft long flattened 3 ins wide. 1 ft in the ground. deposit stone marked +

Fractional T. 19. N. Range 3. W.  
Gila and Salt River Meridian

che

and build mound of earth 2ft high with pits  
2x1x1ft. for 1/4 sec cor. No true mar.

79.90

The cor to Secs 7, 8, 17 and 18.  
Land rolling and sloping SW. Soil 2d rate  
Timber a few Cedars.

West on random line between Secs 7 and 18.  
Va 140 38' East.

40.00

Set a line for temporary 1/4 sec cor

79.22

Intersect W. boundary of Sp 12 lks S. of  
Cor to Secs 7 and 18. From which cor from  
S. 89° 55' E. on true line between Secs 7 and 18.  
Va 140 38' East

39.22

Set a limestone 10x8x8 ins, marked 1/4, set 1/2 in  
the ground and build mound of earth 2ft high  
with pits 2x1x1ft. for 1/4 sec cor. No true mar

79.22

The cor to Secs 7, 8, 17 and 18.  
Land rolling. Soil 2d rate  
No timber or under growth

Fractional T. 19 N. Range 3, W.  
Gila and Salt River Meridian

do

North between Secs 7<sup>th</sup> and 8<sup>th</sup>.  
wa 140° 38' East.

40.00 Set a limestone 12x12x11 ins, marked 1/4, set 2/3  
in the ground. and build mound of stone 2 ft  
high for 1/4 sec cor. No trees near

80.00 Set a post marked and notched, 4 ft long 3 ins  
square, 1 ft in the ground, deposit stone marked X  
and build mound of earth 2 ft high with pits  
2x1x1 ft. for cor to Secs 5, 6, 7, and 8. No trees near.  
Land rolling. Soil 3d rate.  
Timber. a few Cedars

West on random line between Secs 6<sup>th</sup> and 7<sup>th</sup>  
wa 140° 38' East.

40.00 Set a stone for temporary 1/4 sec cor

49.75 Gulch 50 lks wide, flows S.

79.30 Set a post at W. boundary of Sp 19 lks N of  
Cor. to Secs. 6<sup>th</sup> and 7<sup>th</sup>. from which Cor. Iron  
N. 89° 52' E. on true line between Secs 6<sup>th</sup> and 7<sup>th</sup>.  
wa 140° 38' East.



Fractional T. 19. N. Range 3. W.  
Gila and Salt River Meridian

- 39.30 Set a limestone 12x10x5 ins. marked  $\frac{1}{4}$  set  $\frac{2}{3}$  in the ground, and build mound of stone 2 ft high for  $\frac{1}{4}$  sec cot. No trees near.
- 79.30 The Co to Sec 5, 6, 7<sup>th</sup> and 8.  
Land rolling and sloping W. Soil 2<sup>d</sup> and 3<sup>d</sup> rate  
Timber, an occasional cedar.  
April 2<sup>d</sup> 1877

General Description.

The surveyed portion of this Township covers some good arable and grazing lands.

The Township contains considerable cedar of a stunted growth, suitable only to be used for fuel.

The unsurveyed portion of the Township is covered mostly by the "Black Mesa" and comes under the head of waste and useless lands.

L. P. Burton Foster  
U.S. Depy. Surveyor.

## List of Names.

A List of the Names of Individuals employed  
to assist in running, measuring, or marking the  
lines and corners described in the foregoing Field  
Notes of the survey of *the Outdission lands*  
*of Fractional Township 9 North*  
*Range 3 West*  
*Gila and Salt River Meridian*  
*Arizona Territory*

Showing the respective capacities in which they  
acted.

*Almerind Shultz* Chainman.

*Richard Shroppe* Chainman,

*Paul Routschke* Axeman.

Flagman.



24

Final Oath of Assistants.

We hereby certify that we assisted C. Burton  
Foster U. S. Deputy Surveyor, in  
 surveying the out-dimension lands of  
Fractional Township 19 North Range  
3 West  
Gila and Salt River Meridian  
Arizona Territory

and that said Survey has been in all respects, to  
 the best of our knowledge and belief, well and  
 faithfully executed, and the boundary monuments  
 planted according to the instructions furnished by  
 the Surveyor-General.

Amerin S. Skinkle Chainman.  
Richard Shrope Chainman,  
Paul Bruster Axeman.  
 \_\_\_\_\_ Flagman.

William C. Foster

Sworn to and subscribed before me, this 31<sup>st</sup>  
 day of May, 1877

William C. Foster  
 Notary Public





## Final Oath of Deputy Surveyor.

I, *C. Burton Austin*

U. S. Deputy Surveyor, do solemnly swear that  
in pursuance of a contract with John Wasson,  
United States Surveyor-General for Arizona, bear-  
ing date the *11<sup>th</sup>* day of *October*

187*6*. I have well, faithfully and truly, in my  
own proper person, and in strict conformity with  
the instructions furnished by the Surveyor-Gener-  
al, the Surveying Manual, and the laws of the  
United States, surveyed all those portions of *the*

*subdivision lines of Fractional*  
*Township 19 North Range 3 West*  
*Secs 4 & 5 Salt River Meridian*  
*Arizona Territory*

as are repre-  
sented in the foregoing Field Notes as having  
been surveyed under my directions; and I do  
further solemnly swear that all the corners of  
said surveys have been established and perpet-  
uated in strict accordance with the Surveying  
Manual and printed instructions, and also in ac-  
cordance with the additional requirements con-

26

tained in circular instructions from the U. S. Surveyor-General for Arizona, dated September 1, 1873, regarding the establishment of corner boundaries of public surveys, and that the foregoing are the true and original Field Notes of such surveys.

*C. Ruston Foster*  
Deputy Surveyor.

Sworn to and subscribed before me, this 31<sup>st</sup>  
day of May....., 1877.

*William Chatter*  
Notary Public



U. S. Surveyor General's Office,

TUCSON ARIZONA, December 27, 1876.

The foregoing Field Notes of the Survey of the

Subdivision Lines of  
Township 19 North,  
Range 3 West.

Of the Gila and Salt River Base and Meridian, Arizona, executed by

L. Benton Foster,

Deputy Surveyor, under his contract of the

11<sup>th</sup>/<sub>11</sub>

day of October, 1876, having been

critically examined and the necessary corrections and explanations made, the said Field Notes and the surveys they describe are hereby approved.

John Masson.  
Surveyor General.