

Recd April 10 1892 1  
No. 1216 16 Books 1  
Sent  
Com. G.L.O.  
May 27 1892  
Platted, x<sup>d</sup>  
BOOK 1216

1216 Survey approved  
August 4-671 31 1892

No. 1216 **FIELD NOTES** BOOK 1216  
*of the*  
~~GENERAL LAND OFFICE.~~

*Subdivisions*  
T6, S. R 5W. No. 1216  
By Daniel Drummond U.S. D.S.

UNDER CONTRACT N<sup>o</sup> 19.  
Dated June 13, 1891.  
SUR. Tp. Commenced Oct 22/91.  
SUR. Tp. Completed Oct 30./91.

BOOK 1216

1A

(4-674.)

Township 6 S. R. 5 W

6	5	4	3	43	2	22	1
				62		41	20
7	8	9	60	10	39	11	18
				59		37	16
18	17	16	57	15	35	14	13
				55		33	12
19	20	21	53	22	31	23	10
				51		29	8
30	29	28	49	27	28	26	6
				47		26	4
31	32	33	45	34	24	35	1
							36

## Subdivisions T. 6. S. R. 5. W.

chains. Survey Commenced Oct. 22. 1891. with a W<sup>and</sup> L. E. Gurley light Mountain's transit. Heretofore described I set the Instrument over the Cor. to Secs. 1<sup>and</sup> 2, 35<sup>and</sup> 36 Tps. 6<sup>and</sup> 7. S. R. 5. W. and direct the transit on the established South boundary of the township viz.  $N 89^{\circ} 41' E$  and find the variation to be  $13^{\circ} 4'$  East. and at 7.30 am, this morning, I take a solar observation, and find the variation to be identically the same viz.  $13^{\circ} 4'$  East.



## Subdivisions T.6.S. R.5.W.

chs. Thence I run  
 $N 0^{\circ} 1' W$  on a true line  
 bet. Secs. 35 and 36.

Var.  $13^{\circ} 4' E$ ,

40.00 Set a granite Stone  $24 \times 10$   
 $\times 5$  ins. 18 ins. in the ground  
 for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$   
 on W face. dug pits  
 $18 \times 18 \times 12$  ins. N.W.S. of Stone  
 $5\frac{1}{2}$  ft. dist. and raised  
 a mound of earth  $1\frac{1}{2}$  ft.  
 high  $3\frac{1}{2}$  ft. base, alongside

50.10 Mark 10 lks. wide Course N.W.

80.00 Set a granite Stone  
 $16 \times 10 \times 4$  ins. 12 ins. in  
 the ground. for Cor. to Secs.  
 25, 26, 35 and 36. marked  
 with 1 notch on S and E.  
 edges dug pits  $18 \times 18 \times 12$   
 ins. in each Sec.  $5\frac{1}{2}$  ft.

## Subdivisions I.G.S. R.S.W.

chs. dist. and raised a mound  
of earth, 2 ft. high.  $4\frac{1}{2}$   
ft. base. alongside

Land level.

Soil sandy loam 1<sup>st</sup> rate  
Timber. Scattering mesquite

## Subdivisions T. 6. S. R. 5. W.

Chains Thence I run  $N 89^{\circ} 41' E$  on  
 a <sup>randomly line</sup> parallel to S. bdy of township,  
 bet. Secs 25 and 36

Var.  $13^{\circ} 4' E$

40.00 Set temporary  $\frac{1}{4}$  Sec. Cor.

80.04 Intersect east bdy of T<sub>6</sub> at  
 Cor. to Secs. 25, 30, 31 and 36,

as heretofore described

From Thence I run

$S 89^{\circ} 41' W$  on a true line  
 bet. Secs. 25, and 36,

Var.  $13^{\circ} 4' E$

34.10 Wash 15 lks wide Course N.W.

40.02 Set a granite Stone  $15 \times 10 \times 6$   
 ins. 11 ins. in the ground, for  
 $\frac{1}{4}$  Sec. Cor. Marked  $\frac{1}{4}$  on N face  
 dug pits  $18 \times 18 \times 12$  ins. E & W,  
 of Stone  $5 \frac{1}{2}$  ft. dist. and  
 raised a mound of earth  
 $1 \frac{1}{2}$  ft high.  $3 \frac{1}{2}$  ft. base

## Subdivisions T. 6. S. R. 5. W.

Chains alongside.

42.80 Wash 50 lks. wide Course N. W.

80.04 The Cor. to Secs. 25, 26, 35, &amp; 36.

Land level

Soil. Sandy loam 1<sup>st</sup> rate

Timber Palo Verde &amp; Mesquite.



## Subdivisions T.6.S. R.5.W.

Chains Thence I run

N  $0^{\circ} 1' W$ . on a true line

bet. Secs. 25 and 26

Var.  $13^{\circ} 4' E$ 

40.00 Set a post, 4 ft. long, 4 ins. square, with marked stone 12 ins. in the ground, for  $\frac{1}{4}$  sec. Cor. marked  $\frac{1}{4}$  S. on W. face. dug pits, 18 x 18 x 12 ins. N and S of post,  $5\frac{1}{2}$  ft. dist. and raised a mound of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base. Around post.

60.00 Wash, 110 lks wide Course N.W.

80.00 Set a post,  $4\frac{1}{2}$  ft long, 4 ins. square, with marked stone 12 ins. in the ground for Cor. to Secs. 23, 24, 25 + 26  
Marked -

Sub. S. Sec. 24 on N.E.



## Subdivisions I. 6. S. R. 5. W.

Chs. R. 5. W. Sec. 25 on S. E.  
 Sec. 26 on S. W. and  
 Sec. 23 on N. W. faces. with  
 1 notch on E and 2 notches  
 on S edges. dug pits  
 18x18x12 ins. in each  
 Sec. 5 1/2 ft. dist. and  
 raised a mound of earth  
 2 ft high 4 1/2 ft. base  
 around post.

Land level.

Soil Sandy loam 1<sup>st</sup> rate  
 Simbar Palo Verde and Mesquite

## Subdivisions T. 6. S. R. 5. W.

Chains N  $89^{\circ}41'E$  on a random  
line bet. Secs. 24 and 25.

Var.  $13^{\circ}4'E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.

79.96 Intersect E. bdy of township,  
12 links north of Cor. to Secs.  
19, 24, 25 and 30, as herein-  
before described

Thence I run

S  $89^{\circ}46'W$  on a true line  
bet. Secs. 24 and 25.

Var.  $13^{\circ}4'E$

39.98 Set a granite stone  $15 \times 8 \times 6$   
ins. 10 ins. in the ground,

for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$   
on N. face dug pits  $18 \times 18$

$\times 12$  ins E. & W. of stone <sup>5  $\frac{1}{2}$  ft. dist</sup> and  
raised a mound of earth  
 $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft. base,  
alongside.

9

BOOK 1216

Subdivisions T. 6. S. R. 5. W.

chs.

79.96 The Cor. to Secs. 23, 24, 25, and 26.

Land level.

Soil. Sandy loam 1<sup>st</sup> rate

Timber Palo Verde & Mesquite

## Subdivisions T. 6. S. R. 5. W.

Chains  $N 0^{\circ} 1' W$  bet. Secs. 23 and 24.  
Var.  $13^{\circ} 4' E$

40.00 Set a post. 4 ft long. 4 ins. square. with marked stone 12 ins. in the ground for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  S. on W face. dug pits 18x18. x 12 ins N and S. of post.  $5\frac{1}{2}$  ft. dist. and raised a mound of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft. base. around post.

80.00 Set a post.  $4\frac{1}{2}$  ft. long. 4 ins. square. with marked stone 12 ins. in the ground for. Cor. to Secs. 13. 14. 23 + 24 marked.

T. 6. S. S. 13 on N.E.  
R. 5 W. S. 24. on S.E.  
Sec. 23 on S.W. and  
Sec. 14 on N.W. faces



## "Subdivisions I. 6. 1. R. 5. W.

chs. with 1 notch on E, and 3 notches  
 on S, edges, dug pits 18x18x  
 12 ins. in each sec. 5 1/2 ft.  
 dist. and raised a mound of  
 earth 2 ft high, 4 1/2 ft.  
 base, around post.

Land level.

Soil Sandy loam 1<sup>st</sup> rate  
 Timber. Palo Verde & Mesquite

## Subdivisions T. 6. S. R. 5. W.

Chains  $N 89^{\circ} 46' E$  on a random  
line, bet. Secs. 13 and 24.

Var.  $13^{\circ} 4' E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.

80.00 Intersect E. bdy of township  
12 links South of Cor. to Secs.  
13, 18, 19 and 24, as hereinbefore  
described

Thence I run

$S 89^{\circ} 41' W$  on a true line  
bet. Secs. 13 and 24.

Var.  $13^{\circ} 4' E$

40.00 Set a post. 4 ft. long. 4 ins.  
square, with marked stone  
12 ins. in the ground for  $\frac{1}{4}$   
Sec Cor. Marked  $\frac{1}{4} S$  on N. face  
dug pit:  $18 \times 18 \times 12$  ins E &  
W. of post.  $5\frac{1}{2}$  ft. dia and  
raised a mound of earth,  
 $1\frac{1}{2}$  ft high.  $3\frac{1}{2}$  ft. base

Subdivisions J. G. J. R. S. W.

Chs. Around Post.

80.00 The Cor. to Secs. 13, 14, 23 & 24.

Land level.

Soil. Sandy loam 1.4% alkali  
Timber. Palo Verde & Mesquite

# Subdivisions T6.S. Q.5.W.

chs. N 0° 1' W bet. Secs. 13 and 14.

Var. 13° 4' E

40.00 Set a Granite Stone 15 x 10 x 5  
 ins., 11 ins. in the ground  
 for 4 Sec. Cor., marked on  
 West <sup>dup. pits 18x18x12 ins N.E.S. of stone</sup> side  
 of mound of Earth 1 1/2 feet high  
 3 1/2 feet base, alongside of it.

80.00 Set a Granite stone, 20 x 10  
 x 5 ins. 15. ins. in the  
 ground, for Cor. to Secs.  
 11.12.13. & 14, marked with  
 4 watches on S. and 1  
 watch on E. edges; dup  
 pits 18 x 18 x 12 ins. in each  
 sec., 5 1/2 feet dist., and raise  
 a mound of earth 2 feet high  
 4 1/2 feet base, alongside.



## Subdivisions I. 6. S. R. 5. W.

chs.

Land level.

Sail. Sandy loam 1<sup>st</sup> rate  
Timber Palo Verde & Mesquite

## Subdivisions J. G. S. R. S. W.

chains N  $89^{\circ}41'E$  on a random  
line bet. Secs. 12 and 13.

Var.  $13^{\circ}4'E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.

79.94 Intersect E. bdy of Sp at  
Cor. to Secs. 7, 12, 13, and 18.

as heretofore described  
Thence I run

S  $89^{\circ}41'W$  on a true line  
bet. Secs. 12 and 13.

Var.  $13^{\circ}4'E$

16.10 Wash 15. lks. wide Course N.W.

39.97 Set a post, 3 ft. long, 3 ins. square  
with marked stone, 12 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{2}$  ft. on N face; dug pits 18 x 18  
x 12 ins. E and W of post,  $5\frac{1}{2}$  ft  
dist., and raised a mound of  
earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base  
around post.

Subdivisions I. G. S. R. S. W.

chains

79.20 Wash 10 lks wide Course NW.

79.94 The Cor. to Secs. 11, 12, 13 and 14

Land level.

Sail. Sandy loam 1<sup>st</sup> rate

Timber. Palo Verde & Mesquite

Oct. 22, 1891.

## Subdivisions 1, 6, 1, 2, 5, W.

Chains N  $0^{\circ} 1' W$  bet. Secs. 11 and 12  
 Var.  $13^{\circ} 4' E$

0.90 Wash 20 lks wide Course NW.

14.15 Wash 20 " " " N.E.

40.00 Set a post, 3 ft. long, 3 ins. square  
 with marked stone, 12 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked  
 $\frac{1}{4}$  § on W face; dug pits 18 x 18  
 x 12 ins. N and S of post,  $5\frac{1}{2}$  ft  
 dist., and raised a mound of  
 earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base  
 around post.

80.00 Set a Granite stone 15 x 8  
 x 5 ins. 11 ins. in the  
 ground, for Cor. to Secs.  
 1, 2, 11, & 12, marked with  
 $\uparrow$  notches on § and |  
 notch on E. edge; dug  
 pits 18 x 18 x 12 ins. in each  
 sec.,  $5\frac{1}{2}$  ft. dist., and raised  
 a mound of earth  $1\frac{1}{2}$  ft. high,  
 $3\frac{1}{2}$  ft. base around post.



## Subdivisions S. 6, S. R. 5, W.

Cham. a mound of earth 2 ft  
high.  $4\frac{1}{2}$  ft. base  
alongside

Land level

Soil. Sandy loam 1.<sup>st</sup> rate  
Timber Palo Verde & Mesquite

## Subdivisions T. 6. S. R. 5. W.

chains N  $89^{\circ}41'E$  on a random  
line bet. Secs. 1 and 12.  
Var.  $13^{\circ}4'E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.  
80.00 Intersect E. bdy of Sp. at  
Cor. to Secs. 1, 6, 7 and 12.  
as hereinbefore described  
Thence I run  
S  $89^{\circ}41'W$  on a true line  
bet. Secs. 1 and 12.  
Var.  $13^{\circ}4'E$

23.00 Wash 10 lks wide Course NW,

37.90 Wash 20 " " " "

40.00 Set a post, 3 ft. long, 3 ins. square  
with marked stone, 12 ins. in  $\odot$   
ground, for  $\frac{1}{4}$  sec. cor., mark  
 $\frac{1}{4}$   $\$$  on N face; dig pits 18 x 18  
x 12 ins. E and W of post,  $5\frac{1}{2}$  ft  
dist., and raised a mound:  
earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base  
around post.

Subdivisions T. 6 S. R. 5 W.

cho.  
78.30 Wash 15 lks. wide Course NW.  
80.00 The Cor. to Secs. 1, 2, 11 and 12

Land level  
Soil. Sandy loam 1<sup>st</sup> rate  
Timber Palo Verde & Mesquite

# Subdivisions T. 6. S. R. 5. W.

chains N 0° 1' W. bet. Secs. 1 and 2.  
Var. 13° 4' E

10.90 Wash 20<sup>lks</sup> wide Course N. E.

17.80 Wash 20 lks wide " N. W.

37.50 Same Wash. 30 " " N. E.

40.00 Set of Granite stones 16 x 8 x 5  
ins. 12 ins. in the ground  
for a  $\frac{1}{2}$  Sec. Cor., marked 1 on  
W. face, dug pits 18 x 18 x 12  
ins. N. and S. of stone, 5 1/2  
ft. dist. and raised a mound  
of earth 1 1/2 feet high, 3 1/2 ft.  
diam. diameter.

50.60 Wagon road to Gila Bend <sup>S. E. N. E.</sup> line

76.00 Wash. 90 links wide Course NW.

80.43 Intersect N bdy of Tp.  
and 1<sup>st</sup> Stand. par. South,  
at a point. 9.59 chains  
N 89° 42' E from the Stand  
Cor. to Secs. 35, and 36 as



## Subdivisions T. 6 S. R. 5 W.

hereinbefore described  
Where I set a granite  
stone  $16 \times 10 \times 4$  ins. 12 ins  
in the ground, for closing  
Cor. to Secs. 1 and 2. Marked  
C.C. on S face. with 1  
notch on E. and 5 notches  
on W faces. and raised  
a mound of stone  $1\frac{1}{2}$   
ft high. 2 ft. base along =  
side. Pits impracticable

Land level

Sail. Sandy loam 1<sup>st</sup> rate  
Timber. Palo Verde + Mesquite

## Subdivisions T. 6. S. R. 5. W.

chains From the Cor. to Secs. 2, 3, 34  
and 35. on the South bdy of  
the township. the Cor. as  
heretofore described  
Thence I run.

N  $0^{\circ} 1' W$  bet. Secs. 34<sup>th</sup> & 35<sup>th</sup>  
Var.  $13^{\circ} 4' E$

19.40 Wash 70 lks wide Course NW.

28.40 Wash 75 " " " "

40.00 Set a Granite stone 24 x 10 x 4  
ins. 18 ins. in the ground  
for a Sec. Cor., marked  $\frac{1}{2}$  on  
W. face, dug pits 18 x 18 x 12  
ins. N. and S. of stone,  $5\frac{1}{2}$   
feet dist. each raised a mound  
of earth  $1\frac{1}{2}$  feet high,  $3\frac{1}{2}$  ft  
base, alongside.

## Subdivisions T. 6 S. R. 5. W.

chains  
 80.00. Set a granite stone 18 x 8  
 x 6 ins. 12 ins. in the  
 ground, for Cor to Sec.  
 26. 27. 34 and 35 marked with  
 1 notch on S. and 2  
 notches on E. sides; dug  
 pits 18 x 18 x 12 ins. in cor-  
 ner, 5½ ft. dist., and raise  
 a mound of earth 2 feet high  
 with 4½ ft. base alongside

## Land level

Soil. Sandy loam 1<sup>st</sup> rate  
 Timber. Palo Verde & Mesquite



## Subdivisions T. 6. S. R. 5. W.

Chains N  $89^{\circ}41'E$  on a random  
line bet. Secs. 26 and 35.

Var.  $13^{\circ}4'E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.

79.96 Intersect N. and S. line at  
Cor. to Secs. 25, 26, 35 and 36

Thence I run

S  $89^{\circ}41'W$  on a true line  
bet. Secs. 26 and 35.

Var.  $13^{\circ}4'E$

11.70 \$  
39.98 \$ Wash 30 lks wide course N.W.  
Grant's Town 18 x 10 x 4  
ins. 12 ins. in the ground  
for a Sec. Cor., marked 1 on  
N. face, dug pits 18 x 18 x 12  
ins. E. and W. of \$300. 5 1/2  
feet dist. and raised a mound  
of earth 1 1/2 feet high 3 1/2 ft.  
base diameter.

75.90 Wash 30 lks wide Course N.W.



## Subdivisions T. 6 S. R. 5. W.

chain

79.46

The Cor. to Secs. 26, 27, 34<sup>th</sup> and 35

Land level.

Soil. Sandy loam 1<sup>st</sup> rate

Timber. Palo Verde and Mesquite

## Subdivisions T. 6. S. R. 5. W.

chains  $N 0^{\circ} 1' W$ . bet. Secs. 26<sup>and</sup> 27Var.  $13^{\circ} 4' E$ 40.00 Blazed Palo Verde tree 6  
ins. diam. on W side for  
 $\frac{1}{4}$  Sec Cor. Marked  $\frac{1}{4} S$ .53.00 on W side. dug pit's 18x18x12 ins  
N.E.S. of tree  $5\frac{1}{2}$  ft. dist. & piled a mound of earth  
 $1\frac{1}{2}$  ft. high &  $5\frac{1}{2}$  ft. base around tree  
Wash 20 lbs. wide course NW.80.00 Set a Granite stone 18 x 10  
x 4 ins. 12 ins. in the  
ground, for Cor. to Secs.22. 23. 26 & 27, marked with  
2 notches on S. and 2notches on E. edges; dug  
pits 18 x 18 x 12 ins. in eachsec.  $5\frac{1}{2}$  feet dist., and raise  
a mound of earth 2 feet high. $4\frac{1}{2}$  foot base, alongside.

Land level

Soil. Sandy loam 1<sup>st</sup> rate.

Timber Palo Verde and Mesquite

Subdivisions J. 6 S. R. 5 W.

chains  $N 89^{\circ} 41' E$  on a random  
line bet. Sects 23 and 26  
Var.  $13^{\circ} 4' E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.

80.00 Intersect  $N$  and  $S$  line 10  
links  $S$  of Cor to Sects. 23  
24, 25 and 26.

Thence I run on true line  
bet Sects. 23 and 26  $S 89^{\circ} 37' W$   
Var.  $13^{\circ} 4' E$

20.90 Wash. 35 lks. wide Course  $N. W.$

40.00 Set a Granite Stone 16 x 8 x 5  
ins. 11 ins. in the ground  
for  $\frac{1}{4}$  Sec. Cor., marked  $\frac{1}{4}$  sec.  
 $N$ . face, dug pits 18 x 18 x 12  
ins.  $E$  and  $W$  of Cor.  $5\frac{1}{2}$   
feet dist., and raise a mound  
of earth  $1\frac{1}{2}$  feet high,  $3\frac{1}{2}$  ft.  
long, oblong.

## Subdivisions T. 6. S. R. 5. W.

chains

40.55

Wash 25 lks wide Corner N.W.

80.00

The Cor. to Secs. 22. 23. 26 + 27

Layd. level.

Soil Sandy loam. 1<sup>st</sup> rate

Timber. Palo. Verde and Mesquite

Oct. 23. 1891



## Subdivisions J. 6. S. R. 5. W.

chains N  $0^{\circ} 1' W$  bet. Secs. 22 and 23Var.  $13^{\circ} 4' E$ 

40.00 Set a Granite stone, 15 x 10 x 6  
 ins., 11 ins. in the ground  
 for a  $\$$  cor. to Secs. 22 and 23  
 W. from dug pits 18 x 18 x 12  
 ins. North and South of stone,  $5\frac{1}{2}$   
 feet dia. and raised a mound  
 of earth  $1\frac{1}{2}$  ft high on  $3\frac{1}{2}$  ft  
 base diameter.

45.20 Wash. 20 lbs wide Course N.W.

80.00 Set a Granite stone 20 x 8  
 x 4 ins. 15 ins. in the  
 ground, for Cor. to Secs.  
 14, 15, 22 & 23, marked with  
 3 notches on  $\$$  and 2  
 notches on E. edges; dug  
 pits 18 x 18 x 12 ins. in each  
 sec.,  $5\frac{1}{2}$  feet dia. and raised  
 a mound of earth 2 feet high,  
 $1\frac{1}{2}$  ft base diameter.

## Subdivisions T. 6 S. R. 5. W.

Land. level

Soil. Sandy loam 1<sup>st</sup> rate

Timber Palo Verde + mesquite

## Subdivisions T. 6 S., R. 5 W

chains  $N 89^{\circ} 37' E$  on a random  
line bet. Secs. 14 and 23.

Var.  $13^{\circ} 4' E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.

79.96 Intersect  $N$  and  $S$  line 10  
links  $N$  of Cor. to Secs. 13,  
14, 23 and 24.

Thence I run

$S 89^{\circ} 41' W$  on a true line  
bet. Secs. 14 and 23.

Var.  $13^{\circ} 4' E$

39.98 Set 2 Granite stones 15 x 8 x 5  
ins. H ins. in the ground  
for  $\frac{1}{4}$  Sec. Cor., worked  $\frac{1}{2}$  on  
 $N$ -face, dug pits 18 x 18 x 12  
ins. E. and W. of Stone  $5\frac{1}{2}$   
feet dist., each raised a mound  
of earth  $1\frac{1}{2}$  feet high,  $3\frac{1}{2}$  feet  
long, oblong.

No. 1216

34.

BOOK 1216

Subdivisions T. 6. S. R. 5. W.

chains  
40.20

Wash 25 lks wide Course N.W.

79.96

The Cor. to Secs. 14, 15, 22 and 23.

Layd level

Sail. Sandy loam 1<sup>st</sup> rate

Timber Palo Verde + Mesquite



## Subdivisions T. 6. S. R. 5. W.

Chain  $N 0^{\circ} 1' W$  bet. Secs. 14, and 15.

Var.  $13^{\circ} 4' E$

40.00 Set a Granite stone  $16 \times 10 \times 4$   
ins., 12 ins. in the ground  
for  $\frac{1}{2}$  Sec. Cor., marked  $\frac{1}{2}$  on  
W. face, dug pits  $18 \times 18 \times 12$   
ins. N. and S. of stone, 5  
feet dist., and raised a mound  
of earth  $1\frac{1}{2}$  feet high,  $3\frac{1}{2}$  feet  
base, alongside.

80.00 Set a Granite stone  $20 \times 7$   
 $\times 5$  ins. 15 ins. in the  
ground, for Cor. to Secs.  
10, 11, 14 & 15, marked with  
4 notches on  $\frac{1}{2}$  and 2  
notches on E. edges; dug  
pits  $18 \times 18 \times 12$  ins. in each  
sec., 5 $\frac{1}{2}$  feet dist., and raised  
a mound of earth 2 feet high,  
 $4\frac{1}{2}$  feet base, alongside.

Subdivisions T. 6. S. R. 5. W.

Land level.

Soil Sandy loam.

Timber. Palo Verde & Mesquite

## Subdivisions T. 6. S. R. 5. W.

Chains  $N 89^{\circ} 41' E$  on a random  
line bet. Secs. 11 and 14

Var.  $13^{\circ} 4' E$

40.00 Set temporary  $\frac{1}{4}$  Sec Cor.

80.00 Intersect N. and S. line at  
Cor. to Secs. 11, 12, 13, and 14

Thence I run

$S 89^{\circ} 41' W$  on a true line  
bet. Secs. 11 and 14.

Var.  $13^{\circ} 4' E$

40.00 Set 2 Granite Stones 16 x 9 x 7  
ins., 11 ins. in the ground  
for  $\frac{1}{4}$  Sec. Cor., marked  $\frac{1}{4}$  on  
N. face, dug pits 13 x 13 x 12  
ins. E. and W. of Stone, 5 $\frac{1}{2}$   
ft. dist. and raised a mound  
of earth  $1\frac{1}{2}$  ft. high, 3 $\frac{1}{2}$  ft.  
base, diagonals.

47.60 Wash 120 lbs wide Course NW.

51.60 Wash 25 " " " NW.

## Subdivisions T. 6. S. R. 5. W.

chs.  
80.00 The Cor. to Secs. 10. 11. 14. and 15.

Level level.

Soil. Sandy loam 1<sup>st</sup> rate

Timber Palo Verde + Mesquite



## Subdivisions T. 6 S. R. 5 W.

chains N  $0^{\circ} 1' W$  bet. Secs. 10 and 11

Var.  $13^{\circ} 4' E$

40.00 Set a Granite stone 17 x 8 x 4  
 ins. 13 ins. in the ground  
 for a  $\frac{1}{2}$  Sec. Cor., marked  $\frac{1}{2}$  S.  
 W. face, dug pits 13 x 13 x 12  
 ins. N. and S. of stone  $\frac{1}{2}$   
 feet dist., and raised a mound  
 of earth  $1\frac{1}{2}$  feet high, 3 $\frac{1}{2}$  feet  
 base, oblong.

49.35 Wagon <sup>road</sup> Gila Bend to Sunright NE. T. 5 N.

69.40 Wash. 20 lks wide Course Northwest.

80.00 Set a Granite stone 18 x 10  
 x 4 ins. 12 ins. in the  
 grounds for Cor. to Secs.  
 2, 3, 10 & 11, marked with  
 5 notches on S. and 2  
 notches on E. edges; dug  
 pits 13 x 13 x 12 ins. in each  
 one, 5 $\frac{1}{2}$  feet dist., and raised  
 a mound of earth  $1\frac{1}{2}$  feet high, 3 $\frac{1}{2}$  feet base, oblong.

Subdivisions S. 6. S. R. 5, W. 1

chains a mound of earth 2 ft  
high.  $4\frac{1}{2}$  ft. base  
alongside

Land. level

Soil. Sandy loam 1<sup>st</sup> rate  
Timber Palo. Verde & Mesquite

## Subdivisions T. 6. S. R. 5. W.

chains  $N 89^{\circ} 41' E$  on a random  
line bet. Secs. 2 and 11

Var.  $13^{\circ} 4' E$

40.00 Set temporary  $1/4$  Sec Cor.

80.00 Intersect N and S. line at  
Cor. to Secs. 1, 2, 11 and 12

Thence I run

$S 89^{\circ} 41' W$  on a true line  
bet. Secs. 2 and 11

40.00 Set a post, 3 ft. long, 3 ins. square  
with marked stone, 12 ins. in the  
ground, for  $1/4$  sec. cor., mark  
 $1/4$   $\$$  on N face; dig pits 18 x 18  
x 12 ins. E and W of post,  $5\frac{1}{2}$  ft  
dist., and raised a mound of  
earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base  
around post.

58.20 Wagon road to Gila Bend Corner N.E.

64.20 Wagon road Gila Bend to  
Gunsight mine Corner N.E. & S.W.

## Subdivisions T. 6. S. R. 5. W.

chs.  
80.00 The Cor. to Secs. 2, 3, 10 and 17

Land level  
Tail. Sandy loam 1<sup>st</sup> rate  
Timber. Palo Verde & mesquite



## Subdivisions T. 6 S. R. 5. W.

Chains N  $0^{\circ} 1' W$  bet. Secs. 2 and 3Var.  $13^{\circ} 4' E$ 

40.00 Set a post, 3 ft. long, 3 ins. square with marked stone, 12 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mark  $\frac{1}{4}$  §. on W face; dug pits 18 x 18 x 12 ins. N and S of post,  $5\frac{1}{2}$  ft. dist., and raised a mound of earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base around post.

70.82 Southern Pacific Railway running Northeastly & Southwestly

71.60 Wagon road from Gila Bend to Yuma running par. to R.R.

80.33 Intersect N bdy of Tp and 1<sup>st</sup> Standard par South at a point N  $89^{\circ} 42' E$   
 9.98 Chains from the Standard Cor. to Secs 34 and 35, as heretofore

## Subdivisions T. 6. S. R. 5. W.

described at which  
 point. I set a post.  
 $4\frac{1}{2}$  ft. long. 4 ins square  
 with marked stone 12  
 ins. in the ground. for  
 closing cor. to Secs. 2 and  
 3. Marked

C. C. T. 6. S. R. 5. W. on South  
 Sec. 2 on E and

Sec. 3 on W faces. with  
 2 matches on E. and 4  
 matches on W faces. dug  
 pits <sup>18x18x12 ins</sup> S. E. and W of post.  $5\frac{1}{2}$   
 ft. dist. and raised a mud  
 of earth 2 ft high.  $4\frac{1}{2}$  ft  
 base around post.

Land level.

Soil. Sandy loam 1<sup>st</sup> rate  
 Simbar Palo Verde & Mesquite  
 Oct. 24, 1891

Subdivision T. 6 S. - R. 5 W. Cont<sup>d</sup>  
 Charis

From the cor to Seco 3. 4. 33 & 34 on  
 the S. bd'y of the Tp. previously established  
 and heretofore described by me & run  
 $N 0^{\circ} 2' W.$  bet Seco 33 & 34.

Var.  $13^{\circ} 4' E.$

Over level mesa.

40.00 Set a post 4 ft long 4 ins square with  
 marked stone 12 ins in the ground  
 for  $\frac{1}{4}$  Sec Cor. marked  $\frac{1}{4} S$  on W. face  
 dug pits  $18 \times 18 \times 12$  ins N & S of post  
 $5\frac{1}{2}$  ft dist. and raised a mound of  
 earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base around post

50.00 Set a post 4 ft long 4 ins square with  
 marked stone 12 ins in the ground  
 for cor to Secs 27. 28. 33 & 34. marked  
 T. 6 S. S. 27 on NE  
 R. 5 W. S. 34 on SE

S 33 on SW. and

S 28 on NW. faces, with



Subdivisions T. 6 S. - R. 5 W. - Cont<sup>2d</sup>

Chains

1 notch on S. and 3 notches on E  
edges dug pits 18x18x12 ins. in each  
Sec. 5 1/2 ft dist. and raised a mound  
of earth 2 ft high 4 1/2 ft base around post.  
Land, level.

Soil, sandy loam, 1<sup>st</sup> cat.  
Timber, scattering Palo Verde and  
Mesquite



Subdivision T. 6 S. - R. 5 W. - Cont<sup>d</sup>  
 Chain

N.  $89^{\circ}41'E$  on a random line bet  
 Secs 27 & 34

Var.  $13^{\circ}4'E$ .

across level ground.

40.00 Set temp.  $\frac{1}{4}$  Sec. Cor.

80.10 Intersect N & S line 10 lks N. of the  
 cor to Secs 26, 27, 34 & 35

Thence I run

S  $89^{\circ}45'W$  on a true line bet  
 Secs. 27 & 34

Var.  $13^{\circ}4'E$

7.60 Wash 50 lks wide course NW.

22.70 Wash 50 lks wide; course NW.

40.05 Set a granite stone  $16 \times 10 \times 4$  ins  
 10 ins in the ground for  $\frac{1}{4}$  Sec Cor.  
 marked  $\frac{1}{4}$  on N. face, dug pits  
 $18 \times 18 \times 12$  ins. E & W. of stone  $5\frac{1}{2}$  ft  
 dist. and raised a mound of  
 earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside

Subdivisions T. 6 S. - R. 5 W. Cont<sup>d</sup>

Chains

62.70 Wash 45 lks wide course NW.

80.10 The cor to Secs 27. 28. 33 & 34

Land level

Soil, sandy loam 1<sup>st</sup> rate

Timber, Palo verde and mesquite  
brush

Subdivisions T. 6 S. R. 5 W. - Cont<sup>d</sup>  
Chairs

N. 0° 2' W. bet Secs 27 &amp; 28

Var. 13° 4' E

Over level mesa.

- 40.00 A palo verde tree 6 ins. in diam. which I marked  $\frac{1}{4}$  S. and blazed on W. side for  $\frac{1}{4}$  Sec. cor; dug pits 18x18x12 ins N & S of tree 5 $\frac{1}{2}$  ft dist. and raised a mound of earth 1 $\frac{1}{2}$  ft high, 3 $\frac{1}{2}$  ft base around tree.
- 40.30 Wash 50 lbs wide course NW.
- 66.30 Wagon road from Cila Bend to Cunsight mine course NE & SW.
- 80.00 Set a post 4 ft long 4 ins square with marked stone 12 ins in the ground for cor to Secs 21, 22, 27 & 28 marked T. 6 S. S 22 on NE  
R 5 W. S 27 on SE  
S 28 on SW and  
S. 21 on NW faces

Subdivisions T. 6 S. - R. 5 W. - Cont<sup>d</sup>

Chambers

with 2 notches on S and 3 notches  
on E edges, dug pits 18 x 18 x 12 ins  
in each Alc. 5 1/2 ft dist. and raised a mound  
of earth 2 ft high 4 1/2 ft base around  
post.

Land, level

Soil, sandy loam, 1<sup>st</sup> rate

Timber, Scattering Palo Verde  
and Mesquite



Subdivisions T. 6 S. R. 5 W. - Cont<sup>d</sup>  
 Chains

N.  $89^{\circ}45'E$  on a random line bet  
 Secs 22 & 27

Var.  $13^{\circ}4'E$ .

Across level mesa

40.00 Set temp  $\frac{1}{4}$  sec Cor.

80.16 Intersect N & S. line 5 lks S. of  
 the cor. to Secs 22, 23, 26, & 27

Thence I run

S.  $89^{\circ}43'W$ . on a true line bet  
 Secs 22 & 27

Var.  $13^{\circ}4'E$ .

8.10 Wash 15 lks wide course NW.

20.20 Wash 50 lks wide course NW.

40.08 Set a volcanic stone  $15 \times 8 \times 5$  ins  
 10 ins. in the ground for  $\frac{1}{4}$  sec Cor  
 marked  $\frac{1}{4}$  on N. face, dry pits  
 $18 \times 18 \times 12$  ins E & W. of stone  $5\frac{1}{2}$  ft  
 dist. and raised a mound  
 of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base

Subdivision T. 6 S. - R. 5 W. - Cont<sup>d</sup>

Chains

along side

76.50 Wagon road from Cota Bend to  
Gunnright mine, course N E & S W.

80.16 The cor to Secs 21. 22. 27 & 28

Land level

Soil, sandy loam, 1<sup>st</sup> rate

Timber, scattering Palo Verde and  
mesquite brush

Subdivision T. 6 S. R. 5 W - Cont<sup>d</sup>  
 Chains.

N.  $0^{\circ} 2' W$ . bet Secs 21 & 22

Var.  $13^{\circ} 4' E$

Over level ground.

- 40.00 Set a granite stone  $16 \times 8 \times 5$  ins  
 10 ins in the ground for  $\frac{1}{4}$  Sec  
 Cor. marked  $\frac{1}{4}$  on W. face, dug  
 pits  $18 \times 18 \times 12$  ins. N & S. of stone  
 $5\frac{1}{2}$  ft dist and raised a mound  
 of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base  
 along side.
- 57.60 Wash 10 lks wide course NW.
- 79.00 Wash 80 lks wide, course NW.
- 80.00 Set a granite stone  $18 \times 8 \times 6$  ins  
 12 ins. in the ground for cor  
 to Secs 15. 16. 21 & 22. marked  
 with 3 notches on S and E edges  
 dug pits  $18 \times 18 \times 12$  ins. in each  
 Sec.  $5\frac{1}{2}$  ft dist and raised  
 a mound of earth 2 ft high

Subdivision I. to S. - R. 5 W. - Cont<sup>d</sup>

Chain

4 1/2 ft base along side.

Land, level.

Soil sandy loam, 1<sup>st</sup> rate

Timber, scattering Palo Verde  
and mesquite brush



Subdivision T. 6 S. - R. 5 W. - Cont'd

Chairs

N.  $89^{\circ}43'E$  on a random line bet  
Secs 15 & 22.

Var  $13^{\circ}4'E$ .

Across level country.

40.00 Set temp  $\frac{1}{4}$  Sec Cor.

80.04 Intersect N & S line 5 lks S of  
cor. to Secs 14. 15. 22 & 23.

Thence I run

S.  $89^{\circ}41'W$ . on a true line  
bet Secs 15 & 22.

Var  $13^{\circ}4'E$ .

26.00 Wash  $\frac{1}{2}$  lks wide, course NW.

40.02. Set a granite stone  $15 \times 8 \times 5$  ins  
10 ins in the ground for  $\frac{1}{4}$  Sec  
Cor. marked  $\frac{1}{4}$  on N. face, dug  
pits  $18 \times 18 \times 12$  ins E & W. of  
stone  $5\frac{1}{2}$  ft dia and raised  
a mound of earth  $1\frac{1}{2}$  ft high  
 $3\frac{1}{2}$  ft base along side.

Subdivision T. 6 S. - R. 5 W. - Cont<sup>d</sup>

Chains

48.10 Wagon road from Kita Bend  
to Lumsight mine course N & S.

54.10 Wash 20 lks wide course NW.

80.04 The cor to Secs 15. 16. 21 & 22

Land level

Soil sandy loam, 1<sup>st</sup> rate

Timber, scattering Palo Verde

and mesquite brush.

## Subdivision T. 6 S. R. 5 W. - Cont'd

Chain

N.  $0^{\circ}2'$  W. bet Secs 15 & 16Var.  $13^{\circ}4'$  E.

Over level ground.

- 6.15 Wash 25 lks wide course NW.
- 37.35 Wash 35 lks wide course NW.
- 40.00 Set a granite stone  $15 \times 8 \times 5$  ins  
10 ins in the ground for  $\frac{1}{4}$  Sec  
Cor. marked  $\frac{1}{4}$  on W. face,  
dug pits  $18 \times 18 \times 12$  ins. N & S.  
of stone  $5\frac{1}{2}$  ft dist and  
raised a mound of earth  $1\frac{1}{2}$  ft  
high  $3\frac{1}{2}$  ft base alongside.
- 43.15 Wash 25 lks wide, course NW.
- 55.25 Wash 15 lks wide, course NW.
- 80.00 Set a post 4 ft long 4 ins square  
with marked stone 12 ins in  
the ground for cor to Secs 9.10  
15 & 16 marked  
T. 6 S. S. 10 on NE

Subdivision T. 6 S. - R. 5 W. - Cont<sup>d</sup>  
 Chains

R 5 W S. 15 on SE

S 16 on SW and

S 9 on NW faces

with 4 notches on S and 3 notches  
 on E. edges, dug pits 18 X 18 X 12 ins  
 in each Sec. 5 1/2 ft dist and  
 raised a mound of earth 2 ft  
 high 4 1/2 ft base around post.

Land, level

Soil, sandy loam, 1<sup>st</sup> rate

Timber, scattering Palo Verde  
 and mesquite brush.



Subdivision T. 6 S. - R. 5 W. - Cont<sup>d</sup>  
 Chain

N.  $89^{\circ}41'$  E. on a random line bet  
 Secs 10 & 15

Var.  $13^{\circ}4'$  E

Across level near.

40.00 Set temp  $\frac{1}{4}$  Sec Cor.

80.06 Intersect N & S line at cor to Secs  
 10, 11, 14 & 15.

Thence I run

S.  $89^{\circ}41'$  W. on a true line bet  
 Secs 10 & 15

Var  $13^{\circ}4'$  E

40.03 Set a granite stone  $15 \times 10 \times 4$  ins  
 10 ins in the ground for  $\frac{1}{4}$  Sec  
 Cor. marked  $\frac{1}{4}$  on N. face, dug  
 pits  $18 \times 18 \times 12$  ins E & W. of  
 stone, <sup>5 $\frac{1}{2}$  ft. dist.</sup> and raised a mound  
 of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base  
 along side.

68.10 Wagon road from Cita Bend to

## Subdivision T. 6 S. R. 5 W. - Cont'd

Chain

Sight mine course NE &amp; SW.

72.10 Wash 25 lks wide, course NW.

80.06 The cor to Secs 9. 10. 15 &amp; 16

Land level

Soil, sandy loam, 1<sup>st</sup> rateTimber, scattering Palo Verde  
and mesquite brush.Oct 26<sup>th</sup> 1891

N. 0° 2' W. bet Secs 9 &amp; 10

Var. 13° 4' E

Over level ground.

40.00 Set a post 4 ft long 4 ins square  
with marked stone 12 ins in  
the ground for  $\frac{1}{4}$  Sec Cor.marked  $\frac{1}{4}$  S. on W. face, dug <sup>5 ft. dia</sup>pits 18 x 18 x 12 ins N & S. of post  
and raised a mound of earth1 $\frac{1}{2}$  ft high 3 $\frac{1}{2}$  ft base around post80.00 Set a post 4 ft long 4 ins square  
with marked stone

Subdivision T. 6 S. - R. 5 W. - Cont. <sup>d</sup>

12 ins in the ground for  
 Cor to Secs 3, 4, 9 & 10. marked

T. 6 S. S. 3 on NE

R. 5 W. S. 10 on SE

S. 9 on SW and

S. 4 on NW faces,

with 5 notches on S. and 3 notches

on E edges, dug pits 18 x 18 x 12

ins. in each Sec. 5 1/2 ft diam

and raised a mound of earth

2 ft high 4 1/2 ft base around

post

Land level

Soil sandy loam, 1st rate

Timber, scattering Palo Verde

and mesquite brush.



62

BOOK 1216

U. S. Surveyor-General's Office,

TUCSON, A. T. *May* 1892

The foregoing Field Notes of the Surveys of  
*C. G. S. R. S. N.*

Gila and Salt River Meridian

*Arizona* executed by  
*David Drummond*

U. S. Deputy Surveyor, under his contract dated  
*June 13<sup>th</sup> 1891*

having been critically examined, the necessary corrections and explanations made, the said Field Notes and the surveys they describe are hereby approved.

*Royal Johnson*

U. S. Surveyor-General  
for the Territory of Arizona.