

Exhibits

1.

North Range T. 13 N; R. 12 E.
South " T. 14 N; R. 12 E.
West " T. 13 N; R. 12 E.

1318

No. 1318

4-671

FIELD NOTES
GENERAL LAND OFFICE.

No. 1318

copies of 13 11 and 12 E. 1

Field Notes
of the Survey and resurvey of the
Exteriors Spis. 13 N R. ~~12~~ 12 + 13 E.

Gila and Salt River,
Base and Meridian
in the

Territory of Arizona,

as surveyed by

Daniel Drummond

U. S. Deputy Surveyor.

under his Contract No. 28.

dated Feb'y 21. 1893.

Survey Commenced July 27. 1893.

Survey Completed Nov 29. 1893

Index for { BOOK 1317
BOOK 1318

INDEX.

	31.	32.	33.	34.	35.	36.	31.	32.	33.	34.	35.	36.	
	+28	+30	+32	+34	+36	+ ²⁶	+50	+48	+45	+43	+40	+38	+
1.	2						14						6
	+6	5	4	3	2	1	+6	5	4	3	2	1	+6
2.	4	7					12	16	7			12	7
													+
3.	6	18	T.13	N.R.11.E.			13	19	18	T.13	N.R.12.E.	13	18
													+
4.	8	19					24	21	19			24	+
													+
5.	10	30					25	22	30			25	+
													+
6.	12	31					36	25	31			36	+

3.2 STAND. NORTH.

Index for {

BOOK 1317
BOOK 1318
No. 1318

18

INDEX.

FOURTH STAND.

PARALLEL North.

MERIDIAN EAST.

T. 16. N. R. 12. E.

T. 16. N. R. 13. E.

31. 32. 33. 34. 35. 36.
~~105~~ + ~~103~~ + 101 + ~~99~~ + ~~97~~ + ~~95~~
 6. 5. 4. 3. 2. 1.

31. 32. 33. 34. 35. 36.
 119 + 117 + 115 + 113 + 111 + 109
 6. 5. 4. 3. 2. 1.

AUXILIARY

T. 15. N. R. 12. E.

T. 15. N. R. 13. E.

31. 32. 33. 34. 35. 36.
 92 + 90 + 88 + 86 + 83 + 81
 6. 5. 4. 3. 2. 1.

31. 32. 33. 34. 35. 36.
 79 + 77 + 75 + 73 + 71 + 69
 6. 5. 4. 3. 2. 1.

THIRD

T. 14. N. R. 12. E.

T. 14. N. R. 13. E.

31. 32. 33. 34. 35. 36.
 + + + + +
 6. 5. 4. 3. 2. 1.

31. 32. 33. 34. 35. 36.
 54 + 56 + 58 + 60 + 63 + 65
 6. 5. 4. 3. 2. 1.

Extension T 13 N. R 11. E.

I now proceed to the
Standard to Sp. 13 N.
R. 11. E.

10 ins. in my transit on
the true Meridian. (before
adjusted.) and found
the variation of the mag-
netic needle is $13^{\circ}40'E$

July 27. 1893

In the Standard Cor.
to Sp. 13. N. R. 10. E. 11. E
hereinbefore described.
I run North on a
random line.

Va. $13^{\circ}40'E$
and ab. 475.44 chains.

Exteriors T. 13. N. R. 11. E.

the Cor. to Tps. 13 & 14. N. R. 10 & 11. West. 12. 31 ch.

a post. S 8. S 7. and properly m. claim b.

Witnessed, as dect. in the fine rates for by the Surveyor

The falling is 12 s. E

The Correction is 205

to West. per m. and

the true line is bear.

S 1° 29' E

July 7. 1893.

From the Cor. to Tps. 13 & 14 N. R. 10 & 11. E. of rain

S 1° 29' E

on a true line bet. Sec. 1 & 6.

Exteriors T. 13, N. R. 11, E.

- chs. In Va 13° 20' E
 13.50 Gulch 8 lbs made runo NW
 35.60 Set a Sandstone 15 x 10 x 6 in
 10 ins. in the ground. for
 1/4 sec. Cor. marked 1/4 on W
 face Pine 5 in
 diam. 5° W 49 lbs
 dist. 2 + 1 B.S.
 A Pine 26 ins. diam. brass
 N60° E 29 lbs dist. marked
 1/4 S. B.S. —
- 75.60 Rock in place 6 x 4 x 2 ft
 above ground. for Cor. to Secs
 1, 6, 7, & 12. Marked with
 Cross. with 5 marks on S.
 and 1 mark on N. Side
 of Cross. Whence a Pine
 16 ins. diam. brass. N60° E 61 lbs
 dist. marked T. 13, N. R. 11, E. S. 6. B.S.

Exterior of 13 N. R. 11 E.

A Pine 14 ins. diam. trans.
 S $20\frac{1}{2}^{\circ}$ E 158 lks. dist. marked
 T. 13. N. R. 11 E. S 7. B. T.
 A Pine $3\frac{1}{4}$ in diam. trans.
 S 47° W 81 lks. dist. marked
 T. 13. N. R. 11 E. S 7. B. T.
 A Pine 14 ins. diam. trans.
 N 75° W 81 lks. dist. marked
 T. 13. N. R. 10. 6 Sec. 1 B. T.
 Land nearly level
 Soil sandy 2^d rate
 Timber Heavy Pine, 75.60 chs.

S $1^{\circ} 29'$ E on a true line
 bet. Secs. 7^{and} 12.

Va. 13th 40' E
 In dense Pine timber
 40.00 Rock in place 2x1x1 ft.
 above ground. for $\frac{1}{4}$ Sec. Cor.

Exteriors T. 13, N. R. 11, E.

- chs. Marked with Cross. $\frac{7}{14}$
 W. of Cross, whence Pine 24
 ins. diam. bears S 25° E 58 lbs dist
 marked $\frac{1}{4}$ S. B. J.
- A Pine 14 ins. diam bears N 63° W
 17 lbs. dist marked $\frac{1}{4}$ S. B. J.
- 47.30 Gulch 7 ruins S. W.
- 53.50 A Pine 3 on line
 marked with notches on N + S
- 59.60 A Pine 24 ins. diam on line
 marked with 2 notches on N + S Sides
- 80.00 Set a limestone $20 \times 12 \times 6$
 ins. 15 ins. in the ground for
 Cor. to Secs. 7, 12, 13 & 18. marked
 with 2 notches on N. and 4 notches
 on S. edges. Whence A Pine
 22 ins. diam. bears N 13° E 60
 lbs. dist. marked T. 13, N. R. 11 E S. 7. B. J.
 An Oak 6 ins. diam bears

Exteriors S. 13, N. R., 11. E.

chw. S $14\frac{1}{4}^{\circ}$ E 97 lks. dist. marked
 S. 13, N. R. 11. E. S. 18. B. T.
 A Pine 30 ins. diam. brass
 S 49° W 129 lks. dist. marked
 S. 13, N. R. 10 E. S. 13 B. T.
 A Pine 30 ins. diam. brass
 N 52 $^{\circ}$ W 129 lks. dist. marked
 S. 13, N. R. 11 E. S. 12 B. T.
 Land level
 Soil rock & gravelly 3^d rate
 Shrub dense Pine 80. chs.

S $1^{\circ} 29'$ E on a true line
 but. Secs. 13 & 18.

In ^{Pa.} ^{13^o 4^o E} ^{and} ^{13^o 4^o E} timber
 40.00 Set a sandstone 24 x 12 x 4 in
 18 ins. in the ground. for. $\frac{1}{4}$
 Sec. Cor. marked $\frac{1}{4}$ on W face

Exteriors T. 13, N. R. 11, E.

Chs. Whence a Pine 14 ins. diam. bears
 $N 88^{\circ} E$ 14 lks. dist. marked $\frac{1}{4} S. B. J.$
 A Pine 12 ins. diam. bears $S 45^{\circ} W$
 15 lks. dist. marked $\frac{1}{4} S. B. J.$

80.00 Set a Sandstone $20 \times 15 \times 4$ ins.
 15 ins. and for Cor.
 to Secs. 24. Marked
 With 3 na. N & S edges

Whence a Pine 14 ins. diam. bears.
 $N 82^{\circ} E$ 34 lks. dist. marked
 T. 13, N. R. 11, E. S. 18. B. J.
 A Pine 14 ins. diam. bears.

$S 25^{\circ} E$ 65 lks. dist. marked
 T. 13, N. R. 11, E. S. 19 B. J.

An Oak 10 ins. diam. bears

$S 24^{\circ} W$ 66 lks. dist. marked
 T. 13, N. R. 10, E. S. 24 B. J.

A Pine 11 in diam. bears,
 $N 69^{\circ} W$ 26 lks. dist. marked

Exteriors T. 13, N. R. 11, E.

chs. T. 13, N. R. 10, E. S. 13 B. 5,

Land level

Soil Sandy 2^d rate

Timber Pine & Oak. 80 chs.

July 28. 1893.

S 1° 29' true line

cut. Secs. 19th & 24th.

Va 13° 40' E

Through dense Pine & oak timber

40.00 Set. a Sandstone 20 x 12 x 5 ins.

15 ins. in the ground for 1/4 Sec.

Cor. marked 1/4 on W face, whence

A Pine 20 ins. diam. bears S 36° W

51 lts. dist. marked 1/4 S. B. 5.

An. Oak 4 ins diam bears N 67° E

52 lts. dist. marked 1/4 S. B. 5.

40.70 Gulch. 10 lts wide runs Northwly

Extensions T. 13, N. R. 11, E.

chs.

80.00

Set. a Sand stone 28x10x4 ins
21 ins in the ground for Cor.
to Secs. 19, 24, 25 & 30. Marked
with 4 Notches on N. and 2 notches
on S edges. Whence —

A Pine 18 ins diam. bears.
N 62° E dist. marked
T. 13, N. R. 11 B. 1.

A Pine 15 ins diam. bears.
S 38° E 24 lks. dist. marked
T. 13, N. R. 11, E. S. 30. B. 1.

A Pine 6 ins. diam. bears.
S 25° W 33 lks. dist. marked
T. 13, N. R. 10, E. S. 25. B. 1.

A Pine 7 ins. diam. bears.
N 50° W 7 lks. dist. marked
T. 13, N. R. 10, E. S. 24 B. 1.

Land nearly level
Soil gravelly 3^d rate
Timber Pine & Oak. 80 chs.

Exteriors S. 13. N. R. 11. E.

- chs. S. $1^{\circ}29'E$ on a true line
 but. Secs. 25th & 30.
- 4.00 Descend Va. $13^{\circ}40'E$ In dense Pine and Oak timber
- 9.50 Gulch 20 lks. wide runs S.E. usual
- 14.00 Opposite bank bears. S.E. & N.W.
- 40.00 Set a ~~tree~~ $20 \times 10 \times 3$ ins.
 15 in ~~tree~~ ground for $\frac{1}{4}$ Sec.
 Cor. ~~ms~~ on W. face, whence
 A Pine 30 ins. diam. bears.
 N $60^{\circ}E$ 5 lks. dist. marked
 $\frac{1}{4}$ S. 13. 9. — A Pine 5 in.
 diam. bears. S $11^{\circ}W$ 10 lks.
 dist. marked $\frac{1}{4}$ S. 13. 9.
- 45.00 Left bank General Springs
 Gulch. bears. Easterly & Westerly
 descend, abruptly
- 52.25 Stream 30 lks. wide runs Eastly
- 58.30 Opposite bank bears. Eastly & Westly

Exteriors T. 13, N. R. 11, E.

chs.

80.00

Set a Sand stone 22x10x3 ins
16 ins. in the ground for Cor.
to Secs. 25, 30, 31 & 36. Marked
with 5 notches on N & 1 notch
on S edges. Whence

A Pine 24 - diam. brass.

N 22° E 48 - any & marked
T. 13, N. R. 11, E. S. 30 B. T.

A Pine 18 ins. diam. brass.

S 34° E. 50 lks. dist. marked
T. 13, N. R. 11 E. S. 31. B. T.

A Pine 24 ins diam. brass.

S 31° W 41 lks. dist. marked
T. 13, N. R. 10, E. S. 36 B. T.

An Oak 5 ins. diam. brass.

N 29 $\frac{1}{4}$ ° W 53 lks dist. marked
T. 13. N. R. 10, E. S. 25. B. T.

Land breaker

Sail Mackey

Timber Pine & oak. 80 chs.

Exteriors S. 13, N. R. 11, E.

chs. S $1^{\circ}29'$ E on a tree line
bet. Secs. 31nd & 36.

Var. $13^{\circ}40'$ E

40.00 Through dense Pine & Oak timber
Set a sand stone $20 \times 10 \times 5$ ins
15 ins \downarrow the ground for $\frac{1}{4}$ Sec

Corner $\frac{1}{4}$ on W. face, where
A $\frac{1}{4}$ in. diam brass, S 62° E

44 lks. dist, marked $\frac{1}{4}$ S. B. T.

A. Pine 24 ins. diam brass, N 41° W

48 lks. dist, marked $\frac{1}{4}$ S. B. T.

80.00 the Standard Cor. to Sps. 13, N.
Rs. 10 & 11 E. herein before described
Land level.

Soil Story 3^d & 4th Natl

Timber Pine & Oak 80 chs.

July. 29. 1893.

Exteriors S. 13. N. R. 11. E.

I now proceed to the Stand
and Cor. to Sps. 13. N. R. 11 & 12
E. hereinbefore described.

There I run, North, on a
true line. —

$13^{\circ} 42' E$

I set temporary half-
mile & mile Cors. at each,
40 and 80 chs. and at

471. 24 chs. the Cor. to
Sps. 13 & 14. N. R. 11 & 12 E
trans. West. 20.98 chains.

the falling is 20.98 chs East

The Correction for the true
line will therefore be about
3.55 lks. West. per mile, and
the true Course will be

A. $2^{\circ} 33' E$

July 31. 1893.

Exteriors S. 13, N. R. 11, E.

chs. From the Cor. to Sps. 13 &
 14, N. Rs. 11 & 12, E. a post,
 firmly set, and properly
 marked, and witnessed
 as described in the field
 notes furnished to the
 Surveyor. S.

Run. S $2^{\circ} 33' E$ on a true
 line bet. Secs. 1, & 6.

In Pine, Oak and Cottonwood timber
 5.50 descend
 4.75 Gulch, 20 lks. runs. Northwest
 10.17 top of precipice bears. E. & W.
 1.67 descend from precipice bears. E & W.
 2.00 Recross. Gulch, 20 lks. wide runs. N.E.
 20.00 Recross. Gulch 20 lks wide runs. N.W.
 2.50 Recross. Gulch, 20 lks. wide runs. N.E.
 28.50 Ridge bears E. & W. descend
 31.70 Set. a Sandstone $18 \times 12 \times 5$ in

Exteriors T. 13 N. R. 11 E.

- chs 13 ins. in the ground for. $\frac{1}{4}$
 Sec. Cor. marked $\frac{1}{4}$ on W. face
 whence A Pine 14 ins. diam. bears
 $S 42^{\circ} E$ 90 lks. dist. marked
 $\frac{1}{4}$ S. B. T. — A Pine 7 ins diam
 bears West. 33 lks. dist.
 marked $\frac{1}{4}$ S. B. T.
- 33.25 Recross Gulch 20 lks. wide near N.W.
- 35.00 Top high bank to N.W. & S.E. descend
- 65.10 Recross. Gulch. 20 lks. wide near N.E.
- 71.70 A Pine 10 ins. diam. which I
 mark T. 13 N. S. 6 on N.E.
 R 17 E. Sec. 7 on S.E.
 R 10 E S 12 on S.W. ^{2nd}
 S. 1 on N.W. Sides. with 1 notch
 on N and 5 notches on S sides
 for. Cor. to Secs. 1, 6, 7, & 12. whence
 A Pine 15 ins. diam. bears
 $N 3^{\circ} E$ 40 lks. dist. marked

Exteriors J. 13. N. R. 11. E.

J. 13. N. R. 12. E. S. 6 B. T.

A Pine 12 ins. diam. bears.

S 4° E 20 lks. dist. marked

J. 13. N. R. 12. E. S. 7. B. T.

A Pine 16 ins. diam. bears. S 1° W

28 lks. dist. marked

J. 13. N. R. 11. E. S. 12 B. T.

A Pine 8 ins. diam. bears.

N 36½° W 140 lks. dist. marked

J. 13. N. R. 11. E. S. 1. B. T.

Land very rough

Sail rocky 4th rate

Timber Pine, Oak & Cottonwood,

Timber 71.70 chs.

S 2° 33' E on a tree line

bet. Secs 7th and 12.

Ya. 63° 42' E

In Pine and C&W timber

Exteriors I. 13. N. R. 11. E.

- | | |
|-------|---|
| 15.30 | Gulch, 20 lks. wide near N.W. ^{Asend} |
| 20.40 | bank bears. Northerly & southerly ^{Asend} |
| 24.40 | 30 ins. diam. on Pine
with 2 notches on N. & S. Sides |
| 34.3 | l abruptly |
| 36.3 | es Gulch, 10 lks. wide near N.E. |
| 40. | a Sandstone 22x10x5 ins.
ins. in the ground. for. 1/4 Sec.
marked 1/4 on W. face. whence
Pine 18 ins. diam. bears N 82 E.
33 lks. dist. marked 1/4 S. B. J.
A Pine 30 ins. diam. bears
N 50° W 27 lks. dist. marked
1/4 S. B. J. — Asend |
| 42.8 | top bank bears. Northerly & S. itly |
| 51.50 | Gulch, 15 lks. wide bears N.E. asend |
| 55.80 | bank of Gulch bears. N. itly & S. itly |
| 60.50 | Gulch, 50 lks. wide near N.W. |
| 80.00 | Set. a Sandstone 18x12x5 ins |

Exteriors S. 13, N. R. 11, E.

13 ins. in the ground for Cor.
to Secs. 7, 12, 13, 15, 18 marked
with 2 notches

4 notches on
Whence a Pine 1

N $48\frac{1}{2}^{\circ}$ E 76 lks. dist. marked

S. 13, N. R. 12 E. S. 7

A Pine 20 ins. diam.

S $40\frac{1}{2}^{\circ}$ E 80 lks. dist. marked

S. 13, N. R. 12 E. S. 1

A Pine 10 ins. diam.

S 26° W 118 lks. dist. marked

S. 13, N. R. 11 E. S. 13

A Pine 24 ins. diam.

N 30° W 90 lks. dist. marked

S. 13, N. R. 11 E. S. 12

Land very rough & broken

Soil rocky 4 $\frac{1}{2}$ rate

Timber Pine & oak. 80 chs.

Extensions S. 13, N. R. 11, E.

- chs. S $2^{\circ} 33' E$ on a true line
 to Secs. 13rd & 18.
- 21.70[¢] On $13^{\circ} 42' E$ Oak timber
 to and
- 27.00 20 lks wide runs. N.E.
 to bank bs. Neitty & S Neitty
- 29.60 Sandstone $18 \times 10 \times 4$ ins
 in the ground for $\frac{1}{4}$
 Cor. Marked $\frac{1}{4}$ on W. face
- 40.00 in a Pine 18 ins. diam. bears
 $^{\circ} E$ 4 lks. dist. Marked $\frac{1}{4}$ S 13, J.
 Pine 24 ins. diam. bears. N 48° W
 $\frac{1}{2}$ dist. Marked $\frac{1}{4}$ S 13, J.
- 44.10 Pine 24 ins. diam. on line
 Marked with 2 notches on N & S. Sides.
- 80.00 Set a Spar. Stone $16 \times 12 \times 4$ ins
 11 ins. in the ground for. Cor.
 to Secs. 13, 18, 19 & 24. Marked
 with 3 notches on N & S edges.

Exteriors T. 13, N. R. 11, E.

Whene a Pine 30 ins. diam. bears,
 N 85° E 27 lbs. dia. marked
 T. 13, N. R. 12 E. S. 1/2 1/4.

A Pine 16 ins. dia. bears.
 S 18° E 33 lbs. dia. marked
 T. 13, N. R. 12, E. S. 1/2 1/4.

A Pine 20 ins. dia. bears.
 S 20° W 149 lbs. dia. marked
 T. 13, N. R. 11, E. S. 1/2 1/4.

A Pine 28 ins. dia. bears.
 N 84° W 77 lbs. dia. marked
 T. 13, N. R. 11 E. S. 1/2 1/4.

Land broken.

Sail rocky + sandy + pate
 Timber Pine + Oak 50 chs.

August, 1. 1893.

Exteriors S. 13. N. R. 11. E.

- chs. S $2^{\circ}33'E$ on a true line
 but. Secs. 19 & 24.
- 40.00 \times Va. 13 $^{\circ}$ 42' E
 dense Pine Timber
 Sandstone 18x14x5 ins
 in the ground. for $\frac{1}{4}$
 marked $\frac{1}{4}$ on W face
 a Pine 4 ins. diam. brass
 E 10 lbs dist. marked
 B.S. — A Pine 5 in diam
 S 55 $^{\circ}$ W 24 lbs. dist.
 marked $\frac{1}{4}$ S. B.S.
- 50.00 \times Pine 24 ins. diam. on line
 red with 2 notches on N & S sides
- 80.00 \times a Sandstone 20x10x5 ins
 15. ins. in the ground. for
 Cor. to Secs. 19, 24, 25 & 30
 marked with 4 notches on N
 and 2 notches edges. whence
 a Pine 18 ins. diam Brass.

Extensions T. 13. N. R. 11. E.

chs. N 3° E 31 lks. dist. marked,
 T. 13. N. R. 12 E. S 19 B. T.
 A Pine 14 ins diam. trans.
 S 77° E 52 lks. dist. marked
 T. 13. N. R. 12 E. S 19 B. T.
 A Pine 8 ins. diam. trans.
 S 38° W 67 lks. dist. marked
 T. 13. N. R. 11 E. S 19 B. T.
 A Pine 6 ins. diam. trans.
 N 53° W 84 lks. dist. marked
 T. 13. N. R. 11 E. S 19 B. T.
 Land level
 Soil gravelly 3' deep
 Timber dense Pine 20 chs.

S 2° 33' E on a true line
 bet. Secs. 25th and 30.
 Va 13° 42' E

Oxterions T. 13, N. R. 11, E.

- chs. Through dense Pine timber
- 4.00 Gulch 10 lks. wide runs. NNW.
- 33.00 A Pine 16 ins. diam. on line
 id with 2 notches on N + S. Sides
- 37.90 30 ins. diam. on line marked
 notches on N + S. Sides.
- Sandstone 16 X 10 X 5 ins.
 in the ground for $\frac{1}{4}$ Sec.
 marked $\frac{1}{4}$ on W. face. whence
 in 6 ins. diam. brass,
 +^oW 74 lks. dist. marked
 S. B. J. — A Pine 8 ins. diam.
 N 89^oE 25 lks. dist.
 marked $\frac{1}{4}$ S. B. J.
- 64.10 A Pine 30 ins. diam. on line
 marked with 2 notches on N + S. Sides
- 80.00 Set a post. 4 $\frac{1}{2}$ ft. long, 4
 ins. square. 24 ins. in the
 ground for Cor to Secs. 25, 30, 31 & 36

Exteriors S. 13, N. R. 11. E.

Marked S. 13, N. S. 30 on N. E.

R. 12. E. S. 31 on S. E.

R. 11. E. S. 36 on S. W. and

S. 25 on N. W. faces of 5

notches on N. and S. on

S. edges. Whence,

A Pine 10 ins. diam. bears,

N 16° E 75 lbs. dist. marked

S. 13, N. R. 12. E. S. 29. 4.

A Pine 18 ins. diam. bears,

S 35° E 45 lbs. dist. marked

S. 13, N. R. 12. E. S. 29. 5.

A Pine 16 ins. diam. bears,

S 76° W 54 lbs. dist. marked

S. 13, N. R. 11. E. S. 36 B. S.

A Pine 14 ins. diam. bears,

N 37° W 65 lbs. dist. marked

S. 13, N. R. 11. E. S. 25. B. S.

Land level.

Extensions 4.13. N. R. 11. E.

chs. Soil Sandy 2^d rate
Timber dense Pine 80 chs.

4. 33' E on a true line

1.65 W. 31st and 36.

14. Va 13° 42' E

N. enough dense Pine timber
ing 10 lks wide runs West only

0.90 Co. 10 lks wide runs N. W.

Note a fork 4 ft. long. 4 ins

are 24 ins. in the ground

1/4 Sec. Co. marked 1/4 S.

0. W. face. Whence A Pine
8 in. diam. bears. S 47° E 69
lks dist. marked 1/4 S. B. S. —

A Pine 5 ins. diam. bears. S 54° W
7 lks. dist. marked 1/4 S. B. S.

56.15 Trail bears. N. E. 4 S. W.

Extensio J. 13 N. R. 11 E.

ch.
80.00

the Standard Cor. to Tps.
13 N. Rs. 11 & 12 E. as
hereinbefore described
Land nearly all
Soil sandy 2 ^{1/2} miles to
Timber dense ⁱⁿ

August. Timber

————— at 1/2 mi.
wood

I now proceed

Cor. to Tps. 13 & 14 N
11 & 12 E. herein

Thence I run ^{the} ^{or}
a random line ^{to} said
Townships.

Va. 13° 42' E

40.00 old 1/4 Cor. properly marked
80.00 old Sec. Cor. properly marked
120.00 After diligent search, I fail

Exteriors S. 13. N. R. 11. E.

cho. to find any evidence of
the $\frac{1}{4}$ Sec. Cor. Nor do I find
any evidence of Corners.

Having been established on
the 5 miles of this line

447.65 W. to the Cor. to Sps. 138,

14. N. 28.11 E bears,

N. — is. dist. the fall-
ing links S. of the

reaction for the

tr. will be. about

44 S. per mile. and

the Course will be.

$29^{\circ}41'E$

Aj. Diligent Search W.
of the Cor. to Secs. 1, 2, 35 & 36

I fail to find any evi-
dence. of a Survey having
been made.

August 3. 1893.

Exteriors S. 13, N. R. 11, E.

From the Cor. to Rps. 13 & 14,
N. R. 10 & 11, E. Hereinafter
described I run.

S 89° 41' E

on a true line to Sec. 6 & 31.

Va. 13

Through dense timber.

0.00

R. bank of  to base.

Eastward & then descend

28.50

Enter bottom

34.25

Stream 30 ft wide flows E. by

37.65


Set a sandstone 10 x 5 ins.

21 ins. in the  for 1/4 Sec.

Cor. marked 1/4  face, where

a Pine 8 ins. diam.  beans, S. 85° W

211 lbs. dist. marked 1/4 S. B.S.

A Pine 7 ins. diam.  beans N 20° E

73 lbs. dist. marked 1/4 S B.S.

40.40

Recess Clear Creek 80 lbs wide

Extriors T. 13. N. R. 11. E.

Chs. runs. Northeastly.

42.85 ~~Lower~~ Bottom $\frac{1}{2}$ ascend along
slope of Clear Creek

53.50 Clear Creek 80 ft wide
Northeastly.

57.80 $\frac{1}{2}$ Clear Creek brans. Smith

77.65 x udstone 24x12x6 ins.

the ground. for. Cor.

to 6. 31 $\frac{1}{2}$ 32 ^{marked} with

1 on W. and 5 matches
e. Whence

A ~~10~~ 5 ins. diam. brans.

N 63 ~~10~~ lks. dist. marked
T. 14. N. R. 11. E. S. 32. B. J.

A Juniper 8 ins. diam. brans.

S 40° E 63 lks. dist. marked
T. 13. N. R. 11. E. S. 5. B. J.

A Pine 10 ins. diam. brans

S 57° W 102 lks. dist. marked

Exteriors T. 13, N. R. 11, E.

Chs. T. 13, N. R. 11 E. S. 6 B. S.
 A Pine 6 ins. diam. beans.
 N 48° W 63 lks. dist. marked
 T. 14, N. R. 11, E. S. 6 B. S.
 Land Very rough
 Soil rocky
 Timber Pine 77.65 chs.

A 89° 41' E or true line
 bet. Secs. 5
 Va. 13° 4'

Through Pine

4.25 Pine 24 ins. diam. on line marked
 with 2 notches on E & W sides
 10.50 Pine 16 ins. diam. on line marked
 with 2 notches on E & W sides
 31.00 Left bank Clear Creek beans,
 Northeastly & Southeastly descend

Extensions J. 13, N. R. 11. E.

- chs.
- 37.65 Clear Creek 40 lks. wide runs N.E.,
 40.00 Set. a Sandstone 18X14X5 ins
 13 ins. in the ground for. $\frac{1}{4}$ Sec.
 Cor. to $\frac{1}{4}$ on N. face whence
 A. 6 ins. diam. bears N70°W
 7. marked $\frac{1}{4}$ S. B. J.
 A. 6 ins. diam. bears S67°E
 37. marked $\frac{1}{4}$ S. B. J.
- 45.00 Ridg. runs N.E. & S.W.
 45.40 Trail runs N.E. & S.W.
 47.10 Gulch 10 lks. wide. flows N.E.
 53.20 Trail bears N. & S.
 72.40 Gulch 10 lks. wide flows N.
 80.00 Set. a Sandstone 18X10X5 ins
 13 ins. in the ground for.
 Cor. to Secs. 4, 5. 32 & 33. Marked
 with 2 notches on W & 4 notches
 on E edges. Whence
 An Oak 6 ins. diam bears.

Extensions S. 13, N. R. 11 E.

N 36° E 54 lks. dist, marked

S. 14, N. R. 11 E. S 33. B.S.

A Pine 16 ins. in. bears.

S 28° E 74 lks. dist, marked

S. 13, N. R. 11 E. S 33. B.S.

A Pine 14 ins. in. bears.

S 22° W 65 lks. dist, marked

S. 13, N. R. 11 E. S 33. B.S.

A Pine 10 ins. in. bears.

N 36° W 25 lks. dist, marked

S. 14, N. R. 11, E. S 32 B.S.

Land rough & broken

Soil stony 4th class.

Timber 1/2 oak, 80 chs.

just. 4. 1893

S 89° 41' E on a true line

bet. Secs. 4 & 33.

Wa. Va. 13° 40' E.

Exteriors T. 13. N. R. 11. E.

- Chs. Through dense Pine timber ^{head}
- 15.00 divide bet. Clear Creek ^{end} & General Springs Cañons, base N.E.
- 24.60 Set a 20 ins. diam. on line, marked with scratches on E. & W. sides
- 40.00 Set a sandstone 16 x 8 x 5 ins.
- 44 " in the ground for 1/4 Sec
- 48 " marked 1/4 on N. face which
- 48 " 12 ins. diam. from S 16° E
- 52 " 12 " dist. marked 1/4 S. B. 7,
- 54 " 6 ins. diam. from N 39° E
- 56 " 12 " dist. marked 1/4 S. B. 7,
- 57.50 Set a sandstone General Springs Cañon
- 63.00 " " abruptly, leave timber ^{head}
- 76.20 Clear Creek 50 lks. wide ^{near} S. easterly
- 80.00 Set a sandstone 16 x 9 x 8 ins. 11 ins. in the ground. for Cor. to Secs. 3, 4, 33 & 34. marked

Exteriors Y. 13, N. R. 11. E.

chs. with 3 notches on E. & W. edges
and raised a mound of stone
1 1/2 ft. high, 2 ft. base
alongside pits & ... ticable
Land rough & ...
Soil sandy & rocky ³/₄ ⁴/₄ rate
Timber Pine & ... 3 chs.

S. 89° 41' E on ... line
Feb. Recs. 3 & 34
Va. 13° 40' E

descend

- 6.20 Clear Creek 85. lks. ... N. E.
18.20 top of ridge ... W. descend
28.50 Recross. Clear Creek ... with, S. E.
40.00 Set a sandstone 16 x 10 x 8 ins. 11 ins
in the ground for 1/4 Sec. Cor. marked
1/4 on N side, and raised a

Exteriors J. 13. N. R. 11. E.

- chs. mound of Stone $1\frac{1}{2}$ ft. high 2 ft
base alongside. pits impracticable
- 42.40 Clear Creek 90 lks wide runs N.W.
- 53.10 Recross Clear Creek 80 lks wide runs S. the
- 80.00 Sch. Sandstone $38 \times 10 \times 8$ ins.
27 in in the ground, for Cor. to
Sec 34 & 35, marked with
H in W. & 2 notches on E
2 hence.
- A Spruce 12 ins. diam. bears
N. 40 lks. dist. marked
J. 13. N. R. 11. E. S. 35. B. J.
- A Spruce 12 ins. diam. bears
S 46° E 222 lks. dist. marked
J. 13. N. R. 11. E. S. 2. B. J.
- A Pine 16 ins. diam. bears
S 30° W 149 lks. dist. marked
J. 13. N. R. 11. E. S. 3. B. J.
- A Pine 4 ins. diam. bears.

Exterior S. 13. N. R. 11. E.

- chs. N 30° W 24 lks. dist. marked
 S. 14. N. R. 11. E. S. 34. B.S.
 Land rough & broken
 Soil rocky 4th rate
 Timber scattered Pine.
-
- S 89° 41' E to line
 bet. Secs. 4 & 5
 Va. 13°
- .80 Clear Creek 110 ft runs N.E.
 3.00 Leave bottom of
 40.00 Set a sandstone 16x11x6 ins. 11
 ins. in the ground for 1/4 Sec.
 Cor. marked 1/4 on N. face, and
 raised a mound of stone 1 1/2
 ft. high 2 ft. base, alongside
 pits impracticable.
 50.00 Right bank of Clear Creek

Extensions of 13, N. R. 11 E.

Cho.	bears, Northeastly & Southwestly
52.00	Enter Pine timber
64.70	Gulch 10 lks wide runs Northwesterly
80.00	The Cor. to Secs. 1, 2, 35 & 36, hereinafore described Land rough & broken Soil rocky 4 th rate Timber. Scattering Pine Timber 28. chains.

August, 5, 1893.

I find it necessary to resurvey
the line bet. Tps 13, & 14, N R 12 E
as the corners on the third
Auxiliary meridian were
Corrected by me. the line
bet. said Tps. Was incorrectly
surveyed. the corner said
line, not being in alignment.

ECOK

1318

N-Bdy - T³⁸ N. R 12 E.
 Exterior S. 13, N. R 12 E.

chs. I now proceed to the Cor.
 to Tps. 13 & 14, N. R. 12 & 13 E.
 hereinafter described. Thence
 West

bet. Secs. 1 and 36.

Pa. $13^{\circ}42'E$.

Through dense Pine timber

- 20.50 Bank, bears N.W. & S.E. descend
- 28.10 Gulch 10 lks. wide run N.W. ^{and}
- 38.00 Opposite bank bears N.W. & S.E.
- 40.00 Set a Sand stone $17 \times 10 \times 6$ ins.
 12 ins. in the ground. for $\frac{1}{4}$
 Sec. Cor. marked $\frac{1}{4}$ on N. face
 Where a Pine 14 ins. diam. bears,
 $S 31^{\circ} W$ 26 lks. dist. marked
 $\frac{1}{4}$ S B.Y. - A Pine 15 ins. diam.
 bears N $20^{\circ} W$ 80 lks. dist.
 Marked $\frac{1}{4}$ S. B.Y. -
 Old $\frac{1}{4}$ Sec. Cor. bears $S 30^{\circ} E$

BOOK 1318

N-Bdy 39. T. 13 N. R. 12 E.
Extremes S. 13. N. R. 12. E.

chs. 431 lks. dist. Well Establishe
ished, marked, & Witnessed,
Which I destroy.

41.50 Bank. beans. N.W. + S.E. descend,

48.65 Gulch 10 lks. wide runs N.W. ^{ascend}

55.40 Opposite bank beans. N.W. + S.E.

58.10 Bank. beans NW + S.E. descend,

63.90 Gulch 40 lks. wide runs N.W. ^{ascend}

64.50 Trail beans. N.W. + S.E. ascend,

69.00 opposite bank beans. N.W. + S.E.

80.00 Set a Sand stone 18x11x4 ins.
13 ins. in the ground. for Cor. to
Secs. 1, 2, 35 & 36. marked with
1 notch on E and 5 notches on
W. edges. Whence. —

An Oak 12 ins. diam. beans,
N 73° E 4 lks. dist. marked
S. 14. N. R. 12. E. S 36 B. V.
A Pine 14 ins. diam. beans.

N-Bdy T 13 N. P. R 12 E BOOK 1318
Exteriors S. 13, N, R, 12, E.

chs. S 48 $\frac{1}{2}$ ° E 97. lks. dist. marked
S. 13, N, R. 12, E. S. 1, B. S.
An Oak 5 ins. diam. bears,
S 38 $\frac{1}{2}$ ° W 54 lks. dist. marked
S. 13, N, R. 12, E S. 2 B. S.
An Oak 6 ins. diam. bears,
N 27° W 14 lks. dist. marked
S. 14, N, R. 12, E, S. 35, B. S.
Old Sec. Cor. bears, S 36° 45' E
420. lks. dist. A post,
Well Established, marked,
and Witnessed, which I destroy
Laud rough & broken
Soil stony 3^d rate
Timber Pine & Oak, 80. Chains

West
bet. Secs. 2, and 35.

BOOK 1318

N-Bdy T. $7\frac{1}{3}$ N. R. 12 E.
 Extriors J. 12 N. R. 12 E.

chs.

Va. $13^{\circ}42'E$

Through dense Pine timber

40.00 Set. a Sandstone $16 \times 14 \times 4$ ins.
 11 ins. in the ground. for. $\frac{1}{4}$ Sec.
 Cor. marked $\frac{1}{4}$ on N. face whence.

A Pine 18 ins. diam. bears, $N62^{\circ}E$
 45 lbs. dist. marked $\frac{1}{4}$ S. B. J.

An. Oak 5 ins. diam. bears. $S4\frac{1}{2}W$
 54 lbs. dist. marked $\frac{1}{4}$ S. B. J.

Old $\frac{1}{4}$ Sec. Cor. bears. $S36^{\circ}45'E$

388 lbs. dist. A post. Well
 Established marked & Witnessed
 which I destroy. —

50.00 Bank bears. N, W + S, E. descend

55.70 Gulch 10 lbs wide runs. N, W ascend

57.20 Opposite bank bears. N, W + S, E.

80.00 Set. a Sand stone $24 \times 10 \times 6$ ins.
 18 ins. in the ground. for. Cor. to
 Secs. 2, 3, 34 & 35, marked

N- Bdy. 4² 13 N. R. 12 E. BOOK 1318
Exteriors S. 13 N. R. 12 E.

chs. with 2 notches on E and 4 notches
on N edges. When

A Pine 10 ins. diam. bears.

N 67° E 73 lks. dist. marked
S. 14, N. R. 12 E. S. 35. B. Y.

A Pine 14 ins. diam. bears.

S 12° E 49 lks. dist. marked
S. 13, N. R. 12 E. S. 2 B. Y.

An Oak 14 ins. diam. bears

S 45° W 12 lks. dist. marked
S. 13, N. R. 12 E. S. 3. B. Y.

A Pine 15 ins. diam. bears.

N 31° W 83 lks. dist. marked
S. 14, N. R. 12 E. S. 34 B. Y.

Old Sec. Cor. bears. S 37° E
360 lks. dist. A Pastwell
Established. marked &
witnessed. which I destroy
also, marks on Bearing trees

BOOK 1318

N-Bdy ^{43.513} N R 12 E
Extensio S. 12. N. R. 12. E.

chs. Land nearly level
Soil sandy & gravelly 3' rate
Timber Pine & Oak. 80. chas

West.

Pat. Secs. 3, 2d 34.

Through dense Pine & Oak timber
Va. 13° 42' E.

- 19.40 Bank. trans. N.W. + S.E. descend
20.05 A Pine 28 ins. diam. on line mar-
ked with 2 notches on E + W. Sides
29.90 Gulch 10 lks wide runs N.W. ^{ward}
40.00 Opposite bank trans. N.W. + S.E.,
Set a sandstone 16 x 13 x 6 ins. 11
ins. in the ground for 1/4 sec.
Cor. marked 1/4 on N. face. where
A Pine 20 ins. diam. trans. S 62° E
38 lks. dist. marked 1/4 S. 13. E.

N-Bdy, ^{H.H.}T, 3 N, R, 12 E
 Exteriors J, 13, N, R, 12, E.

- chs. An Oak 4 ins. diam. bears. N
 27^o/₂ E 78 lks. dist. marked 1/4 S B. J.
 Old 1/4 Sec. Cor. bears. S 40^o/₄ E
 343 lks. dist. A post well
 established, marked, and
 witnessed, which I destroy
- 42.00 Summit bears. N, W, + S, E, descend
- 43.80 Right bank. Leonards. Cañon
 bears. N, + S, descend
- 49.35 A Pine 20 diam. on line marked
 with 2 notches on E + W. Sides.
- 51.00 descend abruptly & leave timber
- 76.30 Stream 50 lks. wide runs. N. ~~thly~~
- 80.00 Set a Sandstone 16x10x7 ins. 11
 ins. in the ground for Cor. to
 Secs. 3, 4, 33 & 34. Marked
 with 3 notches on E & W edges
 and raised a mound of Stone
 1 1/2 ft. high. 2 ft. base, along side

BOOK 1318

N Bdy ⁴⁵ 7.13 N! R 12 E
Exursions 9.13 N. R 12. E.

chs. Pits impracticable. —
Old sec. Cor. beans. S 60° 20' W
25.18 chains. dist. A Post.
well established, marked, and
witnessed, which I destroy.
Land very rough & broken,
Soil rocky & of rate.
Timber, dense Pine. 57. Chains,
August. 7. 1893.

West.

bet. Secs. 4 and 33.

Va. 13° 42' E

ascend abruptly

12.00 Enta timber ascend less abruptly

16.00 Left bank Leonard's Cañon
fans. Northerty & Southaly.

19.50 Trail beans. N. E. & S. W.

21.50 Bank beans. N. E. & S. W. descend

N-Bdy T13 ⁴⁶R12 E
Extensions J. 12, N. R. 12 E.

BOOK 1318

29.80	Gulch 10 lks. wide runs N.E. around
4.50	opposite bank bears N.E. & S.W.
6.75	Trail bears N.W. & S.E.
10.00	Set a sandstone 18x10x5 ins. 13 ins. in the ground for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face, whence A Pin 20 ins. diam. bears S10°E 66 lks. dist. marked $\frac{1}{4}$ S. B. S. An Oak 7 ins. diam. bears N28E 49 lks. dist. marked $\frac{1}{4}$ S. B. S. Old $\frac{1}{4}$ Sec. Cor. bears S61°22'W 25.47 chs. dist. A Post. well Established. marked, and Witnessed. which I destroy
80.00	Set a sandstone 20x10x7 ins. 15 ins. in the ground. for Cor. to Secs. 4, 5, 32 & 33. marked with 4 notches on E and 2 notches on W. edges. whence —

N-Bdy #73 N R 12 E
Extriors T. 13, N, R. 12 E.

chs. A Pine 12 ins. diam. bears.
N 74° E 27 lks. dist. marked
T. 14, N, R. 12, E. S. 33 B. J.
A Pine 14 ins. diam. bears.
S 15° E 31 lks. dist. marked
T. 13, N, R. 12, E. S. 4 B. J.
A Pine 14 ins. diam. bears.
S 77° W 32 lks. dist. marked
T. 13, N, R. 12, E. S. 5 B. J.
A Pine 16 ins. diam. bears
N 35° W 45 lks. dist. marked
T. 14, N, R. 12, E. S. 32. B. J.
Old Sec Cor. bears. S 61° W
25, 37 chs. A Post well
Established. Marked, and
Witnessed, which I destroy
Land nearly level
Soil sandy 3^d rate
Timber Pine & oak 68. chs.

N - Bdy T, ⁴⁸13 N R 12 E
Exteriors S, 13, N, R, 12, E.

Nest.

bet. Secs. 5th & 32.

Va. 13°42' E

Through dense Pine timber

- 40.00 Set a Sandstone 18x14x6 ins. 13
ins. in the ground. for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on N. face. whence
A Pine 17 ins. diam. bears. N31°W
15 lks. dist. marked $\frac{1}{4}$ S. B. T.
A Pine 6 ins. diam. bears. S65°E
48 lks. dist. marked $\frac{1}{4}$ S. B. T.
Old $\frac{1}{4}$ Sec. Cor. bears. S61°22'W
25.47 chs. A Post. well. established
marked. and witnessed. which I destroy
- 43.60 A Pine 22 ins. diam. on line marked
with 2 notches on E. & W. Sides.
- 45.20 A Pine 20 ins. diam. on line marked
with 2 notches on E. & W. Sides
- 80.00 Set a Sandstone 22x15x6 ins. 16

BOOK 1818

Cr Bdy 4⁹/₁₃ N R 12 E
Extensions J. 13, N, R, 12, E.

Chs. ins. in the ground for. Cor. to Secs.
5.6. 31⁴/₃₂ marked with 5 notches
on E. and 1 notch on W. edges. Whence
A Pine 40 ins. diam. bears,
N 71° E 27 lks. dist, marked
J. 14, N. R. 12, E. S. 32 B. J.
A Pine 36 ins. diam. bears,
S 20° E 52 lks. dist. marked
J. 13, N. R. 12, E. S. 5. B. J.
A Pine 18 ins. diam. bears,
S 84° W 60 lks. dist. marked
J. 13, N. R. 12 E. S. 6 B. J.
A Pine 20 ins. diam. bears,
N 22° W 45 lks. dist. marked
J. 14, N. R. 12, E. S. 31 B. J.
old Sec. Cor. bears. S 61° 43' W
25, 43 chs. dist. a Post. well
Established, marked & Witness
Which I destroy also Bearing trees,

N - Bdy T13⁹ R 12 ~~BOOK~~ 1318
Exteriors S. 13. N. R. 12. E.

Land level
Soil gravelly 2^d rate
Timber Pine and Oaks 80. chs.

Nest.

bet. Secs. 6th & 31.

Va. 13° 42' E

Through dense Pine timber

40.00 Bank bears N.W. & S.E.

Flat rock in place 12 ins. Square
flush with the surface, which
I mark with cross thus + 1/4
or N. Whence

A Pine 7 ins. diam. bears N 31° W
11 lks. dist. marked 1/4 S. B. S.

A Pine 6 ins. diam. bears S 12° W
5 lks. dist. marked 1/4 S. B. S.

Old 1/4 Sec. Cor. bears S 61° 48' W

X-Bdy ^{57.} T 13 N R 12 E
 Extriors T. 13, N, R. 12 E.

- chs. 25.40 chs. dist. A Post. well
 Established, Marked, and
 witnessed, which I destroyed,
 descend
- 45.55 Gulch 20 lks. wide runs N.W. ^{ascend}
- 57.00 Opposite bank bears N.W. & S.E.
- 64.10 Trail bears N.W. & S.E.
- 73.00 Bank bears East & West
- 93.15 Pine 40 ins. diam. on line. marked
 with 2 notches on E. & W. Sides.
- 102.40 Intersect the W. boundary of the
 Sp. 11.66 chs. N. of the Cor. to
 Sp. 13 & 14. N. R. 11 E. where I
 set a Sandstone 20x12x10 ins.
 15 ins. in the ground. for Closing
 Cor. to Sp. 13 & 14. N. R. 12 E
 Marked C.C. on E. with 6 notches
 on N, E. & S. Sides. whence
 A Pine 28 ins. diam. bears.

N-Bdy ⁵⁷ T. 13 N. R. 12 E. 1318
Exteriors T. 13, N. R. 12, E.

N 82° E 108 lks. dist. marked
T. 14, N. R. 12, E. S. 31 B. J.

A Pine 12 ins. diam. frans.

S 46° E 47 lks. dist. marked
T. 13, N. R. 12, E. S. 6 B. J.

An Oak 8 ins. diam. frans.

S 37° W 83 lks. dist. marked C.C.
T. 13 & 14 N. R. 12, E. B. J.

on what is now the Cov. to
Tps. 13 & 14 N. R. 12, E. I obliterate
the marks on the N.E. & S.E. sides
also the marks on the witness trees
N.E. & S.E. of Cov. pertaining to
Range. 12 East. —

Land rolling

Soil gravelly & stony 3^d rate
Timber Pine & oak 102.40 chains.

August 8, 1893.

BOOK 1318

S Bdy 53 T 14 N R 13 E
Extensions T. 13. N. R. 13. E.

Chs. I now proceed to the Cor. to
Tps. 13 & 14, N. Rs. 13 & 14, E.
A Post, firmly set, and
properly marked & witnessed
by Deputy U.S. Surveyor
Coutzen, under his Contract,
No. 27, dated Feby 10, 1893.
From the Established Cor. to
Tps. 13 & 14, N. Rs. 13 & 14, E. I
run West, on a random
line, bet. said Tps.

Ca. $13^{\circ}44'E$

I set temporary half mile,
and mile Corners, at each
40, and 80, chains, and at
495.20 chs. I intersect
the W. boundary of the Tps.
15 lks. S. of the Cor. to Tps.
13 & 14 N. R. 12 & 13. E. here-

S. Bdy. T 14 N ⁵⁴R 13 E BOOK 1318
Exteriors S. 13, N. R 13, E.

chs. in before described. The Correction
for the true line will therefore
be S. $2\frac{1}{2}$ lks. and its Course
will be S $89^{\circ}59'E$.

September 20, 1893

From the Established Cor. to
Sp. 13 X 14. N. Rs. 12 X 13. E.
Truv.

S $89^{\circ}59'E$ on a true line
lat. Secs. 6 X 31.

Pa. $13^{\circ}44'E$

In heavy Pine timber

- 2.10 Trail cross. N.E. + S.W.
34.50 Bank cross. E. by N. + W by S.
41.10 Bank cross. W by N + E by S
43.00 Bank cross. N.W. + S.E. descend
48.00 Gulch 10 lks. wide runs S.E. ^{down}

BOOK 1318

S. Bdy T. 54 N, R. 13 E,
Exteriors but.

- | | |
|---------------|---|
| chs.
52.00 | Ridge bears. N.T.D. descend |
| 55.20 | Set. a Limestone. 18x8x8 ins. 13 ins.
in the ground. for. 1/4 Sec. Cor. marked
1/4 on N. face. Whence a Pine 14 ins.
diam. bears. S 15° E 66 lks. dist. marked
1/4 S. B. Y. - A Pine 8 ins. diam. bears
N 84° E 168 lks. dist. marked 1/4 S. B. Y. |
| 55.60 | Enta bottom |
| 56.00 | Recess Gulch 50 lks. wide runs N.E. |
| 59.10 | Recess Gulch 40 lks wide runs S.E. |
| 62.60 | Recess Gulch, 50 lks. wide runs. N.E. |
| 90.00 | Bank Willow Cañon bears. N.T.D. ^{tribes} leaves, |
| 90.85 | Pine 18 ins. diam. on live. marked
with 2 notches on E. & W. Sides |
| 92.80 | Enta bottom |
| 94.10 | to Stream in Willow Cañon 60 lks
wide runs. N.N.W. |
| 95.20 | Set. a Sandstone 18x10x4 ins. 13
ins. in the ground. for. Cor. to Secs |

S Bdy T14 N. R. 13 E BOOK 1318
T. 13 + 14. N. R. 13 E.

chs
5. 6. 31. & 32. marked with 1 notch
on W. and 5 notches on E. edges
Whence A Pine 24 ins diam. bears
N 73° E 131 lks. dist. marked
T. 14. N. R. 13 E. S. 32. B. J.
A. Pine 14 ins diam. bears
S 73° E 136 lks. dist. marked
T. 13. N. R. 13 E. S. 5. B. J.
dug pits 18 x 18 x 12 ins in. Secs.
6 & 31. 5 1/2 ft. dist. and raised
a mound of earth alongside. No
trees within limits ins Secs. 6. or 31.
Land. rough & broken
Sail. Stormy, 4th rate
Timber Heavy Pine 90 chains

S 89° 59' E on a true line
bet. Secs. 5 & 32.

BOOK

1318

S - Bdy T⁵⁷ 14 N, R 13 E
Exteriors Sect.

chs.

Va. 13°44'E

- 1.70 Leave bottom & ascend
- 12.00 Ridge bears N.T.D., descend
- 15.20 Recross Willow Cañon 60 lks wide
- 20.00 Mrs. South, ascend
Enter pine and fir timber
- 24.70 Ridge bears N.T.D., descend
- 29.30 Willow Cañon 60 lks, runs N. ascend
- 40.00 Fir 10 ins. diam. marked 1/4 S.
on N. side. for 1/4 Sec Cor. where
A Fir 12 ins. diam. bears S54°E
42 lks. dist. marked 1/4 S. B.S.
A Fir 12 ins. diam. bears N22°E
16 lks. dist. marked 1/4 S. B.S.
- 43.70 Opposite bank Willow Cañon
bears N.T.D.
- 49.80 Trail bears N.W. & S.E.
- 80.00 Set a sandstone 20x14x4 ins. 15
ins. in the ground. for Cor. to Secs.
4, 5, 32, & 33, marked with 2 notches

S-Bdy T¹⁴ N¹³ R¹³ E
T¹³ + 14. N. R. 13. E.

BOOK 1318

cks. on N. and 4 notches on E. edges. Whence

A Pine 14 ins. diam. bears.

N 66° E 35 lks. dist. marked

T¹⁴, N, R. 13. E. S. 33 B.S.

A Pine 12 ins. diam. bears.

S 25° E 63 lks. dist. marked

T¹³, N, R. 13. E. S. 4. B.S.

A Pine 4 ins. diam. bears.

S 49° W 6 lks. dist. marked

T¹³, N, R. 13. E. S. 5. B.S.

A Pine 15 ins. diam. bears.

N 52° W 92 lks. dist. marked

T¹⁴, N R. 13. E, S. 32 B.S.

Land very rough & broken

Soil. rocky & gravelly 3^d & 4th rate

Timber. Pine & Fir 60 chains

September 21. 1893

BOOK

1318

S - Bdy 7, 4 N R 13 E

Exteriors bet.

chs. S 89° 59' E on a true line
bet. Secs. 4th & 33.
Va. 13° 44' E

In heavy Pine timber

4.00 Juniper 28 ins. diam. on line. marked
with 2 notches on E. & W. Sides

33.07 Oak 16 ins. diam. on line. marked
with 2 notches on E & W. Sides

36.80 Gulch 20 lbs. wide runs N.E.

40.00 Set a Sandstone 20x8x6 ins. 15 ins
in the ground. for 1/4 Sec Gr. marked
1/4 on N. face, whence a Pine 14 ins
diam. trans. S. 14 lbs. dist. marked
1/4 S. B.S. - A Pine 15 ins. diam. trans.
N 32° E. 39 lbs. dist. marked 1/4 S. B.S.

73.10 Trail bears N.E. & S.W.

80.00 Set a Sandstone 16x10x4 ins. 11 ins
in the ground. for Cor to Secs. 3, 4.
33, & 34. marked with 3 notches on

S - Body T⁶⁰ N R 13 E
J. 13 + 14. N. R. 13 E.

BOOK 1319

chs. E. + N. edges whence
A Juniper 10 ins. diam. trans.
N 50° E 36 lks. dist. marked
J. 14, N. R. 13, E. S. 34. B. J.
A Pine 4 ins. diam. trans.
S 6½° E 43 lks. dist. marked
J. 13, N. R. 13, E. S. 3. B. J.
A Pine 4 ins. diam. trans.
S 40° W 3 lks. dist. marked
J. 13, N. R. 13, E. S. 4. B. J.
A Pine 12 ins. diam. trans
N 60° W 68 lks. dist. marked
J. 14, N. R. 13 E S 33 B. J.
Land nearly level.
Soil gravelly 3^d rate.
Timber Pine & Juniper 80. chs.

S 89° 59' E. on a true line

Continued in
Book 2

S-Bdy - 9 1/4 N. R. 13 E
Exteriors T. 13, N. R. 13, E.

Chs.

BOOK

1318

bet. Secs 3 & 34.

Va 13° 44' E

In heavy Pine timber

- 5.00 Bank bars. N.N.E. + S.S.W. descend
13.90 Gulch 10 lks. wide runs N.N.E. ^{ascend}
22.50 Opposite bank bars. N.N.E. + S.S.W.
40.00 Set a Sandstone 18x12x8 ins. 13 ins
in the ground. for 1/4 Sec. Cr. Marked
1/4 on N. Side. whence. A Pine 18 ins
diam. bears N 18° W 6 lks. dist.
Marked 1/4 S. B.S. - A Pine 4 ins diam
bears S 4° W. 45 lks. dist. marked
1/4 S. B.S. -
48.50 Bank bars. N.W. + S.E. descend
53.80 Enter bottom
54.50 Trail bars. N.W. + S.E.
55.90 Gulch 10 lks. wide runs N.W.
56.30 Leave bottom + ascend
62.50 Opposite bank bars. N.W. + S.E.

