

1438

VOL 1

Copied  
Gd

No. 1438 BOOK 1438

# West Boundary

4-671

FIELD NOTES  
GENERAL LAND OFFICE.

T. 22, N. R. 6, E.

Contract No. 10.

W. C. Secon.

Sum accepted by Commiss  
letter dated February 26/90

## Preliminary Oaths of Assistants.

We L.G. Chapman and  
 and P.S. Bishop  
 do solemnly swear that we will well and faithfully execute the  
 duites of Chain Carriers; that we will level the chain over even  
 and uneven ground, and plumb the tally pins, either by sticking  
 or dropping the same; that we will report the true distance to  
 all notable objects, and the true length of all lines that we assist  
 in measuring, to the best of our skill and ability and in accord-  
 ance with instructions given us in the survey of the West  
boundary of Township 22 N.R.  
6 E. and the interior lines  
of same Township in  
Yavapai County

---

Territory of Arizona.

L.G. Chapman Chainman.

P.S. Bishop Chainman.

Subscribed and sworn to before me, this

day of

Aug 1887

T.Y. Morris  
 Notary Public.

We Emmett Laird and  
James W. Donnelly  
do solemnly swear that we will well and truly perform the  
duties of Flagman and Axeman  
respectively - - -  
in the establishment of corners and other duties according to  
instructions given us, and to the best of our skill and ability,  
in the survey of the West boundary and  
interior lines of Yavapai  
22 N.R. 6 E. Yavapai  
county

Territory of Arizona.

Emmett Laird  
James W. Donnelly <sup>Flagman</sup>  
<sub>Axeman</sub>

Subscribed and sworn to before me this 6 "

day of Aug 1889

T. Morris

Notary Public.

Field Notes  
of the survey of the  
West Boundary  
of Township 22 North of Range  
No. 6 East of the Principal Base<sup>and</sup>  
Meridian in Arizona, in as  
surveyed by  
Washington O. Secor,  
U. S. Deputy Surveyor,  
under his contract No. 10  
Dated June 18, 1889.

Survey commenced Aug. 8, 1889.  
Survey completed Aug. 9, 1889.

## Names &amp; Duties of Assistants.

Washington O. Secor	Compassman
L. A. Chapman	Chairman
P. S. Bishop	Chairman
Emmet Laird	Flagman
J. W. Donnelly	Axeman

# Final Oaths for Surveys.

## ~~LIST OF NAMES.~~

~~BOOK 1438~~

A List of the Names of Individuals employed by  
Washington Secor U. S. Deputy Surveyor to  
 assist in running, measuring and marking the lines and  
 corners described in the foregoing Field Notes of the survey of  
 the West boundary and interior  
 lines of Township 22 N.R.  
6 E. Gila and Salt River Base  
and Meridian Line

~~BOOK 1438~~

of the principal base and meridian in the Territory of Arizona,  
 showing the respective capacities in which they acted.

~~Dr. Chapman Chairman~~

~~P. S. Bishop "~~

~~Emmet Laird Chaplain~~

~~James P. Donnelly Chaplain~~

~~Julius Escherich Cook~~

~~Washington Secor, Comptroller~~

# Final Oaths of Assistants.

We hereby certify that we assisted Washington C. Secor U. S. Deputy Surveyor, in surveying  
The West line of Township 22 N.R. 6 E - and the  
minor lines of said township

**BOOK 1438**

of the principal base and meridian in the Territory of Arizona,  
as are represented in the foregoing field notes as having been  
surveyed by him and under his direction; and that said Survey  
has been in all respects, to the best of our knowledge and belief,  
well and faithfully surveyed, and the corner monuments es-  
tablished according to the instructions furnished by the U. S.  
Surveyor-General for Arizona.

John Chapman Chairman

P. S. Bishop Chairman

Emmet Ward Flagman

James W. Donnelly Auxiliary

Subscribed and sworn to before me this 26<sup>th</sup>

day of August - 1889

T. G. Morris  
Notary Public.

Final Oath of U. S. Deputy Surveyor.

BOOK 1438

I, Washington O. Seeley,

United States Deputy Surveyor, do solemnly swear that in  
pursuance of instructions received from ~~Agent~~

John H. Fiske U. S. Surveyor General for Ari-  
zona bearing date of the 18<sup>th</sup> day of June

1889 I have well, faithfully, and truly, in my own proper  
person and in strict conformity, with the instructions furnish-  
ed by the U. S. Surveyor General for Arizona, the surveying  
manual and the laws of the United States surveyed the West

boundary lines  
of Township 22 N.R. 68

of the principal base and meridian in the Territory of Ari-  
zona, as are represented in the foregoing fields notes as having  
been surveyed by me and under my direction; and I do further  
solemnly swear that all the corners of the said survey have been  
established and perpetuated in strict accordance with the survey-  
ing manual, printed instructions, the special written instruc-  
tions of the U. S. Surveyor General for Arizona, and in the

3C

specific manner described in the field notes, and that the foregoing are the true field notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

Washington O. Scurr.  
U. S. Deputy Surveyor.

Subscribed and sworn to before me, this 26<sup>th</sup>  
day of August 1889

T. G. Morris,  
Notary Public.

BOOK #1438

4

## BOOK 1438

ALBUQUERQUE, N. M.

T. 22 N. R. 6. E.

7	6	5	4	3	2	1
9	7	8	9	10	11	12
10	18	17	16	15	14	13
11	19	20	21	22	23	24
12	30	29	28	27	26	25
13	31	32	33	34	35	36

On the night of Aug. 7. 1889. I took an observation on the star Polaris for the purpose of determining the true meridian <sup>and</sup> the magnetic declination of my needle.

I found the magnetic declination to be  $15^{\circ} 15'$  E. <sup>and</sup> drove stakes on the line thus established.

Before commencing this survey tested my instrument on the line established last night <sup>and</sup> found it correct.

From the cor. to Ips. 21 + 22 N. of Rs. 5 + 6. E. which is a pine stake 3 in. square <sup>and</sup> 3 ft. long, properly marked, set in a mound of stone at the foot of a rocky bluff, among fine timber <sup>near</sup> the E. edge of an open park, with bearing trees also properly marked, I run

No. 1438

N. on a random line on the West Boundary of Twp. 22 N. of R. 6 E. setting temporary  $\frac{1}{4}$  Sec.  $\frac{1}{4}$  Sec. Corr. at every  $40 \frac{1}{4}$  80 chs.  $\frac{1}{4}$  at 6 miles  $\frac{1}{4}$  0.61 chs. I intersect the N. Bdy. of said Twp. at a point 42 lks. W. of corr. to Twp. 22 & 23 N. of R. 5 & 6 E. Thence I run

S.  $0^{\circ} 3'$  W. on a true line

Va.  $15^{\circ} 15' E.$

In fine timber, over rolling ground.

+0.61 Set an igneous rock  $16 \times 15 \times 7$  in. 11 in. in ground for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  on N. face raised a mound of stone alongside.

18.03 A pine tree 40 ins. in diam. on line.

30.61 Set an igneous rock  $18 \times 17 \times 10$  ins. in a mound of stone for corr. to secs. 1, 6, 7 & 12. marked with 1 notch on N.  $\frac{1}{4}$  5 notches on S. edges. ground too rocky to admit the same.

Land rolling. soil rocky  $\frac{1}{4}$  very poor.

Timber fine, some good grass.

S. 6° 3' W. on a true line between secs.

7 + 1/2.

N. 15° 15' E.

- 2.20 Ravine *coursa* S. 60° W.  
22.00 Wagon road bears E + W. ascend  
38.00 Top of rocky ridge bears N.E. + S.W. descend.  
40.00 Set igneous stone 24×15×12 ins. in mound  
of stone - ground too rocky to admit the same -  
for 1 ft sec. cor. marked 1/4 on W. face.  
49.50 Ravine to S. W. ascend W. slope of hill  
52.00 Top of W. slope of hill. descend.  
59.00 Foot of " " " "  
80.00 Set stone 15×15×4 ins. in mound of stone -  
ground too rocky to admit the same - for cor.  
to secs. 7, 12, 13 + 18, marked with 2 notches on N.  
end & notches on S. edges.  
Land rolling, soil very rocky, fine timber  
and some good grass.

August 8, 1889

S. 0° 3' W. on a true line between secs.

13 & 18.

Ya. 15° 15' E.

- 12.70 Pine 30 ins. diam. on line.
- 23.80 Ravine course S. W.
- 29.02 Pine 18 ins. diam. on line.
- 40.00 Set stone 16×15×12 ins. in md. of stone,  
for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on N. face.
- 46.50 Ravine course W.
- 50.63 Pine 12 ins. diam. on line.
- 80.00 Set stone 24×12×12 ins. in md. of stone  
for cor. to secs. 13, 18, 19 & 24, marked with  
3 notches on N. & 3 on S. edges.  
Land rolling, soil very rocky, with  
some good grass, timber, pine.

S.  $0^{\circ} 3'$  W. on a true line between secs.

19 & 24.

Ya.  $15^{\circ} 15'$  E.

- 7.79 Pine 30 ins. diam. on line.
- 9.00 Wagon road bears N.E. + S.W.
- 10.00 Log cabin bears W. dist. 2 chs. ascend
- 19.60 Ravine course S.  $75^{\circ}$  W.
- 30.20 Top of rocky bluff bears N.E. + S.W. descend.
- 38.00 Foot " " " " "
- 40.00 Set stone  $12 \times 12 \times 8$  ins. in md. of stone,  
marked  $\frac{1}{4}$  on W. face for  $\frac{1}{4}$  sec. cor.
- 49.00 Bottom of ravine to the S.W.
- 60.00 Ravine course W. ascend.
- 75.00 Top of ridge, bears E + W. descend.
- 80.00 Set stone  $16 \times 10 \times 4$  ins. in md. of stone for  
cor. to secs. 19, 24, 25 + 30, marked with  
 $\frac{1}{4}$  notches on N. + 2 on S. edges.  
Land broken, soil rocky, 4<sup>th</sup> rate, timber pine,  
some good grass.

S.  $0^{\circ} 3' W.$  on a true line between  
secs. 25<sup>a</sup> & 30.

Ya.  $15^{\circ} 15' E.$

10. 00 Ravine course S.  $30^{\circ} W.$  ascend.  
 32. 00 Top of ridge, bears N.E. + S.W. descend abruptly.  
 39. 00 Bottom of deep gulch course S. W. ascend.  
 40. 00 Set stone  $16 \times 12 \times 4$  ins. in m.d. of stone  
     for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on N. face.  
 50. 00 Top of N. slope of hill descend.  
 59. 75 Ravine course S.  $60^{\circ} W.$  ascend.  
 76. 00 Top of high ridge bearing E + W. descend.  
 80. 00 Set stone  $17 \times 12 \times 5$  ins. in m.d. of stone  
     for cor. to secs. 25, 30, 31 + 36. marked with  
     5 notches on N. + 1 notch on S. edges.  
 Land rough + mountainous, soil rocky,  
 1<sup>st</sup> rat., timber pine, grass.

S.  $0^{\circ} 3'$  W. between secs. 31 + 36 on a  
true line.

Ya.  $15^{\circ} 15'$  E.

- 16.00 Bottom of ravine, course S. W. ascend.  
 29.00 Top of ridge, bears N.  $60^{\circ}$  E + S.  $60^{\circ}$  W. descend.  
 32.00 Ravine, course S.  $75^{\circ}$  W. ascend.  
 40.00 Set stone  $15 \times 12 \times 6$  ins. in mound of stone  
     for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on W. face.  
 50.00 Top of bluff bears N.  $80^{\circ}$  E + S.  $80^{\circ}$  W. descend  
 77.50 Foot of "   
 80.00 Tha cor. to Sps. 21 + 22 N. of R. 5. + 6. E.  
     Land rough & mountainous, soil rocky  
     4<sup>th</sup> rate, fine timber & good grass in many  
     places.

---

Aug. 9, 1889.

### General Description.

The ground on this line is covered with a not very thick growth of yellow pine timber & some very good grass. It is also covered with volcanic rock; that being the only formation of stone on the line.

The township W. of this line is also nearly covered with pine timber, though there are several open parks containing excellent pasturage.

Washington O. Secor.

United States Deputy Surveyor.

W. O. Secor  
1438

BOOK 1438

15

No. 1438

U. S. Surveyor-General's Office,

TUCSON, A. T., Nov. 25<sup>th</sup>, 1889

The foregoing Field Notes of the Surveys of  
West Boundary of  
Township 22 North, Range  
6 East

Gila and Salt River Meridian  
in Arizona, executed by  
Washington O Secor

U. S. Deputy Surveyor, under his contract dated

June 18<sup>th</sup> 1889.

having been critically examined, the necessary corrections and explanations made, the said Field Notes and the surveys they describe are hereby approved.

Papal Johnson  
U. S. Surveyor-General  
for the Territory of Arizona.