

Recd April 10 1892 Book 1

Command. Platted - x 2  
To Gen L. O. May 27, 1892

16 12

Survey approved

August 31, 1892

4-671

1612

BOOK 1612

FIELD NOTES

GENERAL LAND OFFICE

Exteriors  
T6'S. R. 5 W.

By Daniel Drummond, U.S. B.S.

UNDER CONTRACT, N<sup>o</sup> 19.

Dated June 13, 1891.

Survey Commenced Oct. 16/91.

Survey Completed Oct. 13/91.

P. 1

## Index.

T 6 S. R 5 W

	Page	
West Body		1
East "	"	14
South "	"	27

(4-674.)

Township 6 South R. 5 West,

BOOK 1612

1	1	6	5	4	3	2	1	14
12	3	7	8	9	10	11	12	16
13	5	18	17	16	15	14	13	18
24	7	19	20	21	22	23	24	20
25	9	30	29	28	27	26	25	22
36	11	31	32	33	34	35	36	24
		27	29	31	33	35	37	
		(1192-10 M.)		6-389				
		6	5	4	3	2	1	

Exterior Boundaries T. 6. S. R. 3. W.

I set my instrument over the Standard Cor. to Tps. 5. S. R. 5. and 6. W. and deflect from the true meridian heretofore established, the angle  $89^{\circ}42'$  towards the East, Thence I run on the 1<sup>st</sup> Standard par. South  $N 89^{\circ}42' E$ .

Var.  $13^{\circ}4' E$ .

11.56 chains to a point where I establish the Closing Cor. to Tps. 6 S. R. 5 and 6 W. by setting a post  $4\frac{1}{2}$  ft. long 4 ins. square with marked stone 12 ins. in the ground, for Closing Cor. to Tps. 6. S. R. 5 and 6. W.



## Exterior Boundaries T. 6. S. R. 5. W.

Marked.

C. C. Sp. 6. S. on S

R. 5. W. Sec 6 on E and

R. 6. W. Sec. 1 on W faces. with  
6 notches on S. E. and W faces

dug pits 24x18x12 ins.

Crosswise on each line

S. E. and W of post. 6 feet.

dist. and raised a mound

of earth 2 1/2 ft. high 5 ft  
base. around post.

## Exterior Cadastrus T. 6, S. R. 5, W.

chains Thence I run  
South, on a true meridian  
bet. Secs. 1 and 6.

Var.  $13^{\circ}4' E$

40.00 Set a post. 4 ft long, 4  
ins. square, with marked  
stone 12 ins. in the  
ground, for  $1/4$  Sec. Cor.  
Marked  $1/4$  S on W face  
dug pits  $18 \times 18 \times 12$  ins.  
N and S. of post.  $5\frac{1}{2}$  ft.  
dist. and raised a mound  
of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft.  
base around post;

46.45 Wagon road from Gila Bend  
to Yuma running North-  
easterly and Southwesterly

67.30 Southern Pacific Railroad  
running Northeastly and  
Southwesterly

## Exterior Boundaries T. 6. S. R. 5. W.

chains  
20.00

Set a post.  $4\frac{1}{2}$  ft long. 4  
ins. square. with marked  
stone 12 ins. in the ground  
for Cor. to Secs. 1. 6. and 12  
marked T. 6. S. Sec. 6 on N. E.  
R. 5 W Sec. 7 on S. E.  
Sec 12 on S. W. and  
Sec. 1 on N. W. faces  
with 1 notch on N and  
5 notches on S Edges.  
dug pits  $18 \times 18 \times 12$  ins.  
in each Sec.  $5\frac{1}{2}$  ft. dist.  
and raised a mound of  
earth 2 ft high  $4\frac{1}{2}$  ft.  
base. around post.

Layd level.

Soil. Sandy loam 1<sup>st</sup> rate.

No timber.



## Exterior Boundaries T. 6. S. R. 5. W.

Chains Thence I run  
South, bet. Secs. 7<sup>and</sup> 12  
Var.  $13^{\circ} 4' E$

40.00 Set a post, 4 ft long, 4  
ins. square, with marked  
stone 12 ins. in the ground  
for  $\frac{1}{4}$  Sec Cor. marked  
 $\frac{1}{4}$  S on W face, dug  
pits  $18 \times 18 \times 12$  ins. N and S  
of post,  $5\frac{1}{2}$  ft dist. and  
raised a mound of earth  
 $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft base  
around post.

80.00 Set a post,  $4\frac{1}{2}$  ft long 4  
ins square, with marked  
stone 12 ins. in the ground  
for Cor to Secs. 7, 12, 13, & 18  
marked Sp. 6. S. Sec. 7 on N.E.,  
R. 5. W. Sec. 18 on S.E.,  
Sec. 13 on S.W., and



## Exterior Boundaries T.6.S., R.5.W.

chains Sec. 12 on NW faces  
 with 2 notches on N and  
 4 notches on S edges.  
 dug pits 18x18x12 ins.  
 in each sec. 5 1/2 ft. dist.  
 and raised a mound of  
 earth 2 feet high 4 1/2 ft  
 base, around post. —

Land level.

Soil Sandy loam 1:2<sup>21</sup> ratio  
 No timber

## Exterior Boundaries T. 6. S. R. 5. W.

Chains Thence Iron.

South 6th Secs. 13 and 18.

Var.  $13^{\circ} 4' E$ 

40.00 Set a post, 4 ft long, 4 ins. square, with marked stone 12 ins. in the ground for  $\frac{1}{4}$  Sec. Cor. Marked  $\frac{1}{4}$  S on W face. dug pits  $18 \times 18 \times 12$  ins. N and S of post,  $5\frac{1}{2}$  ft dist. and raised a mound of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft base around post.

80.00 Set a post  $4\frac{1}{2}$  ft long 4 ins. square, with marked stone 12 ins. in the ground for Cor. to Secs. 13, 18, 19 and 24 Marked Sp. 6. S. Sec. 18 on N. E. R 5 W Sec. 19 on S. E. R 6 W Sec. 24 on S. W. and

Exterior Boundaries T. 6. S. R. 5. W.

chains Sec. 13 on N.W. faces.  
 with 3 notches on N.E. S. edges  
 dug pits 18x18x12 ins. in  
 each sec. 5 1/2 ft dist. and  
 raised a mound of earth  
 2 ft high. 4 1/2 ft. base  
 around post.

Land level

Soil. Sandy loam. 1<sup>st</sup> rate

No timber

## Exterior Boundaries T. 6. S. R. 5. W.

Chains Thence I run.

South. bet. Secs. 19 and 24.

Var.  $13^{\circ} 4' E$ 

40.00 Set a post, 4 ft long 4 ins. square. with marked stone 12 ins. in the ground for  $\frac{1}{4}$  sec. Cor. marked  $\frac{1}{4}$  S. on W face. dug pits  $18 \times 18 \times 12$  ins. N and S of post,  $5\frac{1}{2}$  ft. dist. and raised a mound of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base around post.

80.00 Set a post,  $4\frac{1}{2}$  ft long 4 ins. square. with marked stone 12 ins. in the ground for Cor. to Secs. 19, 24, 25<sup>30</sup> Marked in T. 6. S. Sec 19 on N. E. R. 5. W. Sec 30 on S. E. R. 6. W. Sec 25 on S. W. and



Exterior Sandaries T. S. R. 5. 77.

chains Sec. 24 on N. W. faces,  
with 4 notches on N and  
2 notches on S edges,  
dug pits 18x18x12 ins.  
in each sec. 5 1/2 ft dist.  
and raised a mound of  
earth 2 ft high 4 1/2 ft.  
base around post.

Land, level,  
Soil, sandy & gravel, 2<sup>d</sup> rate  
No timber.

## Exterior Boundaries T.6.S.R.5.W.

Chains Thence I run

South. bet. Secs. 25<sup>th</sup> and 30.Var.  $13^{\circ}4'E$ 

40.00 Set a post, 4 ft long 4 ins. square, with marked stone 12 ins. in the ground for  $\frac{1}{4}$  sec. Cor. marked in S on N face. dug pits  $18 \times 18 \times 12$  ins. N and S of post,  $5\frac{1}{2}$  ft. dist, and raised a mound of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft base around post.

68.70 Wash. 10 lbs wide course N.W.

80.00 Set a granite stone  $20 \times 10 \times 3$  ins. 15 ins. in the ground, for Cor to Secs 25, 30, 31, and 36. Marked with 5 notches on N and 1 notch on S edges,

Exterior Boundaries N. E. S. W.

dug pits 18 X 18 X 12 ins.  
in each sec. 5 1/2 ft.

dist. and raised a mound  
of earth 2 feet high 4 1/2  
ft base. alongside

Layd. level

Soil sandy loam 1<sup>st</sup> rate

No timber.

## Exterior Boundaries T. 6. S. R. 5. W.

Chains Thence Iron

South, bet. Secs. 31 and 36.

Var.  $13^{\circ} 4' E$ 

40.00 Set a post 4 ft long, 4  
 ins. square, with marked  
 stone 12 ins. in the ground  
 for  $\frac{1}{4}$  Sec. Cor. marked  
 $\frac{1}{4}$  S on W face. dug pit's  
 18x18x12 ins. N and S of  
 post. 5 ft. dist. and  
 raised a mound of earth  
 $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base  
 around post

80.00 Set a post  $4\frac{1}{2}$  ft long  
 4 ins square, with marked  
 stone 12 ins. in the ground  
 for Cor. to Tps 6 and 7. S.  
 R. 5 and 6 W. marked  
 Tp 6. S. R. 5 W Sec. 31 on N. E.  
 Tp 7. S. R. 5 W Sec. 6 on S. E.



## Exterior Boundaries T. 6 S. R. 5 W.

Sp. 7 S. R 6 W Sec. 1 on S. W. <sup>4th</sup>

Sp 6 S. R 6 W Sec 36 on N. W.

faces. with 6 notches on each edge. dug pits 24 x 18 x 12 ins. lengthwise on each line N. S. E and W of post. 6 ft dist and raised a mound of earth 2 1/2 ft high. 5 ft base around post. —

From which

A Mesquite 4 ins. diam. bears N 13° 45' W 162 links dist.

Marked Sp. 6 S. R 6 W Sec 36. B. T.

A Mesquite 6 ins. diam.

bears N 3° E 174 links dist.

Marked Sp. 6 S. R 5 W Sec. 31. B. T.

Level level.

Soil Sandy loam

Timber Mesquite

Oct. 16. 1891.

## Exterior Boundaries T. 6. S. R. 5. W.

chains I now return to the Standard Cor. to Tps. 5. S. R. 4. and 5. W. as recently established by me. and run  $N 89^{\circ} 56' E$  on the 1<sup>st</sup> Standard par. South. 9. 26 chains to a point where I establish the closing Cor. to Tps. 6. S. R. 4. and 5. W. by setting a post.  $4\frac{1}{2}$  ft long 4 ins. square. with marked stone 12 ins. in the ground. for closing Cor. as described above —

Marked

C. C. T. 6. S. on S.

R 4 W Sec 6 on E. and

R 5 W Sec. 1 on W faces

with 6 notches on S. E. & W.

## Exterior Boundaries T. 6. S. R. 5. W.

chains faces, dug pits 24x18x12 ins  
 crosswise on each line S, E,  
 and W of post, 6 ft. dist,  
 and raised a mound of  
 earth  $2\frac{1}{2}$  ft high 5 ft. base  
 around post.

Thence I run

South, on a true meridian  
 bet. Secs. 1 and 6.

Var.  $13^{\circ} 4' E$

24.10 Wash 15 lks wide Course N.W.

40.00 Set a post, 4 ft. long, 4 ins.  
 square, with marked stone  
 12 ins. in the ground, for  
 $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  S.  
 on W face, dug pits  
 18x18x12 ins. N and S of  
 post,  $5\frac{1}{2}$  ft. dist, and  
 raised a mound of earth  
 $1\frac{1}{2}$  ft. high  $3\frac{1}{2}$  ft. base



## Exterior Boundaries T. 6. S. R. 5. W.

Chains Around Post.

80.00 Set a post  $4\frac{1}{2}$  ft. long  
 4 ins. square, with marked  
 stone 12 ins. in the ground  
 for Cor. to Secs. 1, 6, 7<sup>th</sup> and 12.  
 Marked -

T. 6. S. Sec. 6 on N.E.

R 4 W Sec. 7 on S.E.

R 5 W Sec. 12 on S.W. <sup>4th</sup>

Sec. 1 on N.W. <sup>face</sup> with 1

notch on north. and 5 notches

on S edges. dug pits

$18 \times 18 \times 12$  in each sec.

$5\frac{1}{2}$  ft. from post, and  
 raised a mound of earth  
 2 ft high.  $4\frac{1}{2}$  ft base  
 around post.

Land level

Soil. Sandy loam 1<sup>st</sup> rate

Timber. Scattering Palo Verde



## Exterior Boundaries T. 6. S. R. 5. W.

Thence I run  
South. bet. Secs. 7 and 12.  
Var  $13^{\circ} 4' E$

40.00 Set a post. 4 ft. long. 4  
ins. square. with marked  
stone. 12 ins. in the ground  
for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$   
S. on W face. dug pits  
~~18x18x12~~ 12 ins. N. Part S.  
of post.  $5\frac{1}{2}$  ft. dist.  
and raised a mound of  
earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft.  
base. around post.

77.10 Wash 10 lks. wide. Course NW.

80.00 Set a post.  $4\frac{1}{2}$  ft. long. 4  
ins. square. with marked  
stone 12 ins. in the ground  
for Cor. to Secs. 7, 12, 13, & 18  
Marked  
T. 6. S. Sec. 7 on N.E.

## Exterior Boundaries T. 6. S. R. 5. W.

chain R. 4 W. Sec. 18 on S.E.  
 R. 5 W. Sec. 13 on S.W. and  
 Sec. 12 on N.W. faces  
 with 2 notches on N and 4  
 notches on S edges dug  
 pits 18x18x12 in each.  
 Sec. 5 1/2 ft. dist. and raised  
 a mound of earth 2 ft high  
 4 1/2 ft. base. around post.

Land level.

Soil. Sandy loam 1<sup>st</sup> rate  
 Timber. Scattering Palo Verde

---

## Exterior Boundaries T. 6. S. R. 5. W.

Chains Thence I run

South, bet. Secs. 13. and 18.

Var.  $13^{\circ} 4' E$ 

40.00 Set a granite stone  $18 \times 6 \times 5$  ins. 12 ins. in the ground. for.  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  on W face, dug pits  $18 \times 18 \times 12$  ins. N. & S. of stone  $5\frac{1}{2}$  ft. dist. and raised a mound of earth  $1\frac{1}{2}$  ft. high.  $3\frac{1}{2}$  ft. base alongside

80.00 Set a post,  $4\frac{1}{2}$  ft. long. 4 ins. square. with marked stone 12 ins. in the ground for. Cor. to Secs. 13, 18, 19 and 24  
Marked -

Sp. 6. S. Sec. 18 on N.E.

R 4 W Sec. 19 on S.E.

R 5 W Sec. 24 on S.W. and



## Exterior Boundaries T. 6. S. R. 5. W.

Sec. 13 on N.W. faces, with  
3 notches on N.E.S. edges  
dug pits  $18 \times 18 \times 12$  ins.  
in each sec.  $5\frac{1}{2}$  ft. dist.  
and raised a mound of  
earth 2 ft high  $4\frac{1}{2}$  ft base  
around post.

Land level.

Soil. Sandy loam 1<sup>st</sup> rate  
Timber. Scattering Mesquite

---

## Exterior Boundaries T. 6. S. R. 5. W.

chains Thence I run.

South. bet. Secs. 19 and 24.

Var.  $13^{\circ} 4' E$ 

40.00 Set a post, 4 ft. long, 4 ins. square, with <sup>marked</sup> stone, 12 ins. in the ground for  $\frac{1}{4}$  sec. Cor. marked  $\frac{1}{4}$  S. on W face dug pits  $18 \times 18 \times 12$  ins. N & S of post,  $5\frac{1}{2}$  ft. dist, and raised a mound of earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base around post.

80.00 Set a post,  $4\frac{1}{2}$  ft. long, 4 ins. square, with marked stone, 12 ins. in the ground for Cor. to Secs. 19, 24, 25 & 30. Marked —

Sp. 6. S. Sec. 19 on N.E.

R 4 W Sec 30. on S.E.

R 5 W Sec 25 on S.W., and

## Exterior Boundaries J. G. S. Q. 5. W.

Sec. 24 on N. W. faces. with  
4 notches on N and 2 notches  
on S edges. dug pits  
18x18x12 ins. in each sec.  
5 1/2 ft. dist. and raised a  
mound of earth. 2 ft high. 4 1/2  
ft. base. around post.

Land. level.

Soil. Sandy loam. 1<sup>st</sup> rate  
Timber. Scattering mesquite



## Exterior Boundaries T. 6. S. R. 5. W.

Thence I run

South. bet. Secs. 25<sup>th</sup> and 30.

Var.  $13^{\circ} 4' E$ .

40.00 Set a post, 4 ft. long, 4 ins. square, with marked stone 12 ins. in the ground, for  $1/4$  Sec. Cor. Marked  $1/4$  S. on W face, dug pits  $18 \times 18 \times 12$  ins. N<sup>th</sup> and S of post,  $5\frac{1}{2}$  ft. dist. and raised a mound of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft base. Around post.

80.00 Set a sandstone  $20 \times 10 \times 4$  ins. 15 ins. in the ground for Cor to Secs. 25, 30, 31<sup>st</sup> and 36. Marked with 1 notch on S. and 5 notches on N faces, dug pits  $18 \times 18 \times 12$  ins. in each sec.  $5\frac{1}{2}$  ft. dist. and raised a mound of earth

Exterior Boundaries I. G. S. R. S. W.

2 ft high, 4 1/2 ft base  
Alongside

Land level  
Soil. Sandy loam 1<sup>st</sup> rate  
No. Timber.

## Exterior Boundaries J. G. J. R. S. W.

- chains Thence I run  
 South. bet. Secs 31 and 36.  
 Var.  $13^{\circ} 4' E$ .
- 13.15 Wash. 70 lks wide Course NW.  
 40.00 Set. a Stone (granite)  $16 \times 10$   
 $\times 5$  ins. 12 ins. in the ground  
 for.  $\frac{1}{4}$  Sec. Cor. Marked  $\frac{1}{4}$  on  
 N face. dug pits.  $18 \times 18 \times 12$   
 ins. N. & S. of Stone  $5\frac{1}{2}$  ft.  
 dist. and raised a mound  
 of earth  $1\frac{1}{2}$  ft. high  $3\frac{1}{2}$  ft.  
 base. alongside
- 80.00 Set. a post.  $4\frac{1}{2}$  ft. long. 4  
 ins. square. with marked  
 Stone 12 ins. in the ground  
 for. Cor. to Sp 6 and 7 S. R. S.  
 4 and 5. W. Marked -  
 Sp. 6. S. Sec. 31 on N.E.  
 Sp 7 S R. 4. W. Sec 6 on S.E.  
 R. 5 W Sec. 1 on S.W. and



## Exterior Boundaries T. 6. S. R. 5. W.

T. 6. S. R. 5. W. Sec 36 on N. W. face  
 with 6 notches on each edge  
 deep pits 24 x 18 x 12<sup>ins.</sup> length-  
 wise on each line N. S. E. + W.  
 of post, 6 ft. dist. and  
 raised a mound of earth  
 2 1/2 ft. high 5 ft. base  
 around post,  
 from which

A Palo Verde 8 ins. diam.  
 bears N 30° W. 100 links dist  
 marked T. 6. S. R. 5. W. Sec 36. B. 1.  
 An Iron Wood 4 ins. diam.  
 bears S 6° 30' E 320 links dist.  
 marked T. 7. S. R. 4. W. Sec 6. B. 1.

Land level.

Soil. Sandy loam. 1<sup>st</sup> rate

Timber Mesquite + Palo Verde

Oct. 17. 1891.

## Exterior Boundaries T. 6. S. R. 5. W.

chains Thence I run

West on a random line  
on the South boundary  
of T. 6. S. R. 5. W. Setting  
temporary mile and  
half mile Corners.

Variation  $13^{\circ}4'E$

and at 480.20 chains  
Intersect the West. bdy  
of the Township 265  
links North of the Cor.  
to Tps 6<sup>and</sup> 7. S. R. 5<sup>and</sup> 6 W.  
The Correction for the  
true line will therefore  
be 44 links South, and  
20 links East. per mile  
and its course will be  
 $N 89^{\circ}41'E$  from the Cor.  
to Tps 6<sup>+</sup> 7. S. R. 5<sup>+</sup> 6 W as  
recently established by me

## Exterior Boundary T.6.S.R.5.W.

chains Thence I run

N  $89^{\circ}41'E$  bet Secs. 6<sup>and</sup> 31.Var.  $13^{\circ}4'E$ 

40.20 Set a stone (granite)  $24 \times 10 \times 4$  ins. 18 ins. in the ground for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  on N face, <sup>4</sup> dug pits  $18 \times 18 \times 12$  ins. E. & W. of stone  $5\frac{1}{2}$  ft. dist. and raised a mound of earth  $1\frac{1}{2}$  ft. high.  $3\frac{1}{2}$  ft. base alongside. -

80.20 Set a post.  $4\frac{1}{2}$  ft. long. 4 ins. square. with marked stone 12 ins. in the ground for Cor. to Secs. 5. 6. 31 + 32. Marked -

Sp. 6 S. Sec 32 on N.E.

R 5 W Sec. 5 on S.E.

Sp. 7 S. Sec 6 on S.W. <sup>and</sup>



Exterior Boundaries T. 6. S. R. 5. W.

chains

Sec. 31 on N.W. faces. with  
1 notch on W and 5 notches  
on E edges. dug pits. 18x  
18x12 ins. in each sec.  
5 1/2 ft. dist. and raised a  
mound of earth 2 ft high  
4 1/2 ft base. around post.

Land level.

Soil. Sandy loam 1<sup>st</sup> rate

Timber Scattering Mesquite

## Exterior Boundary T.C.S.R. 5, 7.

chain Thence I run

N  $89^{\circ} 41' E$  bet. Secs. 5<sup>th</sup> & 32.Var.  $13^{\circ} 4' E$ 

39.80 Wash. 50 lks. wide Course N.W.

40.00 paint in Wash. I set a  
Sandstone  $16 \times 10 \times 4$  ins.30 lks. west. 11 ins. in the  
ground for.  $\frac{1}{4}$  sec. Cor. Marked  
W.C.  $\frac{1}{4}$  on N face. dug pits<sup>5 1/2 ft. dist</sup>  
18 x 18 x 12 ins. E & W of Stone  
and raised a mound of earth  
 $1\frac{1}{2}$  ft. high.  $3\frac{1}{2}$  ft base  
alongside.80.00 Set. a granite Stone.  $20 \times$   
 $8 \times 4$  ins. 15 ins. in the  
ground. for Cor to Secs.  
4, 5, 32<sup>nd</sup> & 33. Marked with  
2 notches on W<sup>nd</sup> & 4 notches  
on east. edges. dug pits  
 $18 \times 18 \times 12$  ins. in each

## Exterior Boundaries T. 6. S. R. 5. W.

chains Sec. 5  $\frac{1}{2}$  ft. dist. and  
raised a mound of earth  
2 ft high.  $4\frac{1}{2}$  ft. base  
alongside

Land level  
Soil. Sandy loam 1<sup>st</sup> rd  
Timber. Scattering mesquite



## Exterior Boundaries T. 6. S. R. 5. W.

chain Thence I run

N  $89^{\circ} 41' E$  bet. Secs. 4<sup>th</sup> and 33

Var.  $13^{\circ} 4' E$

14.35 Wagon road from Gila Bend  
to Gunsight mine. Running  
North easterly and Southwesterly.

39.30 Wash 50 lks. wide Course N. W.

40.00 Set a post, 4 ft. long, 4 ins  
square, with marked stone  
12 ins. in the ground. for  
 $\frac{1}{4}$  Sec Cor. Marked  $\frac{1}{4}$  S.  
on N face. dug pits  $18 \times$   
 $18 \times 12$  ins. east & west of  
post.  $5\frac{1}{2}$  ft. dist. and  
raised a mound of earth  
 $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base,  
around post.

80.00 Set a Granite Stone  
 $20 \times 9 \times 4$  ins., 15 ins. in  
the ground. for Cor to

## Exterior Boundaries N. 6. A. R. 5. W.

chains Secs. 3, 4, 33, and 34. marked  
with 3 notches on E. & W.  
edges. dug pits 18x18x12  
ins. in each. sec. 5 1/2 ft.  
dist. and raised a mound  
of earth 2 ft. high 4 1/2  
ft. base. alongside

Lead level.

Soil. Sandy loam 1<sup>st</sup> rate  
Timber Scattering mesquite

## Exterior Boundaries T. 6 S. R. 5 W.

- chain Thence I run  
 $N 89^{\circ} 41' E$  bet Secs. 3 and 34  
 Var.  $13^{\circ} 4' E$
- 17.30 Wash 40 lks wide Course N.W.  
 39.50 Wash 30 " " " N.W.  
 40.00 Set. a post, 4 ft. long 4 ins  
 Square, with marked Stone  
 12 ins. in the ground for  $\frac{1}{4}$   
 Sec. Cor. marked  $\frac{1}{4}$  S on  
 N face, dug pits  $18 \times 18 \times 12$   
 ins. E. & W. of post,  $5\frac{1}{2}$  ft.  
 dist. and raised a mound  
 of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft.  
 base around post.
- 80.00 Set. a post,  $4\frac{1}{2}$  ft long 4  
 ins. Square, with marked  
 Stone 12 ins. in the ground  
 for Cor. to Secs. 2, 3, 34 & 35  
 Marked.  
 T. 6 S. Sec. 35 on N.E.



## Exterior Boundaries T. 6. S. R. 5. W.

chains R. 5. W. Sec. 2 on S. E.

Sp. 7. S. Sec. 3 on S. W. and

Sec. 34 on N. W. faces. with  
4 notches on W. and 2 notches  
on E edges. dug pits 18x18  
x 12 ins. in each Sec. 5 1/2  
ft dist. and raised a mud.  
of earth 2 ft. high 4 1/2 ft.  
around post.

Land level.

Soil. Sandy loam 1<sup>st</sup> race

Timber Scattering Mesquite

35,

BOOK 1612  
 Exterior Boundaries T. 6 S. R. 5 W.

chain Thence I run  
 N  $89^{\circ}41'E$ . bet. Secs. 2<sup>nd</sup> and 35  
 Var.  $13^{\circ}4'E$

17.40 Wash 40 lks wide Course N.W.

20.60 Wash 60. " " " N.W.

40.00 Set a post, 4 ft. long, 4 ins. square, with marked stone 12 ins. in the ground, for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}S$  on N face. dug pits  $18 \times 18 \times 12$  ins. E & W of post,  $5\frac{1}{2}$  ft. dist. and raised a mound of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft. base around post.

80.00 Set a post,  $4\frac{1}{2}$  ft. long, 4 ins. square, with marked stone, 12 ins. in the ground for Cor. to Secs. 1, 2, 35 and 36  
 Marked -

## Exterior Boundaries T. 6. S. R. 5. W.

chain Sp. 6. S. Sec. 36 on N.E.  
 R. 5. W. Sec. 1 on S.E.  
 Sp. 7. S. Sec. 2 on S.W. and  
 Sec. 35 on N.W. faces. with  
 5 notches on W and 1 notch  
 on E edges. dug pits 18 X  
 18 X 12 ins. in each sec.  
 5 1/2 ft. dist. and raised a  
 mound of earth 2 ft. high.  
 4 1/2 ft. base. Around post.

Land. level.

Soil. Sandy loam 1<sup>st</sup> rate  
 Timber. Scattering Mesquite



## Exterior Boundaries T. 6. S. R. 5. W.

chains Thence I run

N  $89^{\circ} 41' E$  bet. Secs. 1<sup>st</sup> & 36.

Var.  $13^{\circ} 4' E$ .

40.00 Set a granite Stone  $16 \times 10 \times 4$   
ins. 19 ins. in the ground. for  
 $\frac{1}{4}$  Sec. Cor. Marked  $\frac{1}{4}$  on N  
face. dug pits  $18 \times 18 \times 12$   
ins. E. & W. of Stone  $5 \frac{1}{2}$   
ft. dist. and raised a md.  
of earth  $1 \frac{1}{2}$  ft. high.  $3 \frac{1}{2}$  ft.  
base. alongside

75.30 Wash. 15 lbs wide Course N.W.

80.00 to the Cor. of Sp. 6.  $\frac{3}{4}$  7. S.  
Rs 4<sup>th</sup> & 5. W. as recently  
established by me

Land level.

Soil Sandy loam 1<sup>st</sup> rate

Timber Scattering Mesquite

Oct. 19. 1891.

Exterior Boundaries I. G. S. R. S. W.

Exterors T. G. S. R. S. W.

Latitudes departures,

LINE DESIGNA.	TRUE BEARING	DISTANCE
E. BOUNDARY	SOUTH	Chs. 480.
S "	S 89° 41' W	480.20
W "	NORTH	480.
N "	N 89° 42' E	479.77

CONVERGENCY.

ERROR IN LATITUDE<sup>2</sup><sub>nd</sub> DEPARTURE



Exteriors I. 6, S, R. S. E.

and Closing errors

Latitudes		Departures	
N.	S.	E.	W.
	480.00		
	2.65		480.20
480.00			
2.50		479.77	
482.50	482.65	480.24	480.20
	482.50	480.20	
	.15	.04	

## BOOK 1612

U. S. Surveyor-General's Office,

TUCSON, A. T., *May 26* 1882

The foregoing Field Notes, of the Surveys of  
the Extension of

*T. 6 S. R. 5 W.*

Gila and Salt River Meridian

*Arizona* executed by  
*David Drummond*

U. S. Deputy Surveyor, under his contract dated

*June 13<sup>th</sup> 1891*

having been critically examined, the necessary corrections and explanations made, the said Field Notes and the surveys they describe are hereby approved.

*Raphael Johnson*

U. S. Surveyor-General  
for the Territory of Arizona.