

1942

Arizona

BOOK 1942

Field Notes of

October Series of Tps. 10 North  
Ranges 5 and 6. Tps. 11 North Range  
5 N. Tps. 14 North, Ranges 5, 6, 7  
and 8. Tps. 15 North Ranges 5, 6 and  
7 West of the Navajo Special Meridian  
in the Territory of Arizona.

Surveyed by Edw. A. Darling, U.S.  
Surveyor, under his contract with  
the Hon. Jas. S. Wilson, Commissioner  
of the General Land Office, dated  
Washington D.C. April 29, 1869.

1942

1942

1918

1918

1918

1918

1918

1918

Utah ✓ ✓

Colorado ✓

Utah ✓ ✓												Colorado ✓																																			
31	32	33	34	35	36	37	38	39	40	41	42	31	32	33	34	35	36	37	38	39	40	41																									
6	5	4	3	2	1	6	5	4	3	2	1	6	5	4	3	2	1	6	5	4	3	2	1																								
T.M.N. R.8.W. ✓						T.I.A.N. R.7.W. ✓						T.I.A.N. R.6.W. ✓						T.I.A.N. R.5.W. ✓																													
133 618						132 718						131 818						130 918																													
243 619						242 619						241 819						240 919																													
253 630						252 630						251 930						250 930																													
31	32	33	34	35	36	37	38	39	40	41	42	31	32	33	34	35	36	37	38	39	40	41																									
6	5	4	3	2	1	6	5	4	3	2	1	6	5	4	3	2	1	6	5	4	3	2	1																								
T.I.O.N. R.8.W. ✓												T.I.O.N. R.7.W. ✓												T.I.O.N. R.6.W. ✓												T.I.O.N. R.5.W. ✓											
13 318												13 318												13 318												13 318											
24 419												24 419												24 419												24 419											
25 430												25 430												25 730												25 730											
36 431												36 431												36 631												36 631											
14 14												14 14												14 14												14 14											
7 126												7 126												7 126												7 126											
12 127												12 127												12 127												12 127											
13 128												13 128												13 128												13 128											
24 129												24 129												24 129												24 129											
25 130												25 130												25 130												25 130											
36 131												36 131												36 131												36 131											
1 26												1 26												1 26												1 26											
12 37												12 37												12 37												12 37											
13 318												13 318												13 318												13 318											
24 419												24 419												24 419												24 419											
25 430												25 430												25 730												25 730											
36 431												36 431												36 631												36 631											

M. J. ...



BOOK 1942

Arizona

~~UT 2020~~  
 Field notes of the Exterior Lines  
 of Township No. 10 N. R. 6. West  
 of the Navajo Special Meridian.

BOOK 1942

As only a portion of the South  
 Boundary of Township 10  
 North, Range 6 West, is  
 practicable to run on ac-  
 count of the mountainous  
 country, I run west on  
 South Boundary of sec.  
 26, from corner to Township  
 9 and 10 North, Ranges



Chains  
BOOK 1942

5 and 6 West, between Town-  
ships 9 and 10 North, Range  
6 West.

Var.  $14^{\circ}10' E$ .

40.00 Set sand stone,  $16 \times 12 \times 4$ , for  
 $\frac{1}{4}$  sec. corner as per in-  
structions.

80.00 Set sand stone,  $18 \times 10 \times 3$ ,  
marked as per instructions,  
for the corner to sections 1, 2,  
35 and 36.

Surface rolling. Soil  $2^{\frac{1}{2}}$  rate.  
Prairie

Balance of South Boundary  
of Township 10 North, Range  
6 West, broken and moun-  
tainous. I therefore did  
not extend it any farther west,  
December 9<sup>th</sup> 1869.

In order to run the West Bound-  
ary of Township No. 10 North, Range  
6 West, I commenced at  
the Standard corner to Town-  
ship 11 North, Ranges 6 and  
7 West and ran East 16.20 chs,  
and set closing corner to  
Township 10 North, Ranges 6  
and 7 West, a sand stone,  
 $18 \times 12 \times 4$ , built mound of stone  
around same.

Thence South between  
Ranges 6 and 7 West, and  
secs. 1 and 6, Var.  $14^{\circ}10' E$ .

40.00 Set sand stone,  $20 \times 10 \times 4$ , for  $\frac{1}{4}$   
sec. corner, as per instructions,

80.00 Set sand stone,  $28 \times 24 \times 2$ , marked  
as per instructions, for the  
corner to sections 1, 6, 7 and 12,  
Surface broken, scattering cedar

Chain

and Pinon, 3<sup>d</sup> rate, Soil 3<sup>d</sup> rate.

South between Secs. 7 and 12,  
Var. 14° 10' E.

- 4 000 Set sand stone, 18 X 10 X 3. for 1/4 sec. corner, as per instructions,
- 80 000 Set sand stone, 16 X 16 X 6. marked as per instructions, for the corner to sections 7, 12, 13 + 18, surface broken, scattering Pinon and cedar, 2<sup>d</sup> rate, Soil 3<sup>d</sup> rate.

South between Secs. 13 and 18,  
Var. 14° 10' E.

- 24 000 Leave scattering Pinon and cedar timber, bears East and West,
- 4 000 Set charred post, built mound and dug pits, for 1/4 sec. corner, as per instructions,
- 4 200 Creek, 20 lks wide, course East,
- 80 000 Deposited marked stone set charred post, marked, built mound and dug pits, as per instructions, for the corner to secs. 13, 18, 19 and 24, surface gently rolling, The greater part of this mile is prairie. Soil 1<sup>st</sup> rate.

South between Secs. 19 and 24,  
Var. 14° 10' E.

- 4 000 Set charred post, built mound and dug pits for 1/4 sec. corner, as per instructions,
- 65 400 Enter scattering Pinon and cedar timber, bears E + West,
- 80 000 Set sand stone 16 X 10 X 4. marked as per instructions, for the

Chains

BOOK 1942

corner to secs. 19, 24, 25 and 30,  
Surface level. The greater portion  
of this mile is prairie, balance  
sparsely covered with Pinon  
and cedar, 3/4 rate, Soil 1/4 rate.

South between secs. 25 and 30,  
Var. 14° 10' East,

40.00

Set sand stone, 28 X 10 X 3, for 1/4  
sec. corner, as per instructions

80.00

Set sand stone, 20 X 12 X 3, marked  
as per instructions, for the corner  
to secs. 25, 30, 31 and 36,  
Surface broken, scattering Pinon  
and cedar, 3/4 rate, Soil 3/4 rate.

South between Secs. 31 and 36,

Var. 14° 10' E.

40.00

Set sand stone, 14 X 12 X 3, for 1/4  
sec. corner, as per instructions,  
Place for Township corner in  
mountains, impracticable  
to establish same,  
Surface broken, Scattering Pinon  
and cedar, 3/4 rate, Soil 3/4 rate.

General Description.

This Township is generally  
prairie, there being but a small  
portion covered with scattering  
Pinon and cedar, 3/4 rate,  
Surface generally rolling.  
It is well adapted to grazing  
and large portions of it to  
farming purposes,  
Soil 2/4, 3/4 and 1/4 rate.

measuring chain compared  
with standard & found correct.



Chs. Lks

There being but one full Township in Range 5, South of the Second Standard Parallel, fit for agricultural purposes, I commenced at the corner to Townships 9 and 10 North, Ranges 4 and 5 West, and ran West on True Line, South Boundary of Township 10 North, Range 5 West as follows:

West on True Line, South Boundary of Sec. 36. Var.  $14^{\circ} 10'$  East.

6.50  
40.00  
52.00  
69.00  
80.00

Dry bed of creek, 30 lks wide, course dr.  
Set granite  $12 \times 10 \times 6$  for  $\frac{1}{4}$  Sec. cor as per instructions  
Dry bed of creek 40 lks wide course dr. E.  
Enter scattering timber, bears dr. S S.  
Set Sand Stone  $18 \times 11 \times 3$ , marked as per instructions for the corner to Sections 1, 2, 35 and 36.  
Surface level. Prairie. Soil 1st rate

West on True Line, South Boundary of Sec. 35. Var.  $14^{\circ}$  East.

40.00  
80.00

Set Sand Stone  $26 \times 24 \times 10$  for  $\frac{1}{4}$  Sec. corner as per instructions.  
Set Sand Stone  $14 \times 10 \times 4$  marked as per instructions for the corner to Secs. 2, 3, 34 and 35.  
Surface broken. Piñon and cedar timber 3rd Rate. Soil 3rd rate.

West on True Line, South Boundary of Sec. 34. Var.  $14^{\circ}$  E.

40.00  
44.60  
80.00

Set Sand Stone  $30 \times 12 \times 7$  for  $\frac{1}{4}$  Sec. corner as per instructions.  
Leave scattering Piñon and cedar 3rd rate, bears North and South  
Set Sand Stone  $16 \times 12 \times 3$ , marked as per instructions, for the corner

6 Chains  
BOOK 1942

to sections 3, 4, 33 and 34.  
Surface broken, Scattered Pinon  
and cedar, 3rd Rate, Soil 3rd rate

18.50 Nest on South Boundary of Sec. 33.  
Ta. 14° East  
31.00 Dry bed of creek, 20 links wide, course dr.  
40.00 Dry " " " 35 links wide " "  
57.00 Set Sand Stone 14 x 12 x 3 for 1/4 Sec. Corner  
80.00 as per instructions.  
Dry bed of creek 15 links wide, course dr.  
Deposited marked stone, set charred  
post, marked, built mound and dug  
pits, as per instructions for the corner  
to sections 4, 5, 32 and 33.  
Surface level. Prairie. Soil 1st rate.

40.00 Nest on True Line, South Boundary  
of Sec. 32. Ta. 14° East  
80.00 Set Sand Stone 24 x 12 x 3 for 1/4 Sec.  
corner, as per instructions.  
Set Sand Stone 16 x 14 x 3 marked  
as per instructions, for the corner to  
Secs 5, 6, 31 and 32.  
Surface rolling, Prairie  
Soil 2nd rate.

40.00 Nest on True Line South Boundary  
of Sec. 31. Ta. 14° East  
Set charred post, built mound and  
dug pits for 1/4 Sec. corner, as per in-  
structions.  
54.70 Dry bed of creek, course dr. E.  
78.00 Set Sand Stone 18 x 12 x 3 marked  
and built mound of stones as  
per instructions, for the corner to  
Townships 9 and 10 North Ranges  
5 and 6 West.

Chains.

Surface level. Prairie. Soil 1<sup>st</sup> rate.

BOOK 1942

From corner to Townships 9 and 10 N.  
Ranges 5 and 6 West.

North on West Boundary of Township  
10 North, Range 5 West. as follows:

North on West Boundary of Sec 31.  
Var. 14° East.

40.00 Set Sand Stone 16 x 14 x 5 for 1/4 Sec.  
corner, as per instructions.

80.00 Set Sand Stone, 16 x 12 x 3 marked as  
per instructions for the corner to  
Secs. 25, 30, 31 and 36.

Surface Rolling. Prairie. Soil 2<sup>d</sup> rate

North on West Boundary of Sec. 30  
Var. 14° East.

19.00 Dry bed of creek, 40 ft. wide course  
N. E.

40.00 Set charred post, built mound and  
dug pits for 1/4 Sec. corner as per  
instructions.

80.00 Deposited marked Stone, Set charred  
post, marked, built mound and dug  
pits as per instructions for corner  
to Sections 19, 24, 25 and 30.  
Surface level Prairie, Soil 1<sup>st</sup> rate.

North on West Boundary of Sec.  
19. Var. 14° 15' E.

40.00 Set Sand Stone, 14 x 10 x 5 for 1/4  
Sec. corner, as per instructions.

80.00 Deposited marked Stone, Set charred  
post, marked, built mound and  
dug pits, as per instructions, for  
the corner to Secs. 13, 18, 19 and  
24.



8	Chains	Surface rolling, Prairie Soil 1st rate
BOOK 1942	40.00 80.00	North on West Boundary of Sec. 18 Ta. 140° 15' E. Set charred post and built mound for 1/4 Sec. corner as per instructions, Set Sand Stone 14 x 12 x 3 marked as per instructions for the corner to Secs. 7, 12, 13 and 18. Surface level, Prairie, Soil 1st rate.
40.00 49.50 80.00		North on West Boundary of Sec. 7. Ta. 140° 15' E. Set Sand Stone 14 x 9 x 7 for 1/4 Sec. corner as per instructions. Prairie, 80 links wide, course N. E. Set Sand Stone 24 x 16 x 2 marked as per instructions, for the corner to Secs. 1, 6, 7 & 12. Surface gently rolling, Prairie. Soil 1st rate.
40.00 78.90		North on West Boundary of Sec. 6. Ta. 140° 15' E. Set Sand Stone 18 x 16 x 5 for 1/4 Sec. corner as per instructions. Intersect Second Standard Parallel 14.50 Chs. east of corner to Township 11 North Ranges 5 and 6 West, and set Sand Stone 15 x 12 x 3 marked "C.C" on the South for the corner to Township 10 N. Ranges 5 and 6 West. Surface broken, Prairie, Soil 3rd rate.
		General Description This Township is partly covered with scattering Pinon and cedar, 3rd rate.

but mostly prairie.  
Surface generally rolling.  
It is well adapted to agricultural purposes.  
Soil 2<sup>nd</sup> 1<sup>st</sup> and 3<sup>rd</sup> rate.

Measuring chain compared with standard  
and found correct.

Chains

From corner to Township 11 North.  
 Ranges 5 and 6 West.  
 North on West Boundary of Township  
 11, as follows

North on West Boundary of Sec. 31.  
 Var.  $14^{\circ} 20'$  E.

40.00 Set Sand Stone  $14 \times 12 \times 3$ , for  $\frac{1}{4}$  Sec. corner  
 as per instructions.

80.00 Set Sand Stone,  $16 \times 11 \times 3$ , marked as  
 per instructions, from the corner  
 to Sections 25, 30, 31 and 36.  
 Surface rolling, Prairie, Soil 2<sup>nd</sup> rate.

North on West Boundary of Sec. 30.  
 Var.  $14^{\circ} 20'$  E.

40.00 Set charred post, built mound and  
 dug pits, for  $\frac{1}{4}$  Sec. corner as per  
 instructions.

80.00 Marked surface rock, for the corner  
 to Sections 19, 24, 25, and 30, as per  
 instructions.  
 Surface gently rolling, Prairie.  
 Soil 2<sup>nd</sup> rate and 2<sup>d</sup> rate.

North on West Boundary of Sec. 19.  
 Var.  $14^{\circ} 20'$  E.

41.50 Spring Branch 20 links wide course N.E.  
 40.00 Set Sand Stone  $15 \times 12 \times 3$  for  $\frac{1}{4}$  Sec.  
 corner, as per instructions.

42.50 Spring branch, 15 links wide  
 Course N.  $10^{\circ}$  West.

80.00 Set Sand Stone,  $20 \times 12 \times 4$ .  
 marked as per instructions for  
 the corner to Secs. 13, 18, 19 and 24.  
 Surface broken, Prairie.  
 Soil 3<sup>rd</sup> rate.



<p>12 BOOK</p>	<p>Chains 1942</p>	<p>North on West Boundary of Sec. 18. Var. <math>14^{\circ} 20' E</math>. Set Sand Stone 12 x 11 x 6 for <math>\frac{1}{4}</math> Sec. corner. as per instructions. Set Sand Stone 14 x 12 x 3 marked as per instructions for the corner to Sections 7, 12, 13 and 18. Surface broken. Prairie, Soil 3<sup>rd</sup> rate.</p>
<p>40.00 64.50 80.00</p>		<p>North on West Boundary of Sec. 7. Var. <math>14^{\circ} 20' E</math>. Set Sand Stone 16 x 14 x 5 for <math>\frac{1}{4}</math> Sec. corner, as per instructions. Spring branch, 15 lks wide, course S. E. Set Sand Stone 16 x 14 x 3, marked as per instructions, for the corner to Secs. 1, 6, 7 and 12. Surface rolling, Prairie. Soil 2<sup>nd</sup> rate.</p>
<p>12.00 40.00 80.00</p>		<p>North on West Boundary of Sec. 6. Var. <math>14^{\circ} 20' E</math>. Enter scattering Pinon and cedar, bears E. and West. Set Sand Stone 14 x 12 x 3 for <math>\frac{1}{4}</math> Sec. corner as per instructions Set Sand Stone 18 x 16 x 6 marked as per instructions for the corner to Townships 11 and 12 N. Ranges 5 and 6, West. Surface rolling. Scattering Pinon and cedar. 3<sup>rd</sup> rate. Soil 2<sup>nd</sup> rate.</p>
		<p>East on Random between Townships 11 and 12, North, Range 5 West. Setting temporary half mile and mile corners at every 40 and 80 chains Va. from <math>14^{\circ} 15'</math> to <math>14^{\circ} 20'</math> East</p>

Chains

BOOK 1942

At 479.00 chains intersect Range line  
2.36 chains north of corner to Townships  
11 and 12 north, Ranges 4 and 5 West.  
Therefore the correction will be 1.00.  
Chm East and  $38\frac{1}{2}$  links S. per mile.  
Then West on True Line between  
Townships 11 and 12 north, Range 5  
West as follows:

West on True Line, South Boundary  
of Sec. 36. Var.  $13^{\circ}58' E$ .  
40.00 Set Sand Stone  $18 \times 16 \times 5$ , for  $\frac{1}{4}$  Sec. corner  
as per instructions.  
59.40 break 30 links wide, course dr. E.  
Clear water and gentle current.  
80.00 Set Sand Stone  $24 \times 12 \times 5$  marked as  
per instructions, for the corner to  
Secs. 1, 2, 35 and 36.  
Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

West on True Line South Boundary  
of Sec. 35. Var.  $13^{\circ}58' East$ .  
40.00 Set Sand Stone  $16 \times 15 \times 5$  for  $\frac{1}{4}$  Sec.  
corner as per instructions.  
80.00 Set granite  $20 \times 14 \times 5$  marked as  
per instructions, for the corner to  
Secs. 2, 3, 34 and 35.  
Surface broken, Prairie, Soil 3<sup>rd</sup> rate.

West on True Line, South Boundary of  
Sec. 34. Var.  $13^{\circ}58' E$ .  
40.00 Set Sand Stone  $14 \times 12 \times 3$  for  $\frac{1}{4}$  Sec.  
corner, as per instructions.  
80.00 Deposited marked Stone, Set charred  
post, marked, built mound and  
dug pits, as per instructions  
for corner to Secs 3, 4, 33 and 34.  
Surface rolling, Prairie, Soil 2<sup>d</sup> rate

109  
BOOK 1942  
Chs. 26  
40.00  
71.00  
80.00

West on true line South Boundary of Sec. 33.  
Va.  $14^{\circ} 03'$  East.  
Set charred post, built mound, and dug pits for  $\frac{1}{4}$  Sec. cor. as per instructions.  
Enter scattering Pinon and cedar beams E. & S. W.  
Set Sand Stone  $16 \times 14 \times 4$ , marked as per instructions, for the corner to Secs. 4, 5, 32 and 33.  
Surface rolling, mostly prairie, Soil 2<sup>nd</sup> rate.

40.00  
80.00

West on true line, South Boundary of Sec. 32.  
Va.  $14^{\circ} 03'$  East.  
Set charred post, built mound and dug pits for  $\frac{1}{4}$  Sec. cor. as per instructions.  
Set Sand Stone  $18 \times 16 \times 5$ , marked as per instructions for the corner to Secs. 5, 6, 31 and 32. Surface rolling. Scattering Pinon and cedar, 3<sup>rd</sup> rate. Soil 2<sup>nd</sup> rate.

27.50  
40.00  
79.00

West on true line, South Boundary of Sec. 31.  
Va.  $14^{\circ} 03'$  East.  
Spring branch, 20 links wide course S. E.  
Set Sand Stone  $14 \times 12 \times 4$  for  $\frac{1}{4}$  Sec. cor. as per instructions.  
Corner to Townships 11 and 12 North, Ranges 5 and 6 West.  
Surface rolling, Scattering Pinon and cedar, 3<sup>rd</sup> rate. Soil 2<sup>nd</sup> rate.

General Description  
This Township is mostly prairie. Surface generally rolling, Soil 2<sup>nd</sup> and 3<sup>rd</sup> rate and 1<sup>st</sup> rate. It is well adapted to farming and grazing purposes especially to the latter. There are a few Pinon and cedar trees in the North West portion of the Township.  
Measuring chain compared with Standard and found correct.



chains

As there are but township 14 N. and fractional Township 15 N. in Range 5 West, fit for agricultural purposes, I commenced at corner to Townships 14 and 15 North, Range 4 and 5 West, and ran West on True Line between Townships 14 and 15 North, Range 5 West, as follows.

West on True Line, South Boundary of Sec. 36. Var.  $14^{\circ} 20' E$ .

1.75  
 10.00  
 13.50  
 17.65

Edge of steep bank  
 Foot of slope, bears North and South San Juan river, course N.W.  
 Leave same, low banks, sandy bottom, swift current, clear water, and about 4 feet deep.

Groves of cottonwood and willow on West bank of river. Leave timber.

32.00  
 40.00  
 44.00  
 45.00  
 50.00

Ascend low ridge, bears N. & South.  
 Set sand stone,  $30 \times 14 \times 12$ , for  $\frac{1}{4}$  sec. corner, as per instructions.

Foot of ridge, bears North and South.  
 Leave same, 20 ft. high.

Departed marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to sections 1, 2, 35 and 36.

Surface rolling. Prairie, except along river. Soil 2<sup>d</sup> and 1<sup>st</sup> rate.

West on True Line South Boundary of Sec. 35. Var.  $14^{\circ} 20' E$ .

40.00  
 50.00

Set granite,  $16 \times 12 \times 6$ , for  $\frac{1}{4}$  sec. corner as per instructions.

Set sand stone  $20 \times 10 \times 6$ , marked as per instructions, for the cor to Secs. 2, 3, 34 and 35.

/// Field Notes of the Exterior Lines of Township 14

16 Chans  
Surface broken, Prairie, Soil 3<sup>d</sup>. rate.

BOOK 1942

5.00 Vest on True Line, South Boundary  
of Sec. 34. Var. 14° 20' E.  
Foot of Ridge.  
20.00 Summit of same, 60 feet high, bears  
North and South.  
34.00 Begin descent of ridge  
40.00 Set Sand Stone 24 x 12 x 8 for 1/4 Sec.  
corner, as per instructions.  
80.00 Set Sand Stone 30 x 10 x 6. marked as per  
instructions, for the corner to sections  
3, 4, 33 and 34.  
Surface broken, Prairie, Soil 3<sup>d</sup>. rate.

40.00 Vest on True Line, South Boundary  
of Sec. 33. Var. 14° 20' E.  
Marked Sand Stone boulder, 48 x 40 x 40  
for 1/4 Sec. corner as per instructions,  
80.00 Marked Stone 36 x 18 x 4 as per in-  
structions, for the corner to Secs  
4, 5, 32 and 33.  
Surface rolling, Prairie, Soil 2<sup>d</sup>. rate.

40.00 Vest on True Line, South Boundary  
of Sec. 32. Var. 14° 20' E.  
Set Sand Stone 18 x 12 x 4. for 1/4 Sec. cor.  
as per instructions.  
80.00 Set Sand Stone, 18 x 10 x 6. marked as  
per instructions, for the corner to Secs.  
5, 6, 31 and 32.  
Surface rolling, Prairie, Soil 2<sup>d</sup>. rate.

40.00 Vest on True Line, South Boundary  
of Sec. 31. Var. 14° 20' E.  
Set Sand Stone 14 x 12 x 4 for 1/4 Sec.

Chanis BOOK 1942

77.90 corner as per instructions.  
 Set Sand Stone, 20 x 18 x 4, marked and  
 built mound of Stone, as per instructions  
 for the corner to Townships 14 and 15 North  
 Ranges 5 and 6 West.  
 Surface rolling, Prairie. Soil 2<sup>d</sup> rate.

From corner to Townships 14 and 15  
 North, Ranges 5 and 6 West;  
 North on West Boundary of Fractional  
 Township to 15 North, Range 5 West  
 as follows:  
 North on West Boundary of Fractional  
 Sec. 31. Var. 14° 20' E.

18.00 Dry bed of creek 180 lbs wide. Course  
 East.

40.00 Set Sand Stone, 14 x 12 x 3 for 1/4 Sec. cor.  
 as per instructions.

57.60 Intersect 37<sup>th</sup> Parallel of North Latitude;  
 that being the boundary line between  
 Utah and Arizona, and also the  
 North Boundary of the Navajo Indian  
 Reservation, 30.00 chs. East of the 1st  
 mile corner, and set Sand Stone,  
 20 x 10 x 5, marked "C, C" for the  
 corner to fractional Township 15 North,  
 Ranges 5 + 6 West, as per instructions,  
 Surface rolling, Prairie. Soil 2<sup>d</sup> rate.

### General Description

This township is all Prairie, surface  
 generally rolling.  
 It is well adapted to grazing  
 purposes. Soil 2<sup>d</sup> and 3<sup>d</sup> rate.

Measuring chain compared with  
 standard and found correct.

12 Chavis

BOOK 1942

From corner to Townships 14 and 15 N. Ranges 5 and 6 West, South on True Line on West Boundary of Township 14 North, Range 5 West as follows:

40.00 South on True Line, West Boundary of Sec. 6. Var. 14° East.  
 80.00 Set Sand Stone 14 x 12 x 3 for 1/4 Sec. Corner, as per instructions.  
 80.00 Set Sand Stone 17 x 13 x 3, marked as per instructions, for the corner to sections 1, 6, 7 and 12.  
 Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

40.00 South on True Line, West Boundary of Sec. 7. Var. 14° East.  
 80.00 Set Sand Stone 14 x 12 x 4, for 1/4 Sec. corner, as per instructions.  
 80.00 Set Sand Stone, 16 x 12 x 5, marked as per instructions, for the corner to sections 7, 12, 13 and 18.  
 Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

40.00 South on True Line, West Boundary of Sec. 18. Var. 14° East.  
 80.00 Set granite, 16 x 8 x 6 for 1/4 Sec. corner, as per instructions.  
 80.00 Set Sand Stone, 18 x 14 x 3 marked per instructions for the corner to Secs. 13, 18, 19 and 24.  
 Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

40.00 South on True Line, West Boundary of Sec. 19. Var. 14° East.  
 80.00 Set Sand Stone 14 x 12 x 3 for 1/4 Sec. corner as per instructions.  
 80.00 Set Sand Stone 15 x 13 x 4, marked as per instructions for the corner to sections

chains

19, 24, 25, and 30.  
Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

BOOK 1942

40.00

South on True Line, West Boundary of Sec. 30. Var. 14° East  
Set Sand Stone, 16 x 12 x 4, for 1/4 Sec. corner, as per instructions.

80.00

Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions for the corner to Sections 25, 30, 31 and 36.  
Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

40.00

South on True Line, West Boundary of Sec. 31. Var. 14° East  
Set granite, 16 x 12 x 5, for 1/4 Sec. cor. as per instructions.

80.00

Set Sand Stone, 20 x 10 x 4, marked and built mound of stone, as per instructions, for the corner to Townships 13 and 14 North, Ranges 5 and 6 West.

Surface Broken, Prairie Soil 3<sup>d</sup> rate.  
December 15<sup>th</sup> 1869

East on Random between Townships 13 and 14 North, Range 5 West. Setting temporary half mile and mile corners at every 40 and 80 chains. Var. 14° 10' East. At 478.70 chains, intersect Range line 1.10 chains North of corner to Townships 13 and 14 North, Ranges 4 and 5 West. Therefore the correction will be 130 lks. East and 18 1/3 lks. South per mile. Then west on True Line, South Boundary of Township 14 N. Range 5

BOOK 1942

West as follows:  
 West on True Line, South Boundary of Sec. 36. Var.  $14^{\circ} 02' E$ .  
 40.00 Set Sand Stone,  $12 \times 10 \times 8$ , for  $\frac{1}{4}$  Sec. Corner, as per instructions.  
 80.00 Set granite,  $16 \times 16 \times 12$ , marked as per instructions, for the Corner to Sections 1, 2, 35 and 36.  
 Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

West on True Line, South Boundary of Sec. 35. Var.  $14^{\circ} 02' E$ .  
 40.00 Set Sand Stone,  $20 \times 10 \times 4$ , for  $\frac{1}{4}$  Sec. corner, as per instructions.  
 80.00 Set Sand Stone  $18 \times 14 \times 4$ , marked as per instructions, for the corner to Sections 2, 3, 34 & 35.  
 Surface rolling, Prairie, Soil 2<sup>d</sup> rate.

West on True Line, South Boundary of Sec. 34. Var.  $14^{\circ} 02' E$ .  
 1.00 Water Course, 30 lks wide course dr.  
 40.00 Set granite  $20 \times 10 \times 3$  for  $\frac{1}{4}$  Sec. corner, as per instructions.  
 43.00 Creek, 20 lks, wide course dr. E.  
 80.00 Set granite,  $18 \times 18 \times 10$ , marked as per instructions, for the Corner to Secs. 3, 4, 33 & 34.  
 Surface rocky, Prairie.  
 Soil 3<sup>d</sup> rate.

West on True Line South Boundary of Sec. 33. Var.  $14^{\circ} 02' E$ .  
 52.00 Creek 15 links wide, course dr. E.  
 40.00 Set granite  $18 \times 10 \times 6$  for  $\frac{1}{4}$  Sec. corner as per instructions.



Chain

80.00

Set granite 18 + 8 + 6. marked as per instructions for the corner to Secs. 4.5. 32 and 33.  
Surface rolling. Prairie. Soil 2<sup>d</sup>. rate.

West on True Line, South Boundary of Sec. 32. Var. 14° 02' E.

40.00

Set granite 18 + 8 + 4 for 1/4 Sec. cor. as per instructions.

80.00

Set granite 15 + 10 + 4. marked as per instructions, for the corner to Sections 5. 6. 31. and 32.  
Surface level. Prairie. Soil 2<sup>d</sup>. rate.

West on True line South Boundary of Sec. 31. Var. 14° 02' E.

40.00

Set granite 24 + 24 + 6. for 1/4 Sec. corner as per instructions.

78.70

corner to Townships 13 and 14 North Ranges 5 and 6 West.  
Surface level. Prairie. Soil 2<sup>nd</sup> rate.

### General Description

This Township is all prairie. Surface generally rolling.

There are several creeks coming in from the south, having an average width of 20 links.

It is well adapted to grazing and large portions of it to farming purposes.  
Soil 2<sup>nd</sup> and 3<sup>rd</sup> rate.

Measuring Chain compared with Standard and found correct.


117  
24 Chains  
BOOK 1942

It being impossible to project the line over high ridge lying just west of the Township corner, I commenced at the  $\frac{1}{4}$  Sec corner, between Secs 31 & 36 and ran west 90.60 chains, at which point I offset back to line on East Bank of Creek 20 links wide, course North, and foot of ridge 400 feet high.  
Surface broken. Soil 3<sup>rd</sup> rate Prairie. Then.

- West on true line, South Boundary of Sec. 35. Var.  $14^{\circ} 10' E$
- 40.00 Set Sand Stone,  $14 \times 12 \times 4$  for  $\frac{1}{4}$  Sec corner as per instructions.
- 58.50 Spring branch 20 lks wide. Course North. Cedar and Cottonwood timber along bank
- 80.00 Set Sand Stone  $24 \times 24 \times 6$  marked as per instructions, for the corner to Secs. 2, 3, 34 & 35.  
Surface rolling. Prairie Soil 2<sup>nd</sup> rate.

West on true line South Boundary of 34. Var.  $14^{\circ} 10' E$ .

- 40.00 Set Sand Stone  $25 \times 20 \times 4$  for  $\frac{1}{4}$  Sec. corner as per instructions.
- 40.40 Dry bed of Creek. 20 lks wide. course North.
- 80.00 Set Sand Stone  $24 \times 20 \times 12$



Chains

marked as per instructions for the corner to sections 3, 4, 33 and 34.

Surface rough. Soil 3<sup>rd</sup> rate. Prairie.

Weston True Line. South Boundary of Sec. 33. Var. 14° 10' E.

4 000 Set granite, 18 x 8 x 8, for 1/4 sec. corner, as per instructions.

Foot of bluff, runs out N.E. from Sierra Carrisa.

72.00  
80.00 Set granite, 20 x 12 x 8, marked as per instructions, for the corner to sections 32 and 33.

Surface broken. Prairie. Soil 3<sup>rd</sup> rate.

Weston True Line. South Boundary of Sec. 32. Var. 14° 20' E.

10.00 Begin ascent of bluff, bears N.E.

4 000 Marked sand stone boulder, 4 feet square, for 1/4 sec. corner, as per instructions.

4 200 Dry bed of creek, 20 lks. wide, course N.E.

51 000 Descend bluff.

8 000 Set sand stone, 18 x 10 x 4, marked as per instructions, for the corner to sections 31 and 32.

Surface broken. Prairie. Soil 3<sup>rd</sup> rate.

Weston True Line. South Boundary of Sec. 31. Var. 14° 20' E.

36.00 Dry bed of creek, 40 lks. wide, course N.E.

4 000 Set sand stone, 14 x 12 x 4, for 1/4 sec. corner, as per instructions.

78.40 Set sand stone, 16 x 14 x 3, marked, built mound of stone, for the corner to Township 13 x 14

26 Chains

BOOK 1942

North, Ranges 6 and 7 west  
Surface broken, Prairie, Soil 3<sup>rd</sup> rate.

From corner to Townships 13 and  
14 North, Ranges 6 and 7 west  
North on West Boundary of Township  
14 North, Range 6 West, as follows:

North on West Boundary of sec.  
31. Var. 14° East,

40.00 Set sand stone, 14 x 12 x 6, for 4 sec,  
80.00 corner, as per instructions,  
Set sand stone, 16 x 9 x 3, marked  
as per instructions, for the cor.  
to sections 25, 30, 31 and 36.  
Surface rolling, Prairie, Soil 2<sup>nd</sup> rate.

North on West Boundary of  
Sec. 30. Var. 13° 50' E.

40.00 Set charred post, built mound  
and dug pits, for 4 sec, cor,  
as per instructions,  
80.00 Set sand stone, 24 x 12 x 9, marked  
as per instructions, for the  
corner to sections 19, 24, 25  
and 30.  
Surface rolling, Prairie, Soil 2<sup>nd</sup> rate.

North on West Boundary of Sec.  
19. Var. 13° 50' East.

40.00 Set sand stone, 18 x 12 x 4, for 4 sec,  
corner, as per instructions.  
54.10 Canon, course East,  
58.15 Leave same,  
80.00 Set sand stone, 24 x 12 x 3, marked  
as per instructions, for the  
corner to secs, 13, 18, 19 & 24.  
Surface partly broken, Prairie, Soil 2<sup>nd</sup> rate.

Chains

BOOK 1942

East on Random between Townships, 14 and 15 North, <sup>Range 6 West</sup> setting temporary half-mile and mile corners at every 40 and 80 chains. Var. 14° East. At 477.80 chains, intersect Range line 35 links North of Corner to Townships 14 and 15 North, Ranges 5 and 6 West.

Therefore the correction will be 29 links East and 5 3/4 links South per mile. Then west on True Line, between Townships 14 and 15 North, Range 6 West, as follows;

West on True Line, South Boundary of Sec. 36. Var. 13° 58' E.

27.70 Dry bed of creek, 150 links wide, course N.E.

40.00 Get sand stone, 15 X 12 X 3, for 1/4 sec. cor. as per instructions.

80.00 Get sand stone, 16 X 12 X 8, marked as per instructions, for the cor. to sections 1, 2, 35 and 36. Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

West on True Line, South Boundary of Sec. 35. Var. 13° 58' E.

40.00 Get sand stone, 14 X 12 X 4, for 1/4 sec. corner, as per instructions.

80.00 Get granite, 18 X 12 X 6, marked as per instructions, for the corner to sections 2, 3, 34 and 35.

Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

West on True Line South Boundary of Sec. 34. Var. 13° 58' E.

40.00 Get sand stone, 14 X 12 X 3, for 1/4 sec. corner, as per instructions.

26

Chain

BOOK 27  
1942

North on West Boundary of Sec 18.  
Var.  $13^{\circ} 30' E.$

- 4.00 Leave bluff, 80 feet high, bears East.
  - 40.00 Set sand stone,  $18 \times 12 \times 4$ , for  $\frac{1}{4}$  sec. corner, as per instructions.
  - 80.00 Set sand stone,  $13 \times 10 \times 6$ , marked as per instructions, for the corner to sections 7, 12, 13 and 18.
- Surface broken. Prairie. Soil 2<sup>nd</sup> rate.

North on West Boundary of Sec. 7.  
Var.  $13^{\circ} 48' E.$

- 40.00 Set charred post, built mound and dug pits, for  $\frac{1}{4}$  sec. cor. as per instructions.
  - 80.00 Set sand stone,  $20 \times 12 \times 4$ , marked as per instructions, for the corner to sections 1, 6, 7 and 12.
- Surface rolling. A few dwarf cedars along line.  
Soil 2<sup>nd</sup> rate.

North on West Boundary of Sec. 6.  
Var.  $13^{\circ} 48' E.$

- 40.00 Set sand stone,  $18 \times 10 \times 4$ , for  $\frac{1}{4}$  sec. corner, as per instructions.
  - 80.00 Set sand stone,  $18 \times 12 \times 7$ , marked, and built mound of stone, as per instructions, for the corner to Townships 14 and 10 North, Ranges 6 and 7 west.
- Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.  
Dec. 16<sup>th</sup>, 1869.  
measuring chain compared with standard, and found correct.



Chains

BOOK 1942

80.00 Set sand stone, 16 X 12 X 4, marked as per instructions, for the corner to sections 3, 4, 33 and 34. Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

West on True Line, South Boundary of Sec. 33. Var. 1338' E.

40.00 Set charred post, built mound and dug pits, for 4 sec. corner, as per instructions.

80.00 Set sand stone, 18 X 14 X 4, marked as per instructions, for the corner to sections 4, 5, 32 and 33. Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

West on True Line, South Boundary of Sec. 32. Var. 13258' E.

40.00 Set sand stone, 16 X 12 X 3, for 4 sec. corner, as per instructions.

80.00 Set sand stone, 18 X 12 X 5, marked as per instructions, for the corner to sections 5, 6, 31 & 32. Surface broken. Prairie. Soil 3<sup>rd</sup> rate.

West on True Line, South Boundary of Sec. 31. Var. 13358' E.

40.00 Set charred post, built mound and dug pits, for 4 sec. cor., as per instructions.

77.20 Cor. to Townships 14 and 15 N. Ranges 6 & 7 West. Surface gently rolling. Prairie. Soil 1<sup>st</sup> rate.

General Description.

This township is all prairie upland, surface generally rolling. It is well adapted to farming and grazing purposes, especially to the latter. Soil 2<sup>nd</sup> 3<sup>rd</sup> and 1<sup>st</sup> rate, measuring chain compared with

Chains

BOOK 1942

Standard, <sup>two</sup> found 4 inch <sup>two</sup> long and  
carefully adjusted.

From corner to Townships 14  
and 15 North, Range 6 and 7 west,  
North on West Boundary of frac-  
tional Township 15 North, Range 6  
west, as follows:

North on West Boundary of fractional  
sec. 31. Var. 14° East,

4000 Set charred post, built mound and  
dug pits, for 4 sec. corner, as per  
instructions.

60.85 Intersect the 37<sup>th</sup> Parallel of North  
Latitude, that being the Boundary  
Line between Utah and Arizona,  
and also the North Boundary of  
the Navajo Indian Reservation.  
33.60 chains East of 7<sup>th</sup> mile  
corner and set sand stone 16 x  
12 x 8, marked "E.C." for the  
corner to fractional township  
15 North, Range 6 and 7 west,  
as per instructions.  
Surface level, Prairie Soil 1<sup>st</sup> rate.

General Description.

This Township is all prairie,  
surface generally level,  
it is well adapted to farming  
and grazing purposes.  
Soil 1<sup>st</sup> and 2<sup>nd</sup> rate.

Chains

From corner to Townships 14  
 and 15 North, Ranges 6 and 7  
 West. Weston True Line, be-  
 tween Townships 14 and 15 N,  
 Range 7 west, as follows:

Weston True Line, South Boundary of  
 Sec. 36, Var. 14° 29' E,

- 40.00 Get sand stone, 15 X 12 X 4, for 1/4 sec, cor,  
 as per instructions,
- 80.00 Get sand stone, 18 X 10 X 4, marked as  
 per instructions, for the corner to  
 secs. 1, 2, 35 and 36,  
 Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

Weston True Line, South Boundary of  
 Sec. 35, Var. 14° 20' E,

- 40.00 Get sand stone, 12 X 9 X 8, for 1/4 sec,  
 corner, as per instructions,
- 80.00 Get sand stone, 16 X 10 X 4, marked as  
 per instructions, for the corner  
 to secs. 2, 3, 34 and 35,  
 Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

Weston True Line, South Boundary  
 of Sec. 24, Var. 14° 24' E,

- 40.00 Get sand stone, 12 X 10 X 8, for 1/4 sec, cor,  
 as per instructions,
- 80.00 Get sand stone, 18 X 12 X 3, marked  
 as per instructions, for the  
 corner to sections 3, 4, 33 & 34,  
 Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

Weston True Line. South Boundary of  
 Sec. 33, Var. 14° 29' E,

- \* 80.00 Get sand stone, 32 X 18 X 3, marked  
 as per instructions, for the cor,  
 to secs. 4, 5, 32 and 33.

\* 40.00 Get sand stone, 14 X 10 X 5, for 1/4 sec, corner, as per instructions.

Chains  
BOOK 1942Surface level. Prairie. Soil 2<sup>nd</sup> rate.10.00 Weston True Line, South Boundary  
of Sec. 22. Var. 14° 45' E.Foot of Butte, bears North and South,  
Impossible to project line over  
same, therefore offset 20.00 chs.  
North, thence west 66.70 chs,  
at which point offset back to  
line, at west foot of Butte,80.00 Marked sand stone, 38 x 28 x 10,  
as per instructions, for the  
corner to secs. 5.6. 31 & 32,  
Surface rocky. Prairie. Soil 2<sup>nd</sup> rate.Weston True Line, South Boundary of  
Sec. 21. Var. 14° 45' E.40.00 Set sand stone, 18 x 10 x 4. for  $\frac{1}{4}$  sec.  
corner, as per instructions.77.00 Marked sand stone boulder, 6 x 6 x 3  
feet, as per instructions, for the  
corner to Townships 14 and 15  
North, Ranges 7 and 8 West,  
Surface broken. Prairie Soil 3<sup>rd</sup> rate.  
December. 17<sup>th</sup> 1869.From corner to Townships 14 and  
15 North, Ranges 7 and 8 West,  
North on East Boundary of sec. 36.  
Var. 14° 45' E.40.00 Set sand stone, 16 x 14 x 3. for  $\frac{1}{4}$  sec.  
corner, as per instructions.63.00 Intersect 37<sup>th</sup> Parallel of North  
Latitude, that being the Boundary  
line between Utah and Arizona  
and also the North Boundary of  
the Navajo Indian Reservation,  
37.00 chains East of 13<sup>th</sup> mile  
corner, and set sand stone.

Chains

20 x 12 x 9, marked "C.C." for the corner to Townships 13 North, Ranges 7 and 8 West, Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

West on Random between Townships 14 and 15 North, Range 8 West, setting temporary half mile and mile corners at Every 40 and 80 Chains,

Var. 14° 20' East.

At 476.70 ch. intersect First Guide meridian, 125 links South of corner to Townships 14 and 15 North, Ranges 8 and 9 West,

Therefore the correction will be 20 7/16 links North per mile.

Then East on True Line between Townships 14 and 15 North, Range 8 West, as follows.

East on True Line, South Boundary of Sec. 31. Var. 14° 29' E.

36.70 Set Charred post, built mound and dug pits, for 1/4 sec. corner, as per instructions.

76.70 Deposited marked stone, set Charred post, marked, built mound and dug pits, as per instructions, for the corner to sections 5, 6, 31 and 32.

Surface gently rolling. Prairie. Soil 1<sup>st</sup> rate.

East on True Line South Boundary of Sec. 32. Var. 14° 29' E.

4 000 Set Charred post, built mound and dug pits, for 1/4 sec. corner, as per instructions.

8000 Deposited marked stone, set Charred post, marked, built mound

31  
BOOK 1942

and dug pits, as per instructions,  
for the corner to sections 4,  
5, 32 and 33.  
Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

Easton True Line. South Boundary  
of Sec. 33. Var. 14° 29' E.  
40.00 Set sand stone, 15 X 13 X 4. for 4  
sec. corner, as per instruc-  
tions.  
80.00 Set sand stone, 16 X 14 X 3. marked  
as per instructions, for the  
corner to sections 3, 4, 33 & 34.  
Surface rolling. Prairie.  
Soil 2<sup>nd</sup> rate.

Easton True Line. South Bound-  
ary of Sec. 34. Var. 14° 29' E.  
40.00 Set charred post, built mound  
and dug pits for 4 sec. cor,  
as per instructions.  
80.00 Set sand stone, 15 X 14 X 3. marked as  
per instructions, for the corner  
to sections 2, 3, 34 and 35.  
Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

Easton True Line. South Boundary  
of Sec. 35. Var. 14° 29' E.  
40.00 Set sand stone, 14 X 10 X 8. for 4 sec.  
corner, as per instructions.  
80.00 Set sand stone, 16 X 14 X 3. marked  
as per instructions for the  
corner to sections 1, 2, 35 & 36.  
Surface rolling. Prairie.  
Soil 2<sup>nd</sup> rate.

Easton True Line. South Bound-  
ary of Sec. 36. Var. 14° 29' E.  
40.00 Set charred post, built mound



Lehains

and dug pits, for  $\frac{1}{4}$  sec. corner, as per instructions, corner to Townships 14 and 15 North, Ranges 7 and 8 West, Surface rolling, Prairie Soil 2 $\frac{1}{2}$  rate.

80.00

From corner to Townships 14 and 15 North, Ranges 7 and 8 West, South on True Line, on West Boundary of Township 14 N, Range 7 West, as follows:

South on West Boundary of Sec. 6, Var. 14° 40' E.

20 Foot of bluff, bears S.S. W.  $\frac{1}{4}$  Sec. E.

80 Top of same, 200 feet high, almost perpendicular,

38.30 Leave same, bears East and West,

40.00 Set sand stone, 14 x 12 x 3, for  $\frac{1}{4}$  sec. corner, as per instructions,

80.00 Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to sections 1, 6, 7 and 12.

Surface rolling, Prairie Soil 2 $\frac{1}{2}$  and 3 $\frac{1}{2}$  rate.

South on West Boundary of Sec. 7, Var. 14° 40' E.

40.00 Set charred post, built mound and dug pits, for  $\frac{1}{4}$  sec. cor., as per instructions,

80.00 Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for corner to sections 7, 12, 13 and 18.

Surface gently rolling, Prairie Soil 2 $\frac{1}{2}$  rate.

36 Chains

BOOK 1942

1000 South on West Boundary of  
Sec. 18. Var.  $14^{\circ}40' E.$   
Set charred post, built mound  
and dug pits, for  $\frac{1}{4}$  sec. cor.  
as per instructions.

800.00 Deposited marked stone, set  
charred post, marked, built  
mound and dug pits, as  
per instructions, for the  
corner to sections, 13, 18, 19  
and 24.  
Surface gently rolling. Prairie.  
Soil 1<sup>st</sup> rate.

4000 South on West Boundary of  
Sec. 19. Var.  $14^{\circ} E.$   
Set charred post, built mound  
and dug pits, for  $\frac{1}{4}$  sec. cor.  
as per instructions.

800.00 Deposited marked stone, set  
charred post, marked, built  
mound and dug pits, as per  
instructions, for the corner  
to secs. 19, 24, 25 and 30.  
Surface gently rolling. Prairie.  
Soil 1<sup>st</sup> rate.

4000 South on West Boundary of  
Sec. 30. Var.  $13^{\circ}45' E.$   
Set sand stone,  $18 \times 8 \times 3$ , for  $\frac{1}{4}$   
sec. corner, as per instruc-  
tions.

800.00 Set sand stone,  $15 \times 11 \times 3$ , marked  
as per instructions, for the  
corner to sections 23, 30,  
31 and 36.  
Surface rolling. Prairie.  
Soil 2<sup>nd</sup> rate.

South on West Boundary of

Chains

BOOK 1942

Dec. 31.

Var.  $14^{\circ} 30' E$ .

- 1425 Ravine, 70 lks. wide, course N.E.
- 31.00 Enter scattering Pinon and cedar, bears E & W.
- 40.00 Set sand stone,  $24 \times 10 \times 8$ , for 4 sec. corner, as per instructions.
- 80.00 Set sand stone,  $20 \times 12 \times 7$ , marked and built mound of stone, as per instructions, for the corner to Townships 13 and 14 North, Ranges 7 & 8, West.

Surface rolling. Last half covered with scattering Pinon and cedar.

Soil 2<sup>d</sup> and 3<sup>d</sup> rate.

December, 18<sup>th</sup> 1869.

East on Random between Townships 13 and 14 North, Range 7 west, setting temporary half-mile and mile corners at every 40 and 80 chains. Var.  $14^{\circ} E$ .

At 479.20 Chs. intersect Range Line 18 links North of the corner to Townships, 13 and 14 North, Ranges 6 and 7 west.

Therefore the correction will be 80 lks. East and 3 links South per mile.

Then west on True Line, between Townships, 13 and 14 North, Range 7 West, as follows:

West on True Line. South Boundary of Dec. 36. Var.  $13^{\circ} 59' E$ .

- 45.00 Set sand stone,  $14 \times 12 \times 4$ , for 4 sec. corner, as per instructions.
- 53.00 Enter scattering Pinon timber, bears N.W. and S.E.
- 80.00 Set granite,  $18 \times 10 \times 6$ , marked as per instructions, for the corner

38

chains

BOOK 1942

to sec. 1, 2, 33 and 36,  
 Surface rolling. Partly covered  
 with Pinon timber, 3<sup>rd</sup> rate, Soil 2<sup>nd</sup> rate.

West on True Line, South Boundary  
 of Sec. 35. Var. 14° East.  
 27.50 Leave scattering timber, bears  
 N.E. and S.W.  
 40.00 Set granite, 14 X 10 X 8, for 4 sec.  
 corner as per instructions.  
 80.00 Deposited marked stone, set  
 charred post, marked, built  
 mound and dug pits, as  
 per instructions, for the  
 corner to sections 2, 3, 34 & 35.  
 Surface gently rolling,  
 mostly prairie. Soil 1<sup>st</sup> rate.

West on True Line, South Bound-  
 ary of Sec. 34. Var. 14° East.  
 40.00 Set charred post, built mound  
 and dug pits for 4 sec. cor.  
 as per instructions.  
 62.00 Enter scattering Pinon & cedar,  
 bears N.W. and S.E.  
 80.00 Set granite, 16 X 12 X 6, marked  
 as per instructions, for  
 the corner to sections 3, 4,  
 33 and 34.  
 Surface gently rolling,  
 generally prairie. Soil 1<sup>st</sup> rate.

West on True Line South Bound-  
 ary of Sec. 33. Var. 14° E.  
 40.00 Set charred post, built mound  
 and dug pits, for 4 sec. cor.  
 as per instructions.  
 80.00 Set sand stone, 16 X 14 X 3, marked

Chain

BOOK 1942

as per instructions, for the  
corner to sections 4, 5, 32 & 33,  
Surface rolling. Scattering Pinon  
and cedar, 3<sup>rd</sup> rate. Soil 2<sup>nd</sup> rate,

Western True Line South Boundary  
of Sec. 32. Var. 14<sup>th</sup> East,  
29.80 Ravine, 100 lks, wide, course North.

40.00 Set sand stone, 16 X 13 X 5. feet  
sec. corner, as per instructions.

80.00 Set sand stone, 14 X 12 X 6, marked  
as per instructions, for the corner  
to sections 5, 6, 31 and 32,  
Surface rolling. Scattering Pinon  
and cedar, 2<sup>nd</sup> rate, Soil 2<sup>nd</sup> rate.

Western True Line. South Bound-  
ary of Sec. 31. Var. 13° 59' E,  
40.00 Set sand stone, 18 X 18 X 4, for 4  
sec. corner, as per instructions.

79.20 Corner to Townships 13 X 14,  
North, Ranges 7 and 8 West,  
Surface broken, Scattering  
Pinon and cedar, 3<sup>rd</sup> rate,  
Soil 2<sup>nd</sup> and 3<sup>rd</sup> rate,

General Description.

This Township is mostly  
prairie, surface generally roll-  
ing. It is well adapted  
to farming and grazing  
purposes. Soil 2<sup>nd</sup> 1<sup>st</sup> and 3<sup>rd</sup> rate,

40  
Chains  
BOOK 1942

Weston Random between Townships 13 and 14 North, Range 8 west, setting temporary half mile and mile corners at every 40 and 80 chains. Var.  $14^{\circ} 30' E$ .  
At 479.30 chs. intersect First Guide meridian 175 lks. South of corner to Townships 13 & 14 N. Ranges 8 and 9 west.  
Therefore the correction will be  $29\frac{1}{2}$  North per mile. Then East on True Line, between Townships 13 and 14 North, Range 8 west, as follows:

East on True Line, South Boundary of Sec. 31. Var.  $14^{\circ} 43' E$ .  
39.30 Get sand stone, 18x12x8, for  $\frac{1}{4}$  sec. corner, as per instructions.  
79.30 Get sand stone, 14x12x3, marked as per instructions for the corner to sections 5, 6, 31 & 32. Surface rolling. Scattering Pinon and Cedar, 3 $\frac{1}{2}$  rate. Soil 2 $\frac{1}{2}$  rate.

East on True Line, South Boundary of Sec. 32. Var.  $14^{\circ} 43' E$ .  
40.00 Get sand stone, 16x13x7, for  $\frac{1}{4}$  sec. corner, as per instructions.  
80.00 Get granite, 18x14x6, marked as per instructions, for the corner to secs. 4, 5, 32 & 33. Surface rolling. Scattering Pinon and Cedar, 3 $\frac{1}{2}$  rate. Soil 2 $\frac{1}{2}$  rate.

East on True Line, South Boundary of Sec. 33. Var.  $14^{\circ} 43' E$ .  
40.00 Get charred post, built mound and

Chains  
 80.00 dug pits, for 1/4 Sec. corner, as per instructions.  
 Set Sand Stone, 26 x 16 x 8, marked as per instructions, for the corner to Sections, 3, 4, 33, and 34.  
 Surface broken. Scattering Piñon and cedar, 3<sup>rd</sup> rate.  
 Soil 3<sup>rd</sup> rate

40.00 East on True Line, South Boundary of Sec. 34. Var. 14° 43' E  
 80.00 Set Sand Stone, 16 x 12 x 3, for 1/4 Sec. cor. as per instructions.

80.00 Set Sand Stone, 14 x 12 x 3, marked as per instructions for the corner to Secs. 2, 3, 34 and 35.  
 Surface broken. Scattering Piñon and cedar, 3<sup>rd</sup> rate.  
 Soil 3<sup>rd</sup> rate.

40.00 East on True Line, South Boundary of Sec. 35. Var. 14° 43' E.  
 80.00 Set Sand Stone, 16 x 14 x 5, for 1/4 Sec. corner, as per instructions

80.00 Set Sand Stone 24 x 12 x 4, marked as per instructions for the corner to Secs. 1, 2, 35 & 36.  
 Surface rolling. Scattering Piñon and cedar, 3<sup>rd</sup> rate. Soil 2<sup>d</sup> rate.

40.00 East on True Line, South Boundary of Sec. 36. Var. 14° 43' E.  
 80.00 Set Sand Stone, 16 x 12 x 3, for 1/4 Sec. corner, as per instructions,

corner to Townships, 13 & 14, N. Ranges 7 and 8 West.  
 Surface rolling. Scattering Piñon and cedar, 3<sup>rd</sup> rate.  
 Soil 2<sup>nd</sup> rate.



BOOK 1942

## General Description

This Township is mostly prairie.

Surface generally rolling.

It is well adapted to grazing and large portions of it to farming purposes.

Soil 2<sup>d</sup>. 1<sup>st</sup> and 3<sup>rd</sup> rate.

Measuring chain compared with standard and found correct.

December 19<sup>th</sup>. 1869.

---

Field notes of the Exterior Lines of Township No 15 North  
Range 5 West. of the Navajo Special Meridian.

Chs. 22

From corner to Townships 14 and 15 North  
Ranges 5 and 6 West. North on West Boundary  
of fractional Township No 15 North. Range  
5 West. as follows:

North on West Boundary of fractional  
Sec. 31.

Pa.  $14^{\circ} 20'$  East.

18.00 Dry bed of creek, 180 lks. wide, course East.

40.00 Set Sand Stone 14 + 12 + 3 for  $\frac{1}{4}$  Sec. cor. as per  
instructions.

57.60 Intersect 3<sup>rd</sup> Parallel of North Latitude, that  
being the Boundary Line between Utah  
and Arizona, and also the North Boundary  
of the Navajo Indian Reservation, 30.00 chs.  
East of the 1<sup>st</sup> mile corner, and set Sand  
Stone 20 + 10 + 5, marked "C.C" for the corner  
to fractional Township 15 North Ranges  
5 and 6 West, as per instructions.  
Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

### General Description

This Township is all prairie. Surface  
generally rolling. It is well adapted  
to grazing purposes.

Soil 2<sup>nd</sup> and 3<sup>rd</sup> rate.

Measuring chain compared with Standard  
and found correct.

Exterior lines of Township 15 North Range 7

44

West of the Navajo Special Meridian

Chs. Sths.

BOOK

1942

From corner to Townships 14 and 15 North, Ranges 7 and 8 West, North on East Boundary of Sec. 36 Ta. 14<sup>th</sup> 45<sup>th</sup> East.

40.00 Set Sand Stone .16 x 14 x 3, for 1/4 Sec. cor. as per instructions.

63.00 Intersect 37<sup>th</sup> Parallel of North Latitude, that being the Boundary Line between Utah and Arizona, and also the North Boundary of the Navajo Indian Reservation .37.00 Chs. East of 13<sup>th</sup> mile corner and set sand Stone .20 x 12 x 4, marked "C.C.", for the corner to Township 15 North Ranges 7 and 8 West.

Surface rolling, Prairie, Soil 2<sup>nd</sup> rate.

We hereby certify, that we assisted Chas. A. Darling, U. S. Surveyor, in surveying the Exterior Lines of Townships 10 North Ranges 5 and 6 West. Tps. 11 North Range 5 West. Tps. 14 North Ranges 5, 6, 7, and 8. Tps. 15 North Ranges 5, 6 and 7 West of the Navajo Special Meridian in Territory of Arizona and that said Exterior Lines have been in all respects, to the best of our knowledge and belief, well and faithfully surveyed and the boundary monuments placed according to the instructions furnished by the Commissioner of the General Land Office

Willard S. Paul. compassman

Sheldon W. Shafer }  
John Howe } Chairmen.

Robert L. Darling }  
William J. Stave } Cornermen

Subscribed by the above named persons and sworn to before me, Ehdud N. Darling, U.S. Surveyor, in Township 1 North, Range 6 West of the Navajo Special Meridian, in the Territory of Arizona. This 26<sup>th</sup> day of January 1870.

Ehdud N. Darling  
U. S. Surveyor

I Ehdud N. Darling, U.S. Surveyor do solemnly swear that in pursuance of a contract with Hon Jos. Wilson Commissioner of the General Land office of the United States, bearing date, Wash.ington D.C. April 29<sup>th</sup>. 1869. and in strict conformity to the laws of the United States and the instructions furnished by the said Commissioner of the General Land office, I have faithfully surveyed the Exterior Lines of Townships No. 7, 8, 9, 10 North Ranges 5 and 6, Tps 11 North, Range 5. Tps 14 North. Ranges 5, 6, 7 and 8 and Tps 15 North, Ranges 5, 6 and 7 West of the Navajo Special Meridian, in the Territories of New Mexico and Arizona, and do further solemnly swear that the foregoing are the true and original field notes of such surveys.

Ehdud N. Darling  
U. S. Surveyor

Subscribed by said Ehdud N. Darling

U. S. Surveyor and sworn to before me,  
this 13th day of April 1870.

Wm. Martin J.P.

Department of the Interior  
General Land office  
April 12th. 1870.

The foregoing field notes of the Survey  
of the Exterior lines of Townships  
+ + + + +  
North, Ranges 5 and 6 West, Tps. 11 North  
Range 5 West, Tps. 14 North Ranges 5, 6,  
7 and 8, and Tps 15 North Ranges 5, 6  
and 7 West of the Navajo Special Meridian,  
in the Territories of New Mexico and Arizona,  
Executed by Chas. M. Darling, U. S. Surveyor  
under his contract with the Commissioner  
of the General Land office, dated April 29th  
1869, having been critically examined and  
the necessary corrections and explanations  
made, are, together with the Survey ~~and~~  
describe, approved.

Jos. S. Wilson  
Commissioner.

Department of the Interior  
General Land office  
February 26th 1871

A True Copy

J. M. Mason  
Commissioner