

4-674.

Township 10 N., R. 6 W.

Navajo Special Base and Meridian

6	16	5	11	4	9	3	6	2	3	1
<del>16</del>		<del>15</del>		<del>11</del>		<del>8</del>		<del>6</del>		<del>3</del>
7	15	8	11	9	8	10	6	11	3	12
<del>15</del>		<del>14</del>		<del>10</del>		<del>8</del>		<del>5</del>		<del>3</del>
18	14	17	10	16	7	15	5	14	2	13
<del>14</del>		<del>13</del>		<del>10</del>		<del>7</del>		<del>5</del>		<del>2</del>
19	13	20	9	21	7	22	5	23	2	24
<del>13</del>		<del>12</del>		<del>9</del>		<del>7</del>		<del>4</del>		<del>1</del>
30	12	29	*	28		27	4	26	/	25
<del>13</del>	<del>12</del>	<del>x</del>						<del>4</del>		<del>1</del>
31		32		33		34	x	35	/	36

1956

BOOK 1956

1956

Surreys in Navajo Indian  
Reservation.

1956

Field Notes of the Subdivision  
Lines of Township 10 North.  
Range 6 West of the Navajo  
Special Meridian, in the Terri-  
tones of New Mexico & Arizona, sur-  
veyed under the directions of the  
Hon. Josiah Wilson,

Commissioner of the General Land  
Office, by Enoch N. Darling  
U.S. Surveyor, under his Con-  
tract bearing date Washington D.C.  
April 29<sup>th</sup> 1869. and subsequent  
special instructions.

1956

Commenced December 6<sup>th</sup> 1869.  
and Completed January 4<sup>th</sup> 1870.

Names of Assistants.

George H. Bradt Compassman.

Charles C. Morton }  
Adam Whisker } Chairmen.

Alexander Douglass }  
Joseph Fierheller } Cornermen.

1956

Measuring chain compared  
with standard and found correct.

1956

Field notes of the Subdivision Lines of Township 10.

B Chains

BOOK 1956

North between Secs. 35 and 36.  
 Var.  $14^{\circ} 08' E$ .  
 40.00 Set sand stone,  $16 \times 12 \times 3$ . for  $\frac{1}{4}$   
 Sec. corner, as per instructions.  
 80.00 Set sand stone,  $18 \times 10 \times 8$ , marked  
 as per instructions, for the corner  
 to Secs. 25, 26, 35 and 36.  
 Surface rolling, Prairie Soil 2<sup>nd</sup> rate.

East on Random between Secs. 25 & 36.  
 Var.  $14^{\circ} 08' E$ .  
 40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
 79.70 Intersect Range line at corner  
 to Secs. 25, 30, 31 and 36.  
 Then West on True Line, Var.  $14^{\circ} 08' E$ .  
 39.85 Set charred post, <sup>fault</sup> mound and dug pits,  
 for  $\frac{1}{4}$  Sec. corner, as per instruc-  
 tions.  
 79.70 Corner to Secs. 25, 26, 35 and 36.  
 Surface rolling, Prairie Soil 2<sup>nd</sup> rate.

North between Secs. 25 and 26.  
 Var.  $14^{\circ} 08' E$ .  
 40.00 Set sand stone,  $12 \times 12 \times 8$ , for  $\frac{1}{4}$   
 Sec. corner, as per instructions.  
 80.00 Set sand stone,  $18 \times 18 \times 3$ , marked  
 as per instructions, for the cor-  
 to Secs. 23, 24, 25 and 26.  
 Surface broken. Prairie Soil 2<sup>nd</sup> rate.

East on Random between Secs.  
 24 and 25,  
 Var.  $14^{\circ} 08' E$ .  
 40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
 79.80 Intersect Range line 26 lbs  
 north of corner to Secs. 19, 24,  
 25 and 30.  
 Then N.  $89^{\circ} 49'$  West on a

Tenn. North. Range 6 West the Starajo Special Meridian

2  
BOOK 1000

Chains

39.90 True Line, var.  $14^{\circ}08'$  East.  
Set sand stone,  $18 \times 6 \times 6$ . for  $\frac{1}{4}$  Sec.  
Corner, as per instructions.  
79.80 Corner to Secs. 23, 24, 25 & 26.  
Surface rolling. Prairie. Soil 2<sup>nd</sup> Rate.

North between Secs. 23 and 24.  
var.  $14^{\circ}08'$  E.  
40.00 Set sand stone,  $14 \times 12 \times 3$ . for  $\frac{1}{4}$   
Sec. corner, as per instructions.  
80.00 Set sand stone,  $18 \times 10 \times 6$ , marked  
as per instructions, for the corner  
to Secs. 13, 14, 23 and 24.  
Surface rolling. Prairie. Soil 2<sup>nd</sup> Rate.

East on Random between Secs. 13  
and 24. var.  $14^{\circ}10'$  E.  
40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
80.00 Intersect Range Line 6 E. S.  
of corner to Secs. 13, 18, 19 & 24.

Then S.  $89^{\circ}57'$  W. on True Line.  
var.  $14^{\circ}10'$  East.  
40.00 Set sand stone,  $18 \times 10 \times 4$ . for  $\frac{1}{4}$   
Sec. corner, as per instructions.  
80.00 Corner to Secs. 13, 14, 23 and 24.  
Surface broken. Prairie. Soil 3<sup>rd</sup> Rate.

North between Secs. 13 and 14.  
var.  $14^{\circ}10'$  E.  
40.00 Set sand stone,  $16 \times 12 \times 3$ . for  $\frac{1}{4}$   
Sec. corner, as per instructions.  
80.00 Set sand stone,  $18 \times 12 \times 3$ , marked  
as per instructions, for the corner  
to Secs. 11, 12, 13 and 14.  
Surface rolling. Prairie.  
Soil 2<sup>nd</sup> Rate.

Field Notes of the Subdivision Lines of Township No. 10.

3  
BOOK

Chains  
1956

East on Random between Secs. 12 and 13. Var.  $14^{\circ}08' E$ .  
 40.00 Temporary  $\frac{1}{4}$  Sec. Corner.  
 79.92 Intersect Range Line 6 lbs. North of corner to Secs. 7, 12, 13 and 18.  
 Then N.  $89^{\circ}57' W$ . on True Line. Var.  $14^{\circ}08' E$ .  
 39.96 Set sand stone,  $28 \times 16 \times 4$ , for  $\frac{1}{4}$  Sec. corner, as per instructions.  
 79.92 Corner to Secs. 11, 12, 13 and 14. Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

North between Secs. 11 and 12. Var.  $14^{\circ}12' E$ .  
 40.00 Set sand stone,  $16 \times 10 \times 4$ , for  $\frac{1}{4}$  sec. corner, as per instructions.  
 80.00 Set sand stone,  $16 \times 12 \times 3$ , marked as per instructions for the corner to Secs. 1, 2, 11 and 12. Surface broken. Prairie. Soil 3<sup>rd</sup> rate.

East on Random between Secs. 1 and 12. Var.  $14^{\circ}12' E$ .  
 40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
 80.40 Intersect Range Line at corner to Secs. 1, 6, 7 and 12.  
 Then west on True Line. Var.  $14^{\circ}12' E$ .  
 40.20 Set sand stone,  $14 \times 10 \times 4$ , for  $\frac{1}{4}$  Sec. corner, as per instructions.  
 80.40 Corner to Secs. 1, 2, 11 and 12. Surface broken. Prairie. Soil 2<sup>nd</sup> rate.

North on True Line, between Secs. 1 and 2. Var.  $14^{\circ}14' E$ .  
 40.00 Set sand stone,  $20 \times 10 \times 3$ , for  $\frac{1}{4}$  Sec. corner, as per instructions.  
 79.28 Intersect 2<sup>nd</sup> Standard Parallel.

Chains

17. 27 Chains East of Standard Corner to Secs. 35 and 36, and set sand stone, marked "c.c." for closing corner. Surface broken, Prairie. Soil 2<sup>nd</sup> rate. December. 31<sup>st</sup>/1889.

From corner to Secs. 25, 26, 35 and 36. West on True Line, between Secs. 26 and 35. Var. 14° 06' E.

40.00 Set sand stone, 14 x 12 x 3. for  $\frac{1}{4}$  sec. corner, as per instructions.

80.00 Set sand stone, 16 x 14 x 3. marked as per instructions, for the corner to Secs. 26, 27, 34 and 35. Surface rolling, Prairie. Soil 2<sup>nd</sup> rate.

South on True Line, between Secs. 34 & 35. Var. 14° 06' E.

40.00 Foot of mountains, impracticable to proceed further. Set charred post, built mound and dug pits for  $\frac{1}{4}$  sec. corner, as per instructions. Surface rolling, Prairie. Soil 2<sup>nd</sup> rate.

North between Secs. 26 and 27. Var. 14° 08' E.

40.00 Set sand stone, 16 x 10 x 6, for  $\frac{1}{4}$  sec. cor. as per instructions.

80.00 Set sand stone, 14 x 12 x 6, marked as per instructions for the corner to Secs. 22, 23, 26 and 27. Surface broken, Prairie. Soil 2<sup>nd</sup> Rate.

East on Random between Secs. 23 & 26. Var. 14° 10' E.

40.00 Set temporary  $\frac{1}{4}$  sec. corner.

79.86 Intersect Section line 28 lks. S. of Cor. to Secs. 23, 24, 25 and 26. Then S. 89° 48' W. on True Line. Var. 14° 10' E.

39.93 Set charred post, built mound and dug pits for  $\frac{1}{4}$  sec. cor. as per instructions.

Field notes of the Subdivision Lines of Township No.

5 Chains  
79.86  
BOOK 1956

Corner to Secs. 22, 23, 26 and 27.  
Surface rolling, Prairie. Soil 2<sup>nd</sup> Rate.

North between Secs. 22 and 23.  
Var. 14° 10' East.

40.00 Set charred post, built mound, and dug pits for  $\frac{1}{4}$  sec. cor. as per instructions.

80.00 Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to Secs. 14, 15, 22 & 23.  
Surface rolling, Prairie, Soil 2<sup>nd</sup> Rate.

East on Random between Secs. 14 and 23.  
Var. 14° 10' E.

40.00 Set temporary  $\frac{1}{4}$  sec. corner.

80.18 Intersect Section Line 4 lbs. S. of corner to Secs. 13, 14, 23 & 24.

Then S. 89° 58' W. on a true line, Var. 14° 10' East.

40.09 Set sand stone, 16 x 10 x 6, for  $\frac{1}{4}$  sec. cor. as per instructions.

80.18 Corner to Secs. 14, 15, 22 and 23.  
Surface rolling, Prairie. Soil 2<sup>nd</sup> Rate.

North between Secs. 14 and 15.  
Var. 14° 12' E.

40.00 Set charred post, built mound & dug pits, for  $\frac{1}{4}$  sec. cor. as per instructions.

80.00 Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to Secs. 10, 11, 14 and 15.  
Surface rolling, Prairie, Soil 2<sup>nd</sup> Rate.

East on Random between Secs. 11 & 14.  
Var. 14° 12' E.

Ten North Range 6 West the Navajo Special m.

6  
BOOK 1956

Chains

40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
80.20 Intersect Sec. Line 30 lks. North of  
cor. to Secs. 11, 12, 13 and 14.

Then W.  $89^{\circ} 43' 20''$  on True Line, Var.  $14^{\circ} 12' 6''$ .

40.10 Set sand stone,  $20 \times 16 \times 3$ , for  $\frac{1}{4}$  sec. cor.  
as per instructions.

80.20 Corner to Secs. 10, 11, 14 & 15.  
Surface broken. Prairie. Soil 2<sup>nd</sup> rate.

North between Secs. 10 and 11.

Var.  $14^{\circ} 08' 6''$ .

40.00 Set sand stone,  $14 \times 12 \times 3$ , for  $\frac{1}{4}$  sec.  
corner, as per instructions.

80.00 Set sand stone,  $14 \times 12 \times 3$ , marked  
as per instructions, for the corner  
to Secs. 2, 3, 10 and 11.

Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

Easton Random between Secs. 2 & 11.

Var.  $14^{\circ} 14' 6''$ .

40.00 Set temporary  $\frac{1}{4}$  Sec. corner.

79.96 Intersect Sec. line 12 lks. South of  
corner to Secs. 1, 2, 11 and 12.

Then S.  $89^{\circ} 55' 00''$  W. on True Line, Var.  $14^{\circ} 14' 6''$ .

39.98 Set sand stone,  $20 \times 8 \times 8$ , for  $\frac{1}{4}$  sec. cor.  
as per instructions.

79.96 Corner to Secs. 2, 3, 10 & 11.

Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

North on true Line between Secs. 2 & 3.

Var.  $14^{\circ} 14' 6''$ .

40.00 Set sand stone,  $18 \times 10 \times 3$ , for  $\frac{1}{4}$  sec.  
corner as per instructions.

62.40 Creek, 20 lks. wide, course East

79.48 Intersect Second Standard Parallel,  
14.60 chains East of Standard

cor. to Secs. 34 & 35, and set sand stone,

$20 \times 10 \times 4$ , marked "c.c." for the closing

corner. Surface broken. Prairie

Soil 3<sup>rd</sup> rate, January 1<sup>st</sup> 18 70.



Field notes of the Subdivision Lines of Township 10 N

7 Chains  
BOOK 1956

Measuring chain compared with Standard and adjusted.

From corner to Secs. 22, 23, 26 and 27,  
West on True Line, between Secs.  
22 and 27, Var.  $14^{\circ}08' E$ .

40.00 Set charred post, built mound and dug pits for  $\frac{1}{4}$  sec. cor. as per instructions.

80.00 Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to Secs. 21, 22, 27 & 28, surface rolling, Prairie. Soil 2 $\frac{1}{2}$  rate.

North between Secs. 21 and 22,

Var.  $14^{\circ}08' East$

40.50 Set sand stone, 16 X 10 X 8, for  $\frac{1}{4}$  sec. corner as per instructions.

42.00 Lareek, 10 lks. wide, course N.W.

48.00 Ascend bluff, bears N.E. and S.W.

80.00 Set sand stone, 16 X 12 X 3, marked as per instructions, for the corner to Secs. 15, 16, 21 and 22,

Surface rolling. Prairie. Soil 2 $\frac{1}{2}$  rate.

East on Random between Secs. 15 & 22,

Var.  $14^{\circ}08' E$ .

40.00 Set temporary  $\frac{1}{4}$  sec. corner.

80.00. Intersect Sec. line at corner to Secs. 14, 15, 22, and 23.

Then West on True Line.

Var.  $14^{\circ}08' E$ .

40.00 Set charred post, built mound and dug pits for  $\frac{1}{4}$  sec. corner.

80.00 Corner to Secs. 15, 16, 21 and 22, surface rolling, Prairie. Soil 2 $\frac{1}{2}$  rate.

North between Secs. 15 and 16,

Var.  $14^{\circ}08' East$

40.00 Set charred post, built mound and

North, Range 6 west of the Starvo Special Meridian.

8  
BOOK 1956

Chains

72.00 dug pits, for  $\frac{1}{4}$  Sec. corner,  
80.00 Creek, 20 lks wide, course N.E. East,  
Set sand stone, 18x10x10. marked as  
per instructions, for the Corner to Secs,  
9, 10, 15 and 16.  
Surface rolling, Prairie, Soil 2 $\frac{1}{2}$  rate.

East on Random between Secs. 10 & 15.  
Var. 14° 10' E.

40.00 Set temporary  $\frac{1}{4}$  Sec. corner,  
48.20 Creek, 20 lks wide, course N.E.,  
80.20 Intersect Sec. line 30 links South of  
corner to Secs, 10, 11, 14 and 15.  
Then South 89° 47' W. on True Line.  
Var. 14° 10' E.

40.10 Set sand stone, 18x10x4, for  $\frac{1}{4}$  Sec. corner  
as per instructions,  
80.20 corner to Secs, 9, 10, 15 and 16,  
Surface rolling, Prairie, Soil 2 $\frac{1}{2}$  rate.

North between Secs. 9 and 10.

Var. 14° 12' E.

20.00 Bluff, bears East and west, Enter cedar  
timber

40.00 Set sand stone, 16x8x6, for  $\frac{1}{4}$  sec. corner  
as per instructions.

80.00 Set sand stone, 16x14x3, marked as  
per instructions, for the corner to Secs,  
3, 4, 9 and 10.  
Surface rolling, prairie, Soil 2 $\frac{1}{2}$  Rate.

East on Random between Secs,  
9 and 10. Var. 14° 15' E.

40.00 Set temporary  $\frac{1}{4}$  Sec. corner,

56.70 Creek 25 lks. wide, course North.

80.10 Intersect Sec. line 14 lks. North of Cor  
to Secs, 2, 3, 10 + 11.

Then N. 89° 54' W. on a true line  
Var. 14° 15' E.

40.05 Set sand stone, 14x12x4, for  $\frac{1}{4}$  Sec. cor.

BOOK

chains  
80.00  
1956 -

as per instructions,  
Corner to Secs. 3, 4, 9 and 10.  
Surface broken. Prairie. Soil 2<sup>d</sup> rate.

40.00 North on True Line between Secs 3 and 4,  
Var. 14° 15' E,  
Set sand stone, 14 X 12 X 3, for  $\frac{1}{4}$  sec. cor,  
as per instructions.

80.00 intersect second Standard Parallel,  
1450 chains East of standard  
corner to Secs. 33 and 34, and set  
sand stone, 18 X 10 X 4, marked "C. C." for  
the closing corner to Secs. 3 & 4,  
Surface rolling, Prairie. Soil 2<sup>d</sup> rate.  
January 2<sup>nd</sup> 1870.

40.00 From corner to Secs. 21, 22, 27 and 28,  
West on True Line, between Secs. 21 and 28,  
Var. 14° 05' E,  
Set sand stone, 16 X 12 X 3, for  $\frac{1}{4}$  sec. corner,  
as per instructions.

80.00 Set sand stone, 18 X 10 X 4, marked as per  
instructions, for the corner to Secs.  
20, 21, 28 and 29,  
Surface rolling, Prairie Soil 2<sup>d</sup> rate.

31.00 South on True Line, between Secs. 28 and 29,  
Var. 14° 08' East,  
Foot of mountain, bears N.E. and S.W.  
Set sand stone, 14 X 12 X 3, marked  
"W. C." as witness corner,  
Surface rolling, Prairie. Soil 2<sup>d</sup> rate.

40.00 North between Secs. 20 and 21,  
Var. 14° 10' E,  
Set charred post, built mound and  
dug pits, for  $\frac{1}{4}$  sec. corner, as per  
instructions.

80.00 Set sand stone, 16 X 12 X 6, marked as  
per instructions, for the corner

Chains

to Secs. 16, 17, 20 and 21.  
Surface level. Prairie. Soil 2<sup>nd</sup> rate.

East on Random between Secs.  
16 and 21. Var. 14° 10' E.

40.00 Set temporary  $\frac{1}{4}$  sec. corner.  
54.80 Creek, 15 lks. wide, course north.  
70.00 Foot of Bluff, bears N 78.  
73.50 Top of same.  
79.90 Intersect Sec. line 12 links north  
of corner to Secs. 15, 16, 21 and 22.

Then N. 89° 51' W. on True line Var. 14° 10' E.

39.95 Set sand stone 14 X 12 X 3. for  $\frac{1}{4}$  sec.  
corner, as per instructions.  
79.90 Corner to Secs. 16, 17, 20 and 21.  
Surface rolling. Prairie.  
Soil 2<sup>nd</sup> Rate.

North between Secs. 16 and 17.  
Var. 14° 10' E.

40.00 Set charred post, built mound and  
dug pits for  $\frac{1}{4}$  Sec. corner, as per  
instructions.  
46.50 Creek, 20 lks. wide, course East.  
80.00 Deposited marked stone, set charred  
post, marked, built mound and dug  
pits, as per instructions, for the  
corner to Secs. 8, 9, 16 and 17.  
Surface rolling. Prairie. Soil 2<sup>nd</sup> rate.

East on Random between Secs.  
9 and 16. Var. 14° 12' E.

40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
80.00 Intersect Sec. line 47 links  
south of corner to Secs. 9, 10, 15  
and 16.

Then S. 89° 41' W. on True  
line. Var. 14° 12' East.

Field notes of the Subdivision Lines of Township 40N

BOOK 1956

Chains  
40.00

Set sand stone, 16x10x4, for  $\frac{1}{4}$  sec. corner, as per instructions, corner to Secs. 8, 9, 16 and 17. Surface broken. Prairie Soil 3<sup>rd</sup> rate.

80.00

North between Secs. 8 and 9. Var. 14° 18' E.

40.00

Set charred post, built mound and dug pits, for  $\frac{1}{4}$  sec. corner, as per instructions.

80.00

Deposited marked stone set charred post, marked, built mound and dug pits, as per instructions, for the corner to Secs. 4, 5, 8 and 9. Surface rolling. A few scattering Pinon trees along the line. Soil 2<sup>nd</sup> rate.

East on Random between Secs. 4 and 9.

Var. 14° 18' E.

40.00

Set temporary  $\frac{1}{4}$  sec. corner.

79.88

Intersect Sec. line 20 lks. North of corner to Secs. 3, 4, 9 and 10.

Then N. 89° 51' West on True Line,

Var. 14° 18' E.

39.94

Set Charred post, built mound and dug pits, for  $\frac{1}{4}$  sec. corner, as per instructions.

79.88

Corner to Secs. 4, 5, 8 and 9. Surface rolling. Scattering cedar and Pinon, 3<sup>rd</sup> rate, Soil 2<sup>nd</sup> rate.

North on True Line between Secs. 4 and 5. Var. 14° 18' E.

40.00

Set sand stone, 16x10x6, for  $\frac{1}{4}$  sec. cor. as per instructions.

80.12

Intersect Second Standard Parallel. 14, 40 Chains East of

Chains

Standard corner to Secs 32 and 33.  
and set sand stone, 16 X 14 X 3;  
marked "C.C." for the closing corner  
to Secs. 4 and 5.  
Surface rolling, scattering cedar  
and Pinon, 3<sup>4</sup>/<sub>4</sub> rate. Soil 2<sup>4</sup>/<sub>4</sub> rate.  
January 3<sup>4</sup>/<sub>4</sub> 1870.

Measuring chain compared with Stand-  
ard and adjusted.  
From corner to Secs. 20, 21, 28 and 29.  
West on True Line between Secs. 20 & 29.  
Var. 14° 08' E.

40.00 Set sand stone, 14 X 12 X 3. for  $\frac{1}{4}$  sec. cor.  
as per instructions.  
80.00 Set sand stone, 15 X 10 X 5, marked as per  
instructions, for the corner to Secs.  
19, 20, 29 and 30.  
Surface rolling, scattering Pinon  
and cedar, 3<sup>4</sup>/<sub>4</sub> rate. Soil 2<sup>4</sup>/<sub>4</sub> rate.

South on True Line, between Secs.  
29 and 30. Var. 14° 12' E.

40.00 Set sand stone, 18 X 16 X 8. for  $\frac{1}{4}$  sec.  
corner, as per instructions.  
80.00 Set sand stone, 14 X 12 X 3. marked  
as per instructions, for the corner  
to Secs. 29, 30, 31 and 32.  
Surface rolling. A few Cedars  
along line. Soil 2<sup>4</sup>/<sub>4</sub> Rate.

East on True Line between Secs. 29  
and 32. Var. 14° 08' E.

36.80 Foot of mountain, bears N.E. & S.W.  
Set sand stone, 16 X 10 X 4.  
marked "W.C." for Witness Corner.  
Surface rolling, scattering Pinon  
and cedar, 2<sup>4</sup>/<sub>4</sub> rate.  
Soil 2<sup>4</sup>/<sub>4</sub> Rate.

13 Field notes of the Subdivision Lines of Township No.

BOOK 1956

chains

Weston Random between Secs. 30 and 31. Var.  $14^{\circ} 10'$  East.  
 40.00 Set temporary  $\frac{1}{4}$  sec. corner.  
 77.50 Intersect Range line at corner to Secs. 25, 30, 31 and 36.  
 Then East on True line. Var.  $14^{\circ} 10'$  E.  
 37.50 Set sand stone,  $14 \times 12 \times 3$ , for  $\frac{1}{4}$  sec. corner, as per instructions.  
 77.50 Corner to Secs. 29, 30, 31 and 32. Surface rolling, scattering Pinon and cedar,  $3^{\frac{1}{2}}\%$  Rate. Soil  $2^{\frac{1}{2}}\%$  Rate.

Weston Random between Secs. 19 and 30. Var.  $14^{\circ} 10'$  E.  
 40.00 Set temporary  $\frac{1}{4}$  sec. corner.  
 77.60 Intersect Range line 20 links S. of corner to Secs. 19, 24, 25 & 30.  
 Then S.  $89^{\circ} 51'$  E. on True line. Var.  $14^{\circ} 10'$  E.  
 37.60 Set sand stone,  $14 \times 12 \times 3$ , for  $\frac{1}{4}$  sec. cor. as per instructions.  
 77.60 Corner to Secs. 19, 20, 29 and 30. Surface rolling, scattering Pinon and cedar,  $3^{\frac{1}{2}}\%$  Rate. Soil  $2^{\frac{1}{2}}\%$  Rate.

North between Secs. 19 and 20. Var.  $14^{\circ} 12'$  E.  
 14.00 Leave Timber, bears East & West  
 40.00 Set charred post, built mound and dug pits for  $\frac{1}{4}$  sec. corner, as per instructions.  
 80.00 Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to Secs. 17, 18, 19 and 20. Surface level, mostly prairie. Soil  $1^{\frac{1}{2}}\%$  Rate.

East on Random, between Secs. 17 and 20. Var.  $14^{\circ} 12'$  E.

10 North. Range 6 West the Navajo Special Meridian.

14  
BOOK 1956

chains  
40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
80.12 Intersect Sec. Line 2 2 lks. South of Cor.  
to Secs. 16, 17, 20 and 21.  
Then S.  $89^{\circ}51'W.$  on True Line. Var.  $14^{\circ}12'E.$   
40.06 Set charred post, built mound and dug  
pits for  $\frac{1}{4}$  Sec. corner.  
80.12 Corner to Secs. 17, 18, 19 and 20.  
Surface level. Prairie. Soil 2 $\frac{1}{2}$  Rate.

West on Random between Secs. 18 and 19.  
Var.  $14^{\circ}12'E.$

4.50 Arroya, 60 lks. wide, course N.E.  
40.00 Set temporary  $\frac{1}{4}$  Sec. corner.  
77.26 Intersect Range Line 14 links N. of  
corner to Secs. 13, 18, 19 + 29.  
Then N.  $89^{\circ}54'E.$  on True Line,  
Var.  $14^{\circ}12'E.$

37.26 Set charred post, built mound and dug  
pits, for  $\frac{1}{4}$  Sec. corner, as per instructions.  
77.26 Corner to Secs. 17, 18, 19 + 20.  
Surface level. Prairie. Soil 2 $\frac{1}{2}$  Rate.

North between Secs. 17 and 18.  
Var.  $14^{\circ}12'E.$

4.00 Arroya, 60 links wide, course N.E.  
34.25 Creek, 20 " " course N.E.  
40.00 Set charred post, built mound and  
dug pits, for  $\frac{1}{4}$  Sec. corner, as per  
instructions.  
68.00 Enter cedar timber, bears E + West.  
80.00 Set sand stone, 24 x 12 x 3. marked  
as per instructions, for the cor.  
to Secs. 7, 8, 17 + 18.  
Surface rolling, mostly prairie.  
Soil 2 $\frac{1}{2}$  Rate

East on Random between Secs.  
8 and 17.  
Var.  $14^{\circ}15'E.$

40.00 Set temporary  $\frac{1}{4}$  Sec. corner.



15 Field Notes of the Subdivision Lines of

BOOK 1956

Chains  
79.90

Intersect Sec. line 24 lks. South  
of corner to Secs. 8, 9, 16 & 17.  
Then S.  $89^{\circ}49'$  W. on True Line,  
Var.  $14^{\circ}15'$  East,

39.95 Set sand stone,  $15 \times 15 \times 2$ , for  $\frac{1}{4}$  sec. cor.  
as per instructions,

79.90 Corner to Secs. 7, 8, 17 and 18.  
Surface broken, Scattering Pinon  
and cedar,  $3\frac{1}{2}$  Rate, Soil  $3\frac{1}{2}$  Rate,

Weston Random between Secs. 7 & 18,  
Var.  $14^{\circ}15'$  East.

40.00 Set temporary  $\frac{1}{4}$  Sec. corner.

77.28 Intersect Range line at corner  
to Secs. 7, 12, 13 & 18.

37.28 Then East on True Line, Var.  $14^{\circ}15'$  E.  
Set charred post, built mound  
and dug pits, for  $\frac{1}{4}$  Sec. corner,  
as per instructions,

77.28 Corner to Secs. 7, 8, 17 and 18.  
Surface rolling, Prairie,  
Soil  $2\frac{1}{2}$  Rate.

North between Secs. 7 and 8,  
Var.  $14^{\circ}15'$  E.

40.00 Set sand stone,  $16 \times 12 \times 4$ , for  $\frac{1}{4}$   
Sec. corner, as per instructions.

80.00 Set sand stone,  $14 \times 12 \times 3$ , marked  
as per instructions, for the  
corner to Secs. 5, 6, 7 and 8,  
Surface broken, Scattering  
Pinon and cedar,  $3\frac{1}{2}$  Rate,  
Soil  $3\frac{1}{2}$  Rate.

Easton Random between Secs.  
5 and 8, Var.  $14^{\circ}15'$  E.

40.00 Set temporary  $\frac{1}{4}$  Sec. corner

80.26 Intersect Sec. line at corner to  
Secs. 4, 5, 8 and 9.

Then Weston True Line, Var.  $14^{\circ}15'$  E.

Chains  
40.13

Set sand stone, 18 x 8 x 6, for 4 Sec. Cor. as per instructions.

80.26

Corner to Secs. 5, 6, 7 and 8, Surface rolling, Scattering Pinon and Cedar, 3<sup>rd</sup> rate. Soil 2<sup>nd</sup> rate.

Weston Random between Secs. 6 & 7. Var. 14° 15' E.

40.00

Set temporary 4 Sec. Corner.

77.40

Intersect Range Line 10 lks. S. of Corner to Secs. 1, 6, 7 & 12. Then S. 89° 56' E. on True Line, Var. 14° 15' East.

87.40

Set sand stone, 16 x 10 x 4, for 4 Sec. Corner, as per instructions.

77.40

Corner to Secs. 5, 6, 7 and 8, Surface broken. Scattering Pinon and Cedar, 3<sup>rd</sup> rate. Soil 3<sup>rd</sup> Rate.

North on True Line between Secs. 5 and 6. Var. 14° 15' E.

40.00

Set sand stone, 16 x 12 x 3, for 4 Sec. Cor. as per instructions.

80.20

Intersect Second Standard Parallel 14.30 chains East of the <sup>Standard</sup> Corner to Secs. 31 & 32, and set sand stone, 18 x 12 x 4 marked "C.C." for the Closing Corner to Secs. 5 and 6.

Surface rolling. Scattering Pinon and Cedar, 3<sup>rd</sup> rate. Soil 2<sup>nd</sup> Rate.

General Description,  
The land in this Township is mostly prairie, soil generally 2<sup>nd</sup> rate. It is well adapted to farming and grazing purposes, the latter especially, soil 2<sup>nd</sup> & 3<sup>rd</sup> and 1<sup>st</sup> rate.

BOOK 1956

There is a fine stream of water passing through the Township.

We hereby certify that we assisted Ehdud W Darling, U.S. Surveyor, in subdividing Township 10 North, Range 6 West of the Navajo Special Meridian, in the Territory of New Mexico, and that said Township has been in all respects to the best of our knowledge and belief, well and faithfully surveyed and the boundary monuments planted according to the instructions furnished by the Commissioner of the General Land Office of the United States.

Geo H Bradt Compassman.

Charles C Morton }  
Adam Whicker } Chainmen.

Alex. Douglass }  
Joseph Fairheller } Cornermen.

Subscribed and sworn to by the above named persons, before me Ehdud W Darling, U.S. Surveyor, in Township 10 North,

Range 6 West of the Navajo Special Meridian, in the Territory of Arizona, this 26<sup>th</sup> day of January, 1870.

Ehdud W Darling  
U.S. Surveyor.

I, Ehud A Darling, U.S. Surveyor,  
do solemnly swear that in pur-  
suance of a contract with the  
Hon. Jas. S. Wilson, Commissioner  
of the General Land Office of  
the United States, bearing date  
Washington D.C. April 29<sup>th</sup> 1869,  
and subsequent special in-  
structions, and in strict con-  
formity to the laws of the  
United States; and the instruc-  
tions furnished by the said  
Commissioner of the General  
Land Office of the United  
States, I have faithfully sub-  
divided Townships No. 11, 12,  
" " " " " " " " and  
Township 10 North, Range 6  
West of the Navajo Special  
Meridian, in the Territories of  
New Mexico and Arizona,  
and do further solemnly  
swear that the foregoing are  
the true and original  
field notes of such survey.  
Ehud A Darling  
U.S. Surveyor.

Subscribed by said Ehud  
A Darling, U.S. Surveyor, and  
sworn to before me, this 3<sup>d</sup>  
day of May, 1870.  
John C Cox, J.P.

BOOK 1956

Department of the Interior  
General Land Office  
May 7, 1870

The foregoing field-notes of the survey of  
the subdivisional lines of Townships \* \*  
\* \* \* \* \*  
10 North Range 6 West of the Navajo  
Special Meridian in the Territory of Arizona,  
executed by Chas. R. Darling, under his  
contract of the 29th. April 1869, and sub-  
sequent special instructions, having  
been critically examined and the necessary  
corrections and explanations made, the  
said field notes, and the surveys they describe,  
are hereby approved.

Jos. S. Wilson  
Commissioner

Department of the Interior  
General Land Office  
February 26th 1877

A True Copy

J. A. Munson  
Commissioner