

2724

4-679

2724

SER 2-1914

79
①

Book "E"

Resurvey Subdivisions

FIELD NOTES

BOOK 2724

OF THE ~~RESURVEY~~ OF THE

Subdivision lines of

Township 14 South Range 25 East

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Thomas B. Matthews,

In the capacity of U. S. Surveyor, under instructions dated April 21, 1913,
issued by the United States Surveyor General to govern surveys included in
Group No. 25, which were approved by the Commissioner of the General Land
Office, May 2, 1913, pursuant to authority contained in the Act of
Congress dated August 24, 1912

Re Survey commenced June 3, 1913

Re Survey completed JUNE 14, 1913

BOOK 2724 Book "E"

Book No. 2724

INDEX DIAGRAM.

Township 14 South, Range 25 East

6	37	5	31 3	4	3 27	3	5 22	2	5 18	1
11 36		11 36		11 31		12 26		12 22		12 18
7	36	8	3 30 2	9	3 26	10	5 21	11	5 17	12
14 35		13 35		13 30		13 26		13 21		12 17
18	34	17	2 29	16	25 3	15	4 21	14	5 16	18
8 34		8 33		8 29		9 25		9 20		16 9
19	35	20	2 29	21	3 24	22	4 20	23	6 16	24
10 33	11	10 32		10 28		10 24	11	10 20	9	9 15 10
30	32 2	29	28 2	28	3 24 4	27	4 19	26	6 15	25
7 32		8 32		7 28		7 23		7 19		6 14
31	31 2	32	2 27	33	4 23	34	4 18	35	6 14	36

Notes in Book "A", this Group (25) 2720

— Surveved

2 Random Retracements indexed in Red Figures

37 Sub. Resurveys indexed in Black Figures

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

Retracement and

Resurvey commenced June 3rd, 1913 and executed by Thomas B. Matthews, U. S. Surveyor, with Young & Sons Light Mountain Transit No. 8480, with solar attachment. The horizontal limb is provided with two double verniers placed opposite to each other, reading to single minutes of arc, which is also the least count of the verniers for the lat. and decl. arcs. This instrument was approved by the Supervisor of Surveys Jan 30th, 1913.

I examine the adjustments of the transit and find them to be correct and know from recent test of the solar apparatus, by comparing its indication resulting from solar observations, made during a.m. and p.m. hours, with a mer. established by observation on Polaris, at elongation, that the instrument is in satisfactory adjustment.

I commence at the point for cor. of secs. 5, 6, 31 & 32 on N. bdy. of Tp., previously re-established by me, as described in Book "A" of this Group, setting off 22° 18' N. on decl. arc; 32° 15' on lat. arc, and determining a mer. with the solar at 7h. 30m. a.m., l.m.t.

The magnetic bearing of the true mer. at 7 h. 30 m., a.m., l.m.t. is N. 12° 50' W., the angle thus determined gives the magnetic decl. 12° 50' E.

Thence I run

S. on random line bet. secs. 5 & 6

9.67 Make diligent search for orig. closing cor. of secs. 5 and 6, on E. bdy. of Wilcox Townsite.

40.60 Make diligent search for orig. 1/4 sec. cor., which I fail to find.

80.60 Make diligent search for orig. cor. of secs. 5, 6, 7 & 18, which I also fail to find.

Therefore, I continue my random line South, bet. secs. 7 & 8.

120.60 Make diligent search for 1/4 sec. cor., which I fail to find

161.68 Fall 14 lks. W. of point for original cor. of secs. 7, 8, 17 & 18, as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General. Mound obliterated.

Thence I run

N. 0° 03' W. on temp. line setting temp. 1/4 sec. & sec. cors. at distances proportional to distances given on original plat, and at 161.68 chs. intersect point for cor. of secs. 5, 6, 31 & 32 on N. bdy. of Tp., previously described by me, in Book "A" of this group

From the point for cor. of secs. 7, 8, 17 & 18, described above

I run

South on random line bet. secs. 17 & 18

339.96 Intersect point for orig. 1/4 sec. cor. as determined from stake in S. pit, firmly set & marked as described by the Surveyor General, mound obliterated.

Therefore, the true return bearing is North.

Thence I run

From the point for 1/4 sec. cor.

South on random line bet. secs. 17 & 18, on S. half mile.

39.92 Fall 19 lks. W. of point for orig. cor. of secs. 17, 18, 19 & 20 as determined from stake in S.E. pit firmly set & marked as described by the Surveyor General, mound obliterated.

Therefore, the true return bearing is N. 0° 16' W.

From the point for original cor. of secs. 17, 18, 19 & 20, described above, I run

South on random line bet. secs. 19 & 20

40.00 Make diligent search for 1/4 sec. cor., which I fail to find.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

- 80.00 Make diligent search for orig. cor. of secs. 19, 20, 29 & 30, which I also fail to find. Therefore I continue my random line South making diligent search for $\frac{1}{4}$ sec. & sec. cors. at intervals of 40 and 80 chs. respectively, but find no evidence of original cor. until at
- 239.43 Intersect S. bdy. of Tp. 28 lks. W. of cor. of secs. 5, 6, 31 & 32, previously re-established by me, as described in Book "A" of this Group. Thence I run, N. $0^{\circ}04'$ W. on temp. N. & S. line setting temp. $\frac{1}{4}$ sec. & sec. cors at distances proportional to distances given on original plat, and at 239.43 chs. intersect point for original cor. of secs. 17, 18, 19 & 20, hereinbefore described.
-
- At the cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp. previously reestablished by me, as described in Book "A" of this Group, I set off $22^{\circ}19'$ N. on decl. are and at 11 h. 57^m 151 s., a.m., l.m.t., observe the sun on the mer. and obtain a reading of $32^{\circ}09\frac{1}{2}'$ on lat. arc.
- Thence I run North on random line bet. secs. 32 & 33
- 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find.
- 80.00 Make diligent search for orig. cor. of secs. 28, 29, 32 & 33, which I also fail to find. Therefore, I continue my random line North, bet. secs. 28 and 29.
- 119.58 Fall 35 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set, and marked as described by Surveyor General, mound obliterated.
- Thence I run N. & S. S. $0^{\circ}10'$ E. on temp. line, setting temp. sec. & $\frac{1}{4}$ sec. cors. at distances proportional to distances given on original plat, and at 119.58 chs. intersect the cor. of secs. 4, 5, 32 & 33, previously re-established by me, as described in Book "A" of this Group.
-
- Thence I run From the point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 28 & 29, previously described, North on random line bet. secs. 28 & 29 on N. half mile.
- 40.00 Make diligent search for original cor. of secs. 20, 21, 28 & 29, which I fail to find, therefore, I continue my random line North, bet. secs. 20 and 21.
- 80.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I also fail to find.
- 120.21 Fall 21 lks. W. of point for original cor. of secs. 16, 17, 20 & 21 as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General, mound obliterated.
- Thence I run N. & S. S. $0^{\circ}06'$ W. on temp. line, setting temp. $\frac{1}{4}$ sec. & sec. cors. at distances proportional to distances given on original plat, and at 120.21 chs. intersect pt. for original $\frac{1}{4}$ sec. cor. bet. secs. 28 & 29, hereinbefore described.
-
- From the point for original cor. of secs. 16, 17, 20 & 21, hereinbefore described.
- I run North on random line bet. secs. 16 & 17
- 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find.
- 80.00 Make diligent search for orig. cor. of secs. 8, 9, 16 & 17, which I also fail to find. Therefore, I continue my random line North, bet. secs. 8 and 9.
- 120.33 Fall 3 lks. W. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set & marked as described by Surveyor General, mound obliterated.
- Thence I run N. and S. S. $0^{\circ}01'$ W. on temp. line, setting temp. sec. cor. & $\frac{1}{4}$ cors. at distances proportional to distances given on original plat, and at 120.33 chs. intersect the pt. for bld. cor. of secs. 16, 17, 20 & 21, hereinbefore described.
-

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

Thence I run
 From the point for $\frac{1}{4}$ sec. cor. hereinbefore described.
 North on random line bet. secs. 3 & 9 on N. $\frac{1}{2}$ mile.
 40.00 Make diligent search for orig. cor. of secs. 4, 5, 8 & 9,
 which I fail to find.
 Therefore I continue my random line North, bet. secs. 4 and 5.
 80.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I also
 fail to find.
 121.20 Intersect N. bdy of Tp. 14 Tks. E. of cor. of secs. 4, 5,
 32 & 33, previously re-established by me, as described in
 Book "A" of this Group. Thence I run,
 S. $0^{\circ} 04'$ E. on temp. N. & S. line, setting temp. $\frac{1}{4}$ sec. & sec.
 cors. at distances proportional to distances given on ori-
 ginal plat, and at 121.20 chs. intersect point for origi-
 nal $\frac{1}{4}$ sec. cor. bet. secs. 8 & 9, hereinbefore described.

June 3rd, 1913.

June 4th, 1913:

At 7 h. 30 m., a.m., l.m.t, I set off. $22^{\circ} 25\frac{1}{2}'$ N.
 on decl. arc $32^{\circ} 15'$ on lat. arc and determine a mer. with
 the solar at the cor. of secs. 3, 4, 33 & 34, on N. bdy. of Tp.
 previously reestablished by me, as described in Book "A" of
 this Group. Thence I run;
 South on random line bet. orig. secs. 3 & 4.
 40.51 Make diligent search for $\frac{1}{4}$ sec. cor., which I fail to find.
 81.11 Fall 30 lks. W. of point for orig. cor. of secs. 3, 4, 9 &
 10, as determined from stake in S.E. pit, firmly set &
 marked as described by Surveyor General, mound obliterated.
 Therefore, the true return bearing is N. $0^{\circ} 13'$ W.

Thence I run
 South on random line bet. secs. 9 & 10
 39.96 Fall 5 lks. W. of point for orig. $\frac{1}{4}$ sec. cor., as determined
 from stake in S. pit, firmly set & marked as described by
 Surveyor General, mound obliterated.
 Therefore, the true return bearing is N. $0^{\circ} 04'$ W.

Thence I run
 From point for original $\frac{1}{4}$ sec. cor. described above,
 South on random line bet. secs. 9 & 10, on south half mile.
 40.19 Intersect point for orig. cor. of secs. 9, 10, 15 & 16, as
 determined from stake in S.E. pit, firmly set & marked as
 described by Surveyor General, mound obliterated.
 Therefore, the true return bearing is North.

Thence I run
 South on random line bet. secs. 15 & 16
 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to
 find.
 80.23 Intersect point for orig. cor. of secs. 15, 16, 21 & 22, as
 determined from stake in S.E. pit, firmly set & marked as
 described by Surveyor General, mound obliterated.
 Therefore, the true return bearing is North.

Thence I run
 South on random line bet. secs. 21 & 22
 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to
 find.
 80.00 Make diligent search for orig. cor. of secs. 21, 22, 27 & 28,
 which I also fail to find.
 Therefore, I continue my random line South, bet. secs. 27 & 28.
 120.15 Fall 31 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 27
 & 28, as determined from stake in S. pit, firmly set &

RETRACEMENT, SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

marked as described by Surveyor General, mound obliterated.
 Thence I run
 N. $0^{\circ} 09'$ E. on temp. ^{N. & S.} line setting temp. sec & $\frac{1}{4}$ sec. cors.
 at distances proportional to distances given on original
 plat, and at 120.15 chs. intersect the point for orig. cor. of
 secs. 15, 16, 21 & 22 hereinbefore described.

 Thence I run
 From the point for the orig. $\frac{1}{4}$ sec. cor.
 South on random line bet. secs. 27 & 28, on south half mile.
 40.17 Fall 5 lks. W. of point for the orig. cor. of secs. 27, 28,
 33 & 34 as determined from stake in SE. pit, firmly set &
 marked as described by the Surveyor General, mound obliterated.
 Therefore, the true return bearing is N. $0^{\circ} 04'$ W.

 Thence I run
 South on random line bet. secs. 33 & 34
 39.95 Intersect point for orig. $\frac{1}{4}$ sec. cor. as determined from
 stake in S. pit, firmly set & marked as described by the
 Surveyor General, mound obliterated
 Therefore, the true return bearing is North.

 Thence I run
 From the point for the orig. $\frac{1}{4}$ sec. cor.
 South on random line bet. secs. 33 & 34, on S. half mile.
 39.67 Intersect south bdy. of Tp. 25 lks. W. of cor. of secs.
 3, 4, 33 & 34, previously re-established by me, as described
 in Book "A" of this Group.
 Therefore the true return bearing is N. $0^{\circ} 21'$ W.

 At the corner of secs. 2, 3, 34 & 35 on S. bdy. of Tp. I
 set off $22^{\circ} 26\frac{1}{2}'$ N. on decl. arc; and at 11 h. 58 m. 1 s., a.m., l.m.t, observe the sun on the mer-
 idian and obtain a reading of $32^{\circ} 09\frac{1}{2}'$ on lat. arc.
 Thence I run
 North on random line bet. secs. 34 & 35
 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I fail to find.
 80.21 Intersect the pt. for orig. cor. of secs. 26, 27, 34 & 35,
 as determined from stake in S. Epit, firmly set & marked as
 described by Surveyor General, mound obliterated.
 Therefore, the true return bearing is South.

 Thence I run
 North on random line bet. secs. 26 & 27
 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I fail to find
 80.25 Fall 2 lks. W. of pt. for orig. cor. of secs. 22, 23, 26 &
 27, as determined from stake in S.E. pit, firmly set &
 marked by Surveyor General, mound obliterated.
 Therefore, the true return bearing is S. $0^{\circ} 01'$ W.

 Thence I run
 North on random line bet. secs. 22 & 23
 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find
 80.00 Make diligent for orig. cor. of secs. 14, 15, 22 & 23,
 which I also fail to find.
 Therefore, I continue my random line North, bet. secs. 14 & 15.
 120.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail

RETACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

find.

160.00 Make diligent search for orig. cor. of secs. 10, 11, 14 & 15, which I also fail to find.

201.00 Fall 52 lks. E. of point for orig. sec. corr. bet. secs. 10 & 11, as determined from stake in S. pit, firmly set & marked as described by Surveyor General, mound obliterated. Thence I run S. 0° 09' E. on temporary N. & S. line setting temp. sec. & 1/4 sec. cors. at distances proportional to distances given on original plats, and at 201.00 chs. intersect point for orig. cor. of secs. 22, 23, 26 & 27, hereinbefore described.

Thence I run From point for orig. sec. corr. bet. secs. 10 & 11, hereinbefore described. North on random line bet. secs. 10 & 11 on 1/2 mile

400.66 Intersect point for orig. cor. of secs. 2, 3, 10 & 11, as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General, mound obliterated. Therefore, the true return bearing is South.

Thence I run North on random line bet. secs. 2 & 3

40.00 Make diligent search for orig. sec. cor., which I fail to find.

80.72 Intersect N. bdy. of Tp. 42 lks. W. of cor. of secs. 2, 3, 34 & 35, previously re-established by me as described in Book "A" of this group, the true return bearing is therefore S 70° 18' W. June 4th, 1913.

June 5, 1913 at 7 h. 30 m., a.m., 1. mt t., I set off 22° 32 1/2' N. on decl. arc and 32° 15' on lat. arc & determine a mer. with the solar at the cor. of secs. 1, 2, 35 & 36 on N. bdy of Tp., previously re-established by me as described in Book "A" of this group

Thence I run South on random line bet. secs. 1 & 2

40.25 Make diligent search for orig. sec. cor., which I fail to find

80.25 Make diligent search for orig. cor. of secs. 1, 2, 11 & 12, which I also fail to find.

Therefore, I continue my random line South bet. secs. 11 & 12

120.70 Fall 42 lks. E. of point for orig. sec. cor., as determined from stake in S. pit, firmly set & marked as described by Surveyor General, mound-obliterated. Thence I run N. 0° 12' E. on temporary N. and S. line setting temp. sec. & 1/4 sec. cors. at distances proportional to distances given on original plat, and at 120.70 chs. intersect N. bdy. of Tp. at the cor. of secs. 1, 2, 35 & 36, previously re-established by me as described in Book "A" of this group.

Thence I run, from point for orig. sec. cor. Bet. secs. 11 & 12, hereinbefore described. South on random line bet. secs. 11 & 12 on 3/2 mile

40.30 Fall 4 lks. E. of point for orig. cor. of secs. 11, 12, 13 & 14, as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General. Therefore, the true return bearing is N. 0° 03' E.

Thence I run South on random line bet. secs. 13 & 14

40.00 Make diligent search for orig. sec. cor., which I fail to find.

80.00 Make diligent search for orig. cor. of secs. 13, 14, 23 & 24, which I also fail to find.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

- 120.54 Therefore, I continue my random line South bet. secs. 23 & 24
Fall 56 lks. W. of point for orig. sec. cor., bet secs.
23 & 24, as determined by stake in S. pit, firmly set &
marked as described by Surveyor General, mound obliterated.
Thence I run N. & S.
N. $0^{\circ} 16'$ W. on temp. line setting temp. sec. & $\frac{1}{4}$ sec.
cors. at distances proportional to distances given in or-
iginal plat, and at 120.54 chs. intersect point for cor. of
secs. 11, 12, 13 & 14, hereinbefore described.
-
- 40.00 From point for orig. sec. cor. bet. secs. 23 & 24, hereinbefore
described,
I run
South on random line bet. secs. 23 & 24 on $\frac{1}{2}$ mile
Make diligent search for orig. cor. of secs. 23, 24, 25 &
26, which I fail to find,
80.06 Therefore, I continue my random line South bet. secs. 26 & 25
Fall 9 lks. E. of point for orig. sec. cor. as determined from
stake in S. pit, firmly set & marked as described by the
Surveyor General, mound obliterated.
Thence I run N. & S.
N. $0^{\circ} 04'$ E. on temp. line, setting temp. sec. cors. at
distance proportional to distance given on original plat.
and at 80.06 chs. intersect point for orig. sec. cor. bet. secs
23 & 24, hereinbefore described.
-
- 40.00 From the point for orig. sec. cor. bet. secs. 25 & 26 hereinbefore
ly described.
I run
South on random line bet. secs. 25 & 26 on $\frac{1}{2}$ mile
Make diligent search for orig. cor. of secs. 25, 26, 35 &
36, which I fail to find.
80.00 Therefore, I continue my random line South bet. secs. 35 & 36
Make diligent search for orig. sec. cor. which I also fail
to find.
120.72 Intersect S. bdy. of Tp. 10 lks. W, of cor. of secs. 1,
2, 35 & 36, previously re-established by me as described in
Book "A" of this group
Thence I run
N. $0^{\circ} 03'$ W. on temp. line setting temp. $\frac{1}{4}$ sec. & sec.
cors. at distances proportional to distances given on or-
iginal plats, and at 120.72 chs. intersect point for orig. sec.
cor. bet. secs. 25 & 26, hereinbefore described.
-
- 40.24 At the cor. of secs. 25, 30, 31 & 36 on E. bdy. of Tp. I
set off $22^{\circ} 33'$ N. on decl. arc and at 11 h. 58' m. 11 s.,
a.m., l.m.t., observe the sun on the mer. and obtain a
reading of $32^{\circ} 10\frac{1}{2}'$ on lat. arc.
Thence I run
West on random line bet. secs. 25 & 36
Fall 27 lks. S. of point for orig. sec. cor. as determined
from stake in E. pit, firmly set and marked as described by
Surveyor General, Mound obliterated.
Therefore, the true return bearing is S. $89^{\circ} 37'$ E.
-
- 40.050 Thence I run
From the point for orig. sec. cor.
West on random line bet. secs. 25 & 36 on $\frac{1}{2}$ mile
Make diligent search for orig. cor. of secs. 25, 26, 35 &
36, which I fail to find.
80.32 Therefore, I continue my random line West bet. secs. 26 & 35
Fall 7 lks. S. of point for orig. sec. cor. bet. secs. 26 &
35 as determined by stake in E. pit, firmly set & marked
as described by Surveyor General, mound obliterated.
Thence I run
S. $89^{\circ} 57'$ E. on temp. line bet. secs. 26 & 35, on $\frac{1}{2}$ mile
40.16 Set temp. sec. cor., from which I re-establish point for

RETRACEMENT SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

cor. of secs. 25, 26, 35 & 36, N. 2 lks. and 1 lks. W. of temp. cor. for the above numbered secs, set on temp. N. & S. line.

40.16 From the last above mentioned temp. cor. on temp. E. & W. line, I run S. 89° 57' E. on temp. E. & W. line bet. secs. 25 & 36, on W. 1/2 mile. The point for orig. 1/4 sec. cor. bet. secs. 25 & 36, hereinbefore described.

40.13 From the point for orig. 1/4 sec. cor. bet. secs. 26 & 35, hereinbefore described. I run West on random line bet. secs. 26 & 35, on W. half mile. Fall 6 lks. N. of point for orig. cor. of secs. 26, 27, 34 & 35, hereinbefore described. Therefore, the true return bearing is N. 89° 55' E.

40.27 Thence I run West on random line bet. secs. 27 & 34 Fall 16 lks. N. of point for orig. 1/4 sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General, mound obliterated. Therefore the true return bearing is N. 89° 46' E.

40.10 Thence I run From point for orig. 1/4 sec. cor., West on random line bet. secs. 27 & 34, on west half mile. Fall 1 1/2 lks. N. of point for orig. cor. of secs. 27, 28, 33 and 34, hereinbefore described. Therefore, the true return bearing is N. 89° 59' E.

40.01 Thence I run West on random line bet. secs. 28 & 33 Fall 5 lks. S. of pt. for orig. 1/4 sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General, mound obliterated. Therefore, the true return bearing is S. 89° 56' E.

39.95 Thence I run From point for original 1/4 sec. cor., West on random line bet. secs. 28 & 33 on W. 1/2 mile. Make diligent search for orig. cor. of secs. 28, 29, 32 & 33, which I fail to find. Therefore, I continue my random line West, bet. secs. 29 & 32. 80.00 Make diligent search for original 1/4 sec. cor. which I fail to find. 120.05 Make diligent search for orig. cor. of secs. 29, 30, 31 & 32, which I fail to find. Continue on random line W. bet. secs. 30 & 31. 160.05 Make diligent search for 1/4 sec. cor, which I also fail to find. 199.10 Intersect W. bdy. of Tp. 105 lks. S. of cor. of secs. 25, 30, 31 & 36, previously re-established by me, as described. In Book "A" of this Group. Thence I run, S. 89° 52' E. on temp. E. & W. line, bet. secs. 30 and 31. 38.83 Set temp. 1/4 sec. cor. 78.87 Set temp. sec. cor. from which I re-establish point for cor. of secs. 29, 30, 31 & 32 N. 16 lks. & 15 lks. W. from temp. cor. set. for above numbered secs. set on temp. N. & S. line.

RETRACEMENT, SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

- From the last above mentioned temp. corner on temp. E. & W. line,
I run
S. $89^{\circ} 42'$ E. on temp. ^{E. & W.} line bet. secs. 29 & 32
40.11 Set temp. $\frac{1}{4}$ sec. cor.
80.22 Set temp. sec. cor., from which I reestablish point for cor.
of secs. 28, 29, 32 & 33, N. 13 lks. & 4 lks. W. from temp.
cor. for above numbered secs., set on temp. N. and S. line.
From the last above mentioned temp. cor. on E

temp.
From the last above mentioned temp. cor. on E. & W. line
I run
S. $89^{\circ} 42'$ E. on temp. ^{E. & W.} line bet. secs. 28 & 33 on W. $\frac{1}{2}$ mile.
40.01 Pt. for orig. $\frac{1}{4}$ sec. cor., bet. secs. 28 & 33, hereinbefore
described.

June 5th, 1913.

Jan. 6, 1913; At 7h. 30m., a.m., l.m.t., I set off $22^{\circ} 39'$ N.
on decl. arc, $32^{\circ} 12'$ on lat. arc and determine a mer. with
the solar at the cor. of secs. 17, 18, 19 & 24 on W. bdy.
of Tp., previously reestab. by me, as described in Book "A"
of this Group. Thence I run,
38.31 East on random line bet. secs. 18 & 19
Fall 18 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. as determined
from stake in E. pit, firmly set & marked as described by
Surveyor General, mound obliterated.
Therefore, the true return bearing is S. $89^{\circ} 44'$ W.

Thence I run
East on random line from point for orig. $\frac{1}{4}$ sec. cor., bet. sec.
18 & 19, on E. $\frac{1}{2}$ mile.
40.10 Fall 45 lks. N. of point for orig. cor. of secs. 17, 18, 19
& 20, hereinbefore described.
Therefore, the true return bearing is N. $89^{\circ} 21'$ W.

Thence I run
East on random line bet. secs. 17 & 20
40.15 Fall 6 lks. N. of point for orig. $\frac{1}{4}$ sec. cor. as determined
from stake in E. pit, firmly set & marked as described by
Surveyor General, mound obliterated.
Therefore, the true return bearing is N. $89^{\circ} 55'$ W.

Thence I run orig.
From point for $\frac{1}{4}$ sec. cor.
East on random line bet. secs. 17 & 20, on east half mile.
40.05 Fall 6 lks. N. of point for orig. cor. of secs. 16, 17, 20 &
21, hereinbefore described.
Therefore, the true return bearing is N. $89^{\circ} 55'$ W.

Thence I run
East on random line bet. secs. 16 & 21
40.13 Fall 15 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. as determined
from stake in E. pit, firmly set & marked as described by
Surveyor General.
Therefore, the true return bearing is S. $89^{\circ} 47'$ W.

Thence I run
From point for orig. $\frac{1}{4}$ sec. cor.
East on random line bet. secs. 16 & 21, on E. half mile.
40.10 Fall 13 lks. S. of point for ^{orig.} cor. of secs. 15, 16, 21 & 22,
hereinbefore described.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E:

Therefore, the true return bearing is S. 89° 49' W.

40.00 Thence I run East on random line bet. secs. 15 & 22 Fall 16 lks. S. of point for orig. sec. cor., as determined from stake in E. pit, firmly set & marked as described by Surveyor General, mound obliterated. Therefore, the true return bearing is S. 89° 46' W.

40.035 Thence I run From point for orig. sec. cor. East on random line bet. secs. 15 & 22 on E 1/2 mile Make diligent search for orig. cor. of secs. 14, 15, 22 & 23, which I fail to find. Therefore, I continue my random line East bet. secs. 14 & 23 80.06 Make diligent search for orig. sec. cor., which I fail to find 120.085 Make diligent search for orig. cor. of secs. 13, 14, 23 & 24, which I fail to find. Continue random line E. bet. secs. 13 & 24 160.095 Make diligent search for orig. sec. cor., which I also fail to find. 209.42. Intersect E. bdy. of Tp. 23 lks. S. of cor. of secs. 13, 18, 19 & 24, previously re-established by me as described in Book "A" of this group Thence I run S. 89° 56' W. on temp. E. & W. line bet. secs. 13 & 24 40.05 Set temp. 1/4 sec. cor. 80.10 Set temp. sec. cor., from which I reestablish point for cor. of secs. 13, 14, 23 & 24, N. 8 lks. & E. 27 lks. from temp. cor. set for the above numbered secs. on temp. N. & S. line.

From the last above mentioned temp. cor. on temp. E. & W. line I run S. 89° 56' W. on temp. E. & W. line bet. secs. 14 & 23 40.105 Set temp. 1/4 sec. cor. 80.21 Set temp. sec. cor., from which I reestablish the point for cor. of secs. 14, 15, 22 & 23, N. 17 lks. & E. 30 lks. from temp. cor. for the above numbered secs., set on temp. N. & S. line

From the last above mentioned temp. cor. on temp. E. & W. line I run S. 89° 56' W. on temp. E. & W. line bet. secs. 15 & 22 on E 1/2 mile 40.11 The point for orig. sec. cor., hereinbefore described.

At the cor. of secs. 19, 24, 25 & 30 on E. bdy. of Tp. I set off 22° 39 1/2' N. on decl. arc and at 11 h. 58 m. 21 s., a.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 11 1/2' on lat. arc. Thence I run West on random line bet. secs. 24 & 25. 40.065 Make diligent search for orig. sec. cor., which I fail to find. 80.13 Make diligent search for orig. cor. of secs. 23, 24, 25 & 26 which I also fail to find. 120.48. Therefore, I continue my random line West bet. secs. 23 & 26 Fall 10 lks. S. of point for orig. sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General, mound obliterated. Thence I run S. 89° 57' E. on temp. E. & W. line bet. secs. 23 & 26 on E 1/2 mile 40.15 Set temp. sec. cor. from which I reestablish the point for cor. of secs. 23, 24, 25 & 26, N. 10 lks. & 2 lks. E. from temp. cor. for the above numbered secs., set on temp. E. & S. line.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

- From the last above described temp. point on temp. E. & W. line
I run
S. 89° 57' E. on temp. E. & W. line bet. secs. 24 & 25
40.165 Set temp. $\frac{1}{4}$ sec. cor.
280.33 Intersect the cor. of secs. 19, 24, 25 & 30, on E. bdy. of
Tp., previously re-established by me as described in Book
"A" of this group

- From the point for orig. sec. cor. bet. secs. 23 & 26, here-
inbefore described,
I run
40.12 West on random line bet. secs. 23 & 26 on $W\frac{1}{2}$ mile
Intersect point for orig. cor. of secs. 22, 23, 26 & 27, herein-
before described.
Therefore, the true return bearing is East.

- Thence I run
40.42 West on random line bet. secs. 22 & 27
Fall 10 lks. N. of point for orig. sec. cor. as determined
from stake in E. pit, firmly set & marked as described by
Surveyor General, mound obliterated.
Therefore, the true return bearing is N. 89° 50' E.

- Thence I run
From point for orig. sec. cor.
39.965 West on random line bet. secs. 22 & 27 on $W\frac{1}{2}$ mile
Make diligent search for orig. cor. of secs. 21, 22, 27 &
28, which I fail to find.
Therefore, I continue my random line West bet. secs. 21 & 28
79.92 Make diligent search for orig. sec. cor., which I fail to find.
119.875 Make diligent search for orig. cor. of secs. 20, 21, 28 &
29, which I fail to find. Continue random line W. bet. secs. 20 & 29
159.895 Make diligent search for orig. sec. cor., which I fail to find.
199.915 Make diligent search for orig. cor. of secs. 19, 20, 29 &
30, which I fail to find. Continue random line W. bet. secs. 19 & 30
240.22 Intersect point for orig. sec. cor. bet. secs. 19 & 30, as de-
termined from stake in E. pit, firmly set & marked as de-
scribed by Surveyor General, mound obliterated.
Thence I run East
40.05 On temp. E. & W. line bet. secs. 19 & 30 on $E\frac{1}{2}$ mile
Set temp. sec. cor., from which I determine point for cor.
of secs. 19, 20, 29 & 30, N. 26 lks. and 6 lks. W. of temp.
cor. for above numbered secs., set on temp. N. & E. line.

- From the last above mentioned temp. cor. on temp. E. & W. line
I run East
40.07 On temp. E. & W. line bet. secs. 20 & 29
80.14 Set temp. $\frac{1}{4}$ sec. cor.
Set temp. section corner 20, 21, 28 & 29, from which I de-
termine point for cor. of secs. 20, 21, 28 & 29, S. 12 lks.
& 14 lks. E. of temp. cor. for above numbered secs., set on
temp. N. & S. line.

- From the last above mentioned temp. cor. on temp. E. & W. line
I run East on
40.005 temp. E. & W. line bet. secs. 21 & 28
80.01 Set temp. $\frac{1}{4}$ sec. cor.
Set temp. sec. cor. from which I determine point for cor.
of secs. 21, 22, 27 & 28, S. 2 lks. & 23 lks. W. of temp.
cor. for above numbered secs., set on temp. N. & S. line.

RETRACEMENT, SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

From the last above mentioned temp. cor. set on temp. E. & W. line.
 I run,
 E. on temp. E. & W. line bet. secs. 22 & 27 on $\frac{1}{2}$ mile
 40.02 The point for orig. $\frac{1}{4}$ sec. cor., hereinbefore described.

From point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 19 & 30, hereinbefore described.
 I run
 West on random line bet. secs. 19 & 30 on $\frac{1}{2}$ mile
 38.59 Intersect W. bdy. of Tp. 62 lks. S. of cor. of secs. 19, 24 & 30 previously re-established by me & described in Book A of this group
 Therefore, the true return bearing is S. $89^{\circ} 05'$ E., 38.60 chs.

June 6th, 1913.

June 7, 1913:
 At 7 h. 30 m., a.m., l.m.t., I set off $22^{\circ} 45'$ N. on decl. arc, $32^{\circ} 14'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 1, 6, 7 & 12 on W. bdy. of Tp., previously re-established by me as described in Book A of this group
 East on random line bet. secs. 6 & 7
 37.84 Fall 45 lks. N. of point for orig. $\frac{1}{4}$ sec. cor. determined from stake in E. pit firmly set & marked as described by Surveyer General, mound obliterated.
 Therefore, the true return bearing is N. $89^{\circ} 19'$ W.

Thence I run
 From point for orig. $\frac{1}{4}$ sec. cor.,
 East on random line bet. secs. 6 & 7, on east half mile.
 40.00 Make diligent search for orig. cor. of secs. 5, 6, 7 & 8, which I fail to find.

Therefore, I continue my random line East, bet. secs. 5 & 8
 80.06 Fall 7 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 5 & 8, as determined from stake in E. pit, firmly set & marked as described by Surveyer General, mound obliterated.

Thence I run
 S. $89^{\circ} 57'$ W. on temp. E. & W. line bet. secs. 5 & 8 on $\frac{1}{2}$ mile
 40.01 Set temp. sec. cor., from which I reestablish a point for cor. of secs. 5, 6, 7 & 8, N. 9 lks. dist. and 29 lks. E. of temp. cor. for above numbered secs., set on temp. N. & S. line.

From the last above mentioned temp. cor. on temp. E. and W. line.
 I run,
 S. $89^{\circ} 57'$ W. on temp. E. & W. line bet. secs. 6 & 7
 40.05 Pt. for orig. $\frac{1}{4}$ sec. cor., hereinbefore described.

From pt. for orig. $\frac{1}{4}$ sec. cor. bet. secs. 5 & 8, hereinbefore described
 I run
 East on random line bet. secs. 5 & 8 on $\frac{1}{2}$ mile
 39.96 Make diligent search for orig. cor. of secs. 4, 5, 8 & 9, which I fail to find.

Therefore, I continue my random line East, bet. secs. 4 & 9
 80.005 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I also fail to find.

120.20 Fall 10 lks. S. of point for orig. cor. of secs. 3, 4, 9 & 10, hereinbefore described.

Thence I run
 S. $89^{\circ} 57'$ W. on temp. E. and W. line, bet. secs. 4 and 9.
 40.095 Set temp. $\frac{1}{4}$ sec. cor.

80.19 Set temp. sec. cor., from which I reestablish the point for cor. of secs. 4, 5, 8 & 9, N. 15 lks. & E. 9 lks. from temp. cor. for the above numbered secs., set on temp. N. & S. line.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

- From the last above mentioned temp. cor on temp. E. & W. line,
I run S. $89^{\circ} 57' W.$
Point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 5 & 8, on E. half mile
described.
-
- From pt. for orig. cor. of secs. 3, 4, 9 and 10, hereina-
fore described.
I run
East on random line bet. secs. 3 & 10
Fall 50 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. as determined
from stake in E. pit, firmly set & marked as described by
Surveyer General, mound obliterated.
Therefore, the true return bearing is S. $89^{\circ} 17' W.$
-
- Thence I run
From the point for orig. $\frac{1}{4}$ sec. cor.,
East on random line bet. secs. 3 & 10, on E. half mile.
Fall 1 lk. N. of point for orig. cor. of secs. 2, 3, 10 & 11,
hereinafore described.
Therefore, the true return bearing is N. $89^{\circ} 59' W.$
-
- Thence I run
East on random line bet. secs. 2 & 11
Fall 9 lks. N. of point for orig. $\frac{1}{4}$ sec. cor., as determined
from stake in E. pit, firmly set & marked as described by
Surveyer General.
Therefore, the true return bearing is N. $89^{\circ} 52' W.$
-
- Thence I run
From the point for orig. $\frac{1}{4}$ sec. cor.,
East on random line bet. secs. 2 & 11, on E. half mile.
Make diligent search for orig. cor. of secs. 1, 2, 11 & 12,
which I fail to find.
Therefore, I continue my random line. East, bet. secs. 1 and 12.
-
- Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I also fail to
find.
-
- Intersect E. bdy. of Tp. 10 lks. N. of cor. of secs. 1, 6,
7 & 12, previously re-established by me, as described in Book
"A" of this Group. Thence I run,
N. $89^{\circ} 57' W.$ on temp. E. & W. line bet. secs. 1 & 12
-
- Set temp. $\frac{1}{4}$ sec. cor.
Set temp. sec. cor., from which I reestablish point for cor.
of secs. 1, 2, 11 & 12, S. 5 lks. dist. and 7 lks. E. of
temp. cor. for above numbered secs., set on temp. N. & S. line.
-
- From the last above mentioned temp. cor. on temp. E. & W. line.
I run
S. $89^{\circ} 57' W.$ on temp. E. & W. line bet. secs. 2 & 11, on E. half mile.
Point for orig. $\frac{1}{4}$ sec. cor., hereinafore described.
-
- At the cor. of secs. 7, 12, 13 & 18 on E. bdy. of Tp., re-
estab. by me, as described in Book "A" of this Group.
I set off $22^{\circ} 45\frac{1}{2}' N.$ on decl. arc and at 11 h., 38 m.
32 s., a.m., l.m.t., observe the sun on the mer. and obtain
a reading of $32^{\circ} 13'$ on lat. arc.
Thence I run
West on random line bet. secs. 12 & 13
Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find.
Fall 5 lks. N. of point for orig. cor. of secs. 11, 12, 13 & 14,
hereinafore described.
Therefore, the true return bearing is N. $89^{\circ} 53' E.$

RETRACEMENT, SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

40.13 Thence I run
West on random line bet. secs. 11 & 14
Fall 8 lks. S. of pt. for orig. $\frac{1}{4}$ sec. cor., as determined by stake in E pit, firmly set & marked as described by the Surveyer General, mound obliterated.
Therefore, the true return bearing is S. 89° 53' E.

39.945 Thence I run
From point for orig. $\frac{1}{4}$ sec. cor.
West on random line bet. secs. 11 & 14, on W. $\frac{1}{2}$ mile.
Make diligent search for orig. cor. of secs. 10, 11, 14 & 15, which I fail to find. Continue on random line, bet. secs. 10 & 15.
79.995 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I also fail to find.
119.92 Fall 28 lks. N. of point for orig. cor. of secs. 9, 10, 15 & 16, hereinbefore described.

40.01 Thence I run E. & W.
N. 89° 52' E. on temp. line bet. secs. 10 & 15
Set temp. $\frac{1}{4}$ sec. cor.
80.02 Set temp. sec. cor., from which I determine point for cor. of secs. 10, 11, 14 & 15, N. 26 lks. dist. & 39 lks. E. of temp. cor. for the above numbered secs., set on N. & S. line temp.

39.90 From the last above mentioned temp. cor. on E. & W. line I run E. & W.
N. 89° 52' E. on temp. line bet. secs. 11 & 14, on W. $\frac{1}{2}$ mile.
The point for $\frac{1}{4}$ sec. cor., hereinbefore described.

40.05 From the point for orig. cor. of secs. 9, 10, 15 & 16, hereinbefore described. I run
West on random line bet. secs. 9 & 16
Fall 42 lks. N. of point for orig. $\frac{1}{4}$ sec. cor., as determined from stake in E. pit, firmly set & marked as described by Surveyer General, mound obliterated.
Therefore, the true return bearing is N. 89° 24' E.

40.055 Thence I run orig.
From the point for $\frac{1}{4}$ sec. cor.
West on random line bet. secs. 9 & 16, on W. $\frac{1}{2}$ mile. (find.)
Make diligent search for orig. cor. sec. 8, 9, 16 & 17, which I fail to find. Therefore, I continue my random line, West, bet. secs. 8 & 17.
80.24 Fall 23 lks. N. of pt. for orig. $\frac{1}{4}$ sec. cor. bet. secs. 8 & 17, as determined from stake in E. pit, firmly set & marked as described by Surveyer General, mound obliterated.

40.07 Thence I run E. & W.
N. 89° 50' E. on temp. line bet. secs. 8 & 17, on E. $\frac{1}{2}$ mile.
Set temp. sec. cor. from which I determine the point for cor. of secs. 8, 9, 16 & 17, N. 22 lks. dist. & 6 lks. E. of temp. cor. for the above numbered secs., set on N. & S. line temp.

40.17 From the last above mentioned temp. cor. on E. & W. line I run E. & W.
N. 89° 50' E. on temp. line bet. secs. 9 & 16, on W. $\frac{1}{2}$ mile.
The point for $\frac{1}{4}$ sec. cor., hereinbefore described.

From the point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 8 & 17
The point for orig. cor. of secs. 7, 8, 17 & 18, being plainly visible, I run
N. 89° 50' W. far said cor. pt. on true line, W. $\frac{1}{2}$ mile, bet. sec. 8 and 17.

RETRACEMENT AND
RESURVEY OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

40.16 The point for ^{orig.} cor. of secs. 7, 8, 17 & 18, hereinbefore described.

Pt. for orig. $\frac{1}{4}$ sec. cor. being plainly visible
I run

40.05 N. $89^{\circ} 55'$ W. on true line for said cor. pt. bet. secs. 7 & 18.
Intersect pt. for orig. $\frac{1}{4}$ sec. cor., as determined from stake in E. pit, firmly set & marked as described by Surveyor General, mound obliterated.

The cor. The cor. of secs. 7, 12, 13 & 18 on W. bdy. of Tp., being plainly visible,
I run
N. $89^{\circ} 20'$ W. on true line from pt. for orig. $\frac{1}{4}$ sec. cor. bet. secs. 7 & 18, on W. half mile.
37.83 Intersect W. bdy. of Tp. at cor. of secs. 7, 12, 13 & 18, reestab. by me, as described in Book "A" of this Group.

June 7th, 1913.

RESURVEY OF SUBDIVISION LINES OF T. 14 S., RANGE 25 EAST.

June 9th, 1913:

At 8 h. 0 m., a.m., l.m.t., I set off $22^{\circ} 56'$ N. on decl. arc, $32^{\circ} 09\frac{1}{2}'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 1, 2, 35 & 36 on S. bdy. of Tp. previously reestab. by me, as described in Book "A" of this Group.

Thence I run

N. $0^{\circ} 03'$ W. on true line bet. secs. 35 & 36

Over level land, through lane.

40.24 Set an iron post 7 ft. long, 1 in. in dia., 26 ins. in the ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd $\frac{1}{4}$ S. 35 in W., S 36 in E. & 1913 in S half.

Dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

590000 Dry wash 10 lks. wide, 1 ft. deep, course S. 60° W.

59.00 House, bears W. 2 chs. dist.

80.48 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 25, 26, 35 & 36, with a brass cap marked T. 14 S., R. 25 E in N., & 1913 in S. half, S 26 in N.W., S 25 in N.E., S 36 in S.E. & S 35 in S.W. quadrant.

Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.

Land level.

Soil adobe 12 ins. deep, on hardpan sub-soil

Short salt grass,

No timber.

Thence I run

S. $89^{\circ} 55'$ E. on true line bet. secs. 25 & 36

Over level land.

.75 Wire fence along E. edge of lane, bears N. & S. N.W. cor. of fence bears N. 15 lks. dist. Thence parallel to and S. of lane through pasture.

40.16 Intersect point for orig. $\frac{1}{4}$ sec. cor., hereinbefore described. This cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor. with a brass cap marked $\frac{1}{4}$ S. 25 in N. & S 36 1913 in S half. of post

Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

Note: the above described cor. falls in fence line along S. edge of lane.

Thence I run

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 S., RANGE 25 EAST.

39.75 S. 89° 37' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 25 & 36 on E. half mile.
Through lane
West line of N. & S. lane. N.E. cor. of wire fence bears S. 15 lks.
40.24 Intersect E. bdy. of Tp. at the cor. of secs. 25, 30, 31 & 36, previously reestab. by me, & described in Book "A" of this Land level. Group.
Soil adobe, 12 ins. deep, on hardpan sub-soil.
Short salt grass, scattering mesquite 3 to 4 ft. high.
No timber.

From the cor. of secs. 25, 26, 35 & 36, hereinbefore described
I run
N. 0° 02' W. on true line bet. secs. 25 & 26
Over level land, through lane.
1.15 S.W. cor. of wire fence, bears E. 75 lks.
40.24 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor., being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S. 26 in W., S 25 in E. & 1913 in S. half.
Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Thence I run
N. 0° 06' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 25 & 26, on north half mile.
Note: From the above described cor. N.W. cor. of wire fence bears E. 50 lks.
Thence parallel to and 50 lks. E. of wire fence.
39.50 N.E. cor. of wire fence, bears W. 50 lks.
40.03 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 23, 24, 25, & 26, with a brass cap marked T. 14 S R 25 E in N. & 1913 in S half, S 23 in N.W., S 24 in N.E., & S 25 in S.E. & S 26 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec., $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level.
Soil adobe, 12 ins. deep, on hardpan sub-soil
Short salt grass, no timber,
Note: Wagon road follows along this line

Thence I run
S. 89° 53' E. on true line bet. secs. 24 & 25
Over level land.
.50 S.W. cor. of wire fence, bears N. 50 lks., thence parallel to and 50 lks. S. of wire fence.
39.20 House bears N. $14\frac{1}{2}$ ° W.
40.165 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 24 in N. & S 25 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
79.75 Wagon road, bears N. & S.
80.33 Intersect E. bdy. of Tp. at the cor. of secs. 19, 24, 25 & 30, previously reestablished by me, as "described in Book "A" Land level. (of this Group.
Soil adobe, 12 to 13 ins. deep, on hardpan sub-soil.
Short salt grass.
No timber.

From the cor. of secs. 23, 24, 25 & 26, hereinbefore described.
I run
N. 0° 02' E. on true line bet. secs. 23 & 24

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

	Over level land, through lane. Note: From the above described cor. house bears N. $69\frac{1}{4}^{\circ}$ E. N.E. cor. of wire fence, bears W. 50 lks., thence parallel to and 50 lks. W. of wire fence.
20.00	
40.03	Intersect the point for orig ^l sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows: Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 23 in W., S 24 in E. & 1913 in S half. of post Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor. Thence I run N. $9^{\circ} 07'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 23 & 24, on N. half mile.
23.00	Dry wash 15 lks. wide, course S. 45° W.
30.00	Enter scattering mesquite 3 to 4 ft. high, bears E. & W.
39.50	N.W. cor. of wire fence, bears E. 25 lks.
40.18	Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in ground, for reestab. cor. of secs. 13, 14, 23 & 24, with a brass cap marked T 14 S R 25 E in N., & 1913 in S half, S 14 in N.W., S. 13 in N.E., S 24 in S.E., & S 23 in S.W. quadrant. Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. Land level & rolling. Soil, adobe, 12 to 18 ins. deep on hardpan subsoil. Short salt grass, scattering mesquite brush at N. End of line. No timber. At the above described cor. I set off $22^{\circ} 56\frac{1}{2}'$ N. on decl. arc, and at 11 h. 58 m. 55 s., a.m., l.m.t., observe the sun on the mer. and obtain a reading of $32^{\circ} 12'$ on lat. arc.

	Thence I run N. $89^{\circ} 59'$ E. on true line bet. secs. 13 & 24
1.00	Over level land through lane.
40.05	Phone line bears N. & S. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground, for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 13 in N., S 24 1913 in S half. of post Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. and raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
80.10	Intersect E. bdy. of Tp. at the cor. of secs 13, 18, 19 & 24, previously reestab. by me, and described in Book "A" of this Gp. Land level soil adobe. 12 to 18 ins. deep, on hardpan sub-soil Short salt grass. No timber. Note: wagon road follows along this line.

	From the cor. of secs. 13, 14, 23 & 24, hereinbefore described I run N. $0^{\circ} 27'$ W. on true line bet. secs. 13 & 14
1.00	Over slightly rolling land, through scattering mesquite brush 2 to 4 ft. high.
2.00	Wire fence, bears E. & W.
3.00	Phone line, bears N. 30° W., S. 30° E.
18.00	Phone line, bears E. & W.
30.00	House, bears N. $37\frac{1}{2}^{\circ}$ E.
40.18	Leave rolling land, thence over level land Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 14 in W. S 13 in E. & 1913 in S. half. of post Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor. Note: from the above described cor. house bears S. 89° E. S.W. cor. of wire fence, bears E. 6 lks. dist., also wire fence runs W. from this cor.
80.30	

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

80.36 ~~Intersect to the point for orig. cor. of secs. 11, 12, 13 & 14,~~ previously described. This old cor., being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 11, 12, 13 & 14, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 11 in N.W., S 12 in N.E., S 13 in S.E. & S 14 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor..
 Land level & rolling.
 Soil adobe, 12 to 24 ins. deep on hardpan sub-soil
 Short salt grass, scattering mesquite brush, 3 to 6 ft. high.
 No timber.

 Thence I run
 N. 89° 58' E. on true line bet. secs. 12 & 13
 Over level land, through mesquite brush 3 to 6 ft. high, parallel to and 6 lks. N. of wire fence.
 .06 Wire fence, bears N. & S.
 18.00 Dry wash 10 lks. wide,, course S. 30° W.
 20.00 N.E. cor. of wire fence, bears S. 10 lks.
 40.465 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground, for reestablish 1/4 sec. cor., with a brass cap marked 1/4 S 12 in N. & S 13 1913 in S half.
 Dig pits 18 x 18 x 12 ins. E. & W. of post 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 50.00 Wagon road, bears N. & S.
 72.00 Foundation of house on line.
 75.00 House, bears N. 3 chs. dist.
 80.43 Wire fence, bears N. & S.
 80.93 Intersect E. bdy. of Tp. at the cor. of secs. 7, 12, 13 & 18, previously re-estab. by me, and described in Book "A" of this Group. Land, level and rolling.
 Soil adobe, 12 to 18 ins. deep, on hardpan sub-soil.
 Scattering grass & scattering mesquite brush, 3 to 6 ft. high,
 No timber.

 From the cor. of secs. 11, 12, 13 & 14, hereinbefore described
 I run
 N. 0° 03' E. on true line bet. secs. 11 & 12
 Over level land, parallel to and 6 lks. W. of wire fence.
 33.00 House bears N. 71 1/4° E. 20 chs. dist.
 40.24 N.W. cor. of wire fence, also S.E. cor. of wire fence bears W. 50 lks. from this point.

40.30 Intersect point for orig 1/4 sec. cor., previously described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 11 in W., S 12 in E & 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.

Thence I run
 N. 0° 18' E. from 1/4 sec. cor. on true line bet. secs. 11 & 12, on N. half mile.
 Over slightly rolling land, through center of lane.
 40.15 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in ground for reestab. con. of secs. 1, 2, 11 & 12, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 2 in N.W., S 1 in N.E., S 12 in S.E. & S 11 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor..
 Land level & rolling.
 Soil S 1/2 adobe, 12 ins. deep on hardpan sub-soil. N 1/2 loose, sandy loam, 24 ins. deep/

LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

Short grass, scattering mesquite brush 3 to 6 ft. high.
No timber.

Thence I run

S. 89° 59' E. on true line bet. secs. 1 & 12

Over slightly rolling sandy land through mesquite brush
3 to 6 ft. high, parallel to and 50 lks. S. of wire fence.

.50 Wire fence, bears N. & S.

35.00 Wagon road, bears N. & S.

40.295 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground, for
reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 1 in N.,
S 12 1913 in S half.

Dig pits 18 x 18 x 12 ins. E. & W. of post
3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

42.50 Wire fence and phone line, bears N. 39° W. S. 89° E.

80.59 Intersect E. bdy. of Tp. at cor. of secs. 1, 6, 7 & 12,
previously re-estab. by me, as described in Book "A" of this
Group. Land, level, and rolling.

Loose, sandy soil, 24 ins. deep, scattering short grass
Mesquite brush 3 to 6 ft. high

No timber.

Note: wagon road follows along last 37 chs. of this line.

From the cor. of secs. 1, 2, 11 & 12, hereinbefore de-
scribed

I run

N. 0° 09' E. on true line bet. secs. 1 & 2

Over slightly rolling sandy land, through lane.

90.50 Wire fence, bears E. & W. leave land, thence through mes-
quite brush 3 to 6 ft. high.

.75 Wagon road, bears E. & W.

40.05 Wire fence, bears E. & W.

40.15 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground, for
reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S, 2 in W, S 1 in E & 1913
in S. half.

Dig pits 18 x 18 x 12 ins. N. & S. of post
3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

62.00 S.W. cor. of wire fence, bears E. 50 lks., thence parallel
to & 50 lks. W. of wire fence.

68.50 N.E. cor. of wire fence, bears E. 50 lks. dist.

78.00 Wagon road, bears N.W. & S.E.

80.00 Wire fence, bears N.W. & S.E.

80.55 Intersect N. bdy. of Tp. at the cor. of secs. 1, 2, 35 &
36 previously re-estab. by me, as described in Book "A" of
this Group. Land, level and rolling.

Loose, sandy soil, 24 ins. deep

Scattering short grass, mesquite brush 3 to 6 ft. high

No timber.

June 9th, 1913.

June 10, 1913:

At 8 $\frac{1}{2}$ a.m., 30 m., a.m., l.m.t., I set off 23° 00'
N. on decl arc, 32° 09' $\frac{1}{2}$ " on lat. arc and determine a mer.
with the solar at the cor. of secs. 2, 3, 34 & 35 on S. bdy.
of Tp., previously reestab. by me, as described in Book "A"
of this Group. Thence I run,

North on true line bet. secs. 34 & 35

Over dry bed of old alkali lake.

30.00 Leave dry bed of old alkali lake, thence over rolling
wind built sand ridges.

40.105 Set an iron post 3 ft. long 1 in. in dia., 26 ins. in
ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ 34 in
W., S 35 in E. & 1913 in S half.

Dig pits 18 x 18 x 12 ins. N. & S. of post
3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

80.21 Intersect point for orig. cor. of secs. 22, 26, 27, 34 & 35,
previously described. This old cor. being in a state of
delapidation, I destroy all trace of same, in cor. and
re-establish it in the same place, as follows:

RESURVEY OF SUBDIVISION LINES OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 26, 27, 34 & 35, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 27 in N.W., S 26 in N.E., S 35 in S.E. & S 34 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil S. 30 chs. alkali. N. 50 chs. very sandy.
 No vegetation.

 Thence I run
 N. 89° 55' E. on true line bet. secs. 26 & 35
 Over rolling sandy & alkali land
 40.13 Intersect the point for orig. sec. cor., hereinbefore described. This old cor. being in state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 26 in N. & S 35 1913 in S half.
 Dig pits 18 x 18 x 12 ins. E. & W. of post 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 Thence I run
 S. 89° 59' E. from 1/4 sec. cor. on true line bet. secs. 26 & 35, on east half mile.
 Over level prairie land
 18.00 Wire fence, bears N. & S., also house, bears N. 53 1/2° E
 33.00 Dry wash 10 lks. wide, 4 ft. deep, course South
 39.66 Wire fence, bears N. & S.
 40.16 Intersect the cor. of secs. 25, 26, 35 & 36, hereinbefore described.
 Note: from the above corner, cap. house bears. N. 59° W
 Land rolling.
 Soil alkali.
 No vegetation on W 1/2 of mile. Short salt grass on E 1/2.
 No timber.

 From the cor. of secs. 26, 27, 34 & 35, hereinbefore described
 I run
 N. 0° 01' E. on true line bet. secs. 26 & 27
 Over rolling alkali land.
 2.00 Wash 6 ft. deep, 50 lks. wide, small stream of alkali water 10 lks. wide, 6 ins. deep, course West. Small alkali spring bears E. 2 chs. dist.
 Thence Over level prairie land.
 40.125 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestablish sec. cor. with brass cap, mkd 1/4 S 27 in W., S 26 in E. & 1913 in S. half.
 Dig pits 18 x 18 x 12 ins. N. & S. of post 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 52.00 Wagon road, bears N. 60° E., S. 60° W.
 53.00 Wash 15 lks. wide, 5 ft. deep, course West. Stream of alkali water 10 lks. wide, 6 ins. deep, water seeping out of banks of wash.
 80.25 Intersect the point for orig. cor. of secs. 22, 23, 26 & 27, previously described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 22, 23, 26 & 27, with a brass cap marked T 14 S R 25 E in N., & 1913 in S half, S 22 in N.W., S 23 in N.E., S 26 in S.E. & S 27 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil sandy & alkali.
 Short salt grass.
 No timber.
 Note: from the above described cor. ruins of old adobe house, bears. N. 35 1/4° E.

LINES
RESURVEY OF SUBDIVISIONS OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

	Thence I run East on true line bet. secs. 23 & 26 Over level prairie land.
16.00	Wagon road, bears N. & S.
40.12	Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows: Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 23 in N. & S 26 1913 in S half. of post Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
	Thence I run N. $89^{\circ} 54'$ E. on true line from $\frac{1}{4}$ sec. cor. bet. secs. 23 & 26, on E. half mile.
	Over level, prairie land, through lane. Fence cors. bear N. 50 Lks. & S. 50 lks. dist. from the above described cor. House, bears S. 2 chs. dist.
3.50	W. edge of N. & S. lane.
39.65	Intersect cor. of secs. 23, 24, 25 & 26, hereinbefore described.
40.15	Land level. Soil alkali Short salt grass. No timber.

	From the cor. of secs. 22, 23, 26 & 27, hereinbefore described I run N. $0^{\circ} 04'$ E. on true line bet. secs. 22 & 23
	Over level prairie land
19.50	Dry wash 25 lks. wide, 2 ft. deep, course S. 60° W.
40.20	Set an iron post 3 ft. long, 2 ins. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 22 in W., S 23 in E. & 1913 in S half. of post Dig pits 18 x 18 x 12 ins. N. & S. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
45.22	Ruins of old adobe house, bears S. $61\frac{1}{4}^{\circ}$ E. 20 chs. dist.
63.50	Wagon road, bears N. 45° W., S. 45° E.
80.40	Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 14, 15, 22 & 23, with brass cap, marked T 14 S R 25 E in N., & 1913 in S half, S 15 in N.W., S 14 in N.E., S 23 in S.E. & S 22 in S.W. quadrant. Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. Land level. Soil adobe, 12 ins. deep, on hardpan sub-soil Short salt grass. No timber. Note: at the above described cor. I set off $23^{\circ} 01\frac{1}{2}'$ N. on decl. arc, and at 11 h. 59 m. 7 s., a.m., l.m.t., observe the sun on the mer. and obtain a reading of $32^{\circ} 12'$ on lat. arc.

	Thence I run East on true line bet. secs. 14 & 23
	Over level, prairie land
40.105	Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with brass cap, mkd. $\frac{1}{4}$ S 14 in N. & S 23 1913 in S half. of post Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
41.35	Small cabin, bears S. $18\frac{1}{4}^{\circ}$ E.
48.52	Wagon road, bears N. & S.
52.00	Wagon road, bears N. & S.
75.00	Small cabin, bears S. $40\frac{3}{4}^{\circ}$ W.
80.21	Intersect the cor. of secs. 13, 14, 23 & 24, hereinbefore described. Land level & rolling.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

Soil adobe, 12 ins. deep on hardpan sub-soil
Short salt grass
No timber.

From the cor. of secs. 14, 15, 22 & 23, hereinbefore described
I run
N. 0° 05' W. on true line bet. secs. 14 & 15
Over level prairie land

40.20 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. ~~1~~ sec. cor. with brass cap marked $\frac{1}{4}$ S 15 in W., S 14 in E. & 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

52.00 Wagon road, bears NW and SE.

56.50 Wire fence & telephone line, bears N. 80° W., S. 80° E. fence cors. 1 ch. W. of line, thence parallel to and 1 ch. E. of wire fence, over rolling sandy land.

80.40 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 10, 11, 14 & 15, with a brass cap marked T 14 S R 25 E in N. & 1913 in S. half, S 10 in N.W., S 11 in N.E., S 14 in S.E. & S 15 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth $\frac{1}{2}$ ft. base 2 ft. high W. of cor.
Land level & rolling.
Soil adobe on S. 56 chs., 12 ins. deep on hardpan sub-soil.
N. 24 chs. very sandy wind built sand ridges.
Short salt grass, scattering mesquite brush 3 to 4 ft. high on N. end of line.
No timber.

Thence I run
S. 89° 47' E. on true line bet. secs. 11 & 14
Over rolling sandy land through mesquite brush 3 to 4 ft. high.

39.90 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 11 in N. & S 14 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

Thence I run
S. 89° 53' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 11 & 13, on E. half mile.
Leave mesquite brush, thence over level prairie land.

35.00 Wire fence, bears N. 89° W., S. 89° E.

40.13 Intersect cor. of secs. 11, 12, 13 & 14, hereinbefore described.
Land level & rolling.
Soil $W\frac{1}{2}$ loose sandy in windbuilt ridges. $E\frac{1}{2}$ adobe, 12 ins. deep on hardpan sub-soil
Short salt grass, scattering mesquite brush 3 to 4 ft. high on W. half of mile.
No timber.

From the cor. of secs. 10, 11, 14 & 15, hereinbefore described
I run
N. 0° 43' W. on true line bet. secs. 10 & 11
Over rolling, sandy land, through scattering mesquite brush 1 to 3 ft. high.

1.00 Wire fence, bears E. & W., thence parallel to & 75 lks. E. of wire fence.

40.15 Wire fence, bears E. & W.

LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

- ✓40.20 Intersect point for orig¹/₄ sec. cor., hereinbefore de-
 scribed. This old cor. being in a state of delapidation,
 I destroy all trace of the same, cor. and re-establish it
 in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
 ground for ¹/₄ sec. cor., with a brass cap marked ¹/₄ S 10 in
 W., S 11 in E. & 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. ¹/₃ ft. dist. & raise
 mound of earth ³/₈ ft. base ¹/₂ ft. high W. of cor.
 Thence I run
 ✓North from ¹/₄ sec. cor. on true line ^{N. ¹/₂} bet. secs. 10 & 11
 Parallel to and 50 lks. E. of wire fence.
 20.00 S.W. cor. of wire fence, bears E 50 lks. dist., thence
 through center of lane
 39.50 Wire fence, bears E. & W.
 ✓40.06 Intersect point for orig. cor. of secs. 2, 3, 10 & 11, herein
 before described. This old cor. being in a state of de-
 lapidation, I destroy all trace of the same, cor. and re-
 establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in
 ground for cor. of secs. 2, 3, 10 & 11, with a brass cap
 marked T 14 S R 25 E in N. & 1913 in S half, S 3 in N.W.,
 S 2 in N.E., S 10 in S.E. & S 10 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. ⁵/₈ ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil very sandy, fine texture, 24 ins. deep.
 Scattering grass & mesquite & sage brush 1 to 4 ft. high.
 No timber.
-
- Thence I run
 ✓S. 89° 52' E. on true line bet. secs. 2 & 11
 Over level land, through scattering mesquite brush 3 to
 6 ft. high along land.
 17.00 House, bears S. 3 chd. dist.
 30.00 Phone line bears N. 80° W. S. 80° E.
 ✓40.40 Intersect point for orig¹/₄ sec. cor., hereinbefore described.
 This old cor. being in a state of delapidation, I destroy
 all trace of the same, cor. and re-establish it in the same
 place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the
 ground for ¹/₄ sec. cor., with a brass cap marked ¹/₄ S 2 in
 N. & S 11 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. ¹/₃ ft. dist. & raise
 mound of earth ³/₈ ft. base ¹/₂ ft. high N. of cor.
 Thence I run
 ✓S. 89° 53' E. from ¹/₄ sec. cor. on true line bet. secs.
 2 & 11 on E. half mile.
 .06 Wire fence, bears N. & S., thence parallel to & 50 lks.
 N. of wire fence.
 8.09 Wire fence & phone line, bears N. 89° E. S. 89° W.
 -39.75 Wire fence along W. edge of lane, bears N. & S.
 ✓40.24 Intersect cor. of secs. 1, 2, 11 & 12, hereinbefore de-
 scribed.
 Land level & rolling.
 Soil loose, sandy loam, fine texture, 24 ins. deep.
 Scattering grass, mesquite brush 3 to 6 ft. high
 No timber.
-
- From the cor. of secs. 2, 3, 10 & 11, hereinbefore de-
 scribed
 I run
 ✓N. 0° 18' E. on true line bet. secs. 2 & 3
 Over level sandy land, through mesquite brush 3 to 6 ft.
 high.
 15.15 Wagon road, bears E. & W.
 .50 S.W. cor. of wire fence, bears E. 50 lks., thence parallel
 to and 50 lks. W. of wire fence.
 ✓40.20 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in

LINES
RESURVEY OF SUBDIVISIONS OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ S 3 in W., S 2 in E. & 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 41.00 Wire fence, bears E. & W., thence parallel to and 50 lks. E. of wire fence.
 47.00 Cabin bears E. 5 chs. dist.
 80.00 Wire fence, bears E. & W.
 80.72 Intersect N. bdy. of Tp. at the cor. of secs. 2, 3, 34 & 35, previously re-estab. by me, as described in Book "A" of Land level (this Group).
 Soil loose sandy, fine texture, 24 ins. deep.
 Scattering grass, mesquite brush 3 to 6 ft. high.

June 10th, 1913.

June 11, 1913:

At 8 h. 30 m., a.m., l.m.t.; I set off $23^{\circ}05\frac{1}{2}'$ N. on decl arc, $32^{\circ}09\frac{1}{2}'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 3, 4, 33 & 34, on S bdy. of Tp. previously reestab. by me, as described in Book "A" of this Group.
 Thence I run
 N. $0^{\circ}21'$ W. on true line bet. secs. 33 & 34,
 Over dry bed of old alkali lake.
 39.67 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 33 in W., S 34 in E. & 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

Thence I run
 North from $\frac{1}{4}$ sec. cor. on true line $N. \frac{1}{2}$ bet. secs. 33 & 34
 39.95 Intersect point for orig. cor. of secs. 27, 28, 33 & 34, previously described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 27, 28, 33 & 34, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 28 in N.W., S 27 in N.E., S 34 in S.E. & S 33 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil alkali.
 No vegetation.

Thence I run
 N. $89^{\circ}59'$ E. on true line bet. secs. 27 & 34
 Over dry bed of old alkali lake.
 40.10 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 27 in N. & S 34 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

Thence I run
 N. $89^{\circ}46'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 27 & 34, on east half mile.

10.00 Leave dry bed of old alkali lake, bears N.W. & S.E. Thence over rolling alkali land.

18.50 Wagon road, bears N. & S.
 28.50 Wagon road, bears N. & S.

38.00 Dry wash 25 lks. wide, 3 ft. deep, course S. 30° W.

40.27 Intersect cor. of secs. 26, 27, 34 & 35, hereinbefore described.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

Land level & rolling.
Soil alkali
No vegetation

From the cor. of secs. 27, 28, 33 & 34, hereinbefore described

I run

✓ N. 0° 04' W. on true line bet. secs. 27 & 28

Over dry bed of old alkali lake

40.17 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor., being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 28 in W., S 27 in E. & 1913 in S half.

Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

Thence I run

✓ N. 0° 11' W. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 27 & 28, on N. half mile.

30.00 Leave dry bed of old alkali lake, bears N.W. & S.E., thence over rolling alkali land.

40.05 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 21, 22, 27 & 28, with a brass cap marked T 14 S R 25 E in N. & 1913 in S. half, S 21 in N.W., S 22 in N.E., S 27 in S.E. & S 28 in S.W. quadrant.

Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.

Lane level & rolling.

Soil alkali.

No vegetation.

Thence I run

✓ N. 89° 58' E. on true line bet. secs. 22 & 27

Over rolling alkali land

Dry wash 25 lks. wide, course S. 15° W.

28.00
40.02 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 22 in N. & S 27 1913 in S half.

Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

Thence I run

✓ N. 89° 50' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 22 & 27, on east half mile.

Leave rolling alkali land, thence over level alkali prairie

40.42 Intersect cor. of secs. 22, 23, 26 & 27, hereinbefore described.

Land level & rolling.

Soil alkali

Short salt grass on E $\frac{1}{2}$. No vegetation on W $\frac{1}{2}$.

No timber.

From the cor. of secs. 21, 22, 27 & 28, hereinbefore described

I run

✓ N. 0° 19' E. on true line bet. secs. 21 & 22

Over rolling alkali land

40.05 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with a brass cap, mrd., $\frac{1}{4}$ S 21 in W., 22 in E. & 1913 in S half.

Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.


LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

60.00 Enter dry bed of small alkali lake, extends 3 chs. E. & 6 chs. W. of line.

67.00 Leave dry bed of alkali lake, bears E. & W., thence over level alkali prairie

80.04 Wire fence, bears E. & W., fence corners 6 lks. E. of line.

80.10 Intersect point for orig. cor. of secs. 15, 16, 21 & 22, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 15, 16, 21 & 22, with a brass cap marked T 14 S R 25 E in N. & 1913 in S. half, S 16 in N.W., S 15 in N.E., S 21 in S.W. & S 22 in S.E. quadrants.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil alkali
 Short salt grass
 No timber




Thence I run
 N. 89° 46' E. on true line bet. secs. 15 & 22
 Over rolling, prairie land

09.06 Wire fence, bears N. & S. W., S. 30° E.

40.00 Intersect point for orig. 1/4 sec. cor. hereinbefore described. this old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 15 in N. S 22 1917 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 Thence I run
 N. 89° 41' E. from 1/4 sec. cor. on true line bet. secs. 15 & 22, on E. 1/2 mile.

31.00 Wagon road, bears N. 30° W., S. 30° E.

40.11 Intersect the cor. of secs. 14, 15, 22 & 23 hereinbefore described.
 Land level & rolling.
 Soil alkali 12 ins. deep on hardpan subsoil.
 Short salt grass.
 No timber.



From the cor. of secs, 15, 16, 21 & 22, hereinbefore described
 I run
 North on true line bet. secs. 15 & 16
 Over rolling prairie land, parallel to & 6 lks. W. of wire fence.

40.115 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestablish sec. cor. with brass cap, mkd. 1/4 S 16 in W. S 15 in E. & 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.

69.00 Windmill bears W. 3 chs. dist.

80.13 Wire fence, bears E. & W., NE. cor. of wire fence, bears E. 6 lks. dist.

80.23 Intersect the point for orig. cor. of secs. 9, 10, 15 & 16, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it at the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 9, 10, 15 & 16, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half. S 9 in N.W., S 10 in N.E., S 15 in S.E. & S 16 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil adobe 12 ins. deep on hardpan sub-soil.
 Short salt grass. No timber.

LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

	<p>Thence I run \checkmark N. $89^{\circ} 41'$ E. on true line bet. secs. 10 & 15 Over level prairie land 17.00 Wagon road, bears N. 60° W. S 60° E. 40.01 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in the ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 10 in N. & S 15 1913 in S half. of post Dig pits 13 x 13 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor. 48.00 Dry wash 20 lks. wide, 2 ft. deep, course S. 30° W. 59.00 S.W. cor. of wire fence, bears N. 50 lks. dist., thence parallel to and 50 lks. S. of wire fence. 79.00 Wire fence, bears N. & S. 80.02 Intersect cor. of secs. 10, 11, 14 & 15, hereinbefore de- scribed. Land level & rolling. Soil W 60 chs. adobe, 12 ins. deep on hardpan sub-soil E. 20 chs. loose sandy soil, in windbuilt ridges. Short saltgrass, scattering mesquite & sage brush 2 to 4 ft. high, on E. end of line. No timber.</p> <p style="text-align: center;">-----</p> <p>From the cor. of secs. 9, 10, 15 & 16, hereinbefore de- scribed. I run \checkmark North on true line bet. secs. 9 & 10 Over level prairie land. 8.00 Wagon road, bears N. 60° W., S. 60° E. 40.19 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows: Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 9 in W S 10 in E. & 1913 in S half. of post Dig pits 13 x 13 x 12 ins. N. & S. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor. Thence I run \checkmark N. $0^{\circ} 04'$ W. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 9 & 10, on N. $\frac{1}{2}$ mile. 30.00 Leave level prairie land, thence over windbuilt sand ridges through mesquite & sage brush 2 to 4 ft. high, bears E. & W 39.96 Intersect point for orig. cor. of secs. 3, 4, 9 & 10, herein- before described, this old cor. being in a state of de- lapidation, I destroy all trace of the same, and re- establish it in the same place, as follows: Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 3, 4, 9 & 10, with a brass cap marked $\frac{1}{4}$ 14 S R 25 E in N. & 1913 in S half, S 4 in N.W., S 3 in N.E., S 10 in S.E. & S 9 in S.W. quadrant. Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. Land level & rolling. Soil S. 70 chs. adobe, 12 ins. deep on hardpan sub-soil. N. 10 chs. loose, sandy, fine texture in wind built sand ridges. Short salt grass. Scattering mesquite & sage brush 2 to 4 ft. high on N. end of line. No timber.</p> <p style="text-align: center;">-----</p> <p>Thence I run \checkmark N. $89^{\circ} 17'$ E. on true line bet. secs 3 & 10 Over rolling sandy land, through mesquite & sage brush 2 to 4 ft. high, 50 lks. N. of and parallel to telephone line. 39.40 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:</p>
--	---

LINES
RESURVEY OF SUBDIVISIONS OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 3 in N., & S 10 1913 in S half.

Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

From the above described cor. S.W. cor. of wire fence bears N. 50 lks. dist., thence parallel to and 50 lks. S of wire fence.

Thence I run

S. $89^{\circ} 59'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 3 & 10, on E. $\frac{1}{2}$ mile.

20.00 N.W. cor. of wire fence, bears S. 50 lks. dist., thence through lane.

32.00 House, bears S. 150 lks.

39.50 W. edge of N. & S. lane.

40.03 Intersect the cor. of secs. 2, 3, 10 & 11, hereinbefore described.

Land level & rolling.

Soil loose, sandy, fine texture, 24 ins. deep.

Scattering grass, mesquite & sage brush 2 to 4 ft. high.

No timber.

Note: Wagon road runs along this line.

From the cor. of secs. 3, 4, 9 & 10, hereinbefore described I run

N. $0^{\circ} 13'$ W. on true line bet. secs. 3 & 4

Over rolling, sandy land, through mesquite & sage brush 3 to 4 ft. high.

.10 Wagon road, bears E. & W.

40.30 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 4 in W., S. 3 in E. & 1913 in S half. of post

Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

48.00 Wagon road, bears E. & W.

80.80 Wagon road, bears E. & W.

81.11 Intersect N. bdy. of T₁₀ at the cor. of secs. 3, 4, 33 & 34, previously reestab. by me, as described in Book "A" of this (Group.)

Land level & rolling.

Soil, very sandy, 2 to 3 ft. deep

Scattering grass, sage & mesquite brush 2 to 4 ft. high.

No timber.

June 11th, 1913.

June 12th, 1913:

At 8 h. 20 m., a.m., l.m.t., I set off $23^{\circ} 09\frac{1}{2}'$ N. on decl. arc, $32^{\circ} 09\frac{1}{2}'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 4, 5, 32 & 33 on S. bdy of Tp., previously reestab. by me, as described in Book "A" of this (Group.)

Thence I run

N. $0^{\circ} 12'$ W. on true line bet. secs. 32 & 33

Over dry bed of old alkali lake.

39.86 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 32 in W., S 33 in E. & 1913 in S. half. of post

Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

79.72 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 28, 29, 32 & 33, with brass cap marked T 14 S R 25 E in N. & 1913 in S. half, S 29 in N.W., S. 28 in N.E., S 33 in S.E. & S 32 in S.W. quadrant.

Dig pits 13 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high, W. of cor.

Land level.

Soil alkali.

No vegetation.

LINES
RESURVEY OF SUBDIVISIONS OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

- Thence I run
S. 89° 31' E. on true line bet. secs. 28 & 33
Over dry bed of old alkali lake.
- 4
40.01 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S. 28 in N., S 33 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- Thence I run
S. 89° 56' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 28 & 33, on E. $\frac{1}{2}$ mile.
- 40.01 Intersect the cor. of secs. 27, 28, 33 & 34, hereinbefore described.
Land level.
Soil alkali.
No vegetation.
-
- From the cor. of secs. 28, 29, 32 & 33, hereinbefore described
I run
N. 0° 07' W. on true line bet. secs. 28 & 29
Over dry bed of old alkali lake.
- 39.86 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 29 in W., S 28 in E. & 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
- Thence I run
N. 0° 13' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 28 & 29, on N. $\frac{1}{2}$ mile.
- 40.07 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 20, 21, 28 & 29, with a brass cap marked T 14 S R 25 E in N., & 1913 in S. half, S 20 in N.W., S 21 in N.E., S 28 in S.E. & S 29 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level.
Soil alkali.
No vegetation.
-
- Thence I run
N. 89° 56' E. on true line bet. secs. 21 & 28
Over dry bed of old alkali lake.
- 40.005 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 21 in N. & S 28 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 65.00 Leave dry bed of old alkali lake, bears N.W. & S.E., thence over rolling alkali land
- 80.01 Intersect cor. of secs. 21, 22, 27 & 28, hereinbefore described.
Land level & rolling.
Soil alkali.
No vegetation.
-
- From the cor. of secs. 20, 21, 28 & 29, hereinbefore described
I run
North on true line bet. secs. 20 & 21

LINE
RESURVEY OF SUNDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

40.07 Over dry bed of old alkali lake.
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap marked $\frac{1}{4}$ S 20 in W. S 21 in E. & 1913 in S half. / of post
Dig pits 18 x 18 x 12 ins. N. & S. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

49.00 Leave dry bed of old alkali lake, bears E. & W., thence over slightly rolling alkali prairie.

79.80 S.W. cor. of wire fence, bears E. 10 lks.

80.14 Intersect the point for orig. cor. of secs. 16, 17, 20 & 21 hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 16, 17, 20 & 21, with a brass cap marked T 14 S R 25 E in N., & 1913 in S half, S 17 in N.W., S 16 in N.E., S 21 in S.E. & S 20 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land Level & rolling.
Soil alkali
Short salt grass on N. end of line. No vegetation on S. end of line.
No timber.

Thence I run
N. $89^{\circ} 47'$ E. on true line bet. secs. 16 & 21
Over slightly rolling prairie land.

.10 Wire fence, bears N. & S., parallel to and 6 lks. N. of wire fence.

40.13 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground, for ~~the~~ $\frac{1}{4}$ sec. cor. with a brass cap marked $\frac{1}{4}$ S 16 in N. & S 21 1913 in S. half. / of post
Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
Thence I run
N. $89^{\circ} 49'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 16 & 21 on E. $\frac{1}{2}$ mile.

19.00 Enter dry bed of small alkali lake, bears N. & S., extending 2 chs. N. of line & 5 chs. S. of line.

38.50 Leave dry bed of alkali lake

40.10 Intersect the cor. of secs. 15, 16, 21 & 22, hereinbefore described.
Land level & rolling.
Soil adobe, 12 ins. deep on hardpan sub-soil.
Short salt grass.
No timber.

At the cor. of secs. 16, 17, 20 & 21, hereinbefore described, I set off $23^{\circ} 09\frac{1}{2}'$ N. on decl. arc, and at 11 h. 59 m. 31 s., observe the sun on the mer. and obtain a reading of $32^{\circ} 12'$ on lat. arc.
Thence I run
N. $0^{\circ} 63'$ E. on true line bet. secs. 16 & 17
Over rolling prairie land

.15 Wire fence, bears N. 30° W., S. 30° E.

10.00 Enter dry bed of alkali lake, bears E. & W., extending 3 chs. E & 7 chs. W. of line.

23.00 Leave dry bed of alkali lake

36.00 Enter dry bed of small alkali lake, bears N.E. & S.W.

40.11 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap marked $\frac{1}{4}$ S 17 in W., S 16 in E. & 1913 in S. half. / of post
Dig pits 13 x 13 x 12 ins. N. & S. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

LINES
RESURVEY OF SUBDIVISION Δ OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

- 42.00 Leave dry bed of alkali lake, bears E. & W., extending 2 chs. E. of line & 8 chs. W. of line.
- 67.00 Enter dry bed of alkali lake, bears E. & W., extending E. 1 ch. & W. 10 chs. dist.
- 77.00 Leave dry bed of alkali lake, bears E. & W.
- 79.75 Wire fence, bears E. & W., N.W. cor. of wire fence bears W. 10 lks. dist.
- 80.22 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 8, 9, 16 & 17, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 8 in N.W., S 9 in N.E., S 16 in S.E. & S 17 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level & rolling.
Soil alkali & adobe, 12 ins. deep on hardpan sub-soil.
Short salt grass
No timber.
-
- Thence I run
S. $89^{\circ} 51'$ E. on true line bet. secs. 9 & 16
Over rolling prairie land, parallel to \approx 50 lks. N. of wire fence.
- 40.17 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 9 in N. & S 16 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. E. & W. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
Thence I run
N. $89^{\circ} 24'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 9 & 16, on E. half mile.
- 40.05 Intersect the cor. of secs. 9, 10, 15 & 16, hereinbefore described.
Land level & rolling.
Soil adobe, 12 ins. deep on hardpan sub-soil.
Short salt grass.
No timber.
-
- From the cor. of secs. 8, 9, 16 & 17, hereinbefore described.
I run
N. $0^{\circ} 04'$ W. on true line bet. secs. 8 & 9
Over rolling prairie land
- .50 S.E. cor. of wire fence, bears W. 50 lks. dist., thence parallel to and 50 lks. E. of wire fence.
- 40.11 Intersect the point for orig. $\frac{1}{4}$ sec. cor., hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 8 in W., S 9 in E. & 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. N. & S. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Thence I run
N. $0^{\circ} 04'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 8 & 9, on N. half mile.
- 32.00 Bend in wagon road, bears S. 30° E. & North, thence along wagon road
- 39.75 N.E. cor. of wire fence, bears W. 50 lks. dist.
- 40.22 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 4, 5, 8 & 9, with a brass cap marked T 14 S R 25 E in N. & 1913 in S. half, S 5 in N.W., S 4 in N.E., S 9 in S.E. & S 8 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

Land level & rolling.
Soil adobe, 12 ins. deep, on hardpan sub-soil
Short salt grass.
No timber.

Thence I run
S. 89° 57' E, on true line bet. secs. 4 & 9
Over rolling, sandy land
.10 Wagon road, bears N. & S.
1.50 Wagon road bears N. & S.
1.75 Phone line bears. N. 30° W., S. 30° E.
26.50 Phone line bears, N. 60° W. S. 60° E.
40.095 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 4 in N. & S 9 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
46.00 Enter sage brush 1 to 3 ft. high, bears N. & S.
80.19 Intersect cor. of secs. 3, 4, 9 & 10, hereinbefore described.

Land level & rolling.
Soil loose sandy, fine texture in windbuilt sand ridges.
Short salt grass, mesquite & sage brush 1 to 4 ft. high on E. end of line.
No timber.

From the cor. of secs. 4, 5, 8 & 9, hereinbefore described
I run
N. 0° 08' W. on true line bet. secs. 4 & 5 over rolling
Over rolling prairie land
2.00 Wagon road, bears N. 30° W., S. 30° E.
2.50 Phone line, parallel to wagon road.
13.00 Enter dry bed of lake, bears E. & W., extending 7 chs. E. & 10 chs. W. of line.
26.00 Telephone line, bears E. & W.
30.00 Leave dry bed of lake, bears E. & W.
40.22 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 5 in W., S 4 in E. & 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
From the above described cor. S.E. cor. of wire fence, bears W. 50 lks., thence parallel to & 50 lks. E. of wire fence.

80.26 N.E. cor. of wire fence, bears W. 50 lks.
80.98 Intersect N. bdy. of Tp. at the cor. of secs. 4, 5, 32 & 33, reestab. by me, as described in Book "A" of this Group.
Land level & rolling.
Soil sandy, fine texture, 24 ins. deep, short salt grass.
Scattering mesquite brush at N. end of line.
No timber.

June 12th, 1913.

June 13th, 1913:

At 8 h. 30 m. a.m., l.m.t., I set off 23° 13' N. on decl. arc, 32° 09 $\frac{1}{2}$ ' on lat. arc, and determine a mer. with the solar at the cor. of secs. 5, 6, 31 & 32 on S. bdy. of Tp, reestab. by me, as described in Book "A" of this Group.

Thence I run
N. 0° 10' W. on true line bet. secs. 31 & 32
Over dry bed of old alkali lake.
39.905 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 31 in W., S 32 in E. & 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

RESURVEY OF SUBDIVISION LINES OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

- 79.81 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 29, 30, 31 & 32, with a brass cap marked T 14 S R 25 E in N., & 1913 in S half, S 30 in N.W. S 29 in N.E., S 32 in S.E. & S 31 in S.W. quadrant. Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level
Soil alkali
No vegetation.
-
- Thence I run
S. $89^{\circ} 41'$ E. on true line bet. secs. 29 & 32
Over dry bed of old alkali lake.
- 40.11 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{2}$ sec. cor. with brass cap marked $\frac{1}{2}$ S 29 in N. & S 32 1913 in S. half. /of post
Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 89.22 Intersect the cor. of secs. 28, 29, 32 & 33, hereinbefore described.
Land level.
Soil alkali.
No vegetation.
-
- From the cor. of secs. 29, 30, 31 & 32, hereinbefore described
I run
N. $89^{\circ} 49'$ W. on true line bet. secs. 30 & 31
Over dry bed of old alkali lake.
- 40.06 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{2}$ sec. cor. with brass cap, mkd. $\frac{1}{2}$ S 30 in N. & S 31 1913 in S. half. /of post
Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 78.87 Intersect W. bdy of Tpa at the cor. of secs. 25, 30, 31 & 36 previously re-estab. by me, as described in Book "A" of this Group.
Land level.
Soil alkali.
No vegetation.
-
- From the cor. of secs. 29, 30, 31 & 32, hereinbefore described
I run
N. $0^{\circ} 02'$ E. on true line bet. secs. 29 & 30
Over dry bed of old alkali lake.
- 39.905 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{2}$ sec. cor. with brass cap marked $\frac{1}{2}$ S 30 in W. S 29 in E. & 1913 in S half. of post
Dig pits 18 x 18 x 12 ins. N. & S. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
- 79.81 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 19, 20, 29 & 30, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 19 in N.W., S 20 in N.E., S 29 in S.E. & S 30 in S.W. quadrant. Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level.
Soil alkali
No vegetation.
-
- Thence I run
S, $89^{\circ} 44'$ E. on true line bet. secs. 20 & 29
Over dry bed of old alkali lake.
- 40.07 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{2}$ sec. cor. with brass cap marked $\frac{1}{2}$ S 20 in N. & S 29 1913 in S half. Dig pits 18 x 18 x 12 ins. E. & W. of post 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N.

LINES
RESURVEY OF SUBDIVISION ^A OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

EOOK 2724

80.14 of cor.
Intersect cor. of secs. 20, 21, 28 & 29, hereinbefore described.
Land level.
Soil alkali
No vegetation.

From the cor. of secs. 19, 20, 29 & 30, hereinbefore described

I run over dry bed of old alkali lake
S. 89° 38' W. on true line bet. secs. 19 & 30
40.05 Intersect point for orig. ¹/₄ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¹/₄ sec. cor., with a brass cap marked ¹/₄ S 19 in N. & S 30 1913 in S half. /of post
Dig pits 18 x 18 x 12 ins. E. & W. ¹/₃ ft. dist. & raise mound of earth ³/₂ ft. base ¹/₂ ft. high N. of cor.

Thence I run
N. 89° 05' W. from ¹/₄ sec. cor. on true line bet. secs. 19 & 30, on W. half mile.
38.60 Intersect W. bdy. of Tp. at the cor. of secs. 19, 24, 25 & 30, previously re-estab. by me as described in Book "A" of this Group.
Land level.
Soil alkali.
No vegetation.

From the cor. of secs. 19, 20, 29 & 30, hereinbefore described

I run
N. 0° 02' W. on true line bet. secs. 19 & 20
Over dry bed of old alkali lake.
10.00 Leave dry bed of old alkali lake, bears E. & W.
22.00 Enter dry bed of small alkali lake, bears E. & W., extending E. 3 chs. & W. 7 chs. dist.
27.00 Leave dry bed of old alkali lake, bears E. & W., thence over rolling prairie land.

39.905 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. ¹/₄ sec. cor. with brass cap marked ¹/₄ S 19 in W. S 20 in E. & 1913 in S half. /of post
Dig pits 18 x 18 x 12 ins. N. & S. ¹/₃ ft. dist. & raise mound of earth ³/₂ ft. base ¹/₂ ft. high W. of cor.

54.00 Dry wash 30 lks. wide, 3 ft. deep, course S. 30° E.
73.00 Dry wash 30 lks. wide, 3 ft. deep, course W.

79.81 Intersect the point for orig. cor. of secs. 17, 18, 19 & 20, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 17, 18, 19 & 20, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 18 in N.W., S 17 in N.E., S 20 in S.E. & S 19 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. ⁵/₂ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level & rolling.
Soil, adobe & alkali, 12 ins. deep on hardpan sub-soil
Short salt grass
No timber.

Thence I run
S. 89° 55' E. on true line bet. secs. 17 & 20
Over slightly rolling prairie land
8.00 Enter dry bed of lake, bears N. & S., extending 3 chs. N. & 6 chs. S. of line.
15.00 Leave dry bed of lake, bears N. & S.
39.00 Enter dry bed of lake, bears N. & S., extending 7 chs. N & 3 chs. S. of line.

LINES

RESURVEY OF SUBDIVISION A OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

- 40.15 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, ~~cor.~~ and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 17 in N. & S 20 1913 in S half. /of post
Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
Thence I run
S. $89^{\circ} 55'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 17 & 20, on E. half mile.
- 10.00 Leave dry bed of lake, bears N. & S.
- 40.05 Intersect cor. of secs. 16, 17, 20 & 21, hereinbefore described.
Land level & rolling.
Soil adobe & alkali, 12 ins. deep on hardpan sub-soil
Short salt grass.
No timber.
-
- From the cor. of secs. 17, 18, 19 & 20, hereinbefore described
I run
N. $89^{\circ} 21'$ W. on true line bet. secs. 18 & 19
Over level prairie land
- 40.10 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, ~~cor.~~ and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 18 in N. & S 19 1913 in S half. /of post
Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
Thence I run
S. $89^{\circ} 44'$ W. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 18 & 19
- 38.31 Intersect W. bdy. of T₁ at the cor. of secs. 13, 18, 19 & 24, previously re-established as described in Book "A" of Land level. (this Group.
Soil adobe, 12 ins. deep on hardpan sub-soil
Short salt grass
No timber.
- June 13th, 1913.
-
- June 14, 1913;
At 7 h. 30 m., a.m., l.m.t., I set off $23^{\circ} 16\frac{1}{2}'$ N. on decl arc, $32^{\circ} 12'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 17, 18, 19 & 20, hereinbefore described.
Thence I run
N. $0^{\circ} 16'$ W. on true line bet. secs. 17 & 18
Over slightly rolling prairie land
- 3.00 Enter dry bed of lake, bears E. & W., extending E. 2 chs. and W. 3 chs. from line.
- 7.50 Leave dry bed of lake, bears E. & W.
- 15.50 Dry wash, 30 lks. wide, 2 ft. deep, course S. 60° E.
- 38.00 Dry wash 30 lks. wide, 2 ft. deep, course S. 30° W.
- 39.92 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, ~~cor.~~ and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 13 in W., S 17 in E. & 1913 in S. half /of post
Dig pits 18 x 18 x 12 ins. N. & S. \wedge of cor. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Thence I run
North from $\frac{1}{4}$ sec. cor. on true line \wedge N. $\frac{1}{2}$ bet. secs. 17 & 18
- 39.96 Intersect point for orig. cor. of secs. 7, 8, 17 & 18,

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 2 ins. in dia., 24 ins in ground for cor. of secs. 7, 8, 17 & 18, with a brass cap marked T 14 S R 25 E in N. & 191⁷ in S. half, S 7 in N.W., S 8 in N.E., S 17 in S.E. & S 18 in S.W. quadrant.

Dig pits 18 x 13 x 12 ins. in each sec. 5¹/₂ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.

Land level & rolling.

Soil adobe, 12 ins. deep on hardpan sub-soil.

Short salt grass.

No timber.

Thence I run

S. 89° 50' E. on true line bet. secs. 8 & 17

Over level prairie land

40.16 Intersect point for orig. 1/4 sec. cor. hereinbefore described.

This old cor. being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 8 in N. & S 17 1913 in S. half.

Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. of post & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

Thence I run

N. 89° 31' E. from 1/4 sec. cor. on true line bet. secs. 8 & 17, on E. 1/2 mile.

From the above described cor. S.W. cor. of wire fence bears N. 50 lks. dist., thence parallel to & 50 lks. S. of wire fence.

28.00 Enter dry bed of lake, bears N. & S.

30.00 Leave dry bed of lake, bears N. & S.

40.07 Intersect cor. of secs. 8, 9, 16 & 17, hereinbefore described.

Land level.

Soil adobe, 12 ins. deep on hardpan sub-soil

Short salt grass.

No timber.

From the cor. of secs. 7, 8, 17 & 18, hereinbefore described I run

N. 89° 55' W. on true line bet. secs. 7 & 18

Over level prairie land

3.00 Enter dry bed of lake, bears N. & S., extending 10 chs. N & 3 chs. S. of line.

26.00 Leave dry bed of lake, bears N. & S.

38.00 Wire fence, bears N. & S.

40.05 Intersect point for orig. 1/4 sec. cor. hereinbefore described.

This old cor. being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 7 in N. & S 18 1913 in S half.

Dig pits 13 x 12 x 12 ins. E. & W. 3 ft. dist. of post & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

Thence I run

N. 89° 20' W. from 1/4 sec. cor. on true line bet. secs. 7 & 18

37.33 Wire fence, bears N. & S.

37.83 Intersect W. bdy. of Tp. at the cor. of secs. 7, 12, 13 & 18, previously re-established by me, as described in Book "A" of this

Land level

Soil adobe, 12 ins. deep on hardpan sub-soil.

Short salt grass

No timber.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

- From the cor. of secs. 7, 8, 17 & 18, hereinbefore described.
- I run
N. 0° 09' E. on true line bet. secs. 7 & 8
Over level prairie land
- 15.00 Enter dry bed of small alkali lake, bears E. & W.
18.00 Leave dry bed of alkali lake, bears E. & W.
30.00 Enter dry bed of alkali lake, bears N.E. & S.W.
38.00 Leave dry bed of small alkali lake, bears E. & W.
40.27 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap marked $\frac{1}{4}$ S 7 in W. & S 8 in E. & 1913 in S. half of post
Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
From the above described cor. powder magazine bears N. 49 $\frac{1}{4}$ ° E.
79.30 C. T. McGlone's house, bears N. 24° E.
80.00 Phone line, bears E. & W., also S.E. cor. of wire fence, bears W. 50 lks. dist.
80.54 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 5, 6, 7 & 8, with a brass cap marked T 14 S R 25 E in N. & 1913 in S half, S 6 in N.W., S 5 in N.E., S 8 in S.E. & S 7 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{4}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Land level.
Soil adobe, 12 to 13 ins. deep on hardpan sub-soil.
Short salt grass
No timber.
Note: at the above described cor. I set off 23° 16 $\frac{1}{2}$ ' N. on decl. arc, and at 11 h. 59 m. 55 s., a.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 14' on lat. arc.
-
- Thence I run
S. 89° 55' E. on true line bet. secs. 5 & 8
Over level prairie land.
- 40.01 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 5 in N. & S 8 1913 in S. half. of post
Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
From the above described cor. N.W. cor. of wire fence bears S. 50 lks. dist.
- Thence I run
N. 89° 44' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 5 & 8, on E. half mile.
50 lks. N. of and parallel to wire fence.
- 00.16 Powder magazine, bears S. 6 $\frac{3}{4}$ ° W.
4.00 House, bears S. 2 chs. dist.
10.50 Dry wash 50 lks. wide, 4 ft. deep, course S. 30° E.
40.01 Intersect cor. of secs. 4, 5, 8 & 9, hereinbefore described.
Note: W $\frac{1}{2}$ of this line runs parallel to and 50 lks. N. of telephone line.
Land level & rolling.
Soil adobe, 12 to 13 ins. deep on hardpan sub-soil
Short salt grass
No timber.
-
- From the cor. of secs. 5, 6, 7 & 8, hereinbefore described.
I run
S. 89° 49' W. on true line bet. secs. 6 & 7
Over level prairie land.
- .50 Wire fence & telephone line, bears N. & S., thence parallel to & 50 lks. N. of wire fence

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

- 10.00 Enter dry bed of small alkali lake, bears N. & S.
 - 15.00 Leave dry bed of alkali lake, bears N. & S.
 - 40.00 Wire fence, bears N. & S., S.W. cor. of this fence, bears S. 50 lks. dist.
 - 40.05 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 6 in N. & S 7 1913 in S half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Thence I run
 N. $89^{\circ} 19'$ W. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 6 & 7, on W. $\frac{1}{2}$ mile.
 - 16.50 Enter dry bed of small alkali lake, bears N. & S.
 - 19.50 Leave dry bed of small alkali lake, bears N. & S.
 - 28.00 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 - 30.30 Main line Southern Pacific R.R., bears N. 30° E., S. 30° W.
 - 31.00 Telegraph line, parallel to R.R.
 - 31.75 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 - 37.33 Wire fence, bears N. & S.
 - 37.84 Intersect W. bdy. of Tp. at the cor. of secs. 1, 6, 7 & 12, previously re-established as described in Book "A" of this Land level. (Group).
 Soil adobe, 12 to 18 ins deep on hardpan sub-soil.
 Short salt grass
 No timber.
-
- From the cor. of secs. 5, 6, 7 & 8, hereinbefore described I run
 N. $0^{\circ} 14'$ W. on true line bet. secs. 5 & 6
 Over level prairie land, parallel to & 50 lks. E. of wire fence.
 - 31.00 N.E. cor. of wire fence, bears W. 50 lks.
 - 40.27 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 6 in W., S 5 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 - 44.00 S.E. cor. of wire fence, bears W, 25 lks., thence parallel to wire fence
 - 49.00 House bears W. 1 ch. dist.
 - 49.50 N.E. cor. of wire fence, bears W. 25 lks.
 - 50.00 Wagon road, bears N. 30° W., S. 30° E.
 - 55.00 Dry wash 50 lks. wide, 1 ft. deep, course S. 60° W.
 - 68.50 Wagon road, bears N. 30° W., S. 30° E.
 - 71.71 Intersect E. bdy. of Wilcox Townsite 34.33 chs. N. $29^{\circ} 52'$ E. of S.E. cor. of Townsite, previously re-established by me, as described in Book "A" of this Group.
 At point of intersection, I set an iron post, 3 ft. long, 1 in. in diam, 26 ins. in ground, for reestab. closing corner of secs. 5 & 6, with a brass cap marked T 14 S R 29 E in N. & 1913 in S. half, S 5 in S.E., & S 6 in S.W. quadrant, and CC N. of center.
 Dig pits 24 x 13 x 12 crosswise on each line N. E. & S.W. 3 ft. & S of post 7 ft. dist. & raise a mound of earth 4 ft. base 1 1/2 ft. high, west of cor.
 Thence on blank line bet. secs. 5 & 6 through Wilcox Townsite
 - 81.14 Intersect the point for cor. of secs. 5, 6, 31 & 32 on N. bdy. of Tp., within Wilcox Townsite, previously reestab. by me, as described in Book "A" of this Group. Land level.
 Soil adobe, 12 to 13 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.
 Note: From the point of intersection of secs. 5, 6, 31 & 32 on N. bdy. of Tp. bed, C. T. McGlone's house bears S. 39° E.

GENERAL DESCRIPTION OF TOWNSHIP 14 SOUTH, RANGE 25 EAST.

This township is practically level, the slopes being very gentle towards South and West.

Except for a strip of blow sand in the Northeast of the township, the soil is strong with alkali, sustaining nothing but a short growth of salt grass. The large dry bed of old lake and the numerous small lake beds are so strong of alkali that they are barren of all vegetation.

The low wind built sand ridges in the Northeast part of the township produce a good growth of mesquite and sage brush with some scattering yucas.

There is an abundant supply of water at a depth of from 10 to 30 feet.

The village of Willcox is located in the Northwest corner of this township. The population of Willcox is about 500.

Thomas B. Matthews

U.S. Surveyor.

June 14, 1913.


FOR FINAL OATH OF UNITED STATES SURVEYOR.

SEE BOOK "D"

I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191 _____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

U. S. Surveyor.

Subscribed by said _____, and sworn to before me }
this _____ day of _____, 191 _____ }



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix - Arizona, March 20, 1915

The foregoing field notes of the ^{RE} survey of *the* _____
Subdivision lines of
Township N° 14 South
Range N° 25 East
of the Gila and Salt River Base and Meridian, in the State of Arizona

executed by *Thomas B. Matthews, U.S. Surveyor*
 under his special instructions dated *April 21, 1913 for Group 25*, ~~for~~ having been critically examined, and the necessary corrections and explanations made, the said field notes, and the ~~resurveys~~ they describe, are hereby approved.

Frank D. Ingalls
 U. S. Surveyor General.
 OF ARIZONA.

~~I certify that the foregoing transcript of the field notes of the above-described surveys in _____, has been correctly copied from the original notes on file in this office.~~