

2725

4-679

2725

121.
①

Book "F"

Resurvey Subdivisions

BOOK 2725

SEP. 2-1914

FIELD NOTES

OF THE RESURVEY OF THE

Subdivision lines of

Township 14 South Range 24 East

Of the Gila and Salt River Base and Meridian,

In the State of ARIZONA

EXECUTED BY

Thomas B. Matthews,

In the capacity of U. S. Surveyor, under instructions dated April 21, 1913, issued by the United States Surveyor General to govern surveys included in Group No. 25, which were approved by the Commissioner of the General Land Office, May 2, 1913, pursuant to authority contained in the Act of Congress dated August 24, 1912

ReSurvey commenced June 16, 1913

ReSurvey completed June 28, 1913

Book "F"

BOOK 2725

INDEX DIAGRAM.

Township 14 South, Range 24 East

	6				3					
6	40	5	33	4	28	3	24	2	19	1
	7		6		4		3		1	
39		39		33		28		23		18
13		13	14	14		14		14		14
15										15
7	38	8	32	9	27	10	23	11	18	12
	7		6		4		3		1	
38		38		32		27		23		18
13		13		12		12		12		12
18	37	17	31	16	27	15	22	14	17	13
	7		6		4		3		1	
11	37		36		31		26		22	17
10		10	11		11		11		11	11
12										12
19	36	20	30	21	26	22	21	23	16	24
	7		6		4		3		2	
36		35		30		25		20		16
10		10		10		10	9	9		9
			6				3			
30	35	29	30	28	25	27	20	26	15	25
	7		5		5		2		2	
34		34		29		9		20		15
8		8		8		8		8		8
31	34	32	29	33	24	34	19	35	15	36
	7		5		5		2			

- Notes in Book "A", this Group (2720)
- Surveyed
- Unsurveyed
- 5 Retracement notes indexed in RED figures

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 SOUTH, RANGE 24 E

Retracement &

- ReSurvey commenced June 16th, 1913, and executed by Thomas B. Matthews, U. S. Surveyor, with a Young & Sons Light Mountain Transit No. 8480, with solar attachment. The horizontal limb is provided with two double verniers, placed opposite to each other, reading to single minutes of arc, which is also the least count of the verniers for the lat. and decl. arcs. This instrument was approved by the Supervisor of Surveys Jan. 30th, 1913
- I examine the adjustments of the transit and find them to be correct and know from recent tests of the solar apparatus, by comparing its indications resulting from solar observations, made during a.m. and p.m. hours, with a mer. established by observation on Polaris, at elongation, that the instrument is in satisfactory adjustment.
- At 7 h. 30 m., a.m., l.m.t., I set off $23^{\circ} 21\frac{1}{2}'$ N. on decl. arc, $32^{\circ} 15''$ on lat. arc, and determine a mer. with the solar at the cor. of secs. 1, 2, 35 & 36 on N. bdy of Tp., previously re-established by me & described by me in Book "A"
- The magnetic bearing of the true mer. thus determined is N. $12^{\circ} 50'$ W., the angle thus determined gives the magnetic decl. $12^{\circ} 50'$ E.
- Thence I run
South on random line bet. secs. 1 & 2
- 40.23 Fall 4 lks. W. of point for orig. $\frac{1}{4}$ sec. cor., as determined from stake in S. pit, loosely set & marked as described by Surveyor General,
Therefore, the true return bearing is N. $0^{\circ} 03'$ W.
-
- Thence I run
South from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 1 & 2 on $S\frac{1}{2}$ mile
- 40.00 Make diligent search for orig. cor. of secs. 1, 2, 11 & 12 which I fail to find.
- 80.00 Therefore, I continue my random line South bet. secs. 11 & 12
- 80.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I also fail to find
- 120.30 Fall 17 lks. E. of point for orig. cor. of secs. 11, 12, 13 & 14, as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General.
- Thence I run
N. $0^{\circ} 5'$ E. on temp. N. & S. line bet. secs. 11 & 12
- 40.10 Set temp. $\frac{1}{4}$ sec. cor.
- 80.20 Set temp. cor. for secs. 1, 2, 11 & 12
- 120.30 Intersect point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 1 & 2, hereinbefore described.
-
- From point for orig. cor. of secs. 11, 12, 13 & 14, hereinbefore described
I run
South on random line bet. secs. 13 & 14
- 39.86 Fall 13 lks. E. of point for orig. $\frac{1}{4}$ sec. cor., as determined from stake in S. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 11'$ E.
-
- Thence I run
South from the point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 13 & 14, on $S\frac{1}{2}$ mile
- 40.87 Fall 25 lks. W. of point for orig. cor. of secs. 13, 14, 23 & 24, as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 21'$ W.
-
- Thence I run
South on random line bet. secs. 23 & 24

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 2¹ E.

40.17 Fall 110 lks. E. of point for orig. $\frac{1}{4}$ sec. cor., as determined from stake in S. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is N. $1^{\circ} 35'$ E., 40.19 chs.

Thence I run
South from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 23 & 24, on $S\frac{1}{2}$ mile
40.20 Fall 2 lks. W. of point for orig. cor. of secs. 23, 24, 25 & 26, as determined from stake in S.E. pit, firmly set & marked as described by the Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 02'$ W.

Thence I run
South on random line bet. secs. 25 & 26
39.85 Fall 2 lks. E. of point for orig. $\frac{1}{4}$ sec. cor., as determined from stake in S. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 02'$ E.

Thence I run, South
from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 25 & 26, on $S\frac{1}{2}$ mile
40.00 Make diligent search for orig. cor. of secs. 25, 26, 35 & 36, which I fail to find, therefore, I continue my random line South, bet. secs. 35 & 36.
80.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor, which I fail to find.

119.25 Intersect S. bdy. of Tp. at the cor. of secs. 1, 2, 35 & 36, previously reestab. by me & described by in Book "A"
Thence I run
North on temp. N. & S. line bet. secs. 35 & 36
39.75 Set temp. $\frac{1}{4}$ sec. cor.
79.50 Set temp. cor. for secs. 25, 26, 35 & 36
119.25 Intersect point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 25, & 26, hereinbefore described.

At the cor. of secs. 2, 3, 34 & 35 on S. bdy. of Tp. reestab. by me as described in Book "A", I set off $23^{\circ} 21\frac{1}{2}'$ N. on decl. arc and at 112 h. 00 m. 12 s., a.m., l.m.t., observe the sun on the mer. and obtain a reading of $32^{\circ} 09\frac{1}{2}'$ on lat. arc
Thence I run
North on random line bet. secs. 34 & 35
40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I fail to find.
80.00 Make diligent search for orig. cor. of secs. 26, 27, 34 & 35, which I also fail to find.
Therefore, I continue my random line North, bet. secs. 26 & 27
118.95 Fall 21 lks. W. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 26 & 27, as determined from stake in S. pit, firmly set & marked as described by Surveyor General.
Thence I run S. $0^{\circ} 06'$ W.
from point for orig. $\frac{1}{4}$ sec. cor. on temp. N. & S. line bet. bet. secs. 26 & 27 on $S\frac{1}{2}$ mile
39.65 Set temp. cor. for. secs. 26, 27, 34 & 35.

Thence I run
S. $0^{\circ} 06'$ W. on temp. N. & S. line bet. secs. 34 and 35.
39.65 Set temp. $\frac{1}{4}$ sec. cor.
79.30 Intersect S. bdy. of Tp. at the cor. of secs. 2, 3, 34 & 35, previously re-estab. by me and described in Book "A"

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

From point for orig. $\frac{1}{4}$ sec. cor., hereinbefore described

I run
 40.00 North on random line bet. secs. 26 & 27 on $N\frac{1}{2}$ mile
 Make diligent search for orig. cor. of secs. 22, 23, 26 & 27, which I fail to find, therefore, I continue my random line North. bet. secs. 22 & 23

80.18 Fall 68 lks. W. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 22 & 23, as determined from stake in S. pit, firmly set & marked as described by Surveyor General.

Thence I run
 S. $0^{\circ} 29'$ W. from point for orig. $\frac{1}{4}$ sec. cor. on temp. N. & S. line bet. secs. 22 & 23, on $S\frac{1}{2}$ mile.

40.09 Set temp. cor. for secs. 22, 23, 26 & 27

Thence I run
 40.09 S. $0^{\circ} 29'$ W. on temp. N. & S. line bet. secs. 26 & 27
 Intersect point for orig. $\frac{1}{4}$ sec. cor., hereinbefore described

From point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 22 & 23, hereinbefore described

I run
 40.15 North on random line bet. secs. 22 & 23, on $N\frac{1}{2}$ mile
 Fall 43 lks. W. of point for orig. cor. of secs. 14, 15, 22 & 23, as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General.
 Therefore, the true return bearing is S. $0^{\circ} 37'$ W.

Thence I run
 40.00 North on random line bet. secs. 14 & 15
 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find.

80.97 Fall 24 lks. E. of point for orig. cor. of secs. 10, 11, 14 & 15, as determined from stake in S.E. pit. firmly set & marked as described by Surveyor General.
 Therefore, the true return bearing is S. $0^{\circ} 10'$ E.

Thence I run
 40.00 North on random line bet. secs. 10 & 11
 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find.

80.00 Make diligent search for orig. cor. of secs. 2, 3, 10 & 11, which I also fail to find.
 Therefore, I continue my random line North bet. secs. 2 & 3

120.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find.

160.32 Intersect N. bdy. of Tp. 19 lks. W. of cor. of secs. 2, 3, 34 & 35, previously reestablished by me & described by me in Book "A"
 Thence I run, S. $0^{\circ} 04'$ W.
 on temporary N. & S. line, setting temp. $\frac{1}{4}$ sec. & sec. cors. at distances proportional to distances given on original plat, and at 160.32 chs. intersect point for orig. cor. of secs. 10, 11, 14 & 15, hereinbefore described.

June 16th, 1913.

June 17, 1913
 At 7 h. 30 m., a.m., l.m.t, I set off $23^{\circ} 23\frac{1}{2}'$ N. on decl. arc, $32^{\circ} 15'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 3, 4, 33 & 34, on N. bdy. of Tp., previously reestablished by me & described by me in Book "A"
 Thence I run
 40.78 South on random line bet. secs. 3 & 4
 Fall 54 lks. W. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set & marked as described by Surveyor General.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

Therefore, the true return bearing is N. $0^{\circ} 29'$ W.

40.21 Thence I run from
point for orig. $\frac{1}{4}$ sec. cor. South on random line bet. secs.
3 & 4, on $S\frac{1}{2}$ mile
Fall 5 lks. E. of point for orig. cor. of secs. 3, 4, 9 &
10, as determined from stake in S.E. pit, firmly set &
marked as described by Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 04'$ E.

39.89 Thence I run
South on random line bet. secs. 9 & 10
Intersect the point for orig. $\frac{1}{4}$ sec. cor. as determined
from stake in S. pit, firmly set & marked as described by
Surveyor General.
Therefore, the true return bearing in North.

40.25 Thence I run
South on random line bet. secs. 9 & 10, from the point
for orig. $\frac{1}{4}$ sec. cor., on $S\frac{1}{2}$ mile
Fall 4 lks. E. of point for orig. cor. of secs. 9, 10, 15 &
16, as determined from the four pits and remains of mound
Therefore, the true return bearing is N. $0^{\circ} 03'$ E.

39.95 Thence I run
South on random line bet. secs. 15 & 16
Fall 7 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. as determined
from stake in S. pit, firmly set & marked as described by
Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 06'$ E.

40.24 Thence I run, South
from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs
15 & 16, on $S\frac{1}{2}$ mile
Intersect the point for orig. cor. of secs. 15, 16, 21 &
22, as determined from stake in S.E. pit, firmly set &
marked as described by Surveyor General.
Therefore, the true return bearing is North.

39.95 Thence I run
South on random line bet. secs. 21 & 22
Fall 23 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. as determined
from stake in S. pit, firmly set & marked as described
by the Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 20'$ E.

40.23 Thence I run, South
from point for original $\frac{1}{4}$ sec. cor. on random line bet.
secs. 21 & 22 on $S\frac{1}{2}$ mile
Fall 27 lks. E. of point for the orig. cor. of secs. 21, 22
& 28, as determined from stake in S.E. pit, firmly set
& marked as described by Surveyor General.
Therefore, the true return bearing is N. $0^{\circ} 23'$ E.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

39.95 Thence I run South on random line bet. secs. 27 & 28 Fall 28 lks. E. of the point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set & marked as described by Surveyor General. Therefore, the true return bearing is N. 0° 24' E.

40.21 Thence I run South from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 27 & 28, on $\frac{1}{2}$ mile Fall 28 lks. E. of the point for orig. cor. of secs. 27, 28, 33 & 34, as determined from stake in SE pit, firmly set & marked as described by Surveyor General. Therefore, the true return bearing is N. 0° 24' E.

39.78 Thence I run South on random line bet. secs. 33 & 34 Fall 35 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set & marked as described by Surveyor General. Therefore, the true return bearing is N. 0° 30' E.

39.23 Thence I run South from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 33 & 34, on $\frac{1}{2}$ mile Intersect S. bdy. of Tp. 3 lks. W. of cor. of secs. 3, 4, 33 & 34, reestablished as described in Book "A" of this group Therefore, the true return bearing is N. 0° 03' W.

At the cor. of secs. 4, 5, 32 & 33, on S. bdy. of Tp., reestablished by me as described in Book "A" me, I set off 23° 23 $\frac{1}{2}$ ' N. on decl. arc, and at 12 h. 0 m. 33 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 09 $\frac{1}{2}$ ' on lat. arc

40.03 Thence I run North on random line bet. secs. 32 & 33 Fall 5 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set & marked as described by Surveyor General. Therefore, the true return bearing is S. 0° 04' E.

40.00 Thence I run From the point for orig. $\frac{1}{4}$ sec. cor. North on random line bet. secs. 32 & 33, on $\frac{1}{2}$ mile Make diligent search for orig. cor. of secs. 28, 29, 32 & 33 which I fail to find. Therefore, I continue my random line North, bet. secs. 28 & 29.

80.10 Fall 68 lks. W. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 28 & 29, as determined from stake in S. pit, firmly set & marked as described by Surveyor General.

Thence I run On temp. N. & S. line S. 0° 29' W. At 40.05 chs. set. temp. cor. of secs. 28, 29, 32 & 33 and at 80.10 chs. intersect point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 32 & 33, hereinbefore described.

From point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 28 & 29, hereinbefore described I run

40.00 North on random line bet. secs. 28 & 29, on $\frac{1}{2}$ mile Make diligent search for orig. cor. of secs. 20, 21, 28 & 29 which I fail to find.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

- 79.38 Therefore, I continue my random line North. bet. secs 20&21. Fall 39 lks. W. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 20 & 21, as determined from stake in S. pit, firmly set & marked as described by Surveyor General.
Thence I run, S. $0^{\circ}17'W$.
On temp. N. & S. line. At, 39.69 chs. set temp. cor. for secs. 20, 21, 28 & 29, and at 79.38 chs. intersect point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 28 & 29, hereinbefore described.
-
- 40.02 From point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 20 & 21, hereinbefore described
I run
North on random line bet. secs. 20 & 21, on $N\frac{1}{2}$ mile Fall 31 lks. W. of point for orig. cor. of secs. 16, 17, 20 & 21, as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is S. $0^{\circ}27'W$.
-
- 40.15 Thence I run
North on random line bet. secs. 16 & 17
Fall 2 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set & marked as described by the Surveyor General.
Therefore, the true return bearing is S. $0^{\circ}02'E$.
-
- 40.00 Thence I run
From point for orig. $\frac{1}{4}$ sec. cor.
North on random line bet. secs. 16 & 17 on $N\frac{1}{2}$ mile Fall 3 lks. W. of point for orig. cor. of secs. 8, 9, 16 & 17 as determined from stake in SE. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is S. $0^{\circ}03'W$.
-
- 40.00 Thence I run
North on random line bet. secs. 8 & 9
Make diligent search for orig. $\frac{1}{4}$ sec. cor., which I fail to find.
80.00 Make diligent search for orig. cor. of secs. 4, 5, 8 & 9, which I also fail to find, therefore, I continue my random line North., bet. secs. 4 and 5.
120.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I also fail to find
161.30 Intersect N. bdy. of Tp. 23 lks. E. of cor. of secs. 4, 5, 32 & 33, previously re-estab. by me as described in Book "A"
Thence I run, S. $0^{\circ}06'E$.
On temporary N. & S. line, setting temp. $\frac{1}{4}$ sec. & sec. cors. at distances proportional to distances given on original plat, and at 161.30 chs. intersect the point for orig. cor. of secs. 8, 9, 16 & 17, hereinbefore described.
- June 17th, 1913.
-
- June 18, 1913.
At; 7 h. 30 m., a.m., 1.m.t., I set off $23^{\circ}25\frac{1}{2}'N$. on decl. arc, $32^{\circ}15'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 5, 6, 31 & 32 on N. bdy. of Tp., previously re-estab. by me & described by me in Book "A"
Thence I run
40.09 South on random line bet. secs. 5 & 6
Fall 67 lks. W. of point for orig. $\frac{1}{4}$ sec. cor., as determined from stake set in S. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is N. $0^{\circ}58'W$. 40.10 chs.
-

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 25 E.

Thence I run
 South on random line from point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 5 & 6 on $S\frac{1}{2}$ mile
 40.00 Make diligent search for orig. cor. of secs. 5, 6, 7 & 8, which I fail to find.
 Therefore, I continue my random line South. bet. secs. 7 & 8.
 80.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I also fail to find.
 120.39 Intersect point for orig. cor. of secs. 7, 8, 17 & 18, as determined from stake in S.E. pit firmly set & marked as described by Surveyor General.
 Thence I run North
 on temp. N. & S. line, setting temp. $\frac{1}{4}$ sec. & sec. cors. at distances proportional to distances given on original plat, and at 120.39 chs. intersect point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 5 & 6, hereinbefore described.

 From point for orig. cor. of secs. 7, 8, 17 & 18, hereinbefore described
 I run
 South on random line bet. secs. 17 & 18
 40.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I fail to find.
 80.00 Make diligent search for orig. cor. of secs. 17, 18, 19 & 20, which I fail to find, therefore, I continue my random line South, bet. secs. 19 and 20.
 120.00 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I fail to find.
 160.00 Make diligent search for orig. cor. of secs. 19, 20, 29 & 30, which I fail to find. Continue random line S. bet. secs. 29 & 30.
 199.75 Fall 75 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 29 & 30, as determined from stake in S. pit, firmly set & marked as described by Surveyor General.
 Thence I run N. $0^{\circ}13' E.$
 on temporary N. & S. line, setting temp. sec. & $\frac{1}{4}$ sec. cors. at distances proportional to distances given on original plat, and at 199.75 chs. intersect the point for orig. cor. of secs. 7, 8, 17 & 18, hereinbefore described.

 From point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 29 & 30, hereinbefore described
 I run
 South on random line bet. secs. 29 & 30 on $S\frac{1}{2}$ mile
 40.24 Fall 28 lks. E. of point for orig. cor. of secs. 29, 30, 31 & 32 as determined from stake in S.E. pit, firmly set & marked as described by Surveyor General.
 Therefore, the true return bearing is N. $0^{\circ}24' E.$

 Thence I run
 South on random line bet. secs. 31 & 32
 40.03 Fall 24 lks. E. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in S. pit, firmly set & marked as described by Surveyor General.
 Therefore the true return bearing is N. $0^{\circ}21' E.$

 Thence I run South
 from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 31 & 32 on $S\frac{1}{2}$ mile
 40.47 Intersect S. bdy. of Tp. 13 lks. E. of cor. of secs. 5, 6, 31 & 32, reestab. by me as described in Book "A" of this group
 Therefore, the true return bearing is N. $0^{\circ}11' E.$

 At the cor. of secs. 25, 30, 31 & 36 on W. bdy. of Tp., reestab. by me as described in Book "A" of this group, I set off $23^{\circ}25'$ N. on decl arc, and at 12 h. 0 m. 46 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32°

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

10 1/2' on lat. arc
 Thence I run
 East on random line bet. secs. 30 & 31
 40.49 Make diligent search for orig. 1/4 sec. cor. which I fail to find.
 80.83 Fall 38 lks. S. of point for orig. cor. of secs. 29, 30, 31 & 32 hereinbefore described.
 Therefore the true return bearing is S. 89° 44' W.

 Thence I run
 East on random line bet. sec. 29 & 32
 39.97 Make diligent search for orig. 1/4 sec. cor. which I fail to find.
 79.94 Make diligent search for orig. cor. of secs. 28, 29, 32 & 33, which I also fail to find, therefore, I continue my random line East, bet. secs. 28 and 33.
 120.35 Fall 66 lks. North of point for orig. 1/4 sec. cor. bet. secs. 28 & 33, as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
 Thence I run, N. 89° 41' W.,
 on temporary E. & W. line bet. secs. 28 & 33 on W 1/2 mile
 40.11 Set temp. sec. cor., from which I reestablish point for cor. of secs. 28, 29, 32 & 33 N. 12 lks. & 5 lks. W. of temp. cor. for above numbered secs., set on temp. N. & S. line.

 cor. on temp.
 From the last above mentioned temp. E. & W. line & T. line I run
 N. 39° 41' W. on temp. E. & W. line, bet. secs. 29 and 32.
 40.12 Set temp. 1/4 sec. cor.
 30.24 Intersect point for orig. cor. of secs. 29, 30, 31 & 32, hereinbefore described.

 From point for orig. 1/4 sec. cor. bet. secs. 28 & 33, hereinbefore described
 I run
 East on random line bet. secs. 28 & 33 on E 1/2 mile
 40.31 Fall 82 lks. N. of point for orig. cor. of secs. 27, 28, 33 & 34, hereinbefore described.
 Therefore, the true return bearing is N. 83° 50' W. 40.32 chs.

 Thence I run
 East on random line bet. secs. 27 & 34
 39.96 Make diligent search for orig. 1/4 sec. cor. which I fail to find.
 79.92 Make diligent search for orig. cor. of secs. 26, 27, 34 & 35, which I fail to find, therefore, I continue my random line East, bet. secs. 26 and 35.
 119.97 Make diligent search for orig. 1/4 sec. cor. which I fail to find.
 160.03 Make diligent search for orig. cor. of secs. 25, 26, 35 & 36, which I fail to find. Continue random line E. bet. secs. 25 & 36.
 199.99 Make diligent search for orig. 1/4 sec. cor. which I fail to find.
 240.91 Intersect E. bdy. of Tn. 105 lks. S. of cor. of secs. 25, 30, 31 & 36, reestablished by me as described in Book "A" of this group
 Thence I run, S. 89° 45' W.
 on temporary E. & W. line bet. secs. 25 & 36
 40.12 Set temp. 1/4 sec. cor.
 80.24 Set temp. sec. cor. from which I reestablish the point for cor. of secs. 25, 26, 35 & 36, S. 3 lks. & 33 lks. E. of temp. cor. for the above numbered secs., set on temp. N. & S. line.

 From the last above mentioned temp. cor. on temp. E. & W. line I run, S. 89° 45' W.
 on temporary E. & W. line bet. secs. 26 & 35
 40.215 Set temp. 1/4 sec. cor.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

80.43 Set temp. sec. cor. from which I reestablished the point for cor. of secs. 26, 27, 34 & 35 N. 6 lks. & 9 lks. E. of temp. cor. for the above numbered secs., set on temp. N. & S. line

From the last above mentioned temp. cor. on temp. E. & W. line I run, S. 89° 45' W. on temporary E. & W. line bet. secs. 27 & 34

40.12 Set temp. 1/4 sec. cor.

80.24 Intersect point for orig. cor. of secs. 27, 28, 33 & 34, hereinbefore described.

June 18th, 1913.

June 19, 1913

At 3 h. 0 m., a.m., l.m.t., I set off 23° 26 1/2' N. on decl. arc, 32° 11 1/2' on lat. arc and determine a mer. with the solar at the cor. of secs. 19, 24, 25 & 30, on E. bdy. of Tp. reestablished by me & described in Book "A" of this group

Thence I run West on random line bet. secs. 24 & 25

40.67 Fall 77 lks. N. of point for orig. 1/4 sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General.

Therefore, the true return bearing is N. 38° 54' E. 40.68chs.

Thence I run West from point for orig. 1/4 sec. cor. on random line bet. secs. 24 & 25 on W 1/2 mile

40.11 Intersect point for orig. cor. of secs. 23, 24, 25 & 26, hereinbefore described

Therefore, the true return bearing is East.

Thence I run West on random line bet. secs. 23 & 26

40.14 Fall 2 lks. N. of point for orig. 1/4 sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General.

Therefore, the true return bearing is N. 89° 53' E.

Thence I run West from point for orig. 1/4 sec. cor. on random line bet. secs. 23 & 26 on W 1/2 mile

39.935 Make diligent search for orig. cor. of secs. 22, 23, 26 & 27, which I fail to find, therefore, I continue my random line West. bet secs 22 and 27.

79.58 Fall 23 lks. S. of point for orig. 1/4 sec. cor., as determined from stake in E. pit, firmly set & marked as described by Surveyor General.

Thence I run E. & W. S. 89° 50' E. on temp. line bet. secs. 22 & 27, on E. half mile.

39.85 Set temp. sec. cor. from which I reestablished point for cor. of secs. 22, 23, 26 & 27 N. 25 lks. & 2 lks. E. of temp. cor. for the above numbered secs, set on V.N. & S. line. temp.

From the last above mentioned temp. cor. on E. & W. line I run E. & W.

39.73 S. 89° 50' E. on temp. line bet. secs. 23 & 26 on W. 1/2 mile. Intersect point for 1/4 sec. cor., hereinbefore described. orig.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

- From the point for ^{orig.} $\frac{1}{4}$ sec. cor. bet. secs. 22 & 27 hereinbefore described
I run
40.06 West on random line bet. secs. 22 & 27, on W. half mile.
Fall 11 lks. S. of point for cor. of secs. 21, 22, 27 & 23, hereinbefore described. ^{orig.}
Therefore, the true return bearing is S. 89° 51' E.
-
- Thence I run
West on random line bet. secs. 21 & 28
40.055 Make diligent search for ^{orig.} $\frac{1}{4}$ sec. cor. which I fail to find.
80.11 Make diligent search for ^{orig.} cor. of secs. 20, 21, 23 & 29, which I fail to find, therefore, I continue my random line West, bet. secs. 20 and 29
120.065 Make diligent search for ^{orig.} $\frac{1}{4}$ sec. cor., which I also fail to find.
160.02 Make diligent search for ^{orig.} cor. of secs. 19, 20, 29 & 30, which I fail to find. Continue random line W. bet. secs. 19 & 30.
200.02 Make diligent search for ^{orig.} $\frac{1}{4}$ sec. cor., which I also fail to find.
241.25 Intersect W. bdy. of Tp. 91 lks. S. of the ^{orig.} cor. of secs. 19, 24, 25 & 30, provisionally re-established & confirmed by me as described in Book "A" of this group.
Thence I run ^{E. & W.}
S. 89° 47' E. on temp. ^{E. & W.} line bet. secs. 19 & 30
40.705 Set temp. $\frac{1}{4}$ sec. cor.
80.81 Set temp. sec. cor. from which I reestablish point for cor. of secs. 19, 20, 29 & 30 N. 66 lks. & W 9 lks. from temp. cor. for the above numbered secs., set on ^{N. & S.} line.
temp.
-
- temp.
From the last above mentioned temp. cor. on ^{E. & W.} line
I run ^{E. & W.}
S. 89° 47' E. on temp. ^{E. & W.} line bet. secs. 20 & 29
40.06 Set temp. $\frac{1}{4}$ sec. cor.
80.12 Set temp. sec. cor., from which I reestablish point for cor. of secs. 20, 21, 28 & 29 N. 20 lks. & 16 lks. W. of temp. cor. for the above numbered secs., set on ^{N. & S.} line.
temp.
-
- temp.
From the last above mentioned temp. cor. on ^{E. & W.} line
I run ^{E. & W.}
S. 89° 47' E. on temp. ^{E. & W.} line bet. secs. 21 & 28
40.16 Set temp. $\frac{1}{4}$ sec. cor.
80.32 Intersect point for ^{orig.} cor. of secs. 21, 22, 27 & 28, hereinbefore described. ^{orig.}
-
- At the cor. of secs. 13, 18, 19 & 24 on W. bdy. of Tp., reestab. by me as described in Book "A" by me, I set off 23° 26½' N. on decl. arc and at 12 h. 0 m. 59 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 12' on lat. arc.
Thence I run
East on random line bet. secs. 13 & 19
40.91 Make diligent search for ^{orig.} $\frac{1}{4}$ sec. cor. which I fail to find
80.91 Make diligent search for ^{orig.} cor. of secs. 17, 18, 19 & 20, which I also fail to find, therefore, I continue my random line East, bet. secs. 17 and 20.
121.50 Fall 82 cks. N. of point for ^{orig.} $\frac{1}{4}$ sec. cor. bet. secs. 17 & 20 as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
Thence I run ^{E. & W.}
N. 89° 37' W. on temp. ^{E. & W.} line from point for $\frac{1}{4}$ sec. cor. bet. secs. 17 & 20 on W. $\frac{1}{2}$ mile
40.21 Set temp. sec. cor. from which I reestablish point for cor. of secs. 17, 18, 19 & 20 N. 72 lks. & 13 lks. E. of temp. cor. for the above numbered secs. set on ^{N. & S.} line.
temp.
-

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

From the last above mentioned temp. cor. on temp. E. & W. line,
 I run
 N. 89° 37' W. on temp. ^{E. & W.} line bet. secs. 18 & 19
 40.19 Set temp. $\frac{1}{4}$ sec. cor.
 81.29 Intersect W. bdy. of Tp. at the cor. of secs. 13, 18, 19
 & 24, previously re-established & described by me.

 From the point for ^{orig.} $\frac{1}{4}$ sec. cor. bet. secs. 17 & 20, herein-
 before described
 I run
 East on random line bet. secs. 17 & 20, on east $\frac{1}{2}$ mile.
 40.10 Fall 2 lks. S. of point for ^{orig.} cor. of secs. 16, 17, 20 & 21,
 herebefore described.
 Therefore, the true return bearing is S. 39° 58' W.

 Thence I run
 East on random line bet. secs. 16 & 21
 40.10 Fall 2 lks. N. of point for ^{orig.} $\frac{1}{4}$ sec. cor. as determined from
 stake in E. pit, firmly set & marked as described by Sur-
 veyor General.
 Therefore, the true return bearing is N. 89° 53' W.

 Thence I run
 East from point for ^{orig.} $\frac{1}{4}$ sec. cor. on random line bet. secs.
 16 & 21, on E. half mile.
 40.10 Intersect point for ^{orig.} cor. of secs. 15, 16, 21 & 22, herein-
 before described.
 Therefore, the true return bearing is West.

 Thence I run
 East on random line bet. secs. 15 & 22
 40.00 Intersect point for ^{orig.} $\frac{1}{4}$ sec. cor. as determined from stake
 in E. pit, firmly set & marked as described by Surveyor
 General.
 Therefore the true return bearing is West.

 Thence I run
 East from ^{orig.} point for $\frac{1}{4}$ sec. cor. on random line bet. secs.
 15 & 22, on E. half mile.
 40.08 Intersect point for ^{orig.} cor. of secs. 14, 15, 22 & 23, herein-
 before described.
 Therefore, the true return bearing is West.

 Thence I run
 East on random line bet. secs. 14 & 23
 39.985 Make diligent search for ^{orig.} $\frac{1}{4}$ sec. cor. which I fail to find.
 80.10 Fall 5 lks. N. of point for ^{orig.} cor. secs. 13, 14, 23 & 24,
 herebefore described.
 Therefore, the true return bearing is N. 89° 58' W.

 Thence I run
 East on random line bet. secs. 13 & 24
 40.10 Fall 4 lks. N. of point for ^{orig.} $\frac{1}{4}$ sec. cor. as determined from
 stake in E. pit, firmly set & marked as described by Surveyor
 General.
 Therefore, the true return bearing is N. 89° 57' W.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

- 39.98 Thence I run
East from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 13 & 24 on $E\frac{1}{2}$ mile
Intersect E. bdy. of Tp. 27 lks. S. of cor. of secs. 13, 18, 19 & 24, reestab. by meas. as described in Book "A" of this group
Therefore, the true return bearing is S. $89^{\circ} 37'$ W.
June 19th, 1913.
- June 20, 1913. At 7 h. 30 m. a.m., l.m.t., I set off $23^{\circ} 27\frac{1}{2}'$ N. on decl. arc, $32^{\circ} 13'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 7, 12, 13 & 18 on E. bdy. of Tp., previously reestab. by meas. as described in Book "A"
- 40.75 Thence I run
West on random line bet. secs. 12 & 13
Fall 16 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is S. $89^{\circ} 46'$ E.
- 40.11 Thence I run
West from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 12 & 13 on $W\frac{1}{2}$ mile
Intersect point for orig. cor. of secs 11, 12, 13 & 14, hereinbefore described.
Therefore, the true return bearing is East.
- 40.15 Thence I run
West on random line bet. secs. 11 & 14
Fall 14 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is S. $89^{\circ} 43'$ E.
- 40.14 Thence I run
West on random line bet. secs. 11 & 14 from point for orig. $\frac{1}{4}$ sec. cor. on $W\frac{1}{2}$ mile
Fall 7 lks. S. of point for orig. cor., secs 10, 11, 14 & 15, hereinbefore described.
Therefore, the true return bearing is S. $89^{\circ} 54'$ E.
- 40.10 Thence I run
West on random line bet. secs. 10 & 15
Fall 5 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is S. $89^{\circ} 56'$ E.
- 39.95 Thence I run
West on random line bet. secs. 10 & 15 from point for orig. $\frac{1}{4}$ sec. cor. on $W\frac{1}{2}$ mile
Fall 99 lks. N. of point for orig. cor. secs. 9, 10, 15 & 16, hereinbefore described.
Therefore, the true return bearing is N. $88^{\circ} 35'$ E. 39.96 chs.
- 40.08 Thence I run
West on random line bet. secs. 9 & 16
Fall 11 lks. S. of point for orig. $\frac{1}{4}$ sec. cor. as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
Therefore, the true return bearing is S. $89^{\circ} 51'$ E.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

40.10 Thence I run West from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 9 & 16 on $W\frac{1}{2}$ mile Fall 2 lks. S. of point for orig. cor. of secs 8, 9, 16 & 17, hereinbefore described. Therefore, the true return bearing is S. $89^{\circ} 58'$ E.

39.94 80.21 Thence I run West on random line bet. secs. 8 & 17 Make diligent search for orig. $\frac{1}{4}$ sec. cor. which I fail to find. Fall 72 lks. S. of point for orig. cor. of secs 7, 8, 17 & 18, hereinbefore described. Therefore, the true return bearing is S. $89^{\circ} 29'$ E.

40.13 Thence I run West on random line bet. secs. 7 & 18 Intersect point for orig. $\frac{1}{4}$ sec. cor. determined from stake in E. pit, firmly set & marked as described by Surveyor General. Therefore, the true return bearing is East.

41.22 Thence I run West from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 7 & 18 on $W\frac{1}{2}$ mile Intersect W. bdy. of Tp. 37 lks. S. of cor. of secs. 7, 12, 13 & 18, previously reestab. by me as described in Book "A" Therefore, the true return bearing is S. $89^{\circ} 28'$ E.

At the cor. of secs. 1, 6, 7 & 12 on W. bdy. of Tp. reestab. by me as described in Book "A" of this group set off $23^{\circ} 27'$ N. on decl. arc and at 12 h. 1 m. 12 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of $32^{\circ} 14'$ on lat. arc.

41.15 Thence I run East on random line bet. secs. 6 & 7 Fall 27 lks. N. of point for orig. $\frac{1}{4}$ sec. cor. determined from stake in E. pit, firmly set & marked as described by the Surveyor General. Therefore, the true return bearing is N. $89^{\circ} 37'$ W.

40.00 Thence I run East from point for orig. $\frac{1}{4}$ sec. cor. on random line bet. secs. 6 & 7 on $E\frac{1}{2}$ mile Make diligent search for orig. cor. of secs. 5, 6, 7 & 8, which I fail to find, therefore, I continue my random line East bet. secs. 5 & 8

80.23 Fall 33 lks. N. of point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 5 & 8 as determined from stake in E. pit, firmly set & marked as described by Surveyor General.

40.09 Thence I run N. $89^{\circ} 46'$ W. on temp. E. & W. line bet. secs. 5 & 8 Set temp. sec. cor. from which I reestab. point for cor. of secs. 5, 6, 7 & 8 N. 18 lks., which point co-incides with temp. cor. for above numbered secs., set temp. N. & S. line.

40.14 From the last above mentioned temp. cor. set on temp. E. & W. line I run N. $89^{\circ} 46'$ W. on temp. E. and W. line bet. secs. 6 & 7 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.

RETRACEMENT OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

- From point for orig¹/₄ sec. cor. bet. secs. 5 & 8, hereinbefore described
I run
East on random line bet. secs. 5 & 8 on E¹/₂ mile
- 39.95 Make diligent search for orig. cor. of secs. 4, 5, 8 & 9, which I fail to find, therefore, I continue my random line East. bet. secs. 4 & 9
- 80.20 Fall 26 lks. N. of point for orig¹/₄ sec. cor. bet. secs. 4 & 9 as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
Thence I run N. 89° 49' W.
N. 89° on temp. E. & W. line bet. secs. 4 & 9
- 40.14 Set temp. sec. cor. from which I reestablished point for cor. of secs. 4, 5, 8 & 9 N. 3 lks. & E. 28 lks. from temp. cor. for above numbered secs., set on temp. N. & S. line.
-
- From the last above mentioned temp. cor. set on temp. E. & W. line
I run N. 89° 49' W.
N. 89° on temp. E. & W. line bet. secs. 5 & 8
- 40.06 Intersect point for orig¹/₄ sec. cor. hereinbefore described.
-
- From point for orig¹/₄ sec. cor. bet. secs. 4 & 9, hereinbefore described
I run
East on random line bet. secs. 4 & 9 on E¹/₂ mile
- 40.12 Fall 16 lks. N. of point for orig. cor. of secs. 3, 4, 9 & 10, hereinbefore described.
Therefore, the true return bearing is N. 89° 46' W.
-
- Thence I run
East on random line bet. secs. 3 & 10
- 39.955 Make diligent search for orig¹/₄ sec. cor., which I fail to find.
- 79.91 Make diligent search for orig. cor. of secs. 2, 3, 10 & 11, which I fail to find, therefore, I continue my random line East. bet. secs. 2 & 11
- 119.855 Make diligent search for orig¹/₄ sec. cor., which I fail to find
- 159.80 Make diligent search for orig. cor. of secs. 1, 2, 11 & 12, which I fail to find. Continue random line E. bet. secs. 1 & 12
- 200.60 Fall 39 lks. S. of point for orig¹/₄ sec. cor. bet. secs. 1 & 12 as determined from stake in E. pit, firmly set & marked as described by Surveyor General.
Thence I run S. 89° 53' W.
S. 89° on temp. E. & W. line bet. secs. 1 & 12 on W¹/₂ mile
- 40.20 Set temp. sec. cor. from which I reestablished point for cor. of secs. 1, 2, 11 & 12 N. 27 lks. & 5 lks. E. of temp. cor. for the above numbered secs. set on temp. N. & S. line
-
- From the last above mentioned temp. cor., set on temp. E. & W. line
I run S. 89° 53' W.
S. 89° on temp. E. & W. line bet. secs. 2 & 11
- 40.095 Set temp. ¹/₄ sec. cor.
- 80.19 Set temp. sec. cor. from which I reestablished point for cor. of secs. 2, 3, 10 & 11 N. 59 lks. & 18 lks. E. of temp. cor. for the above numbered secs. set on temp. N. & S. line
-
- From the last above mentioned temp. cor. on temp. E. & W. line
I run S. 89° 53' W.
S. 89° on temp. E. & W. line bet. secs. 3 & 10
- 40.105 Set temp. ¹/₄ sec. cor.
- 80.21 Intersect point for orig. cor. of secs. 3, 4, 9 & 10, hereinbefore described.
-

RESURVEY OF SUBDIVISION LINES OF TOWNSHIP 14 S., RANGE 24 E.

From the point for orig. $\frac{1}{4}$ sec. cor. bet. secs. 1 & 12, hereinbefore described
 I run
 40.40 East on random line bet. secs. 1 & 12 on $E\frac{1}{2}$ mile
 Intersect E. bdy. of Tp. 12 lks. N. of cor. of secs. 1, 6, 7 & 12, reestab. by me as described in Book "A" of this group
 Therefore, the true return bearing is N. $89^{\circ} 50'$ W.
 June 20th, 1913.

RESURVEY OF SUBDIVISION LINES
 OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

June 21, 1913, At; 7 h. 30 m., a.m., 1.m.t., I set off $23^{\circ} 27\frac{1}{2}'$ N. on decl. arc, $32^{\circ} 09\frac{1}{2}'$ on lat. arc and determined a mer. with the solar at the cor. of secs. 1, 2, 35 & 36 on S. bdy of Tp. reestab. by me as described in Book "A" of this group
 Thence I run
 N. $0^{\circ} 14'$ E. on true line bet. secs. 35 & 36
 Over dry bed of old alkali lake.
 39.75 Set an iron post $\frac{7}{8}$ ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap marked $\frac{1}{4}$ S 35 in W., S 36 in E. & 1913 in S half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. \wedge $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 79.50 Set an iron post $\frac{3}{4}$ ft. long, 2 ins. in dia. $\frac{24}{16}$ ins. in ground for reestab. cor. of secs. 25, 26, 35 & 36, with a brass cap marked T 14 S R 24 E in N. & 1913 in S half, S 26 in N.W., S 25 in N.E., S 36 in S.E. & S 35 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil alkali.
 No vegetation.

Thence I run
 N. $89^{\circ} 44'$ E. on true line bet. secs. 25 & 36
 Over dry bed of old alkali lake.
 40.12 Set an iron post $\frac{3}{4}$ ft. long, 1 in. in dia., 26 ins. in the ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap marked $\frac{1}{4}$ S 25 in N. & S 36 1913 in S half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. \wedge $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 80.24 Intersect E. bdy. of Tp. at the cor. of secs. 25, 30, 31 & 36, previously re-estab. by me & described in Book "A".
 Land level.
 Soil alkali
 No vegetation.

From the cor. of secs. 25, 26, 35 & 36, hereinbefore described
 I run
 N. $0^{\circ} 28'$ W. on true line bet. secs. 25 & 26
 Over dry bed of alkali lake.
 28.00 Leave dry bed of old alkali lake, bears E. & W., thence over slightly rolling alkali prairie land, through growth of short salt grass.
 39.75 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
 Set an iron post $\frac{3}{4}$ ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 26 in W., S 25 in E. & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. \wedge $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 Thence Thence I run
 From the $\frac{1}{4}$ sec. cor. N. $0^{\circ} 02'$ E. on true line bet. secs. 25 & 26, on N. half mile.

LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

39.85 Intersect point for ~~orig. cor.~~ of secs. 23, 24, 25 & 26 hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of ~~the same~~, cor. and re-establish it in the same place as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for the cor. of secs. 23, 24, 25 & 26, with a brass cap marked T 14 S R 24 E in N. & 1913 in S half, S 23 in N.W., S 24 in N.E., S 25 in S.E. & S 26 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 S. 23 chs. level land. Alkali soil. No vegetation.
 N. 52 chs. level & rolling. Alkali adobe soil. Short salt grass.
 No timber.

 Thence I run
 East on true line bet. secs. 24 & 25.
 Over level prairie land, through short salt grass.

40.11 Intersect point for ~~orig. 1/2 sec. cor. hereinbefore~~ described. This old cor. being in a state of delapidation, I destroy all trace of ~~same~~, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/2 sec. cor., with a brass cap marked 1/2 S 24 in N. & S 25 1913 in S. half. ~~of post~~
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 Thence I run
 N. 83° 54' E. from 1/2 sec. cor. on true line bet. secs. 24 & 25, on east half mile.

20.00 Enter dry bed of old alkali lake, bears N.E. & S.W.
 40.68 Intersect E. bdy. of Tp. at the cor. of secs. 19, 24, 25 & 30, previously re-established by me as described in Book "A"
 Land from 0 to 60 chs. level & rolling. From 60 to 30 chs. level.
 Soil from 0 to 60 chs. alkali adobe, with short salt grass.
 Soil 60 to 30 chs. alkali, no vegetation.
 No timber.

 From the cor. of secs. 23, 24, 25 & 26, hereinbefore described

I run
 N. 0° 02' W. on true line bet. secs. 23 & 24
 Over slightly rolling prairie land

40.20 Intersect point for ~~orig. 1/4 sec. cor. hereinbefore~~ described. This old cor. being in a state of delapidation, I destroy all trace of ~~the same~~, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 23 in W., S 24 in E. & 1913 in S. half. ~~of post~~
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.

Thence I run
 N. 1° 35' E. from 1/4 sec. cor. on true line bet. secs. 23 & 24, on N. half mile.

40.19 Intersect point for ~~orig. cor.~~ of secs. 13, 14, 23 & 24, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of ~~the same~~, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 13, 14, 23 & 24 with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 14 in N.W., S 13 in N.E., S 24 in S.E. & S 23 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil light adobe, 12 ins. deep on hardpan sub-soil.
 Short salt grass.
 No timber

RESURVEY OF SUBDIVISION Δ OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

Thence I run
 ✓ S. 39° 57' E. on true line bet. secs. 13 & 24
 Over level prairie land.
 4.50 S.W. cor. of wire fence, thence along fence line
 40.10 Intersect point for ~~orig. 1/4 sec. cor. hereinbefore~~ described.
 This old cor. being in a state of delapidation, I destroy
 all trace of the old cor. and re-establish it in the same
 place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
 ground for 1/4 sec. cor., with a brass cap marked 1/4 S 13 in
 N. & S 24 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. E. & W. Δ 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 Thence I run
 ✓ N. 89° 37' E. from 1/4 sec. cor. on true line bet. secs.
 13 & 24.
 .06 S.E. cor. of wire fence, thence over open prairie land
 39.98 Intersect E. bdy. of Tp. at the cor. of secs. 13, 18, 19
 & 24, previously re-estab. ~~be me, &~~ described in Book "A"
 Land level & rolling.
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 At the cor. of secs. 13, 14, 23 & 24, hereinbefore describ-
 ed, I set off 23° 27 1/2' N. on decl. arc, and at 12 h. l.m.
 25 s., p.m., l.m.t., observe the sun on the mer. and obtain
 a reading of 32° 12' on lat. arc.
 Thence I run
 ✓ N. 0° 21' W. on true line bet. secs. 13 & 14
 Over slightly rolling prairie land
 5.00 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 6.75 Main line Southern Pacific R.R., bears N. 30° E., S. 30° W.
 7.50 Telegraph line, parallel to R.R.
 8.25 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 9.00 Wagon road, parallel to R.R.
 10.00 S.E. cor. of wire fence, bears W. 50 lks. dist., thence
 parallel to & 50 lks. E. of wire fence.
 22.00 Phone line, parallel to R.R.
 24,50 S.W. cor. of wire fence, bears E. 50 lks., thence through
 lane.

34.50 Lyman Hays' house, bears E. 250 lks.
 40.87 Intersect point for ~~orig. 1/4 sec. cor. hereinbefore~~ described.
 This old cor. being in a state of delapidation, I destroy
 all trace of ~~the same~~ cor. and re-establish it in the same
 place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
 ground for 1/4 sec. cor., with a brass cap marked 1/4 S 14 in
 W., S 13 in E., & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. Δ 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 Thence I run
 ✓ N. 0° 11' E. from 1/4 sec. cor. on true line bet. secs. 13
 & 14, on N. half mile.

.36 Cors. of wire fences, bear E. & W. 50 lks. dist. each,
 thence continue through lane.
 39.36 S. edge of E. & W. lane, cors. of wire fences bear E. & W.
 50 lks. dist. each.
 39.86 Intersect point for ~~orig. cor. of secs. 11, 12, 13 & 14, here-~~
~~inbefore~~ described. This old cor. being in a state of de-
 lapidation, I destroy all trace of ~~the same~~, cor. and re-estab-
 lish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in
 ground for cor. of secs. 11, 12, 13 & 14, with a brass cap
 marked T 14 S R 24 E in N. & 1913 in S. half, S 11 in N.W.,
 S 12 in N.E., S 13 in S.E. & S 14 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil light adobe, 12 to 13 ins. deep.
 Short salt grass.
 No timber.
 Note: Wagon road passes through lane along this line.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

	Thence I run
	✓ East on true line bet. secs. 12 & 13
	Over level prairie land
.10	Wagon road, bears N. & S.
.50	N.W. cor of wire fence, bears South 50 lks., thence parallel to & 50 lks. N. of wire fence.
16.00	S.W. cor. of wire fence bears N. 50 lks. dist., thence through lane
30.00	S.E. cor. of wire fence, bears N. 50 lks. also N.E. cor. of wire fence bears S. 50 lks. dist.
33.00	Phone line, bears N. 30° E., S. 30° W.
40.11	Intersect point for orig. 1/4 sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same , cor. and re-establish it in the same place, as follows:
	Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 12 in N. & S 13 1913 in S. half.
	Dig pits 18 x 18 x 12 ins. E. & W. ^{/of post} 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
	Thence I run
	✓ S. 89° 46' E. from 1/4 sec. cor. on true line bet. secs. 12 & 13, on east half mile.
.10	Wagon road, bears N. 30° E., S. 30° W.
.30	R.R. right-of-way fence, bears N. 30° E., S. 30° W.
1.00	Telegraph line, bears N. 30° E., S. 30° W.
1.80	Main line Southern Pacific R. R., bears N. 30° E., S. 30° W.
3.20	R.R. right-of-way fence, parallel to R.R., thence parallel to & 50 lks. N. of wire fence.
39.75	Wire fence, bears N. & S. along W. edge of lane
40.35	Intersect E. bdy. of Tp. at the cor. of secs. 7, 12, 13 & 18, previously re-established by me, as described in Book "A"
	Land level
	Soil light adobe, 12 to 18 ins. deep on hardpan sub-soil
	Short salt grass
	No timber.

	From the cor. of secs. 11, 12, 13 & 14, hereinbefore described
	I run
	N. 0° 07" E. on true line bet. secs. 11 & 12
	Over level prairie land
.10	Wagon road, bears E. & W.
.50	S.E. cor. of wire fence, bears W. 50 lks., thence parallel to & 50 lks. E. of wire fence.
40.10	Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. 1/4 sec. cor. with brass cap marked 1/4 S 11 in W., S 12 in E. & 1913 in S. half. ^{/of post}
	Dig pits 18 x 18 x 12 ins. N. & S. ^{/of post} 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
55.00	Small cabin, bears E. 5 chs. dist.
79.70	N.E. cor. of wire fence, bears W. 50 lks. dist.
80.20	Set an iron post 3 ft. long, 2 ins. in dia. ^{24 ins. in ground} for reestab. cor of secs. 1, 2, 11 & 12, with a brass cap marked T. 14 S R 24 E in N. & 1913 in S. half, S 2 in N.W., S 1 in N.E., S 12 in S.E. & S 11 in S.W. quadrant.
	Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
	Land level
	Soil light adobe, 12 to 18 ins. deep on hardpan sub-soil
	Short salt grass
	No timber.

	Thence I run
	✓ S. 89° 44' E. on true line bet. secs. 1 & 12
	Over level prairie land
.10	S.W. cor. of wire fence, bears N. 5 lks. dist., thence along S. side of fence.
20.00	N.W. cor. of wire fence, bears S. 1 ch. dist.
37.00	N.E. cor. of wire fence, bears S. 1 ch. dist.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 20 EAST.

- 40.20 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of ~~the same~~, cor. and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 1 in N. & S 12 1913 in S. half.
Dig pits 18 x 13 x 12 ins. E. & W. ^{/of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
Note: The above described cor. falls in fence line, fence bears N. $39\frac{1}{2}^{\circ}$ W., S. $89\frac{1}{2}^{\circ}$ E.
Thence I run
S. $89^{\circ} 50'$ E. from $\frac{1}{4}$ sec. cor. on true line ^{E. $\frac{1}{2}$} bet. secs. 1 & 12, along N. side of fence
- 40.10 Wire fence, bears N. & S.
- 40.40 Intersect E. bdy. of Tp. at the cor. of secs. 1, 6, 7 & 12, previously re-estab. by me, as described in Book "A"
Land level
Soil light adobe 12 to 18 ins. deep on hardpan sub-soil
Short salt grass
No timber

- From the cor. of secs. 1, 2, 11 & 12, hereinbefore described
I run
North on true line bet. secs. 1 & 2
Over level prairie land
- .05 S.W. cor. of wire fence, bears E. 10 lks. dist.
- .50 S.E. cor. of wire fence, bears W. 50 lks., thence through land
- 20.00 Cor. of wire fence, bears E. 5 lks. dist.
- 40.04 Cor. of wire fence, bears E. 1 lk., also N.E. cor. of wire fence, bears W. 50 lks. dist.
- 40.10 Intersect the point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of ~~of same~~, cor. and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 2 in W. S 1 in E. & 1913 in S. half.
Dig pits 18 x 13 x 12 ins. N. & S. ^{/of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Thence I run
N. $0^{\circ} 04'$ W. from $\frac{1}{4}$ sec. cor. on true line, ^{N. $\frac{1}{2}$} bet. secs. 1 & 2, along W. side of fence.
- 30.00 S.E. cor. of wire fence, bears W. 50 lks. dist., thence through lane.
- 39.00 N.E. cor. of wire fence, bears W. 50 lks. dist.
- 40.10 N.W. cor. of wire fence, bears E. 15 lks. dist.
- 40.23 Intersect N. bdy. of Tp. at the cor. of secs. 1, 2, 35 & 36, previously re-estab. by me, as described in Book "A"
Land level.
Soil light adobe, 12 to 18 ins. deep on hardpan sub-soil
Short salt grass, scattering mesquite brush 3 to 6 ft. high on N. end of line.
No timber.

June 21st., 1913.

June 23, 1913:

- At 7 h. 30 m., a.m., l.m.t., I set off $23^{\circ} 27'$ N. on decl. arc, $32^{\circ} 09\frac{1}{2}''$ on lat. arc and determine a mer. with the solar at the cor. of secs. 2, 3, 34 & 35, previously re-estab. by me as described in Book "A," of this Group.
Thence I run
N. $0^{\circ} 10'$ E. on true line bet. secs. 34 & 35
Over dry bed of old alkali lake
- 39.65 Set an iron post 3 ft. long, 1 in. **indiam.** 26 ins. in ground for re-estab. $\frac{1}{4}$ sec. cor. with a brass cap marked $\frac{1}{4}$ S 34 in W., S 35 in E. & 1913 in S. half.

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

79.30 Dig pits 13 x 13 x 12 ins. N. & S. ^{/of post} 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 26, 27, 34 & 35, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 27 in N.W., S 26 in N.E., S 35 in S.E. & S 34 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil alkali
 No vegetation

40.215 Thence I run N. 39° 49' E. on true line bet. secs. 26 & 35
 Over dry bed of old alkali lake
 Set an iron post 7 ft. long, 1 in. in dia., 26 ins. in ground, for reestab. 1/4 sec. cor. with brass cap, mkd 1/4 S 26 in N. & S 35 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. E. & W. ^{/of post} 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 80.43 Intersect cor. of secs. 25, 26, 35 and 36, hereinbefore described.
 Land level
 Soil alkali
 No vegetation.

13.00 From the cor. of secs. 26, 27, 34 & 35, hereinbefore described I run N. 0° 02' W. on true line bet. secs. 26 & 27.
 Over dry bed of old alkali lake.
 Leave dry bed of old alkali lake bears N.E. & S.W., thence over slightly rolling prairie land
 23.00 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 25.00 Main line of Southern Pacific R.R., bears N. 30° E., S. 30° W.
 26.00 Telegraph line, parallel to R.R.
 27.00 R.R. right-of-way fence, parallel to R.R.
 27.50 Wagon road, parallel to R.R.
 39.65 Intersect point for orig. 1/4 sec. cor., hereinbefore described.

This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 sec. cor., with a brass cap marked S 27 in W. S 26 in E. & 1913 in S. half. ^{/of post}
 Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 Note: from the above described cor. the Hado section house bears E. 11 chs. dist.

1.00 Thence I run N. 0° 31' E. from 1/4 sec. cor. on true line bet. secs. 26 & 27, on N. half mile.
 40.09 Phone line, bears N. 30° E. S 30° W.
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 22, 23, 26 & 27 with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 22 in N.W., S 23 in N.E., S 26 in S.E. & S 27 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil light adobe & alkali, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber

22.00 Thence I run S. 89° 29' E. on true line bet. secs. 23 & 26
 Over level prairie land.
 Phone line bears N. 30° E., S. 30° W.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

- 27.75 Wagon road, bears N. 30° E., S. 30° W.
 28.00 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 29.00 Telegraph line, parallel to R.R.
 30.00 Main line of Southern Pacific R. R., bears N. 30° E., S. 30° W.
 32.00 R.R. right-of-way fence, parallel to R.R.
 39.73 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 23 in N. & S 26 1913 in S. half. of post
 Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Thence I run
 N. 39° 53' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 23 & 26, on east half mile.
 40.14 Intersect cor. of secs. 23, 24, 25 & 26, hereinbefore described.
 Land level & rolling.
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

-
- From the cor. of secs. 22, 23, 26 & 27, hereinbefore described
 I run
 N. 0° 27' E. on true line bet. secs. 22 & 23
 Over level prairie land.
 9.00 Wagon road, bears E. & W., cor. of wire fence, bears W. 2 chs. dist.
 14.00 Wagon road, bears N. 30° E., S. 30° W.
 14.50 Wire fence, bears N. 30° E., S. 30° W.
 39.50 Wire fence, bears E. & W., thence through lane
 40.09 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 22 in W., S 23 in E. & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 Thence I run
 N. 0° 37' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 22 & 23, on north half mile.
 .50 S.W. cor. of wire fence bears E. 50 lks. dist.
 10.00 Page's house, bears W. 2 chs. dist.
 12.00 Cor. of wire fence, bears W. 50 lks.
 39.50 S. edge of E. & W. lane, cors. of wire fence bears E.E. 50 lks. dist.
 40.00 Cor. of wire fence, bears W. 50 lks. dist.
 40.15 Intersect pt. for orig. cor. of secs. 14, 15, 22 & 23, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 14, 15, 22 & 23, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 15 in N.W., S. 14 in N.E., S 23 in S.E. & S 22 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth $\frac{1}{2}$ ft. base 2 ft. high W. of cor.
 Land level. From this cor. Chas. Cook's house brs. N. 12° E.
 Soil light adobe, 12 ins. deep on hardpan sub-soil.
 Short salt grass
 No timber.
 Note: wagon road runs through lane, along N $\frac{1}{2}$ of this line.
-

LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

	Thence I run
	S. $39^{\circ} 58'$ E. on true line bet. secs. 14 & 23
	Over level prairie land
.50	Cors of wire fences, bears N. & S. 50 lks. dist. each, thence through lane.
38.00	Small cabin, bears S. 2 chs. dist.
40.05	Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. , with a brass cap marked $\frac{1}{4}$ S 14 in N. & S 23 1913 in S. half.
	Dig pits 13 x 13 x 12 ins. E. & W. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
40.10	Cors. of wire fences, bears N. & S. 50 lks. dist. each, thence continue through lane.
41.00	Small house, bears S. 2 chs. dist.
60.00	N.E. cor. of wire fence; bears S. 50 lks. dist., leave lane, thence parallel to & 50 lks. S. of wire fence.
67.00	Phone line, bears N. 30° E., S. 30° W.
72.50	S.E. cor. of wire fence, bears N. 50 lks.
73.25	Wagon road, bears N. 30° E., S. 30° W.
74.90	R.R. right-of-way fence, bears N. 30° E., S. 30° W.
75.00	Telegraph line, parallel to R.R.
76.00	Main line of Southern Pacific R.R., bears N. 30° E., S. 30° W.
78.00	R.R. right-of-way fence, parallel to R.R.
80.10	Intersect cor. of secs. 13, 14, 23 & 24, hereinbefore described.
	Land level.
	Soil adobe, 12 ins. deep on hardpan sub-soil.
	Short salt grass.
	No timber.
	Note: wagon road runs through lane along this line.

	At the cor. of secs. 14, 15, 22 & 23, hereinbefore described, I set off $23^{\circ} 26\frac{1}{2}'$ N. on decl. arc, and at 12 h. 1 m. 51 s., p.m., 1.m.t., observe the sun on the mer. and obtain a reading of $32^{\circ} 12'$ on lat. arc.
	Thence I run
	N. $0^{\circ} 10'$ W. on true line bet. secs. 14 & 15
	Over level, prairie land
	Note: from the above described cor. house bears W. 2 chs. dist.
.50	S.W. cor. of wire fence, bears E. 50 lks., thence parallel to & 50 lks. W. of wire fence.
24.00	S.E. cor. of wire fence bears W. 50 lks., thence through lane.
40.485	Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. , with a brass cap marked $\frac{1}{4}$ S. 15 in W., S 14 in E. & 1913 in S half. /of post
	Dig pits 13 x 13 x 12 ins. N. & S. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
	Note: from the above described cor. house bears W. 2 chs. dist.
41.00	Small irrigation ditch, course West, cor. wire fence bears
42.17	E. 50 lks. dist., thence parallel to & 50 lks. E. of wire fence.
42.17	Charlie Cook's house, bears S. 64° E.
60.00	N.E. cor. of wire fence, bears W. 50 lks., also S.W. cor. of wire fence, bears E. 50 lks., thence parallel to & 50 lks. W. of wire fence.
80.50	N.W. cor. of wire fence, bears E. 50 lks.
80.70	Wagon road, bears E. & W.
80.97	Intersect point for orig. cor. of secs. 10, 11, 14 & 15, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
	Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 10, 11, 14 & 15, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 10 in N.W., S 11 in N.E., S 14 in S.E. & S 15 in S.W. quadrant.
	Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
	Land level.
	Soil adobe, 12 to 13 ins. deep on hardpan sub-soil.
	Short salt grass.
	No timber.

LINES BOOK 2725
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

Thence I run
 ✓ S. 89° 54' E. on true line bet. secs. 11 & 14
 Over level prairie land
 .50 Cors. of wire fences, bear N. & S. 50 lks. dist. each,
 thence through lane
 20.25 N.E. cor. of wire fence bears S. 50 lks. dist., thence
 parallel to & 50 lks. S. of wire fence.
 40.14 Intersect point for orig. $\frac{1}{4}$ sec. cor., previously described.
 This old cor. being in a state of delapidation, I destroy
 all trace of the same, and re-establish it in the same
 place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
 ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 11 in
 N. & S 14 1913 in S. half. /of post
 Dig pits 18 x 13 x 12 ins. E. & W. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Thence I run
 S. 89° 49' E. from $\frac{1}{4}$ sec. cor. on true line \wedge E. $\frac{1}{2}$ bet. secs. 11
 & 14, parallel to & 50 lks. S. of wire fence.
 20.20 N.W. cor. of wire fence, bears S. 50 lks. dist., thence
 22.00 through lane
 22.00 Small cabin, bears S. 2 chs. dist.
 39.70 Cors of wire fences, bear N. & S. 50 lks. dist. each
 40.15 Intersect the cor. of secs. 11, 12, 13 & 14, previously
 described.
 Land level.
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.
 Note: wagon road follows along this line.

 From the cor. of secs. 10, 11, 14 & 15, hereinbefore de-
 scribed
 I run
 N. 0° 12' E. on true line bet. secs. 10 & 11
 Over level, prairie land
 .50 Cors. of wire fences, bear E. & W. 50 lks. dist. each,
 thence through lane.
 33.00 Adobe shack, bears W. 2 chs. dist. & a frame house bears
 E. 7 chs. dist.
 40.015 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 10 in
 W. & S 11 in E. & 1913 in S. half. /of post
 Dig pits 18 x 13 x 12 ins. N. & S. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 From the above described cor. cors. of wire fences, bear
 E. & W. 50 lks. dist. each, thence continue through lane
 79.50 S. edge of E. & W. lane, cors. of wire fences bears E. &
 W. 50 lks. dist. each.
 80.03 Set an iron post 3 ft. long, 22 ins. in diam., 24 ins. in ground
 for reestab. cor. of secs. 2, 3, 10 & 11, with a brass cap
 marked T 14 S R 24 E in N. & 1913 in S half, S 3 in N.W.,
 S 2 in N.E., S 11 in S.E. & S 10 in S.W. quadrant.
 Dig pits 18 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 Thence I run
 ✓ S. 89° 53' E. on true line bet. secs. 2 & 11
 Over level prairie land
 .50 Cors. of wire fences, bear N. & S. 50 lks. dist. each,
 thence through lane
 40.095 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 2 in
 N. & S 11 1913 in S. half. /of post
 Dig pits 18 x 13 x 12 ins. E. & W. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Note: Cors. of wire fences bear N. & S. 50 lks. dist.
 from the above described cor., also small house bears

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

- 80.19 bears S. 6° E. 7 chs. dist., thence continue through lane. Intersect the cor. of secs. 1, 2, 11 & 12, hereinbefore described.
Land level.
Soil light adobe, 12 ins. deep on hardpan sub-soil
Short salt grass
No timber.
-
- From the cor. of secs. 2, 3, 10 & 11, hereinbefore described
I run
N. 0° 04' W. on true line bet. secs. 2 & 3
Over level prairie land
- .50 S.V. cor. of wire fence, bears E. 50 lks., thence parallel to & 50 lks. W. of wire fence.
- 33.00 Small adobe house, bears E. 2 chs. dist.
- 40.015 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for re-estab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 3 in W., S 2 in E. & 1913 in S. half. ^{/of post}
Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
From the above described cor. cors. of wire fences bear E. & W. 50 lks. dist. each, thence parallel to & 50 lks. E. of wire fence.
- 80.29 Intersect N. bdy. of Tp. at the cor. of secs. 2, 3, 34 & 35, previously re-estab. by me, as described in Book "A".
Land level
Soil light adobe, 12 ins. deep on hardpan sub-soil
Short salt grass
No timber.
- June 23rd, 1913.
-
- June 24th, 1913:
At 7 h. 30 m., a.m., l.m.t., I set off 23° 26 $\frac{1}{2}$ ' N. on decl. arc, 32° 09 $\frac{1}{2}$ ' on lat. arc and determine a mer. with the solar at the cor. of secs. 3, 4, 33 & 34 on S. bdy. of Tp., previously re-estab. by me, as described in Book "A".
Thence I run
N. 0° 03' W. on true line bet. secs. 33 & 34
Over dry bed of old alkali lake.
- 39.23 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 33 in W., S 34 in E. & 1913 in S. half. ^{/of post}
Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Thence I run
N. 0° 30' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 33 & 34, on N. half mile.
- 11.00 Leave dry bed of old alkali lake, bears E. & W., thence over rolling prairie land
- 39.78 Intersect point for orig. cor. of secs. 27, 28, 33 & 34, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, cor. and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 27, 28, 33 & 34, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 28 in N.W., S 27 in N.E., S 34 in S.E. & S 33 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level & rolling
Soil alkali
Short salt grass on N. end of line
No timber.
-

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

Thence I run
 N.-89° 41' E. on true line bet. secs. 27 & 34
 Over slightly rolling prairie land
 40.12 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 27 in N. & S 34 1913 in S. half. /of post
 Dig pits 18 x 13 x 12 ins. E. & W. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 56.00 Phone line, bears N. 30° E., S. 30° W.
 61.00 Wagon road, bears N. 30° E., S. 30° W.
 63.00 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 63.75 Telegraph line, parallel to R.R.
 64.50 Main line of Southern Pacific R.R. bears N. 30° E., S. 30° W.
 66.00 R.R. right-of-way fence, bears N. 30° E., S. 30° W.
 72.00 Enter dry bed of old alkali lake, bears N.E. & S.W.
 80.24 Intersect cor. of secs. 26, 27, 34 & 35, hereinbefore described.
 Land level & rolling.
 Soil adobe & alkali 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 From the cor. of secs. 27, 28, 33 & 34, hereinbefore described
 I run
 N. 0° 24' E. on true line bet. secs. 27 & 28
 Over slightly rolling prairie land
 40.21 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 28 in W., S 27 in E. & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 Thence I run
 N. 0° 24' E. on true line bet. secs. 27 & 28, from $\frac{1}{4}$ sec. cor., on N. half mile.
 39.95 Intersect point for orig. cor. of secs. 21, 22, 27 & 28 hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 21, 22, 27 & 28, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 21 in N.W., S 22 in N.E., S 27 in S.E. & S 28 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling.
 Soil light adobe 12 ins. deep on hardpan sub-soil
 Short salt grass.
 No timber.

 Thence I run
 S. 89° 51' E. on true line bet. secs. 22 & 27
 Over level prairie land
 40.06 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, cor. and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 22 in N. & S 27 1913 in S. half. /of post
 Dig pits 18 x 13 x 12 ins. E. & W. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Thence I run
 N, 89° 49' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 22 & 27, on E. $\frac{1}{2}$ mile.
 39.85 Intersect cor. of secs. 22, 23, 26 & 27, hereinbefore described.

LINES
RECURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

Land level.
Soil light adobe, 12 ins. deep on hardpan sub-soil
Short salt grass
No timber.

From the cor. of secs. 21, 22, 27 & 23, hereinbefore de-
scribed

I run
N. 0° 23' E. on true line bet. secs. 21 & 22.
Over level prairie land
13.00 Wagon road, bears E. & W.
40.23 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy
all trace of the same, and re-establish it in the same
place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 21 in
W., S 22 in E. & 1913 in S. half. /of post

Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

The above described cor. falls 1 lks. W. of cor. of wire
fence, wire fence bears N. & S. 30° E.

Thence I run
N. 0° 20' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 21
& 22, along W. side of wire fence.

39.90 N.W. cor. of wire fence, bears E. 6 lks. dist.
39.95 Intersect point for orig. cor. of secs. 15, 16, 21 & 22, herein-
before described. This old cor. being in a state of de-
lapidation, I destroy all trace of the same, and re-
establish it in the same place, as follows:

Set an iron post 3 ft. long 2 ins. in dia., 24 ins. in
ground for cor. of secs. 15, 16, 21 & 22, with a brass cap
marked T 14 S R 24 E in N. & 1913 in S. half, S 16 in N.W.,
S 15 in N.E., S 22 in S.E. & S 21 in S.W. quadrant.

Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
raise mound of earth 4 ft. base 2 ft. high W. of cor.

Land level.
Soil light adobe, 12 ins. deep on hardpan sub-soil
Short salt grass.
No timber.

At the above described cor. I set off 23° 26' N. on decl.
arc and at 12 h. 2 m. 4 s., p.m., 1.m.t., observe the sun
on the mer. and obtain a reading of 32° 12' on lat arc.

Thence I run
East on true line bet. secs. 15 & 22
Over level prairie land
.06 Cor. of wire fence, bears S. 5 lks. dist., thence along
N. side of fence.

40.14 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy
all trace of the same, and re-establish it in the same
place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 15 in N.
& S 22 1913 in S. half. /of post

Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

Thence I run E-half
East from $\frac{1}{4}$ sec. cor. on true line bet. secs. 15 & 22
39.58 N.E. cor. of wire fence, bears S. 15 lks. dist.

40.08 Intersect cor. of secs. 14, 15, 22 & 23, hereinbefore
described.

Land level.
Soil light adobe, 12 ins. deep on hardpan sub-soil
Short salt grass
No timber.

Note: Wagon road follows along N. side of this line.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

From the cor. of secs. 15, 16, 21 & 22, hereinbefore described
 I run
 North on true line bet. secs. 15 & 16
 Over level prairie land
 .50 S.E. cor. of wire fence, bears W. 50 lks. dist., thence
 40.24 parallel to & 50 lks. E. of wire fence, wagon road bears E & W
 Intersect point for ~~orig. 1/4 sec. cor. hereinbefore described.~~
 This old cor. being in a state of delapidation, I destroy
 all trace of the same, and re-establish it in the same
 place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
 ground for 1/4 sec. cor., with a brass cap marked 1/4 S 16 in
 W., S 15 in E. & 1913 in S. half. /of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 Thence I run
 N. 0° 06' E. from 1/4 sec. cor. on true line bet. secs. 15
 & 16, on N. 1/2 mile. orig.
 39.95 Intersect point for cor. of secs. 9, 10, 15 & 16, hereinbefore
 described. This old cor. being in a state of delapidation
 I destroy all trace of the same, and re-establish
 it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins in dia., 24 ins. in
 ground for cor. of secs 9, 10, 15 & 16, with a brass cap
 marked T 14 S R 24 E in N. & 1913 in S, half, S 9 in N.W.,
 S 10 in N.E., S 15 in S.E. & S 16 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

Thence I run
 N. 83° 35' E. on true line bet. secs. 10 & 15
 Over level prairie land
 15.00 Wagon road, bears S. 85° E., N. 85° W.
 39.96 Intersect point for ~~orig. 1/4 sec. cor. hereinbefore~~ described.
 This old cor. being in a state of delapidation, I destroy
 all trace of the same, and re-establish it in the same
 place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
 ground for 1/4 sec. cor., with a brass cap marked 1/4 S 10 in
 N. & S 15 1913 in S. half. /of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 Note: from the above described cor. S.W. cor. of wire
 fence, bears N. 50 lks. dist.
 Thence I run E. 1/2
 S. 89° 56' E. from 1/4 sec. cor. on true line bet. secs.
 10 & 15, parallel to & 50 lks. S. of wire fence.
 39.60 S.E. cor. of wire fence, bears N. 50 lks. dist.
 40.10 Intersect cor. of secs. 10, 11, 14 & 15, hereinbefore de-
 scribed.
 Land level
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

From the cor. of secs. 9, 10, 15 & 16, hereinbefore de-
 scribed.
 I run
 N. 0° 03' E. on true line bet. secs. 9 & 10
 Over level prairie land
 09.25 N.E. cor. of wire fence, bears W. 50 lks. dist.
 2.00 Wagon road, bears E. & W.
 20.00 Wire fence, bears E. & W., S.E. cor. of wire fence bears
 E. 50 lks. dist., thence parallel to & 50 lks. W. of wire
 fence.

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

40.25 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 9 in W. S 10 in E. & 1913 in S. half. /of post
 Dig pits 18 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 From the above described cor. cor. of wire fence bears E. 50 lks.
 Thence I run
 North from $\frac{1}{4}$ sec. cor. on true line $N. \frac{1}{2}$ bet. secs. 9 & 10 along W. side of fence.

- 10.00 House, bears E. 7 chs. dist.
- 19.00 Small cabin bears W. 2 chs. dist.
- 25.00 Wire fence, bears N. 3° W., S. 3° E.
- 27.00 Wagon road, bears E. & W.
- 35.00 Wire fence, bears N. 87° E., S. 37° W.

39.89 Intersect point for orig. cor. of secs. 3, 4, 9 & 10, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 3, 4, 9 & 10, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 4 in N.W., S 3 in N.E., S 10 in S.E. & S 9 in S.W. quadrant.
 Dig pits 18 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 Thence I run
 N. $89^{\circ} 27'$ E. on true line bet. secs. 3 & 10
 Over level prairie land
 5.00 Wire fence, bears N. & S.
 19.00 S.W. cor. of wire fence, bears N. 50 lks. dist.

40.105 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 3 in N., & S 10 1913 in S half. of post
 Dig pits 18 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Note: from the above described cor. N.W. cor. of wire fence bears S. 50 lks. dist., also S.E. cor. of wire fence bears N. 50 lks. dist. From 19 chs. to $\frac{1}{4}$ sec. cor., above described, line runs parallel to & 50 lks. S. of wire fence, thence parallel to & 50 lks. N. of wire fence.

- 43.00 H. M. Hall's house, bears S. 3 chs. dist.
- 79.70 N.E. cor. of wire fence, bears S. 50 lks. dist.

80.21 Intersect cor. of secs. 2, 3, 10 & 11, hereinbefore described.
 Land level.
 Soil adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 From the cor. of secs. 3, 4, 9 & 10, hereinbefore described
 I run
 N. $0^{\circ} 04'$ E. on true line bet. secs. 3 & 4.
 Over level prairie land
 18.00 Small cabin bears W, 5 chs. dist.
 20.00 Wire fence, bears E. & W., S.W. cor. of wire fence bears W. 50 lks. dist., thence parallel to & 50 lks. E. of wire fence.

40.21 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:

LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 4 in W., S 3 in E. & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 Note; ~~from~~ the above described cor. wire fence bears E. & W., cor. of wire fence bears W. 50 lks. dist.
 Thence I run N. $0^{\circ} 29'$ W. from $\frac{1}{4}$ sec. cor. on true line \wedge N. $\frac{1}{2}$ bet. secs. 3 & 4, parallel to & 50 lks. E. of wire fence.
 40.78 Intersect N. bdy. of Tp. at the cor. of secs. 3, 4, 33 & 34, previously re-estab. by me, as described in Book "A"
 Land level.
 Soil light adobe 12 ins. deep on hardpan subsoil.
 Scattering mesquite brush 3 to 4 ft. high, short salt grass.
 No timber.

June 24th, 1913.

June 25, 1913:
 At 9 h. 0 m., a.m., l.m.t., I set off $23^{\circ} 25\frac{1}{2}'$ N. on decl. arc, $72^{\circ} 09\frac{1}{2}'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 4, 5, 32 & 33, on E. bdy. of Tp., previously re-estab. by me, as described in Book "A."
 Thence I run N. $0^{\circ} 04'$ W. on true line bet. secs. 32 & 33

40.03 Over dry bed of old alkali-lake
 Intersect point for orig $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, ~~cor.~~ and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 32 in W., S 33 in E. & 1913 in S. half /of post
 Dig pits 13 x 13 x 12 ins. N. & S. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 Thence I run N. $0^{\circ} 25'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 32 & 33, on N. $\frac{1}{2}$ mile.

13.00 Leave dry bed of old alkali lake, bears E. & W., thence over rolling prairie land

40.05 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in ground for reestab. cor. of secs. 28, 29, 32 & 33, with a brass cap marked T 14 S R. 24 E in N. & 1913 in S. half, S 29 in N.W., S 23 in N.E., S 33 in S.E. & S 32 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W, of cor.
 Land level & rolling.
 Soil alkali & adobe
 Short salt grass on N. end of line
 No vegetation from 0 to 57 chs.

Thence I run S. $39^{\circ} 31'$ E. on true line bet. secs. 28 & 33
 Over rolling prairie land

40.11 Intersect point for orig $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, ~~cor.~~ and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground, for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 23 in N. & S 33 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. \wedge 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Thence I run S. $38^{\circ} 50'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 28 & 33, on E. half mile.

40.32 Intersect cor. of secs. 27, 28, 33 & 34, hereinbefore described.

Land level & rolling.
 Soil light adobe 12 ins. deep on hardpan sub-soil
 Short salt grass. No timber.

KLINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

- From the cor. of secs. 28, 29, 32 & 33, hereinbefore described
I run
40.05 ✓ N. 0° 33' E. on true line bet. secs. 28 & 29
Over rolling prairie land
Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S. 29 in W., S 23 in E. & 19 $\frac{1}{3}$ in S. half; /of post
Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth 3 $\frac{1}{2}$ ft. base 1 $\frac{1}{2}$ ft. high W. of cor.
Thence I run
33.00 ✓ N. 0° 03' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 28 & 29, on N. half mile.
38.00 Enter dry bed of small alkali lake.
39.25 Wagon road, bears E. & W.
39.95 S.E. cor. of wire fence, bears W. 50 lks. dist.
39.69 Leave dry bed of small alkali lake, bears E. & W.
Set an iron post 3 ft. long 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 20, 21, 28 & 29, with a brass cap marked T 14 S R 24 E in N. & 19 $\frac{1}{3}$ in S. Half, S 20 in N.W., S. 21 in N.E., S 23 in S.E. & S 29 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. 5 $\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level & rolling.
Soil light adobe, 12 ins. deep on hardpan sub-soil.
Short salt grass
No timber.
At the above described cor. I set off 23° 24 $\frac{1}{2}$ ' N. on decl arc, and at 12 h. 2 m. 16 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 11 $\frac{1}{2}$ ' on lat. arc
-
- Thence I run
6.00 ✓ S. 89° 38' E. on true line bet. secs. 21 & 28
Over level prairie land
40.16 Wagon road, bears N. 30° E. S. 30° W.
Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 21 in N. & S 23 19 $\frac{1}{3}$ in S. half. /of post
Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth 3 $\frac{1}{2}$ ft. base 1 $\frac{1}{2}$ ft. high N. of cor.
80.32 Intersect cor. of secs. 21, 22, 27 & 28, hereinbefore described.
Land level.
Soil light adobe 12 ins. deep on hardpan sub-soil.
Short salt grass.
No timber.
-
- From the cor. of secs. 20, 21, 28 & 29, hereinbefore described
I run
39.69 ✓ N. 0° 31' E. on true line bet. secs. 20 & 21
Over level prairie land 50 lks. E. of & parallel to wire fence.
Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 20 in W, S 21 in E. & 19 $\frac{1}{3}$ in S. half. /of post
Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth 3 $\frac{1}{2}$ ft. base 1 $\frac{1}{2}$ ft. high W. of cor.
From the above described cor. N.E. cor. of wire fence bears W. 6 lks. dist.
Thence I run
N. 0° 27' E. from $\frac{1}{4}$ sec. cor. on N. half mile.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

21.00 Wagon road, bears N. 30° E., S. 30° W.
 31.00 Wagon road, bears N.E. & S.W.
 40.02 Intersect point for orig. cor. of secs. 16, 17, 20 & 21, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins in dia., 24 ins. in ground for cor. of secs. 16, 17, 20 & 21, with a brass cap marked T 10 S R 24 E in N. & 1913 in S. half, S 17 in N.W., S 16 in N.E., S 21 in S.E. & S 20 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. land level.
 Soil light adobe 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 Thence I run
 S. 39° 58' E. on true line bet. secs. 16 & 21
 Over level prairie land
 1.00 S.W. cor. of wire fence, bears N. 50 lks. dist., thence S. of wire fence.
 18.00 Ditch 10 lks. wide, 3 ft. deep, course S. 30° W.
 40.10 Intersect point for orig. 1/4 sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 16 in N. & S 21 1913 in S. half. /of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 Thence I run E. 1/2
 East from 1/4 sec. cor. on true line bet. secs. 16 & 21
 26.00 Enter dry bed of small alkali lake, bears N. & S. extending S. 3 chs. & N. 2 chs. dist.
 27.50 Leave dry bed of small alkali lake, bears N. & S
 39.60 S.E. cor. of wire fence, bears N. 50 lks. dist.
 40.10 Intersect cor. of secs. 15, 16, 21 & 22, hereinbefore described.
 Land level, soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

June 25th, 1913.

June 26, 1913:

At 9 h. 0 m., a.m.; l.m.t., I set off 23° 23' N. on decl. arc, 32° 12' on lat. arc and determine a mer. with the solar at the cor. of secs. 16, 17, 20 & 21, hereinbefore described.
 Thence I run
 N. 0° 02' W. on true line bet. secs. 16 & 17
 Over level prairie land
 .50 Cor. of wire fence, bears E. 1 ch. dist., thence W. of fence.
 5.00 Windmill & well bears E. 4 chs. dist.
 21.00 S.E. cor. of wire fence, bears W. 50 lks., thence through land
 40.15 Intersect point for orig. 1/4 sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 17 in W., S 16 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 From the above described cor. cor. of wire fence bears W. 50 lks. dist.

LINES-

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

	also small cabin bears S. 86° W. & small adobe house bears N. 34 $\frac{1}{4}$ ° W.
	Thence I run N. 0° 03' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 16 & 17 on N. half mile.
-23.40	Same cabin bears S. 37 $\frac{1}{2}$ ° W. and adobe house bears N. 88° W
39.50	Cors. of wire fences bear E. & W. 50 lks. dist. each.
40.00	Intersect point for orig. cor. of secs. 3, 9, 16 & 17, here in- before described. This old cor. being in a state of delap- idation, I destroy all trace of same, and re-estab- lish it in the same place, as follows: Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 3, 9, 16 & 17, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 3 in N.W., S 9 in N.E., S 16 in S.E. & S 17 in S.W. quadrant. Dig pits 13 x 13 x 12 ins. in each sec. 5 $\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. Land level Soil light adobe 12 ins. deep on hardpan sub-soil Short salt grass, with scattering mesquite brush 3 to 5 ft. high along N $\frac{1}{2}$ of mile. No timber.

	Thence I run
	S. 89° 53' E. on true line bet. secs. 9 & 16
	Over level prairie land
.50	Cor. of wire fence, bears S. 50 lks. dist., thence parallel to & 50 lks. N. of wire fence.
40.10	Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows: Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S. 9 in N. & S 16, 1913 in S. half; /of post Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 $\frac{1}{2}$ ft. base 1 $\frac{1}{2}$ ft. high N. of cor. Thence I run
	S. 89° 51' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 9 & 16, on E. half of mile.
28.00	Wire fence, bears N. 83° E. S. 83° W.
39.50	Wire fence, bears N. & S., N.E. cor. of fence bears N. 25 lks. dist.
40.08	Intersect cor. of secs. 9, 10, 15 & 16, hereinbefore de- scribed. Land level Soil adobe 12 ins. deep on hardpan sub-soil Short salt grass No timber.

	From the cor. of secs. 8, 9, 16 & 17, hereinbefore de- scribed I run
	N. 0° 06' E. on true line bet. secs. 8 & 9
	Over level prairie land
20.00	S.W. cor. of wire fence, bears E. 50 lks. dist., thence parallel to & 50 lks. W. of wire fence.
40.00	N.W. cor. of wire fence, bears E. 50 lks.
40.28	Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S. 8 in W., S 9 in E. & 1913 in S. half. /of post Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 $\frac{1}{2}$ ft. base 1 $\frac{1}{2}$ ft. high W. of cor.
45.00	Adobe house on line
48.00	Wire fence bears E. & W.
51.00	Wire fence, bears N. 5° W., S. 5° E.
70.00	Wire fence, bears E. & W., fence cor. bears W. 50 lks. dist. thence parallel to & 50 lks. E. of wire fence.
80.56	Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 4, 5, 8 & 9, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 5 in N.W.

LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

S 4 in N.E., S 9 in S.E. & S 8 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light adobe 12 ins. deep on hardpan subsoil
 Short salt grass
 Scattering mesquite brush 3 to 4 ft. high
 No timber

-
- Thence I run
 ✓ S. 89° 46' E. on true line bet. secs. 4 & 9
 Over level, prairie land
 20.50 Wagon road, bears S.E. & N.W., cor of wire fence bears
 N. 50 lks. dist., thence parallel to & 50 lks. S. of wire
 fence.
 20.25 Wire fence, bears N. & S., N.E. cor. of fence, bears N.
 50 lks. dist., thence through pasture.
 ✓ 40.14 Intersect point for orig. 1/4 sec. cor. hereinbefore described.
 This old cor. being in a state of dilapidation, I destroy
 all trace of same, and re-establish it in the same
 place, as follows:
 Set an iron post 7 ft. long, 1 in. in dia., 26 ins. in
 ground for 1/4 sec. cor., with a brass cap marked S 4 in
 N. & S 9 1913 in S. half. of post
 Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 Thence I run
 ✓ S. 89° 46' E. from 1/4 sec. cor. on true line bet. secs.
 4 & 9, on east half mile.
 ✓ 40.12 Intersect cor. of secs. 3, 4, 9 & 10, hereinbefore de-
 scribed.
 Land level.
 Soil light adobe 12 to 13 ins. deep on hardpan sub-soil
 Good grass.
 No timber.

-
- From the cor. of secs. 4, 5, 8 & 9, hereinbefore described.
 I run
 ✓ N. 0° 18' W. on true line bet. secs. 4 & 5
 Over level, prairie land, through scattering mesquite brush
 3 to 4 ft. high
 .50 Cors. of wire fences bear E. & W. 50 lks. dist. each,
 thence through lane.
 5.00 Cabin, bears W. 7 chs. dist.
 10.00 Cor. of wire fence, bears W. 50 lks. dist.
 25.00 J.P. Cummings' house bears E. 5 chs. dist.
 40.25 Cors. of wire fences, bears E. 75 lks. & W 25 lks. dist.
 ✓ 40.28 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked S 5 in W
 S 4 in E. & 1913 in S. half. of post
 Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 73.00 Wire fence bears N. 3° E., S. 3° W., leave lane, thence
 through edge of pasture
 80.50 Wire fence, bears E. & W., cor. bears E. 15 lks. dist.
 ✓ 80.74 Intersect N. bdy. of Tp. at the cor. of secs. 4, 5, 32 &
 33, previously re-estab. by me, as described in Book "A."
 Land level.
 Soil light adobe 12 ins. deep on hardpan sub-soil
 Short salt grass, scattering mesquite brush 3 to 6 ft. high
 No timber.

June 26th, 1913.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

- June 27, 1913: At 8 h. 30 m., a.m., l.m.t, I set off $23^{\circ} 21'$ N. on decl. arc, $32^{\circ} 09\frac{1}{2}'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 5, 6, 31 & 32 on S. bdy. of Tp. heretofore reestab. by me, as described in Book "A"
- Thence I run
- 40.47 ✓ N. $0^{\circ} 11'$ E. on true line bet. secs. 31 & 32
Over dry bed of old alkali lake
Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 31 in W., S 32 in E. & 1913 in S. half. /of post
Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Thence I run
- 7.00 ✓ N. $0^{\circ} 21'$ E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 31 & 32, on N. $\frac{1}{2}$ mile.
Leave dry bed of old alkali lake, bears E. & W., thence over slightly rolling prairie land.
- 18.00 Wagon road, bears N.E. & S.W.
- 20.00 S.E. cor. of wire fence, bears W. 50 lks., thence parallel to & 50 lks. E. of wire fence.
- 27.00 Dry wash 25 lks. wide, 3 ft. deep, course East.
- 37.50 House, bears W. 3 chs. dist.
- 40.03 Intersect point for orig. cor. of secs. 29, 30, 31 & 32, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 29, 30, 31 & 32, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 30 in N.W., S 29 in N.E., S 32 in S.E. & S 31 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level & rolling.
Soil alkali & adobe
From 0 to 47 chs, no vegetation. From 47 to 30 chs. short salt grass.
No timber.
-
- Thence I run
- 19.00 ✓ S. $39^{\circ} 46'$ E. on true line bet. secs. 29 & 32
Over slightly rolling prairie land, parallel to & 50 lks. S. of wire fence.
- 20.00 S.E. cor. of wire fence bears N. 50 lks. dist.
- 20.00 Wagon road, bears N.E. & S.W.
- 32.00 Small spring bears S. 2 chs. dist.
- 39.50 Dry wash 50 lks. wide, 3 ft. deep, course S. 15° E.
- 40.12 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 29 in N. & S 32 1913 in S. half. /of post
Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 80.24 Intersect cor. of secs. 28, 29, 32 & 33, hereinbefore described.
Land level & rolling
Soil light adobe, 12 to 13 ins. deep on hardpan sub-soil
Short salt grass.
No timber.
-
- From the cor. of secs. 29, 30, 31 & 32, hereinbefore described
I run
- ✓ S. $83^{\circ} 44'$ W. on true line bet. secs. 30 & 31
Over slightly rolling prairie land
- .50 Wire fence, bears N. & S., cors. of fences bears N. & S. 50 lks. dist. each, thence parallel to & 50 lks. N. of wire fence.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

5.25 N.W. cor. of wire fence, bears S. 50 lks. dist.
 18.00 Wire fence bears N. 5° W., S. 5° E.
 35.00 Dry wash 15 lks. wide, 1 ft. deep, course S. 30° E.
 40.17 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the
 ground for reestab. ¹/₄ sec. cor. with brass cap, mkd. ¹/₄ S 30 in
 N. & S 31 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. ¹/₃ ft. dist. & raise
 mound of earth 3 ¹/₂ ft. base 1 ¹/₂ ft. high N. of cor.
 46.50 Wire fence, bears N. & S., enter scattering mesquite brush
 3 to 6 ft. high
 48.00 Wagon road, bears N. & S.
 53.50 Dry wash 30 lks. wide, 3 ft. deep, course N. 60° E.
 63.00 Small cabin, bears S. 50 lks. dist.
 64.00 Windmill & well bears S. 1 ch. dist.
 80.83 Intersect W. bdy. of Tp. at the cor. of secs. 25, 30, 31
 & 36, previously re-estab. by me, as described in Book "A"
 Land level & rolling.
 Soil light adobe, 12 to 13 ins. deep on hardpan sub-soil
 Short salt grass, scattering mesquite brush on ¹/₂ of line.
 No timber.

 From the cor. of secs. 29, 30, 31 & 32, hereinbefore de-
 scribed
 I run
 N. 0° 24' E. on true line bet. secs. 29 & 30
 Over slightly rolling prairie land 50 lks. E. of & parallel
 to wire fence.

.50 Wire fence, bears E. & W.
 20.00 Wire fence, bears E. & W.
 32.50 House, bears W. 2 chs. dist.
 39.00 S.W. cor. of wire fence, bears E. 50 lks. dist.
 40.24 Intersect point for orig. ¹/₄ sec. cor., hereinbefore described.
 This old cor. being in a state of delapidation, I destroy
 all trace of same, and re-establish it in the same
 place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
 ground for ¹/₄ sec. cor., with a brass cap marked ¹/₄ S 30 in
 W., S 29 in E. & 1913 in S half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. ¹/₃ ft. dist. & raise
 mound of earth 3 ¹/₂ ft. base 1 ¹/₂ ft. high W. of cor.
 From the above described cor. N.E. cor. of wire fence
 W. 50 lks. dist.

Thence I run N. half
 N. 0° 05' E. from ¹/₄ sec. cor. on true line bet. secs. 29
 & 30, parallel to & 50 lks. W. of wire fence.
 10.00 Enter scattering mesquite brush 3 to 4 ft. high, bears E.
 & W.

12.50 Debo's house, bears E. 3 chs. dist.
 38.00 N.W. cor. of wire fence, bears E. 50 lks. dist.
 39.00 S.W. cor. of wire fence, bears E. 50 lks. dist.
 39.95 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground
 for reestab. cor. of secs. 19, 20, 29 & 30, with a brass cap
 marked T 14 S R 24 E in N. & 1913 in S. half, S 19 in N.W.,
 S 20 in N.E. S 29 in S.E. & S 30 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 ¹/₂ ft. dist. &
 raise mound of earth 4 ¹/₂ ft. base 2 ft. high W. of cor.
 Land level & rolling
 Soil adobe, 12 to 13 ins. deep on hardpan sub-soil
 Short salt grass & scattering mesquite brush 3 to 6 ft.
 high.
 No timber.

 Thence I run
 S. 39° 27' E. on true line bet. secs. 20 & 29
 Over slightly rolling prairie land, through mesquite
 brush 3 to 6 ft. high
 .50 Wire fence, bears N. & S., thence parallel to & N. of E.
 & W. lane.
 5.00 Leave mesquite brush, bears N. & S.
 29.00 Spring bears N. 3 chs. dist.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

- ✓40.06 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground for reestab. 1/4 sec. cor.**, with a brass cap marked 1/4 S 20 in N. & S 29, 1913 in S. half.
Dig pits 13 x 13 x 12 ins. E. & W. ^{/of post} 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
- 41.00 Wire fence, bears N. & S., N.E. cor. of wire fence bears S. 150 lks., also S.E. cor. of wire fence, bears S. 50 lks.
- 46.50 Wire fence, bears N.W. & S.E., thence along N. of fence
- 49.50 Wagon road, bears N. 30° E., S. 30° W
- 79.60 Wire fence, bears N. & S.
- ✓80.12 Intersect cor. of secs. 20, 21, 28 & 29, hereinbefore described.
Land level & rolling.
Soil light adobe, 12 ins. deep on hardpan sub-soil
Short salt grass with scattering mesquite brush 3 to 6 ft. high on W. end of line.
No timber

At the cor. of secs. 19, 20, 29 & 30, hereinbefore described I set off 23° 20' 1/2" N. on decl. arc, and at 12 h. 2 m. 42 s. 1/2 p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 11' 1/2" on lat. arc.
Thence I run
S. 39° 45' W. on true line bet. secs. 19 & 30.
Over slightly rolling land, through mesquite brush 3 to 6 ft. high

- 40.105 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground for reestab. 1/4 sec. cor.**, with a brass cap marked 1/4 S 19 in N. & S 30 1913 in S. half.
Dig pits 13 x 13 x 12 ins. E. & W. ^{/of post} 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
- 41.00 Wire fence, bears N. & S., N.E. cor. bears N. 50 lks. dist.
- 42.50 Dry wash 15 lks. wide, 3 ft. deep, course S. 30° E.
- 80.81 Intersect W. bdy. of Tp. at the cor. of secs. 19, 20, 25 & 30, previously re-estab. by mesa described in Book "A"
Land level & rolling
Soil adobe, 12 to 13 ins. deep on hardpan sub-soil
Scattering grass, mesquite brush 3 to 6 ft. high.
No timber.

From the cor. of secs. 19, 20, 29 & 30, hereinbefore described I run
N. 0° 25' E. on true line bet. secs. 19 & 20
Over slightly rolling land, through mesquite brush 3 to 6 ft. high, parallel to & 50 lks. W. of wire fence.

- 2.50 Small adobe house, bears W. 5 chs. dist.
- 3.50 Dry wash 1 ch. wide, 2 ft. deep, course East.
- ✓39.95 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground for reestab. 1/4 sec. cor.**, with a brass cap marked 1/4 S 19 in W., S 20 in E. & 1913 in S. half. ^{/of post}
Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
- 78.00 Cor of wire fence, bears E. 50 lks. dist.
- ✓79.90 Set an iron post 3 ft. long, 2 ins. in dia. **24 ins. in ground for reestab. cor of secs. 17, 18, 19 & 20**, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 18 in N.W., S. 17 in N.E., S 20 in S.E. & S 19 in S.W. quadrant
Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level & rolling
Soil adobe 12 ins. deep on hardpan sub-soil
Scattering grass mesquite brush 3 to 6 ft. high
No timber.

Thence I run
S. 83° 35' E. on true line bet. secs. 17 & 20
Over level land through mesquite brush 3 to 6 ft. high

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

16.00 Wire fence bears N. 88° E., S. 33° W.
 20.00 Wire fence, bears N. & S., fence cors. bear N. & S. 50 lks. dist. each, thence parallel to & 50 lks. N. of wire fence.
 40.21 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of ~~same~~, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 17 in N. & S 20 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Thence I run
 N. 89° 58' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 17 & 20, on East half mile.
 20.00 N.E. cor. of wire fence, bears S, 50 lks. dist., leave mesquite brush, bears N. & S.
 40.10 Intersect cor. of secs. 16, 17, 20 & 21, hereinbefore described.
 Land level.
 Soil adobe, 12 to 13 ins. deep on hardpan sub-soil
 Scattering grass, mesquite brush 3 to 6 ft. high
 No timber.

June 27th, 1913.

June 28, 1913:
 At 7 h. 30 m., a.m., l.m.t., I set off 23° 19' N. on decl. arc, 32° 12' on lat. arc and determine a mer. with the solar at the cor. of secs. 17, 18, 19 & 20, hereinbefore described.
 Thence I run
 S. 89° 52' W. true line bet. secs. 18 & 19
 40.19 Over level land through mesquite brush 3 to 6 ft. high
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 18 in N., S 19 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 43.00 Dry wash 15 lks. wide, 3 ft. deep, course S. 30° W.
 81.29 Intersect W. bdy. of Tp. at the cor. of secs. 13, 18, 19 & 24, previously re-established by me, as described in Book "A."
 Land level
 Soil loose gravelly, 12 to 13 ins. deep on clay sub-soil
 Scattering grass, mesquite brush 3 to 6 ft. high.
 No timber.

From the cor. of secs. 17, 18, 19 & 20, hereinbefore described

I run
 N. 0° 05' E. on true line bet. secs. 17 & 18
 Over level land, through mesquite brush 3 to 5 ft. high
 19.00 Dry wash 10 lks. wide, 1 ft. deep, course East.
 26.00 Dry wash 10 lks. wide, 1 ft. deep, course East.
 39.95 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, mkd. $\frac{1}{4}$ S 18 in W., S 17 in E. & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 78.70 Wagon road, bears E. & W.
 79.90 Intersect point for orig. cor. of secs. 7, 8, 17 & 18, hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of ~~same~~, and re-establish it in the same place, as follows:
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 7, 8, 17 & 18, with a brass cap marked T 14 S R 24 E in N. & 1913 in S. half, S 7 in N.W., S 3 in N.E., S 17 in S.E. & S 18 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth $4\frac{1}{2}$ ft. base 12 ft. high W. of cor.
 Land level.
 Soil loose gravelly 12 to 13 ins. deep on clay sub-soil
 Scattering grass, mesquite brush 3 to 6 ft. high
 No timber.

-38-
LINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST

- Thence I run.
S. 89° 29' E. on true line bet. secs. 3 & 17
Over level land, through mesquite brush 3 to 6 ft. high
Wagon road, bears N.E. & S.W.
- 3.00
40.115 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for reestab. $\frac{1}{4}$ sec. cor. with brass cap, marked $\frac{1}{4}$ S 8 in N. & S 17 1913 in S. half.
Dig pits 13 x 13 x 12 ins. E. & W. ^{/of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
From the above described cor. N.W. cor. of wire fence bears S. 50 lks. dist., thence parallel to & 50 lks. N. of wire fence.
- 50.50 Dry wash 15 lks. wide, 2 ft. deep, course S. 60° E.
70.00 Leave mesquite brush, bears N. & S.
79.70 N.E. cor. of wire fence bears S. 50 lks. dist.
30.21 Intersect cor. of secs. 8, 9, 16 & 17, hereinbefore described.
Land level
Soil adobe 12 to 13 ins. deep on hardpan sub-soil
Short salt grass, scattering mesquite brush 3 to 6 ft. high
No timber.
-
- From the cor. of secs. 7, 8, 17 & 18, hereinbefore described
I run
West on true line bet. secs. 7 & 18
Over level land, through mesquite brush 3 to 6 ft. high
- 09.25 S.E. cor. of wire fence, bears N. 50 lks. dist., thence parallel to & 50 lks. S. of wire fence.
39.40 S.W. cor. of wire fence, bears N. 50 lks. dist.
40.13 Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described. This old cor. being in a state of delapidation, I destroy all trace of the same, and re-establish it in the same place, as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 7 in N. & S 13 1913 in S. half.
Dig pits 13 x 13 x 12 ins. E. & W. ^{/of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
Thence I run
N. 89° 28' W. 22' E. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 7 & 18, on west half mile.
- 10.00 Small adobe house bears S. 10 chs. dist.
41.22 Intersect W. bdy of Tp. at the cor. of secs. 7, 12, 13 & 18, previously re-estab. by me, as described in Book "A."
Land level.
Soil, loose gravelly, 12 to 13 ins. deep on clay sub-soil
Scattering grass, scattering mesquite brush 3 to 6 ft. high
No timber.
-
- At the cor. of secs. 7, 8, 17 & 18, hereinbefore described
I set off 23° 18' N. on decl. arc, and at 12 h. 2 m. 54 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 13" on lat. arc.
Thence I run
North on true line bet. secs. 7 & 8
Over level land, through mesquite brush 3 to 6 ft. high
- .50 S.E. cor. of wire fence bears W. 25 lks., thence parallel to & 25 lks. E. of wire fence.
39.00 Wire fence, bears E. & W., fence cor. bears W. 25 lks.
40.13 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 7 in W., S 8 in E. & 1913 in S. half. ^{/of post}
Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Thence parallel to & 50 lks. W. of wire fence.
- 79.80 Wire fence, bears E. & W., fence cor. bears E. 50 lks. dist.
80.00 Wagon road, bears E. & W.
80.26 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in

RESURVEY OF SUBDIVISION ^{LINES} OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

in ground for reestab. cor. of secs. 5, 6, 7 & 8, with a brass cap marked T 14 S R 24 E in N. & 1913 in S half, S 6 in N.W., S 5 in N.E., S 8 in S.E. & S 7 in S.W. quadrant.

Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.

Land level

Soil loose, gravelly 12 to 13 ins. deep on clay sub-soil

Scattering grass, mesquite brush 3 to 6 ft. high.

No timber.

Thence I run

S. 39° 31' E. on true line bet. secs. 5 & 8

Over level land, through mesquite brush 5 to 6 ft. high

.50 Wire fence, bears N. & S., fence cors. bear N. & S. 50 lks. dist each, thence parallel to & 50 lks. S. of wire fence.

27.50 House bears N. 2 chs. dist.

35.00 Small house, bears S. 2 chs. dist.

40.09 Intersect point for orig. 1/4 sec. cor. hereinbefore described

This old cor. being in a state of delapidation, I destroy all trace of same, and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground, for 1/4 sec. cor., with a brass cap marked 1/4 S 5 in N. & S 8 1913 in S. half.

Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

From the above described cor. cor. of wire fence bears N. 50 lks. dist.

Thence I run

S. 39° 52' E. from 1/4 sec. cor. on true line bet. secs. 5 & 8, on E 1/2 mile

20.00 Wire fence, bears N. & S., fence cor. bears N. 50 lks. dist.

33.00 Fence cor. bears N. 50 lks. dist.

39.50 Wire fence, bears N. & S., fence cor. bears N. 50 lks. dist.

40.06 Intersect cor. of secs. 4, 5, 8 & 9, hereinbefore described.

Land level

Soil loose sandy 12 to 13 ins. deep on clay sub-soil

Scattering grass, mesquite brush 3 to 6 ft. high

No timber.

Note: wagon road follows along S. of this line

From the cor of secs. 5, 6, 7 & 8, hereinbefore described

I run

S. 89° 59' W. on true line bet. secs. 6 & 7

Over slightly rolling prairie land through scattering mesquite brush parallel to & 50 lks. N. of wire fence.

2.00 Wagon road, bears N. 30° W., S. 80° E.

40.14 Intersect point for orig. 1/4 sec. cor. hereinbefore described

This old cor. being in a state of delapidation, I destroy all trace of of same, and re-establish it in the same place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for 1/4 sec. cor., with a brass cap marked 1/4 S 6 in N. & S 7 1913 in S half.

Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

Thence I run

N. 89° 37' W. from 1/4 sec. cor. on true line bet. secs. 6 & 7, on W 1/2 mile

40.60 N.W. cor. of wire fence, bears S. 50 lks. dist.

41.15 Intersect W. bdy. of Tp. at the cor. of secs. 1, 6, 7 & 12, previously re-estab. by me as described in Book "A"

Land level & rolling.

Soil loose gravelly sandy loam 12 to 24 ins. deep on clay sub-soil

Good prairie grass, scattering mesquite brush

No timber.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 14 SOUTH, RANGE 24 EAST.

33.00
40.13

From the cor. of secs. 5, 6, 7. & 8, hereinbefore described
I run
North on true line bet. secs. 5 & 6
Over slightly rolling land, through mesquite brush 3 to
6 ft. high, parallel to & 50 lks. W. of wire fence.
Wagon road, bears N.E. & S.W.

Intersect point for orig. $\frac{1}{4}$ sec. cor. hereinbefore described.
This old cor. being in a state of delapidation, I destroy
all trace of the same, and re-establish it in the same
place, as follows:

Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
ground for $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 6 in W.,
S 5 in E. & 1913 in S. half.

Dig pits 18 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

From the above described cor. cor. of wire fence bears
E 50 lks. dist.

Thence I run
N. $0^{\circ} 53'$ W. from $\frac{1}{4}$ sec. cor. on true line bet. secs. 5
& 6, on $N\frac{1}{2}$ mile

28,50
79,90

Dry wash 15 lks. wide, 3 ft. deep, course East.

Wagon road, bears E. & W.

40.10

Intersect N. bdy. of Tp. at the cor. of secs. 5, 6, 31
& 32, previously re-estab. by me as described in Book "A"

Land level & rolling.
Soil, loose gravelly sandy loam, 12 to 24 ins. deep on
clay sub-soil

Scattering grass, mesquite brush 3 to 7 ft. high
No timber.

June 28th, 1913.

GENERAL DESCRIPTION.

This township is practically level, the slope being very
gentle towards the South and East. Excepting for the ex-
treme Northwestern portion the soil is strong with alkali,
sustaining little except a short salt grass. The large
bed of old alkali lake, comprising most of the Southern
tier of sections and some of sections 25 and 26, is so
strong of alkali that it is entirely barren of vegetation.

Excepting for the higher portion of the township in the
Northwestern corner there is an abundant supply of water
to be had at a depth from 10 to 30 feet. A well in the
W.W. $\frac{1}{4}$ of section 6 was dug to a depth of about 90 feet.
before obtaining water.

There are a good many settlers scattered throughout all
parts of this township, excepting the Southeastern corner.

Thomas B. Matthews

June 28, 1913.

U. S. Surveyor.

For FINAL OATH OF UNITED STATES SURVEYOR.

(See Book " D ")

I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191 _____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

U. S. Surveyor.

Subscribed by said _____, and sworn to before me }
 this _____ day of _____, 191 _____



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,
 Phoenix Arizona, March 20 _____, 191 5

The foregoing field notes of the survey of Resurvey of the
Subdivision Lines of
Township No 14 South Range No. 24 East
of the Gila and Salt River Base and Meridian
in the State of Arizona

executed by Thomas B Matthews U.S. Surveyor
 under his special instructions dated April 21, 1913 for Group 25 _____, ~~191~~ _____, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the re surveys they describe, are hereby approved.

Frank Ingalls
 U. S. Surveyor General.
 of Arizona.

~~I certify that the foregoing transcript of the field notes of the above-described surveys in _____, has been correctly copied from the original notes on file in this office.~~