

2727

4-679

2727

Book "H"

Resurvey Subdivisions

FIELD NOTES

BOOK 2727

SEP 2-1914

OF THE RESURVEY OF THE

Subdivision lines of

Township 16 South Range 25 East

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Thomas B. Matthews,

In the capacity of U. S. Surveyor, under instructions dated May 7, 1913, issued by the United States Surveyor General to govern surveys included in Group No. 25, which were approved by the Commissioner of the General Land Office, May 15, 1913, pursuant to authority contained in the Act of Congress dated June 23, 1913.

Re Survey commenced July 12, 1913

Re Survey completed July 22, 1913

(A)

A

Book "H"

BOOK 2727

INDEX DIAGRAM.

Township *16 South*, Range *25 East*

3rd Standard Parallel South

6	24	5	18	4	14	3	9	2	5	1
24		23		18		13		9		4
7	23	8	17	9	13	10	8	11	4	12
23		22		17		12		8		3
18	22	17	17	16	12	15	7	14	3	13
22		21		16		11		7		3
19	21	20	16	21	11	22	7	23	2	24
20		20		15		11		6		2
30	20	29	15	28	10	27	6	26	1	25
19		19		15		10		5		1
31	19	32	14	33	10	34	5	35	1	36

6-151

- Notes in Book "A" (2720)
 - " " " "B"
 - Unsurveyed
- Affidavits on Pages 25-102*

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

Resurvey commenced July 12th, 1913 and executed by Thomas B. Matthews, U. S. Surveyor, with Young & Sons Light Mount-
ain Transit No. 3480, previously described. I examine the
adjustments of the transit and find them to be correct and
know from recent tests of the solar apparatus, by comparing
its indications resulting from solar observations made dur-
ing a.m. and p.m. hours, with a mer. established by obser-
vation on Polaris, at elongation, that the instrument is
in satisfactory adjustment.

At 8 h. 0 m., a.m., l.m.t., I set off 22° 01½' N. on decl.
arc, 31° 59' on lat. arc and determine a mer. with the sol-
ar at the cor. of secs. 1, 2, 35 & 36 on S. bdy. of Tp.,
previously re-established by me, as described in Book "A."

The magnetic bearing of true mer. thus established is N. 12°
55' W., the angle thus determined gives the magnetic decl.
12° 55' E.

Thence I run
N. 0° 01' W. bet. secs. 35 & 36

Over level prairie land through scattering mesquite brush
4 to 5 ft. high

.02 Intersect S.W. cor. of wire fence thence along W. side of
fence along wagon road

40.00 Set an iron post 3-ft. long, 1 in. in dia. 26 ins. in ground
for reestab. ¼ sec. cor., with a brass cap marked ¼ S 35 in
W., S 36 in E. & 1913 in S. half.

Dig pits 13 x 13 x 12 ins. N. & S. of post
3 ft. dist. & raise
mound of earth 3½ ft. base 1½ ft. high W. of cor.

79.50 N.W. cor. of wire fence bears E. 50 lks. dist.

80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground
for reestab. cor. of secs. 25, 26, 35 & 36, with a brass cap
marked T 16 S R 25 E in N. & 1913 in S. half, S 26 in N.W.,
S 25 in N.E., S 36 in S.E. & S 35 in S.W. quadrant.

Dig pits 13 x 13 x 12 ins. in each sec. 5½ ft. dist. &
raise mound of earth 4 ft. base 2 ft. high W. of cor.

Land level
Soil light sandy loam, 12 ins. deep on clay sub-soil
Good grass
Scattering mesquite brush 4 to 5 ft. high
No timber.

Thence I run
N. 39° 55' E. on random line bet. secs. 25 & 36

40.00 Set temp. ¼ sec. cor.

30.12 Intersect E. bdy. of Tp. 7 lks. S. of cor. of secs. 25, 30,
31 & 36, previously re-established by me, as described in Book "A."

Thence I run
S. 89° 52' W. on true line bet. secs. 25 & 36

Over level prairie land along dia wagon road through lane
mesquite brush 4 to 5-ft. high

38.00 A. A. Adling's house bears N. 3 chs. dist.

40.06 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
for reestab. ¼ sec. cor., with a brass cap marked ¼ S 25 in
N. & S 36 1913 in S. half.

Dig pits 13 x 13 x 12 ins. E. & W. of post
3 ft. dist. & raise
mound of earth 3½ ft. base 1½ ft. high N. of cor.

From this cor. cor. of wire fence bears N. 50 lks. dist.

79.30 Wagon road bears N. & S

80.12 The cor. of secs. 25, 26, 35 & 36, hereinbefore described.

Land level
Soil light sandy loam, medium texture, 12 ins. deep on
clay sub-soil
Scattering grass, mesquite brush 4 to 5 ft. high
No timber.

Thence I run
N. 0° 01' W. bet. secs. 25 & 26

Over level prairie land along wagon road through lane.
Wagon road bears E. & W.

.15 H. A. Blanchard's house bears E. 7 chs. dist.

37.50 N.E. cor. of wire fence bears W. 50 lks. dist.

39.50

RESURVEY OF SUBDIVISION ^{LINES} OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

40.00	<p>also cor. of wire fence bears E. 50 lks. dist. Leave lane thence parallel to & W. of wire fence along wagon road Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{2}$ sec. cor., with a brass cap marked $\frac{1}{2}$ S 26 in W., S 25 in E. & 1913 in S. half. ^{of post} Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.</p>
41.00	<p>Fork in wagon road turns N.W.</p>
43.00	<p>Wm. S. Bemis' house bears E. 5 chs. dist.</p>
79.85	<p>Dim wagon road bears E. & W.</p>
80.00	<p>Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 23, 24, 25, & 26, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 23 in N.W., S 24 in N.E., S 25 in S.E. & S 26 in S.W. quadrant. Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. Land level Soil light sandy loam, 12 ins. deep, medium texture, on clay sub-soil Scattering short grass, mesquite brush 4 to 5 ft. high No timber</p>

40.00	<p>Thence I run N. 89° 52' E. on random line bet. secs. 24 & 25 Set temp. $\frac{1}{2}$ sec. cor.</p>
80.18	<p>Intersect E. bdy. of Tp. 4 lks. S. of cor. of secs. 19, 24, 25 & 30, previously re-estab. by me, as described in Book "A"</p>
	<p>Thence I run</p>
	<p>S. 39° 50' W. on true line bet. secs. 24 & 25</p>
	<p>Over level prairie land through scattering mesquite brush 3 to 5 ft. high, parallel to & N. of wire fence.</p>
35.50	<p>J. W. Dunkin's house bears S. 6 chs. dist. thence along dim wagon road</p>
40.09	<p>Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reesta. $\frac{1}{2}$ sec. cor., with a brass cap marked $\frac{1}{2}$ S-24 in N. & S 25 1913 in S. half.</p>
	<p>Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.</p>
	<p>Fork in wagon-road bears-N.E.-</p>
41.50	<p>S.E. cor. of wire fence bears N. 50 lks. dist. also cor. of wire fence bears S. 50 lks. dist., thence through lane</p>
80.18	<p>The cor. of secs. 23, 24, 25 & 26, hereinbefore described.</p>
	<p>Land level</p>
	<p>Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil</p>
	<p>Scattering short grass, mesquite brush 4 to 5 ft. high</p>
	<p>No timber.</p>

	<p>Thence I run</p>
	<p>N. 9° 01' W. bet. secs. 23 & 24</p>
	<p>Over level prairie land along wagon road parallel to & 50 lks. W. of wire fence through mesquite brush 4 to 5 ft. high</p>
5.00	<p>G. A. Cundiff's house bears W. 5 chs. dist.</p>
12.00	<p>Wagon road bears N.E. & S.W.</p>
29.00	<p>S. G. Cundiff's house bears E. 5 chs. dist.</p>
31.00	<p>Cabin bears West 3 chs. dist.</p>
40.00	<p>Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{2}$ sec. cor., with a brass cap marked $\frac{1}{2}$ S 23 in W., S 24 in E. & 1913 in S. half. ^{of post}</p>
	<p>Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.</p>
	<p>From this cor. N.W. cor. of wire fence bears E. 1 ch. dist. leave wagon road bears N.E.</p>
50.00	<p>J. F. Hayden's house bears W. 15 chs. dist.</p>
80.00	<p>Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 13, 14, 23 & 24, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 14 in N.W., S 13 in N.E., S 24 in S.E. & S 23 in S.W. quadrant.</p>

Resurvey of Subdivision lines of Township 16 South, Range 25 East.

Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
 Scattering short grass, mesquite brush 4 to 5 ft. high
 No timber.
 At this cor. I set off 21° 59 1/2' N. on decl. arc, and at 12 h. 5 m. 21 s., p.m.; 1 a.m.t., observe the sun on the mer. and obtain a reading of 32° 02' on lat. arc.

 Thence I run
 40.00 N. 39° 50' E. on random line bet. secs: 13 & 24
 80.24 Set temp. 1/4 sec. cor.
 Intersect E. bdy. of Tp. 7 lks. N. of cor. of secs. 13, 18, 19 & 24, previously re-estab. by me, as described Book "A"
 Thence I run
 35.25 S. 39° 53' W. on true line bet. secs. 13 & 24
 40.12 Over level land through scattering mesquite brush 3 to 6 ft. high
 Wagon road bears N. & S. 15° W.
 40.12 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 13 in N. & S 24 19 13 in S. half.
 Dig pits 13 x 13 x 12 ins. E. & W. 5 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 77.00 Wagon road bears N. & S.
 30.24 The cor. of secs. 13, 14, 23 & 24, hereinbefore described.
 Land level
 Soil light sandy loam, medium texture 12 ins. deep on clay sub-soil
 Good grass, scattering mesquite brush 3 to 6 ft. high
 No timber.

 Thence I run
 19.00 N. 0° 01' W. bet. sec. 13 & 14
 Over level land through mesquite brush 3 to 6 ft. high
 40.00 J. E. Ford's house bears W. 17 chs. dist.
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 14 in W., S 13 in E. & 19 13 in S. half.
 Dig pits 13 x 13 x 12 ins. N. & S. 5 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 60.00 Bend in wagon road bears N. & S. 2° E., thence along wagon road
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 11, 12, 13 & 14, with a brass cap marked T 16 S-R 25 E in N. & 19 13 in S. half, S 11 in N.W., S 12 in N.E., S 13 in S.E., & S 14 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil loose red sandy loam, medium texture, 12 ins. deep on clay sub-soil
 Good grass, mesquite brush 3 to 6 ft. high
 No timber.

 Thence I run
 40.00 N. 39° 53' E. on random line bet. secs: 12 & 13
 30.26 Set temp. 1/4 sec. cor.
 Intersect E. bdy. of Tp. 2 lks. N. of cor. of secs. 7, 12, 13 & 18, previously re-estab. by me, as described in Book "A"
 Thence I run
 25.00 S. 39° 54' W. on true line bet. secs 12 & 13
 Over level land through mesquite brush 3 to 7 ft. high
 Wire fence bears N. & S. S.E. cor. of wire fence bears S. 1 ch. dist.

Subdivision lines of
RESURVEY OF TOWNSHIP 16 SOUTH, RANGE 25 EAST, SUBDIVISIONS

- 27.00 Jno. Deran's house bears N. 6 chs. dist.
28.00 Wagon road bears N. & S.
39.51 Wire fence bears N. & S., S.W. cor. of wire fence bears S. 1 ch. dist.
40.13 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 12 in N. & S 13 1913 in S. half.
Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
80.26 The cor. of secs. 11, 12, 13 & 14, hereinbefore described.
Land level
Soil light sandy loam, medium texture 12 ins. deep on clay sub-soil
Good grass, mesquite brush 3 to 7 ft. high
No timber.
July 12th, 1913.
-
- July 14, 1913, At 10h. 0m., a.m., l.m.t., I set off $21^{\circ} 43'$ N. on decl. arc $32^{\circ} 02\frac{1}{2}'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 11, 12, 13 & 14, hereinbefore described.
Thence I run
N. $0^{\circ} 01'$ W. bet. secs. 11 & 12
Over level land along wagon road
.50 S.E. cor. of wire fence bears W. 50 lks. dist., fork in wagon road bears N.E., thence parallel to & E. of wire fence
40.00 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 11 in W., S 12 in E. & 1913 in S. half. ^{of post}
Dig pits 13 x 13 x 12 ins. N. & S. ^{of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
60.00 H. H. McDuffee's house bears E. 13 chs. dist.
61.00 Wire fence bears E. & W., S.E. cor. of wire fence bears W. 75 lks. dist. enter cultivated field
79.50 Wire fence bears E. & W. N.W. cor. of wire fence bears W. 75 lks. dist. leave cultivated land
30.00 Set an iron post 3 ft. long, 2 ins. in dia. **24 ins. in ground** for reestab. cor. of secs. 1, 2, 11 & 12, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 2 in N.W., S 1 in N.E., S 12 in S.E. & S 11 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level. From this cor. ~~EG Maddox's house~~ bng. S. 45° W.
Soil light sandy loam, medium texture, 12 to 13 ins. deep on clay sub-soil
Good grass, scattering mesquite brush 3 to 6 ft. high
No timber.
-
- Thence I run
N. $89^{\circ} 54'$ E. on random line bet. secs. 1 & 12
40.00 Set temp. $\frac{1}{4}$ sec. cor.
80.32 Intersect E. bdy. of Tp. 5 lks. N. of cor. of secs. 1, 6, 7 & 12, previously re-estab. by me, as described in Book "A."
Thence I run
S. $89^{\circ} 56'$ W. on true line bet. secs. 1 & 12
Over level land through mesquite brush 3 to 6 ft. high
19.00 Wagon road bears N.E. & S.W.
35.00 Mary E. Hunt's house bears S. 7 chs. dist.
40.16 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 1 in N. & S 12 1913 in S. half. ^{of post}
Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
62.00 N.E. cor. of wire fence bears S. 50 lks. dist.
30.32 The cor. of secs. 1, 2, 11 & 12, hereinbefore described.
Land level
Soil light sandy loam, medium texture, 12 to 13 ins. deep on clay sub-soil
Good grass, scattering mesquite brush 3 to 6 ft. high
No timber

SUBDIVISION LINES OF RESURVEY OF TOWNSHIP 16 SOUTH, RANGE 25 EAST, SUBDIVISIONS

Thence I run
 N. 0° 01' W. bet. secs. 1 & 2
 Over level land through mesquite brush 3 to 6 ft. high parallel to & 150 lks. E. of wire fence.
 39.50 Wire fence bears E. & W., S.W. cor. of wire fence bears W. 75 lks.
 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 2 in W., S 1 in E. & 1913 in S. half.
 Dig pits 18 x 18 x 12 ins. N. & S $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 50.00 Cor. of wire fence bears W. 175 lks. dist.
 72.00 Bailey's house bears W. 6 chs. dist.
 79.25 Wire fence bears E. & W., N.W. cor. of wire fence bears W. 90 lks. dist.
 80.03 Intersect Third Standard Parallel South 27.34 chs. S. 39° 51' W. of Standard cor. of secs. 35 & 36, previously reestablished by me, as described Book "B."
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. Closing cor. of secs. 1 & 2, with a brass cap marked CC S. of center, T 16 S R 25 E R 35 S 36 in N. & 1913 in S. half, S 2 in S.E. & S 2 in S.W. quadrant.
 Dig pits 23 x 13 x 12 ins. crosswise on each line E&W. 3 ft. & S of post 7 ft. dist. & raise mound of earth 4 ft. base 2 ft. high S. of cor.
 Land level.
 Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
 Good grass, mesquite brush 3 to 6 ft. high
 No timber.
 Note: Sun is obscured by clouds at noon on this day, rendering an observation for latitude impossible.
 July 14th, 1913.

July 15, 1913: At 8h. 0 m., a.m., 1.m.t., I set off 21° 35' N. on decl. arc, 31° 59' on lat. arc and determine a mer. with the solar at the cor. of secs. 2, 3, 34 & 35, on S. bdy. of Tp., previously reestab. by me, as described in Book "A."
 Thence I run
 N. 0° 01' W. bet. secs. 34 & 35
 Over level land through mesquite brush 3 to 6 ft. high
 .50 S.E. cor. of wire fence bears W. 50 lks. dist. thence parallel to & 50 lks. E. of wire fence along wagon road
 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 34 in W., S 35 in E. & 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. N. & S $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 62.25 A. C. Blank's house bears W. 3 chs. dist.
 79.50 N.E. cor. of wire fence bears W. 50 lks. dist.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 26, 27, 34 & 35, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 27 in N.W., S 26 in N.E., S 35 in S.E. & S 34 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
 Good grass, mesquite brush 3 to 5 ft. high
 No timber.

Thence I run
 N. 39° 56' E. on random line bet. secs. 26 & 35
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.90 Fall 7 lks. N. of cor. of secs. 25, 26, 35 & 36, hereinbefore described.
 Thence I run
 S. 39° 59' W. on true line bet. secs. 26 & 35
 Over level land through mesquite brush 3 to 5 ft. high along wagon road

OF LINES
RESURVEY SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

- .50 Cor. of wire fence bears N. 25 lks. dist., thence parallel to & S. of wire fence
- 9.00 J. M. Rice's house bears N. 3 chs. dist.
- 39.95 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 26 in N. & S 35 1913 in S. half.
- Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 79.40 S.W. cor. of wire fence bears N. 30 lks. dist.
- 79.90 The cor. of secs. 26, 27, 34 & 35, hereinbefore described.
- Land level
Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
Good grass, scattering mesquite brush 3 to 6 ft. high
No timber.
-
- Thence I run
N. $0^{\circ} 01'$ W. bet. secs. 26 & 27
Over level land through ~~land~~ mesquite brush 3 to 5 ft. high
- 40.00 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor. with a brass cap marked $\frac{1}{4}$ S 27 in W., S 26 in E. & 1913 in S. half.
- Dig pits 13 x 13 x 12 ins. N. & S. ^{of post} $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
- From this cor. cor. of wire fences bear **E&W 50 lks. dist each**
- 77.00 W. D.M. Steven's house bears E. 3 chs. dist.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia. **24 ins. in ground** for reestab. cor. of secs. 22, 23, 26 & 27, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 22 in N.W., S 23 in N.E., S 26 in S.E. & S 27 in S.W. quadrant.
- Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
- Land level
Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
Good grass, mesquite brush 3 to 5 ft. high
No timber.
-
- Thence I run
N. $39^{\circ} 59'$ E. on random line bet. secs. 23 & 26
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 30.04 Fall 2 lks S. of cor. of secs. 23, 24, 25 & 26, hereinbefore described.
- Thence I run
S. $39^{\circ} 58'$ W. on true line bet. secs. 23 & 26
Over level land along wagon road through mesquite brush 3 to 6 ft. high
- 20.00 Fork of wagon road bears N.E.
- 38.00 Fork in wagon road bears S.E.
- 39.50 N.E. cor. of wire fence bears S. 50 lks. dist.
- 39.75 S.E. cor. of wire fence bears N. 50 lks. dist., thence through lane.
- 40.02 Set an iron post 3 ft. long, 1 in. in dia. **26 ins. in ground**, for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 23 in N. & S 26 1913 in S. half.
- Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 80.04 The cor. of secs. 22, 23, 26 & 27, hereinbefore described.
- Land level
Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
Good grass
No timber.
-

of 3 LINES OF RESURVEY SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

Thence I run
 N. 0° 01' W. bet. secs. 22 & 23
 Over level land through lane mesquite brush 3 to 5 ft. high
 From this cor, W. T. Hays's house bears N. 71½° E.
 33.00 J. C. Larkin's house bears W. 5 chs. dist.
 39.00 W. T. Hays's house bears S. 46° E.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. ¼ sec. cor., with a brass cap marked S 22 in
 W., S 23 in E. & 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. N. & S. of post 3 ft. dist. & raise
 mound of earth 3½ ft. base 1½ ft. high W. of cor
 From this cor. of wire fence bears E. 50 lks. dist.
 79.50 Cors. of wire fences bears E. & W. 50 lks. dist. each
 leave lane
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground
 for reestab. cor. of secs. 14, 15, 22 & 23, with a brass cap
 marked T 16 S R 25 E in N. & 1913 in S. half, S 15 in N.W.,
 S 14 in N.E., S 23 in S.E. & S 22 in S.W. quadrant.
 Dig pits 18 x 13 x 12 ins. in each sec. 5½ ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on
 clay sub-soil
 Good grass, mesquite brush 3 to 5 ft. high
 No timber.

 Thence I run
 N. 39° 53' E. on random line bet. secs. 14 & 23
 40.00 Set temp. ¼ sec. cor.
 30.02 Fall 12 lks. N. of cor. of secs. 13, 14, 23 & 24, herein-
 before described.
 Thence I run
 N. 39° 57' W. on true line bet. secs. 14 & 23
 Over level land through mesquite brush 3 to 5 ft. high
 39.75 N.E. cor. of wire fence bears E. 50 lks. dist., thence par-
 allel to & N. of wire fence.
 40.01 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. ¼ sec. cor., with a brass cap marked S 14 in
 N. & S 23 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. E. & W. of post 3 ft. dist. & raise
 mound of earth 3½ ft. base 1½ ft. high N. of cor.
 30.02 The cor. of secs. 14, 15, 22 & 23, hereinbefore described.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on
 clay sub-soil
 Good grass, mesquite brushy 3 to 5 ft. high
 No timber.

 Thence I run
 N. 0° 01' W. bet. secs. 14 & 15
 Over level land through mesquite brush 3 to 4 ft. high
 39.90 Wire fence bears E. & W. S.W. cor. of wire fence bears W.
 2 chs. dist., thence parallel to & 2 chs. E. of wire fence.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. ¼ sec. cor., with a brass cap marked S 15 in
 W., S 14 in E. & 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. N. & S. of post 3 ft. dist. & raise
 mound of earth 3½ ft. base 1½ ft. high W. of cor.
 79.50 Wire fence bears E. & W.
 79.75 Wagon road bears E. & W.
 30.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground
 for reestab. cor. of secs. 10, 11, 14 & 15, with a brass cap
 marked T 16 S R 25 E in N. & 1913 in S. half, S 10 in N.W.,
 S 11 in N.E., S 14 in S.E. & S 15 in S.W. quadrant.
 Dig pits 18 x 13 x 12 ins. in each sec. 5½ ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on
 clay sub-soil
 Good grass, mesquite brush 3 to 4 ft. high. No timber.

RESURVEY OF SUBDIVISION LINES OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

Note: at the cor. of secs. 22, 23, 26 & 27 I set off 21° 33' N. on decl. arc and at 12 h. 5 m. 42 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 01' on lat. arc.

July 15th, 1913.

July 17, 1913: At 7h. 120m., a.m., l.m.t., I set off 21° 15 1/2' N. on decl. arc, 32° 02 1/2' on lat. arc and determine a mer. with the solar at the cor. of secs. 10, 11, 14 & 15, hereinbefore described. Thence I run S. 39° 57' E. on random line bet. secs. 11 & 14 40.00 Set temp. 1/2 sec. cor. 30.00 Fall 2 lks. N. of cor. of secs. 11, 12, 13 & 14, hereinbefore described Thence I run N. 39° 56' W. on true line bet. secs. 11 & 14 Over level land along wagon road through scattering mesquite brush 2 to 3 ft. high ,20 Wagon road bears N. & S. .50 S.E. cor. of wire fence bears N. 50 lks. dist. thence parallel to & S. of wire fence 38.00 T. Adling's house bears N. 3 chs. dist. 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26ins. in ground for reestab. 1/2 sec. cor., with a brass cap marked S 11 in N. & S 14 1913 in S. half. Dig pits 13 x 13 x 12 ins. E. & W. of post 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor. 41.25 N.E. cor. of wire fence bears S. 50 lks. dist. thence through lane 46.00 Mamie McCullar's house bears N. 14 chs. dist. 79.00 S.W. cor. of wire fence bears N. 50 lks. dist. 30.00 The cor. of secs. 10, 11, 14 & 15, hereinbefore described Land level Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil Good grass scattering mesquite brush 2 to 3 ft. high. No timber.

Thence I run N. 0° 01' W. bet. secs. 10 & 11 Over level land through scattering mesquite brush 4 to 6 ft. high 1.00 Frame school house bears W. 50 lks. dist. 4.00 Wire fence bears E. & W., S.E. cor. of wire fence bears E. 1 lk. dist. thence along W. side of fence. 40.00 Set an iron post 3-ft. long, 1 in. in dia., 26ins. in ground for reestab. 1/2 sec. cor., with a brass cap marked S 10 in W., S 11 in E. & 1913 in S. half. of post Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor. 43.00 S.E. cor. of wire fence bears W. 30 lks. dist. 51.00 N.E. cor. of wire fence bears W. 30 lks. dist. 51.75 J. A. Fogarty's house bears W. 7 chs. dist. 60.05 Wire fence bears E. & W., N.E. cor. of wire fence bears E 10 lks. dist. 61.00 Wagon road bears N. 10° W., S 10° E. enter scattering yuccas 4 to 7 ft. high. 79.50 Cor of wire fence bears E. 1 ch. dist. 79.75 Wagon road bears E. & W. 30.00 Set an iron post 3 ft. long, 2 ins. in dia. 24ins. in ground for reestab. cor. of secs. 2, 3, 10 & 11, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 3 in N.W., S 2 in N.E., S 11 in S.E. & S 10 in S.W. quadrant. Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor Land level Soil sandy, loam, medium to coarse texture, 12 to 13 ins. deep on clay sub-soil Good grass, mesquite brush & yuccas 3 to 7 ft. high No timber

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

Thence I run
 ✓ S. 39° 56' E, on random line bet. secs. 2 & 11
 40.00 Set temp. 1/4 sec. cor.
 79.90 Fall 21 lks. S. of cor. of secs. 1, 2, 11 & 12, herein-
 before described.
 Thence I run
 S. 89° 55' W. on true line bet. secs. 2 & 11
 Over level land through scattering mesquite brush 3 to 6
 ft. high
 .75 N.W. cor. of wire fence bears S. 50 lks. dist.
 1.00 Wagon road bears N. & S.
 1.75 Cors. of wire fences bear N. & S. 50 lks. dist. each,
 thence through lane along wagon road
 39.95 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 2 in
 N. & S 11 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 40.65 Cors. of wire fences bears N. & S. 50 lks. dist. each
 42.00 Cabin belonging to W.M. McCullar bears S. 3 chs. dist.
 47.00 M. E. McCullar's house bears N. 3 chs. dist.
 79.00 N.W. cor. of wire fence bears S. 50 lks. dist.
 79.90 The cor. of secs. 2, 3, 10 & 11, hereinbefore described.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on
 clay sub-soil
 Good grass, scattering mesquite brush 3 to 6 ft. high
 No timber.
 Note: E. G. Maddox's house bears S. 15' W. 30' dist.
 from cor. of sec. 1, 2, 11 & 12

Thence I run
 ✓ N. 9° 01' W. bet. secs. 2 & 3
 Over level land through mesquite brush 3 to 7 ft. high
 .50 Wire fence bears E. & W.; S.W. cor. of wire fence bears
 W. 125 lks.
 20.00 S.E. cor. of wire fence bears W. 2 chs. dist. thence par-
 allel to and 150 lks. E. of lane
 38.00 C. Chamber's house bears W. 7 chs. dist.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 3 in W.
 S 2 in E. & 1913 in S. half.
 Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 40.03 Wire fence bears E. & W. N.W. cor. of wire fence bears W.
 1 ch. dist. thence parallel to 2 chs. E. of wire fence.
 41.00 Wagon road brs. NE. & SW.
 55.00 Cor. of wire fence brs. W. 2 chs. dist.
 79.77 Wagon road brs. E. and W.
 79.97 Intersect Third Standard Parallel South 27.36 chs. S.
 89° 56' W. of Standard cor. of secs. 34 & 35, previously
 reestab. by me, as described in Book "B."
 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground
 for reestab. Closing cor. of secs. 2 & 3, with a brass cap
 marked CC S. of center, T 16 S R 25 E S 34 S 35 in N. &
 1913 in S. half, S 2 in S.E. & S 3 in S.W. quadrant.
 Dig pits 24 x 13 x 12 ins. crosswise on each line E&W 3ft
 and S. of post. 7 dist. & raise mound of earth 4 ft. base 2
 ft. high S. of cor.
 Note: Wagon road bears S. 15' W. 30' dist. from cor. of sec. 1, 2, 11 & 12
 S. of cor. of sec. 1, 2, 11 & 12
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on
 clay sub-soil
 Good grass, mesquite brush 3 to 7 ft. high.
 No timber.

July 17th, 1913.

July 16, 1913. At 8 h. 20 m., a.m., 1.m.t., I set off 21° 25' N.
 on decl. arc, 31° 59' on lat. arc and determine a mer. with
 the solar at the cor. of secs. 3, 4, 33 & 34, on S. bdy. of
 Tp., previously reestab. by me, as described in Book "A."

RESURVEY OF SUBDIVISION ^{LINES} OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

	Thence I run
	N. 0° 02' W. bet. secs. 33 & 34
.50	Over level prairie land
	Wagon road bears N.W. & S.E., S.W. cor. of wire fence bears
7.00	E. 50 lks. dist, thence parallel to & W. of wire fence.
40.00	E. S. Blank's house bears E. 7 chs. dist.
	Set an iron post 3 ft. long, 1 in. in dia., 26ins. in ground
	for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 33 in
	W., S 34 in E. & 1913 in S. half.
	Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise
	mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
	From this cor. the old $\frac{1}{4}$ sec. cor., which is a basalt stone
	3 x 10 x 6 ins. above ground, firmly set, marks nearly ob-
	literated, bears S. 63° W. 47 lks. dist. I destroy all
	trace of this old cor.
60.00	Also N.W. cor. of wire fence bears E. 50 lks. dist.
30.00	Dim wagon road bears N.E. & S.W.
	Set an iron post 3 ft. long, 2 ins. in dia., 24ins. in ground
	for reestab. cor. of secs, 27, 28, 33 & 34, with a brass cap
	marked T 16 S R 25 E in N. & 1913 in S. half, S 28 in N.W.,
	S 27 in N.E., S 34 in S.E. & S 33 in S.W. quadrant.
	Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
	raise mound of earth 4 ft. base 2 ft. high W. of cor.
	Land level
	Soil alkali 12 ins. deep on hardpan sub-soil
	Salt grass
	No timber.

	Thence I run
40.00	N. 39° 53' E. on random line bet. secs. 27 & 34
79.98	Set temp. $\frac{1}{4}$ sec. cor.
	Intersect cor. of secs. 26, 27, 34 & 35, hereinbefore de-
	scribed.
	Thence I run
	S. 39° 53' W. on true line bet. secs. 27 & 34
.50	Over level land through mesquite brush 3 to 4 ft. high
	Cor. of wire fences bear N. & S. 50 lks. dist. each, thence
39.99	through lane along wagon road
	Set an iron post 3 ft. long, 1 in. in dia., 26ins. in ground
	for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 27 in
	N. & S 34 1913 in S. half.
	Dig pits 13 x 13 x 12 ins. E. & W. of post, 3 ft. dist., & raise a
	mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
	Cors. of wire fences bear N. & S. 50 lks. dist. each.
	Leave lane thence parallel to & S. of wire fence
	Fork in wagon road bears S.W., leave mesquite bears N. & S.
79.50	S.W. cor. of wire fence bears N. 50 lks. dist.
79.98	Cor. of secs. 27, 28, 33 & 34, hereinbefore described.
	Land level
	Soil light sandy loam & alkali, 12 ins. deep on clay
	sub-soil
	Short salt grass, scattering mesquite brush 3 to 4 ft. high
	No timber.

	Thence I run
	N. 0° 02' W. bet. secs. 27 & 28
.20	Over level prairie land parallel to & W. of wire fence
40.00	along wagon road
	Dim wagon road bears E. & W.
	Set an iron post 3 ft. long, 1 in. in dia., 26ins. in ground
	for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 23 in
	W., S 27 in E. & 1913 in S. half.
	Dig pits 13 x 13 x 12 ins. in N. & S. $\frac{1}{3}$ ft. dist. & raise
	mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
	From this cor. cor. of wire fence bears E, 50 lks.
78.00	Enter scattering mesquite brush 3 to 4 ft. high bears N.W.
	& S.E.
80.00	Set an iron post 3 ft. long, 2 ins. in dia., 24ins. in ground
	for reestab. cor. of secs. 21, 22, 27 & 28, with a brass cap
	marked T 16 S R 25 E in N. & 1913 in S. half., S 21 in N.W.,
	S 22 in N.E., S 27 in S.E. & S 23 in S.W. quadrant.

LINES
RESURVEY OF SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light sandy loam, medium texture, 12 to 13 ins. deep on clay sub-soil
 Good grass, scattering mesquite brush 3 to 4 ft. high on N. end of line.
 No timber.

Thence I run
 N. 89° 53' E. on random line bet. secs. 22 & 27
 40.00 Set temp. 1/4 sec. cor.
 80.00 Fall 2 lks. N. of cor. of secs. 22, 23, 26 & 27, hereinbefore described.
 Thence I run
 S. 39° 54' W. on true line bet. secs. 22 & 27
 40.00 Over level land along wagon road through lane mesquite brush 3 to 5 ft. high
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. sec. cor., with a brass cap marked 1/4 S 22 in N. & S 27 1913 in S. half. of post
 Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.
 From this cor. cor.s of wire fences bear N. & S. 50 lks. dist. each.
 79.50 Cor.s of wire fences bear N. & S. 50 lks. dist. each, leave lane
 80.00 The cor. of secs. 21, 22, 27 & 28, hereinbefore described.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
 Good grass, mesquite brush 3 to 5 ft. high
 No timber.

Thence I run
 N. 0° 02' W. bet. secs. 21 & 22
 Over level land along wagon road through mesquite parallel to & 50 lks. W. of wire fence
 110 Dia wagon road bears E. & W.
 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 21 in W., S 22 in E. & 1913 in S. half. of post
 Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 From this cor. D. C. Masters' house bears S. 60° E. 10 chs. dist.
 40.05 Wire fence bears E. & W., S.E. cor. of wire fence bears E. 10 lks. dist. also cor. of wire fence bears E. 160 lks. dist.
 60.00 Wire fence bears N. 1/2° W., S 1/2° E thence through lane
 79.90 Cor. of wire fence bears W. 5 lks. & E. 45 lks. dist.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 15, 16, 21 & 22, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 16 in N.W., S 15 in N.E., S 22 in S.E. & S 21 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
 Good grass, mesquite brush 3 to 5 ft. high
 No timber.

Thence I run
 N. 39° 54' E. on random line bet. secs. 15 & 22
 40.00 Set temp. 1/4 sec. cor.

COLINES

RESURVEY OF SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

30.00	Fall 2 lks. S. of cor. of sec. 14, 15 22 & 23, hereinbefore described. Thence I run S. 39° 53' W. on true line bet. secs. 15 & 22 Along wagon road over level land through mesquite brush 3 to 6 ft. high
2.00	S.E. cor. of wire fence bears N. 50 lks. dist., thence through lane
30.00	Cor. of wire fence bears N. 50 lks. dist.
32.00	T. B. Larkin's house bears S. 5 chs. dist.
36.00	W. Reeder's house bears N. 3 chs. dist.
40.00	Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. sec. cor. , with a brass cap marked S 15 in N. & S 22 1913 in S. half. Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} 3 ft. dist. & raise mound of earth 3½ ft. base 1½ ft. high N. of cor.
41.50	W. L. Larkins' house bears S. 5 chs. dist.
43.00	Mabel E. Reeder's house bears N. 5 chs. dist.
45.00	Cor. of wire fence bears N. 50 lks. dist.
30.00	The cor. of secs. 15, 16, 21 & 22, hereinbefore described. Land level Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil Good grass, mesquite brush 3 to 6 ft. high No timber.

	Thence I run N. 0° 02' W. bet. secs. 15 & 16 Over level land along wagon road through lane, mesquite brush 3 to 6 ft. high
40.00	Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. sec. cor. , with a brass cap marked S 16 in W., S 15 in E. & 1913 in S. half. Dig pits 13 x 13 x 12 ins. N. & S ^{of post} 3 ft. dist. & raise mound of earth 3½ ft. base 1½ ft. high W. of cor. From this cor. Bob Warren's house bears W. 7 chs. dist.
42.50	Also cor. of wire fence bears E. 70 lks. dist. Wire fence bears E. & W. cor. of wire fence bears W. 10 lks. & E. 2 chs. dist., leave lane
79.75	Wire fence bears E. & W.
30.00	Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for cor. of secs. 9, 10, 15 & 16, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 9 in N.W., S 10 in N.E., S 15 in S.E. & S 16 in S.W. quadrant. Dig pits 13 x 13 x 12 ins. in each sec. 5½ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. Land level Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil Good grass, mesquite brush 3 to 6 ft. high No timber. Note: at the cor. of secs. 21, 22, 27 & 23, I set off 21° 23' N. on decl. arc and at 12 h. 5 m. 43 s., p.m., l.a.t. observe the sun on the mer. and obtain a reading of 32° 01' on lat. arc.
	July 16th, 1913.

	July 17, 1913: From cor. of secs. 9, 10, 15 and 16, above described, I run, N. 39° 53' E. on random line bet. secs. 10 & 15
40.00	Set temp. sec. cor.
80.02	Fall 2 lks. N. of cor. of secs. 10, 11, 14 & 15, hereinbefore described. Thence I run S. 39° 54' W. on true line bet. secs. 10 & 15 Over level land through scattering mesquite brush 3 to 6 ft. high along wagon road
2.00	N.W. cor. of wire fence bears S. 50 lks. dist. fork in wagon road turns South

OF LINES RESURVEY SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

3.00 N.E. cor. of wire fence bears S. 50 lks. dist.
4.00 S.E. cor. of wire fence bears N. 50 lks. dist., thence through lane
30.00 Cor. of wire fence bears S. 50 lks. dist.
39.50 Jas. Hutheson's house bears S. 7 chs. dist.
40.01 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 10 in N. & S 15 1913 in S. half. of post
Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
45.00 Cor. of wire fence bears S. 50 lks. dist.
70.00 Cor. of wire fence bears N. 75 lks. dist.
76.00 J. A. Ross' house bears N. 2 chs. dist.
77.00 N.W. cor. of wire fence bears S. 25 lks. dist.
78.00 Wagon road bears N.W. & S.E., N.E. cor. of wire fence bears S. 25 lks. dist.
79.00 S.W. cor. of wire fence bears N. 75 lks. dist.
80.02 The cor. of secs. 9, 10, 15 & 16, hereinbefore described.
Land level
Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
Good grass, mesquite brush 3 to 5 ft. high
No timber.

Thence I run
N. 0° 02' W. bet. secs. 9 & 10
Over level sandy land through mesquite brush 3 to 6 ft. high
.75 Wire fence bears E. & W., S.E. cor. of wire fence bears E. 3 lks. dist., thence parallel to & W. of lane
25.00 Telephone line bears N. 10° E., S. 10° W.
40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 9 in W., S 10 in E. & 1913 in S. half. of post
Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
40.10 Wire fence bears E. & W.
79.70 Wire fence bears E. & W. N.E. cor. of wire fence bears E. 10 lks. dist.
79.80 Wagon road bears E. & W.
80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 3, 4, 9 & 10, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 4 in N.W., S 3 in N.E., S 10 in S.E. & S 9 in SW. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level
Soil sandy loam, medium to coarse texture, 12 to 24 ins. deep on clay sub-soil
Good grass, mesquite brush 3 to 6 ft. high, yuccas 4 to 7 ft. high
No timber.

Thence I run
N. 39° 54' E. on random line bet. secs. 3 & 10
40.00 Set temp. $\frac{1}{4}$ sec. cor.
30.14 Intersect cor. of secs. 2, 3, 10 & 11, hereinbefore described.
Thence I run
S. 39° 54' W. on true line bet. secs. 3 & 10
Over level sandy land through mesquite brush & yuccas 4 to 7 ft. high
1.50 Wagon road bears N. & S.
28.00 Wagon road bears N.E. & S.W.
39.50 N.E. cor. of wire fence bears S. 50 lks. dist.
40.07 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 3 in N. & S 10 1913 in S. half.

OF LINES
RESURVEY SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

- Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 73.00 Telephone line bears N. 10° E., S. 10° W.
- 79.00 N.W. cor. of wire fence bears S. 30 lks. dist.
- 79.50 Wagon road bears N. & S.
- 80.14 Intersect cor. of secs. 3, 4, 9 & 10, hereinbefore described,
Land level
Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
Good grass, mesquite brush & yuccas 4 to 7 ft. high.
No timber.
-
- Thence I run
N. 0° 02' W. bet. secs. 3 & 4
Over level land through mesquite brush & yuccas 4 to 7 ft. high
- .70 Wire fence bears E. & W. S.E. cor. of wire fence bears E. 10 lks. dist., thence parallel to E. & W. of wire fence.
- 37.50 Wire fence bears E. & W.
- 39.00 G. W. Moore's house bears W. 3 chs. dist.
- 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked S 4 in W., S 3 in E. & 1913 in S. half. of post
- Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
- 40.10 Wagon road bears E. & W., cor. of wire fence bears E.
- 40.20 Wire fence bears E. & W., cor. of wire fence bears E. 50 lks. dist. & S.W. cor. of wire fence bears W. 75 lks. dist.
- 79.00 Wire fence bears E. & W. N.W. cor. of wire fence bears W. 125 lks. dist.
- 79.50 Wagon road bears E. & W.
- 79.85 Intersect Third Standard Parallel South 27.30 chs. S. 89° 53' W. of Standard Cor. of secs. 33 & 34, previously re-established by me as described in Book "B."
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. Closing cor. of secs. 3 & 4, with a brass cap marked CC S. of center, T 16 S R 25 E S 33 S 34 in N. & 1913 in S. half, S 3 in S.E. & S 4 in S.W. quadrant.
Dig pits 24 x 13 x 12 ins. crosswise on each line E&W 3 ft. and S. of post 3 ft. dist. & raise mound of earth 4 ft. base 2 ft. high S. of cor.
Land level
Soil sandy, medium to coarse texture, 13 to 24 ins. deep on clay sub-soil
Mesquite brush & yuccas 4 to 7 ft. high, scattering short grass
No timber.
- Note: Sun is obscured by clouds at noon on this day, rendering an observation for latitude impossible.
July 17th, 1913.
-
- July 18, 1913: At 8h. 10 m. a.m., l.m.t., I set off 21° 05' N. on decl. arc, 31° 59' on lat. arc and determine a mer. with the solar at the cor. of secs. 4, 5, 32 & 33, on S. by of Tp. reestab. by me, as described in Book "A."
Thence I run
N. 0° 02' W. bet. secs. 32 & 33
Over level prairie land parallel to E. & W. of wire fence
- 39.75 Wire fence bears E. & W. S.E. cor. of wire fence bears E. 125 lks. dist.
- 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked S 32 in W., S 33 in E. & 1913 in S. half. of post
- Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
- 47.00 Cor. of wire fence bears E. 130 lks. dist.
- 65.00 Cor. of wire fence bears E. 130 lks. dist.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 28, 29, 32 & 33, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 29 in N.W.

RESURVEY OF SUBDIVISION LINES OF TOWNSHIP 16 S., R. 25 East. 15.

Chains.

S 28 in NE?, S 33 in SE., and S 32 in SW quadrants. Dig pits 18x18x12 ins., in each sec. 5 1/2 ft. dist., and raise a mound of earth 4 ft. base 2 ft. high, west of cor.

Land, level.
Soil, light sandy loam, medium texture, 12 ins. deep, on clay subsoil.
Short salt grass.
No timber.

40.00 The cor. of secs. 27, 28, 33 and 34, being plainly visible, I run,
80.00 East on random line, bet. secs. 28 and 33, for said cor. Set temp. 1/4 sec. cor.
Intersect cor. of secs, 27, 28, 33 and 34, hereunbefore described.

Thence I run,
West, on true line, bet. secs. 28 and 33.
Over level prairie land, along dim wagon road.
1.00 Wagon road, brs. N. and S.
27.00 Dim wagon road brs. NW. and SE.
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for reestablished 1/4 sec. cor., with a brass cap, marked, 1/4 S 28 in N., and S 33 1913 in S. half; dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, north of cor.

From this cor. old 1/4 sec. cor., which is a basalt stone 8x5x6 ins. above ground, firmly set and marked as described by Surveyor General, brs. S. 69 1/2 W., 47 lks. dist., I destroy all trace of this old cor.

78.50 Wagon road brs. N. and S.
79.00 Wire fence brs. N. and S.
80.00 The cor. of secs. 28, 29, 32 and 33, hereinbefore described.
Land, level.
Soil, light, sandy loam, medium texture, 12 ins. deep on clay subsoil.
Short salt grass.
No timber.

Thence I run,
N. 0° 02' W., bet. secs. 28 and 29.
Over level prairie land.
39.00 Wire fence brs. NW. and SE.
39.50 Cors. of wire fences br. west 25 lks., and E 75 lks. dist.
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for reestablished 1/4 sec. cor., with a brass cap, marked,

1/4 S 29 in W.,
S 28 in E., and
1913 in S. half; 3 ft. dist.,
dig pits 18x18x12 ins., N. and S. of post, and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, west of cor.

72.00 Thence through lane, along wagon road.
Cor. of wire fence brs. E. 70 lks. dist.
75.00 Samuel Ross's house brs. W. 2 chs. dist.; also E. Chaffee's house brs. E. 5 chs. dist.
78.75 Cors of wire fences bear west 25 lks. and E. 75 lks. dist.; thence across N. and S. lane.

79.75 Cors of wire fences bear W. 25 lks. and E. 75 lks. dist.
80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for reestablished cor. of secs. 20, 21, 28 and 29, with a brass cap, marked,
T 16 S R 25 E in N., and 1913 in S. half;
S 20 in NW., S 21 in NE., S 28 in SE.,
and S 29 in SW. quadrant. Dig pits 18x18x12 ins. in each sec. 5 1/2 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, west of cor.
Land, level.

16. Resurvey of Subdivision Lines of T. 16 S., R. 25 East.

chains,

	Soil, light sandy loam, medium texture, 12 ins. deep on clay subsoil. Good grass. No timber.

	Thence I run, East, on random line, bet. secs. 21 and 28.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	Fall 5 lks. N. of cor. of secs. 21, 22, 27 and 28, hereinbefore described. Thence I run, N. $89^{\circ}58'$ W., on true line, bet. secs. 21 and 28.
	Along wagon road, through scattering mesquite brush, 3 to 4 ft. high.
39.50	Cors of wire fences bear N. 25 and S. 75 lks. dist.; thence through lane.
39.99	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., marked on brass cap, $\frac{1}{4}$ S 21 in N., and S 28 1913 in S. half; dig pits 18x18x12 ins., E. and W. of post 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
45.00	Leave mesquite brush, brs. NW. and SE.
64.00	Wire fence, brs. S. 89° W., N. 89° E.; leave lane.
79.23	Wire fence brs. N. and S.
79.98	The cor. of secs. 20, 21, 28 and 29, hereinbefore described. Land, level. Soil, light, sandy loam, medium texture, 12 ins. deep on clay subsoil. Good grass, scattering mesquite brush, 3 to 4 ft. high, No timber.

	Thence I run, N. $0^{\circ}02'$ W., bet. secs. 20 and 21. Over level land, through lane. From the above described cor., R. A. Chaffee's house brs. N. $44\frac{3}{4}$ E.
35.00	Enter scattering mesquite brush 3 to 4 ft. high, brs. NW. & SE.
40.00	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap, marked, $\frac{1}{4}$ S 20 in W., S 21 in E., and 1913 in S. half; dig pits 18x18x12 ins., N. and S. of post 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, west of cor.
40.30	Cors. of wire fences br. W. 15 lks. dist., and E. 85 lks. dist.
40.50	R. A. Chaffee's house brs. S. $88\frac{1}{2}$ E.
42.00	J. A. Callahan's house brs. E. 2 chs. dist., and J. J. Jones' house brs. west 13 chs. dist.
79.90	Cors of wire fences bear west 10 lks. and east 90 lks. dist.
80.00	Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for reestablished cor. of secs. 16, 17, 20 and 21, with a brass cap, marked, T 16 S R 25 E in N., and 1913 in S. half; S 17 in NW., S 16 in NE., S 21 in SE., and S 20 in SW. quadrant. Dig pits 18x18x12 ins. in each sec. $5\frac{1}{2}$ ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, west of cor. Land, level. Soil, light, sandy loam, medium texture, 12 ins. deep on clay subsoil. Good grass, mesquite brush 3 to 4 ft. high. No timber.

	Thence I run, S. $89^{\circ}58'$ E. on random line, bet. secs. 16 and 21.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect cor. of secs. 15, 16, 21 and 22, hereinbefore described. Thence I run, N. $89^{\circ}58'$ W. on true line, bet. secs. 16 and 21. Over level land, through mesquite brush 4 to 5 ft. high, through lane along wagon road.
4.00	H. L. Birchfield's house brs. S. 2 chs. dist.
40.02	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap, marked, $\frac{1}{4}$ S 16 in N., and S 21 1913 in S. half; Dig pits 18x18x12 ins. E. and W. of post, 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, north of cor.
	From this cor., corner of wire fence brs. S. 30 lks. dist.
80.04	The cor. of secs. 16, 17, 20 and 21, hereinbefore described. Land, level. Soil, light sandy loam, medium texture 12 ins. deep on clay subsoil. Good grass, mesquite brush, 4 to 5 ft. high. No timber.

OF LINES RESURVEY SUBDIVISION OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

Thence I run
 N. 0° 02' W. bet. secs. 16 & 17
 Over level land along wagon road through lane, mesquite brush
 3 to 4 ft. high
 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor. on brass cap marked $\frac{1}{4}$ S 17 in W., S
 16 in E. & 1913 in S. half.
 Dig pits 18 x 18 x 12 ins. E. & S. ^{of post} 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 41.00 G. A. Walker's house bears W. 5 chs. dist.
 79.80 Cors. of wire fences bear W. 5 lks. & E. 95 lks. dist.
 30.00 Set an iron post 3 ft. long 2 ins. in dia. 24 ins. in ground
 for reestab. cor. of secs. 8, 9, 16 & 17, with a brass cap
 marked T 16 S R 25 E in N. & 1913 in S. half, S 8 in N.W.,
 S 9 in N.E., S 16 in S.E. & S 17 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
 raise mound of earth $\frac{1}{2}$ ft. base 2 ft. high W. of cor.
 Land level
 Soil sandy medium texture, 18 to 24 ins. deep on clay sub-
 soil
 Scattering short grass, mesquite brush 3 to 4 ft. high
 No timber.

Thence I run
 S. 99° 58' E. on random line bet. secs. 9 & 16
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.00 Fall 2 lks. S. of cor. of secs. 9, 10, 15 & 16, herein-
 before described.
 Thence I run
 N. 99° 59' W. on true line bet. secs. 9 & 16
 Over level land along wagon road through lane, mesquite
 brush 3 to 6 ft. high
 3.00 Telephone line bears N. 10° E., S. 10° W.
 26.00 W. L. Ross' house bears N. 3 chs. dist.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 9 in
 N. & S 16 1913 in S. half. /of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 From this corner of wire fence bears N. 80 lks. dist.
 30.00 The cor. of secs. 8, 9, 16 & 17, hereinbefore described.
 Land level
 Soil, sandy, medium texture, 18 to 24 ins. deep on clay
 sub-soil
 Scattering short grass, mesquite brush 3 to 4 ft. high
 No timber

Thence I run
 N. 0° 02' W. bet. secs. 8 & 9
 Over level sandy land along W. edge of lane parallel to
 & W. of wagon road, mesquite brush 3 to 5 ft. high
 4.00 H. J. Thomas' house bears W. 1 ch. dist. & S. C. Thomas'
 house bears E. 2 chs. dist.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 3 in
 W., S 9 in E. & 1913 in S. half. /of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 40.20 Cors. of wire fences bear E. & W.
 65.00 Wire fence bears N. $\frac{1}{2}$ ° E., S. $\frac{1}{2}$ ° W.
 79.90 Wire fence bears E. & W. N.E. cor. of wire fence bears E.
 5 lks. dist.
 30.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground
 for reestab. cor. of secs. 4, 5, 8 & 9, with a brass cap
 marked T 16 S R 25 E in N. & 1913 in S. half, S 5 in N.W.,
 S 4 in N.E., S 9 in S.E. & S 8 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.

RESURVEY OF SUBDIVISION LINES ON T. 16 SOUTH, RANGE 25 EAST

Land level
Soil sandy, medium to coarse texture, 18 to 24 ins. deep on clay sub-soil
Scattering grass, mesquite brush & yuccas 4 to 7 ft. high
No timber.

Thence I run
S. 89° 59' E. on random line bet. secs. 4 & 9
40.00 Set temp. $\frac{1}{4}$ sec. cor.
79.98 Fall 12 lks. N. of cor. of secs. 3, 4, 9 & 10, hereinbefore described.

Thence I run
N. 89° 54' W. on true line bet. secs. 4 & 9
37.00 Over level sandy land along wagon road through lane
39.99 mesquite brush & yuccas 4 to 7 ft. high
F. L. Wilson's house bears S. 5 chs. dist. 26 ins. in ground
Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground,
for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 4 in
N. & S 9 1913 in S. half. /of post
Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
From this cor. cor. of wire fences bear N. & S.
52.00 G. W. Anderson's house bears S, 5 chs. dist., also B. F.
Warner's house bears N. 7 chs. dist.
78.93 N.W. cor. of wire fence bears S. 10 lks. dist. and S.W.
cor. of wire fence bears N. 10 lks. dist.
79.50 Wagon road bears N. & S.
79.98 The cor. of secs. 4, 5, 8 & 9, hereinbefore described.

Land level
Soil sandy, medium to coarse texture, 18 to 24 ins. deep on clay sub-soil
Scattering grass, mesquite brush & yuccas 4 to 7 ft. high
No timber.

Thence I run
N. 0° 02' W. bet. secs. 4 & 5
.20 Over level land through mesquite brush 3 to 6 ft. high
.90 Wagon road bears E. & W.
Wire fence bears E. & W., S.E. cor. of wire fence bears
E. 5 lks. dist., thence parallel to & W. of lane
36.00 C. W. Swartz's house bears W. 2 chs. dist.
38.30 Wire fence bears E. & W., N.E. cor. of wire fence bears
E. 3 lks. dist.
39.00 Wagon road bears N.W. & S.E.
40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in
ground for reestab. $\frac{1}{4}$ sec. cor. with a brass cap, mkd. $\frac{1}{4}$ S 5 in
W., S 4 in E. & 1913 in S. half. /of post
Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
40.30 Wire fence bears E. & W., S.W. cor. of wire fence bears
W. 1 ch., dist., thence parallel to & 1 ch. E. of lane.
43.00 T. E. Robert's house bears W. 7 chs. dist.
59.75 Wire fence bears E. & W.
79.50 Wire fence bears E. & W., N.W. cor. of wire fence bears
W. 1 ch. dist.
79.60 Dim wagon road bears E. & W.
79.72 Intersect Third Standard Parallel South 27.27 chs. S. 89°
44' W. of Standard cor. of secs. 32 & 33, previously re-
estab. by me, as described in Book "B,"
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground
for reestab. c. l. s. cor. of secs. 4 & 5, with a brass cap
marked CC S, of center, T 16 S R 25 E S 32 S 33 in N. &
1913 in S. half, S 4 in S.E. & S 5 in S.W. quadrant.
Dig pits 24 x 18 x 12 ins. crosswise on each line E. & W. 3
ft. & S. of post. 7 ft. dist. & raise mound of earth 4 ft. base
2 ft. high S. of cor.
Land level
Soil light sandy loam, medium texture, 12 ins. deep on
clay sub-soil

RESURVEY SUBDIVISIONS OF TOWNSHIP 16 SOUTH, RANGE 25 EAST

Good grass, mesquite brush 3 to 6 ft. high
 No timber.
 Note: sun is obscured by clouds at noon on this day, rendering an observation for latitude impossible.
 July 13th, 1913.

July 19, 1913: At; 8 h. 20 m., a.m., 1.m.t., I set off 20° 54' N. on decl. arc, 31° 59' on lat. arc and determine a mer. with the solar at the cor. of secs. 5, 6, 31 & 32 on S. bdy. of Tp.; previously reestab. by me, as described in Book "A." Thence I run
 N. 0° 03' W. bet. secs. 31 & 32
 Over level prairie land
 39.95 Wire fence bears E. & W., cor. of wire fence bears E. 1 ch. dist., thence parallel to & 1 ch. W. of wire fence.
 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 31 in W., S 32 in E. & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 40.50 Allie Martin's house bears W. 4 chs. dist.
 79.98 Wire fence bears E. & W.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 29, 30, 31 & 32, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 30 in N.W., S 29 in N.E., S 32 in S.E. & S 31 in S.W. quadrants.
 Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber

The cor. of secs. 28, 29, 32 & 33, being plainly visible, I run
 N. 39° 44' E. on random line bet. secs. 29 & 32 for said cor.
 40.00 Set temp. 1/4 sec. cor.
 30.24 Intersect cor. of secs. 28, 29, 32 & 33, hereinbefore described.
 Thence I run
 S. 39° 44' W. on true line bet. secs. 29 & 32
 Over level prairie land
 40.12 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 29 in N. & S 32 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 70.00 Dry shallow wash 30 lks. wide, course N.W.
 79.00 N.E. cor. of wire fence bears S. 1 lk. dist.
 80.24 The cor. of secs. 29, 30, 31 & 32, hereinbefore described.
 Land level
 Soil light adobe 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

The cor. of secs. 25, 30, 31 & 36, on W. bdy. of Tp. being plainly visible, I run,
 S. 89° 53' W. on true line bet. secs. 30 & 31 for said cor.
 Over level prairie land along wire fence
 39.90 Cor. of wire fence bears S. 1 lk. dist.
 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 30 in N. & S 31 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

RESURVEY OF SUBDIVISION LINES OF TWP 16 SOUTH, RANGE 25 EAST

- 78.18 Intersect W. bdy. of Tp. at the cor. of secs. 25, 30, 31 & 36, hereinbefore reestab. by me as described in "Book "A"
Land level
Soil light adobe 12 ins. deep on clay sub-soil
Short salt grass
No timber.
-
- At the cor. of secs. 29, 30, 31 & 32, hereinbefore described, I set off $20^{\circ} 52\frac{1}{2}'$ N. on decl. arc and at 12 h. 6 m. 3 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of $32^{\circ} 0'$ on lat. arc
Thence I run
N. $0^{\circ} 03'$ W. bet. secs. 29 & 30
Over level prairie land.
- 40.00 Wire fence bears E. & W. Reestab. $\frac{1}{4}$ sec. cor., as follows:
Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for $\frac{1}{4}$ sec. cor., with a brass cap marked S 30 in W., S 29 in E. & 1913 in S. half. /of post
Dig pits 13 x 13 x 12 ins. N. & S. $\sqrt{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
- 40.75 Old wagon road bears E. & W.
- 30.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 19, 20, 29 & 30, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 19 in N.W., S 20 in N.E., S 29 in S.E. & S 30 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level
Soil light adobe, 12 ins. deep on clay sub-soil
Short salt grass
No timber
-
- Thence I run
N. $39^{\circ} 44'$ E. on random line bet. secs. 20 & 29
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 30.24 Intersect cor. of secs. 20, 21, 23 & 29, hereinbefore described.
Thence I run
S. $39^{\circ} 44'$ W. on true line bet. secs. 20 & 29
Over level land
- .25 Wire fence bears N. & S., S.E. cor. of wire fence bears S. 25 lks. dist., thence along S. edge of cultivated land
- 15.00 Wire fence bears N. 89° W., S. 89° E., thence along lane
- 40.12 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked S 20 in N. & S 29 1913 in S. half. /of post
Dig pits 13 x 13 x 12 ins. E. & W. $\sqrt{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
From this cor. cor. of wire fence bears N. 30 lks. dist. & N.W. cor. of wire fence bears S. 70 lks. dist. also F. W. Marquart's house bears N. $2\frac{1}{2}^{\circ}$ E. 37 chs. dist. leave lane thence parallel to & S. of wire fence along wagon road
- 30.24 The cor. of secs. 19, 20, 29 & 30, hereinbefore described.
Land level
Soil light adobe on W. half, 12 ins. deep on clay sub-soil, light sandy loam, medium texture, 12 ins. deep on clay sub-soil, on E. half.
Short salt grass
No timber.
-
- The cor. of secs. 19, 24, 25 & 30, on W. bdy. of Tp., being plainly visible, I run,
S. $39^{\circ} 54'$ W. on true line bet. secs. 19 & 30 for said cor.
Over level prairie land along wagon road parallel to & S. of wire fence
- 37.00 W. J. Harper's cabin bears S. 3 chs. dist.

RESURVEY OF SUBDIVISION LINES OF TP. 16 SOUTH, RANGE 25 EAST

40.00 Set an iron post 3 ft. long, 1 in. in dia., **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 19 in N. & S **30, 1913. in S. half;** /of post
 Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 From this cor. cor. of wire fences bear N. & S. 50 lks. dist. each, thence parallel to & W. of wire fence.
 42.00 Wagon road turns N.W.
 78.19 Intersect W. bdy. of Tp. at the cor. of secs. 19, 24, 25 & 30, previously re-estab. by me, as described in Book "A."
 Land level
 Soil light adobe, 12 ins. deep on clay sub-soil
 Short salt grass
 No timber.
 July 19th, 1913.

July 22, 1913: At; 8 h. 0 m., a.m., l.m.t., I set off $20^{\circ} 20\frac{1}{2}'$ N. on decl. arc, $32^{\circ} 01'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 19, 20, 29 & 30, herebefore described.
 Thence I run
 N. $40^{\circ} 03'$ W. bet. secs. 19 & 20
 Over level prairie land
 .30 Wagon road bears E. & W.
 .50 Wire fence bears E. & W., cor. of wire fence bears E. 50 lks. dist., thence parallel to & W. of wire fence.
 30.00 W. C. Harper's house bears E. 15 chs. dist. land
 34.50 Cor. of wire fence bears E. 75 lks. dist. enter cultivated
 35.50 W. J. Harper's house bears W. 5 chs. dist. enter
 40.00 Set an iron post 3 ft. long, 1 in. in dia., **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 19 in W., S 20 in E. & 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 40.50 Wire fence bears E. & W. leave cultivated ground thence across lane
 40.70 Dim wagon road bears E. & W.
 41.20 Wire fence bears E. & W., S.E. cor. of wire fence bears E. 10 lks. dist., thence parallel to & W. of wire fence
 30.00 Set an iron post 3 ft. long, 2 ins. in dia., **24 ins. in ground** for reestab. cor. of secs. 17, 18, 19 & 20, with a brass cap marked T 16 S-R 25 E in N. & 1913 in S. half, S 13 in N.W., S 17 in N.E., S 20 in S.E. & S 19 in S.W. quadrant.
 Dig pits 13 x 13 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light sandy loam, 12 ins. deep on clay sub-soil
 Good grass
 No timber.

Thence I run
 N. $39^{\circ} 44'$ E. on random line bet. secs. 17 & 20
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.30 Fall 5 lks. S. of cor. of secs. 16, 17, 20 & 21, hereinbefore described.
 Thence I run
 S. $39^{\circ} 42'$ W. on true line bet. secs. 17 & 20
 Along dim wagon road through lane, mesquite brush 4 to 7 ft. high
 39.50 N.W. cor. of wire fence bears S. 25 lks. dist., leave lane wagon road turns S.W., thence parallel to & S. of wire fence
 40.15 Set an iron post 3 ft. long, 1 in. in dia., **26 ins. in ground** for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 17 in N. & S 20 1913 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 Enter scattering yuccas 4 to 7 ft. high bear N. & S.
 60.00 Leave scattering mesquite brush & yuccas bears N. & S.
 79.00 S.W. cor. of wire fence bears N. 1 ch. dist.

RESURVEY OF SUBDIVISION LINES OF T¹P¹R 16 SOUTH, RANGE 25 EAST

89.00 Wire fence bears N. & S.
 80.30 The cor. of secs. 17, 18, 19 & 20, hereinbefore described.
 Land level
 Soil sandy, medium to coarse texture, 12 to 18 ins. deep on clay sub-soil.
 Good grass, scattering mesquite brush & yuccas 4 to 7 ft. high
 No timber.

 The cor. of secs. 13, 18, 19 & 24, on W. bdy of Tp. being 10, I plainly visible, I run,
 S. 39° 56' W. on true line bet. secs. 18 & 19 for said cor.

40.00 Over level prairie land
 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 13 in E. & S 19 19 13 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

71.00 Dry shallow wash 75 lks. wide, course North
 78.19 Intersect W. bdy. of Tp. at the cor. of secs. 13, 18, 19 & 24, previously reestab. by mesa described in Book "A"
 Land level
 Soil light adobe 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 From the cor. of secs. 17, 18, 19 & 20, hereinbefore described, I run
 N. 0° 03' W. bet. secs. 17 & 18

40.00 Over level prairie land parallel to & W. of lane
 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 18 in W., S 17 in E. & 19 13 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.

60.00 Scattering mesquite brush 3 to 6 ft. high, bears N.W. & S.E.

79.00 Windmill & Well bears W. 1 ch. dist.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 7, 8, 17 & 18, with a brass cap marked T 16 S R 25 E in N. & 19 13 in S. half, S 7 in N.W., S 8 in N.E., S 17 in S.E. & S 18 in S.W. quadrant.

Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass
 No timber.

 Thence I run
 N. 39° 42' E. on random line bet. secs. 8 & 17

40.00 Set temp. 1/4 sec. cor.
 80.36 Fall 17 lks. N. of cor. of secs. 8, 9, 16 & 17, hereinbefore described.

Thence I run
 S. 39° 49' W. on true line bet. secs. 3 & 17

40.18 Over level sandy land along dim wagon road through lane mesquite brush & yuccas 4 to 7 ft. high
 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 3 in N. & S 17 19 13 in S. half. /of post
 Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

79.11 From this cor. cor. of wire fence bears N. 50 lks. dist.
 79.50 Cors. of wire fences bear N. & S. 50 lks. dist. each.
 Wagon road bears N. & S.

RESURVEY OF SUBDIVISION LINES OF T1P 16 SOUTH, RANGE 25 EAST

30.00 Wire fence bears N. & S.
 39.36 The cor. of secs. 7, 8, 17 & 13, hereinbefore described.
 Land level
 Soil light sandy loam, medium texture, 12 ins. deep on clay sub-soil
 Scattering short grass
 No timber.

 Thence I run
 ✓ S. 39° 56' W. on random line bet. secs. 7 & 13
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 78.26 Intersect W. bdy. of Tp. 2 lks. S. of cor. of secs. 7, 12, 13 & 18, previously reestab. by me, as described in Book "A."

Thence I run
 N. 39° 57' E. on true line bet. secs. 7 & 13
 Over level prairie land
 38.26 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 7 in N. & S 13 1913 in S. half. /of post

Dig pits 13 x 13 x 12 ins. E. & W. 13 ft. dist. & raise mound of earth $3\frac{3}{8}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 60.00 Enter scattering mesquite brush 3 to 6 ft. high bears N. & S.
 78.26 The cor. of secs. 7, 8, 17 & 13, hereinbefore described.
 At this cor. I set off 20° 18' N. on decl. arc and at 12 h. 6 m. 15 s., p.m.; 1.m.t., observe the sun on the mer. and obtain a reading of 32° 02 $\frac{1}{2}$ ' on lat. arc.

Land level
 Soil light adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass, scattering mesquite brush 3 to 6 ft. high on E. end of line
 No timber.

 Thence I run
 ✓ N. 0° 03' W. bet. secs. 7 & 8
 Over level land through scattering mesquite brush 3 to 6 ft. high parallel to & W. of lane

20.00 Leave scattering mesquite brush bears N.E. & S.W.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 7 in W., S 3 in E. & 1913 in S. half. /of post

Dig pits 13 x 13 x 12 ins. N. & S. 13 ft. dist. & raise mound of earth $3\frac{3}{8}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

40.50 Wire fence bears E. & W., N.E. cor. of wire fence bears E. 50 lks. dist.

79.50 Dim wagon road bears E. & W.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 5, 6, 7 & 8, with a brass cap marked T 16 S R 25 E in N. & 1913 in S. half, S 6 in N.W., S 5 in N.E., S 8 in S.E. & S 7 in S.W. quadrant.

Dig pits 13 x 13 x 12 ins. in each sec. 5 $\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.

Land level
 Soil adobe, 12 ins. deep on hardpan sub-soil
 Short salt grass, scattering mesquite brush 3 to 6 ft. high on S. end of line.
 No timber.

 Thence I run
 ✓ N. 39° 49' E. on random line bet. secs. 5 & 8
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 30.43 Fall 5 lks. N. of cor. of secs. 4, 5, 3 & 9, hereinbefore described.

Thence I run
 ✓ S. 39° 51' W. on true line bet. secs. 5 & 3
 Over level land along dim wagon road through lane, mesquite brush 3 to 4 ft. high

35.00 Leave mesquite brush bears N. & S.

RESURVEY OF
SUBDIVISION LINES OF TWP. 16 S. 14, RANGE 25 EAST, SUBDIVISIONS

40.215 Set an iron post 3 ft. long, 1 in. in dia. ~~26 ins. in ground~~
for reestab. ~~1~~ sec. cor., with a brass cap marked ~~1~~ S 5 in
N. & S 8 1913 in S. half.

Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} 3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

Henry Dier's house bears S. 35 chs. dist.

Cors. of wire fences bears N. & S. 50 lks. dist.

The cor. of secs. 5, 6, 7 & 8, hereinbefore described.

Land level

Soil E. half, light sandy loam, medium texture, 12 ins.
deep on clay sub-soil. W. half light adobe 12 ins. deep on
hardpan sub-soil.

Good grass, scattering mesquite brush 3 to 4 ft. high

No timber.

The cor. of secs. 1, 6, 7 & 12, on W. bdy. of Tp. being plain-
ly visible, I run,

N. $39^{\circ} 52'$ W. on true line bet. secs. 6 & 7 for said cor.

Over level land

15.00 Enter dry bed of old alkali lake

40.00 Set an iron post 3 ft. long, 1 in. in dia. ~~26 ins. in ground~~
for reestab. ~~1~~ sec. cor., with a brass cap marked ~~1~~ S 6 in
N. & S 7 1913 in S. half

Dig pits 13 x 13 x 12 ins. E. & W. ^{of post} 3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

73.38 Intersect W. bdy. of Tp. at the cor. of secs. 1, 6, 7 &
12, previously reestab. by me, as described in Book "A."

Land level

Soil alkali

No vegetation.

From the cor. of secs. 5, 6, 7 & 8, hereinbefore describ-
ed, I run

N. $0^{\circ} 03'$ W. bet. secs. 5 & 6

Over level alkali land parallel to & W. of wire fence

40.00 Set an iron post 3 ft. long, 1 in. in dia. ~~26 ins. in ground~~
for reestab. ~~1~~ sec. cor., with a brass cap marked ~~1~~ S 6 in
W., S 5 in E. & 1913 in S. half. /of post

Dig pits 13 x 13 x 12 ins. N. & S. ^{of post} 3 ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

From this cor. cor. of wire fence bears E. 150 lks. dist.

79.35 Intersect Third Standard Parallel South 27.35 chs. S. 39°
~~47'~~ W. of Standard cor. of secs. 31 & 32, previously re-
estab. by by, as described in Book "B."

Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in
ground for reestab. C. cor. of secs. 5 & 6, with a brass cap
marked CC S. of center, T 16 S R 25 E S 31 S 32 in N. &
1913 in S. half, S 5 in S.E. & S 6 in S.W. quadrant.

Dig pits 24 x 13 x 12 ins. crosswise on each line E & W. 3 ft.
& S. of post 7 ft. dist. & raise mound of earth 4 ft. base
2 ft. high S. of cor.

Land level & rolling

Soil alkali

Short salt grass

No timber.

July 22nd, 1913.

GENERAL DESCRIPTION.

This township consists nearly entirely of level land. All
excepting the extreme West & Southwest portions are cover-
ed with a good growth of mesquite brush. The adobe and al-
kali soil of the W. & S.W. supports a good growth of salt
grass which affords very good grazing for stock. The N. &
Eastern portions of the township has been very largely fenced
by settlers who are engaged in dry farming and have obtained
fairly good success. Very good supply of water is obtained
at a depth ranging from 30 to 70 ft. The old Sulphur Spring
Ranch is located in the Eastern part of sec. 33, at which
point an Indian Massacre occurred during the early sett-
lement of the calley.

July 22, 1913.

Thomas B. Matthews
H. S. Surveyor

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Henry Diers, being first duly sworn upon my oath state; that I am the owner by virtue of a legal transfer of the S $\frac{1}{2}$ of sec. 7, sec. 18 & N $\frac{1}{2}$ sec. 19 T.16 S., R.25 E., G. & S.R., B. & M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Santa Ana, California, ~~Arizona~~

Henry Diers

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 14th day of April, 1914, ~~1917~~.

My Commission Expires Jan. 13, 1917

J. H. Mansur
~~United States Surveyor~~
 Notary Public in and for Orange County California

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, W. J. Harper, being first duly sworn upon my oath state; that I am the same person who made Standard entry of the NW 1/4 Sec 29 T16R25E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Pease, Ariz

W. J. Harper

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 19 day of Aug 1911

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.
Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, W. J. Harper, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the SE 1/4 Sec 19 T16N R25E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Peace, Ariz

Wm J Harper

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 19 day of Aug, 1911

Thomas B. Matthews
U. S. Surveyor.

2727

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE
Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 ARIZONA.

I, Peter Adling, being first duly sworn upon my oath state; that I am the the same person who made final homestead entry of the S.E. $\frac{1}{4}$ of secs. 11, Tp. 16 S., Rs. 25 E., G. & S.R. B. & M., Arizona, and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the re-survey thereof; that my postoffice address Pearce, Arizona.

Peter Adling

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 25th day of May, 1914.

Thomas B. Matthews
U.S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, C. A. Patterson, being first duly sworn upon my oath state; that I am the owner by virtue of a legal transfer of the N W 1/4 of sec. 20, T. 16 S., R. 25 E., G. & S. R. B. & M., Ariz.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Genoa, Ill., ARIZONA.



I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 3^d day of October, 1913.



~~UNITED STATES DEPARTMENT OF THE INTERIOR~~
Notary Public.

My commission expires Feb. 8 - 1917

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona. DOCK 2727

I, James A. Fogarty, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the 5 1/2 of NE 1/4 & N 1/2 of SE 1/4 SEC. 10 T16S R25E, G. & S. R. M. and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is ~~XXXXXXXXXXXX~~ Pearce, Arizona.

J. A. Fogarty

I HEREBY CERTIFY THAT the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 24 day of Sept, 1913.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, John Doran, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the SE 1/4 of sec 12 T. 16 S. R. 25 E. G. & S. R. M. and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Hardin Mo. Arizona.

John Doran

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 18 day of Sept, 1913.

W. A. Beery
United States Surveyor.

Notary Public for Ray Co. Mo.

My Commission expires
Apr 22-1916.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Earl S. King, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the SW 1/4 of sec. 12 T. 16 S., R. 25 E. G. & S. R. M., and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Hardin Mo. Arizona.

Earl S. King

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 18 day of Sept, 1913.

J. A. Beery
 United States Surveyor.
 Notary Public for Rayles Mo.

My Commission expires
 Apr 22 - 1916.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, P. W. Hamilton, being first duly sworn upon my oath state; that I am the owner by virtue of a legal transfer of the SE 1/4 + E 1/2 of NW 1/4 + Lots
142, ^{Sec. 31} 7163, R. 25E. G. & S. R., M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Cochise Arizona.

P. W. Hamilton

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 11th day of Sept., 1913.

Thomas E. Matthews
 United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.
Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, F. W. Marguash, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the S. E. 1/4 of Sec. 20, T. 16 S., R. 25 E., T. 9. & S. R. 130m. Ariz.; and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Valparaiso, Ind.

Fred. W. Marguash

Subscribed and sworn to before me this 19th day of September 1913

Peter A. Marguash
Justice of the Peace.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.
Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, J. A. Ross, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the SW 1/4 of sec 10 T16S, R.25E, G4S.B.M. and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my ~~land~~ claim to the lines of the resurvey thereof; that my postoffice address is Santa Ana Arizona.

J. A. Ross

State of California,
County of Orange,

SS.

On this 19 day of Sept, in the year nineteen hundred and 13, A. D., before me, J. D. Price, a Notary Public in and for the said County of Orange, State of California, residing therein, duly commissioned and sworn, personally appeared

J. A. Ross personally known to me to be the person whose name is subscribed to the within instrument, and acknowledged to me that he executed the same.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed my official seal the day and year in this certificate first above written.

J. D. Price
Notary Public in and for Orange County, State of California.

[GENERAL]
Los Angeles Rubber Stamp Co., 131 South Spring St.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, G. F. Allaris, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the Lot 3 Sec 3 T16 S
R25 E, G. H. R. M. and am the legal owner of said tract that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof, that my postoffice address is Willcox Arizona.

G. F. Allaris

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described; and that said affidavit was duly subscribed and sworn to before me this the 10th day of Sept, 1913.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, C. Chambers, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the SE 1/4 of NE 1/4 of N 1/2 of SE 1/4 of sec 37 T16 S. R25 E. 4th R.M. and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Willcox Arizona.

C. Chambers

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 10th day of Sept., 1913.

Thomas B. Matthews
United States Surveyor.



DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, W^m D. Bemis, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the N^W 1/4 of Sec 25 T16N R25E, G4W3M. and am the legal owner of said tract that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof, that my postoffice address is Pine Arizona.

Wm D. Bemis

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described; and that said affidavit was duly subscribed and sworn to before me this the 9th day of Sept, 1913.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, G. F. Allaire, being first duly sworn upon my state; that I am the owner by virtue of a legal transfer of the 1/2 of NW 1/4 & SW 1/4 of sec 3 T16N R25E B&O 17 M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the re-survey thereof; that my postoffice address is Willcox Arizona.

G. F. Allaire

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 10th day of Sept, 1913.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Graz Bailey, being first duly sworn upon my oath state that; I am the owner by virtue of a legal transfer of ~~7~~ 7 SE 1/4 Sec. 6 T16S. R. 25E of SR B & M; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is ~~xxx~~ Willcox, Arizona.

Graz Bailey

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 12 day of Sept, 1913.

Thomas B. Matthews
United States Surveyor.

BOOK 111

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Henry Diers Jr., being first duly sworn upon my oath state; that I am the owner by virtue of a legal transfer of the NW 1/4 of sec. 8 T. 16 S. R 25 E;

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Wilcox Arizona.

Henry Diers Jr.

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 12th day of Sept., 1915.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Henry Diers Jr., being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the NE 1/4 of sec 8 T.16 S., R.25 E. and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Willcox, Arizona.

Henry Diers Jr.

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 12th day of Sept., 1913.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Geo. M. Anderson, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the NW¹ of sec. 9 T 16 S. R25 E. G. & S.R., M., and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Pearce, Arizona.

Geo. M. Anderson

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 5 day of Sept., 1913.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

Mr. Boyce, Gates & Johnson

_____, being first duly sworn upon my oath state; that I am the owner by virtue of a legal transfer of ~~the S 1/2 of sec. 29 & 30, N 1/2 of sec. 32~~ ^{SE 1/4 and S 1/2 of NW 1/4} ~~of sec. 33 T16S R25E~~ ^{of sec. 33 T16S R25E}

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Los Angeles Cal., ~~Arizona~~.

BOICE, GATES & JOHNSON

by C.W. Gates

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 10 day of Sept. 1913.

Thomas B. Matthews
United States Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, -Arizona.

I, James M. Rice, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the SE 1/4 of sec 25 T16 N23 E Q4 R, B4 M; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Denver, Ariz.

James M. Rice

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 3. day of March, 1914.

Thomas B. Matthews
U. S. Surveyor.

BOOK 2127

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, -Arizona.

I, Jon M. Rice, being first duly sworn upon my oath state; that I am the same person who made deed land entry of the SW 1/4 sec. 26 T16N R23E Co. 4 R. B. M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Arrow, Ariz.

Jon Rice

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 3 day of March, 1914.

Thomas B. Matthews
U. S. Surveyor.

BOOK 222

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Sam Ross, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the N.E. 1/4 Sec. 29, T.16S., R.25E. G. & S.R. B.M. Ariz.; and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Santa Ana, Cal.

Samuel Ross

Subscribed and Sworn to before me this
29th day of September 1913

C. E. Parker
 Notary Public in and for the County of Orange, State of California

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, D.C. Masters, being first duly sworn upon my oath state; that I am the same person who made

homestead entry of the SW 1/4 of sec 22 T16N R25E

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address

is Willcox, Ariz.

D.C. Masters

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 13 day of Aug 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, D. C. Masters, being first duly sworn upon my oath state; that I am the same person who made Standard entry of the SE 1/4 of 2010 1725 E that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Willcox, Ariz.

D. C. Masters

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 13 day of Aug 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.
Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, H. A. Moore, being first duly sworn upon my oath state; that I am the same person who made ~~entry~~ entry of the 1925E 1925E 1925E entry of the 1925E 1925E 1925E that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Adelphi, Ariz.

H. A. Moore

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of July 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, J. W. Roberts, being first duly sworn upon my oath state; that I am the same person who made

homestead entry of the NE 1/4 of section 27, T. 15 N., R. 25 E.

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Cochise, Ariz.

J. W. Roberts

I HEREBY CERTIFY That the foregoing affidavit was read to affiant in my presence before affiant affixed signature therefo; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 29 day of July 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, Jas Hutcherson, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the NE 1/4 of sec 15
T16N R25E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the line of the resurvey thereof; that my postoffice address is Peard, Ariz.

Jas Hutcherson

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of July, 1914.

Thomas B. Matthews
 U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona

I, J. C. Jenkins, being first duly sworn upon my oath state; that I am the same person who made improved entry of the SE 1/4 of sec 22 T16N R25E; that I do not desire a special notes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Leanne, Ariz.

J. C. Jenkins

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of July 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona

I, Edna J. Hutcherson, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the N 10 1/4 of sec 10 T16N R25E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Peave, Ariz.

Edna J. Hutcherson

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 25 day of July 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, J. F. Fogarty, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the N.W. 1/4 Sec 4; NE 1/4 R 25 E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Cashua, Ariz.

J. F. Fogarty

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of

July, 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, W. C. Harper, being first duly sworn upon my oath state; that I am the same person who made _____

homestead entry of the 20th June 20
1862 R 25 E; that I do not desire a special

metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof;

that my postoffice address is Phoenix, Arizona

W. C. Harper

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of

July, 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona

I, W.D. Matthews, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the N 1/4 of sec 26 T6 S 19 25 E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Pearce, Ariz.

W.D. Matthews

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 29 day of

July, 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF OROUP25 - Arizona.

I, Mamie Kinzy, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the SW 1/4 of sec 11
T16N R25E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the line of the resurvey thereof; that my postoffice address is Parce, Ariz.

Mamie Kinzy

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 29 day of July, 1914.

Thomas B. Matthews
 U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona.

I, J. A. Fogarty, being first duly sworn upon my oath state; that I am the same person who made ~~homestead~~ ^{Desert land} entry of the Magdalen 7168 R 25 E;

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the line of the resurvey thereof; that my postoffice address is Cochise, Ariz.

J. A. Fogarty

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 29 day of July, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona

I, J. W. Roberts, being first duly sworn upon my oath state; that I am the same person who made Grant Land entry of the N W 1/4 sec 5 2160 R 25 E that I do not desire a special metes and bounds survey of said described land, but agree to conform my ~~rights~~ claim to the lines of the resurvey thereof; that my post-office address is Cochise, Ariz.

J. W. Roberts

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described and that said affidavit was duly subscribed and sworn to before me this the 28 day of July, 1914.

Thomas B. Matthews
U.S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona

I, B. F. Warner, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the W. 1/4 Sec 4; T16 R25 E; that I do not desire a special metes and bounds survey of said described land, but agree to conform my ~~rights~~ claim to the lines of the resurvey thereof; that my post-office address is Cochise, Ariz.

B. F. Warner

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described and that said affidavit was duly subscribed and sworn to before me this the 25 day of July, 1914.

Thomas B. Matthews
U.S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona

I, C. W. Swartz, being first duly sworn upon my oath state; that I am the same person who made

homestead entry of the 184 p. 5 76. AR 25 E

that I do not desire a special metes and bounds survey of said described land, but agree to conform my ~~rights~~

claim to the lines of the resurvey thereof; that my post-

office address is Cochise, Ariz.

C. W. Swartz

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described and that said affidavit was duly subscribed and sworn to before me this the 28 day of July, 1914.

Thomas B. Matthews
U.S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 - Arizona

I, C. W. Swartz, being first duly sworn upon my oath state; that I am the same person who made

Swartz land entry of the U.S. G.O. 571681925 E

that I do not desire a special metes and bounds survey of said described land, but agree to conform my ~~rights~~

claim to the lines of the resurvey thereof; that my post-

office address is Cochise, Ariz.

C. W. Swartz
3

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person herein-

before described and that said affidavit was duly subscribed and sworn to before me this the 28 day of July, 1914.

Thomas B. Matthews
C. W. Swartz
U.S. Surveyor.

TOWNSHIP 16 SOUTH, RANGE 25 EAST

IN obtaining the settlers' agreements to conform their claims to the lines of the resurvey thereof there are a few with whom I have not been able to get in communication, but whose interests have not been impaired to any great extent, as there is no discernable difference between the land within their claims and the land surrounding same.

Thomas B. Matthews
U.S. Surveyor

106
BOOK

For FINAL OATH OF UNITED STATES SURVEYOR.
(See Book "D.")

I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

U. S. Surveyor.

Subscribed by said _____, and sworn to before me }
this _____ day of _____, 191____



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, March 20, 1915.

The foregoing field notes of the ^{re-}survey of _____

Subdivision lines of Township 16 South, Range 25 East, of the
Gila and Salt River Base and Meridian, Arizona,

executed by Thomas B. Matthews, U. S. Surveyor,

under his special instructions dated May 7, _____, 1913, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.
of Arizona.

I certify that the foregoing transcript of the field notes of the above-described surveys in _____
Book "H," _____, has been correctly copied from the original notes on file in this office.

Frank J. Ingalls
U. S. Surveyor General.
of Arizona.

The Santa Fe Pacific Railroad Company, successors in interest to the Atlantic and Pacific Railroad Company, hereby agree to conform the following lieu selections in Township 16 South, Range 25 East, Gila and Salt River Base and Meridian, Arizona, to the lines of the resurvey thereof, as executed by the General Land Office in 1913:

SE $\frac{1}{4}$,
N $\frac{1}{2}$ NW $\frac{1}{4}$ & N $\frac{1}{2}$ SW $\frac{1}{4}$,

sec. 2,
sec. 33.

Dated Topeka, Kansas,

December 14, 1915.

SANTA FE PACIFIC RAILROAD COMPANY.

By

Howell Jones

Its Land Commissioner.

L.V. McCourt & William Riggs,

By W. E. Leverich & Co.

by J. W. Page

Epes Randolph,

By

W. E. Leverich & Co.

by J. W. Page

It is hereby agreed to conform to the lines of the re-survey of Township 16 South, Range 25 East, Gila and Salt River Base and Meridian, Arizona, as executed by the General Land Office in 1913, in so far as the following State lands and sections are concerned:

All,	sec. 16,
W $\frac{1}{2}$ SE $\frac{1}{4}$,	sec. 32,
All,	sec. 36.

Dated Phoenix, Arizona
December 15, 1915

W.A. Moore
State Land Commissioner