

2732

4-679

2732

97

①

Book "M"

BOOK 2732

SEP 2-1914

Resurvey ~ Subdivisions

FIELD NOTES

OF THE ~~REURVEY~~ OF THE

Subdivision lines of

Township 10 South Range 22 East

Of the Gila and Salt River Base and Meridian,

In the State of ARIZONA

EXECUTED BY

Thomas B. Matthews,

In the capacity of U. S. Surveyor, under instructions dated May 7, 1913,

issued by the United States Surveyor General to govern surveys included in

Group No. 25, which were approved by the Commissioner of the General Land

Office, May 15, 1913, pursuant to authority contained in the Act of

Congress dated June 23, 1913.

ReSurvey commenced January 19, 1914

ReSurvey completed " 27, 1914

Book "M"

BOOK 2732

INDEX DIAGRAM.

Township 10 South, Range 22 East

6	24	5	17	4	13	8	9	2	5	1
23		23		17		13		8		4
7	23	8	17	9	12	10	8	11	4	12
22		22		16		12		8		4
18	22	17	16	16	11	15	7	14	3	13
21		21		15		11		7		3
19	20	20	15	21	11	22	7	23	2	24
20		20		15		10		6		2
30	19	29	14	28	10	27	6	26	2	25
19		18		14		10		5		1
31	18	32	13	33	9	34	5	35	1	36

2nd Standard Parallel South

6-151

- _____ Notes in Book "A", this Group (25) (2720)
 - _____ " " " "B" " " " (2721)
 - _____ " " " "B", Group 22 (2714)
 - _____ " " " "C" " 22 (2715)
 - _____ Surveyed
- Affidavits on Pages 25-86

RESURVEY OF SUBDIVISION LINES
 RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

(13)

Resurvey commenced Jan. 19th, 1914, and executed by Thomas, B. Matthews, U. S. Surveyor, with Young & Sons Light Mountain Transit No. 8480, previously described. I examine the adjustments of the transit and find them to be correct, and know from recent tests of the solar apparatus, by comparing its indications resulting from solar observations, made during a.m. and p.m. hours, with a mer. established by observation on Polaris, at elongation, that the instrument is in satisfactory adjustment.

At 8 h. 40 m., a.m., l.m.t., I set off $20^{\circ} 23'$ S. on decl. arc, $32^{\circ} 30\frac{1}{2}'$ on lat. arc and determine a mer. with the solar at the standard cor. of secs. 35 & 36, on 2nd Std. Par. S. re-established by means described in Book "B" of Group 22. The magnetic bearing of the mer. thus established at 8 h. 40 m., a.m., l.m.t., is $N. 12^{\circ} 55'$ W., the angle thus determined gives the magnetic decl. $12^{\circ} 55'$ E.

Thence I run
 N. $0^{\circ} 02'$ W. bet. secs. 35 & 36
 Over level land, through scattering yuccas 3 to 7 ft. high parallel to & 25 lks. E. of wire fence
 29.00 Dry bed of Ash creek, 25 lks. wide, 2 ft. deep course E.
 35.00 Wire fence bears N. $0^{\circ} 30'$ E., S. $0^{\circ} 30'$ W., thence along W. side, of fence.
 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 35 in W., S 36 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 41.50 Irrigation ditch 10 lks. wide, 1 ft. deep, course East.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground for reestab. cor. of secs. 25, 26, 35 & 36, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 26 in N.W., S 25 in N.E., S 36 in S.E. & S 35 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil, dark sandy loam, medium texture, 18 to 24 ins. deep on clay sub-soil
 Bunch grass, scattering yuccas 3 to 7 ft. high
 Scattering walnut trees along banks of Ash creek.

Thence I run
 N. $89^{\circ} 55'$ E. on random line bet. secs. 25 & 36
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.04 Intersect E. bdy. of Tp. 5 lks. N. of cor. of secs. 25, 30 31 & 36, reestab. by means described in Book "C" of Group 22
 Thence I run
 S. $89^{\circ} 57'$ W. on true line bet. secs. 25 & 36
 Over level land through bunch grass 2 to 3 ft. high
 19.00 Wagon road bears N. & S.
 19.85 Wire fence bears N. & S. Thence along N. of wire fence.
 40.02 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 25 in N. & S 36 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. Δ 3 ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 70.00 Wire fence bears N. 89° W., S. 89° E.
 79.94 Wire fence bears N. & S., fence cor. bears N. 15 lks. dist.
 80.04 The cor. of secs. 25, 26, 35 & 36, hereinbefore described.
 Land level
 Soil, dark sandy loam, medium texture, 18 to 24 ins. deep on clay sub-soil
 Bunch grass, 2 to 3 ft. high.
 No timber.

RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

	Thence I run N. 0° 02' W. bet. secs. 25 & 26 Over level prairie land
40.00	Set an iron post 3 ft. long, 1 in in dia. 26 1/2 ins. in ground for reestablishment of sec. cor., with a brass cap marked 1/4 S 26 in W., S 25 in E. & 19 1/3 in S. half, of post
65.00	Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
79.00	Dry wash 20 lks. wide, 1 ft. deep, course East Wire fence bears E. & W., SE. cor. of wire fence bears E. 20 lks. dist.
80.00	Set an iron post 3 ft. long, 2 1/2 ins. in dia. 24 1/2 ins. in ground for reestablishment of cor. of secs. 23, 24, 25 & 26, with a brass cap marked T 10 S R 22 E in N. & 19 1/3 in S. half, S 23 in N.W., S 24 in N.E., S 25 in S.E. & S 26 in S.W. quadrant, Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor. Land level Soil loose sandy loam, 18 to 24 ins. deep, medium texture on clay sub-soil Grama-grass, No timber.

	Thence I run N. 89° 57' E. on random line bet. secs. 24 & 25
40.00	Set temp. 1/4 sec. cor.
80.04	Intersect E. bdy. of Tp. 13 lks. N. of cor. of secs. 19, 24, 25 & 30, reestablished by means described in Book 10 of G. 22
	Thence I run N. 89° 57' W. on true line bet. secs. 24 & 25 Over level land along S. side of wire fence.
10.00	Wire fence bears S. 89° W., N. 89° E., thence along N. side of fence
190 0	Wire fence bears N. & S., Cor. of fence bears S. 3 lks. dist. from which, fences run N. & N. 89° E.
26.00	Ruins of old adobe house bears N. 25 lks. dist.
40.02	Set an iron post 3 ft. long, 1 in. in dia. 26 1/2 ins. in ground for reestablishment of sec. cor., with a brass cap marked 1/4 S 24 in N. & S 25 19 1/3 in S. half of post
44.00	Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
45.30	Small adobe house bears S. 3 chs. dist.
59.60	Wagon road bears N. 51° W., S. 15° E.
79.84	Wire fence bears N. & S.
80.04	Wire fence bears N. & S. SE. cor. brs, S. 1.00 ch. dist. The cor. of secs. 23, 24, 25 & 26, hereinbefore described. Land level. Soil, loose dark sandy loam, medium texture, 18 to 24 ins deep on clay sub-soil. Grama-grass. No timber. At the above described cor. I set off 20° 22' S. on decl. arc, and at 11h. 49m. 16s., a.m., 1.m.t., observe the sun on the mer. and obtain a reading of 32° 32' on lat. arc.


	Thence I run N. 0° 02' W. bet. secs. 23 & 24
40.00	Along W. side of wire fence over level land Set an iron post 3 ft. long, 1 in. in dia. 26 1/2 ins. in ground for reestablishment of sec. cor., with a brass cap marked 1/4 S 23 in W., S 24 in E. & 19 1/3 in S. half. of post
60.25	Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 5 1/2 ft. base 1 1/2 ft. high W. of cor.
60.25	From above described cor. cor. of wire fence bears E. 20 lks. dist., from which, fences run N., S. & W.
60.25	Wire fence bears E. & W., cor. of wire fence bears E. 20 lks. dist., from which, fences run S. & W.
61.50	Wagon road bears N.W. & S.E.
80.00	Set an iron post 3 ft. long, 2 ins. in dia. 24 1/2 ins. in ground for reestablishment of cor. of secs. 13, 14, 23 & 24, with a brass cap

RESURVEY OF SUBDIVISION LINES

BOOK 2732


RESURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

marked T 10 S R 22 E in N. & 1913 in S. half, S 14 in N.W., S 13 in N.E., S 24 in S.E. & S 23 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose dark sandy loam, 18 to 24 ins. deep, medium texture, on clay sub-soil
 Grama-grass.
 No timber.




Thence I run
 S. 89° 57' E. on random line bet. secs, 13 & 24
 40.00 Set temp. 1/4 sec. cor.
 80.00 Intersect E. bdy. of Twp. 7 lks. S. of the cor. of secs. 13, 18, 19 & 24, reestablished by me as described in Book "C" of Group 22

Thence I run
 West on true line bet. secs. 13 & 24
 Over level prairie land, through scattering mesquite brush 2 to 3 ft. high
 40.04 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestablish sec. cor., with a brass cap marked 1/4 S 13 in N., S 24 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 40.10 S.E. cor. of wire fence bears N. 30 lks. dist., thence parallel to & 30 lks. S. of wire fence
 59.50 Wire fence bears N. & S., cor. of wire fence bears N. 30 lks. dist., from which, fences run E., W. & S. Continue along S.
 65.00 Adobe house, bears N. 15 chs. dist. of wire fence.
 79.60 S.W. cor. of wire fence bears N. 30 lks. dist.
 80.08 The cor. of secs. 13, 14, 23 & 24, hereinbefore described.
 Land level
 Soil, loose sandy loam, medium texture, 18 to 24 ins. deep on clay sub-soil.
 Good grama-grass, very scattering mesquite brush 2 to 3 ft. high.
 No timber.



Thence I run
 N. 0° 02' W. bet. secs. 13 & 14
 Over level prairie land
 .30 SW. cor. of wire fence bears E. 50 lks. dist.
 20.50 Wire fence bears E. & W., cor. of fence bears E. 50 lks. dist. from which, fences run E., W., N. & S.
 21.00 Wagon road bears N.W. & S.E.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestablish sec. cor., with a brass cap marked 1/4 S 14 in W., S 13 in E. & 1913 in S. half: of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 From the above described cor. N.W. cor. of wire fence bears E. 50 lks. dist.
 42.00 Wagon road bears E. & W.
 60.50 Wire fence bears E. & W., SE. cor. of fence bears E. 50 lks. dist., thence along W. side of fence.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestablish cor. of secs. 11, 12, 13 & 14, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 11 in N.W., S 12 in N.E., S 13 in S.E. & S 14 in S.W. quadrant
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level
 Soil, loose sandy loam, medium texture, 18 to 24 ins. deep on clay sub-soil.
 Good grama-grass, scattering yuccas 3 to 7 ft. high.
 No timber.



RESURVEY OF SUBDIVISION LINES
RE - SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST.

- Thence I run
 ✓ East on random line bet. secs. 12 & 13
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.14 Intersect E. bdy. of Tp. 2 lks. N. of cor. of secs. 7, 12, 13 & 18, reestab. by means described in Book "C" of Group 22
 Thence I run
 ✓ N. $89^{\circ} 59'$ W. on true line bet. secs. 12 & 13
 Over level prairie land through scattering yuccas and mesquite brush 3 to 7 ft. high
 40.07 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 12 in N. & S 13 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. $\sqrt{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 79.40 Wagon road bears N. & S.
 79.65 Wire fence bears N. & S., N.E. cor. of wire fence bears N. 70 lks. dist.
 80.14 The cor. of secs. 11, 12, 13 & 14, hereinbefore described.
 Land level.
 Soil, loose sandy loam, medium texture, 18 to 24 ins. deep on clay sub-soil.
 Good grama-grass, scattering yuccas & mesquite brush 3 to 7 ft. high.
 No timber.

Jan. 19th 1914.

Jan., 21, 1914

Jan. 21 At 9 h. 0 m. a.m., l.m.t., I set off $19^{\circ} 57\frac{1}{2}'$ S. on decl. arc, $32^{\circ} 34'$ on lat. arc and determine a mer. with the solar at the cor. of secs. 11, 12, 13 & 14, hereinbefore described.

- Thence I run
 ✓ N. $0^{\circ} 02'$ W. bet. secs. 11 & 12
 Over level prairie land through scattering mesquite brush & yuccas 3 to 7 ft. high.
 .70 Wire fence bears E. & W. NE. cor. of fence brs. E., 50 lks.
 17.00 Wagon road bears N.E. & S.W.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 11 in W., S 12 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. $\sqrt{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 41.00 Wagon road bears N.E. & S.W.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 1, 12, 11 & 12, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 2 in N.W., S 1 in N.E., S 12 in S.E. & S 11 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose sandy loam, 18 to 24 ins. deep, medium texture, on clay sub-soil.
 Good grama-grass, scattering yuccas & mesquite brush 3 to 7 ft. high.
 No timber.

- Thence I run
 ✓ S. $89^{\circ} 59'$ E. on random line bet. secs. 1 & 12
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80, 18 Intersect E. bdy. of Tp. 5 lks. N. of the cor. of secs. 1, 6, 7 & 12, reestab. by means described in Book "C" Grp. 22
 Thence I run
 ✓ N. $89^{\circ} 57'$ W, on true line bet. secs. 1 & 12
 Over level prairie land, through scattering mesquite brush & yuccas 3 to 7 ft. high
 40.09 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 1 in N. & S 12 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. $\sqrt{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.

RESURVEY OF SUBDIVISION LINES
RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

59.25 Wagon road, bears N.E. & S.W.
 80.18 The cor. of secs, 1, 2, 11 & 12, hereinbefore described.
 Land level
 Soil, loose sandy loam, medium texture, 18 to 24 ins.
 deep on clay sub-soil.
 Good grama-grass, scattering yuccas & mesquite brush 3
 to 7 ft. high.
 No timber.

 Thence I run
 N. 0° 02' W. on random line bet. secs. 1 & 2
 40.00 Set temp. 1/4 sec. cor.
 79.86 Intersect N. bdy. of Tp. 14 lks. W. of cor. of secs. 1,
 2, 35 & 36, reestab. by me as described in Book "C" of me.
 Group 22
 Thence I run,
 S. 0° 04' W. on true line bet. secs. 1 & 2
 Over level prairie land
 30.00 Dry wash, 30 lks. wide, 1 ft. deep, course S.W.
 39.86 Set an iron post 3 ft. long, 1 in. in dia. 262 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 2 in
 W., S 1 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 79.86 The cor. of secs. 1, 2, 11 & 12, hereinbefore described.
 Land level
 Soil, loose red sandy loam, medium texture, 18 to 24 ins.
 deep on clay sub-soil.
 Good grama-grass.
 No timber

Jan. 21st, 1914.

 Jan 20, 1914; At 8 h. 30 m., a.m., l.m.t, I set off 29° 10' S.
 on decl. arc, 32° 30 1/2' on lat. arc and determine a mer.
 with the solar at the Standard cor. of secs. 34 & 35, on the
 2nd St. Par. St. reestab. by me as described in Book "B" of
 Thence I run
 N. 0° 02' W. bet. secs. 34 & 35
 Over level land
 20.00 S.E. cor. of wire fence, bears W. 10 lks. dist.
 34.00 Dry bed of Ash Creek, 25 lks. wide, 2 ft. deep, course E.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 262 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 34 in
 W. S 35 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 58.50 Irrigation ditch, 10 lks. wide 1 ft. deep, course East
 60.00 Cor. of wire fence bears W. 3 lks. dist, fences run N.S. & W.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 242 ins. in ground
 for reestab. cor. of secs. 26, 27, 34 & 35, with a brass cap
 marked T 10 S R 22 E in N. & 1913 in S. half, S 27 in N.W.,
 S 26 in N.E., S 35 in S.E. & S 34 in S.W. quadrant.,
 Dig pits 18 x 18 x 12 ins. in each sec 5 1/2 ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor..
 Land level.
 Soil, loose red sandy loam, medium texture, 18 to 24 ins.
 deep on clay sub-soil
 Grama & bunch grass, scattering yuccas 3 to 7 ft. high
 No timber, except for scattering walnut trees along bank
 of Ash Creek.

 The cor. of secs. 25, 26, 35 & 36, being plainly visible,
 I run
 N. 89° 56' E. on random line bet. secs. 26 & 35 for said
 cor.
 40.00 Set temp. 1/4 sec. cor.
 80.10 Intersect the cor. of secs. 25, 26, 35 & 36, hereinbe-
 for described.
 Thence I run

RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

	S. 89° 56' W. on true line bet. secs. 26 & 35
	Over level land
34.00	Wagon road bears N.W. & S.E.
40.05	Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 26 in N. & S 35 1913 in S. half. of post
	Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
75.00	Wagon road bears N.W. & S.E.
80.10	The cor. of secs. 26, 27, 34 & 35, hereinbefore described.
	Land level
	Soil, loose sandy loam, medium texture, 18 to 24 ins. deep on clay sub-soil.
	Short grama-grass.
	No timber.

	Thence I run
	N. 0° 02' W. bet. secs. 26 & 27
	Over level prairie land along E. side of wire fence.
.80	Cor of wire fence bears W. 50 lks. dist, fences run N.S. & W.
2.00	Dim wagon road bears N.W. & S.E.
35.00	Wire fence bears N. $\frac{1}{2}$ ° E., S. $\frac{1}{2}$ ° W., thence along W. side of fence.
40.00	Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 27 in W., S 26 in E. & 1913 in S. half. of post
	Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
40.50	Wire fence bears E. & W., Cor. of wire fence bears E 3 lks. dist, from which, fences run N., S., E. & W.
80.00	Set an iron post 3 ft. long, 2 ins. in dia. 26 ins. in ground for reestab. cor. of secs. 22, 23, 26 & 27, with a brass cap marked T 10 S R. 22 E in N. & 1913. in S. half, S 22 in N.W., S 23 in N.E., S 26 in S.E. & S 27 in S.W. quadrant.
	Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
	Land level
	Soil, loose red sandy loam, medium texture, 18. to 24 ins. deep on clay sub-soil
	Short grama-grass
	No timber.
	Note: the N. half of this mile runs parallel to & 1 ch. W. of wire fence.

	Thence I run
	N. 89° 56' E. on random line bet. secs. 23 & 26
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Fall 2 lks. N. of cor. of secs. 23, 24, 25 & 26, hereinbefore described.
	Thence I run
	S. 89° 57' W. on true line bet. secs. 23 & 26
	Over level prairie land parallel to & 1 ch. N. of wire fence.
35.00	Small cabin bears N. 3 chs. dist.
39.50	Wire fence bears N. & S., cor. of wire fence bears S. 1 ch. dist., from which, fences run N., S., E. & W.
40.04	Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 23 in N. & S 26 1913 in S. half. of post
	Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
41.00	Wagon road bears N. & S.
79.00	N.W. cor. of wire fence bears S, 50 lks. dist.
79.25	Wagon road bears N. & S.
80.08	The cor. of secs. 22, 23, 26 & 27, hereinbefore described.
	Land level
	Soil, loose sandy loam, medium texture, 18 to 24 ins. deep on clay sub-soil.
	Short grama grass
	No timber.

Thence I run N. 0° 02' W. bet. secs. 22 & 23
 Over level prairie land
 30.00 Wagon road, bears N.W. & S.E.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 262 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 22 in
 W., S 23 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 Note: At the above described cor. I set off 20° 09 1/2' S. on decl.
 arc, and at 11 h. 48 m. 40 s., a.m., l.m.t., observe the
 sun on the mer. and obtain a reading of 32° 32 1/2' on lat. arc.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 242 ins. in ground
 for reestab. cor. of secs. 14, 15, 22 & 23, with a brass cap
 marked T 10 S R 22 E in N. & 1913 in S. half, S 15 in N.W.,
 S 14 in N.E., S 23 in S.E. & S 22 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose sandy loam, medium texture, 18 to 24 ins. deep
 on clay sub-soil.
 Short grama-grass.
 No timber.

 Thence I run
 N. 89° 57' E. on random line bet. secs. 14 & 23
 40.00 Set temp. 1/4 sec. cor.
 80.06 Fall 12 lks. S. of the cor. of secs. 13, 14, 23 & 24, here-
 inbefore described.
 Thence I run
 S. 89° 52' W. on true line bet. secs. 14 & 23
 Over level prairie land
 10.00 Wagon road bears N. 15° W., S. 15° E.
 20.00 Wire fence bears N. & S.
 40.03 Set an iron post 3 ft. long, 1 in. in dia. 262 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 14 in
 N. & S 23 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 46.00 Wagon road bears N. & S.
 80.06 The cor. of secs. 14, 15, 22 & 23, hereinbefore described.
 Land level.
 Soil, loose sandy loam, medium texture, 18 to 24 ins.
 deep on clay sub-soil
 Short grama-grass
 No timber.

 Thence I run
 N. 0° 02' W. bet. secs. 14 & 15
 Over level prairie land
 22.00 Wagon road bears N.E. & S.W.
 39.90 Wagon road bears E. & W.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 262 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 15 in
 W., S 14 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 40.15 Wire fence bears E. & W.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 242 ins. in ground
 for reestab. cor. of secs. 10, 11, 14 & 15, with a brass cap
 marked T 10 S R 22 E in N. & 1913 in S. half, S 10 in N.W.,
 S 11 in N.E., S 14 in S.E. & S 15 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high N. of cor.,
 Land level.
 Soil, loose sandy loam, medium texture, 18 to 24 ins.
 deep on clay sub-soil.
 Short grama-grass
 No timber.

RESURVEY OF SUBDIVISION LINES
RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

Thence I run
 ✓ N. 89° 52' E. on random line bet. secs. 11 & 14
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.04 Fall 2 lks. N. of cor. of secs. 11, 12, 13, & 14, herein-
 before described.
 Thence I run
 ✓ S. 89° 55' W. on true line bet. secs. 11 & 14
 Over level prairie land, parallel to & 70 lks. S. of wire fence
 14.00 Wire fence, brs. N. & S. Cor. brs. N. 70 lks., from which, fences
 14.00 run E. & S. brs. N. & S., enter cultivated land.
 38.00 House bears S. 7 chs. dist.
 38.50 Wagon road bears N. & S., leave cultivated land
 40.02 Set an iron post 3 ft. long, 1 in. in dia. 262 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 11 in
 N. & S 11 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 42.00 Leave cultivated land, bears N. & S.
 46.00 Wire fence brs. N. & S. Cor. brs. N. 70 lks., fences run E. W. & S.
 47.00 Small adobe house bears N. 15 chs. dist. pasture.
 60.00 Wire fence, N. & S. Cor. brs. N. 70 lks., fences N. S. & E., enter
 80.04 The cor. of secs. 10, 11, 14 & 15, hereinbefore described.
 Land level
 Soil, loose sandy loam, 18 to 24 ins. deep, on clay sub-
 soil, medium texture.
 Grama-grass
 No timber,

Jan. 21, 1914.

Jan. 20. 1914.
 Thence I run
 N. 0° 02' W. bet. secs. 10 & 11. Over level prairie land.
 24.00 Wire fence, brs. E. & W. thence W. of N. & S. line of fence.
 24.00 Cor. brs. E. 50 lks. from which, fences run E., W. & N. fence.
 37.00 Wagon road bears N. 60° W. S 60° E.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 262 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 10 in
 W., S 11 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 43.00 House bears W. 12 chs. dist.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 242 ins. in ground
 for reestab. cor. of secs. 2, 3, 10 & 11, with a brass cap
 marked T 10 S R 22 E in N. & 1913 in S. half, S 3 in N.W.,
 S 2 in N.E., S 11 in S.E. & S 10 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose, sandy loam, medium texture, 12 to 18 ins.
 deep on clay sub-soil.
 Grama-grass
 No timber.

Thence I run
 ✓ N. 89° 53' E. on random line bet. secs. 2 & 11
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.04 Fall 4 lks. S. of the cor. of secs. 1, 2, 11 & 12, herein-
 before described.
 Thence I run
 ✓ S. 89° 51' W. on true line bet. secs. 2 & 11
 Over level prairie land
 5.50 Dry wash, 20 lks wide, 1 ft. deep, course S.W.
 38.00 Wire fence bears N. & S., N.E., cor. of fence bears N.
 8 lks. dist., thence parallel to & S. of wire fence.
 40.02 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 2 in
 N. S 11 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 79.50 Wire fence bears N. & S., cor. of fence bears N. 7 lks.
 dist., from which, fences run E., W. & S.

RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST


BOOK 2732

80.04 The cor. of secs. 2, 3, 10 & 11, hereinbefore described.
 Land level.
 Soil, loose, red sandy loam, medium texture, 12 to 18 ins deep on clay sub-soil.
 Good grama-grass
 No timber.



Thence I run
 N. 0° 02' W. on random line bet. secs. 2 & 3
 40.00 Set temp. 1/4 sec. cor.
 80.09 Intersect N. bdy. of Tp. 8 lks. W. of the cor. of secs. 2, 3, 34 & 35, reestab. by me as described in Book "C" of me. Group 22
 Thence I run
 S. 0° 01' W. on true line bet. secs. 2 & 3
 Over level prairie land
 39.75 Dim wagon road bears N.E. & S.W.
 40.09 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 3 in W., S 2 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 80.02 Wire fence bears E. & W. Cor. brs. E. 50 lks., fences E., W. & S.
 80.09 The cor. of secs. 2, 3, 10 & 11, hereinbefore described.
 Land level.
 Soil, loose red sandy loam, medium texture, 18 to 18 ins. deep on clay sub-soil.
 Good grama-grass, scattering yuccas 3 to 7 ft. high.
 No timber.

Jan. 20th, 1914.



Jan. 22 1914
 At 8 h. 20 m., a.m., 1m., t., I set off 19° 44' S. on decl. arc, 32° 30 1/2' on lat. arc and determine a mer. with the solar at Std. cor. of secs. 33 & 34, on 2nd Std. Par. S., reestab. by me as described in Book "B" of this Group.
 Thence I run
 N. 0° 03' W. bet. secs. 33 & 34
 Over level land through mesquite brush 5 to 7 ft. high
 .50 S.E. cor. of wire fence bears W. 50 lks. dist., thence parallel to fence along wagon road.
 20.00 S.W. cor. of wire fence bears E. 50 lks., thence through land, leave mesquite brush, bears E. & W.
 26.00 F.A. Faught's house bears E. 15 chs. dist. & W. H. Morgan's house bears W. 10 chs. dist.
 27.00 Dry bed of Ash Creek, 25 lks. wide, 3 ft. deep, course East
 29.00 Shallow well bears W. 10 lks. dist.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 33 in W., S 34 in E & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 From the above described cor. cor. of wire fence bears W. 50 lks. dist, from which, fences run N., S. & W.
 43.00 Susan C. Morgan's house bears W. 2 chs. dist.
 60.00 Cor. of wire fence bears E. 50 lks. dist., fences run N.S. & E.
 62.00 Irrigation ditch, 10 lks. wide, 1 ft. deep, course East.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground reestab. cor. of secs. 27, 28, 33 & 34, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 28 in N.W., S 27 in N.E., S 34 in S.E. & S 33 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose sandy loam, medium texture, 24 to 30 ins. deep,
 Grama-grass, mesquite brush 5 to 7 ft. high.
 Scattering walnut trees along creek.



RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

- The cor. of secs. 26, 27, 34 & 35, being plainly visible,
I run
N. 89° 45' E. for said cor. on random line bet. secs. 27
& 34
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
80.02 Intersect the cor. of secs. 26, 27, 34 & 35, hereinbefore described. Thence I run,
S. 89° 45' W. on true line, bet. secs. 27 & 34
Over level prairie land bet. secs. 27 & 34
- .50 Wire fence, brs. N. & S., cor. of wire fence brs. N. 80 lks.
.50 dist., thence parallel to, and 80 lks. of wire fence N. 80
From said cor. fences run N., S. & W. lks. S. of wire fence.
- 40.01 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
for reestab. sec. cor., with a brass cap marked $\frac{1}{4}$ S 27 in
N. & S 34 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
From the above described cor. A. C. Jesse's house bears
S. 2° E. 40 chs. dist., also cor. of wire fence bears N.
80 lks. dist., from which, fences run E., W. & N.
- 79.50 Wire fence bears N. & S. NW. cor. of fences brs. N. 80 lks.
80.02 The cor. of secs. 27, 28, 33 & 34, hereinbefore described.
Land level.
Soil, loose red sandy loam, 12 to 18 ins. deep on clay
sub-soil, medium texture
Scattering grama-grass
No timber.
-
- Thence I run
N. 0° 03' W. bet. secs. 27 & 28
Over level prairie land, along wagon road.
- .80 Cors. of wire fences bear E. & W. 50 lks. dist. each, leave
lane
- 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
for reestab. sec. cor., with a brass cap marked $\frac{1}{4}$ S 28 in
W., S 27 in E. & 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of cor.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in ground
for reestab. cor. of secs. 21, 22, 27 & 28, with a brass cap
marked T 10 S R 22 E in N. & 1913 in S. half, S 21 in N.W.,
S 22 in N.E., S 27 in S.E. & S 28 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
raise mound of earth 4 ft. base 2 ft. high W. of cor..
Land level.
Soil, loose red sandy loam, 12 to 18 ins. deep on clay-
sub-soil, medium texture.
Short grama-grass.
No timber.
-
- Thence I run
N. 89° 45' E. on random line bet. secs. 22 & 27
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
79.92 Fall 5 lks. S. of cor. of secs. 22, 23, 26 & 27, hereinbefore described.
- Thence I run
S. 89° 43' W. on true line bet. secs. 22 & 27
Over level prairie land
- 39.96 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
for reestab. sec. cor., with a brass cap marked $\frac{1}{4}$ S 22 in
N. & S 27 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise
mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 79.80 Wagon road bears N. & S.
79.92 The cor. of secs. 21, 22, 27 & 28, hereinbefore described.
Land level.
Soil, loose red sandy loam, 12 to 18 ins. deep on clay
sub-soil.
Short grama-grass.
No timber.
-

RESURVEY OF SUBDIVISION LINES
RESURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

Thence I run
 ✓ N. 0° 03' W. bet. secs. 21 & 22
 Over level prairie land along wagon road
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 1/2 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 21 in
 W., S 22 in E. & 19 1/3 in S, half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 40.25 S.W. cor. of wire fence bears E. 50 lks. dist., thence par-
 allel to & 50 lks. W. of wire fence.
 76.00 Log cabin bears E. 2 chs. dist.
 79.50 N.W. cor. of wire fence bears E. 50 lks. dist.
 79.90 Wagon road bears E. & W.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 1/2 ins. in ground
 for reestab. cor. of secs. 15, 16, 21 & 22, with a brass cap
 marked T 10 S R 22 E in N. & 19 1/3 in S. half, S 16 in N.W.,
 S 15 in N.E., S 22 in S.E. & S 21 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise
 mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose red sandy loam, medium texture, 12 to 18 ins.
 deep on clay sub-soil.
 Short grama-grass
 No timber.

Thence I run
 ✓ N. 89° 43' E. on random line bet. secs. 15 & 22
 40.00 Set temp. 1/4 sec. cor.
 79.92 Intersect the cor. of secs. 14, 15, 22, & 23, hereinbefore
 described.
 Thence I run
 ✓ S. 89° 43' W. on true line bet. secs. 15 & 22
 Over level prairie land
 16.00 Wagon road bears N.E. & S.W.
 23.00 Wagon road bears S. 20° E. N 20° W.
 58.00 Small adobe house bears N. 3 chs. dist.
 39.96 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 15 in
 N. & S 22 19 1/3 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 From the above described cor. S.E. cor. of wire fence bears
 N. 30 lks. dist. thence along S. side of wire fence.
 60.00 N.E. cor. of wire fence bears S. 60 lks. dist., thence
 through lane
 79.50 Cors. of wire fences bear N. & S. 50 lks. dist. each.
 79.92 The cor. of secs. 15, 16, 21 & 22, hereinbefore described.
 Land level.
 Soil, loose red sandy loam, medium texture, 12 to 18 ins.
 deep on clay sub-soil.
 Short grama-grass
 No timber.

Note At the above described cor. I set off 19° 43' S. on decl.
 arc and at 12 h. 46 m. 36 s., a.m., l.m.t., observe the sun
 on the mer. and obtain a reading of 32° 33' on lat. arc.

Thence I run
 ✓ N. 0° 03' W. bet. secs. 15 & 16
 Over level prairie land
 .50 Cors. of wire fences bear E. & W. 50 lks. dist. each,
 thence through lane.
 3.00 School house bears E. 2 chs. dist.
 6.00 Shallow well bears W. 2 chs. dist.
 25.00 Small cabin bears E. 1 ch. dist.
 31.00 Dry wash 20 lks. wide, 1 ft. deep, course East
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 1/2 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 16 in
 W., S 15 in E. & 19 1/3 in S. half.

RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

of post
 Dig pits 18 x 18 x 12 ins. N. & S. $3\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 From the above described cor. N.W. cor. of wire fence bears E. 50 lks. dist. leave lane, thence along road E. of fence.
 63.00 Fork in wagon road, one branch bears N.E., the other continues along line
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. $24\frac{1}{2}$ ins. in ground for reestab. cor. of secs. 9, 10, 15 & 16, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 9 in N.W., S 10 in N.E. S 15 in S.E. & S 16 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose red sandy loam, 12 to 18 ins. deep on clay sub-soil, medium texture.
 Short grama-grass
 No timber.

 Thence I run
 N. $89^{\circ} 43'$ E. on random line bet. secs. 10 & 15
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.84 Fall 5 lks. S. of cor. of secs. 10, 11, 14 & 15, hereinbefore described.

Thence I run
 S. $89^{\circ} 41'$ W. on true line bet. secs. 10 & 15
 Over level prairie land
 28.00 Ruins of old adobe house on line
 39.90 Wire fence bears N. & S., NE. SE. cor. of fence bears N. 50 lks. dist., thence parallel to & S. of wire fence.
 39.92 Set an iron post 3 ft. long, 1 in. in dia. $26\frac{1}{2}$ ins. in ground for reestab. sec. cor., with a brass cap marked $\frac{1}{4}$ S 10 in N. & S 15 1913 in S. half.

of post
 Dig pits 18 x 18 x 12 ins. E. & W. $3\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 64.00 E. Smith's house bears N. 3 chs. dist.
 66.00 Wagon road bears N.W. & S.E.
 67.00 ~~Wagon road~~ bears N.E. & S.W.
 79.00 Wagon road bears N.W. & S.E.
 79.34 S.W. cor. of wire fence bears N. 50 lks. dist.
 79.84 The cor. of secs. 9, 10, 15 & 16, hereinbefore described.
 Land level.
 Soil, loose red sandy loam, 12 to 18 ins. deep on clay sub-soil, medium texture.
 Short grama-grass
 No timber.

 Thence I run
 N. $0^{\circ} 03'$ W. bet. secs. 9 & 10
 Over level prairie land
 .10 Cor. of wire fence bears W. 50 lks. dist, fences run N.S. & W.
 .50 S.W. cor. of wire fence bears E. 50 lks. dist., thence through lane.

40.00 Set an iron post 3 ft. long, 1 in. in dia. $26\frac{1}{2}$ ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 9 in W., S 10 in E. & 1913 in S. half. Dig pits 18x18x12 ins. N. & S. of post $3\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor. NW, SW fence cor. E. 50 lks. NE. SE fence cor. W. 50 lks.
 49.00 Irrigation ditch 3 lks. wide, 1 ft. deep, course S.E.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. $24\frac{1}{2}$ ins. in ground for reestab. cor. of secs. 3, 4, 9 & 10, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 4 in N.W., S 3 in N.E., S 10 in S.E. & S 9 in S.W. quadrant.
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil, loose red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil.
 Short grama-grass
 No timber.

RESURVEY OF SUBDIVISION LINES
RE-CORRECTION OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

40.00 Thence I run
N. 39°41' E. on random line bet. secs. 3 & 10
Set temp. 1/4 sec. cor.
79.76 Fall 3 lks. N. of cor. of secs. 2, 3, 10 & 11, hereinbefore described.
Thence I run
S. 89° 42' W. on true line bet. secs. 3 & 10
Over level prairie land parallel to & S. of wire fence.
39.25 Wire fence bears N. & S., cor. of wire fence bears N. 15
39.38 lks. dist, from which, fences run E., W. & S.
39.88 Set an iron post 3 ft. long, 1 in. in dia. 26 1/2 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 3 in N. & S 10 1913 in S. half. of post
Dig pits 18 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
79.15 Wire fence bears N. & S., cor. of fence bears N. 50 lks. dist, from which, fences run E. & S.
79.76 The cor. of secs. 3, 4, 9 & 10, hereinbefore described.
Land level
Soil, loose red sandy loam, medium texture 12 to 18 ins. deep on clay sub-soil.
Good grama-grass
No timber.

The cor. of secs. 3, 4, 33 & 34, on N. bdy. of Tp. being plainly visible, I run,
N. 0° 09' W. for said cor. on true line bet. secs. 3 & 4
Over slightly rolling prairie land through lane
.50 N.W. cor. of wire fence bears E. 50 lks. dist. & N.E. cor. of wire fence bears W. 40 lks. dist., leave lane thence over open prairie land
.70 Wagon road turns N.W.
40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 1/2 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 4 in W., S 3 in E. & 1913 in S. half. of post
Dig pits 18 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
80.38 Intersect N. bdy. of Tp. at the cor. of secs. 3, 4, 33 & 34, reestab. by means described in Book "C" of Group 22
Land level & rolling
Soil, loose red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil.
Good grama-grass
No timber.

Jan. 22nd, 1914.

Jan. 23, 1914
Jan. 23rd At 8 30 m., a.m., l.m.t., I set off 19° 29 1/2' S. on decl. arc, 32° 30 1/2' on lat. arc and determine a mer. with the solar at the Standard cor. of secs. 32 & 33, on 2nd Stdy. Eas. S. reestab. by means described in Book "B" of this Group.
Thence I run
N. 0° 03' W. bet. secs. 32 & 33
Over level land through greasewood and sage brush 2 to 3 ft. high
.60 Wire fence bears E. & W. SE. SW. fence cor. brs W. 50 lks. dist., thence parallel to & 50 lks. E. of wire fence.
31.00 Dry bed of Ash Creek course East, leave greasewood & Sagebrush
39.50 Wire fence bears E. & W., one NW fence cor. bears W. 50 lks., enter cultivated land
40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 32 in W., S 33 in E. & 1913 in S. half. of post
Dig pits 18 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
Note: I found the original cor. stone, which is a granite stone 15 x 8 x 4 ins. plainly marked lying loose on top of ground on line 50 lks. S. of cor. Destroy all trace of old cor.
From 1/4 sec. cor. to C.W. Addington's house brs N. 89 1/2° E., 15 lks. dist.
44.50 Irrigation ditch, 10 lks. wide, 2 ft deep, course E. level
50.00 Leave cultivated land, brs E. & W., thence over level prairie land.

RESURVEY OF SUBDIVISION LINES
RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24¹/₂ ins. in ground for reestab. cor. of secs. 28, 29, 32 & 33, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 29 in N.W., S 28 in N.E., S 33 in S.E. & S 32 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. 5¹/₂ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
From the above described cor. the old cor. for the above numbered secs, which is a basalt stone 8 x 10 x 5 ins., firmly set & marked as described by Surveyor General, bears S. 21¹/₄° W. 17 lks. dist., I destroy all trace of this old cor. I also destroy all trace of the old cor. on this side.
Note: From the 1/4 sec. cor. bet. secs. 32 & 33 N.W. Addington's house bears N. 39¹/₂° W. 13 chs. dist.
Land level & rolling
Soil, dark sandy loam, medium to coarse texture, 12 to 24 ins deep on clay sub-soil.
Short grass, grease wood & sage brush 2 to 3 ft. high on S. end of line.
Scattering walnut along banks of Ash Creek.

Thence I run
S. 89° 59' E. on random line bet. secs. 28 & 33
40.00 Set temp. 1/4 sec. cor.
80.04 Intersect the cor. of secs. 27, 28, 33 & 34, hereinbefore described.
Thence I run
N. 89° 59' W. on true line bet. secs. 28 & 33
Over level prairie land
.20 Wagon road bears N. & S.
.50 Wire fence bears N. & S. N.E. cor. of wire fence bears N. 80 lks. dist., thence parallel to & 80 lks. S. of wire fence.
40.02 Set an iron post 3 ft. long, 1 in. in dia. 26²/₃ ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 28 in N. S 33 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3¹/₂ ft. base 1¹/₂ ft. high N. of cor.
40.11 Intersect old 1/4 sec. cor. which is a granite stone 12 x 5 x 6 ins. firmly set & marked as described by the Surveyor General, which I destroy.
Wire fence bears N. & S., cor. of fence bears N. 80 lks. dist. from which, fences run N., S. & E.
60.00 Wire fence bears N. & S., N.E. cor. of fence bears N. 50 lks. dist., thence parallel to & 50 lks. S. of wire fence
79.50 Cor. of wire fence bears N. 50 lks. dist. fences run E.W. & N.
80.04 The cor. of secs., 28, 29, 32 & 33, hereinbefore described.
Land level
Soil, red sandy loam, medium texture, 12 to 18 ins. deep, on clay sub-soil.
Short grass.
No timber.

Thence I run
N. 0° 03' W. bet. secs. 28 & 29
Over level prairie land
.50 Wire fence bears E. & W., SE. SW. fence cor. bears E. 50 lks. dist., thence parallel to wire fence along wagon road.
39.90 Old 1/4 sec. cor. which is a sand stone 6 x 8 x 4 ins., firmly set & marked as described by Surveyor General, bears W. 14 lks. dist., I destroy all trace of this old cor.
N.W. cor. of wire fence bears E. 50 lks. dist.
40.00 Set an iron post 3 ft. long, 1 in. in dia. 26²/₃ ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 29 in W., S 28 in E. & 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3¹/₂ ft. base 1¹/₂ ft. high W. of cor.
71.00 Dry shallow wash 10 lks. wide, course East.
80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24¹/₂ ins. in ground for reestab. cor. of secs. 20, 21, 28 & 29, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 20 in N.W., S 21 in N.E. S 28 in S.E. & S 29 in S.W. quadrant.

RESURVEY OF SUBDIVISION LINES -15-
RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST.

Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level.
Soil, red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil.
Short grass.
No timber.

40.00 Thence I run
80.06 S. 89° 59' E. on random line bet. secs. 21 & 28
Set temp. 1/4 sec. cor.
Intersect the cor. of secs. 21, 22, 27 & 28, hereinbefore described

40.03 Thence I run
N. 89° 59' W. on true line bet. secs. 21 & 28
Over level prairie land
Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked S 21 in N. & S 28 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

60.00 Wagon road bears N.W. & S.E.
80.06 The cor. of secs. 20, 21, 28 & 29, hereinbefore described.
Land level.
Soil, loose red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil.
Short grass.
No timber.

32.00 Thence I run
N. 0° 03' W. bet. secs. 20 & 21
Over level prairie land along wagon road
Small irrigation ditch 5 lks. wide, 1 ft. deep, course N. 70° E..

40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked S 20 in W., S 21 in E. & 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 5 1/2 ft. base 1 1/2 ft. high W. of cor.

40.20 From the above described cor. S.E. cor. of wire fence bears W. 50 lks. dist., thence parallel to & E. of wire fence, along road.
Small irrigation ditch, 3 lks. wide, 1 ft. deep, course East
79.50 N.E. cor. of wire fence bears W. 50 lks. dist.
79.80 Wagon road bears E. & W.

80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 16, 17, 20 & 21, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 17 in N.W., S 16 in N.E., S 21 in S.E. & S 20 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level.
Soil, loose red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil.
Short grass
No timber.

40.00 Thence I run
80.10 S. 89° 59' E. on random line bet. secs. 16 & 21
Set temp. 1/4 sec. cor.
Intersect cor. of secs. 15, 16, 21 & 22, hereinbefore described.

.50 Thence I run
N. 89° 59' W. on true line bet. secs. 16 & 21
Over level prairie land
S.E. cor. of wire fence bears N. 50 lks. dist., thence S. of wire fence along wagon road.

RESURVEY OF SUBDIVISION LINES


RESURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

- 40.05 Set an iron post 3 ft. long, 1 in. in dia., 26 1/2 ins. in ground for reestablishment of sec. cor., with a brass cap marked 1/4 S 16 in N. & S 21 1913 in S. half.
Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
- 80.00 The cor. of secs. 16, 17, 20 & 21, hereinbefore described.
Land level.
Soil, loose red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil.
Short grass.
No timber.
At the above described cor. I set off 19° 29' S. on decl. arc and at 12 h. 48 m. 53 s., p.m., l.m.t., observe the sun on the mer. and obtain a reading of 32° 33' on lat. arc.
-
- Thence I run
N. 0° 03' W. bet. secs. 16 & 17.
Over level prairie land, through scattering grease wood 1 to 2 ft. high.
- .10 Wire fence bears E. & W.
.50 S.E. cor. of wire fence bears W. 50 lks. dist., thence parallel to & E. of wire fence
20.00 Leave scattering grease wood bears E. & W.
40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 1/2 ins. in ground for reestablishment of sec. cor., with a brass cap marked 1/4 S 17 in W., S 16 in E. & 1913 in S. half. of post
Dig pits 13 x 13 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
From the above described cor. N.E. cor. of wire fence bears W. 50 lks. dist.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 1/2 ins. in ground for reestablishment of cor. of secs. 8, 9, 16 & 17, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 8 in N.W. S 9 in N.E., S 16 in S.E. & S 17 in S.W. quadrant.
Dig pits 13 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor..
Land level.
Soil, loose red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil.
Short grass, scattering grease wood 1 to 2 ft. high at N. end of line.
No timber.
-
- Thence I run
N. 89° 59' E. on random line bet. secs. 9 & 16
- 40.00 Set temp. 1/4 sec. cor.
80.12 Fall 2 lks. S. of cor. of secs. 9, 10, 15 & 16 hereinbefore described.
Thence I run
West on true line bet. secs. 9 & 16
Over level prairie land
- .10 Wagon road bears N. & S.
.50 Wire fence bears N. & S., S.E. fence corner bears N. 10 lks. dist., thence along S. side of fence.
- 40.06 Set an iron post 3 ft. long, 1 in. in dia., 26 1/2 ins. in ground for reestablishment of sec. cor., with a brass cap marked 1/4 S 9 in N. & S 16 1913 in S. half. of post
Dig pits 13 x 13 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
- 79.66 Cor. of wire fence bears N. 70. lks. dist., fences run E.W. & N
80.12 The cor. of secs. 8, 9, 16 & 17, hereinbefore described.
Land level.
Soil, loose red sandy loam, medium texture, 12 to 18 ins. deep on clay sub-soil
Short grass.
No timber.
-


RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

Thence I run
 ✓ N. 0° 03' W. bet. secs. 8 & 9
 Over level prairie land.
 7.70 Wire fence bears E. & W., SE. SW. fence course bears E. 50
 lks. dist., thence parallel to & W. of wire fence.
 1.00 Dim wagon road bears E. & W.
 10.00 L.A. Teel's house bears E. 4 chs. dist.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 8 in W.,
 S 9 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 40.25 N.W. cor. of wire fence bears E. 50 lks. dist.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground
 for reestab. cor. of secs. 4, 5, 8 & 9, with a brass cap
 marked T 10 S R 22 E in N. & 1913 in S. half, S 5 in N.W.,
 S 4 in N.E., S 9 in S.E. & S 3 in S.W. quadrant
 Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level.
 Soil loose red sandy loam, medium texture, 12 to 13 ins.
 deep on clay sub-soil
 Short grass
 No timber.



Thence I run
 ✓ East on random line bet. secs. 4 & 9
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.20 Intersect cor. of secs. 3, 4, 9 & 10, hereinbefore de-
 scribed.
 Thence I run
 ✓ West on true line bet. secs. 4 & 9
 Over level prairie land
 .40 Wire fence bears N. & S., NE. cor. of fence bears N. 50
 lks. dist., thence parallel to & S. of wire fence.
 40.05 Wire fence bears N. & S., N.W. cor. of fence bears N. 50
 lks. dist.
 40.10 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 4 in N.,
 & S 9 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. E. & W. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 80.20 The cor. of secs. 4, 5, 8 & 9, hereinbefore described.
 Land level.
 Soil, loose red sandy loam, medium texture, 12 to 18 ins.
 deep on clay sub-soil
 Short grass
 No timber.



Thence I run
 ✓ N. 0° 03' W. on random line bet. secs. 4 & 5
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.45 Intersect N. bdy. of Tp. 17 lks. W. Of the cor. of secs.
 4, 5, 32 & 32, reestab. by me as described in Book "A" of me.
 This Group, Thence I run,
 ✓ S. 0° 04' W. on true line bet. secs. 4 & 5
 Over rolling land
 5.00 Dry wash 30 lks. wide, 3 ft. deep, course N.E., thence
 ascend rocky N. slope 75 ft.
 30.00 Top of ascent, thence over rolling prairie land
 39.00 Dry gulch, 4 chs. wide 6 ft. deep, course N.E.
 40.45 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 5 in
 W., S 4 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. \wedge 3 ft. dist. & raise
 mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
 45.00 Leave rolling land bears E. & W., thence over level
 prairie land
 80.45 The cor. of secs. 4, 5, 8 & 9, hereinbefore described.

RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

Land level, and rolling.
Soil, loose red sandy loam, medium, texture, 12 to 18 ins. deep on S. half, N. half thin & rocky.
Short grama-grass
No timber.

Jan. 23rd, 1914.

-
- At
Jan. 26th, 1914; 9 h. 0 m., a.m., l.m.t., I set off 18° 46½' S. on decl. arc 32° 30½' on lat. arc and determine a mer. with the solar at the Standard cor. of secs. 31 & 32, on 2nd Std. Par. S. reestab. by me as described in Book "B" of this Group
- Thence I run
N. 0° 04' W. bet. secs. 31 & 32
Over level land through scattering walnut & sycamore trees
- .60 Wire fence bears E. & W., cor. of wire fence bears W, 10 lks. dist., from which, fences run E., W. & N. 2° E.
- 2.00 Wire fence bears N. 2° E., S. 2° W., thence along W. of fence
- 10.00 Dry bed of Ash Creek. 25 lks. wide, 4 ft. deep, course E.
- 11.00 Leave scattering timber, bears E. & W. enter cultivated land.
- 20.00 Irrigation ditch 10 lks. wide, 2 ft. deep, course East.
- 25.00 Leave cultivated land, bears E. & W., thence over rolling prairie land
- 39.82 Intersect old ¼ sec. cor. which is a basalt stone 10 x 4 x 12 ins. firmly set & marked as described by the Surveyor General, I destroy all trace of this old cor.
From the above described old cor. fence lines runs S. 1° E., W., N. 3° W. & East..
- 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. ¼ sec. cor., with a brass cap marked ¼ S 31 in W., S 32 in E. & 1913 in S. half. Pits impracticable.
Raise mound of stone 3 ft. base 3 ft. high W. of cor.
- 53.00 Wire fence bears N.E. & S.W.
- 63.00 Dry shallow wash 15 lks. wide, course N.E.
- 79.83 Old cor. of secs. 29, 30, 31 & 32, which is a basalt stone 8 x 6 x 12 ins. firmly set & marked as described by the Surveyor General bears W. 4 lks. dist. I destroy all trace of this old cor.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 29, 30, 31 & 32, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 30 in N.W., S 29 in N.E., S 32 in S.E. & S 31 in S.W. quad. Pits imprac.
Raise mound of stone 3 ft. base 3 ft. high W. of cor.
Land level & rolling.
Soil, loose sandy loam, fine texture 24 to 30 ins. deep from 0 to 25 chs., 25 to 30 chs. thin rocky, coarse texture 6 to 12 ins. deep on clay sub-soil.
Short grass
Scattering walnut & sycamore trees on S. end of line.
-
- Thence I run
S. 89° 59' E. on random line bet. secs. 29 & 32
- 40.00 Set temp. ¼ sec. cor.
- 80.14 Fall 7 lks. S. of cor. of secs. 28, 29, 32 & 33, herein-before described
- Thence I run
S. 89° 58' W. on true line bet. secs. 29 & 32
- 19.00 Over level prairie land
Wire fence bears N. & S., N.W. cor. of fence bears N. 50 lks. dist.
- 23.00 Foot of rocky butte, bears N. & S., ascend rocky E. slope 300 ft.
- 33.00 Summit of ridge bears N.E. & S.W., thence descend rocky N.W. slope 300 ft.
- 40.07 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. ¼ sec. cor., with a brass cap marked ¼ S 29 in N. & S 32 1913 in S. half. Pits impracticable.
Raise mound of stone 2 ft. base 2 ft. high N. of cor.

RESURVEY OF SUBDIVISION LINES
OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

- 40.18 Old $\frac{1}{4}$ sec. cor. which is a basalt stone 10 x 8 x 5 ins. firmly set & marked as described by Surveyor General, bears S. 10 lks. dist. I destroy all trace of the old cor.
- 67.00 Dry wash 15 lks. wide, 2 ft. deep course N.E.
- 80.14 The cor. of secs. 29, 30, 31 & 32, hereinbefore described.
Land rolling & mountainous
Thin rocky soil
Short grass
No timber.

- Thence I run
- 40.00 S. $89^{\circ} 55'$ W. on random line bet. secs. 30 & 31
- 80.06 Set temp. $\frac{1}{4}$ sec. cor.
- 80.06 Intersect W. bdy. of Tp. at the cor. of secs. 25, 30, 31 & 36, reestab. by me as described in Book "A" of this Group
- Thence I run
- 40.00 N. $89^{\circ} 55'$ E. on true line bet. secs. 30 & 31
- 35.00 Over rolling rocky land
- 35.00 Dry rocky wash, 10 lks. wide, 2 ft. deep, course N.E., thence ascend rocky N.W. slope 200 ft.
- 40.06 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 30 in N. & S 31 1913 in S. half. Pits impracticable.
- 50.00 Raise mound of stone 3 ft. base 2 ft. high N. of cor.
- 50.00 Summit of ridge bears N.E. & S.W., thence along S. of ridge
- 55.00 Begin descent along steep rocky S.E. slope
- 77.00 Foot of slope bears N.E. & S.W.
- 80.06 The cor. of secs. 29, 30, 31 & 32, hereinbefore described.
Land rolling & mountainous
Soil, thin & rocky
Short grass
No timber.

- Thence I run
- 5.00 N. $0^{\circ} 04'$ W. bet. secs. 29 & 30
- 5.00 Over rolling rocky land
- 23.00 Foot of rocky ridge bears N.E. & S.W., thence ascend along rocky S.E. slope 150 ft.
- 23.00 Summit of ridge slopes East, thence descend rocky N. slope 150 ft.
- 33.00 Foot of descent bears E. & W., thence over rolling prairie land
- 39.85 Intersect old $\frac{1}{4}$ sec. cor., which is a basalt stone 6 x 8 x 10 x 10 ins. firmly set & marked as described by the Surveyor General. I destroy all trace of this old cor.
- 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 30 in W., S 29 in E. & 1913 in S. half. Pits impracticable.
- Note: Raise mound of stone 3 ft. base 2 ft. high W. of cor.
- Note: At the above described cor. I set off $18^{\circ} 45'$ S. on decl. arc and at 12 h. 12 m. 36 s., p.m., 1 m. t. observe the sun on the mer. and obtain a reading of $32^{\circ} 32'$ on lat. arc.
- 79.86 The old. cor. of secs. 19, 20, 29 & 30, which is a basalt stone 10 x 12 x 8 ins., firmly set & marked as described by Surveyor General bears E. 9 lks. dist., I destroy all trace of this old cor.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in ground for reestab. cor. of secs. 19, 20, 29 & 30, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 19 in N.W., S 20 in N.E., S 29 in S.E. & S 30 in S.W. quad. Pits imprac.
- 80.00 Raise mound of stone 3 ft. base 3 ft. high W. of cor.
- 80.00 Land rolling
- 80.00 Soil, thin & rocky, coarse texture.
- 80.00 Short grass
- 80.00 No timber.

RESURVEY OF SUBDIVISION LINES

SECTION 19 OF TOWNSHIP 10 SOUTH, RANGE 22 EAST.

Thence I run
 40.00 N. 39° 56' E. on random line bet. secs. 20 & 29
 Set temp. 1/4 sec. cor.
 80.14 Fall 5 lks. N. of the cor. of secs. 20, 21, 23 & 29, here-
 inbefore described.
 Thence I run
 40.05 S. 89° 58' W. on true line bet. secs. 20 & 29
 Over rolling rocky land
 Old 1/4 sec. cor., which is a basalt stone 12x5x6 ins. above ground,
 firmly set & marked as described by Surveyor General, bears
 S 15 lks. dist., I destroy all trace of this old cor.
 40.07 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 20 in
 N. & S 29 1913 in S. half. Pits impracticable.
 Raise mound of stone 2 ft. base 2 ft. high N. of cor.
 80.14 The cor. of secs. 19, 20, 29 & 30, hereinbefore described.
 Land rolling
 Soil, thin & very rocky, coarse texture
 Short grass
 No timber.

 Thence I run
 40.00 S. 89° 55' W. on random line bet. secs. 19 & 30
 Set temp. 1/4 sec. cor.
 79.93 Intersect W. bdy. of Tp. 4 lks. S. of the cor. of secs.
 19, 24, 25 & 30, reestab. by me as described in Book "A" of my
 this Group. Thence I run,
 12.00 N. 39° 57' E. on true line bet. secs. 19 & 30
 Over level prairie land through grease wood 1 to 2 ft. high
 Wire fence bears N. 89° W., S 89° E., thence along N. side
 of fence
 39.93 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 19 in
 N. & S 30 1913 in S. half. Pits impracticable.
 Raise mound of stone 2 ft. base 2 ft. high N. of cor.
 39.95 Wire fence bears N. & S. SE. cor. of fence brs. S. 50 lks.
 Old 1/4 sec. cor. which is a basalt stone 10x6x6 ins. above ground
 firmly set & marked as described by the Surveyor General
 bears S. 13 lks. dist. S.W. cor. of wire fence is along
 side of this old cor. I destroy all trace of this old 1/4
 sec. cor.
 Thence over rolling, rocky land
 79.93 The cor. of secs. 19, 20, 29 & 30, hereinbefore described.
 Land level & rolling.
 Soil, W. half loose sandy loam, medium texture, 18 to 24
 ins., deep on clay sub-soil, E. half thin & rocky, coarse
 texture.
 Short grass, grease wood 1 to 2 ft. high
 No timber.

 Thence I run
 20.00 N. 0° 04' W. bet. secs. 19 & 20
 Over rolling rocky land
 Wire fence bears E. & W., SE. SW. fence cor. bears E. 50
 lks. dist., leave rolling rocky land bears E. & W., thence
 over level prairie land, parallel to & 50 lks. W. of wire
 fence.
 24.00 Enter cultivated land bears E. & W.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. 26 ins. in ground
 for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 19 in
 W., S 20 in E. & 1913 in S. half. of post
 Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
 51.00 Wire fence bears E. & W.
 53.00 D. McGirk's house bears W. 10 chs. dist.
 55.00 Wire fence bears E. & W.
 59.75 Wire fence bears E. & W., leave cultivated land, thence
 over open prairie. Fence cor. brs E. 50 lks.
 68.00 Wagon road bears N.E. & S.W.
 70.00 Dry bed of Oak Creek, 20 lks. wide, 3 ft. deep, course
 N.E.

RESURVEY OF SUBDIVISION LINES

RESURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

79.75 S.W. cor. of wire fence bears E. 50 lks. dist.
 80.00 Set an iron post 3 ft. long, 2 ins. in dia. ~~26~~ 26 ins. in ground
 for reestab. cor. of secs. 17, 18, 19 & 20, with a brass cap
 marked T 10 S R 22 E in N. & 1913 in S. half, S 13 in N.W.,
 S 17 in N.E., S 20 in S.E. & S 19 in S.W. quadrant.
 Dig pits 18 x 13 x 12 ins. in each sec. 5 1/2 ft. dist. &
 raise mound of earth 4 ft. base 2 ft. high W. of cor.
 Land level & rolling
 Soil, from 0 to 20 chs. thin & rocky, coarse texture,
 from 20 to 30 chs. loose red sandy loam, medium texture, 12
 to 18 ins. deep on clay sub-soil.
 Short grass, grease wood 1 to 2 ft. high, scattering mes-
 quite brush 3 to 5 ft. high on N. end of line.
 Scattering blackjack & walnut trees along banks of Oak
 Creek.

Thence I run
 40.00 N. 89° 58' E. on random line bet. secs. 17 & 20
 Set temp. 1/4 sec. cor.
 80.14 Fall 7 lks. N. of the cor. of secs. 16, 17, 20 & 21, here-
 inbefore described.
 Thence I run
 N. 89° 59' W. on true line bet. secs. 17 & 20 fence
 Over level prairie land parallel to & 10 lks. S. of wire/
 .50 Cors. of wire fences bears N. & S. 50 lks. dist. each,
 thence through lane parallel to
 2.00 S.W. cor. of wire fence bears N. 10 lks. dist., fence
 turns N. to N. edge of lane. Continue through lane.
 20.00 H. G. Care of wire fence bears N. 50 lks. dist., fences run E.W. &
 35.00 House bears S. 8 chs. dist. N.
 38.00 House bears S. 8 chs. dist.
 40.07 Set an iron post 3 ft. long, 1 in. in dia. ~~26~~ 26 ins. in ground
 for reestab. cor., with a brass cap marked 1/4 S 17 in
 N. & S 20 1913 in S. half. of post
 Dig pits 18 x 13 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
 From the above described cor. cor. of wire fence bears
 S. 60 lks. dist., from which, fences run E., W. & S.
 41.50 W. H. McGirk's house bears N. 1 ch. dist.
 59.00 Wire fence bears N. 39° E., S. 89° W., leave lane thence
 along N. side of fence
 60.00 Wire fence bears N. & S. SE. SW. cor. brs. S. 2 lks.
 67.50 H. W. Nichol's house bears N. 2 chs. dist.
 68.00 Enter cultivated land bears N. & S.
 73.00 Leave cultivated land bears N. & S.
 75.00 Dry bed of Oak Creek, 20 lks. wide, 3 ft. deep, course N.E.
 79.60 Wire fence bears N. & S. SW. cor. brs. S. 25 lks.
 80.14 The cor. of secs. 17, 18, 19 & 20, hereinbefore described.
 Land level
 Soil, loose red sandy loam, medium texture, 12 to 18 ins.
 deep on clay sub-soil.
 Short grass, scattering mesquite brush 3 to 5 ft. high on
 W. end of line
 Scattering blackjack & walnut trees along banks of Oak
 Creek.

The cor. of secs. 13, 18, 19 & 24, on W. bdy. of Tp. being
 plainly visible, I run
 S. 39° 54' W. for said cor. on true line bet. secs. 18 &
 19
 Over level prairie land through scattering mesquite brush
 3 to 5 ft. high
 10.00 Leave scattering mesquite brush bears N. & S.
 40.00 Set an iron post 3 ft. long, 1 in. in dia. ~~26~~ 26 ins. in ground
 for reestab. cor., with a brass cap marked 1/4 S 18 in
 N. & S 19 1913 in S. half. of post
 Dig pits 18 x 13 x 12 ins. E. & W. 3 ft. dist. & raise
 mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.

RESURVEY OF SUBDIVISION LINES

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST

- 41.00 N.E. cor. of wire fence bears S. 50 lks., thence parallel to & 50 lks. N. of wire fence.
- 79.82 Intersect W. bdy. of Tp. at the cor. of secs. 13, 13, 19 & 24, reestab. by means described in Book "A" of this Group.
Land level
Soil, red adobe 12 to 13 ins. deep on clay sub-soil.
Short scattering grass, scattering mesquite brush 3 to 5 ft. high, on E. end, of line.
No timber.
- Jan. 26th, 1914.
-
- Jan. 27, 1914
At 9 h. 0 m., a.m., l.m.t., I set off 13° 32' S. on decl. arc, 32° 33' on lat. arc and determine a mer. with the solar at the cor. of secs. 17, 18, 19 & 20, hereinbefore described.
Thence I run
N. 0° 04' W. bet. secs. 17 & 18
Over level prairie land, parallel to & 50 lks. W. of wire fence.
- 39.50 N.W. cor. of wire fence bears E. 50 lks. dist.
40.00 Set an iron post 3 ft. long, 1 in. in dia 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 13 in W., S 17 in E. & 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. N. & S. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high W. of cor.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia 24 ins. in ground for reestab. cor. of secs. 7, 8, 17 & 18, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 7 in N.W., S 8 in N.E., S 17 in S.E. & S 18 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level.
Soil, red adobe, 12 to 18 ins. deep on clay sub-soil.
Scattering short grass
No timber.
-
- Thence I run
S. 89° 59' E. on random line bet. secs. 8 & 17
40.00 Set temp. 1/4 sec. cor.
80.10 Fall 5 lks. S. of cor. of secs. 8, 9, 16 & 17, hereinbefore described.
Thence I run
S. 89° 59' W. on true line bet. secs. 8 & 17
Over level prairie land
1.00 Wire fence bears N. & S., N.W. cor. of wire fence bears N. 70 lks. dist.
30.00 Dry shallow wash 30 lks. wide, course N.E.
40.05 Set an iron post 3 ft. long, 1 in. in dia 26 ins. in ground for reestab. 1/4 sec. cor., with a brass cap marked 1/4 S 8 in N. & S 17 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. 3 ft. dist. & raise mound of earth 3 1/2 ft. base 1 1/2 ft. high N. of cor.
- 80.10 The cor. of secs. 7, 8, 17 & 18, hereinbefore described.
Land level.
Soil, red adobe, 12 to 18 ins. deep on clay sub-soil
Short grass.
No timber.
-
- Thence I run
S. 89° 54' W. on random line bet. secs. 7 & 18
40.00 Set temp. 1/4 sec. cor.
79.75 Intersect W. bdy. of Tp. at the cor. of secs. 7, 12, 13 & 18, reestab. by means described in Book "A" of this Group.
Thence I run
N. 89° 54' E. on true line bet. secs. 7 & 18
Over level prairie land
30.00 Dry shallow wash 30 lks. wide, course N.E.

RESURVEY OF SUBDIVISION LINES
IN TOWNSHIP 10 SOUTH, RANGE 22 EAST.

- 39.75 Set an iron post 3 ft. long, 1 in. in dia 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 7 in N. & S 18 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 40.18 Old $\frac{1}{4}$ sec. cor., which is a malpais stone 8x8x10 ins. above ground firmly set & marked as described by Surveyor General, on line. I destroy all trace of this old cor.
- 79.75 The cor. of secs. 7, 8, 17 & 18, hereinbefore described.
Land level.
Soil, red adobe, 12 to 18 ins deep on clay sub-soil
Short grass
No timber.

- Thence I run
- 32.00 N. 0° 04' W. bet. secs. 7 & 8
Over level prairie land
Dry shallow wash 10 lks. wide, course East.
- 40.00 Set an iron post 3 ft. long, 1 in. in dia 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 7 in W., S 8 in E. & 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. N. & S. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
- 55.00 Dry shallow wash 20 lks. wide, course N.E.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia 25 ins. in ground for reestab. cor. of secs. 5, 6, 7 & 8, with a brass cap marked T 10 S R 22 E in N. & 1913 in S. half, S 6 in N.W., S 5 in N.E., S 8 in S.E. & S 7 in S.W. quadrant.
Dig pits 18 x 18 x 12 ins. in each sec. $5\frac{1}{2}$ ft. dist. & raise mound of earth 4 ft. base 2 ft. high W. of cor.
Land level
Soil, red adobe, 12 to 18 ins. deep on clay sub-soil
Scattering short grass
No timber.

- Thence I run
- 40.00 N. 89° 59' E. on random line bet. secs. 5 & 8
Set temp. $\frac{1}{4}$ sec. cor.
- 80.08 Intersect the cor. of secs. 4, 5, 8 & 9, hereinbefore described.
Thence I run
- 40.04 S. 39° 59' W. on true line bet. secs. 5 & 8
Over level prairie land
Set an iron post 3 ft. long, 1 in. in dia 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 5 in N. & S 8 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 80.08 The cor. of secs. 5, 6, 7 & 8, hereinbefore described
Land level
Soil, red adobe, 12 to 18 ins. deep on clay sub-soil
Scattering short grass
No timber.

- Thence I run
- 40.00 S. 89° 54' W. on random line bet. secs. 6 & 7
Set temp. $\frac{1}{4}$ sec. cor.
- 79.69 Intersect W. bdy. of Tp. 12 lks. S. of the cor. of secs. 1, 6, 7 & 12, reestab. by me as described in Book "A" of this Group
Thence I run
- 39.69 N. 89° 59' E. on true line bet. secs. 6 & 7
Over level prairie land
Set an iron post 3 ft. long, 1 in. in dia 26 ins. in ground for reestab. $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 6 in N. & S 7 1913 in S. half. of post
Dig pits 18 x 18 x 12 ins. E. & W. $\frac{1}{3}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

RESURVEY OF SUBDIVISION LINES-

RE-SURVEY OF TOWNSHIP 10 SOUTH, RANGE 22 EAST.

- 40.02 Old $\frac{1}{4}$ sec. cor., which is a malpais stone $6 \times 6 \times 14$ ins. above ground loosely set & marked as described by Surveyor General, bears N. 15 lks. dist. I destroy all trace of this old cor.
- 79.69 The cor. of secs. 5, 6, 7 & 8, hereinbefore described.
Land level.
Soil, red adobe, 12 to 18 ins. deep on clay sub-soil
Scattering short grass
No timber.
-
- Thence I run
N. $0^{\circ} 04'$ W. on random line bet. secs. 5 & 6
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.28 Intersect N. bdy. of Tp. 49 lks. W. of cor. of secs. 5, 6, 31 & 32, ~~reestd. by me as described in Book "A" of this Group~~
Thence I run
S. $0^{\circ} 17'$ W. on true line bet. secs. 5 & 6
- Over rolling rocky land.
- 40.28 Set an iron post 3 ft. long, 1 in. in dia. ~~26~~ 26 ins. in ground for a ~~stab.~~ $\frac{1}{4}$ sec. cor., with a brass cap marked $\frac{1}{4}$ S 6 in W., S 5 in E. & 1913 in S. half. of post
Dig pits 18 x 13 x 12 ins. N. & S, $\frac{1}{2}$ ft. dist. & raise mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high W. of cor.
Leave rolling rocky land, thence over level land; bears E & W.
- 80.28 The cor. of secs. 5, 6, 7 & 8, hereinbefore described.
Land level & rolling.
Soil, N. half, thin & rocky, S, half, red adobe 12 to 18 ins. deep on clay sub-soil.
Short grass
No timber.

Jan 27th, 1914.

GENERAL DESCRIPTION.

This township consists of level prairie land, excepting for rocky hills in S. part of secs. 19 & 20 and secs. 29, 30, 31 & 32, and for breaks in the head of Aravaipa Canyon, which occur in the N. half of secs. 4, 5, & 6.

Soil throughout the Eastern half of township consists of loose, red sandy loam, ranging in depth from 12 to 24 ins. It has produced a fair crop of corn by dry farming in secs. 10 & 11. Forage crops are raised by settlers in secs. 32, 33 & 34, mainly by dry farming. Soil in secs. 7, 8, 17 & 18 and a part of secs. 19 & 20 is a red adobe, supporting a very scanty growth of grass. The rocky hills in secs. 29 & 30 and the Northern half of secs. 31 & 32 are covered with very thin soil, which also supports a very thin growth of short grass. The Eastern half of the township is covered with a good growth of grama-grass.

There are a good many settlers scattered over practically this entire township. There are two schools in the township, one located in the S.W. $\frac{1}{4}$ of sec. 15, and the other in the S.W. cor. of secs. 34.

Wells, which will supply water for the entire year have only been found in secs. 16, 14 & 11. Numerous shallow wells have been dug by the settlers which supply water through all except the dry summer months.

Thomas B. Matthews

U.S. Surveyor.

Jan. 27, 1914.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, Mary Long, being first duly sworn upon my oath state; that I am the same person who made Grant Land entry of the SE 1/4 of sec. 1 T10N. R. 22E. S. 7. R. B. 7 M.;

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita Ariz

Mary Long

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 21 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, A. H. Long, being first duly sworn upon my oath state; that I am the same person who made Homestead entry of the NE 1/4 of sec 1 T10S, R. 22E, G. & J. R. B. M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonito Ariz

A. H. Long

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 21 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, W. H. McGirk, being first duly sworn upon my oath state; that I am the owner by virtue of a legal transfer of the NE 1/4 sec 9 T10 N R 22 E BY D. R. B. M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Parita, Ariz

W. H. McGirk

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, L. A. Teel, being first duly sworn upon my oath state; that I am the same person who made bonated entry of the 104 acres 110 S. R. 22 E. S. 4 R. B. & M. that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonata, Ariz.

L. A. Teel

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.
Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, L. A. Teel, being first duly sworn upon my oath state; that I am the same person who made substant entry of the SE 1/4 of sec 9 T10 N. R. 22 E. G. 4 R. B. 4 M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz.

L. A. Teel

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 Arizona.

I, David Smith, being first duly sworn upon my oath state; that I am the same person who made homestead, entry of the NW 1/4 of sec 10 T10N, R22E, S4R, B4M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz.

David Smith
 by E. Smith
 agt.

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan. 1914.

Thomas B. Matthews
 U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 ?Arizona.

I, E. Smith, being first duly sworn upon my oath state; that I am the same person who made homestead, entry of the 11th June 1877; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz.

E. Smith

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 21th day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, C. J. Bevanney, being first duly sworn upon my oath state; that I am the same person who made

homestead entry of the NW 1/4 Sec 4, T10N, R20E, S4E, & NE 1/4 of NW 1/4 of sec 11 T10N, R20E, S4E, B. & M.

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz.

C. J. Bevanney

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 Arizona.

I, Hannah E. Fowler, being first duly sworn upon my oath state; that I am the same person who made

deed land, entry of the W 1/4 Sec 27 T 22 N 4

R 22 E;

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address

is Santa Ana, P.O. 5, box 11 Calif

Hannah E. Fowler

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, Hannah E. Fowler, being first duly sworn upon my oath state; that I am the ^{widow of the} ~~same~~ person who made homestead entry of the 1/2 of NE 1/4 1/2 of NE 1/4 sec 10 T10N R22E, S14T17N; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Santa Ana R.D. 5th Val.

Hannah E. Fowler

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan. 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, Willie Gensch, being first duly sworn upon my oath state; that I am the same person who made bonsted entry of the SW 1/4 sec 13 T10 S R22 E Q1 A P. B. & M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita Ariz

Willie Gensch

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of June, 1914.

Thomas B. Matthews
 U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, Herman Gensch, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the W² & NE¹/₄ NE¹/₄ & NE¹/₄ & NE¹/₄ of sec. 14 T10N R22E; C. & G. R. BY M. that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz..

Herman Gensch

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan. 1914.

James B. Matthews
U. S. Surveyor.

Department of the Interior. United States Land Office.
Phoenix, Arizona.

In re Resurvey of Crisp 25, Arizona.

I, S. L. Nichols, being first duly sworn
upon my oath state; that I am the same person who made

Homestead entry of the 15
2100 R 22 E 24 N 34 W

that I do not desire a special notes and bounds survey
of said described land, but agree to conform my claim
to the resurvey thereof; that my postoffice address is

Bonita Ariz

S. L. Nichols

I HEREBY CERTIFY that the foregoing affidavit was
read to affiant in my presence before affiant affixed
signature thereto; that affiant is to me personally known
that I verily believe affiant to be the identical person
hereinbefore described, and that said affidavit was duly
subscribed and sworn to before me this the 27 day of

Jan

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, - Arizona.

I, J. C. Nichols, being first duly sworn upon my oath at to; that I am the same person who made final homestead proof of the SW 1/4 of sec 15
T18S R22E S4T1R, P. & M.
 and am the legal owner of said tract; that I do not desire a special notes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Chrodona Calif.

J. C. Nichols

I HEREBY CERTIFY THAT THE foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan., 1914.

Thomas B. Matthews
 U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 Arizona.

I, W. H. McGish, being first duly sworn upon my oath state; that I am the same person who made ~~fixix~~

~~sumitted~~ entry of the 1/2 of NE 1/4, SE 1/4
& E 1/2 of NW 1/4 of sec 17 T14N R22E

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz.

W. H. McGish

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me, this the 17 day of

Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

Department of the Interior. United States Land Office.

Phoenix, Arizona.

In re Resurvey of Group 25, Arizona.

I, D. M. Girk, being first duly sworn upon my oath state; that I am the same person who made

Homestead entry of the 1/2 of Sec 15,
NE 1/4 and NW 1/4 of Sec 16 T17N R22E
Co. 9. R. 24. M.

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the resurvey thereof; that my postoffice address is

Bonita Ariz

D. M. Girk

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of

Jan 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, G. St. C. Gerhart, being first duly sworn upon my oath state; that I am the same person who made ~~final~~ Homestead entry of the W 1/2 of sec. 19 T10N R22E. G & A R. B & M. that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz.

Geo. St. C. Gerhart

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan, 1914.

Thomas B. Matthew
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona,

IN RE RESURVEY OF GROUP 25 - Arizona.

I, W. H. McGint, being first duly sworn upon my oath state; that I am the owner by virtue of a legal transfer of the NE 1/4 of sec 20 T10N R22E, Co. 1 R. B. M.

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita Ariz.

W. H. McGint

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

Department of the Interior. United States Land Office.

Phoenix, Arizona.

In re Resurvey of Group 25, Arizona.

I, Harleton W. Nichols, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the W 1/4 of N 1/4 of 11, R 16 E & 1/4 of N 1/4 of 20 T 10 N, R 22 E, S 1 & 2 R. B. Y. M. that I do not desire a special notes and bounds survey of said described land, but agree to conform my claim to the resurvey thereof; that my postoffice address is Bonita Ariz

Harleton W. Nichols

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of Jan 1914

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25 Arizona.

I, E. R. Addington, being first duly sworn upon my oath state; that I am the same person who made ~~first~~ Homestead entry of the NW 1/4 of sec 22 T. 10 N. R. 22 E. 1/4 R. B. M.

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Bonita, Ariz.

E. R. Addington

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me, this the 21 day of

Jan, 1914.

Thomas B. Matthes
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, Adolph Genrich, being first duly sworn upon my oath state; that I am the same person who made

homestead entry of the NE 1/4 of sec 22 & NW 1/4 of sec. 23 T10N R. 22E, STAR. 1372.

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice

address is Bonita, Ariz.

Adolph Genrich

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 21 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, - Arizona.

I, A. M. Morgan, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the NW 1/4 of sec 26 T10S, R. 22 E, S. 4 R, B. & M. and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Wilcox, Arizona.

A. M. Morgan

I HEREBY CERTIFY THAT THE foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described and that said affidavit was duly subscribed and sworn to before me this the 15 day of Feb, 1914.

Thomas B. Walker
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, E. F. Morgan, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the E $\frac{1}{2}$ & NW $\frac{1}{4}$ NE $\frac{1}{4}$, NE $\frac{1}{4}$ & NW $\frac{1}{4}$ & E $\frac{1}{2}$ of d E $\frac{1}{2}$ of sec 31 T10N R28E Ex. R. B. M. that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Willcox, Ariz.

E. F. Morgan

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 27 day of June 1914.

Thomas B. Matthew
U. S. Surveyor,

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, Wm F. Morgan, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the SW 1/4 NE 1/4 Sec 31; 7100 R22E E1/2 R. 15 W. 1/4; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Willcox, Ariz.

Wm F. Morgan

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of Jan, 1914.

Thomas B. Matthe
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, M. J. Morgan, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the SW 1/4 of sec 32 T.10N. R.22E. S.4R. BYM that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Wells, Ariz.

M. J. Morgan

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of Jun., 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, C. W. Addington, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the E 1/2 NE 1/4 of 32 & 10 1/2 of NW 1/4 of 33 of 106, R 22 E. 69-AR, BYM; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Wilcox, Ariz.

C. W. Addington

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 29 day of Jan, 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, W. H. Morgan, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the SE 1/4 of sec 33 T10N R22E

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Wilcox, Ariz.

W. H. Morgan

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 28 day of June 1914.

James B. Matthews
U. S. Surveyor,

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, - Arizona.

I, Joe T. Clark, being first duly sworn upon my oath state; that I am the same person who made final homestead proof of the SE 1/4 of NW 1/4, N 1/4 + SW 1/4 of SW 1/4 of sec. 33 T. 10 N. R. 22 E., S. 1/4 R. 24 W. and am the legal owner of said tract; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is 131 N. Chicago
Los Angeles, Cal
Joe T. Clark

I HEREBY CERTIFY THAT THE foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described and that said affidavit was duly subscribed and sworn to before me this the 13th day of February, 1914.

Geo. S. Myers
U. S. Surveyor.
NOTARY PUBLIC in and for the
County of Los Angeles, State of California

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, Wm. Fought, being first duly sworn upon my oath state; that I am the same person who made homestead entry of the N¹/₂ of NW¹/₄ & N¹/₂ of NW¹/₄ of sec. 34 T10S R22E; C. & G. R. B. & M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Miami, Ariz.

Wm. Fought

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 7 day of Feb., 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.
Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, Arizona.

I, A. J. J. J., being first duly sworn upon my oath state; that I am the same person who made homestead entry of the SE 1/4 of NE 1/4 of Sec 4 of me 34 T10 R22 E, T4R. BY M.; that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Willcox, Ariz.

A. J. J. J.

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known, that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 30 day of Jan., 1914.

Thomas B. Matthews
U. S. Surveyor.

DEPARTMENT OF THE INTERIOR. UNITED STATES LAND OFFICE.

Phoenix, Arizona.

IN RE RESURVEY OF GROUP 25, -Arizona.

I, Susan C. Morgan, being first duly sworn upon my oath state; that I am the same person who made

Surtland entry of the NE 1/4 of Sec 23 & NW 1/4 of Sec 34 T10 N. R 22 E. Co. 11 P. B. 13 N.

that I do not desire a special metes and bounds survey of said described land, but agree to conform my claim to the lines of the resurvey thereof; that my postoffice address is Willcox, Ariz.

Susan C. Morgan

I HEREBY CERTIFY that the foregoing affidavit was read to affiant in my presence before affiant affixed signature thereto; that affiant is to me personally known; that I verily believe affiant to be the identical person hereinbefore described, and that said affidavit was duly subscribed and sworn to before me this the 30 day of Jan., 1914.

Thomas B. Matthews
U. S. Surveyor.

In obtaining the settlers' agreements to conform their claims to the lines of the resurvey thereof there are a few with whom I have not been able to get in communication, but whose interests have not been impaired to any great extent, as there is no discernable difference between the land within their claims and the land surrounding same.

Thomas B. Matthews
U.S. Surveyor

188

88

BOOK 2762

For

FINAL OATH OF UNITED STATES SURVEYOR.
(See Book "D.")

I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191 _____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

U. S. Surveyor.

Subscribed by said _____, and sworn to before me }
this _____ day of _____, 191 _____ }



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, March 20, 1915,

The foregoing field notes of the ^{re-}survey of _____

Subdivision lines of Township 10, South, Range 22 East, of the Gila and Salt River Base and Meridian, Arizona,

executed by Thomas B. Matthews, U. S. Surveyor,

under his special instructions dated May 7, 1913 for Group 25, ~~1913~~ having been critically examined, and the necessary corrections and explanations made, the said field notes, and the resurveys they describe, are hereby approved.

~~U. S.~~ Surveyor General.
of Arizona.

~~I certify that the foregoing transcript of the field notes of the above described surveys in Book "M," has been correctly copied from the original notes on file in this office.~~

~~U. S. Surveyor General.
of Arizona.~~

DEC 16 1915

It is hereby agreed to conform to the lines of the re-survey of Township 10 South, Range 22 East, Gila and Salt River Base and Meridian, Arizona, as executed by the General Land Office in 1914, in so far as the following State lands and selections are concerned:

SW $\frac{1}{4}$; S $\frac{1}{2}$ NW $\frac{1}{4}$ and Lots 3 and 4,	sec. 1,
All,	sec. 2,
All,	sec. 3,
NE $\frac{1}{4}$ and NE $\frac{1}{4}$ SE $\frac{1}{4}$	sec. 11,
N $\frac{1}{2}$ and SE $\frac{1}{4}$	sec. 12,
N $\frac{1}{2}$ and SE $\frac{1}{4}$	sec. 13,
All,	sec. 16,
NE $\frac{1}{4}$ and N $\frac{1}{2}$ SE $\frac{1}{4}$	sec. 24,
NW $\frac{1}{4}$ and W $\frac{1}{2}$ NE $\frac{1}{4}$	sec. 32,
All,	sec. 36.

Dated

Phoenix, ArizonaDecember 15, 1915

J. A. Moore
State Land Commissioner



RECORDED 2732

The Santa Fe Pacific Railroad Company, successors in interest to the Atlantic and Pacific Railroad Company, hereby agree to conform the following lieu selections in Township 10 South, Range 22 East, Gila and Salt River Base and Meridian, Arizona, to the lines of the resurvey thereof, as executed by the General Land Office in 1914:

NE $\frac{1}{4}$	Sec. 9,
SW $\frac{1}{4}$	Sec. 14,-
W $\frac{1}{2}$ SW $\frac{1}{4}$ and S $\frac{1}{2}$ SE $\frac{1}{4}$	Sec. 24,
SW $\frac{1}{4}$ and SW $\frac{1}{4}$ SE $\frac{1}{4}$	Sec. 25,
E $\frac{1}{4}$ and SW $\frac{1}{4}$	Sec. 26,
All	Sec. 35.

Dated Topeka, Kansas,

December 14, 1915.

SANTA FE PACIFIC RAILROAD COMPANY,

By

Howell Jones

Its Land Commissioner.

L.V.McCourt and William Riggs,

By M. E. Leverich & Co.

by John H. Page

Epes Randolph,

By M. E. Leverich & Co.

by John H. Page

M.E.Leverich & Co.,

By

John H. Page