

2975

155

10/22/92

"D"  
4-679

BOOK 2975

# FIELD NOTES

OF THE RESURVEY OF THE

East Boundary of T. 20 N., R. 7 W.,

RETRACEMENT OF THE

Fifth Standard Parallel North, Rs. 6 and part of 5 W. (N. Bdy. T. 20 N.)

and

SURVEY OF THE

East Boundary, and  
Subdivisional Lines of

TOWNSHIP 20 NORTH, RANGE 6 WEST.

Of the Gila and Salt River Base and Meridian,

In the State of ARIZONA

EXECUTED BY

THOMAS W. BATES, and

DAVID W. EATON,

In the capacity of U. S. ~~transitmen~~ under Special Instructions dated January 18, 1918, issued by the United States Surveyor General to govern surveys included in Group No. 86, which were approved by the Commissioner of the General Land Office, January 22, 1918, and Assignment Instructions dated January 26, 1918.

Resurvey  
Retracement & Survey commenced April 27th, 1918.

Resurvey  
Retracement & Survey completed June 2nd, 1918.

2975

2975


1A

2975

BOOK 2975

# INDEX DIAGRAM.

		Township 20 North				Range 6 West						
		10	10	10	11	11	11	12	12			
		5th Standard Parallel North										
8	6	53	5	44	4	37	3	30	2	23	1	16
		52		52		43		37		30		23
7	7	51	8	43	9	36	10	29	11	22	12	15
		51		50		42		36		29		22
6	18	50	17	42	16	35	15	28	14	21	13	15
		49		49		41		34		27		21
6	19	48	20	40	21	34	22	27	23	20	24	14
		47		47		40		33		26		20
6	30	46	29	39	28	32	27	25	26	19	25	13
		46		45		39		32		25		18
5	31	44	32	38	33	31	34	24	35	18	36	13

- Surveyed under this Group.
- Resurveyed " " "
- - - - - Retraced " " "
- Accepted surveys.
-  Areas surveyed as shown by accepted plats on file.

4-679 b

DATE  
~~INDEX~~ DIAGRAM.

Township 20 North, Range 6 West  
5th Standard Parallel North

5-31-18 5-25-18 5-1-18 5-31-18 6	5-31-18 5-30-18 5-28-18 5	6-1-18 5-28-18 5-28-18 4	6-1-18 5-10-18 5-9-18 3	6-1-18 5-10-18 5-10-18 2	6-1-18 5-10-18 5-10-18 5-9-18 1
5-25-18 5-30-18 7	5-30-18 5-30-18 8	5-28-18 5-10-18 5-28-18 9	5-10-18 5-9-18 5-7-18 10	5-10-18 5-10-18 5-10-18 11	5-10-18 5-8-18 5-9-18 12
5-25-18 5-29-18 13	5-30-18 5-27-18 5-28-18 17	5-28-18 5-28-18 16	5-9-18 5-9-18 15	5-7-18 5-7-18 14	5-8-18 5-7-18 5-6-18 18
5-24-18 5-27-18 19	5-27-18 5-22-18 20	5-24-18 5-29-18 21	5-9-18 5-8-18 5-8-18 22	5-6-18 5-6-18 23	5-7-18 5-3-18 5-6-18 24
5-24-18 5-23-18 5-23-18 30	5-24-18 5-22-18 5-23-18 29	5-11-18 5-24-18 5-23-18 28	5-8-18 5-1-18 27	5-4-18 5-2-18 26	5-3-18 5-2-18 4-27-18 25
5-23-18 5-23-18 31	5-22-18 32	5-11-18 5-22-18 33	5-1-18 34	4-30-18 35	4-30-18 4-27-18 36

6-4817

Surveyed on dates shown above by

\_\_\_\_\_ Thomas W. Bates, U. S. Transitman

\_\_\_\_\_ David W. Eaton, U. S. Transitman.

Chains.	<p>Resurvey, Retracement and Survey executed by Thos. W. Bates and David W. Eaton, U. S. Transitmen, on dates shown on page 1 hereof, using Young and Sons light mountain transit No. 8569, with Smith solar attachment, and Young and Sons solar compass No. 8512, respectively. For description of instrument, certificate of approval and field tests of adjustments, see Book "A".</p>
	<p style="text-align: center;">Retracement for Resurvey of the East Boundary of T. 20 N., R. 7 W.</p>
	<p>From the reestablished cor. of Ts. 19 and 20 N., R. 7 W., described in Book "A",</p>
11.90	<p>North on a random line, along the E. bdy. of sec. 36. Intersect the reestablished cor. of Ts. 19 and 20 N., R. 6 E., described in Book "A".</p>
40.00	<p>Intersect the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 36, which is a volcanic stone, 8 X 18 X 16 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.</p>
	<p>The true course and distance of this half mile are therefore North 40.00 chs.</p>
	<p>Thence North on a random line.</p>
38.97	<p>Fall 152 lks. E. of the cor. of secs. 25, 30, 31 and 36, which is a sandstone, 6 X 12 X 5 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.</p>
	<p>The true course and distance of this half mile are therefore N.2°14'W., 39.00 chs.</p>
	<p>North on a random line, along the E. bdy. of sec. 25.</p>
39.74	<p>Fall 5 lks. E. of the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, which is a volcanic stone, 12 X 10 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.</p>
	<p>The true course and distance of this half mile are therefore N.0°4'W., 39.74 chs.</p>
	<p>Thence North on a random line.</p>
40.09	<p>Intersect the cor. of secs. 19, 24, 25 and 30, which is a volcanic stone, 16 X 10 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.</p>
	<p>The true course and distance of this half mile are therefore North 40.09 chs.</p>
	<p>North on a random line, along the E. bdy. of sec. 24.</p>
41.27	<p>Fall 15 lks. W. of the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24, which is a limestone, 4 X 10 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General, except that the SE. bearing tree is a pine, 14 ins. diam., instead of a cedar.</p>
	<p>The true course and distance of this half mile are therefore N.0°13'E., 41.27 chs.</p>
	<p>Thence North on a random line.</p>
38.58	<p>Fall 73 lks. E. of the cor. of secs. 13, 18, 19 and 24, which is a limestone, 6 X 16 X 14 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.</p>
	<p>The true course and distance of this half mile are therefore N.1°5'W., 38.59 chs.</p>

Retracement for Resurvey of the  
East Boundary of T. 20 N., R. 7 W.

Chains.	
39.04	<p>North on a random line, along the E. bdy. of sec. 13. Fall 59 lks. E. of the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, which is a sandstone, 10 X 8 X 8 ins. above ground, marked and witnessed as described by the Surveyor- General. The true course and distance of this half mile are there- fore N.0°52'W., 39.04 chs.</p>
40.18	<p>Thence North on a random line. Intersect the cor. of secs. 7, 12, 13 and 18, which is a limestone, 14 X 6 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor- General. The true course and distance of this half mile are there- fore North 40.18 chs.</p>
38.23	<p>North on a random line, along the E. bdy. of sec. 12. Fall 12 lks. E. of the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12, which is a limestone, 10 X 6 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. The true course and distance of this half mile are there- fore N.0°10'W., 38.23 chs.</p>
39.59	<p>Thence North on a random line. Fall 17 lks. W. of the cor. of secs. 1, 6, 7 and 12, which is a limestone, 12 X 10 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General. The true course and distance of this half mile are there- fore N.0°15'E., 39.59 chs.</p>
39.11	<p>North on a random line, along the E. bdy. of sec. 1. Fall 5 lks. E. of the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, which is a sandstone, 10 X 8 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor- General, except that the bearing tree E. of line is a cedar, 10 ins. diam., instead of a pine. The true course and distance of this half mile are there- fore N.0°4'W., 39.11 chs.</p>
25.57	<p>Thence North on a random line. Intersect the closing cor. of Ts. 20 and 21 N., R. 6 W., on the 5th Standard Parallel North, which is a limestone, 14 X 6 X 4 ins., set in a mound of stone, marked and witnessed as described by the Surveyor-General. The true course and distance of this line are therefore North 25.57 chs.</p>

Resurvey of the  
East Boundary of T. 20 N., R. 7 W.

Chains	From the reestablished cor. of Ts. 19 and 20 N., R. 7 W., described in Book "A". North on a true line, along the E. bdy. of sec. 36. Over level mesa, through heavy timber and dense undergrowth.
11.90	The reestablished cor. of Ts. 19 and 20 N., R. 6 W., described in Book "A".
34.53	Edge of mesa, brs. NE. and SW. Desc. 170 ft.
40.00	The original $\frac{1}{4}$ sec. cor. of secs. 31 and 36, hereinbefore described. This cor. will hereafter refer to sec. 36 only.
50.40	Thence N. 2° 14' W., on a true line, continuing measurement Draw, course E. Asc. 40 ft.
51.91	(40.00 chs. northing from the reestablished cor. of Ts. 19 and 20 N., R. 6 W.) Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, on bed rock, in a mound of stone, for reestablished $\frac{1}{4}$ sec. cor. of sec. 31, T. 20 N., R. 6 W., marked on brass cap :S 31 1918 From which A cedar, 10 ins. diam., brs. N. 30 $\frac{1}{2}$ ° E., 27 lks. dist., marked $\frac{1}{4}$ S31 BT. A cedar, 15 ins. diam., brs. S. 26 $\frac{1}{2}$ ° E., 20 lks. dist., marked $\frac{1}{4}$ S31 BT. Asc. 25 ft.
54.90	Spur, slopes E. 3 chs. Desc. 30 ft.
62.90	Draw, course SE. Asc. 250 ft.
71.40	Edge of rim rock, brs. NE. and SW. Thence over level mesa.
79.00	The original cor. of secs. 25, 30, 31 and 36, hereinbefore described. I destroy the markings on the bearing trees E. of line, making this cor. refer to secs. 25 and 36 only. Land, level mesa and mountainous. Soil, 2nd and 4th rates. Timber, cedar, pinion, juniper and pine. undergrowth, cactus, scrub oak and young timber.
12.93	N. 0° 4' W., on a true line, along the E. bdy. of sec. 25 Over level mesa, through heavy timber and dense undergrowth (80.00 chs. northing from the reestablished cor. of Ts. 19 and 20 N., R. 6 W.) Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, on bed rock, in a mound of stone, for reestablished cor. of secs. 30 and 31, T. 20 N., R. 6 W., marked on brass cap :T 20 N :S 30 :S 31 :R 6 W 1918 From which A cedar, 20 ins. diam., brs. N. 23 $\frac{1}{2}$ ° E., 127 lks. dist., marked T 20 N R 6 W S 30 BT. A cedar, 10 ins. diam., brs. S. 46° E., 181 lks. dist., marked T 20 N R 6 W S 31 BT.
28.73	Rim of canyon, brs. NW. and SE. Desc. 200 ft.
36.53	Draw, in bottom of canyon, course E. Asc. 125 ft.
39.74	The original $\frac{1}{4}$ sec. cor. of secs. 25 and 30, hereinbefore described. This cor. will hereafter refer to sec. 25 only. Thence North on a true line, continuing measurement.
47.93	Rocky point on spur, slopes N. Desc. 115 ft.
52.93	(40.00 chs. northing from the reestablished cor. of secs. 30 and 31, T. 20 N., R. 6 W.) Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, on bed rock, in a mound of stone, for reestablished $\frac{1}{4}$ sec. cor. of sec. 30, marked on brass cap

6

6

Resurvey of the  
East Boundary of T. 20 N., R. 7 W.

Chains

 $\frac{1}{4}$   
:S 30

1918

From which

A pinion, 6 ins. diam., brs. N. 23° E., 109 lks.  
dist., marked  $\frac{1}{4}$  S 30 BT.A cedar, 8 ins. diam., brs. S. 1° E., 36 lks.  
dist., marked  $\frac{1}{4}$  S 30 BT.

Desc. 50 ft.

54.93 Draw, course NE. Asc.

57.93 Short spur, slopes E. Desc.

59.93 Draw, course SE. Asc. 125 ft.

79.83 The original cor. of secs. 19, 24, 25 and 30, hereinbefore described. This cor. will hereafter refer to secs. 24 and 25 only.

Land, level mesa and mountainous.

Soil, 2nd and 4th rates.

Timber, cedar, pinion, pine and juniper.

Undergrowth, scrub oak, cactus and young cedar.

N. 0° 13' E., on a true line, along the E. bdy. of sec. 24. Over mountainous land, through heavy timber and dense undergrowth.

Asc. 50 ft.

2.10 Spur, slopes NE. Desc. 150 ft.

11.85 Draw, course NW. Asc. 25 ft.

13.10 (80.00 chs. northing from the reestablished cor. of secs. 30 and 31, T. 20 N., R. 6 W.)

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, on bed rock, in a mound of stone, for reestablished cor. of secs. 19 and 30, T. 20 N., R. 6 W., marked on brass cap

:T 20 N

:S 19

:S 30

:R 6 W

1918

From which

A cedar, 18 ins. diam., brs. N. 70 $\frac{3}{4}$ ° E., 35 lks.  
dist., marked T 20 N R 6 W S 19 BT.A pine, 12 ins. diam., brs. S. 45° E., 45 lks.  
dist., marked T 20 N R 6 W S 30 BT.

13.60 Low spur, slopes NW. Desc. 225 ft.

35.00 Wash, 38 lks. wide, course NE., asc. S. slope 75 ft.

39.10 Short spur slopes SE. Desc. 15 ft.

41.27 The original  $\frac{1}{4}$  sec. cor. secs. 19 and 24, hereinbefore described. I destroy the markings on the bearing tree east of the line and mark a new bearing tree,A pine 8 ins. in diam., brs. N. 30 $\frac{1}{2}$ ° W., 100 lks.  
dist., marked  $\frac{1}{4}$  S 24 BT.

Thence, N. 1° 5' W., continuing measurement.

41.60 Draw, drains SE. Asc. 50 ft.

52.10 Rocky spur, slopes NE.

53.10 (40.00 chs. northing from the reestablished cor. of secs. 19 and 30, T. 20 N., R. 6 W.)

Set an iron post 3 ft. long, 1 in. in diam., 10 ins. in the ground, on bed rock, in a mound of stone, for reestablished  $\frac{1}{4}$  sec. cor. Sec. 19, mkd. on brass cap
 $\frac{1}{4}$   
:S 19

1918

From which

A cedar 18 ins. diam. brs. N. 70 $\frac{3}{4}$ ° E., 35 lks.  
dist., marked  $\frac{1}{4}$  S 19 BT.A pine 12 ins. diam. brs. S. 45° E., 45 lks.  
dist., mkd.  $\frac{1}{4}$  S 19 BT.

56.50 Draw, course E. Asc. 300 ft.

72.25 Spur, slopes NE. Desc. 150 ft.

78.10 Draw, course E. Asc. 50 ft.

79.86 The original cor. of secs. 13, 18, 19 and 24, hereinbefore described. I destroy the markings on the bearing trees

Resurvey of the  
East Boundary of T. 20 N., R. 7 W.

Chains

E. of line, making this cor. refer to secs. 13 and 24 only.

Land, mountainous.

Soil, 2nd and 4th rates.

Timber, cedar, pinion, juniper and pine.

Undergrowth, scrub oak, cactus and young timber.

N.0° 52'W., on a true line, along the E. bdy. of sec. 13. Over mountainous land, through heavy timber and dense undergrowth. Asc. 15 ft.

- .50 Spur, slopes NE. Desc. 125 ft.
- 4.40 Wash, 35 lks. wide, course S. 70° E. Asc. 160 ft.
- 13.25 (80.00 chs. northing from the reestablished cor. of secs. 19 and 30, T. 20 N., R. 6 W.)

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, on bed rock, in a mound of stone, for reestablished cor. of secs. 18 and 19, marked on brass cap

:T 20 N  
:S 18  
:S 19  
:R 6 W

1918

From which

A pinion, 12 ins. diam., brs. N. 25° E., 26 lks. dist., marked T 20 N R 6 W S 18 BT.

A pinion, 10 ins. diam., brs. S. 72° E., 66 lks. dist., marked T 20 N R 6 W S 19 BT.

Asc. 25 ft.

- 15.75 Spur, slopes E. Desc. 125 ft.
- 24.05 Draw, course E. Asc. 175 ft.
- 34.25 Ridge, brs. NW. and SE. Desc. 75 ft.
- 39.04 The original  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, hereinbefore described. Alongside the original cor., I reestablish a new cor. referring to sec. 13 only as follows:  
Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, on bed rock, in a mound of stone, for reestablished  $\frac{1}{4}$  sec. cor. of sec. 13, marked on brass cap

$\frac{1}{4}$   
S 13:

1918

I destroy the markings on the original bearing tree E. of line, and mark a new bearing tree,

A pine, 12 ins. diam., brs. S. 36 $\frac{1}{2}$ ° W., 20 lks. dist., marked  $\frac{1}{4}$  S 13 BT.

Thence North on a true line, continuing measurement.

- 46.25 Spur, slopes SE. Desc. 40 ft.
- 53.25 (40.00 chs. Northing from the reestablished cor. of secs. 18 and 19, T. 20 N., R. 6 W.)  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished  $\frac{1}{4}$  sec. cor. of sec. 18, T. 20 N., R. 6 W., marked on brass cap

$\frac{1}{4}$   
:S 18

From which 1918

A cedar, 8 ins. diam., brs. N. 40° E., 88 lks. dist., marked  $\frac{1}{4}$  S 18 BT.

A pine, 12 ins. diam., brs. N. 74° E., 65 lks. dist., marked  $\frac{1}{4}$  S 18 BT.

- 56.65 Head of draw, course SE. Asc. 100 ft.
- 63.75 Spur, slopes SE. Desc. 60 ft.
- 71.25 Draw, course E. Asc. 115 ft.
- 77.75 Spur, slopes E. Desc. 80 ft.
- 79.22 The original cor. of secs. 7, 12, 13 and 18, hereinbefore described. This cor. will hereafter refer to secs. 12 and 13.  
Land, mountainous.  
Soil, 2nd and 4th rates.




Chains	Timber, cedar, pinion, pine and juniper. Undergrowth, scrub oak, cactus, and young timber
	N. 0° 10' W., on a true line, along the E. bdy. of sec. 12. Over mountainous land, through heavy timber and dense undergrowth. Desc. 360 ft.
11.03	Enter open valley, course E.
14.03	(80.00 chs. northing from the reestablished cor. of secs. 18 and 19, T. 20 N., R. 6 W. Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, on bed rock, in a mound of stone, for re- established cor. of secs. 7 and 18, marked on brass cap
	:T 20 N :S 7 :S 18 :R 6 W
	1918
	From which
	A cedar, 12 ins. diam., brs. N. 46° E., 95 lks. dist., marked T 20 N R 6 W S 7 BT
	A cedar, 30 ins. diam., brs. S 39½° E., 338 lks. dist., marked T 20 N R 6 W S 18 BT.
15.03	Wash, course E. Asc. 150 ft.
26.05	Enter heavy timber, brs. E. and W.
33.03	Spur, slopes SE. Desc. 70 ft.
37.33	Draw, course SE. Asc. 15 ft.
38.23	The original ¼ sec. cor. of secs. 7 and 12, hereinbefore described. I destroy the markings on the bearing tree E. of line, and mark a new bearing tree, A pine, 6 ins. diam., brs. N. 33° W., 33 lks. dist., marked ¼ S 12 BT.
	Thence N. 0° 15' E., continuing measurement.
54.03	(40.00 chs. northing from the reestablished cor. of secs. 7 and 18, T. 20 N., R. 6 W.) Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, on bed rock, in a mound of stone for reestab- lished ¼ sec. cor. of sec. 7, T. 20 N., R. 6 W., mark- ed on brass cap
	¼ :S 7
	From which 1918
	A pine, 17 ins. diam., brs. N. 21° E., 77 lks. dist., marked ¼ S 7 BT.
	A pine, 6 ins. diam., brs. S. 29° E., 26 lks. dist., marked ¼ S 7 BT.
	Thence over rolling top of spur, slopes E.
70.00	Spur, slopes E. Desc. 135 ft.
77.82	The original cor. of secs. 1, 6, 7 and 12, hereinbefore described. I destroy the markings on the bearing trees E. of line, making this cor. refer to secs. 1 and 12 only.
	Land, mountainous. Soil, 2nd and 4th rates. Timber, cedar, pinion, pine and juniper. Undergrowth, scrub oak, cactus and young timber.
	N. 0° 4' W., on a true line, along the E. bdy. of sec. 1. Over mountainous land, through heavy timber and dense undergrowth. Desc. 125 ft.
3.70	Draw, course E. Asc. 75 ft.
10.60	Short spur, slopes SE. Desc. 75 ft.
13.10	Draw, course SE. Asc. 125 ft.
16.21	(80.00 chs. northing from the reestablished cor. of secs.

Resurvey of the East Boundary of T. 20 N., R. 7 W. BOOK 9

Chains.

7 and 18, T. 20 N., R. 6 W.)

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, on bed rock, in a mound of stone, for reestablished cor. of secs. 6 and 7, T. 20 N., R. 6 W., marked on brass cap



From which

A pine, 12 ins. diam., brs. N.50½°E.,  
29 lks. dist., marked T20N R6W S6 BT.

A pine, 6 ins. diam., brs. S.51°E.,  
36 lks. dist., marked T20N R6W S7 BT.

Asc. 150 ft.

20.21 Spur, slopes E. Desc. 120 ft.

28.71 Head of draw, course E. Asc. 70 ft.

37.21 Spur, slopes E. Desc. 15 ft.

39.11 The original ¼ sec. cor. of secs. 1 and 6, hereinbefore described. I alter this cor. to refer to sec. 1 only by destroying the markings on the bearing tree E. of line, and marking a new bearing tree,


A pine, 6 ins. diam., brs. N.72¼°W.,  
42 lks. dist., marked ¼S1 BT.

Thence North on a true line, continuing measurement.

48.96 Wash, course NE. Desc. 50 ft.

56.21 (40.00 chs. northing from the reestablished cor. of secs. 6 and 7, T. 20 N., R. 6 W.)

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, on bed rock, in a mound of stone, for reestablished ¼ sec. cor. of sec. 6, T. 20 N., R. 6 W., marked on brass cap



From which

A cedar, 10 ins. diam., brs. N.51°E.,  
61 lks. dist., marked ¼S6 BT.

A cedar, 9 ins. diam., brs. S.27¼°E.,  
60 lks. dist., marked ¼S6 BT.

64.68 The original closing cor. of Ts. 20 and 21 N., R. 6 W., on 5th Standard Parallel North, hereinbefore described.

Land, mountainous.

Soil, 2nd and 4th rates.

Timber, cedar, pinion, juniper and pine.

Undergrowth, scrub oak, cactus and young timber.

10 Retracement of the  
5th Standard Parallel North Through Fractional Range 6 West.

Chains.	From the closing cor. of Ts. 20 and 21 N., R. 6 W., on the 5th Standard Parallel North, hereinbefore described, East on a random line, along S. bdy. of fracl. sec. 32. Over level land, through heavy timber and dense undergrowth.
15.00	Leave timber, brs. NW. and SE. Thence across open valley.
20.37	Fall 5 lks. N. of the standard $\frac{1}{4}$ sec. cor. of sec. 32, which is a limestone, 10 X 6 X 3 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General. The true course and distance of this line are therefore S.89°52'E., 20.37 chs.
	Thence East on a random line. Across open valley.
29.00	Wash, course N.
29.65	Enter heavy timber and dense undergrowth, brs. NE. and SW. Asc. 175 ft.
39.65	Spur, slopes N.80°E. Desc.
40.09	Fall 10 lks. N. of the standard cor. of secs. 32 and 33, which is a limestone, 10 X 8 X 8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General. The true course and distance of this half mile are therefore S.89°51'E., 40.09 chs. Land, level and rolling. Soil, 2nd rate. Timber, cedar, pinion, juniper and pine. Undergrowth, cactus, scrub oak and young timber.
	East on a random line, along S. bdy. of sec. 33. Over rolling mountainous land, through heavy timber and dense undergrowth. Desc.
15.00	Desc. on spur, slopes E., 125 ft.
35.00	Leave heavy, enter scattering timber, brs. N. and S.
40.20	Fall 4 lks. N. of the standard $\frac{1}{4}$ sec. cor. of sec. 33, which is a lava stone, 12 X 8 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General. The true course and distance of this half mile are therefore S.89°57'E., 40.20 chs.
	Thence East on a random line.
7.70	Head of wash, course NE.
40.08	Fall 9 lks. N. of the standard cor. of secs. 33 and 34, which is a lava stone, 8 X 6 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General. The true course and distance of this half mile are therefore S.89°52'E., 40.08 chs. Land, rolling mountainous. Soil, 2nd rate. Timber, cedar, pinion, juniper and pine. Undergrowth, scrub oak, cactus and young timber.
	East on a random line, along S. bdy. of sec. 34. Over rolling land, through scattering timber and undergrowth. Desc.
35.00	Leave scattering timber.
40.10	Intersect the standard $\frac{1}{4}$ sec. cor. of sec. 34, which is a sandstone, 10 X 10 X 8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General. The true course and distance of this half mile are therefore East 40.10 chs.
	Thence East on a random line.

Retracement of the 5th Standard Parallel North Through Fractional Range 6 West. 11

Chains.

1.20 Road, brs. N. to Seligman and S. to New Water.  
 3.90 Wash, 30 lks. wide, 6 ft. deep, course NE.  
 38.90 Wash, course N.15°W.  
 40.06 Fall 8 lks. S. of the standard cor. of secs. 34 and 35, which is a lava stone, 14 X 8 X 8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.  
 The true course and distance of this half mile are therefore N.89°53'E., 40.06 chs.  
 Land, rolling.  
 Soil, 2nd and 4th rates.  
 Timber, cedar, pinion, juniper and pine.  
 Undergrowth, cactus, scrub oak and young timber.

East on a random line, along the S. bdy. of sec. 35.  
 Over rolling prairie land.  
 Asc. gradually.  
 6.60 Road, brs. NW. to Seligman and SE. to Prescott.  
 15.00 Asc. 175 ft. Enter scattering timber, brs. NW. and SE.  
 26.50 Edge of mesa; brs. N. and S. Thence over level land.  
 40.03 Fall 6 lks. N. of the standard  $\frac{1}{4}$  sec. cor. of sec. 35, which is a lava stone, 15 X 10 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.  
 The true course and distance of this half mile are therefore S.89°55'E., 40.03 chs.

Thence East on a random line.  
 16.95 Head of draw, course NE. Asc.  
 24.00 Spur, slopes NE. Desc.  
 26.50 Rim of canyon, brs. NE. and SW. Desc. 140 ft.  
 31.60 Wash in canyon, course N. Asc.  
 32.50 Point of spur, slopes N. Desc.  
 35.70 Wash, course NW. Asc. 100 ft.  
 38.95 Rim of canyon, brs. NW. and SE. Thence over rolling land.  
 40.18 Intersect the standard cor. of secs. 35 and 36, which is a lava stone, 10 X 8 X 8 ins. above ground; firmly set, marked and witnessed as described by the Surveyor-General.  
 The true course and distance of this half mile are therefore East 40.18 chs.  
 Land, rolling and mountainous.  
 Soil, 2nd and 4th rates.  
 Timber, cedar, pinion, juniper and pine.  
 Undergrowth, cactus, scrub oak and young timber.

East on a random line, along the S. bdy. of sec. 36.  
 Over rolling land, through scattering timber and undergrowth.  
 Asc. gradually.  
 30.00 Spur, slopes N. Desc. gradually.  
 40.20 Fall 10 lks. N. of the standard  $\frac{1}{4}$  sec. cor. of sec. 36, which is a lava stone, 12 X 6 X 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.  
 The true course and distance of this half mile are therefore S.89°51'E., 40.20 chs.

Thence East on a random line.  
 11.00 Wash, course N. Asc. 90 ft.  
 29.80 Low spur, slopes N. Desc.  
 39.99 Intersect the standard cor. of Ts. 21 N., Rs. 5 and 6 W., which is a lava stone, 14 X 14 X 14 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.  
 The true course and distance of this half mile are therefore East 39.99 chs.

Retracement of the  
12 5th Standard Parallel North Through Fractional Range 6 West.

Chains.

Land, rolling.  
Soil, 2nd and 4th rate.  
Timber, cedar, pinion, pine and juniper.  
Undergrowth, scrub oak, cactus and young timber.

Retracement of Part of the  
5th Standard Parallel North Through Range 5 West.

From the standard cor. of Ts. 21 N., Rs. 5 and 6 W.,  
hereinbefore described,  
East on a random line, along S. bdy. of sec. 31.  
Over rolling land, through scattering timber and undergrowth.

8.80 Wash, course NW. Asc.  
13.50 Low spur, slopes N. Desc.  
21.60 Small canyon, course N. Asc.  
40.96 Fall 52 lks. S. of the standard  $\frac{1}{4}$  sec. cor. of sec. 31,  
which is a lava stone, 14 X 6 X 4 ins. above ground,  
firmly set, marked and witnessed as described by the  
Surveyor-General.

The true course and distance of this half mile are there-  
fore N.89°16'E., 40.96 chs.

Thence East on a random line.

4.20 Wash, course NW.  
26.50 Wash, course NW.  
27.05 Asc. 75 ft.  
33.55 Edge of mesa, brs. NW. and SE. Thence over level mesa,  
through heavy timber.  
40.04 Fall 47 lks. S. of the standard cor. of secs. 31 and 32,  
which is a lava stone, 12 X 10 X 6 ins. above ground,  
firmly set, marked and witnessed as described by the  
Surveyor-General.

The true course and distance of this half mile are there-  
fore N. 89°20'E., 40.04 chs.

Land, rolling and level.  
Soil, 2nd and 4th rate.  
Timber, cedar, pinion, juniper and pine.  
Undergrowth, scrub oak, cactus and young timber.

East on a random line, along the S. bdy. of sec. 32.  
Over level land, through heavy timber and dense under-  
growth.

31.00 Wash, course N.  
40.07 Fall 20 lks. S. of the standard  $\frac{1}{4}$  sec. cor. of sec. 32,  
which is a limestone, 14 X 12 X 2 ins. above ground,  
firmly set, marked and witnessed as described by the  
Surveyor-General.

The true course and distance of this half mile are there-  
fore N.89°43'E., 40.07 chs.

Land, level.  
Soil, 2nd and 4th rate.  
Timber, cedar, pinion, pine and juniper.  
Undergrowth, scrub oak, cactus and young timber.

Survey of the  
East Boundary of T. 20 N., R. 6 W.


BOOK 2975

Chains.

From the cor. of Ts. 19 and 20 N., Rs. 5 and 6 W., described in Book "B",  
North bet. secs. 31 and 36.  
Over mountainous land, through heavy timber and dense undergrowth.  
Desc. 85 ft.

9.50 Wash, course W. Asc. 200 ft.  
38.00 Ridge, brs. E. and W.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap



From which

- A pinion, 12 ins. diam., brs. N.40°E., 31 lks. dist., marked  $\frac{1}{4}$ S31 BT.
- A pinion, 12 ins. diam., brs. N.83 $\frac{1}{4}$ °W., 128 lks. dist., marked  $\frac{1}{4}$ S36 BT.

42.50 Desc. 35 ft.  
47.50 Wash, course W. Asc. 85 ft.  
58.00 Ridge, brs. E. and W. Desc. 100 ft.  
68.00 Wash, course W. Asc. 55 ft.  
77.00 Spur, slopes W. Desc. 30 ft.  
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 10 ins. in the ground, on bed rock, in a mound of stone, for cor. of secs. 25, 30, 31 and 36, marked on brass cap




From which

- A cedar, 14 ins. diam., brs. N.52°E., 56 lks. dist., marked T20N R5W S30 BT.
- A pinion, 10 ins. diam., brs. S.63°E., 10 lks. dist., marked T20N R5W S31 BT.
- A pinion, 14 ins. diam., brs. S.43 $\frac{1}{2}$ °W., 80 lks. dist., marked T20N R6W S36 BT.
- A cedar, 12 ins. diam., brs. N.33 $\frac{1}{2}$ °W., 46 lks. dist., marked T20N R6W S25 BT.

Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, cactus, scrub oak and young timber.

North bet. secs. 25 and 30.  
Over mountainous land, through heavy timber and dense undergrowth.

8.00 Desc. 60 ft.  
19.00 Draw, course W. Asc. 110 ft.  
30.00 Spur, slopes W. Desc. 85 ft.  
40.00 Wash, course W. Asc. 80 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 5 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap



From which

- A cedar, 8 ins. diam., brs. N.5°E., 8 lks. dist., marked  $\frac{1}{4}$ S30 BT.

14

Survey of the  
East Boundary of T. 20 N., R. 6 W.

Chains.

A cedar, 12 ins. diam., brs. N.60°W.,  
45 lks. dist., marked  $\frac{1}{4}$ S25 BT.  
Asc. 90 ft.  
47.00 Spur, slopes NW. Desc. 190 ft.  
64.00 Wash, course NE. Asc. 80 ft.  
78.50 Spur, slopes NE. Desc. 20 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the  
ground, on bed rock, in a mound of stone, for cor. of  
secs. 19, 24, 25 and 30, marked on brass cap

T20N	
R6W	R5W
S24	S19
S25	S30
1918	

## From which

A cedar, 10 ins. diam., brs. N.21°E.,  
32 lks. dist., marked T20N R5W S19 BT.  
A cedar, 14 ins. diam., brs. S.80 $\frac{3}{4}$ °E.,  
42 lks. dist., marked T20N R5W S30 BT.  
A pinion, 12 ins. diam., brs. S.12 $\frac{1}{2}$ °W.,  
60 lks. dist., marked T20N R6W S25 BT.  
A pinion, 12 ins. diam., brs. N.78 $\frac{1}{2}$ °W.,  
37 lks. dist., marked T20N R6W S24 BT.  
Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

North bet. secs. 19 and 24.  
Over mountainous land, through heavy timber and dense  
undergrowth.  
Desc. 160 ft.  
6.00 Wash, course NE.  
11.80 Draw, course E. Asc. 140 ft.  
19.50 Spur, slopes E. 2 chs. Desc. 140 ft.  
25.70 Wash, course E. Asc. 200 ft.  
38.00 Ridge, brs. E. and W. Thence over level land.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

S24	S19
1918	

## From which

A cedar, 14 ins. diam., brs. S.57 $\frac{1}{2}$ °E.,  
31 lks. dist., marked  $\frac{1}{4}$ S19 BT.  
A cedar, 12 ins. diam., brs. S.62°W.,  
41 lks. dist., marked  $\frac{1}{4}$ S24 BT.  
Asc. 60 ft.  
51.00 Top of knoll; thence over flat lava covered top of same.  
70.00 Leave top of knoll, desc. 20 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the  
ground, on bed rock, in a mound of stone, for cor. of  
secs. 13, 18, 19 and 24, marked on brass cap

T20N	
R6W	R5W
S13	S18
S24	S19
1918	

## From which

A pinion, 12 ins. diam., brs. N.72 $\frac{3}{4}$ °E.,  
67 lks. dist., marked T20N R5W S18 BT.

Survey of the  
East Boundary of T. 20 N., R. 6 W.

BOOK 2875

15

Chains.


- A cedar, 12 ins. diam., brs. S.56°10'E.,  
95 lks. dist., marked T20N R5W S19 BT.
- A cedar, 20 ins. diam., brs. S.53½°W.,  
76 lks. dist., marked T20N R6W S24 BT.
- A cedar, 14 ins. diam., brs. N.47°W.,  
40 lks. dist., marked T20N R6W S13 BT.

Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, cactus, scrub oak and young timber.

North bet. secs. 13 and 18.  
Over mountainous land, through heavy timber and dense  
undergrowth.


Desc.

- 16.00 Draw, course NE.
- 26.30 Canyon, course NW. Asc. 35 ft.
- 33.00 Spur, slopes W. Desc. 120 ft.
- 39.70 Canyon, course NW. Asc. 85 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., on solid rock,  
in a mound of stone, for ¼ sec. cor., marked on brass  
cap



From which

- A cedar, 30 ins. diam., brs. S.11°E.,  
34 lks. dist., marked ¼S18 BT.
- A cedar, 14 ins. diam., brs. N.42°W.,  
55 lks. dist., marked ¼S13 BT.
- 40.04 Pinion, 10 ins. diam., on line.
- 48.00 Spur, slopes W. Desc. 180 ft.
- 70.00 Wash, course NE. Asc. 115 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the  
ground, on bed rock, in a mound of stone, for cor. of  
secs. 7, 12, 13 and 18, marked on brass cap



From which

- A cedar, 12 ins. diam., brs. N.46½°E.,  
128 lks. dist., marked T20N R5W S7 BT.
- A cedar, 12 ins. diam., brs. S.59°E.,  
22 lks. dist., marked T20N R5W S18 BT.
- A cedar, 14 ins. diam., brs. S.56°W.,  
38 lks. dist., marked T20N R6W S13 BT.
- A pinion, 12 ins. diam., brs. N.57°W.,  
31 lks. dist., marked T20N R6W S12 BT.

Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

North bet. secs. 7 and 12.  
Over mountainous land, through scattering timber and under-  
growth.

- 38.16 Desc. 180 ft.
- 40.00 Wash, course NE. Continue descent, 20 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the  
ground, on bed rock, in a mound of stone, for ¼ sec.  
cor., marked on brass cap



Survey of the  
East Boundary of T. 20 N., R. 6 W.

Chains.

$\frac{1}{4}$   
 S12 | S 7  
 1918

From which

A cedar, 14 ins. diam., brs. N.20 $\frac{1}{2}$ °E.,  
71 lks. dist., marked  $\frac{1}{4}$ S7 BT.  
A cedar, 24 ins. diam., brs. S.79°W.,  
165 lks. dist., marked  $\frac{1}{4}$ S12 BT.

53.00 Wash, course NW.  
60.00 Same wash, course NE.  
62.80 Same wash, course NW.  
66.50 Foot of cliff, brs. NW. and SE. Asc. 75 ft.  
69.60 Rim rock, brs. NW. and SE. Asc. 30 ft.  
74.85 Top of asc.; thence over level land.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, marked on brass cap

T20N  
 R6W, R5W.  
S 1 | S 6  
 S12 | S 7  
 1918.

From which

A cedar, 12 ins. diam., brs. N.34 $\frac{1}{2}$ °E.,  
147 lks. dist., marked T20N R5W S6 BT.  
A cedar, 14 ins. diam., brs. S.81°E.,  
88 lks. dist., marked T20N R5W S7 BT.  
A cedar, 12 ins. diam., brs. S.41 $\frac{1}{2}$ °W.,  
97 lks. dist., marked T20N R6W S12 BT.  
A cedar, 12 ins. diam., brs. N.69°W.,  
83 lks. dist., marked T20N R6W S1 BT.

Land, level and mountainous.  
Soil, gravelly and rocky, 3rd and 4th rates.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

North bet. secs. 1 and 6.  
Over rolling land, through heavy timber and dense undergrowth.

40.00 Desc. gradually, 60 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S 1 | S 6  
 1918

From which

A cedar, 12 ins. diam., brs. S.88°E.,  
96 lks. dist., marked  $\frac{1}{4}$ S6 BT.  
A cedar, 16 ins. diam., brs. N.6 $\frac{1}{2}$ °W.,  
32 lks. dist., marked  $\frac{1}{4}$ S1 BT.

46.00 Desc. 45 ft.  
Draw, course NW.  
49.11 Intersect the 5th Standard Parallel North 2.25 chs. E. of the standard  $\frac{1}{4}$  sec. cor. of sec. 32, T. 21 N., R. 5 W., hereinbefore described.  
At the point of intersection,  
Set an iron post, 3 ft. long, 3 ins. diam., 10 ins. in the ground, on bed rock, in a mound of stone, for closing cor. of Tps. 20 N., Rs. 5 and 6 W., marked on brass cap

BOOK 2878

Survey of the  
East Boundary of T. 20 N., R. 6 W.

Chains.

T21N R5W  
S32  
S 1 | S 6  
R6W | R5W  
T20N  
C C  
1918

From which  
A pinion, 8 ins. diam., brs. S. 51 $\frac{1}{4}$ ° E.,  
42 lks. dist., marked CC T20N R5W S6 BT.  
A cedar, 20 ins. diam., brs. S. 56 $\frac{3}{4}$ ° W.,  
186 lks. dist., marked CC T20N R6W S1 BT.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, cedar and pinion.  
Undergrowth, cactus, scrub oak and young timber.

Boundaries of T. 20 N., R. 6 W.

Latitudes, departures and closing errors.

Line designated.	True bearing.	Dist. chs.	Latitudes.		Departures	
			N. chs.	S. chs.	E. chs.	W. chs.
South Boundary.	West	503.72				503.72
	North	28.10	28.10			
	N. 2°14'W.	39.00	38.97			1.52
	N. 0° 4'W.	39.74	39.74			.05
	North	40.09	40.09			
West Boundary.	N. 0°13'E.	41.27	41.27		.15	
	N. 1° 5'W.	38.59	38.58			.73
	N. 0°52'W.	39.04	39.04			.59
	North	40.18	40.18			
	N. 0°10'W.	38.23	38.23			.12
	N. 0°15'E.	39.59	39.59		.17	
	N. 0° 4'W.	39.11	39.11			.05
	North	25.57	25.57			
	S. 89°52'E.	20.37		.05	20.37	
	S. 89°51'E.	40.09		.10	40.09	
	S. 89°57'E.	40.20		.04	40.20	
	S. 89°52'E.	40.08		.09	40.08	
	East	40.10			40.10	
North Boundary	N. 89°53'E.	40.06	.08		40.06	
(5th Std. Par.N.)	S. 89°55'E.	40.03		.06	40.03	
	East	40.18			40.18	
	S. 89°51'E.	40.20		.10	40.20	
	East	39.99			39.99	
	N. 89°16'E.	40.96	.52		40.96	
	N. 89°20'E.	40.04	.47		40.04	
	N. 89°43'E.	40.07	.20		40.07	
	East	2.25			2.25	
Last Boundary	South	449.11		449.11		
Convergency					.51	
Totals			449.74	449.55	505.45	506.78
Error in latitude			449.55			505.45
Error in departure			.19			1.33

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of Tp., described in Book "C", N.0°1'W., bet. secs. 35 and 36.  
Over mountainous land, through heavy timber and dense undergrowth.

- 11.00 Desc. 15 ft.
- 11.00 Wash, course SE. Thence over nearly level land.
- 25.00 Asc. 100 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S35 | S36  
 1918

From which

- A cedar, 12 ins. diam., brs. N.80 $\frac{3}{4}$ °E., 55 lks. dist., marked  $\frac{1}{4}$ S36 BT.
- A cedar, 12 ins. diam., brs. N.20°W., 60 lks. dist., marked  $\frac{1}{4}$ S35 BT.

- Asc. 110 ft.
- 49.50 Spur, slopes SE. Desc. 65 ft.
- 59.00 Wash, course E. Asc. 140 ft.
- 63.50 Spur, slopes E. Desc. 80 ft.
- 70.50 Wash, course E. Asc. 50 ft.
- 77.00 Spur, slopes E. Desc. 40 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, on solid rock, in a mound of stone, for cor. of secs. 25, 26, 35 and 36, marked on brass cap

T20N | R6W  
 S26 | S25  
 S35 | S36  
 1918

From which

- A cedar, 16 ins. diam., brs. N.72°E., 51 lks. dist., marked T20N R6W S25 BT.
- A cedar, 12 ins. diam., brs. S.61°E., 23 lks. dist., marked T20N R6W S36 BT.
- A pinion, 10 ins. diam., brs. S.51 $\frac{3}{4}$ °W., 73 lks. dist., marked T20N R6W S35 BT.
- A pinion, 10 ins. diam., brs. N.47 $\frac{3}{4}$ °W., 38 lks. dist., marked T20N R6W S26 BT.

Land, mountainous and nearly level.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

- 40.00 East on a random line, bet. secs. 25 and 36.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.02 Intersect the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of Tp., hereinbefore described.
- Thence
- West on a true line, bet. secs. 25 and 36.
- Over mountainous land, through heavy timber and dense undergrowth.
- Desc. 145 ft.
- 19.50 Draw, course SW. Asc. 90 ft.
- 33.50 Spur, slopes S. Desc. 100 ft.
- 40.01 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

$\frac{1}{4}$  S25  
 $\frac{1}{4}$  S36  
1918

From which

A pinon, 10 ins. diam., brs. N.12 $\frac{1}{2}$ <sup>o</sup>W.,  
73 lks. dist., marked  $\frac{1}{4}$ S25 BT.  
A pinon, 12 ins. diam., brs. S.8<sup>o</sup>W.,  
44 lks. dist., marked  $\frac{1}{4}$ S36 BT.

42.60 Draw, course SE. Asc. 60 ft.  
47.30 Road, brs. NW. to Seligman and SE. to Prescott.  
55.00 Spur, slopes SE. Desc. 20 ft.  
65.50 Draw, course SE. Asc. 100 ft.  
80.02 The cor. of secs. 25, 26, 35 and 36.  
Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

N.0<sup>o</sup>1'W., bet. secs. 25 and 26.  
Over mountainous land, through heavy timber and dense under-  
growth.

Desc. 20 ft.  
1.75 Draw, course E. Asc. 40 ft.  
6.50 Spur, slopes E. Desc.  
19.00 Draw, course E. Asc. 40 ft.  
25.00 Spur, slopes E. Desc. 40 ft.  
33.50 Wash, course SE. Asc. 20 ft.  
33.70 Road, brs. NW. to Seligman and SE. to Prescott.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

S26 | S25  
1918

From which

A cedar, 14 ins. diam., brs. S.78 $\frac{3}{4}$ <sup>o</sup>E.,  
104 lks. dist., marked  $\frac{1}{4}$ S25 BT.  
A cedar, 12 ins. diam., brs. S.68<sup>o</sup>W.,  
100 lks. dist., marked  $\frac{1}{4}$ S26 BT.

Continue ascent, 190 ft.  
58.50 Ridge, brs. NW. and SE. Desc. 100 ft.  
73.00 Wash, course NW. Asc. 30 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the  
ground, on solid rock, in a mound of stone, for cor. of  
secs. 23, 24, 25 and 26, marked on brass cap

T20N R6W  
S23 | S24  
S26 | S25  
1918

From which

A cedar, 14 ins. diam., brs. N.62<sup>o</sup>E.,  
20 lks. dist., marked T20N R6W S24 BT.  
A pinion, 12 ins. diam., brs. S.19<sup>o</sup>E.,  
59 lks. dist., marked T20N R6W S25 BT.  
A cedar, 12 ins. diam., brs. S.71 $\frac{1}{2}$ <sup>o</sup>W.,  
57 lks. dist., marked T20N R6W S26 BT.  
A cedar, 12 ins. diam., brs. N.24<sup>o</sup>W.,  
30 lks. dist., marked T20N R6W S23 BT.

Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, cactus, scrub oak and young timber.

Chains.

40.00 East on a random line, bet. secs. 24 and 25.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.04 Intersect E. bdy. of Tp., 3 lks. N. of the cor. of secs.  
19, 24, 25 and 30, hereinbefore described.  
Thence  
N.  $89^{\circ}59'W.$ , on a true line, bet. secs. 24 and 25.  
Over mountainous land, through heavy timber and undergrowth.  
Along N. slope, descending 35 ft.  
5.55 Wash, course NE. Asc. 175 ft.  
22.45 Spur, slopes NE. Desc.  
27.05 Wash, course N. Asc. 40 ft.  
35.00 Spur, slopes NW. Desc. 20 ft.  
38.05 Draw, course NW. Asc. 10 ft.  
40.02 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$  S24  
 $\frac{1}{4}$  S25  
1918

From which

A cedar, 12 ins. diam., brs. N.  $70\frac{1}{2}^{\circ}W.$ ,  
35 lks. dist., marked  $\frac{1}{4}$  S24 BT.  
A pinion, 12 ins. diam., brs. S.  $16^{\circ}E.$ ,  
32 lks. dist., marked  $\frac{1}{4}$  S25 BT.

43.05 Spur, slopes N. Desc. 10 ft.  
43.95 Draw, course NW. Asc. 25 ft.  
61.95 Draw, course N. Thence along N. slope.  
76.75 Draw, course NW.  
80.04 The cor. of secs. 23, 24, 25 and 26.

Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

N.  $0^{\circ}1'W.$ , bet. secs. 23 and 24.  
Over mountainous and rolling land, through heavy timber  
and dense undergrowth.

Desc.  
1.30 Wash, course NW. Asc.  
3.00 Knoll, slopes W. Desc. 20 ft.  
13.00 Small canyon, course W. Thence along W. slope.  
20.00 Canyon, course NW.  
27.30 Wash, course SW.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$   
S23 | S24  
1918

From which

A pinion, 12 ins. diam., brs. N.  $51^{\circ}E.$ ,  
29 lks. dist., marked  $\frac{1}{4}$  S24 BT.  
A cedar, 12 ins. diam., brs. S.  $68^{\circ}W.$ ,  
40 lks. dist., marked  $\frac{1}{4}$  S23 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the  
ground, on solid rock, in a mound of stone, for cor. of  
secs. 13, 14, 23 and 24, marked on brass cap

T20N R6W  
S14 | S13  
S23 | S24  
1918


Survey of the  
Subdivision of T. 20 N., R. 6 W.

2975

Chains.


From which  
 A pinion, 12 ins. diam., brs. N.69°E.,  
 22 lks. dist., marked T20N R6W S13 BT.  
 A pinion, 12 ins. diam., brs. S.41¼°E.,  
 44 lks. dist., marked T20N R6W S24 BT.  
 A cedar, 12 ins. diam., brs. S.76½°W.,  
 40 lks. dist., marked T20N R6W S23 BT.  
 A cedar, 14 ins. diam., brs. N.41°W.,  
 77 lks. dist., marked T20N R6W S14 BT.  
 Land, rolling and mountainous.  
 Soil, gravelly, thin and dry; 4th rate.  
 Timber, cedar and pinion.  
 Undergrowth, scrub oak, cactus and young timber.

40.00 S.89°59'E., on a random line, bet. secs. 13 and 24.  
 80.00 Set temp. ¼ sec. cor.  
 Intersect E. bdy. of Tp., 11 lks. N. of the cor. of secs.  
 13, 18, 19 and 24, hereinbefore described.  
 Thence  
 N.89°54'W., on a true line, bet. secs. 13 and 24.  
 Over rolling land, through heavy timber and dense under-  
 growth.  
 Asc. gradually.  
 20.00 Divide, brs. NW. and SE. Desc. gradually.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
 ground, on solid rock, in a mound of stone, for ¼ sec.  
 cor., marked on brass cap



From which  
 A cedar, 12 ins. diam., brs. N.19°E.,  
 35 lks. dist., marked ¼S13 BT.  
 A pinion, 12 ins. diam., brs. S.67°W.,  
 60 lks. dist., marked ¼S24 BT.  
 77.00 Knoll. Desc. 10 ft.  
 80.00 The cor. of secs, 13, 14, 23 and 24.  
 Land, rolling.  
 Soil, gravelly, thin dry; 4th rate.  
 Timber, cedar, and pinion.  
 Undergrowth, cactus, scrub oak and young timber.

N.0°1'W., bet. secs. 13 and 14.  
 Over rolling land, through heavy timber and dense under-  
 growth.  
 Desc. 50 ft.  
 9.00 Head of ravine, course W. Asc. 20 ft.  
 14.00 Spur, slopes W. Desc. 160 ft.  
 32.00 Wash, course NW. Asc.  
 36.60 Spur, slopes W. Desc.  
 39.50 Wash, course SW. Asc. 130 ft.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
 ground, on bed rock, in a mound of stone, for ¼ sec.  
 cor., marked on brass cap



From which  
 A cedar, 12 ins. diam., brs. N.46°E.,  
 51 lks. dist., marked ¼S13 BT.  
 A pinion, 12 ins. diam., brs. S.75½°W.,  
 24 lks. dist., marked ¼S14 BT.

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

50.00 Ridge, brs. E. and W. Desc. 300 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, on solid rock, in a mound of stone, for cor. of secs. 11, 12, 13 and 14, marked on brass cap

T20N	R6W
S11	S12
S14	S13
1918	

From which

A pinion, 12 ins. diam., brs. N.70°E.  
26 lks. dist., marked T20N R6W S12 BT.  
A pinion, 12 ins. diam., brs. S.34°E.,  
37 lks. dist., marked T20N R6W S13 BT.  
A cedar, 12 ins. diam., brs. S.16½°W.,  
50 lks. dist., marked T20N R6W S14 BT.  
A cedar, 12 ins. diam., brs. N.34°W.,  
138 lks. dist., marked T20N R6W S11 BT.

Land, rolling.

Soil, gravelly, thin and dry; 4th rate.

Timber, cedar and pinion.

Undergrowth, cactus, scrub oak and young timber.

40.00 S.89°54'E., on a random line, bet, secs. 12 and 13.  
Set temp. ¼ sec. cor.  
79.92 Intersect the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of Tp., hereinbefore described.  
Thence  
N.89°54'W., on a true line, bet. secs. 12 and 13.  
Over mountainous land, through heavy timber and undergrowth.  
Asc. 215 ft.  
21.00 Spur, slopes S. Desc. 335 ft.  
38.40 Wash, course NW. Asc. 15 ft.  
39.96 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, on solid rock, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼ S12	S13
1918	

From which

A cedar, 14 ins. diam., brs. N.62°E.,  
82 lks. dist., marked ¼S12 BT.  
A cedar, 12 ins. diam., S.12½°W.,  
83 lks. dist., marked ¼S13 BT.

41.90 Spur, slopes N. Desc. 50 ft.  
46.90 Draw, course N. Asc. 70 ft.  
53.00 Thence over level top of spur, slopes NW.  
66.90 Desc. 75 ft.  
71.90 Draw, course NW. Asc. 10 ft.  
79.92 The cor. of secs. 11, 12, 13 and 14.  
Land, mountainous and level.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar, and pinion.  
Undergrowth, scrub oak, cactus and young timber.

40.00 N.0°1'W., bet. secs. 11 and 12.  
Over rolling land, through scattering timber and undergrowth.  
Desc. 75 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

$\frac{1}{4}$   
S11 | S12  
1918

From which

A cedar, 14 ins. diam., brs. S.64 $\frac{1}{2}$ °E.,  
229 lks. dist., marked  $\frac{1}{4}$ S12 BT.  
A cedar, 14 ins. diam., brs. N.19 $\frac{1}{2}$ °W.,  
140 lks. dist., marked  $\frac{1}{4}$ S11 BT.

58.00 Desc. gradually, 50 ft.  
61.00 Asc. 20 ft.  
76.00 Level spur, slopes E. Desc. 60 ft.  
80.00 Asc.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 1, 2, 11 and 12, marked on  
brass cap

T20N | R6W  
S 2 | S 1  
S11 | S12  
1918

From which

A cedar, 9 ins. diam., brs. S.9°E.,  
274 lks. dist., marked T20N R6W S12 BT.

No other trees within limits. Raise a mound of stone, 2  
ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.  
Land, rolling.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

40.00 S.89°54'E., on a random line, bet. secs. 1 and 12.  
79.94 Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect the cor. of secs. 1, 6, 7 and 12 on the E. bdy.  
of Tp., hereinbefore described.  
Thence  
15.95 N.89°54'W., on a true line, bet. secs. 1 and 12.  
19.95 Over rolling land, through scattering timber and undergrowth.  
39.97 Rim rock, brs. NW. and SE. Desc. 70 ft.  
Thence over level land:  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S 1  
S12  
1918

From which

A cedar, 12 ins. diam., brs. S.5°W.,  
290 lks. dist., marked  $\frac{1}{4}$ S12 BT.

69.94 No other trees within limits. Raise a mound of stone, 2  
79.94 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.  
Draw, course N.  
The cor. of secs. 1, 2, 11 and 12.  
Land, rolling and level.  
Soil, gravelly, black and dry; 3rd rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus and young timber.

40.00 N.0°1'W., on a true line, bet. secs. 1 and 2.  
Over rolling land, through scattering timber and under-  
growth.  
Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap



Chains.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 2 \mid \text{S } 1 \\ \frac{1}{4} \\ 1918 \end{array}$$

From which

A cedar, 20 ins. diam., brs. S.29 $\frac{1}{2}$ °E.,329 lks. dist., marked  $\frac{1}{4}$ S1 BT.

A cedar, 14 ins. diam., brs. S.60°W.,

250 lks. dist., marked  $\frac{1}{4}$ S2 BT.

48.72 Intersect the 5th Standard Parallel North, 2.67 chs.  
N.89°20'E. of the standard  $\frac{1}{4}$  sec. cor. of sec. 31,  
T. 21 N., R. 5 W., hereinbefore described.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the  
ground, on bed rock, in a mound of stone, for closing  
cor. of secs. 1 and 2, marked on brass cap
$$\begin{array}{c} \text{T21N R5W} \\ \text{S31} \\ \hline \text{S } 2 \mid \text{S } 1 \\ \text{T20N R6W} \\ \text{C } \mid \text{C} \\ 1918 \end{array}$$
And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, S.  
of cor.

Land, rolling.

Soil, gravelly, thin and dry; 4th rate.

Timber, cedar.

Undergrowth, quinine, scrub oak, cactus and young timber.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of  
Tp., described in Book "C",  
N.0°1'W., bet. secs. 34 and 35.

Over rolling mountainous land, through heavy timber and  
dense undergrowth.

Asc. 50 ft.

8.50 Main ridge, brs. N.10°W. and S.10°E. Desc. 30 ft.

16.15 Head of ravine, course E. Thence along E. slope.

21.70 Head of ravine, course S.70°E. Asc. 190 ft.

34.40 Top of hill, with old Indian ruins, brs. W. 1 ch. dist.  
Desc. 100 ft.40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor.,  
marked on brass cap
$$\begin{array}{c} \frac{1}{4} \\ \text{S34 } \mid \text{S35} \\ \frac{1}{4} \\ 1918 \end{array}$$

From which

A pinion, 8 ins. diam., brs. S.72 $\frac{1}{2}$ °E.,101 lks. dist., marked  $\frac{1}{4}$ S35 BT.A pinion, 12 ins. diam., brs. N.78 $\frac{3}{4}$ °W.,56 lks. dist., marked  $\frac{1}{4}$ S34 BT.

42.00 Head of draw, course SE. Asc.

46.00 Main ridge brs. N.10°E. and S.10°W. Desc. 50 ft.

57.10 Ravine, course NW. Thence along W. slope.

61.40 Ravine, course W. Asc. 50 ft.

66.30 Spur, slopes NW. Desc.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the  
ground, on bed rock, in a mound of stone, for cor. of  
secs. 26, 27, 34 and 35, marked on brass cap

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

T20N R6W  
S27 S26  
S34 S35  
1918

From which

- A cedar, 14 ins. diam., brs. N.43 $\frac{3}{4}$ °E.,  
64 lks. dist., marked T20N R6W S26 BT.
- A cedar, 16 ins. diam., brs. S.42 $\frac{1}{2}$ °E.,  
48 lks. dist., marked T20N R6W S35 BT.
- A cedar, 20 ins. diam., brs. S.44 $\frac{3}{4}$ °W.,  
65 lks. dist., marked T20N R6W S34 BT.
- A pinion, 12 ins. diam., brs. N.44 $\frac{1}{2}$ °W.,  
32 lks. dist., marked T20N R6W S27 BT.

Land, rolling mountainous.  
Soil, gravelly clay and sandy loam, 2nd to 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, algerita, mesquite and cactus.

40.00  
79.98

East on a random line, bet. secs. 26 and 35.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect N. and S. line, 9 lks. N. of the cor. of secs.  
25, 26, 35 and 36.

Thence  
N.89°56'W., on a true line, bet. secs. 26 and 35.  
Over mountainous land, through heavy timber and dense under-  
growth.

3.00  
13.00  
19.50  
36.00  
39.99

Asc. 125 ft.  
Wash, course NE. Continue ascent.  
Spur, slopes NE. Desc. 20 ft.  
Wash, course NE. Asc. 180 ft.  
Ridge, brs. NW. and SE. Desc. 140 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor.,  
marked on brass cap

$\frac{1}{4}$  S26  
 $\frac{1}{4}$  S35  
1918

From which

- A cedar, 18 ins. diam., brs. N.15°E.,  
21 lks. dist., marked  $\frac{1}{4}$ S26 BT.
- A cedar, 14 ins. diam., brs. S.5°W.,  
32 lks. dist., marked  $\frac{1}{4}$ S35 BT.

48.00  
63.00  
79.98

Draw, course SE. Asc. 250 ft.  
Hill. Indian ruins br. N. 3 chs. dist. Desc. 140 ft.  
The cor. of secs. 26, 27, 34 and 35.  
Land, mountainous.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, quinine, scrub oak, cactus, algerita and young  
timber.

6.30  
27.10  
33.90  
40.00

N.0°1'W., bet. secs. 26 and 27. dense undergrowth  
Over rolling mountainous land, through heavy timber and  
Asc. 40 ft.  
Ridge, brs. E. and W. Desc. 230 ft.  
Ravine, course NW.  
Same ravine; course NE. Asc. 60 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor.,  
marked on brass cap

$\frac{1}{4}$   
S27 S26  
1918

Chains.

From which

- A pinion, 12 ins. diam., brs. N.30°E.,  
70 lks. dist., marked  $\frac{1}{4}$ S26 BT.  
A pinion, 10 ins. diam., brs. S.79 $\frac{1}{2}$ °W.,  
86 lks. dist., marked  $\frac{1}{4}$ S27 BT.
- 41.90 Spur, slopes NE. Desc. 90 ft.  
48.20 Ravine, course NW. Asc. 25 ft.  
53.00 Spur, slopes W. Desc. 110 ft.  
64.70 Ravine, course W. Asc. 20 ft.  
67.00 Short spur, slopes W. Leave heavy, enter scattering timber.  
Desc. 25 ft.  
69.70 Same ravine, course NE. Asc. 20 ft.  
71.00 Short spur, slopes NE. Desc. 25 ft.  
72.00 Same ravine, course W. Asc. 50 ft.  
74.40 Spur, slopes W. Desc. 50 ft.  
75.70 Draw, course NW. Asc. 50ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., on solid rock,  
in a mound of stone, for cor. of secs. 22, 23, 26 and 27,  
marked on brass cap

T20N	R6W
S22	S23
S27	S26
1918	

From which

- A pinion, 8 ins. diam., brs. N.77 $\frac{1}{2}$ °E.,  
37 lks. dist., marked T20N R6W S23 BT.  
A cedar, 8 ins. diam., brs. S.71 $\frac{1}{2}$ °E.,  
24 lks. dist., marked T20N R6W S26 BT.  
A pinion, 12 ins. diam., brs. S.2°W.,  
30 lks. dist., marked T20N R6W S27 BT.  
A cedar, 14 ins. diam., brs. N.74 $\frac{1}{2}$ °W.,  
54 lks. dist., marked T20N R6W S22 BT.
- Land, rolling mountainous.  
Soil, rocky, 4th rate.  
Timber, cedar and pinion.  
Undergrowth, quinine, scrub oak, cactus and young timber.

- 40.00 S.89°56'E., on a random line, bet. secs. 23 and 26.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.12 Intersect N. and S. line, 5 lks. S. of the cor. of secs.  
23, 24, 25 and 26.  
Thence  
N.89°58'W., on a true line, bet. secs. 23 and 26.  
Over rolling mountainous land, through heavy timber and  
dense undergrowth.  
4.50 Wash, course NW. Asc.  
23.00 Ridge, brs. NW. and SE., and W. Thence along S. slope of  
ridge.  
27.80 Head of draw, course SW.  
40.06 Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$	S23
$\frac{1}{4}$	S26
1918	

From which

- A pinion, 10 ins. diam., brs. N.33 $\frac{1}{2}$ °E.,  
34 lks. dist., marked  $\frac{1}{4}$ S23 BT.  
A pinion, 10 ins. diam., brs. S.53 $\frac{1}{2}$ °W.,  
25 lks. dist., marked  $\frac{1}{4}$ S26 BT.
- 49.55 Road, brs. NW. to Seligman and SE. to Prescott.  
75.10 Leave ridge, brs. E. and NW. Desc. 60 ft.  
80.12 The cor. of secs. 22, 23, 26 and 27.  
Land, rolling mountainous.  
Soil, rocky, 2nd to 4th rate .  
Timber, cedar and pinion.

Survey of the  
Subdivision of T. 20 N., R. 6 W. BOOK 2875 27


Chains.

Undergrowth, quinine, scrub oak, cactus and young timber.

N.0°1'W., bet. secs. 22 and 23.  
Over rolling mountainous land, through heavy timber and dense undergrowth.

Asc. 50 ft.

- 4.80 Spur, slopes N.75°W. Desc. 125 ft.
- 13.00 Ravine, course NW. Asc. 175 ft.
- 13.80 Road, brs. NW. to Seligman and SE. to Prescott.
- 15.00 Cabin brs. West approximately 15 chs. dist. Numerous location shafts and tunnels br. West about 10 chs. dist.
- 18.40 Trail, brs. NW. and SE.
- 30.00 Dim road, brs. NE. and SW.
- 31.40 Spur, slopes NW. Desc. 50 ft.
- 32.10 Dim road, brs. NW. and SE.
- 34.70 Ravine, course NW. Asc. 35 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap




From which

A pinion, 10 ins. diam., brs. N.77°E.,  
24 lks. dist., marked  $\frac{1}{4}$ S23 BT.

A pinion, 10 ins. diam., brs. N.52°W.,  
47 lks. dist., marked  $\frac{1}{4}$ S22 BT.

From this cor., U. S. L. M. No. 2282, Chino Mining District,  
brs. S.79°57'W. 13.69 chs. dist.

- 42.00 Short spur, slopes W. Desc. 115 ft.
- 53.00 Ravine, course SW. Asc. 120 ft.
- 62.60 Spur, slopes NW. Desc. 210 ft.
- 76.00 Enter open valley, brs. NW. and SE.
- 76.30 Wash, course NW.
- 79.80 Leave open valley, brs. NW. and SE., and enter heavy timber.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, marked on brass cap



From which

A pinion, 12 ins. diam., brs. N.44°E.,  
64 lks. dist., marked T20N R6W S14 BT.

A pinion, 20 ins. diam., brs. S.39 $\frac{1}{2}$ °E.,  
82 lks. dist., marked T20N R6W S23 BT.

A pinion, 14 ins. diam., brs. S.59 $\frac{1}{2}$ °W.,  
216 lks. dist., marked T20N R6W S22 BT.

A pinion, 16 ins. diam., brs. N.45 $\frac{1}{2}$ °W.,  
132 lks. dist., marked T20N R6W S15 BT.

Land, rolling mountainous.  
Soil, rocky, 2nd and 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, quinine, cactus and young timber.

- 40.00 S.89°58'E., on a random line, bet. secs. 14 and 23.  
Set temp.  $\frac{1}{4}$  sec. cor.
- 80.10 Intersect N. and S. line, 10 lks. S. of the cor. of secs. 13, 14, 23 and 24.  
Thence  
S.89°58'W., on a true line, bet. secs. 14 and 23.  
Over rolling mountainous land, through heavy timber and

Chains.

- dense undergrowth.  
Desc. 145 ft.  
15.30 Ravine, course NW. Asc. 40 ft.  
20.90 Spur, slopes NW. Desc. 75 ft.  
27.10 Ravine, course SW. Asc. 75 ft.  
37.30 Spur, slopes SW. Leave heavy, enter scattering timber.  
Desc. 60 ft.  
40.05 Set an iron post, 3 ft. long, 1 in. diam., on solid rock,  
in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass  
cap

$$\begin{array}{r} \frac{1}{4} S14 \\ \frac{1}{4} S23 \\ 1918 \end{array}$$

From which

- A cedar, 20 ins. diam., brs. N.  $5\frac{1}{2}^{\circ}$ E.,  
53 lks. dist., marked  $\frac{1}{4}$ S14 BT.  
A cedar, 30 ins. diam., brs. S.  $46\frac{1}{4}^{\circ}$ W.,  
28 lks. dist., marked  $\frac{1}{4}$ S23 BT.  
40.10 Ravine, course S. Asc. along S. slope.  
60.50 Short spur, slopes S. Desc. 225 ft.  
77.10 Leave scattering, enter heavy timber.  
80.10 The cor. of secs. 14, 15, 22 and 23.  
Land, rolling mountainous.  
Soil, rocky, 4th rate.  
Timber, cedar and pinion.  
Undergrowth, quinine, scrub oak, cactus and young timber.

- N.  $0^{\circ}1'$ W., bet. secs. 14 and 15.  
Over rolling mountainous land, through heavy timber and  
dense undergrowth.  
Asc. 135 ft.  
9.70 Short spur, slopes NW. Desc. 110 ft.  
16.20 Draw, course W. Leave heavy, enter scattering timber, brs.  
E. and W. Asc. 235 ft.  
29.50 Spur, slopes W. Thence along W. slope.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \\ S15 \mid S14 \\ 1918 \end{array}$$

From which

- A cedar, 10 ins. diam., brs. N.  $78\frac{1}{2}^{\circ}$ E.,  
61 lks. dist., marked  $\frac{1}{4}$ S14 BT.  
A cedar, 10 ins. diam., brs. S.  $47\frac{1}{2}^{\circ}$ W.,  
70 lks. dist., marked  $\frac{1}{4}$ S15 BT.  
42.00 Spur, slopes NW. Enter heavy timber, brs. NW. and SE. Desc.  
225 ft.  
62.30 Ravine, course NW. Leave heavy, enter scattering timber.  
Continue descent.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the  
ground, on bed rock, in a mound of stone, for cor. of  
secs. 10, 11, 14 and 15, marked on brass cap

$$\begin{array}{r} T20N \mid R6W \\ S10 \mid S11 \\ \hline S15 \mid S14 \\ 1918 \end{array}$$

From which

- A cedar, 12 ins. diam., brs. N.  $85^{\circ}$ E.,  
110 lks. dist., marked T20N R6W S11 BT.  
A cedar, 16 ins. diam., brs. S.  $81\frac{1}{2}^{\circ}$ E.,  
230 lks. dist., marked T20N R6W S14 BT.  
A cedar, 10 ins. diam., brs. S.  $54\frac{3}{4}^{\circ}$ W.,  
65 lks. dist., marked T20N R6W S15 BT.

Survey of the  
Subdivision of T. 20 N., R. 6 W. **BOOK 2975 29**

Chains.

A cedar, 7 ins. diam., brs. N.21 $\frac{1}{2}$ °W.,  
139 lks. dist., marked T20N R6W S10 BT.  
Land, rolling mountainous.  
Soil, gravelly and rocky; 2nd to 4th rate.  
Timber, cedar and pinion.  
Undergrowth, algerita, quinine, scrub oak, cactus and young  
timber.

40.00 N.89°58'E., on a random line, bet. secs. 11 and 14.  
79.86 Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect N. and S. line, 10 lks. S. of the cor. of secs.  
11, 12, 13 and 14.  
Thence  
S.89°54'W., on a true line, bet. secs. 11 and 14.  
Over mountainous land, through heavy timber and scattering  
undergrowth.  
Asc. 10 ft.  
3.50 Spur, slopes N. Desc. 35 ft.  
6.40 Wash, course N. Asc. 40 ft.  
19.00 Spur, slopes N. Thence along N. slope.  
39.93 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$  S11  
 $\frac{1}{4}$  S14  
1918

From which

A cedar, 14 ins. diam., brs. N.32 $\frac{1}{2}$ °W.,  
58 lks. dist., marked  $\frac{1}{4}$ S11 BT.  
A pinion, 14 ins. diam., brs. S.51°E.,  
40 lks. dist., marked  $\frac{1}{4}$ S14 BT.

Desc.  
44.00 Wash, course N. Asc. 40 ft.  
51.00 Spur, slopes N. Desc.  
58.00 Wash, course N. Thence over broken lava beds.  
79.86 The cor. of secs. 10, 11, 14 and 15.  
Land, mountainous and rolling.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, quinine, cactus, algerita and  
young timber.

N.0°1'W., bet. secs. 10 and 11.  
Over rolling land, through scattering timber and under-  
growth.

Desc.  
13.00 Enter heavy timber, brs. E. and W.  
28.80 Wash, course NE. Thence along E. slope.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$   
S10 | S11  
1918

From which

A cedar, 30 ins. diam., brs. N.54 $\frac{1}{4}$ °E.,  
74 lks. dist., marked  $\frac{1}{4}$ S11 BT.  
A cedar, 20 ins. diam., brs. S.47 $\frac{1}{4}$ °W.,  
100 lks. dist., marked  $\frac{1}{4}$ S10 BT.

49.70 Draw, course NW. Asc.  
51.90 Spur, slopes W. 1 ch. Desc.  
53.25 Draw, course W. Asc.

30

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

59.00 Leave heavy, enter scattering timber, brs. E. and W.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the  
ground, on solid rock, in a mound of stone, for cor. of  
secs. 2, 3, 10 and 11, marked on brass cap

T20N	R6W
S 3	S 2
S10	S11
1918	

From which

A cedar, 10 ins. diam., brs. S.0°30'W.,  
337 lks. dist., marked T20N R6W S10 BT.

A cedar, 12 ins. diam., brs. N.11°W.,  
194 lks. dist., marked T20N R6W S3 BT.

No other trees within limits. Raise a mound of stone, 2  
ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, 2nd and 4th rate.

Timber, cedar and pinion.

Undergrowth, quinine, cactus, scrub oak and young timber.

40.00 N.89°54'E., on a random line, bet. secs. 2 and 11.  
Set temp. ¼ sec. cor.  
79.82 Intersect N. and S. line, 7 lks. N. of the cor. of secs.  
1, 2, 11 and 12.

Thence

S.89°57'W., on a true line, bet. secs. 2 and 11.

Over rolling land, through scattering timber and under-  
growth.

29.80 Head of draw, course N.20°E. Asc. gradually.

39.91 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for ¼ sec. cor., marked on brass cap

¼	S 2
¼	S11
1918	

From which

A cedar, 14 ins. diam., brs. N.72°W.,  
119 lks. dist., marked ¼S2 BT.

A cedar, 12 ins. diam., brs. S.3¾°E.,  
139 lks. dist., marked ¼S11 BT.

70.80 Low ridge, brs. N. and S. Desc. gradually.

79.82 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.

Soil, 2nd and 4th rate.

Timber, cedar and pinion.

Undergrowth, scrub oak, cactus, algerita, quinine and young  
timber.

40.00 N.0°1'W., on a true line, bet. secs. 2 and 3.  
Over rolling land, through scattering timber and under-  
growth.  
Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the  
ground, on bed rock, in a mound of stone, for ¼ sec.  
cor., marked on brass cap

S 3	S 2
1918	

Survey of the  
Subdivision of T. 20 N., R. 6 W.

BOOK 2875 31

Chains.

From which


A cedar, 30 ins. diam., brs. S.89 $\frac{3}{4}$ °E.,  
184 lks. dist., marked  $\frac{1}{4}$ S2 BT.  
A cedar, 12 ins. diam., brs. N.11 $\frac{1}{4}$ °W.,  
537 lks. dist., marked  $\frac{1}{4}$ S3 BT.

42.30 Spur, slopes NE. Desc.

48.52 Intersect 5th Standard Parallel North, 4.01 chs. E. of the  
standard  $\frac{1}{4}$  sec. cor of sec. 36, T. 21 N., R. 6 W.,  
hereinbefore described.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the  
ground, on bed rock, in a mound of stone, for closing  
cor. of secs. 2 and 3, marked on brass cap



From which

A cedar, 30 ins. diam., brs. S.29 $\frac{1}{2}$ °E.,  
170 lks. dist., marked CC T20N R6W S2 BT.  
A cedar, 14 ins. diam., brs. S.18 $\frac{3}{4}$ °W.,  
338 lks. dist., marked CC T20N R6W S3 BT.

Land, rolling.

Soil, 2nd and 4th rates..

Timber, cedar and pinion.

Undergrowth, quinine, scrub oak, cactus, algerita and young  
timber.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of  
Tp., described in Book "C",  
N.0°2'W., bet. secs. 33 and 34.

Over mountainous land, through heavy timber and dense under-  
growth.

Asc. 30 ft.


5.00 Spur, slopes W. Desc. 30 ft.

11.00 Wash, course W. Asc. 45 ft.

21.00 Spur, slopes W. Desc. gradually.

35.00 Asc. 20 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap



From which

A pinion, 8 ins. diam., brs. S.85°E.,  
25 lks. dist., marked  $\frac{1}{4}$ S34 BT.  
A pinion, 8 ins. diam., brs. N.74°W.,  
20 lks. dist., marked  $\frac{1}{4}$ S33 BT.

Asc. 15 ft.

42.00 Spur, slopes W. Desc. 10 ft.

58.50 Wash, course W. Desc. 30 ft.

69.00 Low point, drains W. Asc. 50 ft.

79.75 Draw, course SW. Asc.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the  
ground, on bed rock, in a mound of stone, for cor. of  
secs. 27, 28, 33 and 34, marked on brass cap



Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

T20N	R6W
S28	S27
S33	S34
1918	

From which

- A pinion, 12 ins. diam., brs. N.48°E.,  
58 lks. dist., marked T20N R6W S27 BT.
- A cedar, 8 ins. diam., brs. S.20°E.,  
42 lks. dist., marked T20N R6W S34 BT.
- A pinion, 10 ins. diam., brs. S.46½°W.,  
59 lks. dist., marked T20N R6W S33 BT.
- A cedar, 12 ins. diam., brs. N.89°W.,  
19 lks. dist., marked T20N R6W S28 BT.

Land, mountainous and rolling.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, pinion and cedar.  
Undergrowth, cactus, quinine, scrub oak, algerita and young timber.

- 40.00 East on a random line, bet. secs. 27 and 34.
- Set temp. ¼ sec. cor.
- 79.90 Intersect N. and S. line, 12 lks. N. of the cor. of secs. 26, 27, 34 and 35.
- Thence
- N.89°55'W., on a true line, bet. secs. 27 and 34.
- Over rolling and mountainous land, through heavy timber and dense undergrowth.
- Desc.
- 4.90 Asc. 55 ft.
- 17.90 Hill. Desc. 135 ft.
- 28.90 Wash, course NW. Asc.
- 31.90 Low ridge, brs. NW and SE. Desc. 15 ft.
- 34.70 Wash, course NW. Asc. 20 ft.
- 39.95 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, on solid rock, in a mound of stone, for ¼ sec. cor., marked on brass cap

1	S27
4	S34
1918	

From which

- A cedar, 16 ins. diam., brs. N.6½°W.,  
52 lks. dist., marked ¼ S27 BT.
- A pinion, 12 ins. diam., brs. S.4°E.,  
40 lks. dist., marked ¼ S34 BT.
- 69.90 Ridge, brs. NW and SE. Desc. 100 ft.
- 79.75 Draw, course SW. Asc.
- 79.90 The cor. of secs. 27, 28, 33 and 34.
- Land, rolling and mountainous.
- Soil, gravelly, thin and dry; 4th rate.
- Timber, cedar and pinion.
- Undergrowth, scrub oak, cactus, quinine, algerita and young timber.

- 12.95 N.0°2'W., bet. secs. 27 and 28.
- 15.85 Over rolling mountainous land, through heavy timber and dense undergrowth.
- 22.00 Asc. 100 ft.
- 40.00 Ridge, brs. E. and W. Desc. 50 ft.
- Draw, course N.75°E. Asc. 40 ft.
- Spur, slopes NE. Thence over rolling land.
- Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, on solid rock, in a mound of stone, for ¼ sec. cor., marked on brass cap

Chains.

S28 | S27  
1918

From which

A pinion, 8 ins. diam., brs. S.29½°E.,  
35 lks. dist., marked ¼S27 BT.  
A pinion, 12 ins. diam., brs. S.88½°W.,  
145 lks. dist., marked ¼S28 BT.

40.65 Draw, course E. Asc. 50 ft.  
45.40 Spur, slopes E. Desc. 75 ft.  
59.75 Draw, course NE. Asc. 25 ft.  
68.00 Spur, slopes N. Desc.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., on solid rock,  
in a mound of stone, for cor. of secs. 21, 22, 27 and  
28, marked on brass cap

T20N R6W  
S21 | S22  
S28 | S27  
1918

From which

A pinion, 18 ins. diam., brs. N.38½°E.,  
63 lks. dist., marked T20N R6W S22 BT.  
A pinion, 10 ins. diam., brs. S.41°E.,  
13 lks. dist., marked T20N R6W S27 BT.  
A cedar, 10 ins. diam., brs. S.33½°W.,  
25 lks. dist., marked T20N R6W S28 BT.  
A cedar, 15 ins. diam., brs. N.9½°W.,  
80 lks. dist., marked T20N R6W S21 BT.

Land, rolling mountainous.  
Soil, 2nd and 4th rates.  
Timber, cedar and pinion.  
Undergrowth, quinine, cactus, algerita, scrub oak and  
young timber.

40.00 S.89°55'E., on a random line, bet. secs. 22 and 27.  
Set temp. ¼ sec. cor.  
80.10 Intersect N. and S. line, 33 lks. S. of the cor. of secs.  
22, 23, 26 and 27.  
Thence  
S.89°51'W., on a true line, bet. secs. 22 and 27.  
Over rolling mountainous land, through heavy timber and  
dense undergrowth.  
2.00 Leave heavy, enter scattering timber.  
6.70 Spur, slopes 3 chs. S. Desc. 100 ft.  
14.00 Ravine, course N.15°W. Thence along N. slope.  
14.84 From this point, Cor. No. 4 of Iron Horse Mining Claim,  
Survey No. 2282, Chino Mining District, brs. S.60°13'E.,  
3.19 chs. dist. Old shaft, 50 ft. deep, brs. S.78¾°E.  
2.90 chs. dist.  
17.00 Draw, course N.15°E. Asc. 140 ft.  
18.00 Enter heavy timber, brs. N. and S.  
30.00 Flat top spur, slopes N. Desc. 35 ft.  
40.05 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground, on bed rock, in a mound of stone, for ¼ sec. cor.,  
marked on brass cap

¼ S22  
¼ S27  
1918


From which

A pine, 8 ins. diam., brs. N.19°W.,  
37 lks. dist., marked ¼S22 BT.  
A cedar, 16 ins. diam., brs. South  
22 lks. dist., marked ¼S27 BT.

Survey of the  
Subdivision of T. 20 N., R. 6 W.


Chains. Desc. 75 ft.  
45.80 Ravine, course N. Asc. 135 ft.  
53.10 Spur, slopes N. Desc. 65 ft.  
56.80 Ravine, course NW. Asc. 100 ft.  
67.70 Spur, slopes N. Desc. 75 ft.  
74.90 Ravine, course N. Asc. 65 ft.  
80.10 The cor. of secs. 21, 22, 27 and 28.  
Land, rolling mountainous.  
Soil, rocky, 2nd and 4th rates.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus, quinine, algerita and young timber.

N.0°2'W., bet. secs. 21 and 22.  
Over rolling mountainous land, through heavy timber and dense undergrowth.  
Desc. 320 ft. on short spur, slopes N.  
13.90 Ravine, course N.10°E. Continue descent.  
23.00 Enter wash, course N., from S.10°E.  
26.00 Leave wash, course N.15°W. Thence over rolling land.  
31.00 Leave heavy, enter scattering timber, brs. E. and W.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap



From which  
A cedar, 10 ins. diam., brs. S.81 $\frac{3}{4}$ °E.,  
47 lks. dist., marked  $\frac{1}{4}$ S22 BT.  
A cedar, 16 ins. diam., brs. N.59 $\frac{1}{2}$ °W.,  
18 lks. dist., marked  $\frac{1}{4}$ S21 BT.

Thence over gently rolling land.  
77.20 Center of draw, course NW.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on brass cap



From which  
A cedar, 10 ins. diam., brs. N.12 $\frac{1}{4}$ °E.,  
186 lks. dist., marked T20N R6W S15 BT.  
A cedar, 16 ins. diam., brs. S.57°E.,  
270 lks. dist., marked T20N R6W S22 BT.  
A cedar, 24 ins. diam., brs. S.66 $\frac{3}{4}$ °W.,  
413 lks. dist., marked T20N R6W S21 BT.  
A cedar, 12 ins. diam., brs. N.27 $\frac{1}{4}$ °W.,  
430 lks. dist., marked T20N R6W S16 BT.

Land, rolling mountainous, rolling and gently rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus, quinine, algerita and young timber.

40.00 N.89°51'E., on a random line, bet. secs. 15 and 22.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.02 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 14, 15, 22 and 23.  
Thence  
S.89°49'W., on a true line, bet. secs. 15 and 22.  
Over rolling land, through open valley.  
Desc.

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.  
 3.30 Wash, course NW.  
 4.00 Leave valley, brs. NW. and SE. Enter heavy timber, brs. NW. and SE. Asc. 240 ft.  
 15.80 Spur, slopes NW. Desc. 310 ft.  
 39.70 Leave heavy, enter scattering timber, brs. N. and S.  
 40.01 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S15  
 $\frac{1}{4}$  S22  
 1918

From which  
 A pine, 12 ins. diam., brs. N. 20 $\frac{1}{2}$ °W.,  
 54 lks. dist., marked  $\frac{1}{4}$ S15 BT.  
 A pine, 10 ins. diam., brs. S. 60°E.,  
 22 lks. dist., marked  $\frac{1}{4}$ S22 BT.

43.10 Ravine, course NW. Asc. 40 ft.  
 46.00 Road, brs. NW. to Seligman and SE. to Prescott.  
 50.00 Short spur, slopes N. Desc. 30 ft.  
 53.10 Draw, course N. Asc. 50 ft.  
 60.10 Spur, slopes N. Desc.  
 66.80 Draw, course NW. Asc.  
 71.00 Low spur, slopes NW. Desc. 75 ft.  
 80.02 The cor. of secs. 15, 16, 21 and 22.  
 Land, rolling.  
 Soil, gravelly and rocky; 2nd and 4th rate.  
 Timber, cedar, pinion and pine.  
 Undergrowth, scrub oak, cactus, algerita, quinine and young timber.

N. 0° 2' W., bet. secs. 15 and 16.  
 Over rolling land, through scattering timber and undergrowth.  
 Asc.

5.80 Low spur, slopes N. Desc. on spur.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S16 | S15  
 1918

From which  
 A pinion, 20 ins. diam., brs. S. 43°E.,  
 219 lks. dist., marked  $\frac{1}{4}$ S15 BT.  
 A pinion, 14 ins. diam., brs. S. 35°W.,  
 65 lks. dist., marked  $\frac{1}{4}$ S16 BT.

45.00 Spur, slopes N. 10°W. Desc.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap

T20N R6W  
 S 9 | S10  
 S16 | S15  
 1918

From which  
 A pinion, 16 ins. diam., brs. N. 59°E.,  
 278 lks. dist., marked T20N R6W S10 BT.  
 A pinion, 20 ins. diam., brs. S. 69 $\frac{1}{2}$ °E.,  
 223 lks. dist., marked T20N R6W S15 BT.  
 A pinion, 16 ins. diam., brs. S. 48 $\frac{1}{2}$ °W.,  
 499 lks. dist., marked T20N R6W S16 BT.  
 A cedar, 10 ins. diam., brs. N. 88 $\frac{1}{2}$ °W.,  
 258 lks. dist., marked T20N R6W S9 BT.

Chains.

Land, rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar, pine and pinion.  
Undergrowth, scrub oak, cactus, quinine, algerita and  
young timber.

40.00 N.89°49'E., on a random line, bet. secs. 10 and 15.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.18 Intersect N. and S. line, 2 lks. S. of the cor. of secs.  
10, 11, 14 and 15.  
Thence  
S.89°48'W., on a true line, bet. secs. 10 and 15.  
Over rolling land, through scattering timber and under-  
growth.  
20.00 Enter heavy timber, brs. N. and S.  
35.00 Desc. 80 ft.  
40.09 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$  S10  
 $\frac{1}{4}$  S15  
1918

From which

A pine, 14 ins. diam., brs. N.20°W.,  
200 lks. dist., marked  $\frac{1}{4}$ S10 BT.  
A cedar, 14 ins. diam., brs. S.19 $\frac{1}{2}$ °W.,  
115 lks. dist., marked  $\frac{1}{4}$ S15 BT.  
Desc. 45 ft.  
45.90 Ravine, course N.15°W. Asc. 160 ft.  
53.00 Spur, slopes NW. Desc. 215 ft.  
71.30 Road, brs. N. to Seligman and S. to Prescott.  
74.20 Ravine, course N.10°W. Asc. 75 ft.  
80.18 The cor. of secs. 9, 10, 15 and 16.  
Land, rolling and mountainous.  
Soil, 2nd and 4th rates.  
Timber, cedar, pine and pinion.  
Undergrowth, algerita, quinine, scrub oak, cactus and  
young timber.

N.0°2'W., bet. secs. 9 and 10.  
Over rolling land, through scattering timber and dense  
undergrowth.  
Asc. 35 ft.  
10.00 Enter heavy timber, brs. NW. and SE. Desc. 160 ft.  
22.00 Enter open valley, brs. NW. and SE.  
30.00 Wash, course NW. Asc. gradually.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S 9 | S10  
1918

From which

A cedar, 30 ins. diam., brs. N.23 $\frac{1}{2}$ °E.,  
240 lks. dist., marked  $\frac{1}{4}$ S10 BT.  
A pine, 10 ins. diam., brs. N.3°W.,  
530 lks. dist., marked  $\frac{1}{4}$ S9 BT.  
42.55 Road, brs. NW. to Seligman and SE. to Prescott.  
43.50 Enter scattering timber, brs. NW. and SE.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the  
ground, for cor. of secs. 3, 4, 9 and 10, marked on brass  
cap

Survey of the  
Subdivision of T. 20 N., R. 6 W. 3875 37

Chains.

T20N R6W  
S 4 | S 3  
S 9 | S10  
1918

From which

- A cedar, 30 ins. diam., brs. S.82 $\frac{1}{4}$ °E.,  
723 lks. dist., marked T20N R6W S10 BT.
- A cedar, 30 ins. diam., brs. S.79 $\frac{1}{2}$ °W.,  
499 lks. dist., marked T20N R6W S9 BT.
- A cedar, 30 ins. diam., brs. N.42 $\frac{1}{2}$ °W.,  
243 lks. dist., marked T20N R6W S4 BT.

No other trees within limits. Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.

Soil, 2nd and 4th rates.

Timber, cedar, pine and pinion.

Undergrowth, algerita, scrub oak, quinine, cactus and young timber.

40.00  
80.16

N.89°48'E., on a random line, bet. secs. 3 and 10.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect N. and S. line, 23 lks. N. of the cor. of secs. 2, 3, 10 and 11.

Thence

S.89°58'W., on a true line, bet. secs. 3 and 10.  
Over level mesa land, through scattering timber and undergrowth.

10.05  
12.35  
35.15  
40.08

Draw, course N.15°W.  
Draw, course NE.  
Thence over rolling land.  
Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S 3  
S10  
1918

From which

- A cedar, 10 ins. diam., brs. N.79 $\frac{1}{2}$ °E.,  
363 lks. dist., marked  $\frac{1}{4}$ S3 BT.
- A cedar, 30 ins. diam., brs. S.44 $\frac{1}{2}$ °W.,  
187 lks. dist., marked  $\frac{1}{4}$ S10 BT.

60.36  
68.16  
80.16

Main cattle trail to OO ranch, brs. N. and S.  
Draw, course NW.  
The cor. of secs. 3, 4, 9 and 10.  
Land, level and rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar, pine and pinion.  
Undergrowth, algerita, scrub oak, cactus, quinine and young timber.

5.75  
25.30  
28.00  
40.00

N.0°2'W., on a true line, bet. secs. 3 and 4.  
Over rolling land, through scattering timber and undergrowth.  
Small wash, course NW.  
Wash, course NW.  
Wash, course W. Asc. 100 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 4 | S 3  
1918

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

From which

A cedar, 12 ins. diam., brs. N.36½°E.,  
149 lks. dist., marked ¼S3 BT.

A pinion, 12 ins. diam., brs. S.79½°W.,  
160 lks. dist., marked ¼S4 BT.

45.00

Thence over level mesa land.

48.78

Intersect the 5th Standard Parallel North, 4.17 chs. E. of  
the standard ¼ sec. cor. of sec. 35, T. 21 N., R. 6 W.,  
hereinbefore described.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the  
ground, on solid rock, in a mound of stone, for closing  
cor. of secs. 3 and 4, marked on brass cap

T21N R6W	
S35	
S 4	S 3
T20N R6W	
C C	
1918	

From which

A cedar, 10 ins. diam., brs. S.76½°E.,  
138 lks. dist., marked CC T20N R6W S3 BT.

A cedar, 6 ins. diam., brs. S.34°W.,  
115 lks. dist., marked CC T20N R6W S4 BT.

Land, rolling.

Soil, 2nd and 4th rate .

Timber, cedar, pinion and pine.

Undergrowth, scrub oak, cactus, quinine, algerita and  
young timber.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of  
Tp., described in Book "C",  
N.0°3'W., bet. secs. 32 and 33.

Over mountainous land, through heavy timber and dense under-  
growth.

Desc. 25 ft.

2.50

Draw, course SE. Asc. 90 ft.

10.00

Ridge, brs. E. and W. Desc. 150 ft.

32.36

Draw, course NW. Asc. 65 ft.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the  
ground, on bed rock, in a mound of stone, for ¼ sec.  
cor., marked on brass cap

¼	
S32	S33
1918	

From which

A pinion, 14 ins. diam., brs. N.71°E.,  
73 lks. dist., marked ¼S33 BT.

A cedar, 20 ins. diam., brs. S.15°W.,  
43 lks. dist., marked ¼S32 BT.

40.50

Spur, slopes NW. Desc. 70 ft.

44.50

Draw, course NW. Asc. 20 ft.

46.50

Spur, slopes W. Desc. 115 ft.

53.00

Draw, course W. Asc. 250 ft.

70.00

Ridge, brs. E. and W. Desc. 130 ft.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., on solid rock,  
in a mound of stone, for cor. of secs. 28, 29, 32 and  
33, marked on brass cap

T20N R6W	
S29	S28
S32	S33
1918	

Survey of the  
Subdivision of T. 20 N., R. 6 W.

BOOK 2975

Chains.

From which

- A pinion, 14 ins. diam., brs. N.1°E.,  
79 lks. dist., marked T20N R6W S28 BT.
- A cedar, 10 ins. diam., brs. S.56°E.,  
37 lks. dist., marked T20N R6W S33 BT.
- A pinion, 12 ins. diam., brs. S.20¼°W.,  
64 lks. dist., marked T20N R6W S32 BT.
- A pinion, 6 ins. diam., brs. N.65°W.,  
17 lks. dist., marked T20N R6W S29 BT.


Land, mountainous.  
Soil, thin, dry, gravelly; 4th rate.  
Timber, cedar, pinion and pine.  
Undergrowth, quinine, scrub oak, algerita, cactus and  
young timber.

40.00  
79.88

East on a random line, bet. secs. 28 and 33.  
Set temp. ¼ sec. cor.  
Intersect the cor. of secs. 27, 28, 33 and 34.  
Thence  
West on a true line, bet. secs. 28 and 33.  
Over rolling land, through heavy timber and dense under-  
growth.

27.60  
31.90  
35.90  
39.94

Draw, course S. Asc.  
Spur, slopes S. Desc. 20 ft.  
Draw, course SE. Asc. 130 ft.  
Set an iron post, 3 ft. long, 1 in. diam., on solid rock,  
in a mound of stone, for ¼ sec. cor., marked on brass  
cap



From which

- A cedar, 12 ins. brs. N.68°W.,  
28 lks. dist., marked ¼S28 BT.
- A pinion, 12 ins. diam., brs. S.37½°E.,  
60 lks. dist., marked ¼S33 BT.


49.90  
74.40  
79.88

Ridge, brs. NE. and SW. Desc. 130 ft.  
Draw, course N.70°W. Continue descent, 60 ft.  
The cor. of secs. 28, 29, 32 and 33.  
Land, mountainous and rolling.  
Soil, gravelly, thin and dry; 4th rate.  
Timber, cedar and pinion.  
Undergrowth, quinine, scrub oak, cactus, algerita and  
young timber.

N.0°3'W., bet. secs. 28 and 29.  
Over mountainous land, through heavy timber and dense  
undergrowth.

0.25  
2.50  
4.50  
18.00  
26.00  
40.00

Desc.  
Canyon, 20 ft. deep, course NW. Asc. 25 ft.  
Spur, slopes W. Desc. 40 ft.  
Canyon, course W. Asc. 100 ft.  
Spur, slopes NW. Thence over level top of spur.  
Desc. 140 ft.  
Set an iron post, 3 ft. long, 1 in. diam., on solid rock,  
in a mound of stone, for ¼ sec. cor., marked on brass  
cap



From which

- A pinion, 12 ins. diam., brs. S.50½°E.,  
89 lks. dist., marked ¼S28 BT.
- A pinion, 14 ins. diam., brs. N.33°W.,  
10 lks. dist., marked ¼S29 BT.



Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains. Desc. 100 ft.  
42.50 Canyon, course NW. Asc. 180 ft.  
51.00 Spur, slopes NW. Desc. 380 ft.  
69.00 Canyon, course NW. Asc. 260 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., on solid rock,  
in a mound of stone, for cor. of secs. 20, 21, 28 and  
29, marked on brass cap

T20N	R6W
S20	S21
S29	S28
1918	

## From which

A pinion, 12 ins. diam., brs. N.46 $\frac{1}{2}$ °E.,  
82 lks. dist., marked T20N R6W S21 BT.  
A cedar, 12 ins. diam., brs. S.48 $\frac{3}{4}$ °E.,  
200 lks. dist., marked T20N R6W S28 BT.  
A cedar, 12 ins. diam., brs. N.48 $\frac{1}{2}$ °W.,  
59 lks. dist., marked T20N R6W S20 BT.  
No other tree within limits. Raise a mound of stone, 2  
ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.  
Land, mountainous.  
Soil, gravelly, thin and dry.  
Timber, cedar, pinion and pine.  
Undergrowth, quinine, scrub oak, cactus, algerita and  
young timber.

40.00 East on a random line, bet. secs. 21 and 28.  
Set temp.  $\frac{1}{4}$  sec. cor.  
79.80 Intersect N. and S. line, 5 lks. S. of the cor. of secs.  
21, 22, 27 and 28.  
Thence  
S.89°58'W., on a true line, bet. secs. 21 and 28.  
Over rolling mountainous land, through heavy timber and  
dense undergrowth.  
0.10 Short spur, slopes N. Desc. 100 ft.  
5.10 Ravine, course N. Asc. 125 ft.  
18.00 Spur, slopes NE. Desc. 125 ft.  
39.90 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$	S21
	S28
1918	

## From which

A pine, 10 ins. diam., brs. N.27 $\frac{1}{2}$ °W.,  
73 lks. dist., marked  $\frac{1}{4}$ S21 BT.  
A cedar, 20 ins. diam., brs. S.67 $\frac{1}{2}$ °E.,  
47 lks. dist., marked  $\frac{1}{4}$ S28 BT.  
Desc. 40 ft.  
41.75 Draw, course NW. Asc. 150 ft.  
53.00 Spur, slopes NW. Thence over rolling land.  
79.80 The cor. of secs. 20, 21, 28 and 29.  
Land, rolling and rolling mountainous.  
Soil, 2nd and 4th rates.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus, algerita, quinine and  
young timber.


N.0°3'W., bet. secs. 20 and 21.  
Over mountainous land, through heavy timber and dense  
undergrowth.

Survey of the  
Subdivision of T. 20 N., R. 6 W. 2075 41


Chains.	Asc.	
3.00	Spur, slopes W. Desc. 260 ft.	
15.00	Bench, slopes NW. Desc. 90 ft.	
26.50	Draw, course NW. Continue descent, 40 ft.	
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap	
	$\begin{array}{c} \frac{1}{4} \\ \hline S20 \mid S21 \\ \hline 1918 \end{array}$	
	From which	
	A cedar, 20 ins. diam., brs. N.65°E., 11 lks. dist., marked $\frac{1}{4}$ S21 BT.	
	A pinion, 12 ins. diam., brs. N.61°W., 77 lks. dist., marked $\frac{1}{4}$ S20 BT.	
	Desc. 80 ft.	
54.50	Draw, course NW. Asc. 25 ft.	
60.00	Flat spur, slopes NW. Desc. 25 ft.	
66.70	Draw, course NW. Desc. 20 ft.	
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on brass cap	
	$\begin{array}{c} T20N R6W \\ \hline S17 \mid S16 \\ \hline S20 \mid S21 \\ \hline 1918 \end{array}$	
	From which	
	A cedar, 12 ins. diam., brs. N.45°E., 40 lks. dist., marked T20N R6W S16 BT.	
	A cedar, 12 ins. diam., brs. S.53°40'E., 57 lks. dist., marked T20N R6W S21 BT.	
	A cedar, 20 ins. diam., brs. S.76 $\frac{1}{2}$ °W., 390 lks. dist., marked T20N R6W S20 BT.	
	A pinion, 20 ins. diam., brs. N.41 $\frac{1}{2}$ °W., 25 lks. dist., marked T20N R6W S17 BT.	
	Land, mountainous.	
	Soil, 2nd and 4th rates.	
	Timber, cedar and pinion.	
	Undergrowth, scrub oak, cactus, algerita, quinine and young timber.	
	-----	
	N.89°58'E., on a random line, bet. secs. 16 and 21.	
40.00	Set temp. $\frac{1}{4}$ sec. cor.	
79.82	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 15, 16, 21 and 22.	
	Thence	
	West on a true line, bet. secs. 16 and 21.	
	Over rolling land, through scattering timber and undergrowth.	
	Desc.	
4.80	Draw, course NW. Asc.	
19.80	Spur, slopes N. Desc.	
36.80	Draw, course NW. Asc.	
39.91	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap.	
	$\begin{array}{c} S16 \\ \hline \frac{1}{4} S21 \\ \hline 1918 \end{array}$	
	From which	
	A cedar, 12 ins. diam., brs. N.17 $\frac{1}{2}$ °W., 418 lks. dist., marked $\frac{1}{4}$ S16 BT.	
	No other trees within limits. Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.	
42.80	Spur, slopes NW. Desc.	
45.00	Asc.	
50.80	Spur, slopes NW. Desc.	

Chains.  
55.00 Asc.  
62.80 Spur, slopes NW. Desc.  
70.00 Asc.  
78.10 Spur, slopes NW. Desc.  
79.82 The cor. of secs. 16, 17, 20 and 21.  
Land, rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar and pinion.  
Undergrowth, scrub oak, cactus, quinine, algerita and young timber.

N.0°3'W., bet. secs. 16 and 17.  
Over rolling land, through scattering timber and undergrowth.  
5.00 Leave timber, brs. NE. and SW.  
26.90 Wash, course NE.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



From which  
A cedar, 12 ins. diam., brs. S.43°W.,  
390 lks. dist., marked  $\frac{1}{4}$ S17 BT.  
No other trees within limits. Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.  
79.50 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to cor. of secs. 8, 9, 16 and 17, marked on brass cap



From which  
A cedar, 10 ins. diam., brs. S.7 $\frac{1}{2}$ °E.,  
50 lks. dist., marked WC T20N R6W S16 BT.  
No other trees within limits. Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.  
80.00 The true point for cor. of secs. 8, 9 16 and 17 falls in deep wash, course N. W.  
Land, rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar and pinion.  
Undergrowth, cactus, scrub oak, quinine, algerita and young timber.

From the true point for cor. of secs. 8, 9, 16 and 17,  
East on a random line, bet. secs. 9 and 16.  
40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
79.80 Intersect the cor. of secs. 9, 10, 15 and 16.  
Thence  
West on a true line, bet. secs. 9 and 16.  
Over rolling land, through scattering undergrowth.  
Asc. 75 ft.  
8.30 Spur, slopes NW. Desc. 175 ft.  
29.80 Draw, course NW. Enter scattering timber and dense undergrowth, brs. NW. and SE. Asc. 40 ft.  
39.90 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Survey of the  
Subdivision of T. 20 N., R. 6 W.

1875

Chains.

$\frac{1}{4}$  S 9  
S 16  
1918

From which

A cedar, 17 ins. diam., brs. N.26 $\frac{1}{2}$ °W.,  
280 lks. dist., marked  $\frac{1}{4}$ S9 BT.  
An oak, 10 ins. diam., brs. S.44 $\frac{1}{2}$ °E.,  
113 lks. dist., marked  $\frac{1}{4}$ S16 BT.

49.80 Spur, slopes NW. Desc.  
55.00 Asc.  
65.80 Low hill. Desc. 50 ft.  
79.80 The true point for cor. of secs. 8, 9, 16 and 17, in wash,  
course NW.  
Land, rolling.  
Soil, 2nd and 4th rate.  
Timber, cedar, pinion and pine.  
Undergrowth, scrub oak, cactus, quinine, algerita and  
young timber.

From the true point for cor. of secs. 8, 9, 16 and 17,  
N.0°3'W., bet. secs. 8 and 9.  
Over rolling land, through scattering timber and under-  
growth.

.50 High bank of wash, course NW.  
9.00 Same wash, course NE.  
16.40 Same wash, course NW. Asc.  
38.00 Low spur, slopes W. Desc. 20 ft.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 8 | S 9  
1918

From which

A cedar, 20 ins. diam., brs. S.10 $\frac{1}{2}$ °E.,  
100 lks. dist., marked  $\frac{1}{4}$ S9 BT.  
A cedar, 24 ins. diam., brs. S.7°W.,  
163 lks. dist., marked  $\frac{1}{4}$ S8 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 4, 5, 8 and 9, marked on brass  
cap

T20N R6W  
S 5 | S 4  
S 8 | S 9  
1918

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W.  
of cor.

Land, rolling.  
Soil, 2nd and 4th rate.  
Timber, scattering cedar.  
Undergrowth, scrub oak, quinine, algerita, cactus and  
young timber.

40.00 East on a random line, bet. secs. 4 and 9.  
Set temp.  $\frac{1}{4}$  sec. cor.  
79.84 Intersect N. and S. line, 25 lks. N. of the cor. of secs.  
3, 4, 9 and 10.

Thence  
N.89°49'W., on a true line, bet. secs. 4 and 9.  
Over rolling land, through scattering timber and under-  
growth.

18.00 Draw, course NW. Asc.  
26.20 Low spur, slopes N. Desc.  
33.30 Road, brs. N. to Seligman and S. to Prescott. Asc.

Chains.

36.40 Low spur, slopes NW. Desc.  
39.92 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} S 4 \\ \frac{1}{4} S 9 \\ \hline 1918 \end{array}$$

From which

A cedar, 15 ins. diam., brs. N.  $38\frac{1}{4}^{\circ}$  E.,  
209 lks. dist., marked  $\frac{1}{4}$  S4 BT.  
A cedar, 40 ins. diam., brs. S.  $78\frac{1}{4}^{\circ}$  E.,  
245 lks. dist., marked  $\frac{1}{4}$  S9 BT.

40.50 Draw, course NW. Asc.  
50.00 Low spur, slopes NW. Desc.  
79.84 The cor. of secs. 4, 5, 8 and 9.  
Land, rolling.  
Soil, 2nd and 4th rate.  
Timber, cedar, pine and pinion.  
Undergrowth, scrub oak, cactus, algerita, quinine and young timber.

3.80 N.  $0^{\circ}3'$  W., on a true line, bet. secs. 4 and 5.  
Over rolling land, through scattering undergrowth.  
Wash, 30 lks. wide, 6 ft. deep, course NE.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \\ S 5 | S 4 \\ \hline 1918 \end{array}$$

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
47.50 Wash, 30 lks. wide, 6 ft. deep, course NW.  
48.36 Intersect 5th Standard Parallel North, 4.48 chs. N.  $89^{\circ}53'$  E. of the standard  $\frac{1}{4}$  sec. cor. of sec. 34, T. 21 N., R. 6 W., hereinbefore described.  
At the point of intersection,  
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for closing cor. of secs. 4 and 5, marked on brass cap

$$\begin{array}{r} T21N R6W \\ \hline S34 \\ \hline S 5 | S 4 \\ T20N R6W \\ C | C \\ \hline 1918 \end{array}$$

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.  
Land, rolling.  
Soil, 2nd and 4th rate.  
No timber.  
Undergrowth, scrub oak, quinine, cactus and algerita.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of Tp., described in Book "C",  
N.  $0^{\circ}3'$  W., bet. secs. 31 and 32.  
Over rolling land, through open valley.  
3.00 Enter heavy timber and dense undergrowth, brs. NE. and SW.  
Asc. 125 ft.  
13.40 Spur, slopes SE. Desc. 60 ft.  
17.05 Draw, course E. Asc. 90 ft.

Survey of the  
Subdivision of T. 20 N., R. 6 W.

BOOK 2075

45

Chains.  
25.30 Spur, slopes E. Desc. 100 ft.  
34.80 Head of ravine, course E. Asc. 75 ft.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S31 | S32  
1918

## From which

A pinion, 8 ins. diam., brs. N.  $38\frac{3}{4}^{\circ}$ E.,  
18 lks. dist., marked  $\frac{1}{4}$ S32 BT.  
A cedar, 10 ins. diam., brs. S.  $42\frac{1}{4}^{\circ}$ W.,  
115 lks. dist., marked  $\frac{1}{4}$ S31 BT.

42.10 Spur, slopes NE. Desc. 180 ft.  
60.00 Enter open valley, course NE.  
61.00 Wash, course NE.  
64.30 Dim road, brs. NE. and SW.  
68.00 Leave valley, course NE. Enter heavy timber, brs. NE. and SW. Asc. 60 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, marked on brass cap

T20N R6W  
S30 | S29  
S31 | S32  
1918

## From which

A pine, 8 ins. diam., brs. N.  $26\frac{1}{2}^{\circ}$ E.,  
96 lks. dist., marked T20N R6W S29 BT.  
A pine, 12 ins. diam., brs. S.  $27\frac{3}{4}^{\circ}$ E.,  
54 lks. dist., marked T20N R6W S32 BT.  
A pine, 10 ins. diam., brs. S.  $33^{\circ}$ E.,  
30 lks. dist., marked T20N R6W S32 BT.  
A cedar, 12 ins. diam., brs. N.  $62^{\circ}$ W.,  
53 lks. dist., marked T20N R6W S30 BT.

Land, rolling.

Soil, 2nd and 4th rates.

Timber, cedar, pinion and pine.

Undergrowth, cactus, scrub oak, quinine, algerita and young timber.

40.00 East on a random line, bet. secs. 29 and 32.  
Set temp.  $\frac{1}{4}$  sec. cor.  
79.98 Intersect the cor. of secs. 28, 29, 32 and 33.  
Thence  
West on a true line, bet. secs. 29 and 32.  
Over Over mountainous land, through heavy timber and dense undergrowth.  
Desc. 30 ft.  
2.50 Draw, course N. Asc. 130 ft.  
15.00 Spur, slopes NW. Desc. 170 ft.  
39.99 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S29  
 $\frac{1}{4}$  S32  
1918

## From which

A pinion, 20 ins. diam., brs. N.  $5^{\circ}$ E.,  
35 lks. dist., marked  $\frac{1}{4}$ S29 BT.  
A pinion, 10 ins. diam., brs. S.  $29^{\circ}$ E.,  
18 lks. dist., marked  $\frac{1}{4}$ S32 BT.

Desc. 200 ft.  
61.00 Road, brs. NE. to Seligman and SW. to New Watter

Chains.

	Thence over level land.
66.30	Wash, course NE.
70.00	Dim road, brs. NE. and SW. Asc. 100 ft.
79.98	The cor. of secs. 29, 30, 31 and 32. Land, mountainous and level. Soil, gravelly, thin and dry; 4th rate. Timber, cedar and pinion. Undergrowth, quinine and scrub oak.
	West on a random line, bet. secs. 30 and 31.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
105.49	Intersect W. bdy. of Tp., 10 lks. N. of the reestablished cor. of secs. 30 and 31, hereinbefore described. Thence N. $89^{\circ}57'E.$ , on a true line, bet. secs. 30 and 31. Over level land, through heavy timber and dense under- growth.
19.70	Leave level mesa, brs. N. and S. Desc. 265 ft.
30.50	Draw, course NE. Asc. 250 ft.
45.60	Edge of mesa, brs. NE. and SW. Thence over level land.
65.49	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, on bed rock, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{c} \frac{1}{4} S30 \\ \frac{1}{4} S31 \\ 1918 \end{array}$
	From which A cedar, 24 ins. diam., brs. N. $30\frac{3}{4}^{\circ}E.$ , 39 lks. dist., marked $\frac{1}{4}S30$ BT. A pine, 8 ins. diam., brs. S. $24\frac{3}{4}^{\circ}W.$ , 9 lks. dist., marked $\frac{1}{4}S31$ BT.
87.90	Leave mesa, brs. N. and S. Desc. 400 ft., on spur, slopes E.
105.49	The cor. of secs. 29, 30, 31 and 32. Land, level and mountainous. Soil, 2nd and 4th rates. Timber, cedar, pinion and pine. Undergrowth, quinine, scrub oak, cactus, algerita and young timber.
	N. $0^{\circ}3'W.$ , bet. secs. 29 and 30. Over rolling mountainous land, through heavy timber and dense undergrowth. Along broken E. slope.
13.10	Low spur, slopes E. Desc.
32.20	Draw, course E. Asc. 70 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, on bed rock, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{c} \frac{1}{4} \\ S30 \quad   \quad S29 \\ 1918 \end{array}$
	From which A cedar, 6 ins. diam., brs. N. $79\frac{3}{4}^{\circ}E.$ , 31 lks. dist., marked $\frac{1}{4}S29$ BT. A cedar, 6 ins. diam., brs. S. $65\frac{3}{4}^{\circ}W.$ , 21 lks. dist., marked $\frac{1}{4}S30$ BT.
	Asc. 15 ft.
40.80	Spur, slopes NE. Desc. 70 ft.
47.10	Head of draw, course NE. Asc. 50 ft.
60.80	Spur, slopes NE. Desc. 85 ft.
72.90	Draw, course NE. Asc. 100 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground, on bed rock, in a mound of stone, for cor. of

Survey of the  
Subdivision of T. 20 N., R. 6 W.

BOOK 2875

47

Chains.

secs. 19, 20, 29 and 30, marked on brass cap

T20N R6W  
S19 S20  
S30 S29  
1918

From which

- A cedar, 10 ins. diam., brs. N.47 $\frac{1}{4}$ °E.,  
60 lks. dist., marked T20N R6W S20 BT.
- A cedar, 12 ins. diam., brs. S.23 $\frac{3}{4}$ °E.,  
106 lks. dist., marked T20N R6W S29 BT.
- A pine, 10 ins. diam., brs. S.40 $\frac{1}{2}$ °W.,  
126 lks. dist., marked T20N R6W S30 BT.
- A cedar, 6 ins. diam., brs. N.44 $\frac{3}{4}$ °W.,  
30 lks. dist., marked T20N R6W S19 BT.

Land, rolling mountainous.  
Soil, 2nd and 4th rates.  
Timber, cedar, pinion and pine.  
Undergrowth, scrub oak, quinine, cactus, algerita and  
young timber.

40.00  
80.00

East on a random line, bet. secs. 20 and 29.  
Set temp.  $\frac{1}{4}$  sec. cor.

Intersect the cor. of secs. 20, 21, 28 and 29.

Thence

West on a true line, bet. secs. 20 and 29.

Over mountainous land, through heavy timber and dense  
undergrowth.

Desc. 360 ft.

20.00

Leave timber. Thence over level land.

37.00

Road, brs. NE. to Seligman and SW. to New Water.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S20  
 $\frac{1}{4}$  S29  
1918

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N.  
of cor.

46.90

Wash, 15 lks. wide, course NE. Asc. 150 ft.

59.00

Enter heavy timber, brs. NE. and SW.

78.40

Long spur, slopes NE. Desc. 15 ft.

80.00

The cor. of secs. 19, 20, 29 and 30.

Land, level and mountainous.

Soil, 2nd and 4th rates.

Timber, cedar and pinion.

Undergrowth, scrub oak, cactus, algerita, quinine and  
young timber.

40.00  
105.37

S.89°57'W., on a random line, bet. secs. 19 and 30.  
Set temp.  $\frac{1}{4}$  sec. cor.

Intersect W. bdy. of Tp., 21 lks. S. of the reestablished  
cor. of secs. 19 and 30, hereinbefore described.

Thence

S.89°56'E., on a true line, bet. secs. 19 and 30.

Over mountainous land, through heavy timber and dense  
undergrowth.

6.85

Asc.  
Ridge, brs. NE. and SW. Desc. 475 ft.

65.37

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor.,  
marked on brass cap



Chains.

$\frac{1}{4}$  S19  
S30  
1918

From which

A cedar, 20 ins. diam., brs. N.44 $\frac{1}{4}$ °E.,  
74 lks. dist., marked  $\frac{1}{4}$ S19 BT.  
A cedar, 12 ins. diam., brs. S.35 $\frac{1}{2}$ °E.,  
16 lks. dist., marked  $\frac{1}{4}$ S30 BT.

67.35 Leave timber, and enter open valley, course NE.  
73.35 Wash, course NE.  
76.35 Leave open valley, course NE., and enter timber, brs. NE.  
and SW. Asc.  
81.85 Draw, course NW. Asc. 35 ft.  
85.35 Spur, slopes NW. Desc. 25 ft.  
87.35 Head of draw, course NW. Asc. 60 ft.  
93.35 Thence along N. slope.  
105.37 The cor. of secs. 19, 20, 29 and 30.  
Land, rolling mountainous.  
Soil, 2nd and 4th rates.  
Timber, cedar, pinion and pine.  
Undergrowth, scrub oak, cactus, algerita, quinine and  
young timber.

N.0°3'W., bet. secs. 19 and 20.

Over rolling mountainous land, through heavy timber and  
dense undergrowth.

8.50 Desc. 140 ft. on NE. slope.  
35.00 Head of draw, course NW. Asc. 90 ft.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the  
ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

$\frac{1}{4}$   
S19 | S20  
1918

From which

A cedar, 24 ins. diam., brs. S.30 $\frac{1}{2}$ °E.,  
150 lks. dist., marked  $\frac{1}{4}$ S20 BT.  
A cedar, 20 ins. diam., brs. S.67 $\frac{1}{2}$ °W.,  
64 lks. dist., marked  $\frac{1}{4}$ S19 BT.

49.00 Spur, slopes N.10°W. Desc. 150 ft.  
66.00 Enter valley, brs. NE. and SW. Thence through scattering  
timber and undergrowth.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 17, 18, 19 and 20, marked on  
brass cap

T20N | R6W  
S18 | S17  
S19 | S20  
1918

From which

A cedar, 20 ins. diam., brs. N.9 $\frac{1}{2}$ °E.,  
66 lks. dist., marked T20N R6W S17 BT.  
A cedar, 24 ins. diam., brs. S.19 $\frac{1}{4}$ °W.,  
302 lks. dist., marked T20N R6W S19 BT.  
A cedar, 30 ins. diam., brs. N.45 $\frac{1}{4}$ °W.,  
101 lks. dist., marked T20N R6W S18 BT.

No other trees within limits. Raise a mound of stone, 2  
ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling mountainous.

Soil, 2nd and 4th rates.

Timber, cedar, pinion and pine.

Undergrowth, cactus, algerita, quinine, scrub oak and  
young timber.

Survey of the  
Subdivision of T. 20 N., R. 6 W.

BOOK 2975 49

Chains.

40.00 East on a random line, bet. secs. 17 and 20.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.80 Intersect N. and S. line, 21 lks. S. of the cor. of secs.  
 16, 17, 20 and 21,  
 Thence  
 S.  $89^{\circ}51'W.$ , on a true line, bet. secs. 17 and 20.  
 Over rolling land, through scattering timber and under-  
 growth.  
 Desc. gradually.  
 4.80 Leave timber, brs. N. and S. Thence across open valley,  
 course N.  
 15.40 Wash, 30 lks. wide, 10 ft. deep, course N. Asc. 200 ft.  
 16.20 Road, brs. N. to Seligman and S. to New Water.  
 24.80 Enter heavy timber, brs. N. and S.  
 39.90 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the  
 ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
 cor., marked on brass cap

$\frac{1}{4}$  S17  
 S20  
 1918

From which

A cedar, 16 ins. diam., brs. N.  $55\frac{1}{2}^{\circ}E.$ ,  
 110 lks. dist., marked  $\frac{1}{4}$ S17 BT.  
 A cedar, 16 ins. diam., brs. S.  $74\frac{1}{2}^{\circ}E.$ ,  
 72 lks. dist., marked  $\frac{1}{4}$ S20 BT.  
 Ridge, brs. N. and S. Desc. 125 ft.  
 53.80 Head of draw, course NW. Leave heavy, enter scattering  
 timber, brs. NW. and SE. Asc.  
 64.05 Short spur, slopes N. Desc. 50 ft.  
 67.10 Foot of descent; thence over rolling land.  
 79.80 The cor. of secs. 17, 18, 19 and 20.  
 Land, rolling.  
 Soil, 2nd and 4th rate.  
 Timber, cedar and pinion.  
 Undergrowth, scrub oak, cactus, quinine, algerita and  
 young timber.

40.00 N.  $89^{\circ}56'W.$ , on a random line, bet. secs. 18 and 19.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 105.90 Intersect W. bdy. of Tp., 15 lks. S. of the reestablished  
 cor. of secs. 18 and 19, hereinbefore described.  
 Thence  
 S.  $89^{\circ}51'E.$ , on a true line, bet. secs. 18 and 19.  
 Over rolling land, through heavy timber and dense under-  
 growth.  
 Asc. 50 ft.  
 7.40 Spur, slopes SE. Desc. 200 ft.  
 22.90 Draw, course S.  $60^{\circ}E.$  Asc. 100 ft.  
 29.90 Spur, slopes SE. Desc. 200 ft.  
 49.20 Wash, course SE. Asc. 40 ft.  
 51.90 Spur, slopes SE. Desc. 50 ft.  
 58.90 Small wash, course SE.  
 64.20 Wash, course NE.  
 65.40 Leave heavy timber, enter scattering timber, brs. N. and S.  
 65.90 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S18  
 S19  
 1918

From which

A cedar, 20 ins. diam., brs. N.  $54\frac{3}{4}^{\circ}E.$ ,  
 195 lks. dist., marked  $\frac{1}{4}$ S18 BT.  
 A cedar, 12 ins. diam., brs. S.  $73\frac{3}{4}^{\circ}W.$ ,  
 110 lks. dist., marked  $\frac{1}{4}$ S19 BT.  
 104.70 Wash, course NE.  
 105.90 The cor. of secs. 17, 18, 19 and 20.

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

Land, rolling.  
Soil, 2nd and 4th rate.  
Timber, cedar and pinion.  
Undergrowth, cactus, algerita, scrub oak, quinine and  
young timber.

N. 0°3'W., bet. secs. 17 and 18.  
Over rolling land, through scattering timber and under-  
growth.

1.00 Wash, course NE.  
6.00 Wash, course NE.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S18 | S17  
 |  
 1918

From which

A cedar, 10 ins. diam., brs. N. 42 $\frac{1}{2}$ °E.,  
140 lks. dist., marked  $\frac{1}{4}$ S17 BT.  
A cedar, 30 ins. diam., brs. N. 28°W.,  
170 lks. dist., marked  $\frac{1}{4}$ S18 BT.  
45.00 Enter heavy timber, brs. E. and W. Asc.  
55.00 Low spur, slopes E. Desc.  
59.10 Wash, course E. Asc.  
65.00 Low spur, slopes E. Desc.  
79.00 Wash, course NE. Asc. 25 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 7, 8, 17 and 18, marked on  
brass cap

T20N R6W  
 S 7 | S 8  
 S18 | S17  
 1918

From which

A cedar, 10 ins. diam., brs. N. 37°E.,  
100 lks. dist., marked T20N R6W S8 BT.  
A pine, 7 ins. diam., brs. S. 54 $\frac{1}{2}$ °E.,  
73 lks. dist., marked T20N R6W S17 BT.  
A cedar, 10 ins. diam., brs. S. 21 $\frac{1}{2}$ °W.,  
172 lks. dist., marked T20N R6W S18 BT.  
A cedar, 24 ins. diam., brs. N. 70 $\frac{1}{2}$ °W.,  
159 lks. dist., marked T20N R6W S7 BT.

Land, rolling.  
Soil, 2nd and 4th rate.  
Timber, cedar, pinion and pine.  
Undergrowth, scrub oak, cactus, algerita, quinine and  
young timber.

40.00 N. 89°51'E., on a random line, bet. secs. 8 and 17.  
Set temp.  $\frac{1}{4}$  sec. cor.  
79.78 Intersect the true point for cor., of secs. 8, 9, 16 and 17.  
Thence  
S. 89°51'W., on a true line, bet. secs. 8 and 17.  
Over rolling land, through scattering undergrowth.  
Across wash, course NW.  
1.50 Bank of wash, leave wash. Asc. gradually.  
7.70 Road, brs. N. to Seligman and S. to New Water. Asc.  
14.00 Low spur, slopes N. Desc.  
23.00 Wide draw, course NE. Asc.  
30.00 Enter scattering timber, brs. N. and S.  
39.89 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the  
ground, on solid rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
cor., marked on brass cap

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

$\frac{1}{4}$  S 8  
 $\frac{1}{4}$  S 17  
1918

From which

A cedar, 8 ins. diam., brs. N.45 $\frac{1}{2}$ °E.,  
83 lks. dist., marked  $\frac{1}{4}$ S8 BT.

A cedar, 16 ins. diam., brs. S.80 $\frac{1}{4}$ °W.,  
452 lks. dist., marked  $\frac{1}{4}$ S17 BT.

61.50 Enter heavy timber and dense undergrowth.

75.00 Low spur, slopes NE. Desc. 40 ft.

78.20 Wash, course NE. Asc. 25 ft.

79.78 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, 2nd and 4th rates.

Timber, cedar, pinion and pine.

Undergrowth, cactus, algerita, quinine, scrub oak and  
young timber.

40.00

N.89°51'W., on a random line, bet. secs. 7 and 18.

Set temp.  $\frac{1}{4}$  sec. cor.

105.93

Intersect W. bdy. of Tp., 18 lks. S. of the reestablished  
cor. of secs. 7 and 18, hereinbefore described.

Thence

S.89°45'E., on a true line, bet. secs. 7 and 18.

Over rolling land, through dense undergrowth.

4.95

Wash, course SE.

48.55

Wash, course S.

60.95

Enter heavy timber.

65.93

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap.

$\frac{1}{4}$  S 7  
 $\frac{1}{4}$  S 18  
1918

From which

A cedar, 8 ins. diam., brs. N.11°W.,  
82 lks. dist., marked  $\frac{1}{4}$ S7 BT.

A pine, 12 ins. diam., brs. S.25°E.,  
210 lks. dist., marked  $\frac{1}{4}$ S18 BT.

72.55

Wash, course NE. Asc. 50 ft.

84.95

Pass in spur, slopes NE. Desc.

105.93

The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, 2nd and 4th rates.

Timber, cedar, pinion and pine.

Undergrowth, cactus, algerita, quinine, scrub oak and  
young timber.

N.0°3'W., bet. secs. 7 and 8.

Over rolling land, through heavy timber and dense under-  
growth.

Asc.

2.50

Short spur, slopes E. Desc.

8.00

Wash, course E. Leave heavy, enter scattering timber, brs.  
E. and W.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S 7 | S 8  
1918

From which

A cedar, 12 ins. diam., brs. N.47°E.,  
279 lks. dist., marked  $\frac{1}{4}$ S8 BT.

Survey of the  
Subdivision of T. 20 N., R. 6 W.

Chains.

- A cedar, 20 ins. diam., brs. N.  $92\frac{1}{2}^{\circ}$ W.,  
325 lks. dist., marked  $\frac{1}{4}$ S 7 BT.
- 40.10 Draw, course E. Asc. 80 ft.
- 48.50 Spur, slopes NE. Desc. 80 ft.
- 57.50 Draw, course NE. Asc.
- 63.00 Low spur, slopes E. Enter heavy timber, brs. E. and W.  
Thence over rolling land.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 5, 6, 7 and 8, marked on brass  
cap

T20N R6W	
S 6	S 5
S 7	S 8
1918	

From which

- A pine, 6 ins. diam., brs. N.  $70\frac{1}{2}^{\circ}$ E.,  
9 lks. dist., marked T20N R6W S5 BT.
- A cedar, 7 ins. diam., brs. S.  $38\frac{1}{2}^{\circ}$ E.,  
39 lks. dist., marked T20N R6W S8 BT.
- A cedar, 14 ins. diam., brs. S.  $21^{\circ}$ W.,  
17 lks. dist., marked T20N R6W S7 BT.
- A cedar, 16 ins. diam., brs. N.  $40\frac{1}{2}^{\circ}$ W.,  
11 lks. dist., marked T20N R6W S6 BT.
- Land, rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar, pine and pinion.  
Undergrowth, scrub oak, algerita, quinine, cactus and  
young timber.

- N.  $89^{\circ}51'$ E., on a random line, bet. secs. 5 and 8.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.82 Intersect N. and S. line, 9 lks. S. of the cor. of secs.  
4, 5, 8 and 9.
- Thence  
S.  $89^{\circ}47'$ W., on a true line, bet. secs. 5 and 8.  
Over rolling land, through scattering undergrowth.
- 3.50 Wash, 30 lks. wide, 8 ft. deep, course NE.
- 8.50 Road, brs. N. to Seligman and S. to New Water. Asc. 125  
ft.
- 39.91 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$ S 5	
$\frac{1}{4}$ S 8	
1918	

- And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N.  
of cor.
- 44.00 Enter heavy timber and dense undergrowth.
- 79.82 The cor. of secs. 5, 6, 7 and 8.  
Land, rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar, pinion and pine.  
Undergrowth, algerita, cactus, quinine, scrub oak and  
young timber.

- N.  $89^{\circ}45'$ W., on a random line, bet. secs. 6 and 7.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 105.57 Intersect the reestablished cor. of secs. 6 and 7, on the  
W. bdy. of Tp., hereinbefore described.
- Thence  
S.  $89^{\circ}45'$ E., on a true line, bet. secs. 6 and 7.  
Over rolling land, through heavy timber and dense under-  
growth.  
Desc. 200 ft.
- 14.55 Wash, course NE. Asc..

Survey of the  
Subdivision of T. 20 N., R. 6 W.

53

Chains.

15.55 Point of spur, slopes NE. 3 chs. Desc.  
 17.75 Wash, course N. Asc. 175 ft.  
 25.55 Spur, slopes N.75°E. Desc. 320 ft.  
 55.55 Wash, course SE.  
 63.85 Wash, course NE. Asc.  
 65.57 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \text{ S } 6 \\ \text{S } 7 \\ \hline 1918 \end{array}$$

From which

A cedar, 24 ins. diam., brs. N.29 $\frac{1}{4}$ °E.,  
 153 lks. dist., marked  $\frac{1}{4}$ S6 BT.  
 A cedar, 16 ins. diam., brs. S.66 $\frac{1}{2}$ °W.,  
 71 lks. dist., marked  $\frac{1}{4}$ S7 BT.

91.45 Spur, slopes NE. Desc. Leave heavy timber, brs. NE. and  
 SW.

98.00 Asc.  
 103.75 Low spur, slopes NE. Desc.  
 105.57 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.  
 Soil, 2nd and 4th rates.  
 Timber, cedar, pinion and pine.  
 Undergrowth, scrub oak, algerita, cactus, quinine and  
 young timber.

N.0°3'W., on a true line, bet. secs. 5 and 6.  
 Over rolling land, through heavy timber and dense under-  
 growth.

15.00 Leave heavy, enter scattering timber, brs. E. and W.  
 27.90 Wash, course NE. Asc.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
 ground, on bed rock, in a mound of stone, for  $\frac{1}{4}$  sec.  
 cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \\ \text{S } 6 \text{ | } \text{S } 5 \\ \hline 1918 \end{array}$$

From which

A pine, 14 ins. diam., brs. S.81 $\frac{3}{4}$ °E.,  
 275 lks. dist., marked  $\frac{1}{4}$ S5 BT.  
 A pine, 10 ins. diam., brs. N.55 $\frac{1}{4}$ °W.,  
 160 lks. dist., marked  $\frac{1}{4}$ S6 BT.

42.50 Low spur, slopes E. Desc.  
 48.53 Intersect the 5th Standard Parallel North, 4.97 chs.  
 S.89°52'E. of the standard  $\frac{1}{4}$  sec. cor. of sec. 33,  
 T. 21 N., R. 6 W., hereinbefore described.

At the point of intersection,  
 Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the  
 ground, on bed rock, in a mound of stone, for closing  
 cor. of secs. 5 and 6, marked on brass cap

$$\begin{array}{r} \text{T21N R6W} \\ \text{S33} \\ \hline \text{S } 6 \text{ | } \text{S } 5 \\ \text{T20N R6W} \\ \text{C | C} \\ \hline 1918 \end{array}$$

From which

A pine, 24 ins. diam., brs. S.65 $\frac{1}{4}$ °E.,  
 287 lks. dist., marked CC T20N R6W S5 BT.  
 A cedar, 5 ins. diam., brs. S.23 $\frac{1}{4}$ °W.,  
 125 lks. dist., marked CC T20N R6W S6 BT.

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, S. of  
 cor.

Chains.

Land, rolling.  
Soil, 2nd and 4th rates.  
Timber, cedar, pinion and pine.  
Undergrowth, scrub oak, cactus, quinine, algerita and young timber.

## GENERAL DESCRIPTION.

This township contains rough and rolling mountainous land in the South, East and Western parts, and in the central and northern parts low rolling hills with open valleys. An escarpment in the lime stone crosses this township in an East and West direction near the center. North of this escarpment are low rounded hills covered with scattering cedar and pinion pine, and undergrowth of quinine brush, oak, algerita, while south of the escarpment the hills are more broken and mountainous, with a heavy growth of cedar and pine timber and dense undergrowth.

The only water that is to be found in this township is found in the abandoned shafts at the old abandoned iron mines.

The soil is gravelly, thin, and in most places very rich, the northeast part being covered with volcanic ash, can be classified from 2nd to 4th rate. All the land in this township is suitable for grazing purposes for it is all covered with good grass.

Indications of iron are found in Secs. 14, 15, 22, 23, 26 and 27, and several patented claims are found in this district, All claims are tied to U. S. L. M. 2282, which is located in the NE $\frac{1}{4}$  SE $\frac{1}{4}$ , Sec. 22. No other mineral was found in this district.

There are no settlers living in this township.

BOOK 2876

4-680

FIELD ASSISTANTS.

To David W. Eaton.

NAMES.	CAPACITY.
Sammel K. Hallbeck	First Chainman.
David Eaton	Second Chainman.
Edd Smith	Cornerman.
Lee J. Ferbstein	Flagman.
Floyd M. Brown	Axman.



BOOK 2975

CERTIFICATE OF UNITED STATES TRANSITMAN.

I, David W. Eaton, U. S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General, for Group 86, Arizona, bearing date of the eighteenth day of January, 1918, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the East Boundary and the Subdivisional Lines of

TOWNSHIP 20 NORTH, RANGE 6 WEST,

of the Gila & Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 86, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Helena, Mont., Oct. 29th 1920
Place Date

David W. Eaton
U. S. Transitman

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

191

The foregoing field notes of the survey of

executed by

under his special instructions dated, 191, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.

4-680

BOOK 2975

FIELD ASSISTANTS.

To Thomas W. Bates.

NAMES.	CAPACITY.
Theo. Vander Meer	First Chainman.
Dick Blend	Second Chainman.
Sidney J. Ferbstein	Flagman.
Ralph Hall	Cornerman, 2nd Chainman.
Bryan Smith	Axman, 1st Chainman.

BOOK 2975

CERTIFICATE OF UNITED STATES TRANSITMAN.

I, Thomas W. Bates, U. S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General, for Group 86, Arizona, bearing date of the eighteenth day of January, 1918, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, re surveyed all those parts or portions of the East Boundary of T. 20 N., R. 7 W., retraced the Fifth Standard Parallel North, RS. 6 and part of 5 W. (N. Bdy. T. 20 N.), and Surveyed all those parts or portions of the Subdivisional Lines of

TOWNSHIP 20 NORTH, RANGE 6 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 86, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such re survey, retracement and survey.

Place. Paris Idaho, November 15, 1920 Date

Thomas W. Bates U. S. Transitman

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, November 24, 1920.

The foregoing field notes of the re survey of the East Boundary of T. 20 N., R. 7 W., Retracement of the Fifth Standard Parallel North, R. 6 and part of R. 5 W. (N. Bdy. T. 20 N.), and survey of the East boundary and the Subdivisional Lines of TOWNSHIP 20 NORTH, RANGE 6 WEST,

of the Gila and Salt River Base and Meridian, in State of Arizona, executed by Thomas W. Bates and David W. Eaton, U. S. Transitmen, under special instructions dated January 18, 1918, for Group 86, Ariz, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the re retracements, and surveys, they describe, are hereby approved.

Frank B. Cook U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.