

2995

Book "B"
4-679

BOOK 2995

FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION LINES

of

TOWNSHIP 25 NORTH, RANGE 1 EAST.

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

Richard R. Mitchell, U. S. Transitman.

~~In the capacity of U. S. Surveyor~~, under instructions dated March 6, 1915,
issued by the United States Surveyor General to govern surveys included in
Group No. 54, which were approved by the Commissioner of the General Land
Office, December 14, 1915.

Survey commenced June 27, 1916.

Survey completed July 10, 1916.

Executed under Assignment
Instructions dated May 6, 1916.

2995

2995

1A

BOOK 1895

INDEX DIAGRAM.

Township 25 North, Range 1 East.

Book "C"

<i>Book "D"</i>	<i>Gila and Salt River Meridian (Resurveyed)</i>	6	32	5	35	4	20	3	14	2	8	1	
		32		32		25		19		13		7	
		7	31	8	24	9	19	10	12	11	7	12	
		31		30		24		18		12		6	
		18	30	17	23	16	18	15	11	14	6	13	
		29		29		23		17		11		5	
		19	29	20	22	21	17	22	10	23	4	24	
		28		28		22		16		10		4	
		30	27	29	21	28	15	27	9	26	3	25	
		27		26		21		15		9		3	
31	26	32	20	33	14	34	8	35	2	36			
		<i>6th Standard Parallel North</i>											
		<i>Group 52</i>											

Group 55

- Surveved under this group--notes in this book/
- Surveved under this group--notes in book "A".
- Surveved under group No. 52.

Book "B".

BOOK 2995

DATE DIAGRAM

for

T. 25 N., R. 1 E.

	6/28-16				6/27-16					
Meridian (Resurveyed)	7/10-16	7/10-16	7/10-16	7/16-16	7/16-16	7/16-16	7/17-16	7/17-16	6/28-16	6/28-16
	7/10-16	7/10-16	7/10-16	7/16-16	7/16-16	7/16-16	7/17-16	7/17-16	6/28-16	6/28-16
Salt River	7/10-16	7/10-16	7/10-16	7/3-16	7/3-16	7/3-16	6/29-16	6/29-16	6/27-16	6/27-16
	7/10-16	7/10-16	7/10-16	7/3-16	7/3-16	7/3-16	6/29-16	6/29-16	6/27-16	6/27-16
Gila and Salt River	7/8-16	7/8-16	7/8-16	7/3-16	6/30-16	6/30-16	6/29-16	6/29-16	6/27-16	6/27-16
	7/8-16	7/8-16	7/8-16	7/2-16	6/30-16	6/30-16	6/29-16	6/29-16	6/27-16	6/27-16
	7/8-16	7/8-16	7/2-16	6/30-16	6/30-16	6/29-16	6/27-16	6/27-16		

The subdivision was executed by Richard R. Mitchell, U. S. Transitman, on the dates shown on the above diagram.

2. Subdivision of T. 25 N., R. 1 E.

Chains.

Survey commenced June 25, 1916, and executed with Young and Sons' light mountain transit No. 8533, with Smith solar attachment. The horizontal limb is provided with two double verniers placed opposite to each other, reading to single minutes of arc, which is also the least count of the verniers of the latitude and declination arcs.

The instrument was examined, tested on the true meridian at Phoenix, Arizona, found correct, and was approved by the Assistant Supervisor of Surveys for Arizona and California, conditional upon satisfactory field tests, May 6, 1916.

I examine the adjustments of the transit, and correct the level and collimation errors. Then, to test the solar apparatus, by comparing its indications, resulting from solar observations made during a.m. and p.m. hours with a meridian determined by observations on Polaris, I proceed as follows:-

At our camp in sec. 17, T. 25 N., R. 1 E., near the cor. of secs. 7, 8, 17 and 18, in lat. $35^{\circ} 34'$ N., long. $112^{\circ} 18'$ W., using a meridian established by W. C. Thorn, U. S. Surveyor, from observations on Polaris at elongation, in accordance with the Manual of Instructions, at 8 hrs. 3 m., a.m., l.m.t., I set off $35^{\circ} 34'$ N. on the lat. arc; $23^{\circ} 24\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar. The meridian thus determined strikes 1' to the east of the meridian determined by observations on Polaris at elongation.

At 4 hrs. 5 m., p.m., l.m.t., I set off $35^{\circ} 34'$ N. on the lat. arc; $23^{\circ} 24'$ N. on the decl. arc; and determine a meridian with the solar. The meridian thus determined strikes 1' to the west of the meridian determined by observations on Polaris at elongation.

The solar apparatus, by a.m., and p.m. observations, defines positions for meridians which depart less than $1\frac{1}{2}'$ from the true meridian determined by observations on Polaris at elongation; therefore, since the instrument satisfies the conditions of our instructions, I conclude that it is in satisfactory adjustment.

June 25, 1916.

I commence at the standard cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., which is an iron post, re-established as described under current Group No. 52.

Thence


N. $0^{\circ} 1'$ W., bet. secs. 35 and 36.

Over rolling land, through scattering timber and undergrowth.

24.98 Draw, 2 chs. wide, course N. 20° W.

27.18 Road, brs. N. 25° W. and S. 47° E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

45.00 Enter scattering timber, brs. E. and W. Thence along W. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 25, 26, 35 and 36, marked on brass cap

Subdivision of T. 25 N., R. 1 E.

3.

chains.

T25N	R1E
S26	S25
S35	S36
1916	

From which
 A pinion, 8 ins. diam., brs. N.16° 35' E., 100 lks. dist., marked T25N R1E S25 BT.
 A pinion, 6 ins. diam., brs. S.39½° E., 105 lks. dist., marked T25N R1E S36 BT.
 A cedar, 6 ins. diam., brs. S.82° 10' W., 115 lks. dist., marked T25N R1E S35 BT.
 A pinion, 6 ins. diam., brs. N.17° 10' W., 93 lks. dist., marked T25N R1E S26 BT.

Land, rolling.
 Soil, sand and rocky loam; 2nd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 25 and 36.
 80.02 Set temp. ¼ sec. cor.
 Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, described in Book A.

Thence
 S.89° 58' W., on a true line, bet. secs. 25 and 36.
 Over gently rolling land, through scattering timber and undergrowth.

40.01 Asc. gradually to
 Low ridge, brs. N. and S.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S25
S36
1916

From which
 A pinion, 6 ins. diam., brs. N.25° 55' E., 74 lks. dist., marked ¼ S25 BT.
 A pinion, 6 ins. diam., brs. S.23° 20' E., 120 lks. dist., marked ¼ S36 BT.


70.04 Desc. gradually to
 Draw, 1 ch. wide, course NW. Road in this draw, brs. N. 46° W and S.62° E. Asc. 30 ft. to
 80.02 The cor. of secs. 25, 26, 35 and 36.

Land, gently rolling.
 Soil, sandy, with scattering rocks; 2nd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, algerita and sagebrush.
 White gramma grass.


8.45 N.0° 1' W., bet. secs. 25 and 26.
 9.96 Over rolling land, through scattering timber and undergrowth.
 24.92 Desc. 55 ft.
 40.00 Road, brs. N.70° W. and S.70° E.
 Draw, 1 ch. wide, course N.70° W. Asc. 55 ft. to
 Spur, slopes W. Desc. 40 ft. to
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

4. Subdivision of T. 25 N., R. 1 E.

Chains.




From which
 A pinion, 8 ins. diam., brs. S.63 $\frac{1}{4}$ ° E., 57 lks. dist., marked $\frac{1}{4}$ S25 BT.
 A cedar, 10 ins. diam., brs. S.54 $\frac{1}{2}$ ° W., 32 lks. dist., marked $\frac{1}{4}$ S26 BT.
 Asc. gradually to
 65.00 Ridge, brs. NW. and SE. Desc. gradually.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, marked on brass cap



dig pits, 18 X 18 X 12 ins., in each sec., 5 $\frac{1}{2}$ ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
 Land, rolling.
 Soil, red sandy loam, rocky surface; 3rd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

East on a random line, bet. secs. 24 and 25.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.98 Intersect E. bdy. of Tp., 7 lks. S. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, described in Book "A".
 Thence
 S.89° 57' W., on a true line, bet. secs. 24 and 25.
 Over rolling land, through scattering undergrowth.
 Desc. 105 ft. to
 14.80 Bottom of canyon, 1 ch. wide, course NE. Asc. 150 ft. to
 30.00 Desc. gradually.
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
 50.00 Head of draw, 1 ch. wide, course SE. Asc. gradually.
 79.98 The cor. of secs. 23, 24, 25 and 26.
 Land, rolling.
 Soil, sandy and rocky; 3 rd rate.
 No timber.
 Undergrowth, sagebrush and algerita.


N.0° 1' W., bet. secs. 23 and 24.
 Over rolling land, through scattering timber and undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Subdivision of T. 25 N., R. 1 E.

Chains.



80.00 and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 13, 14, 23 and 24, marked on brass cap




From which
 A pinion, 6 ins. diam., brs. N.28¼° E., 130 lks. dist., marked T25N R1E S13 BT.
 A cedar, 6 ins. diam., brs. S.75° 50' E., 108 lks. dist., marked T25N R1E S24 BT.
 A pinion, 6 ins. diam., brs. S.19° 40' W., 127 lks. dist., marked T25N R1E S23 BT.
 A cedar, 6 ins. diam., brs. N.41°10' W., 93 lks. dist., marked T25N R1E S14 BT.
 Land, rolling.
 Soil, rocky and sandy; 3rd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 13 and 24.
 Set temp. ¼ sec. cor.
 80.03 Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, described in Book "A".

Thence
 S.89° 58' W., on a true line, bet. secs. 13 and 24.
 Over rolling land, through scattering timber and undergrowth.

20.00 Desc. 105 ft. to
 Draw, 1 ch. wide, course N.70° W. Asc. 25 ft.
 40.01½ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
 43.00 Thence across bottom of Red Lake Canyon.
 Bed of Red Lake Canyon, 1 ch. wide, 10 ft. deep, course N. 70° W.
 44.00 Leave bed of Red Lake Canyon; asc. 185 ft. to
 68.90 Desc. 30 ft. to
 71.85 Draw, 1 ch. wide, course N.20° E. Asc. 35 ft. to
 80.03 The cor. of secs. 13, 14, 23 and 24.

Land, rolling.
 Soil, sandy and rocky; 3rd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

6. Subdivision of T. 25 N., R. 1 E.

Chains.

- N.0° 1' W., bet. secs. 13 and 14.
Over rolling land, through scattering undergrowth.
Desc. 90 ft. to
5.00 Asc. 50 ft. to
10.00 Desc. 30 ft. to
20.00 Asc. 30 ft. to
24.70 Desc. 50 ft. to
29.65 Enter Red Lake Canyon, course NW.
36.15 Bed of Red Lake Canyon, 1 ch. wide, 10 ft. deep, course N.
70° W. Asc. 155 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S14 | S13
 1916

- and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W.
of cor.
45.00 Leave Red Lake Canyon, course N.70° W. Continue ascent to
64.77 Spur, slopes NW. Desc. 35 ft. to
72.20 Draw, 40 lks. wide, 5 ft. deep, course NW. Asc. 40 ft. to
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 11, 12, 13 and 14, marked on
brass cap

T25N | R1E
 S11 | S12
 S14 | S13
 1916

- and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W.
of cor.
Land, rolling.
Soil, rocky; and sandy; 3rd rate.
No timber.
Undergrowth, sagebrush and algerita.
White gramma grass.

- East on a random line, bet. secs. 12 and 13.
40.00 Set temp. $\frac{1}{4}$ sec. cor.
80.04 Intersect E. bdy. of Tp., 2 lks. S. of the cor. of secs.
7, 12, 13 and 18, which is an iron post, described in
Book "A".
Thence
S.89° 59' W., on a true line, bet. secs. 12 and 13.
Over rolling land, through scattering undergrowth.
Desc. gradually to.
15.00 Thence over gently rolling land.
40.02 Set an iron post, 3 ft long, 1 in. diam., 10 ins. in the
ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
brass cap

$\frac{1}{4}$ S12
 $\frac{1}{4}$ S13
 1916


- and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N.
of cor.
80.04 The cor. of secs. 11, 12, 13 and 14.
Land, rolling and gently rolling.
Soil, sandy loam; 2nd rate.
No timber.
Undergrowth, sagebrush and algerita.
White gramma grass.

Subdivision of T. 25 N., R. 1 E.

7.


Chains.

19.00 N.0° 1' W., bet. secs. 11 and 12.
 Over rolling land, through scattering undergrowth.
 34.00 Head of draw, course W. Asc. gradually 50 ft. to
 Ridge, brs. NW. and SE. Desc. gradually.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
 ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
 brass cap



69.98 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
 dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
 high, W. of cor.


75.00 Draw, 1 ch. wide, course NW.
 80.00 Enter scattering timber, brs. E. and W.
 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of
 stone, for cor. of secs. 1, 2, 11 and 12, marked on
 brass cap



From which
 A cedar, 10 ins. diam., ors. S.87° 40' W., 90 lks. dist.,
 marked T25N R1E S11 BT.
 A pinion, 6 ins. diam., brs. N.27° 50' W., 145 lks.
 dist., marked T25N R1E S2 BT.
 No other trees within limits. Raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, rolling.
 Soil, sandy; 2nd rate.
 Timber, scattering cedar.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 1 and 12.
 80.04 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect E. bdy. of Tp., 8 lks. S. of the cor. of secs.
 1, 6, 7 and 12, which is an iron post, described in
 Book "A".

40.02 Thence
 S.89° 57' W., on a true line, bet. secs. 1 and 12.
 Over rolling land, through scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



42.35 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
 dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
 high, N. of cor.

80.04 Road, brs. N.44° W. and S.33° E.
 The cor. of secs. 1, 2, 11 and 12.
 Land, rolling.
 Soil, red, sandy loam; 2nd rate.
 No timber.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

8. Subdivision of T. 25 N., R. 1 E.

Chains.
 40.00 N.0° 1' W., on a random line, bet. secs. 1 and 2.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.16 Intersect N. bdy. of Tp., 2 lks. W. of the cor. of secs.
 1, 2, 35 and 36, which is an iron post, described in
 Book "A".
 Thence
 South on a true line, bet. secs. 1 and 2.
 Over rolling land, through scattering undergrowth.
 Desc. gradually, 110 ft.
 10.15 Enter timber, brs. NW. and SE.
 25.16 Road, brs. N.30° W. and SE.
 30.00 Foot of descent. Asc. 25 ft. to
 40.16 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 2 | S 1
 1916

From which
 A cedar, 6 ins. diam., brs. S.70° 20' E., 45 lks. dist.,
 marked $\frac{1}{4}$ S1 BT.
 A cedar, 6 ins. diam., brs. N.79° W., 50 lks. dist.,
 marked $\frac{1}{4}$ S2 BT.
 Desc. to
 55.20 Draw, 1 ch. wide, course W. Asc. to
 65.00 Desc. 65 ft. to
 73.25 Draw, 1 ch. wide, course W. Asc. 75 ft. to
 80.16 The cor. of secs. 1, 2, 11 and 12.
 Land, rolling.
 Soil, sandy and rocky; 3rd rate.
 Timber, cedar and pinion.
 Undergrowth, sagebrush.
 White gramma grass.

From the standard cor. of secs. 2, 3, 34 & 35, on the S. bdy.
 of the Tp., which is an iron post, re-established as
 described under current Group No. 52,
 N.0° 1' W., bet. secs. 34 and 35.
 Over rolling land, through scattering timber and under-
 growth.
 Desc. 50 ft. to
 2.37 Draw, 50 lks. wide, course W. Asc. 90 ft. to
 13.00 Desc. 55 ft. to
 21.34 Draw, 1 ch. wide, course N.70° W. Asc. to
 26.35 Desc. 30 ft. to
 31.30 Asc. 50 ft. to
 40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of
 stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S34 | S35
 1916

From which
 A cedar, 6 ins. diam., brs. S.81° 40' E., 66 lks. dist.,
 marked $\frac{1}{4}$ S35 BT.
 A cedar, 6 ins. diam., brs. S.46 $\frac{1}{2}$ ° W., 68 lks. dist.,
 marked $\frac{1}{4}$ S34 BT.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of
 stone, for cor. of secs. 26, 27, 34 and 35, marked on
 brass cap

Subdivision of T. 25 N., R. 1 E.

Chains.

T25N | R1E
S27 | S26
S34 | S35
1916

From which
A cedar, 6 ins. diam., brs. N.30° 10' E., 57 lks. dist.,
marked T25N R1E S26 BT.
No other trees within limits. Raise a mound of stone,
3 ft. base, 2½ ft. high, W. of cor.
Land, rolling.
Soil, sandy and rocky; 3rd rate.
Timber, scattering cedar.
Undergrowth, sagebrush and algerita.
White gramma grass.

40.00 East on a random line, bet. secs. 26 and 35.
Set temp. ¼ sec. cor.
79.99 Intersect N. and S. line, 7 lks. N. of the cor. of secs.
25, 26, 35 and 36.
Thence
N.89° 57' W., on a true line, bet. secs. 26 and 35.
Over rolling land, through scattering timber and under-
growth. Desc. 55 ft.
10.00 Leave timber, brs. N. and S.
20.00 Enter draw, course N.20° W.
27.30 Road, brs. N.20° W. and S.10° E.
30.00 Leave draw, course N.20° W.
39.99½ Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
ground, in a mound of stone, for ¼ sec. cor., marked on
brass cap

¼ S26
¼ S35
1916

and raise a mound of stone, 3 ft. base, 2½ ft. high,
N. of cor.
79.99 The cor. of secs. 26, 27, 34 and 35.
Land, rolling.
Soil, sandy; 2nd rate.
Timber, scattering cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

6.50 N.0° 1' W., bet. secs. 26 and 27.
Over rolling land, through scattering undergrowth.
Road, brs. S.75° E. and S.86° W.
20.00 Enter scattering timber, brs. E. and W.
35.00 Leave timber, brs. E. and W. Desc. 155 ft.
40.00 Set an iron post, 3ft. long, 1 in. diam., 26 ins. in the
ground, for ¼ sec. cor., marked on brass cap

¼
S27 | S26
1916

and raise a mound of stone, 3 ft. base, 2½ ft. high,
W. of cor.
68.96 Road, brs. N.40° W. and S.45° E.
69.97 Foot of desc. Draw, 4 chs. wide, course NW. Asc. 70 ft.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of
stone, for cor. of secs. 22, 23, 26 and 27, marked on
brass cap

10.

Subdivision of T. 25 N., R. 1 E.

Chains.

T25N	R1E
S22	S23
S27	S26
1916	

From which
 A pinion, 6 ins. diam., brs. N.79½° E., 56 lks. dist., marked T25N R1E S23 BT.
 A pinion, 8 ins. diam., brs. N.23° 20' W., 132 lks. dist., marked T25N R1E S22 BT.
 No other trees within limits. Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
 Land, rolling.
 Soil, sandy; 2nd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 23 and 26.
 79.80 Set temp. ¼ sec. cor.
 Intersect N. and S. line, 24 lks. N. of the cor. of secs. 23, 24, 25 and 26,
 Thence
 N.89° 50' W., on a true line, bet. secs. 23 and 26.
 Over rolling land, through scattering timber and undergrowth.
 39.90 Desc. gradually to
 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼	S23
¼	S26
1916	

and raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
 Asc. to
 60.00 Ridge, brs. NW. and SE. Desc. 110 ft. to
 79.80 The cor. of secs. 22, 23, 26 and 27.
 Land, rolling.
 Soil, shallow, sandy and rocky; 3rd rate.
 Timber, scattering cedar.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

24.91 N.0° 1' W., bet. secs. 22 and 23.
 40.00 Over rolling land, through scattering timber and undergrowth.
 Asc. 105 ft. to
 Ridge, brs. NW. and SE. Thence over gently rolling land.
 Set an iron post, 3ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼	
S22	S23
1916	

and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
 80.00 Desc. gentle N. slope to
 Set an iron post, 3ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 14, 15, 22 and 23, marked on brass cap

Subdivision of T. 25 N., R. 1 E.

11.

Chains.

T25N	R1E
S15	S14
S22	S23
1916	

and raise a mound of stone, 3 ft. base, 2½ ft. high,
W. of cor.
Land, rolling.
Soil, shallow, sandy; 2nd rate.
Timber, scattering cedar.
Undergrowth, sagebrush and algerita...
White gramma grass.

40.00 East on a random line, bet. secs. 14 and 23.
79.94 Set temp. ¼ sec. cor.
Intersect N. and S. line, 8 lks. N. of the cor. of secs.
13, 14, 23 and 24.
Thence
N.89° 57' W., on a true line, bet. secs. 14 and 23.
Over rolling land, through scattering timber and under-
growth.
10.10 Desc. 55 ft. to
19.95 Draw, 1 ch. wide, course N. Asc. 105 ft. to
39.97 Thence over gently rolling land.
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
ground, in a mound of stone, for ¼ sec. cor., marked on
brass cap

¼ S14
¼ S23
1916

79.94 and raise a mound of stone, 3 ft. base, 2½ ft. high, N.
of cor.
The cor. of secs. 14, 15, 22 and 23.
Land, rolling and gently rolling.
Soil, sandy and rocky; shallow; 3rd rate.
Timber, scattering cedar and pinion.
Undergrowth, sagebrush and algerita...
White gramma grass.

14.92 N.0° 1' W., bet. secs. 14 and 15.
29.75 Over rolling land, through scattering timber and under-
34.02 growth.
40.00 Desc. 100 ft. to
Draw, 1 ch. wide, course W. Asc. 140 ft. to
Ridge, brs. NW. and SE. Desc. 15 ft. to
Draw, 50 lks. wide, course N.70° W. Thence over gently
rolling land.
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
ground, in a mound of stone, for ¼ sec. cor., marked on
brass cap

¼
S15 S14
1916

70.00 From which
80.00 A pinion, 6 ins. diam., brs. N.75° W., 140 lks. dist.,
marked ¼ S15 BT.
No other trees within limits. Raise a mound of stone, 3
ft. base, 2½ ft. high, W. of cor.
Desc. NE. slope, 30 ft. to
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 10, 11, 14 and 15, marked on

Chains, brass cap

T25N | R1E
 S10 | S11
 S15 | S14
 1916

From which
 A cedar, 6 ins. diam., brs. N.4° 10' E., 133 lks. dist., marked T25N R1E S11 BT.
 A cedar, 12 ins. diam., brs. S.6° 20' E., 120 lks. dist., marked T25N R1E S14 BT.
 A pinion, 8 ins. diam., brs. S.5¼° W., 118 lks. dist., marked T25N R1E S15 BT.
 A pinion, 6 ins. diam., brs. N.52° 10' W., 59 lks. dist., marked T25N R1E S10 BT.
 Land, rolling and gently rolling.
 Soil, shallow, sandy; 3rd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00
 79.99

The cor. of secs. 11, 12, 13 and 14, being plainly visible, I run for said cor. from last sec. cor. S.89° 55' E., on a random line, bet. secs. 11 and 14. Set temp. ¼ sec. cor. Intersect N. and S. line, at the cor. of secs. 11, 12, 13 and 14.

15.15
 20.10
 30.00
 39.99½

Thence N.89° 55' W., on a true line, bet. secs. 11 and 14. Over rolling land, through scattering undergrowth. Desc. 75 ft. to Draw, 50 lks. wide, course NW. Asc. 15 ft. to Desc. 95 ft. to Draw, 1 ch. wide, course SW. Asc. to Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

1/4 S11
 1/4 S14
 1916

50.10
 79.99

and raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor. Desc. 80 ft. to Bottom of Red Lake Canyon, 5 chs. wide, course NE. Asc. 140 ft. to The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, red, rocky and sandy; 3rd rate. No timber. Undergrowth, sagebrush and algerita. White gramma grass.

26.35
 29.85
 35.00

N.0° 1' W., bet. secs. 10 and 11. Over broken land, through scattering timber and undergrowth. Desc. 155 ft. Barb wire fence, brs. E. and W. Red Lake Canyon, 3 chs. wide, course N.70° W. Thence along E. side of Red Lake Canyon. Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, for witness cor. to ¼ sec. cor., marked on brass cap

Chains.

$\frac{1}{4}$
 S10 | S11
 W C
 1916

- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 40.00 Center of Red Lake Canyon, 3 chs. wide, course N. Impracticable to set cor. here.
- Asc. 20 ft. to
- 42.46 Dam across Red Lake Canyon.
- 44.45 Barb wire fence, brs. E. and W. Leave Red Lake Canyon, course N. 70° W. Asc. 65 ft. to
- 58.77 Spur, slopes NW. Desc. 115 ft. to
- 68.62 Bottom of Cataract Canyon, 4 chs. wide, course N. 20° E. Asc. 115 ft. to
- 80.00 Set an iron post, 3 ft. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone, for cor. of secs. 2, 3, 10 and 11, marked on brass cap

T25N | R1E
 S 3 | S 2
 S10 | S11
 1916

From which

- A pinion, 6 ins. diam., brs. N. $37\frac{1}{2}^\circ$ E., 130 lks. dist., marked T25N R1E S2 BT.
- A pinion, 12 ins. diam., brs. S. 32° E., 239 lks. dist., marked T25N R1E S11 BT.
- A pinion, 12 ins. diam., brs. S. $79^\circ 55'$ W., 72 lks. dist., marked T25N R1E S10 BT.
- A pinion, 18 ins. diam., brs. N. $43^\circ 10'$ W., 68 lks. dist., marked T25N R1E S3 BT.

Land, broken.
 Soil, rocky; 3rd rate.
 Timber, pinion and cedar.
 Undergrowth, sagebrush and algerita.

- 40.00 East on a random line, bet. secs. 2 and 11.
- Set temp. $\frac{1}{4}$ sec. cor.
- 80.06 Intersect N. and S. line, 26 lks. N. of the cor. of secs. 1, 2, 11 and 12.
- Thence
- N. $89^\circ 49'$ W., on a true line, bet. secs. 2 and 11.
- Over rolling and mountainous land, through scattering brush.
- 5.20 Draw, 4 chs. wide, course N.
- 20.05 Enter timber, brs. N. and S.
- 40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 2
 S11
 1916

- From which
- A pinion, 10 ins. diam., brs. N. $29^\circ 35'$ E., 110 lks. dist., marked $\frac{1}{4}$ S2 BT.
- A cedar, 6 ins. diam., brs. S. 42° E., 47 lks. dist., marked $\frac{1}{4}$ S11 BT.
- 45.05 Ridge, brs. NE. and SW. Desc. 200 ft. to
- 70.25 Bottom of Cataract Canyon, 5 chs. wide, course N. Asc. 115 ft. to
- 80.06 The cor. of secs. 2, 3, 10 and 11.
- Land, rolling and mountainous.
- Soil, shallow, rocky; 3rd rate.


14.

Subdivision of T. 25 N., R. 1 E.

chains.


Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

40.00 N.0° 1' W., on a random line, bet. secs. 2 and 3.
Set temp. $\frac{1}{4}$ sec. cor.
80.37 Intersect N. bdy. of Tp., 5 lks. W. of the cor. of secs.
2, 3, 34 and 35, which is an iron post, described in
Book "A".
Thence
S.0° 1' W., on a true line, bet. secs. 2 and 3.
Over broken and mountainous land, through scattering
timber and undergrowth.
Desc. 105 ft. to
10.65 Mouth of draw from SW. Dam brs. SW. 5 chs. Asc. 125 ft.
20.35 Thence along E. slope above Cataract Canyon.
30.35 Desc. 120 ft. to
40.37 Bottom of Cataract Canyon, 3 chs. wide, course NE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W.
of cor.
Asc. 90 ft. to
45.70 Spur, slopes W. Desc. 80 ft. to
55.55 Cataract Canyon, 3 chs. wide, course W. Asc. 120 ft. to
65.35 Desc. 30 ft. to
80.37 The cor. of secs. 2, 3, 10 and 11.
Land, broken and mountainous.
Soil, shallow, rocky; 3rd rate.
Timber, pinion and cedar.
Undergrowth, sagebrush and algerita.
White gramma grass.

From the standard cor. of secs. 3, 4, 33 & 34, on the S. bdy.
of the Tp., which is an iron post, reestablished as
described under current Group No. 52,
N.0° 2' W., bet. secs. 33 and 34.
Over rolling land, through scattering timber and under-
growth.
15.00 Desc. 95 ft. to
29.92 Draw, 2 chs. wide, course NE. Asc. 55 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
brass cap



From which
A cedar, 6 ins. diam., brs. S.65 $\frac{1}{2}$ ° E., 31 lks. dist.,
marked $\frac{1}{4}$ S34 BT.
A pinion, 6 ins. diam., brs. S.62 $\frac{1}{4}$ ° W., 52 lks. dist.,
marked $\frac{1}{4}$ S33 BT.
45.00 Spur, slopes E. Desc. 135 ft. to
63.83 Draw, 1 ch. wide, course N.70° E. Road in draw, brs. N.
80° E. and W. Asc. 90 ft. to

Subdivision of T. 25 N., R. 1 E. 15.

Chains.
80.00

Set an iron post, 3 ft. long, 2 ins. diam., in a mound of stone, for cor. of secs. 27, 28, 33 and 34, marked on brass cap

T25N R1E
S28 S27
S33 S34
1916

From which

A pinion, 6 ins. diam., brs. N.35° 35' E., 117 lks. dist., marked T25N R1E S27 BT.

A cedar, 6 ins. diam., brs. S.56° E., 101 lks. dist., marked T25N R1E S34 BT.

A cedar, 6 ins. diam., brs. S.59½° W., 31 lks. dist., marked T25N R1E S33 BT.

A pinion, 6 ins. diam., brs. N.55° 20' W., 33 lks. dist., marked T25N R1E S28 BT.

Land, rolling.

Soil, sandy and rocky; 3rd rate.

Timber, cedar and pinion.

Undergrowth, sagebrush.

White gramma grass.

40.00
80.08

East on a random line, bet. secs. 27 and 34.

Set temp. ¼ sec. cor.

Intersect N. and S. line, 15 lks. S. of the cor. of secs. 26, 27, 34 and 35.

Thence

S.89° 54' W., on a true line, bet. secs. 27 and 34.

Over rolling land, through scattering undergrowth.

Asc. slightly.

5.20
10.20
15.00
35.10

Ridge, brs. N. and S. Desc. 140 ft.

Road, brs. NE. and S.70° W.

Road, brs. NW. and SE.

Bottom of Cataract Canyon, 2 chs. wide, 10 ft. deep, course NE. Asc. 30 ft. to

40.04

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼ S27
¼ S34
1916

From which

A cedar, 16 ins. diam., brs. N.85° E., 150 lks. dist., marked ¼ S27 BT.

A cedar, 8 ins. diam., brs. S.27° 40' W., 74 lks. dist., marked ¼ S34 BT.

From this point, old corral brs. N. 4 chs. dist.

43.15
45.15
50.10
80.08

Road, brs. NE. and SW.

Draw, 1 ch. wide, course NE. Asc. 145 ft.

Enter timber, brs. NE. and SW.

The cor. of secs. 27, 28, 33 and 34.

Land, rolling.

Soil, shallow, sandy and rocky; 3rd rate.

Timber, cedar and pinion.

Undergrowth, sagebrush and algerita.

White gramma grass.

10.00
39.60

N.0° 2' W., bet. secs. 27 and 28.

Over rolling land, through heavy timber and scattering undergrowth.

Asc. 30 ft. to


Spur, slopes NE. Desc. 140 ft.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for witness cor. to ¼ sec.

16. Subdivision of T. 25 N., R. 1 E.


Chains

cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

- 40.00 True point for ¼ sec. cor. falls in dry creek bed, 50 lks. wide, course NE. Asc. 135 ft. to
- 67.90 Spur, slopes E. Desc. 20 ft. to
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on brass cap




A pinion, 10 ins. diam., brs. N.67½° E., 1 ch. dist., marked T25N R1E S22 BT.
 A cedar, 6 ins. diam., S.55½° E., 135 lks, dist., marked T25N R1E S27 BT.
 A pinion, 8 ins. diam., brs. S.66° 5' W., 280 lks. dist., marked T25N R1E S28 BT.
 A pinion, 8 ins. diam., brs. N.62¼° W., 122 lks. dist., marked T25N R1E S21 BT.

Land, rolling.
 Soil, shallow; sandy and rocky; 3rd rate.
 Timber, cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

- 40.00 East on a random line, bet. secs. 22 and 27. Set temp. ¼ sec. cor.
- 79.97 Intersect N. and S. line, 24 lks. S. of the cor. of secs. 22, 23, 26 and 27.

Thence S.89° 50' W., on a true line, bet. secs. 22 and 27. Over rolling land, through scattering timber and undergrowth.

- 7.80 Desc. 80 ft. to
- 9.80 Draw, 3 chs. wide, course NW. Asc. 65 ft.
- 12.75 Road, brs. N.40° W. and S.40° E.
- 19.95 Desc. 30 ft. to
- 39.98 Enter Cataract Canyon, course N.20° E.
- 41.97 The true point for ¼ sec. cor. falls in Cataract Canyon, 10 ft. deep, course N.70° E.
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness cor. to ¼ sec. cor., marked on brass cap




and raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

- 45.15 Leave Cataract Canyon, course N.70° E. Asc. 205 ft. to
 - 69.95 Desc. 35 ft. to
 - 74.95 Asc. 25 ft. to
 - 79.97 The cor. of secs. 21, 22, 27 and 28.
- Land, rolling.
 Soil, sandy and rocky; 3rd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.


Subdivision of T. 25 N., R. 1 E. 17.

Chains.

N.0° 2' W., bet. secs. 21 and 22.
 Over rolling land, through scattering timber and undergrowth.
 Desc. 35 ft. to
 5.00 Draw, 2 chs. wide, course NE. Thence over rolling land.
 25.00 Asc. 40 ft. to
 35.00 Desc. 70 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap




From which
 A cedar, 6 ins. diam., brs. S. 26° E., 131 lks. dist., marked $\frac{1}{4}$ S22 BT.
 A pinion, 8 ins. diam., brs. S.46° 40' W., 205 lks. dist., marked $\frac{1}{4}$ S21 BT.
 55.00 Draw, 50 lks. wide, course NE.
 70.00 Leave timber, brs. NW. and SE. Desc. 45 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on brass cap



dig pits, 18 X 18 X 12 ins., in each sec., 5 $\frac{1}{2}$ ft. dist., and spread the dirt around the post.

Land, rolling.
 Soil, shallow, sandy; 2nd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 15 and 22.
 79.91 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 30 lks. S. of the cor. of secs. 14, 15, 22 and 23.
 Thence
 S.89° 47' W., on a true line, bet. secs. 15 and 22.
 Over rolling land, through scattering timber and undergrowth.
 Desc. 95 ft. to
 15.10 Asc. 30 ft. to
 20.10 Ridge, brs. N. and S. Desc. 120 ft. to
 30.00 Bottom of Cataract Canyon, 3 chs. wide, course N.20° E.
 Asc. 105 ft.
 39.95 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

42.30 Spur, slopes SE. Desc. 100 ft. to
 54.90 Draw, 2 chs. wide, course SE. Asc. gradually.
 66.70 Road, brs. N.42° W. and SE.
 79.91 The cor. of secs. 15, 16, 21 and 22.

Chains.

Land, rolling.
Soil, shallow, sandy and rocky; 3rd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

N.0° 2' W., bet. secs. 15 and 16.
Over rolling land, through scattering timber and undergrowth.

Desc. gradually.

13.90

Road, brs. N.54° W. and S.42° E.

20.00

Draw, 5 chs. wide, course S.70° E. Asc. 190 ft.

29.83

Enter heavy timber, brs. E. and W.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

 $\frac{1}{4}$

S16 | S15

1916

From which

A cedar, 10 ins. diam., brs. S.72° 40' E., 110 lks. dist., marked $\frac{1}{4}$ S15 BT.

A pinion, 8 ins. diam., brs. S.36° 50' W., 24 lks. dist., marked $\frac{1}{4}$ S16 BT.

45.00

Ridge, brs. E. and W. Desc. 105 ft. to

64.91

Draw, 1 ch. wide, course S.70° E. Asc. 55 ft. to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap

T25N | R1E

S 9 | S10

S16 | S15

1916

From which

A pinion, 6 ins. diam., brs. N.49° 35' E., 223 lks. dist., marked T25N R1E S10 BT.

A pinion, 8 ins. diam., brs. S.56° E., 330 lks. dist., marked T25N R1E S15 BT.

A pinion, 10 ins. diam., brs. S.8° W., 480 lks. dist., marked T25N R1E S16 BT.

A pinion, 6 ins. diam., brs. N74 $\frac{1}{4}$ ° W., 301 lks. dist., marked T25N R1E S9 BT.

Land, rolling.

Soil, shallow, sandy and rocky; 3rd rate.

Timber, cedar and pinion.

Undergrowth, sagebrush and algerita.

White gramma grass.

East on a random line, bet. secs. 10 and 15.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

80.05

Intersect N. and S. line, 30 lks. S. of the cor. of secs. 10, 11, 14 and 15.

Thence

S.89° 47' W., on a true line, bet. secs. 10 and 15.

Over rolling land, through scattering timber and undergrowth.

Desc. 210 ft. to

25.60

Bottom of Cataract Canyon, 3 chs. wide, course N. Asc. 190 ft.

40.02 $\frac{1}{2}$

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on

Subdivision of T. 25 N., R. 1 E. 19.

Chains.

brass cap

$\frac{1}{4}$ S10
S15
1916

From which

A cedar, 6 ins. diam., brs. N.34 $\frac{1}{2}$ ° W., 13 lks. dist., marked $\frac{1}{4}$ S10 BT.
A cedar, 6 ins. diam., brs. S.6 $\frac{1}{2}$ ° W., 85 lks. dist., marked $\frac{1}{4}$ S15 BT.

65.05 Top of ascent, brs. NE. and SW. Leave timber, brs. N. and S. Thence over gently rolling land.

80.05 The cor. of secs. 9, 10, 15 and 16.
Land, rolling.

Soil, sandy, shallow; 3rd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

N.0° 2' W., bet. secs. 9 and 10.
Over gently rolling land, through scattering undergrowth.
Enter timber, brs. E. and W.

35.00
40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S 9 | S10
1916

From which

A cedar, 8 ins. diam., brs. N.40° 35' E., 87 lks. dist., marked $\frac{1}{4}$ S10 BT.
A pinion, 6 ins. diam., brs. S.30 $\frac{3}{4}$ ° W., 141 lks. dist., marked $\frac{1}{4}$ S9 BT.

55.00 Leave timber, brs. E. and W.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, in a mound of stone, for cor. of secs. 3, 4, 9 and 10, marked on brass cap

T25N | R1E
S 4 | S 3
S 9 | S10
1916

and raise a mound of stone, 3 ft. base, $\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.
Soil, shallow, **sandy**; 2nd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

East on a random line, bet. secs. 3 and 10.

40.00 Set temp. $\frac{1}{4}$ sec. cor.
80.00 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence S.89° 56' W., on a true line, bet. secs. 3 and 10.

Over rolling land, through scattering timber and undergrowth. Asc. gradually to

20.00 Ridge brs. N. and S. Desc. gradually to
40.00 Draw, 3 chs. wide, course S.20° E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on

Chains.

brass cap

$\frac{1}{4}$ S 3
S 10
1916

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high,
N. of cor.

- 60.00 Leave timber, brs. N. and S.
- 80.00 The cor. of secs. 3, 4, 9 and 10.
- Land, rolling.
- Soil, shallow, sandy; 2nd rate.
- Timber, cedar and pinion.
- Undergrowth, sagebrush and algerita.
- White gramma grass.

- 40.00 N.0° 2' W., on a random line, bet. secs. 3 and 4.
- Set temp. $\frac{1}{4}$ sec. cor.
- 80.48 Intersect N. bdy. of T., 5 lks. E. of the cor. of secs. 3, 4, 33 and 34, which is an iron post, described in Book "A".
- Thence
- S.0° 4' E., on a true line, bet. secs. 3 and 4.
- Over rolling land, through scattering timber and undergrowth.
- 10.48 Leave timber, brs. E. and W.
- 40.48 Draw, course E.
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S 4 | S 3
1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and spread the dirt around the post.

- 51.19 Road, brs. E. and W.
- 60.50 Enter timber, brs. NE. and SW.
- 70.50 Leave timber, brs. E. and W.
- 80.48 The cor. of secs. 3, 4, 9 and 10.
- Land, rolling.
- Soil, 2nd rate.
- Timber, cedar and pinion.
- Undergrowth, sagebrush and algerita.
- White gramma grass.

- 15.00 From the standard cor. of secs. 4, 5, 32 & 33, on the S. bdy. of the Tp., which is an iron post, re-established as described under current Group No. 52,
- 39.50 N. 0° 3' W., bet. secs. 32 and 33.
- 40.00 Over rolling land, through scattering undergrowth.
- Road, brs. E. and W.
- Road, brs. NW and SE.
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S 32 | S 33
1916

BOOK 2005

Subdivision of T. 25 N., R. 1 E. 21.

Chains.

65.00 and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.
 80.00 Enter scattering timber, brs. E. and W.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of stone, for cor. of secs. 28, 29, 32 and 33, marked on brass cap

T25N	R1E
S29	S28
S32	S33
1916	

and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.
 Land, rolling.
 Soil, red, sandy; 2nd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 28 and 33.
 80.12 Set temp. 1/4 sec. cor.
 80.12 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 27, 28, 33 and 34.
 Thence
 N.89° 56' W., on a true line, bet. secs. 28 and 33.
 Over rolling land, through scattering undergrowth and heavy timber.
 Asc. 45 ft. to
 15.10 Spur, slopes NE. Desc. gradually.
 40.06 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4	S28
4	S33
1916	

From which
 A pinion, 10 ins. diam., brs. N.54° 10' W., 200 lks. dist., marked 1/4 S28 BT.
 A pinion, 10 ins. diam., brs. S.17° 20' W., 130 lks. dist., marked 1/4 S33 BT.
 80.12 The cor. of secs. 28, 29, 32 and 33.
 Land, rolling.
 Soil, red, sandy; 2nd rate.
 Timber, cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

10.00 N.0° 3' W., bet. secs. 28 and 29.
 40.00 Over gently rolling land, through scattering timber and undergrowth.
 Thence over level land.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4	
S29	S28
1916	

From which
 A cedar, 6 ins. diam., brs. S.52° 20' E., 180 lks. dist., marked 1/4 S28 BT.
 A pinion, 10 ins. diam., brs. N.57° 20' W., 74 lks. dist., marked 1/4 S29 BT.

22.

Subdivision of T. 25 N., R. 1 E.

chains.									
80.00	<p>Thence over gently rolling land. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, marked on brass cap</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T25N</td><td>R1E</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td>S29</td><td>S28</td></tr> <tr><td colspan="2">1916</td></tr> </table> <p>and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor. Land, level and rolling. Soil, red, sandy; 2nd rate. Timber, cedar and pinion. Undergrowth, sagebrush and algerita. White gramma grass.</p>	T25N	R1E	S20	S21	S29	S28	1916	
T25N	R1E								
S20	S21								
S29	S28								
1916									
40.00	<p>East on a random line, bet. secs. 21 and 28. Set temp. ¼ sec. cor.</p>								
80.02	<p>Intersect N. and S. line, 11 lks. N. of the cor. of secs. 21, 22, 27 and 28. Thence N. 89° 55' W., on a true line, bet. secs. 21 and 28. Over rolling land, through scattering timber and undergrowth.</p>								
25.00	<p>Draw, 2 chs. wide, course NE.</p>								
40.01	<p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>¼</td><td>S21</td></tr> <tr><td>¼</td><td>S28</td></tr> <tr><td colspan="2">1916</td></tr> </table> <p>From which A pinion, 6 ins. diam., brs. N. 55° E., 218 lks. dist., marked ¼ S21 BT. A pinion, 6 ins. diam., brs. S. 10° 40' E., 232 lks. dist., marked ¼ S28 BT.</p>	¼	S21	¼	S28	1916			
¼	S21								
¼	S28								
1916									
65.00	<p>Draw, 1 ch. wide, course N.</p>								
80.02	<p>The cor. of secs. 20, 21, 28 and 29. Land, rolling. Soil, red, sandy; 2nd rate. Timber, scattering cedar and pinion. Undergrowth, sagebrush and algerita. White gramma grass.</p>								
35.00	<p>N. 0° 3' W., bet. secs. 20 and 21. Over rolling land, through scattering undergrowth.</p>								
40.00	<p>Draw, 3 chs. wide, course E. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>¼</td><td></td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td colspan="2">1916</td></tr> </table> <p>and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p>	¼		S20	S21	1916			
¼									
S20	S21								
1916									
70.00	<p>Head of draw, course NE.</p>								
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 16, 17, 20 and 21, marked on brass cap</p>								

Chains.

T25N	R1E
S17	S16
S20	S21
1916	

and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
 Land, rolling.
 Soil, sandy; 2nd rate.
 No timber.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 16 and 21.
 Set temp. ¼ sec. cor.
 79.92 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 15, 16, 21 and 22.
 Thence
 N.89° 58' W., on a true line, bet. secs. 16 and 21.
 Over rolling land, through scattering undergrowth.
 19.90 Enter heavy timber, brs. NW. and SE.
 35.00 Draw, 1 ch. wide, course N.
 39.96 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	S16
¼	S21
1916	

From which
 A pinion, 8 ins. diam., brs. N.44° 10' E., 36 lks. dist., marked ¼ S16 BT.
 A pinion, 12 ins. diam., brs. S.18° 10' W., 99 lks. dist., marked ¼ S21 BT.

Asc. gradually.
 59.90 Spur, slopes N. Desc. to
 70.00 Draw, 1 ch. wide, course N. Asc. 65 ft. to
 79.92 The cor. of secs. 16, 17, 20 and 21.
 Land, rolling.
 Soil, sandy; 2nd rate.
 Timber, cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 N.0° 3' W., bet. secs. 16 and 17.
 Over gently rolling land, through scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼	S17	S16
1916		

68.70 and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
 Road, brs. E. and W.
 70.00 Draw, course S.70° E. Asc. 70 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on brass cap

24.

Subdivision of T. 25 N., R. 1 E.

Chains.

T25N R1E
 S 8 | S 9
 S17 | S16
 1916

and raise a mound of stone, 3 ft. base, 2 1/2 ft. high,
 W. of cor.
 Land, rolling.
 Soil, red, sandy; 2nd rate.
 No timber.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00
 79.85

East on a random line, bet. secs. 9 and 16.
 Set temp. 1/4 sec. cor.
 Intersect N. and S. line, 11 lks. N. of the cor. of secs.
 9, 10, 15 and 16,

39.92 1/2

Thence
 N. 89° 55' W., on a true line, bet. secs. 9 and 16.
 Over rolling land, through scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
 ground, in a mound of stone, for 1/4 sec. cor., marked on
 brass cap

1/4 S 9
 S16
 1916

59.85
 79.85

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
 dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft.
 N. of cor.

Enter timber, brs. N. and S. Asc. 90 ft. to
 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.
 Soil, black, sandy; 2nd rate.
 Timber, cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00

N. 0° 3' W., bet. secs. 8 and 9.
 Over gently rolling land, through scattering timber and
 undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for 1/4 sec. cor., marked on brass cap

1/4
 S 8 | S 9
 1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
 dist.; and spread the dirt around the post.

41.00
 45.00
 80.00

Road, brs. N. 68° E. and S. 85° W.
 Draw, 5 chs. wide, course E.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for cor. of secs. 4, 5, 8 and 9, marked on
 brass cap

T25N R1E
 S 5 | S 4
 S 8 | S 9
 1916

dig pits, 18 X 18 X 12 ins., in each sec., 5 1/2 ft. dist.;
 and spread the dirt around the post.

Subdivision of T. 25 N., R. 1 E.

25.

Chains.

Land, rolling.
Soil, red, sandy; 2nd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

40.00 East on a random line, bet. secs. 4 and 9.
Set temp. $\frac{1}{4}$ sec. cor.
79.88 Intersect N. and S. line, 16 lks. N. of the cor. of secs.
3, 4, 9 and 10.
Thence
N.89° 53' W., on a true line, bet. secs. 4 and 9.
Over rolling land, through scattering undergrowth.
14.90 Enter timber, brs. N. and S.
24.90 Leave timber, brs. N. and S.
29.90 Road, brs. NE. and SW.
34.90 Draw, 5 chs. wide, course N.
39.94 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 4
S 9
1916

79.88 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
dist.; and spread the dirt around the post.
The cor. of secs. 4, 5, 8 and 9.
Land, rolling.
Soil, 2nd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

40.00 N.0° 3' W., on a random line, bet. secs. 4 and 5.
Set temp. $\frac{1}{4}$ sec. cor.
80.45 Intersect N. bdy. of Tp., 24 lks. E. of the cor. of secs.
4, 5, 32 and 33, which is an iron post, described in
Book "A".
Thence
S.0° 13' E., on a true line, bet. secs. 4 and 5.
Over gently rolling land, through scattering timber and
undergrowth.
40.45 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S 5 S 4
1916

80.45 and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high,
W. of cor.
The cor. of secs. 4, 5, 8 and 9.
Land, gently rolling.
Soil, sandy; 2nd rate.
Timber, scattering cedar.
Undergrowth, sagebrush and algerita.
White gramma grass.

26.


Subdivision of T. 25 N., R. 1 E.

Chains

From the standard cor. of secs. 5, 6, 31 & 32, on the S. bdy. of the Tp., which is an iron post, re-established as described under current Group No. 52., N.0° 3' W., bet. secs. 31 and 32. Over gently rolling land, through scattering timber and undergrowth.

7.90
40.00

Road, brs. NW. and SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap




From which

- A cedar, 10 ins. diam., brs. S.31° 20' E., 50 lks. dist., marked 1/4 S32 BT.
- A cedar, 12 ins. diam., brs. S.14° 20' W., 78 lks. dist., marked 1/4 S31 BT.

65.00
80.00

Road, brs. N.70° W. and SE.
Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, in a mound of stone, for cor. of secs. 29, 30, 31 and 32, marked on brass cap



From which

- A cedar, 15 ins. diam., brs. N.50° 25' E., 96 lks. dist., marked T25N R1E S29 BT.
- A cedar, 12 ins. diam., brs. S.61° 50' E., 79 lks. dist., marked T25N R1E S32 BT.
- A cedar, 10 ins. diam., brs. S.72° 20' W., 104 lks. dist., marked T25N R1E S31 BT.
- A pinion, 8 ins. diam., brs. N.42° 40' W., 91 lks. dist., marked T25N R1E S30 BT.

Land, gently rolling.
Soil, red, sandy; 2nd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.


40.00
79.99

East on a random line, bet. secs. 29 and 32.
Set temp. 1/4 sec. cor.
Intersect N. and S. line, 2 lks. S. of the cor. of secs. 28, 29, 32 and 33.

Thence
S.89° 50' W., on a true line, bet. secs. 29 and 32.
Over gently rolling land, through scattering timber and undergrowth.

35.00
39.99 1/2

Head of draw, 5 chs. wide, course SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



From which

- A cedar, 10 ins. diam., brs. N.58° 20' W., 199 lks. dist., marked 1/4 S29 BT.
- A cedar, 10 ins. diam., brs. S.76° 35' W., 358 lks. dist., marked 1/4 S32 BT.

65.00
79.99

Draw, 5 chs. wide, course NW.
The cor. of secs. 29, 30, 31 and 32.

Subdivision of T. 25 N., R. 1 E.

Chains.

Land, gently rolling.
Soil, red, sandy; 2nd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.

40.00
79.83


West on a random line, bet. secs. 30 and 31.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect Gila and Salt River Meridian, 29 lks. S. of the
cor. of secs. 25, 30, 31 and 36, which is an iron
post, re-established as described in Book "A".
Thence
S. 89° 48' E., on a true line, bet. secs. 30 and 31.
Over gently rolling land, through scattering timber and
undergrowth.

14.85
27.35

Road, brs. NE. and SW.
Draw, course N.
Road, brs. N. 20° W. and S. 20° E.

39.83

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
brass cap




79.83

From which
A pinion, 6 ins. diam., brs. N. 45° E., 64 lks. dist.,
marked $\frac{1}{4}$ S30 BT.
A cedar, 18 ins. diam., brs. S. 43° 40' W., 60 lks.
dist., marked $\frac{1}{4}$ S31 BT.
The cor. of secs. 29, 30, 31 and 32.
Land, gently rolling.
Soil, red, sandy; 2nd rate.
Timber, cedar and pinion.
Undergrowth, sagebrush and algerita.


10.00
30.00
40.00

N. 0° 3' W., bet. secs. 29 and 30.
Over gently rolling land, through scattering timber and
undergrowth.
Draw, 5 chs. wide, course NW.
Leave timber, brs. E. and W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



65.00
80.00

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and spread the dirt around the post.
Head of draw, 2 chs. wide, course NW.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 19, 20, 29 and 30, marked on
brass cap



dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.;
and spread the dirt around the post.

28.

Subdivision of T. 25 N., R. 1 E.

Chains.

Land, gently rolling.
Soil, sandy; 2nd rate.
Timber, scattering cedar and pinion.
Undergrowth, sagebrush and algerita.
White gramma grass.

- 40.00 East on a random line, bet. secs. 20 and 29.
Set temp. $\frac{1}{4}$ sec. cor.
80.22 Intersect N. and S. line, 2 lks. S. of the cor. of secs.
20, 21, 28 and 29.
Thence
S.89° 59' W., on a true line, bet. secs. 20 and 29.
Over gently rolling land, through scattering undergrowth
and timber.
40.11 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\frac{1}{4} \frac{S20}{S29}$$

1916

- From which
A cedar, 8 ins. diam., brs. N.17° 50' W., 100 lks. dist.,
marked $\frac{1}{4}$ S20 BT.
A cedar, 8 ins. diam., brs. S.58° E., 127 lks. dist.,
marked $\frac{1}{4}$ S29 BT.
50.22 Draw, course N.
80.22 The cor. of secs. 19, 20, 29 and 30.
Land, gently rolling.
Soil, sandy; 2nd rate.
Timber, scattering cedar.
Undergrowth, sagebrush and algerita.
White gramma grass.

- 40.00 West on a random line, bet. secs. 19 and 30.
Set temp. $\frac{1}{4}$ sec. cor.
79.71 Intersect Gila and Salt River Meridian, 14 lks. S. of the
cor. of secs. 19, 24, 25 and 30, which is an iron post,
re-established as described in Book "A".
Thence
S.89° 54' E., on a true line, bet. secs. 19 and 30.
Over rolling land, through scattering timber and under-
growth.
31.40 Road, brs. N.20° E. and S.30° W.
34.70 Draw, 5 chs. wide, course N.
39.71 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\frac{1}{4} \frac{S19}{S30}$$


1916

- and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N.
of cor.
54.70 Draw, 3 chs. wide, course NW.
79.71 The cor. of secs. 19, 20, 29 and 30.
Land, rolling.
Soil, red, sandy; 2nd rate.
Timber, scattering cedar.
Undergrowth, sagebrush and algerita.
White gramma grass.


Subdivision of T. 25 N., R. 1 E.

Chains.

40.00 N.0° 3' W., bet. secs. 19 and 20.
 Over gently rolling land, through scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
 ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
 brass cap




80.00 and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high,
 W. of cor.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for cor. of secs. 17, 18, 19 and 20, marked on
 brass cap



and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high,
 W. of cor.
 Land, gently rolling.
 Soil, red, sandy; 2nd rate.
 No timber.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 East on a random line, bet. secs. 17 and 20.
 80.25 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 11 lks. N. of the cor. of secs.
 16, 17, 20 and 21.

Thence
 N.89° 55' W., on a true line, bet. secs. 17 and 20.
 Over gently rolling land, through scattering undergrowth.
 25.25 Draw, 5 chs. wide, course N.20° E.
 40.12 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
 ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
 brass cap



75.25 and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N.
 of cor.
 80.25 Draw, 5 chs. wide, course N.
 The cor. of secs. 17, 18, 19 and 20.
 Land, gently rolling.
 Soil, shallow, sandy; 2nd rate.
 No timber.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 West on a random line, bet. secs. 18 and 19.
 79.52 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect Gila and Salt River Meridian 19 lks. S. of the
 cor. of secs. 13, 18, 19 and 24, which is an iron post,
 re-established as described in Book "A".

Thence
 S.89° 52' E., on a true line, bet. secs. 18 and 19.
 Over gently rolling land, through scattering timber and
 undergrowth.
 17.30 Road, brs. N.20° W. and S.20° E.
 39.52 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

30.

Subdivision of T. 25 N., R. 1 E.

chains.

$\frac{1}{4}$	S18
$\frac{1}{4}$	S19
	1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and spread the dirt around the post.

42.80 Road, brs. N. and S.

44.50 Draw, 5 chs. wide, course N.

79.52 The cor. of secs. 17, 18, 19 and 20.
Land, gently rolling.
Soil, sandy; 2nd rate.
Timber, scattering cedar.
Undergrowth, sagebrush and algerita.
White gramma grass.

40.00 N. 0° 3' W., bet. secs. 17 and 18.
Over gently rolling land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$	
S17	S18
	1916

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

73.30 Road, brs. N. 70° E. and SW.

75.00 Draw, 5 chs. wide, course S. 70° E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap

T25N	R1E
S 7	S 8
S18	S17
	1916

dig pits, 18 X 18 X 12 ins., in each sec., 5 $\frac{1}{2}$ ft. dist.; and spread the dirt around the post.

Land, gently rolling.
Soil, red, sandy; 2nd rate.
No timber.
Undergrowth, sagebrush and algerita.
White gramma grass.

40.00 East on a random line, bet. secs. 8 and 17.
Set temp. $\frac{1}{4}$ sec. cor.

80.22 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 8, 9, 16 and 17.

Thence

10.00 N. 89° 56' W., on a true line, bet. secs. 8 and 17.

40.11 Draw 5 chs. wide, course S. through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$	S 8
$\frac{1}{4}$	S17
	1916

55.20 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and spread the dirt around the post.
Road, brs. S. 70° E. and NE.

BOOK 2095

Subdivision of T. 25 N., R. 1 E.

Chains.

62.00 From this point, dirt dam, 6 ft. high, brs. S. about 7. chs. dist.

80.22 The cor. of secs. 7, 8, 17 and 18.
Land, gently rolling.
Soil, 2nd rate.
No timber.
Undergrowth, sagebrush and algerita.


40.00 West on a random line, bet. secs. 7 and 18.
Set temp. 1/4 sec. cor.

79.36 Intersect Gila and Salt River Meridian, 26 lks. S. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, re-established as described in Book "A".

Thence

S.89° 49' E., on a true line, bet. secs. 7 and 18.

39.36 Over gently rolling land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for 1/4 sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

79.36 The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling.
Soil, red, sandy; 2nd rate.
No timber.
Undergrowth, sagebrush and algerita.
White gramma grass.


N.0° 3' W., bet. secs. 7 and 8.

Over rolling land, through scattering undergrowth.
Asc.90 ft.

10.00 Enter timber, brs. E. and W.

24.93 Ridge, brs. E. and W. Thence over gently rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap




From which

A cedar, 10 ins. diam., brs. S.39° 10' E., 134 lks. dist., marked 1/4 S 8 BT.

A cedar, 8 ins. diam., brs. N.14 1/2° W., 345 lks. dist., marked 1/4 S 7 BT.

75.00 Leave timber, brs. E. and W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, marked on brass cap



dig pits, 18 X 18 X 12 ins., in each sec., 5 1/2 ft. dist.; and spread the dirt around the post.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, cedar and pinion.

Undergrowth, sagebrush and algerita.

White gramma grass.

32.

Subdivision of T. 25 N., R. 1 E.

Chains

40.00 East on a random line, bet. secs. 5 and 8.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.98 Intersect N. and S. line, 4 lks. N. of the cor. of secs.
 4, 5, 8 and 9.
 Thence
 N. $89^{\circ} 58'$ W., on a true line, bet. secs. 5 and 8.
 Over rolling land, through scattering undergrowth.
 20.00 Enter timber, brs. NW. and SW.
 36.60 Road, brs. NW. and SE.
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
 ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
 brass cap

$\frac{1}{4} \frac{S 5}{S 8}$
 1916

From which
 A pinion, 6 ins. diam., brs. N. $58^{\circ} 5'$ W., 64 lks. dist.,
 marked $\frac{1}{4} S 5$ BT.
 A pinion, 18 ins. diam., brs. S. $39^{\circ} 40'$ W., 173 lks.
 dist., marked $\frac{1}{4} S 8$ BT.
 50.00 Leave timber, brs. NW. and SE.
 70.00 Low divide, brs. NW. and SE. Desc. gradually to
 79.98 The cor. of secs. 5, 6, 7 and 8.
 Land, rolling.
 Soil, 2nd rate.
 Timber, scattering cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

40.00 West on a random line, bet. secs. 6 and 7.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.24 Intersect Gila and Salt River Meridian 33 lks. S. of the
 cor. of secs. 1, 6, 7 and 12, which is an iron post,
 re-established as described in Book "A".
 Thence
 S. $89^{\circ} 46'$ E., on a true line, bet. secs. 6 and 7.
 Over gently rolling land, through scattering timber and
 1.65 Draw, course NE. (undergrowth.)
 39.24 Draw, 3 chs. wide, course N.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap


$\frac{1}{4} \frac{S 6}{S 7}$
 1916

From which
 A cedar, 6 ins. diam., brs. N. 50° W., 222 lks. dist.,
 marked $\frac{1}{4} S 6$ BT.
 A cedar, 6 ins. diam., brs. S. $76^{\circ} 20'$ W., 324 lks.
 dist., marked $\frac{1}{4} S 7$ BT.
 64.24 Leave timber, brs. N. and S.
 79.24 The cor. of secs. 5, 6, 7 and 8.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, cedar and pinion.
 Undergrowth, sagebrush.
 White gramma grass.

40.00 N. $0^{\circ} 3'$ W., on a random line, bet. secs. 5 and 6.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.40 Intersect N. bdy. of Tp., 27 lks. E. of the cor. of secs.
 5, 6, 31 and 32, which is an iron post, established as
 described in Book "A".
 Thence
 S. $0^{\circ} 15'$ E., on a true line, bet. secs. 5 and 6.

Chains.

20.40 Over gently rolling land, through scattering timber and undergrowth.
 Asc. slightly to
 40.40 Low ridge, brs. NW. and SE. Desc. gradually to
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



80.40 From which
 A pinion, 8 ins. diam., brs. N.65° E., 56 lks. dist., marked $\frac{1}{4}$ S5 BT.
 A cedar, 6 ins. diam., brs. S.72° W., 34 lks. dist., marked $\frac{1}{4}$ S6 BT.
 Leave timber, brs. E. and W.
 The cor. of secs. 5, 6, 7 and 8.
 Land, gently rolling.
 Soil, sandy; 2nd rate.
 Timber, cedar and pinion.
 Undergrowth, sagebrush and algerita.
 White gramma grass.

GENERAL DESCRIPTION.

This township consists of rolling land, draining northward, covered with sage and algarretta brush, and scattering cedar and pinion timber.
 The soil consists of sandy clay and loam, with clay subsoil, very shallow, with bed rock outcropping in places.
 White gramma grass affords good grazing.
 There is no water, except that in dams in Cataract Canyon and in draws.
 There are no settlers.

BOOK "B".

SPECIAL SUBDIVISIONAL DIAGRAM

for

GROUP No. 54.

6	5	4	3	2	1	6	5	4	3	2	1	6	5	4	3	2	1
7	8	9	10	11	12	7	8	9	10	11	12	7	8	9	10	11	12
13	14	15	16	17	18	13	14	15	16	17	18	13	14	15	16	17	18
19	20	21	22	23	24	19	20	21	22	23	24	19	20	21	22	23	24
25	26	27	28	29	30	25	26	27	28	29	30	25	26	27	28	29	30
31	32	33	34	35	36	31	32	33	34	35	36	31	32	33	34	35	36
6	5	4	3	2	1	6	5	4	3	2	1	6	5	4	3	2	1
7	8	9	10	11	12	7	8	9	10	11	12	7	8	9	10	11	12
13	14	15	16	17	18	13	14	15	16	17	18	13	14	15	16	17	18
19	20	21	22	23	24	19	20	21	22	23	24	19	20	21	22	23	24
25	26	27	28	29	30	25	26	27	28	29	30	25	26	27	28	29	30
31	32	33	34	35	36	31	32	33	34	35	36	31	32	33	34	35	36
6	5	4	3	2	1	36	35	34	33	32	31	6	5	4	3	2	1
7	8	9	10	11	12	37	38	39	40	41	42	7	8	9	10	11	12
13	14	15	16	17	18	13	14	15	16	17	18	13	14	15	16	17	18
19	20	21	22	23	24	19	20	21	22	23	24	19	20	21	22	23	24
25	26	27	28	29	30	25	26	27	28	29	30	25	26	27	28	29	30
31	32	33	34	35	36	31	32	33	34	35	36	31	32	33	34	35	36

J

- Letters indicate books in which subdivisional lines are to be found.
- Lines surveyed by W. H. Thorn, U. S. Surveyor.
- Lines surveyed by Heber P. Purington, U. S. Transitman.
- Lines surveyed by Richard R. Mitchell, U. S. Transitman.
- Lines of accepted surveys or current groups.

36/35 For names and duties of assistants, see page 78, Book "A".
 CERTIFICATES OF U. S. SURVEYOR AND U. S. TRANSITMEN,

We, W. H. Thorn, and Richard R. Mitchell and Heber P. Purington, U. S. Surveyor and U.S. Transitmen, respectively, hereby certify on honor that, in pursuance of special instructions received from the U.S. Surveyor General, for Arizona for Group No. 54, Arizona, bearing date of the 6th day of March, 1915, we have well, faithfully, and truly, in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the Subdivision Lines of

GROUP 54

in the State of Arizona, which are represented in the foregoing field notes, and those in Books "C," "D," "E," "F," "G," "H," "I," and "J," and by the diagram on the reverse hereof, as having been executed by us, and under our direction; and we do further certify on honor that all the corners of said surveys have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U.S. Surveyor General for Arizona for Group No. 54, and in the specific manner described in our respective field notes and that the foregoing, and notes in Books "C," "D," "E," "F," "G," "H," "I," and "J," are the original field notes of such surveys.

W. H. Thorn
 U. S. Surveyor.

Heber P. Purington
 U. S. Transitman. 1-11-18

Richard R. Mitchell
 U. S. Transitman.

A P P R O V A L .

OFFICE OF UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, August 2 1918

The foregoing field notes of the Survey of the Subdivision lines of

TOWNSHIP 25 NORTH, RANGE 1 EAST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, executed by W. H. Thorn, U. S. Surveyor, under special instructions, dated March 6, 1915, for Group 54, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Frank P. Frost
 U. S. Surveyor General of Arizona.

~~I certify that the foregoing transcript of the field notes of the above described surveys in Book "B," of Group 54, has been correctly copied from the original notes on file in this office.~~

U. S. Surveyor General of Arizona.