

3014

Book "K"

4-679

145  
MAR 4 - 1918  
①

BOOK 3014

# FIELD NOTES

OF THE SURVEY OF THE

WEST BOUNDARY AND SUBDIVISION LINES OF TOWNSHIP 11 SOUTH, RANGE 26 EAST,

AND

RESURVEY OF

2ND STANDARD PARALLEL SOUTH, THROUGH RANGE 26 AND PART OF RANGE 25 EAST,

SOUTH BOUNDARY OF TOWNSHIP 11 SOUTH, RANGE 26 EAST, AND

WEST BOUNDARY OF TOWNSHIP 11 SOUTH, RANGE 27 EAST,

Of the Gila and Salt River Base and Meridian,

In the State of Arizona,

EXECUTED BY

QUINTIN CAMPBELL, U. S. Transitman,

and

W. B. KIMMEL, U. S. Surveyor,

~~In the capacity of U. S. Surveyor~~, under instructions dated October 7, 1915,

issued by the United States Surveyor General to govern surveys included in

Group No. 63, which were approved by the Commissioner of the General Land

Office, October 28, 1915.

Survey Commenced April 23, 1917.

Survey Completed May 26, 1917.

Executed under Assignment  
Instructions dated Feb. 1, 1916.

3014

3014

(1A)

3014  
Book "K"

Group 63 - - Arizona.

ECCN 3014

### INDEX DIAGRAM.

		Township 11 South, Range 26 East.											
		6	5	4	4	3	3	3	3	2			
		2nd Standard Parallel South											
21	6	50	5	42	4	37	3	31	2	26	1	13 and 17	
	50		49		42		36		31		26		
20	7	49	8	41	9	36	10	31	11	25	12	12 and 16	
	48		48		41		35		30		25		
20	18	47	17	40	16	35	15	30	14	25	13	12 and 15	
	47		47		40		34		29		24		
19	19	46	20	39	21	34	22	29	23	24	24	12 and 14	
	45		45		39		33		28		23		
19	30	44	29	38	28	33	27	28	26	23	25	12 and 13	
	44		43		38		33		27		22		
18	31	43	32	37	33	32	34	27	35	22	36	11 and 13	
	6 and 11	6 and 10	7 and 10	7 and 9	7 and 8	7 and 8							

- Surveyed under this group--notes in this book (3014)
- Resurveyed under this group--notes in this book (3014)
- Surveyed under this group--notes in Book "L" (3015)
- Resurveyed under this group--notes in Book "L" (3015)
- Accepted surveys.
- Unsurveyed.

Chains

Work executed by Quintin Campbell, U. S. Transitman, and W. B. Kimmel, U. S. Surveyor, on dates shown on page of this book, using Young & Sons' light mountain transits Nos. 8499 and 8478 respectively, both instruments having Smith solar attachments. The horizontal limbs are provided with two double verniers placed opposite to each other, reading to single minutes of arc, which is also the least count of the verniers of the lat. and decl. arcs. Instrument No. 8499 was approved by the Assistant Supervisor of Surveys of District No 5, subject to satisfactory field tests, on Dec. 7, 1916, and instrument No. 8478 on May 21, 1917.

Field Test of Transit No. 8499, by Quintin Campbell.

Apr. 20, 1917.

At my camp near the cor. of secs. 17, 18, 19 and 20, in lat.  $32^{\circ}28'N.$ , long.  $109^{\circ}43'W.$ , I set up transit, examine level and collimation adjustments and correct errors.

At 4h 00m, p.m., l.m.t., I set off  $32^{\circ}28'$  on the lat. arc  $11^{\circ}36'N.$  on the decl. arc, and determine a meridian with the solar, marking a point in the same by driving a tack in a wooden stake firmly set in the ground 5 chs. N. of my station.

At 8h 25m, p.m., l.m.t., I observe Polaris in position and mark the line of sight upon the ground. I notice that Mizar is in the eastern sky.

Greenwich l.m.t. of U. C. of Polaris = 11h 37.4 m., a.m.  
U. C. of Polaris, l.m.t. of my station, 11h 36.1 m., a.m.  
Local mean time of observation, 8h 25m., p.m.  
Time elapsed since culmination, 8h 48.9 m.,  
which is the hour angle of Polaris, or argument for table.

Decl. of Polaris =  $88^{\circ}51'52.5''$ .  
Azimuth, from table, =  $0^{\circ}59'$  W. of N.

Apr. 21, 1917.

I turn off the azimuth of Polaris  $0^{\circ}59'$  to the E., and mark the meridian thus determined by a tack driven in the stake previously set by the P.M. solar.

At 8h 00m, a.m., l.m.t., I set off  $32^{\circ}28'$  on the lat. arc  $11^{\circ}49\frac{1}{2}'N.$  on the decl. arc, and determine a meridian with the solar.

The results of the a.m. and p.m. solars agree within less than one minute of arc with the true meridian established by the Polaris observation; from which it is concluded that the adjustments are satisfactory.

Test of Instrument No. 8478, by W. B. Kimmel.

May 22, 1917.

I set up transit at camp in sec. 9, near the  $\frac{1}{4}$  sec. cor. on W. bdy., in lat.  $32^{\circ}29'N.$ , long.  $109^{\circ}42'W.$ , examine the level and collimation adjustments and correct errors.

At 7h 52m p.m., l.m.t., I observe Polaris in position and mark the line of sight upon the ground. I notice that Mizar is in the eastern sky.

Greenwich l.m.t. of U. C. of Polaris = 9h 31.8m, a.m.  
U. C. of Polaris, l.m.t. of my station, 9h 30.5m, a.m.  
Local mean time of observation, 7h 52m, p.m.  
Time elapsed since culmination, 10h 21.5m,  
which is the hour angle of Polaris, or argument for table.

Declination of Polaris =  $88^{\circ}55'44''$ .  
Azimuth of Polaris, from table, =  $0^{\circ}33'$  W. of N.

May 23, 1917.

I turn off the azimuth of Polaris  $0^{\circ}33'$  to the E., and mark the meridian thus determined by a tack driven in a stake firmly set in the ground 5 chs. N. of my station.

At 8h 00m, l.m.t., I set off  $32^{\circ}29'$  on the lat. arc,  $20^{\circ}33\frac{1}{2}'N.$  on the decl. arc, and determine a meridian with the solar.

Resurvey of 2nd St. Par. S., through R. 26 and Part of R. 25 E.,  
 Resurvey of S. Bdy. of T. 11 S., R. 26 E.,  
 Resurvey of W. Bdy. of T. 11 S., R. 27 E., and  
 Survey of W. Bdy. and Subdivision of T. 11 S., R. 26 E.

2

Chains

Test of Instrument No. 8478, cont'd.

At 4h 00m, p.m., l.m.t., I set off 32°29' on the lat. arc, and 20°37½' N. on the decl. arc, and determine a meridian with the solar.

The results of the a.m. and p.m. solars agree with the true meridian determined by the Polaris observation by less than one minute of arc; from which I conclude that the adjustments are satisfactory.

At convenient times throughout the work both instruments were tested and the adjustments maintained, by comparison with meridians determined by observations on Polaris.

The magnetic bearing of the true meridian, at 8h 00m, a.m., is N.13°30'W. The angle thus determined gives for the magnetic declination 13°30'E.

Resurvey of 2nd St. Par. S., Through R. 26 E.

I begin at the standard cor. of Ts. 10 S., Rs. 26 and 27 E., which is a granite stone, 10x8x4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General; which I reestablish as follows:  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, beside original cor., marked on brass cap

SC  
 T10S  
 R26E | R27E  
 S36 | S31

1917  
 and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

12.50 Thence WEST, on tangent, S. of sec. 36, (according to instructions) over rolling land, through scattering undergrowth.

31.02 Road from "WA" Ranch to Bailey Well bears NE. and SW. Intersect the closing cor. of Ts. 11 S., Rs. 26 and 27 E., which is a wooden post, 4 ins. square, 3 ft. above ground, firmly set, marked and witnessed as described by the Surveyor General.

34.00 Wash, 100 lks. wide, course NE.

40.00 After diligent search in this vicinity, fail to find any trace of the standard ¼ sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished standard ¼ sec. cor., marked on brass cap

SC  
 ¼S36

1917  
 and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

69.70 Wash, 100 lks. wide, 2 ft. deep, course N.70°E.

80.00 After diligent search in this vicinity, fail to find any trace of the old standard cor. of secs. 35 and 36.

N. 1 link from the tangent,

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished standard cor. of secs. 35 and 36, marked on brass cap

S C  
 T10S | R26E  
 S35 | S36

1917

Chains

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Land, rolling.  
Soil, sand, gravel and rocky; 4th rate.  
No timber.  
Undergrowth, catclaw, mesquite.

20.00  
40.00

S.89°59'W., on the tangent, S. of sec. 35,  
over level land, through scattering underbrush.  
Wash, 30 lks. wide, course N.  
After diligent search in this vicinity, fail to find any trace of the standard 1/4 sec. cor.  
N., 1 lk. from the tangent,  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished standard 1/4 sec. cor., marked on brass cap

SC  
1/4 S35

1917

68.50  
80.00

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.  
Wash, 100 lks. wide, course NE.  
After diligent search in this vicinity, fail to find any trace of the standard cor. of secs. 34 and 35.  
N., 3 lks. from the tangent,  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished standard cor. of secs. 34 and 35, marked on brass cap

SC  
T10S | R26E  
S34 | S35

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Land, level desert.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

.75  
15.00  
40.00

N.89°59'W., on tangent, S. of sec. 34,  
over rolling land, through scattering underbrush.  
Wash, 50 lks. wide, course N.75°E.  
Wash, 75 lks. wide, course N.75°E.  
After diligent search in this vicinity, fail to find any trace of the standard 1/4 sec. cor.  
N., 4 lks. from the tangent,  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished standard 1/4 sec. cor., marked on brass cap

SC  
1/4 S34

1917

51.50  
66.90  
67.60  
68.00  
78.26

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.  
Small wash, course NE.  
Road from Willcox to Solomonsville, bears N. and S.  
Wash, 20 lks. wide, 2 ft. deep, course NE.  
Small, seep spring, 50 lks. S. of tangent. Inadequate for reservation as public watering place.  
Fall 15.13 chs. S. of the original standard cor. of secs.

Resurvey of 2nd St. Par. S., Through R. 26 E.

Chains

80.00 33 and 34, which is a stone, firmly set, marked and witnessed as described by the Surveyor General.  
I destroy this cor.  
N., 6 lks. from the tangent,  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished standard cor. of secs. 33 and 34, marked on brass cap

S C  
T10S | R26E  
S33 | S34

1917  
and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Land, rolling and hilly.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

27.25 S.89°58'W., on tangent, S. of sec. 33,  
38.55 over hilly land, through scattering underbrush, on top of low ridge bearing E. and W. Asc. gradually.  
Summit of ascent, bears NW. and SE.

40.00 Fall 14.22 chs. S. of the original standard ¼ sec. cor., identified by a dilapidated mound of stone without any marked stone. I destroy same.

N., 8 lks. from the tangent,  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished standard ¼ sec. cor., marked on brass cap

S C  
¼S33

1917  
and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

45.00 Wash, 30 lks. wide, course N.70°E.  
A well, 20 ft. deep, containing good water, bears N., 5 chs. dist. Corral at well. Asc.

54.75 Spur, bears N. 135 ft. above standard ¼ sec. cor. Desc. 55 ft.

60.55 Bed of ravine, course N. Asc. 50 ft.

69.60 Top of spur, bearing N. Desc. 35 ft.

74.60 Bed of ravine, 15 lks. wide, course N.80°E.

80.00 After diligent search in this vicinity, fail to find any trace of the old standard cor. of secs. 32 and 33.

N., 10 lks. from the tangent,  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished standard cor. of secs. 32 and 33, marked on brass cap

S C  
T10S | R26E  
S32 | S33

1917  
and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Land, hilly and mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, catclaw and mesquite.

S.89°58'W., on the tangent, S. of sec. 32,  
over mountainous land, through scattering underbrush.  
Asc. 175 ft.


Resurvey of 2nd St. Par. S. Through R. 26 E.

Chains	
11.40	Ridge, bears NW. and SE. Desc. 75 ft.
20.90	Wash, 20 lks. wide, course S. Asc. 150 ft.
36.56	Summit of ascent, on S. slope of spur. Desc. gradually.
39.58	Fall 14.43 chs. S. of the original standard $\frac{1}{4}$ sec. cor., identified by a mound of stone without marked stone, which I destroy.
40.00	N. 13 lks. from the tangent, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished standard $\frac{1}{4}$ sec. cor., marked on brass cap
	SC <u><math>\frac{1}{4}</math>S32</u>
	1917
	and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
48.70	Enter Valley, edge bears NW. and SE.
69.70	Wash, 30 lks. wide, 2 ft. deep, course S. Leave valley and asc.
79.00	Top of granite spur projecting S.
80.00	After diligent search in this vicinity, fail to find any trace of the original standard cor. of secs. 31 and 32. N. 16 lks. from the tangent, Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished standard cor. of secs. 31 and 32, marked on brass cap
	S C T10S   R26E <u>S31   S32</u>
	1917
	and raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
	Land, mountainous and rolling. Soil, rocky; 4th rate. No timber. Undergrowth, catclaw and mesquite.
	S. 89° 57' W., on the tangent, S. of sec. 31, over mountainous land, through scattering undergrowth. Asc. 100 ft.
11.80	Ridge, bears NE. and SW. Desc. 160 ft.
27.00	Asc. 35 ft.
33.50	Desc. 25 ft.
34.90	Bed of ravine, course N. Asc.
40.00	After diligent search in this vicinity, fail to find any trace of the original standard $\frac{1}{4}$ sec. cor. N. 19 $\frac{1}{2}$ lks. from the tangent, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished standard $\frac{1}{4}$ sec. cor., marked on brass cap
	SC <u><math>\frac{1}{4}</math>S31</u>
	1917
	and raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
47.93	Spur, projecting N., 155 ft. above bed of ravine. Desc. 190 ft.
58.52	Bed of ravine, course N. Asc. 95 ft.
60.75	Ridge, bears N. and S. Desc. 95 ft.
65.50	Wash, 50 lks. wide, course N. Asc. 160 ft.
74.95	Spur, bears N.
80.00	After diligent search in this vicinity, fail to find any trace of the original standard cor. of Ts. 10 S., Rs. 25 and 26 E. N. 23 $\frac{1}{2}$ lks. from the tangent,

Resurvey of 2nd St. Par. S., Through R. 26 E.

Chains

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished standard cor. of Ts. 10 S., Rs. 25 and 26 E., marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Land, mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, scrub oak and catclaw.

Resurvey of Part of 2nd St. Par. S., Through R. 25 E.

From the reestablished standard cor. of Ts. 10 S., Rs. 25 and 26 E., hereinbefore described;

WEST, according to instructions, on the parallel, on S. bdy. of sec. 36, over rough mountainous land, through underbrush. Desc. 20 ft.

- 3.10 Bed of ravine, course N. Asc. 35 ft.
- 4.50 Top of spur projecting N. Desc. 35 ft.
- 7.30 Bed of ravine, course N. Asc. 300 ft.
- 23.55 Top of ridge, bearing NE. and SW. Desc. 135 ft.
- 28.41 Intersect the closing cor. of Ts. 11 S., Rs. 25 and 26 E., established at the intersection of the W. bdy. of T. 11 S., R. 26 E. with the parallel, as hereinafter described.

Land, rough mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, cedar, scrub oak and catclaw.

Resurvey of S. Bdy. of T. 11 S., R. 26 W.

Retracement.

From the cor. of Ts. 11 and 12 S., Rs. 25 and 26 E., which is a malpais stone, 10x8x6 ins. above ground, marked and witnessed as described by the Surveyor General;

- 39.28 EAST, on a random line, along S. bdy. of sec. 31. Fall 18 lks. N. of the ¼ sec. cor., which is a malpais stone, 18x8x8 ins. above ground, marked and witnessed as described by the Surveyor General.
- 77.73 Fall 35 lks. N. of the cor. of secs. 5, 6, 31 and 32, which is a malpais stone, 18x8x5 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

EAST, from pt. 35 lks. N. of the cor. of secs. 5, 6, 31 and 32, on a random line, along S. bdy. of sec. 32.



Resurvey of S. Bdy. of T. 11 S., R. 26 W. (Retracement, continued.)

Chains

40.34 Fall 60 lks. N. of the  $\frac{1}{4}$  sec. cor., which is a stone, 12x10x8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

79.47 Fall 82 lks. N. of the cor. of secs. 4, 5, 32 and 33, which is a malpais stone, firmly set, marked and witnessed as described by the Surveyor General.

---

Continue same random EAST, along S. bdy. of sec. 33.

40.03 Fall 99 lks. N. of the  $\frac{1}{4}$  sec. cor., which is a malpais stone, 8x6x5 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

80.07 Fall 122 lks. N. of the cor. of secs. 3, 4, 33 and 34, which is a malpais stone, 10x8x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

---

Continue same random line EAST, along S. bdy. of sec. 34.

40.03 Fall 142 lks. N. of the  $\frac{1}{4}$  sec. cor., which is a malpais stone, 20x10x12 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

As the E. half of the Tp bdy. is not subject to rectification, the true return course for this half-mile is therefore N.89°43'W., 40.03 chs.

80.11 Fall 162 lks. N. of the cor. of secs. 2, 3, 34 and 35, which is a malpais stone, 10x8x5 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

The true return course and distance for this half-mile is therefore N.89°43'W., 40.08 chs.

---

Continue same random line EAST, along S. bdy. of sec. 35.

40.02 Fall 182 lks. N. of the  $\frac{1}{4}$  sec. cor., which is a malpais stone, 10x8x5 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

The true return course and distance for this half-mile is therefore N.89°43'W., 40.02 chs.

79.98 Fall 200 lks. N. of the cor. of secs. 1, 2, 35 and 36, which is a malpais stone, 10x8x4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

The true course and distance for the E. half of this mile is therefore N.89°45'W., 39.96 chs.

---

Continue same random line EAST, along S. bdy. of sec. 36.

40.97 Fall 218 lks. N. of the witness cor. to  $\frac{1}{4}$  sec. cor., which is a stone, 10x8x4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

The true return course and distance for this part of the mile is therefore N.89°45'W., 40.97 chs.



8 Resurvey of S. hdy. of T. 11 S., R. 26 W. (Retracement, continued.)


Chains

80.11 Fall 240 lks. N. of the cor. of Ts. 11 and 12 S., Rs. 26 and 27 E., which is a malpais stone, 12x10x8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

The true return course and distance for this part of the mile is therefore N.89°49'W., 39.14 chs.

Resurvey.

I begin at the cor. of Ts. 11 and 12 S., Rs. 26 and 27 E., hereinbefore described, which I reestablish as follows: Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground in place of the original cor., marked on brass cap



T12S

1917


and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Thence N.89°41'W., on a true line, bet. secs. 1 and 36, over rolling land, through scattering underbrush.

29.10 Wash, course SE.

39.14 The witness cor. to 1/4 sec. cor., hereinbefore described, which I reestablish as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground in place of the original cor., marked on brass cap



and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.

Thence N.89°45'W.

1.00 The true pt. for 1/4 sec. cor.


1.47 Wash, 100 lks. wide, 6 ft. deep, course S.70°E.

17.97 Wash, 15 lks. wide, 3 ft. deep, course N.

38.37 Small wash, 5 lks. wide, course NE.

40.97 The cor. of secs. 1, 2, 35 and 36, hereinbefore described, which I reestablish as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, in place of original cor., marked on brass cap



S2 | S1

T12S

1917

and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling and hilly.

Soil, rocky; 4th rate.

No timber.

Undergrowth, catclaw and mesquite.

N.89°45'W., bet. secs. 2 and 35,

over rolling land, through scattering underbrush.

5.40 Ridge, bears NW. and SE.

13.00 Wash, course SE.

Chains

25.00 Low ridge, bears NW. and SE.  
 38.00 Small wash, course S.  
 39.96 The  $\frac{1}{4}$  sec. cor., hereinbefore described, which I reestablish as follows:  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground in place of original cor., marked on brass cap

$\frac{1}{4}$  S35  
 S 2  
 1917

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, N. of cor.

-----  
 Thence N.89°43'W.  
 12.02 Ridge, bears N. and S.  
 25.02 Wash, 15 lks. wide, 3 ft. deep, course S.  
 35.02 Wash, 10 lks. wide, 3 ft. deep, course N.20°E.  
 40.02 The cor. of secs. 2, 3, 34 and 35, hereinbefore described, which I reestablish as follows:  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, in place of original cor., marked on brass cap

T11S	R26E
S34	S35
S3	S2
T12S	
1917	

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and hilly.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

---

N.89°43'W., bet. secs. 3, and 34,  
 over rolling land, through scattering underbrush.  
 12.61 Wash, 10 lks. wide, course SE.  
 37.11 Low ridge, bears NW. and SE.  
 40.08 The  $\frac{1}{4}$  sec. cor., hereinbefore described, which I reestablish as follows:  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground in place of original cor., marked on brass cap

$\frac{1}{4}$  S34  
 S 3  
 1917

and raise a mound of stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

42.11 Wash, 10 lks. wide, 2 ft. deep, course SE.  
 44.11 Wash, 15 lks. wide, 2 ft. deep, course SE.  
 80.11 The cor. of secs. 3, 4, 33 and 34, hereinbefore described, which I reestablish as follows:  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground in place of original cor., marked on brass cap


T11S	R26E
S33	S34
S4	S3
T12S	
1917	

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and hilly.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.


Chains

34.07 WEST, on true line, bet. secs. 4 and 33,  
 40.00 over rolling hilly land, through scattering underbrush.  
 Wash, 20 lks. wide, course SE.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for reestablished  $\frac{1}{4}$  sec. cor., marked on brass  
 cap



and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high,  
N. of cor.

45.07 Destroy old cor., hereinbefore described.  
 61.67 Ridge, bears SE and NW, 4 chs. wide. Desc. 35 ft.  
 67.07 Wash, 100 lks. wide, course S.  
 80.00 Wash, 100 lks. wide, course SE.  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
 ground, for reestablished cor. of secs. 4, 5, 32 and 33,  
 marked on brass cap




and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high,  
W. of cor.

Destroy old cor., hereinbefore described.


Land, rolling and hilly.  
 Soil, rocky; 4th rate.  
 No timber.  
 Underbrush, catchlaw and mesquite.

7.00 WEST, bet. secs. 32 and 5,  
 16.50 over rolling mountainous land, through scattering under-  
 16.90 growth. Asc. 46 ft.  
 38.50 Ridge, bears NW. and SE. Desc.  
 40.00 Road from Wilcox to Solomonsville, bears N. and S.  
 Wash, course S., 65 ft. below ridge. Asc.  
 Fence, bears N. and S.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for reestablished  $\frac{1}{4}$  sec. cor., marked on brass  
 cap



and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high,  
N. of cor.

40.50 Destroy old cor., hereinbefore described.  
 50.70 Bed of ravine, course NE. Continue ascent.  
 57.00 Summit of ascent, 440 ft. above wash, noted at 16.90 ch. pt.  
 65.00 Saddle in ridge bearing E. and W. Asc. 130 ft.  
 71.76 Desc. 80 ft.  
 75.90 Head of draw, course S. Asc. 40 ft.  
 80.00 Top of spur, projecting S. Desc. 45 ft.  
 Set an iron post, 3 ft. long, 3 ins. diam., 10 ins. in the  
 ground and 20 ins. in a mound of stone, for reestablished  
 cor. of secs. 5, 6, 31 and 32, marked on brass cap



and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high,  
W. of cor.


Destroy old cor., hereinbefore described.

Resurvey of S. Bdy. of T. 11 S., R. 26 E.



Chains

Land, rolling mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, catclaw and mesquite.

- WEST, bet. secs. 6 and 31,  
over rolling mountainous land, through scattering  
undergrowth. Desc. 85 ft.
- 9.54 Head of ravine, course S. Asc. 100 ft.
- 15.50 Top of ridge, bearing N. and S. Desc. 80 ft.
- 24.34 Bed of ravine, course S. Asc. 175 ft.
- 33.30 Top of ridge, bearing N. and S. Desc.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the  
ground, and 20 ins. in a mound of stone, for reestablished  
 $\frac{1}{4}$  sec. cor., marked on brass cap



- and raise a mound of stone, 3 ft. base, 3 ft. high,  
N. of cor.
- Destroy old cor., hereinbefore described.
- 44.54 Head of ravine, course S., 175 ft. below ridge. Desc.  
225 ft.
- 59.14 Bed of canyon, course S. Asc. 150 ft.
- 68.70 Top of ridge, bears N. and S. Desc. 140 ft.
- 77.27 (122 lks. S. of the old cor., hereinbefore described,  
which I destroy.)  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for reestablished cor. of Ts. 11 and 12 S.,  
Rs. 25 and 26 E., marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Land, rolling mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, mesquite.

Dependent Resurvey of W. Bdy. of T. 11 S., R. 27 E.

Retracement.

- From the reestablished cor. of Ts. 11 and 12 S., Rs. 26  
and 27 E., hereinbefore described;
- 39.78 NORTH, on a random line, bet. secs. 31 and 36.  
Fall 11 lks. E. of the  $\frac{1}{4}$  sec. cor., which is a malpais  
stone, 12x8x4 ins. above ground, firmly set, marked  
and witnessed as described by the Surveyor General.
- The true course and distance for this half-mile is there-  
fore N.0°09'W., 39.78 chs.
- 79.34 Intersect the cor. of secs. 25, 30, 31 and 36, which is  
a granite stone, 10x8x4 ins. above ground, firmly set,  
mkd. and witnessed as described by the Surveyor General.

Chains

Retracement, continued.

The true course for this half-mile is therefore N.0°09'E.  
Dist. is 39.56 chs.

39.69 NORTH, on random, bet. secs. 25 and 30.  
Fall 11 lks. W. of the  $\frac{1}{4}$  sec. cor., which is a stone,  
12x12x4 ins. above ground, firmly set, marked and wit-  
nessed as described by the Surveyor General.

The true course and distance for this half-mile is there-  
fore N.0°09'E., 39.69 chs.

79.61 Fall 11 lks. W. of the cor. of secs. 19, 24, 25 and 30,  
which is a granite stone, 6x6x5 ins. above ground,  
firmly set, marked and witnessed as described by the  
Surveyor General.

The true course and distance for this half-mile is there-  
fore NORTH, 39.92 chs.

39.86 Continue same random NORTH, bet. secs. 19 and 24.  
Fall 15 lks. W. of the  $\frac{1}{4}$  sec. cor., which is a granite stone,  
10x8x4 ins. above ground, firmly set, marked and wit-  
nessed as described by the Surveyor General.

The true course and distance for this half-mile is there-  
fore N.0°03'E., 39.86 chs.

79.78 Fall 15 lks. W. of the old cor. of secs. 13, 18, 19 and 24,  
which is a granite stone, 10x8x4 ins. above ground,  
firmly set, marked and witnessed as described by the  
Surveyor General.

The true course and distance for this half-mile is there-  
fore NORTH, 39.92 chs.

39.83 Continue same random NORTH, bet. secs. 13 and 18.  
Fall 17 lks. W. of the  $\frac{1}{4}$  sec. cor., which is a granite  
stone, 8x6x6 ins. above ground, firmly set, marked  
and witnessed as described by the Surveyor General.

The true course and distance for this half-mile is there-  
fore N.0°02'E., 39.83 chs.

79.45 Fall 25 lks. W. of the cor. of secs. 7, 12, 13 and 18,  
which is a wooden post, 3 ins. square, 3 ft. above  
ground, marked and witnessed as described by the  
Surveyor General.

The true course and distance for this half-mile is there-  
fore N.0°07'E., 39.62 chs.

40.00 Continue same random line NORTH, bet. secs. 7 and 12.  
After diligent search in this vicinity, fail to find any  
trace of the old  $\frac{1}{4}$  sec. cor.

79.58 Fall 28 lks. W. of the cor. of secs. 1, 6, 7 and 12,  
which is a granite stone, 8x6x4 ins. above ground,  
firmly set, marked and witnessed as described by the  
Surveyor General.

Chains

The true course and distance for this mile is therefore N.0°01'E., 79.58 chs.

40.00 Continue same random line NORTH, bet. secs. 1 and 6. After diligent search in this vicinity, fail to find any trace of the old  $\frac{1}{4}$  sec. cor.

79.72 Fall 34 lks. W. of the closing cor. of Ts. 11 S., Rs. 26 and 27 E., which is a wooden post, 4 ins. square, 3 ft. above ground, marked and witnessed as described by the Surveyor General.

The true course and distance for this mile is therefore N.0°03'E., 79.72 chs.


Resurvey.

Returning to the reestablished cor. of Ts. 11 and 12 S., Rs. 26 and 27 E., hereinbefore described;

2.00 Thence N.0°09'W., on true line, on W. bdy. of sec. 31, over rolling land, through scattering underbrush. Wash, 100 lks. wide, course SE.

26.50 Wash, 50 lks. wide, 2 ft. deep, course E.

39.78 The old  $\frac{1}{4}$  sec. cor., hereinbefore described, which I re-establish as follows:  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, marked on brass cap




1917  
and dig pits, 18x18x12 ins., 3 ft. dist., N. and S. of post.

4.82 Thence N.0°09'E. Wash, 50 lks. wide, course E.

13.82 Rocky hill, bears E. and W.

19.82 Wash, 20 lks. wide, 2 ft. deep, course E.

39.56 The cor. of secs. 25, 30, 31 and 36, hereinbefore described, which I reestablish as cor. of secs. 30 and 31 only, as follows:  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, marked on brass cap



1917  
and raise a mound of stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high, E. of cor.

Land, hilly and rolling.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, catclaw and mesquite.

.66 N.0°09'E., on W. bdy. of sec. 30, over rolling land, through scattering underbrush. (80.00 chs. N. of the cor. of Ts. 11 and 12 S., Rs. 26 and 27 E.,)

Chains

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 25 and 36, marked on brass cap

T11S  
S25  
-----  
S36  
R26E

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

5.20

Small wash, course E.

13.40

Wash, 200 lks. wide, 2 ft. deep, course E.

38.40

Wash, 10 lks. wide, 2 ft. deep, course E.

39.69

The old 1/4 sec. cor. bet. secs. 25 and 30, hereinbefore described, which I reestablish as 1/4 sec. cor. of sec. 30 only, as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, marked on brass cap

1/4 S30

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.

-----  
Thence NORTH.

.97

(40.00 chs. N. of the reestablished cor. of secs. 25 and 26,)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished 1/4 sec. cor. of sec. 25, marked on brass cap

1/4 S25

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

27.81

Road from Bowie to Solomonville bears NW. and SE.

39.92

Wash, 20 lks. wide, course E.

The old cor. of secs. 19, 24, 25 and 30, hereinbefore described, which I reestablish as cor. of secs. 19 and 30 only, as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, marked on brass cap

T11S  
S19  
-----  
S30  
R27E

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.

Land, rolling.

Soil, 3rd rate.

No timber.

Undergrowth, catclaw and mesquite.

1.05

N.0°03'E., on W. bdy. of sec. 19, over gently rolling land, through scattering underbrush. (80.00 chs. N. of the reestablished cor. of secs. 25 and 36)

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 24 and 25, marked on brass cap



Resurvey of W. Bdy. of T. 11 S., R. 27 E.

Chains

T11S
S24
S25
R26E

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

4.00 Wash, 30 lks. wide, 2 ft. deep, course E.

16.00 Wash, 30 lks. wide, 3 ft. deep, course E.

36.00 Wash, 3½ chs. wide, course E.

39.86 The old ¼ sec. cor., hereinbefore described, which I reestablish to pertain solely to sec. 19, as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, marked on brass cap

¼S19
------

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high, E. of cor.

Thence NORTH.

.44 Wash, 30 lks. wide, 2 ft. deep, course E.

1.19 (40.00 chs. N. of the reestablished cor. of secs. 24 and 25)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished ¼ sec. cor. of sec. 24, marked on brass cap

¼S24
------

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

39.64 Wash, 20 lks. wide; 2 ft. deep, course E.

39.92 The old cor. of secs. 13, 18, 19 and 24, hereinbefore described, which I reestablish as cor. of secs. 18 and 19 only, as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, marked on brass cap

T11S
S18
S19
R27E

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high, E. of cor.

Land, rolling.

Soil, gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

N.0°02'E., on the W. bdy. of sec. 18, over rolling land, through scattering underbrush.

1.27 (80.00 chs. N. of the reestablished cor. of secs. 24 and 25.)

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 13 and 24, marked on brass cap

T11S
S13
S24
R26E

1917

Chains

and raise a mound of stone, 2½ ft. base, 2 ft. high,  
W. of cor.

39.83 The old ¼ sec. cor., hereinbefore described, which I rees-  
tablish to pertain solely to sec. 18, as follows:  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, marked on brass cap

1/4 S18

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high,  
E. of cor.

Thence N.0°07'E.

1.44 (40.00 chs. N. of the reestablished cor. of secs. 13 and  
24)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for reestablished ¼ sec. cor. of sec. 13,  
marked on brass cap

1/4 S13

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high,  
W. of cor.

3.17 Desc. into wash.

8.17 Middle of wash, 10 chs. wide, course E.

20.58 Small spur, projecting E.

25.57 Wash, 30 lks. wide, 2 ft. deep, course E.

38.67 Wash, 100 lks. wide, 2 ft. deep, course E.

39.62 The old cor. of secs. 7, 12, 13 and 18, hereinbefore des-  
cribed, which I reestablish as cor. of secs. 7 and 18  
only, as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, marked on brass cap

T11S

S7

S18

R27E

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high,  
E. of cor.

Land, rolling.

Soil, gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

N.0°01'E., on W. bdy. of sec. 7,  
over rolling land, through scattering underbrush.

1.82 (80.00 chs. N. of the cor. of secs. 13 and 24,)

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for reestablished cor. of secs. 12 and 13,  
marked on brass cap

T11S

S12

S13

R26E

1917

and raise a mound of stone, 2½ ft. base, 2 ft. high,  
W. of cor.

17.00 Wash, 40 lks. wide, course E.

29.70 Desc. to wash.

33.50 Middle of wash, 50 lks. wide, course E.

39.79 (Proportional distance,)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for reestablished ¼ sec. cor. of sec. 7, marked

Chains

on brass cap

1/4 S7

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.

41.82 (40.00 chs. N. of the reestablished cor. of secs. 12 and 13,) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished 1/4 sec. cor. of sec. 12, marked on brass cap

1/4 S12

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

79.58 The old cor. of secs. 1, 6, 7 and 12, hereinbefore described, which I reestablish as cor. of secs. 6 and 7 only, as follows: Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, marked on brass cap

T11S

S6

S7

R27E

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.

Land, rolling.

Soil, gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

2.24 N.0°03'E., on W. bdy. of sec. 6, over rolling land, through scattering undergrowth. (80.00 chs. N. of the reestablished cor. of secs. 12 and 13,) Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 1 and 12, marked on brass cap

T11S

S1

S12

R26E

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

16.30 Wash, 2 ft. deep, 50 lks. wide, course E.

33.50 Wash, 100 lks. wide, 1 ft. deep, course E.

39.86 (Proportional distance,)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished 1/4 sec. cor. of sec. 6, marked on brass cap

1/4 S6

1917

and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.

42.24 (40.00 chs. N. of the reestablished cor. of secs. 1 and 12,) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished 1/4 sec. cor. of sec. 1, marked on brass cap

1/4 S1

1917

Chains

and raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.  
 53.25 Road, bears NE. and SW. from Bailey Wells to W.A. Ranch.  
 60.00 Wash, 30 lks. wide, 2 ft. deep, course E.  
 79.72 The old closing cor. of Ts. 11 S., Rs. 26 and 27 E., on 2nd St. Par. S., hereinbefore described, which I reestablish as follows:  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, marked on brass cap  
 T10S R26E  
 S36  
 S1 | S6  
 R26E | R27E  
 T11S  
 CC  
 1917  
 and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.  
 Land, rolling.  
 Soil, gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.


Survey of W. Bdy. of T. 11 S., R. 26 E.

From the reestablished cor. of Ts. 11 and 12 S., Rs. 25 and 26 E., hereinbefore described;  
 NORTH, bet. secs. 31 and 36,  
 over mountainous land, through scattering scrub cedar. Asc. 115 ft., along W. side of ridge.  
 16.00 Top of spur projecting W. Desc. 90 ft.  
 24.34 Bed of ravine, course W. Asc. 115 ft.  
 32.38 Top of spur projecting SW. Thence along W. side of ridge.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in a mound of stone, of solid rock, for ¼ sec. cor., marked on brass cap  
 ¼  
 S36 | S31  
 1917  
 from which  
 A cedar, 20 ins. diam., bears S.5°W., 110 lks. dist., marked ¼ S36 BT.  
 No other bearing tree available. Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.  
 52.00 Top of ridge, bears N.5°W. and S.5°E. Asc. gradually, along E. side of same.  
 64.27 Well and windmill bear E., 37 chs. dist.; well 40 ft. deep, containing good water.  
 72.00 Bed of ravine, course S.10°E. Asc. along E. side of same.  
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, marked on brass cap  
 T11S  
 R25E | R26E  
 S25 | S30  
 S36 | S31  
 1917  
 and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.


Chains

Land, mountainous.  
Soil, rocky; 4th rate.  
Timber, scattering scrub cedar.

- NORTH, bet. secs. 25 and 30,  
over mountainous land, through scattering cedar and  
juniper. Asc. 73 ft.
- 6.17 Top of ridge, bears NW. and SE. Desc. 220 ft.
- 15.50 Bed of ravine, course E. Asc. 193 ft.
- 24.10 Summit of ascent, on E. side of ridge. Thence along E.  
side of same.
- 33.00 Begin descent.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



- from which
- A cedar, 6 ins. diam., bears S.  $7\frac{1}{2}^{\circ}$  W., 129 lks. dist.,  
marked  $\frac{1}{4}$  S25 BT.
- A juniper, 12 ins. diam., bears N.  $29^{\circ} 20'$  E., 160 lks. dist.,  
marked  $\frac{1}{4}$  S30 BT.
- 41.97 Bed of ravine, course E., 190 ft. below beginning of descent.  
Asc. 150 ft.
- 49.15 Spur, bears E. Desc. 100 ft.
- 60.12 Small wash, course E. Asc.
- 61.07 Fence, bears E. and W.
- 63.33 Spur, projecting E., 50 ft. above wash. Desc. 57 ft.
- 69.20 Wash, 75 lks. wide, 3 ft. deep, course S.  $15^{\circ}$  E.
- 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for cor. of secs. 19, 24, 25 and 30, marked on  
brass cap



- 1917
- and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,  
W. of cor.

Land, mountainous, and rolling.  
Soil, rocky; 4th rate.  
Timber, cedar and juniper.

- NORTH, bet. secs. 19 and 24,  
over rolling land, through scattering timber and dense  
underbrush.
- 18.70 Head of ravine, course E.
- 34.90 Middle of ravine, 45 ft. deep, course E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



- and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.
- 44.00 Middle of ravine, 45 ft. deep, course E.
- 47.60 Wash, 50 lks. wide, course SE.
- 64.80 Wash, 40 lks. wide, course E. Ascend.
- 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the

Chains

ground, for cor. of secs. 13, 18, 19 and 24, marked on brass cap

T11S	
R25E	R26E
S13	S18
S24	S19

1917

and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling and hilly.  
Soil, rocky; 4th rate.  
Timber, cedar.  
Undergrowth, oak brush, manzanita and soap-weed.

NORTH, bet. secs. 13 and 18,  
over mountainous land, through scattering timber and underbrush. Asc. 90 ft.

20.10 Top of ridge, bears E. and W. Desc. 90 ft.

25.32 Bed of ravine, course E. Asc. 50 ft.

28.30 Ridge, bears E. and W. Desc.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4	
S13	S18

1917

from which

A cedar, 10 ins. diam., bears N. 33 1/2° W., 27 lks. dist., marked 1/4 S13 BT.

No other bearing tree available. Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

43.44 Wash, 20 lks. wide, course NE., 137 ft. below ridge. Enter rolling land.

47.47 Wash, 2 chs. wide, course E.

53.97 Road, bears E. and W.

58.40 Wash, 75 lks. wide, 4 ft. deep, course E.

61.60 Road, bears E. and W.

69.70 Wash, 30 lks. wide, course SE.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, marked on brass cap

T11S	
R25E	R26E
S12	S 7
S13	S18

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous, and rolling.  
Soil, rocky; 4th rate.  
Timber, scattering cedar.  
Undergrowth, catclaw and mesquite.


NORTH, bet. secs. 7 and 12,  
over mountainous land, through scattering timber and undergrowth. Asc. 15 ft. to top of ridge.

1.40 Wash, 50 lks. wide, course S. 10° E. Asc. 475 ft.


8.50 (On top of ridge, bearing E. and W.,)  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

Survey of W. bdy. of T. 11 S., R. 26 E.

Chains




from which  
 A cedar, 14 ins. diam., bears N.57 $\frac{1}{2}$ °W., 230 lks. dist., marked  $\frac{1}{4}$  S12 BT.  
 A cedar, 12 ins. diam., bears N.27 $\frac{1}{2}$ °W., 145 lks. dist., marked  $\frac{1}{4}$  S7 BT.  
 Desc. 330 ft.  
 59.62 Wash, 100 lks. wide, 2 ft. deep, course E. Asc. 160 ft.  
 77.58 Summit of ascent. Desc. 60 ft.  
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, marked on brass cap



from which  
 A cedar, 8 ins. diam., bears S.58°W., 50 lks. dist., marked T11S R25E S12 BT.  
 A cedar, 24 ins. diam., bears N.45°E., 280 lks. dist., marked T11S R26E S6 BT.  
 No other bearing tree available. Raised a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rough mountainous.  
 Soil, rocky; 4th rate.  
 Timber, cedar.  
 Undergrowth, catclaw and oak brush.


NORTH, bet. secs. 1 and 6,  
 over mountainous land, through scattering timber and underbrush. Desc. 50 ft.  
 2.00 Bed of ravine, course E. Asc.  
 7.00 Top of spur projecting E. Desc. 30 ft.  
 9.50 Bed of ravine, course SE. Asc. 80 ft.  
 14.70 Top of spur, projecting SE.  
 17.70 Desc. 110 ft.  
 28.90 Bed of canyon, course SE. Asc. 300 ft.  
 36.20 Top of ridge, bears E. and W. Desc.  
 38.25 Fence, bears E. and W.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and 18 ins. in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap



from which  
 A cedar, 14 ins. diam., bears S.55 $\frac{1}{4}$ °W., 176 lks. dist., marked  $\frac{1}{4}$  S1 BT.  
 A cedar, 12 ins. diam., bears S.67 $\frac{1}{2}$ °E., 27 lks. dist., marked  $\frac{1}{4}$  S6 BT.  
 44.46 Ravine, course NE., 250 ft. below ridge. Desc. along W. side of same, 144 ft.  
 58.77 Bed of ravine, course E. Asc. 160 ft.  
 69.27 Top of ridge, bears NE. and SW. Desc. 260 ft.  
 75.93 Intersect 2nd St. Par. S., 28.41 chs. W. of the reestablished cor. of Ts. 10 S., Rs. 25 and 26 E., hereinbefore described.  
 At point of intersection  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the

Chains

ground, for closing cor. of Ts. 11 S., Rs. 25 and 26 E., marked on brass cap



and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, S. of cor.


Land, mountainous.  
Soil, rocky; 4th rate.  
Timber, cedar.  
Undergrowth, oak and catclaw.

Subdivision of T. 11 S., R. 26 E.

From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp. reestablished as hereinbefore described;

N.0°01'W., bet. secs. 35 and 36, over rolling land, through scattering underbrush.


- 14.50 Wash, 20 lks. wide, 2 ft. deep, course SE.
- 30.30 Wash, 50 lks. wide, 3 ft. deep, course E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



from which  
An oak, 18 ins. diam., bears N.2°10'W., 445 lks. dist., marked 1/4 S35 BT.

No other bearing tree available. Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

- 44.00 Wash, 100 lks. wide, course SE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on brass cap



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling desert.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, scrub mesquite, and catclaw.

- 40.00 EAST, on a random line, bet. secs. 25 and 36.
- 80.04 Set temp. 1/2 sec. cor.
- 80.04 Intersect the E. bdy. of Tp. 40 lks. N. of the cor. of secs. 25 and 36, reestablished as hereinbefore described.

Thence N.89°43'W., on a true line, bet. secs. 25 and 36,



Chains

40.02 over rolling desert, through scattering underbrush.  
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed-rock and 14 ins. in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S25  
S36  
1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

50.00 Enter wash, 30 lks. wide, course NE. Thence along bed of same.

73.00 Leave wash, comes from NW., course E.

80.04 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

2.20 N.0°01'W., bet. secs. 25 and 26,  
over rolling desert, through scattering underbrush.  
Wash, 20 lks. wide, 2 ft. deep, course SE.; heads 10 chs. West.

27.50 Wash, 30 lks. wide, 6 ft. deep, course E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S26 | S25  
1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

49.70 Wash, 40 lks. wide, 2 ft. deep, course SE.

62.30 Wash, 20 lks. wide, 2 ft. deep, course E.

75.00 Wash, 75 lks. wide, 2 ft. deep, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to rock and 10 ins. in a mound of stone, for cor. of secs. 23, 24, 25 and 26, marked on brass cap

T11S | R26E  
S23 | S24  
S26 | S25

1917  
and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.  
Soil, rocky and sandy; gravelly, 4th rate.  
No timber.  
Undergrowth, scrub mesquite and catclaw.

40.00 S.89°43'E., on a random line, bet. secs. 24 and 25.  
Set temp.  $\frac{1}{4}$  sec. cor.

80.08 Intersect E. bdy. of Tp. 2 lks. N. of the cor. of secs. 24 and 25, reestablished as hereinbefore described.

18.20 Thence N.89°42'W., on a true line, bet. secs. 24 and 25,  
over rolling desert, through scattering underbrush.

20.88 Wash, 40 lks. wide, 3 ft. deep, course NE.

Road from Bowie to Solomonsville, bears NW. and SE.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap


$\frac{1}{4}$  S24  
S25  
1917

Chains


and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.  
47.30 Wash, 30 lks. wide, 4 ft. deep, course SE.  
80.08 The cor. of secs. 23, 24, 25 and 26.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, scrub mesquite and catclaw.

N.0°01'W., bet. secs. 23 and 24,  
over rolling desert, through scattering undergrowth.  
11.25 Wash, 10 lks. wide, 3 ft. deep, course E.; heads 10 chs. W.  
27.80 Wash, 30 lks. wide, 2 ft. deep, course E.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the  
ground to rock and 12 ins. in a mound of stone, for  
 $\frac{1}{4}$  sec. cor., marked on brass cap



1917  
and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.  
44.50 Wash, 100 lks. wide, 6 ft. deep, course E.  
50.00 Round, rocky hill, 100 ft. high, bears W., 10 chs. dist.  
65.00 Wash, 40 lks. wide, 4 ft. deep, course E.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 13, 14, 23 and 24, marked on  
brass cap




1917  
and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, scrub mesquite and catclaw.

S.89°42'E., on a random line, bet. secs. 13 and 24.  
40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
80.04 Intersect E. Bdy. of Tp. 2 lks. S. of the reestablished cor.  
of secs. 13 and 24, hereinbefore described.

Thence N.89°43'W., on a true line, bet. secs. 13 and 24,  
over rolling desert, through scattering undergrowth.  
32.00 Enter sandy wash, course SE., 30 lks. wide and 5 ft. deep.  
Thence along same.

38.00 Leave wash, comes from NW.  
40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.  
60.04 Prospect hole, 6x6 ft., 20 ft. deep, bears N., 6 chs. dist.  
Copper and vanadium outcroppings.  
62.54 Same wash, 30 lks. wide, 2 ft. deep, course NE.  
62.55 Road from Solomonsville, to Bowie bears NW. and SE.


Chains

63.24 Prospect hole, 6x6 ft., 30 ft. deep, bears N., 4 chs. dist. Copper and vanadium outcroppings. Hole contains about 15 ft. of water.


80.04 The cor. of secs. 13, 14, 23 and 24.

Land, rolling and level.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

N.0°01'W., bet. secs. 13 and 14,  
over rolling desert, through scattering underbrush.  
14.00 Wash, 20 lks. wide, 4 ft. deep, course E.  
20.80 Road from Solomonsville to Bowie bears NW. and SE.  
26.00 Wash, 40 lks. wide, 2 ft. deep, course E.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



80.00 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked on brass cap




1917  
and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.  
Soil, rocky, sandy and gravelly, with some hardpan; 4th rate.  
No timber.  
Undergrowth, scrub mesquite and catclaw.

40.00 S.89°43'E., on a random line, bet. secs. 12 and 13,  
Set temp. 1/4 sec. cor.  
80.00 Intersect E. bdy. of Tp. 8 lks. S. of the reestablished cor. of secs. 12 and 13, hereinbefore described.

40.00 Thence N.89°46'W., on a true line, bet. secs. 12 and 13, over rolling desert, through scattering underbrush.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



80.00 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.  
The cor. of secs. 11, 12, 13 and 14.

Land, level and rolling.  
Soil, rocky, sandy and gravelly, with some hardpan; 4th rate.  
No timber.  
Undergrowth, scrub mesquite and catclaw.

Chains

N.0°01'W., bet. secs. 11 and 12,  
 over rolling desert, through scattering undergrowth.  
 5.20 Wash, 75 lks. wide, 2 ft. deep, course E.  
 34.80 Wash, 25 lks. wide, 2 ft. deep, course E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S11 | S12

1917  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

64.80 Wash, 30 lks. wide, 4 ft. deep, course E.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 1, 2, 11 and 12; marked on  
 brass cap

T11S | R26E  
 S2 | S1  
 S11 | S12

1917  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

Land, rolling.  
 Soil, rocky, sandy and gravelly, with hardpan; 4th rate.  
 No timber.  
 Undergrowth, scrub mesquite and catclaw.

S.89°46'E., on a random line, bet. secs. 1 and 12.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.94 Intersect E. bdy. of Tp. 7 lks. N. of the reestablished  
 cor. of secs. 1 and 12, hereinbefore described.

Thence N.89°43'W., on a true line, bet. secs. 1 and 12,  
 over rolling desert, through scattering underbrush.  
 24.40 Wash, 5 chs. wide, 4 ft. deep, course NE.  
 39.97 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 1  
 $\frac{1}{4}$  ———  
 S12  
 1917  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.

79.94 The cor. of secs. 1, 2, 11 and 12.

Land, rolling desert.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

N.0°01'W., bet. secs. 1 and 2,  
 over rolling land, through scattering underbrush.  
 6.50 Wash, 150 lks. wide, 2 ft. deep, course E.  
 16.00 Road bears NE. and SW. from Bailey Wells to W.A. ranch.  
 22.20 Wash, 20 lks. wide, 2 ft. deep, course E.  
 31.50 Wash, 100 lks. wide, course E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S2 | S1  
 1917

Chains

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

55.60  
76.92

Wash, 30 lks. wide, 2 ft. deep, course E.  
Intersect N. bdy. of Tp., (2nd St. Par. S.,) 9.03 chs. E. of the reestablished standard 1/4 sec. cor. on S. bdy. of sec. 35, hereinbefore described.

At point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 1 and 2, marked on brass cap

T10S R11E  
S35  
-----  
S2 | S1  
T11S | R26E  
C C  
1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

Land, rolling.

Soil, gravelly and rocky; 2nd and 3rd rate.

No timber.

Undergrowth, mesquite and catclaw.

From the reestablished cor. of secs. 2, 3, 34 and 35, on S. bdy. of Tp., hereinbefore described;

N.0°01'W., bet. secs. 34 and 35, over rolling and hilly desert, through scattering undergrowth.

21.50  
40.00

Wash, 50 lks. wide, 3 ft. deep, course E.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4  
S34 | S35  
1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

40.20

Wash, 40 lks. wide, 2 ft. deep, course E. Thence over rocky, hilly land, bears E. and W. Asc. 120 ft.

54.10

Top of ridge, bears E. and W. Desc. 90 ft.

63.00

Wash, 20 lks. wide, 4 ft. deep, course SE. Asc. 50 ft.

80.00

Top of ridge, bears NW. and SE.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to rock and 12 ins. in a mound of stone, for cor. of secs. 22, 23, 26 and 27, marked on brass cap

T11S | R26E  
S27 | S26  
-----  
S34 | S35

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling on S. and hilly on N. half of mile.

Soil, rocky, sandy and gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

40.00  
80.04

EAST, on a random line, bet. secs. 26 and 35.

Set temp. 1/4 sec. cor.

Intersect N. and S. line 44 lks. N. of the cor. of secs. 25, 26, 35 and 36.

Chains

Thence N.89°41'W., on a true line, bet. secs. 26 and 35,  
 over rolling desert, through scattering undergrowth.  
 18.74 Wash, 20 lks. wide, 2 ft. deep, course SE.  
 34.00 Wash, 30 lks. wide, 2 ft. deep, course SE.  
 40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S26
$\frac{1}{4}$
S35
1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.  
 67.00 Wash, 75 lks. wide, 2 ft. deep, course SE. Thence over  
 hilly land, bears NW. and SE. Asc. 80 ft.  
 80.04 The cor. of secs. 26, 27, 34 and 35.

Land, E. 67 chs. rolling and remainder hilly.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

N.0°01'W., bet. secs. 26 and 27,  
 over hilly desert, through scattering undergrowth.  
 Desc. 60 ft.  
 10.80 Wash, 50 lks. wide, 2 ft. deep, course SE. Asc. 60 ft.  
 25.00 Low ridge, bears E. and W. Desc. 60 ft.  
 30.00 Wash, 20 lks. wide, 2 ft. deep, course E.  
 37.30 Wash, 25 lks. wide, 2 ft. deep, course E. Asc. 20 ft.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the  
 ground to rock and 8 ins. in a mound of stone, for  $\frac{1}{4}$   
 sec. cor., marked on brass cap

$\frac{1}{4}$
S27   S26
1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Asc. 85 ft.  
 46.40 Ridge, bears E. and W. Desc. 90 ft.  
 54.22 Wash, 30 lks. wide, 4 ft. deep, course E. Asc. 150 ft.  
 66.50 Ridge, bears E. and W. Desc. 60 ft.  
 71.40 Wash, 20 lks. wide, 3 ft. deep, course E. Asc. 30 ft.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the  
 ground to rock and 12 ins. in a mound of stone, for  
 cor. of secs. 22, 23, 26 and 27, marked on brass cap

T11S   R26E
S22   S23
S27   S26
1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

Land, hilly.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

S.89°41'E., on a random line, bet. secs. 23 and 26.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.10 Intersect N. and S. line 2 lks. S. of the cor. of secs.  
 23, 24, 25 and 26.

Thence N.89°42'W., on a true line, bet. secs. 23 and 26,  
 over rolling land, through scattering undergrowth.

Chains

15.60 Wash, 20 lks. wide, 1 ft. deep, course SE.  
40.05 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, marked on brass cap

$\frac{1}{4}$  S23  
S26  
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

71.00 Wash, 20 lks. wide, 4 ft. deep, course SE. Thence over hilly land, bears NW. and SE. Asc. 100 ft.

80.10 The cor. of secs. 22, 23, 26 and 27.

Land, E. 71 chs. rolling and W. 9.10 chs. hilly.

Soil, rocky, sandy and gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

N.0°01'W., bet. secs. 22 and 23, over hilly desert land, through scattering undergrowth. Desc. 80 ft.

6.90 Rocky ravine, 50 lks. wide, course SE. Asc. 160 ft.

13.60 Top of ridge, bears E. and W. Desc. 140 ft.

18.50 Wash, 20 lks. wide, 3 ft. deep, course E. Asc. 100 ft.

38.00 Top of rocky hill, bears E. and W. Desc. 30 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to rock and 12 ins. in a mound of stone, for ¼ sec. cor., marked on brass cap

$\frac{1}{4}$   
S22 | S23

1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Desc. 50 ft., over rolling land.

49.00 Wash, 150 lks. wide, course E. Thence over rolling land.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, marked on brass cap

T11S | R26E  
S15 | S14  
S22 | S23

1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, hilly on S. and rolling on N. half of line.

Soil, rocky, sandy and gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

40.00 S.89°42'E., on a random line, bet. secs. 14 and 23.

80.08 Set temp. ¼ sec. cor.

Intersect N. and S. line 13 lks. S. of the cor. of secs. 13, 14, 23 and 24.

Thence N.89°48'W., on a true line, bet. secs. 14 and 23, over rolling desert land, through scattering undergrowth.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

S14  
 $\frac{1}{4}$  S23  
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high,

Chains

N. of cor.  
80.08 The cor. of secs. 14, 15, 22 and 23.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

10.00 N.0°01'W., bet. secs. 14 and 15,  
over rolling desert land, through scattering undergrowth.  
Wash, 20 lks. wide, 2 ft. deep, course E.  
25.75 Wash, 125 lks. wide, 3 ft. deep, course E.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S15	S14
-----	-----

1917

and dig pits, 18x18x12 ins., 3 ft. dist., N. and S.  
of cor.

55.00 Wash, 100 lks. wide, 4 ft. deep, course E.

77.50 Wash, 10 lks. wide, 1 ft. deep, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 10, 11, 14 and 15, marked on  
brass cap

T11S	R26E
S10	S11

S15	S14
-----	-----

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

40.00 S.89°48'E., on a random line, bet. secs. 11 and 14.  
Set temp.  $\frac{1}{4}$  sec. cor.

80.10 Intersect N. and S. line 5 lks. S. of the cor. of secs.  
11, 12, 13 and 14.

Thence N.89°50'W., on a true line, bet. secs. 11 and 14,  
over rolling desert land, through scattering under-  
growth.

20.10 Wash, 40 lks. wide, 2 ft. deep, course NE.

40.05 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S11
-----

 $\frac{1}{4}$ 

S14
-----

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.

50.00 Enter wash, 20 lks. wide 2 ft. deep, course N.80°E.  
Thence along same.

69.00 Leave wash, comes from SW.

69.60 Road from Solomonsville to Bowie, bears NW. and SE.

80.10 The cor. of secs. 10, 11, 14 and 15.

Land, rolling desert.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, catclaw and mesquite.



Subdivision of T. 11 S., R. 26 E.


Chains

N.0°01'W., bet. secs.10 and 11,  
 over rolling desert land, through scattering undergrowth.  
 7.90 Road from Solomonsville to Bowie bears N. and SE.  
 12.50 Wash, 50 lks. wide, 4 ft. deep, course E.  
 32.50 Wash, 30 lks. wide, 5 ft. deep, course E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



1917  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

49.00 Wash, 75 lks. wide, 1 ft. deep, course E.  
 60.70 Road from Bailey Well to "W.A." Ranch bears E. and W.  
 76.00 Wash, 30 lks. wide, 3 ft. deep, course E.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 2, 3, 10 and 11, marked on  
 brass cap




1917  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

Land, rolling desert.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

S.89°50'E., on a random line, bet. secs. 2 and 11.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.08 Intersect N. and S. line 2 lks. S. of the cor. of secs.  
 1, 2, 11 and 12.

Thence N.89°51'W., on a true line, bet. secs.2 and 11,  
 over rolling desert land, through scattering undergrowth.  
 15.10 Wash, 100 lks. wide, 3 ft. deep, course NE.  
 40.04 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
 ground to rock and 14 ins. in a mound of stone, for  $\frac{1}{4}$   
 sec. cor., marked on brass cap



1917  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.

42.80 Road from Bailey Well to "W.A." Ranch bears NE. and SW.  
 52.58 Wash, 40 lks. wide, 1 ft. deep, course NE.  
 80.08 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

N.0°01'W., bet. secs. 2 and 3,  
 over level land, through scattering undergrowth.  
 19.30 Wash, 100 lks. wide, 3 ft. deep, course E.  
 31.00 Wash, 30 lks. wide, 2 ft. deep, course E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Chains

1/4  
S3 | S2

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

67.20  
76.59

Wash, 20 lks. wide, 3 ft. deep, course E.  
Intersect N. bdy. of Tp., (2nd St. Par. S.,) 8.97 chs. E. of the reestablished standard 1/4 sec. cor. of S. bdy. of sec. 34, hereinbefore described.

At point of intersection,  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 2 and 3, marked on brass cap

T10S R26E  
S34  
-----  
S3 | S2  
T11S | R26E  
C C

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

Land, level and rolling.  
Soil, 2nd and 3rd rate.  
No timber.  
Undergrowth, mesquite and catclaw.

From the reestablished cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp., hereinbefore described;

N.0°02'W., bet. secs. 33 and 34, over hilly desert land, through scattering undergrowth. Desc. 60 ft., over N. slope.

7.50  
19.80  
31.00  
40.00

Wash, 20 lks. wide, 2 ft. deep, course E. Asc. 100 ft.  
Top of ridge, bears NW. and SE. Desc. 70 ft.  
Wash, 10 lks. wide, 2 ft. deep, course E.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4  
S33 | S34

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

42.00  
52.90  
68.80  
80.00

Wash, 20 lks. wide, 1 ft. deep, course SE. Asc. 90 ft.  
Top of hilly ridge, bears NW. and SE. Desc. 90 ft.  
Wash, 20 lks. wide, 2 ft. deep, course SE. Asc. 50 ft.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on brass cap

T11S | R26E  
S28 | S27  
-----  
S33 | S34

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, hilly.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, catclaw and mesquite.

Subdivision of T. 11 S., R. 26 E.

Chains

S.89°43'E., on a random line, bet. secs. 27 and 34.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.12 Intersect N. and S. line 5 lks. N. of the cor. of secs. 26, 27, 34 and 35.

Thence N.89°41'W., on a true line, bet. secs. 27 and 34, over hilly desert land, through scattering undergrowth. Asc. 40 ft., along summit of hilly ridge, bearing E. and W.

27.00 Summit of ascent; desc. 55 ft., over NW. slope.  
 40.06 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S27  
 S34  
 1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

80.12 Thence over rolling desert land.  
 The cor. of secs. 27, 28, 33 and 34.

Land, hilly on E. and rolling on W. half of line.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

---

N.0°02'W., bet. secs. 27 and 28, over hilly desert land, through scattering undergrowth.  
 9.75 Wash, 30 lks. wide, 2 ft. deep, course E. Asc. 165 ft.  
 30.30 Top of rocky ridge, bearing E. and W. Desc. 150 ft.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S28 | S27  
 1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

48.00 Wash, 30 lks. wide, 2 ft. deep, course SE.  
 50.00 Asc. 240 ft., over rocky S. slope.  
 62.90 Top of rocky ridge bears E. and W. Desc. 220 ft.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to rock and 16 ins. in a mound of stone, for cor. of secs. 21, 22, 27 and 28, marked on brass cap

T11S | R26E  
S21 | S22  
 S28 | S27  
 1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, hilly.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.


---

S.89°41'E., on a random line, bet. secs. 22 and 27.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.20 Intersect N. and S. line 8 lks. S. of the cor. of secs. 22, 23, 26 and 27.

Thence N.89°44'W., on a true line, bet. secs. 22 and 27, Over hilly desert land, through scattering undergrowth. Asc. 70 ft.

Chains

5.00 Summit of ascent, on N. side of hill. Thence along top of hilly ridge, bearing E. and W.  
 35.00 Desc. along N. slope of hilly ridge, 40 ft.  
 40.10 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.


Desc. 30 ft.

45.70 Ft. of slope of hill, bears NE. and SW. Thence over rolling desert land.  
 70.95 Wash, 30 lks. wide, 3 ft. deep, course SE. Asc. 20 ft.  
 80.20 The cor. of secs. 21, 22, 27 and 28.

Land, hilly on E. 45.70 chs. of line and rolling on remainder. Soil, rocky, sandy and gravelly; 4th rate. No timber. Undergrowth, scrub mesquite and catclaw.


N.0°02'W., bet. secs. 21 and 22, over rolling desert land, through scattering undergrowth.

3.40 Wash, 10 lks. wide, 10 ft. deep, course SE.  
 21.10 Wash, 6 lks. wide, 3 ft. deep, course E.  
 25.50 Wash, 20 lks. wide, 1 ft. deep, course SE.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

45.00 Wash, 10 lks. wide, 2 ft. deep, course SE.  
 76.10 Wash, 100 lks. wide, 2 ft. deep, course E.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on brass cap



1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.


Land, rolling. Soil, rocky, sandy and gravelly; 4th rate. No timber. Undergrowth, scrub mesquite and catclaw.

40.00 S.89°44'E., on a random line, bet. secs. 15 and 22. Set temp.  $\frac{1}{4}$  sec. cor.  
 80.26 Intersect N. and S. line 7 lks. N. of the cor. of secs. 14, 15, 22 and 23.

Thence N.89°41'W., on a true line, bet. secs. 15 and 22, over level desert land, through scattering scrub underbrush.

40.13 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Chains




and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

80.26 The cor. of secs. 15, 16, 21 and 22.

Land, level desert.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, scrub mesquite and catclaw.


N.0°02'W., bet. secs. 15 and 16,  
over rolling desert land, through scattering undergrowth.

- 20.25 Wash, 20 lks. wide, 1 ft. deep, course E.
- 25.00 Wash, 50 lks. wide, 2 ft. deep, course E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

- 52.80 Wash, 20 lks. wide, 2 ft. deep, course E.
- 70.00 Wash, 10 lks. wide, 1 ft. deep, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap




and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

- 40.00 S.89°41'E., on a random line bet. secs. 10 and 15.
- 80.26 Set temp. ¼ sec. cor.
- 80.26 Intersect N. and S. line at the cor. of secs. 10, 11, 14 and 15.

Thence N.89°41'W., on a true line, bet. secs. 10 and 15,  
over rolling desert land, through scattering undergrowth.

- 40.13 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 55.26 Wash, 20 lks. wide, 2 ft. deep, course NE.
- 80.26 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber. Undergrowth, mesquite and catclaw.

Chains

N.0°02'W., bet. secs. 9 and 10,  
over rolling and level desert land, through scattering  
undergrowth.

1.50 Wash, 10 lks. wide, 1 ft. deep, course E.  
27.20 Wash, 10 lks. wide, 1 ft. deep, course E.  
37.70 Road from Willcox to Solomonsville, brs. NE. and SW.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} \\ \hline S\ 9 \quad | \quad S10 \end{array}$$

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

44.25 Wash, 25 lks. wide, 2 ft. deep, course NE.  
57.60 Road from Bailey Well to "W.A." Ranch bears E. and W.  
62.20 Wash, 50 lks. wide, 2 ft. deep, course E.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 3, 4, 9 and 10, marked on  
brass cap

$$\begin{array}{c} T11\ S \quad | \quad R26E \\ \hline S4 \quad | \quad S3 \\ \hline S\ 9 \quad | \quad S10 \end{array}$$

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Land, level and rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

40.00 S.89°41'E., on a random line, bet. secs. 3 and 10.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.20 Intersect N. and S. line 2 lks. N. of the cor. of secs.  
2, 3, 10 and 11.

Thence N.89°40'W., on a true line, bet. secs. 3 and 10,  
over level desert land, through scattering undergrowth.  
30.20 Wash, 80 lks. wide, 2 ft. deep, course NE.  
40.10 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$$\begin{array}{c} S\ 3 \\ \hline \frac{1}{4} \\ \hline S10 \end{array}$$

1917

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.

42.80 Wash, 30 lks. wide, 2 ft. deep, course S.70°E.  
62.60 Road from Willcox to Solomonsville, brs. NE and SW.  
80.20 The cor. of secs. 3, 4, 9 and 10.

Land, level.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

7.50 N.0°02'W., bet. secs. 3 and 4,  
over level land, through scattering undergrowth.  
40.00 Wash, 75 lks. wide, 3 ft. deep, course E.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Chains




1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

- 47.05 Enter hills.
- 60.30 Top of spur projecting SE. Thence along E. slope.
- 76.06 Same spur projecting SW. Desc. on NW. slope.

Intersect N. bdy. of T., ( 2nd St. Par. S., ) 8.68 chs. E. of the reestablished standard ¼ sec. cor. of S. bdy. of sec. 33, hereinbefore described.

At point of intersection Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 3 and 4, marked on brass cap



and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.


Land, level on S. half-mile and rolling hills on remainder of line.  
 Soil, 2nd rate on level land, and 3rd and 4th rate on remainder.  
 No timber.  
 Undergrowth, mesquite and catclaw.

From the reestablished cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp., hereinbefore described;

N.0°02'W., bet. secs. 32 and 33, over hilly desert land, through scattering undergrowth. Desc. 30 ft.

- 2.00 Bed of ravine, 10 lks. wide at bottom, course E. Asc. 60 ft.
- 8.00 Top of spur projecting E. Desc. 95 ft.
- 15.80 Wash, 40 lks. wide, 3 ft. deep, course S.20°E.
- 31.60 Wash, 30 lks. wide, 3 ft. deep, course SE.
- 35.00 Sharp bend in road running W. and N. from Willcox to Solomonville, bears W., 5 chs. dist.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Ascend 140 ft.

- 54.00 Top of ridge, bears NW. and SE. Desc. 140 ft.
- 63.70 Bed of ravine, 20 lks. wide at bottom, course SE.; heads 10 chs. NW. of line. Asc. 70 ft.
- 71.30 Top of ridge bears E. and W. Desc. 70 ft.
- 79.00 Wash, 20 lks. wide, 2 ft. deep, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, marked on brass cap

Chains

T11S	R26E
S29	S28
S32	S33

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, hilly.

Soil, rocky, sandy and gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

- EAST, on a random line, bet. secs. 28 and 33.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.96 Intersect N. and S. line 7 lks. N. of the cor. of secs. 27, 28, 33 and 34.
- Thence N.  $89^{\circ}57'$  W., on a true line, bet. secs. 28 and 33, over hilly desert land, through scattering undergrowth. Asc. 30 ft.
- 7.00 Top of slope of hill bears N. Thence along N. slope of ridge bearing E. and W.
- 30.00 Rocky draw, 20 lks. wide, 10 ft. deep, course N.; heads 5 chs. S.
- 39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap
- |               |      |
|---------------|------|
| $\frac{1}{4}$ | S28  |
|               | S33  |
|               | 1917 |
- and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.
- 79.80 Wash, 10 lks. wide, 2 ft. deep, course NE.  
 79.96 The cor. of secs. 28, 29, 32 and 33.

Land, hilly.

Soil, rocky, sandy and gravelly; 4th rate.

No timber.

Undergrowth, mesquite and catclaw.

- N.  $0^{\circ}02'$  W., bet. secs. 28 and 29, over hilly desert land, through scattering undergrowth. Desc. slightly.
- 18.00 Wash, 30 lks. wide, 5 ft. deep, course E.  
 32.50 Wash, 40 lks. wide, 5 ft. deep, course E.  
 39.00 Wash, 20 lks. wide, 2 ft. deep, course SE.  
 \*40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to rock, and 8 ins. in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap
- |               |     |      |
|---------------|-----|------|
| $\frac{1}{4}$ | S29 | S28  |
|               |     |      |
|               |     | 1917 |
- from which  
 A cedar, 12 ins. diam., bears S.  $27^{\circ}$  W., 88 lks. dist., marked  $\frac{1}{4}$  S29 BT.  
 No other bearing tree available. Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- 51.00 Wash, 30 lks. wide, 2 ft. deep, course SE. Asc. 160 ft.  
 70.70 Top of ridge, bearing W. and SE. Desc. 40 ft.  
 79.00 Wash, 15 lks. wide, 2 ft. deep, course E.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, marked on brass cap



Chains

T11S	R26E
S20	S21
S29	S28

1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, hilly.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

40.00 S.89°57'E., on a random line, bet. secs. 21 and 28.  
Set temp. ¼ sec. cor.  
80.04 Intersect N. and S. line 16 lks. N. of the cor. of secs. 21, 22, 27 and 28.

Thence N.89°50'W., on a true line, bet. secs. 21 and 28, over hilly desert land, through scattering undergrowth, along N. slope of hill.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	S21
¼	S28
	1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

45.00 Leave hill, bearing N. and S. Thence over rolling land.  
80.04 The cor. of secs. 20, 21, 28 and 29.

Land, hilly on E. and rolling on W. half of line.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

5.00 N.0°02'W., bet. secs. 20 and 21,  
over hilly desert land, through scattering undergrowth.  
Foot of hill, bears E. and W. Asc. 150 ft.  
24.24 Top of hill. Ridges bear NE., SE. and W. Desc. 130 ft.  
39.85 Ravine, 10 lks wide at bottom, course N.10°E.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to rock and 18 ins. in a mound of stone, for ¼ sec. cor., marked on brass cap.

¼	S20	S21
		1917

from which  
A cedar, 12 ins. diam., bears S.36°45'E., 22 lks. dist., marked ¼ S21 BT.  
A cedar, 12 ins. diam., bears N.7°W., 36 lks. dist., marked ¼ S20 BT.

43.70 Leave hills, bearing NE. and SW. Thence over rolling land.  
52.00 Wash, 100 lks. wide, 12 ft. deep, course E.  
58.40 Wash, 30 lks. wide, 5 ft. deep, course E.  
60.00 Road from Solomonsville to Wilcox bears NE. and SW.  
60.00 Road from Solomonsville to Ten Ranch bears E. and W.  
65.20 Wash, 100 lks. wide, 1 ft. deep, course E.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on brass cap

Chains

T11S	R26E
S17	S16
S20	S21

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Land, hilly on S. and rolling on N. half of line.  
Soil, rocky, sandy and gravelly; 4th rate.  
Timber, scattering cedar.  
Undergrowth, mesquite and catclaw.

40.00 S.  $89^{\circ}50'E.$ , on a random line, bet. secs. 16 and 21.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.02 Intersect N. and S. line 4 lks. N. of the cor. of secs.  
15, 16, 21 and 22.

40.01 Thence N.  $89^{\circ}48'W.$ , on a true line, bet. secs. 16 and 21,  
over rolling desert land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$	S16
	S21

1917

60.82 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.  
80.02 Road from Solomonville to Willcox bears NE. and SW.  
The cor. of secs. 16, 17, 20 and 21.

Land, rolling.  
Soil, rocky, sandy and gravelly; 4th rate.  
No timber.  
Undergrowth, scattering mesquite and catclaw.

3.40 N.  $0^{\circ}02'W.$ , bet. secs. 16 and 17,  
over rolling desert land, through scattering undergrowth.  
10.50 Wash, 20 lks. wide, 2 ft. deep, course E.  
38.10 Wash, 50 lks. wide, 2 ft. deep, course E.  
40.00 Wash, 20 lks. wide, 1 ft. deep, course E.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$	S17	S16
---------------	-----	-----

1917

47.00 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.  
66.20 Wash, 20 lks. wide, 2 ft. deep, course E.  
79.60 Wash, 100 lks. wide, 2 ft. deep, course E.  
80.00 Wash, 10 lks. wide, 2 ft. deep, course E.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 8, 9, 16 and 17, marked on  
brass cap

T11S	R26E
S8	S9
S17	S16

1917


and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Chains

Land, rolling.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

40.00 S.89°48'E., on a random line, bet. secs. 9 and 16.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.16 Intersect N. and S. line 4 lks. S. of the cor. of secs.  
 9, 10, 15 and 16.


25.36 Thence N.89°50'W., on a true line, bet. secs. 9 and 16,  
 over level desert land, through scattering undergrowth.  
 Road from Solomonsville to Wilcox bears NE. and SW.  
 40.08 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.  
 48.06 Wash, 60 lks. wide, 2 ft. deep, course N.80°E.  
 56.66 Road from "W.A." Ranch to Willcox bears N. and S.  
 80.16 The cor. of secs. 8, 9, 16 and 17.

Land, level desert.  
 Soil, sandy, rocky and gravelly; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

2.50 N.0°02'W., bet. secs. 8 and 9,  
 over rolling desert land, through scattering under-  
 growth.  
 20.00 Wash, 15 lks. wide, 2 ft. deep, course E.  
 25.75 Wash, 30 lks. wide, 3 ft. deep, course E.  
 34.85 Wash, 30 lks. wide, 3 ft. deep, course E.  
 37.00 Barbed wire fence bears NE. and SW.  
 40.00 Road bears E. and W.  
 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in  
 the ground to rock and 14 ins. in a mound of stone,  
 for  $\frac{1}{4}$  sec. cor., marked on brass cap



from which  
 The SW. cor. of an adobe house at "W. A." Ranch bears  
 N.56°30'E., 290 lks. dist.  
 Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of cor.  
 Enter hills, bearing NE. and W.  
 40.50 Reservoir, 100 ft. long, 50 ft. wide, bears E., 5 chs. dist.  
 41.60 Adobe house at "W. A." Ranch bears E., 242 lks. dist.  
 42.00 Well and windmill bears E., 450 lks. dist.  
 46.00 Wash, 20 lks. wide, 3 ft. deep, course SE. Asc. 120 ft.,  
 over rocky S. slope to top of ridge.  
 46.70 Barbed wire fence, bears NW. and SE.  
 55.40 Top of ridge, bears E. and W. Desc. 100 ft. to ft. of hill.  
 58.70 Barbed wire fence bears E. and W.  
 66.50 Ft. of slope bears E. and W. Thence over level desert,  
 bears E. and W.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 4, 5, 8 and 9, marked on  
 brass cap

Chains

T11S	R26E
S5	S4
S8	S9

1917

from which  
 A hackberry, 6 ins. diam., bears N.42 $\frac{1}{2}$ °W., 123 lks. dist.,  
 marked T11S R26E S5 BT.  
 No other bearing trees available. Raise a mound of  
 stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling, hilly and level.  
 Soil, rocky, sandy and gravelly; 4th rate.  
 Timber, scattering cedar and hackberry.  
 Undergrowth, mesquite and catclaw.

40.00 S.89°50'E., on a random line, bet. secs. 4 and 9.  
 80.28 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line at the cor. of secs. 3, 4, 9 and 10.

32.18 Thence N.89°50'W., on a true line, bet. secs. 4 and 9,  
 over rolling land, through scattering undergrowth.  
 40.14 Fence, bears NW. and SE.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$	S 4
	S 9
	1917

and raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high,  
 N. of cor.  
 45.88 Wash, 30 lks. wide, 2 ft. deep, course NE.  
 55.28 Enter wash, 30 lks. wide, 2 ft. deep, course NE. Thence  
 up bed of same.  
 77.78 Leave wash, comes from NW., course E.  
 80.28 The cor. of secs. 4, 5, 8 and 9.

Land, rolling and level.  
 Soil, 4th rate; decomposed granite.  
 No timber.  
 Undergrowth, mesquite and catclaw.


.15 N.0°02'W., bet. secs. 4 and 5,  
 17.50 ascending over hilly land, through scattering timber  
 32.40 and undergrowth.  
 40.00 Wash, 30 lks. wide, 2 ft. deep, course E. Asc. 290 ft.  
 Top of hill. Desc. 193 ft.  
 Ft. of slope.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$	S5	S4
		1917

from which  
 A cedar, 10 lks. diam., bears S.87°45'W., 300 lks. dist.,  
 marked  $\frac{1}{4}$  S5 BT.  
 No other bearing tree available. Raise a mound of  
 stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.  
 48.50 Wash, 30 lks. wide, 3 ft. deep, course SE.  
 76.01 Intersect N. bdy. of Tp., (2nd St. Par. S., ) 8.35 chs.  
 E. of the reestablished standard  $\frac{1}{4}$  sec. cor. on S. bdy  
 of sec. 32, hereinbefore described.

Chains

At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., in a mound of stone on solid rock, for closing cor. of secs. 4 and 5, marked on brass cap



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.


Land, hilly on S. half and rolling on N. half. Soil, rocky, sandy and gravelly; 4th rate. Timber, cedar. Undergrowth, mesquite and catclaw.

From the reestablished cor. of secs. 5, 6, 31 and 32, on S. bdy. of Tp., hereinbefore described;

N.0°03'W., bet. secs. 31 and 32, over mountainous land, through scattering timber and undergrowth. Asc. 100 ft.

5.80  
40.00

Ridge, bears N.70°W. and S.70°E. Desc. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



from which A hackberry, 8 ins. diam., bears S.62°E., 11 lks. dist., marked 1/4 S32 BT.

No other bearing tree available. Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

41.00

Wash, 40 lks. wide, 3 ft. deep, course S.70°E., 390 ft. below ridge.

43.30

Fence bears E. and W.

43.90

Road bears E. and W.

44.20

Fence bears E. and W.

45.00

E. J. Moyer's house bears W., 5 chs. dist.

50.00

Low ridge, bears E. and W.

54.00


Small wash, 10 lks. wide, course E.

54.90

Fence, bears E. and W.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous and hilly. Soil, 4th rate. Timber, cedar. Undergrowth, mesquite and catclaw.

EAST, On a random line, bet. secs. 29 and 32.

40.00

Set temp. 1/4 sec. cor.

79.82

Intersect N. and S. line 9 lks. S. of the cor. of secs. 28, 29, 32 and 33.

Chains

Thence S.89°56'W., on a true line, bet. secs. 29 and 32,  
 over rolling, hilly land, through scattering undergrowth.  
 Asc. gradually along N. side of ridge.  
 12.00 Road from Willcox to Solomonsville bears N. and S.  
 29.30 Top of ridge, bears SE. and W. Thence along ridge.  
 29.62 Old road bears N. and S.  
 39.91 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the  
 ground and 12 ins. in a mound of stone, for  $\frac{1}{4}$  sec. cor.,  
 marked on brass cap

$$\frac{1}{4} \frac{S29}{S32}$$
 1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
 N. of cor.  
 49.60 Saddle in ridge, bearing E. and W. Asc.  
 54.50 Summit, on ridge. Desc.  
 58.10 Saddle in ridge. Asc. 90 ft.  
 68.00 Summit, on ridge. Desc.  
 74.82 Bottom of ravine, course SE. Asc. 65 ft.  
 79.82 The cor. of secs. 29, 30, 31 and 32.

Land, rolling hills.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, mesquite and catclaw.

WEST, on a random line, bet. secs. 30 and 31.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 77.19 Intersect W. bdy. of Tp. 8 lks. N. of the cor. of secs.  
 25, 30, 31 and 36, hereinbefore described.

Thence N.89°57'E., on a true line, bet. secs. 30 and 31,  
 over mountainous land, through scattering timber and  
 undergrowth. Asc.  
 2.20 Ridge, bears NW. and SE. Desc. 275 ft.  
 14.97 Wash, 30 lks. wide, 3 ft. deep, course SE. Asc.  
 37.19 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
 ground to rock and 14 ins. in a mound of stone, for  $\frac{1}{4}$   
 sec. cor., marked on brass cap

$$\frac{1}{4} \frac{S30}{S31}$$
 1917

from which

A cedar, 14 ins. diam., bears N.60 $\frac{1}{2}$ °E., 77 lks. dist.,  
 marked  $\frac{1}{4}$  S30 BT.

A cedar, 15 ins. diam., bears S.57 $\frac{1}{2}$ °E., 178 lks. dist.,  
 marked  $\frac{1}{4}$  S31 BT.


40.00 Top of spur projecting SE., 350 ft. above wash. Desc. 240  
 ft.  
 50.16 Bottom of ravine, course S. Asc. 260 ft.  
 60.30 Top of ridge, at bend, bearing NW. and NE. A spur pro-  
 jects SE. Desc. 420 ft.  
 77.19 The cor. of secs. 29, 30, 31 and 32.

Land, mountainous.  
 Soil, rocky; 4th rate.  
 Timber, cedar.  
 Undergrowth, mesquite and catclaw.

N.0°03'W., bet. secs. 29 and 30,  
 over rolling mountainous land, through scattering under-  
 growth.  
 15.00 Desc. 72 ft.


Chains

- 15.00 Bottom of ravine, course E. Asc. 90 ft.
- 23.20 Spur projecting SE. Desc. 65 ft.
- 30.20 Bottom of ravine, course E. Ascend.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

- 41.00 Saddle on E. and W. ridge. Desc.
- 43.44 Ravine, course SE. Asc.
- 67.60 Fence, bears NW. and SE.
- 72.10 Ridge, bears NW. and SE., 130 ft. above ravine. Desc. 65 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap




1917  
and raise a mound of stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

Land, mountainous and hilly.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, mesquite and catclaw.

- 40.00 N.89°56'E., on a random line, bet. secs. 20 and 29. Set temp.  $\frac{1}{4}$  sec. cor.
- 79.82 Intersect N. and S. line 14 lks. N. of the cor. of secs. 20, 21, 28 and 29.

Thence N.89°58'W., on a true line, bet. secs. 20 and 29, over rolling land, through scattering undergrowth.

- 1.32 Wash, 30 lks. wide, 3 ft. deep, course S.80°E.
- 17.12 Low spur projecting N.
- 27.92 Road from Willcox to Solomonville bears NW. and SE.
- 31.92 Fence bears NW. and SE.
- 39.91 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

- 60.66 Top of hill bears N. and S. Desc. 75 ft.
- 67.36 Bottom of ravine, course S. Asc. 85 ft.
- 77.22 Top of hill bears NW. and SE. Desc.
- 78.32 Bottom of ravine, course SE.
- 79.82 The cor. of secs. 19, 20, 29 and 30.

Land, rolling and hilly.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, ocotillo, mesquite and catclaw.

- 40.00 S.89°57'W., on a random line, bet. secs. 19 and 30. Set temp.  $\frac{1}{4}$  sec. cor.

Chains

77.15 Intersect W. bdy. of Tp. 5 lks. N. of the cor. of secs. 19, 24, 25 and 30, hereinbefore described.

Thence N. 89° 55' E., on a true line, bet. secs. 19 and 30, over mountainous land, through scattering undergrowth. Asc. 100 ft.

18.74 Ridge bears N. and S. Desc. 92 ft.

31.88 Ravine, course N. Asc. 60 ft.

35.27 Spur projecting N. Desc.

37.15 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and 14 ins. in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \text{ S19} \\ \hline \text{S30} \\ 1917 \end{array}$$

and raise a mound of stone, 2  $\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

67.50 Bottom of ravine, course SE., 150 ft. below spur. Asc.

71.93 Fence, bears N. and S.

74.65 Low ridge, bears NW. and SE., 85 ft. above bottom of ravine. Desc. 30 ft.

77.15 The cor. of secs. 19, 20, 29 and 30.

Land, mountainous.  
Soil, rocky 4th rate.  
No timber.  
Undergrowth, scrub mesquite, oak and catclaw.

N. 0° 03' W., bet. secs. 19 and 20, over rolling land, through scattering undergrowth. Asc.

5.00 Low ridge, bears E. and W.

38.50 Ravine, course E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \\ \hline \text{S19} | \text{S20} \\ \hline 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, 1  $\frac{1}{2}$  ft. high, W. of cor.

41.20 Road bears E. and W.

41.70 Fence bears E. and W.

46.61 Ravine, course E.

48.60 Well, 30 ft. deep, containing good water, bears W 2 chs. dist.

52.45 Edwin Gleeson's house, ("Ten Ranch") bears E., 28.22 chs. dist.

57.50 Ridge bears E. and W.

58.65 Old prospect tunnel bears E., 33 chs. dist. Indications of copper.

75.00 Wash, 30 lks. wide, 4 ft. deep, course E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on brass cap

$$\begin{array}{r} \text{T11S} | \text{R26E} \\ \hline \text{S18} | \text{S17} \\ \hline \text{S30} | \text{S29} \\ \hline 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, 1  $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and hilly.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, scrub oak, mesquite and catclaw.



Chains

40.00 S.89°58'E., on a random line, bet. secs. 17 and 20.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.98 Intersect N. and S. line 4 lks. N. of the cor. of secs.  
 16, 17, 20 and 21.

Thence N.89°56'W., on a true line, bet. secs. 17 and 20,  
 over rolling land, through scattering undergrowth.  
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S17  
 S20  
 1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.  
 73.30 Fence, bears NW. and SE.  
 79.98 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.  
 Soil, decomposed granite; 4th rate.  
 No timber.  
 Undergrowth, mesquite, catclaw and scrub oak.

40.00 S.89°55'W., on a random line, bet. secs. 18 and 19.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 77.07 Intersect W. bdy. of Tp. 9 lks. N. of the cor. of secs.  
 13, 18, 19 and 20, hereinbefore described.

Thence N.89°51'E., on a true line, bet. secs. 18 and 19,  
 over rolling land, through scattering undergrowth.  
 3.07 Small ravine, course SE.  
 11.87 Prospect shaft, 30 ft. deep, bears S., 15 lks. dist.  
 37.07 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S18  
 S19  
 1917

and raise a mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.  
 77.07 The cor. of secs. 13, 18, 19 and 24.

Land, level and rolling.  
 Soil, decomposed granite; 3rd and 4th rate.  
 No timber.  
 Undergrowth, catclaw, scrub oak and mesquite.

N.0°03'W., bet. secs. 17 and 18,  
 over rolling land, through scattering undergrowth.  
 15.20 Fence, bears N.15°W. and S.15°E.  
 17.70 Wash, 20 lks. wide, 2 ft. deep, course E. ,  
 19.00 Same fence, bears NE. and SW.  
 25.00 Top of hill.  
 37.90 Wash, 50 lks. wide, 2 ft. deep, course E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S18 | S17  
 1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 55.50 Wash, 20 lks. wide, 2 ft. deep, course E.  
 70.00 Wash, 10 lks. wide, 5 ft. deep, course E.  
 78.30 Road bears E. and W.

Chains

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap

T11S	R26E
S7	S8
S18	S17

1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling and hilly.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, catclaw, scrub oak and mesquite.

40.00 S.89°56'E., on a random line, bet. secs. 8 and 17.  
Set temp. ¼ sec. cor.

80.04 Intersect N. and S. line 4 lks. S. of the cor. of secs. 8, 9, 16 and 17.

Thence N.89°58'W., on a true line, bet. secs. 8 and 17, over level desert land, through scattering undergrowth.

9.84 Wash, 20 lks. wide, 2 ft. deep, course S.80°E.  
37.94 Wash, 50 lks. wide, 2 ft. deep, course SE.  
38.64 Fence, bears NE. and SW.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	S 8
	S17
	1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

77.04 Road bears N.80°E. and S.80°W.  
80.04 The cor. of secs. 7, 8, 17 and 18.

Land, level.  
Soil, decomposed granite, 4th rate.  
No timber.  
Undergrowth, catclaw, and scrub mesquite.

40.00 S.89°51'W., on a random line, bet. secs. 7 and 18.  
Set temp. ¼ sec. cor.

76.80 Intersect W. bdy. of Tp. 3 lks. N. of the cor. of secs. 7, 12, 13 and 18, hereinbefore described.

Thence N.89°50'E., on a true line, bet. secs. 7 and 18, over mountainous land, through scattering undergrowth. Asc. 250 ft.

19.76 Spur projecting NE. Desc. 140 ft. along S. side of same.  
34.40 Same spur projecting SE. Desc.  
36.80 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	S 7
	S18
	1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.


48.80 Small ravine, course S., 240 ft. below spur. Asc.  
56.62 Spur projects SE. Desc. 80 ft.  
62.53 Ravine, course S. Asc. 40 ft.  
69.35 Spur, projecting SE. Desc. 55 ft.  
76.80 The cor. of secs. 7, 8, 17 and 18.

Chains

Land, mountainous and hilly.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, catclaw and scrub mesquite and oak.

N.0°03'W., bet. secs. 7 and 8,  
over rolling mountainous land, through scattering  
timber and undergrowth.


- 14.00 Wash, 30 lks. wide, course SE. Asc.
- 19.10 Road bears NW. and SE.
- 33.40 Summit of ascent, 120 ft. above wash., on W. side of hill.  
Desc. 100 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



from which  
A cedar, 6 ins. diam., bears S.45°W., 5 lks. dist.,  
marked  $\frac{1}{4}$  S7 BT.

No other bearing tree available. Raise a mound of  
stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

- 40.50 Wash, 20 lks. wide, 2 ft. deep, course SE. Asc. 130 ft.
- 56.00 Ridge, bears E. and W. Desc. 35 ft.
- 65.74 Bed of ravine, course E. Asc. 50 ft.
- 72.55 Ridge bears E. and W. Desc. 50 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the  
ground and 14 ins. in a mound of stone, for cor. of secs.  
5, 6, 7 and 8, marked on brass cap



1917


and raise a mound of stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high,  
W. of cor.

Land, rolling mountainous.  
Soil, rocky; 4th rate.  
Timber, scattering cedar, and scrub oak.  
Undergrowth, mesquite and catclaw.

- 40.00 S.89°58'E., on a random line, bet. secs. 5 and 8.  
Set temp.  $\frac{1}{4}$  sec. cor.
- 80.12 Intersect N. and S. line 12 lks. N. of the cor. of secs.  
4, 5, 8 and 9.

Thence N.89°53'W., on a true line, bet. secs. 5 and 8,  
over rolling land, through scattering undergrowth  
and timber.

- 7.52 Fence bears N. and S.
- 40.06 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
ground to rock and 18 ins. in a mound of stone, for  $\frac{1}{4}$   
sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
N. of cor.

- 47.27 Wash, course NE.
- 59.92 Same wash, 30 lks. wide, 2 ft. deep, course SE.
- 80.12 The cor. of secs. 5, 6, 7 and 8.

Chains

Land, rolling.  
Soil, rocky 4th rate.  
Timber, cedar, oak and hackberry.  
Undergrowth, mesquite and catclaw.

40.00 S. 89° 50' W., on a random line, bet. secs. 6 and 7.  
Set temp.  $\frac{1}{4}$  sec. cor.  
76.60 Intersect W. bdy. of Tp. 24 lks. N. of the cor. of secs. 1, 6, 7 and 12, hereinbefore described.

Thence N. 89° 40' E., on a true line, bet. secs. 6 and 7, over mountainous land, through scattering timber and undergrowth. Desc. 50 ft.  
10.00 Bottom of ravine, course SE. Asc. 35 ft.  
16.80 Spur, projecting SE. Desc. 100 ft.  
26.70 Bottom of ravine, course SE. Asc. 127 ft.  
31.90 Spur, projecting SE. Desc.  
36.60 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 6  
 $\frac{1}{4}$  ———  
S 7  
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

49.00 Bottom of ravine, course S., 150 ft. below spur. Asc. 150 ft.  
56.70 Spur, bearing E. and SE. Desc. 322 ft.  
76.60 The cor. of secs. 5, 6, 7 and 8.

Land, mountainous.  
Soil, rocky: 4th rate.  
Timber, cedar.  
Undergrowth, scrub mesquite and catclaw.

N. 0° 03' W., bet. secs. 5 and 6, over hilly land, through scattering undergrowth.  
5.10 Wash, 20 lks. wide, 5 ft. deep, course E.  
10.70 Ravine, course SE. Asc. 240 ft., on S. slope of ridge.  
32.17 Ridge, bears NW. and SE. Thence along E. side of same.  
40.00 Spur, projecting E.  
Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground and 20 ins. in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S 6 | S 5  
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

53.97 Fence, bears E. and W.  
54.86 Same ridge, bears E. and SW., 160 ft. above spur. Desc. 450 ft.

75.43 Intersect N. bdy. of Tp., (2nd St. Par. S.,) 8.17 chs. E. of the reestablished standard  $\frac{1}{4}$  sec. cor. on S. bdy. of sec. 31, hereinbefore described.  
At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground and 16 ins. in a mound of stone, for closing cor. of secs. 5 and 6, marked on brass cap

T10S R26E  
S31  
S 6 | S 5  
T11S R26E  
C C  
1917

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
S. of cor.

Land, hilly and mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, scrub oak and catclaw.

Boundaries of T. 11 S., R. 26 E.

Latitudes, Departures and Closing Errors.

Line designated	True Course	Dist. chs.	Latitudes		Departures	
			N. chs.	S. chs.	E. chs.	W. chs.
South Boundary,	N.89°41'W.	39.14	.22			39.14
	N.89°45'W.	80.93	.35			80.93
	N.89°43'W.	120.13	.60			120.13
	WEST	237.27				237.27
West Boundary,	NORTH	475.93	475.93			
North Boundary, 2nd St. Par. S.	EAST	477.39			477.39	
East Boundary	S.0°3'W.	79.72		79.72		.07
	S.0°1'W.	79.58		79.58		.02
	S.0°7'W.	39.62		39.62		.16
	S.0°2'W.	39.83		39.83		.05
	SOUTH	39.92		39.92		
	S.0°3'W.	39.86		39.86		.04
	SOUTH	39.92		39.92		
	S.0°09'W. S.0°09'E.	79.25 39.78		79.25 39.78		.21
Convergency					.46	
Totals			477.10	477.48	477.96	478.02
				477.10		477.96
Error in latitude,				.38		
Error in departure,						.06

**LOCATION:** This township is located about 20 miles NE. of Willcox, Arizona, in the eastern edge and on the foothills of the Pinaleno Mountains.

**SURFACE:** The Pinaleno Mountains extend through the western and southern part of the township. The western part is steeply sloping mountains, the southern part being hilly. The northeastern part of the township is generally rolling and level desert land.

**SOIL:** The soil is all rocky, sandy and gravelly; 4th rate, and entirely unsuited for agricultural purposes.

**VEGETATION:** A small number of cedars and a few hackberry trees are found in the western part of the township in the mountains. Scrub mesquite, catclaw and tesota are found over practically the entire area. Scrub oak exists in the mountains. Grass is present in sufficient quantity to afford grazing only.

**WATER:** There are no natural springs available for public watering places. Water can be obtained in the beds of some of the larger ravines by digging wells. Wells are located as follows: one at the "W A" Ranch in sec. 9; one in a ravine in sec. 19, W. of the "Ten" Ranch, and one in sec. 31. These wells furnish good water. A small seep appears in sec. 3, but is too small to be of value and is undeveloped.

**MINERALS:** The prevailing geological formation is granite. There are outcroppings of quartz and indications of copper, iron, silver and vanadium in the Pinaleno Mountains. Two abandoned copper prospects are located in section 13, and a tunnel exists near the "TEN" Ranch in sec. 20. No commercial values have been developed.

**SETTLERS:** There are settlers in sections 9, 20 and 31.

**VALUE:** The grazing and possibly the minerals represent the chief value of the land.

CERTIFICATE OF UNITED STATES SURVEYOR.

I, Quintin Campbell, U. S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for Group 63, Arizona, bearing date of the 7th day of October, 1915, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the West Boundary and subdivision lines of TOWNSHIP 11 SOUTH, RANGE 26 EAST, and resurveyed all those parts or portions of the 2ND STANDARD PARALLEL SOUTH, THROUGH RANGE 26 AND PART OF RANGE 25 EAST, all those parts or portions of the SOUTH BOUNDARY OF TOWNSHIP 11 SOUTH, RANGE 26 EAST, and all those parts or portions of the WEST BOUNDARY OF TOWNSHIP 11 SOUTH, RANGE 27 EAST, all of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Group 63, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Quintin Campbell
U. S. Transitman.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

191

The foregoing field notes of the survey of

executed by

under his special instructions dated, 191, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.

Book "K"  
Group 63 - - - Arizona.

4-680

Township 11 South, Range 26 East.

DATE DIAGRAM.

		31	32	33		34	35	36					
		5-1-17	4-28-17	4-28-17	4-26-17	Resurveyed 4-26-17	4-25-17	4-25-17	4-25-17				
2nd Standard Parallel South													
5-1-17	6	5-25-17	5-25-17	5-12-17	4	5-26-17	5-9-17	5-7-17	2	5-26-17	5-23-17	1	4-25-17
5-1-17	7	5-24-17	5-21-17	5-12-17	5-9-17	5-7-17	5-9-17	5-7-17	11	5-4-17	5-4-17	12	4-25-17
5-1-17	18	5-24-17	5-18-17	5-11-17	5-9-17	5-7-17	5-9-17	5-7-17	14	5-4-17	5-4-17	13	4-24-17
4-30-17	19	5-24-17	5-18-17	5-11-17	5-9-17	5-7-17	5-8-17	5-5-17	23	5-4-17	5-3-17	24	4-24-17
4-30-17	30	5-16-17	5-16-17	5-10-17	5-8-17	5-5-17	5-8-17	5-5-17	26	5-3-17	5-3-17	25	4-24-17
4-30-17	31	5-16-17	5-16-17	5-8-17	5-8-17	5-5-17	5-5-17	5-3-17	35	5-3-17	4-24-17	36	4-24-17
Resurveyed													

6-2764

Surveys and resurveys executed on dates shown in yellow on above diagram, by Quintin Campbell, U. S. Transitman.

Surveys executed on dates shown in blue on above diagram, by W. B. Kimmel, U. S. Surveyor.



CERTIFICATE OF UNITED STATES SURVEYOR.

I, W. B. Kimmel, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for Group 63, Arizona, bearing date of the 7th day of October, 1915, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the subdivision lines of TOWNSHIP 11 SOUTH, RANGE 26 EAST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Group 63, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

William B. Kimmel, U. S. Surveyor.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, April 29, 1918.

The foregoing field notes of the survey of the West boundary and subdivision lines of TOWNSHIP 11 SOUTH, RANGE 26 EAST, and the resurvey of the 2ND STANDARD PARALLEL SOUTH THROUGH RANGE 26 AND PART OF RANGE 25 EAST, THE SOUTH BOUNDARY OF TOWNSHIP 11 SOUTH, RANGE 26 EAST, and the WEST BOUNDARY OF TOWNSHIP 11 SOUTH, RANGE 27 EAST, all of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by Quintin Campbell, U. S. Transitman and W. B. Kimmel, U. S. Surveyor, under his special instructions for Group 63, Arizona, dated Oct. 7, 1915, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys and resurveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.