

3015

Book "L".
4-679

BOOK 3015

FIELD NOTES

OF THE SURVEY OF THE

WEST BOUNDARY AND SUBDIVISION LINES OF TOWNSHIP 10 SOUTH, RANGE 26 EAST,

AND THE RESURVEY OF

NORTH BOUNDARY OF TOWNSHIP 10 SOUTH, RANGE 26 EAST,

AND

WEST BOUNDARY OF TOWNSHIP 10 SOUTH, RANGE 27 EAST.

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

W. B. KIMMEL,

In the capacity of U. S. Surveyor, under instructions dated October 7, 1915, issued by the United States Surveyor General to govern surveys included in Group No. 63, which were approved by the Commissioner of the General Land Office, October 28, 1915.

Survey Commenced May 25, 1917.

Survey Completed June 13, 1917.

Executed under Assignment
Instructions dated Feb. 1, 1916.

3015

3015

204
119

Book "L"

Group 63 - - Arizona.

BOOK 3015

INDEX DIAGRAM.

477.56
WEST

Township 10 South, Range 26 East.

	9	9	8	7	7	6	
13	6 39	5 32	4 27	3 22	2 17	1	1 and 5
	39	38	32	27	22	17	
12	7 38	8 31	9 26	10 21	11 16	12	1 and 4
	38	37	31	26	21	16	
12	18 37	17 30	16 25	15 20	14 16	13	1 and 4
	36	36	30	25	20	15	
11	19 35	20 30	21 24	22 19	23 15	24	1 and 3
	35	34	29	24	19	14	
11	30 34	29 29	28 23	27 18	26 14	25	1 and 2
	33	33	28	23	18	13	
10	31 32	32 27	33 22	34 18	35 13	36	1

WEST

2nd Standard Parallel South

477.56
WEST

- Surveyed under this group---notes in this book.
- Resurveyed under this group-- " " " " .
- Surveyed under this group---notes in Book "K".
- Resurveyed under this group-- " " " " .
- Accepted surveys.
- Unsurveyed.

Resurvey of W. Bdy. of T. 10 S., R. 27 E.,
Resurvey of N. Bdy. of T. 10 S., R. 26 E., and
Survey of W. Bdy. and Subdivision of T. 10 S., R. 26 E.

Chains

Work executed by W. B. Kimmel, U. S. Surveyor, using Young & Sons' light mountain transit No. 8478, which is described, with record of approval by the Assistant Supervisor of Surveys, and description of field tests, in Book K.
The dates on which the various parts of the work were performed are shown on diagram on page 41 of this book.
The magnetic declination is 13°30'E.

Resurvey of W. Bdy. of T. 10 S., R. 27 E.

Retracement.

From the reestablished standard cor. of Ts. 10 S., Rs. 26 and 27 E., described in Book K,
40.00 NORTH, on a random line, bet. secs. 31 and 36. After diligent search in this vicinity, fail to find any trace of the $\frac{1}{4}$ sec. cor.
79.64 Intersect the old cor. of secs. 25, 30, 31 and 36, which is a granite stone, 8x6x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

39.86 NORTH, on a random line, bet. secs. 25 and 30. Fall 1 lk. E. of the old $\frac{1}{4}$ sec. cor., which is a granite stone, 6x6x4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.
79.76 Fall 3 lks. E. of the old cor. of secs. 19, 24, 25 and 30, which is a charred stake with remains of nearly obliterated mound.

The true course for this mile is therefore N.0°01'W.

319.04 NORTH, along W. bdrs. of secs. 19, 18, 7 and 6., setting temp. cors. at intervals of 40.00 chs. and making diligent search for the old cors., which are missing. Fall 90 lks. E. of the cor. of Ts. 9 and 10 S., Rs. 26 and 27 E., which is a wooden post, 4 ins. square, 2 ft. above ground, firmly set, marked and witnessed as described by the Surveyor General.

The true course for this distance is therefore N.0°10'W., and the proportional length of the W. bdy. of each section is 79.76 chs.

Resurvey.

I return to the reestablished standard cor. of Ts. 10 S., Rs. 26 and 27 E.
Thence NORTH, on W. bdy. of sec. 31,

Chains

- over rolling desert land, through scattering undergrowth.
- 8.30 Road bears NE. and SW.
15.15 Wash, 30 lks. wide, 3 ft. deep, course E.
39.82 (Proportional distance)
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished $\frac{1}{4}$ sec. cor., marked on brass cap
- $\frac{1}{4}$
S36 | S31
1917
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 71.70 Wash, 30 lks. wide, 2 ft. deep, course NE.
79.64 The original cor. of secs. 25, 30, 31 and 36, hereinbefore described, which I reestablish for secs. 30 and 31 as follows;
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, marked on brass cap
- T10S
S30

S31
R27E
- 1917
and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.
- Land, rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite and catclaw.
-
- .36 N.0°01'W., on W. bdy. of sec. 30,
over rolling desert land, through scattering undergrowth.
(80.00 chs. N. of the standard Tp. cor.,)
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 25 and 36, marked on brass cap
- T10S
S25

S36
R26E
- 1917
and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 31.36 Wash, 20 lks. wide, 2 ft. deep, course NE.
39.86 The original $\frac{1}{4}$ sec. cor., hereinbefore described, which I reestablish for sec. 30 only, as follows:
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, marked on brass cap
- $\frac{1}{4}$ S30
- 1917
and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.
- 40.36 (40.00 chs. N. of the reestablished cor. of secs. 25 and 36,)
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished $\frac{1}{4}$ sec. cor. of sec. 25, marked on brass cap
- $\frac{1}{4}$ S25
- 1917

Resurvey of W.Bdy. of T. 10 S., R. 27 E.

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

79.76 The original cor. of secs. 19, 24, 25 and 36, hereinbefore described, which I reestablish for secs. 19 and 30 only, as follows:
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, marked on brass cap

T10S
S19
S30
R27E

1917

and dig pits, 24x24x12 ins., NE. and SE. of post, 6 ft. dist.

Land, gently rolling.
Soil, 2nd rate.
No timber.
Undergrowth, mesquite and catclaw.

N.0°10'W., on W. bdy. of sec. 19, over rolling land, through scattering undergrowth.

.60 (80.00 chs. N. of the reestablished cor. of secs. 25 and 36,)
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 24 and 25, marked on brass cap

T10S
S24
S25
R26E

1917

and dig pits, 24x24x18 ins., NW. and SW. of post, 6 ft. dist. Gleeson's well bears N.62°W., 8 chs. dist.

.75 Dim road, bears NW. and SE.

39.50 Wash, 25 lks. wide, 2 ft. deep, course NE.

39.88 (Proportional distance,) set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished ¼ sec. cor. of sec. 19, marked on brass cap

¼S19

1917

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

40.60 (40.00 chs. N. of the reestablished cor. of secs. 24 and 25,)
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished cor. of sec. 24, marked on brass cap

¼S24

1917

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

79.76 (Proportional distance,) set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 18 and 19, marked on brass cap

T10S
S18
S19
R27E

1917

and dig pits, 24x24x12 ins., NE. and SE. of post, 6 ft. dist.

Chains

Land, rolling.
Soil, 2nd rate.
No timber.
Undergrowth, mesquite and catclaw. Some yucca.

.84 N.0°10'W., on W. bdy. of sec. 18,
over gently rolling desert land, through scattering
undergrowth.
(80.00 chs. N. of the reestablished cor. of secs. 24 and
25.)
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
ground, for reestablished cor. of secs. 13 and 24,
marked on brass cap

T10S
S13
S24
R26E

4.94 and dig pits, 24x24x12 ins., NW. and SW. of post, 6
39.88 ft. dist.
Wash, 20 lks. wide, 2 ft. deep, course NE.
(proportional distance,) set an iron post, 3 ft. long, 1
in. diam., 26 ins. in the ground, for reestablished $\frac{1}{4}$
sec. cor. of sec. 18, marked on brass cap

$\frac{1}{4}$ S18

40.84 and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
dist.
(40.00 chs. N. of the reestablished cor. of secs. 13 and
24.)
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for reestablished $\frac{1}{4}$ sec. cor. of sec. 13,
marked on brass cap

$\frac{1}{4}$ S13

43.04 and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
70.84 Wash, 30 lks. wide, 2 ft. deep, course E.
79.44 Wash, 35 lks. wide, 3 ft. deep, course E.
79.76 Wash, 20 lks. wide, 2 ft. deep, course E.
(Proportional distance,) set an iron post, 3 ft. long,
3 ins. diam., 24 ins. in the ground, for reestablished
cor. of secs. 7 and 18, marked on brass cap

T10S
S7
S18
R27E

1917
and dig pits, 24x24x12 ins., NE. and SE. of post, 6
ft. dist.

Land, gently rolling.
Soil, decomposed granite; 2nd rate.
No timber.
Undergrowth, mesquite and catclaw, with some yucca.

N.0°10'W., on W. bdy. of sec. 7,
over gently rolling desert land, through scattering
undergrowth.

Resurvey of W. Bdy. of T. 10 S., R. 27 E. 5

Chains

1.08 (80.00 chs. N. of the reestablished cor. of secs. 13 and 24,)
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 12 and 13, marked on brass cap

T10S
S12
S13
R26E

1917

and dig pits, 24x24x12 ins., NW. and SW. of post, 6 ft. dist.

39.88 (Proportional distance,) set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished $\frac{1}{4}$ sec. cor. of sec. 7, marked on brass cap

$\frac{1}{4}$ S7

1917

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

41.08 (40.00 chs. N. of the reestablished cor. of secs. 12 and 13,)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished $\frac{1}{4}$ sec. cor. of sec. 12, marked on brass cap

$\frac{1}{4}$ S12

1917

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

42.68 Wash, 20 lks. wide, 2 ft. deep, course NE.

67.28 Wash, 100 lks. wide, 1 ft. deep, course E.

79.76 (Proportional distance,) set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 6 and 7, marked on brass cap

T10S
S6
S7
R27E

1917

and dig pits, 24x24x12 ins., NE. and SE. of post, 6 ft. dist.

Land, gently rolling.

Soil, decomposed granite; 2nd rate.

No timber.

Undergrowth, yucca, mesquite and catclaw.

N.0°10'W., on W. bdy. of sec. 6,
 over gently rolling desert land, through scattering undergrowth.

1.32 (80.00 chs. N. of the reestablished cor. of secs. 12 and 13,)

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished cor. of secs. 1 and 12, marked on brass cap

T10S
S1
S12
R26E

1917

and dig pits, 24x24x12 ins., NW. and SW. of post, 6 ft. dist.

Resurvey of W. Bdy. of T. 10 S., R. 27 E.

Chains

18.92 Wash, 30 lks. wide, 1 ft. deep, course E.
 39.88 (Proportional distance,) set an iron post, 3 ft. long,
 1 in. diam., 26 ins. in the ground, for reestablished
 $\frac{1}{4}$ sec. cor. of sec. 6, marked on brass cap

$\frac{1}{4}$ S6

1917

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
 dist.

41.32 (40.00 chs. N. of the reestablished cor. of secs. 1 and
 12,)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for reestablished $\frac{1}{4}$ sec. cor. of sec. 1, marked
 on brass cap

$\frac{1}{4}$ S1

1917

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
 dist.

79.76 The original cor. of Ts. 9 and 10 S., Rs. 26 and 27 E.,
 hereinbefore described; which I reestablish as follows:
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
 ground, marked on brass cap

T9S	
R26E	R27E
S36	S31

S1 | S6

T10S

1917

dig pits, 24x24x12 ins., on each line, N., E., and W.,
 4 ft., and S. of post 8 ft. dist.

Land, gently rolling.

Soil, 2nd rate.

No timber.

Undergrowth, mesquite, yucca and catclaw.

Resurvey of N. Bdy. of T. 10 S., R. 26 E.

NOTE: I first retrace the N. bdy. of the Tp., and find
 the old cors. all in place and at practically identical
 courses and distances as described in the original
 record; no differences being developed sufficient
 to warrant any alteration in the same. As some of
 these old cors. are in poor condition, I resurvey the
 line, using the old courses and distances, and setting
 iron posts in place of the original cors., as follows:

From the reestablished cor. of Ts. 9 and 10 S., Rs. 26
 and 27 E., hereinbefore described;

WEST, bet. secs. 1 and 36,

over rolling desert land, through scattering undergrowth.

24.60 Wash, 25 lks. wide, 2 ft. deep, course NE.

40.00 The old $\frac{1}{4}$ sec. cor., which is a wooden post, 4 ins. diam.,
 rotted off, marked and witnessed as described by the
 Surveyor General; which I reestablish as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, marked on brass cap

$\frac{1}{4}$ S36

S 1

1917

Resurvey of N. Bdy. of T. 10 S., R. 26 E.

7

Chains

and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

64.00 Wash, 20 lks. wide, 2 ft. deep, course NE.

80.00 The old cor. of secs. 1, 2, 35 and 36, which is a wooden post, 4 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General; which I reestablish as follows:
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground beside old cor., marked on brass cap

T9S	R26E
S35	S36
<hr/>	
S2	S1
T10S	
1917	

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.
Soil, 2nd rate.
No timber.
Undergrowth, yucca, mesquite and catclaw.

WEST, bet. secs. 2 and 35,
over rolling desert land, through scattering undergrowth.

22.30 Wash, 15 lks. wide, 2 ft. deep, course N.

40.00 The original ¼ sec. cor., which is a wooden post, 4 ins. square, 24 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General, which I reestablish as follows:
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground beside old cor., marked on brass cap

S35	
<hr/>	
S 2	
1917	

and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

80.00 The old cor. of secs. 2, 3, 34 and 35, which is a stone, 8x6x4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General; which I reestablish as follows:
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground beside old cor., marked on brass cap

T 9S	R26E
S34	S35
<hr/>	
S3	S2
T10S	
1917	

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.
Soil, decomposed granite; 2nd rate.
No timber.
Undergrowth, yucca, mesquite and catclaw.

WEST, bet. secs. 3 and 34,
over rolling desert land, through scattering undergrowth.

8.30 Wash, 75 lks. wide, 3 ft. deep, course N.70°E.

21.40 Same wash, 20 lks. wide, 2 ft. deep, course SE.

31.00 Same wash, course NE.

40.00 The old ¼ sec. cor., which is a stone, 8x6x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. I reestablish cor. as follows;

Chains

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground beside old cor., marked on brass cap

S34
—
¼
S 3
1917

80.00

The old cor. of secs. 3, 4, 33 and 34, identified by partly obliterated pits and mound, the cor. having disappeared. I reestablish same as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, marked on brass cap

T 9S R26E
S33 S34
—
S4 S3
T10S
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, 3rd rate.

No timber.

Undergrowth, mesquite and catclaw, with some yucca.

WEST, bet. secs. 4 and 33, over rolling land, through scattering undergrowth.

1.10

Road from Safford to Willcox bears N. and S.

34.90

Road bears NE. and SW.

40.00

The old ¼ sec. cor., which is a granite stone, 8x6x5 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. I reestablish cor. as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground beside old cor., marked on brass cap

S33
—
¼
S 4
1917

and dig pits, 1stx1stx1st2 ins., E. and W. of post, 3 ft. dist.

41.80

Wash, 30 lks. wide, 3 ft. deep, course N.

70.10

Wash, 30 lks. wide, 3 ft. deep, course N.

80.00

The old cor. of secs. 4, 5, 32 and 33, which is a granite stone, 8x6x4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. I reestablish cor. as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground beside original cor., marked on brass cap

T19S R26E
S32 S33
—
S5 S4
T10S
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, 2nd and 3rd rate.

No timber.

Undergrowth, yucca, mesquite and catclaw.

Resurvey of N. Bdy. of T. 10 S., R. 26 E.

Chains

WEST, bet. secs. 5 and 32,
 over hilly land, through scattering undergrowth. Asc.
 gradually.

10.00 Low spur projecting N. Desc. gradually.
 20.00 Small wash, course N.
 32.50 Road bears NE. and SW.
 40.00 The original $\frac{1}{4}$ sec. cor., which is a granite stone, 18x8x8
 ins., lying on top of ground between two pits, marked
 as described by the Surveyor General. I reestablish
 cor. as follows:
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground beside old cor., marked on brass cap

S32
$\frac{1}{4}$
S 5
1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
 N. of cor.

59.00 Wash, 40 lks. wide, 2 ft. deep, course N.
 68.00 Asc. 120 ft., on E. slope of spur.
 80.00 The original cor. of secs. 5, 6, 31 and 32, which is a
 sandstone, 18x10x6 ins., lying on a mound of stone,
 marked as described by the Surveyor General. I rees-
 tablish cor. as follows:
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
 ground by old cor., marked on brass cap

T 9S R26E
S31 S32
S6 S5
T10S
1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
 W. of cor.

Land, hilly.
 Soil, rocky; 3rd rate.
 No timber.
 Undergrowth, yucca, mesquite and catclaw.

WEST, bet. secs. 6 and 31,
 over hilly land, through scattering undergrowth. Asc.

2.00 Spur projecting N. Desc. 110 ft.
 16.83 Bed of ravine, course NW. Asc. 130 ft.
 36.00 Spur, projecting NW. Desc.
 40.00 The original $\frac{1}{4}$ sec. cor., which is a stone, 12x12x12 ins.
 above ground, firmly set, marked and witnessed as des-
 cribed by the Surveyor General. I reestablish cor.
 as follows:
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground beside old cor., marked on brass cap

S31
$\frac{1}{4}$
S 6
1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
 N. of cor.

65.50 Bed of ravine, course N., 200 ft. below spur. Asc. 85
 ft.
 74.40 Spur, projects N. Desc. 60 ft.
 79.54 The cor. of Ts. 9 and 10 S., Rs. 25 and 26 E., which is a
 granite stone, 10x8x6 ins. above ground, firmly set,
 marked and witnessed as described by the Surveyor
 General. I reestablish cor. as follows:
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
 ground beside old cor., marked on brass cap

T9S
R25E R26E
S36 S31
S1 S6
T 10 S
1917

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high,
S. of cor.

Land, hilly.
Soil, rocky; 3rd rate.
No timber.
Undergrowth, mesquite and catclaw.

Survey of W. Bdy. of T. 10 S., R. 26 E.

From the reestablished standard cor. of Ts. 10 S., Rs.
25 and 26 E., described in Book K,

NORTH, on a random line along W. bdy. of Tp., setting
temp. cors. at intervals of 40.00 chs.

478.76 Fall 100 lks. E. of the reestablished cor. of Ts. 9 and
10 S., Rs. 25 and 26 E., hereinbefore described. The
true course for this line is therefore N.0°07'W.

Returning to the reestablished standard cor. of Ts. 10 S.,
Rs. 25 and 26 E.,


N.0°07'W., on a true line, bet. secs. 31 and 36,
over mountainous land, through scattering undergrowth.
Desc. 135 ft.

11.31 Wash, 40 lks. wide, course N.15°E.

33.00 Enter same wash, course N.; comes from SE.

39.00 Leave wash, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for ¼ sec. cor., marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high,
W. of cor.


An oak, 10 ins. diam., bears N.38¼°W., 75 lks. dist.,
marked ¼ S36 BT. No other bearing tree available.

44.00 Same wash, course NE. Asc. 120 ft., on SE. slope.

54.65 Spur, projects E. Thence along E. slope.

71.22 Spur projects E. Desc. 120 ft., on NE. slope.

80.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the
ground, for cor. of secs. 25, 30, 31 and 36, marked on
brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high,
W. of cor.

Land, mountainous and hilly.
Soil, rocky; 4th rate.
No timber.
Undergrowth, scrub oak, mesquite and catclaw.

Survey of W. Bdy. of T. 10 S., R. 26 E.

Chains

N.0°07'W., bet. secs. 25 and 30,
 over rolling land, through scattering undergrowth.
 29.14 Wash, 50 lks. wide, course E.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
 ground and 12 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap

$\frac{1}{4}$	
S25	S30
1917	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

53.00 Asc. 340 ft., on S. slope, over mountainous land.
 78.13 Top of spur projecting E.
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 4 ins. in the
 ground and 24 ins. in a mound of stone, for cor. of secs.
 19, 24, 25 and 30, marked on brass cap

T10S	
R25E	R26E
S24	S19

S25	S30
1917	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

Land, rolling and mountainous.
 Soil, rocky; 4th rate.
 No timber.
 Undergrowth, yucca, mesquite and catclaw.

N.0°07'W., bet. secs. 19 and 24,
 over mountainous land, through scattering undergrowth.
 Desc. 380 ft., along NE. slope of spur.
 31.03 Small ravine, course NW. Asc.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
 ground and 12 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap

$\frac{1}{4}$	
S24	S19
1917	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

43.97 Summit of ascent, on W. slope of spur, 130 ft. above bottom
 of ravine. Desc. 200 ft.
 50.25 Ft. of slope. Thence over rolling land.
 68.89 Fence, bears E. and W.
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
 ground, for cor. of secs. 13, 18, 19 and 24, marked on
 brass cap

T10S	
R25E	R26E
S13	S18


S24	S19
1917	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

Land, mountainous and rolling.
 Soil, rocky; 3rd rate.
 No timber.
 Undergrowth, yucca, mesquite and catclaw.


Chains

N.0°07'W., bet. secs. 13 and 18,
 over level land, through scattering undergrowth.
 37.45 Wash, 40 lks. wide, 1 ft. deep, course E.
 Road, in wash, bears E. and W.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
 ground and 12 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap



1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 65.00 Asc. 290 ft., on S. slope of ridge, over mountainous land.
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the
 ground and 12 ins. in a mound of stone, for cor. of secs.
 7, 12, 13 and 18, marked on brass cap




1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.


Land, level, rolling and mountainous.
 Soil, 3rd and 4th rate.
 No timber.
 Undergrowth, mesquite, yucca and catclaw.

N.0°07'W., bet. secs. 7 and 12,
 over mountainous land, through scattering cedar and
 undergrowth. Asc. 290 ft.
 20.70 Top of ridge bears NE. and SW. Thence along W. side of
 same.
 31.16 Same ridge, bears SE. and N. Thence along top. Desc. 110 ft.
 36.00 Saddle. Asc. 70 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
 ground and 14 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap



1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 Desc. 215 ft.
 57.00 Saddle. Continue along top of ridge.
 68.40 Top of 100 ft. bluff facing N. Branches of ridge run NE.
 and NW. Desc. 450 ft. on N. side of ridge.
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
 ground, for cor. of secs. 1, 6, 7 and 12, marked on
 brass cap



1917


and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, cedar. Undergrowth, mesquite and catclaw.

Survey of W. bdy. of T. 10 S., R. 26 E.

Chains

N.0°07'W., bet. secs. 1 and 6,
 over rough mountainous land, through scattering cedar
 and undergrowth. Desc. on rough NW. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
 ground and 14 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 50.00 Bottom of ravine, course NW., 520 ft. below sec. cor.
 Asc. 40 ft.

64.00 Spur, projecting NW. Desc. 177 ft.
 78.76 The reestablished cor. of Ts. 9 and 10 S., Rs. 25 and 26
 E., hereinbefore described.


Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, cedar.
 Undergrowth, oak brush, mesquite and catclaw.

Subdivision of T. 10 S., R. 26 E.

From the reestablished standard cor. of secs. 35 and 36,
 on S. bdy. of Tp., (2nd St. Par. S.,)


N.0°08'W., (parallel to the mean bearing of the E. bdy.
 of the Tp.,) bet. secs. 35 and 36,
 over rolling desert land, through scattering under-
 growth.

18.40 Wash, 20 lks. wide, 2 ft. deep, course NE.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

48.50 Wash, 40 lks. wide, 1 ft. deep, course NE.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for cor. of secs. 25, 26, 35 and 36, marked on
 brass cap



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

Land, rolling.
 Soil, rocky; 2nd and 3rd rate.
 No timber.
 Undergrowth, mesquite, yucca and catclaw.


EAST, on a random line, bet. secs. 25 and 36.

Chains

40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.14 Intersect E. bdy. of Tp. at the cor. of secs. 25, and 36, reestablished as hereinbefore described.

Thence WEST, on a true line, bet. secs. 25 and 36, over rolling desert land, through scattering undergrowth.

40.07 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

47.84 Wash, 40 lks. wide, 2 ft. deep, course NE.

80.14 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.

Soil, 3rd rate.


No timber.

Undergrowth, yucca, mesquite and catclaw.

N.0°08'W., bet. secs. 25 and 26, over gently rolling desert land, through scattering undergrowth.

7.00 Road bears NE. and SW.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{2}$ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

42.20 Wash, 40 lks. wide, 3 ft. deep, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, marked on brass cap



1917

and dig pits, 18x18x12 ins., in each sec., $5\frac{1}{2}$ ft. dist.,

Land, gently rolling.

Soil, 2nd rate.

No timber.

Undergrowth, yucca, mesquite and catclaw.

EAST, on a random line, bet. secs. 24 and 25.


40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.28 Intersect E. bdy. of Tp. 7 lks. S. of the reestablished cor. of secs. 24 and 25, hereinbefore described.

Thence S.89°57'W., on a true line, bet. secs. 24 and 25, over gently rolling desert land, through scattering undergrowth.

10.28 Road to Gleeson's well bears NE. and SW. Well is about 6 chs. dist., NE. of this station.

40.14 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




Subdivision of T. 10 S., R. 26 E.

Chains


and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.
 42.00 Wash, 30 lks. wide, 2 ft. deep, course NE.
 80.28 The cor. of secs. 23, 24, 25 and 26.

Land, gently rolling.
 Soil, 2nd rate.
 No timber.
 Undergrowth, yucca, mesquite and catclaw.

N.0°08'W., bet. secs. 23 and 24,
 over gently rolling desert land, through scattering undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



1917
 and dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.
 52.60 Wash, 40 lks. wide, 3 ft. deep, course E.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked on brass cap




1917
 and dig pits, 18x18x12 ins., in each sec., $5\frac{1}{2}$ ft. dist.
 Land, gently rolling.
 Soil, 2nd rate.
 No timber.
 Undergrowth, mesquite and catclaw.

EAST, on a random line, bet. secs. 13 and 24.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.34 Intersect E. bdy. of Tp. 11 lks. N. of the cor. of secs. 13 and 24, reestablished as hereinbefore described.

Thence N.89°55'W., on a true line, bet. secs. 13 and 24, over gently rolling desert land, through scattering undergrowth.

1.34 Wash, 20 lks. wide, 2 ft. deep, course NE.
 40.17 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




1917
 and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.
 41.84 Wash, 40 lks. wide, 1 ft. deep, course NE.
 80.34 The cor. of secs. 13, 14, 23 and 24.


Land, gently rolling.
 Soil, 2nd rate.
 No timber.
 Undergrowth, yucca, mesquite and catclaw.

Chains

N.0°08'W., bet. secs. 13 and 14,
 over gently rolling land, through scattering undergrowth.
 5.00 Wash, 30 lks. wide, 2 ft. deep, course NE.
 34.60 Wash, 20 lks. wide, 2 ft. deep, course NE.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



1917
 and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
 dist.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for cor. of secs. 11, 12, 13 and 14, marked on
 brass cap




1917
 and dig pits, 18x18x12 ins., in each sec., $5\frac{1}{2}$ ft. dist.

Land, gently rolling and level.
 Soil, 1st and 2nd rate.
 No timber.
 Undergrowth, yucca, mesquite and catclaw.

40.00 **EAST**, on a random line, bet. secs. 12 and 13.
 Set temp. $\frac{1}{4}$ sec. cor.
 80;34 Intersect E. bdy. of Tp. at the reestablished cor. of secs.
 12 and 13, hereinbefore described.

Thence **WEST**, on a true line, bet. secs. 12 and 13,
 over slightly rolling and level desert land, through
 scattering undergrowth.
 40.17 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




and dig pits, 18x18x12 ins., E. and W. of post, 3 ft.
 dist.

80.34 The cor. of secs. 11, 12, 13 and 14.

Land, level and rolling.
 Soil, 1st and 2nd rate.
 No timber.
 Undergrowth, mesquite and catclaw.

N.0°08'W., bet. secs. 11 and 12,
 over level desert land, through scattering undergrowth.
 10.30 Wash, 25 lks. wide, 2 ft. deep, course NE.
 32;00 Wash, 25 lks. wide, 2 ft. deep, course E.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



1917
 and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
 dist.
 48.20 Wash, 20 lks. wide, 2 ft. deep, course E.

Chains

62.80 Wash, 30 lks. wide, 2 ft. deep, course E.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, marked on brass cap

T10S	R26E
S2	S1
S11	S12

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, level.

Soil, decomposed granite; 2nd rate.

No timber.

Undergrowth, yucca, mesquite and catclaw.

40.00 EAST, on a random line, bet. secs. 1 and 12.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.40 Intersect E. bdy. of Tp. 2 lks. S. of the reestablished cor. of secs. 1 and 12, hereinbefore described.

Thence S. $89^{\circ}59'$ W., on a true line, bet. secs. 1 and 12, over rolling desert land, through scattering undergrowth.

40.20 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$	S 1
	S12
	1917

and dig pits, $18 \times 18 \times 12$ ins., E. and W. of post, 3 ft. dist.

61.00 Wash, 30 lks. wide, 3 ft. deep, course N. 80° E.

69.90 Same wash, course S. 80° E.

80.40 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.

Soil, decomposed granite; 2nd rate.

No timber.

Undergrowth, yucca, mesquite and catclaw.

40.00 N. $0^{\circ}08'$ W., on a random line, bet. secs. 1 and 2.
 Set temp. $\frac{1}{4}$ sec. cor.
 78.49 Intersect N. bdy. of Tp., 37 lks. W. of the reestablished cor. of secs. 1, 2, 35 and 36, hereinbefore described.

Thence S. $0^{\circ}08'$ W., on a true line, bet. secs. 1 and 2, over rolling desert land, through scattering undergrowth.

38.49 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$	S2	S1
---------------	----	----

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

78.00 Wash, 30 lks. wide, 3 ft. deep, course E.

78.49 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.

Soil, decomposed granite; 2nd and 3rd rate.

No timber.

Undergrowth, yucca, mesquite and catclaw.

Chains

From the reestablished standard cor. of secs. 34 and 35, on S. bdy. of Tp., (2nd St. Par. S.,) described in Book "K."

N.0°08'W., bet. secs. 34 and 35, over rolling desert land, through scattering undergrowth.

- 2.00 Wash, 20 lks. wide, 1 ft. deep, course NE.
- 12.00 Wash, 40 lks. wide, 2 ft. deep, course E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S34 | S35

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

51.10 Road, bears NE. and SW.

67.60 Wash, 40 lks. wide, 3 ft. deep, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked on brass cap

T10S | R26E
S27 | S26

S34 | S35

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, decomposed granite; 2nd and 3rd rate.

No timber.

Undergrowth, mesquite, yucca and catclaw.

40.00 EAST, on a random line, bet. secs. 26 and 35.

Set temp. $\frac{1}{4}$ sec. cor.

79.98 Intersect N. and S. line 6 lks. S. of the cor. of secs. 25, 26, 35 and 36.

Thence S.89°57'W., on a true line, bet. secs. 26 and 35, over rolling desert land, through scattering undergrowth.

8.88 Road, bears NE. and SW.

28.08 Wash, 30 lks. wide, 1 ft. deep, course NE.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S26
S35
1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

67.38 Wash, 25 lks. wide, 4 ft. deep, course NE.

79.98 The cor. of secs. 26, 27, 34 and 35.

Land, rolling.

Soil, decomposed granite; 2nd and 3rd rate.

No timber.

Undergrowth, mesquite, catclaw and yucca.

N.0°08'W., bet. secs. 26 and 27, over gently rolling desert land, through scattering undergrowth.

26.80 Wash, 40 lks. wide, 3 ft. deep, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains

$\frac{1}{4}$
 S27 | S26

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 67.80 Wash, 20 lks. wide, 2 ft. deep, course NE.
- 77.80 Wash, 30 lks. wide, 1 ft. deep, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap

T10S | R26E
 S22 | S23

 S27 | S26

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.
 Soil, decomposed granite; 2nd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

- 40.00 EAST, on a random line, bet. secs. 23 and 26.
- Set temp. $\frac{1}{4}$ sec. cor.
- 80.00 Intersect N. and S. line 5 lks. S. of the cor. of secs. 23, 24, 25 and 26.

Thence S. $89^{\circ}58'$ W., on a true line, bet. secs. 23 and 26, over rolling desert land, through scattering undergrowth.

- 34.30 Wash, 30 lks. wide, 1 ft. deep, course NE.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S23

$\frac{1}{4}$

 S26
 1917

and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

- 78.00 Wash, 30 lks. wide, 3 ft. deep, course NE.
- 80.00 The cor. of secs. 22, 23, 26 and 27.

Land, rolling.
 Soil, decomposed granite; 2nd and 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

- N. $0^{\circ}08'$ W., bet. secs. 22 and 23, over gently rolling desert land, through scattering undergrowth.
- 37.50 Wash, 20 lks. wide, 2 ft. deep, course NE.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S22 | S23

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 69.70 Wash, 30 lks. wide, 4 ft. deep, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the

Chains

ground, for cor. of secs. 14, 15, 22 and 23, marked on brass cap

T10S	R26E
S15	S14
S22	S23

1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, gently rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00
79.96

N.89°58'E., on a random line, bet. secs. 14 and 23.
Set temp. ¼ sec. cor.
Intersect N. and S. line at the cor. of secs. 13, 14, 23 and 24.

Thence S.89°58'W., on a true line, bet. secs. 14 and 23, over gently rolling desert land, through scattering undergrowth.

2.56
34.96
39.98

Wash, 20 lks. wide, 2 ft. deep, course NE.
Wash, 40 lks. wide, 1 ft. deep, course NE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

S14	
¼	
S23	
1917	

and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. Dist.

70.46
79.96

Wash, 30 lks. wide, 1 ft. deep, course NE.
The cor. of secs. 14, 15, 22 and 23.

Land, gently rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

4.40
40.00

N.0°08'W., bet. secs. 14 and 15, over gently rolling desert land, through scattering undergrowth.
Wash, 20 lks. wide, 2 ft. deep, course NE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

S15	S14
1917	

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

41.80
80.00

Wash, 15 lks. wide, 2 ft. deep, course NE.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, marked on brass cap

T10S	R26E
S10	S11
S15	S14

1917


and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Chains

Land, gently rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00 EAST, on a random line, bet. secs. 11 and 14.
Set temp. 1/4 sec. cor.
79.92 Intersect N. and S. line 2 lks. N. of the cor. of secs. 11, 12, 13 and 14.


Thence N.89°59'W., on a true line, bet. secs. 11 and 14, over rolling desert land, through scattering undergrowth.
12.32 Wash, 20 lks. wide, 2 ft. deep, course NE.
39.96 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap




and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
50.42 Wash, 30 lks. wide, 2 ft. deep, course NE.
66.92 Wash, 10 lks. wide, 3 ft. deep, course NE.
79.92 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

N.0°08'W., bet. secs. 10 and 11, over gently rolling desert land, through scattering undergrowth.
26.00 Wash, 20 lks. wide, 1 ft. deep, course NE.
37.15 Road bears NE. and SW.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



and dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.
44.80 Wash, 20 lks. wide, 2 ft. deep, course E.
75.10 Road, bears E. and W.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, marked on brass cap



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.


22

Subdivision of T. 10 S., R. 26 E.

Chains


- EAST, on a random line, bet. secs. 2 and 11.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.96 Intersect N. and S. line 3 lks. S. of the cor. of secs. 1, 2, 11 and 12.
- Thence S.89°59'W., on a true line, bet. secs. 2 and 11, over rolling desert land, through scattering undergrowth.
 1.20 Wash, 20 lks. wide, 3 ft. deep, course N.80°E.
 39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
- $$\frac{1}{4} \frac{S 2}{S 11}$$
- 1917
- 79.96 The cor. of secs. 2, 3, 10 and 11.
- Land, rolling.
 Soil, gravelly; 2nd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.
-
- N.0°08'W., on a random line, bet. secs. 2 and 3.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 78.48 Intersect N. bdy. of Tp. 30 lks. W. of the cor. of secs. 2, 3, 34 and 35, reestablished as hereinbefore described.
- Thence S.0°05'W., on a true line, bet. secs. 2 and 3, over rolling desert land, through scattering undergrowth.
 38.48 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground and 12 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap
- $$\frac{1}{4} \frac{S 3}{S 2}$$
- 1917
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 66.08 Wash, 20 lks. wide, 2 ft. deep, course NE.
 78.48 The cor. of secs. 2, 3, 10 and 11.
- Land, rolling.
 Soil, rocky; 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.
-
- From the reestablished standard cor. of secs. 33 and 34, on S. bdy. of Tp., (2nd St. Par. S.,) described in Book WK. 111111,
- N.0°09'W., bet. secs. 33 and 34, over rolling hilly land, through scattering undergrowth.
 Asc.
 7.90 Top of low hill. Desc.
 12.80 Wash, 30 lks. wide, 2 ft. deep, course E.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains



and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

- 65.80 Wash, 40 lks. wide, 2 ft. deep, course E.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on brass cap




and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, hilly and rolling.
 Soil, rocky; 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

- 40.00 East, on a random line, bet. secs. 27 and 34.
- 79.94 Set temp. ¼ sec. cor.
Intersect N. and S. line at the cor. of secs. 26, 27, 34 and 35.

Thence WEST, on a true line, bet. secs. 27 and 34, over rolling desert land, through scattering undergrowth.

- 32.34 Wash, 30 lks. wide, 1 ft. deep, course NE.
- 39.97 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 60.04 Road from Willcox to Safford bears N. and S.
- 61.14 Wash, 20 lks. wide, 4 ft. deep, course NE.
- 79.94 The cor. of secs. 27, 28, 33 and 34.

Land, rolling.
 Soil, decomposed granite; 2nd and 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

- 11.00 N.0°09'W., bet. secs. 27 and 28, over rolling and hilly land, through scattering undergrowth.
- 13.60 Wash, 20 lks. wide, 3 ft. deep, course E.
- 20.00 Road, bears NE. and SW.
- 35.56 Asc. SE. slope of spur.
- 40.00 Rocky granite spur, projects E. Desc.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in a mound of stone on solid rock, for ¼ sec. cor., marked on brass cap

Chains

$\frac{1}{4}$
 S28 | S27
 1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

80.00 Thence over rolling land.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on brass cap

T10S | R26E
~~S21~~ | S22
 S28 | S27
 1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, hilly and rolling.
 Soil, rocky; 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

40.00 EAST, ON a random line, bet. secs. 22 and 27.
 Set temp. ¼ sec. cor.
 79.82 Intersect N. and S. line 4 lks. S. of the cor. of secs. 22, 23, 26 and 27.

36.32 Thence S.89°58'W., on a true line, bet. secs. 22 and 27, over rolling desert land, through scattering undergrowth.
 Wash, 20 lks. wide, 3 ft. deep, course NE.
 39.91 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

$\frac{1}{4}$ ———
 S22
 S27
 1917

and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

59.57 Road from Willcox to Safford bears N. and S.
 69.92 Wash, 15 lks. wide, 2 ft. deep, course NE.
 79.82 The cor. of secs. 21, 22, 27 and 28.


Land, rolling.
 Soil, decomposed granite; 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

7.80 N.0°09'W., bet. secs. 21 and 22, over rolling desert land, through scattering undergrowth.
 Wash, 20 lks. wide, 2 ft. deep, course E.
 30.00 Wash, 30 lks. wide, 2 ft. deep, course NE.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

$\frac{1}{4}$
 S21 | S22
 1917

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 49.30 Wash, 20 lks. wide, 2 ft. deep, course E.
 65.00 Wash, 25 lks. wide, 2 ft. deep, course E.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for cor. of secs. 15, 16, 21 and 22, marked on
 brass cap




1917

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 Land, rolling.
 Soil, decomposed granite; 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

EAST, on a random line, bet. secs. 15 and 22,
 40.00 Set a temp. ¼ sec. cor.
 79.80 Intersect N. and S. line 6 lks. S. of the cor. of secs.
 14, 15, 22 and 23.


Thence S.89°57'W., on a true line, bet. secs.15 and 22,
 over rolling desert land, through scattering undergrowth.
 3.70 Wash, 30 lks. wide, 2 ft. deep, course NE.
 39.90 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for ¼ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, 1½ ft. high,
 N. of cor.
 54.30 Wash, 20 lks. wide, 2 ft. deep, course NE.
 66.40 Road from Willcox to Safford bears N. and S.
 79.80 The cor. of secs.15, 16, 21 and 22.


Land, rolling.
 Soil, decomposed granite; 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

N.0°09'W., bet. secs. 15 and 16,
 over rolling desert land, through scattering undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for ¼ sec. cor., marked on brass cap



1917

And raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for cor. of secs. 9, 10, 15 and 16, marked on
 brass cap



1917

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

EAST, on a random line, bet. secs. 10 and 15.
40.00 Set temp. ¼ sec. cor.
79.76 Intersect N. and S. line 8 lks. S. of the cor. of secs. 10, 11, 14 and 15.

Thence S.89°57'W., on a true line, bet. secs. 10 and 15, over rolling desert land, through scattering undergrowth.
20.46 Wash, 30 lks. wide, 2 ft. deep, course NE.
39.88 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

S10
¼
S15
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
41.96 Road bears NE. and SW.
57.96 Wash, 30 lks. wide, 1 ft. deep, course N.
67.66 Road from Wallcox to Safford bears N. and S.
79.76 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.
Soil, decomposed granite; 2nd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

N.0°09'W., bet. secs. 9 and 10, over rolling land, through scattering undergrowth.
17.30 Wash, 25 lks. wide, 2 ft. deep, course NE.
35.40 Dim road bears NE. and SW.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground and 8 ins. in a mound of stone, for ¼ sec. cor., marked on brass cap

¼
S 9 | S10
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
59.00 Wash, 100 lks. wide, 3 ft. deep, course NE.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap

T10S | R26E
S4 | S3
S 9 | S10
1917

and dig pits, 18x18x12 ins., in each sec., 5½ ft. dist.

Chains

Land, rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00 EAST, on a random line, bet. secs. 3 and 10.
79.74 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line 2 lks. S. of the cor. of secs.
2, 3, 10 and 11.

39.87 Thence S. $89^{\circ}59'W.$, on a true line, bet. secs. 3 and 10,
over rolling land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ $\frac{S\ 3}{S10}$
1917

and dig pits, 18x18x12 ins., E. and W. of post, 3 ft.
dist.

70.44 Road from Willcox to Safford bears N. and S.
76.24 Wash, 100 lks. wide, 3 ft. deep, course NE.
79.74 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.
Soil, decomposed granite; 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00 N. $0^{\circ}09'W.$, on a random line, bet. secs. 3 and 4.
78.55 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. bdy. of Tp. 12 lks. E. of the reestablished
cor. of secs. 3, 4, 33 and 34, hereinbefore described.

9.45 Thence S. $0^{\circ}14'E.$, on a true line, bet. secs. 3 and 4,
38.55 over rolling desert land, through scattering undergrowth.
Road from Willcox to Safford bears N. $10^{\circ}W.$ and S. $10^{\circ}E.$
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S4 | S3
1917

and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
dist.

78.55 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.
Soil, decomposed granite; 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

From the reestablished standard cor. of secs. 32 and 33,
on S. bdy. of Tp.; (2nd St. Par. S.) described in
Book "K."
N. $0^{\circ}09'W.$, bet. secs. 32 and 33,

Chains

over rocky E. slope, on mountainous land, through scattering undergrowth.
 3.90 Desc. on broken N. slope, 65 ft.
 18.34 Bottom of gulch, course SE. Asc. 113 ft., on rocky S. slope.
 36.00 Ridge, bears NW. and SE. Desc. on N. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground and 20 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S32 | S33
 1917

from which
 A cedar, 14 ins. diam., bears N.68°E., 77 lks. dist., marked $\frac{1}{4}$ S33 BT.
 A cedar, 8 ins. diam., bears N.31°W., 158 lks. dist., marked $\frac{1}{4}$ S32 BT.
 55.60 Gulch, course E., 325 ft. below ridge. Asc. 150 ft.
 66.70 Rocky spur, projecting NE. Desc. 194 ft.
 77.50 Gulch, course E. Asc. on rocky S. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground and 16 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

T10S | R26E
 S29 | S28
 S32 | S33

1917
 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rough and mountainous.
 Soil, rocky; 4th rate.
 Timber, scattering cedar.
 Undergrowth, scrub oak.

40.00 EAST, on a random line, bet. secs. 28 and 33.
 79.94 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line 6 lks. S. of the cor. of secs. 27, 28, 33 and 34.

Thence S.89°57'W., on a true line, bet. secs. 28 and 33, over hilly land, through scattering undergrowth.
 18.40 Road, bears NE. and SW.
 23.65 Phil Von Gausig's house bears S.60°W., 14 chs. dist.
 33.30 Wash, 30 lks. wide, 1 ft. deep, course SE.
 39.97 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground and 10 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap


S28
 $\frac{1}{4}$
 S33
 1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 62.30 Asc. 115 ft., on SE. slope of spur, over mountainous land.
 72.00 Top of spur, projecting S. Desc. along S. side of same.
 79.94 The cor. of secs. 28, 29, 32 and 33.


Land, hilly and mountainous.
 Soil, rocky; 3rd rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

Chains

N.0°09'W., bet. secs. 28 and 29,
 over mountainous land, through scattering undergrowth.
 Asc. 450 ft., over rocky S. slope.
 22.50 Rocky ridge bears NE. and SW. Thence along W. slope.
 24.70 Ridge, bears NW. and SE. Desc. on NE. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of
 stone on solid rock, for $\frac{1}{4}$ sec. cor., marked on brass
 cap



1917
 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 47.40 Bottom of gulch, course E., 375 ft. below ridge. Asc.
 170 ft., on rocky SE. slope.
 68.00 Spur, projects NE. Desc. 175 ft., on N. slope.
 80.00 Point for cor. of secs. 20, 21, 28 and 29 falls on steeply
 sloping rock ledge where it is impracticable to estab-
 lish a monument. Therefore I establish a witness cor.
 as follows:
 80.10 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the
 ground and 18 ins. in a mound of stone, for witness
 cor. to the cor. of secs. 20, 21, 28 and 29, marked on
 brass cap




W C
 1917
 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, scattering cedar.
 Undergrowth, mesquite and catclaw.

EAST, from true cor. pt., on a random line, bet. secs.
 21 and 28,
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.06 Intersect N. and S. line 2 lks. S. of the cor. of secs.
 21, 22, 27 and 28.

Thence S.89°59'W., on a true line, bet. secs. 21 and 28,
 over rolling desert land, through scattering under-
 growth.
 39.50 Wash, 30 lks. wide, 2 ft. deep, course NE.
 40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



1917
 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 N. of cor.
 Asc. 160 ft., on SE. slope of spur, over mountainous land.
 Desc. 100 ft., along S. side of spur.
 52.00 Gulch, course S. Asc. 220 ft., along S. side of rocky spur.
 56.75 Top of spur projects N.80°E.; comes from S. Desc.
 79.00 Thence cor. of secs. 20, 21, 28 and 29.
 80.06

Land, E. half rolling and remainder of line mountainous.
 Soil, 3rd and 4th rate.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

30


Subdivision of T. 10 S., R. 26 E.

Chains

- N.0°09'W., bet. secs. 20 and 21, (from true cor. pt.,)
over mountainous land, through scattering undergrowth.
Desc. 225 ft., on N. slope of rocky spur.
- 14.20 Ft. of slope. Enter wash, 20 lks. wide, 2 ft. deep,
course N., comes from SW.
- 23.00 Leave same, course NE. Thence over level land.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
- | | |
|---------------|-----|
| $\frac{1}{4}$ | |
| S20 | S21 |
| 1917 | |
- and dig pits, 18x18x12 ins., N. and S. of post, 3 ft.
dist.
- 73.10 Dim road, bears NE. and SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 16, 17, 20 and 21, marked on
brass cap
- | | |
|-------|------|
| T10S | R26E |
| S17 | S16 |
| ----- | |
| S20 | S21 |
| 1917 | |
- Land, mountainous and level.
Soil, 2nd and 3rd rate; granite formation.
Timber, hackberry and mulberry trees.
Undergrowth, mesquite, catclaw and yucca.
-
- EAST, on a random line, bet. secs. 16 and 21.
- 40.00 Set temp: $\frac{1}{4}$ sec. cor.
- 80.10 Intersect N. and S. line 18 lks. S. of the cor. of secs.
15, 16, 21 and 22.
- Thence S.89°52'W., on a true line, bet. secs. 16 and 21,
over level desert land, through scattering undergrowth.
- 40.05 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
- | | |
|---------------|--|
| S16 | |
| $\frac{1}{4}$ | |
| ----- | |
| S21 | |
| 1917 | |
- and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
N. of cor.
- 76.80 Dim road, bears NE. and SW.
- 80.10 The cor. of secs. 16, 17, 20 and 21.
- Land, level.
Soil, decomposed granite; 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.
-
- N.0°09'W., bet. secs. 16 and 17,
over gently rolling desert land, through scattering
undergrowth.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
ground and 12 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor.,
marked on brass cap
- | | |
|---------------|-----|
| $\frac{1}{4}$ | |
| S17 | S16 |
| 1917 | |

Chains

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.


Land, gently rolling.
Soil, rocky; 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00 EAST, on a random line, bet. secs. 9 and 16.
Set temp. ¼ sec. cor.
80.08 Intersect N. and S. line 11 lks. N. of the cor. of secs. 9, 10, 15 and 16.

Thence N.89°55'W., on a true line, bet. secs. 9 and 16, over rolling desert land, through scattering undergrowth.

.58 Wash, 25 lks. wide, 2 ft. deep, course N.
32.58 Road, bears NE. and SW.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap




and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

80.08 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.
Soil, decomposed granite; 2nd and 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.


N.0°09'W., bet. secs. 8 and 9, over rolling desert land, through scattering undergrowth.
2.80 Wash, 100 lks. wide, 3 ft. deep, course E.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Chains

Land, rolling.
Soil, decomposed granite; 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00 EAST, on a random line, bet. secs. 4 and 9.
Set temp. $\frac{1}{4}$ sec. cor.
80.08 Intersect N. and S. line 13 lks. S. of the cor. of secs. 3, 4, 9 and 10.

40.04 Thence S. $89^{\circ}54'W.$, on a true line, bet. secs. 4 and 9, over rolling desert land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and 12 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\frac{1}{4} \begin{array}{r} S\ 4 \\ S\ 9 \\ 1917 \end{array}$$

80.08 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
The cor. of secs. 4, 5, 8 and 9.

Land, rolling.
Soil, decomposed granite; 3rd rate.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00 N. $0^{\circ}09'W.$, on a random line, bet. secs. 4 and 5.
Set temp. $\frac{1}{4}$ sec. cor.
78.76 Intersect N. bdy. of Tp. 6 lks. E. of the reestablished cor. of secs. 4, 5, 32 and 33, hereinbefore described.

38.76 Thence S. $0^{\circ}12'E.$, on a true line, bet. secs. 4 and 5, over rolling desert land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\frac{1}{4} \begin{array}{r} S5\ | \ S4 \\ 1917 \end{array}$$

39.76 and raise a mound of
Wash, course NE. Thence along same.
63.26 Leave wash, course N.; comes from SE.
64.06 Road, bears NE. and SW.
66.56 Same wash, 30 lks. wide, 1 ft. deep, course NE.
78.76 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.
Soil, 3rd rate; granite formation.
No timber.
Undergrowth, mesquite, catclaw and yucca.

From the reestablished standard cor. of secs. 31 and 32, on S. bdy. of Tp., (2nd St. Par. S.,) described in Book "K":

N. $0^{\circ}10'W.$, bet. secs. 31 and 32, over mountainous land, through scattering undergrowth. Asc. 340 ft., over rocky S. slope.

Chains

- 15.50 Ridge, bears E. and W. Desc. on N. slope.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
- $\frac{1}{4}$
S31 | S32
1917
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 50.90 Gulch, course NE., 680 ft. below ridge. Asc.
76.70 Rocky spur projects NE. Desc. on NW. slope.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground and 22 ins. in a mound of stone, for cor. of secs. 29, 30, 31 and 32, marked on brass cap
- T10S | R26E
S30 | S29

S31 | S32
1917
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- Land, mountainous.
Soil, rocky; 4th rate.
No timber.
Undergrowth, scrub oak and catclaw.
-
- 40.00 EAST, on a random line, bet. secs. 29 and 32.
Set temp. $\frac{1}{4}$ sec. cor.
80.10 Intersect N. and S. line 12 lks. S. of the cor. of secs. 28, 29, 32 and 33.
- Thence S. $89^{\circ}55'$ W., on a true line, bet. secs. 29 and 32, over rolling land, through scattering undergrowth. Asc. 25 ft., over gradual slope.
- 10.00 Saddle in low ridge bears N. and S. Desc. gradually on rolling NW. slope.
- 40.05 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
- S29
 $\frac{1}{4}$ -----
S32
1917
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
- 72.45 Wash, course N.
80.10 The cor. of secs. 29, 30, 31 and 32.
- Land, rolling and hilly.
Soil, rocky; 3rd and 4th rate.
No timber.
Undergrowth, mesquite and catclaw.
-
- 40.00 WEST, on a random line, bet. secs. 30 and 31.
Set temp. $\frac{1}{4}$ sec. cor.
79.88 Intersect W. bdy. of Tp. 9 lks. N. of the cor. of secs. 25, 30, 31 and 36, hereinbefore described.
- Thence N. $89^{\circ}56'$ E., on a true line, bet. secs. 30 and 31, over hilly land, through scattering undergrowth. Desc. 100 ft., along NE. slope.
- 24.22 Wash, 20 lks. wide, 2 ft. deep, course N. Asc. gradually.
36.02 Summit of ascent, on N. side of low hill. Desc. gradually.

Chains

39.88 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground and 22 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S30
S31
1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

46.08 Wash, 20 lks. wide, 3 ft. deep, course NE.

47.48 Dim road bears NE. and SW.

74.88 Ft. of slope of mountain bears NE. and SW. Asc. 50 ft., on NW. slope.

79.88 The cor. of secs. 29, 30, 31 and 32.

Land, hilly and mountainous.
Soil, rocky; 3rd rate.
No timber.
Undergrowth, mesquite, and catclaw.

N.0°10'W., bet. secs. 29 and 30, over mountainous land, through scattering undergrowth. Desc. 100 ft., on NW. slope.

10.00 Ft. of slope, bears NE. and SW. Thence over rolling land.

32.65 Dim road bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S30 | S29
1917

from which

tree, 38 ins. diam., bears S.72°E., 325 lks. dist., marked $\frac{1}{4}$ S29 BT.

No other bearing tree available. Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

55.00 Wash, 15 lks. wide, 3 ft. deep, course NE.

75.15 Wash, 40 lks. wide, 4 ft. deep, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap

T10S | R26E
S19 | S20
S30 | S29

1917
and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous and rolling.
Soil, 3rd rate; granite formation.
No timber.
Undergrowth, mesquite and catclaw.

EAST, on a random line, bet. secs. 20 and 29.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.88 Intersect N. and S. line at the cor. of secs. 20, 21, 28 and 29. (True cor. pt., 10 lks. S. of witness cor.)

Thence WEST, on a true line, bet. secs. 20 and 29, over mountainous land, through dense undergrowth, along rocky N. slope.

4.65 Desc. 25 ft., on rocky W. slope.

7.00 Bottom of gulch, course N. Asc. 70 ft., on rocky NE. slope.

Subdivision of T. 10 S., R. 26 E.

Chains

19.60 Spur projects N. Desc. 210 ft., on NW. slope.
 39.94 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground and 6 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ $\frac{S20}{S29}$
 1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

46.08 Road bears NE. and SW.
 47.90 Ft. of slope of butte bears NE. and SW. Asc. side of same.

51.23 Top of small rocky butte bears N. and S. Desc. rocky NW. slope.

52.38 Ft. of slope. Thence over rolling land.
 54.48 Wash, 280 lks. wide, 4 ft. deep, course NE.
 64.68 Wash, 100 lks. wide, 1 ft. deep, course NE.
 79.88 The cor. of secs. 19, 20, 29 and 30.

Land, mountainous and rolling.
 Soil, rocky; 4th rate. Granite formation.
 No timber.
 Undergrowth, scrub oak.

WEST, on a random line, bet. secs. 19 and 30.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.84 Intersect W. bdy. of Tp. 9 lks. N. of the cor. of secs. 19, 24, 25 and 30, hereinbefore described.

Thence N. $89^{\circ}56'E.$, on a true line, bet. secs. 19 and 30, over mountainous land, through dense undergrowth. Desc. 400 ft.

24.84 Ft. of slope of mountain. Thence over rolling land.
 39.84 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ $\frac{S19}{S30}$
 1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

79.84 The cor. of secs. 19, 20, 29 and 30.

Land, mountainous and rolling.
 Soil, rocky; 3rd rate. Granite formation.
 No timber.
 Undergrowth, mesquite and catclaw.

N. $0^{\circ}10'W.$, bet. secs. 19 and 20, over rolling land, through undergrowth.
 5.00 Asc. 455 ft., on S. slope of rocky ridge.
 24.67 Top of ridge bears E. and W. Desc. over N. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground and 12 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ $\frac{S19}{S20}$
 1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

50.00 Ft. of slope, 445 ft. below top of ridge. Thence over rolling land,
 60.30 Fence, bears E. and W.
 68.00 Asc. 250 ft., on rocky S. slope of butte.

Chains

76.40 Top of spur of butte projects W. Desc. 113 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground and 14 ins. in a mound of stone, for cor. of secs. 17, 18, 19 and 20, marked on brass cap

T10S	R26E
S18	S17
S19	S20

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling and mountainous.
 Soil, rocky; 3rd and 4th rate.
 No timber.
 Undergrowth, mesquite and catclaw.

40.00 EAST, on a random line, bet. secs. 17 and 20.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.90 Intersect N. and S. line 14 lks. N. of the cor. of secs. 16, 17, 20 and 21.

Thence N. $89^{\circ}54'$ W., on a true line, bet. secs. 17 and 20, over rolling land, through undergrowth.
 18.40 Wash, 100 lks. wide, 2 ft. deep, course N. 20° E.
 39.40 Wash, 50 lks. wide, 1 ft. deep, course N. Asc.
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S17

 $\frac{1}{4}$

S20

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

A hackberry tree, 10 ins. diam., bears N. 71° E., marked $\frac{1}{4}$ S17 BT.
 No other bearing tree available.

52.70 Rocky spur, projects SE., 100 ft. above wash. Desc. 100 ft.

73.00 Asc. 90 ft., over SE. slope.

78.40 Spur, projects NE.

79.90 The cor. of secs. 17, 18, 19 and 20.

Land, mountainous and rolling.
 Soil, rocky; 3rd and 4th rate.
 No timber. A few hackberry trees.
 Undergrowth, mesquite, catclaw and yucca.

40.00 WEST, on a random line, bet. secs. 18 and 19.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.65 Intersect W. bdy. of Tp. 12 lks. S. of the cor. of secs. 13, 18, 19 and 24, hereinbefore described.

Thence S. $89^{\circ}55'$ E., on a true line, bet. secs. 18 and 19, over rolling land, through undergrowth.

17.15 Wash, 20 lks. wide, 2 ft. deep, course N.

39.65 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S18

 $\frac{1}{4}$

S19

1917

and dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.


61.65 Wash, 20 lks. wide, 1 ft. deep, course N.

Chains

62.65 Asc. 180 ft., along NW. slope of spur, over mountainous land.
79.65 The cor. of secs. 17, 18, 19 and 20.

Land, mountainous and rolling.
Soil, rocky; 3rd rate. Granite formation.
No timber.
Undergrowth, mesquite, catclaw and yucca.


10.00 N.0°10'W., bet. secs. 17 and 18,
40.00 over mountainous land, through undergrowth. Desc.
150 ft., on NW. slope of butte.
Ft. of steep slope. Desc. gradually, over rolling land.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for ¼ sec. cor., marked on brass cap



1917

and raise a mound of stone, 2 ft. base, 1½ ft. high,
W. of cor.

72.40 Road bears NE. and SW.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 7, 8, 17 and 18, marked on
brass cap




1917

and raise a mound of stone, 2 ft. base, 1½ ft. high,
W. of cor.

Land, mountainous and rolling.
Soil, rocky; 3rd rate. Granite formation.
No timber.
Undergrowth, mesquite, catclaw and yucca.

40.00 EAST, on a random line, bet. secs. 8 and 17.
79.98 Set temp. ¼ sec. cor.
Intersect N. and S. line 12 lks. N. of the cor. of secs.
8, 9, 16 and 17.

4.00 Thence N.89°55'W., on a true line, bet. secs. 8 and 17,
39.99 over rolling desert land, through undergrowth.
Wash, 100 lks. wide, 4 ft. deep, course NE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for ¼ sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base, 1½ ft. high,
N. of cor.

64.33 Road, bears NE. and SW.
79.98 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.
Soil, rocky; 3rd rate. Granite formation.
No timber.
Undergrowth, mesquite, catclaw and yucca.

Chains

40.00 WEST, on a random line, bet. secs. 7 and 18.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.51 Intersect W. bdy. of Tp. 6 lks. N. of the cor. of secs. 7, 12, 13 and 18, hereinbefore described.

Thence N.89°57'E., on a true line, bet. secs. 7 and 18, over mountainous land, through undergrowth, along S. side of spur of mountain.

30.00 Spur, slopes S. Begin descent.
 39.51 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground and 20 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap,

$$\begin{array}{r} \frac{1}{4} \quad S \quad 7 \\ \hline S18 \\ 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

70.10 Ft. of slope. Wash, 50 lks. wide, 2 ft. deep, course N., 480 ft. below spur. Thence over rolling land.
 79.51 The cor. of secs. 7, 8, 17 and 18.

Land, mountainous and rolling.
 Soil, 3rd and 4th rate.
 Timber, scattering scrub cedar.
 Undergrowth, catclaw and yucca.

26.20 N.0°10'W., bet. secs. 7 and 8,
 over rolling land, through undergrowth.
 40.00 Wash, 50 lks. wide, 4 ft. deep, course N.20°E.
 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground and 10 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \\ S7 \quad | \quad S8 \\ \hline 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

40.90 Wash, 75 lks. wide, 10 ft. deep, course E.
 61.00 Asc. 200 ft., on SE. slope of rocky spur of mountain.
 74.86 Top of ridge bears E. and W. Desc. 50 ft., on NE. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground to rock and 22 ins. in a mound of stone, for cor. of secs. 5, 6, 7 and 8, marked on brass cap

$$\begin{array}{r} T10S \quad | \quad R26E \\ \hline S6 \quad | \quad S5 \\ \hline S7 \quad | \quad S8 \\ \hline 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, rolling and mountainous.
 Soil, rocky; 3rd and 4th rate. Granite formation.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

40.00 EAST, on a random line, bet. secs. 5 and 8.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.10 Intersect N. and S. line 9 lks. N. of the cor. of secs. 4, 5, 8 and 9.

Thence N.89°56'W., on a true line, bet. secs. 5 and 8, over rolling desert land, through undergrowth.

Subdivision of Township 10 South, Range 26 East.

39.

Chains.

- 3.40 Wash, 25 lks. wide, 2 ft. deep, course N.
- 14.00 Road brs. NE. and SW.
- 32.60 Wash, 20 lks. wide, 2 ft. deep, course NE.
- 40.05 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap,

$\frac{1}{4}$ S 5
 $\frac{1}{4}$ S 8
 1917

- 45.00 Wash, 100 lks. wide, 2 ft. deep, course N. Ascend along E. slope of spur, 170 ft., over mountainous land.
- 60.00 Top of spur, brs. NE. Ascend along same 210 ft.
- 80.10 The cor. of secs. 5, 6, 7 and 8.
 Land, rolling and mountainous.
 Soil, 3rd and 4th rate; granite formation.
 No timber.
 Undergrowth, mesquite, catclaw and yucca.

- 40.00 WEST, on a random line, bet. secs. 6 and 7.
 Set temp. $\frac{1}{4}$ sec. cor.
- 79.40 Intersect W. bdy. of Tp. 2 lks. N. of the cor. of secs. 1, 6, 7 and 12, hereinbefore described.
 Thence,
 N. 89° 59' E., on a true line, bet. secs. 6 and 7.
 Over mountainous land, thru scattering timber and undergrowth. Ascend along steep NW. slope.
- 6.90 Top of bluff, 60 ft. high, facing W.
- 32.00 Top of ridge, brs. E. and SW., 600 ft. above sec. cor.
 Thence along top of ridge.
- 39.40 Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap,

$\frac{1}{4}$ S 6
 $\frac{1}{4}$ S 7
 1917

- and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
- 46.10 Leave top of ridge, brs. S. 80° E. and W. Descend 750 ft., over rocky NE. slope.
- 79.40 The cor. of secs. 5, 6, 7 and 8.
 Land, mountainous.
 Soil, rocky, 4th rate.
 Timber, cedar.
 Undergrowth, scrub oak, catclaw and yucca.

- 40.00 N. 0° 10' W., on a random line, bet. secs. 5 and 6.
 Set temp. $\frac{1}{4}$ sec. cor.
- 78.60 Intersect N. bdy. of Tp. 12 lks. W. of the cor. of secs. 5, 6, 31 and 32, reestablished as hereinbefore described.
 Thence,
 S. 0° 05' E., on a true line, bet. secs. 5 and 6.
 Over mountainous land, thru undergrowth; ascend 50 ft. over N. slope of spur.
- 3.30 Top of spur, slopes NW. Thence along top of same.
- 21.50 Leave top of spur, sloping N.; comes from SW. Descend 110 ft. to ravine.
- 35.30 Bottom of ravine, course NE.
- 38.60 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap,

$\frac{1}{4}$ S 6 | S 5
 1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

40. Subdivision of Township 10 North Range 26 West.

Chains.				
52.00	Ascend 300 ft. on NE. slope.			
78.60	the cor. of secs. 5, 6, 7 and 8.			
	Land, mountainous.			
	Soil, rocky, 3rd and 4th rate.			
	No timber.			
	Undergrowth, low scrub mesquite, catclaw and yucca.			

Boundaries of Township 10 South, Range 26 East. Latitudes, departures, and closing errors.				

Line designated,	True course.	Dist.	Latitudes.	Departures.
			N. S.	E. W.
South bdy. (2nd. Std. Par. S)	West,	480.00		480.00
West boundary,	N. 0° 7' W.	478.76	478.76	1.00
North boundary,	East,	479.54		479.54
East boundary,	S. 0° 10' E.	319.04	319.04	.90
	S. 0° 1' E.	79.76	79.76	.03
	South,	79.64	79.64	
Convergency,				.46
	Totals,		478.76 478.44	480.93 481.00
			478.44	480.93
	Error in latitude,		0.32	
	Error in departure,			0.07

GENERAL DESCRIPTION.LOCATION:

This township is located in the SE. portion of the State of Arizona at the foot of east slope of the Pinaleno Mts., about 26 miles NE. from the town of Wilcox, Arizona.

SURFACE:

The east five tiers of sections are rolling, desert land, draining northeast. The west tier of secs. is mountainous, hilly and rolling.

SOIL:

The soil of the greater part of the township is gravelly and rocky, 2nd and 3rd rate. In the west tiers of secs., the soil is rocky, 3rd and 4th rate.

VEGETATION:

The only timber consists of a scattering growth in the west tier of secs. Over the remainder of the township a scattering undergrowth of scrub mesquite, scrub oak, catclaw and yucca prevails. A fair growth of grass suitable for grazing exists in all parts of the township.

WATER:

There are no natural springs or permanent running water in the township. Good water is obtained from a well in SE. $\frac{1}{4}$ of sec. 24, known as "Gleason's Well," and from another well in SW $\frac{1}{4}$ of sec. 33.

MINERALS:

No evidence of valuable mineral deposits exists in any part of the township.

SETTLERS:

Only one settler is located in the township, Phil Von Gausig in NE $\frac{1}{4}$ of sec. 33.

IMPROVEMENTS:

Several roads traverse the township. House and corral in sec. 33, fence in secs. 19 and 20, and wells in secs. 24 and 33 are the only improvements observed.

BOOK 3015

Book "L"

Group 63 - - - Arizona.
4-680

Township 10 South, Range 26 East.

DATE DIAGRAM

							RESURVEYED						
		5-31-17	5-31-17	5-31-17	5-30-17	5-30-17	5-30-17	5-30-17	5-30-17	5-30-17			
6-6-17	6	6-12-17	5	6-13-17	4	6-13-17	3	6-13-17	2	6-8-17	1	5-29-17	
6-1-17	7	6-11-17	8	6-12-17	9	6-9-17	10	6-8-17	11	6-8-17	12	5-29-17	
6-1-17	18	6-11-17	17	6-11-17	16	6-9-17	15	6-9-17	14	6-2-17	13	5-29-17 RESURVEYED	
6-1-17	19	6-4-17	20	6-4-17 6-5-17	21	6-7-17	22	6-7-17	23	6-2-17	24	5-29-17 RESURVEYED	
6-1-17	30	5-25-17	29	6-5-17	28	6-7-17	27	6-7-17	26	6-6-17	25	5-29-17	
5-25-17	31	6-4-17	32	6-5-17	33	6-7-17	34	6-6-17	35	6-2-17	36	5-29-17	

2nd Standard Parallel South						
6	5	4	3	2	1	6-2764

Surveys and resurveys executed on dates shown in blue on above diagram, by W. B. Kimmel, U. S. Surveyor.

CERTIFICATE OF UNITED STATES SURVEYOR.

I, WILLIAM B. KIMMEL, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for Group 63, Arizona, bearing date of the 7th day of October, 1915, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the West boundary and subdivision lines of TOWNSHIP 10 SOUTH, RANGE 26 EAST, and resurveyed all those parts or portions of the North boundary of TOWNSHIP 10 SOUTH, RANGE 26 EAST, and of the West boundary of TOWNSHIP 10 SOUTH, RANGE 27 EAST.

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Group 63, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

William B. Kimmel, U. S. Surveyor.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL, Phoenix, Arizona, April 29, 1918.

The foregoing field notes of the survey of the West boundary and subdivision lines of Township 10 South, Range 26 East, and the resurvey of the North boundary of Township 10 South, Range 26 East, and of the West boundary of Township 10 South, Range 27 East, all of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by William B. Kimmel, U. S. Surveyor, under his special instructions for Group 63, Arizona, dated Oct. 7, 1915, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys and resurveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.