

3025

Book "J."

4-679

G.L.O. letter "E"  
March 29, 1919.

57

(1)

(Subdivisions)

BOOK 3025

# FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISIONAL LINES

of

TOWNSHIP 11 NORTH, RANGE 16 WEST,

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

Alexander T. Harris, and John Gonin

U. S. Transitmen,

~~In the capacity of U. S. Surveyor~~, under instructions dated February 13., 1915,  
issued by the United States Surveyor General to govern surveys included in  
Group No. 48, which were approved by the Commissioner of the General Land  
Office, February 26., 1915.

Survey commenced February 7., 1916.

Survey completed February 28., 1916.

3025

3025

58  
1A

BOOK 3025

Book "J."  
Group 48 - - Arizona.

Township 11 North, Range 16 West.

## INDEX DIAGRAM.

		Township 11 North, Range 16 West.										
		6	30	5	23	4	17	8	12	2	7	1
		30		30		22		17		12		6
West		7	29	8	22	9	16	10	11	11	6	12
		29		28		21		16		11		5
Meridian		18	28	17	21	16	15	15	10	14	5	13
		27		27		20		15		10		4
Guide		19	26	20	20	21	15	22	9	23	4	24
		26		25		19		14		9		3
4th		30	25	29	19	28	14	27	8	26	3	25
		24		24		19		13		8		2
		31	23	32	18	33	13	34	7	35	2	36

T. 11 N. R. 16 W.

————— Surveyed under this Group. Notes in this book.

————— Surveyed under this Group. Notes in Book "A."

————— Surveyed under this Group. Notes in Book "H."

————— Surveyed under this Group. Notes in Book "I."

————— Surveyed under this Group. Notes in Book "K."

————— Surveyed under this Group. Notes in Book "L."

Book "J"

Group 48 - - - Arizona

Township 11 North, Range 16 West,

DATE DIAGRAM.

	2-23-16	2-23-16	2-23-16	2-22-16	2-22-16	2-22-16
2-11-16	6 2-10-16	5 2-10-16	4 2-28-16	3 2-28-16	2 2-24-16	1 2-24-16
2-11-16	7 2-8-16	8 2-10-16	9 2-10-16	10 2-17-16	11 2-17-16	12 2-18-16
2-5-16	18 2-8-16	17 2-8-16	16 2-9-16	15 2-10-16	14 2-16-16	13 2-16-16
2-5-16	19 2-8-16	20 2-8-16	21 2-9-16	22 2-9-16	23 2-16-16	24 2-16-16
2-5-16	30 2-8-16	29 2-8-16	28 2-9-16	27 2-9-16	26 2-16-16	25 2-16-16
2-5-16	31 2-7-16	32 2-8-16	33 2-9-16	34 2-9-16	35 2-16-16	36 2-16-16
	11-10-15	11-10-15	11-10-15	11-11-15	11-11-15	2-15-16

Lines dated in red were surveyed by Alexander T. Harris, U. S. Transitman.

Lines dated in blue were surveyed by John Gonin, U. S. Transitman.

Surveyed under this group. Refer in book "I."

Surveyed under this group. Refer in book "I."

Surveyed under this group. Refer in book "I."

Surveyed under this group. Refer in book "I."

## 2. Subdivision of T. 11 N., R. 16 W.

Chains.

Surveys hereinafter described were executed by Alexander T. Harris and John Gonin, U. S. Transitmen, on dates shown on page 1 hereof, using Young and Sons' light mountain transits Nos. 8611 and 8492, respectively, described with certificates of approval and tests in Books "A" and "B," respectively.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., which is an iron post, described in Book "A."

N.0° 1' W., bet. secs. 35 and 36.

Over level bottom land, through dense undergrowth.

3.10

Road, brs. E. and W.

12.75

Rail fence, brs. E. and W.

18.20

Four wire fence, brs. E. and W.

22.70

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, on the left bank of the Bill Williams River, brs. E. and W., for witness cor. to  $\frac{1}{2}$  sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} \\ W|C \\ S35|S36 \\ 1916 \end{array}$$

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

40.00

True point for  $\frac{1}{2}$  sec. cor. falls where the cor. would be destroyed.

40.50

Left bank of Bill Williams River, brs. E. and W. Thence across Bill Williams River, 1 ft. deep, course W.

45.50

Right bank of Bill Williams River, brs. E. and W. Thence across bottom land.

55.50

Leave River bottom

61.84

Road, brs. NE. and SW.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on brass cap

$$\begin{array}{c} T11N R16W \\ S26 \quad S25 \\ \hline S35 \quad S36 \\ 1916 \end{array}$$

$$\begin{array}{c} S35 \quad S36 \\ 1916 \end{array}$$

and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, level river bottom.

Soil, sandy; 1st rate.

Timber, cottonwood.

Undergrowth, mesquite, arrow-weed and sagebrush.

East on a random line, bet. secs. 25 and 36.

40.00

Set temp.  $\frac{1}{2}$  sec. cor.

80.02

Intersect E. bdy. of Tp., 9 lks. S. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, described in Book "A."

Thence

S.89° 56' W., on a true line, bet. secs. 25 and 36.

Over level bottom land, through dense undergrowth.

23.00

Fence, brs. N. and S.

25.00

From this point, E. T. Miner's house brs. N. 5 chs. dist.


29.50

Fence, brs. N. and S.

40.01


Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for  $\frac{1}{2}$  sec. cor., marked on brass cap

Chains.




and raise a mound of stone, 2 ft. base, 1½ ft. high,  
N. of cor.  
50.00 Leave bottom land, brs. N. and S. Asc. 70 ft. to  
54.05 Top of ascent, brs. N. and S. Thence over rolling land.  
80.02 The cor. of secs. 25, 26, 35 and 36.  
Land, E. half mile, level; W. half mile, rolling.  
Soil, E. half mile, 1st rate; W. half mile, 3rd rate.  
No timber.  
Undergrowth, greasewood, palo verde, cactus, ocotillo  
and cat claw.

N.0° 1' W., bet. secs. 25 and 26.  
Over broken land, through scattering undergrowth.  
17.70 Asc. 20 ft. to  
22.70 Desc. 40 ft. to  
27.65 Enter wash, 5 ft. bank, course SW.  
32.65 Leave wash, 5 ft. bank, course SW. Thence over gently  
rolling land.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for ¼ sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2½ ft. high,  
W. of cor.  
80.00 Asc. gradually 60 ft. to  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 23, 24, 25 and 26, marked on  
brass cap



and raise a mound of stone, 3 ft. base, 2½ ft. high,  
W. of cor.  
Land, broken and gently rolling.  
Soil, gravelly; 3rd rate.  
No timber.  
Undergrowth, palo verde, greasewood and sagebrush.  
Drainage, S.

40.00 N.89° 56' E., on a random line, bet. secs. 24 and 25.  
Set temp. ¼ sec. cor.  
79.96 Intersect E. bdy. of Tp., 9 lks. S. of the cor. of secs.  
19, 24, 25 and 30, which is an iron post, described in  
Book "A."  
Thence  
S.89° 52' W., on a true line, bet. secs. 24 and 25.  
Over rolling land, through scattering undergrowth.  
Desc. 35 ft. to  
1.45 Wash, course SW. Asc. 85 ft. to  
3.36 Thence over gently rolling land.  
39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

4.

Subdivision of T. 11 N., R. 16 W.

Chains

ground, for 1/4 sec. cor., marked on brass cap

S24



S25  
1916


and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
N. of cor.

- 50.56 Desc. 30 ft. to
- 53.14 Ravine, course S. Asc. 30 ft. to
- 55.56 Thence over gently rolling land.
- 73.76 Wash, course S.
- 79.96 The cor. of secs. 23, 24, 25 and 26.

Land, rolling and gently rolling.  
Soil, 3rd rate.  
No timber.  
Undergrowth, cactus, greasewood, palo verde, ocotillo,  
cat claw and mesquite.


N.0° 1' W., bet. secs. 23 and 24.  
Over rolling land, through scattering undergrowth.

- 10.00 Desc. 25 ft. to
- 15.00 Wash, course SE. Asc. 30 ft. to
- 20.00 Thence over gently rolling land.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2 1/2 ft. high,  
W. of cor.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 13, 14, 23 and 24, marked on  
brass cap




and raise a mound of stone, 3 ft. base, 2 1/2 ft. high,  
W. of cor.

Land, rolling and gently rolling.  
Soil, gravelly; 3rd rate.  
No timber.  
Undergrowth, palo verde, greasewood, and sagebrush.  
Drainage, S. and SW.

- 40.00 N. 89° 52' E., on a random line, bet. secs. 13 and 24.  
Set temp. 1/4 sec. cor.
- 79.89 Intensect E. bdy. of Tp., 7 lks. S. of the cor. of secs.  
13, 18, 19 and 24, which is an iron post, described in  
Book "A."
- Thence  
S. 89° 49' W., on a true line, bet. secs. 13 and 24.  
Over gently rolling land, through scattering undergrowth.
- 39.94 1/2 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., marked on brass cap

Chains.

S13



S24  
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

57.60  
77.60  
79.89


Wash, course S.  
Wash, course S.  
The cor. of secs. 13, 14, 23 and 24.  
Land, gently rolling.  
Soil, 3rd rate.

No timber.  
Undergrowth, cactus, palo verde, ocotillo, greasewood, mesquite and cat claw.

N.0° 1' W., bet. secs. 13 and 14.

12.10  
40.00


Over rolling land, through scattering undergrowth.  
Enter wash, course S.20° E. Comes from N.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

50.00  
80.00

Leave wash, course S. Comes from NE. Asc. 50 ft. to  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked on brass cap



and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.  
Soil, gravelly; 3rd rate.  
No timber.  
Undergrowth, palo verde, greasewood, sagebrush and cactus.  
Drainage, S. and SW.

N.89° 49' E., on a random line, bet. secs. 12 and 13.

40.00  
79.83

Set temp. 1/4 sec. cor.  
Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, described in Book "A."

Thence

S.89° 52' W., on a true line, bet. secs. 12 and 13.  
Over rolling land, through scattering undergrowth.

7.00  
11.95  
16.50  
21.40  
25.70  
39.91 1/2

Asc. 45 ft. to  
Desc. 35 ft. to  
Asc. 45 ft. to  
Desc. 55 ft. to  
Asc. 30 ft. to  
Desc. 50 ft. to  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap


6. Subdivision of T. 11 N., R. 16 W.

Chains.


S12  
 $\frac{1}{4}$   
 S13  
 1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.  
 Thence over gently rolling land.  
 47.30 Enter wash, course S.  
 57.30 Leave wash, course S.  
 79.83 The cor. of secs. 11, 12, 13 and 14.  
 Land, rolling and gently rolling.  
 Soil, 4th rate.  
 No timber.  
 Undergrowth, cactus, greasewood, ocotillo and palo verde.

N.0° 1' W., bet. secs. 11 and 12.  
 Over rolling land, through scattering undergrowth.  
 Desc. 25 ft. to  
 5.00 Asc. 45 ft. to  
 22.10 Desc. 25 ft. to  
 32.10 Asc. 45 ft. to  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the  
 ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on  
 brass cap



and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W.  
 of cor. Thence over gently rolling land.  
 65.00 Asc. 110 ft. to  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 1, 2, 11 and 12, marked on  
 brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, rolling.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, greasewood, palo verde, mesquite, cactus,  
 ocotillo, cat claw and ironwood.

40.00 N.89° 52' E., on a random line, bet. secs. 1 and 12.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.90 Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs.  
 1, 6, 7 and 12, which is an iron post, described in  
 Book "A."  
 Thence  
 S.89° 50' W., on a true line, bet. secs. 1 and 12.  
 Over rolling land, through scattering undergrowth.  
 Asc. 50 ft. to  
 9.65 Desc. 30 ft. to  
 16.90 Wash, course S. Asc. 100 ft. to  
 36.90 Desc. 40 ft. to  
 39.95 Set a iron post, 3 ft. long, 1 in dia., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




Chains.	
<p>50.90 63.60 74.90 79.90</p>	<p style="text-align: center;">S 1 <math>\frac{1}{4}</math> S12 1916</p> <p>and raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, N. of cor. Asc. 45 ft. to Desc. 55 ft. to Asc. 40 ft. to Desc. 40 ft. to The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, 3rd rate. No timber. Undergrowth, greasewood, palo verde, cactus, ocotillo, cat claw, mesquite and iron wood.</p>
<p>40.00 80.32  6.72 35.32 40.32</p>	<p>N.0° 1' W., on a random line, bet. secs. 1 and 2. Set temp. <math>\frac{1}{4}</math> sec. cor. Intersect N. bdy. of Tp., 11 lks. E. of the cor. of secs. 1, 2, 35 and 36, which is an iron post, described in Book "A." Thence S.0° 6' E., on a true line, bet. secs. 1 and 2. Over rolling land, through scattering undergrowth. Wash, course SW. Asc. 30 ft. to Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., marked on brass cap</p>
<p>48.87 53.82 55.32 70.32 80.32</p>	<p style="text-align: center;"><math>\frac{1}{4}</math> S2 S1 1916</p> <p>and raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor. Desc. 60 ft. to Asc. 30 ft. to Desc. 45 ft. to Enter wash, course SW. Leave wash, course SW. Asc. slightly to The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, 3rd rate. No timber. Undergrowth, greasewood, ocotillo, palo verde, mesquite, cat claw and ironwood.</p>
<p>7.86 15.50 40.00 55.50</p>	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., which is an iron post. described in Book "A." N.0° 1' W., bet. secs. 34 and 35. Over rolling land, through scattering timber and under- growth. Desc. 55 ft. to Left bank of Bill Williams River, 15 ft. high, brs. E. and W. Thence across Bill Williams River, 1 ft. deep, course W. Right bank of Bill Williams River, brs. E. and W. Thence over level bottom land. True point for <math>\frac{1}{4}</math> sec. cor. falls in dry bed of Bill Williams River. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the</p>

8. Subdivision of T. 11 N., R. 16 W.

Chains.



ground, for witness cor. to  $\frac{1}{4}$  sec. cor., marked on brass cap



dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 True point for cor. of secs. 26, 27, 34 and 35 falls in bed of Bill Williams River, where it would be destroyed.

80.30 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to cor. of secs. 26, 27, 34 and 35, marked on brass cap



and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and level.

Soil, sandy; 1st rate.

Timber, cottonwood.

Undergrowth, mesquite, arrow-weed and cat claw.

From the true point for cor. of secs. 26, 27, 34 and 35, East on a random line, bet. secs. 26 and 35.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 25, 26, 35 and 36.

Thence


N.  $89^{\circ} 56'$  W., on a true line, bet. secs. 26 and 35.

Over gently rolling land, through scattering undergrowth.

18.78 Enter wash, 5 ft. bank, course S.

35.75 Leave wash, course S.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

80.00 The true point for cor. of secs. 26, 27, 34 and 35.

Land, gently rolling.

Soil, gravelly; 3rd rate.

No timber.

Undergrowth, ironwood, greasewood, sagebrush and cat claw.

Drainage, S.

From the true point for cor. of secs. 26, 27, 34 and 35, N.  $0^{\circ} 11'$  W., bet. secs. 26 and 27.

0.30 Over rolling land, through scattering undergrowth.

0.30 The witness cor. to cor. of secs. 26, 27, 34 and 35.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Subdivision of T. 11 N., R. 16 W.

Chains.

$\frac{1}{4}$   
 S27 | S26  
 1916

and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,  
 W. of cor.  
 Asc. gradually to  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 22, 23, 26 and 27, marked on  
 brass cap

T11N R16W  
 S22 | S23  
 -----  
 S27 | S26  
 1916

and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, ironwood, greasewood, and sage-  
 brush.  
 Drainage, S.

40.00 S.  $89^{\circ} 56'$  E., on a random line, bet. secs. 23 and 26.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.90 Intersect N. and S. line, 7 lks. S. of the cor. of secs.  
 23, 24, 25 and 26.  
 Thence  
 N.  $89^{\circ} 59'$  W., on a true line, bet. secs. 23 and 26.  
 Over rolling and broken land, through scattering under-  
 growth.  
 29.90 Enter wash, course S.  
 39.90 Leave wash, course S.  
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S23  
 $\frac{1}{4}$  ———  
 S26  
 1916

and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,  
 N. of cor.  
 44.75 Enter wash, course S.  
 48.75 Leave wash, 5 ft. bank, course S.  
 79.90 The cor. of secs. 22, 23, 26 and 27.  
 Land, rolling and broken.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, greasewood, palo verde and sagebrush.  
 Drainage, S.

19.67 N.  $0^{\circ} 1'$  W., bet. secs. 22 and 23.  
 Over rolling land, through scattering undergrowth.  
 40.00 Enter wash, 2 ft. bank, course SW.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S22 | S23  
 1916

10. Subdivision of T. 11 N., R. 16 W.

Chains.

50.00 and raise a mound of stone, 3 ft. base, 2½ ft. high,  
 W. of cor.  
 80.00 Leave wash, 2 ft. bank, course S. Comes from NE.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 14, 15, 22 and 23, marked on  
 brass cap

T11N R16W  
 S15 S14

S22 S23  
 1916

and raise a mound of stone, 3 ft. base, 2½ ft. high,  
 W. of cor.  
 Land, rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, greasewood, palo verde, ironwood, sagebrush  
 and cat claw.  
 Drainage, S.

40.00 S.89° 59' E., on a random line, bet. secs. 14 and 23.  
 79.90 Set temp. ¼ sec. cor.  
 79.90 Intersect N. and S. line, 2 lks. N. of the cor. of secs.  
 13, 14, 23 and 24.  
 Thence  
 39.95 N.89° 58' W., on a true line, bet. secs. 14 and 23.  
 Over gently rolling land, through scattering undergrowth.  
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for ¼ sec. cor., marked on brass cap

S14

¼  
 S23  
 1916

79.90 and raise a mound of stone, 3 ft. base, 2½ ft. high,  
 N. of cor.  
 79.90 The cor. of secs. 14, 15, 22 and 23.  
 Land, gently rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood and sagebrush.  
 Drainage, S.

19.30 N.0° 1' W., bet. secs. 14 and 15.  
 29.20 Over rolling land, through scattering undergrowth.  
 29.20 Enter wash, 5 ft. bank, course SW.  
 40.00 Leave wash, 2 ft. bank, course SW.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for ¼ sec. cor., marked on brass cap


¼  
 S15 S14  
 1916

75.00 and raise a mound of stone, 3 ft. base, 2½ ft. high,  
 W. of cor.  
 80.00 Thence across wash, course S.20° E. Comes from N.  
 80.00 Leave wash, course S. Comes from NE.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 10, 11, 14 and 15, marked on  
 brass cap

Subdivision of T. 11 N., R. 16 W.

11.

Chains.




and raise a mound of stone, 3 ft. base, 2½ ft. high,  
 W. of cor.  
 Land, rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, ironwood, greasewood, sagebrush  
 and cactus.

40.00  
79.98

S.89° 58' E., on a random line, bet. secs. 11 and 14.  
 Set temp. ¼ sec. cor.  
 Intersect N. and S. line, 5 lks. S. of the cor. of secs.  
 11, 12, 13 and 14.

39.99

Thence  
 West on a true line, bet. secs. 11 and 14.  
 Over gently rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for ¼ sec. cor., marked on brass cap




47.92  
62.92  
72.88  
79.98

and raise a mound of stone, 3 ft. base, 2½ ft. high,  
 N. of cor.  
 Thence across wash, course SW.  
 Leave wash, 2 ft. bank, course SW.  
 Enter wash, course SW.  
 Leave wash, 2 ft. bank, course SW.  
 The cor. of secs. 10, 11, 14 and 15.  
 Land, gently rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, ironwood, greasewood and sage-  
 brush.


40.00

N.0° 1' W., bet. secs. 10 and 11.  
 Over gently rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for ¼ sec. cor., marked on brass cap



80.00

and raise a mound of stone, 3 ft. base, 2½ ft. high,  
 W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 2, 3, 10 and 11, marked on  
 brass cap



## 12. Subdivision of T. 11 N., T. 16 W.

chains.

	<p>and raise a mound of stone, 3 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of cor. Land, gently rolling. Soil, gravelly; 3rd rate. No timber. Undergrowth, palo verde, greasewood and sagebrush. Drainage, S. and SW.</p>
40.00 79.94	<p>East on a random line, bet. secs. 2 and 11. Set temp. <math>\frac{1}{4}</math> sec. cor. Intersect N. and S. line, 2 lks. S. of the cor. of secs. 1, 2, 11 and 12. Thence S. <math>89^{\circ} 59'</math> W., on a true line, bet. secs. 2 and 11. Over gently rolling land, through scattering undergrowth. Enter wash, 5 ft. bank, course SW. Leave wash, 4 ft. bank, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., marked on brass cap</p>
1.40 14.94 39.97	<p style="text-align: center;">S 2 <math>\frac{1}{4}</math> ——— S11 1916</p>
61.94 70.44 79.94	<p>and raise a mound of stone, 3 ft. base, <math>2\frac{1}{2}</math> ft. high, N. of cor. Enter wash, 5 ft. bank, course SW. Leave wash, 2 ft. bank, course SW. The cor. of secs. 2, 3, 10 and 11. Land, gently rolling. Soil, gravelly; 3rd rate. No timber. Undergrowth, greasewood, palo verde and sagebrush. Drainage, S. and SW.</p>
40.00 80.35	<p>N. <math>0^{\circ} 1'</math> W., on a random line, bet. secs. 2 and 3. Set temp. <math>\frac{1}{4}</math> sec. cor. Intersect N. bdy. of Tp., 11 lks. E. of the cor. of secs. 2, 3, 34 and 35, which is an iron post, described in Book "A."</p>
40.35	<p>Thence S. <math>0^{\circ} 6'</math> E., on a true line, bet. secs. 2 and 3. Over gently rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., marked on brass cap</p>
	<p style="text-align: center;"><math>\frac{1}{4}</math> S3   S2 1916</p>
45.53 77.65 80.35	<p>and raise a mound of stone, 3 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of cor. Wash, 50 lks. wide, 5 ft. deep, course S. <math>20^{\circ}</math> W. Center of wash, 1 ch. wide, 5 ft. deep, course SW. The cor. of secs. 2, 3, 10 and 11. Land, gently rolling. Soil, gravelly; 3rd rate. No timber. Undergrowth, palo verde, greasewood and sagebrush. Drainage, S. and SW.</p>

Subdivision of T. 11 N., R. 16 W.

Chains.


From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., which is an iron post, described in Book "A", N.0° 2' W., bet. secs. 33 and 34.

Over broken land, through scattering undergrowth. Desc. to

16.18 Old road, brs. N.80° W. and S.80° E.

Enter bottom land, brs. E. and W. Thence over level land, through dense undergrowth.

17.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for witness cor. to 1/4 sec. cor., marked on brass cap



dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

17.50 Left bank of Bill Williams River, brs. E. and W. Thence across Bill Williams River, 2 ft. deep, course W.



21.50 Leave water, brs. E. and W. Thence across dry bed of Bill Williams River.

40.00 True point for 1/4 sec. cor. falls in dry bed of Bill Williams River.

80.00 True point for cor. of secs. 27, 28, 33 and 34, falls in dry bed of Bill Williams River.

89.00 Leave Bill Williams River, course W. Bank 4 ft. high. Thence over level bottom land to

89.60 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to cor. of secs. 27, 28, 33 and 34, marked on brass cap



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, level and broken.

Soil, 4th rate on slopes; sandy, 3rd rate on level.

No timber.

Undergrowth, palo verde, cactus, greasewood and cat claw.

Drainage, N.

40.00 From the true point for cor. of secs. 27, 28, 33 and 34. East on a random line, bet. secs. 27 and 34.

79.90 Set temp. 1/4 sec. cor.

Intersect N. and S. line, 7 lks. N. of the true point for cor. of secs. 26, 27, 34 and 35.

Thence

N.89° 57' W., on a true line, bet. secs. 27 and 34.

Over bottom land of Bill Williams River, through scattering timber and undergrowth.

39.95 True point for 1/4 sec. cor. falls in high water bed of Bill Williams River, where it would be destroyed.

79.90 The true point for cor. of secs. 27, 28, 33 and 34.

Land, level.

Soil, sandy; 1st rate.

Timber, cottonwood.


Undergrowth, arrow-weed and mesquite.

14.


Subdivision of T. 11 N., R. 16 W.

Chains.

From the witness cor. to cor. of secs. 27, 28, 33 and 34,  
 9.60 chs. N. of the true point for cor. of secs. 27,  
 28, 33 and 34,  
 N.0° 2' W., bet. secs. 27 and 28, continuing measurement.  
 Over level land, through scattering undergrowth.  
 29.60 Leave level land, brs. E. and W. Thence over rolling land.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Asc. 70 ft. to  
 53.93 Short spur, slopes S.15° W. Desc. 30 ft. to  
 61.31 Enter wash, course SW.  
 77.61 Leave wash, course S.15° W. Asc. slightly to  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 21, 22, 27 and 28, marked on  
 brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, level and rolling.  
 Soil, rocky; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood and ironwood.  
 Drainage, S.

40.00 S.89° 57' E., on a random line, bet. secs. 22 and 27.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.08 Intersect N. and S. line, 2 lks. N. of the cor. of secs.  
 22, 23, 26 and 27.  
 Thence  
 N.89° 56' W., on a true line, bet. secs. 22 and 27.  
 Over rolling land, through scattering undergrowth.  
 13.17 Enter wash, 2 ft. bank, course S.  
 23.16 Leave wash, 2 ft. bank, course S.  
 34.23 Enter wash, 5 ft. bank, course S.  
 40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,  
 N. of cor.  
 49.40 Leave wash, 5 ft. bank, course S.  
 80.08 The cor. of secs. 21, 22, 27 and 28.  
 Land, rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, ironwood, greasewood and sagebrush.




Subdivision of T. 11 N., R. 16 W.


15.

Chains.

15.38 N.0° 2' W., bet. secs. 21 and 22.  
 Over rolling land, through scattering undergrowth.  
 40.00 Center of wash, 2 chs. wide, course W.  
 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




78.00 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 80.00 Desc. 25 ft. to  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 15, 16, 21 and 22, marked on  
 brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, rolling.  
 Soil, rocky; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, cat claw and cactus.  
 Drainage, S.

40.00 S.89° 56' E., on a random line, bet. secs. 15 and 22.  
 79.98 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line, at the cor. of secs. 14, 15, 22  
 and 23.

Thence  
 N.89° 56' W., on a true line, bet. secs. 15 and 22.  
 Over rolling land, through scattering undergrowth.  
 10.00 Desc. 35 ft. to  
 14.97 Enter wash, 5 ft. bank, course S.  
 30.00 Leave wash, 2 ft. bank, course S. Asc. 45 ft. to  
 33.60 Thence over gently rolling land.  
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




79.98 and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,  
 N. of cor.  
 The cor. of secs. 15, 16, 21 and 22.  
 Land, rolling and gently rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, ironwood and sage-  
 brush.  
 Drainage, S.

N.0° 2' W., bet. secs. 15 and 16.  
 Over rolling land, through scattering undergrowth.  
 Desc. to

16. Subdivision of T. 11 N., R. 16 W.


Chains.

1.00 Enter wash, 2 ft. bank, course S.20° W.  
 9.96 Leave wash, 2 ft. bank, course S.20° W.  
 28.16 Enter wash, course SW.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

41.64 Leave wash, course SW.  
 55.02 Enter wash, course SW.  
 70.02 Leave wash, course SW.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap




and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, ironwood, greasewood, sagebrush and cactus.  
 Drainage, S.

40.00 S.89° 56' E., on a random line, bet. secs. 10 and 15.  
 79.96 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 10, 11, 14 and 15.

Thence  
 39.98 N.89° 57' W., on a true line, bet. secs. 10 and 15.  
 Over gently rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

63.80 Enter wash, course SW.  
 73.80 Leave wash, course SW.  
 79.96 The cor. of secs. 9, 10, 15 and 16.  
 Land, gently rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, ironwood and sagebrush.  
 Drainage, S. and SW.


N.0° 2' W., bet. secs. 9 and 10.  
 Over rolling land, through scattering undergrowth.

Subdivision of T. 11 N., R. 16 W.

Chains.

19.20  
20.50  
40.00


Asce. 35 ft. to  
Desc. 70 ft. to  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00

Thence over gently rolling land.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.


Land, rolling and gently rolling.  
Soil, 3rd rate.  
No timber.  
Undergrowth, cactus, greasewood, ocotillo, palo verde, ironwood and cat claw.

40.00  
79.97

S.89° 57' E., on a random line, bet. secs. 3 and 10.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect N. and S. line, 14 lks. N. of the cor. of secs. 2, 3, 10 and 11.

12.57  
39.98 $\frac{1}{2}$

Thence  
N.89° 51' W., on a true line, bet. secs. 3 and 10.  
Over rolling land, through scattering undergrowth.  
Wash, course SW.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

79.97

The cor. of secs. 3, 4, 9 and 10.  
Land, rolling.  
Soil, 3rd rate  
No timber.  
Undergrowth, greasewood, palo verde, ironwood, cactus, ocotillo and cat claw.

40.00  
80.12

N.0° 2' W, on a random line, bet. secs. 3 and 4.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect N. bdy. of Tp., 11 lks. E. of the cor. of secs. 3, 4, 33 and 34, which is an iron post, described in Book "A,"  
Thence  
S.0° 7' E., on a true line, bet. secs. 3 and 4.

## 18. Subdivision of T. 11 N., R. 16 W.

Chains.

40.12 Over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S4 | S3  
1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

65.00 Wash, course SW.

80.12 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.

Soil, 3rd rate.

No timber.

Undergrowth, greasewood, palo verde, cactus, ironwood, ocotillo and cat claw.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., which is an iron post, described in Book "A," N.0° 2' W., bet. secs. 32 and 33.

Over broken land, through scattering undergrowth.

Asc. to

1.09 Spur, slopes N. Desc. 60 ft., on spur.

8.65 Asc. 20 ft. to

11.03 Leave spur, slopes NW. Desc. 55. ft. to

19.08 Foot of desc., brs. E. and W. Road, brs. N.60° W. and S.60° E. Thence over level land, through dense undergrowth.

27.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness cor. to  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
W | C  
S32 | S33  
1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

27.50 Left bank of Bill Williams River, brs. E. and W. Thence across Bill Williams River, 2 ft. deep, course W.

32.50 Leave water in Bill Williams River, course W. Thence across dry bed of Bill Williams River.

40.00 The true point for  $\frac{1}{4}$  sec. cor. falls in channel of Bill Williams River.

80.00 The true point for cor. of secs. 28, 29, 32 and 33 falls in high water channel of Bill Williams River.

95.50 Leave river bottom, brs. E. and W.

96.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to cor. of secs. 28, 29, 32 and 33, marked on brass cap

T11N R16W  
S29 | S28

S32 | S33  
W | C  
1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Land, broken and level.

Soil, 2nd, 3rd and 4th rate.

No timber.

Undergrowth, mesquite, cat claw, palo verde and cactus.


Subdivision of T. 11 N., R. 16 W.

Chains.


Drainage, S.

40.00 From the true point for cor. of secs. 28, 29, 32 and 33,  
 79.87 East on a random line, bet. secs. 28 and 33.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line, 9 lks. N. of the true point for  
 cor. of secs. 27, 28, 33 and 34.  
 Thence  
 N.  $89^{\circ} 56'$  W., on a true line, bet. secs. 28 and 33.  
 Over level land, across sand bar.  
 39.93  $\frac{1}{2}$  True point for  $\frac{1}{4}$  sec. cor. falls in high water channel of  
 Bill Williams River, where it would be destroyed.  
 79.87 The true point for cor. of secs. 28, 29, 32 and 33.  
 Land, level.  
 Soil, sandy; 3rd rate.  
 No timber.  
 No undergrowth.

25.06 From the witness cor. to cor. of secs. 28, 29, 32 and 33,  
 30.05 16.00 chs. N. of the true point for cor. of secs. 28, 29,  
 40.00 32 and 33,  
 N.  $0^{\circ} 2'$  W., bet. secs. 28 and 29, continuing measurement.  
 Over level and rolling land, through scattering undergrowth.  
 Asc. 60 ft. to  
 Desc. 45 ft. to  
 Enter wash, course SW. Comes from N.  
 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



80.00 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 20, 21, 28 and 29, marked on  
 brass cap



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, level and rolling.  
 Soil, sandy and gravelly; 3rd and 4th rate.  
 No timber.  
 Undergrowth, palo verde and cactus.  
 Drainage, S.

40.00 S.  $89^{\circ} 56'$  E., on a random line, bet. secs. 21 and 28.  
 79.74 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line, 2 lks. S. of the cor. of secs.  
 21, 22, 27 and 28.  
 Thence  
 N.  $89^{\circ} 57'$  W., on a true line, bet. secs. 21 and 28.  
 Over broken land, through scattering undergrowth.  
 2.60 Center of wash, 6. chs. wide, course SE.

20.

Subdivision of T. 11 N., R. 16 W.

chains.

7.60 Asc. 45 ft. to  
 Desc. 95 ft. into wash, course S.  
 27.30 Leave wash, course S. Asc. 75 ft. to  
 33.30 End of spur, slopes S. Desc. 55 ft. to  
 38.32 Wash, 7 chs. wide, course S.  
 39.87 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S21

 $\frac{1}{4}$ S28  
1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.

52.62 Asc. 50 ft. to  
 Spur, slopes S.  $21\frac{1}{2}^{\circ}$  W. Desc. 100 ft. to  
 60.36 Enter wash, course S.  
 79.74 The cor. of secs. 20, 21, 28 and 29.  
 Land, level and broken.  
 Soil, rocky; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, cat claw, greasewood and cactus.

N.  $0^{\circ}$  2' W., bet. secs. 20 and 21.  
 Over level bottom of wash, course S., through scattering  
 undergrowth.  
 20.00 Leave wash, course S. Comes from N.  $10^{\circ}$  E. Asc. 100 ft.  
 to  
 38.66 Head of small ravine, course S.  $15^{\circ}$  E. Thence along E.  
 slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

 $\frac{1}{4}$ 

S20 S21

1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

63.94 Head of gulch, course S.  $10^{\circ}$  E. Thence over rolling E.  
 slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 16, 17, 20 and 21, marked on  
 brass cap

T11NR16W  
S17 S16S20 S21  
1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

Land, rolling and broken.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, sagebrush and cactus.

40.00 S.  $89^{\circ}$  57' E., on a random line, bet. secs. 16 and 21.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.72 Intersect N. and S. line, 2 lks. N. of the cor. of secs.  
 15, 16, 21 and 22.



Chains.

17.65

Leave wash, 2 ft. bank, course S.

39.89

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 9

$\frac{1}{4}$  ———

S 16

1916

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, N. of cor.

41.13

Enter wash, 2 ft. bank, course S.

64.55

Leave wash, 5 ft. bank course S.

79.78

The cor. of secs. 8, 9, 16 and 17.

Land, rolling.

Soil, gravelly; 3rd rate.

No timber.

Undergrowth, greasewood, palo verde, ironwood and sagebrush.

Drainage, S.

N.0° 2' W., bet. secs. 8 and 9.

Over gently rolling land, through scattering undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$

S 8 | S 9

1916

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, marked on brass cap

T11NR16W

S 5 | S 4

S 8 | S 9

1916

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

Land, gently rolling.

Soil, gravelly; 3rd rate.

No timber.

Undergrowth, palo verde, ironwood, greasewood and cactus.

Drainage, S.

S.89° 52' E., on a randomline, bet. secs. 4 and 9.

40.00

Set temp.  $\frac{1}{4}$  sec. cor.

79.72

Intersect N. and S. line, 11 lks. S. of the cor. of secs. 3, 4, 9 and 10.

Thence

N.89° 57' W., on a true line, bet. secs. 4 and 9.

Over rolling land, through scattering undergrowth.

5.00

Center of wash, 10 chs. wide, course S.

29.10


Enter wash, course S.

39.86

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




Chains.



S 9  
1916


and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 57.00 Leave wash, course S.  
 79.72 The cor. of secs. 4, 5, 8 and 9.  
 Land, rolling.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, cactus, ironwood, ocotillo and cat claw.

40.00 N.0° 2' W., on a random line, bet. secs. 4 and 5.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.10 Intersect N. and S. line, 40 lks. E. of the cor. of secs. 4, 5, 32 and 33, which is an iron post, described in Book "A."  
 Thence  
 40.10 S.0° 19' E., on a true line, bet. secs. 4 and 5.  
 Over rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



57.70 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 80.10 Road, brs. NE. to Yucca and SW.  
 The cor. of secs. 4, 5, 8 and 9.  
 Land, rolling.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, greasewood, palo verde, cactus, ocotillo and sagebrush.

8.64 From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., which an iron post, described in Book "A,"  
 8.73 N.0° 3' W., bet. secs. 31 and 32.  
 11.30 Over mountainous land, through scattering undergrowth.  
 Desc. 250 ft.  
 Road, brs. E. and W.  
 30.34 Rail fence, brs. E. and W.  
 Foot of descent; thence over level land, across river bottom.  
 From this point, NE. cor. of A. C. Jones' house brs. S.  $13\frac{1}{4}$ ° W., about 18 chs. dist.  
 30.63 Rail fence, brs. E. and W.  
 30.70 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness cor. to  $\frac{1}{4}$  sec. cor., marked on brass cap



dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.

## 24. Subdivision of T. 11 N., R. 16 W.

chains.

- high, W. of cor.  
 40.00 The true point for  $\frac{1}{4}$  sec. cor. falls in Bill Williams River bottom, where it would be destroyed.  
 42.70 Left bank of Bill Williams River, brs. E. and W.  
 74.40 Enter water in Bill Williams River, course W. and W.  
 77.00 Right bank of Bill Williams River, brs. E. and W.  
 80.00 True point for cor. of secs. 29, 30, 31 and 32, falls in bottom land of Bill Williams River, where it would be destroyed.  
 82.60 Four strand wire fence, brs. E. and W.  
 82.65 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to cor. of secs. 29, 30, 31 and 32, marked on brass cap

T11N R16W  
 S30 | S29  
 -----  
 S31 | S32  
 W C  
 1916

dig pits, 18 X 18 X 12 ins., NE., SE., SW. and NW. of post,  $5\frac{1}{2}$  ft. dist; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.  
 Land, level and broken.  
 Soil, sandy; 1st rate.  
 Timber, scattering cottonwood.  
 Undergrowth, arrow-weed.

- 40.00 From the true point for cor. of secs. 29, 30, 31 and 32, East on a random line, bet. secs. 29 and 32.  
 80.06 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.06 Intersect N. and S. line, 14 lks. N. of the true point for cor. of secs. 28, 29, 32 and 33.  
 Thence  
 N.  $89^{\circ} 54'$  W., on a true line, bet. secs. 29 and 32.  
 Over level land, through scattering timber and dense undergrowth.  
 40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap


S29  
 -----  
 $\frac{1}{4}$   
 S32  
 1916

- from which  
 A willow, 12 ins. diam., brs. N.  $33^{\circ} 10'$  E., 102 lks. dist.; marked  $\frac{1}{4}$  S29 BT.  
 A willow, 9 ins. diam., brs. S.  $30\frac{1}{2}^{\circ}$  W., 38 lks. dist., marked  $\frac{1}{4}$  S32 BT.  
 80.06 The true point for cor. of secs. 29, 30, 31 and 32.  
 Land, level.  
 Soil, sandy; 2nd and 3rd rate.  
 Timber, scattering cottonwood.  
 Undergrowth, mesquite, arrow-weed and cat claw.

- 40.00 From the true point for cor. of secs. 29, 30, 31 and 32, West on a random line, bet. secs. 30 and 31.  
 78.98 Set temp.  $\frac{1}{4}$  sec. cor.  
 78.98 Intersect Fourth Guide Meridian West, 21 lks. S. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, described in Book "B".  
 Thence


Chains.

5.00 S. 89° 51' E., on a true line, bet. secs. 30 and 31.  
 23.85 Over level river bottom, through dense undergrowth.  
 38.98 From this point, Martinez' house brs. N. 4.50 chs. dist.  
 Brush fence, brs. N. and S.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




78.98 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.  
 dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.  
 high, N. of cor.  
 The true point for cor. of secs. 29, 30, 31 and 32.  
 Land, level.  
 Soil, 1st rate.  
 Timber, cottonwood.  
 Undergrowth, arrow-weed.

7.65 From the witness cor. to cor. of secs. 29, 30, 31 and 32,  
 10.15 2.65 chs. N. of the true point for cor. of secs. 29, 30,  
 16.45 31 and 32,  
 N. 0° 3' W., bet. secs. 29 and 30, continuing measurement.  
 Over level bottom land, through dense undergrowth.  
 Road, brs. E. and W.  
 37.00 Four strand wire fence, brs. E. and W.  
 40.00 Leave river bottom, brs. E. and W. Thence over rolling  
 land.  
 Enter wash, 2 ft. bank, course S. 20° W.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



49.70 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.  
 80.00 dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.  
 high, W. of cor.  
 Leave wash, 2 ft. bank, course S. 20° W.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 19, 20, 29 and 30, marked on  
 brass cap



and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, level and rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, sagebrush and cactus.

40.00 S. 89° 54' E., on a random line, bet. secs. 20 and 29.  
 80.12 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 20,  
 21, 28 and 29.


26.

Subdivision of T. 11 N., R. 16 W.


chains.

7.50	Thence
31.86	N.89° 56' W., on a true line, bet. secs. 20 and 29.
40.06	Over level bottom of wash, through scattering undergrowth.
	Leave wash, course S. Thence over rolling land.
	Center of wash, 9.00 chs. wide, course SW.
	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the
	ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	S20
	$\frac{1}{4}$ ———
	S29
	1916
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
	N. of cor.
63.26	Center of draw, 7 chs. wide, course SW.
80.12	The cor. of secs. 19, 20, 29 and 30.
	Land, level and rolling.
	Soil, 3rd and 4th rate.
	No timber.
	Undergrowth, palo verde, greasewood, sagebrush and cactus.
	Drainage, S.
40.00	N.89° 51' W., on a random line, bet. secs. 19 and 30.
78.86	Set temp. $\frac{1}{4}$ sec. cor.
	Intersect Fourth Guide Meridian West, 5 lks. N. of the cor.
	of secs. 19, 24, 25 and 30, which is an iron post,
	described in Book "A".
	Thence
	S.89° 53' E., on a true line, bet. secs. 19 and 30.
	Over broken land, through scattering undergrowth.
38.86	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	S19
	$\frac{1}{4}$ ———
	S30
	1916
	and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high,
	N. of cor.
42.65	Enter wash, 5 ft. bank, course S.
47.75	Road, brs. N. to Yucca and S. to Planet.
56.15	Leave wash, course S. Thence over gently rolling land.
65.66	Asc. 70 ft. to
75.06	Desc. to
78.86	The cor. of secs. 19, 20, 29 and 30.
	Land, broken.
	Soil, gravelly; 3rd rate.
	No timber.
	Undergrowth, palo verde, greasewood, and cactus.
	Drainage, S.
7.80	N.0° 3' W., bet. secs. 19 and 20.
12.75	Over rolling land, through scattering undergrowth.
31.20	Asc. 45 ft. to
40.00	Desc. 40 ft. to
	Asc. 65 ft. to
	Thence over rolling land.
	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains.




80.00 and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on brass cap



and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.  
 Land, rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, sagebrush and cactus.  
 Drainage, S.

40.00 S. 89° 56' E., on a random line, bet. secs. 17 and 20.  
 80.16 Set temp. 1/4 sec. cor.  
 Intersect N. and S. line, at the cor. of secs. 16, 17, 20 and 21.

Thence  
 N. 89° 56' W., on a true line, bet. secs. 17 and 20.  
 Over rolling land, through scattering undergrowth.  
 29.50 Draw, course S.  
 40.08 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for 1/4 sec. cor., marked on brass cap



65.00 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.  
 80.16 Draw, course SW.  
 The cor. of secs. 17, 18, 19 and 20.  
 Land, rolling.  
 Soil, 2nd and 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, sagebrush and cactus.  
 Drainage, S.

40.00 N. 89° 53' W., on a random line, bet. secs. 18 and 19.  
 78.76 Set temp. 1/4 sec. cor.  
 Intersect Fourth Guide Meridian West, 14 lks. N. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, described in Book "A."

Thence  
 S. 89° 59' W., on a true line, bet. secs. 18 and 19.  
 Over rolling land, through scattering undergrowth.  
 30.00 Enter wash, 2 ft. bank, course S.  
 38.76 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

28.

Subdivision of T. 11 N., R. 16 W..

Chains.

S18

$\frac{1}{4}$  ———

S19  
1916

and raise a mound of stone, 3 ft. base, 2½ ft. high,  
N. of cor.

41.50

Leave wash, course S.

71.50

Road, brs. NE. to Yucca and SW. to Planet.

78.76

The cor. of secs. 17, 18, 19 and 20.

Land, rolling.

Soil, gravelly; 3rd rate.

No timber.

Undergrowth, palo verde, greasewood and sagebrush.

Drainage, S.

N.0° 3'W., bet. secs. 17 and 18.

Over rolling land, through scattering undergrowth.

10.50

Road, brs. NE. to Yucca and SW. to Planet.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for ¼ sec. cor., marked on brass cap

$\frac{1}{4}$

S18 | S17  
1916

and raise a mound of stone, 3 ft. base, 2½ ft. high,  
W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 7, 8, 17 and 18, marked on  
brass cap

T11N R16W  
S 7 | S 8

S18 | S17  
1916

and raise a mound of stone, 3 ft. base, 2½ ft. high,  
W. of cor.

Land, rolling.

Soil, gravelly; 3rd rate.

No timber.

Undergrowth, palo verde, greasewood, sagabrush and cactus.

Drainage, S.

S.89° 56' E., on a random line, bet. secs. 8 and 17.

40.00

Set temp. ¼ sec. cor.

80.06

Intersect N. and S. line, at the cor. of secs. 8, 9, 16 and  
17.

Thence

N.89° 56' W., on a true line, bet. secs. 8 and 17.

Over rolling land, through scattering undergrowth.

40.03

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for ¼ sec. cor., marked on brass cap

S 8

$\frac{1}{4}$  ———

S17  
1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,


Subdivision of T. 11 N., R. 16 W.

Chains.

46.00 N. of cor.,  
 80.06 Road, brs. NE. to Yucca and SW. to Planet.  
 The cor. of secs. 7, 8, 17 and 18.  
 Land, rolling.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, greasewood, palo verde, cactus, ocotillo and  
 cat claw.


40.00 N. 89° 59' W., on a random line, bet secs. 7 and 18.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 78.60 Intersect Fourth Guide Meridian West, 14 lks. S. of the cor.  
 of secs. 7, 12, 13 and 18, which is an iron post,  
 described in Book "A."

Thence  
 38.60 S. 89° 53' E., on a true line, bet. secs. 7 and 18.  
 Over gently rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




78.60 and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high,  
 N. of cor.  
 The cor. of secs. 7, 8, 17 and 18.  
 Land, gently rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, palo verde, greasewood, sagebrush and cactus.  
 Drainage, S.

40.00 N. 0° 3' W., bet. secs. 7 and 8.  
 Over rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



80.00 and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
 W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 5, 6, 7 and 8, marked on  
 brass cap



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, rolling.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, palo verde, cactus, greasewood and cat claw.

30. Subdivision of T. 11 N., R. 16 W.

Chains.

40.00 S. 89° 56' E., on a random line, bet. secs. 5 and 8.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.15 Intersect N. and S. line, 5 lks. N. of the cor. of secs.  
 4, 5, 8 and 9.  
 Thence  
 N. 89° 54' W., on a true line, bet. secs. 5 and 8.  
 Over gently rolling land, through scattering undergrowth.  
 6.50 Road, brs, NE. to Yucca and SW. to Planet.  
 40.07 $\frac{1}{2}$  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 5  
 $\frac{1}{4}$   
 S 8  
 1916

and raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high,  
 N. of cor.  
 80.15 The cor. of secs. 5, 6, 7 and 8.  
 Land, gently rolling.  
 Soil, gravelly; 3rd rate.  
 No timber.  
 Undergrowth, greasewood, palo verde, sagebrush and cactus.  
 Drainage, S.

40.00 N. 89° 53' W., on a random line, bet. secs. 6 and 7.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 78.58 Intersect 4th Guide Meridian West, 26 lks. N. of the cor.  
 of secs. 1, 6, 7 and 12, which is an iron post,  
 described in Book "A."  
 Thence  
 N. 89° 56' E., on a true line, bet. secs. 6 and 7.  
 Over rolling land, through scattering undergrowth.  
 38.58 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 6  
 $\frac{1}{4}$   
 S 7  
 1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
 N. of cor.  
 41.58 Wash, course SW.  
 78.58 The cor. of secs. 5, 6, 7 and 8.  
 Land, rolling.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, greasewood, palo verde, cactus, ocotillo and  
 cat claw.

40.00 N. 0° 3' W., on a random line, bet. secs. 5 and 6.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.98 Intersect N. bdy. of Tp., 37 lks. E. of the cor. of secs.  
 5, 6, 31 and 32, which is an iron post, described in  
 Book "A."  
 Thence  
 S. 0° 19' E., on a true line, bet. secs. 5 and 6.  
 Over rolling land through scattering undergrowth.  
 5.00 Wash, course SW.  
 39.98 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



Chains.

$\frac{1}{4}$   
 S 6 | S 5  
 1916

79.98 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 The cor. of secs. 5, 6, 7 and 8.  
 Land, rolling.  
 Soil, 3rd rate.  
 No timber.  
 Undergrowth, palo verde, cactus, greasewood, ocotillo and cat claw.

GENERAL DESCRIPTION.

This township consists of level and rolling land, drained by wide washes, which empty into the Bill Williams River. The Bill Williams River flows westerly through the southern tier of sections.

Undergrowth consists of ironwood, greasewood, palo verde, ocotillo, cat claw, mesquite, arrow-weed and cactus. There is no timber.

The soil is rocky, 3rd and 4th rate except for narrow areas of 1st and 2nd rate soil along the Bill Williams River.

Martinez is located in sec. 30, and A. C. Jones in secs. 31 and 32. E. T. Miner is located in sec. 25.

The Bill Williams river at the time of the survey hereinbefore described, was in an abnormal stage owing to recent heavy rains, and normally, is a stream of much less than 3 chs. in width, and is therefore, not a considerable stream.

92  
BOOK 3025

32

34

TRANSITMEN

CERTIFICATE OF UNITED STATES SURVEYOR.  
See Book "B."

I, \_\_\_\_\_, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for \_\_\_\_\_ bearing date of the \_\_\_\_\_ day of \_\_\_\_\_, 191 \_\_\_\_\_, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of \_\_\_\_\_ of the \_\_\_\_\_ Meridian, in the State of \_\_\_\_\_, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for \_\_\_\_\_ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

\_\_\_\_\_  
U. S. Surveyor

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,


Phoenix, Arizona, MAY 17 1918, 191 \_\_\_\_\_

The foregoing field notes of the survey of the \_\_\_\_\_  
Subdivision Lines of \_\_\_\_\_

TOWNSHIP 11 NORTH, RANGE 16 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by Alexander T. Harris, and John Gonin, U. S. Transitmen,  
under his special instructions dated Feb. 13, 1915, for Group 48, Arizona, 191 \_\_\_\_\_, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

  
U. S. Surveyor General.

~~I certify that the foregoing transcript of the field notes of the above described surveys in \_\_\_\_\_  
\_\_\_\_\_ has been correctly copied from the original notes on file in this office.~~