

3056

Book "P."

4-679

BOOK 3056

(Subdivisions)

FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION LINES

of

TOWNSHIP 4 NORTH, RANGE 4 WEST,

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

Roy J. Gill and Hans D. Voigt,

U.S. Transitmen.

~~In the capacity of U.S. Surveyor~~, under instructions dated December 12., 1914,
issued by the United States Surveyor General to govern surveys included in
Group No. 39, which were approved by the Commissioner of the General Land
Office, January 7., 1915.

Survey commenced December 21., 1915.

Survey completed January 8., 1916.

3056

3056

127







128
(1A)

BOOK 8053

Book "P"
(Subdivisions)
Group 39 - Arizona.

INDEX DIAGRAM.

		Township 4 North				Range 4 West					
		First		Standard		Parallel		North			
West. Meridian Guide First	6	25	5	19	4	15	3	10	2	6	1
	25		25		18		14		10		6
	7	24	8	18	9	14	10	10	11	6	12
	24		23		18		13		9		5
	18	23	17	17	16	13	15	9	14	5	13
	22		22		17		13		9		5
	19	22	20	16	21	12	22	8	23	4	24
	21		21		16		12		8		4
	30	20	29	16	28	11	27	8	26	4	25
	20		20		15		11		7		3
	31	19	32	15	33	11	34	7	35	3	36

-  Subdivision lines surveyed under this Group.
-  Township boundaries surveyed under this Group.
Notes in Book "B."
-  Standard lines surveyed under this Group.
Notes in Book "A."
-  Standard lines resurveyed under this Group.
Notes in Book "A."
-  Accepted surveys.
-  Unsurveyed lines.

SUBDIVISIONS OF
TOWNSHIP 4 NORTH, RANGE 4 WEST.

DATE DIAGRAM.

First Standard Parallel North, Resurvey.

	1-4-16	1-4-16	1-4-16	1-4-16	1-4-16	1-4-16	1-3-16
	6	5	4	3	2	1	
	1-7-16	1-7-16	1-8-16	1-8-16	1-8-16	1-4-16	12-20-15
	7	8	9	10	11	12	
	1-7-16	1-7-16	1-7-16	1-8-16	1-5-16	12-22-15	12-20-15
	18	17	16	15	14	13	
	1-7-16	1-7-16	1-6-16	1-5-16	1-7-16	12-22-15	12-20-15
	19	20	21	22	23	24	
	1-7-16	1-6-16	1-5-16	1-4-16	12-22-15	12-21-15	12-20-15
	30	29	28	27	26	25	
	1-6-16	1-5-16	1-4-16	12-22-15	12-21-15	12-21-15	12-20-15
	31	32	33	34	35	36	
	1-5-16	1-4-16	12-22-15	12-21-15	12-21-15	12-20-15	12-20-15
	12-9-15	12-9-15	12-9-15	12-9-15	12-9-15	12-9-15	12-9-15

First Guide Meridian West

Lines dated in red were surveyed by Roy J. Gill,
U. S. Transitman.

Lines dated in green were surveyed by Hans D. Voigt,
U. S. Transitman.

Subdivision of T.4 N., R.4 W.

Chains

Survey executed by Roy J. Gill, U. S. Transitman, and Hans D. Voigt, U. S. Transitman, using Young and Son's light mountain transits Nos. 8583 and 8293 respectively.

From recent and repeated field tests of the transits and solar attachments, they are known to be in satisfactory adjustment.

During the survey of the township, the transits and solar attachments were maintained in adjustment by frequent tests on a true meridian, determined by observations on Polaris, all necessary corrections for adjustment being made.

From the cor. of secs. 1, 2, 35, and 36, on S. bdy. of Tp., as described in book "B.", N. 0° 1' W. bet. secs. 35 and 36.

Over rolling and hilly land. Asc. steep slope, 223 ft. to

6.50
40.00

Top of spur slopes NW., desc. N. slope, 368 ft. to Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4
S 35:S 36

1915

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

45.00
80.00

Desc. N. slope, 69 ft. to Thence over rolling land.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T 4 N R 4 W
S 26:S 25
S 35:S 36
1915

dig pits, 18 X 18 X 12 ins., in each sec., 5 1/2 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling and mountainous. Soil, rocky 4th rate.

Timber, scattering palo verde and cat claw.

40.00
79.96

East on a random line bet. secs. 25 and 36. Set temp. 1/4 sec. cor.

Intersect E. bdy. of Tp. at cor. of secs. 25, 30, 31 and 36, as described in book "B."

Thence

West on a true line bet. secs. 25 and 36. Over level land, through scattering timber.

39.98

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 25
S 36
1915

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

79.96

Cor. of secs. 25, 26, 35 and 36. Land, level.

Soil, 3rd rate.

Timber, scattering paloverde and cat claw.

Chains	
9.60 40.00	<p>N. 0° 1' W. bet. secs. 25 and 26. Over level land, through scattering timber. Wagon road brs. E. and W.</p>
	<p>Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 26:S 25</p>
	<p style="text-align: center;">1915</p> <p>dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.</p>
	<p style="text-align: center;">T 4 N R 4 W S 23:S 24 S 26:S 25</p>
	<p style="text-align: center;">1915</p> <p>dig pits, 18 X 18 X 12 ins. in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.</p>
	<p>Land, level. Soil, 2nd rate. Timber, scattering palo verde and cat claw.</p>
40.00 79.95	<p>East on a random line bet. secs. 24 and 25. Set temp. $\frac{1}{4}$ sec. cor. Intersect E. bdy. of Tp. at cor. of secs. 19, 24, 25 and 30, as described in book "B."</p>
	<p>Thence West on a true line bet. secs. 24 and 25. Over level land, through scattering timber.</p>
39.97 $\frac{1}{2}$	<p>Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	<p style="text-align: center;">$\frac{1}{4}$ S 24 $\frac{1}{4}$ S 25 1915</p>
79.95	<p>dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p>
	<p>Cor. of secs. 23, 24, 25 and 26. Land, level. Soil, 2nd rate. Timber, scattering palo verde and cat claw.</p>
40.00	<p>N. 0° 1' W. bet. secs. 23 and 24. Over level land, through scattering timber.</p>
	<p>Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 23:S 24</p>
	<p style="text-align: center;">1915</p> <p>dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.</p>
	<p style="text-align: center;">T 4 N R 4 W S 14:S 13 S 23:S 24 1915</p>

Subdivision of T.4 N., R.4 W.

Chains

dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
 Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde and cat claw.

40.00
79.99

East on a random line bet. secs. 13 and 24.
 Set temp. ¼ sec. cor.
 Intersect E. bdy. of Tp., 1 lk. S. of cor. of secs. 13, 18, 19 and 24, described in book "B."

39.99½

Thence
 West on a true line bet. secs. 13 and 24.
 Over level land, through scattering timber.
 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ S 13
 ¼ S 24
 1915

79.99

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
 Cor. of secs. 13, 14, 23 and 24.
 Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde and cat claw.

40.00

N. 0° 1' W. bet. secs. 13 and 14.
 Over level land, through scattering timber.
 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼
 S 14:S 13

1915

80.00

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.

T 4 N R 4 W
 S 11:S 12
 S 14:S 13
 1915

dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
 Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, scattering greasewood.

40.00

80.04

East on a random line bet. secs. 12 and 13.
 Set temp. ¼ sec. cor.
 Intersect E. bdy. of Tp. 3 lks. S. of cor. of secs. 7, 12, 13 and 18, described in book "B".

40.02

Thence
 S. 89° 59' W. on a true line bet. secs. 12 and 13.
 Over level land, through scattering timber.
 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

6

Subdivision of T.4 N., R.4 W.

Chains	
80.04	$\frac{1}{4} \frac{S 12}{S 13}$ <p style="text-align: center;">1915</p> <p>dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.</p> <p>Cor. of secs. 11, 12, 13 and 14.</p> <p>Land, level.</p> <p>Soil, 2nd rate.</p> <p>Timber, scattering palo verde and cat claw.</p>
25.25 40.00	<p>N. 0° 1' W. bet. secs. 11 and 12.</p> <p>Over level land, through scattering timber.</p> <p>Wagon road brs. E. and W., (E. to windmill).</p> <p>Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec., cor., with brass cap mkd.</p> $\frac{1}{4} S 11:S 12$
58.10 80.00	<p style="text-align: center;">1916</p> <p>dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.</p> <p>Wagon road brs. NE. and SW.</p> <p>Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.</p> $T 4 N R 4 W$ $\frac{S 2 :S 1}{S 11:S 12}$
40.00 79.95	<p style="text-align: center;">1916</p> <p>dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.</p> <p>Land, level.</p> <p>Soil, 2nd rate.</p> <p>Timber, scattering palo verde and cat claw.</p> <hr/> <p>East on a random line bet. secs. 1 and 12.</p> <p>Set temp. ¼ sec. cor.</p> <p>Intersect E. bdy. of Tp. 5 lks. S. of cor. of secs. 1, 6, 7 and 12, as described in book "B."</p> <p>Thence</p> <p>S. 89° 58' W. on a true line bet. secs. 1 and 12.</p> <p>Over level land, through scattering timber.</p>
39.97½	<p>Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \frac{S 1}{S 12}$ <p style="text-align: center;">1916</p>
42.50 79.95	<p>dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.</p> <p>Road brs. NE. and SW.</p> <p>Cor. of secs. 1, 2, 11 and 12.</p> <p>Land, level.</p> <p>Soil, 2nd rate.</p> <p>Timber, scattering palo verde.</p>
40.00	<p>N. 0° 1' W. on a true line bet. secs. 1 and 2.</p> <p>Over level land, through scattering timber.</p> <p>Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in</p>

Subdivision of T.4 N., R.4 W.

Chains

the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
 $\frac{1}{4}$
 S 2 : S 1

1916
 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

70.64 Intersect 1st standard parallel N., 24.48 chs. W. of of east ab. the standard cor. of Ts. 5 N., Rs. 3 and 4 W., as described in book "A." At point of intersection, Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for C.C. of secs. 1 and 2, with brass cap mkd.

T 5 N R 4 W
 S 36
 S 2 : S 1
 T 4 N : R 4 W
 C C

1915
 dig pits, 24 X 18 X 12 ins., crosswise on each line, E., and W., 3 ft. and S. of post, 7 ft. dist., and raise a mound of eath, 4 ft. base, 2 ft. high, S. of cor.

Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde,

From the cor. of secs. 2, 3, 34 and 35, on S. bdy. of Tp., as described in book "B."
 N. $0^{\circ} 1'$ W. bet. secs. 34 and 35.
 Over level land, through scattering timber.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 34 : E 35

1915
 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

46.00 Wash, 40 lks. wide, 5 ft. deep, course, W.
 79.00 Wash, 75 lks. wide, 5 ft. deep, course, W.
 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

T 4 N R 4 W
 S 27 : S 26
 S 34 : S 35

1915
 dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde and cat claw.

East on a random line bet. secs. 26 and 35.

40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.89 Intersect N. and S. line, 4 lks. S. of cor. of secs. 25, 26, 35 and 36.

Thence
 S. $89^{\circ} 58'$ W. on a true line bet. secs. 26 and 35.
 Over level land, through scattering timber.

12.30 Wagon road brs. NE. and SW.
 39.94 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains

 $\frac{1}{4}$ S 26 $\frac{1}{4}$ S 35

1915

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

65.90 Wash, 45 lks. wide, 4 ft. deep, course, NW.

79.00 Wash, 75 lks. wide, 5 ft. deep, course, NW.

79.89 Cor. of secs. 26, 27, 34 and 35.

Land, level.

Soil, 3rd rate.

Timber, scattering palo verde and cat claw.

N. 0° 1' W. bet. secs. 26 and 27.

Over level land, through scattering timber.

5.00 Wash, 75 lks. wide, 4 ft. deep, course, W.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$
S 27:S 26

1915

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$
ft. high, W. of cor.

50.30 Wash, 40 lks. wide, 2 ft. deep, course, NW.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in
the ground, for cor. of secs. 22, 23, 26 and 27,
with brass cap mkd.

T 4 N R 4 W

S 22:S 23

S 27:S 26

1915

dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.;
and raise a mound of earth, $3\frac{1}{2}$ ft. base, 2 ft. high,
W. of cor.

Land, level.

Soil, 2nd rate.

Timber, scattering palo verde and cat claw.

East on a random line bet. secs. 23 and 26.

40.00 Set temp. $\frac{1}{4}$ sec. cor.79.97 Intersect N. and S. line, 2 lks. N. of cor. of secs. 23,
24, 25 and 26.

Thence

N. 89° 59' W. on a true line bet. secs. 23 and 26.

Over level land, through scattering timber.

39.98 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 23 $\frac{1}{4}$ S 26

1915

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, N. of cor.

79.97 Cor. of secs. 22, 23, 26 and 27.

Land, level.

Soil, 2nd rate.

Timber, scattering palo verde.

Undergrowth, greasewood.

N. 0° 1' W. bet. secs. 22 and 23.

Over level land, through scattering timber.

Subdivision of T.4 N., R.4 W.

Chains

34.00 Wagon road brs. NE. and SW.
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4
S 22:S 23

1916

80.00 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

T 4 N R 4 W
S 15:S 14
S 22:S 23

1916

dig pits, 18 X 18 X 12 ins., in each sec., 5 1/2 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level. --- Soil, 2nd rate.
Timber, scattering palo verde.

East on a random line bet. secs. 14 and 23..

40.00 Set temp. 1/4 sec. cor.
80.16 Intersect N. and S. line, 10 lks. S. of cor. of secs. 13, 14, 23 and 24.

Thence

S. 89° 56' W. on a true line bet. secs. 14 and 23.
Over level land, through scattering timber.

40.08 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 14
S 23

1916

80.16 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

Cor. of secs. 14, 15, 22 and 23.
Land, gently rolling and level. --- Soil, 2nd rate.
Timber, scattering palo verde.

N. 0° 1' W. bet. secs. 14 and 15.

40.00 Over level land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4
S 15:S 14

1916

80.00 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

T 4 N R 4 W
S 10:S 11
S 15:S 14

1916

dig pits, 18 X 18 X 12 ins., in each sec., 5 1/2 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level. --- Soil, 2nd rate.
Timber, scattering palo verde.

East on a random line bet. secs. 11 and 14.

40.00 Set temp. 1/4 sec. cor.
79.91 Intersect N. and S. line, 5 lks. S. of cor. of secs. 11, 12, 13 and 14.

Thence

S. 89° 58' W. on a true line bet. secs. 11 and 14.

10

Subdivision of T.4 N., R.4 W.

Chains
39.95½ Over level land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor.; with brass cap mkd.
¼ S 11
¼ S 14
1916
dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

79.91 Cor. of secs. 10, 11, 14 and 15.
Land, level.---- Soil, 2nd rate.
Timber, scattering palo verde.

N. 0° 1' W. bet. secs. 10 and 11.
Over gently rolling land, through scattering timber.
Wagon road, brs. E. and W.

27.20
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
¼
S 10:S 11
1916
dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.
T 4 N R 4 W
S 3 :S 2
S 10:S 11
1916
dig pits, 18 X 18 X 12 ins., in each sec.; 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, gently rolling. --- Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

East on a random line bet. secs. 2 and 11.
40.00 Set temp. ¼ sec. cor.
79.98 Intersect N. and S. line, 8 lks. S. of cor. of secs. 1, 2, 11, and 12,
Thence
S. 89° 57' W. on a true line bet. secs. 2 and 11.

39.99 Over level land, through scattering timber,
Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
¼ S 2
¼ S 11
1916
dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

79.98 Cor. of secs. 2, 3, 10 and 11.
Land, level and rolling.--- Soil, 2nd and 3rd rates.
Timber, scattering palo verde and cat claw.

N. 0° 1' W. on a true line bet. secs. 2 and 3.
Over gently rolling land, through scattering timber.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
¼
S 3 :S 2
1916
dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

70.67 Intersect 1st standard parallel N., 24.37 chs. W. of reestab. standard cor. of secs. 35 and 36, T.5 N., R.4 W., as described in book "A". At point of intersection,
Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for C.C. of secs. 2 and 3, with brass cap mkd.

Subdivision of T.4 N., R.4 W.

Chains

T 5 N R 4 W
S 35
S 3:S 2
T 4 N:R 4 W
C C
1916

dig pits, 24 X 18 X 12 ins., crosswise on each line, E. and W., 3 ft. and S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, S. of cor.

Land, gently rolling.
Soil, 3rd rate.
Timber, scattering palo verde.

From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp., as described in book "EB,"

N. 0° 2' W. bet. secs. 33 and 34.

Over level land, through scattering timber.

40.00

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4
S 33:S 34

1915

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with, brass cap mkd.

T 4 N R 4 W
S 28:S 27
S 33:S 34

1915

dig pits, 18 X 18 X 12 ins. in each sec., 5 1/2 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

East on a random line bet. secs. 27 and 34.

40.00

Set temp. 1/4 sec. cor.

79.92

Intersect N. and S. line, 9 lks. S. of cor. of secs. 26, 27, 34 and 35.

Thence

S. 89° 56' W. on a true line bet. secs. 27 and 34.

Over level land, through scattering timber.

39.96

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 27
1/4 S 34
1915

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

44.10

Wash, 40 lks. wide, 3 ft. deep, course, NW.

79.92

Cor. of secs. 27, 28, 33 and 34.

Land, level.
Soil, 3rd rate.
Timber, scattering palo verde and cat claw.

N. 0° 2' W. bet. secs. 27 and 28.

Over level land, through scattering timber.

12

Subdivision of T.4 N., R.4 W.

Chains

32.50

Wash, 40 lks. wide, 3 ft. deep, course, W.

40.00

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4}$$
 S 28:S 27

1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

47.50

Wash, 30 lks. wide, 3 ft. deep, course, W.

65.10

Wagon road, brs. E. and W.

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T 4 N R 4 W

S 21:S 22

S 28:S 27

1916

dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 3 ft. base, 2 ft. high, W. of cor.

Land, level, and rolling.

Soil, 2nd rate.

Timber, scattering palo verde.

40.00

East on a random line bet. secs. 22 and 27.

79.92

Set temp. $\frac{1}{4}$ sec. cor.

Intersect N. and S. line, 3 lks. S. of cor. of secs. 22, 23, 26 and 27.

Thence

S. $89^{\circ} 59'$ W. on a true line bet. secs. 22 and 27.

39.96

Over gently rolling land, through scattering timber.

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \frac{S 22}{S 27}$$

1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

40.20

Wagon road brs. N. and S.

42.40

Wash, 75 lks. wide, 4 ft. deep, course, S.

79.92

Cor. of secs. 21, 22, 27 and 28.

Land, gently rolling.

Soil, 2nd rate.

Timber, scattering palo verde and cat claw.

21.30

N. $0^{\circ} 2'$ W. bet. secs. 21 and 22.

Over level land, through scattering timber.

40.00

Wagon road brs. NE. and SW.

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4}$$
 S 21:S 22

1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

T 4 N R 4 W

S 16:S 15

S 21:S 22

1916

Subdivision of T.4 N., R.4 W.

Chains	
	<p>dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, level. Soil, 2nd rate. Timber, scattering palo verde.</p>
40.00 79.88	<p>East on a random line bet. secs. 15 and 22. Set temp. ¼ sec. cor., Intersect N. and S. line at cor. of secs. 14, 15, 22 and 23. Thence West on a true line bet. secs. 15 and 22. Over level land, through scattering timber. Wagon road bns. NE. and SW. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p>
21.90 39.24	<p style="text-align: center;"> $\frac{1}{4}$ S 15 $\frac{1}{4}$ S 22 1916 </p>
79.88	<p>dig pits, 18 X 18 X 12 ins. E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor. Cor. of secs. 15, 16, 21 and 22. Land, level. Soil, 2nd rate. Timber, scattering palo verde.</p>
40.00	<p>N. 0° 2' W. bet. secs. 15 and 16. Over level and gently rolling land, through scattering timber. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 16:S 15 1916 </p>
80.00	<p>dig pits, 18 X 18 X 12 ins. N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.</p> <p style="text-align: center;"> T 4 N R 4 W <u>S 9 :S 10</u> S 16:S 15 1916 </p>
40.00 79.97	<p>dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist. and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, 2nd rate. Timber, scattering palo verde.</p> <p>East on a random line bet. secs. 10 and 15. Set temp. ¼ sec. cor. Intersect N. and S. line, 1 lk. N. of cor. of secs. 10, 11, 14 and 15. Thence West on a true line bet. secs. 10 and 15. Over level land, through scattering timber.</p>

14

Subdivision of T.4 N., R.4 W

<p>Chains 13.00 39.98½</p>	<p>Wagon road brs. N. and S. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">¼ $\frac{S 10}{S 15}$ 1915</p> <p>dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.</p>
<p>79.97</p>	<p>Cor. of secs. 9, 10, 15 and 16. Land, level. Soil, 2nd rate. Timber, scattering palo verde.</p>
<p>19.00 40.00</p>	<p>N. 0° 2' W. bet. secs. 9 and 10. Over gently rolling land, through scattering timber. Wagon road brs. E. and W. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">¼ S 9 : S 10</p> <p style="text-align: center;">1916</p> <p>dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise amount of earth, 3½ ft. base, 1½ ft. high, W. of cor.</p>
<p>80.00</p>	<p>Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.</p> <p style="text-align: center;">T 4 N R 4 W S 4 : S 3 S 9 : S 10 1916</p> <p>dig pits, 18 X 18 X 12 ins. in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, 2nd rate. Timber, scattering palo verde and cat claw.</p>
<p>40.00 80.00</p>	<p>East on a random line bet. secs. 3 and 10. Set temp. ¼ sec. cor. Intersect N. and S. line, 2 lks. S. of cor. of secs. 2, 3, 10 and 11. Thence</p>
<p>40.00</p>	<p>S. 89° 59' W. on a true line bet. secs. 3 and 10. Over gently rolling land, through scattering timber. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p>
<p>80.00</p>	<p style="text-align: center;">¼ $\frac{S 3}{S 10}$ 1916</p> <p>dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.</p> <p>Cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, 2nd rate. Timber, scattering palo verde.</p>

Subdivision of T.4 N..R.4 W.

Chains

40.00 N. 0° 2' W. bet. secs. 3 and 4.
 Over level and rolling land, through scattering timber.
 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 4 :S 3

70.76 1916
 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 Intersect 1st standard parallel N., 24.29 chs. W. of reestab.
 standard cor. of secs. 34 and 35, as described in
 book "A". At point of intersection
 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in
 the ground, for C.C. of secs. 3 and 4, with brass cap
 mkd.

T 5 N R 4 W
S 34
 S 4:S 3
 T 4 N:R 4 W
 C C

1916
 dig pits, 24 X 18 X 12 ins., crosswise on each line,
 E. and W., 3 ft., and S. of cor. 7 ft. dist.; and
 raise a mound of earth, 4 ft. base, 2 ft. high, S. of
 cor.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, scattering palo verde and cat claw.

40.00 From the cor. of secs. 4, 5, 32 and 33, on Sbdy. of Tp.,
 as described in book "B."
 N. 0° 2' W. bet. secs. 32 and 33.
 Over gently rolling land, through scattering timber.
 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 32:S 33

55.00 1916
 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
 dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
 high, W. of cor.

80.00 Wash, 75 lks. wide, 4 ft. deep, course; S. 30° W.
 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in
 the ground for cor. of secs. 28, 29, 32 and 33, with
 brass cap mkd.

T 4 N R 4 W
S 29:S 28
 S 32:S 33

1916
 dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft.
 dist.; and raise a mound of earth, 4 ft. base, 2 ft.
 high, W. of cor.
 Land, level, and gently rolling.
 Soil, 2nd and 3rd rates.
 Timber, scattering palo verde and mesquite.

40.00 East on a random line bet. secs. 28 and 33.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.98 Intersect N. and S. line, 6 lks. S. of cor. of secs. 27,
 28, 33 and 34.

39.99 Thence
 S. 89° 57' W. on a true line bet. secs. 28 and 33.
 Over gently rolling land, through scattering timber.
 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

16

Subdivision of T. 4 N., R. 4 W.

Chains

$\frac{1}{4}$ S 28
S 33
1916

79.98 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
Cor. of secs. 28, 29, 32 and 33.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.

1.80 N. 0° 2' W. bet. secs. 28 and 29.
Over level land, through scattering timber.
Road, brs. NE. and SW.
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
S 29: S 28

80.00 1916
dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high W. of cor.
Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

T 4 N R 4 W
S 20: S 21
S 28: S 29

1916
dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.

40.00 East on a random line bet. secs. 21 and 28.
Set temp. $\frac{1}{4}$ sec. cor.
79.87 Intersect N. and S. line, 10 lks. S. of cor. of secs. 21, 22, 27 and 28.

Thence
S. 89° 56' W. on a true line bet. secs. 21 and 28.
Over level land, through scattering timber.
19.62 Wagon road, brs. NE. and SW.
39 23½ Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 21
S 28
1916

79.87 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
Cor. of secs. 20, 21, 28 and 29.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.

40.00 N. 0° 2' W. bet. secs. 20 and 21.
Over gently rolling land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Subdivision of T.4 N., R.4 W.

Chains

$\frac{1}{4}$
S 20:S 21

1916

dig pits, 18 X 18 X 12 ins., N. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

- 55.00 Wash, 150 lks. wide, 10 ft. deep, course, W.
- 75.00 Wash, 115 lks. wide, 20 ft. deep, course, W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

T 4 N R 4 W

S 17:S 16
S 20:S 21

1916

dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.
Soil, 2nd and 3rd rate.
Timber, scattering palo verde.

- 40.00 East on a random line bet. secs. 16 and 21.
- 79.90 Set temp. $\frac{1}{4}$ sec. cor.
- 79.90 Intersect N. and S line, at cor. of secs. 15, 16, 21 and 22.

Thence

West on a true line bet. secs. 16 and 21.
Over level and rolling land, through scattering timber.

- 39.95 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 16
S 21
1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

- 79.90 Cor. of secs. 16, 17, 20 and 21.
- Land, gently rolling.
- Soil, 2nd rate.
- Timber, scattering palo verde.

N. 0° 2' W. bet. secs. 16 and 17.
Over level and rolling land, through scattering timber.

- 10.00 Left bank of wash, 25 ft. deep, course, W.
- 15.00 Right bank of same wash, course W.
- 29.93 Wash, course, W.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 17:S 16

1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

Thence over rolling land.

- 54.90 Bank of Hassayampa River flat, brs. NE. and SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.

T 4 N R 4 W

S 8 :S 9
S 17:S 16

1916

18

Subdivision of T.4 N R 4 W.

Chains

dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.;
and raise a mound of earth, 4 ft. base, 2 ft. high,
W. of cor.

Land, level and rolling.
Soil, 2nd and 3rd rates.
Timber, scattering palo verde.

40.00 East on a random line bet. secs. 9 and 16.
Set temp. $\frac{1}{4}$ sec. cor.
79.90 Intersect N. and S. line, 9 lks. S. of cor. of secs.
9, 10, 15 and 16.

Thence
S. $89^{\circ} 56'$ W. on a true line bet. secs. 9 and 16.
Over level land, through scattering timber.
39.95 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 9 \\ S 16 \\ 1916 \end{array}$$

79.90 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, N. of cor.
Cor. of secs. 8, 9, 16 and 17.
Land, level and gently rolling.
Soil, 2nd and 3rd rates.
Timber, scattering palo verde.

12.20 N. $0^{\circ} 2'$ W. bet. secs. 8 and 9.
Over level Hassayampa River flat.
Road brs. E. and W., W. to windmill.
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 8 : S 9 \end{array}$$

80.00 1916
dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$
ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in
the ground, for cor. of secs. 4, 5, 8 and 9, with
brass cap mkd.

$$\begin{array}{l} T 4 N R 4 W \\ S 5 : S 4 \\ S 8 : S 9 \\ 1916 \end{array}$$

dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft.
dist.; and raise a mound of earth, 4 ft. base, 2 ft.
high, W. of cor.

Land, level.
Soil, 2nd rate.
No timber.
Undergrowth, palo verde, cat claw, mesquite, and grease-
wood.

40.00 East on a random line bet. secs. 4 and 9.
Set temp. $\frac{1}{4}$ sec. cor.
79.80 Intersect N. and S. line, at cor. of secs. 3, 4, 9 and
10.

Thence
West on a true line bet. secs. 4 and 9.
Over gently rolling land.

00.00

Subdivision of T.4 N., R.4 W.

Chains

39.90 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 4 / S 9 1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise amount of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

79.80 Cor. of secs. 4, 5, 8 and 9. Land, gently rolling. Soil, 2nd and 3rd rates. Timber, scattering palo verde.

40.00 N. 0° 2' W. on a true line bet. secs. 4 and 5. Over level valley land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 5 : S 4

1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

70.85 Intersect 1st standard parallel N., 23.82 chs. W. of reestab. standard cor. of secs. 33 and 34, as described in book "A." At point of intersection, Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for C.C. of secs. 4 and 5, with brass cap mkd.

T 5 N R 4 W / S 33

S 5 : S 4

T 4 N : R 4 W

C C

1916

dig pits, 24 X 18 X 12 ins., crosswise on each line, E. and W., 3 ft. and S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, S. of cor.

Land, level. Soil, 2nd rate. Timber, none. Undergrowth, palo verde, mesquite, cat claw, cactus and greasewood.

40.00 From the cor. of secs. 5, 6, 31 and 32, on S. bdy. of Tp., described in book "B." N. 0° 3' W. bet. secs. 31 and 32. Over gently rolling land, through scattering timber. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 31 : S 32

1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T 4 N R 4 W

S 30 : S 29

S 31 : S 32

1916

Chains	
	<p>dig pits, 18 X 18 X 12 ins., in each sec.; 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, gently rolling. Soil, 2nd and 3rd rates. Timber, scattering palo verde.</p>
40.00	East on a random line bet. secs. 29 and 32. Set temp. ¼ sec. cor.
80.00	Intersect N. and S. line, 10 lks. S. of cor. of secs. 28, 29, 32 and 33. Thence S. 89° 56' W. on a true line bet. secs. 29 and 32. Over level land, through scattering timber.
1.50	Wagon road brs. NE. and SW.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 29 \\ S 32 \\ 1916 \end{array}$
80.00	<p>dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor. Cor. of secs. 29, 30, 31 and 32. Land, level. Soil, 2nd rate. Timber, scattering palo verde.</p>
40.00	West on a random line bet. secs. 30 and 31. Set temp. ¼ sec. cor.
79.67	Intersect W. bdy. of Tp. (1st Guide Mer. W.) 8 lks. S. of cor. of secs. 25, 30, 31 and 36, described in Book "A." Thence S. 89° 57' E. on a true line bet. secs. 30 and 31. Over rolling land, through scattering timber. In Hassayampa River flat.
10.00	Main channel of Hassayampa River, about 3 chs. wide, dourse, S.
25.00	E. bank of Hassayampa River flat brs. N. and S.
39.67	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 30 \\ S 31 \\ 1916 \end{array}$
50.00	and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Asc. 28 ft. to
51.30	Over nearly level land, to
55.00	Asc. 18 ft. to
56.30	Over nearly level land, to
60.00	Asc. 22 ft. to
79.67	Over nearly level land, to Cor. of secs. 29, 30, 31 and 32. Land, level and rolling. Soil, 2nd and 3rd rate. Timber, scattering palo verde.
35.00	N. 0° 3' W. bet. secs. 29 and 30. Over level and hilly land, through scattering timber.
39.93	Wash, 225 lks. wide, 5 ft. deep, course, W.
40.00	N. bank of wash, 150 lks. wide, 30 ft. deep, course, W. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

Subdivision of T.4 N., R.4 W.

Chains

$\frac{1}{4}$
S 30:S 29

1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Asc. 28 ft. to
42.67 Desc. 30 ft. to
44.92 Wash, 3 chs. wide, 20 ft. deep, course, W.
54.29 Asc. 35 ft. to
54.89 Over level land, to
59.85 Desc. 40 ft. to
62.24 Asc. 20 ft. to
64.80 Desc. 28 ft. to
69.80 Over level land, to
71.79 Asc. 14 ft. to
74.78 Desc. 17 ft. to
78.00 Bank of Hassayampa River flat, brs. NE. and SW.

Thence over Hassayampa River flat.
80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T 4 N R 4 W
S 19:S 20
S 30:S 29
1916

dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level and hilly.
Soil, 3rd rate.
Timber, scattering palo verde,

40.00 East on a random line bet. secs. 20 and 29.
79.92 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 2 lks. S. of cor. of secs. 20, 21, 28 and 29.

Thence
S. 89° 59' W. on a true line bet. secs. 20 and 29.
Over rolling land, through scattering timber.
39.96 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 20
S 29
1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

45.00 Desc. gradual slope, 174 ft. to
79.00 Bank of Hassayampa River flat brs. NE. and SW.
79.92 Cor. of secs. 19, 20, 29 and 30.
Land, rolling.
Soil, 2nd and 3rd rate.
Timber, scattering palo verde.

40.00 West on a random line bet. secs. 19 and 30.
79.73 Set temp. $\frac{1}{4}$ sec. cor.
Intersect W. bdy. of Tp., (1st Guide Mer. W.) 8 lks. S. of cor. of secs. 19, 24, 25 and 30, described in Book "A."

Thence
S. 89° 57' E. on a true line bet. secs. 19 and 30.
Over Hassayampa River flat, through scattering timber.
1.10 Wagon road brs. N. and S., N. to windmill.
39.73 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

22

Subdivision of T.4 N., R.4 W.

Chains

$$\frac{1}{4} \frac{S 19}{S 30}$$
 11916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

73.00 Main channel of the Hassayampa River, 3 chs. wide, course, S.
79.73 Cor., of secs. 19, 20, 29 and 30.
Soil, 2nd rate. Land, level.
Timber, scattering palo verde.

N. 09° 3' W. bet. secs. 19 and 20.

Over level land, of the Hassayampa River flat, through scattering timber.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins., in the ground, for ¼ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 19}{S 20}$$

1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 in. in diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

T 4 N R 4 W

S 18:S 14

S 19:S 20

1916

dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level.

Soil, 2nd rate.

Timber, scattering palo verde, and cat claw.

East on a random line bet. secs. 17 and 20.

40.00 Set temp. ¼ sec. cor.

79.86 Intersect N. and S. line, 12 lks. S. of cor. of secs. 16, 17, 20 and 21, with

Thence

S. 89° 55' W. on a true line bet. secs. 17 and 20.

Over gently rolling land, through scattering timber.

28.86 Wash, 150 lks. wide, 4 ft. deep, course, N. 75° W.

32.86 Bank of Hassayampa River flat, brs. NE. and SW.

39.93 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 17}{S 20}$$
 1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of post,

79.86 Cor. of secs. 17, 18, 19 and 20.

Land, level and gently rolling.

Soil, 2nd and 3rd rates.

Timber, scattering palo verde and cat claw.

West on a random line bet. secs. 18 and 19.

40.00 Set temp. ¼ sec. cor.

79.70 Intersect W. bdy. of Tp., (1st Guide Mer. W.) 26 lks. S. of cor. of secs. 13, 18, 19 and 24, described in Book "A."

Thence

Subdivision of T.4 N.,R.4 W.

Chains	
	S. 89° 49' E. on a true line bet. secs. 18 and 19. Desc. 51 ft. to
5.00	Thence over gently rolling land,
27.10	Main road brs. N. and S.
30.00	Enter Hassayampa River flat, brs. N. and S.
39.70	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 18 \\ S 19 \\ 1916 \end{array}$
	dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
77.50	Main channel of Hassayampa River, about 2 chs. wide, course, S.
79.70	Cor. of secs. 17, 18, 19 and 20. Land, level and rolling. Soil, 2nd rate. No timber. Undergrowth, palo verde, mesquite, cat claw, greasewood, sagebrush and cactus.
<hr/>	
	N. 0° 3' W. bet. secs. 17 and 18. Along the main channel of the Hassayampa River, through scattering undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 18:S 17 \\ 1916 \end{array}$
	dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
77.00	Leave main channel of Hassayampa River, course, from N. 5° E. to S.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.
	$\begin{array}{r} T 4 N R 4 W \\ S 7 :S 8 \\ S 18:S 17 \\ 1916 \end{array}$
	dig pits, 18 X 18 X 12 ins., in each sec.; 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, level. Soil, sandy, 2nd rate. No timber. Undergrowth, palo verde, mesquite, cat claw and greasewood.
<hr/>	
	East on a random line bet. secs. 8 and 17.
40.00	Set temp. ¼ sec. cor.
79.70	Intersect N. and S. line, 2 lks. N. of cor. of secs. 8, 9, 16 and 17. Thence
	N. 89° 59' W. on a true line bet. secs. 8 and 17. Over level land, of Hassayampa River flat, through scattering undergrowth.
39.85	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 8 \\ S 17 \\ 1916 \end{array}$

Chains	
77.50	dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
79.70	Main channel of Hassayampa River, about 2 chs. wide, course, S. Cor. of secs. 7, 8, 17 and 18. Land, level. Soil, sandy 2nd rate. No timber. Undergrowth, palo verde, mesquite, cat claw and greasewood.
40.00	West on a random line, bet. secs. 7 and 18.
79.63	Set temp. ¼ sec. cor. Intersect W. bdy. of Tp., (1st Guide Mer. W.) 30 lks. S of cor. of secs. 7, 12, 13 and 18, described in Book "A." Thence S. 89° 47' E. on a true line bet. secs. 7 and 18. Over gently rolling land, through scattering undergrowth. Road brs. NW. and SE. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
35.70	$\begin{array}{r} \frac{1}{4} \text{ S } 7 \\ \text{S } 18 \\ \hline 1916 \end{array}$
47.10	and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
59.60	Main road to windmill, brs. N. and S.
79.63	Enter Hassayampa River flat, brs. N. and S. Cor. of secs. 7, 8, 17 and 18. Land, gently rolling. Soil, 2nd rate. No timber. Undergrowth, palo verde, mesquite, sagebrush, greasewood. and cactus.
28.00	N. 0° 3' W. bet. secs. 7 and 8. Over level land, of Hassayampa River flat,, through scattering undergrowth.
37.00	Enter channel of Hassayampa River, course, from N. 10° W. to S. 10° E.
40.00	Leave river channel course, from NW. to SE.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
80.00	$\begin{array}{r} \text{S } 7 \text{ : } \text{S } 8 \\ \hline 1916 \end{array}$
80.00	dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor. Thence along E. bank of channel. Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.
80.00	$\begin{array}{r} \text{T } 4 \text{ N } \text{R } 4 \text{ W} \\ \text{S } 6 \text{ : } \text{S } 5 \\ \hline \text{S } 7 \text{ : } \text{S } 8 \\ \hline 1916 \end{array}$
80.00	dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, level. Soil, sandy 2nd rate. No timber. Undergrowth, palo verde, mesquite, cat claw, greasewood and sagebrush.

Subdivision of T.4 N., R.4 W.

Chains	
40.00	East on a random line bet. secs. 5 and 8.
79.80	Set temp. $\frac{1}{4}$ sec. cor.
	Intersect N. and S. line, 12 lks. N. of cor. of secs.
	4, 5, 8 and 9.
	Thence
	N. $89^{\circ} 55'$ W. on a true line bet. secs. 5 and 8.
	Over level land, through dense undergrowth.
39.90	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
	the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 5}{S \ 8}$
	1916
	dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
	dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
	high, N. of cor.
79.80	Cor. of secs. 5, 6, 7 and 8.
	Land, level bottom land.
	Soil, sandy 2nd rate.
	No timber.
	Undergrowth, palo verde, mesquite, cat claw and greasewood.

Chains

70.70

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
 Intersect 1st standard parallel N., 23.67chs.W.of reestab. standard cor. of secs. 32 and 33, as described in book "A:" X At point of intersection,
 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for C.C. of secs. 5 and 6, with brass cap mkd.

T 5 N R 4 W
 S 32
 S 6:S 5
 T 4 N:R 4 W
 C C
 1916

dig pits, 24 X 18 X 12 ins., crosswise on each line, E. and W., 3 ft. and S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, S. of cor.
 Land, level.
 Soil, 2nd rate.
 No timber.
 Undergrowth, greasewood.

--- GENERAL DESCRIPTION ---

This township consists of level land, throughout with the exception of the extreme SE. and W. and NW. portions, which are gently rolling or hilly.
 The Hassayampa River, whose overflow area may constitute a strip about one mile wide flows towards the S. and SW., through the W. one-third of the township, the main channel of the river being about 2 chs. wide. This river contains little or no water during the dry season, but during periods of considerable rain is subject to overflow of the surrounding flat country.
 The soil varies from sandy 2nd rate to stony 3rd rate according to the land surface, whether level or rolling.
 The vegetation consists of palo verde, cat claw, mesquite, greasewood, cactus and sagebrush.
 A windmill is located near the road, in the W. half of section 8.

- .0000.-

CERTIFICATES
For ~~FINAL OATH~~ OF UNITED STATES SURVEYOR TRANSITMEN,

See Book "C"

I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

U. S. Surveyor.

Subscribed by said _____, and sworn to before me }
 this _____ day of _____, 191____



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, JUL 20 1918

The foregoing field notes of the survey of the
Subdivision Lines of

TOWNSHIP 4 NORTH, RANGE 4 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by Roy J. Gill and Hans D. Voigt, U. S. Transitmen,
 under his special instructions dated Dec. 12, 1914, for Group 39, Arizona 191____, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.

~~I certify that the foregoing transcript of the field notes of the above-described surveys in _____, has been correctly copied from the original notes on file in this office.~~