

3060

Book "T"

4-679

(Subdivisions)

BOOK 3060

257

FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION LINES

OF

TOWNSHIP 4 NORTH, RANGE 6 WEST.

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

Roy J. Gill and Hans D. Voigt,

U.S. Transitmen,

~~In the capacity of U. S. Surveyor~~, under instructions dated December 12., 1914, issued by the United States Surveyor General to govern surveys included in Group No. 39, which were approved by the Commissioner of the General Land Office, January 7., 1915.

Survey commenced January 28., 1916.

Survey completed February 11., 1916.

3060

3060

1A






BOOK 3060

Book "T"
 (Subdivisions)
 Group 39 - Arizona.

INDEX DIAGRAM.

Township 4 North, Range 6 West.

First Standard Parallel North										
6	28	5	21	4	15	3	12	2	7	1
28		28		21		16		11		7
7	27	8	21	9	15	10	11	11	6	12
27		26		20		15		11		6
18	25	17	20	16	15	15	10	14	5	13
25		25		19		14		10		5
19	25	20	19	21	14	22	9	23	4	24
24		24		18		13		9		4
30	23	29	18	28	13	27	8	26	4	25
23		22		18		13		8		3
31	22	32	17	33	12	34	7	35	3	36

-  Subdivision lines surveyed under this Group.
-  Township boundaries surveyed under this Group.
Notes in Book "B."
-  Standard lines resurveyed under this Group.
Notes in Book "A."
-  Unsurveyed lines.
-  Accepted surveys.

SUBDIVISIONS OF
TOWNSHIP 4 NORTH, RANGE 6 WEST.

DATE INDEX.

2-9-16	2-9-16	2-9-16	2-9-16	2-9-16	2-9-16	1-5-16
First	Standard	Parallel	North,	Resurvey.		
6	5	4	3	2	1	
2-11-16	2-11-16	2-11-16	2-10-16	2-9-16	2-7-16	1-26-16
7	8	9	10	11	12	
2-11-16	2-10-16	2-10-16	2-9-16	2-7-16	2-7-16	1-26-16
18	17	16	15	14	13	
2-10-16	2-10-16	2-9-16	2-7-16	2-7-16	2-7-16	1-26-16
19	20	21	22	23	24	
2-10-16	2-9-16	2-7-16	2-7-16	2-7-16	1-28-16	1-26-16
30	29	28	27	26	25	
2-5-16	2-5-16	2-7-16	2-7-16	1-28-16	1-28-16	1-26-16
31	32	33	34	35	36	
2-5-16	2-7-16	2-7-16	1-28-16	1-28-16	1-26-16	1-26-16
1-22-16	1-21-16	1-21-16	1-21-16	1-21-16	1-21-16	1-21-16

Lines dated in red ink were surveyed by Roy J. Gill,
U.S. Transitman.

Lines dated in green were surveyed by Hans D. Voigt,
U. S. Transitman.

Subdivision of T.4 N., R.6 W.

Chains

Survey executed by Roy J. Gill and Hans D. Voigt, U. S. Transitmen, using Young and Son's light mountain transits Nos. 8583 and 8293 respectively. From recent and repeated field tests of the transits and solar attachments, they are known to be in satisfactory adjustment. During the survey of the subdivision of this township, the transits and solar attachments were maintained in adjustment by frequent tests on a true meridian, determined by observations on Polaris, all necessary adjustments being made.

40.00 From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., described in book "B."
N. 0° 1' W. bet. secs. 35 and 36.
Over gently rolling land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap
S35 | S36
1916

80.00 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins., diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, mkd. on brass cap
T4N R6W
S26 | S25
S35 | S36
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

40.00 East on a random line bet. secs. 25 and 36.
79.92 Set temp. $\frac{1}{4}$ sec. cor.
Intersect E. bdy. of Tp., 3 lks. S. of cor. of secs. 25, 30, 31 and 36, as described in book "B."
Thence
S. 89° 59' W. on a true line bet. secs. 25 and 36.
Over gently rolling land, through scattering timber.
19.90 Wash, course, SE.
29.90 Wash, 6 ft. deep, course, SE.
39.96 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. mkd. on brass cap
 $\frac{1}{4}$ S 25
S 36
1916

58.60 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
69.90 Wagon road to Wickenburg brs. N. and S.
79.92 Wash, 75 lks. wide, 6 ft. deep, course, SE.
The cor. of secs. 25, 26, 35 and 36.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

Chains

N. 0° 1' W. bet. secs. 25 and 26.
 Over gently rolling land, through scattering undergrowth.
 .90 Wash, 10 lks. wide, 4 ft. deep, course, S. 70° E.
 8.00 Wash, 60 lks. wide, 3 ft. deep, course, E.
 13.70 Wash, 15 lks. wide, 6 ft. deep, course, E.
 29.30 Road brs. N. 60° W. and S. 60° E.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap.

S26 | S25
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 44.30 Wash, 2 chs. wide, 15 ft. banks, course, E.
 54.50 Wash, 20 lks. wide, 4 ft. deep, course, SE.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground for cor. of secs. 23, 24, 25 and 26, mkd.
 on brass cap

T4N R6W
 S23 | S24
 S26 | S25
 1916

dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft.
 dist.; and raise a mound of earth, 4 ft. base, 2 ft.
 high, W. of cor.
 Land, rolling.
 Soil, 2nd rate.
 No timber.
 Undergrowth, cat claw, sagebrush, mesquite, greasewood,
 and palo verde.

40.00 East on a random line bet. secs. 24 and 25.
 79.99 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect E. bdy. of Tp. 5 lks. N. of cor. of secs.
 19, 24, 25 and 30, as described in book "B."
 Thence
 39.99½ N. 89° 58' W. on a true line bet. secs. 24 and 25.
 Over rolling land, through scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S 24
 $\frac{1}{4}$ S 25
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 N. of cor.
 54.20 Road brs. N. and S.
 79.99 The cor. of secs. 23, 24, 25 and 26.
 Land, rolling.
 Soil, gravelly, 3rd rate.
 No timber.
 Undergrowth, cat claw, palo verde, mesquite, sagebrush
 and greasewood.

1.00 N. 0° 1' W. bet. secs. 23 and 24.
 40.00 Over rolling land, through scattering timber and under-
 growth.
 Dim road brs. NW. and SE.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

Subdivision of T.4 N., R.6 W.

Chains

1
S23 | S24
1916

80.00 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, mkd. on brass cap

T4N R6W
S14 | S13
S23 | S24
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.
Undergrowth, greasewood and sagebrush.

40.00 East on a random line bet. secs. 13 and 24.
Set temp. 1/4 sec. cor.
80.02 Intersect E. bdy. of Tp. 22 lks. N. of cor. of secs. 13, 18, 19 and 24, as described in book "B."

Thence
N. 89° 51' W. on a true line bet. secs. 13 and 24.
Over level land, through scattering timber and undergrowth.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

1/4 S 13
S 24
1916

45.50 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
Wash, course, SE.
52.50 Road brs. N. and S.
80.02 The cor. of secs. 13, 14, 23 and 24.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.
Undergrowth, sagebrush and greasewood.

11.00 N. 0° 1' W. bet. secs. 13 and 14.
Over gently rolling land, through scattering undergrowth.
Wash, 35 lks. wide, 4 ft. deep, course, E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

1/4 S 14 | S 13
1916

80.00 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs, 11, 12, 13 and 14, mkd. on brass cap

T4N R6W
S11 | S12
S14 | S13
1916

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 Land, gently rolling.
 Soil, gravelly, 3rd rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw, sagebrush
 and greasewood.

40.00
80.14

East on a random line bet. secs. 12 and 13.
 Set temp. ¼ sec. cor.
 Intersect E. bdy. of Tp. 16 lks. N. of cor. of secs. 7,
 12, 13 and 18, as described in book "B".

14.35
40.07

Thence
 N. 89° 53' W. on a true line bet. secs. 12 and 13.
 Over rolling land, through scattering undergrowth.
 Wash, 15 lks. wide, 5 ft. deep, course, SE.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for ¼ sec. cor., mkd. on brass cap

¼ S 12
 S 13
 1916

53.85
78.84
80.14

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
 dist.; and raise a mound of earth, 3½ ft. base, 1½ ft.
 high, N. of cor.
 Road brs. N. and S.
 Road brs. N. 20° W. and S. 20° E.
 The cor. of secs. 11, 12, 13 and 14.
 Land, rolling.
 Soil, gravelly, 3rd rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw, sagebrush
 and greasewood.

2.00
40.00

N. 0° 1' W. bet. secs. 11 and 12.
 Over rolling land, through scattering undergrowth.
 Road brs. NW. and SE.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for ¼ sec. cor., mkd. on brass cap

S 11 | S 12
 1916

68.20
80.00

dig pits, 18 X 18 X 12 ins. N. and S. of post, 3 ft.
 dist.; and raise a mound of earth, 3½ ft. base, 1½ ft.
 high, W. of cor.
 Wash, 20 lks. wide, 4 ft. deep, course, E.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of secs. 1, 2, 11 and 12, mkd. on
 brass cap

T4N R6W
 S 2 | S 1
 S11 | S12
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 Land, rolling.
 Soil, 2nd rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw, sagebrush
 and greasewood.

Subdivision of T.4 N..R.6 W.

Chains

40.00
80.16

East on a random line bet. secs. 1 and 12.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect E. bdy. of Tp., 13 lks. N. of cor. of secs.
1, 6, 7 and 12, as described in book "B."

Thence

32.76
40.08

N. $89^{\circ} 54'$ W. on a true line bet. secs. 1 and 12.
Over rolling land, through scattering undergrowth.
Wash, 25 lks. wide, 4 ft. deep, course, S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 1
S 12
1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, N. of cor.

54.56
58.76
80.16

Road brs. N. and S.
Wash, 50 lks. wide, 4 ft. deep, course, SE.
The cor. of secs. 1, 2, 11, and 12.

Land, rolling.

Soil, 2nd rate.

No timber.

Undergrowth, greasewood, cat claw, sagebrush, palo verde
and mesquite.

40.00

N. $0^{\circ} 1'$ W. bet. secs. 1 and 2.
Over level land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. diam.; 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S 2 | S 1
1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, W. of cor.

70.21

Intersect 1st standard parallel N., 18.68 chs W. of reestab.
standard cor. of Ts. 5 N., Rs. 5 and 6 W., as described
in book "A" At point of intersection,
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for C.C. of secs. 1 and 2, mkd. on brass
cap mkd.

T5N R6W
S36
S 2 | S 1
T4N | R6W
C C
1916

dig pits, 24 X 18 X 12 ins., crosswise on each line,
E. and W., 3 ft. and S. of post, 7 ft. dist.; and
raise a mound of earth, 4 ft. base, 2 ft. high, S. of
cor.

Land, level.

Soil, 2nd rate.

Timber, scattering palo verde and cat claw.

From the cor. of secs. 2, 3, 34 and 35. on S. bdy. of Tp.,
as described in book "B."

N. $0^{\circ} 1'$ W. bet. secs. 34 and 35.

Over gently rolling land, through scattering undergrowth.

Chains

14.30

Wash, 30 lks. wide, 5 ft. deep, course, E.

33.20

Wash, 50 lks. wide, 4 ft. deep, course, SE.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S34 | S35
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

49.20

Road brs. E. and W.

71.30

Dim road brs. E. and W.

78.80

Wash, 25 lks. wide, 4 ft. deep, course, S. 70° E.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, mkd. on brass cap

T4N R6W
S27 | S26
S34 | S35
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, 2nd rate.

No timber.

Undergrowth, mesquite, palo verde, cat claw, sagebrush and greasewood.

40.00

East on a random line bet. secs. 26 and 35.

80.00

Set temp. $\frac{1}{4}$ sec. cor.

Intersect N. and S. line 7 lks. S. of cor. of secs. 25, 26, 35 and 36.

Thence

S. 89° 57' W. on a true line bet. secs. 26 and 35.

Over rolling land, through scattering undergrowth.

14.00

Road brs. NW. and SE.

32.30

Wash, 10 lks. wide, 4 ft. deep, course, S.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 26
S 35
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

55.70

Wash, 100 lks. wide, 5 ft. deep, course, S.

61.30

Wash, 25 lks. wide, 4 ft. deep, course, S.

68.75

Wash, 25 lks. wide, 3 ft. deep, course, S.

69.50

Wash, 30 lks. wide, 4 ft. deep, course, SE.

80.00

The cor. of secs. 26, 27, 34 and 35.

Land, rolling.

Soil, gravelly, 3rd rate.

No timber.

Undergrowth, cat claw, sagebrush, greasewood, mesquite, and palo verde.

N. 0° 1' W. bet. secs. 26 and 27.

Over rolling land, through scattering timber. and undergrowth.

7.50

Wash, course, SE.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

Subdivision of T.4 N. R.6 W.

Chains

$\frac{1}{4}$
S27 | S26
1916

46.50 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
80.00 dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, W. of cor.
Wash, 80 lks. wide, course, SE.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 22, 23, 26 and 27, mkd.
on brass cap

T4N R6W
S22 | S23
S27 | S26
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
Land, rolling.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.
Undergrowth, sagebrush and greasewood.

40.00 East on a random line bet. secs. 23 and 26.
79.96 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 11 lks. N. of cor. of secs.
23, 24, 25 and 26.

Thence
N. 89° 55' W. on a true line bet. secs. 23 and 26.
Over level land, through scattering timber and under-
growth.

13.00 Wash, 1 ch. wide, course, S.
39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 23
S26
1916

67.50 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
79.96 N. of cor.
Wash, 100lks. wide, course, SE.
The cor. of secs. 22, 23, 26 and 27.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.
Undergrowth, sagebrush and greasewood.

25.50 N. 0° 1' W. bet. secs. 22 and 23.
40.00 Over gently rolling land, through scattering undergrowth.
Wash, 100 lks. wide, 8 ft. deep, course, SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S22 | S23
1916

68.70 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
80.00 W. of cor.
Wash, 2 chs. wide, 15 ft. deep, course, S. 70° E.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 14, 15, 22 and 23, mkd.
on brass cap

T4N R6W
S15 | S14
S22 | S23
1916

Chains

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
Land, rolling.
Soil, 2nd rate.
No timber.
Undergrowth, palo verde, cat claw, sagebrush, and grease-
wood.

40.00 East on a random line bet. secs. 14 and 23.
79.90 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 16 lks. S. of cor. of secs. 13,
14, 23 and 24.
Thence
39.95 S. $89^{\circ} 53'$ W. on a true line bet. secs. 14 and 23.
Over rolling land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{r} \frac{1}{4} \text{ S } 14 \\ \hline \text{S } 23 \\ \hline 1916 \end{array}$$

51.20 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
65.20 dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
79.90 high, N. of cor.
Road brs. N. and S.
Road, brs. NW. and SE.
The cor. of secs. 14, 15, 22 and 23.
Land, rolling.
Soil, 3rd rate.
No timber.
Undergrowth, palo verde, mesquite, sagebrush, greasewood
and cat claw.

13.10 N. $0^{\circ} 1'$ W. bet. secs. 14 and 15.
40.00 Over gently rolling land, through scattering undergrowth.
Dim road brs. NW. and SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{r} \frac{1}{4} \\ \text{S } 15 \text{ S } 14 \\ \hline 1916 \end{array}$$

80.00 dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 10, 11, 14 and 15, mkd.
on brass cap

$$\begin{array}{r} \text{T4N R6W} \\ \text{S10 S11} \\ \hline \text{S15 S14} \\ \hline 1916 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
Land, gently rolling.
Soil, gravelly, 3rd rate.
Timber, none.
Undergrowth, mesquite, palo verde, cat claw, sagebrush
and greasewood.

Subdivision of T.4 N., R.6 W.

11

Chains

Eas

40.00

79.82

East on a random line bet. secs. 11 and 14.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 16 lks. S. of cor. of secs.
11, 12, 13 and 14.

Thence
S. $89^{\circ} 53'$ W. on a true line bet. secs, 11 and 14.
Over rolling land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ $\frac{S 11}{S 14}$
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

73.00

79.82

Wash, 25 lks. wide, 4 ft. deep, course, S.
The cor. of secs. 10, 11, 14 and 15.
Land, gently rolling.
Soil, gravelly, 3rd rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw, sagebrush
and greasewood.

40.00

N. $0^{\circ} 1'$ W. bet. secs. 10 and 11.
Over level land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ $\frac{S 10}{S 11}$
1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 2, 3, 10 and 11, mkd.
on brass cap

T4N R6W
 $\frac{S 3}{S 10}$ | $\frac{S 2}{S 11}$
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

Land, level.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

40.00

79.80

East on a random line bet. secs. 2 and 11.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line at cor. of secs. 1, 2, 11 and 12.
Thence

39.90

West on a true line bet. secs. 2 and 11.
Over level land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ $\frac{S 2}{S 11}$
1916

dig pits, 18 X 18 X 12 ins. E. and W. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, N. of cor.

79.80

The cor. of secs. 2, 3, 10 and 11.

Chains

Land, level.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

40.00

N. 0° 1' W. on a true line bet. secs. 2 and 3.
Over gently rolling land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S 3 | S 2
1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, W. of cor.

69.50

70.40

Wash, 20 lks. wide, 5 ft. deep, course, S. 70° E.
Intersect 1st. standard parallel N. 18.45 chs. W. of reestab.
standard cor. of secs. 35 and 36, T.5 N., R.6 W., as
described in book "A." At point of intersection,
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for C.C. of secs. 2 and 3, mkd. on brass
cap

T5N R6W
S35
S 3 | S 2
T4N | R6W
C C
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
S. of cor.

Land, gently rolling.

Soil, 2nd rate.

No timber.

Undergrowth, palo verde, cat claw, sagebrush, mesquite
and greasewood.

40.00

From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp.,
as described in book "B,"

N. 0° 2' W. bet. secs. 33 and 34.

Over level land, through scattering timber and undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S33 | S34
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

60.00

80.00

Wash, course SE.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 27, 28, 33 and 34, mkd.
on brass cap

T4N R6W
S28 | S27
S33 | S34
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

Land, level.

Soil, 2nd rate.

Timber, scattering palo verde and cat claw.

Undergrowth, greasewood.

Subdivision of T.4 N., R.6 W.

Chains

40.00
79.96

East on a random line bet. secs. 27 and 34.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 3 lks. S. of cor. of secs.
26, 27, 34 and 35.

Thence
S. $89^{\circ} 59'$ W. on a true line bet. secs. 27 and 34.
Over level land, through scattering timber.

3.15
39.98

Wash, 30 lks. wide, course, SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 27
 $\frac{1}{4}$ S 34
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

52.46
79.96

Wash, 50 lks. wide, course, SE.
The cor. of secs. 27, 28, 33 and 34.
Land, level.
Soil, sandy 2nd rate.
Timber, scattering palo verde and cat claw.

N. $0^{\circ} 2'$ W. bet. secs. 27 and 28 .
Over rolling land, through scattering undergrowth.

15.00
25.00
40.00

Wash, 70 lks. wide, 10 ft. deep, course, E.
Wash, 75 lks. wide, 10 ft. deep, course, E.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S28 $\frac{1}{4}$ S27
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

52.90
66.80
71.90
80.00

Wash, 20 lks. wide, 4 ft. deep, course, E.
Dim road brs. NW. and SE.
Wash, 20 lks. wide, 4 ft. deep, course, E.
Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in
the ground, for cor. of secs. 21, 22, 27 and 28, mkd.
on brass cap

T4N R6W
S21 | S22
S28 | S27
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

Land, gently rolling.
Soil, gravelly, 3rd rate.
No timber.
Undergrowth, palo verde, cat claw, mesquite, sagebrush,
and greasewood.

40.00
79.98

East on a random line bet. secs. 22 and 27
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 16 lks. S. of cor. of secs. 22,
23, 26 and 27.

19.00
24.00

Thence
S. $89^{\circ} 53'$ W. on a true line bet. secs. 22 and 27.
Over gently rolling land, through scattering undergrowth.
Road brs. NW. and SE.
Wash, 15 lks. wide, 4 ft. deep, course, SE.

Chains
39.99

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{r} \frac{1}{4} \text{ S } 22 \\ \text{S } 27 \\ 1916 \end{array}$$

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

51.90

Wash, 35 lks. wide, 3 ft. deep, course, SE.

56.10

Wash, 20 lks. wide, 3 ft. deep, course, SE.

63.30

Wash, 100 lks. wide, 3 ft. deep, course, SE.

79.98

The cor. of secs. 21, 22, 27 and 28.

Land, gently rolling.

Soil, gravelly, 3rd rate.

No timber.

Undergrowth, palo verde, cat claw, sagebrush, and greasewood.

N. 0° 2' W. bet. secs. 21 and 22.

Over gently rolling land, through scattering undergrowth

5.50

Wash, 25 lks. wide, 4 ft. deep, course, E.

15.00

Wash, 50 lks. wide, 4 ft. deep, course, E.

16.00

Wash, 50 lks. wide, 4 ft. deep, course, SE.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{r} \frac{1}{4} \\ \text{S } 21 \text{ S } 22 \\ 1916 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

44.80

Wash, 20 lks. wide, 3 ft. deep, course, E.

64.00

Wash, 35 lks. wide, 5 ft. deep, course, SE.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, mkd. on brass cap

$$\begin{array}{r} \text{T4N R6W} \\ \text{S16 S15} \\ \text{S21 S22} \\ 1916 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.

Soil, gravelly, 3rd rate.

No timber.

Undergrowth, palo verde, cat claw, mesquite, sagebrush and greasewood.

East on a random line bet. secs. 15 and 22.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

79.90

Intersect N. and S. line, 10 lks. S. of cor. of secs. 14, 15, 22 and 23.

Thence

S. 89° 56' W. on a true line bet. secs. 15 and 22.

Over gently rolling land, through scattering undergrowth.

5.90

Wash, 150 lks. wide, 5 ft. deep, course, S.

10.30

Wash, 75 lks. wide, 3 ft. deep, course, S.

Subdivision of T.4 N., R.6 W.

Chains
39.95

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

1/4 S 15
S 22
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

44.90
54.40
79.90

Wash, 150 lks. wide, 3 ft. deep, course, S.
Wash, 25 lks. wide, 4 ft. deep, course, S.
The cor. of secs. 15, 16, 21 and 22.

Land, gently rolling.
Soil, gravelly, 3rd rate.
No timber.

Undergrowth, mesquite, palo verde, cat claw, sagebrush and greasewood.

40.00

N. 0° 2' W. bet. secs. 15 and 16.
Over gently rolling land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

1/4 S 16 | S 15
1916

dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

50.00
80.00

Wash, 45 lks. wide, 3 ft. deep, course, E.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, mkd. on brass cap

T4N R6W
S 9 | S 10
S 16 | S 15
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

40.00
79.85

East on a random line bet. secs. 10 and 15.
Set temp. 1/4 sec. cor.
Intersect N. and S. line 10 lks. N. of cor. of secs. 10, 11, 14 and 15.

Thence
N. 89° 56' W. on a true line bet. secs. 10 and 15.
Over level land, through scattering timber.

39.92 1/2

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

1/4 S 10
S 15
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

75.85

Wash, 75 lks. wide, 4 ft. deep, course, SE.

Chains
79.85

The cor. of secs. 9, 10, 15 and 16.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.

5.00
34.70
40.00

N. 0° 2' W. bet. secs. 9 and 10
Over gently rolling land, through scattering undergrowth.
Wash, 100 lks. wide, 8 ft. deep, course, SE.
Road brs. NW. and SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S 9 | S 10
1916

80.00

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 3, 4, 9 and 10, mkd.
on brass cap

T4N R6W
S 4 | S 3
S 9 | S 10
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
Land, gently rolling.
Soil, gravelly, 3rd rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw, sagebrush,
and greasewood.

40.00
79.92

East on a random line bet. secs. 3 and 10.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 8 lks. S. of cor. of secs. 2, 3
10 and 11.

39.40
39.96

Thence
S. 89° 57' W. on a true line bet. secs. 3 and 10.
Over gently rolling land, through scattering undergrowth.
Wash, 30 lks. wide, 4 ft. deep, course, S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 3
S 10
1916

79.92

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.
The cor. of secs. 3, 4, 9 and 10.
Land, gently rolling.
Soil, gravelly, 3rd rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw, sagebrush
and greasewood.

40.00

N. 0° 2' W. on a true line bet. secs. 3 and 4.
Over gently rolling land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

Chains

S 4 | S 3
1916

63.90 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,
70.50 W. of cor.
Wash, 20 lks. wide, 4 ft. deep, course, SE.
Intersect 1st standard parallel N. 18.38 chs. W. of reestab.
standard cor. of secs. 34 and 35, T.5 N., R.6 W., as
described in book "A." At point of intersection,
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for C.C. of secs. 3 and 4, mkd. on brass cap

T5N R6W
S34
S 4 | S 3
T4N R6W
C C
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,
S. of cor.
Land, gently rolling.
Soil, gravelly, 3rd rate.
No timber.
Undergrowth, mesquite, palo verde, cat claw, sagebrush
and greasewood.

2.40 From the cor. of secs. 4, 5, 32 and 33, on S. hdy. of Tp.,
as described in book "B,"
N. 0° 2' W. bet. secs. 32 and 33.
Over hilly land, through scattering undergrowth.
7.99 Wash, 20 lks. wide, 5 ft. deep, course, E.
17.49 Asc. steep S. slope, 156 ft. to
19.26 Point of spur slopes E. Desc. N. slope, 47 ft. to
23.12 Head of wash, course, E. Asc. S. slope, 23 ft. to
25.60 Point of spur slopes, E. Desc. N. slope, 37 ft. to
40.00 Head of wash, course, E. Asc. S. slope, 27 ft. to
Point of spur slopes, E. Desc. N. slope, 216 ft. to
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for 1/4 sec. cor. mkd. on brass cap

S32 | S33
1916

53.18 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,
W. of cor.
Desc. N. slope, 122 ft. to
Wash, 15 lks. wide, 5 ft. deep, course, E. Asc. S. slope
90 ft. to
62.39 Point of spur slopes NE. Desc. N. slope, 98 ft. to
74.48 Wash, 20 lks. wide, 4 ft. deep, course, NE.
Thence over rolling land, to
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground for cor. of secs. 28, 29, 32 and 33, mkd.
on brass cap

T4N R6W
S29 | S28
S32 | S33
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,
W. of cor.
Land mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, cat claw, cactus, ocotillo,
sagebrush and greasewood.

Chains

40.00 East on a random line bet. secs. 28 and 33.
 79.76 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 19 lks. S. of cor. of secs.
 27, 28, 33 and 34.
 Thence
 S. $89^{\circ} 52'$ W. on a true line bet. secs. 28 and 33.
 Over gently rolling land, through scattering undergrowth.
 14.60 Dim road brs. NW. and SE.
 39.88 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{c} \frac{1}{4} S 28 \\ \frac{1}{4} S 33 \\ 1916 \end{array}$$

79.76 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 N. of cor.
 The cor. of secs. 28, 29, 32 and 33.
 Land, gently rolling.
 Soil, gravelly, 3rd rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw, cactus,
 sagebrush and greasewood.

21.00 N. $0^{\circ} 2'$ W. bet. secs. 28 and 29.
 30.00 Over gently rolling land, through scattering undergrowth
 40.00 Wash, 20 lks. wide, 6 ft. deep, course, E.
 Wash, 15 lks. wide, 4 ft. deep, course, E.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{c} S29 \uparrow S28 \\ 1916 \end{array}$$

40.20 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 71.10 Wash, 30 lks. wide, 8 ft. deep, course, E.
 78.60 Dim road brs. NW. and SE.
 80.00 Wash, 100 lks. wide, 4 ft. deep, course, E.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of secs. 20, 21, 28 and 29, mkd.
 on brass cap

$$\begin{array}{c} T4N R6W \\ S20 | S21 \\ S29 | S28 \\ 1916 \end{array}$$

and raise a mound of stone, 2 ft base, $1\frac{1}{2}$ ft. high
 W. of cor.
 Land, gently rolling.
 Soil, gravelly 3rd rate.
 Undergrowth, mesquite, palo verde, cactus, cat claw,
 sagebrush and greasewood.

40.00 East on a random line bet. secs. 21 and 28.
 79.82 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 18 lks. S. of cor. of secs.
 21, 22, 27 and 28.
 Thence
 S. $89^{\circ} 52'$ W. on a true line bet. secs. 21 and 28.
 Over gently rolling land, through scattering undergrowth.

Subdivision of T.4 N., R.6 W.

Chains
17.80
39.91

Wash, 25 lks. wide, 4 ft. deep, course, SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 21
S 28
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

44.80
76.70
79.82

Wash, course, S.
Same wash, course, NE.
The cor. of secs. 20, 21, 28 and 29.

Land, gently rolling.
Soil, 3rd rate.
No timber.
Undergrowth, palo verde, mesquite, sagebrush, cat claw,
cactus and greasewood.

30.00
40.00

N. 0° 2' W. bet. secs. 20 and 21. sec. 20 and 21.
Over gently rolling land, through scattering timber.
Wash, 75 lks. wide, 4 ft. deep, course, E.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$
S20 | S21
1916

dig pits 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 16, 17, 20 and 21, mkd.
on brass cap

T4N R6W
S17 | S16
S20 | S21
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

40.00
79.78

East on a random line bet. secs. 16 and 21.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 14 lks. N. of cor. of secs. 15,
16, 21 and 22.

Thence
N. 89° 54' W. on a true line bet. secs. 16 and 21.
Over gently rolling land, through scattering timber.

39.89

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 16
S 21
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

74.75

Wash, 110 lks. wide, 4 ft. deep, course, SE.

Chains
79.78

The cor. of secs. 16, 17, 20 and 21.
Land, rolling, and level.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

2.20
38.50
40.00

N. 0° 2' W. bet. secs. 16 and 17.
Over gently rolling land, through scattering undergrowth.
Wash, 2 chs. wide, 4 ft. deep, course, SE.
Road brs. N. 10° W. and S. 10° E.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S17 | S16
1916

80.00

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 8, 9, 16 and 17, mkd.
on brass cap.

T4N R6W
S 8 | S 9
S17 | S16
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
Land, gently rolling.
Soil, gravelly, 3rd rate.
No timber.
Undergrowth, mesquite, palo verde, cat claw, sagebrush,
ocotillo and greasewood.

40.00
79.92

East on a random line bet. secs. 9 and 16.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 9 lks. S. of cor. of secs.
9, 10, 15 and 16,

Thence

10.50
24.90
39.96

S. 89° 56' W. on a true line bet. secs. 9 and 16.
Over gently rolling land, through scattering undergrowth.
Wash, 40 lks. wide, 3 ft. deep, course, S.
Wash, 2 chs. wide, 3 ft. deep, course, SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 9
S 16
1916

79.92

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.
The cor. of secs. 8, 9, 16 and 17.
Land, gently rolling.
Soil, 3rd rate, gravelly.
No timber.
Undergrowth, cat claw, sagebrush, palo verde, greasewood
and mesquite.

Subdivision of T.4 N., R.6 W.

Chains

N. 0° 2' W. bet. secs. 8 and 9.
 Over gently rolling land, through scattering undergrowth.
 31.90 Wash, 40 lks. wide, 5 ft. deep, course, SE.
 39.00 Wash, 15 lks. wide, 4 ft. deep, course, SE.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$
 S 8 | S 9
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 76.30 Road, brs. NE. and SW., from Vulture to Independent mine.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of secs. 4, 5, 8 and 9, mkd. on
 brass cap

T4N. R6W
 S 5 | S 4
 S 8 | S 9
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 Land, gently rolling.
 Soil, gravelly, 3rd rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw, sagebrush
 and greasewood.

40.00 East on a random line bet. secs. 4 and 9.
 79.92 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 16 lks. S. of cor. of secs.
 3, 4, 9 and 10.
 Thence
 S. 89° 53' W. on a true line bet. secs. 4 and 9.
 Over gently rolling land, through scattering undergrowth.
 24.70 Road brs. N. and S.
 39.96 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in
 the ground, to solid rock, in a mound of stone, for
 $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 4
 S 9
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 N. of cor.
 44.90 Wash, 100 lks wide, 6 ft. deep, course, S.
 78.60 Road brs NE. and SW. Vulture to Independent mine.
 79.92 The cor. of secs. 4, 5, 8 and 9,
 Land, gently rolling.
 Soil, 3rd rate, gravelly.
 No timber.
 Undergrowth, mesquite, palo verde, cat. claw, sagebrush
 and greasewood.

21.00 N. 0° 2' W. on a true line bet. secs. 4 and 5.
 23.20 Over gently rolling land, through scattering undergrowth.
 40.00 Wash, 50 lks. wide, 3 ft. deep, course, SE.
 Wash, 60 lks. wide, 3 ft. deep, course, SE.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$
 S 5 | S 4
 1916

and raise a mound of stone 2 ft. base, 1½ ft. high, W.
 of cor.

Chains
70.70

Intersect 1st standard parallel N., 18.22 chs. W. of reestablished standard cor. of secs. 33 and 34, as described in book "A." X At point of intersection, Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for C.C. of secs. 4 and 5, mkd. on brass cap

T5N R6W
S33
S 5 | S 4
T4N | R6W
C C
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

Land, gently rolling.

Soil, gravelly, 3rd rate.

No timber.

Undergrowth, mesquite, cat claw, sagebrush, palo verde and greasewood.

23.53

40.00

From the cor. of secs. 5, 6, 31 and 32, on S. bdy. of Tp., as described in book "B,"

N. 0° 3' W. bet. secs. 31 and 32.

Over mountainous land, through scattering undergrowth.

Asc. steep S. slope, of mountain 700 ft. to

Top of high ridge brs. N. 70° W. and S. 70° E.

Desc. steep N. slope 628 ft. to

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

S31 | S32
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Head of wash, course, N. 10° W.

Desc. 246 ft. to

64.00

Asc. 40 ft. to

67.40

Point of spur slopes N. Desc. 207 ft. to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, to solid rock, in a mound of stone, for cor. of secs. 29, 30, 31 and 32. mkd. on brass cap

T4N R6W
S30 | S29
S31 | S32
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky, 4th rate.

No timber.

Undergrowth, mesquite, cat claw, sagebrush, greasewood and palo verde.

40.00

79.94

East on a random line bet. secs. 29 and 32.

Set temp. 1/4 sec. cor.

Intersect N. and S. line, 2 lks. N. of cor. of secs. 28, 29, 32 and 33.

Thence

N. 89° 59' W. on a true line bet. secs. 29 and 32

Over rolling land, through scattering undergrowth.

22.05

Wash, 30 lks. wide, 5 ft. deep, course, S.

39.97

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in

Subdivision of T.4 N., R.6 W.

Chains

the ground, for 1/4 sec. cor., mkd. on brass cap

1/4 S 29
1/4 S 32
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

56.05
79.94

Wash, 25 lks. wide, 4 ft. deep, course, S.
The cor. of secs. 29, 30, 31 and 32.

Land, rolling.
Soil, rocky, 3rd rate.
No timber.

Undergrowth, mesquite, palo verde, cat claw, sagebrush and greasewood.

40.00
79.20

West on a random line bet. secs. 30 and 31.
Set temp. 1/4 sec. cor.
Intersect W. bdy. of Tp., 24 lks. N. of cor. of secs. 25, 30, 31 and 36, described in book "B."

Thence N. 89° 50' E. on a true line bet. secs. 30 and 31.
Over rolling and mountainous land, through scattering undergrowth and timber.

4.75
8.70
9.70

Wash, 150 lks. wide, 20 ft. deep, course, NE.
Wagon road in wash, brs. NE. and SW
Wagon road brs. N. and S. from Vulture to Independent Mine.

25.00
29.85

Asc. 80 ft. to
Crest of ridge brs. N. and S.
Thence over rolling slope to

39.38
39.20

Asc. W. slope, 139 ft. to
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

1/4 S 30
1/4 S 31
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

47.71

Asc. W. slope, 217 ft. to
Crest of mountain brs. NW. and SE.; desc. E. slope, 404 ft. to

69.99
79.20

Bottom of mountain. Thence over rolling land, to
The cor. of secs. 29, 30, 31 and 32.
Land, rolling and mountainous.
Soil, rocky, 4th rate.
Timber, scattering palo verde and cat claw.
Undergrowth, scattering greasewood.

34.92
40.00

N. 0° 3' W. bet. secs. 29 and 30.
Over rolling land, through scattering timber.
Wash, 150 lks. wide, 4 ft. deep, course, E.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., mkd. on brass cap

S30 1/4 S29
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

70.00

Wash, 76 lks. wide, 10 ft. deep, course, E.

24

Subdivision of T.4 N. R.6 W.

Chains
80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, mkd. on brass cap

$$\begin{array}{r} T4N R6W \\ S19|S20 \\ S30|S29 \\ 1916 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, 2nd and 3rd rates.

Timber, scattering palo verde and cat claw.

40.00
79.83

East on a random line bet. secs. 20 and 29.

Set temp. $\frac{1}{4}$ sec. cor.

Intersect N. and S. line, 2 lks. S. of cor. of secs. 20, 21, 28 and 29.

Thence

S. $89^{\circ} 59'$ W. on a true line bet. secs. 20 and 29.

Over rolling land, through scattering timber.

39.91 $\frac{1}{2}$

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{r} \frac{1}{4} S 20 \\ S 29 \\ 1916 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

79.83

The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, 2nd and 3rd rates.

Timber, scattering palo verde and cat claw.

40.00
78.95

West on a random line bet. secs. 19 and 30.

Set temp. $\frac{1}{4}$ sec. cor.

Intersect W. bdy. of Tp. 22 lks. N. of cor. of secs. 19, 24, 25 and 30, as described in book "B."

Thence

N. $89^{\circ} 50'$ E. on a true line bet. secs. 19 and 30.

Over rolling land, through scattering undergrowth.

35.85

Road hrs. N. 10° W. and S. 10° E. from Vulture to Independent Mine.

38.95

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$$\begin{array}{r} \frac{1}{4} S 19 \\ S 30 \\ 1916 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

43.45
78.95

Wash, 100 lks. wide, 3 ft. deep, course, S. 60° W.

The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, 4th rate.

No timber.

Undergrowth, mesquite, cat claw, sagebrush, cactus, ocotillo and greasewood.

Chains

10.45 N. 0° 3' W. bet. secs. 19 and 20.
 Over rolling land, through scattering undergrowth.
 15.20 Road brs. S. 80° W. and N. 80° E.
 21.30 Wash, 20 lks. wide, 6 ft. deep, course, E.
 39.10 Wash, 20 lks. wide, 5 ft. deep, course, E.
 40.00 Road brs. NE. and SW. Vulture to Independent Mine.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S19 | S20
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 49.00 Wash, 15 lks. wide, 5 ft. deep, course, E.
 61.50 Wash, 50 lks. wide, 3 ft. deep, course, E.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of secs. 17, 18, 19 and 20, mkd.
 on brass cap

T4N R6W
 S18 | S17
 S19 | S20
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 W. of cor.
 Land, rolling.
 Soil, gravelly, 3rd rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw, ocotillo,
 sagebrush and greasewood.

40.00 East on a random line bet. secs. 17 and 20.
 80.00 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 7 lks. S. of cor. of secs. 16,
 17, 20 and 21.
 Thence
 S. 89° 57' W. on a true line bet. secs. 17 and 20.
 40.00 Over rolling land, through scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor. mkd. on brass cap

$\frac{1}{4}$ S 17
 S 20
 1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,
 N. of cor.
 59.80 Road brs. NE. and SW. from Vulture to Independent Mine.
 75.00 Wash; course; SE.
 80.00 The cor. of secs. 17, 18, 19 and 20.
 Land, rolling.
 Soil, gravelly, 3rd rate.
 No timber.
 Undergrowth, cat claw, mesquite, palo verde, cactus,
 ocotillo, sagebrush and greasewood.

40.00 West on a random line bet. secs. 18 and 19.
 78.84 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect W. bdy. of Tp., 16 lks. N. of cor. of secs.
 13, 18, 19 and 24, as described in book "B."

Chains

38.84 Thence
 N. 89° 53' E. on a true line bet. secs. 18 and 19.
 Over rolling land, through scattering timber.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 18
 S 19
 1916

78.84 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 N. of cor.
 The cor. of secs. 17, 18, 19 and 20.
 Land, rolling.
 Soil, 2nd and 3rd rates.
 Timber, scattering palo verde and cat claw.

4.00 N. 0° 3' W. bet. secs. 17 and 18.
 40.00 Over rolling land, through scattering timber.
 Wash, 90 lks. wide, 8 ft. deep, course, SE.
 Set an iron post, 3 ft. long 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S18 | S17
 1916

55.00 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 80.00 W. of cor.
 Wash, 150 lks. wide, 10 ft. deep, course, E.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of secs. 7, 8, 17 and 18, mkd.
 on brass cap

T4N R6W
 S 7 | S 8
 S18 | S17
 1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 Land, rolling.
 Soil, 2nd and 3rd rates.
 Timber, scattering palo verde and cat claw.

40.00 East on a random line bet. secs. 8 and 17.
 79.94 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 17 lks. S. of cor. of secs. 8,
 9, 16 and 17.
 Thence
 S. 89° 53' W. on a true line bet. secs. 8 and 17.
 Over rolling land, through scattering undergrowth and
 timber.

28.64 Wagon road brs. N. and S. from Vulture to Independent Mine.
 39.97 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 8
 S 17
 1916

45.00 dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
 56.40 dist.; and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
 high, N. of cor.
 Asc. 63 ft. to
 Top of rocky butte.
 Desc 71 ft. to

Subdivision of T.4 N., R.6 W.

Chains
60.00
79.94

Over rolling land, to
The cor. of secs. 7, 8, 17 and 18.
Land, rolling and mountainous.
Soil, 2nd and 3rd rates.
Timber, scattering palo verde and cat claw.

40.00
78.80

West on a random line bet. secs. 7 and 18.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect W. bdy. of Tp. 20 lks. N. of cor. of secs.
7, 12, 13 and 18, as described in book "B."

38.80

Thence
N. 89° 51' E. on a true line bet. secs. 7 and 18.
Over rolling land, through scattering timber.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 7
S 18
1916

dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft.
high, N. of cor.

78.80

The cor. of secs. 7, 8, 17 and 18.
Land, rolling.
Soil, 2nd and 3rd rates.
Timber, scattering palo verde and cat claw.

20.00
39.94
40.00

N. 0° 3' W. bet. secs. 7 and 8.
Over rolling land, through scattering timber.
Wash, 45 lks. wide, 3 ft. deep, course, E.
Asc. 52 ft. to
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap

S 8
S 7
1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
W. of cor.

47.33
54.00
65.00
78.45
80.00

Asc. 209 ft. to
Top of butte. Desc. 75 ft. to
Asc. 85 ft. to
Top of point of butte. Desc. 195 ft. to
Bottom of descent.
Set an ironpost, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 5, 6, 7 and 8, mkd. on
brass cap

T4N R6W
S 6 | S 5
S 7 | S 8
1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
W. of cor.

Land, rolling and mountainous.
Soil, rocky, 3rd and 4th rates.
Timber, scattering palo verde and cat claw.

28

Subdivision of T. 4 N. R. 6 W.

Chains

40.00	East on a random line bet. secs. 5 and 8. Set temp. $\frac{1}{4}$ sec. cor.
79.97	Intersect N. and S. line 11 lks. S. of cor. of secs. 4, 5, 8 and 9. Thence S. $89^{\circ} 55'$ W. on a true line bet. secs. 5 and 8. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap $\frac{1}{4} \begin{array}{r} S 5 \\ S 8 \\ 1916 \end{array}$ dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
39.98 $\frac{1}{2}$	
79.97	The cor. of secs. 5, 6, 7 and 8. Land, gently rolling. Soil, 2nd rate. Timber, scattering palo verde and cat claw. Undergrowth, mesquite, cactus, ocotillo, greasewood and sagebrush.
40.00	West on a random line bet. secs. 6 and 7. Set temp. $\frac{1}{4}$ sec. cor.
78.70	Intersect W. bdy. of Tp. 7 lks. N. of cor. of secs. 1, 6, 7 and 12, as described in book "B." Thence N. $89^{\circ} 57'$ E. on a true line bet. secs. 6 and 7. Over rolling and hilly land, through scattering timber.
38.70	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap $\frac{1}{4} \begin{array}{r} S 6 \\ S 7 \\ 1916 \end{array}$ and raise a mound of stone, ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
44.10	Asc. 114 ft. to
55.92	Top of hill brs. NW. and SE. Desc. 119 ft. to
64.90	Thence over rolling land to
78.70	The cor. of secs. 5, 6, 7 and 8, Land, rolling and mountainous. Soil, 3rd and 4th rates. Timber, scattering palo verde and cat claw.
40.00	N. $0^{\circ} 3'$ W. on a true line bet. secs. 5 and 6. Over rolling land, through scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap $\begin{array}{r} S 6 \\ S 5 \\ 1916 \end{array}$ and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
45.00	Wash, 150 lks. wide, 20 ft. deep, course, E.
65.00	Wash, 7 chs. wide, 10 ft. deep, course, E.

Chains
70.80

Intersect 1st standard parallel N., 18.27 chs. W. of reestab. standard cor. of secs. 32 and 33, as described in book "A.". At point of intersection, Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for C.C. of secs. 5 and 6, mkd. on brass cap

T5N R6W
S32
S 6 | S 5
T4N | R6W
C C
1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.

GENERAL DESCRIPTION

The extreme southwest part of this township is mountainous with a few rolling hills in the northwest part. The remainder of the land is level or nearly level. The general drainage is from the NW. to the SE. The soil is gravelly or stony, on the level portions and rocky in the hills. The timber and undergrowth consists of palo verde, mesquite cat claw, ocotillo, cactus, sagebrush and greasewood. There are no settlers. No water has been developed.

----0----

CERTIFICATE OF ASSISTANTS.

We, the undersigned, hereby certify upon honor that we assisted, to the best of our skill and ability, _____, U. S. Surveyor, during the periods and in the capacities stated opposite our several signatures, in surveying all those parts or portions of _____

3060

of the _____ Meridian, in the State of _____ which are represented in the foregoing field notes as having been executed by him, and under his direction; and that said survey has been, in all respects, to the best of our knowledge and belief, well and faithfully executed.

NAME.	PERIOD OF SERVICE.		CAPACITY.
	BEGUN.	ENDED.	

Subscribed and certified to before me on the dates of the final service as shown above.

U. S. Surveyor.

CERTIFICATES

FOR

~~FINAL~~ ~~GATH~~ OF UNITED STATES TRANSITMEN.

ECCT 3060

See Book "C."

I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191 _____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____

_____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

U. S. Surveyor.

Subscribed by said _____, and sworn to before me }
this _____ day of _____, 191 _____ }



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,
Phoenix, Arizona, JUL 20 1918

The foregoing field notes of the survey of the _____
Subdivision Lines of
TOWNSHIP 4 NORTH, RANGE 6 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by Roy J. Gill and Hans D. Voigt, U. S. Transitmen, under his special instructions dated Dec. 12, 1914, for Group 39, Arizona, 191 _____, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above described surveys in _____ has been correctly copied from the original notes on file in this office.