

3107

G.L.O. letter "E" 95
March 29, 1919.

Book "C"

4-679

BOOK 3107

JAN 7 1918

FIELD NOTES

RE-
OF THE SURVEY OF THE

South boundary (1st Standard Parallel N., thru. Range 8 W.),

and SURVEY of the

East and North boundaries, and

Subdivision lines of

TOWNSHIP 5 NORTH, RANGE 8 WEST,

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

Roy J. Gill, U. S. Surveyor,

and

Hans D. Voigt, U.S. Transitman,

~~In the capacity of U. S. Surveyor~~, under instructions dated September 24, 1915,

issued by the United States Surveyor General to govern surveys included in

Group No. 59, which were approved by the Commissioner of the General Land

Office, October 8, 1915.

Resurvey & Survey commenced February 22, 1916.

Resurvey & Survey completed March 3, 1916.

3107

3107

1A

3107

Book "C"

Group 59 - - - Arizona.

BOOK 3107

INDEX DIAGRAM.

Township		5 North.				Range 8 West.					
13	13	12	12	11	11						
6	42	5	35	4	29	3	24	2	19	1	9
42		42		34		29		24		19	
7	41	8	34	9	28	10	23	11	18	12	9
41		40		33		28		23		18	
18	40	17	33	16	27	15	23	14	17	13	8
39		39		32		27		22		17	
19	38	20	32	21	27	22	22	23	17	24	8
37		37		31		26		21		16	
30	36	29	31	28	26	27	21	26	16	25	7
36		35		30		25		20		15	
31	35	32	30	33	25	34	20	35	15	36	7
5		5		4		3		3		2	

Unsurveyed

Book "B."

First Standard Parallel North.

- Surveyed or resurveyed under this Group. Notes in this book.
- Surveyed or resurveyed under this Group.
- Surveyed under Group 4.

Book "C".

Group 59, Arizona.

Township 5 North, Range 8 West.

DATE DIAGRAM.

3-1-16	3-1-16	3-1-16	3-1-16	3-1-16	3-1-16	3-1-16
6	5	4	3	2	1	
3-3-16	3-3-16	3-3-16	3-2-16	3-2-16	3-2-16	2-23-16
7	8	9	10	11	12	
3-3-16	3-3-16	3-2-16	3-1-16	2-29-16	2-29-16	2-23-16
18	17	16	15	14	13	
3-3-16	3-2-16	3-1-16	2-29-16	2-29-16	2-28-16	2-23-16
19	20	21	22	23	24	
3-2-16	3-2-16	3-1-16	2-29-16	2-29-16	2-28-16	2-23-16
30	29	28	27	26	25	
3-1-16	3-1-16	2-29-16	2-29-16	2-28-16	2-28-16	2-23-16
31	32	33	34	35	36	
3-28-16	2-29-16	2-29-16	2-28-16	2-28-16	2-28-16	2-23-16
2-28-16	2-28-16	2-28-16	2-28-16	2-22-16	2-22-16	

Lines dated in blue were surveyed by Roy J. Gill,
U. S. Surveyor.

Lines dated in red were surveyed by Hans D. Voigt,
U. S. Transitman.

2. Second Resurvey of First Standard Parallel North Through Range 8 West.

Chains.

Resurvey commenced and executed with Young and Sons' light mountain transit No. 8293, with Smith solar attachment. For description of instrument and certificate of approval, see Book "I".

Knowing from recent and repeated tests of this instrument on a meridian determined by a series of direct observations on the sun for azimuth, as described in the field notes of current Group No. 39, that this instrument is in adjustment, I proceed to the resurvey of the first standard parallel North through Range 8 West.

On this resurvey, I destroy all traces of the cors. established during the first resurvey of this line.

From the standard cor. of Ts. 5 N., Rs. 7 and 8 W., which is an iron post, described in Book "B",

West on the tangent, S. of sec. 36.

Over mountainous land, through scattering timber and undergrowth.

5.00 Desc. 90 ft. to
23.00 Draw, 25 lks. wide, 4 ft. deep, course N. Asc 65 ft. to
32.30 Low spur, slopes N. Desc. 55 ft. to

Difference between measurements of 40.00 chs. by two sets of chainmen is 10 lks.; position of middle point

By 1st set, 39.95 chs.

By 2nd set, 40.05 chs.; the mean of

which is

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked on brass cap

S C
1/4 S 36

1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

45.00 Asc. 40 ft. to
49.90 Desc. 50 ft. to
50.10 Draw, 20 lks. wide, 3 ft. deep, course N. Asc. 95 ft.
59.70 Road, brs. N. and S.

69.16 Spur, slopes N. Desc. 35 ft. to
Draw, 25 lks. wide, 4 ft. deep, course N. Asc. 85 ft. to
Difference between measurements of 80.00 chs. by two sets of chainmen is 4 lks.; position of middle point

By 1st set, 79.98 chs.

By 2nd set, 80.02 chs.; the mean of

which is

80.00 Spur, slopes N.
N. 1 lk. from the tangent,
Set an iron post, 3 ft. long, 3 ins. diam., in a mound of stone, for standard cor. of secs. 35 and 36, marked on brass cap

S C
T5N R8W
S35 | S36

1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Land, mountainous.

Soil, 4th rate.

Timber, scattering palo verde.

Undergrowth, mesquite, cat claw, sagebrush, ocotillo, greasewood and cactus.

Second Resurvey of the
First Standard Parallel North Through Range 8 West.

Chains.	<p>S.89° 59' W., on the tangent, S. of sec. 35. Over mountainous land, through scattering timber and undergrowth.</p> <p>17.50 Desc. 35 ft. to 36.75 Draw, 30 lks wide, 3 ft. deep, course N. Asc. 75 ft. to Desc. 20 ft. to</p> <p>Difference between measurements of 40.00 chs. by two sets of chainmen in 5 lks.; position of middle point By 1st set, 39.975 chs. By 2nd set, 40.025 chs.; the mean of which is</p> <p>40.00 N. 2 lks. from the tangent, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;">S C <u>$\frac{1}{4}$S 35</u> 1916</p> <p>And raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p> <p>48.70 Asc. 25 ft. to 69.60 Desc. 40 ft. to 70.00 Asc. 15 ft. to Desc. 35 ft. to</p> <p>Difference between measurements of 80.00 chs. by two sets of chainmen is 8 lks.; position of middle point By 1st set, 79.96 chs., By 2nd set, 80.04 chs.; the mean of which is</p> <p>80.00 N. 3 lks. from the tangent, Set an iron post, 3 ft. long, 3 ins. diam., 14 ins. in the ground, in a mound of stone, for standard cor. of secs. 34 and 35, marked on brass cap</p> <p style="text-align: center;">S C T5N R8W <u>S34 S35</u> 1916</p> <p>And raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p> <p>Land, mountainous and rolling. Soil, 4th rate. Timber, scattering palo verde. Undergrowth, mesquite, cat claw, sagebrush and greasewood.</p>
	<p>S.89° 59' W., on the tangent, S. of sec. 34. Over rolling land, through scattering timber and undergrowth.</p> <p>10.00 Asc. 25 ft. to 26.50 Spur, slopes NW. Desc. 45 ft. to 40.00 Draw, 50 lks. wide, 5 ft. deep, course NW. Asc. 60 ft. to No difference between measurements of 40.00 chs. by two sets of chainmen.</p> <p>40.00 N. 4 lks. from the tangent, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;">S C <u>$\frac{1}{4}$S 34</u> 1916</p> <p>And raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p> <p>55.46 Low spur, slopes N. Desc. 50 ft. to</p>

4. Second Resurvey of the First Standard Parallel North Through Range 8 West.

Chains. 61.80	Draw, 50 lks. wide, 4 ft. deep, course N. Asc. 60 ft. to Difference between measurements of 80.00 chs. by two sets of chainmen is 2 lks.; position of middle point By 1st set, 79.99 chs. By 2nd set, 80.01 chs.; the mean of which is
80.00	N. 6 lks. from the tangent, Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of secs. 33 and 34, marked on brass cap S C T5N R8W S33 S34 1916 And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Land, rolling. Soil, 3rd rate. Timber, scattering palo verde. Undergrowth, mesquite, sagebrush, cat claw, ocotillo, cactus and greasewood.
4.94 10.07 26.32 34.23	S. 89° 58' W., on the tangent, S. of sec. 33. Over rolling mountainous land, through scattering timber and undergrowth. Asc. 50 ft. to Spur, slopes N. Desc. 110 ft. to Draw, 25 lks. wide, 4 ft. deep, course N. Asc. 175 ft. to Spur, slopes S. 30° E. Desc. 100 ft. to Head of draw, 10 lks. wide, 2 ft. deep, course S. Asc. 150 ft.
40.00	Difference between measurements of 40.00 chs. by two sets of chainmen is 5 lks.; position of middle point By 1st set, 39.985 chs. By 2nd set, 40.025 chs.; the mean of which is N. 8 lks. from the tangent, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard sec. cor., marked on brass cap S C 1/4 S 33 1916 And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
53.90 64.53 67.56 72.35 76.70	Desc. 120 ft. to Head of draw, 10 lks. wide, 3 ft. deep, course S. Asc. 70 ft. to Spur, slopes S. Desc. gradually to Head of draw, 10 lks. wide, 3 ft. deep, course SE. Asc. 100 ft. to Ridge, brs. N. and S. Desc. 35 ft. to
80.00	Difference between measurements of 80.00 chs. by two sets of chainmen is 2 lks.; position of middle point By 1st set, 79.99 chs. By 2nd set, 80.01 chs.; the mean of which is N. 11 lks. from the tangent, Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of secs. 32 and 33, marked on brass cap

Second Resurvey of the
First Standard Parallel North Through Range 8 West. 5.

Chains.

S C
T5N | R8W
S32 | S33

1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
Land, rolling mountainous.
Soil, 4th rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

S. 89° 58' W., on the tangent, S. of secs. 32.
Over mountainous land, through scattering timber and undergrowth.
Desc. 95 ft. to
14.30 Head of draw, 10 lks. wide, 4 ft. deep, course N. Asc. 40 ft. to
16.84 Low spur, slopes N. Desc. 80 ft. to
24.85 Thence over gently rolling land.
Difference between measurements of 40.00 chs. by two sets of chainmen is 10 lks.; position of middle point
By 1st set, 40.05 chs.;
By 2nd set, 39.95 chs.; the mean of which is
40.00 N. 14 lks. from the tangent,
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard 1/4 sec. cor., marked on brass cap

S C
1/4 S 32

1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
41.10 Draw, 15 lks. wide, 4 ft. deep, course N. Asc. 25 ft. to
57.27 Low spur, slopes N. Desc. 20 ft. to
64.80 Draw, 10 lks. wide, 4 ft. deep, course N. Asc. 85 ft. to
65.40 Spur, slopes N. Desc. 100 ft. to
74.84 Draw, 20 lks. wide, 4 ft. deep, course N. Asc. 25 ft. to
No difference between measurements of 80.00 chs. by two sets of chainmen.
80.00 N. 17 lks. from the tangent,
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground for standard cor. of secs. 31 and 32. marked on brass cap

S C
T5N | R8W
S31 | S32

1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
Land, mountainous.
Soil, 4th rate.
Timber, scattering palo verde.
Undergrowth, cat claw, mesquite, sagebrush, greasewood, ocotillo and cactus.

S. 89° 57' W., on the tangent, S. of sec. 31.
Over mountainous land, through scattering timber and undergrowth.

6. Second Resurvey of the First Standard Parallel North Through Range 8 West.

Chains.

Asc. 80 ft. to
 4.66 Ridge, brs. N.30° W. and S. 30 E. Desc. 70 ft. to
 11.35 Draw, 25 lks. wide, 5 ft. deep, course S.
 19.35 Draw, 25 lks. wide, 8 ft. deep, course S. Asc. 125 ft. to
 25.23 Spur, slopes SW. Desc. 240 ft.
 Difference between measurements of 40.00 chs. by two sets
 of chainmen is 10 lks.; position of middle point
 By 1st set, 40.05 chs.
 By 2nd set, 39.95 chs.; the mean of
 which is
 40.00 N. 21 lks. from the tangent,
 Set an iron post, 3 ft. long, 1 in. diam., in a mound of
 stone, for standard 1/4 sec. cor., marked on brass cap

S C
1/4 S31

1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N of cor.

47.69 Draw, 10 lks. wide, 4 ft. deep, course S. Asc. 65 ft. to
 55.48 Spur, slopes S. Desc. 70 ft. to
 68.11 Draw, 10 lks. wide, 4 ft. deep, course S. Asc. 25 ft. to
 69.80 Spur, slopes S. Desc. 130 ft. to
 Difference between measurements of 81.39 chs. by two sets
 of chainmen is 6 lks.; position of middle point
 By 1st set, 81.42 chs.
 By 2nd set, 81.36 chs.; the mean of

which is
 81.39 N. 25 lks. from the tangent,
 A point 3.14 chs. S. of the standard cor. of Ts. 5 N., Rs.
 8 and 9 W., which is a limestone, 10 X 8 X 12 ins. above
 ground, firmly set, marked and witnessed as described
 by the Surveyor-General.
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
 ground, for angle point, marked on brass cap

T5N
 R9W | R8W
 S36 |
 S | C
 ——— | S31
 A/P
 1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, NE of cor.

Land, mountainous.
 Soil, 4th rate.
 Timber, palo verde.
 Undergrowth, mesquite, sagebrush, cat claw and greasewood.

East Boundary of T. 5 N., R. 8 W.

7.

Chains.

From the standard cor. of Ts. 5 N., Rs. 7 and 8 W., which is an iron post, described in Book "B", North bet. secs. 31 and 36. Over mountainous land, through scattering timber and undergrowth.

7.07 Desc. 40 ft. to
 Draw, 15 lks. wide, 5 ft. deep, course W. Asc. 110 ft. to

16.17 Spur, slopes E. Desc. 175 ft. to

29.40 Asc. 15 ft. to

31.90 Desc. 30 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

43.30 Asc. 25 ft. to

44.95 Desc. 15 ft. to

58.40 Asc. 55 ft. to


64.90 Desc. to

66.55 Asc. 25 ft. to

69.80 Spur, slopes E. Desc. 35 ft. to

80.00 Asc. 80 ft. to

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.
 Soil, 4th rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush, ocotillo and greasewood.


North bet. secs. 25 and 30. Over rough, rolling land, through scattering timber and undergrowth.

10.00 Asc. 60 ft. to

20.80 Desc. 115 ft. to

39.00 Draw, 25 lks. wide, 4 ft. deep, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

42.50 Road, brs. E. and W. Thence over gently rolling land.

71.50 Draw, 25 lks. wide, 10 ft. deep, course E.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, marked on brass cap

8. East Boundary of T. 5 N., R. 8 W.

Chains.

T5N	
R8W	R7W
S24	S19
S25	S30
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, rolling and rough rolling.
 Soil, 3rd rate.
 Timber, palo verde.
 Undergrowth, cat claw, sagebrush, mesquite, ocotillo and greasewood.

North bet. secs. 19 and 24..

Over rolling land, through scattering timber and undergrowth.

3.80 Draw, 50 lks. wide, 10 ft. deep, course NE. Asc. 40 ft. to
 14.00 Desc. 25 ft. to
 29.95 Asc. 35 ft. to
 37.60 Desc. 25 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	
S24	S19
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

41.70 Draw, 25 lks. wide, 4 ft. deep, course E. Asc. 45 ft. to
 71.30 Spur, slopes EE. Desc. to
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, marked on brass cap

T5N	
R8W	R7W
S13	S18
S24	S19
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, sagebrush, cat claw, mesquite, ocotillo and greasewood.

North bet. secs. 13 and 18.

Over rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	
S13	S18
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

55.90 Draw, 20 lks. wide, 3 ft. deep, course NE.
 79.90 Draw, 50 lks. wide, 4 ft. deep, course NE.

East Boundary of T. 5 N., R. 8 W.

9.

Chains. 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, marked on brass cap

T5N	
R8W	R7W
S12	S 7
S13	S18
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, rolling.
Soil, gravelly; 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, sagebrush, ocotillo, cat claw and greasewood.

40.00 North bet. secs. 7 and 12.
Over rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

1	
S12	S 7
1916	

42.50 Draw, 20 lks. wide, 3 ft. deep, course E.
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, marked on brass cap

T5N	
R8W	R7W
S 1	S 6
S12	S 7
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, sagebrush, cat claw, ocotillo, greasewood and palo verde.

15.00 North bet. secs. 1 and 6.
25.00 Over rolling mountainous land, through scattering timber and undergrowth.
32.70 Desc. 45 ft. to
38.70 Asc. 25 ft. to
40.00 Desc. 55 ft. to
Draw, 150 lks. wide, 3ft. deep, course E. Asc. 450 ft.
Road, brs. E. and W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

1	
S 1	S 6
1916	

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.

10. East Boundary of T. 5 N., R. 8 W.

Chains.

80.00

dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Set an iron post, 3 ft. long, 3 ins. diam., in a mound of stone, for cor. of Ts. 5 and 6 N., Rs. 7 and 8 W., marked on brass cap

T6N	
R8W	R7W
S36	S31
S 1	S 6
T5N	
1916	

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.
Land, rolling and mountainous.
Soil, 4th rate.
Timber, scattering palo verde.
Undergrowth, cat claw, sagebrush, ocotillo, mesquite and greasewood.

North Boundary of T. 5 N., R. 8 W.

Chains.

Survey commenced and executed with Buff and Buff light mountain solar transit No. 7732, with Smith solar attachment. For description of instrument and certificate of approval, see Book "I".

Knowing from recent and repeated tests of this instrument on a meridian determined by a series of direct observations on the sun for azimuth, as described in current Group 39, that it is in adjustment, I proceed to the survey of the N. bdy. of T. 5 N., R. 8 W.

Knowing that it will be necessary to set a closing cor. against the W. bdy. of the Tp.,

I begin at the cor. of Ts. 5 and 6 N., Rs. 7 and 8 W., which is an iron post, hereinbefore described.

West on a true line, bet. secs. 1 and 36.

Over mountainous land, through scattering timber and undergrowth.

Desc. 85 ft. to Thence along S. slope.

10.00

Asc. 30 ft. to Spur, slopes S. Desc. 80 ft. to

20.00

22.37

Asc. 65 ft.

35.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

40.00

1/4 S36
S 1
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

50.00

Thence along N. slope to

64.84

Desc. 255 ft. to

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 2, 2, 35 and 36, marked on brass cap

T6N R8W
S35 | S36
S 2 | S 1
T5N
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous.

Soil, 4th rate.

Timber, scattering palo verde.

Undergrowth, cat claw.

West on a true line, bet. secs. 2 and 35.

Over mountainous land, through scattering timber and undergrowth.

Desc. 70 ft. to Thence over gently rolling land.

10.00

Road, brs. NW. and SE.

27.54

Road, brs. NW. and SE.

30.00

Draw, 75 lks. wide, 2 ft. deep, course SE.

31.94

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

40.00

1/4 S35
S 2
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 2, 3, 34 and 35, marked on brass cap

12.

North Boundary of T. 5 N., R. 8 W.

Chains.

T6N R8W
 S34 | S35
 S 3 | S 2
 T5N
 1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, mountainous and gently rolling.
 Soil, 3rd and 4th rates.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00

West on a true line, bet. secs. 3 and 34.
 Over gently rolling land, through scattering timber and undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

1 S34
 4 S 3
 1916

80.00

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 33 and 34, marked on brasscap

T6N R8W
 S33 | S34
 S 4 | S 3
 T5N
 1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00

West on a true line, bet. secs. 4 and 33.
 Over level land, through scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

1 S33
 4 S 4
 1916

70.84
80.00

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
 Road, brs. NW. and SE.
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 4, 5, 32 and 33, marked on brass cap

T6N R8W
 S32 | S33
 S 5 | S 4
 T5N
 1916

Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

North Boundary of T. 5 N., R. 8 W.

13.

Chains.

Land, level.
Soil, 2nd and 3rd rate.
Timber, none.
Undergrowth, greasewood.

40.00

West on a true line, bet. secs. 5 and 32.
Over level land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4} \frac{S32}{S5}$
1916

80.00

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 31 and 32, marked on brass cap

T6N R8W
S 6 | S 5
S31 | S32
T5N
1916

Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, level.
Soil, 2nd rate.
No timber.
Undergrowth, greasewood.

8.10
40.00

West on a true line, bet. secs. 6 and 31.
Over level land, through scattering undergrowth.
Road, brs. N. and S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4} \frac{S31}{S6}$
1916

80.23

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
Intersect the Second Guide Meridian West, 3.25 chs. S. of the cor. of Ts. 5 and 6 N., Rs. 8 and 9 W., which is an iron post, properly set, marked and witnessed as described by the Surveyor-General.
At the point of intersection, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for closing cor. of Ts. 5 and 6 N., R. 8 W., marked on brass cap

T6N | T6N
R8W | R8W
S 1 | S31 C C
S 6 | S 6
R9W | T5N
1916

Dig pits, 30 X 24 X 12 ins., crosswise on each line, N. and S., 4 ft., and E. of post, 8 ft. dist.; and raise a mound of earth, 5 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.

14. North Boundary of T. 5 N., R. 8 W.

Chains.	Land, level. Soil, 2nd and 3rd rates. Timber, none. Undergrowth, greasewood.						
Boundaries of T. 5 N., R. 8 W. Latitudes, departures and closing errors.							
Line designated.	True bearing.	Dist.	Latitudes.		Departures.		
			N.	S.	E.	W.	
South Boundary. (1st Std. Par. N)	West.	chs. 480.00	chs.	chs.	chs.	chs. 480.00	
West Boundary. (2nd Guide Mer. W.)	North.	479.88	479.88				
North Boundary.	East.	480.23			480.23		
East Boundary.	South.	480.00		480.00			
Convergency.					.49		
Totals			479.88	480.00	480.72	480.00	
				479.88	480.00		
Error in latitude				.12			
Error in departure						.72	

Subdivision of T. 5 N., R. 7 W.

Chains.

Survey commenced and executed with Buff and Buff light mountain transit No. 7732, and Young and Sons' light mountain transit No. 8293, each instrument being equipped with Smith solar attachment. For description of instruments and certificate of approval, see Book A. Knowing from recent and repeated tests of these instruments on a meridian determined by a series of direct observations on the sun for azimuth, that they are in adjustment, we proceed to the subdivision of T. 5 N., R. 8 W.

I begin at the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp, which is an iron post, hereinbefore described.


Thence
N.0° 1' W., bet. secs. 35 and 36.

40.00 Over rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 East on a random line, bet. secs. 25 and 36. Set temp. $\frac{1}{4}$ sec. cor.

79.86 Intersect E. bdy. of Tp., 13 lks. S. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, hereinbefore described.

Thence
S.89° 54' W., on a true line, bet. secs. 25 and 36.


Over mountainous land, through scattering timber and undergrowth.

6.25 Asc. 95 ft. to Ridge, brs. N. and S. Desc. 130 ft. to

15.00 Thence over gently rolling land.

34.00 Draw, 90 lks. wide, 10 ft. deep, course N. Asc. 80 ft. to

39.93 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

63.90 Desc. 120 ft. to Draw, 105 lks. wide, 10 ft. deep, course N.
64.10 Road, brs. N. and S.


16.

Subdivision of T. 5 N., R. 8 W.


Chains.

79.86 Thence over gently rolling land.
The cor. of secs. 25, 26, 35 and 36.
Land, mountainous, rolling and gently rolling.
Soil, 3rd and 4th rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.0° 1' W., bet. secs. 25 and 26.
Over rolling and gently rolling land, through scattering
timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



80.00 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs 23, 24, 25 and 26, marked on
brass cap




And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
Land, rolling and gently rolling.
Soil, 3rd and 4th rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.89° 54' E., on a random line, bet. secs. 24 and 25.
Set temp. $\frac{1}{4}$ sec. cor.
79.92 Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs.
19, 24, 25 and 30, which is an iron post, hereinbefore
described.

Thence
S.89° 57' W., on a true line, bet. secs. 24 and 25.
Over gently rolling land, through scattering timber and
undergrowth.

8.40 Draw, 75 lks. wide, 10 ft. deep, course N.
23.70 Road, brs. NW. and SE.
39.96 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



63.95 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of cor.
79.92 Draw, 75 lks. wide, 6 ft. deep, course N.
The cor. of secs. 23, 24, 25 and 26.
Land, gently rolling.
Soil, 2nd and 3rd rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

Subdivision of T. 5 N., R. 8 W.


Chains.

N.0° 1' W., bet. secs. 23 and 24.
Over rolling land, through scattering timber and undergrowth.

22.00 Draw, 75 lks. wide, 15 ft. deep, course NE.

34.98 Road, brs. NE. and SW.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

70.10 Road, brs. NW. and SE., in draw, 90 lks. wide, 4 ft. deep, course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked on brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.89° 57' E., on a random line, bet. secs. 13 and 24.

Set temp. 1/4 sec. cor.


79.89 Intersect E. bdy. of Tp. 5 lks. N. of the cor. of secs. 13, 18, 19 and 24, hereinbefore described.

Thence

S.89° 59' W., on a true line, bet. secs. 13 and 24.

Over rolling land, through scattering timber and undergrowth.

39.94 1/2 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

54.90 Draw, 45 lks. wide, 3 ft. deep, course NW.

58.90 Draw, 45 lks. wide, 4 ft. deep, course N.

79.89 The cor. of secs. 13, 14, 23 and 24.

Land, rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

N.0° 1' W., bet. secs. 13 and 14.

Over rolling land, through scattering timber and undergrowth.

2.30 Draw, course NE.

7.40 Same draw, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

18.

Subdivision of T. 5 N., R. 8 W.

Chains.

$\frac{1}{4}$
 S14 | S13
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 40.50 Draw, 100 lks. wide, 3 ft. deep, course NE.
- 45.00 Draw, 70 lks. wide, 3 ft. deep, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked on brass cap

T5N | R8W
 S11 | S12
 S14 | S13
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

- 40.00 N. $89^{\circ} 59'$ E., on a random line, bet. secs. 12 and 13.
- 79.88 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect E. bdy. of Tp., 7 lks. S. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, hereinbefore described.

Thence
 S. $89^{\circ} 56'$ W., on a true line, bet. secs. 12 and 13.
 Over gently rolling land, through scattering timber and undergrowth.

- 28.90 Draw, 20 lks. wide, 6 ft. deep, course S.
- 39.94 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S12
 S13
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 79.88 The cor. of secs. 11, 12, 13 and 14.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, palo verde.
 Undergrowth, mesquite, cat claw, sagebrush, cactus and greasewood.

- 12.70 N. $0^{\circ} 1'$ W., bet. secs. 11 and 12.
- 40.00 Over rolling land, through scattering timber and undergrowth.
 Draw, 50 lks. wide, 3 ft. deep, course E.
 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S11 | S12
 1916

Chains

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Desc. 45 ft. to
 54.00 Wash, course SE. Asc. 120 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of stone, for cor. of secs. 1, 2, 11 and 12, marked on brass cap

T5N	R8W
S 2	S 1
S11	S12
1916	

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, mountainous and gently rolling.
 Soil, 4th rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, greasewood, cactus, cat claw and sagebrush.

40.00 N. $89^{\circ} 56'$ E., on a random line, bet. secs. 1 and 12.
 79.98 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect E. bdy. of Tp., 2 lks. N. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, hereinbefore described.
 Thence
 S. $89^{\circ} 57'$ W., on a true line, bet. secs. 1 and 12.
 Over rolling land, through scattering timber and undergrowth.
 Asc. gradually to
 25.00 Low ridge, brs. N. and S. Desc. 70 ft.
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 1	
S12	
1916	

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 40.80 Draw, 10 lks. wide, 2 ft. deep, course N. Asc. gradually to
 55.25 Desc. 30 ft. to
 60.30 Asc. 220 ft. to
 79.98 The cor. of secs. 1, 2, 11 and 12.
 Land, rolling.
 Soil, 4th rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush, cactus and greasewood.

40.00 N. $0^{\circ} 1'$ W., on a random line, bet. secs. 1 and 2.
 80.08 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. bdy. of Tp., 7 lks. E. of the cor. of secs. 1, 2, 35 and 36, which is an iron post, hereinbefore described.
 Thence
 S. $0^{\circ} 4'$ E., on a true line, bet. secs. 1 and 2.
 Over rolling land, through scattering timber and undergrowth.
 Asc. 20 ft. to
 8.20 Spur, slopes W. Desc. 145 ft. to
 23.90 Draw, 100 lks. wide, 4 ft. deep, course E. Thence over gently rolling land.
 24.00 Road, brs. E. and W.
 38.78 Road, brs. E. and W.

20.

Subdivision of T. 5 N., R. 8 W.

Chains.

40.08

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.08

Asc. 200 ft. to
The cor. of secs. 1, 2, 11 and 12.
Land, rolling.
Soil, 4th rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush, cactus and greasewood.

From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., which is an iron post, hereinbefore described, N.0° 1' W., bet. secs. 34 and 35.
Over rolling land, through scattering timber and undergrowth.

9.95

Asc. 35 ft. to
Ridge, brs. NW. and SE. Desc. 75 ft. to

19.90

Draw, course NW. Thence over gently rolling land.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, in a mound of stone, for cor. of secs. 26, 27, 34 and 35, marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling and gently rolling.
Soil, 2nd and 3rd rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00

East on a random line, bet. secs. 26 and 35.
Set temp. $\frac{1}{4}$ sec. cor.

79.97

Intersect N. and S. line, at the cor. of secs. 25, 26, 35 36.

West on a true line, bet. secs. 26 and 35.

1.70

Asc. 10 ft. to
Desc. 20 ft. to

5.00

Asc. 25 ft. to

10.00

Desc. 85 ft. to

19.50

Draw, 45 lks. wide, 10 ft. deep, course NW.

25.00

Draw, 75 lks. wide, 6 ft. deep, course N. Asc. 50 ft. to

Subdivision of T. 5 N., R. 8 W.

Chains.

39.98 1/2

Ridge, brs. N. and S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4 S26
S35
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

45.05
50.05
55.00
60.00
79.97

Desc. 30 ft. to
Asc. slightly to
Ridge, brs. N. and S. Desc. 40 ft. to
Asc. slightly to
Ridge, brs. N. and S. Desc. 65 ft. to
The cor. of secs. 26, 27, 34 and 35.
Land, rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00

N.0° 1' W., bet. secs. 26 and 27.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

S27 S26
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

42.60
55.00
72.50

Draw, 100 lks. wide, 4 ft. deep, course NE.
Same draw, course NW.
Road, brs. NW. and SE.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap

T5N R8W
S22 | S23
S27 | S26
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

40.00
80.10

East on a random line, bet. secs. 23 and 26.
Set temp. 1/4 sec. cor.
Intersect N. and S. line, 1 lk. S. of the cor. of secs. 23, 24, 25 and 26.

Thence
West on a true line, bet. secs. 23 and 26.
Over rolling land, through scattering timber and undergrowth.

10.40
27.70
33.10

Desc. 50 ft. to
Draw, 25 lks. wide, 4 ft. deep, course N. Asc. 35 ft. to
Low spur, slopes N. Desc. 40 ft. to
Draw, course N.70° E. Thence over gently rolling land.

22.

Subdivision of T. 5 N., R. 8 W.

<p>Chains. 40.05</p>	<p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\frac{1}{4}$ S23 $\frac{1}{4}$ S26 1916 </p> <p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p>
<p>60.00 65.10 80.10</p>	<p>Asc. slightly to Low spur, brs. S. Desc. 25 ft. to The cor. of secs. 22, 23, 26 and 27. Land, rolling and gently rolling. Soil, 3rd rate. Timber, scattering palo verde. Undergrowth, mesquite, cat claw, sagebrush and greasewood.</p>
<p>19.50 20.70 35.00 40.00</p>	<p>N.0° 1' W., bet. secs. 22 and 23. Over gently rolling land, through scattering timber and undergrowth.</p> <p>Draw, 25 lks. wide, 5 ft. deep, course W. Road, brs. E. and W. Draw, 100 lks. wide, 4 ft. deep, course NE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\frac{1}{4}$ S22 S23 1916 </p> <p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p>
<p>50.00 77.10 80.00</p>	<p>Draw, course NW. Same draw, course NE. Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, in a mound of stone, for cor. of secs. 14, 15, 22 and 23, marked on brass cap</p> <p style="text-align: center;"> T5N R8W S15 S14 S22 S23 1916 </p> <p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, 4th rate. Timber, scattering palo verde. Undergrowth, mesquite, cat claw, sagebrush and greasewood.</p>
<p>40.00 80.12</p>	<p>East on a random line, bet. secs. 14 and 23. Set temp. $\frac{1}{4}$ sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs. 13, 14, 23 and 24. Thence S.89° 58' W., on a true line, bet. secs. 14 and 23. Over rolling land, through scattering timber and undergrowth.</p> <p>0.30 Draw, 25 lks. wide, 3 ft. deep, course N. Asc. 70 ft. to 2.00 Road, brs. NW. and SE. 18.10 Low spur, slopes N. Desc. 75 ft. to 38.00 Draw, course N. Asc. 50 ft. 40.06 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p>

Subdivision of Township 5 North, Range 8 West.

Chains.

$\frac{1}{4}$ S 14
S 23
1916

62.30 and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
Spur, slopes N. Descend 90 ft. to
79.00 Draw, course NE.
80.12 The cor. of secs. 14, 15, 22 and 23.
Land, rolling. Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, sage brush, catclaw and greasewood.

N. 0° 1' W., bet. secs. 14 and 15.
Over gently rolling land, through scattering timber and undergrowth.

14.00 Draw, 150 lks. wide, 10 ft. deep, course E.
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap,

S 15 S 14
1916

80.00 dig pits 18x18x12 ins., N. & S. of post, 3 ft. dist., and raise a mound of earth 3½ ft. base, 1½ ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 10, 11, 14 and 15, marked on brass cap,

T 5N R 8W
S 10 S 11
S 15 S 14
1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, gently rolling.
Soil, 3rd and 4th rate.
Timber, scattering palo verde; undergrowth, catclaw.

N. 89° 58' E., on a random line, bet. secs. 11 and 14.
40.00 Set temp. ¼ sec. cor.
80.12 Intersect N. and S. line, 5 lks. N. of cor. of secs. 11, 12, 13 & 14.
Thence,
West, on a true line, bet. secs. 11 and 14.
Over gently rolling land, through scattering timber and undergrowth.

40.06 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap,

$\frac{1}{4}$ S 11
S 14
1916

44.20 and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
Road brs. NW. and SE.
67.70 Road brs. N. and S.
80.12 The cor. of secs. 10, 11, 14 and 15.
Land, gently rolling. Soil, 3rd rate.
Timber, scattering palo verde. Undergrowth, catclaw.

N. 0° 1' W., bet. secs. 10 and 11.
Over rolling land, through scattering timber and undergrowth.
13.00 Draw, 15 lks. wide, 4 ft. deep, course E. Ascend slightly to
27.30 Spur, slopes E. Descend 50 ft. to
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap,

S 10 S 11
1916

45.00 and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Thence over gently rolling land.
55.00 Road brs. NW. and SE.
75.00 Road brs. N. 10° E. and S. 10° W.
80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 2, 3, 10 and 11, marked on brass cap,

T 5N R 8W
S 3 S 2
S 10 S 11
1916

24. Subdivision of Township 5 North, Range 8 West.

Chains.	and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Land, rolling. Soil, 2nd rate. Timber, scattering palo verde. Undergrowth, catclaw, mesquite, sage brush, cactus & greasewood.

	East, on a random line, bet. secs. 2 and 11.
40.00	Set temp. ¼ sec. cor.
80.08	Intersect N. and S. line, 2 lks. S. of cor. of secs. 1, 2, 11 & 12. Thence, S. 89° 59' W., on a true line, bet. secs. 2 and 11. Over rolling and mountainous land, through scattering timber and undergrowth. Ascend to
2.60	Point of spur, slopes S. 80° E. Descend to
11.05	Head of gulch, course SE. Ascend 110 ft. to
22.15	Top of butte. Descend 370 ft.
40.04	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap,
	$\frac{1}{4} \begin{array}{c} S 2 \\ S 11 \\ 1916 \end{array}$
	and raise a mound of stone 2 ft. base, 1½ ft. high, N. of cor.
46.10	Draw, 15 lks. wide, 4 ft. deep, course N. Ascend 45 ft. to
50.15	Low spur, slopes N. Descend 35 ft. to
60.10	Ascend 25 ft. to
63.40	Descend 40 ft.
78.50	Road brs. N. 10° E. and S. 10° W.
80.08	The cor. of secs. 2, 3, 10 and 11. Land, rolling and mountainous. Soil, rocky, 4th rate. Timber, scattering mesquite and palo verde. Undergrowth, cactus and sage brush, catclaw and greasewood.

	N. 0° 1' W., on a random line, bet. secs. 2 and 3.
40.00	Set temp. ¼ sec. cor.
80.06	Intersect N. bdy. of Tp., 2 lks. E. of the cor. of secs. 2, 3, 34 and 35, which is an iron post, hereinbefore described. Thence, S. 0° 2' E., on a true line, bet. secs. 2 and 3. Over rolling land, through scattering timber and undergrowth.
3.05	Draw, 10 lks. wide, 2 ft. deep, course E.
40.06	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap,
	$S 3 \frac{1}{4} S 2$ 1916
	and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
49.25	Road brs. N. 80° E. and S. 80° W.
67.95	Draw, 1 chain wide, 3 ft. deep, course NE.
75.65	Draw, 30 lks. wide, 3 ft. deep, course E.
80.06	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, 3rd rate. Timber, scattering palo verde. Undergrowth, mesquite, catclaw, sage brush, cactus and

Subdivision of T. 5 N., R. 8 W.

Chains.

greasewood.

From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., which is an iron post, hereinbefore described, N.0° 2' W., bet. secs. 33 and 34.

Over rolling mountainous land, through scattering timber and undergrowth.

Desc. 50 ft. to

6.00 Head of draw, 20 lks. wide, 4 ft. deep, course NE. Asc. gradually.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S33 | S34

1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

55.00 Asc. 115 ft. to

64.85 Spur, slopes E. Desc. 70 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on brass cap

T5N | R8W
S28 | S27
S33 | S34
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling mountainous.

Soil, 3rd rate.

Timber, scattering palo verde.

Undergrowth, mesquite, cat claw, sagebrush, greasewood and ocotillo.

East on a random line, bet. secs. 27 and 34.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.06 Intersect N. and S. line, 1 lk. S. of the cor. of secs. 26, 27, 34 and 35,

Thence

West on a true line, bet. secs. 27 and 34.

Over rolling land, through scattering timber and undergrowth.

10.05 Draw, 1 ch. wide, 4 ft. deep, course NE.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S27
S34
1916

Dig pits, 18 X 18 X 12 ins., E. and W. of cor., 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

51.15 Draw, 1 ch. wide, 4 ft. deep, course S.70° E. Asc. 120 ft. to

76.35 Desc. 90 ft. to

80.06 The cor. of secs. 27, 28, 33 and 34.

Land, rolling and mountainous.

Soil, 3rd rate.


Timber, scattering palo verde.

Chains.


Undergrowth, cat claw, sagebrush and greasewood.

N.0° 2' W., bet. secs. 27 and 28.
Over rolling land, through scattering timber and undergrowth.

4.95 Desc. 45 ft. to
Draw, 3 chs. wide, 10 ft. deep, course E. Thence over gently rolling land.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



80.00 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on brass cap




And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Land, rolling and gently rolling.
Soil, 3rd and 4th rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 East on a random line, bet. secs. 22 and 27.
Set temp. $\frac{1}{4}$ sec. cor.
80.10 Intersect N. and S. line, 6 lks. N. of the cor. of secs. 22, 23, 26 and 27.

Thence
N.89° 57' W., on a true line, bet. secs. 22 and 27.
Over gently rolling land, through scattering timber and undergrowth.

1.50 Road, brs. NW. and SE.
5.20 Draw, 150 lks. wide, 6 ft. deep, course N.
25.10 Asc. 25 ft. to
30.10 Desc. 35 ft. to
35.10 Draw, 75 lks. wide, 10 ft. deep, course S. Asc. 85 ft.
40.05 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

45.30 Desc. 95 ft. to
55.15 Asc. 50 ft. to
63.50 Desc. 15 ft. to
65.10 Thence over gently rolling land.
80.10 The cor. of secs. 21, 22, 27 and 28.
Land, rolling and gently rolling.
Soil, 3rd and 4th rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

Chains. N.0° 2' W., bet. secs. 21 and 22.
 Over gently rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} \\ \text{S21} \uparrow \text{S22} \\ \text{1916} \end{array}$$

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

62.00 Draw, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on brass cap

$$\begin{array}{c} \text{T5N} | \text{R8W} \\ \text{S16} | \text{S15} \\ \text{S21} | \text{S22} \\ \text{1916} \end{array}$$

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.
 Soil, 3rd and 4th rates.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00 S.89° 57' E., on a random line, bet. secs. 15 and 22.
 Set temp. $\frac{1}{4}$ sec. cor.

80.17 Intersect N. and S. line, 14 lks. S. of the cor. of secs. 14, 15, 22 and 23.

Thence
 S.89° 57' W., on a true line, bet. secs. 15 and 22.
 Over rolling land, through scattering timber and undergrowth.

15.25 Asc. 70 ft. to
 20.25 Desc. 30 ft. to
 25.20 Asc. 35 ft. to
 30.15 Desc. 40 ft. to
 40.08 $\frac{1}{2}$ Thence over gently rolling land.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} \text{ S15} \\ \text{S22} \\ \text{1916} \end{array}$$

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

80.17 The cor. of secs. 15, 16, 21 and 22.
 Land, rolling and gently rolling.
 Soil, 3rd and 4th rates.
 Timber, palo verde.
 Undergrowth, cat claw.

N.0° 2' W., bet. secs. 15 and 16.
 Over gently rolling land, through scattering timber and undergrowth.

31.00 Draw, 10 lks. wide, 3 ft. deep, course E. Asc. 30 ft. to
 39.00 Spur, slopes E. Desc. 30 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains.	
	<div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ S16 \mid S15 \\ 1916 \end{array}$ </div> <p>And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p> <p>44.00 Draw, 20 lks. wide, 3 ft. deep, course W. Asc. 35 ft. to 63.00 Low spur, slopes E. Desc. gradually to 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap</p> <div style="text-align: center;"> $\begin{array}{c} T5N R8W \\ S 9 \mid S10 \\ S16 \mid S15 \\ 1916 \end{array}$ </div> <p>And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p> <p>Land, rolling and gently rolling. Soil, 3rd rate. Timber, scattering palo verde. Undergrowth, cat claw, sagebrush, mesquite, cactus and greasewood.</p>
<p>40.00 80.12 8.70 20.25 26.70 40.06 65.10 80.12</p>	<p>N.89° 57' E., on a random line, bet. secs. 10 and 15. Set temp. ¼ sec. cor. Intersect N. and S. line, 16 lks. N. of the cor. of secs. 10, 11, 14 and 15. Thence N.89° 56' W., on a true line, bet. secs. 10 and 15. Over rolling land, through scattering timber and undergrowth. Asc. 25 ft. to Spur, slopes SE. Desc. 55 ft. to Head of draw, 10 lks. wide, 3 ft. deep, course S. Asc. 65 ft. to Low spur, brs. N. and S. Desc. 80 ft. to Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap</p> <div style="text-align: center;"> $\begin{array}{c} S10 \\ \frac{1}{4} \mid S15 \\ 1916 \end{array}$ </div> <p>And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Desc. gradually to Draw, 25 lks. wide, 4 ft. deep, course N. Thence over gently rolling land. The cor. of secs. 9, 10, 15 and 16. Land, rolling and gently rolling. Soil, 4th rate. Timber, scattering palo verde. Undergrowth, sagebrush, cat claw, mesquite, cactus and greasewood.</p>
<p>18.38 31.65 40.00</p>	<p>N.0° 2' W., bet. secs. 9 and 10. Over rolling land, through scattering timber and undergrowth. Asc. 40 ft. to Low spur, slopes NE. Desc. 50 ft. to Draw, 25 lks. wide, 3 ft. deep, course NE. Thence over gently rolling land. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the</p>

Subdivision of T. 5 N., R. 8 W.

Chains.

ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S 9 $\frac{1}{4}$ S 10
1916

46.80 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00 Draw, 50 lks. wide, 4 ft. deep, course NE. Asc. 45 ft. to
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap

T5N | R8W
S 4 | S 3
S 9 | S 10
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Land, rolling and gently rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, palo verde, cat claw, sagebrush, cactus and greasewood.

40.00 S.89° 56' E., on a random line, bet. secs. 3 and 10.
80.06 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 5 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence
N.89° 58' W., on a true line, bet. secs. 3 and 10.
Over gently rolling land, through scattering timber and undergrowth.

4.05 Draw, 25 lks. wide, 3 ft. deep, course NE.
19.25 Road, brs. NW. and SE.
22.55 Draw, 70 lks. wide, 3 ft. deep, course NE.
40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 3
S 10
1916

80.06 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
The cor. of secs. 3, 4, 9 and 10.
Land, gently rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00 N.0° 2' W., on a random line, bet. secs. 3 and 4.
80.06 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. bdy. of Tp., 4 lks. E. of the cor. of secs. 3, 4, 33 and 34, which is an iron post, hereinbefore described.

Thence
S.0° 4' E., on a true line, bet. secs. 3 and 4.
Over gently rolling land, through scattering timber and undergrowth.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

30.

Subdivision of T. 5 N., R. 8 W.

Chains.

$\frac{1}{4}$
 S 4 | S 3
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 56.95 Road, brs. E. and W.
 78.75 Road, brs. NE. and SW.
 80.06 The cor. of secs. 3, 4, 9 and 10.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, greasewood, cat claw, mesquite and sagebrush.

From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., which is an iron post, hereinbefore described, N.0° 2' W., bet. secs. 32 and 33.
 Over rolling land, through scattering timber and undergrowth.
 Desc. 90 ft. to
 24.90 Thence over gently rolling land.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S32 | S33
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Asc. 105 ft. to
 53.37 Top of hill. Desc. 90 ft. to
 59.73 Asc. 80 ft. to
 66.11 Top of hill. Desc. 145 ft. to
 79.23 Draw, 75 lks. wide, 4 ft. deep, course E.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, marked on brass cap

T5N | R8W
 S29 | S28
 S32 | S33
 1916


And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, mountainous and gently rolling.
 Soil, 3rd and 4th rates.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00 East on a random line, bet. secs. 28 and 33.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.10 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 27, 28, 33 and 34.
 Thence
 S.89° 59' W., on a true line, bet. secs. 28 and 33.
 Over mountainous land, through scattering timber and undergrowth.
 Asc. 40 ft. to
 7.60 Desc. 20 ft. to
 11.10 Asc. 160 ft. to
 18.45 Ridge, brs. N. and S. Desc. 215 ft. to
 33.10 Draw, 90 lks. wide, 20 ft. deep, course N. Thence over gently rolling land.

Subdivision of T. 5 N., R. 8 W.

Chains.
40.05

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

69.60
80.10

Draw, 75 lks. wide, 4 ft. deep, course NE.
The cor. of secs. 28, 29, 32 and 33.
Land, mountainous and gently rolling.
Soil, 3rd and 4th rates.
Timber, scattering palo verde and cat claw.
Undergrowth, cat claw.

10.00
18.51
36.89
40.00

N.0° 2' W., bet. secs. 28 and 29.
Over rolling mountainous land, through scattering timber and undergrowth.
Asc. 85 ft. to
Spur, slopes NE. Desc. 50 ft. to
Draw, 50 lks. wide, 3 ft. deep, course S.70° E. Asc. 225 ft.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

54.27
62.84
79.00
80.00

Spur, and top of butte, slopes NE. Desc. 210 ft. to
Draw, 25 lks. wide, 5 ft. deep, course E. Asc. 320 ft. to
Spur, slopes E. Desc. 20 ft. to
Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, in a mound of stone, for cor. of secs. 20, 21, 28 and 29, marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.
Soil, 4th rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, cactus, sagebrush and greasewood.

40.00
80.10

N.89° 59' E., on a random line, bet. secs. 21 and 28.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 2 lks. S. of the cor. of secs. 21, 22, 27 and 28.

28.10
40.05

Thence
S.89° 58' W., on a true line, bet. secs. 21 and 28.
Over gently rolling land, through scattering timber and undergrowth.
Draw, 20 lks. wide, 4 ft. deep, course N.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains.

$\frac{1}{4}$ S21
~~S28~~
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

50.10 Asc. 420 ft. to
 80.10 The cor. of secs. 20, 21, 28 and 29.
 Land, gently rolling and mountainous.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, cactus, sagebrush and greasewood.

N.0° 2' W., bet. secs. 20 and 21.
 Over mountainous land, through scattering timber and undergrowth.

31.66 Desc. 360 ft. to
 40.00 Draw, 15 lks. wide, 4 ft. deep, course E. Asc. 25 ft. to Spur, slopes E.
 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S20 | S21
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

53.00 Desc. 25 ft. to
 78.40 Draw, 10 lks. wide, 4 ft. deep, course NW. Asc. 125 ft. to
 80.00 Rocky spur, slopes N.20° W. and S.20° E. Desc. 15 ft. to
 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of stone, for cor. of secs. 16, 17, 20 and 21, marked on brass cap

T5N	R8W
S17	S16
S20	S21

1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.
 Soil, 4th rate.
 Timber, scattering palo verde.
 Undergrowth, sagebrush, cat claw, mesquite, cactus, and greasewood.

40.00 N.89° 58' E., on a random line, bet. secs. 16 and 21.
 79.90 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 15, 16, 21 and 22.

Thence
 S.89° 55' W., on a true line, bet. secs. 16 and 21.
 Over gently rolling land, through scattering timber and undergrowth.

6.50 Draw, 15 lks. wide, 4 ft. deep, course S. Asc. 30 ft. to
 19.90 Low spur, slopes N. Desc. 30 ft. to
 21.10 Draw, 10 lks. wide, 2 ft. deep, course N. Asc. 30 ft. to
 39.95 Spur, slopes N.
 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

Subdivision of T. 5 N., R. 8 W.

Chains.

$\frac{1}{4}$ S16
 $\frac{1}{4}$ S21
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
Desc. 50 ft. to
45.10 Draw, 25 lks wide, 3 ft. deep, course N. Asc. 30 ft. to
65.05 Desc. 25 ft to
70.05 Asc. 115 ft. to
79.90 The cor. of secs. 16, 17, 20 and 21.
Land, gently rolling and mountainous.
Soil, 4th rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush, cactus and greasewood.

N.0° 2' W., bet. secs. 16 and 17.
Over gently rolling land, through scattering timber and undergrowth.
Desc. 65 ft. to
9.95 Thence over gently rolling land.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S17 | S16
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
79.00 Draw, 90 lks. wide, 10 ft. deep, course E.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on brass cap

T5N | R8W
S 8 | S 9
S17 | S16
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Land, rolling and gently rolling.
Soil, 2nd and 3rd rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.89° 55' E., on a random line, bet. secs. 9 and 16.
Set temp. $\frac{1}{4}$ sec. cor.
79.86 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 9, 10, 15 and 16.
Thence
S.89° 52' W., on a true line, bet. secs. 9 and 16.
Over gently rolling land, through scattering timber and undergrowth.
Asc. 45 ft. to
5.00 Low ridge, brs. N. and S. Desc. 35 ft. to
10.00 Thence over gently rolling land.
39.93 Set an iron post, 3ft. long, lin. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 9
 $\frac{1}{4}$ S16
1916

34.

Subdivision of T. 5 N., R. 8 W.

Chains.

66.35 79.86	<p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Draw, 90 lks. wide, 4 ft. deep, course N. The cor. of secs. 8, 9, 16 and 17. Land, rolling and gently rolling. Soil, 2nd and 3rd rates. Timber, scattering palo verde. Undergrowth, cat claw.</p>
40.00	<p>N.0° 2' W., bet. secs. 8 and 9. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \text{S } 8 \text{ } \text{ S } 9 \\ \hline 1916 \end{array}$ </p> <p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Road, brs. NE. and SW.</p>
48.20 80.00	<p>Set an iron post, 3 ft. long, 2 ins diam., 24 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, marked on brass cap</p> <p style="text-align: center;"> $\begin{array}{c} \text{T5N} \text{R8W} \\ \text{S } 5 \text{S } 4 \\ \text{S } 8 \text{S } 9 \\ \hline 1916 \end{array}$ </p> <p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, gently rolling. Soil, 2nd rate. Timber, scattering palo verde. Undergrowth, scattering cat claw.</p>
40.00 79.92	<p>N.89° 52' E., on a random line, bet. secs. 4 and 9: Set temp. $\frac{1}{4}$ sec. cor. Intersect N. and S. line, 9 lks. N. of the cor. of secs. 3, 4, 9 and 10. Thence</p>
3.12 39.96	<p>S.89° 56' W., on a true line, bet. secs. 4 and 9. Over gently rolling land, through scattering timber and undergrowth. Road, brs. NE. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \text{ S } 4 \\ \hline \text{S } 9 \\ \hline 1916 \end{array}$ </p>
79.92	<p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. The cor. of secs. 4, 5, 8 and 9. Land, gently rolling. Soil, 2nd rate. Timber, scattering palo verde. Undergrowth, cat claw.</p>

Subdivision of T. 5 N., R. 8 W.

Chains.

40.00 N.0° 2' W., on a random line, bet. secs. 4 and 5.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.10 Intersect N. bdy. of Tp., 2 lks. E. of the cor. of secs.
 4, 5, 32 and 33, which is an iron post, hereinbefore
 described.

Thence
 S.0° 3' E., on a true line, bet. secs. 4 and 5.
 Over gently rolling land, through scattering timber and
 undergrowth.

40.10 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
 ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
 brass cap




And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
 of cor.

80.10 The cor. of secs. 4, 5, 8 and 9.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, greasewood.

40.00 From the standard cor. of secs. 31 and 32, on the S. bdy.
 of the Tp., which is an iron post, hereinbefore described,
 N.0° 3' W., bet. secs. 31 and 32.
 Over rolling land, through scattering timber and undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
 of cor.

73.90 Draw, 50 lks. wide, 4 ft. deep, course SW.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for cor. of secs. 29, 30, 31 and 32, marked on
 brass cap



Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.;
 and raise a mound of earth, 4 ft. base, 2 ft. high, W.
 of cor.

Land, rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush, ocotillo and
 greasewood.

40.00 East on a random line, bet. secs. 29 and 32.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.96 Intersect N. and S. line, 6 lks. N. of the cor. of secs.
 28, 29, 32 and 33.

Thence
 N.89° 57' W., on a true line, bet. secs. 29 and 32.
 Over rolling land, through scattering timber and under-
 growth.

36.

Subdivision of T. 5 N., R. 8 W.

Chains.

4.95 Head of draw, 25 lks. wide, 4 ft. deep, course S.
 17.00 Draw, 20 lks. wide, 11 ft. deep, course S. Asc. 70 ft. to
 20.05 Desc. 40 ft. to
 29.95 Asc. 45 ft. to
 34.95 Low ridge, brs. N. and SE. Thence along S. slope.
 39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S29
 $\frac{1}{4}$ S32
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
 of cor.

67.70 Spur, slopes SW. Desc. 90 ft. to
 Draw, 15 lks. wide, 4 ft. deep, course N. Asc. 30 ft. to
 75.65 Spur, slopes N. Desc. 40 ft. to
 79.96 The cor. of secs. 29, 30, 31 and 32.
 Land, rolling.
 Soil, 4th rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, cactus, sagebrush and
 greasewood.

West on a true line, bet. secs. 30 and 31.
 Over rolling land, through scattering timber and under-
 growth.
 10.00 Draw, 50 lks. wide, 4 ft. deep, course NW.
 18.00 Road, brs. NE. and SW.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in a
 mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S30
 $\frac{1}{4}$ S31
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
 of cor.

42.90 Road, brs. N. and S.
 46.00 Draw, 25 lks. wide, 5 ft. deep, course NE. Asc. 45 ft. to
 52.17 Low ridge, brs. N. and S. Desc. 55 ft. to
 81.08 Intersect 2nd Guide Meridian West, 3.05 chs. S. of the cor.
 of secs. 25, 30, 31 and 36, which is an iron post,
 properly set, marked and witnessed as described by the
 Surveyor-General.
 At the point of intersection, set an iron post, 3 ft. long,
 2 ins. diam., 24 ins. in the ground, for closing cor.
 of secs. 30 and 31, marked on brass cap

T5N	T5N
S36	S30 CC
R9W	R8W
1916	

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E.
 of cor.

Land, rolling and gently rolling.
 Soil, 4th rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, cactus, sagebrush and
 greasewood.

N.0° 3' W., bet. secs. 29 and 30.
 Over gently rolling land, through scattering timber and
 undergrowth.

Subdivision of T. 5 N., R. 8 W.

Chains.	
6.30	Road, brs. NE. and SW.
33.98	Road, brs. E. and W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{c} \frac{1}{4} \\ \hline S30 S29 \\ 1916 \end{array}$
	And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
44.68	Road, brs. NW. and SE.
64.74	Road, brs. NE. and SW.
72.54	Road, brs. NW. and SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap
	$\begin{array}{c} T5N R8W \\ S19 S20 \\ \hline S30 S29 \\ 1916 \end{array}$
	And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, gently rolling. Soil, 3rd rate. Timber, scattering palo verde. Undergrowth, cat claw.
40.00	S. $89^{\circ}57'E.$, on a random line, bet. secs. 20 and 29.
80.03	Set temp. $\frac{1}{4}$ sec. cor.
	Intersect N. and S. line, at the cor. of secs. 20, 21, 28 and 29.
	Thence
	N. $89^{\circ}57'W.$, on a true line, bet. secs. 20 and 29.
	Over mountainous land, through scattering timber and undergrowth.
	Desc. 110 ft. to
6.05	Asc. 105 ft. to
10.75	Spur, slopes S. Desc. 320 ft. to
30.05	Asc. 25 ft. to
40.01 $\frac{1}{2}$	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{c} S20 \\ \hline \frac{1}{4} S29 \\ 1916 \end{array}$
	And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
80.03	Thence over gently rolling land.
	The cor. of secs. 19, 20, 29 and 30.
	Land, mountainous and gently rolling.
	Soil, 3rd and 4th rates.
	Timber, scattering palo verde.
	Undergrowth, cat claw.
	West on a true line, bet. secs. 19 and 30. Over gently rolling land, through scattering timber and undergrowth.
3.30	Road, brs. N. and S.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains.

$\frac{1}{4}$ S19
S30
1916

60.70 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 63.29 Draw, 75 lks. wide, 5 ft. deep, course NW.
 80.89 Road, brs. NW. and SE.
 Intersect the 2nd Guide Meridian West, 2.90 chs. S. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, properly set, marked and witnessed as described by the Surveyor-General.
 At the point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 19 and 30, marked on brass cap

T5N | T5N
S25 | S19
R9W | S30 - CC
R8W
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

3.96 N.0°3'W., bet. secs. 19 and 20.
 15.44 Over rolling land, through scattering timber and undergrowth.
 Asc. 35 ft. to
 Desc. 30 ft. to
 29.94 Draw, 45 lks. wide, 10 ft. deep, course NW. Thence over
 37.04 gently rolling land.
 Asc. 75 ft. to
 Desc. 80 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S19 | S20
1916

44.95 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 69.12 Asc. 175 ft. to
 80.00 Top of hill; desc. 115 ft. to
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on brass cap

T5N R8W
S18 | S17
S19 | S20
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, mountainous and gently rolling.
 Soil, 3rd and 4th rates.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

Subdivision of T. 5 N., R. 8 W.

Chains.

40.00 S. 89° 57' E., on a random line, bet. secs. 17 and 20.
Set temp. $\frac{1}{4}$ sec. cor.

80.10 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 16, 17, 20 and 21.
Thence
N. 89° 51' W., on a true line, bet. secs. 17 and 20.
Over mountainous land, through scattering timber and undergrowth.
Asc. 20 ft. to
3.15 Ridge, brs. NW. and SE. Desc. 140 ft. to
15.30 Draw, 75 lks. wide, 3 ft. deep, course NW. Thence over gently rolling land.
35.30 Asc. 220 ft.
40.05 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S17

 S20
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

45.90 Ridge, brs. NW. and SE. Desc. 255 ft. to
55.10 Thence over gently rolling land.
80.10 The cor. of secs. 17, 18, 19 and 20.
Land, mountainous and gently rolling.
Soil, 3rd and 4th rates.
Timber, scattering palo verde.
Undergrowth, cat claw.

West on a true line, bet. secs. 18 and 19.
Over mountainous land, through scattering timber and undergrowth.
Asc. 55 ft. to
4.01 Spur, slopes NE. Desc. 30 ft. to
10.00 Asc. 30 ft. to
12.35 Desc. 85 ft.
14.45 Road, brs. N. and S.
16.54 Draw, 20 lks. wide, 3 ft. deep, course N. Asc. 75 ft. to
26.07 Spur, slopes NW. Desc. 170 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S18

 S19
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

52.00 Draw, 50 lks. wide, 4 ft. deep, course N. Asc. 45 ft. to
63.80 Desc. 35 ft. to
70.00 Thence over gently rolling land.
80.77 Intersect 2nd Guide Meridian West, 2.92 chs. S. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, properly set, marked and witnessed as described by the Surveyor-General.
At the point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 18 and 19, marked on brass cap

T5N | T5N
 | S18
S24 | S19 CC
R9W | R8W
 | 1916


And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.
Land, mountainous and gently rolling.

40. Subdivision of T. 5 N. R. 8 W.


Chains.

Soil, 4th rate.
Timber, palo verde.
Undergrowth, mesquite, cat claw, sagebrush, cactus and greasewood.

3.40 N.0° 3' W., bet. secs. 17 and 18.
10.00 Over mountainous land, through scattering timber and under growth.
17.52 Asc. 40 ft. to
28.72 Ridge, brs. E. and W. Desc. to
40.00 Thence over gently rolling land.
Road, brs. NW. and SE.
Road, brs. E. and W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



80.00 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap




And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Land, mountainous and gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, greasewood.

40.00 S.89° 51' E., on a random line, bet. secs. 8 and 17.
80.08 Set temp. 1/4 sec. cor.
Intersect N. and S. line, 9 lks. S. of the cor. of secs. 8, 9, 16 and 17.

Thence
N.89° 55' W., on a true line, bet. secs. 8 and 17.
Over gently rolling land, through scattering timber and undergrowth.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



45.10 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
80.08 Road, brs. NE. and SW.
The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, sagebrush and greasewood.

Chains.

West on a true line, bet secs. 7 and 18.
 Over rolling land, through scattering timber and undergrowth.

16.80 Draw, 25 lks. wide, 3 ft. deep, course N.
 18.80 Road, brs. N. and S.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 7
 $\frac{1}{4}$ S 18
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

55.00 Asc. 30 ft. to
 60.00 Low ridge, brs. N. 30° W. and S. 30° E. Desc. 30 ft. to
 80.63 Intersect 2nd Guide Meridian West, 3.04 chs. S. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, properly set, marked and witnessed as described by the Surveyor-General.

At the point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 7 and 18, marked on brass cap

T5N	T5N
S13	S 7
R9W	S18 CC
	R8W
	1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.
 Land, rolling and gently rolling.
 Soil, 4th rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

N. 0° 3' W., bet. secs. 7 and 8.
 Over rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 7 | S 8
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, marked on brass cap

T5N	R8W
S 6	S 5
S 7	S 8
	1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush, ocotillo and greasewood.

42.

Subdivision of T. 5 N., R. 8 W.

chains.

40.00 S.89° 55' E., on a random line, bet. secs. 5 and 8.
Set temp. $\frac{1}{4}$ sec. cor.
80.05 Intersect N. and S. line, 16 lks. S. of the cor. of secs. 4, 5, 8 and 9.

Thence

S.89° 58' W., on a true line, bet. secs. 5 and 8.
Over gently rolling land, through scattering timber and undergrowth.

40.02 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 5
 $\frac{1}{4}$ S 8
1916

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

80.05 The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling.

Soil, 2nd rate.

Timber, scattering palo verde.

Undergrowth, mesquite, cat claw, greasewood and sagebrush.

West on a true line, bet. secs. 6 and 7.

Over gently rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 6
 $\frac{1}{4}$ S 7
1916

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

44.60 Road, brs. N. and S.

50.00 Road, brs. N. and S.

80.45 Intersect 2nd Guide Meridian West, 3.27 chs. S. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, properly set, marked and witnessed as described by the Surveyor-General.

At the point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 6 and 7, marked on brass cap

T5N | T5N
S12 | S 6
S 7 | CC
R9W | R8W
1916

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.

Land, gently rolling.

Soil, 3rd rate.

Timber, scattering palo verde.

Undergrowth, mesquite, cat claw, sagebrush, ocotillo and greasewood.

40.00 N.0° 3' W., on a random line, bet. secs. 5 and 6.


Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect N. bdy. of Tp., 4 lks. W. of the cor. of secs. 5, 6, 31 and 32, which is an iron post, hereinbefore described.

Subdivision of T. 5 N., R. 8 W.

Chains.

Thence
 S.0° 1' E., on a true line, bet. secs. 5 and 6.
 Over gently rolling land, through scattering timber and
 undergrowth.
 40.08 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
 dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
 high, W. of cor.
 80.08 The cor. of secs. 5, 6, 7 and 8.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, palo verde, cactus and
 greasewood.

General Description.

This township consists of rolling, rolling mountainous
 and mountainous land. The rolling portions extend through
 the north western part. Most of this township is of the
 rolling mountainous nature, with many washes and gulches.
 Mountainous land extends through the southern as well as
 the southwestern portions.
 The average soil is rocky, ranging from 3rd to 4th rate.
 Undergrowth is greasewood, palo verde, sagebrush, ocotillo,
 and mesquite.
 There is no water in this township.

BOOK 3107

~~FINAL OATH OF UNITED STATES SURVEYOR.~~

~~I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.~~

~~U. S. Surveyor.~~

~~Subscribed by said _____, and sworn to before me }
this _____ day of _____, 191____~~



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL;

Phoenix, Ariz. JUN 28 1916, 191____

The foregoing field notes of the survey of _____ the _____

~~East and North Boundaries and Subdivisional Lines and Resurvey of the South Boundary (First Std. Parallel North Thru Range 8 West) of TOWNSHIP 5 NORTH, RANGE 8 WEST,~~

~~of the Gila and Salt River Base and Meridian, in the State of Arizona,~~

~~executed by Roy J. Gill, U. S. Surveyor and Hans D. Voigt, U. S. Transitman, under ~~his~~ special instructions dated Sept. 24, 1915, for Group 59, Arizona, _____, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.~~

~~*Frank P. [Signature]*
U. S. Surveyor General.~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in _____, has been correctly copied from the original notes on file in this office.~~