

3112

G.L.O. letter "E"  
March 29, 1919 329

Book "H"  
4-679

①

BOOK 3112

Jan 7 1918

# FIELD NOTES

OF THE SURVEY OF THE

East and North Boundaries, and

Subdivision lines

of

TOWNSHIP 6 NORTH, RANGE 3 WEST.

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

Roy J. Gill, U. S. Surveyor,

and

Hans D. Voigt, U. S. Transitman,

~~In the capacity of U. S. Surveyor~~, under instructions dated September 24, 1915,  
issued by the United States Surveyor General to govern surveys included in  
Group No. 59, which were approved by the Commissioner of the General Land  
Office, October 8, 1915.

Survey commenced March 31, 1916.

Survey completed April 10, 1916.

Executed under Assignment  
Instructions dated November 26, 1915.

3112

3112

Book "H"

Group 59 - - - - Arizona.

BOOK 3112

INDEX DIAGRAM.

Township 6 North, Range 3 West.

		5		6		6		7		7		
Book "F"	6	35	5	28	4	25	3	18	2	15	1	4
	34		34		27		22		17		13	
	7	33	8	27	9	22	10	17	11	12	12	4
	33		33		26		21		16		12	
	18	32	17	25	16	21	15	16	14	11	18	3
	32		31		25		20		16		11	
	19	31	20	25	21	20	22	15	23	10	24	3
	30		30		24		19		15		10	
80	29	29	24	28	19	27	14	26	10	25	2	
29		29		24		19		14		9		
31	28	32	25	33	18	34	13	35	9	36	2	
Book "E"	Book "G"											Book "A"

Unsurveyed

- Surveeyed under this Group. Notes in this book.
- Surveeyed or resurveeyed under this Group.
- Surveeyed in 1872.

6N 3W

Book "H".  
 Group 59, Arizona.  
 Township 6 North, Range 3 West.

DATE DIAGRAM.

	4-7-16	4-7-16	4-7-16	4-7-16	4-7-16	4-7-16	
3-25-16	6 4-1-16	5 4-10-16	4 4-10-16	3 4-10-16	2 4-10-16	1 4-8-16	4-6-16
3-25-16	7 4-1-16	8 4-1-16	9 4-1-16	10 4-10-16	11 4-10-16	12 4-10-16	4-6-16
3-25-16	18 4-3-16	17 4-3-16	16 4-3-16	15 4-3-16	14 4-10-16	13 4-10-16	4-6-16
3-25-16	19 4-3-16	20 4-3-16	21 4-3-16	22 4-3-16	23 4-8-16	24 4-8-16	4-6-16
3-25-16	30 4-3-16	29 4-3-16	28 4-3-16	27 4-3-16	26 4-7-16	25 4-7-16	4-6-16
3-25-16	31 4-1-16	32 4-1-16	33 4-1-16	34 4-3-16	35 4-7-16	36 4-7-16	4-6-16
	3-17-16	3-17-16	3-17-16	3-17-16	3-17-16	3-17-16	

Lines dated in blue were surveyed by Roy J. Gill,  
U. S. Surveyor.

Lines dated in red were surveyed by Hand S. Voigt,  
U. S. Transitman.

2. East Boundary of T. 6 N., R. 3 W.

Chains.

Survey executed with Buff and Buff light mountain transit No. 7732, with Smith solar attachment. For description of instrument and certificate of approval, see Book "I". Knowing from recent and repeated tests of this instrument on a meridian determined by a series of direct observations on the sun for azimuth, that it is in adjustment, I proceed to the survey of the E. bdy. of T. 6 N., R. 3 W.

40.00

From the cor. of Ts. 5 and 6 N., Rs. 2 and 3 W., which is an iron post, described in Book "G", North bet. secs. 31 and 36. Over level land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

54.85


Draw, 45 lks. wide, 2 ft. deep, course SE.

60.30

Same draw, course SW.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, marked on brass cap




And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, level.  
Soil, 2nd rate.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

40.00

North bet. secs. 25 and 30. Over level land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for 1/4 sec. cor., marked on brass cap




And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

75.00

Draw, 45 lks. wide, 1 ft. deep, course SE.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 19, 24, 25 and 30, marked on brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.  
Land, level.


East Boundary of T. 6 N., R. 3 W.

Chains.


Soil, 2nd rate.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

North bet. secs. 19 and 24.  
Over level and gently rolling land, through scattering  
timber and undergrowth.

5.00 Draw, 45 lks. wide, 1 ft. deep, course SW.  
40.00 Set an iron post, 3 ft. long, 1 in diam., 12 ins. in the  
ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on  
brass cap



80.00 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of cor.  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for cor. of secs. 13, 18, 19 and 24, marked on  
brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of cor.  
Land, level and gently rolling.  
Soil, 2nd rate.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

North bet. secs. 13 and 18.  
Over gently rolling land, through scattering timber and  
undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



60.50 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of cor.

Road, brs. E. and W.  
62.00 Draw, 45 lks. wide, 2 ft. deep, course SE.  
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for cor. of secs. 7, 12, 13 and 18, marked on  
brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of cor.  
Land, gently rolling.  
Soil, 2nd rate.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

4. East Boundary of T. 6 N., R. 3 W.

Chains.

North bet. secs. 7 and 12.  
Over gently rolling land, through scattering timber and undergrowth.

40.00 Wash, 15 lks. wide, 1 ft. deep, course SE.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S12 | S 7  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

60.00 Asc. 110 ft. to

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 10 ins. in the ground, in a mound of stone, for cor. of secs. 1, 6, 7 and 12, marked on brass cap

T6N  
R3W | R2W  
S 1 | S 6  
S12 | S 7  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, gently rolling and hilly.  
Soil, 2nd and 4th rates.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

North bet. secs. 1 and 6.  
Over mountainous land, through scattering timber and undergrowth.

5.63 Asc. 65 ft. to

14.82 Top of hill; desc. 50 ft. to

40.00 Foot of descent; thence over gently rolling land.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S 1 | S 6  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 Set an iron post, 3ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of Ts. 6 and 7 N., Rs. 2 and 3 W., marked on brass cap

T7N  
R3W | R2W  
S36 | S31  
S 1 | S 6  
T6N  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and hilly.  
Soil, 2nd and 3rd rates.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

North Boundary of T. 6 N., R. 3 W.

Chains.

From the cor. of Ts. 6 and 7 N., Rs. 2 and 3 W., which is an iron post, hereinbefore described,  
West on a random line, along the N. bdy. of T. 6 N., R. 3 W., setting temp.  $\frac{1}{4}$  sec. and sec. cors. at intervals of 40.00 chs.; and at 459.32 chs., fall 1.47 chs. S. of the cor. of Ts. 6 N., Rs. 3 and 4 W., which is an iron post, reestablished as described in Book "F".  
The falling answers to a correction of  $0^{\circ} 11'$ , or 26 lks. N. per mile, counting from the NE. cor. of the Tp.; therefore

S.  $89^{\circ} 49'$  E., on a true line, bet. secs. 6 and 31.  
Over rolling land, through scattering timber and undergrowth.  
0.65 Wash, 10 lks. wide, course S.  
6.85 Wash, 6 lks. wide, course S.  
8.55 Wash, 6 lks. wide, course SW.  
15.20 Wash, 6 lks. wide, course SW. Asc. 115 ft.  
19.32 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S31  
 $\frac{1}{4}$  S 6  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
35.30 Ridge, brs. NW. and SE. Desc. 205 ft. to  
47.15 Wash, 50 lks. wide, course S. Thence over rolling land.  
59.32 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 31 and 32, marked on brass cap

T7N R3W  
S31 | S32  
S 6 | S 5  
T6N  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
Land, rolling and mountainous.  
Soil, 3rd rate.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

S.  $89^{\circ} 49'$  E., on a true line, bet. secs. 5 and 32.  
Over rolling hills, through scattering timber and undergrowth.  
27.70 Wash, 10 lks. wide, course S.  
30.85 Telephone line, brs. NE. and SW.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{2}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S32  
 $\frac{1}{4}$  S 5  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
41.60 Road, brs. N. and S.  
45.80 Wash, 50 lks. wide, course SW.  
75.00 Wash, 8 lks. wide, course S.  
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground, in a mound of stone, for cor. of secs. 4, 5, 32 and 33, marked on brass cap

6.

North Boundary of T. 6 N., R. 3 W.

chains.

T7N	R3W
S32	S33
S 5	S 4
T6N	
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, rolling hills.  
 Soil, 3rd rate.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw and greasewood.

33.20  
35.90  
40.00

S.89° 49' E., on a true line, bet. secs. 4 and 33.  
 Over rolling land, through scattering timber and undergrowth.  
 Road, brs. N. to Castle Hot Springs and S. to Morristown.  
 Wash, 12 lks. wide, course SW.  
 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

S33	
¼	S 4
1916	

61.90  
80.00

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.  
 Road, brs. NE. and SW.  
 Set an iron post, 3 ft. long, 3 ins. diam., 16 ins. in the ground, in a mound of stone, for cor. of secs. 3, 4, 33 and 34, marked on brass cap

T7N	R3W
S33	S34
S 4	S 3
T6N	
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, rolling.  
 Soil, 3rd rate.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw and greasewood.

40.00

S.89° 49' E., on a true line, bet. secs. 3 and 34.  
 Over rolling hills, through scattering timber and undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap.

S34	
¼	S 3
1916	

45.70  
80.00

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.  
 Wash, 80 lks. wide, course S.  
 Set an iron post, 3 ft. long, 3 ins. diam., 14 ins. in the ground, in a mound of stone, for cor. of secs. 2, 3, 34 and 35, marked on brass cap



North Boundary of T. 6 N., R. 3 W.

7.

Chains.

T7N	R3W
S34	S35
S 3	S 2
T6N	
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, rolling hills.  
 Soil, 3rd rate.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw and greasewood.

24.90  
40.00

S.89° 49' E., on a true line, bet. secs. 2 and 35.  
 Over rolling hills, through scattering timber and undergrowth.  
 Wash, 10 lks. wide, course S.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	S35
¼	S 2
1916	

58.50  
65.20  
78.00  
80.00

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Wash, 10 lks. wide, course S.  
 Wash, 8 lks. wide, course SW.  
 Wash, 8 lks. wide, course S.  
 Set an iron post, 3 ft. long, 3 ins. diam., 14 ins. in the ground, in a mound of stone, for cor. of secs. 1, 2, 35 and 36, marked on brass cap

T7N	R3W
S35	S36
S 2	S 1
T6N	
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, rolling hills.  
 Soil, 3rd rate.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw and greasewood.

40.00

S.89° 49' E., on a true line, bet. secs. 1 and 36.  
 Over rolling land, through scattering timber and undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	S36
¼	S 1
1916	

80.00

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.  
 The cor. of Ts. 6 and 7 N., Rs. 2 and 3 W.  
 Land, rolling.  
 Soil, rocky; strewn with boulders.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw and greasewood.

X

Boundaries of T. 6 N., R. 3 W.

Latitudes, departures and closing errors.

Line designated.	True bearing.	Dist. chs.	Latitudes.		Departures.	
			N. chs.	S. chs.	E. chs.	W. chs.
South boundary	S. 89° 59' W.	479.65		.14		479.65
West boundary.	North.	481.36	481.36			
North boundary.	East S. 89° 49' E.	20.12 459.32		1.47	20.12 459.32	
East boundary.	South.	480.00		480.00		
Convergency					.49	
Totals			481.36	481.61 481.36	479.93 479.65	479.65
Error in latitude.				.25		
Error in departure					.28	

Subdivision of T. 6 N., R. 3 W.

9.

Chains.

Survey commenced and executed with Buff and Buff light mountain transit No. 7732, and Young and Sons' light mountain transit No. 8293, each instrument being equipped with Smith solar attachment. For description of instrument and certificate of approval, see Book "I".  
 Knowing from recent and repeated tests of these instruments on a meridian determined by a series of direct observations on the sun for azimuth that they are in adjustment, we proceed to the subdivision of T. 6 N., R. 3 W.


I commence at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of Tp., which is an iron post, described in Book "G".

Thence

N.0° 1' W., bet. secs. 35 and 36.

Over gently rolling land, through scattering timber and undergrowth.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

40.20 Wash, 20 lks. wide, 3 ft. deep, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, gently rolling.

Soil, rocky; 3rd rate.

Timber, scattering palo verde and mesquite.

Undergrowth, cat claw, sagebrush, cactus and greasewood.

40.00 N.89° 59' E., on a random line, bet. secs. 25 and 36.

79.92 Set temp.  $\frac{1}{4}$  sec. cor.

Intersect N. and S. line, 5 lks. N. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, hereinbefore described.

Thence


S.89° 57' W., on a true line, bet. secs. 25 and 36.

Over gently rolling land, through scattering timber and undergrowth.

22.00 Wash, 65 lks. wide, 3 ft. deep, course S.

37.20 Road, brs. N. and S.

39.96 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

47.10 Wash, 20 lks. wide, 4 ft. deep, course S.

79.92 The cor. of secs. 25, 26, 35 and 36.

Land, gently rolling

Soil, 3rd rate.

Timber, scattering mesquite and palo verde.

Undergrowth, cat claw, sagebrush and greasewood.

10. Subdivision of T. 6 N., R. 3 W.

Chains.  
N.0° 1' W., bet. secs. 25 and 26.  
Over gently rolling land, through scattering timber and undergrowth.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S26 | S25  
 |  
 1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
79.00 Wash, 15 lks. wide, 3 ft. deep, course SW.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, marked on brass cap

T6N | R3W  
 S23 | S24  
 S26 | S25  
 1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, sagebrush, cat claw, cactus and greasewood.

40.00 N.89° 57' E., on a random line, bet. secs. 24 and 25.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.01 Intersect E. bdy. of Tp., 7 lks. S. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, described hereinbefore.

Thence  
S.89° 54' W., on a trueline, bet. secs. 24 and 25.  
Over gently rolling land, through scattering timber and undergrowth.  
8.10 Wash, 20 lks. wide, 2 ft. deep, course SE.  
38.90 Wash, 15 lks. wide, 3 ft. deep, course S.  
40.00 $\frac{1}{2}$  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S24  
 S25  
 1916

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
55.00 Road, brs. N. and S.  
68.60 Wash, 25 lks. wide, 3 ft. deep, course S.  
79.70 Wash, 20 lks. wide, 2 ft. deep, course SW.  
80.01 The cor. of secs. 23, 24, 25 and 26.  
Land, gently rolling.  
Soil, gravelly; 2nd and 3rd rates.  
Timber, scattering mesquite and paloverde.  
Undergrowth, cat claw, cactus, sagebrush and greasewood.

40.00 N.0° 1' W., bet. secs. 23 and 24.  
Over gently rolling land through scattering timber and undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Subdivision of T. 6 N., R. 3 W.

11.

nChains.

S23 | S24

1916

80.00 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.  
Set an iron post, 3 ft long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked on brass cap

T6N | R3W  
S14 | S13  
S23 | S24  
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.  
Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, greasewood, sagebrush, cat claw and ca ctus.

40.00 N. 89° 54' E., on a random line, bet. secs. 13 and 24.  
Set temp. 1/4 sec. cor.  
80.03 Intersect E. bdy. of Tp., 14 lks. N. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, hereinbefore described.

Thence  
West on a true line, bet. secs. 13 and 24.  
Over gently rolling land, through scattering timber and undergrowth.

25.00 Draw, 25 lks. wide, 3 ft. deep, course S.  
39.95 Wash, 30 lks. wide, 3 ft. deep, course SW.  
40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4 S13  
S24  
1916

63.25 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.  
Wash, 20 lks. wide, 9 ft. deep, course S.  
77.85 Road, brs. NW. and SE.  
80.03 The cor. of secs. 13, 14, 23 and 24.  
Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, greasewood.

1.50 N. 0° 1' W., bet. secs. 13 and 14.  
Over gently rolling land, through scattering timber and undergrowth.  
40.00 Road, brs. N. 60° W. and S. 60° E.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4  
S14 | S13  
1916

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

12.

Subdivision of T. 6 N., R. 3 W.

Chains.  
80.00

Set an iron post 3 ft long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked on brass cap

T6N | R3W  
S11 | S12  
S14 | S13  
1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, gently rolling.

Soil, 3rd rate; gravelly.

Timber, scattering palo verde and mesquite.

Undergrowth, cat claw, cactus, sagebrush and greasewood.

40.00

East on a random line, bet. secs. 12 and 13.

79.99

Set temp. ¼ sec. cor.

Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, hereinbefore described.

Thence

S. 89° 58' W., on a true line, bet. secs. 12 and 13.

Over gently rolling land, through scattering timber and undergrowth.

4.80

Wash, 30 lks. wide, 3 ft. deep, course SE.

35.00

Wash, 30 lks. wide, 3 ft. deep, course SE.

39.99½

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S12  
¼ S13  
1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

60.73

Wash, 20 lks. wide, 3 ft. deep, course SE.

79.99

The cor. of secs. 11, 12, 13 and 14.

Land, gently rolling.

Soil, 3rd rate.

Timber, dense mesquite and palo verde.

Undergrowth, greasewood.

40.00

N. 0° 1' W., bet. secs. 11 and 12.

Over gently rolling land, through scattering timber and undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S11 | S12  
1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, marked on brass cap

T6N | R3W  
S 2 | S 1  
S11 | S12  
1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Chains.

Land, gently rolling.  
Soil, rocky; 3rd rate.  
Timber, scattering mesquite and palo verde.  
Undergrowth, cat claw, mesquite, cactus, sagebrush and greasewood.

40.00 N.89° 58' E., on a random line, bet. secs. 1 and 12.  
Set temp. 1/4 sec. cor.  
80.10 Intersect E. bdy. of Tp., 16 lks. N. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, hereinbefore described.

Thence  
N.89° 55' W., on a true line, bet. secs. 1 and 12.  
Over mountainous land, through scattering timber and undergrowth.  
Asc. 65 ft. to  
5.50 Top of hill; desc. 170 ft. to  
20.10 Foot of descent; thenceover gently rolling land.  
39.95 Wash, 5 lks. wide, course S.  
40.05 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for 1/4 sec. cor., marked on brass cap

S 1  
1/4 S12  
1916

80.10 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.  
The cor. of secs. 1, 2, 11 and 12.  
Land, mountainous and gently rolling.  
Soil, 3rd and 4th rates.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

40.00 N.0° 1' W., on a random line, bet. secs. 1 and 2.  
Set temp. 1/4 sec. cor.  
80.43 Intersect N. bdy. of Tp., 2 lks. W. of the cor. of secs. 1, 2, 35 and 36, which is an iron post, hereinbefore described.

Thence  
South on a true line, bet. secs. 1 and 2.  
Over gently rolling land, through scattering timber and undergrowth.  
40.43 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

S 2 1/4 S 1  
1916

80.43 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.  
The cor. of secs. 1, 2, 11 and 12.  
Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, cat claw, sagebrush, cactus and greasewood.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., which is an iron post, described in Book "G",

14. Subdivision of T. 6 N., R. 3 W.

Chains.

40.00 N.0° 1' W., bet. secs. 34 and 35.  
Over level land, through scattering timber and undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S34 | S35  
1916

80.00 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked on brass cap

T6N | R3W  
S27 | S26  
S34 | S35  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor

Land, gently rolling.  
Soil, 2nd and 3rd rates.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

40.00 N.89° 59' E., on a random line, bet. secs. 26 and 35.  
Set temp.  $\frac{1}{4}$  sec. cor.

80.02 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 25, 26, 35 and 36.

Thence

S.89° 57' W., on a true line, bet. secs. 26 and 35.

40.01 Over level land, through scattering timber and undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S26  
S35  
1916

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

42.20 Wash, 15 lks. wide, 4 ft. deep, course S.

50.00 Wash, 20 lks. wide, 3 ft. deep, course SE.

80.02 The cor. of secs. 26, 27, 34 and 35.

Land, level.

Soil, 3rd rate.

Timber, scattering palo verde and mesquite.

Undergrowth, cat claw, sagebrush, cactus and greasewood.

40.00 N.0° 1' W., bet. secs. 26 and 27.  
Over level land, through scattering timber and undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S27 | S26  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the



Chains.

ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap

T6N	R3W
S22	S23
S27	S26

1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, level.  
 Soil, 2nd and 3rd rates.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw and greasewood.

40.00  
80.06

N.89° 57' E., on a random line, bet. secs. 23 and 26.  
 Set temp. ¼ sec. cor.  
 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 23, 24, 25 and 26.

Thence  
 S.89° 58' W., on a true line, bet. secs. 23 and 26.  
 Over gently rolling land, through scattering timber and undergrowth.

6.30  
40.03

Wash, 15 lks. wide, 4 ft. deep, course S.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼	S23
¼	S26

1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor

42.30  
60.00  
67.90  
80.06

Wash, 20 lks. wide, 4 ft. deep, course S.  
 Wash, 35 lks. wide, 3 ft. deep, course S.  
 Wash, 20 lks. wide, 3 ft. deep, course S.  
 The cor. of secs. 22, 23, 26 and 27.  
 Land, gently rolling.  
 Soil, gravelly; 3rd rate.  
 Timber, scattering mesquite and palo verde.  
 Undergrowth, cat claw, sagebrush, cactus and greasewood.

40.00

N.0° 1' W., bet. secs. 22 and 23.  
 Over gently rolling land, through scattering timber and undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼	S22	S23
---	-----	-----

1916

80.00

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22, and 23, marked on brass cap

T6N	R3W
S15	S14
S22	S23

1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor  
 Land, gently rolling.

16.

Subdivision of T. 6 N., R. 3 W.

Chains.

Soil, gravelly; 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, cat claw, sagebrush, cactus and greasewood.

40.00 N. 89° 58' E., on a random line, bet. secs. 14 and 23.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.14 Intersect N. and S. line, 5 lks. N. of the cor. of secs.  
13, 14, 23 and 24,  
Thence  
West on a true line, bet. secs. 14 and 23.  
Over gently rolling land, through scattering timber and  
undergrowth.  
7.95 Wash, 15 lks. wide, 3 ft. deep, course S.  
38.65 Wash, 40 lks. wide, course SE.  
40.07 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S14  
 $\frac{1}{4}$  S23

1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N.  
of cor.

40;25 Wash, 20 lks. wide, course S.  
63.15 Wash, 10 lks wide, course S.  
80.14 The cor. of secs. 14, 15, 22 and 23.  
Land, gently rolling.  
Soil, 3rd rate.  
Timber, palo verde and mesquite.  
Undergrowth, greasewood.

40.00 N. 0° 1' W., bet. secs. 14 and 15.  
Over gently rolling land, through scattering timber and  
undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the  
ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on  
brass cap

S15 | S14

1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the  
ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on  
brass cap

T6N | R3W  
S10 | S11  
S15 | S14

1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of cor.


Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering palo verde.  
Undergrowth, cat claw and greasewood.

40.00 East on a random line, bet. secs. 11 and 14.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.10 Intersect N. and S. line, 2 lks. S. of the cor. of secs.

Subdivision of T. 6 N., R. 3 W.


Chains.

11, 12, 13 and 14.  
 Thence  
 S.89° 59' W., on a true line, bet. secs. 11 and 14.  
 Over gently rolling land, through dense timber and  
 undergrowth.  
 11.00 Draw, 25 lks. wide, 4 ft. deep, course SE.  
 21.40 Wash, 20 lks. wide, 2 ft. deep, course S.  
 24.70 Road, brs. NW. and SE.  
 40.05 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N.  
 of cor.  
 45.00 Wash, 20 lks. wide, 5 ft. deep, course S.  
 48.40 Wash, 20 lks. wide, 2 ft. deep, course SE.  
 80.10 The cor. of secs. 10, 11, 14 and 15.  
 Land, gently rolling.  
 Soil, 3rd rate.  
 Timber, dense mesquite and palo verde.  
 Undergrowth, cat claw, and greasewood.

N.0° 1' W., bet. secs. 10 and 11.  
 Over gently rolling land, through scattering timber and  
 undergrowth.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the  
 ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on  
 brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of cor.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 2, 3, 10 and 11, marked on  
 brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of cor.  
 Land, gently rolling.  
 Soil, 3rd rate.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw.

N.89° 59' E., on a random line, bet. secs. 2 and 11.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.11 Intersect N. and S. line, 26 lks. S. of the cor. of secs.  
 1, 2, 11 and 12.  
 Thence  
 S.89° 48' W., on a true line, bet. secs. 2 and 11.  
 Over gently rolling land, through scattering timber and  
 undergrowth.  
 40.05 $\frac{1}{2}$  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



Chains.

$\frac{1}{4}$  S 2  
S 11  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

44.60 Wash, 20 lks. wide, 5 ft. deep, course S.

45.10 Road, brs. N. and S.

60.70 Wash, 15 lks. wide, 5 ft. deep, course SE.

70.90 Wash, 15 lks. wide, 9 ft. deep, course SE.

79.85 Road, brs. NE. and SW.

80.11 The cor. of secs. 2, 3, 10 and 11.

Land, gently rolling.

Soil, 3rd rate.

Timber, scattering palo verde and mesquite.

Undergrowth, cat claw, cactus, sagebrush and greasewood.

40.00 N.0° 1' W., on a random line, bet. secs. 2 and 3.

Set temp.  $\frac{1}{4}$  sec. cor.

80.93 Intersect N. bdy. of Tp., 6 lks. W. of the cor. of secs. 2, 3, 34 and 35, which is an iron post, hereinbefore described.

Thence

S.0° 2' W., on a true line, bet. secs. 2 and 3.

Over gently rolling land, through scattering timber and undergrowth.

40.93 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 3  $\frac{1}{4}$  S 2  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

75.95 From this point, small house and mine shaft. br. W. 10 chs. dist.

80.93 The cor. of secs. 2, 3, 10 and 11.

Land, gently rolling.

Soil, 3rd rate.

Timber, scattering palo verde.

Undergrowth, cat claw and greasewood.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., which is an iron post, described in Book "G", N.0° 2' W., bet secs. 33 and 34.

Over gently rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 33  $\frac{1}{4}$  S 34  
1916

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on brass cap


T6N R3W  
S28 S27  
S33 S34  
1916

Subdivision of T. 6 N., R. 3 W.

Chains.


And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, gently rolling.  
 Soil, 3rd rate.  
 Timber, scattering palo verde and mesquite.  
 Undergrowth, greasewood, sagebrush, ocotillo, cactus.

40.00 N.89° 59' E., on a random line, bet. secs. 27 and 34.  
 Set temp. ¼ sec. cor.  
 80.01 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 26, 27, 34 and 35.  
 Thence  
 N.89° 59' W., on a true line, bet. secs. 27 and 34.  
 Over level land, through scattering timber and undergrowth.  
 31.20 Wash, 45 lks. wide, 2 ft. deep, course SE.  
 40.00½ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap




80.01 And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.  
 The cor. of secs. 27, 28, 33 and 34.  
 Land, level.  
 Soil, 2nd and 3rd rates.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw.

40.00 N.0° 2' W., bet. secs. 27 and 28.  
 Over gently rolling land, through scattering timber and undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



80.00 And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on brass cap



And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, gently rolling.  
 Soil, 3rd rate.  
 Timber, scattering mesquite and palo verde.  
 Undergrowth, greasewood, sagebrush, ocotillo and cactus.

40.00 S.89° 59' E., on a random line, bet. secs. 22 and 27.  
 Set temp. ¼ sec. cor.  
 79.92 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 22, 23, 26 and 27.

Chains.

Thence

West on a true line, bet. secs. 22 and 27.  
Over level land, through scattering timber and undergrowth.

20.00

Draw, 50 lks. wide, 2 ft. deep, course S.

39.96

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S22  
+ S27  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

79.92

The cor. of secs. 21, 22, 27 and 28.

Land, level.

Soil, 2nd and 3rd rates.

Timber, scattering palo verde.

Undergrowth, cat claw and greasewood.

N.0° 2' W., bet. secs. 21 and 22.

Over gently rolling land, through scattering timber and undergrowth.

11.00

Wash, 15 lks. wide, 4 ft. deep, course SW.

21.70

Wash, 15 lks. wide, 4 ft. deep, course SE.

24.60

Same wash, course SW.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S21 | S22  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

48.00

Wash, 25 lks. wide, 5 ft. deep, course SE.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, in a mound of stone, for cor. of secs. 15, 16, 21 and 22, marked on brass cap

T6N | R3W  
S16 | S15  
S21 | S22  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, gently rolling.

Soil, rocky; 3rd rate.

Timber, scattering palo verde and mesquite.

Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood.

East on a random line, bet. secs. 15 and 22.

40.00

Set temp.  $\frac{1}{4}$  sec. cor.

80.00

Intersect N. and S. line, 2 lks. N. of the cor. of secs. 14, 15, 22 and 23.

Thence

N.89° 59' W., on a true line, bet. secs. 15 and 22.

Over gently rolling land, through scattering timber and undergrowth.

13.70

Wash, 20 lks. wide, 4 ft. deep, course SSE.

23.50

Wash, 25 lks. wide, 3 ft. deep, course SE.

37.30

Wash, 20 lks. wide, 4 ft. deep, course S.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, for  $\frac{1}{4}$  sec. cor.,

Subdivision of T. 6 N., R. 3 W.

21.

Chains

ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S15  
S22  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

- 48.00 Wash, 20 lks. wide, 4 ft. deep, course S.
- 60.50 Wash, 20 lks. wide, 3 ft. deep, course SW.
- 62.20 Wash, 15 lks. wide, 4 ft. deep, course S.
- 75.20 Wash, 50 lks. wide, 4 ft. deep, course S.
- 80.00 The cor. of secs. 15, 16, 21 and 22.

Land, gently rolling.  
Soil, 2nd and 3rd rates.  
Timber, scattering palo verde and mesquite  
Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood.

N.0° 2' W., bet. secs. 15 and 16.

Over gently rolling land, through scattering timber and undergrowth.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S16 | S15  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

- 42.20 Wash, 25 lks. wide, 4 ft. deep, course S.70° E.
- 62.70 Wash, 25 lks. wide, 4 ft. deep, course SW.
- 79.20 Wash, 15 lks. wide, 4 ft. deep, course SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap

T6N | R3W  
S 9 | S10  
S16 | S15  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering mesquite and palo verde.  
Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood.

S.89° 59' E., on a random line, bet. secs. 10 and 15.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.94 Intersect N. and S. line; at the cor. of secs. 10, 11, 14 and 15.

Thence

N.89° 59' W., on a true line, bet. secs. 10 and 15.

Over gently rolling land, through scattering timber and undergrowth.

- 6.30 Wash, 10 lks. wide, 4 ft. deep, course SE.
- 17.30 Wash, 15 lks. wide, 3 ft. deep, course SW.
- 39.97 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S10  
S15  
1916

Chains.

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 42.10 Wash, 10 lks. wide, 5 ft. deep, course S.  
 45.00 Wash, 15 lks. wide, 10 ft. deep, course SW.  
 73.70 Wash, 20 lks. wide, 9 ft. deep, course S.  
 79.94 The cor. of secs. 9, 10, 15 and 16.  
 Land, gently rolling.  
 Soil, 3rd rate.  
 Timber, scattering palo verde and mesquite.  
 Undergrowth, greasewood.

N.0° 2' W., bet. secs. 9 and 10.  
 Over gently rolling land, through scattering timber and undergrowth.  
 33.80 Dim road, brs. NE. and SW.  
 40.00 Set an iron post, 3 ft. long, lin. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 9 \text{ | S } 10 \\ \hline 1916 \end{array}$$

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 43.60 Wash, 15 lks. wide, 4 ft. deep, course SW.  
 50.50 Wash, 18 lks. wide, 3 ft. deep, course SW.  
 56.30 Wash, 20 lks. wide, 2 ft. deep, course SW.  
 78.30 Wash, 35 lks. wide, 3 ft. deep, course SW.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap

$$\begin{array}{c} \text{T6N | R3W} \\ \text{S 4 | S 3} \\ \hline \text{S 9 | S 10} \\ \hline 1916 \end{array}$$

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Land, gently rolling.  
 Soil, rocky; 3rd rate.  
 Timber, scattering mesquite and palo verde.  
 Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood.

40.00 S.89° 59' E., on a random line, bet. secs. 3 and 10.  
 Set temp. ¼ sec. cor.  
 79.97 Intersect N. and S. line, 19 lks. N. of the cor. of secs. 2, 3, 10 and 11.

Thence  
 N.89° 51' W., on a true line, bet. secs. 3 and 10;  
 Over gently rolling land, through scattering timber and undergrowth.  
 5.45 Wash, 15 lks. wide, 8 ft. deep, course S.  
 8.45 Road, brs. N. and S.  
 34.10 Wash, 20 lks. wide, 5 ft. deep, course S.  
 39.98½ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} \text{ S } 3 \\ \hline \text{S } 10 \\ \hline 1916 \end{array}$$

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 43.95 Wash, 20 lks. wide, 9 ft. deep, course S.



Subdivision of T. 6 N., R. 3 W. 23.

Chains.  
79.97

The cor. of secs. 3, 4, 9 and 10.  
Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, cat claw and greasewood.

40.00

N.0° 2' W., on a random line, bet. secs. 3 and 4.  
Set temp.  $\frac{1}{4}$  sec. cor.

81.01

Intersect N. bdy. of Tp., 5 lks. E. of the cor. of secs. 3, 4, 33 and 34, which is an iron post, hereinbefore described.

Thence

S.0° 4' E., on a true line, bet. secs. 3 and 4.  
Over gently rolling land, through scattering timber and undergrowth.

29.00

Enter wash, 15 lks. wide, 4 ft. deep, course S. Comes from NE.

38.20

Leave wash, course SW.

41.01

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

60.00

Wash, 15 lks. wide, 4 ft. deep, course W.

80.50


Wash, 1 ch. wide, 3 ft. deep, course SW.

81.01

The cor. of secs. 3, 4, 9 and 10.  
Land, gently rolling.  
Soil, 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, ocotillo, cat claw, sagebrush and greasewood.

40.00

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., which is an iron post, described in Book "G", N.0° 2' W., bet. secs. 32 and 33.  
Over level land, through scattering timber and undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

45.00

Wash, 45 lks. wide, 2 ft. deep, course SE.

64.40

Road, brs. NW. and SE.

65.35


S. F., P. and P. Ry., brs. N.47° W. and S.47° E.

66.00

Telephone and Telegraph line, brs. N.47° W. and S.47° E.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, marked on brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, level.

Chains.

Soil, 2nd rate.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw.

40.00 N.89° 59' E., on a random line, bet. secs. 28 and 33.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.12 Intersect N. and S. line, 2 lks. N. of the cor. of secs.  
 27, 28, 33 and 34.  
 Thence  
 West on a true line, bet. secs. 28 and 33.  
 Over level land, through scattering timber and undergrowth.  
 18.30 Wash, 50 lks. wide, 2 ft. deep, course SE.  
 40.06 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S28  
 $\frac{1}{4}$  S33  
 1916

80.12 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.  
 dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.  
 high, N. of cor.  
 The cor. of secs. 28, 29, 32 and 33.  
 Land, level.  
 Soil, 2nd rate.  
 Undergrowth, cat claw and greasewood.  
 Timber, scattering palo verde.

27.90 N.0° 2' W., bet. secs. 28 and 29.  
 Over level land, through scattering timber and undergrowth.  
 40.00 Old road, brs. NE. and SW.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S29 | S28  
 1916

64.50 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of cor.  
 80.00 Wash, 45 lks. wide, 4 ft. deep, course SW.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 20, 21, 28 and 29, marked on  
 brass cap

T6N | R3W  
 S20 | S21  
 S29 | S28  
 1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of cor.  
 Land, level.  
 Soil, 2nd rate.  
 Timber, scattering palo verde.  
 Undergrowth, greasewood.

40.00 East on a random line, bet. secs. 21 and 28.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.20 Intersect N. and S. line, 10 lks. S. of the cor. of secs.  
 21, 22, 27 and 28.  
 Thence  
 S.89° 56' W., on a true line, bet. secs. 21 and 28.  
 Over gently rolling land, through scattering timber and  
 undergrowth.

Subdivision of T. 6 N., R. 3 W.

Chains.  
 15.70 Wash, 20 lks. wide, 4 ft. deep, course S.  
 20.70 Wash, 50 lks. wide, 3 ft. deep, course S.  
 35.00 Wash, 15 lks. wide, 4 ft. deep, course S.  
 40.10 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S21  
 $\frac{1}{4}$  S28  
 1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

47.80 Wash, 15 lks. wide, 4 ft. deep, course S.  
 75.00 Wash, 20 lks. wide, 6 ft. deep, course S.  
 80.20 The cor. of secs. 20, 21, 28 and 29.  
 Land, gently rolling.  
 Soil, 2nd and 3rd rates.  
 Timber, scattering palo verde and mesquite.  
 Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood

40.00 N.0° 2' W., bet. secs. 20 and 21.  
 Over level land, through scattering timber and undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S20 | S21  
 1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

72.70 Wash, 60 lks. wide, 10 ft. deep, course SW.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on brass cap

T6N | R3W  
 S17 | S16  
 S20 | S21  
 1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Land, level.  
 Soil, 2nd rate.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw.

40.00 N.89° 56' E., on a random line, bet. secs. 16 and 21.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.18 Intersect N. and S. line, 7 lks. N. of the cor. of secs. 15, 16, 21 and 22.  
 Thence  
 S.89° 59' W., on a true line, bet. secs. 16 and 21.  
 Over gently rolling land, through scattering timber and undergrowth.

11.80 Wash, 25 lks. wide, 4 ft. deep, course S.  
 20.00 Wash, 55 lks. wide, 5 ft. deep, course S.  
 40.09 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

Chains.

$\frac{1}{4}$  S16  
S21  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

41.40 Wash, 12 lks. wide, 4 ft. deep, course S.

72.40 Wash, 15 lks. wide, 4 ft. deep, course S.

80.18 The cor. of secs. 16, 17, 20 and 21.

Land, gently rolling.

Soil, 2nd and 3rd rates.

Timber, scattering palo verde and mesquite.

Undergrowth, cat claw, sagebrush, ocotillo and greasewood.

40.00

N.0° 2' W., bet. secs. 16 and 17.

Over gently rolling land, through scattering timber and undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
S17 | S16  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

66.20 Road, brs. NE. and SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on brass cap

T6N | R3W  
S 8 | S 9  
S17 | S16  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, gently rolling.

Soil, 2nd rate.

Timber, scattering palo verde.

Undergrowth, cat claw.

40.00

N.89° 59' E., on a random line, bet. secs. 9 and 16.

Set temp.  $\frac{1}{4}$  sec. cor.

80.25

Intersect N. and S. line, 2 lks. N. of the cor. of secs. 9, 10, 15 and 16.

thence

West on a true line, bet. secs. 9 and 16.

Over gently rolling land, through scattering timber and undergrowth.

8.25

Wash, 90 lks. wide, 10 ft. deep, course S.

17.05

Old road, brs. NE. and SW.

21.25

Wash, 150 lks. wide, 10 ft. deep, course SW.

30.25

Wash, 90 lks. wide, 2 ft. deep, course SW.

40.12 $\frac{1}{2}$

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S 9  
S16  
1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.


Subdivision of T. 6 N., R. 3 W.

Chains.  
80.25

The cor. of secs. 8, 9, 16 and 17.  
Land, gently rolling.  
Soil, 2nd and 3rd rates.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

40.00

N.0° 2' W., bet. secs. 8 and 9.  
Over gently rolling land, through scattering timber and undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

70.00

Leave gently rolling land. Asc. 110 ft. to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, in a mound of stone, for cor. of secs. 4, 5, 8 and 9, marked on brass cap



And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, gently rolling and hilly.  
Soil, 3rd and 4th rates.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

40.00

East on a random line, bet. secs. 4 and 9.  
Set temp.  $\frac{1}{4}$  sec. cor.

80.32

Intersect N. and S. line, 30 lks. N. of the cor. of secs. 3, 4, 9 and 10.

Thence

N.89° 47' W., on a true line, bet. secs. 4 and 9.  
Over gently rolling land, through scattering timber and undergrowth.

1.00


Wash, 2 chs. wide, 2 ft. deep, course S.

40.10

Wash, 6 lks. wide, 1 ft. deep, course S.

40.16

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

60.00

Leave gently rolling land; asc. 170 ft. to


72.18

Ridge, brs. NW. and SE. Desc. 65 ft. to

80.32

The cor. of secs. 4, 5, 8 and 9.  
Land, gently rolling and hilly.  
Soil, 3rd and 4th rates.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

Chains. N.0° 2' W., on a random line, bet. secs. 4 and 5.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 81.00 Intersect N. bdy. of Tp., at the cor. of secs. 4, 5, 32 and 33, which is an iron post, hereinbefore described, Thence  
 S.0° 2' E., on a true line, bet. secs. 4 and 5.  
 Over rolling land, through scattering timber and undergrowth.  
 21.10 Asc. to  
 23.70 Desc. 75 ft.  
 29.91 Telephone line, brs. NE. and SW.  
 30.20 Road, brs. NE. and SW.  
 31.00 Foot of descent; thence over rolling land.  
 33.30 From this point, tent house of Orion Group Mine, brs. W. 3 chs. dist.  
 41.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap




And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

47.00 Asc. 90 ft. to  
 60.25 Desc. 30 ft. to  
 60.80 Asc. 100 ft. to  
 73.60 Spur, slopes NW. Desc. 200 ft. to  
 81.00 The cor. of secs. 4, 5, 8 and 9.  
 Land, rolling and hilly.  
 Soil, 3rd and 4th rates.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw


From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., which is an iron post, described in Book "G", N.0° 3' W., bet. secs. 31 and 32.  
 Over gently rolling land, through scattering timber and undergrowth.

6.20 Road, brs. NW. to Morrystown and SE. to Phoenix,  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, marked on brass cap



Dig pits, 18 X 18 X 12 ins., in each sec.,  $5\frac{1}{2}$  ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, Land, gently rolling.  
 Soil, 2nd rate.  
 Timber, scattering mesquite and palo verde.  
 Undergrowth, cat claw, sagebrush, and greasewood.

Subdivision of T. 6 N., R. 3 W.

2.

Chains.	
40.00	N. 89° 59' E., on a random line, bet. secs. 29 and 32.
80.01	Set temp. $\frac{1}{4}$ sec. cor.
	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 28, 29, 32 and 33.
	Thence
	West on a true line, bet. secs. 29 and 32.
	Over level land, through scattering timber and undergrowth.
15.00	Telephone and Telegraph Line, brs. N. 47° W and S. 47° E.
15.65	S. F., P. & P. Ry., brs. N. 47° 2' W. and S. 47° 2' E.
19.50	Road, brs. NW. and SE.
20.00 $\frac{1}{2}$	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{r} \frac{1}{4} S29 \\ \hline S32 \\ 1916 \end{array}$
	And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
40.00	Wash, 45 lks. wide, 4 ft. deep, course S.
63.50	Wash, 90 lks. wide, 3 ft. deep, course SW.
80.01	The cor. of secs. 29, 30, 31 and 32.
	Land, level.
	Soil, 1st and 2nd rates.
	Timber, scattering palo verde.
	Undergrowth, cat claw.
40.00	S. 89° 59' W., on a random line, bet. secs. 30 and 31.
79.77	Set temp. $\frac{1}{4}$ sec. cor.
	Intersect W. bdy. of Tp., 2 lks. N. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, described in Book "F".
	Thence
	N. 89° 58' E., on a true line, bet. secs. 30 and 31.
	Over level land, through scattering timber and undergrowth.
32.50	Road, brs. NW. and SE.
39.77	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{r} \frac{1}{4} S30 \\ \hline S31 \\ 1916 \end{array}$
	And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
79.77	The cor. of secs. 29, 30, 31 and 32.
	Land, level.
	Soil, 2nd rate.
	Timber, scattering palo verde.
	Undergrowth, cat claw.
40.00	N. 0° 3' W., bet. secs. 29 and 30.
	Over level land, through scattering timber and undergrowth.
	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{r} \frac{1}{4} \\ S30   S29 \\ \hline 1916 \end{array}$
59.30	Dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Road, brs. N. 47° W. to Morrystown and S. 47° E. to Phoenix.

<p>Chains. 60.03 60.83 80.00</p>	<p>S. F., P. &amp; P. Ry., brs. N.47° W. and S.47° E. Telephone and telegraph line, brs. N.47° W. and S.47° E. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap</p> <p style="text-align: center;"> <table border="1"> <tr><td>T6N</td><td>R3W</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td>S30</td><td>S29</td></tr> </table>  1916                 </p> <p>Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, level. Soil, 2nd rate. Timber, scattering mesquite and palo verde. Undergrowth, cat claw, sagebrush and greasewood.</p>	T6N	R3W	S19	S20	S30	S29
T6N	R3W						
S19	S20						
S30	S29						
<p>40.00 80.06</p>	<p>East on a random line, bet. secs. 20 and 29. Set temp. ¼ sec. cor. Intersect N. and S. line, 4 lks. S. of the cor. of secs. 20, 21, 28 and 29. Thence S.89° 58' W., on a true line, bet. secs. 20 and 29. Over gently rolling land, through scattering timber and undergrowth.</p>						
<p>7.95 11.45 32.65 40.03</p>	<p>Wash, 20 lks. wide, 4 ft. deep, course SW. Wash, 25 lks. wide, 5 ft. deep, course S. Wash, 15 lks. wide, 3 ft. deep, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap</p> <p style="text-align: center;"> <table border="1"> <tr><td>1</td><td>S20</td></tr> <tr><td>4</td><td>S29</td></tr> </table>  1916                 </p> <p>And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p>	1	S20	4	S29		
1	S20						
4	S29						
<p>62.65 80.06</p>	<p>Wash, 50 lks wide, 3 ft. deep, course S. The cor. of secs. 19, 20, 29 and 30. Land, gently rolling. Soil, 2nd and 3rd rates. Timber, scattering palo verde and mesquite. Undergrowth, cat claw, sagebrush and greasewood.</p>						
<p>40.00 79.66</p>	<p>S.89° 58' W., on a random line, bet. secs. 19 and 30. Set temp. ¼ sec. cor. Intersect W. bdy. of Tp., 2 lks. S. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, described in Book "P". Thence N.89° 59' E., on a true line, bet. secs. 19 and 30. Over gently rolling land, through scattering timber and undergrowth.</p>						
<p>1.20 10.20 39.66</p>	<p>Road, brs. N.10° W. to Morrystown and S.10° E. to Phoenix. Dim road, brs. N. and S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap</p> <p style="text-align: center;"> <table border="1"> <tr><td>1</td><td>S19</td></tr> <tr><td>4</td><td>S30</td></tr> </table>  1916                 </p> <p>Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft.</p>	1	S19	4	S30		
1	S19						
4	S30						




Subdivision of T. 6 N., R. 3 W.

Chains.

high, N. of cor.  
 55.80 Road, brs. NW and SE.  
 56.90 Wash, 25 lks. wide, 4 ft. deep, course S.  
 58.30 S. F., P. & P. Ry., brs. N.47° W. and S.47° E.  
 59.20 Telephone and telegraph line, brs. N.47° W. and S.47° E.  
 79.66 The cor. of secs. 19, 20, 29 and 30.  
 Land, gently rolling.  
 Soil, 2nd rate.  
 Timber, scattering mesquite and paloverde.  
 Undergrowth, cat claw, sagebrush, cactus and greasewood.

N.0° 3' W., bet. secs. 19 and 20.  
 Over gently rolling land, through scattering timber and undergrowth.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins.,  $\frac{1}{4}$  W. and S. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft high, W. of cor.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on brass cap




Dig pits, 18 X 18 X 12 ins., in each sec.,  $5\frac{1}{2}$  ft. dist. and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.  
 Land, gently rolling.  
 Soil, 2nd rate  
 Timber, scattering mesquite and palo verde.  
 Undergrowth, cat claw, sagebrush, cactus and greasewood.

N.89° 58' E., on a random line, bet secs. 17 and 20.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.03 Intersect N. and S. line, 2 lks. N. of the cor. of secs 16, 17, 20 and 21.  
 Thence

S.89° 59' W., on a true line, bet. secs. 17 and 20.  
 Over gently rolling land, through scattering timber and undergrowth.

23.30 Wash, 30 lks. wide, 4 ft. deep, course S.  
 40.01 $\frac{1}{2}$  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise amount of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 49.60 Wash, 55 lks. wide, 4 ft. deep, course S.  
 62.00 Wash, 20 lks. wide, 4 ft. deep, course S.  
 80.03 The cor. of secs. 17, 18, 19 and 20.  
 Land, gently rolling.  
 Soil, 2nd and 3rd rates.  
 Timber, scattering mesquite and palo verde.

Chains.

Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood.

40.00 S.89° 59' W., on a random line, bet. secs. 18 and 19.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.52 Intersect. W. bdy. of Tp., 5 lks. S. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, described in Book "F".  
 Thence  
 S.89° 59' E., on a true line, bet. secs. 18 and 19.  
 Over gently rolling land, through scattering timber and undergrowth.  
 0.80 Telephone line, brs. NE. and SW.  
 2.30 Road, brs. NE. to Hot Springs and SW. to Morrystown.  
 18.30 Wash, 25 lks. wide, 2 ft. deep, course S.  
 39.52 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S18  
 S19  
 1916

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 60.60 Wash, 15 lks. wide, 2 ft. deep, course S.  
 60.80 Dim road, brs. NE. and SW.  
 72.30 Wash, 20 lks. wide, 4 ft. deep, course SW.  
 79.52 The cor. of secs. 17, 18, 19 and 20.  
 Land, gently rolling.  
 Soil, 2nd rate.  
 Timber, scattering mesquite and palo verde.  
 Undergrowth, cat claw, sagebrush, cactus and greasewood.

N.0° 3' W., bet. secs. 17 and 18.  
 Over gently rolling land, through scattering timber and undergrowth.  
 5.00 Wash, 15 lks. wide, 3 ft. deep, course SW.  
 6.60 Dim road, brs. NE. and SW.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$   
 S18 | S17  
 1916

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 78.80 Telephone line, brs. N. 60° E. and S. 60° W.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18 marked on brass cap

T6N | R3W  
 S 7 | S 8  
 S18 | S17  
 1916

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Land, gently rolling.  
 Soil, 3rd and 4th rates.  
 Timber, scattering palo verde and mesquite.  
 Undergrowth, cat claw, sagebrush, cactus and greasewood.

Subdivision of T. 6 N., R. 3 W.

33.

Chains.

40.00 N.89° 59' E., on a random line, bet. secs. 8 and 17.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.03 Intersect N. and S. line, 5 lks. S. of the cor. of secs.  
 8, 9, 16 and 17.

Thence

S.89° 57' W., on a true line, bet. secs. 8 and 17.  
 Over gently rolling land, through scattering timber and  
 undergrowth.

35.50 Wash, 90 lks. wide, 4 ft. deep, course S.

40.01 $\frac{1}{2}$  Set an iron post,  $\frac{3}{4}$  ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 8  
 $\frac{1}{4}$  S17  
 1916

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N.  
 of cor.

78.00 Telephone line, brs. NE. and SW.

80.03 The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling.  
 Soil, 2nd and 3rd rates.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw.

40.00 N.89° 59' W., on a random line, bet. secs. 7 and 18.  
 Set temp.  $\frac{1}{4}$  sec. cor.

79.56 Intersect W. bdy. of Tp., 5 lks. S. of the cor. of secs.  
 7, 12, 13 and 18, which is an iron post, described in  
 Book "F".

Thence

S.89° 57' E., on a true line, bet. secs. 7 and 18.  
 Over rolling land, through scattering timber and undergrowth.

36.55 Wash, 60 lks. wide, 10 ft. deep, course SW.

39.56 Set an iron post,  $\frac{3}{4}$  ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S 7  
 S18  
 1916

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N.  
 of cor.

44.25 Wash, 90 lks. wide, 10 ft. deep, course S.

63.60 Road, brs. NE. to Castle Hot Springs and SW. to Morristown.

79.56 The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling and rolling.  
 Soil, 2nd and 3rd rates.  
 Timber, scattering palo verde.  
 Undergrowth, cat claw.

N.0° 3' W., bet. secs. 7 and 8.

Over gently rolling land, through scattering timber and  
 undergrowth.

23.90 Road, brs. NE. to Castle Hot Springs and SW. to Morristown.

26.40 Wash, 20 lks. wide, 4 ft. deep, course W.

34.40 Wash, 40 lks. wide, 4 ft. deep, course SW.

40.00 Set an iron post,  $\frac{3}{4}$  ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

S 7  $\frac{1}{4}$  S 8  
 1916

34.

Subdivision of T. 6 N., R. 3 W.

Chains.

80.00 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, marked on brass cap

T6N	R3W
S 6	S 5
S 7	S 8
1916	

And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
Land, gently rolling.  
Soil, rocky; 3rd rate.  
Timber, scattering palo verde and mesquite.  
Undergrowth, cat claw, sagebrush, cactus and greasewood.

40.00 N.  $89^{\circ} 57'$  E., on a random line, bet. secs. 5 and 8.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.12 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 4, 5, 8 and 9.  
Thence  
S.  $89^{\circ} 59'$  W., on a true line, bet. secs. 5 and 8.  
Over hilly land, through scattering timber and undergrowth.  
Desc. 70 ft. to  
14.94 Foot of descent; thence over gently rolling land.  
40.06 Set an iron post, 3 ft. long, 1 in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$ S 5
S 8
1916

40.76 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
Telephone line, brs. NE. to Castle Hot Springs and SW. to Morristown.  
42.20 Road, brs. NE. to Castle Hot Springs and SW. to Morristown.  
80.12 The cor. of secs. 5, 6, 7 and 8.  
Land, gently rolling and hilly.  
Soil, 3rd rate.  
Timber, scattering palo verde.  
Undergrowth, cat claw.

40.00 N.  $89^{\circ} 57'$  W., on a random line, bet. secs. 6 and 7.  
Set temp.  $\frac{1}{2}$  sec. cor.  
79.42 Intersect W. bdy. of Tp., 5 lks. N. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, described in Book "B".  
Thence  
S.  $89^{\circ} 59'$  E., on a true line, bet. secs. 6 and 7.  
Over gently rolling land, through scattering timber and undergrowth.  
39.42 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$ S 6
S 7
1916

50.00 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
Asc. 60 ft. to  
56.00 Spur, slopes S. Desc. 25 ft. to  
59.45 Wash, 15 lks. wide, 4 ft. deep, course S. Asc. 40 ft. to

Subdivision of T. 6 N., R. 3 W.

Chains.

66.20 Spur, slopes S. Desc. 30 ft.  
 69.70 Telephone line, brs. NE. and SW.  
 71.90 Wash, 10 lks. wide, 4 ft. deep, course S. Thence over rolling land.  
 79.42 The cor. of secs. 5, 6, 7 and 8.  
 Land, gently rolling, rolling and hilly.  
 Soil, 3rd rate.  
 Timber, scattering palo verde and mesquite.  
 Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood.

40.00 N.0° 3' W., on a random line, bet. secs. 5 and 6.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 81.19 Intersect N. bdy. of Tp., 33 lks. W. of the cor. of secs. 5, 6, 31 and 32, which is an iron post, hereinbefore described.  
 Thence  
 S.0° 11' W., on a true line, bet. secs. 5 and 6.  
 Over rolling land, through scattering timber and undergrowth.  
 3.20 Wash, 15 lks. wide, 3 ft. deep, course W. Asc. 80 ft.  
 11.20 Center of brush corral.  
 16.20 Ridge, brs. E. and W. Desc. 45 ft. to  
 41.19 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 81.19 The cor. of secs. 5, 6, 7 and 8.  
 Land, rolling, hilly and gently rolling.  
 Soil, 3rd rate.  
 Timber, scattering mesquite and palo verde.  
 Undergrowth, cat claw, sagebrush, ocotillo, cactus and greasewood.

General Description.

This township, with the exception of the northwest cor., which is broken and hilly, consists of level and gently rolling land, covered with mesquite and palo verde timber, and greasewood, sagebrush, cat claw and cactus undergrowth. The soil on the slopes may be classed as 3rd and 4th rates, but on the plains, it is 1st or 2nd rate, of good texture. Lack of water makes it valuable for grazing purposes only.  
 There are no settlers. The S. F., P & P. Ry. passes through the south west quarter of the township in a northwesterly direction.

FOR CERTIFICATES OF U. S. SURVEYOR & U. S. TRANSITMAN, SEE BOOK "A".  
~~FINAL OATH OF UNITED STATES SURVEYOR.~~

BOOK 3112

I, \_\_\_\_\_, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for \_\_\_\_\_ bearing date of the \_\_\_\_\_ day of \_\_\_\_\_, 191 \_\_\_\_\_, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of \_\_\_\_\_

\_\_\_\_\_ of the \_\_\_\_\_ Meridian, in the State of \_\_\_\_\_, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for \_\_\_\_\_ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

\_\_\_\_\_  
U. S. Surveyor.

Subscribed by said \_\_\_\_\_, and sworn to before me }  
this \_\_\_\_\_ day of \_\_\_\_\_, 191 \_\_\_\_\_ }



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Ariz. JUN 28 1918, 191 \_\_\_\_\_

The foregoing field notes of the survey of \_\_\_\_\_ the \_\_\_\_\_

East and North Boundaries

and

Subdivisional lines

of

TOWNSHIP 6 NORTH, RANGE 3 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, executed by Roy J. Gill, U. S. Surveyor and Hans D. Voigt, U. S. Transitman, under his special instructions dated Sept. 24, 1915, for Group 59, Arizona, 191 \_\_\_\_\_, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

*[Signature]*  
U. S. Surveyor General.

~~I certify that the foregoing transcript of the field notes of the above described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.~~