

3113

Gen. L. O. Letter "E"
March 29, 1919. 369

Book "I"

4-679

JAN 7 1918

1

BOOK 3113

FIELD NOTES

OF THE SURVEY OF THE

East and North Boundaries, and

Subdivision Lines

of

TOWNSHIP 5 NORTH, RANGE 6 WEST,

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

Roy J. Gill, U. S. Surveyor,

and

Hans D. Voigt, U. S. Transitman,

~~In the capacity of U. S. Surveyor~~, under instructions dated September 24., 1915,
issued by the United States Surveyor General to govern surveys included in
Group No. 59, which were approved by the Commissioner of the General Land
Office, October 8., 1915.

Survey commenced February 12., 1916.

Survey completed February 19., 1916.

6-151

Executed under Assignment
Instructions dated November 26, 1915.

3113

3113

1A

3113

Book "I"

Group 59 - - - - Arizona.

BOOK 3113

INDEX DIAGRAM.

Township 5 North, Range 6 West.											
6		6		7		7		7		8	
6	35	5	28	4	24	3	19	2	14	1	4
35		34		28		23		19		14	
7	34	8	28	9	23	10	18	11	13	12	4
33		33		27		23		18		13	
18	33	17	27	16	22	15	17	14	12	13	3
32		32		26		22		17		12	
19	31	20	26	21	21	22	16	23	12	24	3
31		31		25		21		16		11	
30	30	29	25	28	20	27	15	26	11	25	2
30		29		25		20		15		10	
31	29	32	24	33	19	34	15	35	10	36	2

First Standard Parallel North.

———— Surveyed under this Group. Notes in this Book.

———— Surveyed or resurveyed under this Group.

———— Resurveyed under Group. 39.

Book "I".
 Group 59, Arizona.
 Township 5 North, Range 6 West.

DATE DIAGRAM.

	2-14-16	2-14-16	2-14-16	2-14-16	2-14-16	2-14-16	
2-14-16	6	5	4	3	2	1	2-14-16
2-17-16	2-17-16	2-17-16	2-17-16	2-17-16	2-16-16	2-16-16	2-17-16
2-14-16	7	8	9	10	11	12	2-14-16
2-17-16	2-17-16	2-17-16	2-17-16	2-16-16	2-15-16	2-15-16	2-17-16
2-14-16	13	17	16	15	14	13	2-14-16
2-17-16	2-17-16	2-17-16	2-16-16	2-16-16	2-15-16	2-15-16	2-17-16
2-14-16	19	20	21	22	23	24	2-14-16
2-19-16	2-17-16	2-16-16	2-16-16	2-15-16	2-15-16	2-12-16	2-19-16
2-14-16	29	29	28	27	26	25	2-14-16
2-16-16	2-16-16	2-16-16	2-15-16	2-15-16	2-12-16	2-12-16	2-16-16
2-14-16	31	32	33	34	35	36	2-14-16
2-16-16	2-16-16	2-15-16	2-15-16	2-12-16	2-12-16	2-12-16	2-16-16

Lines dated in blue were surveyed by Roy J. Gill,
U. S. Surveyor.

Lines dated in red were surveyed by Hans D. Voigt,
U. S. Transitman.

Chains

Survey commenced and executed with Buff and Buff light mountain solar transit No. 7732, with Smith solar attachment. The horizontal limb is provided with two double verniers, placed opposite to each other, reading to single minutes of arc, which is also the least count of the verniers of the latitude and declination arcs. This instrument was examined, tested on the true meridian at Phoenix, Arizona, found correct, and was approved, conditional upon satisfactory field tests, by the Assistant Supervisor of Surveys for Arizona and California, November 26, 1915.

In this, and the following surveys of this group, a clinometer and 5-ch tape were used, slope angles read on sloping ground and the correct horizontal distance computed for each item of topography.

Knowing from recent and repeated tests of this instrument on a meridian determined by a series of direct observations on the sun for azimuth, as described in current Group 39, that it is in adjustment, I proceed to the survey of the E. bdy. of T. 5 N., R. 6 W.

From the standard cor. of Ts. 5 N., Rs. 5 and 6 W., which is an iron post, described in the field notes of current Group No. 39.

North bet. secs. 31 and 36.

40.00

Over level land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

1
S36 | S31
1916

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, marked on brass cap

T5N
R6W | R5W
S25 | S30
S36 | S31
1916

Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level.

Soil, 2nd rate.

Timber, scattering palo verde.

Undergrowth, cat claw.

North bet. secs. 25 and 30.

40.00

Over level land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

1
S25 | S30
1916

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the

East Boundary of T. 5 N., R. 6 W.

Chains.

ground, for cor. of secs. 19, 24, 25 and 30, marked on brass cap



Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level.
Soil, 1st and 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00

North bet. secs. 19 and 24.
Over level land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, marked on brass cap




Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level.
Soil, 1st and 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00

North bet. secs. 13 and 18.
Over level land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, marked on brass cap

4. East Boundary of T. 5 N., R. 6 W.

Chains.

T5N
 R6W | R5W
 S12 | S 7
 S13 | S18
 1916

Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, level.
 Soil, 1st and 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

10.00 North bet. secs. 7 and 12.
 40.00 Over level and gently rolling land, through scattering timber and undergrowth.
 Road, brs. NW. and SE.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S12 | S 7
 1916

80.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, marked on brass cap

T5N
 R6W | R5W
 S 1 | S 6
 S12 | S 7
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, level and gently rolling.
 Soil, 1st and 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00 North bet. secs. 1 and 6.
 Over level land, through scattering timber and undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 1 | S 6
 1916

60.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 77.00 Draw, 75 lks. wide, 10 ft. deep, course E.
 80.00 Draw, 75 lks. wide, 10 ft. deep, course SE.
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of Ts. 5 and 6 N., Rs. 5 and 6 W., marked on brass cap

East Boundary of T. 5 N., R. 6 W.

Chains.

T6N	
R6W	R5W
S36	S31
S 1	S 6
T5N	
1916	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, level.
 Soil, 1st and 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

6. North Boundary of T. 5 N., R. 6 W.

Chains.

From the cor. of Ts. 5 and 6 N., Rs. 5 and 6 W., here-
inbefore described,
West on a random line, along the N. bdy. of T. 5 N., R. 6
W., setting temp. $\frac{1}{4}$ sec. and sec. cors. at intervals
of 40.00 chs.; and at 479.13 chs., intersect W. bdy.
of T. 5 N., R. 6 W., 9 lks. S. of the cor. of Ts. 5 and
6 N., Rs. 6 and 7 W., which is an iron post, described
in Book "B". The falling answers to a correction of
 $0^{\circ} 1'$, or 1 lk. N. per mile, counting from the NE. cor.
of the Tp.; therefore

S. $89^{\circ} 59'$ E., on a true line, bet. secs. 31 and 6.
Over level land, through scattering timber and under-
growth.

39.13 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \text{ S31} \\ \hline \text{S 6} \\ 1916 \end{array}$$

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of cor.

79.13 Set an iron post, 3 ft. long, 3 ins. diam., 18 ins. in the
ground, in a mound of stone, for cor. of secs. 5, 6, 31
and 32, marked on brass cap

$$\begin{array}{r} \text{T6N R6W} \\ \text{S31 | S32} \\ \hline \text{S 6 | S 5} \\ \text{T5N} \\ 1916 \end{array}$$

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.

Land, level.
Soil, 2nd and 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

S. $89^{\circ} 59'$ E., on a true line, bet. secs. 5 and 32.
Over gently rolling land, through scattering timber and
undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\begin{array}{r} \frac{1}{4} \text{ S32} \\ \hline \text{S 5} \\ 1916 \end{array}$$

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

59.50 Road, brs. NW 80° W. and S. 80° E.
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
ground, for cor. of secs. 4, 5, 32 and 33, marked on
brass cap

$$\begin{array}{r} \text{T6N | R6W} \\ \text{S32 | S33} \\ \hline \text{S 5 | S 4} \\ \text{T5N} \\ 1916 \end{array}$$


And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.

Land, gently rolling.
Soil, 2nd rate.
Timber, scattering plao verde.
Undergrowth, cat claw.

North Boundary of T. 5 N., R. 6 W.

Chains.

S.89° 59' E., on a true line, bet. secs. 4 and 33.
 Over gently rolling land, through scattering timber and undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 72.05 Road, brs. N. and S.
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 33 and 34, marked on brass cap




And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, gently rolling.
 Soil, 2nd and 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

S.89° 59' E., on a true line, bet. secs. 3 and 34.
 Over gently rolling land, through scattering timber and undergrowth.
 29.55 Road, brs. N. and S.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 34, 35, 2 and 3, marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, gently rolling.
 Soil, 2nd and 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

S.89° 59' E., on a true line, bet. secs. 2 and 35.
 Over gently rolling land, through scattering timber and undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

8. North Boundary of T. 5 N., R. 6 W.

Chains.

$\frac{1}{4}$ S35
S 2
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

79.55 From this point, U. S. L. M. No. 2511 brs. N.48° 18' E.
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, marked on brass cap

T6N R6W
S 35 S36
S 2 S 1
T5N
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.
Soil, 2nd and 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

S.89° 59' E., on a true line, bet. secs. 1 and 36.
Over gently rolling land, through scattering timber and undergrowth.

15.15 Road, brs. NE. and SW.
31.80 From this point, marble headstone of Francisca Valencia, in a graveyard of about 60 graves, brs. N. 2 chs. dist.
38.00 Road, brs. NE. and SW.
39.55 From this point, U. S. L. M. No. 2511 brs. N.23° 50' E. NW. cor. No. 4 Sanders Mining Claim, brs. N.32° W. SE. cor. Henry M. Love Mining Claim brs. N.17° 48' E.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S36
S 1
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

43.05 Road, brs. N. and S.
61.50 Draw, 75 lks. wide, 10 ft. deep, course SE.
67.55 Road, brs. NW. and SE.
69.55 Draw, 75 lks. wide, 10 ft. deep, course SE.
71.80 From this point, U. S. L. M. No. 2511 brs. N.6° 6' W. NW. cor. No. 4 Sanders Mining Claim brs. N.54° 32' W. SE. cor. Henry M. Love Mining Claim brs. N.55° 58' W. SE. cor. No. 2 Pit Gold Mining Claim Survey No. 2522 brs. N.35° 5' W., 9.55 chs. dist.
80.00 The cor. of Ts. 5 and 6 N., Rs. 5 and 6 W.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

T. 5 N., R. 6 W.

9.

Boundaries of T. 5 N., R. 6 W.
 Latitudes, departures and closing errors.

Line designated.	True bearing.	Dist. chs.	Latitudes.		Departures.	
			N. chs.	S. chs.	E. chs.	W. chs.
South Boundary. 1st. St. Par. N.	West.	480.00				480.00
West Boundary.	North.	480.00	480.00			
North Boundary.	S. 89° 59' E.	479.13		.09	479.13	
East Boundary.	South.	480.00		480.00		
Convergency					.49	
Totals			480.00	480.09	479.62	480.00
				480.00		479.62
Error in latitude				.09		
Error in departure						.38

10.

Subdivision of T. 5 N., R. 6 W.

Chains.

Survey commenced and executed with Buff and Buff light mountain transit No. 7732, and Young and Sons' light mountain transit No. 8293, each instrument being equipped with Smith solar attachment. For description of instrument No. 7732, see hereinbefore. This description is also applicable to instrument No. 8293.

Instrument No. 8293 was examined, tested on the true meridian at Phoenix, Arizona, found correct, and was approved, conditional upon satisfactory field tests, by the Assistant Supervisor of Surveys for Arizona and California, November 26 1915.

Knowing from recent and repeated tests of instrument No. 8293 on a meridian determined by a series of direct observations on the sun for azimuth, that it is in adjustment, I proceed to the survey of the subdivisions of T. 5 N., R. 6 W.

From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., which is an iron post, described in the field notes of current group No. 39,

N.0° 1' W., bet. secs. 35 and 36.


Over gently rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on brass cap



Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.

Soil, 2nd rate.

Timber, palo verde.

Undergrowth, cat claw, mesquite, sagebrush and greasewood.

40.00 East on a random line, bet. secs. 25 and 36.

Set temp. $\frac{1}{4}$ sec. cor.


80.00 Intersect E. bdy. of Tp., 1 lk. S. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, hereinbefore described.

Thence

West on a true line, bet. secs. 25 and 36.

Over gently rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Subdivision of T. 5 N., R. 6 W.

11.

chains.
80.00

The cor. of secs. 25, 26, 35 and 36.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00

N.0° 1' W., bet. secs. 25 and 26.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



80.00

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, marked on brass cap




Dig pits, 18 X 18 X 12 ins., in each sec., 5 1/2 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, sagebrush, cat claw and greasewood.

40.00
79.94

East on a random line, bet. secs. 24 and 25.
Set temp. 1/4 sec. cor.
Intersect E. bdy. of Tp., 8 lks. S. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, hereinbefore described.

39.97

Thence
S.89° 57' W., on a true line, bet. secs. 24 and 25.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



79.94

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.
The cor. of secs. 23, 24, 25 and 26.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw, sagebrush, mesquite and greasewood.

12.

Subdivision of T. 5 N., R. 6 W.

Chains.	
40.00	<p>N.0° 1' W., bet. secs. 23 and 24. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p>
80.00	<p style="text-align: center;"> $\frac{1}{4}$ S23 S24 1916 </p> <p>Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked on brass cap</p> <p style="text-align: center;"> T5N R6W S14 S13 S23 S24 1916 </p> <p>Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, gently rolling. Soil, 1st and 2nd rate. Timber, scattering palo verde. Undergrowth, cat claw.</p>
40.00	<p>N.89° 57' E., on a random line, bet. secs. 13 and 24. Set temp. $\frac{1}{4}$ sec. cor.</p>
80.00	<p>Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, described hereinbefore. Thence</p>
40.00	<p>West on a true line, bet. secs. 13 and 24. Over level land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\frac{1}{4}$ S13 S24 1916 </p>
80.00	<p>Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor. The cor. of secs. 13, 14, 23 and 24. Land, level. Soil, 1st and 2nd rate. Timber, scattering palo verde. Undergrowth, cat claw.</p>
40.00	<p>N.0° 1' W., bet. secs. 13 and 14. Over level land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\frac{1}{4}$ S14 S13 1916 </p> <p>Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.</p>

Subdivision of T. 5 N., R. 6 W.

13.

Chains.

80.00 dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked on brass cap

T5N R6W
 S11|S12
 S14|S13
 1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.
 Land, level.
 Soil, sandy, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00 East on a random line, bet. secs. 12 and 13.
 80.00 Set temp. ¼ sec. cor.
 80.00 Intersect E. bdy. of Tp., 8 lks. S. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, hereinbefore described.

Thence
 S. 89° 57' W., on a true line, bet. secs. 12 and 13.
 Over level land, through scattering undergrowth.

1.00 Wash, 20 lks. wide, course S.
 39.50 Wash, 45 lks. wide, course S.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

1/4 S12
 1/4 S13
 1916

80.00 And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 80.00 The cor. of secs. 11, 12, 13 and 14.
 Land, level.
 Soil, sandy and gravelly; 2nd rate.
 No timber.
 Undergrowth, cat claw.

40.00 N. 0° 1' W., bet. secs. 11 and 12.
 Over level and gently rolling land, through scattering timber and undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

1/4
 S11 | S12
 1916

79.35 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
 80.00 Road, brs. NE. and SW.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, marked on brass cap

T5N R6W
 S 2 | S 1
 S11 | S12
 1916

14.

Subdivision of T. 5 N., R. 6 W.

Chains.

	<p>And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, level and gently rolling. Soil, 2nd and 3rd rate. Timber, scattering palo verde. Undergrowth, cat claw.</p>
40.00 79.97	<p>N. $89^{\circ} 57'$ E., on a random line, bet. secs. 1 and 12. Set temp. $\frac{1}{4}$ sec. cor. Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, hereinbefore described. Thence West on a true line, bet. secs. 1 and 12. Over gently rolling land, through scattering timber and undergrowth. Asc. 30 ft. to Desc. 35 ft. to Road, brs. NW. and SE. Thence over level land. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\frac{1}{4}$ S 1 S 12 1916 </p> <p>Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p>
5.00 12;00 39.98 $\frac{1}{2}$	<p>Road, brs. NE. and SW. The cor. of secs. 1, 2, 11 and 12. Land, gently rolling and level. Soil, 2nd rate. Timber, scattering palo verde. Undergrowth, cat claw.</p>
79.65 79.97	<p>N. $0^{\circ} 1'$ W., on a random line, bet. secs. 1 and 2. Set temp. $\frac{1}{4}$ sec. cor. Intersect N. bdy. of Tp., 3 lks. E. of the cor. of secs. 1, 2, 35 and 36, which is an iron post, hereinbefore described. Thence S. $0^{\circ} 2'$ E., on a true line, bet. secs. 1 and 2. Over gently rolling land, through scattering timber and undergrowth. Road, brs. NE. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;"> $\frac{1}{4}$ S 2 S 1 1916 </p> <p>Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p>
17.50 39.99	<p>Asc. 30 ft. to Top of small hill. Desc. 40 ft. to Thence over level land, The cor. of secs. 1, 2, 11 and 12. Land, gently rolling. Soil, 3rd rate. Timber, scattering palo verde. Undergrowth, cat claw.</p>
60.00 65.00 70.00 79.99	<p>Asc. 30 ft. to Top of small hill. Desc. 40 ft. to Thence over level land, The cor. of secs. 1, 2, 11 and 12. Land, gently rolling. Soil, 3rd rate. Timber, scattering palo verde. Undergrowth, cat claw.</p>

Subdivision of T. 5 N., R. 6 W.

chains.

From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., which is an iron post, described in the field notes of current Group No. 39, N.0° 1' W., bet. secs. 34 and 35. Over gently rolling land, through scattering timber and undergrowth.

25.00
40.00

Draw, 20 lks. wide, course E.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



80.00

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked on brass cap



Dig pits, 18 X 18 X 12 ins., in each sec., 5 1/2 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, greasewood and sagebrush.

40.00
80.01

East on a random line, bet. secs. 26 and 35.
Set temp. 1/4 sec. cor.
Intersect N. and S. line, 2 lks. S. of the cor. of secs. 25, 26, 35 and 36.

Thence S.89° 59' W., on a true line, bet. secs. 26 and 35. Over gently rolling land, through scattering timber and undergrowth.

40.00 1/2

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap



80.01

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

The cor. of secs. 26, 27, 34 and 35.
Land, gently rolling.
Soil, 2nd rate; gumbo subsoil.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00

N.0° 1' W., bet. secs. 26 and 27. Over level land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

16. Subdivision of T. 5 N., R. 6 W.

Chains.

$$\begin{array}{c} \frac{1}{4} \\ \hline S27 | S26 \\ \hline 1916 \end{array}$$

80.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap

$$\begin{array}{c} T5N R6W \\ \hline S22 | S23 \\ \hline S27 | S26 \\ \hline 1916 \end{array}$$

Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, level.
Soil, 1st and 2nd rate.
No timber.
Undergrowth, greasewood, mesquite, cat claw and sagebrush.

40.00 N.89° 59' E., on a random line, bet. secs. 23 and 26.
79.97 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 2 lks. N. of the cor. of secs. 23, 24, 25 and 26.
Thence
West on a true line, bet. secs. 23 and 26.
Over level land, through scattering timber and undergrowth.
39.98 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} S23 \\ \hline \frac{1}{4} S26 \\ \hline 1916 \end{array}$$

79.97 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
The cor. of secs. 22, 23, 26 and 27.
Land, level.
Soil, 1st and 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

25.00 N.0° 1' W., bet. secs. 22 and 23.
Over level land, through scattering timber and undergrowth.
40.00 Road, brs. N.10° E. and S.10° W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{2}$ sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{2} \\ \hline S22 | S23 \\ \hline 1916 \end{array}$$

80.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, marked on brass cap

Chains.

T5N R6W
 S15 | S14
 S22 | S23
 1916

Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
 Land, level.
 Soil, 2nd rate.
 Timber, palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00
79.96

East on a random line, bet. secs. 14 and 23.
 Set temp. ¼ sec. cor.
 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 13, 14, 23 and 24.

39.98

Thence
 S.89° 59' W., on a true line, bet. secs. 14 and 23.
 Over gently rolling land, through scattering timber and undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S14
 S23
 1916

59.35
79.96

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
 Road, brs. N.10° E. and S.10° W.
 The cor. of secs. 14, 15, 22 and 23.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

3.80
23.70
40.00

N.0° 1' W., bet. secs. 14 and 15.
 Over gently rolling land, through scattering timber and undergrowth.
 Road, brs. NE. and SW.
 Draw, 45 lks. wide, course SE.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼
 S15 | S14
 1916

80.00

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, marked on brass cap

T5N R6W
 S10 | S11
 S15 | S14
 1916

Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

18.

Subdivision of T. 5 N., R. 6 W.

Chains.

Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00
79.92

N.89° 59' E., on a random line, bet. secs. 11 and 14.
Set temp. 1/4 sec. cor.
Intersect N. and S. line, 5 lks. S. of the cor. of secs. 11, 12, 13 and 14.

Thence
S.89° 57' W., on a true line, bet. secs. 11 and 14.
Over gently rolling land, through scattering timber and undergrowth.

1.40
29.60
39.96

Draw, 30 lks. wide, 3 ft. deep, course SE.
Road, brs. N.10° E. and S.10° W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1 S11
4 S14
1916

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

68.20
79.92

Road, brs. N. and S.
The cor. of secs. 10, 11, 14 and 15.

Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, sagebrush and greasewood.

40.00

N.0° 1' W., bet. secs. 10 and 11.
Over rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1
S10 | S11
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

43.30
47.10
80.00

Draw, 20 lks. wide, 3 ft. deep, course SE.
Road, brs. NE. and SW.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, marked on brass cap

T5N R6W
S 3 | S 2
S10 | S11
1916

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw, mesquite, sagebrush and greasewood.

Subdivision of T. 5 N., R. 6 W.

chains.

40.00 N.89° 57' E., on a random line, bet. secs. 2 and 11.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.96 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 1, 2, 11 and 12.
 Thence
 S.89° 59' W., on a true line, bet. secs. 2 and 11.
 Over gently rolling land, through scattering timber and undergrowth.
 29.05 Road, brs. NW. and SE.
 39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 2
 $\frac{1}{4}$ S 11
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 51.05 Road, brs. N. and S.
 53.65 Road, brs. NE. and SW.
 66.95 Draw, 25 lks. wide, 2 ft. deep, course SE.
 79.96 The cor. of secs. 2, 3, 10 and 11.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.100 N.0° 1' W., on a random line, bet. secs. 2 and 3.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.02 Intersect N. bdy. of Tp., 14 lks. E. of the cor. of secs. 2, 3, 34 and 35, which is an iron post, hereinbefore described.
 Thence
 S.0° 7' E., on a true line, bet. secs. 2 and 3.
 Over rolling land, through scattering timber and undergrowth.
 40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 3 | S 2
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 80.02 The cor. of secs. 2, 3, 10 and 11.
 Land, rolling.
 Soil, 4th rate.
 Timber, palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., which is an iron post, described in the field notes of current group No. 39.
 N.0° 2' W., bet. secs. 33 and 34.
 Over level land, through scattering timber and undergrowth.
 38.00 Draw, 45 lks. wide, 3 ft. deep, course E.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap


20.

Subdivision of T. 5 N., R. 6 W.

Chains.




80.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on brass cap




Dig pits, 18 X 18 X 12 ins., in each sec., 5 $\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde and cat claw.
Undergrowth, cat claw.

40.00 East on a random line, bet. secs. 27 and 34.
Set temp. $\frac{1}{4}$ sec. cor.
79.98 Intersect N. and S. line, 6 lks. N. of the cor. of secs. 26, 27, 34 and 35.
Thence
N. 89° 57' W., on a true line, bet. secs. 27 and 34.
Over level land, through scattering timber and undergrowth.
39.40 Road, brs. N. and S.
39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



73.00 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
79.98 Road, brs. N. and S.
The cor. of secs. 27, 28, 33 and 34.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N. 0° 2' W., bet. secs. 27 and 28.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



80.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on brass cap

Chains.

T5N R6W
 S21|S22
 S28|S27
 1916

Dig pits, 18 X 18 X 12 ins., in each sec., 5 $\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00
 80.00
 9.15
 38.30
 40.00

S. 89° 57' E., on a random line, bet. secs. 22 and 27.
 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 22, 23, 26 and 27.
 Thence
 West on a true line, bet. secs. 22 and 27.
 Over gently rolling land, through scattering timber and undergrowth.
 Road, brs. N. 10° E. and S. 10° W.
 Road, brs. N. and S.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S22
 S27
 1916

80.00

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
 The cor. of secs. 21, 22, 27 and 28.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, palo verde, cat claw, sagebrush and greasewood.

40.00

N. 0° 2' W., bet. secs. 21 and 22.
 Over level land, through scattering timber and undergrowth.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{2}$ sec. cor., marked on brass cap

$\frac{1}{2}$
 S21|S22
 1916

80.00

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on brass cap

T5N R6W
 S16|S15
 S21|S22
 1916

22.

Subdivision of T. 5 N., R. 6 W.

Chains.

Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
 Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00 East on a random line, bet. secs. 15 and 22.
 Set temp. ¼ sec. cor.
 80.01 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 14, 15, 22 and 23.
 Thence
 N. 89° 56' W., on a true line, bet. secs. 15 and 22.
 Over level land, through scattering timber and undergrowth.
 4.00 Road, brs. NE. and SW.
 40.00½ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S15
 ¼ S22
 1916

80.01 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
 The cor. of secs. 15, 16, 21 and 22.
 Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

16.90 N. 0° 2' W., bet. secs. 15 and 16.
 Over gently rolling land, through scattering timber and undergrowth.
 Road, brs. NE. and SW.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S16 | S15
 1916

61.10 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
 Road, brs. NE. and SW.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap

T5N R6W
 S 9 | S10
 S16 | S15
 1916

Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering paloverde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

Subdivision of T. 5 N., R. 6 W.


Chains.

40.00 S.89° 56' E., on a random line, bet. secs. 10 and 15.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.06 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 10, 11, 14 and 15.
 Thence
 N.89° 58' W., on a true line, bet. secs. 10 and 15.
 Over gently rolling land, through scattering timber and undergrowth.
 40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 41.05 Road, brs. NE. and SW.
 73.15 Road, brs. NE. and SW.
 80.06 The cor. of secs. 9, 10, 15 and 16.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, palo verde.
 Undergrowth, cat claw, mesquite, sagebrush and greasewood.

39.40 N.0° 2' W., bet. secs. 9 and 10.
 Over level land, through scattering timber and undergrowth.
 Road, brs. NE. and SW.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, level.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00 S.89° 58' E., on a random line, bet. secs. 3 and 10.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.94 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 2, 3, 10 and 11.
 Thence
 N.89° 59' W., on a true line, bet. secs. 3 and 10.
 Over level land, through scattering timber and undergrowth.
 39.97 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains.

$\frac{1}{4}$ S 3
S10
1916

79.94 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
The cor. of secs. 3, 4, 9 and 10.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.0° 2' W., on a random line, bet. secs. 3 and 4.
Set temp. $\frac{1}{4}$ sec. cor.
79.96 Intersect N. bdy. of Tp., 34 lks. E. of the cor. of secs. 3, 4, 33 and 34, which is an iron post, hereinbefore described.
Thence
S.0° 17' E., on a true line, bet. secs. 3 and 4.
Over gently rolling land, through scattering timber and undergrowth.
9.95 Road, brs. NW. and SE.
16.45 Road, brs. NE. and SW.
39.96 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S 4 $\frac{1}{4}$ S 3
1916

79.96 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
The cor. of secs. 3, 4, 9 and 10.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., which is an iron post, described in the field notes of current Group No. 39,
N.0° 2' W., bet. secs. 32 and 33.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S32 $\frac{1}{4}$ S33
1916

80.00 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, marked on brass cap

T5N R6W
S29 | S28
S32 | S33
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Subdivision of T. 5 N., R. 6 W.

Chains.


Land, gently rolling.
Soil, gravelly; 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00
79.96

East on a random line, bet. secs. 28 and 33.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 1 lk. N. of the cor. of secs.
27, 28, 33 and 34.
Thence

39.98

West on a true line, bet. secs. 28 and 33.
Over gently rolling land, through scattering timber and
undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




72.00
79.96

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of cor.
Draw, 25 lks. wide, 4 ft. deep, course SE. Thence along
S. bank of draw.
The cor. of secs. 28, 29, 32 and 33.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw, mesquite, sagebrush and greasewood.

40.00

N.0° 2' W., bet. secs. 28 and 29.
Over level land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



41.70
80.00

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
high, W. of cor.
Road, brs. NE. and SW.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 20, 21, 28 and 29, marked on
brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00
79.82

East on a random line, bet. secs. 21 and 28.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 2 lks. N. of the cor. of secs.

26.

Subdivision of T. 5 N., R. 6 W.

Chains.	
	21, 22, 27 and 28.
.	Thence
39.91	N. 89° 59' W., on a true line, bet. secs. 21 and 28. Over level land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{r} \frac{1}{4} \text{ S21} \\ \hline \frac{1}{4} \text{ S28} \\ 1916 \end{array}$
	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. N. of cor.
57.80	Road, brs. NE. and SW.
79.82	The cor. of secs. 20, 21, 28 and 29. Land, level. Soil, 2nd rate. Timber, scattering palo verde. Undergrowth, cat claw.
	N. 0° 2' W., bet. secs. 20 and 21.
40.00	Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
	$\begin{array}{r} \frac{1}{4} \\ \text{S20} \mid \text{S21} \\ 1916 \end{array}$
80.00	Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on brass cap
	$\begin{array}{r} \text{T5N R6W} \\ \text{S17} \mid \text{S16} \\ \hline \text{S20} \mid \text{S21} \\ 1916 \end{array}$
	Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
	Land, gently rolling. Soil, 2nd rate. Timber, scattering palo verde. Undergrowth, cat claw, ocotillo, mesquite, sagebrush and greasewood.
40.00	S. 89° 59' E., on a random line, bet. secs. 16 and 21. Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect N. and S. line, 5 lks. S. of the cor. of secs. 15, 16, 21 and 22. Thence
	S. 89° 59' W., on a true line, bet. secs. 16 and 21. Over gently rolling land, through scattering timber and undergrowth.
9.40	Road, brs. NE. and SW.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

Subdivision of T. 5 N., R. 6 W.

Chains.

$\frac{1}{4}$ S16
S21
1916

79.90 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
The cor. of secs. 16, 17, 20 and 21.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

6.90 N.0° 2' W., bet. secs. 16 and 17.
Over level land, through scattering timber and undergrowth.
Road, brs. NE. and SW.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

$\frac{1}{4}$
S17 | S16
1916

70.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
Road, brs. NE. and SW.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on brass cap

T5N R6W
S 8 | S 9
S17 | S16
1916

Dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.89° 59' E., on a random line, bet. secs. 9 and 16.
Set temp. ¼ sec. cor.
79.95 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 9, 10, 15 and 16.

Thence
West on a true line, bet. secs. 9 and 16.
Over level land, through scattering timber and undergrowth.
39.97½ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

$\frac{1}{4}$ S 9
S16
1916

69.95 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
Road, brs. NE. and SW.
79.95 The cor. of secs. 8, 9, 16 and 17.
Land, level.
Soil, 2nd rate.


Chains.

Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.0° 2' W., bet. secs. 8 and 9.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




43.30 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{8}$ ft. base, $1\frac{1}{8}$ ft. high, W. of cor.
80.00 Road, brs. E. and W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, marked on brass cap



Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{8}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, gently rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sasebrush and greasewood.

40.00 East on a random line, bet. secs. 4 and 9.
79.99 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 6 lks. S. of the cor. of secs. 3, 4, 9 and 10.
Thence
S.89° 57' W., on a true line, bet. secs. 4 and 9.
Over level land, through scattering timber and undergrowth.
39.99 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



79.99 And raise a mound of stone, 2 ft. base, $1\frac{1}{8}$ ft. high, N. of cor.
The cor. of secs. 4, 5, 8 and 9.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 N.0° 2' W., on a random line, bet. secs. 4 and 5.
80.00 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. bdy. of Tp., 21 lks. E. of the cor. of secs. 4, 5, 32 and 33, which is an iron post, hereinbefore described.
Thence

Subdivision of T. 5 N., R. 6 W.

Chains.

4.50 S.0° 11' E., on a true line, bet. secs. 4 and 5.
 Over gently rolling land, through scattering timber and undergrowth.
 40.00 Road, brs. E. and W.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



80 00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 The cor. of secs. 4, 5, 8 and 9.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

30.50 From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., which is an iron post, described in the field notes of current group No. 39,
 40.00 N.0° 3' W., bet. secs. 31 and 32.
 Over gently rolling land, through scattering timber and undergrowth.
 Draw, 75 lks. wide, 10 ft. deep, course E.
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



45.00 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 80.00 Draw, 150 lks. wide, 4 ft. deep, course E.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, cat claw.

40.00 East on a random line, bet. secs. 29 and 32.
 79.90 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 3 lks. N. of the cor. of secs. 28, 29, 32 and 33.
 Thence
 N.89° 59' W., on a true line, bet. secs. 29 and 32.
 Over level land, through scattering timber and undergrowth.
 28.00 Road, brs. NE and SW.
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

30.

Subdivision of T. 5 N., R. 6 W.

chains.

$\frac{1}{4}$ S20
 $\frac{1}{4}$ S32
1916

79.90 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
The cor. of secs. 29, 30, 31 and 32.
Land, level.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, cat claw.

40.00 West on a random line, bet. secs. 30 and 31.
79.87 Set temp. $\frac{1}{4}$ sec. cor.
Intersect W. bdy. of Tr., 7 lks. N. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, described in Book "B".
Thence
N.89° 57' E., on a true line, bet. secs. 30 and 31.
32.00 Over rolling land, through scattering timber and undergrowth.
39.87 Draw, 35 lks. wide, 4 ft. deep, course SW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S30
 $\frac{1}{4}$ S31
1916

48.40 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
54.00 Draw, 100 lks. wide, 4 ft. deep, course S.
79.87 Draw, 120 lks. wide, 4 ft. deep, course S.
The cor. of secs. 29, 30, 31 and 32.
Land, rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, palo verde, cat claw, sagebrush and greasewood.

33.00 N.0° 3' W., bet. secs. 29 and 30.
40.00 Over gently rolling land, through scattering timber and undergrowth.
Draw, 20 lks. wide, 4 ft. deep, course SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S30 | S29
1916

76.90 And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00 Road, brs. N.70° E. and S.70° W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap

T5N R6W
S19 | S20
S30 | S29
1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Land, gently rolling.

chains.

Soil, 2nd rate.
Timber, palo verde.
Undergrowth, cat claw, sagebrush, greasewood and mesquite.

40.00 S.89° 59' E., on a random line, bet. secs. 20 and 29.
80.03 Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. and S. line, 7 lks. S. of the cor. of secs.
20, 21, 28 and 29.

Thence
40.01 $\frac{1}{2}$ S.89° 58' W., on a true line, bet. secs. 20 and 29.
Over gently rolling land, through scattering timber and
undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S20
 $\frac{1}{4}$ S29
1916

77.95 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
80.03 dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft.
high, N. of cor.

Road, brs. NE. and SW.
The cor. of secs. 19, 20, 29 and 30.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00 S.89° 57' W., on a random line, bet. secs. 19 and 30.
79.86 Set temp. $\frac{1}{4}$ sec. cor.
Intersect W. bdy. of Tp., 7 lks. S. of the cor. of secs.
19, 24, 25 and 30, which is an iron post, described in
Book "B".

Thence
East on a true line, bet. secs. 19 and 30.
Over gently rolling land, through scattering timber and
undergrowth.

39.86 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S19
 $\frac{1}{4}$ S30
1916

79.86 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft.
high, N. of cor.

The cor. of secs. 19, 20, 29 and 30.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde and mesquite.
Undergrowth, mesquite and greasewood.

40.00 N.0° 3' W., bet. secs. 19 and 20.
Over level land, through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S19 | S20
1916

32.

Subdivision of T. 5 N., R. 6 W.

Chains.

80.00 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on brass cap

T5N R6W
 S18(S17
 S19|S20
 1916

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, level.
 Soil, 1st and 2nd rates.
 Timber, none.
 Undergrowth, greasewood.

40.00 N.89° 58' E., on a random line, bet. secs. 17 and 20.
 Set temp. ¼ sec. cor.
 79.99 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 16, 17, 20 and 21.
 Thence
 West on a true line, bet. secs. 17 and 20.
 Over level land, through scattering undergrowth.
 12.00 Road, brs. NE. and SW.
 39.99½ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S17
 S20
 1916

79.99 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
 The cor. of secs. 17, 18, 19 and 20.
 Land, level.
 Soil, 1st and 2nd rate.
 Timber, none.
 Undergrowth, greasewood.

40.00 West on a random line, bet. secs. 18 and 19.
 Set temp. ¼ sec. cor.
 79.85 Intersect W. bdy. of Tp., 3 lks. S. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, described in the field notes of current Group No. 39.
 Thence
 S.89° 59' E., on a true line, bet. secs. 18 and 19.
 Over gently rolling land, through scattering timber and undergrowth.
 27.70 Road, brs. NE. and SW.
 39.85 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S18
 S19
 1916

79.85 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
 The cor. of secs. 17, 18, 19 and 20.
 Land, gently rolling.
 Soil, 2nd rate.
 Timber, palo verde.

Subdivision of T. 5 N., R. 6 W.


Chains. Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00 N.0° 3' W., bet. secs. 17 and 18.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



43.10 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Road, brs. NE. and SW.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap




Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
Land, gently rolling.
Soil, 2nd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00 East on a random line, bet. secs. 8 and 17.
Set temp. $\frac{1}{4}$ sec. cor.
80.05 Intersect N. and S. line, at the cor. of secs. 8, 9, 16 and 17.

Thence
West on a true line, bet. secs. 8 and 17.
Over gently rolling land, through scattering timber and undergrowth.

40.02 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



80.05 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
The cor. of secs. 7, 8, 17 and 18.
Land, gently rolling.
Soil, 2nd rate.
Timber, palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00 N.89° 59' W., on a random line, bet. secs. 7 and 18.
Set temp. $\frac{1}{4}$ sec. cor.
79.73 Intersect W. bdy. of Tp., 2 lks. S. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, described in Book "B".
Thence

34

Subdivision of T. 5 N., R. 6 W.

Chains.

S. 89° 58' E., on a true line, bet. secs. 7 and 18.
 Over gently rolling land, through scattering timber and undergrowth.

39.73 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 7
 $\frac{1}{4}$ S 18
 1916

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

79.73 The cor. of secs. 7, 8, 17 and 18.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, scattering palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

N. 0° 3' W., bet. secs. 7 and 8.
 Over gently rolling land, through scattering timber and undergrowth.

39.70 Road, brs. E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 7 | S 8
 1916

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, marked on brass cap

T5N R6W
 S 6 | S 5
 $\frac{1}{4}$ S 7 | S 8
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, gently rolling.
 Soil, 3rd rate.
 Timber, palo verde.
 Undergrowth, mesquite, cat claw, sagebrush and greasewood.

East on a random line, bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect N. and S. line, at the cor. of secs. 4, 5, 8 and 9.

Thence
 West on a true line, bet. secs. 5 and 8.
 Over gently rolling land, through scattering timber and undergrowth.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 5
 $\frac{1}{4}$ S 8
 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Subdivision of T. 5 N., R. 6 W.

Chains.
80.02


The cor. of secs. 5, 6, 7 and 8.
Land, gently rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, mesquite, cat claw, sagebrush and greasewood.

40.00
79.69

N.89° 58' W., on a random line, bet. secs. 6 and 7.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect W. bdy. of Tp., 5 lks. S. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, described in Book "B".

39.69

Thence
S.89° 56' E., on a true line, bet. secs. 6 and 7.
Over gently rolling land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



79.69

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
The cor. of secs. 5, 6, 7 and 8.
Land, gently rolling.
Soil, 3rd rate.
Timber, scattering palo verde.
Undergrowth, cat claw, mesquite, sagebrush and greasewood.

40.00
80.02

N.0° 3' W., on a random line, bet. secs. 5 and 6.
Set temp. $\frac{1}{4}$ sec. cor.
Intersect N. abdy. of Tp., 21 lks. E. of the cor. of secs. 5, 6, 31 and 32, which is an iron post, hereinbefore described.

36.60
40.02

Thence
S.0° 12' E., on a true line, bet. secs. 5 and 6.
Over gently rolling land, through scattering timber and undergrowth.
Road, brs. N.70° E. and S. 70° W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



80.02

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
The cor. of secs. 5, 6, 7 and 8.
Land, gently rolling.
Soil, 4th rate.
Timber, scattering palo verde.
Undergrowth, sagebrush, mesquite, cat claw and greasewood.

56.

General Description.

This township consists of level and rolling land, covered with greasewood and cholla undergrowth, and mesquite, catclaw and palo verde, which varies from low shrubbery to fair sized trees.

The soil ranges from sandy loam, 2nd rate, 8 to 12 ins. deep, on gumbo subsoil, to gravelly and rocky soil, 3rd rate. It is most adapted to grazing purposes.

There is no water in the township.

FOR CERTIFICATES OF U. S. SURVEYOR AND U. S. TRANSITMAN. SEE BOOK "A"
~~FINAL OATH OF UNITED STATES SURVEYOR.~~

I, _____, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for _____ bearing date of the _____ day of _____, 191____, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ of the _____ Meridian, in the State of _____, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for _____ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

U. S. Surveyor.

Subscribed by said _____, and sworn to before me }
this _____ day of _____, 191____ }



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Ariz. JUN 28 1918, 191____

The foregoing field notes of the survey of the _____
East and North Boundaries and
Subdivisional Lines
of

TOWNSHIP 5 NORTH, RANGE 6 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, executed by Roy J. Gill, U. S. Surveyor and Hans D. Voigt, U. S. Transitman, under ~~his~~ special instructions dated Sept. 24, 1915, for Group 59, Arizona, 191____, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Frank R. Frost

U. S. Surveyor General.

~~I certify that the foregoing transcript of the field notes of the above described surveys in _____, has been correctly copied from the original notes on file in this office.~~