

33  
①

3125

Book "L."

4-679

(Subdivisions) BOOK 3125

# FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION LINES

OF

TOWNSHIP 18 NORTH, RANGE 17 WEST,

3125

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

3125

EXECUTED BY

Mans H. Coffin, Jr., and Howard G. Mason,

U. S. Transitmen,

~~In the capacity of U. S. Surveyor~~, under instructions dated January 7, 1915,  
issued by the United States Surveyor General to govern surveys included in  
Group No. 46, which were approved by the Commissioner of the General Land  
Office, January 22, 1915.

Survey commenced February 9, 1916.

Survey completed February 19, 1916.

Instructions dated Jan. 28, 1915 and Nov. 6, 1915.

34  
1A

3125  
Book "L."  
Group 46- Arizona.  
(Subdivisions)

BOOK 3125

INDEX DIAGRAM.

Township 18 North,										Range 17 West.									
6	27	5	20	4	15	3	10	2	5	1									
26		26		19		15		10		5									
7	25	8	19	9	14	10	9	11	4	12									
25		24		18		14		9		4									
18	24	17	18	16	13	15	8	14	4	13									
23		23		18		13		8		3									
19	23	20	17	21	12	22	7	23	3	24									
22		22		17		12		7		2									
30	21	29	16	28	11	27	7	26	2	25									
21		20		16		11		6		1									
31	20	32	15	33	11	34	6	35	1	36									

Subdivision lines surveyed under this Group.

Township boundaries surveyed under this Group.  
Notes in Book "B." 3115

Township boundaries resurveyed under this Group.  
Notes in Book "B." 3115

Accepted surveys.

Subdivision of T. 18 N., R. 17 W.

16

Chains

Survey executed jointly by Mans H. Coffin, Jr. & Howard G. Mason, U. S. Transitmen, on dates shown on diagram on page 29 of this book.

The instruments used are described, with record of approval by the assistant supervisor of surveys, and field tests, in Book J. The adjustments were tested and maintained through the survey by frequent comparison with meridians determined by observations on Polaris.

The magnetic declination in this township is 14°45'E.

From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., described in Book "B"

7.50 N.0°01'W., bet. secs. 35 and 36,  
over rolling land, through scattering undergrowth.  
40.00 Wash, 2 chs. wide, course SW.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S35 S36

1916

80.00 dig pits, 18x18x12 ins. N. and S. of post, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap, marked

T18N	R17W
S26	S25
S35	S36

1916

dig pits, 18x18x12 ins., in each sec.,  $5\frac{1}{2}$  ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling desert.  
Soil, shallow and sandy; 2nd and 3rd rate.  
No timber.  
Undergrowth, yucca, greasewood and cactus.

40.00 East, on a random line, bet. secs. 25 and 36.  
80.12 Set temp.  $\frac{1}{4}$  sec. cor.

Intersect E. bdy. of Tp. 2 lks. S. of the cor. of secs. 25, 30, 31 and 36, described in Book "B"

Thence S.89°59'W., on a true line, bet; secs. 25 and 36, over mountainous land, through scattering undergrowth. Desc. 200 ft., along rolling S. slope.

9.40 Asc. 230 ft.  
17.20 Rocky spur bears SE. Desc. 360 ft. on SW. slope.  
31.60 Mt. of slope bears SE. and NW. Thence over rolling land,  
40.06 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 25  
 $\frac{1}{4}$  -----  
S 36  
1916

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Chains	
80.12	The cor. of secs. 25, 26, 35 and 36. Land, mountainous in E. 31.60 chs. and rolling in W. part. Soil, sandy; 4th rate. No timber. Undergrowth, catclaw and cactus.
25.00	N.0°01'W., bet. secs. 25 and 26, over rolling land, through scattering undergrowth; over broken W. slope.
40.00	Leave rolling land, bearing NW. and SE., and asc. SW. slope. Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, on solid rock, for $\frac{1}{4}$ sec. cor., with brass cap, marked
	S26 S25 1916 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft high, W. of cor.
49.30	Rocky spur, 715 ft. above 25 ch. pt., slopes NW. Desc. 235 ft., along broken NW. slope.
57.50	Asc. 75 ft.
62.30	Desc. 380 ft.
78.00	Gulch, course NW. Asc.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap, marked
	T18N   R17W S23   S24 ----- S26   S25 1916 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft high, W. of cor.
	Land, rolling in S. 25 chs. and mountainous in N. part. Soil, 2nd and 3rd rate on rolling land, and rocky; 4th rate on mountainous land. No timber. Undergrowth, yucca, greasewood and cactus.
40.00	East, on a random line, bet. secs. 24 and 25. Set temp. $\frac{1}{4}$ sec. cor.
79.78	Intersect E. bdy. of Tp. 15 lks. N. of the cor. of secs. 19, 24, 25 and 30, described in Book "B"
	Thence N.89°54'W., on a true line, bet. secs. 24 and 25, over mountainous land, through scattering undergrowth. Asc. 80 ft., over rolling S. slope.
10.00	Thence desc. on rolling SW. slope.
39.89	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for $\frac{1}{4}$ sec. cor., with brass cap, marked
	S 24 $\frac{1}{4}$ ----- S 25 1916 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
55.56	Gulch, 635 ft. below 10 ch. pt., course NW. Asc. 170 ft. on NE. slope.
67.60	Spur slopes NW. Desc. 210 ft., on SW. slope.
79.78	The cor. of secs. 23, 24, 25 and 26.

Subdivision of T. 18 N., R. 17 W.

Chains

Land, mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, catclaw, cactus and palo verde.

N.0°01'W., bet. secs. 23 and 24,  
over mountainous land, through scattering undergrowth.  
Asc. 280 ft., on SW. slope.  
13.40- Rocky spur slopes W. Desc. 360 ft., along broken NW. slope.  
39.20 Draw, course NW. Asc. SW. slope.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of  
stone, on solid rock, for  $\frac{1}{4}$  sec. cor., with brass cap,  
marked

S23 | S24

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.  
52.60 Spur, 230 ft. above draw, slopes W. Desc. 140 ft., on  
N. slope.

59.20 Draw, course W. Asc. 160 ft., on S. slope.

79.10 Spur slopes W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 13, 14, 23 and 24, with brass  
cap, marked

T18N | R17W  
S14 | S13  
-----  
S23 | S24

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.

Land, mountainous.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, yucca and cactus.

40.00 East, on a random line, bet. secs. 13 and 24.  
Set temp.  $\frac{1}{4}$  sec. cor.  
79.82 Intersect E. bdy. of Tp. 16 lks. S. of the cor. of secs.  
13, 18, 19 and 24, described in Book "B"

Thence S.89°53'W., on a true line, bet. secs. 13 and 24,  
over rolling land, through scattering undergrowth.  
Desc. 220 ft., gradually.

39.00 Willow Creek, containing stream 6 lks. wide, course NW.

39.91 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 13  
 $\frac{1}{4}$  -----

S 24

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
N. of cor.

79.82 The cor. of secs. 13, 14, 23 and 24.


Land, rolling.  
Soil, sandy; 2nd and 3rd rate.  
No timber.  
Undergrowth, greasewood and cactus.

4


Subdivision of T. 18 N., R. 17 W.

Chains

N.0°01'W., bet. secs. 13 and 14,  
 over mountainous land, through scattering undergrowth.  
 Desc. NW. slope, 70 ft.  
 12.50 Willow Creek, containing stream 3 lks. wide, course SW.  
 Enter rolling land bearing NE. and SW.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



1916  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 11, 12, 13 and 14, with brass  
 cap, marked




1916  
 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

Land, mountainous for 12.50 chs. and rolling for balance.  
 Soil, sandy; 2nd and 3rd rate.  
 No timber.  
 Undergrowth, greasewood, cactus, ocotillo and crucifixion  
 thorn.

40.00 East, on a random line, bet. secs. 12 and 13.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.70 Intersect E. bdy. of Tp. 23 lks. S. of the cor. of secs.  
 7, 12, 13 and 18, described in Book "B"

Thence S.89°50'W., on a true line, bet. secs. 12 and 13,  
 over rolling land, through scattering undergrowth.  
 16.30 Rock Creek, 8 lks. wide, course NW. Running water.  
 32.30 Rock Creek, containing stream 6 lks. wide, at bend from  
 SW. course to NW. course.  
 39.85 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.  
 43.70 Rock Creek, containing stream 4 lks. wide, course SW.  
 65.90 Rock Creek, containing stream 4 lks. wide, course NW.  
 79.70 The cor. of secs. 11, 12, 13 and 14.

Land, rolling and rolling mountainous.  
 Soil, **rocky and sandy**; 4th rate.  
 No timber.  
 Undergrowth, catclaw, greasewood and cactus.

N.0°01'W., bet. secs. 11 and 12,  
 over rolling land, through scattering undergrowth.  
 4.00 Rock Creek, containing small stream, course W. Enter  
 mountainous land bearing E. and W. Asc. 355 ft.  
 27.00 Desc. 275 ft.  
 40.00 At ft. of slope,  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked


Subdivision of T. 18 N., R. 17 W.

Chains



1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.  
Thence over rolling land, bearing E. and W.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 1, 2, 11 and 12, with brass cap,  
marked




1916

dig pits, 18x18x12 ins., in each sec., 5½ ft. dist.,  
and raise a mound of earth, 4 ft. base, 2 ft. high,  
W. of cor.  
Land, mountainous in S. half and rolling in N.  
Soil, rocky; 3rd and 4th rate.  
No timber.  
Undergrowth, cactus, catclaw and scattering juniper.

40.00 East, on a random line, bet. secs. 1 and 12.  
Set temp. ¼ sec. cor.  
79.60 Intersect E. bdy. of Tp. 26 lks. S. of the cor. of secs.  
1, 6, 7 and 12, described in Book "B"


Thence S.89°49'W., on a true line, bet. secs. 1 and 12,  
over mountainous land, through scattering undergrowth.  
Desc. steep W. slope 800 ft.  
39.80 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for ¼ sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1½ ft. high,  
N. of cor.  
Thence over rolling land.  
79.60 The cor. of secs. 1, 2, 11 and 12.  
Land, mountainous.  
Soil, rocky; 3rd and 4th rate.  
No timber.  
Undergrowth, cactus, greasewood, juniper and ocotillo.

40.00 N.0°01'W., on a random line, bet. secs. 1 and 2.  
Set temp. ¼ sec. cor.  
80.18 Intersect N. bdy. of Tp. 12 lks. E. of the cor. of secs.  
1, 2, 35 and 36, described in Book "B"

Thence S.0°06'E., on a true line, bet. secs. 1 and 2,  
over mountainous land, through scattering undergrowth.  
Desc. 85 ft.  
10.00 Ft. of slope. Thence over rolling land.  
40.18 Set an iron post, 3 ft. long, 1 in. diam., in a mound of  
stone, (impracticable to set post in the ground) for  
¼ sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.


Chains

80.18 The cor. of secs. 1, 2, 11 and 12.

Land, mountainous in N. 10 chs., and rolling in S. part.  
Soil, 3rd and 4th rate.  
No timber.  
Undergrowth, greasewood and cactus.

-----  
From the cor. of secs. 2, 3, 34 and 35, on S. bdy. of Tp.,  
described in Book "B,"


N.0°01'W., bet. secs. 34 and 35,  
over rolling land, through scattering undergrowth.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



1916

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,  
and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 26, 27, 34 and 35, with brass  
cap, marked



1916


dig pits, 18x18x12 ins., in each sec.,  $5\frac{1}{2}$  ft. dist.,  
and raise a mound of earth, 4 ft. base, 2 ft. high,  
W. of cor.

Land, gently rolling.  
Soil, gravelly; 2nd rate.  
No timber.  
Undergrowth, cactus and catclaw.

-----  
40.00 East, on a random line, bet. secs. 26 and 35.  
Set temp.  $\frac{1}{4}$  sec. cor.

80.12 Intersect N. and S. line at the cor. of secs. 25, 26, 35 and  
36, described in Book "B".

40.06 Thence West, on a true line, bet. secs. 26 and 35,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.,  
and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.

80.12 The cor. of secs. 26, 27, 34 and 35.

Land, rolling.  
Soil, sandy and rocky; 4th rate.  
No timber.  
Undergrowth, cactus, greasewood and yucca.


-----




Subdivision of T. 18 N., R. 17 W.

Chains

N.0°01'W., bet. secs. 26 and 27,  
 over rolling land, through scattering yucca trees and  
 varied undergrowth.  
 39.85 Wash, course W. Enter mountainous land bearing E. and W.  
 40:00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of  
 stone, (impracticable to set post in the ground) for  
 1/4 sec. cor., with brass cap, marked




1916  
 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
 W. of cor.  
 Asc. 460 ft., on broken S. slope.  
 75.00 Spur slopes SE. Desc. 25 ft., on NE. slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of  
 stone, (impracticable to set post in the ground) for  
 cor. of secs. 22, 23, 26 and 27, with brass cap, marked



1916  
 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
 W. of cor.  
 Land, rolling in S. half and mountainous in N.  
 Soil, 2nd and 4th rate; rocky;  
 No timber. Scattering yucca trees.  
 Undergrowth, sage, cactus, catclaw.

40.00 East, on a random line, bet. secs. 23 and 26.  
 Set temp. 1/4 sec. cor.  
 80.42 Intersect N. and S. line 7 lks. N. of the cor. of secs.  
 23, 24, 25 and 26.

Thence N.89°57'W., on a true line, bet. secs. 23 and 26,  
 over rolling hills, through scattering undergrowth.  
 Desc. 70 ft., on SW. slope.  
 6.50 Gulch, course NW. Asc. 90 ft., along N. slope.  
 20.40 Desc. on W. slope.  
 40.21 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the  
 ground, surrounded by a mound of stone, (impracticable  
 to set post farther in the ground) for 1/4 sec. cor.,  
 with brass cap, marked




and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
 N. of cor.  
 42.10 Wash, 250 ft. below 20.40 ch. pt., 20 lks; wide, course  
 SW. Thence over less broken ground.  
 60.40 Enter mountainous land, and asc. 315 ft., on NE. slope.  
 80.42 The cor. of secs. 22, 23, 26 and 27.

Land, rolling hills in E. 60 chs., and mountainous in  
 W. part.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, cactus, catclaw and palo verde.

N.0°01'W., bet. secs. 22 and 23,  
 over mountainous land, through scattering undergrowth.  
 Desc. 380 ft., on rocky NE. slope.

Chains

25.00 Wash, course W. Asc. broken SW. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, (impracticable to set post in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked




1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

46.25 Spur, 100 ft. above wash, slopes W.

68.20 Willow Creek, dry, course SW. Enter rolling land bearing NE. and SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, mountainous.

Soil, rocky; 3rd and 4th rate.

No timber.

Undergrowth, sage, cactus and greasewood.

40.00 East, on a random line, bet. secs. 14 and 23.


Set temp.  $\frac{1}{4}$  sec. cor.

80.24 Intersect N. and S. line 36 lks. N. of the cor. of secs. 13, 14, 23 and 24.

Thence N.89°45'W., on a true line, bet. secs. 14 and 23, over rolling mountainous land, through scattering undergrowth. Desc. 220 ft.

25.00 Ft. of slope.

40.12 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

55.25 Willow Creek, 5 lks. wide, course SW. Enter rolling land bearing NE. and SW.

80.24 The cor. of secs. 14, 15, 22 and 23.

Land, rolling and rolling mountainous.

Soil, sandy; 2nd and 3rd rate.

No timber.


Undergrowth, cactus, greasewood, ocotillo and juniper.

N.0°01'W., bet. secs. 14 and 15, over rolling land, through scattering undergrowth and yucca trees.

28.50 Wash, course NW.

34.00 Wash, course W.


40.00 Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, (impracticable to set post in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked



Subdivision of T. 18 N., R. 17 W.

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.  
45.80 Wash, course W.  
70.50 Wash, course SW.  
80.00 Set an iron post, 2 ft. long, 2 ins. diam., 12 ins. in  
the ground, surrounded by a mound of stone, (impracticable  
to set post farther in the ground) for cor. of secs.  
10, 11, 14 and 15, with brass cap, marked




1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.

Land, rolling and rolling mountainous.  
Soil, rocky; 2nd and 3rd rate.  
Timber, yucca.  
Undergrowth, cactus and catclaw.

40.00 East, on a random line, bet. secs. 11 and 14.  
Set temp, ¼ sec. cor.  
80.20 Intersect N. and S. line 10 lks. N. of the cor. of secs.  
11, 12, 13 and 14.

40.10 Thence N. 89° 56' W., on a true line, bet. secs. 11 and 14,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for ¼ sec. cor., with brass cap, marked




1916

60.00 dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.  
80.20 and raise a mound of earth, 3½ ft. base, 1½ ft. high,  
N. of cor.  
Asc. 105 ft., on NE. slope, over mountainous land.  
The cor. of secs. 10, 11, 14 and 15.

Land, mountainous in W. 20 chs. and rolling in E. part.  
Soil, rocky; 3rd and 4th rate.  
No timber.  
Undergrowth, greasewood, catclaw, cactus, crucifixion  
thorn, ocotillo and palo verde.

13.60 N. 0° 01' W., bet. secs. 10 and 11,  
over mountainous land, through scattering undergrowth.  
16.80 Desc. 100 ft., on NE. slope.  
Stream, course SW.  
40.00 Stream, course SW. Thence over rolling land.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for ¼ sec. cor., with brass cap, marked



1916

80.00 dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.  
and raise a mound of earth, 3½ ft. base, 1½ ft. high,  
W. of cor.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 2, 3, 10 and 11, with brass  
cap, marked

Chains

T18N	R17W
S3	S2
S10	S11


1916

dig pits, 18x18x12 ins., in each sec., 5 1/2 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling and mountainous. Soil, sandy; 2nd and 3rd rate. No timber. Undergrowth, greasewood, cactus, catclaw, juniper and ocotillo.

40.00 East, on a random line, bet. secs. 2 and 11. Set temp. 1/4 sec. cor.  
80.30 Intersect N. and S. line 29 lks. N. of cor. of secs. 1, 2, 11 and 12.

40.15 Thence N. 89°48' W., on a true line, bet. secs. 2 and 11, over rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked




80.30 dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.  
The cor. of secs. 2, 3, 10 and 11.

Land, rolling. Soil, 2nd and 3rd rate. No timber. Undergrowth, greasewood and cactus.

40.00 N. 0°01' W., on a random line. bet. secs. 2 and 3. Set temp. 1/4 sec. cor.  
80.12 Intersect N. bdy. of Tp. 29 lks. W. of cor. of secs. 2, 3, 34 and 35, described in Book "B."

25.10 Thence S. 0°11' W., on a true line, bet. secs. 2 and 3, over mountainous land, through scattering undergrowth. Asc. 525 ft., on NE. slope.

40.12 Spur slopes NW. Desc. S. slope. Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, for 1/4 sec. cor., with brass cap, marked



50.10 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. Impracticable to set post in the ground. Ft. of slope, 570 ft. below spur. Enter rolling land bearing E. and W.

80.12 The cor. of secs. 2, 3, 10 and 11.

Land, rolling and mountainous. Soil, rocky; 3rd and 4th rate. No timber. Undergrowth, cactus and greasewood.


Subdivision of T. 18 N., R. 17 W.

Chains

From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp., described in Book D,

N.0°02'W., bet. secs. 33 and 34, over gently rolling land, through scattering undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked




1916

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

73.40 Wash, course W. Asc. 100 ft.; on rocky S. slope of butte.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 27, 28, 33 and 34, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.


Land, 73.40 chs. rolling and balance mountainous. Soil, 4th rate; sandy on rolling and rocky on mountainous land. No timber except scattering yucca trees. Undergrowth, cactus.

40.00 East, on a random line, bet. secs. 27 and 34. Set temp. 1/4 sec. cor.

80.08 Intersect N. and S. line 3 lks. N. of the cor. of secs. 26, 27, 34 and 35.

Thence N.89°59'W., on a true line, bet. secs. 27 and 34, over rolling land, through scattering undergrowth.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked



dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

70.00 Ft. of slope bears NW. and SE. Asc. 105 ft., on NE. slope.

75.00 Ridge bears NW. and SE. Thence along S. slope.

80.08 The cor. of secs. 27, 28, 33 and 34.

Land, rolling. Soil, sandy; 4th rate. No timber. Undergrowth, cactus, yucca and greasewood.

N.0°02'W., bet. secs. 27 and 28, over mountainous land, through scattering undergrowth. Asc. 105 ft., on rocky S. slope.


3.65 Rocky ridge bears NW. about 15 chs. and SE. about 7 chs. Desc. 250 ft., on NE. slope.

13.20 Ft. of slope. Enter rolling land.

36.80 Wash, course W.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

56.50 Wash, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 21, 22, 27 and 28, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling in N. 67 chs. and mountainous in S. part.

No timber.

Soil, sandy; 4th rate.

Undergrowth, cactus, catclaw and greasewood.

40.00 East, on a random line, bet. secs. 22 and 27.

Set temp.  $\frac{1}{4}$  sec. cor.


79.98 Intersect N. and S. line 5 lks. S. of the cor. of secs. 22, 23, 26 and 27.

Thence S.  $89^{\circ}58'$  W., on a true line, bet. secs. 22 and 27, over mountainous land, through scattering undergrowth. Asc. 185 ft., on rocky NE. slope.

4.00 Spur slopes NE. Desc. 290 ft., on NW. slope.

22.70 Ridge bears NW. and SE. Continue descent 390 ft., on SW. slope, over cliffs.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Thence over rolling land.

79.98 The cor. of secs. 21, 22, 27 and 28.

Land, mountainous in E. half and rolling in W.

Soil, 4th rate.

No timber.


Undergrowth, cactus, yucca and greasewood.

N.  $0^{\circ}02'$  W., bet. secs. 21 and 22,

over gently rolling land, through scattering undergrowth.

.30 Wash, 30 lks. wide, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked



Subdivision of T. 18 N., R. 17 W.

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.  
53.00 Rocky ledge bears NE. and SW.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the  
ground, surrounded by a mound of stone, (impracticable  
to set post farther in the ground) for cor. of secs.  
15, 16, 21 and 22, with brass cap, marked

T18N	R17W
S16	S15
S21	S22

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.

Land, rolling.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, cactus, catclaw, palo verde and ocotillo.

40.00 East, on a random line, bet. secs. 15 and 22.  
80.00 Set temp. ¼ sec. cor.  
Intersect N. and S. line 15 lks. S. of the cor. of secs.  
14, 15, 22 and 23.

Thence S. 89° 54' W., on a true line, bet. secs. 15 and 22,  
over rolling land, through scattering undergrowth.  
28.00 Ft. of butte bears N. and SW. Asc.  
34.00 Top of butte. Desc. SW. slope.  
38.00 Ft. of slope. Thence over rolling land.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
ground, surrounded by a mound of stone, (impracticable  
to set post farther in the ground) for ¼ sec. cor.,  
with brass cap, marked

S 15
¼ -----
S 22
1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
N. of cor.  
80.00 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.  
Soil, sandy; 2nd and 3rd rate.  
No timber.  
Undergrowth, greasewood, cactus and palo verde.

40.00 N. 0° 02' W., bet. secs. 15 and 16,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
ground, surrounded by a mound of stone, ( impracticable  
to set post farther in the ground ) for ¼ sec. cor.,  
with brass cap, marked

¼
S16   S15
1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,  
W. of cor.  
74.00 Wash, 50 lks. wide, course SW.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 9, 10, 15 and 16, with brass  
cap, marked

14

Subdivision of T. 18 N., R. 17 W.

Chains

T18N	R17W
S 9	S10
S16	S15

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, rocky; 4th rate.

No timber.

Undergrowth, greasewood, cactus and catclaw.

East, on a random line, bet. secs. 10 and 15.

40.00 Set temp. ¼ sec. cor.

79.72 Intersect N. and S. line 30 lks. S. of the cor. of secs. 10, 11, 14 and 15.

Thence S. 89° 47' W., on a true line, bet. secs. 10 and 15, over rolling land, through scattering undergrowth.

39.86 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked

S 10

¼ -----

S 15

1916

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist., and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

79.72 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.

Soil, sandy; 2nd and 3rd rate.

No timber.

Undergrowth, greasewood and cactus.

N. 0° 02' W., bet. secs. 9 and 10,

over rolling land, through scattering undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked

¼

S 9 | S10

1916

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked

T18N	R17W
S4	S3
S 9	S10

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, rocky; 4th rate.

No timber.

Undergrowth, greasewood, catclaw and ocotillo.



Subdivision of T. 18 N., R. 17 W.

Chains

40.00 East, on a random line, bet. secs. 3 and 10.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.90 Intersect N. and S. line at the cor. of secs. 2, 3, 10 and 11.

Thence West, on a true line, bet. secs. 3 and 10, over rolling land, through scattering undergrowth.  
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 3  
 $\frac{1}{4}$  -----  
 S 10  
 1916

79.90 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.  
 Soil, sandy; 2nd and 3rd rate.  
 No timber.  
 Undergrowth, greasewood, cactus and ocotillo.

40.00 N.0°02'W., on a random line, bet. secs. 3 and 4.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.71 Intersect N. bdy. of Tp. 19 lks. W. of the cor. of secs. 3, 4, 33 and 34, described in Book "B"

Thence S.0°06'W., on a true line, bet. secs. 3 and 4, over rolling land, through scattering undergrowth. Asc. Spur slopes SW. Desc. 115 ft. on S. slope.  
 8.70 Ft. of slope bears E. and W.  
 19.70  
 39.71 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

$\frac{1}{4}$   
 S4 | S3  
 1916

79.71 dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, greasewood, catclaw and cactus.

From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp. described in Book "B"


40.00 N.0°02'W., bet. secs. 32 and 33, over rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

$\frac{1}{4}$   
 S32 | S33  
 1916

80.00 dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, surrounded by a mound of stone, (impracticable

Chains

to set post farther in the ground) for cor. of secs. 28, 29, 32 and 33, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling desert.

Soil, sandy and rocky; 3rd and 4th rate.

No timber.

Undergrowth, greasewood, cactus and yucca.

40.00

East, on a random line, bet. secs. 28 and 33.

80.08

Set temp. ¼ sec. cor.

Intersect N. and S. line 4 lks. N. of the cor. of secs. 27, 28, 33 and 34.


10.00

Thence N.89°58'W., on a true line, bet. secs. 28 and 33, over mountainous land, through scattering undergrowth. Desc. along S. side of butte, 130 ft.

40.04

Ft. of slope. Thence over rolling land.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for ¼ sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

80.08

The cor. of secs. 28, 29, 32 and 33.

Land, 10 chs. mountainous in E. part, and rolling in W.

Soil, rocky and sandy; 4th rate.

No timber.


Undergrowth, greasewood, catclaw, cactus and yucca.

40.00

N.0°02'W., bet. secs. 28 and 29,

over rolling land, through scattering undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for ¼ sec. cor., with brass cap, marked




dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

42.40

Wash, 100 lks. wide, course SW.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 20, 21, 28 and 29, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base, 1½ ft. high,

Chains

W. of cor.


Land, rolling desert.  
Soil, sandy and rocky; 4th rate.  
No timber.  
Undergrowth, greasewood and cactus.

40.00  
80.14

East, on a random line, bet. secs. 21 and 28.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect N. and S. line 11 lks. S. of the cor. of secs. 21, 22, 27 and 28.

4.35  
40.07

Thence S.  $89^{\circ}55'W.$ , on a true line, bet. secs. 21 and 28, over rolling land, through scattering undergrowth.  
Wash, 40 lks. wide, course SW.  
Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.


80.14

The cor. of secs. 20, 21, 28 and 29.

Land, rolling.  
Soil, rocky; 4th rate.  
No timber.  
Undergrowth, cactus, greasewood and palo verde.

40.00


N.  $0^{\circ}02'W.$ , bet. secs. 20 and 21, over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

75.00  
80.00

Ft. of slope bears NW. and SE. Asc. 35 ft.  
Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 16, 17, 20 and 21, with brass cap, marked



1916  
and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.


Land, rolling desert.  
Soil, sandy and rocky; 4th rate.  
No timber.  
Undergrowth, greasewood, catclaw, cactus and palo verde.

Chains

East, on a random line, bet. secs. 16 and 21.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.20 Intersect N. and S. line 4 lks. S. of the cor. of secs. 15, 16, 21 and 22.

Thence S.  $89^{\circ}58'W.$ , on a true line, bet. secs. 16 and 21, over mountainous land, through scattering undergrowth. Asc. on NE. slope of butte.

40.10 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, surrounded by a mound of stone, ( impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

45.00 Top of butte. Desc. 840 ft., on SW. slope.  
 80.20 The cor. of secs. 16, 17, 20 and 21.

Land, mountainous.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, greasewood and cactus.


N.  $0^{\circ}02'W.$ , bet. secs. 16 and 17, over mountainous land, through scattering undergrowth, along rocky SW. slope.

19.75 Point of spur, 85 ft. above sec. cor., slopes W. Desc. 60 ft., on N. slope.

24.70 Foot of slope. Thence over rolling land,

32.00 Wash, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, surrounded by a mound of stone, ( impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked




1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

51.50 Wash, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.


Land, rolling.  
 Soil, rocky and sandy; 4th rate.  
 No timber.  
 Undergrowth, greasewood, cactus and ocotillo.

East, on a random line, bet. secs. 9 and 16,  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.30 Intersect N. and S. line 7 lks. S. of the cor. of secs. 9, 10, 15 and 16.

Chains

40.15 Thence S.89°57'W., on a true line, bet. secs. 9 and 16, over rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec.cor., with brass cap, marked




and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

80.30 The cor. of secs. 8, 9, 16 and 17.


Land, rolling.  
 Soil, sandy; 2nd and 3rd rate.  
 No timber.  
 Undergrowth, greasewood, cactus and catclaw.

40.00 N.0°02'W., bet. secs. 8 and 9, over rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap, marked




1916

dig pits, 18x18x12 ins. in each sec., 5½ ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling.  
 Soil, sandy and rocky; 4th rate.  
 No timber.  
 Undergrowth, greasewood, cactus, catclaw and ocotillo.

40.00 East, on a random line, bet. secs. 4 and 9.  
 Set temp.  $\frac{1}{4}$  sec.cor.  
 80.12 Intersect N. and S. line 3 lks. N. of the cor. of secs. 3, 4, 9 and 10.

40.06 Thence N.89°59'W., on a true line, bet. secs. 4 and 9, over rolling land, through scattering undergrowth.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

80.12 The cor. of secs. 4, 5, 8 and 9.  
 Soil, sandy; 2nd and 3rd rate. No timber. Land, rolling.  
 Undergrowth, greasewood and cactus.

Chains

N.0°02'W., on a random line, bet. secs. 4 and 5.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.64 Intersect N. and S. line 5 lks. W. of the cor. of secs.  
 4, 5, 32 and 33, described in Book "B"

Thence South, on a true line, bet. secs. 4 and 5,  
 over rolling land, through scattering undergrowth.  
 3.65 Wash, 5 lks. wide, course SW.  
 11.65 Wash, 150 lks. wide, course SW.  
 39.64 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S5 | S4

1916

79.64 dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,  
 and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 The cor. of secs. 4, 5, 8 and 9.  
 Land, rolling.  
 Soil, rocky; 4th rate.  
 No timber.  
 Undergrowth, scattering greasewood, catclaw and cactus.

From the cor. of secs. 5, 6, 31 and 32, on S. bdy. of Tp.,  
 described in Book "B"  
 N.0°03'W., bet. secs. 31 and 32,  
 over rolling land, through scattering undergrowth.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S31 | S32

1916

80.00 dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,  
 and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 29, 30, 31 and 32, with brass  
 cap, marked

T18N | R17W  
 S30 | S29  
 S31 | S32

1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.  
 Land, rolling.  
 Soil, sandy; 2nd and 3rd rate.  
 No timber.  
 Undergrowth, greasewood, cactus and yucca.

East, on a random line, bet. secs. 29 and 32.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.04 Intersect N. and S. line 5 lks. S. of cor. of secs.  
 28, 29, 32 and 33.

Thence S.89°58'W., on a true line, bet. secs. 29 and 32,  
 over rolling land, through scattering undergrowth.  
 40.02 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the  
 ground, surrounded by a mound of stone, (impracticable

Chains

to set post farther in the ground) for 1/4 sec. cor., with brass cap, marked

S 29  
1/4 -----  
S 32  
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

51.90  
75.00  
80.04

Wash, 40 lks. wide, course SW.  
Wash, 3 chs. wide, course SW.  
The cor. of secs. 29, 30, 31 and 32.

Land, rolling.  
Soil, rocky and sandy; 4th rate.  
No timber.  
Undergrowth, greasewood, catclaw and cactus.

40.00

West, on a true line, bet. secs. 30 and 31, over rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked

S 30  
1/4 -----  
S 31  
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

139.13

Intersect W. bdy. of Tp. 18.16 chs. S. of the old cor. of secs. 25, 30, 31 and 36, which is a stone, properly marked, set, and witnessed as described by the surveyor general.

At point of intersection Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 30 and 31, with brass cap, marked

T18N | T18N  
S30  
S36 ----CC  
S31  
R18W | R17W

1916 dig pits, 24x18x12 ins., crosswise on each line, N. and S. of post, 3 ft., and E. 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, E. of cor.

Land, rolling.  
Soil, rocky and sandy; 4th rate.  
No timber.  
Undergrowth, greasewood, cactus, catclaw.

40.00

N.0°03'W., bet. secs. 29 and 30, over rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked

1/4  
S30 | S29  
1916

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap, marked

Chains

T18N	R17W
S19	S20
S30	S29

1915

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, sandy; 2nd and 3rd rate.

No timber.

Undergrowth, greasewood, cactus and yucca.

East, on a random line, bet. secs. 20 and 29.

40.00 Set temp. ¼ sec. cor.

80.06 Intersect N. and S. line 10 lks. S. of the cor. of secs. 20, 21, 28 and 29.

Thence S. 89° 56' W., on a true line, bet. secs. 20 and 29, over rolling land, through scattering undergrowth.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for ¼ sec. cor., with brass cap, marked

S 20

¼ -----

S 29

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

80.06 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, sandy; 4th rate.

No timber.

Undergrowth, greasewood, catclaw and cactus.

West, on a true line, bet. secs. 19 and 30, over rolling land, through scattering undergrowth.

39.00 Wash, 60 lks. wide, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for ¼ sec. cor., with brass cap, marked

S 19

¼ -----

S 30

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

115.00 Wash, 40 lks. wide, course SW.

138.95 Intersect W. bdy. of Tp. 17.96 chs. S. of the old cor. of secs. 19, 24, 25 and 30, which is a stone, properly marked, set, and witnessed as described by the surveyor general.

At point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 19 and 30, with brass cap, marked

T18N	T18N
------	------

S19

S25 22--CC

S30

R18W	R17W
------	------

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.




Subdivision of T. 18 N. R. 17 W.


Chains

Rolling land.  
Soil, sandy and rocky; 4th rate.  
No timber.  
Undergrowth, greasewood, catclaw and cactus.

40.00 N.0°03'W., bet. secs. 19 and 20,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked



80.00 and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
W. of cor.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 17, 18, 19 and 20, with brass  
cap, marked




1916  
and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
W. of cor.

Land, rolling.  
Soil, sandy; 2nd and 3rd rate.  
No timber.  
Undergrowth, greasewood, cactus and catclaw.

40.00 East, on a random line, bet. secs. 17 and 20.  
Set temp. 1/4 sec. cor.  
80.10 Intersect N. and S. line 30 lks. S. of the cor. of secs.  
16, 17, 20 and 21.


40.05 Thence S.89°47'W., on a true line, bet. secs. 17 and 20,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked



80.10 dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.,  
and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high,  
N. of cor.

80.10 The cor. of secs. 17, 18, 19 and 20.  
Land, rolling.  
Soil, sandy; 2nd and 3rd rate.  
No timber.  
Undergrowth, greasewood and cactus.

40.00 West, on a true line, bet. secs. 18 and 19,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked



Chains

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

138.88 Intersect W. bdy. of Tp. 17.99 chs. S. of the old cor. of secs. 13, 18, 19 and 24, which is a stone, properly marked, set, and witnessed as described by the surveyor general.

At point of intersection  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 18 and 19, with brass cap, marked

T18N	T18N
	S18
S24	----CC
	S19
R18W	R17W
	1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E. of cor.

Land, rolling.  
Soil, sandy; 2nd and 3rd rate.  
No timber.  
Undergrowth, greasewood and cactus.

N.0°03'W., bet. secs. 17 and 18, over rolling land, through scattering undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked

	1/4
S18	S17
	1916

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap, marked

T18N	R17W
S7	S8
S18	S17
	1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.  
Soil, sandy; 3rd rate.  
No timber.  
Undergrowth, greasewood, catclaw and cactus.

East, on a random line, bet. secs. 8 and 17.

40.00 Set temp. 1/4 sec. cor.

80.06 Intersect N. and S. line 26 lks. S. of the cor. of secs. 8, 9, 16 and 17.

Thence S.89°49'W., on a true line, bet. secs. 8 and 17, over rolling land, through scattering undergrowth.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked

S	8
1/4	-----
	S 17
	1916

Subdivision of T. 18 N., R. 17 W.

Chains

60.00 dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.,  
and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high,  
N. of cor.  
80.06 Wash, course SW.  
The cor. of secs. 7, 8, 17 and 18.

Land, rolling.  
Soil, sandy; 2nd and 3rd rate.  
No timber.  
Undergrowth, greasewood and cactus.

40.00 West, on a true line, bet. secs. 7 and 18, over rolling  
land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

S 7  
-----  
1/4  
S 18  
1916

130.30 dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.,  
and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high,  
N. of cor.  
138.56 Telephone line bears N.7°40'E., and S.7°40'W.  
Intersect W. bdy. of Tp. 18.00 chs. S. of the old cor. of  
secs. 7, 12, 13 and 18, which is a stone, properly marked,  
set, and witnessed as described by the surveyor general.

At point of intersection  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for closing cor. of secs. 7 and 18, with brass  
cap, marked

T18N T18N  
S7  
S13 -----CC  
S18  
R18W R17W  
1916

dig pits, 24x18x12 ins., crosswise on each line, N. and  
S. 3 ft., and E. of post, 7 ft. dist., and raise a mound  
of earth, 4 ft. base, 2 ft. high, E. of cor.

Land, rolling.  
Soil, sandy; 3rd and 4th rate.  
No timber.  
Undergrowth, greasewood and cactus.

40.00 N.0°03'W., bet. secs. 7 and 8,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

1/4  
S7 | S8  
1916

80.00 dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,  
and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high,  
W. of cor.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 5, 6, 7 and 8, with brass cap,  
marked

T18N R17W  
S6 | S5  
-----  
S7 | S8  
1916

dig pits, 18x18x12 ins., in each sec., 5 1/2 ft. dist.,

26

Subdivision of T. 18 N., R. 17 W.

Chains

and raise a mound of earth, 4 ft. base, 2 ft. high,  
W. of cor.

Land, rolling.

Soil, sandy; 2nd and 3rd rate.

No timber.

Undergrowth, greasewood and cactus.

40.00 East, on a random line, bet. secs. 5 and 8.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.10 Intersect N. and S. line 19 lks. S. of the cor. of secs.  
4, 5, 8 and 9.

40.05 Thence S.  $89^{\circ}52'W.$ , on a true line, bet. secs. 5 and 8,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 5  
 $\frac{1}{4}$  -----  
S 8  
1916

80.10 and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.  
The cor. of secs. 5, 6, 7 and 8.

Land, rolling.

Soil, sandy; 2nd and 3rd rate.

No timber.

Undergrowth, greasewood and cactus.

40.00 West, on a true line, bet. secs. 6 and 7,  
over rolling land, through scattering undergrowth.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 6  
 $\frac{1}{4}$  -----  
S 7  
1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.

108.00 Wash, course SW.  
116.80 Telephone line bears N.  $7^{\circ}40'E.$ , and S.  $7^{\circ}40'W.$   
125.50 Telegraph line bears N.  $9^{\circ}10'E.$  and S.  $9^{\circ}10'W.$   
126.30 A. T. and S. F. Ry. track bears N.  $9^{\circ}10'E.$  and S.  $9^{\circ}10'W.$   
128.10 Telegraph line bears N.  $9^{\circ}10'E.$  and S.  $9^{\circ}10'W.$   
131.10 National highway bears NE. and SW.  
138.32 Intersect W. bdy. of Tp. 17.69 chs. S. of the old cor. of  
secs. 1, 6, 7 and 12, which is a stone, properly marked,  
set, and witnessed as described by the surveyor general.

At point of intersection:

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for closing cor. of secs. 6 and 7, with brass  
cap, marked

T18N | T18N  
S6  
S12 | ---CC  
S7  
R18W | R17W  
1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
E. of cor.

Land, rolling.

Soil, sandy; 2nd and 3rd rate.

No timber.

Undergrowth, greasewood and cactus.

Chains

40.00 N.0°03'W., on a random line, bet. secs. 5 and 6.  
 Set temp.  $\frac{1}{4}$  sec. cor.

79.60 Intersect N. bdy. of Tp. 10 lks. E. of the cor. of secs.  
 5, 6, 31 and 32, described in book "B"

Thence S.0°07'E., on a true line, bet. secs. 5 and 6,  
 over rolling land, through scattering undergrowth.

39.60 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

$\frac{1}{4}$   
 S6 | S5

1916

79.60 dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,  
 and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

The cor. of secs. 5, 6, 7 and 8.

Land, rolling.  
 Soil, sandy; 2nd and 3rd rate.  
 No timber.  
 Undergrowth, greasewood and cactus.

For table of latitudes, departures and closing errors, see  
 book "B"

General Description.

This township is level and rolling in the west part and  
 rough and mountainous in the East.

The soil is rocky and gravelly; unfit for cultivation.

There is no permanent water, no timber or evidence of  
 valuable minerals; and there are no settlers.

SUBDIVISIONS OF  
TOWNSHIP 18 NORTH, RANGE 17 WEST.

DATE    DIAGRAM.

3-3-16	3-2-16	2-19-16	2-19-16	2-18-16	2-18-16
6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
4-17-15	4-17-15	4-17-15	4-17-15	4-17-15	4-17-15

2-18-16  
2-17-16  
2-17-16  
2-17-16  
2-16-16  
2-9-16

4-17-16

Lines dated in violet were surveyed by Fred N. Wardwell,  
U. S. Surveyor.

Lines dated in blue were surveyed by Howard G. Mason,  
U. S. Transitman.

Lines dated in yellow were surveyed by Mans H. Coffin, Jr.  
U. S. Transitman.

~~FINAL OATH OF UNITED STATES SURVEYOR.~~

I, \_\_\_\_\_, U. S. Surveyor, do solemnly swear that, in pursuance of special instructions received from the U. S. Surveyor General for \_\_\_\_\_ bearing date of the \_\_\_\_\_ day of \_\_\_\_\_, 191\_\_\_\_, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of \_\_\_\_\_

\_\_\_\_\_ of the \_\_\_\_\_ Meridian, in the State of \_\_\_\_\_, which are represented in the foregoing field notes as having been executed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for \_\_\_\_\_ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

\_\_\_\_\_  
U. S. Surveyor.

Subscribed by said \_\_\_\_\_, and sworn to before me }  
this \_\_\_\_\_ day of \_\_\_\_\_, 191\_\_\_\_



APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, November 22, 1918.

The foregoing field notes of the survey of \_\_\_\_\_ the \_\_\_\_\_

SUBDIVISION LINES of \_\_\_\_\_

TOWNSHIP 18 NORTH, RANGE 17 WEST, of the \_\_\_\_\_

Gila and Salt River Base and Meridian, in the State of Arizona, executed by Mans H. Coffin, Jr., and Howard G. Mason, U.S. Transitmen, under ~~the~~ special instructions dated January 7, 1915, for Group 46, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.  
of Arizona.

~~certify that the foregoing transcript of the field notes of the above described surveys in \_\_\_\_\_ has been correctly copied from the original notes on file in this office.~~