

3198

P

Book "D"

4-679

BOOK 3198

APR 10 1916

# FIELD NOTES

RE-  
OF THE SURVEY OF THE

Gila and Salt River Meridian, thru Township 24 North,

6th. Standard Parallel North, thru Range 1 West, and

North boundary of Township 23 North, Range 1 West, and

SURVEY of

West Boundary and Subdivision Lines,

of

TOWNSHIP 24 NORTH, RANGE 1 WEST,

*Of the Gila and Salt River Base and Meridian,*

*In the State of Arizona.*

EXECUTED BY

J. P. Davis and Edward N. Thompson,

U.S. Transitmen

~~In the capacity of U.S. Surveyor~~, under instructions dated December 11, 1915,

issued by the United States Surveyor General to govern surveys included in

Group No. 52, which were approved by the Commissioner of the General Land

Office, January 26, 1916.

Survey commenced April 17, 1916.

Survey completed May 12, 1916.

Executed under Assignment  
Instructions dated Dec. 11, 1915

3198

3198

19

3198  
 Book "D"  
 Group 52 - Arizona

BOOK 3198

INDEX DIAGRAM.

| Township 24 North, Range 1 West, |    |    |    |    |    |    |    |    |    |    |    |   |
|----------------------------------|----|----|----|----|----|----|----|----|----|----|----|---|
| 8                                |    |    | 7  |    |    | 6  |    |    | 5  |    |    |   |
| 6th Standard Parallel North.     |    |    |    |    |    |    |    |    |    |    |    |   |
| 12                               | 6  | 38 | 5  | 32 | 4  | 27 | 3  | 22 | 2  | 16 | 1  | 4 |
| 39                               |    | 39 |    | 33 |    | 27 |    | 22 |    | 16 |    |   |
| 13                               | 7  | 39 | 8  | 34 | 9  | 28 | 10 | 22 | 11 | 17 | 12 | 4 |
| 40                               |    | 40 |    | 34 |    | 28 |    | 23 |    | 17 |    |   |
| 13                               | 18 | 41 | 17 | 35 | 16 | 29 | 15 | 23 | 14 | 18 | 13 | 3 |
| 42                               |    | 41 |    | 35 |    | 29 |    | 24 |    | 18 |    |   |
| 14                               | 19 | 42 | 20 | 35 | 21 | 30 | 22 | 24 | 23 | 19 | 24 | 3 |
| 43                               |    | 43 |    | 36 |    | 30 |    | 25 |    | 19 |    |   |
| 14                               | 30 | 44 | 29 | 36 | 28 | 31 | 27 | 25 | 26 | 20 | 25 | 2 |
| 45                               |    | 44 |    | 37 |    | 31 |    | 26 |    | 20 |    |   |
| 15                               | 31 | 45 | 32 | 37 | 33 | 32 | 34 | 26 | 35 | 21 | 36 | 1 |
| 9                                |    | 10 |    | 10 |    | 11 |    | 11 |    | 12 |    |   |

Gila and Salt River Meridian

- Surveyed under this group--notes in this book. 3198
- Resurveyed under this group--notes in this book. 3198
- ===== Surveyed in 1883.
- surveyed under this group--notes in book "E". 3199
- Surveyed in 1894.
- Resurveyed under this group--notes in book "E". 3199
- Resurveyed under this group--notes in book "F". 3200
- ===== Surveyed under this group--notes in book "F". 3200
- Surveyed under group 54.

Resurvey of G. and S. R. Mer., through T. 24 N.,  
 Resurvey of 6th St. Par. N., through R. 1 W.,  
 Resurvey of N. Bdy., T. 23 N., R. 1 W., and  
 Survey of W. Bdy. and Subdivisions of T. 24 N., R. 1 W.

Chains

Work executed jointly by U. S. Transitmen J. P. Davis  
 and Edward N. Thompson.

The instruments used are described, with record of approval by the assistant supervisor of surveys for Arizona and California, and field tests, in books A. and B. The adjustments were tested and maintained throughout the work by comparison of the results of solar observations with the true meridian, as determined by observations on Polaris.

The magnetic declination in this township is 17°35'E.

Resurvey of G. and S. R. Mer., through T. 24 N.

I begin at the old cor. of Tps. 23 and 24 N., Rs. 1 E. and 1 W., which is a post, firmly set, marked, and witnessed as described by the surveyor general, and reestablish this cor. as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked

|      |     |
|------|-----|
| T24N |     |
| RIW  | R1E |
| S36  | S31 |
| S 1  | S 6 |
| T23N |     |
| 1916 |     |

from which

- A cedar, 14 ins. diam., bears N.87°E., 13 lks. dist., marked T24N R1E S31 BT,
- A cedar, 12 ins. diam., bears S.47¼°E., 47 lks. dist., marked T23N R1E.S6 BT,
- A cedar, 10 ins. diam., bears S.58°W., 14 lks. dist., marked T23N RIW S1 BT, and
- A cedar, 18 ins. diam., bears N:44¼°W., 58 lks. dist., marked T24N RIW S36 BT.

I obliterate all evidence of old. cor.

Thence, as per instructions,  
 North on a true line, setting new cors. at intervals of 40 chs., and obliterating old cors wherever found;  
 bet. secs. 31 and 36,  
 over rolling land, through dense timber, on N. slope.

- 2.00 Brush fence bears N. and S.10°E.
- 3.50 Brush fence bears S.75°E. A wire fence, 20 lks. E. of line, runs N.
- 12.93 Draw, course W. Wire fence bears N.5°W. and S.5°E. Asc. gradually on S. slope.
- 23.00 Low spur extends W.
- 27.85 Draw, course W.
- 31.35 Low spur extends N.80°W.
- 35.83 Draw, course S.70°W.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked

|      |     |
|------|-----|
| ¼    |     |
| S36  | S31 |
| 1916 |     |

from which

- A cedar, 10 ins.diam., bears S.55¼°E., 89 lks. dist., marked ¼ S31 BT, and

2

## Resurvey of G. and S. R. Mer., through T. 24 N.

Chains

70.00 A cedar, 20 ins. diam., bears S.20 $\frac{1}{2}$ °W., 16 lks. dist.,  
marked  $\frac{1}{4}$  S36 BT.  
80.00 Head of draw, course S.85°E.  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for cor. of secs. 25, 30, 31 and 36, with brass cap,  
marked

|      |     |
|------|-----|
| T24N |     |
| RLW  | R1E |
| S25  | S30 |
| S36  | S31 |

1916

from which

A pinyon, 6 ins. diam., bears N.81°45'E., 35 lks. dist.,  
marked T24N R1E S30 BT,  
A cedar, 12 ins. diam., bears S.32°45'E., 83 lks. dist.,  
marked T24N R1E S31 BT,  
A cedar, 6 ins. diam., bears S.26 $\frac{1}{2}$ °W., 71 lks. dist.,  
marked T24N RLW S36 BT, and  
A pinyon, 7 ins. diam., bears N.80 $\frac{1}{4}$ °W., 13 lks. dist.,  
marked T24N RLW S25 BT.

Land, rolling.

Soil, gravel; 2nd rate.  
Timber, cedar and pinyon.  
Gamma grass.

40.00 North, bet. secs. 25 and 30,  
over rolling land, through dense timber.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

|               |     |
|---------------|-----|
| $\frac{1}{4}$ |     |
| S25           | S30 |

1916

from which

A cedar, 7 ins. diam., bears S.58 $\frac{1}{4}$ °E., 56 lks. dist.,  
marked  $\frac{1}{4}$  S30 BT, and  
A pinyon, 7 ins. diam., bears S.24°W., 80 lks. dist.,  
marked  $\frac{1}{4}$  S25 BT.

45.00 Head of draw, course N.20°W.  
45.50 Road bears N.20°W. and S.30°E.  
63.30 Wash, course W.  
68.45 Low spur extends W.  
72.40 Wash, course W.  
76.40 Low spur extends W.  
79.40 Draw, course N.85°W.  
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for cor. of secs. 19, 24, 25 and 30, with brass  
cap, marked

|      |     |
|------|-----|
| T24N |     |
| RLW  | R1E |
| S24  | S19 |
| S25  | S30 |

1916

from which

A pinyon, 7 ins. diam., bears N.21°45'E., 28 lks. dist.,  
marked T24N R1E S19 BT,  
A cedar, 10 ins. diam., bears S.84°E., 67 lks. dist.,  
marked T24N R1E S30 BT,  
A cedar, 30 ins. diam., bears S.78°10'W., 56 lks. dist.,  
marked T24N RLW S25 BT, and  
A cedar, 36 ins. diam., bears N.23°10'W., 36 lks. dist.,  
marked T24N RLW S24 BT.

Land, rolling. Soil, gravel; 2nd and 3rd rate.  
Timber, cedar and pinyon. Gamma grass.


Resurvey of G. and S. R. Mer., through T. 24 N. 3

Chains

North, bet. secs. 19 and 24,  
over rolling land, through dense timber.

12.50  
24.00  
40.00


Draw, course N.80°W.  
Top of rise bears N.75°E. and S.75°W.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked



from which  
A cedar, 14 ins. diam., bears N.81°E., 57 lks. dist.,  
marked 1/4 S19 BT, and  
A pinyon, 8 ins. diam., bears S.15°W., 48 lks. dist.,  
marked 1/4 S24 BT.

55.00  
72.52  
80.00

Draw, course N.75°W. Asc. gradually on S. slope.  
House bears S.72°55'W.  
Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the  
ground, for cor. of secs. 13, 18, 19 and 24, with brass  
cap, marked




from which  
A cedar, 8 ins. diam., bears N.73°45'E., 91 lks. dist.,  
marked T24N R1E S18 BT,  
A pinyon, 9 ins. diam., bears S.78°E., 24 lks. dist.,  
marked T24N R1E S19 BT,  
A pinyon, 8 ins. diam., bears S.76°W., 12 lks. dist.,  
marked T24N R1W S24 BT, and  
A cedar, 8 ins. diam., bears N.54°45'W., 31 lks. dist.,  
marked T24N R1W S13 BT.

Land, rolling.  
Soil, gravel; 3rd rate.  
Timber, cedar and pinyon.  
Gamma grass.

North, bet. secs. 13 and 18,  
over rolling land, through dense timber.

38.50  
40.00


Draw, course N.75°W.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked



from which  
A cedar, 16 ins. diam., bears N.81°20'E., ( ) lks. dist.;  
marked 1/4 S18 BT, and  
A cedar, 9 ins. diam., bears N.88°35'W., ( ) lks. dist.;  
marked 1/4 S13 BT.

59:40  
65.50  
80.00

Low spur slopes N.70°W.  
Draw, course N.75°W.  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
ground, for cor. of secs. 7, 12, 13 and 18, with brass  
cap, marked



Chains

from which

A pinyon, 8 ins. diam., bears N.15°E., 24 lks. dist., marked T24N R1E S7 BT,

A cedar, 12 ins. diam., bears S.6°15'E., 37 lks. dist., marked T24N R1E S18 BT,

A pinyon, 9 ins. diam., bears S.70°15'W., 95 lks. dist., marked T24N R1W S13 BT, and

A cedar, 9 ins. diam., bears N.61°30'W., 50 lks. dist., marked T24N R1W S12 BT.

Land, rolling.

Soil, gravel; 3rd rate.

Timber, cedar and pinyon.

Gamma grass.

40.00

North, bet. secs. 7 and 12,

over rolling land, through dense timber.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked

1/4

S12 | S7

1916

from which

A cedar, 24 ins. diam., bears S.57 1/2°E., 130 lks. dist., marked 1/4 S7 BT, and

A cedar, 8 ins. diam., bears S.27°W., 169 lks. dist., marked 1/4 S12 BT.

41.00

Road bears N.75°W. and S.75°E. Draw, course N.75°W.

57.80

Draw, course S.80°E.

77.90

Draw, course N.75°E.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, with brass cap, marked

T24N

R1W | R1E

S1 | S6

S12 | S7

1916

from which

A cedar, 10 ins. diam., bears N.41 1/4°E., 36 lks. dist., marked T24N R1E S6 BT,

A cedar, 24 ins. diam., bears S.56°10'E., 26 lks. dist., marked T24N R1E S7 BT,

A pinyon, 7 ins. diam., bears S.33°45'W., 85 lks. dist., marked T24N R1W S12 BT, and

A pinyon, 12 ins. diam., bears N.32°50'W., 21 lks. dist., marked T24N R1W S1 BT.

Land, rolling.

Soil, gravel; 3rd rate.

Timber, cedar and pinyon.

Gamma grass.

12.50

North, bet. secs. 1 and 6,

over rolling land, through dense timber.

40.00

Draw, course S.85°E.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked

1/4

S1 | S6

1916

Resurvey of G. and S. R. Mer., through T. 24 N.

Chains

54.50  
80100


from which

A cedar, 9 ins. diam., bears S.48°E., 35 lks. dist., marked  $\frac{1}{4}$  S6 BT, and

A cedar, 10 ins. diam., bears S.55 $\frac{1}{4}$ °W., 74 lks. dist., marked  $\frac{1}{4}$  S1 BT.

Low spur extends NE.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of Tps. 24 and 25 N., Rs. 1 E. and 1 W., with brass cap, marked



T24N  
1916

from which

A cedar, 14 ins. diam., bears N.64°E., 15 lks. dist., marked T25N R1E S31 BT,

A cedar, 10 ins. diam., bears S.48°E., 44 lks. dist., marked T24N R1E S6 BT,

A cedar, 14 ins. diam., bears S.56 $\frac{1}{2}$ °W., 37 lks. dist., marked T24N RLW S1 BT, and

A cedar, 12 ins. diam., bears N.31 $\frac{1}{2}$ °W., 81 lks. dist., marked T25N RLW S36 BT.

Land, rolling.

Soil, gravel; 3rd rate.

Timber, cedar and pinyon.

Gamma grass.

Resurvey of 6th St. Par. N., through R. 1 W.

At a point 4 lks. S. of the standard cor. of Tps. 24 and 25 N., Rs. 1 E. and 1 W., hereinbefore described, I deflect from the meridian an angle of 89°58.2' to the West.

Thence, as per instructions, I proceed with the resurvey of 6th St. Par. N., setting new standard cors. at intervals of 40 chs.; and, investigation having shown that owing to the condition of the S. bdy. of T. 24 N., R. 1 W., this township will be subdivided from N. to S., marking the standard cors. to refer to the area S. of the parallel.

N.89°58'W., on the secant, S. of sec. 36, over rolling land, through scattering timber and undergrowth.


8.00 Enter dense timber.

32.90 Leave timber, bearing NE. and SW. Thence across open flat.

38.00 Road bears N.20°E. and S.20°W. Draw, course N.60°E.

40.00 (N. 2 lks. from the secant)

Set an iron post, 3 ft. long, 1 in. diam., for standard  $\frac{1}{4}$  sec. cor. and  $\frac{1}{4}$  sec. cor. of sec. 1, with brass cap, marked



1916

from which


A cedar, 16 ins. diam., bears N.15°E., 252 lks. dist., marked SC  $\frac{1}{4}$  S36 BT, and

A cedar, 14 ins. diam., bears S.55 $\frac{1}{4}$ °E., 184 lks. dist., marked  $\frac{1}{4}$  S1 BT.

Chains

73.50  
80.00

Enter dense timber.  
Draw, course N.20°E.  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of secs. 35 and 36 and cor. of secs. 1 and 2, with brass cap, marked




from which  
A cedar, 8 ins. diam., bears N.33°E., 31 lks. dist., marked SC T25N RLW S36 BT,  
A cedar, 14 ins. diam., bears S.42½°E., 37 lks. dist., marked T24N RLW S1 BT,  
A pinyon, 8 ins. diam., bears S.47½°W., 55 lks. dist., marked T24N RLW S2 BT, and  
A cedar, 30 ins. diam., bears N.26°W., 75 lks. dist., marked SC T25N RLW S35 BT.

Land, rolling.  
Soil, gravelly; 2nd rate.  
Timber, cedar and pinyon.  
Undergrowth, quinine and algerita.  
Gramma grass.

17.00  
40.00


N.89°59'W., on the secant, through sec. 35, over rolling land, through dense timber, and scattering undergrowth.  
Draw, course NE.  
(S. 1 lk. from the secant)  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard ¼ sec. cor., and ¼ sec. cor. of sec. 2, with brass cap, marked



from which  
A cedar, 7 ins. diam., bears N.36°45'W., 38 lks. dist., marked SC ¼ S35 BT, and  
A cedar, 16 ins. diam., bears S.65°45'W., 30 lks. dist., marked ¼ S2 BT.

46.00  
71.30  
80.00

Desc. on SW. slope.  
Draw, course S.  
(S. 2 lks. from the secant)  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of secs. 34 and 35 and cor. of secs. 2 and 3, with brass cap, marked



from which  
A cedar, 24 ins. diam., bears N.17°45'E., 14 lks. dist., marked SC T25N RLW S35 BT,  
A cedar, 10 ins. diam., bears S.58°45'E., 50 lks. dist., marked T24N RLW S2 BT,  
A pinyon, 7 ins. diam., bears S.22°W., 111 lks. dist., marked T24N RLW S3 BT, and  
A pinyon, 6 ins. diam., bears N.55°W., 43 lks. dist., marked SC T25N RLW S34 BT.

Land, rolling. Soil, gravelly; 3rd rate.  
Timber, cedar and pinyon. Undergrowth, algerita.



Resurvey of 6th St. Par. N., through R. 1 W.

Chains

N.89°59'W., on the secant, through sec. 34,  
 over rolling land, through dense timber and scattering  
 undergrowth.  
 40.00 (S. 3 lks. from the secant)  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for standard  $\frac{1}{4}$  sec. cor. and  $\frac{1}{4}$  sec. cor. of sec.  
 3, with brass cap, marked

SC  
 S34  
 $\frac{1}{4}$  -----  
 S 3  
 1916

from which  
 A cedar, 8 ins. diam., bears N.28°W., 108 lks. dist.,  
 marked SC  $\frac{1}{4}$  S34 BT, and  
 A cedar, 9 ins. diam., bears S.71 $\frac{1}{2}$ °E., 29 lks. dist.,  
 marked  $\frac{1}{4}$  S3 BT.

57.60 Draw, course NW.  
 80.00 (S. 3 lks. from the secant)  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
 ground, for standard cor. of secs. 33 and 34 and cor. of  
 secs. 3 and 4, with brass cap, marked

S C  
 T25N | RLW  
 S33 | S34  
 -----  
 S4 | S3  
 T24N  
 1916

from which  
 A cedar, 20 ins. diam., bears N.63 $\frac{1}{2}$ °E., 279 lks. dist.,  
 marked SC T25N RLW S34 BT,  
 A cedar, 24 ins. diam., bears S.19 $\frac{1}{4}$ °E., 162 lks. dist.,  
 marked T24N RLW S3 BT,  
 A cedar, 8 ins. diam., bears S.72°W., 75 lks. dist.,  
 marked T24N RLW S4 BT, and  
 A cedar, 7 ins. diam., bears N.28 $\frac{1}{2}$ °W., 63 lks. dist.,  
 marked SC T25N RLW S33 BT.

Land, rolling.  
 Soil; gravelly; 2nd rate.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita.  
 Gramma grass.

-----  
 West, on the secant, through sec. 33,  
 over rolling land, through cedar timber.  
 1.90 Grand Canyon road bears N.15°E. and S.15°W.  
 11.70 Draw, course N.  
 40.00 (S. 3 lks. from the secant)  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for standard  $\frac{1}{4}$  sec. cor., and  $\frac{1}{4}$  sec. cor. of  
 sec. 4, with brass cap, marked

SC  
 S33  
 $\frac{1}{4}$  -----  
 S 4  
 1916

from which  
 A cedar, 10 ins. diam., bears N.4 $\frac{1}{4}$ °W., 99 lks. dist.,  
 marked SC  $\frac{1}{4}$  S 33 BT, and  
 A cedar, 9 ins. diam., bears S.18°E., 168 lks. dist.,  
 marked  $\frac{1}{4}$  S4 BT.

64.00 Draw, course N.20°E.  
 80.00 (S. 2 lks. from the secant)  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
 ground, for standard cor. of secs. 32 and 33 and cor. of  
 secs. 4 and 5, with brass cap, marked

Chains

|      |     |
|------|-----|
| S C  |     |
| T25N | RLW |
| S32  | S33 |
| S5   | S4  |
| T24N |     |
| 1916 |     |

from which

- A cedar, 14 ins. diam., bears N.62°45'E., 62 lks. dist., marked SC T25N RLW S33 BT,
- A cedar, 36 ins. diam., bears S.66°E., 166 lks. dist., marked T24N RLW S4 BT,
- A cedar, 16 ins. diam., bears S.56¼°W., 48 lks. dist., marked T24N RLW S5 BT, and
- A cedar, 9 ins. diam., bears N.77½°W., 49 lks. dist., marked SC T25N RLW S32 BT.

Land, rolling.

Soil, gravelly; 2nd rate.  
 Timber, cedar and pinyon.  
 Gramma grass.

S.89°59'W., on the secant, through sec. 32, over rolling land, through dense timber and scattering undergrowth.

40.00 (S. 1 lk. from the secant)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard ¼ sec. cor., and ¼ sec. cor. of sec. 5, with brass cap, marked

|      |       |
|------|-------|
| SC   |       |
| S32  |       |
| ¼    | ----- |
| S 5  |       |
| 1916 |       |

from which

- A pinyon, 7 ins. diam., bears N.30¼°W., 22 lks. dist., marked SC ¼ S32 BT, and
- A pinyon, 8 ins. diam., bears S.20½°E., 37 lks. dist., marked ¼ S5 BT.

49.00 Draw, course N.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of secs. 31 and 32, and cor. of secs. 5 and 6, with brass cap, marked

|      |     |
|------|-----|
| S C  |     |
| T25N | RLW |
| S31  | S32 |
| S6   | S5  |
| T24N |     |
| 1916 |     |

from which

- A cedar, 14 ins. diam., bears N.40½°E., 51 lks. dist., marked SC T25N RLW S32 BT,
- A cedar, 14 ins. diam., bears S.64°E., 43 lks. dist., marked T24N RLW S5 BT,
- A cedar, 16 ins. diam., bears S.63°45'W., 18 lks. dist., marked T24N RLW S6 BT, and
- A cedar, 10 ins. diam., bears N.12¼°W., 75 lks. dist., marked SC T25N RLW S31 BT.

Land, rolling.

Soil, gravelly; 2nd rate. Clay sub-soil.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita.  
 Gramma grass.

S.89°59'W., on the secant, S. of sec. 31, over rolling land, through dense timber.

22.00 Draw, course S.10°W.

Resurvey of 6th St. Par. N., through R. 1 W. 9

Chains

40.00

(N. 2 lks. from the secant)  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard  $\frac{1}{4}$  sec. cor., and  $\frac{1}{4}$  sec. cor. of sec. 6, with brass cap, marked

SC  
S31  
 $\frac{1}{4}$  -----  
S 6  
1916

from which  
A cedar, 8 ins. diam., bears N.76°W., 35 lks. dist., marked SC  $\frac{1}{4}$  S31 BT, and  
A cedar, 12 ins. diam., bears S.74°W., 46 lks. dist., marked  $\frac{1}{4}$  S6 BT.

56.50

Draw, course S.20°W. Asc. on E. slope, very gradually.

78.00

Top of ascent.

80.00

(N. 4 lks. from the secant)  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of Tps. 25 N., Rs. 1 and 2 W., and cor. of Tps. 24 N., Rs. 1 and 2 W., with brass cap, marked

S C  
T25N  
R2W | R1W  
S36 | S31  
-----  
S1 | S6  
T24N  
1916

from which  
A cedar, 16 ins. diam., bears N.52°E., 13 lks. dist., marked SC T25N R1W S31 BT,  
A pinyon, 7 ins. diam., bears S.26°E., 40 lks. dist., marked T24N R1W S6 BT,  
A cedar, 10 ins. diam., bears S.25°W., 60 lks. dist., marked T24N R2W S1 BT, and  
A cedar, 20 ins. diam., bears N.34 $\frac{1}{2}$ °W., 9 lks. dist., marked SC T25N R2W S36 BT.  
I raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

Land, rolling.  
Soil, 3rd rate.  
Timber, cedar and pinyon.  
Gamma grass.

Resurvey of N. Bdy., T. 23 N., R. 1 W.

I begin at the old cor. of Tps. 23 and 24 N., Rs. 1 and 2 W., which is a limestone, 12x10x8 ins. above ground, marked and witnessed as described by the surveyor general, which I reestablish as follows:

With stone, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked

T24N  
R2W | R1W  
S36 | S31  
-----  
S1 | S6  
T23N  
1916

Thence, on true courses computed from fallings of random lines,

S.87°00'E., on N. bdy. of sec. 6,

Chains

over rolling hills, through cedar and pinyon timber and scattering undergrowth. Asc. gradually on SW. slope.

14.00 Top of rise bears NW. and SE. Desc. gradually on broken NE. slope.

39.64 The old  $\frac{1}{4}$  sec. cor., which is a limestone, 14x12x10 ins. above ground, marked and witnessed as described by the surveyor general. Reestablish same as  $\frac{1}{4}$  sec. cor. of secs. 6 and 31 by marking another bearing tree as hereinafter described. Destroy marking on old bearing tree NW of cor.

From cor.,  
 A cedar, 6 ins. diam., bears S.11°45'W., 89 lks. dist., which I mark  $\frac{1}{4}$  S6 BT. A cedar, 6 ins. diam., brs. S. 45° E., 87 lks. dist.; mkd.  $\frac{1}{4}$  S 6 B T. (original BT.)  
 Thence N.89°38'E., on E. half of N. bdy. of sec. 6.

2.70 Draw, course NW. Asc. 95 ft.

15.40 Spur slopes SW.

25.40 Ridge bears NW. and SE. Desc. gradually on NE. slope.

40.01 The old cor. of secs. 5, 6, 31 and 32, which is a decayed cedar, marked and witnessed as described by the surveyor general. The bearing tree in sec. 32 is destroyed. I reestablish cor. as follows:  
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked

|      |     |
|------|-----|
| T24N | RLW |
| S31  | S32 |
| S6   | S5  |
| T23N |     |

1916

from which  
 A pinyon, 6 ins. diam., bears N.11°30'E., 63 lks. dist. which I mark T24N RLW S32 BT.  
 The other old bearing trees are in good condition.

Land, rolling hills.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, quinine and algerita.

S.85°08'E., on N. bdy. of sec. 5,  
 over rolling land, through cedar and pinyon timber and scattering undergrowth, descending gradually on NE. slope.

7.40 Draw, course NE.

39.84 The old  $\frac{1}{4}$  sec. cor., which is a limestone, 10x8x6 ins. above ground, marked and witnessed as described by the surveyor general. hereinafter pertaining to sec. 5,

Thence N.89°40'E., on N. bdy. of E. half of sec. 5.

16.30 Leave timber, and cross valley, bearing NW.

37.30 Leave valley and enter timber.

40.04 The old cor. of secs. 4, 5, 32 and 33, which is a limestone, 14x8x6 ins. above ground, marked and witnessed as described by the surveyor general. hereinafter pertaining solely to secs. 4 and 5.

N.89°46'E., on N. bdy. of sec. 4,  
 over rolling land, through cedar and pinyon timber and scattering undergrowth.

18.00 Leave timber, and enter valley, bearing NW.

35.40 Road bears NW. and SE.

37.70 Wash, course NW.

40.05 The old  $\frac{1}{4}$  sec. cor., which is a sandstone, 8x8x6 ins. above ground, marked and witnessed as described by the surveyor general, hereinafter pertaining solely to sec. 4.

Chains

1.20 Thence S.89°04'E., on N. bdy. of E. half of sec. 4.  
 Wash, course SW.  
 7.95 Wash, course NW.  
 19.95 Road bears NW. and SE.  
 40.00 The old cor. of secs. 3, 4, 33 and 34, which is a malpais stone, 10x6x6 ins. above ground, marked and witnessed as described by the surveyor general, hereinafter pertaining solely to secs. 3 and 4.  
 Land, W. 60 chs. rolling and E. part level.  
 Soil, rocky; 3rd rate, on rolling land, and sandy loam, 1st rate, on level land.  
 Timber. cedar and pinyon.  
 Undergrowth, quinine and algerita.

40.28 N.89°56'E., on N. bdy. of sec. 3,  
 over gently rolling land, through scattering cedar timber.  
 The old  $\frac{1}{4}$  sec. cor., which is a decayed post, marked and witnessed as described by the surveyor general.  
 I reestablish same as  $\frac{1}{4}$  sec. cor. of sec. 3 only, as follows:  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap, marked

$\frac{1}{4}$  S3  
1916

from which  
 A cedar, 14 ins. diam., bears S.26 $\frac{1}{2}$ °W., 60 lks. dist., marked  $\frac{1}{4}$  S3 BT, and  
 A cedar, 7 ins. diam., bears S.37 $\frac{1}{2}$ °E., 48 lks. dist., marked  $\frac{1}{4}$  S3 BT.

20.42 Thence, S.89°56'E., on N. bdy. of E. half of sec. 3  
 Draw, course S.75°W.  
 40.04 The old cor. of secs. 2, 3, 34 and 35, which is a limestone, 12x8x8 ins. above ground, marked and witnessed as described by the surveyor general.  
 Land, gently rolling.  
 Soil, gravelly; 2nd and 3rd rate.  
 Timber, cedar.  
 Gramma grass.

10.00 S.89°33'E., on N. bdy. of sec. 2,  
 over gently rolling land, through scattering timber.  
 Draw, course SW.  
 38.00 Enter dense timber, bearing N. and S.  
 40.18 The old  $\frac{1}{4}$  sec. cor., which is a limestone 7x5x5 ins. above ground, marked and witnessed as described by the surveyor general; Reestablish cor. to refer to sec. 2 only by marking trees as follows:  
 A pinyon, 7 ins. diam., bears S.78°E., 26 lks. dist., marked by me  $\frac{1}{4}$  S2 BT, and  
 A pinyon, 6 ins. diam., bears S.26 $\frac{1}{2}$ °W., 104 lks. dist., marked by me  $\frac{1}{4}$  S2 BT.

15.25 Thence S.86°41'E., on N. bdy. of E. half of sec. 2.  
 Head of draw, course S.75°E.  
 19.70 Asc. gradually along SW. slope.  
 32.70 Wash, course S.75°W. Asc.  
 40.66 The old cor. of secs. 1, 2, 35 and 36, which is a limestone, 8x7x6 ins. above ground, marked and witnessed as described by the surveyor general. The old bearing trees are decayed, so I mark others as follows:  
 A pinyon, 7 ins. diam., bears S.14 $\frac{1}{2}$ °E., 54 lks. dist., marked T23N RLW S1 BT, and  
 A cedar, 24 ins. diam., bears S.45°W., 28 lks. dist., marked T23N RLW S2 BT.  
 Land, rolling. Soil, gravelly; 3rd rate.  
 Timber, cedar and pinyon. Gramma grass.

Chains

S.83°41'E., on N. bdy. of sec. 1,  
 along broken SW. slope, through dense timber.  
 6.55 Wash, course S.  
 26.70 Draw, course S.20°W. Asc. 100 ft.  
 31.00 Spur slopes S.30°W. Desc. 100 ft.  
 38.00 Wash, course S.15°W. Asc. on W. slope.  
 40.11 The old  $\frac{1}{4}$  sec. cor., which is a limestone, 9x8x8 ins. above  
 ground, marked and witnessed as described by the surveyor  
 general. Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 N. of cor.

-----  
 Thence S.87°28'E., on N. bdy. of E. half of sec. 1.  
 3.80 Spur slopes S.10°W. (60 ft. above wash). Desc. 50 ft.,  
 on E. slope.  
 16.40 Wash, course S.15°W. Asc. 150 ft., on W. slope.  
 40.10 The reestablished cor. of Tps. 23 and 24 N., Rs. 1 E. and  
 1 W., hereinbefore described.

Land, rolling and broken.  
 Soil, 3rd rate.  
 Timber, cedar and pinyon.  
 Gramma grass.


-----  
 W. Boundary, T. 24 N., R. 1 W.  
 -----

Beginning at the reestablished standard cor. of Tps. 25 N.,  
 Rs. 1 and 2 W., and cor. of Tps. 24 N., Rs. 1 and 2 W.,  
 hereinbefore described;

465.56 Thence South, on a random line, bet. Rs. 1 and 2 W.  
 Fall 18 lks. W. of the reestablished cor. of Tps. 23 and  
 24 N., Rs. 1 and 2 W., hereinbefore described; which  
 gives for the true course, S.0°01'E.

Returning to point of beginning,  
 Thence, on true line, S.0°01'E., bet. secs. 1 and 6,  
 over rolling land, on SW. slope, through cedar and pinyon  
 timber and scattering undergrowth.

8.00 Thence on SE. slope.  
 18.00 Draw, course SW. Thence along SW. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which

A cedar, 20 ins. diam., bears S.32°E., 103 lks. dist.,  
 marked  $\frac{1}{4}$  S6 BT, and

A cedar, 24 ins. diam., bears S.14°45'W., 58 lks. dist.,  
 marked  $\frac{1}{4}$  S1 BT.

58.50 Desc. 80 ft., on SE. slope.  
 66.20 Draw, course SW. Thence on NW. slope.  
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 1, 6, 7 and 12, with brass cap,  
 marked



from which


A pinyon, 8 ins. diam., bears N.15°E., 48 lks. dist.,  
 marked T24N R1W S6 BT,

Chains


A cedar,, 10 ins. diam., bears S.84°30'E., 44 lks. dist., marked T24N R1W S7 BT,  
 A pinyon, 8 ins. diam., bears S.76°30'W., 61 lks. dist., marked T24N R2W S12 BT, and  
 A pinyon, 6 ins. diam., bears N.53°15'W., 54 lks. dist., marked T24N R2W S1 BT.

Land, rolling.  
 Soil, 2nd and 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita.

14.00 S.0°01'E., bet. secs. 7 and 12,  
 27.00 over rolling land, through cedar and pinyon timber and scattering undergrowth; on NW. slope.  
 35.00 Spur slopes SW. Thence along broken SW. slope.  
 40.00 Spur slopes SW. Desc. 120 ft., on SE. slope.  
 Wash, course SW. Asc. on NW. slope.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which  
 A pinyon, 6 ins. diam., bears N.37°10'E., 54 lks. dist., marked  $\frac{1}{4}$  S7 BT, and  
 A pinyon, 8 ins. diam., bears N.47°W., 27 lks. dist., marked  $\frac{1}{4}$  S12 BT.  
 41.00 Spur, 70 ft. above wash, slopes SW. Desc. 70 ft., on SE. slope.  
 47.80 Wash, course W. Asc. 100 ft., on N. slope.  
 58.50 Spur, slopes SW. Desc. on SE, slope.  
 75.00 Leave timber.  
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 7, 12, 13 and 18, with brass cap, marked



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling hills.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, quinine and algerita.

16.00 S.0°01'E., bet. secs. 13 and 18,  
 19.80 over rolling land, on SE. slope.  
 40.00 Enter valley, extending SW.  
 Road bears NW. and SE.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

54.50 Wash, course SW. Thence along broken NW. slope.

Chains

63.00 Enter timber.  
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, with brass cap, marked

|      |     |
|------|-----|
| T24N |     |
| R2W  | RLW |
| S13  | S18 |
| S24  | S19 |

1916

from which  
 A pinyon, 14 ins. diam., bears N.9°30'E., 196 lks. dist., marked T24N RLW S18 BT.  
 No other bearing trees within limits. Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling and level.  
 Soil, sandy loam; 2nd rate on level land, and rocky; 3rd rate on rolling land.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita and quinine.

S.0°01'E., bet. secs. 19 and 24, over rolling land, on NW slope, through scattering timber and undergrowth.

39.00 Draw, course NW. Thence along NE. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked

|     |     |
|-----|-----|
| ¼   |     |
| S24 | S19 |

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

79.00 Ridge, 300 ft. above draw, bears NW. and SE. Desc. on SE. slope.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, with brass cap, marked

|      |     |
|------|-----|
| T24N |     |
| R2W  | RLW |
| S24  | S19 |
| S25  | S30 |

1916

from which  
 A cedar, 8 ins. diam., bears S.58°E., 68 lks. dist., marked T24N RLW S30 BT.  
 No other bearing trees within limits. Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.


Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita and quinine.

S.0°01'E., bet. secs. 25 and 30, over rolling hills, through scattering timber and undergrowth. Desc. 130 ft., on SE. slope.


7.75 Wash, course SW. Thence along NW. slope.  
 14.00 Thence on SE. slope.  
 38.70 Ash Fork-Grand Canyon road bears NE. and SW.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked



Chains




from which  
 A cedar, 16 ins. diam., bears S.36°15'E., 127 lks. dist., marked  $\frac{1}{4}$  S30 BT.  
 No bearing tree within limits in sec. 25. Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 41.00 Draw, course SW. Thence along broken SW. slope.  
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap, marked



from which  
 A cedar, 6 ins. diam., bears N.42°40'E., 110 lks. dist., marked T24N R1W S30 BT,  
 A pinyon, 6 ins. diam., bears S.29°30'E., 129 lks. dist., marked T24N R1W S31 BT,  
 A cedar, 8 ins. diam., bears S.76°W., 186 lks. dist., marked T24N R2W S36 BT, and  
 A cedar, 36 ins. diam., bears N.9°20'W., 141 lks. dist., marked T24N R2W S25 BT.

Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita.

S.0°01'E., bet. secs. 31 and 36,  
 over rolling land, through scattering timber and undergrowth. Desc. gradually on SW. slope.  
 11.00 Draw, course NW. Asc. gradually, on NE. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



from which  
 A cedar, 6 ins. diam., bears N.79°45'E., 86 lks. dist., marked  $\frac{1}{4}$  S31 BT, and  
 A cedar, 8 ins. diam., bears S.72°30'W., 85 lks. dist., marked  $\frac{1}{4}$  S36 BT.


52.00 Spur slopes NE.  
 56.00 Draw, course NE.  
 61.00 Ridge bears NW and SE. Desc. gradually on SW. slope.  
 65.56 The reestablished cor. of Tps. 23 and 24 N., Rs. 1 and 2 W., hereinbefore described.

Land, rolling.  
 Soil, gravelly; 2nd and 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita and quinine.

Chains

From the standard cor. of secs. 35 and 36, and cor. of secs. 1 and 2, on 6th St. Par. N., hereinbefore described,

40.00 S.0°01'E., bet. secs. 1 and 2, over rolling land, through dense cedar and pinyon timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked



from which


A cedar, 22 ins. diam., bears N.83 1/2°E., 24 lks. dist., marked 1/4 S1 BT, and

A pinyon, 12 ins. diam., bears S.70 1/2°W., 68 lks. dist., marked 1/4 S2 BT.

63.50 Draw, course S.70°W.

64.00 Road bears S.70°W. and N.70°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap, marked



from which

A cedar, 12 ins. diam., bears N.60°E., 53 lks. dist., marked T24N R1W S1 BT,

A cedar, 8 ins. diam., bears S.59°50'E., 89 lks. dist., marked T24N R1W S12 BT,

A cedar, 16 ins. diam., bears S.12°45'W., 73 lks. dist., marked T24N R1W S11 BT, and

A pinyon, 12 ins. diam., bears N.48 1/2°W., 90 lks. dist., marked T24N R1W S2 BT.

Land, rolling.

Soil, gravelly; 2nd rate.

Timber, cedar and pinyon.

Buffalo grass.


40.00 East, on a random line, bet. secs. 1 and 12.

80.06 Set temp. 1/4 sec. cor.

Intersect G. and S. R. Mer. 2 lks. N. of the cor. of secs. 1, 6, 7 and 12, hereinbefore described.

Thence N.89°59'W., on a true line, bet. secs. 1 and 12, over gently rolling land, through dense timber.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked



from which

A cedar, 8 ins. diam., bears N.51°45'W., 50 lks. dist., marked 1/4 S1 BT, and

A cedar, 9 ins. diam., bears S.22°45'E., 46 lks. dist., marked 1/4 S12 BT.

80.06 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.

Soil, gravelly; 2nd rate.

Timber, cedar and pinyon.

Buffalo grass.

Chains

S.0°01'E., bet. secs. 11 and 12,  
 over rolling land, through dense timber.

5.00 Road bears N.85°W. and S.85°E.

11.20 Draw, course S.85°W. A reservoir, 3 chs. wide, 5 chs.  
 long, bears E., 2 chs. dist.

16.00 Low spur extends W.

20.00 Draw, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

$\frac{1}{4}$   
 S11 | S12  
 1916

from which  
 A cedar, 30 ins. diam., bears N.73°E., 50 lks. dist.,  
 marked  $\frac{1}{4}$  S12 BT, and  
 A cedar, 9 ins. diam., bears S.22°45'W., 32 lks. dist.,  
 marked  $\frac{1}{4}$  S11 BT.

78.90 Draw, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 11, 12, 13 and 14, with brass  
 cap, marked

T24N | RLW  
 S11 | S12  
 ---  
 S14 | S13  
 1916

from which  
 A cedar, 16 ins. diam., bears N.58°45'E., 111 lks. dist.,  
 marked T24N RLW S12 BT,  
 A cedar, 36 ins. diam., bears S.19°E., 23 lks. dist.,  
 marked T24N RLW S13 BT,  
 A pinyon, 7 ins. diam., bears S.47°W., 119 lks. dist.,  
 marked T24N RLW S14 BT, and  
 A cedar, 24 ins. diam., bears N.79°W., 72 lks. dist.,  
 marked T24N RLW S11 BT.

Land, rolling.  
 Soil, gravelly; 2nd rate.  
 Timber, cedar and pinyon.  
 Buffalo grass.

-----

East, on a randomline, bet. secs. 12 and 13.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 Intersect G. and S. R. Mer. 4 lks. N. of the cor. of secs.  
 7, 12, 13 and 18, hereinbefore described.

Thence N.89°58'W., on a true line, bet. secs. 12 and 13,  
 over rolling land, through dense timber.

16.15 Draw, course S.70°W.

21.65 Spur slopes SW.

34.15 Draw, course S.70°W.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 12  
 $\frac{1}{4}$  -----  
 S 13  
 1916

from which  
 A cedar, 14 ins. diam., bears N.9°W., 105 lks. dist.,  
 marked  $\frac{1}{4}$  S12 BT, and  
 A cedar, 16 ins. diam., bears S.22 $\frac{1}{2}$ °W., 44 lks. dist.,  
 marked  $\frac{1}{4}$  S13 BT.


62.00 Road bears N. and S. Draw, course S.25°W.

78.95 Draw, course N.85°W.

79.96 The cor. of secs. 11, 12, 13 and 14.  
 Land, rolling. Soil, gravelly; 2nd rate.  
 Timber, cedar and pinyon. Buffalo grass.


Chains

S.0°01'E., bet. secs. 13 and 14,  
 over rolling land, through cedar and pinyon timber and  
 scattering undergrowth. Asc. 80 ft., on gentle NE. slope.  
 16.00 Low ridge bears E. and W. Desc. 65 ft., on S. slope.  
 30.00 Wash, course W. Small reservoir on line. Asc. on N. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



from which  
 A pinyon, 12 ins diam., bears S.22°10'E., 35 lks. dist.,  
 marked  $\frac{1}{4}$  S13 BT, and  
 A pinyon, 6 ins. diam., bears S.12°W., 27 lks. dist.,  
 marked  $\frac{1}{4}$  S14 BT.

46.00 Spur extends W. Desc. on gentle S. slope.  
 53.00 Head of draw, course W. Thence along W. slope.  
 70.00 Wire fence bears S. from a point 50 lks. E. of line.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 13, 14, 23 and 24, with brass  
 cap, marked




from which  
 A pinyon, 14 ins. diam., bears N.66°45'E., 64 lks. dist.,  
 marked T24N R1W S13 BT,  
 A pinyon, 8 ins. diam., bears S.73°45'E., 86 lks. dist.,  
 marked T24N R1W S24 BT,  
 A cedar, 6 ins. diam., bears S.43°20'W., 68 lks. dist.,  
 marked T24N R1W S23 BT, and  
 A cedar, 36 ins. diam., bears N.56°W., 60 lks. dist.,  
 marked T24N R1W S14 BT.

Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita.

40.00 East, on a random line, bet. secs. 13 and 24.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.02 Intersect G. and S. R. Mer. 5 lks. N. of the cor. of secs.  
 13, 18, 19 and 24, hereinbefore described.

40.01 Thence N.89°58'W., on a true line, bet. secs. 13, and 24,  
 over rolling land, through cedar and pinyon timber and  
 scattering undergrowth. Desc. on gentle W. slope.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which  
 A pinyon, 6 ins. diam., bears N.33°E., 47 lks. dist.,  
 marked  $\frac{1}{4}$  S13 BT, and  
 A pinyon, 10 ins. diam., bears S.34°15'W., 119 lks. dist.,  
 marked  $\frac{1}{4}$  S24 BT.

48.00 End of W. slope.  
 57.25 Wire fence bears NW. and SE.  
 69.90 Road bears NW. and SE.  
 76.30 Wire fence bears N. and S.  
 78.00 Top of rise bears N. and S.  
 80.02 The cor. of secs. 13, 14, 23 and 24.


Land, rolling. Soil, rocky; 3rd rate.  
 Timber, cedar and pinyon. Undergrowth, quinine.

Chains

S.0°01'E., bet. secs. 23 and 24,  
 over rolling land, through dense timber.  
 14.82 Draw, course N.70°W.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the  
 ground, surrounded by a mound of stone, (impracticable  
 to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with  
 brass cap, marked



from which  
 A cedar, 14 ins. diam., bears N.41 $\frac{1}{4}$ °E., 61 lks. dist.,  
 marked  $\frac{1}{4}$  S24 BT, and  
 A cedar, 10 ins. diam., bears S.55 $\frac{1}{2}$ °W., 27 lks. dist.,  
 marked  $\frac{1}{4}$  S23 BT.  
 65.00 Draw, course NW.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 23, 24, 25 and 26, with brass  
 cap, marked




from which  
 A cedar, 26 ins. diam., bears N.22°E., 25 lks. dist.,  
 marked T24N R1W S24 BT,  
 A cedar, 10 ins. diam., bears S.22 $\frac{1}{2}$ °E., 25 lks. dist.,  
 marked T24N R1W S25 BT,  
 A cedar, 10 ins. diam., bears S.40°W., 15 lks. dist.,  
 marked T24N R1W S26 BT, and  
 A cedar, 12 ins. diam., bears N.40 $\frac{1}{4}$ °W., 20 lks. dist.,  
 marked T24N R1W S23 BT.

Land, rolling.  
 Soil, gravelly; 2nd rate.  
 Timber, cedar and pinyon.  
 Buffalo grass.

-----  
 East, on a random line, bet. secs. 24 and 25.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.00 Intersect G. and S. R. Mer. at the cor. of secs.19, 24,  
 25 and 30, hereinbefore described.

Thence West, on a true line, bet. secs. 24 and 25,  
 over rolling land, through dense timber.  
 2.60 Draw, course N.65°W.  
 17.50 Draw, course N.30°W.  
 18.30 Road bears N.30°W.  
 29.00 Wash, course N.15°E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which  
 A pinyon, 5 ins. diam., bears S.8 $\frac{1}{4}$ °E., 49 lks. dist.,  
 marked  $\frac{1}{4}$  S25 BT, and  
 A pinyon, 7 ins. diam., bears N.79 $\frac{1}{2}$ °W., 31 lks. dist.,  
 marked  $\frac{1}{4}$  S24 BT.  
 48.50 Draw, course N.  
 74.50 Wagon trail, new, bears N.20°E. and S.20°W.  
 80.00 The cor. of secs. 23, 24, 25 and 26.

Land, rolling. Soil, gravelly; 2nd rate.  
 Timber, cedar and pinyon. Buffalo grass.


-----

Chains

S.0°01'E., bet. secs. 25 and 26,  
 over rolling land, through cedar and pinyon timber and  
 scattering undergrowth, along NE. slope.  
 6.00 Spur slopes NW. Thence along SW. slope.  
 30.00 Draw, course SE. Thence along SE. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



from which  
 A cedar, 10 ins. diam., bears N.37°50'E., 52 lks. dist.,  
 marked  $\frac{1}{4}$  S25 BT, and  
 A cedar, 10 ins. diam., bears S.88°45'W., 41 lks. dist.,  
 marked  $\frac{1}{4}$  S26 BT.  
 70.00 Wash, course SW. Asc. on NW. slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 25, 26, 35 and 36, with brass  
 cap, marked




from which  
 A pinyon, 10 ins. diam., bears N.85°25'E., 100 lks. dist.,  
 marked T24N R1W S25 BT,  
 A pinyon, 8 ins. diam., bears S.11°30'E., 96 lks. dist.,  
 marked T24N R1W S36 BT,  
 A pinyon, 12 ins. diam., bears S.68°35'W., 54 lks. dist.,  
 marked T24N R1W S35 BT, and  
 A pinyon, 10 ins. diam., bears N.6°35'W., 74 lks. dist.,  
 marked T24N R1W S26 BT.

Land, rolling.  
 Soil, gravelly; 2nd rate. Limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, quinine and algerita.

40.00 East, on a random line, bet. secs. 25 and 36,  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.00 Intersect G. and S. R. Mer. 4 lks. S. of the cor. of secs.  
 25, 30, 31 and 36, hereinbefore described.

Thence S.89°58'W., on a true line, bet. secs. 25 and 36,  
 over gently rolling land, through cedar and pinyon timber  
 and scattering undergrowth, on SW. slope.  
 2.10 Wire fence bears NW. and SE.  
 7.90 Wash, course NW. Thence on NE. slope.  
 13.00 Thence on SW. slope.  
 30.80 Wire fence bears NE. and SW.  
 39.20 Wash, course NW. Thence on NW. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which  
 A cedar, 10 ins. diam., bears N.80°30'W., 106 lks. dist.,  
 marked  $\frac{1}{4}$  S25 BT, and  
 A pinyon, 10 ins. diam., bears S.24°15'W., 110 lks. dist.,  
 marked  $\frac{1}{4}$  S36 BT.  
 52.00 Low spur extends NW. Thence along SW. slope.  
 58.00 Wash, course NW. Thence on NW. slope.  
 80.00 The cor. of secs. 25, 26, 35 and 36.  
 Land, rolling. Soil, gravelly; 3rd rate.  
 Timber, cedar and pinyon. Undergrowth, algerita and quinine.

Chains

40.00 S.0°01'E., on a random line, bet. secs. 35 and 36.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 73.73 Intersect S. bdy. of Tp. 35 lks. W. of the cor. of secs.  
 1, 2, 35 and 36, hereinbefore described.

Thence N.0°17'W., on a true line, bet. secs. 35 and 36,  
 over rolling land, through dense timber. Desc. gradually  
 80 ft.

11.40 Draw, course S.35°W. Asc. gradually, 130 ft.  
 33.73 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
 ground, surrounded by a mound of stone, (impracticable  
 to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with  
 brass cap, marked



from which

A cedar, 18 ins. diam., bears N.48 $\frac{1}{2}$ °E., 88 lks. dist.,  
 marked  $\frac{1}{4}$  S36 BT, and

A cedar, 8 ins. diam., bears S.70 $\frac{1}{4}$ °W., 41 lks. dist.,  
 marked  $\frac{1}{4}$  S35 BT.

38.83 Draw, course N.80°W.

49.35 Low spur slopes W.

67.50 Draw, course W.

70.75 Low spur slopes W.

73.73 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.

Soil, 3rd rate; dolomite formation.

Timber, cedar and pinyon.


Buffalo grass.

From the standard cor. of secs. 34 and 35, and cor. of  
 secs. 2 and 3, on 6th St. Par. N., hereinbefore described,

S.0°01'E., bet. secs. 2 and 3,  
 over rolling land, through dense timber.

34.50 Draw, course S.60°E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which

A pinyon, 16 ins. diam., bears S.53 $\frac{1}{4}$ °E., 20 lks. dist.,  
 marked  $\frac{1}{4}$  S2 BT, and

A pinyon, 12 ins. diam., bears N.43 $\frac{1}{4}$ °W., 30 lks. dist.,  
 marked  $\frac{1}{4}$  S3 BT.

64.00 Draw, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
 ground, for cor. of secs. 2, 3, 10 and 11, with brass  
 cap, marked



from which

A pinyon, 10 ins. diam., bears N.47°E., 70 lks. dist.,  
 marked T24N R1W S2 BT,

A pinyon, 7 ins. diam., bears S.73 $\frac{1}{4}$ °E., 70 lks. dist.,  
 marked T24N R1W S11 BT,

A cedar, 40 ins. diam., bears S.26°W., 125 lks. dist.,  
 marked T24N R1W S10 BT, and

A pinyon, 10 ins. diam., bears N.12°W., 102 lks. dist.,  
 marked T24N R1W S3 BT.

Chains

Land, rolling.  
Soil, gravelly; clay sub-soil; 3rd rate.  
Timber, cedar and pinyon.  
Buffalo grass.

40.00 East, on a random line, bet. secs. 2 and 11.  
Set temp. 1/4 sec. cor.  
80.00 Intersect N. and S. line at the cor. of secs. 1, 2, 11 and 12.

22.00 Thence West, on a true line, bet. secs. 2 and 11,  
over rolling land, through dense timber.  
23.00 Enter draw from SE., course W.  
23.00 Leave draw, course SW., at junction with draw from NE.  
A road bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

S 2  
1/4 -----  
S 11  
1916

from which  
A cedar, 36 ins. diam., bears N.26°45'W., 27 lks. dist.,  
marked 1/4 S2 BT, and  
A cedar, 10 ins. diam., bears S.43°45'E., 11 lks. dist.,  
marked 1/4 S11 BT.

78.50 Draw, course S.25°W.  
80.00 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.  
Soil, 2nd rate.  
Timber, cedar and pinyon.  
Buffalo grass.

3.00 S.0°01'E., bet. secs. 10 and 11,  
over rolling land, through scattering timber, on gentle  
S. slope.

15.50 Leave timber. Thence across valley extending SW.  
15.60 Wash, course SW.  
16.60 Road bears NE. and SW.  
18.00 Enter timber, on NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

1/4  
S10 | S11  
1916

from which  
A cedar, 10 ins. diam., bears S.59°45'E., 74 lks. dist.,  
marked 1/4 S11 BT, and  
A cedar, 6 ins. diam., bears S.19°20'W., 72 lks. dist.,  
marked 1/4 S10 BT.

59.00 Low spur extends W. Thence on gentle SW. slope.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 10, 11, 14 and 15, with brass  
cap, marked

T24N | R1W  
S10 | S11  
-----  
S15 | S14  
1916

from which  
A cedar, 6 ins. diam., bears N.72°20'E., 88 lks. dist.,  
marked T24N R1W S11 BT,  
A cedar, 10 ins. diam., bears S.14°10'E., 302 lks. dist.,  
marked T24N R1W S10 BT,



Subdivision of T. 24 N., R. 1 W.

Chains

A pinyon, 8 ins. diam., bears S.6°30'W., 112 lks. dist., marked T24N R1W S15 BT, and  
 A cedar, 18 ins. diam., bears N.69°10'W., 67 lks. dist., marked T24N R1W S10 BT.

Land, rolling.  
 Soil, 2nd and 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita.

40.00 East, on a random line, bet. secs. 11 and 14.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.04 Intersect N. and S. line 2 lks. N. of the cor. of secs. 11, 12, 13 and 14.

Thence N.89°59'W., on a true line, bet. secs. 11 and 14, over rolling land, through scattering timber and undergrowth.


40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked  
 S 11  
 $\frac{1}{4}$  -----  
 S 14  
 1916

from which  
 A pinyon, 10 ins. diam., bears N.60°10'W., 60 lks. dist., marked  $\frac{1}{4}$  S11 BT, and  
 A pinyon, 8 ins. diam., bears S.50°30'W., 70 lks. dist., marked  $\frac{1}{4}$  S14 BT.

54.00 Ridge bears NW. and SE. Desc. 190 ft., along SW. slope.  
 80.04 The cor. of secs. 10, 11, 14 and 15.


Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita.

40.00 S.0°01'E., bet. secs. 14 and 15, over rolling land, through dense timber.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



from which  
 A pinyon, 7 ins. diam., bears S.74°E., 51 lks. dist., marked  $\frac{1}{4}$  S14 BT, and  
 A cedar, 18 ins. diam., bears N.39 $\frac{1}{2}$ °W., 75 lks. dist., marked  $\frac{1}{4}$  S15 BT.

42.95 Wash, course W.  
 64.50 Low spur extends W.  
 72.35 Draw, course W.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 14, 15, 22 and 23, with brass cap, marked



from which  
 A cedar, 16 ins. diam., bears N.77°45'E., 133 lks. dist., marked T24N R1W S14 BT,  
 A pinyon, 14 ins. diam., bears S.1°E., 37 lks. dist., marked T24N R1W S23 BT,

Chains

A cedar, 10 ins. diam., bears S.36°W., 98 lks. dist.,  
 marked T24N RLW S15 BT, and  
 A cedar, 12 ins. diam., bears N.47½°W., 80 lks. dist.,  
 marked T24N RLW S10 BT.

Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Buffalo grass.


40.00 East, on a random line, bet. secs. 14 and 23.  
 Set temp. ¼ sec. cor.  
 80.02 Intersect N. and S. line 11 lks. N. of the cor. of secs.  
 13, 14, 23 and 24.

40.01 Thence N.89°55'W., on a true line, bet. secs. 14 and 23,  
 over rolling land, through dense timber.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for ¼ sec. cor., with brass cap, marked  
 S 14  
 ¼-----  
 S 23  
 1916


from which  
 A cedar, 7 ins. diam., bears S.21°W., 28 lks. dist.,  
 marked ¼ S23 BT, and  
 A pinyon, 9 ins. diam., bears N.40°45'E, 77 lks. dist.,  
 marked ¼ S14 BT.  
 53.10 Low spur extends NW.  
 65.00 Draw, course N.70°W.  
 80.02 The cor. of secs. 14, 15, 22 and 23.

Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Buffalo grass.

9.00 S.0°01'E., bet. secs. 22 and 23,  
 over rolling land, through cedar and pinyon timber and  
 scattering undergrowth, along NE. slope.  
 40.00 Low spur slopes NW. Thence on SW. slope.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for ¼ sec. cor., with brass cap, marked



from which  
 A cedar, 24 ins. diam., bears S.46°20'E., 75 lks. dist.,  
 marked ¼ S23 BT, and  
 A cedar, 20 ins. diam., bears S.19°20'W., 199 lks. dist.,  
 marked ¼ S22 BT.  
 48.60 Draw, course NW. Thence along NE. slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the  
 ground, for cor. of secs. 22, 23, 26 and 27, with brass  
 cap, marked



from which  
 A cedar, 10 ins. diam., bears N.85°15'E., 22 lks. dist.,  
 marked T24N RLW S23 BT,  
 A cedar, 8 ind. diam., bears S.15°45'E., 173 lks. dist.,  
 marked T24N RLW S26 BT,

Chains

A cedar, 8 ins. diam., bears S.47°10'W., 98 lks. dist., marked T24N RLW S27 BT, and  
A cedar, 36 ins. diam., bears N.41°40'W., 56 lks. dist., marked T24N RLW S22 BT.

Land, rolling.  
Soil, 2nd and 3rd rate; limestone formation.  
Timber, cedar and pinyon.  
Undergrowth, quinine and algerita.

40.00 East, on a random line, bet. secs. 23 and 26.  
80.00 Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect  $\frac{1}{4}$  N. and S. line 11 lks. N. of the cor. of secs. 23, 24, 25 and 26.

5.00 Thence N.89°55'W., on a true line, bet. secs. 23 and 26, over rolling land, through cedar and pinyon timber and scattering undergrowth, on NE. slope.  
40.00 End of NE. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked  
S 23  
 $\frac{1}{4}$  -----  
S 26  
1916

from which  
40.50 A cedar, 30 ins. diam., bears N.50°40'E., 87 lks. dist., marked  $\frac{1}{4}$  S23 BT, and  
54.00 A cedar, 6 ins. diam., bears S.11°15'W., 37 lks. dist., marked  $\frac{1}{4}$  S26 BT.  
70.80 Draw, course SW.  
80.00 Draw, course NW.  
Wash, course NW.  
The cor. of secs. 22, 23, 26 and 27.

Land, rolling.  
Soil, gravel; 3rd rate.  
Timber, cedar and pinyon.  
Undergrowth, quinine and algerita.

18.85 S.0°01'E., bet. secs. 26 and 27, over rolling land, through dense timber.  
26.90 Draw, course S.60°W.  
40.00 Draw, course N.75°W.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

$\frac{1}{4}$   
S27 | S26  
1916

60.50 from which  
80.00 A cedar, 18 ins. diam., bears S.83 $\frac{1}{2}$ °E., 57 lks. dist., marked  $\frac{1}{4}$  S26 BT, and  
A pinyon, 14 ins. diam., bears N.44°W., 71 lks. dist., marked  $\frac{1}{4}$  S27 BT.  
Draw, course SW.  
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap, marked

T24N | RLW  
S27 | S26  
-----  
S34 | S35  
1916

from which


Chains

A cedar, 20 ins. diam., bears N.43 $\frac{1}{2}$ °E., 9 lks. dist., marked T24N RLW S26 BT,  
 A cedar, 10 ins. diam., bears S.33 $\frac{1}{2}$ °E., 47 lks. dist., marked T24N RLW S35 BT,  
 A cedar, 24 ins. diam., bears S.64 $\frac{1}{2}$ °W., 94 lks. dist., marked T24N RLW S34 BT, and  
 A cedar, 12 ins. diam., bears N.80 $\frac{1}{2}$ °W., 52 lks. dist., marked T24N RLW S27 BT.

Land, rolling.  
 Soil, 3rd rate; dolomite formation.  
 Timber, cedar and pinyon.  
 Buffalo grass.

40.00 East, on a random line, bet. secs. 26 and 35.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.22 Intersect N. and S. line 20 lks. N. of the cor. of secs. 25, 26, 35 and 36.

Thence N.89°51'W., on a true line, bet. secs. 26 and 35, over rolling land, through dense timber.  
 12.10 Draw, course S.70°W.  
 16.90 Draw, course N.70°W. Same draw last noted.  
 27.00 Same draw, course S.  
 40.11 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which  
 A cedar, 20 ins. diam., bears N.0°15'E., 73 lks. dist., marked  $\frac{1}{4}$  S26 BT, and  
 A cedar, 26 ins. diam., bears S.17 $\frac{1}{2}$ °E., 59 lks. dist., marked  $\frac{1}{4}$  S35 BT.  
 49.20 Draw, course S.60°W.  
 54.80 Draw, course SW.  
 75.20 Low ridge bears NE. and SW.  
 80.22 The cor. of secs. 26, 27, 34 and 35.

Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Undergrowth, none.  
 Buffalo grass.

40.00 S.0°01'E., on a random line, bet. secs. 34 and 35.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 71.36 Intersect S. bdy. of Tp. 12 lks. E. of the cor. of secs. 2, 3, 34 and 35, hereinbefore described.

Thence N.0°04'E., on a true line, bet. secs. 34 and 35, over open valley.  
 6.34 Leave valley, which bears SW. Enter timber.  
 31.36 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



from which  
 A cedar, 8 ins. diam., bears S.83°E., 38 lks. dist., marked  $\frac{1}{4}$  S35 BT, and  
 A cedar, 10 ins. diam., bears S.82°15'W., 41 lks. dist., marked  $\frac{1}{4}$  S34 BT.  
 68.35 Low ridge bears NE. and SW. Thence on NW. slope.

Chains

71.36 The cor. of secs. 26, 27, 34 and 35.

Land, rolling.  
Soil, 2nd and 3rd rate; rocky.  
Timber, cedar and pinyon.

-----  
From the standard cor. of secs. 33 and 34, and cor. of  
secs. 3 and 4, on 6th St. Par. N., hereinbefore described.

Thence S.0°02'E., bet. secs. 3 and 4,  
over level land, through scattering timber and undergrowth.

5.30 Ash Fork Grand Canyon road bears N. and S.  
24.60 Same road, bearing N. and S.  
37.000 Desc. on gentle S. slope.  
39.90 Same road bears N. and S.10°E.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

1/4  
S4 | S3  
1916

from which

A cedar, 10 ins. diam., bears N.75°E., 61 lks. dist.,  
marked 1/4 S3 BT, and  
A cedar, 8 ins. diam., bears N.69°10'W., 37 lks. dist.,  
marked 1/4 S4 BT.

80.00 Thence along gentle SE. slope.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 3, 4, 9 and 10, with brass  
cap, marked

T24N | RLW  
S4 | S3  
-----  
S9 | S10  
1916

from which

A cedar, 30 ins. diam., bears N.77°E., 11 lks. dist.,  
marked T24N RLW S3 BT,  
A cedar, 12 ins. diam., bears S.88°E., 20 lks. dist.,  
marked T24N RLW S10 BT,  
A pinyon, 8 ins. diam., bears S.67°15'W., 8 lks. dist.,  
marked T24N RLW S9 BT, and  
A pinyon, 8 ins. diam., bears N.73°20'W., 80 lks. dist.,  
marked T24N RLW S4 BT.

Land, rolling.  
Soil, sandy loam; 3rd rate.  
Timber, cedar and pinyon.  
Undergrowth, algerita.

-----  
40.00 East, on a random line, bet. secs. 3 and 10.  
79.98 Set temp. 1/4 sec. cor.  
Intersect N. and S. line 7 lks. S. of the cor. of secs.  
2, 3, 10 and 11.

Thence S.89°57'W., on a true line, bet. secs. 3 and 10,  
over rolling land, through cedar and pinyon timber.

5.00 Leave timber. Thence across valley, extending SW.  
15.00 Enter timber.  
31.00 Draw, course S.  
39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

S 3  
1/4 -----  
S 10  
1916

Chains

from which

A cedar, 8 ins. diam., bears N.6°30'W., 55 lks. dist., marked 1/4 S3 BT, and

A cedar, 6 ins. diam., bears S.11°45'W., 21 lks. dist., marked 1/4 S10 BT.

42.00 Low spur extends SE. Desc. gradually on NW. slope.

46.00 Draw, course SW.

57.00 Leave timber.

66.50 Grand Canyon-Ash Fork road bears N. and S.

71.00 Enter timber.

79.98 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.

Soil, gravelly; 3rd rate.

Timber, cedar and pinyon.


S.0°02'E., bet. secs. 9 and 10,

over rolling land, along E. slope, through scattering timber and undergrowth.

1.00 Leave timber.

20.00 Enter scattering timber.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for 1/4 sec. cor., with brass cap, marked



from which

A pinyon, 12 ins. diam., bears S.20°E., 125 lks. dist., marked 1/4 S10 BT, and

A pinyon, 8 ins. diam., bears S.21°15'W., 173 lks. dist., marked 1/4 S9 BT.

44.50 Wash, course E.


50.00 Low spur extends E.

71.00 Leave timber; thence across valley, extending SW.

75.75 Ash Fork-Grand Canyon road bears NE. and SW.

78.00 Wash, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap, marked



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.

Soil, limestone; 3rd rate.

Timber, cedar and pinyon.

Undergrowth, algerita.

East, on a random line, bet. secs. 10 and 15.


40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line at the cor. of secs. 10, 11, 14 and 15.

Thence West, on a true line, bet. secs. 10 and 15, over rolling land, through scattering timber.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked

Chains




and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 41.60 Draw, course N.15°W.
- 47.50 Low spur extends N.10°E.
- 51.00 Draw, course N.15°E.
- 65.00 Leave timber, bearing N.70°E. and S.70°W.
- 74.00 Road bears N.75°E. and S.75°W.
- 77.60 Draw, course S.70°W.
- 80.00 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.  
Soil, gravelly; 2nd rate.  
Timber, cedar and pinyon.


S.0°02'E., bet. secs.15 and 16, across open valley, extending SW.

- 2.30 Wash, course SW. Thence along NW. slope.
- 3.00 Road bears NE. and SW.
- 7.00 Enter timber.
- 34.50 Ridge bears NE. and SW. Desc. on SE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked



from which  
A cedar, 18 ins. diam., bears S.5°10'E., 58 lks. dist., marked ¼ S15 BT, and  
A pinyon, 12 ins. diam., bears S.34°W., 21 lks. dist., marked ¼ S16 BT.

- 78.00 Leave timber, and enter valley, extending SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 15, 16, 21 and 22, with brass cap, marked



from which  
A pinyon, 12 ins. diam., bears N.51°25'W., 143 lks. dist., marked T24N R1W S16 BT.  
No other bearing trees available. Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.  
Soil, 3rd rate; limestone formation.  
Timber, cedar and pinyon.  
Undergrowth, quinine and algerita.

- 40.00 East, on a random line, bet. secs. 15 and 22.
- 80.08 Set temp. ¼ sec. cor.  
Intersect N. and S. line at the cor. of secs. 14, 15, 22 and 23.

Thence West, on a true line, bet. secs. 15 and 22, over rolling land, through scattering timber and undergrowth. Desc. on gentle SW. slope.

- 15.10 Draw, course NW.
- 36.00 Low spur extends NW. Thence on gentle SW. slope.

30

Subdivision of T. 24 N., R. 1 W.

Chains

40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 15

 $\frac{1}{4}$  -----

S 22

1916

from which

A cedar, 10 ins. diam., bears North, 2 lks. dist., marked  $\frac{1}{4}$  S15 BT, and

A pinyon, 8 ins. diam., bears S.45°W., 167 lks. dist., marked  $\frac{1}{4}$  S22 BT.

50.15 Wash, course NW. Thence on gentle NE. slope.

57.00 Thence along spur sloping W.

66.00 Desc. on NW. slope.

72.00 Leave timber.

76.15 Wash, 115 ft. below 66 ch. pt., course SW. Thence across valley, extending SW.

80.08 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.

Soil, 3rd rate; limestone formation.

Timber, cedar and pinyon.

Undergrowth, quinine and algerita.

S.0°02'E., bet. secs. 21 and 22,  
over rolling, open land,

3.60 Draw, course N.70°W. Thence on N. slope.

5.00 Enter dense timber, bearing E. and W.

21.60 Ridge, 200 ft. above draw, bears N. and S.

31.60 Ridge bears S.10°E. Thence along broken W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

 $\frac{1}{4}$ 

S21 | S22

1916

from which

A pinyon, 9 ins. diam., bears N.24 $\frac{1}{2}$ °E., 48 lks. dist., marked  $\frac{1}{4}$  S22 BT, and

A cedar, 16 ins. diam., bears S.51°45'W., 9 lks. dist., marked  $\frac{1}{4}$  S21 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap, marked

T24N | R1W

S21 | S22

S28 | S27

1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
W. of cor.

Land, rolling.

Soil, 3rd rate; limestone formation.

Timber, cedar and pinyon.

Buffalo grass.

East, on a random line, bet. secs. 22 and 27.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 Intersect N. and S. line 3 lks. N. of the cor. of secs. 22, 23, 26 and 27.

Thence N.89°59'W., on a true line, bet. secs. 22 and 27,  
over rolling land, through dense timber.




Subdivision of T. 24 N., R. 1 W.

Chains

35.00  
40.00

Wash, course S.30°W.  
Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, on a rock ledge, for 1/4 sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.


49.00  
56.50  
67.35  
80.02

Flat topped spur extends S.5°W. Desc. 50 ft.  
Draw, course S.35°E. Asc. 125 ft., on E. slope.  
Ridge bears N.15°W. and S.15°E. Desc. 125 ft., on W. slope.  
The cor. of secs. 21, 22, 27 and 28.

Land, rolling.  
Soil, 3rd rate; dolomite formation.  
Timber, cedar and pinyon.  
Buffalo grass.

31.00  
40.00


S.0°02'W., bet. secs. 27 and 28, over rolling land, along broken SW. slope, through scattering timber and undergrowth.  
Draw, course SW.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked



from which  
A cedar, 10 ins. diam., bears N.10°15'E., 62 lks. dist., marked 1/4 S27 BT, and  
A cedar, 6 ins. diam., bears S.67°10'W., 127 lks. dist., marked 1/4 S28 BT.

72.00  
79.00  
80.00

Draw, course SW.  
Spur slopes SW.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap, marked



from which  
A cedar, 30 ins. diam., bears S.49°10'E., 256 lks. dist., marked T24N R1W S34 BT, and  
A pinyon, 6 ins. diam., bears N.43°40'W., 253 lks. dist., marked T24N R1W S28 BT.  
No other bearing trees available.  
Dig pits, 18x18x12 ins., in each sec., 5 1/2 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling.  
Soil, gravelly; 2nd and 3rd rate.  
Timber, cedar and pinyon.  
Undergrowth, algerita.

40.00  
80.02


East, on a random line, bet. secs. 27 and 34.  
Set temp. 1/4 sec. cor.  
Intersect N. and S. line 20 lks. S. of the cor. of secs. 26, 27, 34 and 35.

Chains

21.80 Thence S.89°51'W., on a true line, bet. secs. 27 and 34,  
over rolling land, through dense timber. Desc. 150 ft.

39.00 Small ravine, course SW.  
Leave timber.

40.01 On spur extending SW.,  
Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the  
ground, surrounded by a mound of stone, (impracticable  
to set post farther in the ground) for 1/4 sec. cor., with  
brass cap, marked



from which


A cedar, 12 ins. diam., bears N.12°30'E., 66 lks. dist.,  
marked 1/4 S27 BT, and

A pinyon, 6 ins. diam., bears S.21°E., 22 lks. dist.,  
marked 1/4 S34 BT.

80.02 Thence on broken SW. slope.  
The cor. of secs. 27, 28, 33 and 34.

Land, rolling.  
Soil, 3rd rate; limestone formation.  
Timber, cedar and pinyon.  
Undergrowth, algerita.


40.00 S.0°03'W., on a true line, bet. secs. 33 and 34,  
over rolling land, through very scattering timber.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked



dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,  
and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high,  
W. of cor.

71.10 Intersect S. bdy. of Tp. 31 lks. S.89°56'E. of the cor.  
of secs. 3 and 4, re-established as hereinbefore described.

At point of intersection  
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in  
the ground, for closing cor. of secs. 33 and 34, with  
brass cap, marked



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
N. of cor.

Land, rolling.  
Soil, 2nd rate; gravelly.  
Timber, cedar and pinyon.  
Buffalo grass:

40.00 From the cor. of secs. 4 and 5, and standard cor. of secs.  
32 and 33, on 6th St. Par. N., hereinbefore described,

S.0°02'E., bet. secs. 4 and 5,  
over rolling land, through dense timber.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

Chains

$$\begin{array}{c} \frac{1}{4} \\ | \\ S5 | S4 \\ | \\ 1916 \end{array}$$

from which  
 A cedar, 24 ins. diam., bears N.26°E., 47 lks. dist.,  
 marked  $\frac{1}{4}$  S4 BT, and  
 A cedar, 8 ins. diam., bears S.23 $\frac{1}{4}$ °W., 93 lks. dist.,  
 marked  $\frac{1}{4}$  S5 BT.  
 68.00 Draw, course NE.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the  
 ground, for cor. of secs. 4, 5, 8 and 9, with brass cap,  
 marked

$$\begin{array}{c} T24N | R1W \\ \hline S5 | S4 \\ \hline S8 | S9 \\ | \\ 1916 \end{array}$$

from which  
 A cedar, 20 ins. diam., bears N.86°45'E., 41 lks. dist.,  
 marked T24N R1W S4 BT,  
 A cedar, 18 ins. diam., bears S.13 $\frac{1}{2}$ °E., 75 lks. dist.,  
 marked T24N R1W S9 BT,  
 A pinyon, 16 ins. diam., bears S.42 $\frac{1}{2}$ °W., 128 lks. dist.,  
 marked T24N R1W S8 BT, and  
 A cedar, 12 ins. diam., bears N.36°W., 19 lks. dist.,  
 marked T24N R1W S5 BT.  
 Land, rolling.  
 Soil, gravelly; 2nd rate.  
 Timber, cedar and pinyon.  
 Buffalo grass.

40.00 East, on a random line, bet. secs. 4 and 9.  
 80.02 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line 5 lks. N. of the cor. of secs.  
 3, 4, 9 and 10.

Thence N.89°58'W., on a true line, bet. secs. 4 and 9,  
 over rolling land, through dense timber.  
 24.50 Draw, course S.20°E.  
 28.45 Low spur extends SE.  
 33.45 Draw, course S.65°E. (Comes from W). Thence along draw.  
 38.45 Leave draw, & comes from S.70°W.  
 40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

$$\begin{array}{c} S4 \\ \frac{1}{4} \text{-----} \\ S9 \\ | \\ 1916 \end{array}$$

from which  
 A pinyon, 6 ins. diam., bears N.27 $\frac{1}{2}$ °E., 47 lks. dist.,  
 marked  $\frac{1}{4}$  S4 BT, and  
 A cedar, 10 ins. diam., bears S.2 $\frac{1}{4}$ °E., 131 lks. dist.,  
 marked  $\frac{1}{4}$  S9 BT.  
 47.50 Same draw, course S.75°E.  
 54.95 Spur extends S.30°E.  
 74.45 Draw, course N.10°E.  
 80.02 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.  
 Soil, gravel formation; 2nd rate.  
 Timber, cedar and pinyon.  
 Buffalo grass.

Chains

S.0°02'E., bet. secs. 8 and 9,  
over rolling land, through dense timber.

9.45- Low ridge bears N.30°W. and S.30°E. Thence along broken  
SW. slope.

39.40 Draw, course S.70°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for 1/4 sec. cor., with brass cap, marked

1/4  
S8 | S9  
1916

from which

A cedar, 16 ins. diam., bears N.29 1/4°E., 27 lks. dist.,  
marked 1/4 S9 BT, and

A pinyon, 16 ins. diam., bears N.87°W., 53 lks. dist.,  
marked 1/4 S8 BT.

50.00 Desc. 125 ft.

57.20 Wash, course N.80°W. Asc. 80 ft., on N. slope.

61.60 Spur extends W. Desc. 225 ft., on broken S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the  
ground, for cor. of secs. 8, 9, 16 and 17, with brass  
cap, marked

T24N | R1W  
S8 | S9  
-----  
S17 | S16  
1916

from which

A pinyon, 8 ins. diam., bears N.84 1/2°E., 41 lks. dist.,  
marked T24N R1W S9 BT,

A pinyon, 12 ins. diam., bears S.66 1/4°E., 108 lks. dist.,  
marked T24N R1W S16 BT,

A cedar, 14 ins. diam., bears S.44°W., 173 lks. dist.,  
marked T24N R1W S17 BT, and

A cedar, 16 ins. diam., bears N.40°W., 10 lks. dist.,  
marked T24N R1W S8 BT.

Land, rolling.

Soil, 3rd rate; limestone formation.

Timber, cedar and pinyon.

Buffalo grass.

-----  
East, on a random line, bet. secs. 9 and 16.

40.00 Set temp. 1/4 sec. cor.

79.96 Intersect N. and S. line 2 lks. N. of the cor. of secs.  
9, 10, 15 and 16.

Thence N.89°59'W., on a true line, bet. secs. 9 and 16,  
over rolling land, through dense cedar and pinyon timber.

.65 Draw, course S.50°W.

2.25 Grand Canyon road bears N.50°E. and S.50°W.

22.45 Low spur extends S.20°W.

31.60 Spur extends SW.

36.60 Draw, course S.15°W.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground, surrounded by a mound of stone, (impracticable  
to set post farther in the ground) for 1/4 sec. cor., with  
brass cap, marked

S 9  
1/4 -----  
S 16  
1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high,  
N. of cor.

43.10 Spur extends S.25° E.

50.00 Draw, course S.20°E.

65.00 Spur slopes S.

78.50 Small draw, course S.10°E.

79.96 The cor. of secs. 8, 9, 16 and 17.

Chains

Land, rolling.  
Soil, 3rd rate; limestone formation.  
Timber, cedar and pinyon.  
Buffalo grass.

40.00 S.0°02'E., bet. secs. 16 and 17,  
over slightly rolling land,  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S17 | S16

1916

dig pits, 18x18x12 ins., N. and S. of post, 3 ft., dist.  
and raise a mound of earth, 3 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high,  
W. of cor.

50.00 Center of large draw, course S.50°W.

62.80 Grand Canyon road bears N.60°E. and S.60°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 16, 17, 20 and 21, with brass  
cap, marked

T24N | R1W  
S17 | S16  
S20 | S21

1916

dig pits, 18x18x12 ins., in each sec., 5 $\frac{1}{2}$  ft. dist.,  
and raise a mound of earth, 4 ft. base, 2 ft. high,  
W. of cor.

Land, gently rolling.  
Soil, gravelly; 2nd and 3rd rate.  
Buffalo grass.

40.00 East, on a random line, bet. secs. 16 and 21.  
Set temp.  $\frac{1}{4}$  sec. cor.  
79.80 Intersect N. and S. line 4 lks. S. of the cor. of secs.  
15, 16, 21 and 22.

Thence S.89°58'W., on a true line, bet. secs. 16 and 21,  
over rolling, open land.

6.80 Draw, course N.70°W.

16.80 Same draw, course S.70°W.

39.90 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 16  
 $\frac{1}{4}$  -----  
S 21

1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
N. of cor.

54.30 Road bears N.15°E. and S.15°W.

79.80 The cor. of secs. 16, 17, 20 and 21.

Land, rolling.  
Soil, 2nd rate.  
Buffalo grass.


S.0°02'E., bet. secs. 20 and 21,  
over level land, through scattering undergrowth.

19.00 Enter scattering timber.

27.00 Leave timber and enter valley, extending SW.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked



1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.


65.00 Enter scattering timber on NW. slope.

72.00 Low spur extends NW. thence on SW. slope.

75.00 Leave timber.

79.00 Wash, course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly; 2nd rate, and 3rd rate, limestone formation.

Timber, cedar and pinyon.

Undergrowth, algerita.

East, on a random line, bet. secs. 21 and 28.


40.00 Set temp. 1/4 sec. cor.

79.90 Intersect N. and S. line 19 lks. S. of the cor. of secs. 21, 22, 27 and 28.

Thence S.89°52'W., on a true line, bet. secs. 21 and 28, over rolling land, through scattering timber on broken SW. slope. Desc. gradually, 150 ft.,

29.90 Leave timber.

39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked



1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

56.90 Enter timber. Draw, course SW.

69.90 Leave timber.

70.90 Low spur extends NW.

77.60 Wash, course NW.

79.90 The cor. of secs. 20, 21, 28 and 29.

Land, rolling.

Soil, gravelly; 2nd rate, and limestone formation, 3rd rate.

Timber, cedar and pinyon.

Undergrowth, algerita.

S.0°02'E., bet. secs. 28 and 29, over nearly level land.

5.25 Road bears N.20°W. and S.20°E.

18.80 Draw, course N.20°E.

22.00 Same draw, course N.5°W.


30.00 Same draw, course N.20°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for 1/4 sec. cor., with

E

Chains

brass cap, marked




1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

45.00  
80.00

Enter scattering timber and undergrowth.  
Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 28, 29, 32 and 33, with brass cap, marked



1916

from which

- A cedar, 14 ins. diam., bears N.10°45'E., 175 lks. dist., marked T24N R1W S28 BT,
- A cedar, 30 ins. diam., bears S.18½°E., 135 lks. dist., marked T24N R1W S33 BT,
- A pinyon, 10 ins. diam., bears S.13½°W., 210 ft. dist., marked T24N R1W S32 BT, and
- A cedar, 10 ins. diam., bears N.84°45'W., 196 lks. dist., marked T24N R1W S29 BT.


Land, rolling and level.  
Soil, 2nd rate.  
Timber, cedar and pinyon.  
Undergrowth, algerita.

40.00  
79.86

East, on a random line, bet. secs. 28 and 33.  
Set temp. ¼ sec. cor.  
Intersect N. and S. line 17 lks. S. of the cor. of secs. 27, 28, 33 and 34.

39.93

Thence S.89°53'W., on a true line, bet. secs. 28 and 33, over rolling land, through scattering timber.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.


63.30  
66.65  
79.86

Road bears N. and S.  
Draw, course N.  
The cor. of secs. 28, 29, 32 and 33.

Land, rolling.  
Soil, gravelly; 2nd rate.  
Timber, pinyon and cedar.  
Buffalo grass.

15.00  
24.00  
40.00

S.0°03'W., on a true line, bet. secs. 32 and 33, over slightly rolling land, through very scattering timber.  
Draw, course N.30°E.  
Road bears NW. and SE.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap, marked



1916

Chains

70.42 and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
Intersect S. bdy. of Tp. 66 lks. N.89°46'E. of the cor. of secs. 4 and 5, reestablished as hereinbefore described.

At point of intersection  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 32 and 33, with brass cap, marked

|          |   |     |
|----------|---|-----|
|          | C | C   |
| T24N     |   | R1W |
| S32      |   | S33 |
| -----    |   |     |
| S 4      |   |     |
| T23N R1W |   |     |
| 1916     |   |     |

from which  
A cedar, 24 ins. diam., bears N.27½°W., 334 lks. dist., marked T24N R1W S32 BT, and  
A pinyon, 14 ins. diam., bears N.64°E., 161 lks. dist., marked T24N R1W S33 BT.

Land, slightly rolling.  
Soil, gravelly, with clay sub-soil; 2nd rate.  
Timber, cedar.

22.00 From the cor. of secs. 5 and 6, and standard cor. of secs. 31 and 32, on 6th St. Par. N., hereinbefore described,

32.50 S.0°03'E., bet. secs. 5 and 6,  
over rolling land, through cedar and pinyon timber and scattering undergrowth, along gentle NW. slope.

40.00 Spur extends W. Thence on SW. slope.

Draw, course W. Thence on NW. slope.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for ¼ sec. cor., with brass cap, marked

|      |   |    |
|------|---|----|
|      | ¼ |    |
| S6   |   | S5 |
| 1916 |   |    |

from which  
A cedar, 6 ins. diam., bears S.84°30'E., 7 lks. dist., marked ¼ S5 BT, and  
A cedar, 12 ins. diam., bears N.79°W., 11 lks. dist., marked ¼ S6 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap, marked

|         |  |     |
|---------|--|-----|
| T24N    |  | R1W |
| S6      |  | S5  |
| -----   |  |     |
| S7   S8 |  |     |
| 1916    |  |     |

from which  
A cedar, 12 ins. diam., bears N.72°35'E., 125 lks. dist., marked T24N R1W S5 BT,  
A pinyon, 10 ins. diam., bears S.20°30'E., 82 lks. dist., marked T24N R1W S8 BT,  
A cedar, 8 ins. diam., bears S.36°15'W., 46 lks. dist., marked T24N R1W S7 BT, and  
A cedar, 6 ins. diam., bears N.32°10'W., 57 lks. dist., marked T24N R1W S6 BT.

Land, rolling. Soil, gravelly loam; 3rd rate.  
Timber, cedar and pinyon. Undergrowth, algerita.




Subdivision of T. 24 N., R. 1 W.

Chains

40.00 East, on a random line, bet. secs. 5 and 8.  
 79.98 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line 7 lks. N. of the cor. of secs.  
 4, 5, 8 and 9.

39.99 Thence N.89°57'W., on a true line, bet. secs. 5 and 8,  
 over rolling land, through cedar and pinyon timber.  
 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the  
 ground, surrounded by a mound of stone, (impracticable  
 to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with  
 brass cap, marked




from which  
 A pinyon, 8 ins. diam., bears N.56°W., 25 lks. dist.,  
 marked  $\frac{1}{4}$  S5 BT, and  
 A cedar, 6 ins. diam., bears S.43°45'W., 76 lks. dist.,  
 marked  $\frac{1}{4}$  S8 BT.

67.50 Ridge bears NW. and SE. Thence on gentle SW. slope.  
 79.00 Thence on gentle NW. slope.  
 79.98 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.  
 Soil, 3rd rate. Limestone formation.  
 Timber, cedar and pinyon.

40.00 West, on a random line, bet. secs. 6 and 7.  
 80.07 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect W. bdy. of Tp. 11 lks. N. of the cor. of secs.  
 1, 6, 7 and 12, hereinbefore described.

11.40 Thence N.89°55'E., on a true line, bet. secs. 6 and 7,  
 over rolling land, through dense timber.  
 22.15 Draw, course N.15°E.  
 27.80 Draw, course NW.  
 40.07 Draw, course N.20°W.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked




from which  
 A cedar, 8 ins. diam., bears N.56 $\frac{1}{4}$ °W., 11 lks. dist.,  
 marked  $\frac{1}{4}$  S6 BT, and  
 A cedar, 20 ins. diam., bears S.47°W., 79 lks. dist.,  
 marked  $\frac{1}{4}$  S7 BT.

63.50 Draw, course NW.  
 80.07 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.  
 Soil, gravelly; 2nd rate.  
 Timber, cedar and pinyon.  
 Buffalo grass.

8.50 S.0°03'E., bet. secs. 7 and 8,  
 over rolling land, through dense timber.  
 40.00 Draw, course N.65°W.  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked



Chains

from which

A cedar, 26 ins. diam., bears S.4°E., 39 lks. dist., marked  $\frac{1}{4}$  S8 BT, andA cedar, 15 ins. diam., bears S.15°W., 36 lks. dist., marked  $\frac{1}{4}$  S7 BT.

40.20 Wash, course S.35°W. Thence along W. slope.

68.80 Low spur extends S.75°W.

80.00 Set an iron post 3 ft. long, 2 ins. diam., 12 ins. in the ground, (impracticable to set post farther in the ground) for cor. of secs. 7, 8, 17 and 18, with brass cap, marked

|      |     |
|------|-----|
| T24N | RLW |
| S7   | S8  |
| S18  | S17 |

1916

from which

A cedar, 14 ins. diam., bears N.56 $\frac{1}{4}$ °E., 74 lks. dist., marked T24N RLW S8 BT,

A cedar, 16 ins. diam., bears S.42°E., 197 lks. dist., marked T24N RLW S17 BT,

A cedar, 12 ins. diam., bears S.21 $\frac{1}{2}$ °W., 27 lks. dist., marked T24N RLW S18 BT, and

A pinyon, 12 ins. diam., bears N.59°W., 83 lks. dist., marked T24N RLW S7 BT.

Land, rolling.

Soil, gravelly; 3rd rate.

Timber, cedar and pinyon.

Buffalo grass.

East, on a random line, bet. secs. 8 and 17.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Intersect N. and S. line 2 lks. N. of the cor. of secs. 8, 9, 16 and 17.

Thence N.89°59'W., on a true line, bet. secs. 8 and 17, along broken S. slope, through dense timber.

22.00 Wash, course S.15°W.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 8

 $\frac{1}{4}$  -----

S 17

1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

44.00 Draw, course S.25°W.

79.98 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, gravelly; 2nd rate.

Timber, cedar and pinyon.

Buffalo grass.

West, on a random line, bet. secs. 7 and 18.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.94 Intersect W. bdy. of Tp. 11 lks. S. of the cor. of secs. 7, 12, 13 and 18, hereinbefore described.

Thence S.89°55'E., on a true line, bet. secs. 7 and 18, over rolling land, on broken S. slope, through scattering undergrowth.

1.20 Wash, course S. Asc. 160 ft.

20.00 Spur extends S. Enter scattering timber.


32.50 Wash, course W.

37.00 Spur extends S.

39.94 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, surrounded by a mound of stone, (impracticable

Chains

to set post farther in the ground) for 1/4 sec. cor., with brass cap, marked



from which

A cedar, 14 ins. diam., bears S.61°E., 49 lks. dist., marked 1/4 S18 BT,

No other bearing trees within limits. Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.


56.00  
65.00  
74.00  
79.94

Wash, course S.  
Low spur extends S.  
Wash, course S.  
The cor. of secs. 7, 8, 17 and 18.

Land, rolling.  
Soil, 3rd rate; limestone formation.  
Timber, cedar and pinyon.  
Undergrowth, quinine and algerita.

25.00  
40.00


S.0°03'E., bet. secs. 17 and 18,  
over rolling land, through scattering timber.  
Leave timber, and enter valley, bearing NW.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap, marked



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

51.50  
52.85  
62.00

Wash, course NW.  
Road bears NW. and SE.  
Spur extends NE. Thence on gentle SW. slope.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap, marked



1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.  
Soil, gravelly loam; 2nd rate.  
Timber, cedar.

40.00  
79.98

East, on a random line, bet. secs. 17 and 20.  
Set temp. 1/4 sec. cor.  
Intersect N. and S. line at the cor. of secs. 16, 17, 20 and 21.

19.83  
25.00  
39.99

Thence West, on a true line, bet. secs. 17 and 20,  
over level, open land.  
Ash Fork-Grand Canyon road bears NE. and SW.  
Enter timber, on gentle SE. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for 1/4 sec. cor., with brass cap, marked

Chains

S 17  
 $\frac{1}{4}$  -----  
 S 20  
 1916

from which  
 A pinyon, 8 ins. diam., bears N.33°30'E., 41 lks. dist.,  
 marked  $\frac{1}{4}$  S17 BT, and  
 A pinyon, 9 ins. diam., bears S.55°20'E., 75 lks. dist.,  
 marked  $\frac{1}{4}$  S20 BT.

45.00 Low spur extends SW. Thence along NW. slope.  
 60.00 Leave timber.  
 71.40 Wash, course NW.  
 74.90 Road bears NW. and SE.  
 79.98 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.  
 Soil, gravelly loam; 2nd rate, and 3rd rate, limestone  
 formation.  
 Timber, cedar and pinyon.  
 Undergrowth, quinine and algerita.

40.00 West, on a random line, bet. secs. 18 and 19.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.14 Intersect W. bdy. of Tp. 3 lks. S. of the cor. of secs.  
 13, 18, 19 and 24, hereinbefore described.

14.65 Thence S.89°59'E., on a true line, bet. secs. 18 and 19,  
 over rolling land, through scattering timber.  
 Enter dense timber, bearing N. and S.  
 25.65 Low spur extends N. Desc. 130 ft.  
 40.14 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S 18  
 $\frac{1}{4}$  -----  
 S 19  
 1916

from which  
 A cedar, 16 ins. diam., bears N.45°W., 108 lks. dist.,  
 marked  $\frac{1}{4}$  S18 BT, and  
 A cedar, 20 ins. diam., bears S.29°E., 66 lks. dist.,  
 marked  $\frac{1}{4}$  S19 BT.

40.35 Draw, course N.  
 75.15 Low spur extends N.50°E. Leave timber, bearing N. and S.  
 80.14 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.  
 Soil, 2nd rate; gravel formation.  
 Timber, cedar and pinyon.

35.00 S.0°03'E., bet. secs. 19 and 20,  
 over level open land.  
 40.00 Enter scattering cedar timber, bearing NW. and E.  
 Set an iron post, 3 ft; long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor.;, with brass cap, marked

$\frac{1}{4}$   
 S19 | S20  
 1916

from which  
 A cedar, 14 ins.diam., bears S.55°E., 18 lks. dist.,  
 marked  $\frac{1}{4}$  S20 BT, and  
 A cedar, 12 ins. diam., bears S.42°W., 67 lks. dist.,  
 marked  $\frac{1}{4}$  S19 BT.

50.80 Grand Canyon road bears N.20°E. and S.20°W.  
 Draw, course N.20°E.  
 55.00 Enter dense cedar and pinyon timber, bearing N.30°E. and  
 S.30°W.

Subdivision of T. 24 N., R. 1 W.

Chains

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for cor. of secs. 19, 20, 29 and 30, with brass cap, marked

|      |     |
|------|-----|
| T24N | R1W |
| S19  | S20 |
| S30  | S29 |

1916

from which

- A cedar, 10 ins. diam., bears N.23 $\frac{1}{2}$ °E., 125 lks. dist., marked T24N R1W S20 BT,
- A cedar, 16 ins. diam., bears S.88 $\frac{1}{4}$ °E., 87 lks. dist., marked T24N R1W S29 BT,
- A cedar, 7 ins. diam., bears S.37 $\frac{1}{2}$ °W., 90 lks. dist., marked T24N R1W S30 BT, and
- A cedar, 7 ins. diam., bears N.83 $\frac{1}{2}$ °W., 28 lks. dist., marked T24N R1W S19 BT.

Land, level and rolling.

- Soil, clay, 1st rate, on level land, and 3rd rate, dolomite formation, on rolling land.
- Timber, cedar and pinyon.
- Buffalo grass.

40.00 East, on a random line, bet. secs. 20 and 29.  
 80.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect N. and S. line 5 lks. N. of the cor. of secs. 20, 21, 28 and 29.

Thence N.89°58'W., on a true line, bet. secs. 20 and 29, over level, open land.

1.40 Wash, course N.89°E.  
 4.00 Road bears N.20°W. and S.20°E.  
 11.00 Draw, (containing wash noted at 1.40 ch. pt.) course S. Enter cedar and pinyon timber.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

|                     |
|---------------------|
| S 20                |
| $\frac{1}{4}$ ----- |
| S 29                |
| 1916                |

from which

- A cedar, 6 ins. diam., bears N.44°W., 205 lks. dist., marked  $\frac{1}{4}$  S20 BT, and
- A cedar, 14 ins. diam., bears S.8°E., 158 lks. dist., marked  $\frac{1}{4}$  S29 BT.

56.60 Road bears NE. and SW.  
 80.00 The cor. of secs. 19, 20, 29 and 30.

- Land, rolling.
- Soil, 2nd rate; limestone formation.
- Timber, cedar and pinyon.
- Buffalo grass.

40.00 West, on a random line, bet. secs. 19 and 30.  
 80.16 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect W. bdy. of Tp. 7 lks. S. of the cor. of secs. 19, 24, 25 and 30, hereinbefore described.

Thence S.89°57'E., on a true line, bet. secs. 19 and 30, over rolling land, through scattering timber.

10.25 Low spur extends N.50°W.  
 30.00 Low ridge bears N.15°E. and S.15°W.  
 40.16 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

Chains

S 19  
 $\frac{1}{4}$  -----  
 S 30  
 1916

from which

A cedar, 8 ins. diam., bears N.21°E., 138 lks. dist., marked  $\frac{1}{4}$  S19 BT, and

A cedar, 14 ins. diam., bears S.18°45'W., 48 lks. dist., marked  $\frac{1}{4}$  S30 BT.

67.45 Draw, course N.20°E.

Grand Canyon road bears N.20°E. and S.20°W.

80.16 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.  
 Soil, 2nd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Buffalo grass.

30.00 S.0°03'E., bet. secs. 29 and 30,  
 over rolling land, through dense timber and undergrowth.  
 Timber and undergrowth becomes scattering.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

S30 | S29  
 1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

40.50 Road bears NW. and SE. Wide, flat draw, course NW.

65.00 Shallow draw, course N.20°E.

70.00 Enter dense cedar and pinyon timber.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap, marked

T24N | R1W  
 S30 | S29  
 -----  
 S31 | S32

1916

from which

A cedar, 10 ins. diam., bears N.23 $\frac{1}{2}$ °E., 205 lks. dist., marked T24N R1W S29 BT,

A cedar, 7 ins. diam., bears S.35°E., 215 lks. dist., marked T24N R1W S32 BT,

A cedar, 8 ins. diam., bears S.49°W., 35 lks. dist., marked T24N R1W S31 BT, and

A cedar, 10 ins. diam., bears N.83 $\frac{1}{2}$ °W., 231 lks. dist., marked T24N R1W S30 BT.

Land, rolling.  
 Soil, 2nd rate; limestone formation.  
 Timber, pinyon and cedar.  
 Buffalo grass.

40.00 East, on a random line, bet. secs. 29 and 30.  
 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 Intersect N. and S. line 6 lks. N. of the cor. of secs. 28, 29, 32 and 33.

Thence N.89°57'W., on a true line, bet. secs. 29 and 30, over rolling land, through dense timber.

18.10 Road bears NW. and SE.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 5 ins. in the ground, surrounded by a mound of stone, (impracticable to set post farther in the ground) for  $\frac{1}{4}$  sec. cor., with brass cap, marked

Chains

S 29  
 $\frac{1}{4}$  -----  
 S 32  
 1916

from which  
 A cedar, 7 ins. diam., bears N.53°45'E., 92 lks. dist.,  
 marked  $\frac{1}{4}$  S29 BT, and  
 A cedar, 8 ins. diam., bears S.21°W., 84 lks. dist.,  
 marked  $\frac{1}{4}$  S32 BT.  
 42.50 Low ridge bears N.15°E. and S.15°W.  
 80.02 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.  
 Soil, 3rd rate; limestone formation.  
 Timber, cedar and pinyon.  
 Buffalo grass.

40.00 West, on a random line, bet. secs. 30 and 31.  
 80.13 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect W. bdy. of Tp. 5 lks. S. of the cor. of secs.  
 25, 30, 31 and 36.

Thence S.89°58'E., on a true line, bet. secs. 30 and 31,  
 over rolling land, through cedar and pinyon timber, on  
 SW. slope.  
 12.00 Spur extends NW. Thence along broken NW. slope.  
 26.00 Draw, course NW. Thence along SW. slope.  
 40.13 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
 ground, surrounded by a mound of stone, (impracticable  
 to set post farther in the ground) for  $\frac{1}{4}$  sec. cor.,  
 with brass cap, marked

S 30  
 $\frac{1}{4}$  -----  
 S 31  
 1916

from which  
 A cedar, 6 ins. diam., bears N.35°30'W., 71 lks. dist.,  
 marked  $\frac{1}{4}$  S30 BT, and  
 A pinyon, 8 ins. diam., bears S.41°W., 17 lks. dist.,  
 marked  $\frac{1}{4}$  S31 BT.  
 48.00 Ridge bears NW. and SE. Thence on NE. slope.  
 55.50 Wash, course NW. Thence on SW. slope.  
 60.00 Spur extends N. Thence on NE. slope.  
 77.00 Draw, course NE.  
 80.13 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.  
 Soil, 3rd rate; limestone.  
 Timber, cedar and pinyon.  
 Undergrowth, algerita and quinine.

40.00 S.0°03'W., on a random line, bet. secs. 31 and 32.  
 67.31 Set temp;  $\frac{1}{4}$  sec. cor.  
 Intersect S. bdy. of Tp. 27 lks. E. of the cor. of secs.  
 5, 6, 31 and 32, hereinbefore described.

Thence N.0°17'E., on a true line, bet. secs. 31 and 32,  
 over rolling land, through timber and undergrowth, along  
 broken NE. slope.  
 27.31 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap, marked

$\frac{1}{4}$   
 S31 | S32  
 1916

from which  
 A pinyon, 6 ins. diam., bears S.63°15'E., 63 lks. dist.,

Chains

33.30 marked  $\frac{1}{4}$  S32 BT, and  
 67.31 A pinyon, 6 ins. diam., bears N.71°W., 27 lks. dist.,  
 marked  $\frac{1}{4}$  S31 BT.  
 thence along spur extending N.  
 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.  
 Soil, gravelly; 3rd rate.  
 Timber, cedar and pinyon.  
 Undergrowth, quinine and algerita.

Boundaries of T. 24 N., R. 1 W.

Latitudes, Departures, and Closing Errors.

| Line Designated                       | True Course   | Dist.<br>chs. | Latitudes  |                  | Departures |                  |
|---------------------------------------|---------------|---------------|------------|------------------|------------|------------------|
|                                       |               |               | N.<br>chs. | S.<br>chs.       | E.<br>chs. | W.<br>chs.       |
| South Boundary                        | N. 87° 28' W. | 40.10         | 1.77       |                  |            | 40.10            |
|                                       | N. 83° 41' W. | 40.11         | 4.40       |                  |            | 39.87            |
|                                       | N. 86° 41' W. | 40.66         | 2.35       |                  |            | 40.59            |
|                                       | N. 89° 33' W. | 40.18         | .31        |                  |            | 40.18            |
|                                       | N. 89° 56' W. | 40.04         | .05        |                  |            | 40.04            |
|                                       | N. 89° 56' W. | 40.28         | .05        | .05              |            | 40.28            |
|                                       | N. 89° 04' W. | 40.00         | .65        |                  |            | 40.00            |
|                                       | S. 89° 46' W. | 40.05         |            | .16              |            | 40.05            |
|                                       | S. 89° 40' W. | 40.04         |            | .23              |            | 40.04            |
|                                       | N. 85° 08' W. | 39.84         | 3.38       |                  |            | 39.70            |
|                                       | S. 89° 38' W. | 40.01         |            | .26              |            | 40.01            |
| N. 87° 00' W.                         | 39.64         | 2.07          |            |                  | 39.59      |                  |
| West Boundary                         | N. 0° 01' W.  | 465.56        | 465.56     |                  |            | .14              |
| North Boundary<br>6th St. Par. N.     | East          | 480.00        |            |                  | 480.00     |                  |
| East Boundary<br>G. and S. R.<br>Mer. | South         | 480.00        |            | 480.00           |            |                  |
| Convergancy                           |               |               |            |                  | .51        |                  |
| Totals                                |               |               | 480.54     | 480.76<br>480.54 | 480.51     | 480.59<br>480.51 |
| Error in Latitude                     |               |               |            | .26              |            |                  |
| Error in Departure                    |               |               |            |                  |            | .08              |



BOOK 3198

|         |                 |               |                 |               |                 |               |
|---------|-----------------|---------------|-----------------|---------------|-----------------|---------------|
|         | 4-29-16 4-28-16 | 4-29-16       | 4-29-16 4-27-16 | 4-27-16       | 4-27-16 4-26-16 | 4-26-16       |
| 5-29-16 | 6<br>5-8-16     | 5<br>5-5-16   | 4<br>5-3-16     | 3<br>5-2-16   | 2<br>5-2-16     | 1<br>5-1-16   |
| 5-1-16  | 7<br>5-10-16    | 8<br>5-8-16   | 9<br>5-4-16     | 10<br>5-4-16  | 11<br>5-3-16    | 12<br>5-3-16  |
| 5-1-16  | 18<br>5-11-16   | 17<br>5-10-16 | 16<br>5-9-16    | 15<br>5-6-16  | 14<br>5-4-16    | 13<br>5-4-16  |
| 5-1-16  | 19<br>5-12-16   | 20<br>5-11-16 | 21<br>5-10-16   | 22<br>5-9-16  | 23<br>5-8-16    | 24<br>5-6-16  |
| 5-1-16  | 30<br>5-12-16   | 29<br>5-12-16 | 28<br>5-11-16   | 27<br>5-11-16 | 26<br>5-9-16    | 25<br>5-9-16  |
| 5-12-16 | 31<br>4-17-16   | 32<br>4-18-16 | 33<br>4-18-16   | 34<br>4-18-16 | 35<br>4-18-16   | 36<br>4-18-16 |

Blue lines indicate surveys by E. N. Thompson, U.S.T. on various dates shown.

Red lines indicate surveys by J.P. Davis, U.S.T., on various dates shown.

182

48

BOOK 3198

CERTIFICATES OF UNITED STATES TRANSITMEN.

We, J. P. Davis and Edward N. Thompson, U. S. Transitmen, hereby certify on honor that, in pursuance of special instructions received from the U. S. Surveyor General of Arizona, for Group No. 52, Arizona, bearing date of the 11th day of December, 1915, we have well, faithfully and truly, in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions and the laws of the United States, resurveyed all those parts or portions of the Gila and Salt River Meridian, through Township 24 North, the 6th. Standard Parallel North, through Range 1 West, and North boundary of Township 23 North, Range 1 West, and the Survey of all those parts or portions of the West boundary and Subdivision lines of Township 24 North, Range 1 West, of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes, and by the diagram on the reverse hereof, as having been executed by us, and under our direction; and we do further certify on honor that all the corners of said resurvey and survey have been reestablished, established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Arizona for Group No. 52. and in the specific manner described in our respective field notes, and that the foregoing are the original field notes of such resurveys and surveys.

J. P. Davis  
U. S. Transitman.

Edward N. Thompson  
U. S. Transitman.

A P P R O V A L .

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, June 20, 1918.

The foregoing field notes of the Resurvey of the Gila and Salt River Meridian, through Township 24 North, 6th. Standard Parallel North, through Range 1 West, and North boundary of Township 23 North, Range 1 West, and Survey of West boundary and Subdivision lines of Township 24 North, Range 1 West, of the Gila and Salt River Base and Meridian, in the State of Arizona, executed by J. P. Davis and Edward N. Thompson, U. S. Transitmen, under special instructions dated December 11, 1915, for Group 52, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the resurveys and surveys they describe, are hereby approved.

Frank O. Frith  
U. S. Surveyor General of Arizona.

~~I certify that the foregoing transcript of the field notes of the above-described resurveys and surveys in Book "D," of Group 52 has been correctly copied from the original notes on file in this office.~~

U. S. Surveyor General of Arizona.