

3727

Original

BOOK "E"

(1)

BOOK 3727

FIELD NOTES

OF THE SURVEY OF THE

East, West, North and South Boundaries,

and all of the Subdivision lines of

Township 18 South, Range 2 West.

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

William H. Thorn, U.S. Cadastral Engineer

and

Otis O. Gould, U.S. Transitman

In the capacity of U. S. Surveyor^s, under Special Instructions dated September 26, 1919 issued by the United States Surveyor General to govern surveys included in Group No. 101, Arizona, which were approved by the Commissioner of the General Land Office, October 22, 1919, and Assignment Instructions dated October 17, 1925.

Survey commenced November 7, 1925

Survey completed December 15, 1925

3727

3727

(1A)

Book "E"

Group 101 - Arizona

BOOK 3727

INDEX DIAGRAM.

PAPAGO INDIAN RESERVATION

| | 10 | 9 | 9 8 | 8 | 7 | 7 | |
|----|-------|-------|--------------|----------|-------|----|---|
| 11 | 6 47 | 5 40 | 4 34 | 3 29 | 2 24 | 1 | 3 |
| | 47 | 46 | 40 39 | 34 | 29 28 | 23 | |
| 11 | 7 46 | 8 39 | 9 34 | 10 28 | 11 23 | 12 | 3 |
| | 45 | 45 | 39 38 | 33 | 28 22 | 22 | 4 |
| 12 | 18 44 | 17 38 | 16 33 | 15 27 | 14 22 | 13 | 4 |
| | 44 | 44 43 | T.185. 38 37 | R.2W. 32 | 27 26 | 21 | |
| 12 | 19 43 | 20 37 | 21 32 | 22 26 | 23 21 | 24 | 4 |
| | 43 | 42 | 37 36 | 31 | 26 | 20 | 5 |
| 13 | 30 42 | 29 36 | 28 31 | 27 25 | 26 20 | 25 | 5 |
| | 41 41 | 41 | 36 30 | 30 | 25 19 | 19 | |
| 13 | 31 40 | 32 35 | 33 30 | 34 24 | 35 19 | 36 | 6 |
| 14 | | | 29 | | | | |
| | 18 17 | 17 | 17 16 | 16 | 15 | 15 | |

PAPAGO INDIAN RESERVATION

————— Surveyed under this group.

----- Unsurveyed.

Book "E"
Group 101-Arizona

Township 18 South, Range 2 West.

DATE DIAGRAM
1925

| | | | | | | |
|-------|-------------|------------|------------|------------|-------------|-------------|
| | 11-14 | 11-13 | 11-13 | 11-13 | 11-12 | 11-12 |
| 11-14 | 6 12-15 | 5 12-15 | 4 12-14 | 3 12-12 | 2 12-11 | 1 12-10 |
| 11-14 | 7 12-15 | 8 12-14 | 9 12-9 | 10 12-8 | 11 12-10 | 12 12-1 |
| 11-14 | 16 12-14 | 17 12-9 | 16 12-8 | 15 12-8 | 14 12-1 | 13 11-30 |
| 11-14 | 19 12-9 | 20 12-7 | 21 12-5 | 22 12-3 | 23 11-30 | 24 11-30 |
| 11-14 | 30 12-7 | 29 12-5 | 28 12-4 | 27 12-3 | 26 11-30 | 25 11-30 |
| 11-14 | 31 12-5 | 32 12-4 | 33 12-4 | 34 12-3 | 35 11-30 | 36 11-11 |
| | 11-11 | 11-11 | 11-11 | 11-11 | 11-11 | 11-11 |

Indicates lines surveyed by William H. Thorn, U.S. C.E., on dates shown thereon

Indicates lines surveyed by Otis O. Gould, U.S. Transitman, on dates shown thereon.

The surveys hereinafter described were commenced on Nov. 7, 1925, and were executed on the dates shown on page 1, hereof, by William H. Thorn, U.S. Cadastral Engineer and Otis O. Gould, U.S. Transitman, using respectively, Young and Sons transits Nos. 8592 and 8541. The instruments are equipped with full vertical circles and improved Smith solar attachments: the horizontal limbs are provided with two double verniers placed opposite to each other reading to single minutes of arc, which is also the least count of the latitude and declination arcs of the solar attachment. Unless otherwise specified, all azimuth determinations are accomplished with the solar attachment.

INSTRUMENT TESTS

The test for transit No. 8592 is identical with that described on page 25, Book "D" of this Group. Following is test of transit No. 8541.

Dec. 6, 1925: in camp near the cor. of secs. 25, 26, 35 and 36, T. 18 S., R. 3 W., Gila and Salt River Base and Meridian, in latitude $31^{\circ}49'30''N.$, longitude $112^{\circ}32'19''W.$, on meridian described on page 2, Book "D" of this Group, at 9h. 00m. a.m. l.m.t., set off $31^{\circ}49'$ on the lat. arc, and $22^{\circ}27'S.$ on the decl. arc, and determine a meridian with the solar, which agrees with the true meridian.

Instrument adjustments having been examined and found correct, at approx. noon, with the lat. arc unchanged, observe the sun on the meridian. The resulting reading on the decl. arc is $22^{\circ}29'S.$, which agrees with the computed decl. of the sun.

At 3h. 00m. p.m. l.m.t., with the lat. arc unchanged, set off $22^{\circ}29'S.$ on the decl. arc and determine a meridian with the solar, which coincides with the true meridian.

As all of the solar observations taken hourly during the usual working hours come within 1' of the true meridian, conclude that the adjustments of the instrument are satisfactory.

Unless otherwise specified all measurements are made with Lufkin steel tapes 5 chains in length, compared with a Lufkin standard steel tape, 1 chain in length and found correct. The measurements are made on the slope, the vertical angles determined with clinometers and the slope measurements properly reduced to true horizontal distances.

(3)

Survey of East Boundary of T.18 S., R.2 W.

| Chains | | |
|--------|---|--|
| | From the cor. of Tps. 17 and 18 S., Rs. 1 and 2 W., set 2 days ago, described in Book "D" of this Group. South, bet. secs. 1 and 6. Over mountainous land; thru scattering undergrowth. Desc. 202 ft. over S. slope. | |
| 14.00 | Dry wash, 10 lks. wide, course S.70°E., Asc. 297 ft. over N. slope. | |
| 40.00 | Set an iron post, 3 ft. long, 1 in. in dia., 14 ins. in the ground to bedrock, with rock, 10 x 10 x 10 ins., marked with cross (+) deposited at bottom, supported by a mound of stone 3 ft. base, 20 ins. high, for $\frac{1}{4}$ sec. cor., with brass cap marked. | |
| | $\begin{array}{c} \uparrow \\ S1 S6 \\ 1925 \end{array}$ | |
| | No trees available. Asc. 206 ft. over N. slope. | |
| 46.06 | Spur, slopes S.70°E. Raise a mound of stone 3 ft. base, 4 ft. high on line. Desc. 449 ft. over S. slope. | |
| 64.00 | Dry wash, 10 lks. wide, course S.70°E. | |
| 66.00 | Asc. 193 ft. over broken NE. slope. | |
| 80.00 | Set an iron post, 3 ft. long, 2 ins. in dia., on bedrock, with rock, 6 x 6 x 4 ins., marked with cross (+) deposited at bottom, supported by a mound of stone, 3 ft. base 2 $\frac{1}{2}$ ft. high, for cor. of secs. 1, 6, 7 and 12, with brass cap marked. | |
| | $\begin{array}{c} T18S \\ R2W R1W \\ S1 S6 \\ \hline S12 S7 \\ 1925 \end{array}$ | |
| | No trees available. Land: mountainous. Soil: rocky, 4th rate. Timber: none. Undergrowth: greasewood, palo verde, sage and cactus. | |
| | ----- | |
| | South, bet. secs. 7 and 12. Over mountainous land; thru dense undergrowth. Asc. 47 ft. over NE. slope. | |
| 1.98 | Spur, slopes E. Raise a mound of stone, 5 ft. base, 4 ft. high on line. Desc. 139 ft. over SE. slope. | |
| 9.80 | Ravine, course E. Asc. 466 ft. over NE. slope. | |
| 29.06 | Raise a mound of stone, on line, 4 ft. base 3 ft. high. | |
| 34.00 | Desc. 90 ft. over S. slope. | |
| 40.00 | Set an iron post, 3 ft. long, 1 in. in dia., on bedrock, with rock, 12 x 10 x 10 ins., marked with cross (+), deposited at bottom, supported by a mound of stone, 4 ft. base 2 $\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor., with brass cap marked. | |
| | $\begin{array}{c} \uparrow \\ S12 S7 \\ 1925 \end{array}$ | |
| | No trees available. Desc. 124 ft. over S. slope. | |
| 43.50 | Head of ravine, course SE. Along E. slope. | |
| 47.00 | Asc. 84 ft. over NE. slope. | |
| 51.67 | Spur, slopes SE. Raise a mound of stone, 3 ft. base, 3 ft. high on line. Desc. 504 ft. over SW. slope. | |
| 67.00 | Enter canyon, course S.70°E. | |
| 68.18 | Mound of stone, 3 ft. base, 3 ft. high, brs. E., 10 lks. dist. | |

Survey of East Boundary of T.18 S., R.2 W.

Chains
 70.20 Dry wash, 20 lks. wide, course S.70°E. Asc. 139 ft. over NE slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 14 ins. in the ground to bedrock, with rock marked with cross (+) deposited at bottom, supported by a mound of stone, 3 ft. base, 1½ ft. high, for cor. of secs. 7,12,13 and 18, with brass cap marked

T18S
 R2W R1W
 S12 | S7
 S13 | S18
 1925

No trees available.
 Land: mountainous.
 Soil: rocky, 4th rate.
 Timber: none.
 Undergrowth: greasewood, sage, palo verde and cactus.

South, bet. secs. 13 and 18.
 Over mountainous land; thru dense undergrowth.
 Asc. 213 ft. over NE. slope.
 9.02 Spur, slopes S.70°E.; raise a mound of stone, 4 ft. base, 3 ft. high, on line. Desc. 394 ft. over S. slope.
 33.00 Dry wash, 10 lks. wide, course S.70°E.
 34.00 Asc. 141 ft. over broken NE. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 6 ins. in the ground to bedrock, with rock marked with cross (+) deposited at bottom, supported by a mound of stone, for ¼ sec. cor., with brass cap marked

S13 | S18
 1925

No trees available.
 Asc. 508 ft. over broken NE. slope.
 60.48 Ridge, brs. NW. and SE. Raise a mound of stone 3 ft. base, 3 ft. high, on line. Desc. 512 ft. over SW. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 4 ins. in the ground to bedrock, with rock marked with cross (+) deposited at bottom, supported by a mound of stone, 3 ft. base 2 ft. high, for cor. of secs. 13,18,19 and 24, with brass cap marked

T18S
 R2W R1W
 S13 | S18
 S24 | S19
 1925

No trees available.
 Land: mountainous.
 Soil: rocky, 4th rate.
 Timber: none.
 Undergrowth: greasewood, palo verde and cactus.

South, bet. secs. 19 and 24.
 Over rolling land; thru dense undergrowth.
 Desc. 270 ft. over broken SW. slope.
 22.50 Leave hills, bearing NW. and SE. Over sandy flat.
 31.50 Dry wash, 10 lks. wide, course SE.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¼ sec. cor., with brass cap marked

Survey of East Boundary of T.18 S., R.2 W.

Chains

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S24} | \text{S19} \\ \hline 1925 \end{array}$$

No trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of cor.

53.80

Dry wash, 10 lks. wide, course SE.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 6 ins. in the ground to bedrock, with rock 12 x 10 x 10 marked with cross (+) deposited at bottom, supported by a mound of stone, 3 ft. base, 2 ft. high, for cor. of secs. 19, 24, 25 and 30, with brass cap marked

$$\begin{array}{c} \text{T18S} \\ \text{R2W R1W} \\ \hline \text{S24} | \text{S19} \\ \hline \text{S25} | \text{S30} \\ \hline 1925 \end{array}$$

No trees available.

Land: rolling and level.

Soil: sandy and rocky, 2nd and 3rd rates.

Timber: none.

Undergrowth: greasewood, sage, mesquite, palo verde, cactus.

1.00

South bet. secs. 25 and 30.

Over level land; thru dense undergrowth.

13.19

Leave flat. Asc. 90 ft. over NE. slope.

17.90

Spur, slopes SE. Desc. 124 ft. over SE. slope.

40.00

Over flat.

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S25} | \text{S30} \\ \hline 1925 \end{array}$$

from which

A mesquite, 6 ins. in dia., brs. N. 9° 30' E., 28 lks. dist., marked $\frac{1}{4}$ S30 BT.A mesquite, 6 ins. in dia., brs. S. 10 $\frac{1}{2}$ ° W., 100 lks. dist., marked $\frac{1}{4}$ S25 BT.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 25, 30, 31 and 36, with brass cap marked

$$\begin{array}{c} \text{T18S} \\ \text{R2W R1W} \\ \hline \text{S25} | \text{S30} \\ \hline \text{S36} | \text{S31} \\ \hline 1925 \end{array}$$

from which

A mesquite, 6 ins. in dia., brs. N. 12 $\frac{1}{2}$ ° E., 216 lks. dist., marked T18S R1W S30 BT.A mesquite, 6 ins. in dia., brs. N. 3 $\frac{1}{2}$ ° W., 344 lks. dist., marked T18S R2W S25 BT.

No other trees available.

Dig pits 18 x 18 x 12 ins., one in each sec. 5 ft. dist.

Land: level and rolling.

Soil: adobe, 2nd rate.

Timber: none.

Undergrowth: greasewood, sage, mesquite and cactus.

Survey of East Boundary of T.18 S., R. 2 W.

Chains.

South bet. secs. 31 and 36.
Over level land; thru dense undergrowth.
40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked;

S36 | S31
1925

from which

A mesquite, 5 ins. in dia., brs. S.5°E., 246 lks. dist., marked $\frac{1}{4}$ S31 BT.

A mesquite, 5 ins. in dia., brs. S.47°W., 209 lks. dist., marked $\frac{1}{4}$ S36 BT.

80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 26 ins. in the ground, for cor. of T.18 S., R. 2 W., and Frac. T.19 S., R. 2 W., with brass cap marked

T18S
R2W | R1W
S36 | S31
S1 | S6
T19S
1925

from which

A mesquite, 4 ins. in dia., brs. N.58°E., 5 lks. dist., marked BT.

A mesquite, 4 ins. in dia., brs. S.14°E., 117 lks. dist., marked BT.

A mesquite, 4 ins. in dia., brs. S.28 $\frac{1}{2}$ °W., 165 lks. dist., marked BT.

A mesquite, 4 ins. in dia., brs. N:46 $\frac{1}{2}$ °W., 172 lks. dist., marked BT.

Land: level, drains SE.

Soil: adobe, 2nd rate.

Timber: none.

Undergrowth: greasewood, sage, mesquite and cactus.

Survey of North Boundary of T.18 S., R.2 W.

Chains

From the cor. of Tps. 17 and 18 S., Rs. 1 and 2 W., described in Book "D" of this Group.

West, bet. secs. 1 and 36.

Over rolling land; thru scattering undergrowth.

Desc. 109 ft. over SW. slope.

28.00

Draw, course S. Asc. 186 ft. over SE. slope.

40.00

Set an iron post, 3 ft. long, 1 in. in dia., 2 ins. in the ground to bedrock, with rock 12 x 24 x 24 ins., marked with cross (+) deposited at bottom, supported by a mound of stone 3 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap marked

S36
S1
1925

No trees available.

Asc. 400 ft. over broken SE. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 1, 2, 35 and 36, with brass cap marked

T17SR2W
S35 | S36
S2 | S1
T18S
1925

No trees available.

Raise a mound of stone, 3 ft. base, 3 ft. high W. of cor.

Land: rolling.

Soil: rocky, 2nd rate.

Timber: none.

Undergrowth: palo verde, ocotillo, cactus.

West, bet. secs. 2 and 35.

Over mountainous land; thru scattering undergrowth.

Asc. broken SE. slope 142 ft.

12.80

Small spur, slopes SE. Desc. 40 ft. over SW. slope.

14.40

Large ravine, course SE. Asc. 727 ft. over broken NE. slope.

40.00

Set an iron post, 3 ft. long, 1 in. in dia., 8 ins. in the ground to bedrock, with rock 18 x 12 x 6 ins., marked with cross (+) deposited at bottom, supported by a mound of stone 3 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap marked

S35
S2
1925

No trees available.

Asc. 310 ft. over NE. slope.

51.20

Top of ascent. Over plateau.

51.72

U.S.G.S. signal brs. S. 45° 15' E., approx. 20.00 chs. dist. Raise a mound of stone 3 ft. base, 2 ft. high, on line.

59.48

U.S.G.S. signal brs. S. 56° 30' E.; raise a mound of stone 3 ft. base 2 ft. high, on line.

Desc. 326 ft. over W. slope.

79.00

True point for sec. cor. falls on inaccessible slope of cliff. Set an iron post, 3 ft. long, 2 ins. in dia., on bedrock, with rock, 12 x 12 x 12 ins., marked with cross (+) deposited at bottom, supported by a mound of stone 3 ft. base, 2 $\frac{1}{2}$ ft. high, for wit. cor. to cor. of secs. 2, 3, 34 and 35, with brass cap marked

Survey of North Boundary of T.18 S., R.2 W.

Chains

| | |
|---------|-----|
| T17NR2W | |
| WC S34 | S35 |
| S3 | S2 |
| T18S | |
| 1925 | |

No trees available.
 80.00 Point for cor. of secs. 2,3,34 and 35 is inaccessible.
 Land: mountainous.
 Soil: rocky, 4th rate.
 Timber: none.
 Undergrowth: greasewood, mesquite, sage, ocatillo and
 palo verde.

From true point for cor. of secs. 2,3,34 and 35.
 West, bet. secs. 3 and 34.
 Over mountainous land; thru scattering undergrowth.
 Desc. broken W. slope 456 ft.
 10.00 Cliff, 75 ft. high, faces W.
 17.00 Ravine, course N. Asc. 419 ft. over broken E. slope.
 29.50 N. end of peak on ridge bearing N. and S. Desc. 341 ft.
 over W. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., on cross (+)
 on bedrock, supported by a mound of stone 3 ft. base,
 2½ ft. high, for ¼ sec. cor., with brass cap marked

| | |
|------|----|
| S34 | |
| 4 | S3 |
| 1925 | |

No trees available.
 Desc. 547 ft. over broken W. slope.
 61.85 Cliff, 100 ft. high, faces W.
 75.00 Dry wash, 40 lks. wide, in canyon, course S.20°W. Asc.
 196 ft. over broken E. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., on bedrock,
 with rock 12 x 12 x 6 ins. deposited at bottom, sup-
 ported by a mound of stone, 3 ft. base 2½ ft. high,
 for cor. of secs. 3,4,33 and 34, with brass cap marked

| | |
|---------|-----|
| T17SR2W | |
| S33 | S34 |
| S4 | S3 |
| T18S | |
| 1925 | |

No trees available.
 Land: mountainous.
 Soil: rocky, 4th rate.
 Timber: none.
 Undergrowth: greasewood, mesquite, palo verde, ocatillo
 and cactus.

West, bet. secs. 4 and 33.
 Over mountainous land; thru scattering undergrowth.
 Asc. 34 ft. over E. slope.
 1.14 Spur, slopes S.20°W. Raise a mound of stone 3 ft. base,
 2 ft. high, on line. Desc. 510 ft. over broken SW.
 slope.
 35.00 Leave mountainous, over rolling land.
 39.70 Small knoll, brs. N. and S. Raise a mound of stone, 3 ft.
 base, 2 ft. high.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
 the ground for ¼ sec. cor., with brass cap marked

Survey of the North Boundary of T.18 S., R.2 W.

Chains

S33
S4
1925

No trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

54.00 Dry wash, 20 lks. wide, course SW.

61.49 Dry wash, 20 lks. wide, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 20 ins. in the ground, supported by a mound of stone, for cor. of secs. 4,5,32 and 33, with brass cap marked

T17SR2W
S32 | S33
S5 | S4
T18S
1925

No trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land: rolling and mountainous.

Soil: rocky, 3rd rate.

Timber: none.

Undergrowth: mesquite, greasewood, palo verde, sage and cactus.

West, bet. secs. 5 and 32.

Over gently rolling land; thru dense undergrowth.

39.00 Dry wash, 20 lks. wide, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S32
S5
1925

from which

A mesquite, 6 ins. in dia., brs. S.53 $\frac{1}{4}$ °W., 73 lks. dist., marked $\frac{1}{4}$ S2 BT.

A palo verde, 6 ins. in dia., brs. N.3°W., 141 lks. dist., marked $\frac{1}{4}$ S35 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 6 ins. in the ground, supported by a mound of stone, for cor. of secs. 5,6,31 and 32, with brass cap marked

- T17SR2W
S31 | S32
S6 | S5
T18S
1925

from which

A palo verde, 6 ins. in dia., brs. N.39 $\frac{1}{2}$ °E., 50 lks. dist., marked T17S R2W S32 BT.

A palo verde, 6 ins. in dia., brs. S.57 $\frac{1}{4}$ °E., 89 lks. dist., marked T18S R2W S5 BT.

A palo verde, 6 ins. in dia., brs. S.11 $\frac{1}{2}$ °W., 65 lks. dist., marked T18S R2W S6 BT.

A palo verde, 6 ins. in dia., brs. N.83 $\frac{1}{2}$ °W., 125 lks. dist., marked T17S R2W S31 BT.

Land: gently rolling.

Soil: rocky adobe.

Timber: none.

Undergrowth: greasewood, palo verde, sage, mesquite and cactus.

Survey of the North Boundary of T.18 S., R. 2 W.

Chains.

West, bet. secs. 6 and 31.
 Over gently rolling land; thru dense undergrowth.
 11.80 Dry wash, 20 lks. wide, course S.20°W.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 8 ins. in
 the ground, with rock marked with cross (+) deposited
 at bottom, supported by a mound of stone, 3 ft. base,
 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap marked

S31
 $\frac{1}{4}$ S6
 1925

No trees available.
 47.00 Dim road, brs. NE. and SW.
 79.40 (True point for Tp. cor. falls in wash) Set an iron
 post, 3 ft. long, 3 ins. in dia., 26 ins. in the
 ground for witness cor. to cor. of Ts. 17 and 18 S., R. 2
 and 3 W., with brass cap, marked

T17S
 R3W R2W
 WC $\frac{S36}{S1}$ $\frac{S31}{S6}$
 T18S
 1925

No trees available.
 Raise a mound of stone, 3 ft. base, 3 ft. high, S. of
 cor.
 80.00 True point for Tp. cor. falls in wash, 10 lks. wide, course SW.
 Raise a mound of stone 3 ft. base, 3 ft. high, at this point.
 Land: gently rolling.
 Soil: rocky, 3rd rate.
 Timber: none.
 Undergrowth: mesquite, sage, greasewood, palo verde and
 cactus.

Survey of the West Boundary of T.18 S., R.2 W.

Chains

From the point for the cor. of Tps. 17 and 18 S., Rs. 2 and 3 W., hereinbefore described.
 South, bet. secs. 1 and 6.
 Over rolling land; thru dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in the ground, supported by a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\begin{array}{c} \uparrow \\ S1 | S6 \\ \hline 1925 \end{array}$

from which
 An ironwood, 5 ins. in dia., brs. S.17°E., 87 lks. dist., marked BT.
 An ironwood, 5 ins. in dia., brs. N.56 $\frac{1}{2}$ °W., 110 lks. dist., amrked BT.

45.00 Leave rolling; over flat land.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 1,6,7 and 12, with brass cap marked

$\begin{array}{c} T18S \\ R3W | R2W \\ \hline S1 | S6 \\ \hline S12 | S7 \\ \hline 1925 \end{array}$

No trees available.
 Dig pits, 18 x 18 x 12 ins., one in each sec. 3 ft. dist.
 Land: level and rolling.
 Soil: adobe, 3rd rate.
 Timber: none.
 Undergrowth: greasewood, ironwood, ocatillo, mesquite, palo verde and cactus.

South, bet. secs. 7 and 12.
 Over flat; thru dense undergrowth;

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\begin{array}{c} \uparrow \\ S12 | S7 \\ \hline 1925 \end{array}$

from which
 A mesquite, 6 ins. in dia., brs. S.1 $\frac{1}{2}$ °E., 206 lks. dist., marked $\frac{1}{4}$ S7 BT.
 A mesquite, 6 ins. in dia., brs. N.16 $\frac{1}{2}$ °W., 207 lks. dist., marked $\frac{1}{4}$ S12 BT.

76.50 Indian road, brs. S.20°E. and N.20°W.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 7,12,13 and 18, with brass cap marked

$\begin{array}{c} T18S \\ R3W | R2W \\ \hline S12 | S7 \\ \hline S13 | S18 \\ \hline 1925 \end{array}$

from which
 A mesquite, 6 ins. in dia., brs. N.85 $\frac{1}{4}$ °E., 100 lks. dist., marked T18S R2W S7 BT.
 A mesquite, 6 ins. in dia., brs. S.42°E., 100 lks. dist., marked BT.
 A mesquite, 6 ins. in dia., brs. S.9 $\frac{1}{4}$ °W., 108 lks.


Survey of the West Boundary of T.18 S., R.2 W.

Chains

dist., marked BT.
 A mesquite, 6 ins. in dia., brs. N.42½°W., 96 lks.
 dist., marked BT.
 Land: flat, drains SW.
 Soil: adobe, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite, palo verde and cactus.

40.00

South, bet. secs. 13 and 18.
 Over level land; thru dense undergrowth.
 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for ¼ sec. cor., with brass cap marked



from which


A mesquite, 6 ins. in dia., brs. N.28°E., 138 lks.
 dist., marked BT.
 A mesquite, 6 ins. in dia., brs. N.76½°W., 103 lks.
 dist., marked ¼ S13 BT.

50.00

Old road, brs. NW. and S.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, with brass cap marked




from which

A mesquite, 5 ins. in dia., brs. N.78°E., 190 lks.
 dist., marked T18S R2W S18 BT.
 A mesquite, 4 ins. in dia., brs. S.10°E., 68 lks.
 dist., marked T18S R2W S19 BT.
 A mesquite, 6 ins. in dia., brs. S.62°W., 72 lks.
 dist., marked T18S R3W S24 BT.
 A mesquite, 4 ins. in dia., brs. N.0°30'W., 51 lks.
 dist., marked BT.

Land: level.
 Soil: adobe, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite, ironwood and cactus.

40.00

South, bet. secs. 19 and 24.
 Over level land; thru dense undergrowth.
 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¼ sec. cor., with brass cap marked



from which

A mesquite, 6 ins. in dia., brs. S.11°E., 57 lks.
 dist., marked ¼ S19 BT.
 A mesquite, 6 ins. in dia., brs. S.67°W., 118 lks.
 dist., marked ¼ S24 BT.


80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 19, 24, 25 and 30, with

Survey of the West Boundary of T.18 S., R22 W.

Chains

brass cap marked




from which

- A mesquite, 6 ins. in dia., brs. N.47 $\frac{1}{2}$ °E., 78 lks. dist., marked T18S R2W S19 BT.
- A mesquite, 5 ins. in dia., brs. S.17 $\frac{1}{2}$ °E., 6 lks. dist., marked BT.
- A mesquite, 5 ins. in dia., brs. S.11°W., 79 lks. dist., marked BT.
- A mesquite, 6 ins. in dia., brs. N.43 $\frac{1}{2}$ °W., 117 lks. dist., marked T18S R3W S24 BT.

Land: level.
 Soil: adobe, 1st and 2nd rates.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite, and cactus.

49.00

South, bet. secs. 25 and 30.
 Over level land; thru dense undergrowth.
 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for sec. cor., with brass cap marked




from which

- A mesquite, 4 ins. in dia., brs. N. 54°E., 6 lks. dist., marked $\frac{1}{4}$ S30 BT.
- A mesquite, 4 ins. in dia., brs. S.61 $\frac{1}{2}$ °W., 15 lks. dist., marked $\frac{1}{4}$ S25 BT.

79.60
80.00

Road, brs. NW. to Ajo and SE.
 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 25, 30, 31 and 36, with brass cap marked



from which

- A mesquite, 6 ins. in dia., brs. N.42°E., 72 lks. dist., marked T18S R2W S30 BT.
- A mesquite, 6 ins. in dia., brs. S.47°E., 40 lks. dist., marked T18S R2W S31 BT.
- A mesquite, 4 ins. in dia., brs. S.38°W., 68 lks. dist., marked BT.
- A mesquite, 6 ins. in dia., brs. N.35°W., 51 lks. dist., marked T18S R3W S25 BT.

Land: level.
 Soil: adobe, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite and cactus.

36.50

South, bet. secs. 31 and 36.
 Over level land; thru dense undergrowth.
 Old road, brs. NW. and SE.

X

Survey of the West Boundary of T.18 S., R.2 W.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

| | |
|------|-----|
| S36 | S31 |
| 1925 | |

from which

A mesquite, 6 ins. in dia., brs. N.88°E., 33 lks. dist., marked $\frac{1}{4}$ S31 BT.A mesquite, 6 ins. in dia., brs. N.15 $\frac{1}{2}$ °W., 170 lks. dist., marked $\frac{1}{4}$ S36 BT.

41.50 Dry wash, 20 lks. wide, course N.30°W.

71.60 Road, brs. NW. and SE.

80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 16 ins. in the ground, supported by a mound of stone, 3 ft. base 1 $\frac{1}{2}$ ft. high, for cor. of Ts. 18 S., Rs. 2 and 3 W., and frac. Ts. 19 S., Rs. 2 and 3 W., with brass cap, marked

| | |
|------|-----|
| T18S | |
| R3W | R2W |
| S36 | S31 |
| S1 | S6 |
| T19S | |
| 1925 | |

from which

A mesquite, 6 ins. in dia., brs. N.36°E., 153 lks. dist., marked T18S R2W S31 BT.

An ironwood, 10 ins. in dia., brs. S.77°E., 163 lks. dist., marked T19S R2W S6 BT.

A mesquite, 6 ins. in dia., brs. S.55°W., 141 lks. dist., marked T19S R3W S1 BT.

A palo verde, 6 ins. in dia., brs. N.20 $\frac{1}{2}$ °W., 84 lks. dist., marked T18S R3W S36 BT.

Land: level.

Soil: adobe, 2nd rate.

Timber: none.

Undergrowth: greasewood, sage, mesquite and palo verde.

Survey of the South Boundary of T.18 S., R.2 W.

Chains

From cor. of Ts. 18 S., Rs. 2 and 3 W., and Frac. Ts. 19 S., Rs. 2 and 3 W., hereinbefore described.
 East, on a random line, on the S. bdy. of the Tp., setting temp. cor. at 40.00 ch. intervals.
 480.75 Fall 44 lks. S. of cor. of Ts. 18 S., Rs. 1 and 2 W., and Frac. Ts. 19 S., Rs. 1 and 2 W., hereinbefore described.
 Thence
 S. 89° 57' W., on a true line, bet. secs. 1 and 36.
 Over level land; thru dense undergrowth.
 14.10 Dry wash, 10 lks. wide, course S. 30° E.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S36
 S1
 1925

No trees available.
 Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 1, 2, 35 and 36, with brass cap marked

T18SR2W
 S35 | S36
 S2 | S1
 T19S
 1925

- from which
- A mesquite, 4 ins. in dia., brs. N. 72° E., 45 lks. dist., marked BT.
 - A mesquite, 6 ins. in dia., brs. S. 19 1/4° E., 107 lks. dist., marked T19S R2W S1 BT.
 - A mesquite, 4 ins. in dia., brs. S. 41 1/4° W., 133 lks. dist., marked BT.
 - A mesquite, 6 ins. in dia., brs. N. 29 1/4° W., 27 lks. dist., marked T18S R2W S35 BT.

Land: level, drains SE.
 Soil: adobe, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite and cactus.

S. 89° 57' W., bet. secs. 2 and 35.
 Over level land; thru dense undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S35
 S2
 1925

from which

- A mesquite, 5 ins. in dia., brs. S. 63 1/2° W., 54 lks. dist., marked S2 BT
- A mesquite, 8 ins. in dia., brs. N. 44° W., 76 lks. dist., marked S35 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 2, 3, 34 and 35, with brass cap marked

T18SR2W
 S34 | S35
 S3 | S2
 T19S
 1925

from which

Survey of the South Boundary of T.18 S., R.2 W.

Chains

- A mesquite, 8 ins. in dia., brs. N.39°E., 291 lks. dist., marked T18S R2W S35 BT.
- A mesquite, 8 ins. in dia., brs. S.24°E., 65 lks. dist., marked BT (only).
- A mesquite, 4 ins. in dia., brs. S.24½°W., 27 lks. dist., marked BT.
- A mesquite, 6 ins. in dia., brs. N.26½°W., 45 lks. dist., marked T18S R2W S34 BT.

Land: level, drains S4.
 Soil: adobe, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite and cactus.

40.00

S.89°57'W., bet. secs. 3 and 34.
 Over level land; through dense undergrowth.
 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¼ sec. cor., with brass cap marked

S34
~~S3~~
 1925

from which

- A mesquite, 8 ins. in dia., brs. S.38½°E., 59 lks. dist., marked ~~¼~~ S3 BT.
- A mesquite, 4 ins. in dia., brs. N.76°E., 17 lks. dist., marked BT.

51.40
 80.00

Road, brs. S4. to Manager's Dam and NW. to Perseniambe.
 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 3, 4, 33 and 34, with brass cap marked

T18SR2W
 S33 | S34
 S4 | S3
 T19S
 1925

from which

- A mesquite, 6 ins. in dia., brs. N.65°E., 60 lks. dist., marked T18SR2W S34 BT.
- A mesquite, 6 ins. in dia., brs. S.10½°E., 151 lks. dist., marked T19S R2W S3 BT.
- A mesquite, 6 ins. in dia., brs. S.14°W., 58 lks. dist., marked T19S R2W S4 BT.
- A mesquite, 12 ins. in dia., brs. N.1°W., 34 lks. dist., marked T18S R2W S33 BT.

Land: level, drains S4.
 Soil: adobe, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, mesquite, sage and cactus.

40.00

S.89°57'W., bet. secs. 4 and 33.
 Over level land; thru dense undergrowth.
 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¼ sec. cor., with brass cap marked

S33
~~S4~~
 1925

from which

- A mesquite, 9 ins. in dia., brs. S. 44½°W., 76 lks. dist., marked ¼ S4 BT.
- A mesquite, 9 ins. in dia., brs. N.29½°W., 97 lks. dist., marked ¼ S33 BT.

Survey of the South Boundary of T.18 S., R.2 W.

Chains
80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 4, 5, 32 and 33, with brass cap marked

T18SR2W
S32 | S33
S5 | S4
T19S
1925

from which

- A mesquite, 5 ins. in dia., brs. N. 55 1/4° E., 49 lks. dist., marked T18S R2W S33 BT.
- A mesquite, 6 ins. in dia., brs. S. 77 1/4° E., 88 lks. dist., marked T19SR2W S4 BT.
- A mesquite, 6 ins. in dia., brs. S. 81 1/2° W., 39 lks. dist., marked T19S R2W S5 BT.
- A mesquite, 6 ins. in dia., brs. N. 37° W., 100 lks. dist., marked T18S R2W S32 BT.

Land: level.
Soil: adobe, 2nd rate.
Timber: none.
Undergrowth: greasewood, mesquite, sage and cactus.

40.00

S. 89° 57' W., bet. secs. 5 and 32.
Over level land; thru dense undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

S32
S5
1925

from which

- A mesquite, 6 ins. in dia., brs. N. 73 1/4° E., 105 lks. dist., marked 1/4 S32 BT.
- A mesquite, 6 ins. in dia., brs. S. 45° W., 101 lks. dist., marked 1/4 S5 BT.

74.10

Road, brs. N. 20° W. and S. 20° E.

78.00

Over rock-strewn land.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground, for cor. of secs. 5, 6, 31 and 32, with brass cap marked

T18SR2W
S31 | S32
S6 | S5
T19S
1925

No trees available.
Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Land: level, drains NE.
Soil: adobe, 2nd rate.
Timber: none.
Undergrowth: greasewood, sage, mesquite and cactus.

2.30

39.80

40.00

S. 89° 57' W., bet. secs. 6 and 31.
Over level land; thru dense undergrowth.
Dry wash, 10 lks. wide, course N.
Dry wash, 10 lks. wide, course N.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

Survey of the South Boundary of T.18 S., R.2 W.

Chains

$\frac{1}{4}$ $\frac{331}{36}$
1925

No trees available.
Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

44.70
56.50
67.50
80.75

Dry wash, 10 lks. wide, course N.
Dry wash, 20 lks. wide, course N.
Road bears NW and SE 19;
The cor. of Ts. 18 S., Rs. 2 and 3 W., and frac. Ts. 19 S., Rs. 2 and 3 W., hereinbefore described.

Boundaries of Township 18 South, Range 2 West.
Latitudes, departures and closing errors


| Line designated | True bearing | Distance | Latitudes | | Departures | |
|------------------------------|---------------|----------|-----------|--------|------------|--------|
| | | | N. | S. | E. | W. |
| South Boundary | S. 89° 57' W. | 480.75 | | .44 | | 480.75 |
| West Boundary | North | 480.00 | 480.00 | | | |
| North Boundary | East | 480.00 | | | 480.00 | |
| East Boundary | South | 480.00 | | 480.00 | | |
| Convergency | | | | | .45 | |
| Totals - - - - - | | | 480.00 | 480.44 | 480.45 | 480.75 |
| | | | | 480.00 | | 480.45 |
| Error in latitude - - - - - | | | -0.44 | | | |
| Error in departure - - - - - | | | | | 0.30 | |

Survey of Subdivision of Township 18 South, Range 2 West

Chains


From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.
N. 0° 01' W., bet. secs. 35 and 36.

40.00 Over level land; thru dense undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



from which
A mesquite, 5 ins. in dia., brs. S. 1° E., 135 lks. dist., marked $\frac{1}{4}$ S36 BT.
A mesquite, 8 ins. in dia., brs. N. 26 $\frac{1}{2}$ ° W., 71 lks. dist., marked $\frac{1}{4}$ S35 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 25, 26, 35 and 36, with brass cap marked




from which
A mesquite, 8 ins. in dia., brs. S. 54 $\frac{1}{2}$ ° E., 71 lks. dist., marked T18S R2W S36 BT.
A mesquite, 6 ins. in dia., brs. S. 2° W., 21 lks. dist., marked T18S R2W S35 BT.
A mesquite, 6 ins. in dia., brs. N. 50° W., 149 lks. dist., marked T18S R2W S26 BT.
No other trees available.
Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.

Land: level, drains SE.
Soil: adobe, 2nd rate.
Timber: none.
Undergrowth: greasewood, sage, mesquite and cactus.

20.00 N. 89° 57' E., on a random line bet. secs. 25 and 36.
Set ~~amp.~~ $\frac{1}{4}$ sec. cor.
80.00 Fall 2 lks. N. of cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described

Thence
S. 89° 58' W., on a true line bet. secs. 25 and 36.

40.00 Over level land; thru dense undergrowth;
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



from which
A mesquite, 6 ins. in dia., brs. S. 52 $\frac{1}{2}$ ° W., 87 lks. dist., marked $\frac{1}{4}$ S36 BT.
A mesquite, 6 ins. in dia., brs. N. 77° W., 79 lks. dist., marked $\frac{1}{4}$ S25 BT.

80.00 The cor. of secs. 25, 26, 35, and 36.

Land: level, drains SE.
Soil: adobe, 2nd rate.
Timber: none.
Undergrowth: greasewood, sage and mesquite.

000000

N. 0° 01' W., bet. secs. 25 and 26.
Over level land; thru dense undergrowth.

Survey of Subdivision of Township 18 South, Range 2 West

Chains
40.00

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S26 | S25
1925

from which

A mesquite, 6 ins. in dia., brs. S.81 $\frac{1}{2}$ °E., 73 lks. dist., marked $\frac{1}{4}$ S25 BT.

A mesquite, 6 ins. in dia., brs. S.2 $\frac{1}{2}$ °W., 73 lks. dist., marked $\frac{1}{4}$ S26 BT.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 23, 24, 25 and 26, with brass cap marked

T18SR2W
S23 | S24
S26 | S25
1925

from which

A mesquite, 14 ins. in dia., brs. N.43 $\frac{1}{2}$ °E., 82 lks. dist., marked T18S R2W S24 BT.

A mesquite, 6 ins. in dia., brs. S.2°E., 110 lks. dist., marked T18S R2W S25 BT.

A mesquite, 6 ins. in dia., brs. S.35 $\frac{1}{2}$ °W., 154 lks. dist., marked T18S R2W S26 BT.

A mesquite, 6 ins. in dia., brs. N.57°W., 82 lks. dist., marked T18S R2W S23 BT.

Land: level; drains SE.

Soil: adobe, 2nd rate.

Timber: none.

Undergrowth: greasewood, sage and mesquite.

40.00

N.89°58'E., on a random line, bet. secs. 24 and 25. Set temp. $\frac{1}{4}$ sec. cor.

79.96

Fall 2 lks. N. of the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.

Thence

S. 89°59'W., on a true line bet. secs. 24 and 25.

Over mountainous land; through dense undergrowth.

Asc. 342 ft. over NE. slope.

16.60

Ridge, brs. NW. and SE. Desc. 309 ft. over W. slope.

29.00

Foot of hills, brs. NW. and SW. Over flat.

39.98

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S24
S25
1925

from which

A mesquite, 6 ins. in dia., brs. S.54°E., 161 lks. dist., marked $\frac{1}{4}$ S25 BT.

A mesquite, 10 ins. in dia., brs. N.77 $\frac{1}{2}$ °W., 44 lks. dist., marked $\frac{1}{4}$ S24 BT.

62.00

Dry wash, 10 lks. wide, course S.25°E.

79.96

The cor. of secs. 23, 24, 25, and 26.

Land: level and mts.

Soil: adobe, 2nd rate.

Timber: none.

Undergrowth: greasewood, sage, mesquite and cactus.

N. 90° 11' W., bet. secs. 23 and 24.

Survey of Subdivision of Township 18 South, Range 2 West

| | |
|--------|--|
| Chains | N.0°1'W., bet. secs. 23 and 24. Over level land; thru dense undergrowth. Dry wash, 10 lks. wide, course S.20°E. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked |
| 38.80 | |
| 40.00 | |
| | |
| | from which A mesquite, 8 ins. in dia., brs. S.40 $\frac{1}{2}$ °E., 57 lks. dist., marked $\frac{1}{4}$ S24 BT. A mesquite, 6 ins. in dia., brs. N.47 $\frac{1}{2}$ °W., 74 lks. dist., marked $\frac{1}{4}$ S23 BT. |
| 59.00 | Dry Wash, 10 lks. wide, course S.20°E. |
| 80.00 | Set an iron post, 3 ft. long, 2 ins. in dia., 20 ins. in the ground, supported by a mound of stone, for cor. of secs. 13,14,23 and 24, with brass cap marked |
| | |
| | from which An ironwood, 6 ins. in dia., brs. S.75 $\frac{1}{2}$ °W., 84 lks. dist., marked T18S R2W S24 BT. A palo verde, 6 ins. in dia., brs. S.21 $\frac{1}{2}$ °W., 18 lks. dist., marked T18S R2W S23 BT. No other trees available. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. |
| | Land: level. Soil: adobe, 2nd and 3rd rates. Timber: none. Undergrowth: greasewood, sage, mesquite, palo verde and ironwood. |
| | ----- |
| | N.89°59'E., on a random line bet. secs. 13 and 24. |
| 40.00 | Set temp. $\frac{1}{4}$ sec. cor. |
| 80.02 | Fall 16 lks. S. of the cor. of secs. 13,18,19 and 24, on the E. bdy. of the Tp., hereinbefore described. |
| | Thence S.89°52'W., on a true line bet. secs. 13 and 24. Over rolling land; thru dense undergrowth. Desc. broken SW. slope 169 ft. |
| 25.00 | Leave hills, bearing NW. and SE. Over flat. |
| 34.00 | Dry wash, 20 lks. wide, course S.20°E. |
| 40.01 | Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked |
| | |
| | from which An ironwood, 8 ins. in dia., brs. N.4 $\frac{1}{2}$ °E., 135 lks. dist., marked $\frac{1}{4}$ S13 BT. A palo verde, 10 ins. in dia., brs. S.79°E., 119 lks. dist., marked $\frac{1}{4}$ S24 BT. |
| 85.02 | The cor. of secs. 13,14,23 and 24. Land: level and rolling. Soil: rocky adobe, 2nd and 3rd rates. Undergrowth: greasewood, mesquite, sage, palo verde, cactus and ironwood. |
| | ----- |

Survey of Subdivision of Township 18 South, Range 2 West

| | |
|--------|---|
| Chains | N. 0°01'W., bet. secs. 13 and 14. Over level land; thru dense undergrowth. |
| 40.00 | Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked |
| | $\begin{array}{c} \frac{1}{4} \\ \hline S14 S13 \\ \hline 1925 \end{array}$ |
| | No trees available. Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. |
| 43.90 | Dry wash, 20 lks. wide, course SE. |
| 60.00 | Leave flat. Over rolling land. Asc. 169 ft. over SW. slope. |
| 80.00 | Set an iron post, 3 ft. long, 2 ins. in dia., 10 ins. in the ground for bedrock, with rock 10 x 10 x 6 ins., marked with cross (+) deposited at bottom, supported by a mound of stone, 4 ft. base, 1 $\frac{1}{2}$ ft. high, for cor. of secs. 11, 12, 13 and 14, with brass cap marked |
| | $\begin{array}{c} T18SR2W \\ \hline S11 S12 \\ \hline S14 S13 \\ \hline 1925 \end{array}$ |
| | No trees available. Land: level and rolling. Soil: rocky and adobe, 2nd and 3rd rates. Timber: none. Undergrowth: mesquite, greasewood, ironwood, palo verde, sage, organ pipe and cactus. |
| 40.00 | N. 89°52'E., on a random line bet. secs. 12 and 13. Set temp. $\frac{1}{4}$ sec. cor. |
| 80.00 | Fall 2 lks. N. of the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described. Thence S. 89°53'W., on a true line, bet. secs. 12 and 13. Over mountainous land; thru dense undergrowth. Asc. broken NE. slope 450 ft. |
| 40.00 | Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground to bedrock, with rock, 12 x 10 x 6 ins., deposited at bottom (marked with cross), supported by a mound of stone 4 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap marked |
| | $\begin{array}{c} S12 \\ \hline \frac{1}{4} \\ \hline S13 \\ \hline 1925 \end{array}$ |
| 56.80 | No trees available. Asc. broken NE. slope 527 ft. |
| 80.00 | Top of Bailey Peak. Desc. broken SW. slope 710 ft. The cor. of secs. 11, 12, 13 and 14. Land: mountainous. Soil: rocky, 4th rate. Timber: none. Undergrowth: palo verde, mesquite, ironwood, organ pipe and cactus. |
| 5.70 | N. 0°01'W., bet. secs. 11 and 12. Over mountainous land; thru scattering undergrowth. Asc. 114 ft. over SW. slope. |
| 15.00 | Spur, slopes SW. Desc. 129 ft. over NW. slope. |
| 19.80 | Draw, course SW. Asc. 28 ft. over SE. slope. Spur, slopes SW. Desc. 52 ft. over NW. slope. |

Survey of the Subdivision of Township 18 South, Range 2 West

Chains
 25.80 Draw, course SW. Asc. 358 ft. over SE. slope.
 40.00 Point for $\frac{1}{4}$ sec. cor. falls on face of cliff.
 40.10 Set an iron post, 3 ft. long, 1 in. in dia., on bedrock,
 with stone 20 x 18 x 12 ins., marked with cross (+)
 deposited at bottom, supported by a mound of stone,
 4 ft. base, 2 $\frac{1}{2}$ ft. high, for wit. cor. to $\frac{1}{4}$ sec. cor.,
 with brass cap marked

S11 | S12
 W C
 1925

No trees available.
 Asc. 26 ft. over SE. slope.
 41.00 Spur, slopes SW. Desc. 154 ft. over NW. slope.
 52.30 Short spur, slopes W. Desc. 31 ft. over NW. slope.
 65.00 Ravine, course SW. Asc. 313 ft. over S. slope.
 80.00 Impossible to monument the sec. cor. at this point.
 80.43 Set an iron post, 3 ft. long, 2 ins. in dia., 6 ins. in
 the ground, with stone 14 x 12 x 10 ins., marked
 with cross (+) deposited at bottom, supported by a
 mound of stone, 4 ft. base, 2 ft. high, for wit. cor. to
 cor. of secs. 1, 2, 11 and 12, with brass cap marked

T18SR2W
 S2 | S1
 S11 | S12
 W C
 1925

No trees available.
 Land: mountainous.
 Soil: rocky, 4th rate.
 Timber: none.
 Undergrowth: greasewood, sage, palo verde, ironwood,
 mesquite and cactus.

 From true point for cor. of secs. 1, 2, 11 and 12.
 N. 89° 53' E., on a random line bet. secs. 1 and 12.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.16 Fall 7 lks. N. of the cor. of secs. 1, 6, 7 and 12, on the
 E. bdy. of the Tp., hereinbefore described.
 Thence
 S. 89° 56' W., on a true line, bet. secs. 1 and 12.
 Over mountainous land; thru scattering undergrowth.
 Asc. 522 ft. over NE. slope.
 17.50 Spur, slopes N. Desc. 141 ft. over NW. slope.
 40.08 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in
 the ground to bedrock, supported by a mound of stone,
 for $\frac{1}{4}$ sec. cor., with brass cap marked

S1
 S12
 1925

No trees available.
 Raise a mound of stone, 3 ft. base 2 ft. high, N. of
 cor.
 Asc. 87 ft. along N. slope.
 49.50 Ravine, course NE. Asc. 372 ft. over E. slope.
 63.20 Ridge, brs. N. and S. Desc. 290 ft. over W. slope.
 70.10 Ravine, course SW. Asc. 40 ft. along S. slope.
 80.16 The true point for cor. of secs. 1, 2, 11 and 12.
 Land: mountainous.
 Soil: rocky, 4th rate.
 Timber: none.
 Undergrowth: greasewood, sage, palo verde and cactus.

Survey of Subdivision of Township 18 South, Range 2 West

Chains

40.00
80.08


From the true point for the cor. of secs. 1, 2, 11 and 12. North, on a random line, bet. secs. 1 and 2. Set temp. $\frac{1}{4}$ sec. cor. Fall 2 lks. W. of the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.

16.00
37.00
40.08

Thence S. $9^{\circ}01'W.$, on a true line bet. secs. 1 and 2. Over mountainous land; thru scattering undergrowth. Along E. slope. Ravine, course E. Asc. 200 ft. over N. slope. Spur, slopes NE.

42.08

Point for $\frac{1}{4}$ sec. cor. falls on face of cliff. Desc. SE. slope 100 ft. Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground, supported by a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high for wit. cor. to $\frac{1}{4}$ sec. cor., with brass cap marked



No trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

49.38

Asc. 298 ft. over N. slope. Ridge, brs. E. and W. U.S.G.S. Tri. Pt. brs. N. $46^{\circ}42'W.$ Desc. 812 ft. over SE. slope.

79.65

(0.43 chs. N. $10^{\circ}11'W.$ from sec. cor. point) The witness cor. to cor. of secs. 1, 2, 11 and 12, hereinbefore described.

80.08


The true point for cor. of secs. 1, 2, 11 and 12, hereinbefore described. Land, mountainous. Soil, rocky, 4th rate. Timber, none. Undergrowth, greasewood, sagebrush, scrub palo verde and cactus.

40.00

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. $0^{\circ}01'W.$, on a true line, bet. secs. 34 and 35.

Over level land; thru scattering undergrowth. Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



from which

A mesquite, 10 ins. in dia., brs. S. $0^{\circ}30'E.$, 225 lks. dist., marked $\frac{1}{4}$ S35 BT.

A mesquite, 10 ins. in dia., brs. S. $37\frac{1}{2}^{\circ}W.$, 177 lks. dist., marked $\frac{1}{4}$ S34 BT.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap marked



from which

A mesquite, 6 ins. in dia., brs. N. $44^{\circ}E.$, 120 lks. dist., marked T18S R2W S26 BT.

A mesquite, 6 ins. in dia., brs. S. $17^{\circ}E.$, 111 lks. dist., marked T18S R2W S35 BT.

A mesquite, 8 ins. in dia., brs. S. $84^{\circ}W.$, 55 lks. dist., marked T18S R2W S34 BT.

No other trees available.

Survey of Subdivision of Township 18 South, Range 2 West.

Chains

Dig pits 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: level.

Soil: sandy loam, 1st. rate.

Timber: none.

Undergrowth: greasewood, sage and mesquite.

40.00

N. 89° 57' E., on a random line bet. secs. 26 and 35.

Set temp. $\frac{1}{4}$ sec. cor.

79.88

Fall 5 lks. S. of the cor. of secs. 25, 26, 35 and 36.

Thence

S. 89° 55' W., on a true line bet. secs. 26 and 36.

Over level land; thru scattering undergrowth.

39.94

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S26
S35
1925

No trees available.

Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist.

79.88

The cor. of secs. 26, 27, 34 and 35.

Land: level.

Soil: sandy, 1st. rate.

Timber: none.

Undergrowth: greasewood, sage and mesquite.

40.00

N. 0° 01' W., bet. secs. 26 and 27.

Over level land; through scattering undergrowth.

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S27 | S26
1925

from which

A mesquite, 10 ins. in dia., brs. S. 21° W., 182 lks. dist., marked $\frac{1}{4}$ S27 BT.

A mesquite, 10 ins. in dia., brs. N. 32° E., 135 lks. dist., marked $\frac{1}{4}$ S26 BT.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 22, 25, 26 and 27, with brass cap marked

T18SR2W
S22 | S23
S27 | S26
1925

No trees available.

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land: level.

Soil: sandy, 1st. rate.

Timber: none.

Undergrowth: greasewood, sage and mesquite.

40.00

N. 89° 55' E., on a random line, bet. secs. 23 and 26.

Set temp. $\frac{1}{4}$ sec. cor.

79.96

Fall 2 lks. S. of the cor. of secs. 23, 24, 25 and 26.

Thence

Survey of the Subdivision of Township 18 South, Range 2 West

| Chains | |
|--------|---|
| | S.89°54'W., on a true line, bet. secs. 25 and 26. Over level land; thru scattering undergrowth. |
| 26.80 | Dry wash, 5 lks. wide, course S.E. |
| 39.98 | Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked |
| | $\begin{array}{c} \frac{1}{4}S23 \\ \frac{1}{4}S26 \\ 1925 \end{array}$ |
| | No trees available. |
| | Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist. |
| 52.60 | Dry wash, 20 lks. wide, course S. |
| 79.96 | The cor. of secs. 22, 23, 26 and 27. Land: level. Soil: sandy, 1st. and 2nd. rates. Timber: none. Undergrowth: greasewood, sage and mesquite. |
| | ----- |
| | N.0°01'W., bet. secs. 22 and 23. |
| | Over level land; thru scattering undergrowth. |
| 40.00 | Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked |
| | $\begin{array}{c} \frac{1}{4}S22 \quad \frac{1}{4}S23 \\ 1925 \end{array}$ |
| | No trees available. |
| | Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. |
| 42.00 | Dry wash, 5 lks. wide, course S.E. |
| 58.30 | Dry wash, 5 lks. wide, course S.E. |
| 74.00 | Dry wash, 2- lks. wide, course S.E. |
| 80.00 | Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 14, 15, 22 and 23, with brass cap marked |
| | $\begin{array}{c} T18SR2W \\ \frac{1}{4}S15 \quad \frac{1}{4}S14 \\ \frac{1}{4}S22 \quad \frac{1}{4}S23 \\ 1925 \end{array}$ |
| | from which |
| | A mesquite, 6 ins. in dia., brs. N. 25 $\frac{1}{2}$ °E., 171 lks. dist., marked T18S R2W S14 BT. |
| | A mesquite, 6 ins. in dia., brs. S.77°E., 86 lks. dist., marked T18S R2W S23 BT. |
| | A palo verde, 6 ins. in dia., brs. S.22 $\frac{1}{2}$ °W., 138 lks. dist., marked T18S R2W S22 BT. |
| | A mesquite, 8 ins. in dia., brs. N.55 $\frac{1}{2}$ °W., 82 lks. dist., marked T18S R2W S15 BT. |
| | Land: level. |
| | Soil: adobe, 2nd rate. |
| | Timber: none. |
| | Undergrowth: palo verde, mesquite, greasewood, sage and cactus. |
| | ----- |
| | N.89°54'E., on a random line bet. secs. 14 and 23. |
| 40.00 | Set temp. $\frac{1}{4}$ sec. cor. |
| 80.06 | Fall 9 lks. N. of the cor. of secs. 13, 14, 23 and 24. Thence |
| | S.89°58'W., on a true line, bet. secs. 14 and 23. |
| | Over level land; thru scattering undergrowth. |
| 11.50 | Dry wash, 10 lks. wide, course S. |

Survey of Subdivision of Township 18 South, Range 2 West

Chains
22.40
40.03

Dry wash, 40 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S14
S23
1925

from which

- A palo verde, 10 ins. in dia., brs. N.6°E., 259 lks. dist., marked $\frac{1}{4}$ S14 BT.
- A palo verde, 10 ins. in dia., brs. S.86 $\frac{1}{2}$ °E., 258 lks. dist., marked $\frac{1}{4}$ S23 BT.

62.80
74.10
80.06

Dry wash, 20 lks. wide, course S.
Dry wash, 10 lks. wide, course S.
The cor. of secs. 14, 15, 22 and 23.
Land: level.
Soil: sandy and rocky, 3rd rate.
Timber: none.
Undergrowth: greasewood, sage, mesquite, palo verde, and cactus.

N.0°01'W., bet. secs. 14 and 15.
Over level land; thru scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S15 | S14
1925

from which

- A mesquite, 6 ins. in dia., brs. N.55 $\frac{1}{2}$ °E., 48 lks. dist., marked $\frac{1}{4}$ S14 BT.
- A palo verde, 6 ins. in dia., brs. N.25 $\frac{1}{2}$ °W., 133 lks. dist., marked $\frac{1}{4}$ S15 BT.

42.70
49.50
80.00

Dry wash, 20 lks. wide, course SW.
Dry wash, 20 lks. wide, course SW.
Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 10, 11, 14 and 15, with brass cap marked

T18SR2W
S10 | S11
S15 | S14
1925

from which

- A palo verde, 6 ins. in dia., brs. N.81°E., 190 lks. dist., marked T18S R2W S11 BT.
- A palo verde, 8 ins. in dia., brs. S.65°E., 138 lks. dist., marked T18S R2W S14 BT.
- A palo verde, 6 ins. in dia., brs. S.81°W., 118 lks. dist., marked T18S R2W S15 BT.
- A palo verde, 8 ins. in dia., brs. N.62 $\frac{1}{2}$ °W., 199 lks. dist., marked T18S R2W S10 BT.

Land: level.
Soil: rocky, 3rd rate.
Timber: none.
Undergrowth: greasewood, sage, palo verde, mesquite and cactus.

40.00

N.89°58'E., on a random line, bet. secs. 11 and 14.
Set temp. $\frac{1}{4}$ sec. cor.

Survey of Subdivision of Township 16 South, Range 2 West.

Chains
79.90 Fall 5 lks. N. of the cor. of secs. 11, 12, 13 and 14.
Thence
West, on a true line, bet. secs. 11 and 14.
Over rolling land; thru scattering undergrowth.
1.70 Ravine, course S. Asc. 57 ft. over E. slope.
11.20 Spur, slopes S. Desc. 197 ft. over W. slope.
89.50 Wash, 20 lks. wide, course S. Over gently rolling land.
39.95 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S11
S14
1925

No trees available.

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N.
of cor.

70.50 Wash, 3 lks. wide, course S.
79.90 The cor. of secs. 10, 11, 14 and 15.
Land: rolling.
Soil: sandy and rocky, 1st and 3rd rates.
Timber: none.
Undergrowth: greasewood, sage, mesquite, palo verde and
cactus.

40.00 N. 0° 01' W., bet. secs. 10 and 11.
Over level land; thru scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S10 | S11
1925

No trees available.

Raise a mound of stone 3 ft. base, 1 $\frac{1}{2}$ ft. high, W.
of cor.

41.20 Dry wash, 20 lks. wide, course SW.
51.30 Dry wash, 5 lks. wide, course SW.
60.00 Asc: 62 ft. over S. slope.
80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 6 ins. in
the ground, with a rock marked with a cross (+)
deposited at bottom, supported by a mound of stone,
4 ft. base, 2 ft. high, for cor. of secs. 2, 3, 10 and
11, with brass cap marked

T18SR2W
S3 | S2
S10 | S11
1925

No trees available.

Land: flat; slopes S.

Soil: rocky adobe, 2nd rate.

Timber: none.

Undergrowth: greasewood, sage, palo verde, mesquite and
cactus.

40.00 East, on a random line, bet. secs. 2 and 11.
79.96 Set temp. $\frac{1}{4}$ sec. cor.
Fall 10 lks. N. of true point for cor. of secs. 1, 2, 11
and 12.

Thence

N. 89° 56' W., on a true line, bet. secs. 2 and 11.

Over rolling land; thru scattering undergrowth.

Survey of Subdivision of Township 18 South, Range 2 West

Chains

Asc. 10 ft. over E. slope.
 1.30 Spur, slopes S. Along S. slope.
 4.00 Ravine, course S.
 6.30 Spur, slopes S. Desc. 80 ft. over SW. slope.
 10.60 Ravine, course S. Asc. 143 ft. over SE. slope.
 22.40 Spur, slopes S. Desc. 314 ft. over W. slope.
 39.98 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S2
 311
 1925

No trees available.
 Raise a mound of stone 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of
 cor.

Desc. 250 ft. over W. slope.
 63.60 Dry wash, 15 lks. wide, course S. Over flat.
 79.40 Dry wash, 10 lks. wide, course S.
 79.96 The cor. of secs. 2, 3, 10 and 11.
 Land: mountainous.
 Soil: rocky, 3rd rate.
 Timber: none.
 Undergrowth: greasewood, sage, palo verde and cactus.

North, on a random line, bet. secs. 2 and 3.
 49.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.23 Fall 7 lks. W. of the true point for cor. of secs. 2, 3,
 34 and 35, on the N. bdy. of the Tp., hereinbefore
 described.
 Thence
 S. 0° 03' W., on a true line, bet. secs. 2 and 3.
 Over mountainous land; through scattering undergrowth.
 Desc. 862 ft. over SW. slope.
 36.40 Ravine, course SW. Asc. 60 ft. over NW. slope
 40.23 Set an iron post, 3 ft. long, 1 in. in dia., 6 ins. in
 the ground to bedrock, with stone marked with cross
 (+) deposited at bottom, supported by a mound of stone
 3 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass
 cap marked

S3 | S2
 1925

No trees available.
 Asc. 226 ft. over NW. slope.
 60.20 Spur, slopes SW. Desc. 134 ft. over S. slope.
 80.23 The cor. of secs. 2, 3, 10 and 11.
 Land: mountainous.
 Soil: rocky, 4th rate.
 Timber: none.
 Undergrowth: palo verde, greasewood, sage and cactus.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the
 Tp., hereinbefore described.
 N. 0° 02' W., bet. secs. 33 and 34.
 Over level land; thru scattering undergrowth.
 11.55 Road, brs. NW. and SE.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S33 | S34
 1925

Survey of Subdivision of Township 18 South, Range 2 West.

Chains

from which
 A mesquite, 8 ins. in dia., brs. N.64°E., 140 lks.
 dist., marked $\frac{1}{4}$ S34 BT.
 A mesquite, 10 ins. in dia., brs. N.34°W., 16 lks.
 dist., marked $\frac{1}{4}$ S33 BT.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in
 the ground for cor., of secs. 27, 28, 33 and 34, with
 brass cap marked

T18SR2W
 S28 | S27
 S33 | S34
 1925

from which
 A mesquite, 6 ins. in dia., brs. N.29°E., 162 lks.
 dist., marked T18S R2W S27 BT.
 A mesquite, 6 ins. in dia., brs. S.43½°E., 105 lks.
 dist., marked T18S R2W S34 BT.
 A mesquite, 7 ins. in dia., brs. S.48°W., 103 lks.
 dist., marked T18S R2W S33 BT.
 A mesquite, 12 ins. in dia., brs. N.15½°W., 168
 lks. dist., marked T18S R2W S28 BT.
 Land: level.
 Soil: sandy, 1st. rate.
 Timber: none.
 Undergrowth: greasewood, mesquite, sage and cactus.

N.89°57'E., on a random line bet. secs. 27 and 34.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.98 Fall 5 lks. S. of the cor. of secs. 26, 27, 34 and 35.
 Thence
 S.89°55'W., on a true line bet. secs. 27 and 34.
 Over level land; thru scattering undergrowth.
 39.99 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S27
 S34
 1925

No trees available.
 Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft.
 dist.
 79.98 The cor. of secs. 27, 28, 33 and 34.
 Land: level.
 Soil: sandy, 1st. rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite and cactus.

N.0°02'W., bet. secs. 27 and 28.
 Over level land; thru dense undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S28 | S27
 1925

from which
 A mesquite, 8 ins. in dia., brs. S.61°E., 53 lks.
 dist., marked $\frac{1}{4}$ S27 BT.
 A mesquite, 6 ins. in dia., brs. N.71½°W., 115 lks.
 dist., marked $\frac{1}{4}$ S28 BT.
 43.00 Dry wash, 4 lks. wide, course SE.

Survey of Subdivision of Township 18 South, range 2 West

| | | | | | | | | | |
|-----------------|--|---------|--|------|-----|------|-----|------|--|
| Chains 80.00 | Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs 21,22,27 and 28, with brass cap marked | | | | | | | | |
| | <table border="1"> <tr><td colspan="2">T18SR2W</td></tr> <tr><td>S21</td><td>S22</td></tr> <tr><td>S28</td><td>S27</td></tr> <tr><td colspan="2">1925</td></tr> </table> | T18SR2W | | S21 | S22 | S28 | S27 | 1925 | |
| T18SR2W | | | | | | | | | |
| S21 | S22 | | | | | | | | |
| S28 | S27 | | | | | | | | |
| 1925 | | | | | | | | | |
| | <p>from which</p> <ul style="list-style-type: none"> A mesquite, 12 ins. in dia., brs. N.45½°E., 141 lks. dist., marked T18S R2W S22 BT. A mesquite, 6 ins. in dia., brs. S.39½°E., 147 lks. dist., marked T18S R2W S27 BT. A mesquite, 6 ins. in dia., brs. S.44°W., 134 lks. dist., marked T18S R2W S28 BT. A mesquite, 10 ins. in dia., brs. N.53°W., 340 lks. dist., marked T18S R2W S21 BT. <p>Land: level. Soil: sandy, 1st. rate. Timber: none. Undergrowth: greasewood, mesquite and cactus.</p> | | | | | | | | |
| 40.00 | N.89°55'E., on a random line, bet. secs. 22 and 27. Set temp. ¼ sec. cor. | | | | | | | | |
| 79.94 | Fall 18 lks. N. of the cor. of secs. 22,23,26 and 27. Thence | | | | | | | | |
| | N.89°57'W., on a true line, bet. secs. 22 and 27. Over level land; thru scattering undergrowth. | | | | | | | | |
| 39.97 | Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for ¼ sec. cor., with brass cap marked | | | | | | | | |
| | <table border="1"> <tr><td colspan="2">S22</td></tr> <tr><td colspan="2">S27</td></tr> <tr><td colspan="2">1925</td></tr> </table> | S22 | | S27 | | 1925 | | | |
| S22 | | | | | | | | | |
| S27 | | | | | | | | | |
| 1925 | | | | | | | | | |
| | <p>from which</p> <ul style="list-style-type: none"> A mesquite, 6 ins. in dia., brs. N.20°E., 37 lks. dist., marked ¼ S22 BT. A mesquite, 4 ins. in dia., brs. S.27°E., 142 lks. dist., marked ¼ S27 BT. <p>46.90 Dry wash, 5 lks. wide, course S. 67.40 Dry wash, 2 lks. wide, course S. 79.94 The cor. of secs. 21,22,27 and 28. Land: level. Soil: sandy, 1st. rate. Timber: none. Undergrowth: greasewood, mesquite and cactus.</p> | | | | | | | | |
| 25.00 | N.0°02'W., bet. secs. 21 and 22. Dry wash, 5 lks. wide, course SW. | | | | | | | | |
| 40.00 | Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for ¼ sec. cor., with brass cap marked | | | | | | | | |
| | <table border="1"> <tr><td colspan="2">S21 S22</td></tr> <tr><td colspan="2">1925</td></tr> </table> | S21 S22 | | 1925 | | | | | |
| S21 S22 | | | | | | | | | |
| 1925 | | | | | | | | | |
| | <p>from which</p> <ul style="list-style-type: none"> A mesquite, 10 ins. in dia., brs. S.10½°E., 218 lks. dist., marked ¼ S22 BT. A mesquite, 6 ins. in dia., brs. N.7°W., 225 lks. dist., marked ¼ S21 BT. <p>66.60 Dry wash, 5 lks. wide, course SW.</p> | | | | | | | | |

Survey of Subdivision of Township 18 South, Range 2 West

Chains
89.00

Set an iron post, 3 ft. long, 2 ins. in dia., 23 ins. in the ground for cor. of secs. 15, 16, 21 and 22, with brass cap marked

T18SR2W
S16 | S15
S21 | S22
1925

from which

A mesquite, 12 ins. in dia., brs. N.71½°E., 66 lks. dist., marked T18S R2W S15 BT.

A mesquite, 6 ins. in dia., brs. S.54°W., 175 lks. dist., marked T18S R2W S21 BT.

A mesquite, 8 ins. in dia., brs., N.53°W., 181 lks. dist., marked T18S R2W S16 BT.

No other trees available.

Raise a mound of stone 3 ft. base 1 1/2 ft. high, W. of cor.

Land: level.

Soil: sandy and rocky.

Timber: none.

Undergrowth: greasewood, mesquite and cactus.

40.00
79.84

S.89°57'E., on a random line bet. secs. 15 and 22.

Set temp. 1/4 sec. cor.

Run 12 lks. S. of the cor. of secs. 14, 15, 22 and 23.

Thence

S.89°58'W., on a true line bet. secs. 15 and 22.

Over level land: thru scattering undergrowth.

1.19 Dry wash, 30 lks. wide, course S.

18.60 Dry wash, 5 lks. wide, course SW.

22.10 Dry wash, 10 lks. wide, course S.

34.10 Dry wash, 10 lks. wide, course S.

39.92 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 1/4 sec. cor., with brass cap marked

1/4 S15
S22
1925

from which

A mesquite, 8 ins. in dia., brs. N.82°E., 224 lks. dist., marked 1/4 S15 BT.

A mesquite, 8 ins. in dia., brs. S.17°W., 74 lks. dist., marked 1/4 S22 BT.

42.30 Dry wash, 5 lks. wide, course SW.

43.70 Dry wash, 10 lks. wide, course S.

54.30 Dry wash, 5 lks. wide, course S.

69.70 Dry wash, 10 lks. wide, course SW.

79.84 The cor. of secs. 15, 16, 21 and 22.

Land: level.

Soil: sandy and rocky, 2nd and 3rd rates.

Timber: none.

Undergrowth: mesquite, palo verde, greasewood and cactus.

38.70
40.00

N.0°02'W., bet. secs. 15 and 16.

Over level land: thru scattering undergrowth.

Dry wash, 5 lks. wide, course SW.

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 1/4 sec. cor., with brass cap marked

1/4 S16 | S15
1925

Survey of Subdivision of Township 18 South, Range 2 West.

Chains

No trees available.
Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

42.50
74.90
80.00

Dry wash, 6 lks. wide, course SW.
Dry wash, 10 lks. wide, course SW.
Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground, for cor. of secs. 9,10,15 and 16, with brass cap marked

T18SR2W
S9 | S10
S16 | S15
1925

No trees available.
Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

Land: gently rolling.
Soil: rocky, 3rd. rate.
Timber: none.
Undergrowth: greasewood, sage, mesquite, palo verde and cactus.

40.00
79.86

N. 89° 58' E., on a random line, bet. secs. 10 and 15.
Set temp. 1/4 sec. cor.
Fall 4 lks. N. of the cor. of secs. 10,11,14 and 15.
Thence

6.90
19.20
20.90
39.93

West, on a true line bet. secs. 10 and 15.
Over level land; thru scattering undergrowth.
Wash, 20 lks. wide, course S.
Wash, 15 lks. wide, course S.
Wash, 15 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 1/4 sec. cor., with brass cap marked

S10
1/4 S15
1925

No trees available.
Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

60.00
70.10
79.86

Over rolling land. Asc. 74 ft. over SE. slope.
Small spur, slopes S. Desc. 128 ft. over SW. slope.
The cor. of secs. 9,10,15 and 16.
Land: level and rolling.
Soil: sandy and rocky, 2nd and 3rd. rates.
Timber: none.
Undergrowth: greasewood, mesquite and cactus.

19.00
32.00
40.00

N. 0° 02' W., bet. secs. 9 and 10.
Over rolling land; thru scattering undergrowth.
Asc. 211 ft. over SW. slope.
Ridge, brs. E. and W. Desc. 185 ft. over N. slope.
Dry wash, 20 lks. wide, course W. Over flat.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 1/4 sec. cor., with brass cap marked

S9 | S10
1925

from which
A palo verde, 6 ins. in dia., brs. S. 78 1/2° E., 69 lks. dist., marked 1/4 S10 BT.

Survey of Subdivision of Township 18 South, Range 2 West.

Chains

A palo verde, 8 ins. in dia., brs. N.60°W., 116 lks. dist., marked $\frac{1}{4}$ S9 BT.
 49.10 Dry wash, 5 lks. wide, course SW.
 52.00 Dry wash, 15 lks. wide, course SW.
 54.40 Dry wash, 8 lks. wide, course SW.
 70.80 Dry wash, 6 lks. wide, course SW.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 3, 4, 9 and 10, with brass cap marked

T18SR2W
 S4 | S3
 S9 | S10
 1925

No trees available.
 Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
 Land: level and rolling.
 Soil: rocky, 3rd. rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite, palo verde, cactus, etc.

 East, on a random line bet. secs. 3 and 10.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.94 Fall 11 lks. N. of the cor. of secs. 2, 3, 10 and 11.
 Thence
 N.89°55'W., on a true line, bet. secs. 3 and 10.
 Over rolling land; thru scattering undergrowth.
 13.70 Dry wash, 100 lks. wide, course SW.
 22.40 Dry wash, 50 lks. wide, course S. Asc. 73 ft. over SE. slope.
 37.20 Spur, slopes S. Desc. 147 ft. over SW. slope.
 39.97 Set an iron post, 3 ft. long, 1 in. in dia., 8 ins. in the ground, supported by a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S3
 S10
 1925

No trees available.
 Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
 Desc. 126 ft. over SW. slope.
 54.70 Dry wash, 10 lks. wide course S. Over gently rolling land.
 64.60 Dry wash, 10 lks. wide, course SW.
 74.30 Dry wash, 5 lks. wide, course SW.
 79.94 The cor. of secs. 3, 4, 9 and 10.
 Land: rolling.
 Soil: rocky, 3rd rate.
 Timber: none.
 Undergrowth: greasewood, sage, ironwood, palo verde, mesquite and cactus.

 North, on a random line, bet. secs. 3 and 4.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.13 Fall 5 lks. E. of the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.
 Thence
 S.0°02'E., on a true line, bet. secs. 3 and 4.
 Over rolling land; thru scattering undergrowth.
 Asc. 44 ft. over NE. slope.
 2.20 Spur, slopes SE. Desc. 340 ft. over S. slope.
 21.20 Desc. gently.

Survey of Subdivision of Township 18 South, Range 2 West

Chains
39.83

(True point for $\frac{1}{4}$ sec. cor. falls on sloping bedrock.) Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for witness cor. to $\frac{1}{4}$ sec. cor., with brass cap marked



No trees available.

40.13

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. True point for $\frac{1}{4}$ sec. cor. Desc. 23 ft. over S. slope.

42.50

Dry wash, 50 lks. wide, course SW. Asc. 77 ft. over NW. slope.

60.50

Spur, slopes SW. Desc. 151 ft. over SE. slope.

79.20

Dry wash, 10 lks. wide, course SW.

80.13

The cor. of secs. 3, 4, 9 and 10.


Land: rolling.
Soil: rocky, 3rd. rate.
Timber: none.

Undergrowth: greasewood, sage, palo verde, mesquite, ironwood and cactus.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.

40.00

N. 0° 02' W., bet., secs. 32 and 33. Over level land; thru scattering undergrowth. Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



from which

A mesquite, 8 ins. in dia., brs. N. 2° E., 90 lks. dist., marked $\frac{1}{4}$ S33 BT.

A mesquite, 6 ins. in dia., brs. S. 81° W., 87 lks. dist., marked $\frac{1}{4}$ S32 BT.

45.30


Road, brs. NW. and SE.

55.00

Road, brs. NW. and SE.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 28, 29, 32 and 33, with brass cap marked



from which

A mesquite, 6 ins. in dia., brs. N. 74 1/2° E., 64 lks. dist., marked T18S R2W S28 BT.

A mesquite, 6 ins. in dia., brs. S. 61° W., 111 lks. dist., marked T18S R2W S32 BT.

A mesquite, 6 ins. in dia., brs. N. 29 1/2° W., 185 lks. dist., marked T18S R2W S29 BT.

No other trees available.

Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.

Land: level.
Soil: sandy 1st. rate.
Timber: none.
Undergrowth: greasewood and mesquite.

Survey of Subdivision of Township 18 South, Range 2 West

Chains

40.00 N. 89°57'E., on a random line bet. secs. 28 and 33.
Set temp. $\frac{1}{4}$ sec. cor.
79.86 Fall 14 lks. N. of the cor. of secs. 27, 28, 33 and 34.
Thence
N. 89°57'W., on a true line, bet. secs. 28 and 33.
Over level land; thru scattering undergrowth.
39.93 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S28
S33
1925

No trees available.

Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft.
dist.

79.86 The cor. of secs. 28, 29, 32 and 33.
Land: level.
Soil: sandy, 1st. rate.
Timber: none.
Undergrowth: greasewood and mesquite.

40.00 N. 0°02'W., bet. secs. 28 and 29.
Over level land; thru scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S29 | S28
1925

No trees available.

Dig pits, 18 x 18 x 12 ins., one each N. and S. 3 ft.
dist.,

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in
the ground for cor. of secs. 20, 21, 28 and 29, with
brass cap marked

T18SR2W
S20 | S21
S29 | S28
1925

No trees available.

Dig pits, 18 x 18 x 12 ins., one in each sec. 3 ft.
dist.

Land: level.
Soil: sandy, 2nd rate.
Timber: none.
Undergrowth: greasewood, mesquite and cactus.

40.00 S. 89°57'E., on a random line. bet. secs. 21 and 28.
Set temp. $\frac{1}{4}$ sec. cor.
79.84 Fall 14 lks. S. of the cor. of secs. 21, 22, 27 and 28.
Thence
S. 89°57'W., on a true line bet. secs. 21 and 28.
Over level land; thru scattering undergrowth.
34.30 Dry wash, 5 lks. wide, course S.
39.92 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the
ground for $\frac{1}{4}$ sec. cor., with brass cap marked


$\frac{1}{4}$ S21
S28
1925

Survey of Subdivision of Township 18 South, Range 2 West.


Chains

79.84 from which
 A mesquite, 10 ins. in dia., brs. N.63 $\frac{1}{4}$ °E., 68 lks. dist., marked $\frac{1}{4}$ S21 BT.
 A mesquite, 8 ins. in dia., brs. S.31 $\frac{1}{4}$ °W., 132 lks. dist., marked $\frac{1}{4}$ S28 BT.
 The cor. of secs. 20,21,28 and 29.
 Land: level.
 Soil: Sandy and rocky, 2nd and 3rd rates.
 Timber: none.
 Undergrowth: mesquite, greasewood and cactus.

40.00 N.0°02'W., bet. secs. 20 and 21.
 Over level land; thru scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



80.00 from which
 A mesquite, 6 ins. in dia., brs. S.61°E., 48 lks. dist., marked $\frac{1}{4}$ S21 BT.
 A mesquite, 8 ins. in dia., brs. N.10 $\frac{1}{2}$ °W., 161 lks. dist., marked $\frac{1}{4}$ S20 BT.
 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 16,17,20 and 21, with brass cap marked




from which
 A mesquite, 6 ins. in dia., brs. N.62°E., 325 lks. dist., marked T18S R2W S16 BT.
 A mesquite, 6 ins. in dia., brs. S.12°E., 227 lks. dist., marked T18S R2W S21 BT.
 A mesquite, 6 ins. in dia., brs. S.6 $\frac{1}{2}$ °W., 160 lks. dist., marked T18S R2W S20 BT.
 A mesquite, 6 ins. in dia., brs. N.47 $\frac{1}{2}$ °W., 328 lks. dist., marked T18S R2W S17 BT.
 Land: slightly rolling.
 Soil: sandy and rocky, 2nd and 3rd rates.
 Timber: none.
 Undergrowth: greasewood, mesquite and cactus.

40.00 N.89°57'E., on a random line, bet. secs. 16 and 21.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.12 Fall 4 lks. N. of the cor. of secs. 15,16,21 and 22.
 Thence

S.89°59'W., on a true line, bet. secs. 16 and 21.
 Over level land; thru scattering undergrowth.

13.10 Dry wash, 4 lks. wide, course SW.

40.06 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



from which
 A mesquite, 6 ins. in dia., brs. S.18°E., 208 lks. dist., marked $\frac{1}{4}$ S21 BT.

Survey of Subdivision of Township 18 South, Range 2 West.

Chains

- A mesquite, 6 ins. in dia., brs. N.42 $\frac{3}{4}$ °E., 276 lks. dist., marked $\frac{1}{4}$ S16 BT.
- 64.10 Dry wash, 5 lks. wide, course SW.
- 67.60 Dry wash, 4 lks. wide, course S.
- 80.12 The cor. of secs. 16,17,20 and 21.
Land: level.
Soil: sandy and rocky, 2nd and 3rd rates.
Timber: none.
Undergrowth: greasewood, sage, mesquite, palo verde and cactus.
-
- 40.00 N.0°02'W., bet. secs. 16 and 17.
Over level land; thru scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$
S17 | S16
1925
- from which
A mesquite, 6 ins. in dia., brs. N.13 $\frac{1}{2}$ °E., 88 lks. dist., marked $\frac{1}{4}$ S16 BT.
A mesquite, 6 ins. in dia., brs. N.56 $\frac{1}{4}$ °W., 233 lks. dist., marked $\frac{1}{4}$ S17 BT.
- 60.00 Dry wash, 8 lks. wide, course SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 8,9,16 and 17, with brass cap marked
- T18SR2W
S8 | S9
S17 | S16
1925
- No trees available.
Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
Land: slightly rolling.
Soil: sandy and rocky, 2nd and 3rd rates.
Timber: none.
Undergrowth: greasewood, sage, mesquite and cactus.
-
- 40.00 S.89°59'E., on a random line bet. secs. 9 and 16.
Set temp. $\frac{1}{4}$ sec. cor.
- 79.98 Intersect cor. of secs. 9,10,15 and 16.
Thence
N.89°59'W., on a true line bet. secs. 9 and 16.
Over level land; thru scattering undergrowth.
- 39.99 Set an iron post, 3 ft. long; 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$ S9
S16
1925
- from which
A palo verde, 12 ins. in dia., brs. S.70°W., 186 lks. dist., marked $\frac{1}{4}$ S16 BT.
No other trees available.
Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
- 46.60 Dry wash, 5 lks. wide, course SW.

Survey of Subdivision of Township 18 South, Range 2 West

Chains
79.98

The cor. of secs. 8,9,16 and 17.
Land: level.
Soil: sandy and rocky, 2nd. and 3rd. rates.
Timber: none.
Undergrowth: greasewood, sage, mesquite, palo verde
and cactus.

3.70
7.50
22.60
27.00
40.00

N.0°02'W., bet. secs. 8 and 9.
Over level land; thru scattering undergrowth.
Dry wash, 10 lks. wide, course SW.
Dry wash, 10 lks. wide, course SW.
Dry wash, 5 lks. wide, course SW.
Dry wash, 5 lks. wide, course SW.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for sec. cor., with brass cap marked

1/4
S8|S9
1925

43.80
68.40
80.00

No trees available.
Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W.
of cor.
Dry wash, 10 lks. wide, course SW.
Dry wash, 10 lks. wide, course SW.
Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in
the ground for cor. of secs. 4,5,8 and 9, with brass
cap marked

T18SR2W
S5|S4
S8|S9
1925

No trees available.
Dig pits 18 x 18 x 12 ins., one in each sec., 3 ft.
dist.
Land: level.
Soil: sandy and rocky, 2nd. and 3rd. rates.
Timber: none.
Undergrowth: greasewood, sage, mesquite, palo verde
and cactus.

40.00
79.78
9.20
25.80
39.89

S.89°59'E., on a random line bet. secs. 4 and 9.
Set temp. sec. cor.
Fall 13 lks. N. of the cor. of secs. 4,5,9 and 10.
Thence
N.89°54'W., on a true line, bet. secs. 4 and 9.
Dry wash, 10 lks. wide, course SW.
Dry wash, 30 lks. wide, course SW.
Set an iron post, 3 ft. long, 1 in. in dia., 6 ins. in
the ground to bedrock, supported by a mound of stone,
3 ft. base, 1 1/2 ft. high, for 1/4 sec. cor., with brass
cap marked

1/4 S4
S9
1925

54.30
74.10

No trees available.
Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N.
of cor.
Dry wash, 6 lks. wide, course SW.
Dry wash, 15 lks. wide, course SW.

Survey of Subdivision of Township 18 South, Range 2 West

Chains.
79.79

The cor. of secs. 4,5,8 and 9.
Land: level.
Soil: sandy and rocky, 2nd. and 3rd. rates.
Timber: none.
Undergrowth: greasewood, sage, palo verde, mesquite,
ironwood and cactus.

40.00
79.72

North, on a random line bet. secs. 4 and 5.
Set temp. $\frac{1}{4}$ sec. cor.
Fall 30 lks. E. of the cor. of secs. 4,5,32 and 33, on
the N. bdy. of the Tp., hereinbefore described.

18.70
39.70

Thence
S. $0^{\circ}13'$ E., on a true line, bet. secs. 4 and 5.
Over level land; thru scattering undergrowth.
Dry wash, 10 lks. wide, course SW.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \updownarrow \\ S5 | S4 \\ 1925 \end{array}$$

No trees available.

Raise a mound of stone, 3 ft. base, 12 ft. high, W.
of cor.

73.10
79.72

Dry wash, 10 lks. wide, course SW.
The cor. of secs. 4,5,8 and 9.
Land: level.
Soil: sandy and rocky, 2nd. and 3rd. rates.
Timber: none.
Undergrowth: greasewood, sage, palo verde mesquite,
ironwood and cactus.

8.20
40.00

From the cor. of secs. 5,6,31 and 32, on the S. bdy. of
the Tp., hereinbefore described.
N. $0^{\circ}03'$ W., bet. secs. 31 and 32.
Over level land; thru scattering undergrowth.
Road, brs. NW. and SE.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \updownarrow \\ S31 | S32 \\ 1925 \end{array}$$

from which

A mesquite, 6 ins. in dia., brs. N. 19° E., 56 lks.
dist., marked $\frac{1}{4}$ S32 BT.

A mesquite, 8 ins. in dia., brs. S. $59\frac{1}{4}^{\circ}$ W., 156 lks.
dist., marked $\frac{1}{4}$ S31 BT.

80.00

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground, for cor. of secs. 29,30,31 and 32, with
brass cap marked

$$\begin{array}{c} T18SR2W \\ S30 | S29 \\ S31 | S32 \\ 1925 \end{array}$$

from which

A mesquite, 10 ins. in dia., brs. N. 82° E., 192 lks.
dist., marked T18S R2W S29 BT.

A mesquite, 10 ins. in dia., brs. S. $24\frac{1}{2}^{\circ}$ E., 175
lks. dist., marked T18S R2W S32 BT.

Survey of Subdivision of Township 18 South, Range 2 West

Chains.

A mesquite, 6 ins. in dia., brs. S.28°W., 125 lks.
dist., marked T18S R2W S31 BT.

A mesquite, 8 ins. in dia., brs. N.40°W., 113 lks.
dist., marked T18S R2W S30 BT.

Land: level.

Soil: sandy, 2nd. rate.

Timber: none.

Undergrowth: greasewood, mesquite and cactus.

40.00

N.89°57'E., on a random line bet. secs. 29 and 32.

80.18

Set temp. $\frac{1}{4}$ sec. cor.

Fall 9 lks. S. of the cor. of secs. 28, 29, 32 and 33.

Thence

S.89°53'W., on a true line, bet. secs. 29 and 32.

27.50

Over level land; thru scattering undergrowth.

40.09

Road, brs. SE. and NW.

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S29 $\frac{1}{4}$ S32

1925

from which

A mesquite, 6 ins. in dia., brs. S.52 $\frac{1}{2}$ °E., 50 lks.
dist., marked $\frac{1}{4}$ S29 BT.

A mesquite, 8 ins. in dia., brs. N.9 $\frac{3}{4}$ °W., 48 lks.
dist., marked $\frac{1}{4}$ S32 BT.

80.18

The cor. of secs. 29, 30, 31 and 32.

Land: level.

Soil: sandy, 2nd. rate.

Timber: none.

Undergrowth: greasewood, mesquite and cactus.

40.00

S.89°57'W., on a random line bet. secs. 30 and 31.

80.83

Set temp. $\frac{1}{4}$ sec. cor.Fall 21 lks. N. of the cor. of secs. 25, 30, 31 and 36, on
the W. bdy. of the Tp., hereinbefore described.

Thence

N.89°48'E., on a true line, bet. secs. 30 and 31.

2.50

Over level land; through scattering undergrowth.

26.90

Road, brs. N.80°W., and S.80°E.

40.83

Dry wash, 4 lks. wide, course NW.

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S30 $\frac{1}{4}$ S31

1925

from which

A mesquite, 6 ins. in dia., brs. S.39 $\frac{3}{4}$ °W., 210 lks.
dist., marked $\frac{1}{4}$ S31 BT.

A mesquite, 4 ins. in dia., brs. N. 9 $\frac{1}{4}$ °W., 175 lks.
dist., marked BT.

80.83

The cor. of secs. 29, 30, 31 and 32.

Land: level.

Soil: sandy, 1st. rate.

Timber: none.

Undergrowth: greasewood, mesquite, sage and cactus.

N.0°03'W., bet. secs. 29 and 30.

Over level land; thru scattering undergrowth.

Survey of Subdivision of Township 18 South, Range 2 West


| | |
|-----------------|---|
| Chains 40.00 | <p>Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;"> $\frac{1}{4}$ S30 S29 1925 </p> <p>from which A mesquite, 8 ins. in dia., brs. S.55°E., 64 lks. dist., marked $\frac{1}{4}$ S29 BT. A mesquite, 6 ins. in dia., brs. N.39$\frac{1}{2}$°W., 105 lks. dist., marked $\frac{1}{4}$ S30 BT.</p> |
| 71.25 80.00 | <p>Road, brs. SE. and NW.</p> <p>Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 19,20,29 and 30, with brass cap marked</p> <p style="text-align: center;"> T18SR2W S19 S20 S30 S29 1925 </p> <p>from which A mesquite, 6 ins. in dia., brs. N.89°E., 70 lks. dist., marked BT (only). A mesquite, 6 ins. in dia., brs. S.81$\frac{1}{2}$°W., 212 lks. dist., marked T18S R2W S30 BT. No other trees available. Raise a mound of stone 3 ft. base, 1$\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land: level. Soil: sandy and rocky, 2nd. and 3rd. rates. Timber: none. Undergrowth: greasewood, sage, mesquite and cactus.</p> <p>-----</p> |
| 40.00 80.16 | <p>N.89°53'E., on a random line, bet. secs. 20 and 29.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p> <p>Fall 20 lks. N. of the cor. of secs. 20,21,28 and 29. Thence</p> |
| 40.08 | <p>N.89°59'W., on a true line, bet. secs. 20 and 29. Over level land; thru scattering undergrowth.</p> <p>Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;"> $\frac{1}{4}$ S20 S29 1925 </p> |
| 80.16 | <p>from which A mesquite, 6 ins. in dia., brs. S.49°E., 59 lks. dist., marked $\frac{1}{4}$ S29 BT. A mesquite, 6 ins. in dia., brs. N.39°W., 64 lks. dist., marked BT (only).</p> <p>The cor. of secs. 19,20,29 and 30. Land: level. Soil: sandy, 2nd. rate. Timber: none. Undergrowth: greasewood, sage, mesquite and cactus.</p> <p>-----</p> |
| 40.00 80.80 | <p>S.89°48'W., on a random line, bet. secs. 19 and 30.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p> <p>Fall 5 lks. N. of the cor. of secs. 19,24,25 and 30, on the W. bdy. of the Tp., hereinbefore described. Thence</p> |

Survey of

Subdivision of Township 18 South, Range 2 West

Chains

40.80 N.89°46'E., on a true line, bet. secs. 19 and 30.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 1/4 sec. cor., with brass cap marked



from which

A mesquite, 8 ins. in dia., brs. S.84°W., 68 lks. dist., marked 1/4 S30 BT.

A mesquite 8 ins. in dia., brs. N.43°W., 126 lks. dist., marked 1/4 S19 BT.

75.00 Road, brs. NW. and SE.

80.80 The cor. of secs. 19,20,29 and 30.

Land: level.

Soil: sandy, 2nd. rate.

Timber: none.

Undergrowth: greasewood, sage, mesquite, and cactus.

40.00 N.0°03'W., bet. secs. 19 and 20.
Over level land; thru scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 1/4 sec. cor., with brass cap marked




from which

A mesquite, 10 ins. in dia., brs. S.71 1/2°E., 315 lks. dist., marked 1/4 S20 BT.

A mesquite, 10 ins. in dia., brs. S.48°W., 48 lks. dist., marked 1/4 S19 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 17,18,19 and 20, with brass cap marked



from which

A mesquite, 6 ins. in dia., brs. N.27°E., 69 lks. dist., marked T18S R2W S17 BT.

A mesquite, 6 ins. in dia., brs. S.57 1/2°E., 176 lks. dist., marked T18S R2W S20 BT.

A mesquite, 8 ins. in dia., brs. S.28 1/2°W., 237 lks. dist., marked T18S R2W S19 BT.

A mesquite, 6 ins. in dia., brs. N.58°W., 97 lks. dist., marked T18S R2W S18 BT.

Land: rolling, and level.

Soil: sandy, 2nd. rate.

Timber: none.

Undergrowth: greasewood, sage, mesquite and cactus.

40.00 S.89°59'E., on a random line, bet. secs. 17 and 20.
Set temp. 1/4 sec. cor.
80.04 Fall 12 lks. S. of the cor. of secs. 16,17,20 and 21.
Thence
S.89°56'W., on a true line bet. secs. 17 and 20.
Over level land; thru scattering undergrowth.

Survey of Subdivision of Township 18 South, Range 2 West

Chains
40.02Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked.
$$\begin{array}{r} \frac{1}{4}S17 \\ \frac{1}{4}S20 \\ 1925 \end{array}$$

from which

A mesquite, 6 ins. in dia., brs. S.25°E., 27 lks. dist., marked $\frac{1}{4}$ S20 BT.A mesquite, 6 ins. in dia., brs. N.3°W., 156 lks. dist., marked $\frac{1}{4}$ S17 BT.

80.04

The cor. of secs. 17,18,19 and 20.

Land: slightly rolling.

Soil: sandy and rocky, 2nd, and 3rd. rates.

Timber: none.

Undergrowth: greasewood, sage, mesquite and cactus.

40.00

S.89°46'W., on a random line bet. secs. 18 and 19.

Set tem. $\frac{1}{4}$ sec. cor.

80.74

Intersect the cor. of secs. 13,18,19 and 24, on the W. bdy. of the Tp., hereinbefore described.

Thence

N.89°46'E., on a true line bet. secs. 18 and 19.

Over level land; thru scattering undergrowth.

40.74

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{r} \frac{1}{4}S18 \\ \frac{1}{4}S19 \\ 1925 \end{array}$$

No trees available.

Dig pits 18 x 18 x 12 ins., one each E. and W., 3 ft. dist.

40.80

Road, brs. NW. and SE.

80.74

The cor. of secs. 17,18,19 and 20.

Land: level.

Soil: sandy, 2nd. rate.

Timber: none.

Undergrowth: greasewood, sage and mesquite.

40.00

N.0°03'W., bet. secs. 17 and 18.

Over level land; thru scattering timber.

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{r} \frac{1}{4}S18 \quad \frac{1}{4}S17 \\ 1925 \end{array}$$

from which

A palo verde, 8 ins. in dia., brs. N.89°E., 99 lks. dist., marked $\frac{1}{4}$ S17 BT.A mesquite, 10 ins. in dia., brs. S.48°W., 62 lks. dist., marked $\frac{1}{4}$ S18 BT.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 7,8,17 and 18, with Brass cap marked

$$\begin{array}{r} T18SR2W \\ \frac{1}{4}S7 \quad \frac{1}{4}S8 \\ \frac{1}{4}S18 \quad \frac{1}{4}S17 \\ 1925 \end{array}$$

Survey of Subdivision of Township 18 South, Range 2 West

| | |
|---|--|
| <p>Chains</p> <p>40.00</p> <p>80.08</p> <p>5.60</p> <p>31.40</p> <p>40.04</p> <p>80.08</p> <p>40.00</p> <p>80.47</p> <p>2.70</p> <p>40.57</p> <p>56.00</p> <p>80.57</p> | <p>from which</p> <p>A mesquite, 8 ins. in dia., brs. N.52°E., 214 lks. dist., marked $\frac{1}{4}$S8 R2W S8 BT.</p> <p>A mesquite, 6 ins. in dia., brs. S.36°E., 259 lks. dist., marked $\frac{1}{4}$S8 R2W S17 BT.</p> <p>A mesquite, 3 ins. in dia., brs. S.12°W., 117 lks. dist., marked $\frac{1}{4}$S8 R2W S18 BT.</p> <p>A mesquite, 4 ins. in dia., brs. N.55$\frac{1}{2}$°W., 78 lks. dist., marked BT.</p> <p>Land: level.</p> <p>Soil: sandy, 2nd. rate.</p> <p>Timber: none.</p> <p>Undergrowth: greasewood, sage and mesquite.</p> <hr/> <p>N.89°56'E. on random line, bet. secs. 8 and 17.</p> <p>Set temp. $\frac{1}{4}$ sec. cor. $\frac{1}{4}$S8 R2W S17 BT.</p> <p>Fall 5 lks. S. of the cor. of secs. 8, 9, 16 and 17.</p> <p>Thence</p> <p>S.89°34'W., on a true line bet. secs. 8 and 17.</p> <p>Over level land; thru scattering undergrowth.</p> <p>Dry wash, 10 lks. wide, course SW.</p> <p>Dry wash, 15 lks. wide, course SW.</p> <p>Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$S8 $\frac{1}{4}$S17 1925</p> <p>from which</p> <p>A mesquite, 10 ins. in dia., brs. S.41°W., 54 lks. dist., marked $\frac{1}{4}$S17 BT.</p> <p>A mesquite, 8 ins. in dia., brs. N.9°W., 71 lks. dist., marked $\frac{1}{4}$S8 BT.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land: level.</p> <p>Soil: sandy and rocky, 2nd. and 3rd. rates.</p> <p>Timber: none.</p> <p>Undergrowth: greasewood, sage, mesquite, palo verde, and cactus.</p> <hr/> <p>S.89°46'W., on a random line, bet. secs. 7 and 18.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p> <p>Fall 2 lks. S. of the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Thence</p> <p>N.89°47'E., on a true line, bet. secs. 7 and 18.</p> <p>Over level land; thru scattering undergrowth.</p> <p>Road, brs. NW. and SE.</p> <p>Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$S7 S18 1925</p> <p>No trees available.</p> <p>Dig pits 18 x 18 x 12 ins., one each E. and W., 3 ft. dist.</p> <p>Dry wash, 30 lks. wide, course SW.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land: level.</p> <p>Soil: sandy, 1st. rate.</p> <p>Timber: none.</p> <p>Undergrowth: greasewood, sage and mesquite.</p> <hr/> |
|---|--|

Survey of Subdivision of Township 18 South, Range 2 West

Chains

N.0°03'W., bet. secs. 7 and 8.
 Over level land; thru scattering undergrowth.
 34.10 Dry wash, 10 lks. wide, course SW.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 29 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S7 | S8
 1925

from which
 A mesquite, 8 ins. in dia., brs. S.30°E., 25 lks.
 dist., marked $\frac{1}{4}$ S8 BT.
 A mesquite, 8 ins. in dia., brs. S.9°W., 193 lks.
 dist., marked $\frac{1}{4}$ S7 BT.

63.00 Dry wash, 20 lks. wide, course SW.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in
 the ground for cor. of secs. 5,6,7 and 8, with brass
 cap marked

T18SR2W
 S6 | S5
 S7 | S8
 1925

No trees available.
 Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W.
 of cor.
 Land: level.
 Soil: sandy and rocky, 2nd. rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite, palo verde
 and cactus.

40.00 N.89°54'E., on a random line, bet. secs. 5 and 8.
 Set temp. $\frac{1}{4}$ sec. cor.
 80.14 Fall 5 lks. N. of the cor. of secs. 4,5,8 and 9.
 Thence
 S. 89°56'W., on a true line, bet. secs. 5 and 8.
 Over level land; thru scattering undergrowth.

3.90 Dry wash, 20 lks. wide, course SW.
 20.60 Dry wash, 5 lks. wide, course SW.
 40.07 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S5
 S8
 1925

from which
 A mesquite, 10 ins. in dia., brs. N.64°W., 160 lks.
 dist., marked $\frac{1}{4}$ S5 BT.
 No other trees available.
 Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high,
 N. of cor.

50.10 Dry wash, 6 lks. wide, course S.
 73.40 Dry wash, 20 lks. wide, course SW.
 80.14 The cor. of secs. 5,6,7 and 8.
 Land: level.
 Soil: sandy, 2nd. rate.
 Timber: none.
 Undergrowth: greasewood, sage, palo verde and mesquite.

Survey of Subdivision of Township 18 South, Range 2 West

Chains
 40.00 S. 89° 47' W., on a random line, bet. secs. 6 and 7.
 80.34 Set temp. $\frac{1}{4}$ sec. cor.
 Fall 4 lks. N. of the cor. of secs. 1, 6, 7 and 12, on
 the W. bdy. of the Tp., hereinbefore described.
 Thence
 40.34 N. 89° 45' E., on a true line, bet. secs. 6 and 7.
 Over level land; thru scattering undergrowth.
 Set an iron post, 3 ft. long, 1 in. in dia. 28 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ 86
 87
 1925

No trees available.
 Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft.
 dist.
 45.00 Dry wash, 15 lks. wide, course S.
 80.34 The cor. of secs. 5, 6, 7 and 8.
 Land: level.
 Soil: sandy and rocky, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite, palo verde,
 ironwood and cactus.

40.00 North, on a random line, bet. secs. 5 and 6.
 79.65 Set temp. $\frac{1}{4}$ sec. cor.
 Fall 20 lks. E. of the cor. of secs. 5, 6, 31 and 32, on
 the E. bdy. of the Tp., hereinbefore described.
 Thence
 12.20 S. 0° 09' E., on a true line, bet. secs. 5 and 6.
 39.65 Over level land; thru scattering undergrowth.
 Dry wash, 10 lks. wide, course SW.
 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S6 | S5
 1925

No trees available.
 Raise amount of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W.
 of cor.
 79.65 The cor. of secs. 5, 6, 7 and 8.
 Land: level.
 Soil: rocky, 3rd rate.
 Timber: none.
 Undergrowth: greasewood, sage, mesquite, palo verde,
 ironwood and cactus.

GENERAL DESCRIPTION

T. 18 S., R. 2 W. is level, except for a range of volcanic
 mountains in the N.E. part. Its soil is sand and
 adobe, generally of a good depth.
 It has no timber, but has a heavy growth of mesquite,
 ironwood, palo verde, greasewood, sage and different
 varieties of cactus on its level ground, with a
 smaller amount of the same in the mountains.
 It has no water and no residents. A fair road crosses
 the S.W. corner.

Township 18 South, Range 2 West
Final Tests.

FINAL TESTS

Young & Sons Transits Nos. 8592 and 8541

Dec. 20, 1925: examine the adjustments of the instruments and correct all errors; then to test the solar apparatus by comparing its indications from observations made during a.m. and p.m. hours with a meridian established by Polaris observation, proceed as follows:

At place, and on meridian described on page 2 of Book "D" of this Group, on Dec. 20, 1925, 9h 00m. a.m., l.m.t., set off $51^{\circ}49\frac{1}{2}'$ on the lat. arcs, and $23^{\circ}24'S.$ on the decl. arcs and determine meridians with the solars. The resulting lines agree with the true meridian.

At app. noon, with the lat. arcs unchanged, observe the sun on the meridian; the resulting reading of the decl. arcs is $23^{\circ}24\frac{1}{2}'S.$, which agrees with the computed decl. of the sun.

At 3h. 00m., p.m., l.m.t., with the lat. arcs unchanged, set off $23^{\circ}24\frac{1}{2}'$ on the decl. arcs, and determine meridians with the solars; which coincide with the true meridian.

As solar observations taken during all of the usual working hours agree within 1' with the true meridian, conclude that the adjustment of the instruments have remained satisfactory.

4-680

FIELD ASSISTANTS.
to Otis O. Gould, U.S. Transitman

| NAMES. | CAPACITY. |
|---------------|-----------------|
| Homer Klippel | First Chainman |
| Earl Uffer | Second Chainman |
| Wm. Kroll | Moundsman |
| Pilcher Brown | Flagman |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

CERTIFICATE OF UNITED STATES TRANSITMAN.

I, Otis O. Gould, U.S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for Group 101, Arizona bearing date of the 26th day of September, 1919, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the Subdivision lines of Township 18 South, Range 2 West,

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in and by diagram on page 1 hereof the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Group 101, Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Place Phoenix Arizona

Otis O. Gould, U.S. Transitman

Date May 1, 1926

APPROVAL

Office of the United States

19

The foregoing field notes of the survey of

executed by under his special instructions dated 10 having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office

4-680

FIELD ASSISTANTS.
to William H. Thorn, U.S. Cadastral Engineer

| NAMES. | CAPACITY. |
|------------------|-----------------|
| Walter Thomas | First Chainman |
| Albert Bailey | Second Chainman |
| Homer Pepper | Moundsman |
| George M. Tucker | Flagman |
| Milton Stevens | Axman |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

CERTIFICATE OF UNITED STATES CADASTRAL ENGINEER.

I, William H. Thorn, U.S. Cad. Engineer, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General, for Group 101, Arizona, bearing date of the 26th day of September, 1919, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the East, West, North and South Boundaries and Subdivision lines of Township 18 South, Range 2 West,

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes and by diagram on page 1 hereof as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 101, Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Place Phoenix Arizona

William H. Thorn
U.S. Cadastral Engineer.

Date May 21st 1926

APPROVAL.

OFFICE OF THE UNITED STATES Supervisor of Surveys.

Denver, Colorado, August 23, 1926.

The foregoing field notes of the survey of the East, West, North and South Boundaries and all of the Subdivision lines of Township 18 South, Range 2 West of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by William H. Thorn, U.S. Cadastral Engineer under his special instructions dated September 26, 1919, for Group 101, Ariz, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U.S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in Book 3727 of Group 101, Arizona, has been correctly copied from the original notes on file in this office.

U.S. Supervisor of Surveys