

1

BOOK 3926

# FIELD NOTES

OF THE RESURVEY OF

Part of the SOUTH BOUNDARY

of Township 1 South, Range 3 West

AND OF THE SURVEY OF

WEST BOUNDARY

and

SUBDIVISION LINES

of

Township 2 South, Range 3 West

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Benjamin J. Kinsey

and Karl L. Siebecker

U.S. Surveyors

*In the capacity of U. S. Surveyor<sup>s</sup>, under Special Instructions dated July 15, 1930, issued by the District Cadastral Engineer to govern surveys included in Group No. 164 Arizona, which were approved by the Commissioner of the General Land Office, August 5, 1930, and Assignment Instructions: to Kinsey dated Jan. 12, 1931, to Siebecker dated Dec. 23, 1930.*

Resurvey and Survey commenced February 10, 1931.

Resurvey and Survey completed March 13, 1931.

3926

3926

119

BOOK 3926

# INDEX DIAGRAM.

T.1S.:R.4W.

T.1S.:R.3W.

*Note: The survey of the Range Line in T.2S. is transcribed herein and also in Book "C".  
 In Book "C" the notes describe topography and all corr. referring to T.2S.:R.4W.  
 The notes herein omit topography and describe only corr. referring to T.2S.:R.3W.*

36	31	32	33	34	35	36
8	7	7	6	6	5	4
11 6 45 44	5 37 44	4 30 36	8 23 29	2 17 23	1 17	
11 7 43 43	8 36 42	9 28 35	10 22 28	11 16 22	12 16	
10 18 42 41	17 35 41	16 27 34	15 21 27	14 15 21	18 15 14	
10 19 40 40	20 34 40 39	21 26 33	22 20 26 25	23 14 20 19	24 14 13	
9 30 39 38 39	29 32 38	28 25 32 31	27 19 25 24	26 13 19 18	25 13 12	
9 31 38 37	32 31 32	33 24 33	34 18 34	35 12 35	36 36	

GOVERNMENT PRINTING OFFICE

————— Surveyed under this group.

----- Resurveyed under this group.

————— Accepted, surveyed lines.

Areas surveyed as per accepted plats on file.

Book "B"

Group 164 Arizona

DATE DIAGRAM

(1931)

BOOK 3926

T.1S-R.4W.

T.1S-R.3W.

Surv. in 1882  
Resurv. in 1916

	36	31	32	33	34	35	36					
		Feb. 11	Feb. 11	Feb. 11	Feb. 10	Feb. 10	Feb. 10					
March 12	6	March 13	5	March 11	4	March 11	3	March 9	2	March 9	1	
March 13	March 13	March 13	March 11	March 11	March 11	March 9	March 9	March 9	March 9	March 9	March 9	
March 2	7	March 13	8	March 6	9	March 11	10	March 9	11	March 9	12	
March 10	March 10	March 10	March 6	March 5	March 5	March 9	March 5	March 9	March 4	March 9	March 3	
March 2	18	March 10	17	March 6	16	March 5	15	March 4	14	March 3	13	
March 10	March 10	March 10	March 6	T.2S. March 6	March 5	R.3W. March 5	March 5	March 4	March 4	March 3	March 3	
March 2	19	March 10	20	March 6	21	March 5	22	March 4	23	March 3	24	
March 7	March 7	March 6	March 6	March 6	March 5	March 5	March 5	March 4	March 4	March 3	March 3	
March 2	30	March 7	29	March 6	28	March 5	27	March 4	26	March 3	25	
March 7	March 7	March 7	March 7	March 6	March 5	March 5	March 5	March 4	March 4	March 3	March 3	
Feb. 28	31	March 7	32	Feb. 24	33	March 5	34	Feb. 23	35	March 3	36	
March 7	March 7	March 7	Feb. 24	March 5	March 5	March 5	March 5	Feb. 23	March 3	March 3	March 3	

Surveyed in 1916

————— Surveyed under this group by Benj. J. Kinsey, U.S. Surveyor on dates (1931) shown thereon, and as described in the notes herein.

- - - - - Surveyed under this group by Benj. J. Kinsey, U.S. Surveyor. Date diagram and notes in Book "A."

————— Resurveyed under this group by Karl L. Siebecker, U.S. Surveyor on dates (1931) shown thereon, and as described in the notes herein.

- - - - - Resurveyed under this group by Karl L. Siebecker, U.S. Surveyor. Date diagram and notes in Book "C."

————— Surveyed under this group by Benj. J. Kinsey, U.S. Surveyor. Date diagram and notes in Book "C."

————— Resurveyed under this group by Karl L. Siebecker, U.S. Surveyor. Date diagram and notes in Book "D."

————— Accepted, surveyed lines.

The resurveys and surveys herein described were executed on dates shown on diagram on page 1 hereof.

The resurveys were executed by Karl L. Siebecker, U.S. Surveyor, using a Young & Sons transit No. 8487, and the surveys were executed by Benjamin J. Kinsey, U.S. Surveyor using a Buff transit No. 18000, and a Young & Sons transit No. 8540. Each of said instruments is equipped with an improved Smith solar attachment, and otherwise conforms to standard requirements of the General Land Office.

Young & Sons transit No. 8487 was approved by the district cadastral engineer for the Calif.-Ariz. district on October 20, 1930, and the Buff transit No. 18000 and the Young & Sons transit No. 8540, were approved by same officer on January 12, 1931, both approvals made subject to satisfactory field tests of said instruments.

The directions of the lines were determined by solar transit method. The measurements were made with Lallie steel tapes 5 chs. in length, graduated every link for the first 100 lks., and thereafter at intervals of 10 links. The tapes were tested by comparison with a Lufkin standard tape and found correct. All measurements were made on the slope; the vertical angles were determined by clinometers in good adjustment; the field notes herein record the horizontal equivalents.

The data furnished with the special instructions gives the geographic position of the SE. cor. of T. 2 S., R. 3 W. in latitude  $33^{\circ}12'07''N.$ , and longitude  $112^{\circ}30'48''W.$

-----  
 PRELIMINARY FIELD TEST of  
 Young & Sons Transit No. 8487  
 by Karl L. Siebecker, U.S. Surveyor.  
 -----

January 4, 1931: in camp at the Beloat Ranch, near the center of SW $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 6, T. 1 S., R. 2 W., latitude  $33^{\circ}22'N.$ , longitude  $112^{\circ}30\frac{1}{2}'W.$ , at 1h. 12.6m. a.m. by watch, which reads correct 105th meridian time as determined by radio signals, observe Polaris at western elongation, making six sights, three each with the telescope in direct and reversed positions, and turn an angle from a tack in a fence post about 10 chs. NW. The mean angle to the mark is  $64^{\circ}22'42''$  westerly. The azimuth of Polaris is  $1^{\circ}16'18''$  to the east, therefore the bearing of the mark is  $N. 65^{\circ}39'W.$

In order to verify the latitude of this station and the reading of the watch, make a meridian observation of the sun, first setting on the lower limb and noting the transit of the west limb, then, after reversal of the instrument, setting on the upper limb and noting the transit of the east limb, as follows:

Mean observed altitude	= $33^{\circ}54'35''$
Reduced latitude	= $33^{\circ}22'08''$
Mean watch time of observation	= 12h. 40m. 15s.
Watch fast of l.m.t.	= 30m. 11s.

Same in reference to radio time signals and calculated difference in longitude = 30m.

Every hour from 7 to 11 a.m. and from 1 to 5 p.m. make proper settings on the arcs of the solar attachment and ascertain that the resulting orientation of the instrument, when compared with the meridian established by Polaris observation, has a maximum error of less than 30".

February 10, 1931: at camp and on same meridian herein-  
before described, at 8h. 0m. a.m., app. t., set off  
33°22'N. on the lat. arc, 14°29'S. on the decl. arc,  
and orient the instrument with the solar. The line  
of sight agrees with the meridian.  
At 4h. 0m. p.m., app. t., with the lat. arc unchanged,  
set off 14°22½'S. on the decl. arc, and repeat the  
test with the solar; the line of sight thus defined  
agrees within 1' with the meridian.  
The observed magnetic declination is 14°35'E.

PRELIMINARY FIELD TEST of  
Buff Transit No.18000 and Young & Sons Transit No.8540.  
by Benjamin J. Kinsey, U.S.Surveyor.

February 18, 1931: at station near the center of SE¼ of  
sec.28, T.2 S., R.3 W., G.&S.R. B.& M., Arizona,  
latitude 33°13'25"N., longitude 112°34'09"W., examine  
the adjustments of the transits and find no errors;  
then, to test the workings of the solar apparatus,  
proceed as follows:

At 9h.41m. p.m., l.m.t., using Buff transit No.18000,  
observe Polaris at western elongation, making four  
observations, two each with the telescope in direct  
and reversed positions, and mark the mean point in the  
line thus determined by a tack in a peg driven firmly  
in the ground about 5 chs. N.

Azimuth of Polaris at western elongation = 1°16'04"

February 19, 1931: at 8h.0m. a.m., app. t., lay off the  
azimuth of Polaris 1°16' to the east and mark the  
meridian thus determined by a nail in a peg driven  
firmly in the ground about 5 chs. N.

At 9h.00m. a.m., app. t., set off 33°13½'N. on the lat.  
arcs, 11°25½'S. on the decl. arcs, and determine a  
meridian with each solar, both of which are found to  
agree with the true meridian.

At app. noon, with the lat. arcs unchanged, observe the  
sun on the meridian; the resultant reading of each of  
the decl. arcs is 11°23'S., which agrees with the  
computed declination of the sun.

At 3h.00m. p.m., app. t., with the lat. arcs unchanged,  
set off 11°20'S. on the decl. arcs, and determine a  
meridian with each solar, both of which are found to  
agree with the true meridian.

As all of the observations taken with both instruments  
during the usual hours of solar work define positions  
for meridian which agree within 1' with the true  
meridian, conclude that the instruments are in satis-  
factory adjustment.

Resurvey of Part of the South Boundary of T.1 S., R.3 W.

Chains The South bdy. of T.1 S., R.3 W. was surveyed in 1882 by R.C. Powers, U.S.D.S., establishing all cor. monuments thereon with a common reference to areas on both sides of the line.

The east half of the S. bdy. of sec. 36 was resurveyed in 1916 by W.H. Thorn, U.S.S., who reconstructed the SE. cor. of the Tp., and the S.  $\frac{1}{4}$  sec. cor. of sec. 36, altering both of said cors. to refer to areas N. of line only.

No other resurvey, and no retracement of any part of this Tp. bdy. is of record.

The following notes describe a resurvey of the west  $5\frac{1}{2}$  miles of said Tp. bdy., westerly from the S.  $\frac{1}{4}$  sec. cor. of sec. 36 to the SW. cor. of the Tp., reconstructing all existing cor. monuments by setting brass-capped iron posts alongside, reestablishing all missing cors. by proportion bet. existing cors., and altering all cors. to refer to areas N. of line only.

-----  
Retracement for Resurvey.  
-----

From the S.  $\frac{1}{4}$  sec. cor. of sec. 36,  
West, on random line, searching diligently at record intervals for the original cor. monuments, and setting temp. cors. at such intervals.  
Fail to find any trace of an old cor. until at

401.35 Fall 47 lks. S. of the original  $\frac{1}{4}$  sec. cor. of secs. 6 and 31.  
True course and dist. of Tp. bdy. from S.  $\frac{1}{4}$  sec. cor. of sec. 36 to the original  $\frac{1}{4}$  sec. cor. of secs. 6 and 31 are therefore, N.  $89^{\circ}56'W.$ , 401.35 chs., which, to maintain original proportion between cor. intervals, gives ten intervals of 40.135 chs. each for the reestablishment of the missing cor. monuments on said Tp. bdy.

Thence  
West, on random line, on S. bdy. of sec. 31 (W.  $\frac{1}{2}$ )

39.97 Fall 59 lks. S. of the original cor. of Ts. 1 and 2 S., Rs. 3 and 4 W.  
True course and dist. of W.  $\frac{1}{2}$  of S. bdy. of sec. 31 are therefore, N.  $89^{\circ}09'W.$ , 39.97 chs.

-----  
Resurvey.  
-----

The S.  $\frac{1}{4}$  sec. cor. of sec. 36 is an iron post, 1 in. diam., projecting 10 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

Thence  
N.  $89^{\circ}56'W.$ , on true line, on S. bdy. of sec. 36 (W.  $\frac{1}{2}$ )  
Over rolling land, thru scattering timber and patches of dense undergrowth.

1.40 Wash, 20 lks. wide, course SE.

40.14 (Proportional dist.) Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished cor. of secs. 35 and 36 only, with brass cap mkd.

T1S R3W  
S35 | S36  
-----  
T2S R3W  
S1  
1931

from which  
a paloverde, 4 ins. in diam., brs. N.  $70\frac{1}{2}^{\circ}E.$ ,  
222 lks. dist., mkd. BT only.  
an ironwood, 8 ins. in diam., brs. N.  $33\frac{3}{4}^{\circ}W.$ ,  
194 lks. dist., mkd. T1S R3W S35 BT

Resurvey of Part of the South Boundary of T.1 S., R.3 W.

Chains	<p>Land, rolling. Soil, gravelly loam, 3rd rate. Timber, paloverde, mesquite, ironwood, and catclaw. Undergrowth, same, with greasewood, cacti, and ocotillo.</p> <hr/> <p>N. 89° 56' W., on true line, on S. bdy. of sec. 35. Over hilly land, thru scattering timber and patches of dense undergrowth. Desc. 25 ft. over W. slope.</p> <p>14.95 Wash, 20 lks. wide, course S. Asc. 25 ft. 25.50 Spur, slopes S. Desc. 40 ft. 35.80 Wash, 20 lks. wide, course S. Asc. 20 ft. to 40.13 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished <math>\frac{1}{4}</math> sec. cor. of sec. 35 only, with brass cap mkd.</p> <p style="text-align: center;"><u><math>\frac{1}{4}</math> S35</u></p> <p style="text-align: center;">1931</p> <p style="text-align: right;">from which</p> <p>a paloverde, 6 ins. in diam., brs. N. 62° E., 95 lks. dist., mkd. <math>\frac{1}{4}</math> S35 BT a paloverde, 4 ins. in diam., brs. N. 46<math>\frac{3}{4}</math>° W., 67 lks. dist., mkd. <math>\frac{1}{4}</math> S35 BT</p> <p>Asc. 95 ft. over E. slope.</p> <p>44.00 Spur, slopes S. Desc. 70 ft. 49.80 Head of draw, course NE. Asc. 70 ft. 59.50 Spur, slopes N. Desc. 85 ft. to 80.27 (Proportional dist.) Set an iron post, 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished cor. of secs. 34 and 35, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W <u>S34   S35</u> T2S R3W S2</p> <p style="text-align: center;">1931</p> <p style="text-align: right;">from which</p> <p>a paloverde, 6 ins. in diam., brs. N. 48<math>\frac{1}{2}</math>° E., 113 lks. dist., mkd. T1S R3W S35 BT a paloverde, 6 ins. in diam., brs. N. 2° W., 64 lks. dist., mkd. T1S R3W S34 BT</p> <p>Land, hilly. Soil, gravelly and rocky loam, 3rd rate. Timber, paloverde, ironwood, mesquite and catclaw. Undergrowth, same, with greasewood, cacti, and ocotillo.</p> <hr/> <p>N. 89° 56' W., on true line, on S. Bdy. of sec. 34. Over rolling land, thru scattering timber and patches of dense undergrowth.</p> <p>4.20 Wash, 30 lks. wide, course N. 10.00 Wash, 40 lks. wide, course NE. 14.70 Road, brs. NE. and SW. 40.13 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for reestablished <math>\frac{1}{4}</math> sec. cor. of sec. 34 only, with brass cap mkd.</p> <p style="text-align: center;"><u><math>\frac{1}{4}</math> S34</u></p> <p style="text-align: center;">1931</p> <p style="text-align: right;">from which</p> <p>an ironwood, 8 ins. in diam., brs. N. 35° E. 410 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT a paloverde, 6 ins. in diam., brs. N. 2° W. 423 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT</p> <p>Thence over steep E. slope. Asc. 300 ft. over boulders and ledges.</p>
--------	--

Resurvey of Part of the South Boundary of T.1 S., R.3 W.

Chains  
 75.30 Spur, slopes SE. Desc. slightly.  
 76.20 Head of draw, course SE. Asc.  
 77.90 Ridge, brs. NE. and S. Desc. 65 ft. to  
 80.27 (Proportional dist.) Set an iron post, 3 ft. long, 2 ins. in diam., over a cross (X) mkd. on rock ledge, and raise a mound of stone around post, for reestablished cor. of secs. 33 and 34. only, with brass cap mkd.

T1S R3W  
 S33 | S34  
 T2S R3W  
 S3  
 1931

from which  
 a paloverde, 4 ins. in diam., brs. West  
 56 lks. dist., mkd. BT only.

Land, E.  $\frac{2}{3}$  rolling. W.  $\frac{2}{3}$  mountainous.  
 Soil, gravelly and rocky loam, 4th rate.  
 Timber, paloverde, mesquite, ironwood, and catclaw.  
 Undergrowth, greasewood and cacti.

N. 89° 56' W., on true line, on S. bdy. of sec. 33.  
 Over mountainous land, thru widely scattering timber and patches of dense undergrowth.  
 Asc. 10 ft. over SE. slope.  
 1.00 Rock ledge, brs. NW. and SE. Desc. 150 ft.  
 7.40 Draw, course SW. Asc. 100 ft.  
 11.00 Short spur, slopes SW. Desc. 100 ft.  
 38.90 Road, brs. NE. and SW.  
 40.13 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. in diam., 17 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished  $\frac{1}{4}$  sec. cor. of sec. 33 only, with brass cap mkd.

$\frac{1}{4}$  S33  
 1931

from which  
 an ironwood, 9 ins. in diam., brs. N. 51° E.,  
 309 lks. dist., mkd.  $\frac{1}{4}$  S33 BT  
 an ironwood, 16 ins. in diam., brs. N. 80  $\frac{1}{2}$ ° W.,  
 251 lks. dist., mkd.  $\frac{1}{4}$  S33 BT

43.30 Wash, 50 lks. wide, course SW. Asc. 85 ft.  
 53.40 Spur, slopes S. Desc. 80 ft.  
 58.30 Draw, course S. Asc. 20 ft.  
 61.10 Spur, slopes S. Desc. 85 ft.  
 64.00 Draw, course S. Asc. 195 ft.  
 80.00 Ridge, brs. N. and S. Desc. 5 ft. to  
 80.27 (Proportional dist.) Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for reestablished cor. of secs. 32 and 33 only, with brass cap mkd.

T1S R3W  
 S32 | S33  
 T2S R3W  
 S4  
 1931

from which  
 a paloverde, 4 ins. in diam., brs. N. 7  $\frac{1}{2}$ ° W.,  
 25 lks. dist., mkd. BT only.  
 No other bearing trees available.  
 raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.  
 Land, mountainous.  
 Soil, rocky and gravelly loam, 4th rate.  
 Timber, paloverde, ironwood and mesquite.  
 Undergrowth, same, with greasewood, cacti and ocotillo.



Resurvey of Part of the South Boundary of T.1 S., R.3 W.

Chains N. 89° 56' W., on true line, on S. bdy. of sec. 32.  
 Over mountainous land, thru widely scattering timber  
 and patches of dense undergrowth.  
 Desc. 65 ft. over W. slope.  
 7.65 Draw, course S. Asc. 200 ft.  
 13.15 Spur, slopes S. Desc. 60 ft.  
 17.85 Wash, 20 lks. wide, course SE. Asc. 240 ft.  
 31.85 Ridge, brs. NW. and SE. Desc. 70 ft.  
 37.00 Head of draw, course S. Asc. 30 ft.  
 39.45 Spur, slopes SW. Desc. slightly to  
 40.13 (Proportional dist.) Set an iron post, 3 ft. long, 1 in.  
 in diam., 12 ins. in the ground to bedrock, over a  
 cross (X) mkd. on bedrock, and raise a mound of stone  
 around post, for reestablished  $\frac{1}{4}$  sec. cor. of sec. 32  
 only, with brass cap mkd.

$\frac{1}{4}$  S32

1931

Desc. 205 ft. over NW. slope.  
 47.65 Draw, course S. Asc. 50 ft.  
 54.00 Spur, slopes S. Desc. 185 ft. over broken NW. slope.  
 61.30 Spur, slopes SW.  
 65.85 Draw, course NW.  
 74.00 Head of draw, course N. Asc. 35 ft.  
 78.00 Top of low knoll. Desc. 40 ft. to  
 80.27 (Proportional dist.) Set an iron post, 3 ft. long, 2 ins.  
 in diam., 27 ins. in the ground, for reestablished  
 cor. of secs. 31 and 32 only, with brass cap mkd.

T1S R3W

S31	S32
-----	-----

T2S R3W

S5

1931

from which  
 a paloverde, 5 ins. in diam., brs. N. 14 $\frac{1}{2}$ ° E.,  
 133 lks. dist., mkd. T1S R3W S32 BT  
 a paloverde, 8 ins. in diam., brs. N. 88 $\frac{1}{2}$ ° W.,  
 121 lks. dist., mkd. T1S R3W S31 BT

Land, mountainous.  
 Soil, rocky and gravelly loam, 4th rate.  
 Timber, paloverde, ironwood, and mesquite.  
 Undergrowth, same, with greasewood, cacti and ocotillo.

N. 89° 56' W., on true line, on S. bdy. of sec. 31 (E.  $\frac{1}{2}$ )  
 Over mountainous land, thru widely scattering timber  
 and patches of dense undergrowth.  
 Asc. 45 ft. over SE. slope.  
 4.40 Spur, slopes SW. Desc. 95 ft.  
 22.10 Wash, 30 lks. wide, course N. Asc. 45 ft.  
 31.40 Top of small peak. Desc. 160 ft. to  
 40.13 Intersect the original  $\frac{1}{4}$  sec. cor. of secs. 6 and 31,  
 which is a granite stone, 10x12x18 ins. above ground,  
 firmly set, mkd. and witnessed as described in the  
 official record.  
 Reconstruct this cor. monument and alter its reference  
 as follows:  
 alongside old cor. stone, set an iron post, 3 ft. long,  
 1 in. in diam., 30 ins. in the ground to bedrock, and  
 raise a mound of stone around post, for  $\frac{1}{4}$  sec. cor. of  
 sec. 31 only, with brass cap mkd.

## Resurvey of Part of the South Boundary of T.1 S., R.3 W.

Chains

1/4 S31

1931

from which  
 a paloverde, 4 ins. in diam., brs. N.87°E.  
 104 lks. dist., mkd. BT only.

a paloverde, 6 ins. in diam., brs. N.49°W.,  
 151 lks. dist., mkd. BT only.

Thence

N.89°09'W., on true line, on S. bdy. of sec. 31 (W. 1/4)  
 Over rolling land, thru scattering timber and dense  
 undergrowth.

23.35

Road, brs. NW. and SE.

30.45

Wash, 20 lks. wide, course NW.

39.97

Intersect the original cor. of Ts. 1 and 2 S., Rs. 3 and  
 4 W., which is a decayed wooden post, 3 ins. square,  
 projecting 18 ins. above ground, marking faintly  
 visible but illegible. Slight traces of four pits,  
 one each N., S., E. and W. of post.

Reconstruct this cor. monument and alter its reference  
 as follows:

alongside old post, set an iron post, 3 ft. long,  
 3 ins. in diam., 28 ins. in the ground, for cor. of  
 Ts. 1 S., Rs. 3 and 4 W. only, with brass cap mkd.

T1S

R4W | R3W

S36 | S31

T2S | R3W

S6

1931

from which  
 a paloverde, 8 ins. in diam., brs. N.37 1/4°E.,  
 380 lks. dist., mkd. T1S R3W S31 BT

a paloverde, 6 ins. in diam., brs. N77 1/2°W.,  
 302 lks. dist., mkd. T1S R4W S36 BT

Land, E. 1/2 mountainous; W. 1/2 rolling.

Soil, E. 1/2 rocky, 4th rate; W. 1/2 gravelly loam, 3rd rate.

Timber, paloverde, ironwood, mesquite, and catclaw.

Undergrowth, same, with greasewood, cacti and ocotillo.

The continued satisfactory adjustment of the Buff transit  
 No. 8487, used in the execution of the resurvey describ-  
 ed in the foregoing notes, is indicated from tests of  
 same described in Book "C" of this group (T.2 S.,  
 R.4 W.)

Survey of the West Bdy. of T. 2 S., R. 3 W.

Chains

The following notes describe the survey of the west bdy. of T. 2 S., R. 3 W., identical in position with the east bdy. of T. 2 S., R. 4 W., establishing corners at regular intervals for areas to the east only, counting from closing cor. of Ts. 2 & 3 S., R. 3 W., which is 2.69 chs. N. from the corner of Ts. 2 & 3 S., R. 4 W. Topography omitted because of description in book "C" of this group.

From closing cor. of Ts. 2 & 3 S., R. 3 W., described in book "A" of this group.

37.31 North, on true line, on W. bdy. of sec. 31. Intersect the 1/4 sec. cor. of sec. 36, T. 2 S., R. 4 W., described in book "C" of this group.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the 1/4 sec. cor. of sec. 31 only, with brass cap mkd.

1/4 S31

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. distant.

77.31 Intersect the cor. of secs. 25 and 36, T. 2 S., R. 4 W., described in book "C" of this group.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 30 and 31, only, with brass cap mkd.

T2S T2S  
R4W R3W  
S25 S30  
S31

1931

No bearing trees available; raise a mound of stone 3 ft. base, 1 1/2 ft. high E. of cor. 3 ft. dist.

37.31 North, on true line, on W. bdy. of sec. 30. Intersect the 1/4 sec. cor. of sec. 25, T. 2 S., R. 4 W., described in book "C" of this group.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the 1/4 sec. cor. of sec. 30, with brass cap mkd.

1/4 S30

1931

No bearing trees available. Dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. dist.

77.31 Intersect the cor. of secs. 24 and 25, T. 2 S., R. 4 W., described in book "C" of this group.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 19 and 30, only, with brass cap mkd.

T2S T2S  
R4W R3W  
S24 S19  
S30

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. NE. & SE. of cor. 3 ft. dist.

Survey of the West Bdy. of T. 2 S., R. 3 W.

Chains

37.31 North, on true line, on W. bdy. of sec. 19.  
Intersect the 1/4 sec. cor. of sec. 24, T. 2 S., R. 4 W., described in book "C" of this group.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the 1/4 sec. cor. of sec. 19, with brass cap mkd.

1/4 S19

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. dist.

77.31 Intersect the cor. of secs. 13 & 24, T. 2 S., R. 4 W., described in book "C" of this group.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 18 & 19, with brass cap mkd.

T2S T2S  
R4W R3W  
S13 S18

S19

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. NE. & SE. of cor. 3 ft. distant.

37.31 North, on true line, on W. bdy. of sec. 18.  
Intersect the 1/4 sec. cor. of sec. 13, T. 2 S., R. 3 W., described in book "C".

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the 1/4 sec. cor. of sec. 18 only, with brass cap mkd.

1/4 S18

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. dist.

77.31 Intersect the cor. of secs. 12 & 13, T. 2 S., R. 4 W., described in book "C" of this group.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 7 & 18, only, with brass cap mkd.

T2S T2S  
R4W R3W  
S12 S7

S18

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. NE. & SE. of cor. 3 ft. dist.

North, on true line, on W. bdy. of sec. 7.

Survey of the West Bdy. of T. 2 S., R. 3 W.

Chains  
 North, on true line, on W. bdy. of sec. 7.  
 37.31 Intersect the  $\frac{1}{4}$  sec. cor. of sec. 12, T.2 S., R.4 W., described in book "C" of this group.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of sec. 7 only, with brass cap mkd.  
 $\frac{1}{4}$  S7  
 1931  
 No bearing trees available; dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. dist.  
 77.31 Intersect the cor. of secs. 12 & 13, T.2 S., R. 4 W., described in book "C" of this group.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 6 and 7, only, with brass cap mkd.  

T2S	T2S
R4W	R3W
S1	S6
	S7

 1931  
 No bearing trees available, raise a mound of stone 4 ft. base, 2 ft. high E. of cor. 3 ft. distant.

---

North, on true line, on W. bdy. of sec. 6.  
 37.31 Intersect the  $\frac{1}{4}$  sec. cor. of sec. 1, T.2 S., R.4 W., described in book "C" of this group.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 15 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post for the  $\frac{1}{4}$  sec. cor. of sec. 6, with brass cap mkd.  
 $\frac{1}{4}$  S6  
 1931  
 79.63 Intersect the closing cor. of T. 2 S., R. 3 and 4 W., described in book "C" of this group.

---

Survey of the Subdivision Lines of T.2 S., R.3 W.

The following notes describe the survey of the subdivision lines of T.2 S., R.3 W.


From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., described in book "A" of this group.  
N.0°01'W., on true line, bet. secs. 35 & 36.

Over rolling desert land, thru scattering timber & undergrowth.

4.20 Wash, 20 lks. wide, course NE.


11.80 Same wash, course NW.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 35 & 36, with brass cap mkd.



No bearing trees available.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 25, 26, 35 & 36, with brass cap mkd.



No bearing trees available, dig pits 18 x 18 x 12 ins. NW, NE, SE, and SW of cor. 3 ft. dist.

Land, rolling.  
Soil, sandy, stony 2nd. & 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

East, on random line, bet. secs. 25 & 36.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Intersect the cor. of secs. 25, 30, 31 and 36, on E. bdy. of Tp., established by W.H.Thorn, U.S.S., 1916, which is an iron post 2 ins. in diam., firmly set and projecting 12 ins. above ground, with brass cap properly mkd. and witnessed by pits NW, NE, SE and SW of cor.

Thence,

West, on true line, bet. secs. 25 and 36.


Over rolling desert land, thru scattering timber & undergrowth.

14.00 Wash, 10 lks. wide, course NE.

35.00 Wash, 10 lks. wide, course N.

37.30 Wash, 20 lks. wide, course N.

39.99 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 25 & 36, with brass cap mkd.



1931

No bearing trees available, dig pits 18 x 18 x 12 ins. E. and W. of cor. 3 ft. dist.

Survey of the Subdivision Lines of T.2 S., R.3 W.


Chains

56.00 Wash, 50 lks. wide, course N.  
76.10 Wash; 10 lks. wide, course NE.  
79.98 The cor. of secs. 25, 26, 35 & 36.

Land, rolling.  
Soil, sandy loam, 3rd. rate.  
Timber, paloverde & ironwood.  
Undergrowth, greasewood and cacti.


N.0°01'W., on true line, bet. secs. 25 & 26.  
Over rolling desert land, thru scattering timber & undergrowth.

32.50 Wash, 10 lks. wide, course NW.  
37.00 Same wash, course NE.  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 25 & 26, with brass cap mkd.



1931  
No bearing trees available.

41.60 Wash, 10 lks. wide, course NW.  
46.70 Road, brs. E-W.  
48.80 Same wash, course NE. Thence along W. edge of same.  
53.00 Wash turns to NE.  
72.60 Wash, 10 lks. wide, course NE.  
80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 23, 24, 25 & 26, with brass cap mkd.



1931  
No bearing trees available; dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. dist.

Land, rolling.  
Soil, sandy loam, 2nd. and 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00 East, on a random line, bet. secs. 24 and 25.  
Set temp.  $\frac{1}{4}$  sec. cor.  
79.94 Fall 2 lks. S. of the cor. of secs. 19, 24, 25 & 30, which is an iron post 2 ins. in diam., firmly set & projecting 12 ins. above ground, with brass cap properly mkd. and witnessed by four pits NW, NE, SE and SW of cor. 3 ft. distant.

Thence,  
S.89°59'W., on true line, bet. secs. 24 & 25.  
Over rolling desert land, thru scattering timber & undergrowth.

0.35 Wash, 10 lks. wide, course N.  
18.60 Wash, 20 lks. wide, course N.  
23.50 Wash, 20 lks. wide, course N.

Survey of the Subdivision Lines of T.2 S. R.3 W.

Chains

38.20  
39.97

Wash, 20 lks. wide, course N.  
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the 1/4 sec. cor. of secs. 24 & 25, with brass cap mkd.

1/4 S 24  
1/4 S 25

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor.

64.95  
71.25  
79.94

Wash; 10 lks. wide, course N.  
Wash, 10 lks. wide, course NW.  
The cor. of secs. 23, 24, 25 & 26.

Land, rolling.  
Soil; sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00

N.0°01'W., on true line, bet. secs. 23 & 24.  
Over rolling desert land, thru scattering timber & undergrowth.

Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the 1/4 sec. cor. of secs. 23 & 24, with brass cap mkd.

1/4  
S23 | S24

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. distant.

48.50  
80.00

Wash, 10 lks. wide, course NE.  
Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 13, 14, 23 & 24, with brass cap mkd.

T2S R3W  
S14 | S13  
S23 | S24

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00  
79.96

N.89°59'E., on random line, bet. secs. 13 and 24.  
Set temp. 1/4 sec. cor.

Fall 17 lks. N. of the cor. of secs. 13, 18, 19 and 24 on E. bdy. of Tp., which is an iron post 3 ins. in diam., firmly set and projecting 13 ins. above ground, with brass cap properly mkd. and witnessed by pits NW, NE, SE and SW of cor.


Thence,  
N.89°54'W., on true line, bet. secs. 13 and 24.  
Over rolling land, thru scattering timber & undergrowth.



Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

13.55 Wash, 50 lks. wide, course N.  
39.98 Set an iron post 3 ft. long, 1 in. in diam., 25 ins. in the ground for the 1/4 sec. cor. of secs. 13 & 24, with brass cap mkd.




1931

No bearing trees available; dig pits 18 x 18 x 12 ins. E-W. of cor. 3 ft. distant.

56.95 Wash, 10 lks. wide, course N.  
69.55 Wash, 20 lks. wide, course NE.  
76.95 Wash, 10 lks. wide, course N.  
79.96 The cor. of secs. 13, 14, 23 and 24.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.


40.00 N.0°01'W., on true line, bet. secs. 13 and 14. Over rolling land, thru scattering timber & undergrowth. Set an iron post 3 ft. long, 1 in. in diam., 25 ins. in the ground for the 1/4 sec. cor. of secs. 13 and 14, with brass cap mkd.



1931

No bearing trees available; dig pits 18 x 18 x 12 ins. N. & S. of cor. 3 ft. distant.

48.80 Wash, 20 lks. wide, course N., from SE.  
64.00 Leave wash, turns to NE.  
66.70 Wash, 20 lks. wide, course NE.  
80.00 Set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, deposit a stone mkd. with a (X) at base of post, raise a mound of stone about post, for the cor. of secs. 11, 12, 13 and 14, with brass cap mkd.



1931

No bearing trees available.


Land, rolling.  
Soil, sandy loam 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00 S.89°54'E., on random line, bet. secs. 12 & 13. Set temp. 1/4 sec. cor.  
79.94 Fall 14 lks. N. of the cor. of secs. 7, 12, 13 and 18, on E. bdy. of Tp., which is an iron post 3 ins. in diam., firmly set & projecting 12 ins. above ground with brass cap properly mkd. & witnessed by pits, NW NE, SE and SW of cor.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

Thence,  
 N. 89° 48' W. on true line, bet. secs. 12 & 13.  
 Over rolling land, thru scattering timber & undergrowth.  
 10.00 Center of wash, 100 lks. wide, course N.  
 35.75 Wash, 10 lks. wide, course N.  
 39.97 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for the  $\frac{1}{4}$  sec. cor. of secs. 12 & 13, with  
 brass cap mkd.




1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
 E. -W. of cor. 3 ft. distant.

56.75 Wash, 50 lks. wide, course NE.  
 71.85 Center of wash, 100 lks. wide, course NW.  
 79.94 The cor. of secs. 11, 12, 13 and 14.

Land, rolling.  
 Soil, sandy & stony 3rd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.


N. 0° 01' W., on true line, bet. secs. 11 and 12.  
 Over rolling land, thru scattering timber & undergrowth.  
 5.00 Wash, 10 lks. wide, course NE.  
 22.50 Wash, 10 lks. wide, course NE.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in  
 the ground to bedrock, deposit a stone mkd. with a  
 cross (X) at base of post, raise a mound of stone  
 about post, for the  $\frac{1}{4}$  sec. cor. of secs. 11 & 12,  
 with brass cap mkd.



1931

No bearing trees available.

50.60 Cleared road, brs. NE-SW.  
 63.90 Wash, 20 lks. wide, course E.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in  
 the ground for the cor. of secs. 1, 2, 11 and 12,  
 with brass cap mkd.



1931


from which,  
 a paloverde, 12 ins. in diam., brs. N. 21° W., 597 lks.  
 dist., mkd. T2S R3W S2 BT  
 a paloverde, 10 ins. in diam., brs. N. 17° E., 292 lks.  
 dist., mkd. T2S R3W S1 BT  
 No other bearing trees available, dig pits 18 x 18 x  
 12 ins. NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling.  
 Soil, sandy loam, 3rd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

40.00 S. 89°48'E., on random line, bet. secs. 1 & 12.  
 Set temp. 1/4 sec. cor.  
 79.94 Fall 9 lks. S. of the cor. of secs. 1, 6, 7 & 12, on E. bdy. of Tp., which is an iron post 3 ins. in diam., firmly set & projecting 12 ins. above ground and with brass cap properly mkd. & witnessed by four pits, NW, NE, SE and SW of cor.  
 Thence,  
 39.97 N. 89°52'W., on true line, bet. secs. 1 and 12.  
 Over rolling land, thru scattering timber & undergrowth. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the 1/4 sec. cor. of secs. 1 & 12, with brass cap mkd.




1931  
 No bearing trees available; dig pits 18 x 18 x 12 ins. E-W of cor. 3 ft. distant.

51.00 Wash, 20 lks. wide, course NE.  
 51.50 Cleared road, brs. NE-SW.  
 62.75 Same wash, course SE.  
 68.65 Same wash, course NE.  
 74.75 Same wash, 20 lks. wide, course SE.  
 79.94 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

N. 0°01'W., on true line, bet. secs. 1 and 2.  
 Over rolling land, thru scattering timber & undergrowth.  
 3.90 Wash, 20 lks. wide, course SE.  
 34.40 Wash, 5 lks. wide, course E.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the 1/4 sec. cor. of secs. 1 and 2, with brass cap mkd.




1931 from which,  
 a paloverde, 6 ins. in diam., brs. S. 11°W., 24 lks. dist., mkd. 1/4 S2 BT

Leave rolling enter mountainous land, brs. E-W.  
 Asc. 52 ft. over S. slope.  
 45.00 Low spur, brs. W. Desc. 34 ft. over N. slope.  
 52.40 Wash, 10 lks. wide, course SW.  
 58.00 Low spur, brs. E. Desc. 29 ft. over N. slope.  
 62.40 Wash, 10 lks. wide, course SE.  
 Asc. 21 ft. over gradual S. slope.  
 79.33 Intersect the S. bdy. of sec. 35, T. 1 S., R. 3 W., at 102 lks. S. 89°56'E. of the reestablished 1/4 sec. cor. of sec. 35, T. 1 S., R. 3 W., hereinbefore described.  
 At point of intersection set an iron post 3 ft. long, 2 ins. in diam., on bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the closing cor. of secs. 1 and 2, with brass cap mkd.

Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains



No bearing trees available.

Land, rolling and mountainous.  
Soil, rocky 3rd. & 4th. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

From the cor. of secs. 2, 3, 34 & 35, on S. bdy. of Tp.,  
described in book "A" of this group.

N.0°01'W., on true line, bet. secs. 34 & 35.

Over rolling land, thru scattering timber & undergrowth.

2.00 Wash, 10 lks. wide, course NE.

24.00 Lv. rolling enter mountainous land, brs. E-W.

Asc. 98 ft. over S. slope.

34.30 Rocky spur, brs. W. Desc. 41 ft. over N. slope.

35.50 Head of wash, course NW. Asc. gradual SW slope.

39.50 Rocky spur, brs. NW. Desc. gradual NE slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., on bedrock,  
on cross (X) cut in same, supported by a mound of  
stone, for the ~~base~~ cor. of secs. 34 & 35, with  
brass cap marked

1/4



1931

No bearing trees available.


Desc. 92 ft. over NE slope.

44.30 Wash, 10 lks. wide, course NW. Asc. gradual SW slope.

66.00 Wash, 5 lks. wide, course NE.

Lv. mountainous land, enter rolling land, brs. NE-SW

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins.  
in the ground for the cor. of secs. 26, 27, 34 & 35,  
with brass cap mkd.



1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling & mountainous.  
Soil, stony 3rd. & 4th. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

Thence,  
East, on random line, bet. secs. 26 & 35.

40.00 Set temp. 1/2 sec. cor.  
79.96 Fall 5 lks. N. of the cor. of secs. 25, 26, 35 & 36.


Thence,  
N.89°58'W., on true line, bet. secs. 26 & 35.

Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

12.05  
39.98

Over rolling desert land, thru scattering timber & undergrowth.  
Center of wash, 100 lks. wide, course NE.  
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, with brass cap mkd.




50.00  
65.00  
70.00  
79.96

1931 from which,  
an ironwood, 6 ins. in diam., brs. S.79°W., 220 lks. dist., mkd.  $\frac{1}{4}$  S35 BT  
No other bearing tree available; raise a mound of stone 3 ft. base,  $1\frac{1}{2}$  ft. high N. of cor. 3 ft. dist.  
Low divide, brs. N-S.  
Center of wash, 100 lks. wide, course N.  
Low ridge, brs. N-S.  
The cor. of secs. 26, 27, 34 & 35.

Land, rolling.  
Soil, rocky 3rd. rate.  
Timber, paloverde & ironwood.  
Undergrowth, greasewood and cacti.

36.90  
40.00


N.0°01'W., on true line, bet. secs. 26 and 27.  
Over rolling land, thru scattering timber & undergrowth.  
Road, brs. E-W.  
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 26 & 27, with brass cap mkd.



68.00  
80.00

1931 from which,  
a paloverde, 14 ins. in diam., brs. N.68 $\frac{1}{2}$ °W., 131 lks. dist., mkd.  $\frac{1}{4}$  S27 BT  
a paloverde, 14 ins. in diam., brs. East, 253 lks. dist., mkd.  $\frac{1}{4}$  S26 BT

Wash, 20 lks. wide, course NW.  
Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 22, 23, 26 & 27, with brass cap mkd.



1931  
No bearing trees available. Dig pits, 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. dist.  
Land, rolling.  
Soil, rocky and sandy loam, 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.


40.00  
79.86

S.89°58'E., on random line, bet. secs. 23 & 26.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 16 lks. S. of the cor. of secs. 23, 24, 25 & 26.  
Thence,  
S.89°55'W., on true line, bet. secs. 23 & 26.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

2.15 Wash, 10 lks. wide, course N.  
 24.60 Wash, 5 lks. wide, course N.  
 39.93 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 23 & 26, with brass cap mkd.




1931

No bearing trees available; dig pits 18 x 18 x 12 ins. E-W of cor. 3 ft. distant.

54.45 Wash, 5 lks. wide, course N.  
 76.15 Wash, 50 lks. wide, course N.  
 79.86 The cor. of secs. 22, 23, 26 & 27.

Land, rolling.  
 Soil, sandy loam, 3rd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.


N.0°01'W., on true line, bet. secs. 22 & 23.  
 Over rolling land, thru scattering timber & undergrowth.  
 5.30 Wash, 10 lks. wide, course NW.  
 6.70 Wash, 10 lks. wide, course NW.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 22 & 23, with brass cap mkd.



1931

No bearing trees available; dig pits 18 x 18 x 12 ins. N-S of cor. 3 ft. distant.

62.30 Wash, 10 lks. wide, course NW.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 14, 15, 22 & 23, with brass cap mkd.



1931


No bearing trees available; dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. dist.

Land, rolling.  
 Soil, sandy loam, 2nd. and 3rd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

40.00 N.89°55'E., on random line, bet. secs. 14 & 23.  
 79.90 Set temp.  $\frac{1}{4}$  sec. cor.  
 Fall 2 lks. N. of the cor. of secs. 13, 14, 23 & 24.  
 Thence,  
 S.87°50'W., on true line, bet. secs. 14 & 23.


Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains S.89°56'W., on true line, bet. secs. 14 and 23.  
 Over rolling land, thru scattering timber & undergrowth.  
 12.80 Wash, 10 lks. wide, course N.  
 31.00 Wash, 10 lks. wide, course N.  
 39.95 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for the  $\frac{1}{4}$  sec. cor. of secs. 14 & 23, with  
 brass cap mkd.




1931  
 No bearing trees available; dig pits 18 x 18 x 12 ins.  
 E-W of cor. 3 ft. distant.  
 55.00 Wash, 10 lks. wide, course N.  
 73.40 Wash, 10 lks. wide, course N.  
 79.90 The cor. of secs. 14, 15, 22 & 23.  
 Land, rolling.  
 Soil, sandy loam 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

N.0°01'W., on true line, bet. secs. 14 & 15.  
 Over rolling land, thru scattering timber & undergrowth.  
 21.10 Wash, 5 lks. wide, course NW.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for the  $\frac{1}{4}$  sec. cor. of secs. 14 & 15, with  
 brass cap mkd.



1931 from which,  
 a paloverde, 10 ins. in diam., brs. N.30°W., 242 lks.  
 dist., mkd.  $\frac{1}{4}$  S15 BT  
 a paloverde 6 ins. in diam., brs. S.50°E., 27 lks.  
 dist., mkd.  $\frac{1}{4}$  S14 BT  
 42.80 Wash, 10 lks. wide, course NW.  
 50.20 Cleared road, brs. NE-SW.  
 73.70 Wash, 10 lks. wide, course SW.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in  
 the ground to bedrock, deposit a stone mkd. with a  
 cross (X) at base of post, raise a mound of stone  
 about post, for the cor. of secs. 10, 11, 14 & 15,  
 with brass cap mkd.




1931 from which,  
 a paloverde, 8 ins. in diam., brs. N.27°E., 237 lks.  
 dist., mkd. T2S R3W S11 BT  
 a paloverde, 10 ins. in diam., brs. S.75°E., 145 lks.  
 dist., mkd. T2S R3W S14 BT  
 No other bearing trees available.  
 Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and cacti.  
 Undergrowth, greasewood and cacti.

Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

40.00 N.89°56'E., on a random line, bet. secs. 11 and 14.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.98 Fall 16 lks. N. of the cor. of secs. 11, 12, 13 and 14.  
 Thence,  
 N.89°57'W., on true line, bet. secs. 11 and 14.  
 Over rolling desert land, thru scattering timber & undergrowth.  
 5.00 Wash, 5 lks. wide, course NE.  
 39.99 Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14, with brass cap mkd.




1931

No bearing trees available.

50.00 Low divide, brs. N-S.  
 50.20 Cleared road, brs. NE-SW.  
 67.60 Wash, 10 lks. wide, course SW.  
 78.30 Wash, 10 lks. wide, course SW.  
 79.98 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.


N.0°01'W., on true line, bet. secs. 10 and 11.  
 Over rolling desert land, thru scattering timber & undergrowth.  
 37.00 Low divide, brs. NW-SE.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 10 & 11, with brass cap mkd.



1931

from which,  
 a paloverde, 8 ins. in diam., brs. S.37°E., 165 lks. dist., mkd.  $\frac{1}{4}$  S11 BT  
 a paloverde, 6 ins. in diam., brs. S.37°W., 130 lks. dist., mkd.  $\frac{1}{4}$  S10 BT

79.80 Wash, 10 lks. wide, course SE.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the cor. of secs. 2, 3, 10 and 11, with brass cap mkd.



1931

No bearing trees available.




Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

Land, rolling.  
Soil, rocky and sandy 2nd. and 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00 S.89°57'E., on a random line, bet. secs. 2 & 11.  
Set temp. 1/4 sec. cor.  
80.00 Fall 7 lks. S. of the cor. of secs. 1, 2, 11 & 12.  
Thence,  
West, on true line, bet. secs. 2 and 11.  
Over rolling land, thru scattering timber & undergrowth.  
38.70 Wash, 50 lks. wide, course SE.  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
the ground for the 1/4 sec. cor. of secs. 2 and 11,  
with brass cap mkd.




1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
E-W of cor. 3 ft. distant.

65.00 Asc. 58 ft. over E. slope.  
71.70 Low spur, brs. S. Desc. 29 ft. over W. slope to  
80.00 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.  
Soil, sandy and rocky 3rd. and 4th. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.


3.20 N.0°01'W., on true line, bet. secs. 2 and 3.  
12.70 Over rolling land, thru scattering timber & undergrowth.  
Asc. gradual S. slope.  
18.00 Low spur, brs. W. Desc. gradual N. slope.  
40.00 Wash, at head, course SW.  
Spur, brs. NW. Asc. gradual S. slope.  
Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in  
the ground to bedrock, deposit a stone mkd. with a  
cross (X) at base of post, raise a mound of stone  
about post, for the 1/4 sec. cor. of secs. 2 and 3, with  
brass cap mkd.



1931

No bearing trees available.  
Continue slight ascent of S. slope.

40.50 Low divide, brs. NE-SW.  
42.50 Road, brs. NE-SW.  
79.26 Intersect the S. bdy. of sec. 34, T.1 S., R.3 W., at  
1.26 chs. S.89°56'E. from the reestablished 1/4 sec. cor.  
of sec. 34, hereinbefore described.  
At point of intersection set an iron post 3 ft. long,  
2 ins. in diam., 24 ins. in the ground for the closing  
cor. of secs. 2 & 3, with brass cap mkd.



CC

1931

from which,

## Survey of the Subdivision Lines of T.2 S., R.3 W.

## Chains

a paloverde, 5 ins. in diam., brs. S.63°E., 223 lks. dist., mkd. T2S R3W S2 CCBT  
 a paloverde, 4 ins. in diam., brs. S.60°W., 126 lks. dist., mkd. BT only.

Land, rolling.

Soil, stony 4th. rate.

Timber, paloverde and ironwood.

Undergrowth, greasewood and cacti.

From cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Twp., described in Book "A" of this group,

N.0°02'W., on true line, bet. secs. 33 & 34.

Over rolling land, thru scattering timber & undergrowth. Desc. 15 ft. over NW slope.

1.80 Head of wash, course NE. 2 chs. SW to saddle, brs. NE-SW. Enter mountainous land, brs. N-S. Asc. 140 ft. over SE slope.

13.00 Spur, brs. E. Desc. 142 ft. over NE slope.

32.90 Wash, 10 lks. wide, course NE. Lv. mtns. over rolling land, brs. NW-SE.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 33 & 34, with brass cap mkd.

$\frac{1}{4}$   
 S33 | S34

1931

No bearing trees available;

66.50 Road, brs. NW-SE.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for the cor. of secs. 27, 28, 33 & 34, with brass cap mkd.

T2S R3W  
 S28 | S27  
 S33 | S34

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling and mountainous.

Soil, rocky 4th. rate on S $\frac{1}{2}$ ; N $\frac{1}{2}$  sandy loam, 3rd. rate.

Timber, paloverde and ironwood.

Undergrowth, greasewood and cacti.

40.00 East, on a random line, bet. secs. 27 and 34.

Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Fall 9 lks. S. of the cor. of secs. 26, 27, 34 & 35.

Thence,

S.89°56'W., on true line, bet. secs. 27 & 34.

Over rolling land, thru scattering timber & undergrowth.

11.00 Wash, 10 lks. wide, course NE.

27.50 Wash, 15 lks. wide, course NW.

39.99 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 27 & 34, with brass cap mkd.

Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

$\frac{1}{4}$  S 27  
S 34

1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
E-W of cor. 3 ft. distant.

43.40 Wash, 10 lks. wide, course NW.  
55.70 Wash, 10 lks. wide, course NW.  
79.00 Road, brs. NW.-SE.  
79.98 The cor. of secs. 27, 28, 33 & 34.  
Land, rolling.  
Soil, rocky and sandy loam, 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

1.60 N.0°02'W., on true line, bet. secs. 27 and 28.  
22.00 Over rolling land, thru scattering timber & undergrowth.  
39.30 Road, brs. NW.-SE thru scattering timber & undergrowth.  
40.00 Road, brs. E.-W.  
Wash, 10 lks. wide, course NW.  
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
the ground for the  $\frac{1}{4}$  sec. cor. of secs. 27 & 28, with  
brass cap mkd.

$\frac{1}{4}$   
S28 | S27

1931

from which,

an ironwood, 16 ins. in diam., brs. N.78°W., 16 lks.  
dist., mkd.  $\frac{1}{4}$  S28 BT  
an ironwood, 20 ins. in diam., brs. S.40°E., 288 lks.  
dist., mkd.  $\frac{1}{4}$  S27 BT

65.00 Wash, 5 lks. wide, course NW.  
68.90 Wash, 10 lks. wide, course NW.  
80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in  
the ground for the cor. of secs. 21, 22, 27 and 28,  
with brass cap mkd.

T2S | R3W  
S21 | S22  
S28 | S27

1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
NW, NE, SE and SW of cor. 3 ft. distant.


Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00 N.89°56'E., on a random line, bet. secs. 22 & 27.  
79.92 Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect the cor. of secs. 22, 23, 26 & 27.  
Thence,  
S.89°56'W., on true line, bet. secs. 22 & 27.  
Over rolling desert land, thru scattering timber & under-  
growth.  
5.50 Wash, 10 lks. wide, course NW.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

19.80 Wash, 10 lks. wide, course NW.  
 29.10 Wash, 10 lks. wide, course NW.  
 35.80 Wash, 10 lks. wide, course NW.  
 39.96 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 22 & 27, with brass cap mkd.




1931 from which,  
 an ironwood, 14 ins. in diam., brs. N.67 $\frac{1}{2}$ °E., 412 lks. dist., mkd.  $\frac{1}{4}$  S22 BT  
 a paloverde, 6 ins. in diam., brs. S.85 $\frac{1}{2}$ °W., 121 lks. dist., mkd.  $\frac{1}{4}$  S27 BT

45.30 Wash, 10 lks. wide, course NW.  
 70.40 Wash, 10 lks. wide, course N.  
 79.92 The cor. of secs. 21, 22, 27 & 28.


Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

40.00 N.0°02'W., on true line, bet. secs. 21 & 22. Over rolling land, thru scattering timber & undergrowth. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 21 & 22, with brass cap mkd.



1931  
 No bearing trees available; dig pits 18 x 18 x 12 ins. N. and S. of cor. 3 ft. distant.

44.40 Wash, 10 lks. wide, course NW.  
 65.10 Wash, 10 lks. wide, course NW.  
 66.50 Cleared road, brs. NE-SW.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for the cor. of secs. 15, 16, 21 & 22, with brass cap mkd.



1931 from which,  
 a mesquite, 8 ins. in diam., brs. N.27°E., 300 lks. dist., mkd. T2S R3W S15 BT  
 a mesquite, 20 ins. in diam., brs. S.80°E., 279 lks. dist., mkd. T2S R3W S22 BT  
 No other bearing trees available; dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde, ironwood and mesquite.  
 Undergrowth, greasewood and cacti.

Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

N. 89°56'E., on a random line, bet. secs. 15 and 22.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.92 Fall 3 lks. S. of the cor. of secs. 14, 15, 22 & 23.  
 Thence,  
 S. 89°55'W., on true line, bet. secs. 15 & 22.  
 Over rolling desert land thru scattering timber & undergrowth.

6.40 Wash, 20 lks. wide, course N.  
 30.40 Wash, 50 lks. wide, course N.  
 39.96 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 15 & 22, with brass cap mkd.

$\frac{1}{4}$  S 15  
S 22

1931

No bearing trees available; dig pits 18 x 18 x 12 ins. E-W of cor. 3 ft. distant.

61.35 Cleared road, brs. NE-SW.  
 62.80 Center of wash, 100 lks. wide, course NW.  
 77.30 Wash, 50 lks. wide, course NW.  
 79.92 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

N. 0°02'W., on true line, bet. secs. 15 & 16.  
 Over rolling land, thru scattering timber & undergrowth.

5.50 Wash, 20 lks. wide, course NW.  
 21.80 Center of wash, 200 lks. wide, course NW.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 15 & 16, with brass cap mkd.

$\frac{1}{4}$   
S16 | S15

1931

45.00 Wash, 50 lks. wide, course W.  
 72.10 Road, brs. NE-SW.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

T2S R3W  
S9 | S10  
S16 | S15

1931


No bearing trees available; raise a mound of stone 3 ft. base, 2 ft. high W. of cor. 3 ft. distant.

Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

40.00 N.89°55'E., on a random line, bet. secs. 10 & 15.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.88 Fall 5 lks. N. of the cor. of secs. 10, 11, 14 & 15.  
 Thence,  
 S.89°57'W., on true line, bet. secs. 10 and 15.  
 Over rolling land, thru scattering timber & undergrowth.  
 1.90 Wash, 5 lks. wide, course S.  
 12.10 Wash, 5 lks. wide, course SW.  
 19.00 Wash, 5 lks. wide, course SW.  
 36.80 Wash, 5 lks. wide, course SW.  
 39.94 Set an iron post 3 ft. long, 1 in. in diam., 18 ins. in  
 the ground to bedrock, deposit a stone mkd. with a  
 cross (X) at base of post, raise a mound of stone  
 about post, for the  $\frac{1}{4}$  sec. cor. of secs. 10 & 15  
 with brass cap mkd.




1931

No bearing trees available.

72.10 Road, brs. NE and SW.  
 79.88 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.  
 Soil, sandy loam 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

6.80 N.0°02'W., on true line, bet. secs. 9 and 10.  
 17.80 Over rolling land, thru scattering timber & undergrowth.  
 Wash, 10 lks. wide, course SW.  
 40.00 Wash, 20 lks. wide, course NW.  
 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10;  
 with brass cap mkd.




1931

from which,

a paloverde, 9 ins. in diam., brs. S.12 $\frac{1}{2}$ °E., 184 lks.  
 dist., mkd.  $\frac{1}{4}$  S10 BT  
 No other bearing tree available; dig pits 18 x 18 x  
 12 ins. N.-S. of post 3 ft. dist.

50.15 Wash, 10 lks. wide, course W.  
 54.50 Wash, 20 lks. wide, course SW.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 22 ins. in  
 the ground to bedrock, deposit a stone mkd. with a  
 cross (X) at base of post, raise a mound of stone  
 about post, for the cor. of secs. 3, 4, 9 & 10, with  
 brass cap mkd.



1931

from which,

a paloverde, 4 ins. in diam., brs. N.56°W., 72 lks.  
 dist., mkd. T2S R3W S4 BT  
 a paloverde, 10 ins. in diam., brs. N.67 $\frac{1}{2}$ °E., 121 lks.  
 dist., mkd. T2S R3W S3 BT


Survey of the Subdivision Lines of T. 2 S., R. 3 W.

No other bearing trees available.

Land, rolling.  
Soil, sandy 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00 N.89°57'E., on a random line, bet. secs. 3 & 10.  
Set temp. 1/4 sec. cor.  
80.00 Fall 5 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence,  
S.89°55'W., on true line, bet. secs. 3 and 10.  
Over rolling land, thru scattering timber & undergrowth.  
Desc. 31 ft. over West slope.  
5.80 Wash, 5 lks. wide, course SE.  
10.30 Road, brs. NE-SW.  
15.70 Wash, 10 lks. wide, course S.  
28.60 Wash, 20 lks. wide, course SE.  
39.50 Top of rocky butte, 20 lks. wide, brs. N-S., about 60 ft.  
above surrounding land.  
Desc. 18 ft. over West slope.  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 6 ins. in  
the ground to bedrock, deposit a stone mkd. with a  
cross (X) at base of post, raise a mound of stone  
about post; for the 1/4 sec. cor. of secs. 3 and 10,  
with brass cap mkd.



1931

No bearing trees available.


Desc. 46 ft. over W. slope.  
42.00 Foot of hill, brs. N-S.  
79.35 Center of wash, 100 lks. wide, course SW.  
80.00 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.  
Soil, rocky 4th. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains


N.0°02'W., on true line, bet. secs. 3 and 4.  
 Over rolling land, thru scattering timber & undergrowth.  
 0.55 Wash, 10 lks. wide, course SW.  
 6.70 Wash, 10 lks. wide, course SW.  
 31.30 Center of wash, 50 lks. wide, course SW.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 16 ins. in  
 the ground to bedrock, deposit a stone mkd. with a  
 cross (X) at base of post, for the  $\frac{1}{4}$  sec. cor. of  
 secs. 3 & 4, with brass cap mkd.



No bearing trees available.

43.70 Wash, 10 lks. wide, course SW.  
 Leave rolling enter mountainous land, brs. E-W.  
 Asc. 35 ft. over S. slope.  
 51.80 Same wash, course SE.  
 54.50 Same wash, course SW.  
 67.80 Spur, brs. S.  
 Desc. 46 ft. over N. slope.  
 75.10 Center of wash, 50 lks. wide, course SW.  
 78.80 Road, brs. NE-SW.  
 79.21 Intersect the S. bdy. of sec. 33, T.1 S., R.3 W., at  
 1.52 chs. S.89°56' E. from the reestablished  $\frac{1}{4}$  sec.  
 cor. of sec. 33, T.1 S., R. 3 W., hereinbefore des-  
 cribed.

At point of intersection set an iron post 3 ft. long,  
 2 ins. in diam., 22 ins. in the ground to bedrock,  
 deposit a stone mkd. with a cross (X) at base of  
 post, raise a mound of stone about post, for the  
 closing cor. of secs. 3 and 4, with brass capmkd.



No bearing trees available.

Land, rolling and mountainous.

Soil, rocky 4th. rate.


Timber, paloverde and ironwood.

Undergrowth, greasewood and cacti.



Survey of the Subdivision Lines of T. 2 S., R. 3 W.


Chains From cor. of secs. 4, 5, 32, and 33, on S. bdy. of the Tp. described in Book "A" of this group  
 N.0°02'W., on true line, bet. secs. 32 & 33.  
 Over rolling land, thru scattering timber & undergrowth.  
 8.20 Round butte, 20 ft. high on line.  
 9.70 Wash, 5 lks. wide, course SW.  
 21.30 Wash, 30 lks. wide, course W.  
 31.00 Wash, 20 lks. wide, course SW.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, deposit a stone mkd. with a (Cross) X at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 32 & 33, with brass cap mkd.



1933

No bearing trees available.

46.80 Wash, 10 lks. wide, course SW.  
 Leave rolling, enter mountainous land, brs. E-W.  
 Asc. 34 ft. over S. slope.  
 57.00 Ridge, brs. NE-SW. A pass brs. west about 3 chs. dist.  
 Desc. 88 ft. over NW slope.  
 72.80 Head of wash, course NW.  
 Asc. 123 ft. over S. slope.  
 79.00 Spur, brs. NW. Desc. 27 ft. over NE slope to  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 16 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the cor. of secs. 28, 29, 32 & 33, with brass cap mkd.



1931

No bearing trees available.

Land, rolling and mountainous.

Soil, rocky 4th. rate.

Timber, paloverde and ironwood.


Undergrowth, greasewood and cacti.

40.00 East, on random line, bet. secs. 28 and 33.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.14 Fall 14 lks. N. of the cor. of secs. 27, 28, 33 & 34.  
 Thence,  
 N.89°54'W., on true line, bet. secs. 28 and 33.  
 Over rolling land, thru scattering timber & undergrowth.  
 7.00 Wash, 10 lks. wide, course NW.  
 27.00 Wash, 10 lks. wide, course N.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

31.00 Wash, 20 lks. wide, course N.  
 40.07 Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 33, with brass cap mkd.



1931


No bearing trees available.  
 Lv. rolling, enter mountainous land, brs. NE-SW.  
 47.50 Rocky spur, brs. NE. Desc. 68 ft. over W. slope.  
 50.90 Head of wash, course NW. Asc. 99 ft. over NE slope.  
 56.10 Spur, brs. N.  
 Desc. 41 ft. over W. slope.  
 57.60 Head of wash, course N.  
 62.50 Rocky spur, brs. N.  
 Desc. 107 ft. over W. slope.  
 69.00 Wash, 10 lks. wide, course N.  
 Asc. 106 ft. over E. slope.  
 71.60 Rocky spur, brs. N.  
 Desc. 47 ft. over W. slope.  
 76.00 Head of wash, course N.  
 Asc. 19 ft. over E. slope.  
 80.14 The cor. of secs. 28, 29, 32 and 33.

Land, rolling and mountainous.

Soil, rocky 4th. rate.

Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

N.0°02'W., on true line, bet. secs. 28 and 29.  
 Over rolling land, thru scattering timber & undergrowth.  
 7.60 Wash, 10 lks. wide, course NW.  
 14.20 Wash, 10 lks. wide, course NW.  
 29.20 Wash, 10 lks. wide, course NW.  
 32.10 Wash, 20 lks. wide, course NW.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 28 & 29, with brass cap mkd.



1931 from which,  
 an ironwood, 12 ins. in diam., brs. N.21 $\frac{1}{2}$ °E., 156 lks. dist., mkd.  $\frac{1}{4}$  S28 BT  
 an ironwood, 16 ins. in diam., brs. S.4°W., 295 lks. dist., mkd.  $\frac{1}{4}$  S29 BT

48.90 Road, brs. NW-SE.  
 69.60 Wash, 10 lks. wide, course NW.

BOOK 3926


Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains							
80.00	<p>Set an iron post 3 ft. long, 2 ins. in diam. 26 ins. in the ground for the cor. of secs. 20, 21, 28 &amp; 29, with brass cap mkd.</p> <table border="1" data-bbox="812 416 982 551"> <tr><td>T2S</td><td>R3W</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td>S29</td><td>S28</td></tr> </table> <p>1931 from which,  a paloverde, 14 ins. in diam., brs. N.89<sup>3</sup>/<sub>4</sub>°W., 428 lks. dist., mkd. T2S R3W S20 BT  an ironwood, 10 ins. in diam., brs. S.65<sup>1</sup>/<sub>2</sub>°E., 305 lks. dist., mkd. T2S R3W S28 BT  No other bearing trees available, dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. distant.</p> <p>Land, rolling and mountainous.  Soil, sandy loam 3rd. &amp; 4th. rate.  Timber, paloverde and ironwood.  Undergrowth, greasewood and cacti.</p>	T2S	R3W	S20	S21	S29	S28
T2S	R3W						
S20	S21						
S29	S28						
40.00	S.89°54'E., on a random line, bet. secs. 21 & 28.						
80.22	Set temp. <sup>1</sup> / <sub>4</sub> sec. cor.						
	Fall 2 lks. N. of the cor. of secs. 21, 22, 27 & 28. Thence,						
19.40	N.89°53'W., on true line, bet. secs. 21 & 28.						
29.00	Over rolling land, thru scattering timber & undergrowth. Wash, 10 lks. wide, course NW.						
40.11	Wash, 5 lks. wide, course NW.						
	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the <sup>1</sup> / <sub>4</sub> sec. cor. of secs. 21 & 28, with brass cap mkd.						
	<table border="1" data-bbox="730 1438 893 1518"> <tr><td><sup>1</sup>/<sub>4</sub></td><td>S 21</td></tr> <tr><td></td><td>S 28</td></tr> </table>	<sup>1</sup> / <sub>4</sub>	S 21		S 28		
<sup>1</sup> / <sub>4</sub>	S 21						
	S 28						
55.60	1931 from which,						
79.60	an ironwood, 8 ins. in diam., brs. N.27°E., 351 lks. dist., mkd. <sup>1</sup> / <sub>4</sub> S21 BT						
80.22	a paloverde, 10 ins. in diam., brs. S.73°E., 332 lks. dist., mkd. <sup>1</sup> / <sub>4</sub> S28 BT						
	Wash, 5 lks. wide, course NW.						
	Wash, 5 lks. wide, course NW.						
	The cor. of secs. 20, 21, 28 and 29.						
	Land, rolling.						
	Soil, sandy loam, 2nd. rate.						
	Timber, paloverde and ironwood.						
	Undergrowth, greasewood and cacti.						
1.60	N.0°02'W., on true line, bet. secs. 20 & 21.						
7.80	Over rolling land, thru scattering timber & undergrowth. Wash, 5 lks. wide, course NW.						
40.00	Road, cleared, brs. NE-SW.						
	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the <sup>1</sup> / <sub>4</sub> sec. cor. of secs. 20 & 21, with brass cap mkd.						
	<table border="1" data-bbox="795 2257 974 2365"> <tr><td>S20</td><td>S21</td></tr> </table>	S20	S21				
S20	S21						
	1931						
	No bearing trees available; dig pits 18 x 18 x 12 ins. N-S. of cor. 3 ft. distant.						
43.50	Road, brs. NE-SW.						
52.10	Wash, 15 lks. wide, course NW.						

Survey of the the Subdivision Lines of T. 2 S., R.3 W.

Chains

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 16, 17, 20 and 21, with brass cap mkd.



1931 from which, a paloverde, 8 ins. in diam., brs. S.82½°W., 155 lks. dist., mkd. T2S R3W S20 BT No other bearing trees available; dig pits 18 x 18 x 12 ins. NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling. Soil, sandy loam, 2nd. rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.


40.00 S.89°53'E., on a random line, bet. secs. 16 & 21. Set temp. ¼ sec. cor.

80.28 Fall 5 lks S. of cor. of secs. 15, 16, 21 & 22. Thence,

N.89°55'W., on true line, bet. secs. 16 & 21. Over rolling land, thru scattering timber & undergrowth.

38.30 Wash, 10 lks. wide, course NW.

40.14 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the ¼ sec. cor. of secs. 16 & 21, with brass cap mkd.



1931 from which, a paloverde, 18 ins. in diam., brs. N.86°E., 331 lks. dist., mkd. ¼ S 16 BT a paloverde, 10 ins. in diam., brs. S.62½°E., 219 lks. dist., mkd. ¼ S21 BT

51.60 Road, brs. NE-SW.

66.10 Wash, 10 lks. wide, course NW.

80.28 The cor. of secs. 16, 17, 20 & 21.


Land, rolling. Soil, sandy loam, 2nd. rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.

N.0°02'W., on true line, bet. secs. 16 & 17. Over rolling land, thru scattering timber & undergrowth.

12.00 Wash, 10 lks. wide, course NW.

38.30 Wash, 100 lks. wide, course W.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, raise a mound of stone about post, for the ¼ sec. cor. of secs. 16 & 17, with brass cap mkd.




1931 from which, a paloverde, 14 ins. in diam., brs. East, 119 lks. dist., mkd. ¼ S16 BT a paloverde, 6 ins. in diam., brs. S.71°W., 43 lks. dist., mkd. ¼ S17 BT

BOOK 2026

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 22 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post for the cor. of secs. 8, 9, 16 and 17, with brass cap mkd.




1931

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00 S. 89° 55' E., on random line, bet. secs. 9 and 16.  
80.30 Set  $\frac{1}{4}$  sec. corner line, bet. secs. 9 and 16.  
80.30 Fall 2 lks. S. of the cor. of secs. 9, 10, 15 & 16.  
80.30 Thence 1/2 sec. S. of the cor. of secs. 9, 10, 15 & 16.  
N. 89° 56' W., on true line, bet. secs. 9 & 16.

25.00 Over rolling land, thru scattering timber & undergrowth.  
Wash, 20 lks. wide, course SW.

40.15 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 9 & 16, with brass cap mkd.




1931

No bearing trees available; raise a mound of stone 3 ft. base, 2 ft. high N. of cor. 3 ft. distant.

52.00 Wash, 30 lks. wide, course SW.  
80.30 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00 N. 0° 02' W., on true line, bet. secs. 8 & 9.  
~~Over rolling land, thru scattering timber & undergrowth.~~  
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 8 & 9, with brass cap marked



1931

from which,  
a paloverde, 10 ins. in diam., brs. N. 32° E., 295 lks. dist., mkd.  $\frac{1}{4}$  S9 BT  
a paloverde, 8 ins. in diam., brs. N. 38° W., 284 lks. dist., mkd.  $\frac{1}{4}$  S8 BT

42.20 Wash, 20 lks. wide, course W.  
57.70 Wash, 10 lks. wide, course SW.

Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

65.90  
80.00

Wash, 10 lks. wide, course SW.  
Set an iron post 3 ft. long, 2 ins. in diam., 22 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T2S	R3W
S5	S4
S8	S9

1931 from which,  
a paloverde, 5 ins. in diam., brs. N.17°W., 72 lks. dist., mkd. T2S R3W S5 BT  
a paloverde, 4 ins. in diam., brs. N.80°E., 190 lks. dist., mkd. T2S R3W S4 BT  
No other bearing trees available.  
Land, rolling.  
Soil, sandy and rocky loam, 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00  
80.24

S.89°56'E., on a random line, bet. secs. 4 and 9.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 9 lks. S. of the cor. of secs. 3, 4, 9 and 10.  
Thence,  
West, on true line, bet. secs. 4 and 9.  
Over rolling land, thru scattering timber & undergrowth.

2.20  
40.12

Wash, 10 lks. wide, course SW.  
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{2}$  sec. cor. of secs. 4 and 9, with brass cap mkd.

$\frac{1}{4}$	S 4
	S 9

1931 from which;  
a mesquite, 12 ins. in diam., brs. N.67°E., 312 lks. dist., mkd.  $\frac{1}{4}$  S4 BT  
a mesquite, 14 ins. in diam., brs. S.74°W., 40 lks. dist., mkd.  $\frac{1}{4}$  S 9 BT

41.75  
72.35  
80.24

Enter large wash, course SW.  
Wash, 5 lks. wide, course S.  
The cor. of secs. 4, 5, 8 and 9.  
Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

6.90  
19.30  
27.00  
31.50  
36.00  
39.00

N.0°02'W., on true line, bet. secs. 4 & 5.  
Over rolling land, thru scattering timber & undergrowth.  
Center of wash, 50 lks. wide, course W.  
Wash, 10 lks. wide, course SW.  
Asc. 29 ft. over SE slope.  
Spur, brs. SW. Desc. 38 ft. over NW slope.  
Wash, 50 lks. wide, course W.  
Asc. gradual S. slope.  
Road, brs. E-W.  
Wash, 10 lks. wide, course SW.

BOOK 37

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

40.00 Set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the 1/4 sec. cor. of secs. 4 & 5, with brass cap marked

1/4  
S5 S4

1931

No bearing trees available.  
47.80 Wash, 10 lks. wide, course SW. Enter mountainous land.  
60.990 Wash, 20 lks. wide, course SW. Asc. 228 ft. over S. slope.  
78.89 Set an iron post 3 ft. long, 2 ins. in diam., on bedrock, deposit a stone mkd. with a cross at base of post, raise a mound of stone about post, for the witness cor. to closing cor. of secs. 4 & 5, with brass cap mkd.

W C  
T1S R3W  
S32  
S5 S4  
T2S R3W

CC  
1931

79.29 No bearing trees available.  
Intersect the S. bdy. of sec. 32, T.1 S., R.3 W., at 1.66 chs. S. 89°56'E from the reestablished 1/4 sec. cor. of sec. 32, hereinbefore described.

True point for the closing cor. falls on precipitous slope where it is impracticable to monument the corner; establish witness cor. as hereinbefore described.

Land, rolling & mountainous.  
Soil, rocky 4th. rate.  
Timber, paloverde and ironwood and mesquite.  
Undergrowth, greasewood and cacti.

-----  
From the cor. of secs. 5, 6, 31 & 32, on S. bdy. of Tp., described in Book 1A of this group, N.0°03'W., on true line, bet. secs. 31 & 32.

Over mountainous land, thru scattering timber & undergrowth.  
Along rocky top of spur, from N.  
4.00 Leave spur, from NE; desc. 80 ft. over NW slope.  
12.00 Wash, 20 lks. wide, course W.  
Over level land.  
28.65 Wash, 50 lks. wide, course W. Asc. 271 ft. over S. slope.  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, deposit a rock mkd. with a cross (X) at base of post, raise a mound of stone about post, for the 1/4 sec. cor. of secs. 31 & 32, with brass cap mkd.

1/4  
S31 S32

1931

No bearing trees available.  
40.50 Asc. 13 ft. over S. slope.  
51.50 Ridge, brs. E-W. Desc. 251 ft. over N. slope.  
Head of wash, course NW. Asc. 91 ft. over SW slope.

## Survey of the Subdivision Lines of T. 2 S., R. 3 W.

## Chains

56.60 Rocky spur, brs. West. Desc. 162 ft. over NW slope.  
 70.00 Leave mountainous land, brs. NE-SW. Over rolling land to  
 75.40 Wash, 5 lks. wide, course NW.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in  
 the ground for the cor. of secs. 29, 30, 31 & 32,  
 with brass cap mkd.

T2S	R3W
S30	S29
S31	S32

1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
 NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling and mountainous.  
 Soil, rocky 4th. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

40.00 East, on a random line, bet. secs. 29 & 32.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.14 Fall 5 lks. N. of the cor. of secs. 28, 29, 32 & 33.  
 Thence,  
 N.89°58'W., on true line, bet. secs. 29 and 32.  
 Over rolling land, thru scattering timber & undergrowth.  
 Desc. 163 ft. over NW slope.  
 14.60 Wash, 10 lks. wide, course N.  
 Asc. 70 ft. over E. slope.  
 24.00 Rocky spur, brs. N. Desc. 69 ft. over W. slope.  
 40.07 Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in  
 the ground to bedrock, deposit a stone mkd. with a  
 cross (X) at base of post, raise a mound of stone  
 about post, for the  $\frac{1}{4}$  sec. cor. of secs. 29 & 32,  
 with brass cap mkd.

$\frac{1}{4}$ S 29
S 32

1931

No bearing trees available.

46.60 Wash, 10 lks. wide, course NW.  
 80.14 The cor. of secs. 29, 30, 31 and 32.

Land, rolling and mountainous.  
 Soil, rocky 4th. rate.  
 Timber, paloverde & ironwood.  
 Undergrowth, greasewood and cacti.

40.00 West, on a random line, bet. secs. 30 & 31.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 77.09 Fall 2 lks. S. of the cor. of secs. 30 & 31, only, on  
 W. bdy. of Tp., hereinbefore described.  
 Thence,  
 S.89°59'E., on true line, bet. secs. 30 & 31.  
 Over rolling land, thru scattering timber & undergrowth.  
 4.20 Wash, 5 lks. wide, course NW.  
 30.90 Wash, 5 lks. wide, course NW.



Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains  
37.09 (40.00 chs. in departure from East.)  
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 30 & 31, with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 30}{S\ 31}$

1931

No bearing trees available.  
Dig pits 18 x 18 x 12 ins. E-W. of cor. 3 ft. distant.

73.00 Main road, brs. NE-SW.  
77.09 The cor. of secs. 29, 30, 31 & 32.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde & ironwood.  
Undergrowth, greasewood and cacti.

---

N.0°03'W., on true line, bet. secs. 29 & 30.  
Over rolling land, thru scattering timber & undergrowth.  
19.40 Wash, 50 lks. wide, course NW.  
26.00 Low spur, brs. West.  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 29 & 30, with brass cap mkd.

$\frac{1}{4}$   
S30 | S29

1931

a paloverde, 10 ins in diam., brs. N.6°W., 251 lks. dist., mkd.  $\frac{1}{4}$  S30 BT. No other bearing tree available. Dig pits 18x18x12 ins., one each N. & S. of cor. 3 ft. dist.

55.35 Main road, brs. NE-SW.  
64.00 Wash, 10 lks. wide, course NW.  
80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 19, 20, 29 & 30, with brass cap mkd.

T2S R3W  
S19 | S20  
S30 | S29

1931

No bearing trees available, raise a mound of stone 3 ft. base, 2 ft. high W. of cor. 3 ft. distant.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

---

S.89°58'E., on a random line, bet. secs. 20 & 29.  
40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
80.12 Fall 5 lks. S. of the cor. of secs. 20, 21, 28 & 29.  
Thence,  
West, on true line, bet. secs. 20 & 29.  
Over rolling land, thru scattering timber & undergrowth.  
10.65 Cleared road, brs. NE-SW.  
15.50 Wash, 5 lks. wide, course NW.  
37.50 Road, brs. NW-SE.  
40.06 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of secs. 20 & 29, with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 20}{S\ 29}$

1931

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

<p>Chains</p> <p>40.08</p> <p>42.70</p> <p>50.70</p> <p>79.40</p> <p>80.12</p>	<p>No bearing trees available.          Dig pits 18x18x12 ins., one each E.-W. of cor. 3 ft. dist.          Road, brs. NW-SE.          New road, brs. N-S.          Main road, brs. NE-SW.          Wash, 10 lks. wide, course NW.          The cor. of secs. 19, 20, 29 &amp; 30.</p> <p>Land, rolling.          Soil, sandy loam, 2nd. rate.          Timber, paloverde and ironwood.          Undergrowth, greasewood and cacti.</p>						
<p>40.00</p> <p>76.80</p>	<p>N.89°59'W., on a random line, bet. secs. 19 &amp; 30.          Set temp. <math>\frac{1}{4}</math> sec. cor.          Fall 2 lks. N. of the cor. of secs. 19 &amp; 30, on W. bdy. of Tp., hereinbefore described.          Thence,          East, on true line, bet. secs. 19 &amp; 30.          Over rolling land, thru scattering timber &amp; undergrowth. (40.00 chs. in departure from East) set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the <math>\frac{1}{2}</math> sec. cor. of secs. 19 &amp; 30, with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math> <math>\frac{S\ 19}{S\ 30}</math> </div>						
<p>76.80</p>	<p style="text-align: center;">1931</p> <p>No bearing trees available; dig pits 18 x 18 x 12 ins. E-W of cor. 3 ft. distant.          The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling.          Soil, sandy loam, 2nd. rate.          Timber, paloverde and ironwood.          Undergrowth, greasewood and cacti.</p>						
<p>0.30</p> <p>18.00</p> <p>40.00</p>	<p>N.0°03'W., on true line, bet. secs. 19 and 20.          Over rolling land, thru scattering timber &amp; undergrowth.          Wash, 10 lks. wide, course NW.          Wash, 5 lks. wide, course NW.          Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the <math>\frac{1}{2}</math> sec. cor. of secs. 19 &amp; 20, with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>          S19      S20       </div>						
<p>45.00</p> <p>62.70</p> <p>70.00</p> <p>80.00</p>	<p style="text-align: center;">1931</p> <p>No bearing trees available; dig pits 18 x 18 x 12 ins. N-S. of cor. 3 ft. distant.          Wash, 5 lks. wide, course NW.          Wash, 5 lks. wide, course NW.          Wash, 5 lks. wide, course NW.          Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in the ground for the cor. of secs. 17, 18, 19 and 20, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T2S</td> <td>R3W</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> </table> <p>1931</p> </div>	T2S	R3W	S18	S17	S19	S20
T2S	R3W						
S18	S17						
S19	S20						

Survey of the Subdivision Lines of T.2 S., R.3 W.

Chains

No bearing trees available; dig pits 18 x 18 x 12 ins.  
NW, NE, SE and SW of cor. 3 ft. distant.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

East, on random line, bet. secs. 17 & 20.  
40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
80.06 Fall 14 lks. N. of the cor. of secs. 16, 17, 20 and 21.  
Thence,  
N. 89° 54' W., on true line, bet. secs. 17 & 20.  
Over rolling land, thru scattering timber & undergrowth.  
23.20 Wash, 10 lks. wide, course NW.  
40.03 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
the ground for the  $\frac{1}{4}$  sec. cor. of secs. 17 & 20, with  
brass cap mkd.

$\frac{1}{4}$  S 17  
            
S 20

1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
E-W of cor. 3 ft. distant.

41.75 Wash, 10 lks. wide, course NW.  
67.65 Wash, 10 lks. wide, course NW.  
73.60 Wash, 10 lks. wide, course NW.  
80.06 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

West, on a random line, bet. secs. 18 & 19.  
40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
76.69 Intersect the cor. of secs. 18 & 19 only, on W. bdy. of  
Tp., hereinbefore described.  
Thence,  
East, on true line, bet. secs. 18 & 19.  
Over rolling land, thru scattering timber & undergrowth.  
36.69 (40.00 chs. in departure from east) set an iron post  
3 ft. long, 1 in. in diam., 26 ins. in the ground for  
the  $\frac{1}{4}$  sec. cor. of secs. 18 & 19, with brass cap mkd.

$\frac{1}{4}$  S 18  
            
S 19

1931

No bearing trees available; dig pits 18 x 18 x 12 ins.  
E-W of cor. 3 ft. distant.


45.00 Center of wash, 100 lks. wide, course SW.  
58.60 Wash, 5 lks. wide, course SW.  
76.69 The cor. of secs. 17, 18, 19 & 20.

Land, rolling.  
Soil, sandy loam, 2nd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.


Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

7.70 N.0°03'W., on true line, bet. secs. 17 and 18.  
 39.00 Over rolling land, thru scattering timber & undergrowth.  
 40.00 Center of big wash, 100 lks. wide, course W.  
 Low ridge, brs. E-W.  
 Set an iron post 3 ft. long, 1 in. indiam., 18 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 17 & 18, with brass cap mkd.




71.00 Wash, 10 lks. wide, course W.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 8 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the cor. of secs. 7, 8, 17 & 18, with brass cap mkd.



1931 from which,  
 a paloverde, 10 ins. in diam., brs. N.77°E., 106 lks. lks. dist. mkd. T2S R3W S8 BT  
 a paloverde, 10 ins. in diam., brs. S.85°E., 80 lks. dist., mkd. T2S R3W S17 BT

Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

40.00 S.89°54'E., on random line, bet. secs. 8 and 17.  
 80.04 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect the cor. of secs. 8, 9, 16 & 17.  
 Thence,  
 N.89°54'W., on true line, bet. secs. 8 & 17.  
 40.02 Over rolling land, thru scattering timber & undergrowth.  
 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 8 & 17, with brass cap mkd.



No bearing trees available; dig pits 18 x 18 x 12 ins. E-W of cor. 3 ft. distant.

50.56 Wash, 10 lks. wide, course NW.  
 65.60 Round knoll, 15 ft. high, on line.  
 69.75 Wash, 50 lks. wide, course SW.  
 79.00 Wash, 5 lks. wide, course S.  
 80.04 The cor. of secs. 7, 8, 17 & 18.

Land, rolling.  
 Soil, sandy loam, 2nd. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains	
40.00 76.60	<p>West, on a random line, bet. secs. 7 and 18. Set temp. <math>\frac{1}{4}</math> sec. cor. Intersect the cor. of secs. 7 and 18, on W. bdy. of Tp, hereinbefore described.</p>
36.60	<p>Thence, East, on a true line, bet. secs. 7 &amp; 18. Over rolling land, thru scattering timber &amp; undergrowth. (40.00 chs. in departure from east) set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 18, with brass cap mkd.</p>
	$\frac{1}{4} \begin{array}{c} S 7 \\ S 18 \end{array}$
	<p>1931 from which, a paloverde, 8 ins. in diam., brs. N.60°W., 70 lks. dist., mkd. <math>\frac{1}{4}</math> S7 BT a paloverde, 8 ins. in diam., brs. S.10°W., 137 lks. dist., mkd. <math>\frac{1}{4}</math> S18 BT</p>
76.60	<p>The cor. of secs. 7, 8, 17 and 18.  Land, rolling. Soil, rocky 2nd. and 3rd. rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.</p>
5.95 25.00 36.00 40.00	<p>N.0°03'W., on true line, bet. secs. 7 &amp; 8. Over molling land, thru scattering timber &amp; undergrowth. Wash, 5 lks. wide, course SE. Low spur, brs. SW. Wash, 5 lks. wide, course W. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 &amp; 8, with brass cap marked</p>
	$\frac{1}{4} \begin{array}{c} S 7 \\ S 8 \end{array}$
	<p>1931 No bearing trees available; raise a mound of stone 3 ft. base, 1<math>\frac{1}{2}</math> ft. high W. of cor. 3 ft. dist.</p>
41.40 66.70 80.00	<p>Wash, near head, course NW. Wash, 5 lks. wide, course NW. Set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, deposit stone mkd. with a cross (X) at base of post, raise a mound of stone about post for the cor. of secs. of 5, 6, 7 and 8, with brass cap mkd.</p>
	$\begin{array}{c c} T2S & R3W \\ \hline S6 & S5 \\ \hline S7 & S8 \end{array}$
	<p>1931 from which, a paloverde, 10 ins. in diam., brs. S.46°E., 173 lks. dist., mkd. T2S R3W S8 BT No other bearing trees available.</p>

## Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

Land, rolling.  
Soil, sandy and stony 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00  
80.06

S. 89° 54' E., on a random line, bet. secs. 5 and 8.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 7 lks. S. of the cor. of secs. 4, 5, 8 and 9.

31.85  
39.35  
40.03

Thence,  
N. 89° 57' W., on true line, bet. secs. 5 and 8.  
Over rolling land, thru scattering timber & undergrowth.  
Wash, 100 lks. wide, course SW.  
Wash, 20 lks. wide, course SW.  
Set an iron post 3 ft. long, 1 in. in diam., 15 ins. in the ground to bedrock, deposit a stone mkd. with a cross (X) at base of post, raise a mound of stone about post, for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 8, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 5}{S \ 8}$$

1931

No bearing trees available.

43.25  
62.80  
80.06

Same wash, course NW.  
Bend in big wash, from NE to NW.  
The cor. of secs. 5, 6, 7 and 8.

Land, rolling.  
Soil, sandy and rocky loam, 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

40.00  
76.51

West, on random line, bet. secs. 6 and 7.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 11 lks. S. of the cor. of secs. 6 and 7 on W. bdy. of Tp., hereinbefore described.

3.71  
12.50  
36.51

Thence,  
S. 89° 55' E., on true line, bet. secs. 6 and 7.  
Over rolling land, thru scattering timber & undergrowth.  
Road, brs. NE-SW.  
Wash, 10 lks. wide, course NW.  
(40.00 chs. in departure from East) set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7; with brass cap mkd.

$$\frac{1}{4} \frac{S \ 6}{S \ 7}$$

1931


No bearing trees available; raise a mound of stone 3 ft. base, 1 $\frac{1}{2}$  ft. high N. of cor. 3 ft. distant.47.31  
51.50  
58.50  
76.51

Wash, 50 lks. wide, course N.  
Round knoll, 50 ft. high on line.  
Center of wash, 100 lks. wide, course NW.  
The cor. of secs. 5, 6, 7 and 8.  
Land, rolling.  
Soil, rocky 3rd. rate.  
Timber, paloverde and ironwood.  
Undergrowth, greasewood and cacti.

Survey of the Subdivision Lines of T. 2 S., R. 3 W.

Chains

11.50 N.0°03'W., on true line, bet. secs. 5 & 6.  
 40.00 Over rolling land, thru scattering timber & undergrowth.  
 Center of wash, 75 lks. wide, course NW.  
 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for the  $\frac{1}{4}$  sec. cor. of secs. 5 & 6, with  
 brass cap mkd.




1931 from which,  
 a paloverde, 14 ins. in diam., brs. N.1 $\frac{1}{4}$ °W., 240  
 lks. dist., mkd.  $\frac{1}{4}$  S6 BT  
 an ironwood 10, ins. in diam., brs. N.21°E., 209  
 lks. dist., mkd.  $\frac{1}{4}$  S5 BT

42.00 Wash, 20 lks. wide, course NW.  
 43.30 Wash, 10 lks. wide, course SW.  
 45.20 Road, brs. E-W.  
 54.10 Wash, 10 lks. wide, course W.  
 59.00 Wash, 10 lks. wide, course W.  
 69.50 Rocky ridge, brs. NE-SW.  
 Desc. 30 ft. over NW slope.

74.20 Wash, near head, course NW. Asc. gradual S. slope.  
 79.33 Intersect the S. bdy. of sec. 31, T.1 S., R.3 W., at  
 1.54 chs. S.89°56' E. from the  $\frac{1}{4}$  sec. established  $\frac{1}{4}$  sec.  
 cor. of sec. 31, hereinbefore described.

At point of intersection set an iron post 3 ft. long,  
 2 ins. in diam., 8 ins. in the ground to bedrock,  
~~deposit a stone mkd. with a cross, (X) at base of~~  
 post, for the closing cor. of secs. 5 & 6, with  
 brass cap mkd.



No bearing trees available.  
 Land, rolling.  
 Soil, rocky 4th. rate.  
 Timber, paloverde and ironwood.  
 Undergrowth, greasewood and cacti.

For the continued satisfactory adjustments of the in-  
 strument refer to Preliminary Field Test described  
 in book "C" of this group.

General Description.

Land; the lands embraced within this township are generally rolling desert in character with the exception of the South tier and the North tier of section where desert hills enter therein. The drainage is to the NE and to the NW a low divide crossing the township from N. and S. following closely the second range of sections.

Soil; chiefly a sandy loam, of 2nd. rate quality; in the hills a rocky 4th. rate covers the slopes.

Timber, paloverde and ironwood, with some mesquite with commercial value as firewood only.

Undergrowth; greasewood, and the various forms of cacti life, including the Sahuaro, predominates.

Water; there is no living water within the Tp. At intermittent periods the washes carry streams of flood water.

Settlement; there were no settlers residing within the Tp. at the time of survey, tho much of the area has been located under the Homestead Laws.

Roads; One good road, traverses the Tp. from SW to NE. other roads are in poor condition.

Mineral; no evidence of mineral was noted.

Industry; fitted for farming only in the event that water is obtained from points outside the Tp.

---





CERTIFICATE OF UNITED STATES SURVEYOR.

I, Karl L. Siebecker, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer, for Group 164, Arizona bearing date of the 15th day of July, 1930, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, resurveyed all those parts or portions of

the South Boundary of

Township 1 South, Range 3 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes and by diagram on page 1 hereof as having been executed by me, and under my direction; and that all the corners of said resurvey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer, for Group 164, Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such resurvey.

Karl L. Siebecker
U. S. Surveyor
San Francisco, Calif. July 10th 1931.

APPROVAL.

Office of U. S. Supervisor of Surveys,

193

The foregoing field notes of the survey of

executed by

under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in

has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.



CERTIFICATE OF UNITED STATES SURVEYOR.

I, Benjamin J. Kinsey, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer, for Group 164 Arizona bearing date of the 15th day of July, 1930, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of

the West Boundary

and

Subdivision Lines of

Township 2 South, Range 3 West of the Gila and Salt

River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes and by diagram on page 1 hereof as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer, for Group 164, Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Place: Phoenix, Arizona.

Date: May 20-1920.

Benjamin J. Kinsey

U. S. Surveyor.

APPROVAL.

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colo., June 14, 1932

The foregoing field notes of the resurvey of Part of the South boundary of

Township 1 South, Range 3 West

and of the survey of

the West boundary and

Subdivision Lines of

Township 2 South, Range 3 West

of the Gila and Salt River Base and Meridian, in the State of Arizona

executed by Karl L. Siebecker and Benjamin J. Kinsey, U.S. Surveyors.

under special instructions dated July 15, 1930 for Group 164, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the resurveys and surveys they describe, are hereby approved.

Wm. H. ...

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in

has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.