

BOOK 3946

FIELD NOTES

OF RETRACEMENT OF THE

3rd Standard Parallel North thru Part of Range 2 West

Part of the Boundary of Fort Whipple Timber Reserve

Patented Mining Claims, Min. Surveys Nos. 1572 and 1752

Forest Homestead Entry Survey N. 69

and Part of the Subdivision Lines of

Township 13 North, Range 2 West

AND OF RESURVEY OF

3rd Standard Parallel North thru Part of Range 2 West

East, West, and North Boundaries and

Part of the Subdivision Lines of

Township 13 North, Range 2 West

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Benjamin J. Kinsey

U.S. Surveyor

In the capacity of U. S. Surveyor, under Special Instructions dated April 16, 1930, issued by the District Cadastral Engineer to govern surveys included in Group No. 157-Arizona, which were approved by the Commissioner of the General Land Office, April 25, 1930, and Assignment Instructions dated May 6, 1930

Retracement & Survey commenced May 16, 1930

Retracement & Resurvey completed Sept. 26, 1930

3946

3/946

INDEX DIAGRAM.

Township -----, Range -----

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Book "A"
Group 157 Arizona
Township 13 North Range 2 West
INDEX-DIAGRAM

BOOK 3946

	28 95	29 30 5	30 31 81 4 82	31 32 69 3 68	32 33 59 2 60 59	33 49 1 48	18 17
24 7	93	8	79 9	67 10	58 11	48 12	17 16
23 92	92	91	78 77	66	57 56	47	47
23 18	90 17	76	77 16	65 15	56 14	46 13	16 15
22 89 90	89 88	<i>T. 13 N. - R. 2 W.</i>		76 75	65 64	55 54	46 45
22 19	88 20	75 21	63 22	54 23	44 24	15 14	
21 86 87	87 86	74 73	62	53 52	43 42	14	
21 30	85 29	72 28	61 27	51 26	42 25	14 13	
20 84	84 83	72 71	38 37	50 36 50	41 40	13	
20 31	82 32	70 33	37 34	36 35 35	39 36	12	
10 9	8	7 4	<i>FORT WHIPPLE TIMBER RESERVE</i>		6		

97
CORNUCOPIA
Mining Claim
98
GOLD TRAIL
Mining Claim

24 19 20 21 22 23 24 19
 FRAC. T. 12 1/2 N. R. 3 W. FRAC. T. 12 1/2 N. R. 2 W. FRAC. T. 12 1/2 N. R. 1 W.

- Lines retraced under this group.
- Lines resurveyed under this group.
- Accepted, surveyed lines.
- Unsurveyed.
- Areas surveyed as per accepted plats on file.

Ties to U.S. Geological Survey Bench Marks - Page 99.

Book "A"
 Group 157 Arizona
 Township 13 North, Range 2 West

DATE DIAGRAM
 1930

9-4	9-2 6 9-3	7-18 5 9-17	9-26 4 9-18	9-18 3 8-14	9-17 2 7-29	9-19 1 8-13	7-16
9-4	7 9-6	8 9-1	9 8-29	10 8-21	11 8-15	12 8-7	8-15
9-5	18 9-17	17 9-15	16 8-21	15 8-21	14 7-16	13 8-9	8-7
9-15	19 9-16	20 6-26	21 7-19	22 5-28	23 5-17	24 6-21	7-25
9-15	30 9-16	29 7-3	28 6-6	27 5-28	26 5-21	25 6-18	6-16
9-15	31 7-7	32 7-7	33 6-7	34 6-7	35 6-24	36 6-12	6-16
		3rd	Standard	Parallel	North		

Retracement
 "CORNUCOPIA"
 MINING CLAIM
 6-23
 Retracement
 "GOLD TRAIL"
 MINING CLAIM
 6-23

Resurveyed by Benjamin J. Kinsey, U.S. Surveyor, on dates (1930) shown thereon. Notes herein.

Retraced by Benjamin J. Kinsey, U.S. Surveyor, on dates (1930) shown thereon. Notes herein.

Accepted, surveyed lines.

The retracements and resurveys herein described were executed by Benjamin J. Kinsey, U.S. Surveyor, on dates shown on diagram on page 2 hereof, using Buff transit No. 18000, and Young & Sons transit No. 8540. Both of said instruments are equipped with Smith solar attachments, and otherwise conform to the standard requirements of the General Land Office.

 PRELIMINARY FIELD TEST of INSTRUMENTS.

May 14, 1930,

at station near the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, T. 13 N., R. 2 W., G. & S. R. B. & M., Arizona, latitude $34^{\circ}29'N.$, longitude $112^{\circ}27'W.$, examine the adjustments of the transits and find no existing errors, then, to test the workings of the solar apparatus, proceed as follows:

May 15, 1930,

at 4h. 10m., a.m., l.m.t., using Buff transit No. 18000, observe Polaris at eastern elongation, making four observations, two each with the telescope in direct and reversed positions, and marking the mean point in the line thus determined by a tack in a stake driven firmly in the ground about 5 chs. north.

Azimuth of Polaris at eastern elongation = $1^{\circ}18' 5''$

At 8h. 0m., a.m., lay off the azimuth of Polaris $1^{\circ}18'$ to the west, and mark the true meridian thus determined by a tack in a stake driven firmly in the ground about 5 chs. north.

At 9h. 0m., a.m., app. t., set off $34^{\circ}29'N.$ on the lat. arcs, $18^{\circ}48\frac{1}{2}'N.$ on the decl. arcs, and determine a meridian with each solar, finding both to agree with the true meridian.

At apparent noon, with the lat. arcs unchanged, observe the sun on the meridian, and obtain a reading of $18^{\circ}50\frac{1}{2}'N.$ on each decl. arc, which agrees with the computed declination of the sun.

At 3h. 0m., p.m., app. t., with the lat. arcs unchanged, set off $18^{\circ}52'N.$ on the decl. arcs, and determine a meridian with each solar, finding both to agree with the true meridian.

As all of the observations taken during the usual hours of solar work agree within 1' with the true meridian, conclude that the instruments are in satisfactory adjustment.

Unless otherwise specified all azimuth determinations are accomplished with the solar attachments except the special observations upon Polaris upon which to test the solar apparatus.

All measurements recorded herein were made with a Lallie 5-chain steel tape, compared with a Lufkin standard steel tape and found correct.

The measurements are made on the slope, vertical angles determined by clinometer, and the slope measurements properly reduced to true horizontal equivalents for entry in the field notes.

4 Retracement of 3rd Std. Par. N. thru Part of R. 2 W.

Chains

The 3rd Std. Par. N. was surveyed thru Range 2 West by O.H. Case, U.S.D.S. in 1871.
 In 1918, D.W. Eaton, U.S.T., resurveyed the south bdrs. of secs. 35, 34, 33, and the E. $\frac{1}{4}$ of sec. 32, T. 13 N., R. 2 W., reconstructing and reestablishing the cors. thereon, in connection with his survey of the Ft. Whipple Timber Reserve in secs. 33, 34 and 35, T. 13 N., R. 2 W.
 In 1927, S.E. Blout, U.S.C.E., retraced the west $\frac{1}{2}$ miles of the Parallel in R. 2 W.
 No other retracement or resurvey of the 3rd Std. Par. N. in R. 2 W. is of record.

 The following notes describe a retracement of the Par. south of the E. $\frac{1}{4}$ of sec. 33, T. 13 N., R. 2 W., omitting topography because of close agreement of same with the 1918 resurvey record.

 The std. cor. of secs. 33 and 34, T. 13 N., R. 2 W. is described in the record of the 1918 resurvey by Eaton as a granite boulder exposed 4x4x3 ft. above ground, marked with a cross (X) on top, SC FWTR on N. face, and 3 grooves on each of E. and W. faces, and witnessed by a white oak tree, 10 ins. diam., N. 52° W., 17 lks. dist., marked SC T13N R2W S33 BT.

Find this cor. monument to be an iron post, 3 ins. diam., projecting 12 ins. above ground, firmly set alongside a granite boulder exposed 5x4x3 ft. above ground, marked SC on W. face, and 3 grooves on each of E. and W. faces. Brass cap on iron post marked

T13N R2W
 F W T R
 SC
 S33/S34

1918

and witnessed by the record bearing tree.

There is no record of this cor. having been reconstructed and monumented as described above.

Thence

N. 89° 40' W. (1918 resurvey record) on random line, on the S. bdy. of sec. 33 (E. $\frac{1}{4}$), and line 5-6 of bdy. of Ft. Whipple Timber Reserve.

19.67

Over rolling land, thru scattering timber and undergrowth. Fall 11 lks. N. of the std. E. $\frac{1}{6}$ sec. cor. of sec. 33 and Cor. No. 5 (SW. cor.) of F.W.T.R., which is an iron post, 2 ins. diam., projecting 12 ins. above ground, firmly set, marked on brass cap as per record, and witnessed by a mound of stone NE. of cor. No bearing trees.

39.35

Continue line and measurement. Leave bdy. of F.W.T.R.

Fall 23 lks. N. of the reestablished std. $\frac{1}{4}$ sec. cor. of sec. 33, which is an iron post, 1 in. diam., projecting 16 ins. above ground, firmly set in ground and mound of stone, and marked on brass cap as per record.

True course and dist. of E. $\frac{1}{4}$ of S. bdy. of sec. 33 are therefore, West, 39.35 chs., and the std. E. $\frac{1}{6}$ sec. cor. of sec. 33 and Cor. No. 5 of F.W.T.R. is in proper alignment bet. the sec. cor. and the $\frac{1}{4}$ sec. cor.

At a point 12.00 chs. S. 24° W. from the above described std. $\frac{1}{4}$ sec. cor. find the original std. $\frac{1}{4}$ sec. cor. of sec. 33, which is a fallen pine tree, 18 ins. in diam., plainly marked $\frac{1}{4}$ S BT. Obliterate this marking as it is considered advisable to retain the reestablished std. $\frac{1}{4}$ sec. cor. of sec. 33 in the position in which it was set by Eaton in 1918.

Land, rolling. Soil, rocky, 3rd and 4th rate.
 Timber, pine and oak. Undergrowth, scrub oak, manzanita and cacti.

Resurvey of 3rd Std. Par. N. thru Part of R. 2 W. 5

Chains	<p>The 3rd. Std. Par. N., was surveyed thru Range 2 West, by O.H. Case, U.S.D.S., in 1871. In 1918, D.W. Eaton, U.S.T. resurveyed the Par. on S. bdy. of secs. 35, 34, 33, and E. 1/2 of S. bdy. of sec. 32. In 1927, Sidney E. Blout, U.S. Cadastral Engineer, retraced the S. bdy. of sec. 31 and W. 1/2 of S. bdy. of sec. 32 in connection with the reestablishment of the Cor. of Ts. 13 N., Rs. 2 and 3 West. No other retracement or resurvey of this line is of record. The following notes describe a dependent resurvey of the Parallel S. of secs. 31, 32, 36 and W. 1/2 of sec. 33. of said portion together with certain corrections to the original survey.</p>
40.00 76.46	<p style="text-align: center;"><u>Retracement for Resurvey.</u></p> <p>From the original Std. Cor. of Ts. 13 N., Rs. 1 and 2 W., West, on a random line, on the S. bdy. of sec. 36. No trace of the original std. 1/4 sec. cor. of sec. 36 found in this vicinity, after diligent search. Continue line and measurement. Fall 10.18 chs. North of the original std. cor. of secs. 35 and 36. True course and dist. of the S. bdy. of sec. 36 are therefore S. 82° 25' W., 77.14 chs.</p>
46.90	<p>From the reestablished Std. 1/4 sec. cor. of sec. 33. West, on a random line, on the S. bdy. of sec. 33, (W. 1/2) Fall 9.07 chs. North of the original Std. cor. of secs. 32 & 33. True course and dist. of the W. 1/2 of S. bdy. of sec. 33 are therefore S. 79° 03' W., 47.77 chs.</p>
30.89	<p>Thence, West, on a random line, on the S. bdy. of sec. 32. (E. 1/2) Fall 10.64 chs. South of the original standard 1/4 sec. cor. of sec. 32. True course and dist. of the E. 1/2 of the S. bdy. of sec. 32 are therefore N. 71° 00' W., 32.67 chs.</p>
40.00	<p>Thence, N. 88° 25' W., on a random line, on the S. bdy. of sec. 32 (W. 1/2) No trace of the original std. cor. of secs. 31 and 32, found in this vicinity, after diligent search. Set temp. cor. Continue line and measurement, on the S. bdy. of sec. 31.</p>
80.00	<p>No trace of the original Std. 1/4 sec. cor. of sec. 31 found in this vicinity after diligent search. Set temp. cor.</p>
120.00	<p>Intersect the reestablished cor. of Ts. 13 N., Rs. 2 and 3 West. True course and dist. of this part of the 3rd. Std. Par. N. are therefore N. 88° 25' W., 120.00 chs., which to maintain original proportion bet. cor. intervals thereon gives three intervals of 40.00 chs. each for the reestablishment of the missing std. cors.</p>

Chains

Resurvey.

The original std. cor. of Ts. 13 N., Rs. 1 and 2 W., is an oak tree, 16 ins. in diam., in good condition, scribed on three faces as follows:

- N. face, SC TX111N
- E. " , R1WSXXX1
- W. " , R2WSXXXV1

witnessed by an oak, 15 ins. in diam., which brs. S.60°E., 22 lks. dist., marks illegible.

an oak, 10 ins. in diam., brs. N.51°W., 50 lks. dist., marked but illegible.

Reconstruct this cor. monument and alter its reference as follows:

On N. side of original tree cor. set an iron post 3 ft. long, 1 1/2 ins. in diam., 24 ins. in the ground for std. cor. of T.13 N., R.2 W. only (SE. cor.) with brass cap marked

SC
T13N
R2W
S36

1930 from which, an oak, 14 ins. in diam., brs. N.37°W., 62 lks. dist. marked SC T13N R2W S36 BT

an oak, 10 ins. in diam., brs. N.62°W., 84 lks. dist. marked SC T13N R2W S36 BT

Thence, S.82°25'W., on true line, on S. bdy. of sec. 36. Over mountainous land, thru thick timber and undergrowth. Desc. 119 ft. over NW slope.

- 5.50 Wash, 10 lks. wide, course NW. Asc. 204 ft. over NE slope.
- 25.60 Spur, brs. N. Desc. 187 ft. over NW slope.
- 33.40 Wash, 10 lks. wide, course N. Asc. 53 ft. over E. slope.
- 38.57 (proportional dist.) Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished std. 1/4 sec. cor. of sec. 36, with brass cap marked

S C
1/4 S 36

1930 from which, a spruce, 8 ins. in diam., brs. N.55 1/2°E., 15 lks. dist., marked SC 1/4 S 36 BT
an oak, 8 ins. in diam., brs. N.64°W., 61 lks. dist., marked SC 1/4 S 36 BT

Continue line and measurement.

- Asc. gradual E. slope.
- 40.60 Spur, brs. N. Desc. 173 ft. over NW slope.
- 45.00 Trail, brs. N. & S.
- 45.50 Wash, 20 lks. wide, course NW. Asc. 60 ft. over NE slope.
- 51.30 Spur, brs. N. Desc. 54 ft. over NW slope.
- 56.00 Branch spur, brs. NW. Desc. 181 ft. over SW slope.
- 62.60 Wash, 5 lks. wide, course N.80°W. Desc. gradually down same.
- 66.65 Same wash, course SW. Wire fence (Prescott City fence) brs. NW-SE. Asc. gradual SE slope.
- 69.50 Spur, brs. SW. Desc. 189 ft. over W. slope to

chains

77.14 Intersect the reconstructed original std. cor. of secs. 35 and 36, which is an iron post, 2 ins. diam., projecting 18 ins. above ground, firmly set in ground and mound of stone, marked on brass cap as per record, and witnessed by three properly marked bearing trees, one each NE., NW. and SW. of cor.


Land, mountainous.
Soil, rocky, 4th rate.
Timber, yellow pine, spruce, juniper and oak.
Undergrowth, scrub oak, mahogany and manzanita.

From the reestablished std. 1/4 sec. cor. of sec. 33, T.13 N., R.2 W., hereinbefore described,

- S. 79° 3' W., on true line, on S. bdy. of sec. 33 (W. 1/2)
- Over mountainous land, thru dense timber and undergrowth.
- Ascend slightly over E. slope to
- 1.10 Spur, brs. S. Desc. 193 ft. over NW. slope.
- 14.00 Hassayampa Creek, 100 lks. wide, in bottom of canyon, containing a stream of water, 30 lks. wide, 12 ins. deep, course N.
- Asc. 54 ft. over rolling NE. slope.
- 21.20 Spur, brs. NW. Desc. 15 ft. over SW. slope.
- 22.10 Wash, 10 lks. wide, course N. Asc. 41 ft. over E. slope.
- 24.00 Spur, brs. N. Asc. 54 ft. along N. slope.
- 30.50 Spur, brs. NW. Desc. 45 ft. over SW. slope.
- 34.00 Wash, 10 lks. wide, course NW. Asc. 26 ft. over NE. slope.
- 34.20 Old road, brs. NW.-SE.
- 36.40 Spur, brs. N. Desc. 40 ft. over W. slope.
- 39.50 Wash, 10 lks. wide, course N.
- Asc. 29 ft. over E. slope.
- 42.00 Spur, brs. N. Desc. 87 ft. over W. slope to

47.77 Intersect the original std. cor. of secs. 32 and 33, which is a granite stone 14x18x9 ins. above ground, firmly set, marked with 2 grooves on W., 4 grooves on E. and 6 grooves on N. face, and witnessed by remains of two of the three original bearing trees:
Stump of a pine, 2 ft. high, N. 79° E., 14 lks. dist., marked SXXXIII
Stump of a pine, 2 ft. high, S. 21° E., 19 lks. dist., marked TXL1N SIV BT
Find no trace of record NW. bearing tree.

Reconstruct this cor. monument as follows:
alongside the original cor. stone, set an iron post, 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, and raise a mound of stone around post, for std. cor. of secs. 32 and 33, T.13 N., R.2 W., with brass cap marked



1930

- from which
- a yellow pine, 12 ins. diam., brs. N. 50° W., 24 lks. dist., marked SC T13N R2W S32 BT
- a yellow pine, 10 ins. diam., brs. N. 15 1/2° E., 50 lks. dist., marked SC T13N R2W S33 BT

From this cor., the std. cor. of same secs. reestablished in the 1918 resurvey bears N. 50° 9' E. 13.32 chs. dist., and is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, properly marked on

8 Resurvey of the 3rd Std. Par. N. thru Part of R.2 W.

chains

brass cap, and witnessed by a mound of stone N. of cor. As the Eaton reestablished std. cor. of secs. 32 and 33 now ceases to function as public land cor., remove the iron post, and scatter the mound of stone.


Land, mountainous.
Soil, rocky, 4th rate.
Timber, yellow pine, juniper and oak.
Undergrowth, scrub oak, mahogany, manzanita and cacti.

N. 71° 00' W., on true line, on S. bdy. of sec. 32 (E. 1/2)
Over mountainous land, thru dense timber and undergrowth.
Asc. 17 ft. over NE. slope.

- 2.50 Spur, brs. NW. Desc. 111 ft. over W. slope.
- 7.15 Old road, brs. N.-S.
- 8.70 Wash, 5 lks. wide, course SW. Asc. gradually over SE. slope.
- 11.70 Spur, slopes W. from NE. Desc. 44 ft. over W. slope.
- 13.00 Wash, 5 lks. wide, course NW. Asc. slightly over NE. slope.
- 13.80 Spur, brs. NW. Desc. 13 ft. over SW. slope.
- 15.50 Wash, 20 lks. wide, course NW. Asc. 10 ft. over NE. slope.
- 16.90 Spur, brs. NW. Desc. 11 ft. over SW. slope.
- 18.30 Shallow wash, course N. Road, brs. N.-S.
Asc. gradually over E. slope.
- 23.50 Shallow wash, course NW. Desc. 17 ft. over NW. slope.
- 28.00 Enter Hassayampa Creek bottom in bend of creek course NW. from NE.
Thence across rocky creek bottom.
- 30.70 Leave creek bottom. Asc. 17 ft. over NE. slope.
- 32.15 Old road, brs. NW.-SE.
- 32.67 Intersect the reconstructed original std. 1/4 sec. cor. of sec. 32, which is an iron post, 1 in. diam., projecting 14 ins. above ground, firmly set in ground and mound of stone, marked on brass cap as per record, and witnessed by two properly marked bearing trees, one each NE. and SE. of cor.

Thence
N. 88° 23' W., on true line, on S. bdy. of sec. 32 (W. 1/2)
Over mountainous land, thru dense timber and undergrowth.
Asc. 151 ft. over NE. slope.

- 8.75 Spur, brs. NE. Desc. 290 ft. over steep NW. slope
- 17.90 Branch spur, brs. NW.
- 22.20 S. edge of Hassayampa Creek bottom, at bend in same from NE. to NW.
Asc. 74 ft. over NE. slope.
- 34.40 Spur, brs. NW. Desc. 106 ft. over SW. slope to
- 39.70 East edge of Hassayampa Creek bottom. Set an iron post, 3 ft. long, 2 ins. in diam., 8 ins. in the ground to bedrock, and raise a mound of stone around post, for witness cor. to reestablished std. cor. of secs. 31 and 32, with brass cap marked



1930

No bearing trees available.
Chisel an 8 in. cross (X) and BO S32 on SW. face of an outcropping ledge of rock, 5 ft. high, bearing N. and S. alongside the W.C.

chains	Continue across rocky creek bottom.
40.00	<p>True point for reestablishment of the std. cor. of secs. 31 and 32 falls on an outcropping ledge of rock in creek bottom, where it is impracticable to monument the cor., therefore witness cor. is established at 30 lks. S. 88° 23' E. as described.</p> <p>At true cor. point cut an 8 in. cross (X) in the rock ledge, and NE. of cross 5 lks. dist. cut BO S32 in the surface rock.</p> <p>From this cor. point, U.S.L.M. No. 1771 bears N. 29 1/4° W., 24.29 chs. dist. Said mineral monument is a granite boulder exposed 6x5x4 ft. above ground, marked USLM No. 1771 on N. face, and witnessed by a properly marked bearing tree NW. of mon.</p> <p>Land, mountainous and creek bottom. Soil, rocky, 4th rate. Timber, yellow pine and oak. Willow and cottonwood in the creek bottom. Undergrowth, scrub oak, catclaw cacti and manzanita.</p> <hr/> <p>From true point for reestablished std. cor. of secs. 31 and 32, N. 88° 23' W., on true line, on S. bdy. of sec. 31. Over rocky bottom of Hassayampa Creek, thru scattering timber and undergrowth.</p> <p>0.50 Stream of water, 20 lks. wide, 6 ins. deep, course S. Continue across creek bottom.</p> <p>1.00 West edge of Hassayampa Creek bottom, brs. N.-S. Leave creek bottom, and enter mountainous land, scattering timber and dense undergrowth. Asc. 226 ft. over steep E. slope.</p> <p>2.50 Road, brs N.-S.</p> <p>6.70 Spur, brs. SE. Desc. 52 ft. over SW. slope.</p> <p>15.80 Head of wash, course S. Asc. 57 ft. over E. slope.</p> <p>18.50 Branch spur, brs. S. Desc. 102 ft. over W. slope.</p> <p>19.50 Trail, brs. N.-S.</p> <p>21.15 Wash, 10 lks. wide, course S. Asc. 280 ft. over steep brushy E. slope.</p> <p>33.20 Ridge, brs. E.-W. Desc. 34 ft. over NW. slope.</p> <p>38.70 Wash, near head, course SW. Asc. 16 ft. over E. slope</p> <p>39.50 Spur, brs. SW. Desc. 34 ft. over W. slope to</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, deposit a stone marked with a cross (X) at base of post, and raise a mound of stone around post, for reestablished std. 1/4 sec. cor. of secs. 31, with brass cap marked</p> <p style="text-align: center;">S C 1/4 S31 ----- 1930</p> <p>No bearing trees available.</p> <p>46.30 Desc. 94 ft. over W. slope. Wash, 20 lks. wide, course S. Asc. 28 ft. over E. slope.</p> <p>49.10 Spur, brs. S. Desc. 361 ft. over steep W. slope.</p> <p>61.20 Wash, 10 lks. wide, course S.</p>

chains	Asc. 39 ft. over E. slope.
66.00	Spur, brs. S. Desc. 141 ft. over W. slope.
70.20	Wash, 20 lks.wide, course S. Asc. 380 ft. over steep E. slope.
79.00	Ridge, brs. N. and S. Desc. 28 ft. over W. slope to
80.00	Intersect the reestablished std. cor.of T.13 N.,R.2 W. and SE. cor. of T.13 N.,R.3 W., which is an iron post, 3 ins.in diam., projecting 18 ins.above ground,firmly set inground and mound of stone,and properly marked on brass cap. No bearing trees or other accessories.
	Land, creek bottom and mountainous. Soil, rocky, 4th rate. Timber, juniper and oak. Willow and cottonwood in creek bottom and along the washes. Undergrowth, scrub oak,manzanita,mountain mahogany and cacti.

Resurvey of the East Bdy. of Township 13 North, Range 2 West 11

Chains

The East bdy. of T.13 N., R.2 W. was surveyed due South by O.H. Case, U.S.D.S. in 1871, establishing common reference cors. thereon at 40 ch. intervals, and establishing the std. cor. of Ts. 13 N., Rs. 1 and 2 W. at 480 chs. S. from the cor. of Ts. 13 & 14 N., Rs. 1 & 2 W. No retracement or resurvey of any part of this Tn. bdy. is of record.

The following notes describe a resurvey of the entire line as a dependent resurvey of the E. bdy. of T.13 N., R.2 W., reconstructing existing cor. monuments with altered reference to areas W. of line only, and reestablishing missing corners at proportional intervals between existing cors., also with reference to areas W. of line only.

The reestablishment on this line of cors. referring to areas E. of line only is described in Book "D" of this group under heading of "Resurvey of West Bdy. of T.13 N., R.1 W."

Retracement for Resurvey.

39.15 From original cor. of Ts. 13 & 14 N., Rs. 1 & 2 W., South, on random line, on E. bdy. of sec. 1 (N. $\frac{2}{3}$) Fall 1.54 chs. W. of original $\frac{1}{4}$ sec. cor. of secs. 1 & 6. True course and dist. of N. $\frac{2}{3}$ of E. bdy. of sec. 1 are therefore, N. 2°15'W., 39.18 chs.

40.61 Thence, South, on random line, on E. bdy. of sec. 1 (S. $\frac{2}{3}$) Fall 26 lks. E. of original cor. of secs. 1, 6, 7 and 12. True course and dist. of S. $\frac{2}{3}$ of E. bdy. of sec. 1 are therefore, N. 0°22'E., 40.61 chs.

254.70 From original cor. of secs. 1, 6, 7 and 12, S. 2°34'E., on random line, on E. bdrs. of secs. 12, 13 and 24, for distance only, a flag on the original cor. of secs. 19, 24, 25 and 30 being visible at such bearing. Make diligent search and set temp. cors. at record intervals.

Find no trace of any original cor. until at Intersect the original cor. of secs. 19, 24, 25 and 30. True course and dist. of Tp. bdy. from this cor. to the cor. of secs. 1, 6, 7 and 12 are therefore, N. 2°34'W., 254.70 chs., which, to maintain record proportion between cor. intervals thereon, gives six intervals of 42.45 chs. each, for the reestablishment of the missing cors.

35.84 From original cor. of secs. 19, 24, 25 and 30, South, on random line, on E. bdy. of sec. 24 (N. $\frac{2}{3}$) Fall 54 lks. E. of original $\frac{1}{4}$ sec. cor. of secs. 19 and 24. True course and dist. of N. $\frac{2}{3}$ of E. bdy. of sec. 24 are therefore, N. 0°52'E., 35.84 chs.

40.70 Thence, South, on random line, on E. bdy. of sec. 24 (S. $\frac{2}{3}$) Intersect the original cor. of secs. 25, 30, 31 and 36. True course and dist. of S. $\frac{2}{3}$ of E. bdy. of sec. 24 are therefore, North, 40.70 chs.

38.70 From original cor. of secs. 25, 30, 31 and 36, South, on random line, on E. bdy. of sec. 36 (N. $\frac{2}{3}$) Fall 61 lks. E. of original $\frac{1}{4}$ sec. cor. of secs. 31 & 36. True course and dist. of N. $\frac{2}{3}$ of E. bdy. of sec. 36 are therefore, N. 0°54'E., 38.70 chs.

40.00 Thence, S. 3°15'W., on random line, for dist. only, flag on objective cor. being visible at such bearing. Intersect the reconstructed std. cor. of T.13 N., R.2 W. only (SE. cor.) hereinbefore described. True course and dist. of S. $\frac{2}{3}$ of E. bdy. of sec. 36 are therefore, N. 3°15'E., 40.00 chs.

Chains	From the std. cor. of T. 13 N., R. 2 W. only (SE. cor.) on the 3rd Std. Par. N., hereinbefore described, N. 3°15'E., on true line, on E. bdy. of sec. 36 (S. 2)
	Over mountainous land, thru dense timber and undergrowth. Desc. 106 ft. over NW. slope.
4.50	Head of wash, course W. Desc. 21 ft. over W. slope.
8.70	Spur, brs. W. Desc. 70 ft. over N. slope.
15.00	Wash, 10 lks. wide, course NW. Asc. 17 ft. over W. slope.
18.60	Desc. 81 ft. over NW. slope.
24.40	Creek, containing small stream of water, course SW. Asc. 300 ft. over rolling S. slope to ridge.
27.40	U.S. Forest Service trail to Lookout Tower on Spruce Mt., brs. E.-W.
39.90	Ridge, brs. E.-W. Thence across top of ridge to
40.00	Intersect the original $\frac{1}{4}$ sec. cor. of secs. 31 and 36, which is a yellow pine tree, 24 ins. diam., marked $\frac{1}{4}$ S BT on each of E. and W. faces. No accessories. Reconstruct this cor. monument and alter its reference as follows: alongside and on W. side of tree, set an iron post, 1 in. diam., 6 ins. in the ground to bedrock, and raise a mound of stone around post, for E. $\frac{1}{4}$ sec. cor. of sec. 36, with brass cap marked $\frac{1}{4}$ S36 1930
	from which a yellow pine, 14 ins. in diam., brs. N. 70°W., 36 lks. dist., marked $\frac{1}{4}$ S36 BT a yellow pine, 8 ins. in diam., brs. N. 77°W., 40 lks. dist., marked $\frac{1}{4}$ S36 BT U.S.F.S. Spruce Mt. Lookout Tower brs. N. 76°49'E. about 25 chs. dist. Vertical angle +8° Hoist of "Midnite Test" mine, brs. N. 16° 2'E., Vertical angle -5 $\frac{1}{2}$ ° Highest peak of Granite Mt. brs. N. 34°W. Vertical angle zero.
	Thence N. 0°54'E., on true line, on E. bdy. of sec. 36 (N. 2) Over mountainous land, thru dense timber and undergrowth. Desc. 371 ft. over steep N. slope.
12.40	Wash, 10 lks. wide, course NW. Asc. 9 ft. over SW. slope.
13.90	Spur, brs. W. Desc. 101 ft. over N. slope.
17.65	Wash, 20 lks. wide, course W. Asc. 162 ft. over S. slope to ridge.
18.83	Intersect S. end line (2-3) of "Nil Desperandum" unpatented lode mining claim, M.S. No. 1549 at 3.60 chs. S. 89°00'E. from Cor. No. 2 thereof. Thence across unpatented mineral land.
25.50	Ridge, brs. E.-W. Desc. 180 ft. over N. slope.
34.45	Small wash, 10 lks. wide, course NW. Asc. 21 ft. over SW. slope.
36.35	Spur, brs. NW. Desc. 52 ft. over N. slope.
37.70	Small wash, course NW. Asc. gradually over SW. slope to
38.70	Intersect original cor. of secs. 25, 30, 31 and 36, which is a granite stone 10x10x16 ins., loosely set in a mound of stone, and marked with one notch on N. face. No other marks visible.

Resurvey of the East Bdy. of T.13 N., R.2 W.

Chains One of the original bearing trees, an oak, 14 ins. in diam., blazed but marking obliterated by decay, bears S.10°E., 13 lks. dist.
 No trace of the original SW. bearing tree remains.
 Reconstruct this cor.monument and alter its reference as follows:
 remove the mound of stone, and in center of its position reset old cor.stone 10 ins.in the ground, and alongside same set an iron post, 3 ft.long, 2 ins. in diam., 12 ins.in the ground to bedrock, and raise a mound of stone around post, for cor.of secs.25 and 36 only, with brass cap marked

T13N
 S25
 S36
 R2W.

1930

from which
 A yellow pine, 14 ins.in diam., brs. N.7°W., 36 lks. dist., marked T13N R2W S25 BT
 a yellow pine, 24 ins.in diam., brs. S.11°W., 95 lks. dist., marked T13N R2W S36 BT

Land, mountainous.
 Soil, rocky, 4th rate.
 Timber, yellow pine, spruce, fir and juniper.
 Undergrowth, scrub oak, mahogany, manzanita and laurel.

North, on true line, on E. bdy. of sec.25 (S. 1/4)
 Over mountainous land, thru dense timber and undergrowth.
 Across unpatented mining claims of M.S.No.1549.
 Asc. 20. ft. over West slope.

0.80 Intersect N. end line(4-1) of "Nil Desperandum" unpatented lode mining claim, M.S.No.1549, at 30 lks.N.89°W. from Cor.No.4 thereof.
 Continue across unpatented M.S.1549.

5.00 Desc. 142 ft. over N. slope.

12.40 East fork of Groom Creek, course NW., containing a small stream of running water, 6 lks.wide, 4 ins.deep.
 Asc. 30 ft. over S. slope.

15.80 Spur, bears W. Group of mining shacks E. and W. of line at this point.
 Desc. 55 ft. over N. slope.

18.40 Road, bears E. and W.

19.30 NE. fork of Groom Creek, 10 lks.wide, course SW.
 Asc. 182 ft. over S. slope.

24.26 Intersect line 4-5 of "Stull" patented lode mining claim of M.S.No.1752 Amended, at 1.79 chs. N.28°18'E. from theoretical point for Cor.No.5 thereof.
 This intersection was computed, based upon the intersection of the range line with the N. end line(4-5) of the "Gold Trail" claim of same M.S., and a retracement of line 5-1 of same claim, as Cor.No.5 of the "Stull" could not be identified.
 Thence across "Stull" and "Gold Trail" patented lode mining claims of M.S.No.1752.

28.70 Spur, bears W. Desc.140 ft. over N. slope.

35.85 Wash, 5 lks.wide, course SW. Asc.43 ft. over SE.slope.

39.20 Spur, bears SW. Asc. slightly over W. slope to

40.70 Intersect original 1/4 sec.cor.of secs.25 and 30, which is a dead pin oak tree, 10 ins.in diam., marked 1/4 S on W. face, and witnessed by a dead and fallen oak tree, W. 33 lks.dist., blazed but illegibly marked.
 Reconstruct this cor.monument and alter its reference as follows:
 alongside the tree cor., on its W. side, set an iron post, 3 ft.long, 1 in.in diam., 24 ins.in the ground,

14 Resurvey of the East Bdy. of T.13 N., R.2 W.

Chains for $\frac{1}{4}$ sec.cor.of sec.25 only, with brass cap marked

$\frac{1}{4}$ S25

1930

from which

a yellow pine, 14 ins.in diam., brs. S.43°W., 49 lks. dist., marked $\frac{1}{4}$ S25 BT

a yellow pine, 18 ins.in diam., brs. N.13°W., 21 lks. dist., marked $\frac{1}{4}$ S25 BT

Thence

N.0°52'E., on true line, on E. bdy.of sec.25 (N. $\frac{1}{4}$)

Over mountainous land, thru dense timber & undergrowth.

Across patented mineral land, M.S.No.1752.

Desc. 23 ft. over NW.slope.

- 1.40 Wash, 5 lks.wide, course SW.from N. Asc.70 ft.in wash.
- 4.40 Leave wash, course S. from NW. Asc.98 ft.over S.slope
- 7.35 Telephone line, brs. N.30°W.-S.30°E.
- 13.04 Intersect N.end line(4-5) of "Gold Trail" pat.lode mining claim, M.S.1752, at 4.11 chs.N.78°45'E. from Cor.No.5. Leave patented mineral land.
- 15.13 Intersect S. end line(4-1) of "Cornucopia" pat.lode mining claim, M.S.1572, at 4.55 chs.N.74°38'E. from Cor. No.1. Retracement of this claim, hereinafter described fails to locate Cor.No.4, therefore the bearing of S. end line is assumed parallel to that obtained for the N. end line.
- Thence across patented mineral land.
- 15.60 Road, Prescott to "Midnite Test" mine, brs. NW.-SE.
- 17.10 Electric power transmission line, brs. NW.-SE.
- 17.40 Divide, brs. E.-W. Desc.275 ft.over steep N.slope.
- 25.10 Wire fence belonging to City of Prescott, brs.NW.-SE.
- 28.25 Change from N. to W.slope. Continue descent.
- 35.84 Intersect point of original location of the cor.of secs. 19, 24, 25 and 30, determined from one of the original bearing trees: an oak, 10 ins.diam., S.28°W., 75 lks. dist., marked TXIIN RIW SXXV
No trace of original SE. bearing tree can be found. Reconstruct this cor.monument and alter its reference as follows: at original point of location; set an iron post, 3 ft.long, 2 ins.in diam., 24 ins.in the ground, for cor.of secs.24 and 25 only, with brass cap marked

T13N

S24

S25

R2W

1930

from which

a yellow pine, 18 ins.in diam., brs. S.52 $\frac{1}{2}$ °W., 83 lks. dist., marked T13N R2W S25 BT

a yellow pine, 8 ins.in diam., brs. N.77°W., 82 lks. dist., marked T13N R2W S24 BT

Land, mountainous. Soil, rocky, 4th rate.

Timber, yellow pine, oak and juniper.

Undergrowth, cacti, catclaw and scrub oak.

N.2°34'W., on true line, on E. bdy. of sec.24.

Over mountainous land, thru dense timber & undergrowth.

Across pat. mineral land, M.S.1572.

Desc. 344 ft. over steep NW. slope.

- 0.27 Intersect N. end line(2-3) of "Cornucopia" pat.lode mining claim, M.S.1572, at 79 lks.S.74°38'W. from Cor. No.3 thereof. Leave patented mineral land.
- 10.00 Wash, 10 lks.wide, course NE. Asc.32 ft. over SE.slope.
- 26.00 Spur, brs. NE. Desc. 96 ft. over NW. slope.
- 29.00 Wash, 10 lks.wide, course NE. Asc.23 ft. over SE. slope
- 35.00 Change to E. slope. Desc. 14 ft. to

Resurvey of the East Bdy. of T. 13 N., R. 2 W. 15

Chains

42.45 (Proportionate point) set an iron post 3 ft. long, 1 in in diam., 24 ins. in the ground for the reestablished $\frac{1}{4}$ sec. cor. of sec. 24, T.13 N., R.2 W., only, with brass cap marked

$\frac{1}{4}$ S24

1930

from which, a yellow pine, 10 ins. in diam., brs. S.27 $\frac{1}{2}$ °W., 19 lks. dist., marked $\frac{1}{4}$ S24 BT a yellow pine, 8 ins. in diam., brs. N.44 $\frac{1}{4}$ °W., 12 lks. dist., marked $\frac{1}{4}$ S24 BT

Along level east slope.

- 42.60 Spur, brs. NE. Desc. 80 ft. over NW slope.
- 45.90 Wash, 10 lks. wide, course NE. Asc. 99 ft. over SE slope.
- 51.30 Spur, brs. NE. Desc. 85 ft. over NW slope.
- 55.75 Wash, 10 lks. wide, course NE. Asc. 38 ft. over S. slope.
- 58.20 Spur, brs. East. Desc. 23 ft. over N. slope.
- 59.20 Wash, 5 lks. wide, course SE. Asc. 167 ft. over S. slope.
- 70.20 Ridge, brs. E-W. Desc. 52 ft. over N. slope.
- 72.80 Head of wash, course NE. Desc. 14 ft. over E. slope to
- 84.90 (Proportionate point) set an iron post 3 ft. long, 2 ins. in diam., 20 mins. in the ground to bedrock, raise a mound of stone about post, for the reestablished cor. of secs. 13 and 24, T.13 N., R.2 W., only, with brass cap marked

T13N
S13
S24
R2W

1930

from which, a yellow pine, 9 ins. in diam., brs. N.12°W., 37 lks. dist., marked T13N R2W S13 BT a yellow pine, 8 ins. in diam., brs. S.17°W., 26 lks. dist., marked T13N R2W S24 BT

Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush, manzanita, catclaw & cacti.

N.2°34'W., on true line, on E. Bdy. of sec.13.
Over mountainous land, thru thick timber & undergrowth.
Desc. 51 ft. over NW slope.

- 1.90 Wash, 10 lks. wide, course NE. Asc. 44 ft. over SE slope.
- 5.20 Spur, brs. E. Desc. 84 ft. over N. slope.
- 8.90 Wash, 10 lks. wide, course SE. Asc. 263 ft. over S. slope.
- 23.30 Ridge, brs. E-W. Desc. 168 ft. over NW slope.
- 33.20 Spur, brs. NW. Desc. 120 ft. over NE slope.
- 42.45 (Proportionate point) set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of sec. 13, T.13 N., R.2 W., only, with brass cap marked

$\frac{1}{4}$ S13

1930

from which, an oak, 5 ins. in diam., brs. S.4°W., 37 lks. dist., marked $\frac{1}{4}$ S13 BT

Chains

a pine, 8 ins. in diam., brs. N.59°W., 19 lks. dist., marked 1/4 S 13 BT

Desc. 26 ft. over NE slope.

49.50 wash, 5 lks. wide, course NW. Asc. gradual SW slope.

50.40 Spur, brs. NW. Desc. 6 ft. over NE slope.

51.60 wash, 10 lks. wide, course NE. Asc. 13 ft. over SE slope.

53.65 Spur, brs. E. Desc. 36 ft. over N. slope.

55.40 wash, 10 lks. wide, course E. Asc. 68 ft. over S. slope.

58.50 Spur, brs. E. Desc. 24 ft. over N. slope.

64.10 Wash, 10 lks. wide, course E. Asc. 119 ft. over SE slope.

70.90 Ridge, brs. NE-SW. Desc. 204 ft. over N. slope to

79.10 Wash, 5 lks. wide, course NE. Asc. gradual SE slope.

79.90 Spur, brs. E. Desc. 21 ft. over gradual N. slope to

81.40 Wash, 5 lks. wide, course SE. Asc. 41 ft. over SE slope.

84.90 (Proportionate point) set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, deposit a stone, marked with a cross (X) at base of post, raise a mound of stone about post, for the reestablished cor. of secs. 12 and 13, T.13 N., R.2 W., only, with brass cap marked

T13N
S12
S13
R2W

1930 from which,

a juniper, 8 ins. in diam., brs. S.84°W., 71 lks. dist., marked T13N R2W S13 BT
No other bearing tree available.

Land, mountainous.

soil, rocky 4th. rate.

timber, yellow pine, oak and juniper.

Undergrowth, oakbrush, manzanita and cacti.

N.2°34'W., on true line, on E. Bdy. of sec. 12.

Over mountainous land, thru scattering timber and dense undergrowth.

Asc. 90 ft. over S. slope.

5.40 Ridge, brs. NE-SW. Desc. 126 ft. over NW slope.

8.30 Wash, 10 lks. wide, course NE. Continue descent.

11.65 Wash, 10 lks. wide, course NE. Asc. 28 ft. over SW slope.

13.90 Spur, brs. E. Desc. 22 ft. over N. slope.

15.65 wash, 10 lks. wide, course E. Asc. 61 ft. over S. slope.

19.90 Spur, brs. East. Desc. 34 ft. over N. slope.

23.45 wash, 10 lks. wide, course E. Asc. 100 ft. over SE slope.

33.90 Ridge, brs. NE-SW. Desc. 197 ft. over N. slope.

42.45 (Proportionate point) set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, deposit a stone marked with a cross (X) at base of post, raise a mound of stone about post, for the reestablished 1/4 sec. cor. of sec. 12, T. 13 N., R.2 W., only, with brass cap marked

1/4 S12


1930

No bearing trees available.

Chains

- ✓ 44.60 Desc. 44 ft. over N. slope.
- ✓ 49.00 Wash, 10 lks. wide, course NE. Asc. 25 ft. over S. slope.
- ✓ 52.55 Spur, brs. E. desc. gradual NE slope.
- ✓ 53.15 Wash, 10 lks. wide, course SE. Asc. 130 ft. over S. slope.
- ✓ 58.30 Old road, brs. NW-SE. Old tunnel on line.
- ✓ 68.50 Ridge, brs. NE and W. Desc. 112 ft. over NW slope.
- ✓ 70.90 Wash, 10 lks. wide, course NE. Asc. 19 ft. over S. slope.
- ✓ 75.75 Spur, brs. E. Desc. 43 ft. over N. slope.
- ✓ 84.00 Wash, 10 lks. wide, course E. Asc. 51 ft. over S. slope.
- ✓ 84.90 Ridge, brs. E-W. Desc. 6 ft. over N. slope to


Intersect the original cor. of secs. 1, 36, 7 and 12, which is a stone 8 x 10 x 12 ins. above ground, marked with 1 and 5 grooves on N. and S. faces, respectively, firmly set in a mound of stone; no bearing trees. Reconstruct this cor. monument and alter its reference as follows:
 Alongside original cor. stone, set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the reconstructed cor. of secs. 1 and 12, T. 13 N., R. 2 W., only, with brass cap marked



1930 from which,
 a juniper, 12 ins. in diam., brs. S. 48° W., 91 lks. dist., marked T13N R2W S12 BT
 a pinion, 6 ins. in diam., brs. N. 85° W., 100 lks. dist., marked T13N R2W S1 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, oak, pine and juniper.
 Undergrowth, oakbrush, manzanita, catclaw and cacti.

-
- 0.18 N. 0° 22' E., on true line, on E. bdy. of sec. 1 (S. 1/2)
 Over mountainous land, thru scattering timber & undergrowth.
 Over gradual NW slope.
 - 9.40 Intersect cor. of wire fences, which br. N. and W.
 Desc. 133 ft. over NW slope.
 - 38.60 Wash, 10 lks. wide, course NE. Asc. 70 ft. over SE slope.
 - 40.61 Ridge, brs. NE-SW. Desc. gradual NW slope to
 Intersect the original 1/4 sec. cor. of secs. 1 and 6, which is a stone 6 x 8 x 10 ins. above ground, firmly set and marked 1/4 on W. face. No bearing trees.
 Reconstruct this cor. monument and alter its reference as follows:
 Alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in ground to bedrock, raise a mound of stone about post, for the reconstructed 1/4 sec. cor. of sec. 1, with brass cap marked




1930 from which,

Chains

a pinion, 6 ins. in diam.; brs. S. $29\frac{1}{4}^{\circ}$ W.; 234 lks. dist.; marked $\frac{1}{4}$ S1 B1
 a cedar; 6 ins. in diam., brs. N. $27\frac{1}{2}^{\circ}$ W.; 80 lks. dist.; marked $\frac{1}{4}$ S1 B1
 A house, brs. N. $73\frac{1}{4}^{\circ}$ W., about 10 chs. dist.
 A barn, brs. N. 62° W., 13 chs. dist.

Thence;
 N. $2^{\circ}15'$ W., on true line, on E. bdy. of sec. 1, ($N\frac{1}{2}$)
 Desc. 253 ft. over N. slope, along wire fence.
 Wash, 10 lks. wide, course E. Asc. 57 ft. over SE slope.
 road, brs. E-W.
 Spur, brs. East. Desc. 34 ft. over N. slope.
 Cor. of wire fence, brs. S. and E.
 Wire fence, brs. W. and NE.
 wash, 10 lks. wide, course E. Asc. gradual S. slope to
 intersect the original cor. of Ts. 13 and 14 N., Rs. 1
 and 2 W., which is a stone 10 x 12 x 12 ins. up,
 firmly set, marked with six grooves on N, S, E, and
 W. faces. No bearing trees.

reconstruct this cor. monument as follows:
 Alongside the original cor. stone, set an iron post 3 ft.
 long, 3 ins. in diam., 24 ins. in the ground, for the
 cor. of Ts. 13 and 14 N., R. 1 & 2 W., with brass
 cap marked



T13N
 1930

No bearing trees available; raise a mound of stone
 4 ft. base, 2 ft. high W. of cor. 3 ft. distant.

Land, mountainous.
 Soil, rocky 4th. rate.
 timber, oak, pinion and juniper, some yellow pine.
 Undergrowth, oakbrush, manzanita, catclaw and cacti.

- ✓ 18.20
- ✓ 24.18
- ✓ 27.18
- ✓ 35.78
- ✓ 35.88
- ✓ 36.60
- 39.18

Resurvey of the West Bdy. of T. 13 N., R. 2 W. 19

Chains

The West bdy. of T. 13 N., R. 2 W., was surveyed by O.H. Case, U.S.D.S., in 1871, establishing corners thereon with a common reference to areas on both sides of the line. In 1927, Sidney E. Blout, U.S.C.E., in connection with the reestablishment of the SW. cor. of T. 13 N., R. 2 W., retraced the S. half of the W. bdy. of said T., found and reconstructed the original cor. of secs. 13, 18, 19 and 24, retaining its original area reference. No other retracements or resurvey is of record.

The following notes describe a dependent resurvey of the W. Bdy. of T. 13 N., R. 2 W., reestablishing missing cors. by proportionate method and reconstructing defective original cors. thereon, with reference to areas on the east side of the line only.

Retracement for Resurvey.

From the original cor. of Ts. 13 and 14 N., Rs. 2 and 3 W., hereinafter described.

39.80 South, on a random line, on the west bdy. of sec. 6. Find no trace of the original $\frac{1}{4}$ sec. cor. of secs. 1 & 6, after diligent search. Continue line and measurement.
76.59 Fall 1.47 chs. east of the original cor. of secs. 1, 6, 7 and 12.
True course and dist. of the west bdy. of sec. 6 are therefore N.1°06'E., 76.60 chs.

38.50 South, on a random line, on W. bdy. of sec. 7 ($N\frac{1}{2}$) Fall 32 lks. west of the original $\frac{1}{4}$ sec. cor. of secs. 7 and 12.
True course and dist. of the $N\frac{1}{2}$ of W. bdy. of sec. 7 are therefore N.0°29'W., 38.50 chs.

38.65 Thence, South, on a random line, on W. bdy. of sec. 7 ($S\frac{1}{2}$) Fall 73 lks. west of the original cor. of secs. 7, 12, 13 and 18.
True course and dist. of the $S\frac{1}{2}$ of W. bdy. of sec. 7 are therefore N.1°05'W., 38.66 chs.

40.00 South, on a random line, on W. bdy. of sec. 18. Find no trace of the original $\frac{1}{4}$ sec. cor. of secs. 13 and 18, after diligent search.
84.34 Fall 1.96 chs. west of the original reconstructed cor. of secs. 13, 18, 19 and 24.
True course and dist. of the west bdy. of sec. 18 are therefore N.1°20'W., 84.36 chs.

239.82 South, on a random line, on the south half of the W. bdy. of T. 13 N., R. 2 W., making diligent search at record intervals but find no trace of any original cor., until at Fall 9.35 chs. west of reestablished std. cor. of T. 13 N., R. 2 W. (SW. cor.) and cor. of T. 13 N., R. 3 W. (SE. cor.).
True course and dist. of this part of the W. bdy. of T. 13 N., R. 2 W., are therefore N.2°14'W., 240.00 chs., which, to maintain original proportion bet. cor. intervals, gives six intervals of 40.00 chs. each for the reestablishment of the missing cors. thereon.

Chains

Re-Survey.

From the reestablished ~~Std. cor. of T. 13 N., R. 2 W. (SW. cor.) and cor. of T. 13 N., R. 2 W. (SE. cor.)~~ heretofore described, N.2°14'W., on a true line, on W. bdy. of sec. 31. Over mountainous land, thru scattering timber and dense undergrowth.

- 2.50 Along level W. slope.
- 12.50 Ridge, brs. NW and SE. Asc. gradual SE slope.
- 27.80 Spur, brs. E. Desc. 157 ft. over rolling NE slope.
- 30.00 Wash, 10 lks. wide, course SE. Asc. 52 ft. over SW slope.
- 32.90 Spur, brs. SE. Desc. 19 ft. over NE slope.
- 37.20 Wash, 10 lks. wide, course SE. Asc. 74 ft. over SW slope.
- 40.00 Spur, brs. SE. Desc. 43 ft. over NE slope to
- Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the reestablished $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap marked

$\frac{1}{4}$ S31

1930 from which, a juniper, 8 ins. in diam., brs. N.32°E., 52 lks. dist., marked $\frac{1}{4}$ S 31 BT
No other bearing tree available, raise a mound of stone 4 ft. base 2 ft. high east of cor. 3 ft. dist.

- 47.90 Desc. 41 ft. over NE slope.
- Wash, 20 lks. wide, course SE, small stream of running water in center. Asc. 441 ft. over steep SW slope.
- 61.60 White Spar Highway, brs. E-W.
- 66.70 Spur, brs. SE. Desc. 58 ft. over NE slope.
- 74.00 Head of wash, course SE. Asc. 140 ft. over SW slope.
- 79.30 Spur, brs. SE. Desc. 10 ft. over NE slope to
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, deposit a stone marked with a cross (+) at base of post, raise a mound of stone about post for the reestablished cor. of secs. 30 and 31, only, with brass cap marked

T13N
S30
S31
R2W

1930 from which, a juniper, 8 ins. in diam., brs. N.25 $\frac{1}{4}$ °E., 214 lks. dist., marked T13N R2W S30 BT
No other bearing tree available.

Land, mountainous.
Soil, rocky 4th. rate.
Timber, oak, pinion and juniper.
Undergrowth, oakbrush, catclaw and cacti.

-
- N.2°14'W., on true line, on W. bdy. of sec. 30.
 - Over mountainous land, thru scattering timber & undergrowth.
 - Desc. 177 ft. over NE slope.
 - 7.70 White Spar Highway, brs. E-W.
 - 9.30 Wash, 10 lks. wide, course E. Asc. 34 ft. over S. slope.
 - 13.00 Spur, brs. E. Desc. 151 ft. over N. slope.

Chains

18.70 Wash, 20 lks. wide, course SE. Asc. gradually up wash.
 19.90 Leave wash, from NE. Asc. 61 ft. over S. slope.
 22.00 Spur end, from W. Desc. 21 ft. over N. slope.
 22.90 Same wash as above noted; course E.
 Asc. 103 ft. over rolling SW slope to
 31.65 Spur, slopes W. Desc. 18 ft. over NW slope.
 32.65 Same wash, course SW. Asc. 158 ft. over S. slope to cor.
 35.30 White Spar Highway, brs. E-W.
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in
 the ground for the $\frac{1}{4}$ sec. cor. of sec. 30 only, with
 brass cap marked

$\frac{1}{4}$ S 30

1930 from which,
 a juniper, 10 ins. in diam., brs. S.29 $\frac{1}{4}$ °E., 126 lks.
 dist., marked $\frac{1}{4}$ S 30 BT
 No other bearing tree available, raise a mound of stone
 3 ft. base, 2 ft. high E. of cor. 3 ft. dist.

Asc. 60 ft. over rolling SW slope.
 62.00 Ridge, brs. NW and SE. Desc. 16 ft. over NE slope.
 67.60 Head of wash, course SE. Asc. 24 ft. over SW slope.
 70.30 Spur, brs. SE. Desc. 135 ft. over NE slope.
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 22 ins. in
 the ground to bedrock, raise a mound of stone about
 post, for the cor. of secs. 19 and 30 only, with
 brass cap marked

T13N
S19
S30
R2W

1930 from which,
 a juniper, 8 ins. in diam., brs. N.77 $\frac{1}{4}$ °E., 208 lks.
 dist., marked T13N R2W S19 BT
 an oak, 6 ins. in diam., brs. S.54°E., 108 lks.
 dist., marked T13N R2W S30 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, oak, pine and juniper.
 Undergrowth, oakbrush, manzanita, catclaw and cacti:

N.2°14'W., on true line, on W. bdy. of sec. 19.
 Over mountainous land, thru thick timber & undergrowth.
 Desc. gradual N. slope.
 .70 Head of wash, course E. Asc. 78 ft. over S. slope.
 5.20 Spur, brs. SE. Desc. 58 ft. over NE slope.
 19.80 Spur, brs. NE. Desc. 266 ft. over NW slope.
 30.40 Wash, 20 lks. wide, course NE. Asc. 163 ft. over SE slope.
 38.00 Spur, brs. NE. Desc. 25 ft. over NW slope.
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 16 ins. in
 the ground to bedrock, deposit a stone marked with a
 cross (X) at base of post, raise a mound of stone
 about post, for the $\frac{1}{4}$ sec. cor. of sec. 19 only,
 with brass cap marked

Chains

1/4 S19

1930 from which,
a yellow pine, 8 ins. in diam., brs. S. 64° E., 40 lks.
dist., marked 1/4 S. 19 BT.

42.60 Desc. 115 ft. over steep NW slope.
Wash, 20 lks. wide, course NE. Asc. 195 ft. over SW slope.
57.00 Spur, brs, SE. Asc. 132 ft. over SE slope.
70.00 Same spur, brs. SW. Asc. 19 ft. over SW slope to
80.00 intersect the original reconstructed cor. of secs. 13, 18,
19 and 24, which is an iron post 2 ins. in diam.,
firmly set, projecting 20 ins. above ground and mound
of stone, with brass cap properly marked. Alongside
cor. post is a granite stone 8 x 14 x 6 ins. above
mound, with three notches on S. and N. edges, respec-
tively.
No bearing trees.
Alter this cor. monument to refer to Secs. 18 and 19 only,
by changing markings on brass cap to read:

T13N
S18
S19
R2W

1930

Land, mountainous.
Soil, rocky 4th. rate.
Timber, pine, oak and juniper.
Undergrowth, oakbrush, manzanita, catclaw and cacti.

14.40 N. 1° 20' W., on true line, on W. bdy. of sec. 18.
Over mountainous land, thru thick timber & undergrowth.
Asc. 192 ft. over SW slope.
33.10 West edge of peak, on ridge, which brs. E-W. Desc. 390
33.50 ft. over N. slope.
wash, 10 lks. wide, course NW. Asc. gradual SW slope.
42.18 Spur, brs. west. Desc. 74 ft. over N. slope.
(Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
20 ins. in the ground to bedrock, deposit a rock
marked with a cross (+) at base of post, raise a mound
of stone about post, for the 1/4 sec. cor. of sec. 18
only, with brass cap marked


1/4 S18

1930 from which,
a yellow pine, 14 ins. in diam., brs. N. 48° E., 17 lks.
dist., marked 1/4 S18 BT
No other bearing tree available.

Desc. 54 ft. over N. slope.

Chains

44.95 road, brs. NW-SE.
 45.45 Wash, 10 lks. wide, course West. Asc. 27 ft. over SW slope.
 49.85 Spur, brs. west. Desc. 54 ft. over N. slope.
 51.75 Wash, 10 lks. wide, course West. Asc. 35 ft. over S. slope.
 55.40 Thence along W. slope.
 61.65 Telephone line, brs. N. $59\frac{1}{2}^{\circ}$ E. - S. $59\frac{1}{2}^{\circ}$ W.
 62.85 Spur, brs. west. Desc. 54 ft. over N. slope.
 68.75 Old road, brs. NE-SW.
 69.10 Wash, 10 lks. wide, course West.
 - 70. Asc. gradual SW slope.
 70.35 Spur, brs. NW. Desc. 54 ft. over NE slope.
 73.45 Wash, 10 lks. wide, course NW. Asc. 53 ft. over SW slope.
 77.40 Power line, brs. S. $49\frac{1}{2}^{\circ}$ W. - N. $49\frac{1}{2}^{\circ}$ E.
 80.40 Ridge, brs. NW-SE. Asc. 40 ft. over SE slope.
 84.36 Intersect the cor. of secs. 7, 12, 13 and 18, which is a stone 10 x 10 x 8 ins. loosely set in mound of stone, marked with the and four grooves on N. and S. edges respectively, from which, a stump of pine tree, 3 ft. in diam., 2 ft. above ground, brs. S. $74\frac{1}{2}^{\circ}$ E., 73 lks. dist., some scribe marks are on scattered portions of the face of this tree. No trace of record NW bearing tree now remains. Reconstruct this cor. monument and alter its reference as follows:
 Alongside the original cor. stone, set an iron post 3 ft. long, 2 ins. in diam., 16 ins. in the ground to bed-rock, raise a mound of stone about post, for the reconstructed cor. of secs. 7 and 18 only, with brass cap marked



1930 from which,
 a yellow pine, 14 ins. in diam., brs. N. 36° E., 23 lks. dist., marked T13N R2W S7 BT
 a yellow pine, 9 ins. in diam., brs. S. 49° E., 19 lks. dist., marked T13N R2W S18 BT
 Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita and cacti.

N. $1^{\circ}05'$ W., on true line, on W. bdy. of sec. 7, (S $\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth.
 Asc. 7 ft. over SE slope.
 2.00 Ridge, brs. NE-SW. Desc. 150 ft. over steep NW slope.
 7.50 Wash, 10 lks. wide, course NE. Asc. 13 ft. over SE slope.
 13.00 Spur, brs. NE. Desc. 52 ft. over NW slope.
 14.20 Wash, 10 lks. wide, course NE. Asc. 6 ft. over SE slope.
 15.00 Spur, brs. NE. Desc. 20 ft. along N. slope.
 19.00 Desc. 90 ft. over NE slope.
 23.10 Wash, 20 lks. wide, course E. Asc. 30 ft. over S. slope.
 24.50 Spur, brs. NE. Desc. 64 ft. over NW slope.
 27.00 Wash, 10 lks. wide, course NE. Asc. 15 ft. over SE slope.
 29.50 Copper Basin road, brs. NE-SW.
 31.60 Spur, brs. NE. Desc. gradual N. slope.
 35.00 Junction of washes from NW-SW thence SE.

Chains

58.66

Asc. 60 ft. over SW slope.
 intersect the original $\frac{1}{4}$ sec. cor. of secs. 7 and 12,
 which is a granite stone 16 x 12 x 8 ins. above ground,
 firmly set in mound of stone, marked $\frac{1}{4}$ on W. face.
 The record bearing trees are gone.
 Reconstruct this cor. monument and alter its reference
 as follows:
 Alongside the original cor. set an iron post 3 ft. long,
 1 in. in diam., 16 ins. in the ground to bedrock,
 raise a mound of stone about post, for the recon-
 structed $\frac{1}{4}$ sec. cor. of sec. 7 only, with brass cap
 marked

$\frac{1}{4}$ S7

1930 from which,
 a yellow pine, 30 ins. in diam., brs. S.71°E., 60 lks.
 dist., marked $\frac{1}{4}$ S7 BT.
 a yellow pine, 10 ins. in diam., brs. N.29°E., 14 lks.
 dist., marked $\frac{1}{4}$ S7 BT

N.0°29'W., on true line, on W.bdy. of sec. 7, ($N\frac{1}{2}$)
 Asc. gradual SW slope.

1.00 Spur, brs. SE. Desc. 42 ft. over NE slope.
 3.35 wire fence, brs. about N. and S. Along same.
 4.20 Wash, 5 lks. wide, course SE. Asc. 35 ft. over SW slope.
 7.80 Spur, brs. E. Desc. 12 ft. over N. slope.
 9.00 Shallow wash, course E. Asc. 26 ft. over gradual S. slope.
 15.05 wire fence, brs. NW-SE.
 16.60 Spur, brs. East. Desc. 133 ft. over N. slope.
 24.30 wire fence, turns to NE.
 26.80 Bottom of canyon, stream of water in same, 20 lks. wide,
 6 ins. deep, course NE. Asc. 176 ft. over steep
 SE slope.

33.00 wire fence, brs. NE-SW.
 37.80 wire fence, brs. NW-SE. (SE about 20 lks. to junction
 with fences from S. and NE.)

38.50 intersect the original cor. of secs. 1, 6, 7 and 12,
 which is a granite boulder 6 ft. x 4 ft. x 4 ft.
 The original marks as well as the bearing trees have
 gone, but this cor. monument was identified by
 John Dieruff, for many years owner of land adjacent
 to this cor.

Reconstruct this cor. monument and alter its reference
 as follows:

On top of boulder set a brass cap 3 ins. in diam., cem-
 ented firmly in place, for the reconstructed cor.
 of secs. 6 and 7, marked

T13N
 S6
 S7
 R2W

1930 from which,
 a juniper, 20 ins. in diam., brs. S.64°E., 33 lks.
 dist., marked T13N R2W S7 BT
 a 3 in. cross chiseled in SW face of large boulder
 brs. N.16°E., 52 lks. dist. Add BO S6.
 No other bearing tree available.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, pine, oak & juniper.
 Undergrowth, oak, manzanita, cacti.

Resurvey of the West Bdy. of T. 13 N., R. 2 W.

chains	<p>N.1° 6'E., on true line; on W. bdy. of sec.6. Over mountainous land; thru scattering timber and undergrowth. Desc. 18 ft. over NE. slope. 10.10 Spur, brs. E. Continue gradual descent along E.slope. 12.60 Old road, brs. NW.-SE: 21.60 Spur, brs. NE. Desc. 95 ft. over NW. slope. 32.05 Wash, 20 lks.wide, course NE. Asc.42 ft. over SE.slope. 37.00 Spur, brs. NE. Desc.gradually over NW. slope to</p> <p>38.40 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. in diam., 16 ins.in the ground to bedrock, deposit a stone marked with a cross(X) at base of post, and raise a mound of stone around post, for reestablished W. $\frac{1}{4}$ sec.cor.of sec.6, with brass cap marked</p> <p style="text-align: center;"> $\frac{1}{4}$ S6 1930</p> <p>from which a juniper, 4 ins. diam., brs. N:52$\frac{1}{4}$°E., 16 lks. dist., marked $\frac{1}{4}$ S6 BT No other bearing tree available.</p> <p>Desc. 67 ft. over NE. slope. 44.00 Wash, 20 lks.wide, course NE. Asc.23 ft. over SE.slope. 44.70 Spur, brs. E. Desc.24 ft. over N. slope. 47.50 Wash, 20 lks.wide, course SE. Stream of water, 10 lks. wide, 5 ins.deep, course SE. Asc. 70 ft. over S. slope. 50.80 Spur, brs. NE. Desc. 109 ft. over NW. slope. 51.30 Trail, brs E.-W. 59.40 Wash, 20 lks.wide, course NE. Asc. 30 ft. over SE. slope. 61.00 Spur, brs. E. Desc. 11 ft. over N. slope. 62.70 Wash, 10 lks.wide, course SE. Asc.135 ft. over SW.slope. 71.00 Spur, brs. SE. Desc. 30 ft. over NE. slope. 75.15 Wash, 10 lks.wide, course E. Asc. 14 ft. over gradual S. slope to</p> <p>76.60 Intersect the original cor. of Ts.13 and 14 N., Rs.2 and 3 W., hereinafter described.</p> <p>Land, mountainous. Soil, rocky, 4th rate. Timber, pine, oak, pinion and juniper. Undergrowth, scrub oak, manzanita, cacti and catclaw.</p> <hr style="border-top: 1px dashed black;"/>
--------	--

chains

The North Bdy. of T. 13 N., R. 2 W. was surveyed by S.W. Foreman, U.S.D.S. in 1871, establishing all cors. thereon with a common reference to areas both sides of the line.

In 1928, S.E. Blout, U.S.C.E. retraced and resurveyed the east half of said Tp. bdy., reestablishing the cor. of secs. 2, 3, 34 & 35 and the cor. of secs. 3, 4, 33 & 34, and reconstructing the cor. of secs. 1, 2, 35 & 36, retaining the original common reference of such cors.

No other retracement or resurvey of any part of this Tp. bdy. is of record.

The following notes describe a dependent resurvey of the entire bdy., reestablishing missing original cors. by proportion, and reconstructing all defective original cors., retaining original reference of all cors.

Retracement for Resurvey.

From the reconstructed original cor. of Ts. 13 and 14 N., Rs. 1 and 2 W., hereinbefore described,

S. 83° 4' W., (1928 retracement record) on random line,
bet. secs. 1 and 36 (E. $\frac{1}{4}$)

40.27 Intersect original $\frac{1}{4}$ sec. cor.

True course and dist. are therefore, N. 83° 4' E., 40.27 chs.
Thence,

S. 86° 30' W., (1928 retracement record) on random line,
bet. secs. 1 and 36 (W. $\frac{1}{4}$)

38.33 Intersect the reconstructed original cor. of secs. 1, 2,
35 and 36.

True course and dist. are therefore, N. 86° 30' E., 38.33 chs.

S. 89° 35' W., (1928 resurvey record) on random line,
bet. secs. 2 and 35.

40.00 Find no trace of original $\frac{1}{4}$ sec. cor. Set temp. $\frac{1}{4}$ sec. cor.
Continue line and measurement.

79.30 Intersect reestablished cor. of secs. 2, 3, 34 and 35.

True course and dist. are therefore, N. 89° 35' E., 79.30 chs.

S. 89° 35' W., (1928 resurvey record) on random line,
bet. secs. 3 and 34.

40.00 Find no trace of original $\frac{1}{4}$ sec. cor. Set temp. $\frac{1}{4}$ sec. cor.
Continue line and measurement.

79.30 Intersect reestablished cor. of secs. 3, 4, 33 and 34.

True course and dist. are therefore, N. 89° 35' E., 79.30 chs.

West, on random line, bet. secs. 4 and 33.

Along center of Gurley St., City of Prescott, Ariz.

40.00 Find no trace of original $\frac{1}{4}$ sec. cor.

This point is in the pavement of Gurley St. at bend of St. from E. to N. 84° W., and at intersection with Fleury Ave. which extends N. herefrom. Westerly from this point Gurley St. is designated as Gurley Avenue, according to 1930 map of Prescott, Ariz.

At about 10 chs. W. the random line enters Block 6 of Fleury Addition and is obstructed by buildings, fences and other improvements which render chaining on said line impracticable, therefore traverse to the objective sec. cor. as follows:

mark 40.00 ch. point in random line by a cross on the pavement,
Thence

N. 84° 00' W., 16.37 chs. along Gurley Ave. to its intersection with N. end of Park Ave.

Thence

chains S. 6° 00' W., 5.38 chs. along Park Ave. to its inter-
 section with E. end of Beauvoir
 Terrace.
 Thence
 N. 83° 30' W., 6.41 chs. along Beauvoir Terrace to bend
 in same from S. 83½° E. to N. 48° W.
 Thence
 West 3.34 chs.
 S. 58° 43' W., 5.06 " across Anderson Subdivision to
 N. 72° 31' W., 4.37 " point in Gurley Ave. at E. end
 of Juniper St., and S. end of
 Alto St.
 Thence
 N. 76° 21' W., 2.02 chs. along Juniper St.
 Thence
 N. 56° 50' W., 3.75 chs. to intersection with the accept-
 ed cor. of secs. 4, 5, 32 and 33,
 under a wire fence bearing N.
 and S. along E. side of County
 Road, same bearing, and on the
 western limit of the City of
 Prescott, as per 1930 map.

The latitude and departure of this traverse are, 1.70
 chs. south, and 40.14 chs. west, respectively, there-
 fore the random line extended would at
 80.14 Fall 1.70 chs. N. of accepted cor. of secs. 4, 5, 32 & 33.
 True course and dist. are therefore, N. 88° 47' E., 80.16 chs.

West, on random line, bet. secs. 5 and 32 (E. ¼)
 39.91 Fall 58 lks. N. of original ¼ sec. cor.
 True course and dist. are therefore, N. 89° 10' E., 39.91 chs.
 Thence,


West, on random line, bet. secs. 5 and 32 (W. ¼)
 39.91 Fall 58 lks. N. of original cor. of secs. 5, 6, 31 and 32.
 True course and dist. are therefore, N. 89° 10' E., 39.91 chs.

West, on random line, bet. secs. 6 and 31 (E. ¼)
 40.06 Fall 40 lks. N. of original ¼ sec. cor.
 True course and dist. are therefore, N. 89° 26' E., 40.06 chs.
 Thence

West, on random line, bet. secs. 6 and 31 (W. ¼)
 39.39 Fall 77 lks. N. of original cor. of Ts. 13 and 14 N.,
 Rs. 2 and 3 W.
 True course and dist. are therefore, N. 88° 53' E., 39.40 chs.

Resurvey.

The original cor. of Ts. 13 and 14 N., Rs. 2 and 3 W. is a
 granite stone 20x14x10 ins. above ground, firmly set
 in ground and mound of stone, and marked with 6 grooves
 on each of E., W., N. and S. faces. No bearing trees.
 Reconstruct this cor. monument as follows:
 remove the mound of stone, and alongside old cor. stone,
 set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the
 ground to bedrock, and raise a mound of stone around
 post, for cor. of Ts. 13 & 14 N., Rs. 2 & 3 W., with brass
 cap marked



1930

from which
 a juniper, 10 ins. diam., brs. N. 74½° E., 34 lks.
 dist., marked T14N R2W S31 BT

chains

a juniper, 14 ins. diam., brs. S. $15\frac{3}{4}^{\circ}$ E., 181 lks.
dist., marked T13N R2W S6 BT
a pinion, 12 ins. diam., brs. S. $54\frac{1}{2}^{\circ}$ W., 156 lks.
dist., marked T13N R3W S1 BT
a juniper, 14 ins. diam., brs. N. 3° W., 29 lks.
dist., marked T14N R3W S36 BT
Thumb Butte bears N. 20° W.

Thence

N. $88^{\circ}53'$ E., on true line, bet. secs. 6 and 31 (W. $\frac{1}{4}$)
Over mountainous land, thru scattering timber and under-
growth.

Desc. gradually over NE. slope.

3.00 Wash, 10 lks. wide, course SE. Asc. 9 ft. over SW. slope.
7.30 Spur, brs. SE. Desc. 16 ft. over E. slope.
9.30 Wash, 10 lks. wide, course S. Asc. 21 ft. over W. slope.
11.00 Spur, brs. S. Desc. 16 ft. over NE. slope.
15.80 Wash, 10 lks. wide, course SE. Asc. 14 ft. over SW. slope.
17.90 Spur, brs. SE. Desc. 14 ft. over rocky E. slope.
37.55 Wire fence, brs. N.-S.

39.40 Intersect the original $\frac{1}{4}$ sec. cor., which is a granite
stone 20x18x6 ins. above ground, firmly set, and marked
 $\frac{1}{4}$ on N. face. No bearing trees.

Reconstruct this cor. monument as follows:

alongside old cor. stone, set an iron post, 3 ft. long,
1 in. diam., 12 ins. in the ground to bedrock, and raise
a mound of stone around post, for $\frac{1}{4}$ sec. cor. of secs.
6 and 31, with brass cap marked

$$\frac{1}{4} \begin{array}{c} S 31 \\ \hline S 6 \end{array}$$

1930

from which

a pinion, 8 ins. diam., brs. N. 23° E., 19 lks.
dist., marked $\frac{1}{4}$ S31 BT
a pinion, 8 ins. diam., brs. S. 82° W., 30 lks.
dist., marked $\frac{1}{4}$ S6 BT

Thence

N. $89^{\circ}26'$ E., on true line, bet. secs. 6 and 31 (E. $\frac{1}{4}$)
Over mountainous land, thru scattering timber and dense
undergrowth.

Desc. 32 ft. over SE. slope.

3.50 Wash, 10 lks. wide, course E. from SW.
Desc. 46 ft. in wash to
10.00 Leave wash, course SE. Enter level land.
14.70 Same wash, course NE. Enter rolling land. Leave dense
undergrowth.
18.16 Wire fence, brs. NW. and S. 88° E.
19.15 Road, brs. E.-W. Thumb Butte Dairy brs. NW. about 2 chs.
dist. Thence along road.
29.50 Electric power transmission line, brs. NW.-SE.
36.20 Leave road, brs. W.-SE.


40.06 Intersect original cor. of secs. 5, 6, 31 and 32, which is
a granite stone 30x20x20 ins., firmly set in a mound
of stone, marked with 1 groove on W. face, and 5 grooves
on E. face, and witnessed by
a yellow pine stump, 3 ft. diam., about 5 ft. high,
S. $12\frac{3}{4}^{\circ}$ E., 44 lks. dist., marked TXIIIN RIIW SV BT
a yellow pine snag, 30 ins. diam., N. 39° W., 35 lks.
dist., marked TXIVN RIIW SXXXI BT

Reconstruct this cor. monument as follows:

remove the mound of stone, and in center on its position
reset old cor. stone on surface rock, and alongside same
set an iron post, 3 ft. long, 2 ins. diam., and raise a
mound of stone around post, for cor. of secs. 5, 6, 31 and
32, with brass cap marked

Resurvey of the North Bdy. of T. 13 N., R. 2 W.

chains




1930

from which
 a 4 in. cross (X) chiseled on SE. face of large granite boulder, brs. N. 60° 40' W., 26 lks. dist., add BO S31.
 an oak, 12 ins. diam., brs. S. 39 1/4° W., 76 lks. dist., marked T13N R2W S6 BT
 a 4 in. cross (X) and BO S5 alongside cross, on NW. face of large boulder, brs. S. 18 1/4° E., 49 lks. dist.
 a 4 in. cross (X) and BO S32 alongside cross, chiseled on SW. face of large boulder, brs. N. 40° E., 18 lks. dist.

This sec. cor. is alongside fence cor., wire fences Land, mountainous, level and rolling. extend E. and S.
 Soil, rocky, 4th rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, scrub oak, manzanita, catclaw and cacti.

- 6.00 Wash, 10 lks wide, course SE. Asc. gradually over SW. slope.
- 14.20 House bears N. about 2.50 chs. dist.
- 16.50 Fence, brs. N.-S.
- 21.90 Telephone line, brs. NE.-SW.
- 22.00 Electric power transmission line, brs. NE.-SW.
- 22.10 Road, brs. NE.-SW.
- 23.25 Fence, brs. N.-S. Joins E.-W. fence about 25 lks. S.
- 26.60 Fence, brs. N.-S. Joins E.-W. fence about 10 lks. S.
- 32.10 Fence, brs. N.-S. Joins E.-W. fence 5 lks. S.
- 32.50 Shallow wash, with small stream of water, course NE. Asc. 30 ft. over W. slope to 1/4 sec. cor.
- 33.60 Fence, brs. N.-S. Joins E.-W. fence 10 lks. S.
- 39.30 Fence cor. brs. S. about 25 lks. dist. from which fences extend W. and S.

39.91 Intersect original 1/4 sec. cor. of secs. 5 and 32, which is a granite stone 8x12x12 ins. above ground, firmly set in ground and mound of stone, and marked 1/4 on N. face. No bearing trees.
 Reconstruct this cor. monument as follows:
 remove the mound of stone, and alongside old cor. stone set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, and raise a mound of stone around post, for 1/4 sec. cor. of secs. 5 and 32, with brass cap marked



1930

from which
 an oak, 14 ins. diam., brs. N. 19° E., 31 lks. dist., marked 1/4 S32 BT
 a yellow pine, 9 ins. diam., brs. S. 67 1/2° E., 13 lks. dist., marked 1/4 S5 BT

- Thence
 N. 89° 10' E., on true line, bet. secs. 5 and 32 (E. 1/4)
 Over rolling land, thru scattering timber and undergrowth.
 Asc. slightly over W. slope.
- 3.00 Spur, brs. N. Desc. 50 ft. over E. slope.
 - 10.00 Old road, brs. NE.-SW.
 - 17.90 Wash, 10 lks. wide, course NW. Road, brs. NW.-SE.
 - 21.00 Road, brs. N.-S.

chains

26.50 Electric power transmission line, brs. NE.-SW.

27.90 Wash, 10 lks.wide, course NE.

32.20 Wire fence, brs. N.-S. Fence cor. brs. S. 3 lks. dist. from which fences extend E. and N.

34.50 Old road, brs. NE.-SW.

35.90 Stone wall, brs. N.-S. Corners with fence from W. at about 20 lks. S.
Thence across yard of Cottage Heights Auto Camp.

39.30 County road, brs. N.-S.

39.91 Intersect the accepted cor. of secs.4,5,32 and 33, which is an iron pipe, 1 in.diam., projecting 8 ins.above the ground, firmly set, under a wire fence bearing N.and S. on the western limit of the City of Prescott, Ariz., as per 1930 city map. A signed statement as to the local recognition of this cor.mon., by Milton Updegraff a settler of long residence in the vicinity, was obtained.
The cor.is witnessed by
a yellow pine, 16 ins.diam., N.60 $\frac{1}{2}$ °E., 18 lks. dist., marked T14N R2W S33 BT
Reconstruct this cor.monument as follows:
alongside the iron pipe, set an iron post, 3 ft.long, 2 ins.diam., 12 ins.in the ground to bedrock, and raise a mound of stone around post, for cor. of secs.4,5,32 and 33, with brass cap marked

T14N	R2W
S32	S33
S5	S4
T13N	

1930

from which
an oak, 6 ins.diam., brs. N.22°W., 21 lks. dist., marked T14N R2W S32 BT
an oak, 6 ins.diam., brs. S.56 $\frac{1}{2}$ °E., 20 lks. dist., marked T13N R2W S4 BT
No other tree available.
a 4 in.cross(X) cut on boulder, brs. S.8°10'W., 20 lks. dist. Mark B0 05 alongside the cross.

Land, rolling.
Soil, rocky, 4th rate. Some, good, 2nd rate.
Timber, pine oak and juniper.
Undergrowth, scrub oak and cacti.

N.88°47'E., on true line, bet. secs.4 and 33.
Over open rolling land, thru the City of Prescott, Ariz.
Measurement to temp. $\frac{1}{4}$ sec.cor.by traverse hereinbefore decided.
Points on true line are given in approximate distances as scaled from 1930 city map.

3.94 Center of Alto St., 50 ft.wide, brs.N.6°E. and S.6°W.

7.40 Center of Gurley Ave., 60 ft.wide, brs.N.47°E.-S.47°W.
Flynn's sanatarium brs. N. about 2 chs. dist.

15.00 Center of Beauvoir Terrace, 50 ft.wide, brs.N.48°W. and S.48°E. Thence across Block 7 of Fleury's Addition, thru buildings, fences and other improvements.

23.00 Center of Park Ave., 75 ft.wide, brs. N.6°E.-S.6°W.
Thence across Block 6 of Fleury's Addition.

30.00 Alley, brs. N.-S.

33.20 Center of Summit Ave., 90 ft.wide, brs.N.-S.
Thence across Block 5 of Fleury's Addition.

From temp. $\frac{1}{4}$ sec.cor.on random line, measure 1.04 chs. S.34°25 $\frac{1}{2}$ 'W. to point on true line at

39.56 East side of wooden fence surrounding the old Territorial Governor's residence.
Set an iron post, 3 ft.long, 1 in. diam., 30 ins.in the

Resurvey of the North Bdy. of T. 13 N., R. 2 W.

chains	<p>ground, with a stone marked with a cross (X) deposited at base of post, for witness cor. to reestablished $\frac{1}{4}$ sec.cor. of secs.4 and 33, with brass cap marked,</p> <div style="text-align: center;"> $\begin{array}{c} S\ 33 \\ \hline \frac{1}{4} \text{---} WC \\ S\ 4 \end{array}$ </div> <p style="text-align: center;">1930</p> <p>No bearing trees available.</p> <p>40.08 True point for reestablishment of the $\frac{1}{4}$ sec.cor. falls in alley, bearing N.-S., near its N. end at intersection with Gurley St., where it is impracticable to monument the cor., therefore witness cor. is established on true line at 52 lks. S. $88^{\circ}47'W$. as described.</p> <p>The east half of the true line bet. secs.4 and 33 crosses Blocks F, E, and 13 of the original townsite of Prescott and buildings and other improvements prevent chaining, therefore points on the true line are given in approximate distances based upon the measurements taken on the random line along the center of Gurley St.</p> <p>42.90 Center of McCormick St., 66 ft. wide, brs. N.-S. Thence across Block E.</p> <p>46.00 Granite Creek, 100 lks. wide, course N.</p> <p>49.10 Center of Granite St., 80 ft. wide, brs. N.-S. Thence across Block 13.</p> <p>55.45 Center of Montezuma St., 100 ft. wide, brs. N.-S. Thence across N. side of Plaza.</p> <p>58.25 Leave the Plaza and enter Gurley St. bearing E.-W.</p> <p>62.20 Center of Cortez St., 100 ft. wide, brs. N.-S. Continue along Gurley St.</p> <p>68.70 Center of Marina St., 100 ft. wide, brs. N.-S.</p> <p>75.13 Center of Alarcon St., 100 ft. wide, brs. N.-S.</p> <p>80.16 Intersect the reestablished cor. of secs. 3, 4, 33 and 34, which is a brass cap, its top set flush with surface of the street pavement, on center line of Gurley St., in line with the W. side of Pleasant St. Cap is marked as recorded in the notes of the 1928 resurvey by S.E. Blout, U.S.C.E.</p> <p>Land, rolling. Soil, gravelly and rocky, 3rd rate. Timber and undergrowth, none.</p> <hr style="border-top: 1px dashed black;"/> <p>N. $89^{\circ}35'E$, on true line, bet. secs. 3 and 34. Over rolling land, thru City of Prescott, Arizona, along center line of Gurley St.</p> <p>0.76 Center of Pleasant St., 100 ft. wide, brs. N.-S.</p> <p>7.20 Center of Mt. Vernon Ave., 100 ft. wide, brs. N.-S.</p> <p>13.63 Center of Virginia St., 100 ft. wide, brs. N.-S.</p> <p>19.01 Center of Washington Ave., 60 ft. wide, brs. N.-S.</p> <p>22.00 City Limit as per 1930 city map, extends S. and E. from this point.</p> <p>Thence along City Limit and center line of Gurley St.</p> <p>25.00 Center of Arizona Ave., 60 ft. wide, extends S.</p> <p>27.72 Center of U.S. Highway No. 89 curving to NE. joins the center line of Gurley St. at this point. Leave center line of Gurley St. Cont. along City Limit.</p> <p>29.69 City limit extends N. and W. from this point. Leave City of Prescott.</p> <p>30.45 Center of Penn Ave., 60 ft. wide, extending S. from U.S. Highway No. 89. Thence across vacant land in Block J of Joslin Subdivision. Enter scattering timber and undergrowth.</p> <p>35.90 Center of Colorado Ave, 60 ft. wide, brs. N.-S. Thence across Block H of Joslin Subdivision.</p> <p>39.65 (Midpoint) Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished $\frac{1}{4}$ sec. cor. of secs. 3 and 34, with brass cap marked</p>
--------	---

chains

$$\frac{1}{4} \frac{S\ 34}{S\ 3}$$

1930

from which

a juniper, 8 ins. diam., brs. S.80°E., 88 lks.
 dist., marked $\frac{1}{4}$ S3 BT
 an oak, 14 ins. diam., brs. N.16 $\frac{1}{2}$ °E., 16 lks.
 dist., marked $\frac{1}{4}$ S34 BT

- 40.00 Center of Crook Ave., 60 ft. wide, bearing N.-S. along
 E. side of Joslin Subdivision.
 40.70 Wash, 5 lks. wide, course NW.
 41.50 Old road, brs. NW.-SE.
 50.39 Electric power transmission line, brs. N.25 $\frac{1}{2}$ °W.-S.25 $\frac{1}{2}$ °E.
 55.35 Road, brs. N.30°W.-S.30°E.
 57.80 Wash, course N. Enter mountainous land.
 Asc. 93 ft. over NW. slope.
 64.80 Spur, brs. N. Desc. 47 ft. over NE. slope to
 74.30 Top of bank, brs. N.-S. Desc. 58 ft. over E. slope.
 77.30 Wash, 50 lks. wide, course N. Enter nearly level bottom
 land.
 78.55 Road, brs. N.-S.10°E.
 78.90 Wire fence, brs. N.-S.
 79.30 Intersect the reestablished cor. of secs. 2, 3, 34 and 35,
 which is an iron post, 2 ins. diam., projecting 9 ins.
 above ground, firmly set, properly marked on brass cap,
 and witnessed by a mound of stone W. of cor.

Land, rolling, mountainous and nearly level.
 Soil, gravelly and rocky, 3rd and 4th rate.
 Timber, pine, oak and juniper.
 Undergrowth, scrub oak and cacti.

N.89°35'E., on true line, bet. secs. 2 and 35.
 Over nearly level land, thru scattering timber and under-
 growth.

- 0.15 Foot of slope, brs. N.-S. Pump and well brs. S. 10 lks.
 dist. Leave nearly level and enter mountainous land.
 Asc. 257 ft. over steep rocky W. slope.
 19.30 Spur, brs. N.20°W. Desc. 155 ft. over E. slope.
 29.65 Ravine, course N. Asc. 79 ft. over W. slope.
 32.39 Wire fence, brs. N.30°W.-S.30°E. Fence cor. brs. S.
 30 lks. dist. from which fences extend E. and N.30°W.
 39.65 (Midpoint) Set an iron post, 3 ft. long, 1 in. diam.,
 18 ins. in the ground to bedrock, and raise a mound of
 stone around post, for reestablished $\frac{1}{4}$ sec. cor. of
 secs. 2 and 35, with brass cap marked

$$\frac{1}{4} \frac{S\ 35}{S\ 2}$$

1930

from which

a pinion, 9 ins. diam., brs. N.43°E., 188 lks.
 dist., marked $\frac{1}{4}$ S35 BT
 a juniper, 12 ins. diam., brs. S.77°W., 151 lks.
 dist., marked $\frac{1}{4}$ S2 BT

- 40.00 Fence cor. from which fences extend S. and S.88°W.
 42.80 Spur, brs. N. Desc. 16 ft. over NE. slope.
 46.14 Ravine, course N.10°W. Asc. 154 ft. over SW. slope.
 47.80 Spur, brs. N.20°W. Desc. 20 ft. over E. slope.
 50.10 Ravine, course N. Asc. 23 ft. over W. slope.
 50.55 Spur, brs. N. Desc. 5 ft. over NE. slope.
 51.38 Ravine, course N. Asc. 101 ft. over W. slope.
 58.30 Spur, brs. N. Desc. 27 ft. over E. slope.
 61.40 Ravine, course N. E. end of wire fence brs. N. 30 lks.
 dist. Asc. 27 ft. over W. slope.


Resurvey of the North Bdy. of T. 13 N., R. 2 W.

chains

- 64.30 Spur, brs. N. Desc. 12 ft. over E. slope
- 67.67 Ravine, course N. Enter dense undergrowth.
Asc. 160 ft. over W. slope to
- 75.80 Point of spur, sloping NW. Asc. 51 ft. over N. slope to
- 79.30 Intersect the reconstructed original cor. of secs. 1, 2, 35 and 36, which is an iron post, 2 ins. diam., projecting 16 ins above ground, firmly set in ground and mound of stone, and properly marked on brass cap.

Land, mountainous.
Soil, gravelly and rocky, 3rd and 4th rate.
Timber, pinion, juniper and oak.
Undergrowth, scrub oak, cacti and catclaw.

- N. 86° 30' E., on true line, bet. secs. 1 and 36 (W. 1/4)
Over mountainous land, thru scattering timber and dense undergrowth. Asc. 120 ft. over NW. slope.
- 5.58 Spur, brs. N. Desc. 103 ft. over E. slope.
- 10.33 Ravine, course NE. Asc. 65 ft. over NW. slope.
- 20.06 Fence cor. from which barbed wire fence extends N. 86 1/2° E. and SW. At 4 chs. SW. this fence turns to SE.
Thence along N. side of fence.
- 20.08 Spur, brs. N. Desc. 212 ft. over E. slope to
- 30.73 Ravine, course NE. Desc. 17 ft. over NE. slope.
- 32.58 Ravine, course N. Asc. 21 ft. over NW. slope to
- 38.33 Spur, brs. N. Intersect the original 1/4 sec. cor. of secs. 1 and 36, which is a granite stone 7x8x8 ins. above ground, firmly set, marked 1/4 on N. face, on N. side of barbed wire fence bearing N. 88 1/2° E. and S. 88 1/2° W.
Reconstruct this cor. monument as follows:
alongside old cor. stone, set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, and raise a mound of stone around post, for 1/4 sec. cor. of secs. 1 and 36, with brass cap marked



1930

No bearing trees available.

- Thence
- N. 83° 4' E., on true line, bet. secs. 1 and 36 (E. 1/2)
Over mountainous land, thru scattering timber and dense undergrowth. Desc. 170 ft. over E. slope.
- 0.02 Barbed wire fence extending N. from fence cor. 2 lks. S. where it joins barbed wire fence bearing N. 88 1/2° E. and S. 88 1/2° W.
- 12.93 Ravine, course NE. Asc. 15 ft. over NW. slope.
- 15.52 Point of spur, sloping N. Desc. 36 ft. over NE. slope.
- 17.40 Ravine, course N. Asc. 143 ft. over W. slope.
- 22.37 Old trail, brs. N.-S.
- 29.27 Ridge, brs. N. 10° E.-S. Leave dense and enter scattering undergrowth. Desc. 65 ft. over SE. slope to Tp. cor.
- 33.77 Telephone line, brs. NW.-SE. At 6 chs. SE. turns to NE.
- 40.27 Intersect the reconstructed original cor. of Ts. 13 & 14 N., Rs. 1 & 2 W., hereinbefore described.

Land, mountainous.
Soil, rocky, 4th rate.
Timber, pine, oak and juniper.
Undergrowth, scrub oak, catclaw and cacti.

Boundaries of Township 13 North, Range 2 West Latitudes, departures and closing errors.						
Line designated	True bearing	Dist.	Latitudes		Departures	
			N.	S.	E.	W.
South boundary (3rd Std.Par.N.)	S. 82° 25' W.	77.14		10.18		76.46
	N. 87° 59' W.	41.52	1.46			41.49
	S. 89° 50' W.	41.26		.12		41.26
	N. 88° 21' W.	79.01	2.27			78.98
	West	39.35				39.35
	S. 79° 3' W.	47.77		9.07		46.90
	N. 71° 00' W.	32.67	10.64			30.89
	N. 88° 23' W.	120.00	3.39			119.95
West boundary	N. 2° 14' W.	240.00	239.82			9.36
	N. 1° 20' W.	84.36	84.34			1.96
	N. 1° 5' W.	38.66	38.65			.73
	N. 0° 29' W.	38.59	38.50			.32
	N. 1° 6' E.	76.60	76.59		1.47	
North boundary	N. 88° 53' E.	39.40	.77		39.39	
	N. 89° 26' E.	40.06	.40		40.06	
	N. 89° 10' E.	79.82	1.16		79.81	
	N. 88° 47' E.	80.16	1.70		80.14	
	N. 89° 35' E.	158.60	1.15		158.60	
	N. 86° 30' E.	38.33	2.34		38.26	
	N. 83° 4' E.	40.27	4.86		39.98	
East boundary	S. 2° 15' E.	39.18		39.15	1.54	
	S. 0° 22' W.	40.61		40.61		.26
	S. 2° 34' E.	254.70		254.45	11.41	
	S. 0° 52' W.	35.84		35.84		.54
	South	40.70		40.70		
	S. 0° 54' W.	38.70		38.70		.61
S. 3° 15' W.	40.00		39.94		2.27	
Convergency					.49	
Totals			508.04	508.76	491.15	491.33
				508.04		491.15
	Error in latitude			0.72		
	Error in departure					0.18

Retracement of Part of the Bdy. of Ft. Whipple Timber Reserve.

chains

The Ft. Whipple Timber Reserve consists of the $E\frac{1}{2}SE\frac{1}{4}$ of sec. 33, $SW\frac{1}{4}$ and $E\frac{1}{2}$ of sec. 34, and the $W\frac{1}{2}W\frac{1}{2}$ of sec. 35, T.13 N., R.2 W. The bdy. of same was surveyed by D.W. Eaton, U.S.T. in 1918, establishing monuments at each of the six angle points in said bdy.

No retracement or resurvey of any part of this Reserve bdy. is of record.

The following notes describe a retracement of line 6-1 of the Reserve bdy., the same being the meridional sixteenth sec. line of the west half of sec. 35. The topography along this line is omitted from these notes by reason of substantial agreement of same with the record of Eaton's survey.

Cor. No. 6 of Ft. Whipple Timber Reserve (SE. cor.) and std. $W\frac{1}{6}$ sec. cor. of sec. 35, on 3rd Std. Par. N., at midpoint of $W\frac{1}{2}$ of S. bdy. of sec. 35, is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, marked on brass cap as per record, and witnessed by two properly marked bearing trees, one each NE. and NW. of cor.

Thence
 N. $1^{\circ}00'E.$, (record course) on random line, on line 6-1 of F.W.T.R. bdy. and meridional sixteenth sec. line of $W\frac{1}{2}$ of sec. 35.

81.63

Over rolling land, thru dense timber and undergrowth.
 Intersect Cor. No. 1 of F.W.T.R. (NE. cor.) and $W\frac{1}{6}$ sec. cor. of secs. 26 and 35, which is an iron post, 2 ins. diam., projecting 12 ins. above ground, firmly set, marked on brass cap as per record, and witnessed by a mound of stone SW. of cor. No bearing trees.

True course and dist. of line 6-1 of F.W.T.R. bdy. are therefore, N. $1^{\circ}00'E.$, 81.63 chs.

Land, rolling.
 Soil, gravelly and rocky, 3rd and 4th rate.
 Timber, pine and oak.
 Undergrowth, scrub oak and manzanita.

Retracement of
Part of the Subdivision Lines of T. 13 N., R. 2 W.

- chains
- The subdivision lines of T.13 N.,R.2 W. were surveyed in 1871 by O.H.Case, U.S.D.S.
The N. $\frac{1}{4}$ of line bet. secs.26 and 27 was retraced in 1911 by J.W.Waara,U.S.M.S. in connection with Forest Home-
stead Entry No.69.
The line bet. secs.27 and 28, the W. $\frac{1}{2}$ of line bet. secs. 26 and 35, and the subdivision lines bounding secs. 33 and 34, were resurveyed in 1918 by D.W.Eaton,U.S.T.
No other retracement or resurvey of the subdivision lines of this Tp. is of record.
The following notes describe a retracement of the W. $\frac{1}{2}$ of line bet.secs.26 and 35, and the subdivision lines bounding sec.34. Topography is omitted by reason of close agreement of same with the record of the Eaton resurvey.
-
- The reconstructed original std. cor.of secs.34 and 35, T.13 N.,R.2 W.,on 3rd Std.Par.N. and line 5-6 of Bdy. of Ft.Whipple Timber Reserve, is an iron post, 3 ins. diam.,projecting 12 ins.above ground,firmly set in ground alongside the original cor.stone, stone and brass cap of iron post marked as per record, and witnessed by six properly marked bearing trees, one each NE. and NW. of cor., and two each SE. and SW. of cor.
Thence
N. 1° 45'E.(1918 resurvey record) on random line,bet. secs.34 and 35 (S. $\frac{1}{4}$).
Over rolling land,thru dense timber and undergrowth, across Ft.Whipple Timber Reserve.
- 41.07 Intersect the reestablished $\frac{1}{4}$ sec.cor.of secs.34 and 35, which is an iron post, 1 in. diam.,projecting 10 ins. above ground,firmly set,marked on brass cap as per record, and witnessed by two properly marked bearing trees, one each NE. and SW. of cor.
True course and dist. of S. $\frac{1}{4}$ of line bet. secs.34 and 35 are therefore, N. 1°45'E.,41.07 chs.
Thence
N. 1°45'E.,(1918 resurvey record) on random line, bet. secs.34 and 35 (N. $\frac{1}{4}$)
Over rolling land,thru dense timber and undergrowth, across Ft.Whipple Timber Reserve.
- 41.20 Intersect the reconstructed original cor.of secs.26,27, 34 and 35,which is an iron post, 2 ins. diam.,projecting 12 ins.above ground,firmly set in ground alongside the original cor.stone, stone and brass cap of iron post marked as per record, and witnessed by four properly marked bearing trees, one each NE.,SE.,SW., and NW. of cor.
True course and dist. of N. $\frac{1}{4}$ of line bet.secs.34 and 35 are therefore, N. 1°45'E., 41.20 chs.
Land, rolling.
Soil, sandy and rocky, 3rd and 4th rate.
Timber, pine and oak.
Undergrowth, scrub oak and cacti.
-
- The reconstructed original $\frac{1}{4}$ sec. cor. of secs.26 and 35 is an iron post, 1 in.in diam.,projecting 16 ins. above ground,firmly set in ground and mound of stone, with brass cap marked as per record, and witnessed by three properly marked bearing trees,one each NE.,SE., and SW. of cor.
Thence
N.88°15'W.(1918 resurvey record) on random line, bet. secs.26 and 35 (W. $\frac{1}{4}$).
Over rolling land,thru dense timber and undergrowth.
19.43 Fall 12 lks. N. of Cor.No.1 of Ft.Whipple Timber Reserve (NE.cor.) and W. $\frac{1}{6}$ sec.cor.of secs.26 and 35, herein-
before described.
Continue line and measurement along part of the Bdy.of

Retracement of
Part of the Subdivision Lines of T. 13 N., R. 2 W.

chains

38.86 F.W.T.R. (line 1-2)
 Fall 24 lks. N. of the reconstructed original cor. of
 secs. 26, 27, 34 and 35, hereinbefore described.
 True course and dist. of W. $\frac{1}{4}$ of line bet. secs. 26 and
 35 are therefore, N. 88° 36' W., 38.86 chs. and Cor. No. 1
 of F.W.T.R. is at midpoint and in proper alinement
 bet. the $\frac{1}{4}$ sec. cor. and the sec. cor.

Land, rolling.
 Soil, sandy and rocky, 3rd and 4th rate.
 Timber, pine and oak.
 Undergrowth, scrub oak and cacti.

From the reconstructed original std. cor. of secs. 33
 and 34, T. 13 N., R. 2 W., on 3rd Std. Par. N., and line 5-6
 of F.W.T.R. Bdy., hereinbefore described,
 N. 1° 12' E. (1918 resurvey record) on random line, bet.
 secs. 33 and 34 (S. $\frac{1}{4}$)
 Over rolling land, thru dense timber and undergrowth,
 across Ft. Whipple Timber Reserve.

40.52 Intersect the reestablished $\frac{1}{4}$ sec. cor. of secs. 33 and
 34, on line 3-4 of F.W.T.R. Bdy., which is an iron
 post, 1 in. in diam., projecting 10 ins. above ground,
 firmly set, marked on brass cap as per record, and
 witnessed by one properly marked bearing tree NE. of
 cor., and a mound of stone W. of cor.
 True course and dist. of S. $\frac{1}{4}$ of line bet. secs. 33 and
 34 are therefore, N. 1° 12' E., 40.52 chs.

Thence
 N. 1° 12' E., (1918 resurvey record) on random line, bet.
 secs. 33 and 34 (N. $\frac{1}{4}$)
 Over rolling land, thru dense timber and undergrowth.

40.61 Intersect the reestablished cor. of secs. 27, 28, 33 and
 34, which is an iron post, 2 ins. in diam., projecting
 12 ins. above ground, firmly set, marked on brass cap
 as per record, and witnessed by four properly marked
 bearing trees, one each NE., SE., SW. and NW. of cor.
 True course and dist. of N. $\frac{1}{4}$ of line bet. secs. 33 and
 34 are therefore, N. 1° 12' E., 40.61 chs.

Land, rolling.
 Soil, gravelly, 3rd rate.
 Timber, oak and pine.
 Undergrowth, scrub oak and cacti.

From the reconstructed original cor. of secs. 26, 27, 34
 and 35, hereinbefore described,
 N. 88° 33' W., (1918 resurvey record) on random line, bet.
 secs. 27 and 34 (E. $\frac{1}{4}$)
 Over rolling land, thru dense timber and undergrowth,
 along part of line 1-2 of F.W.T.R. Bdy.

39.71 Fall 70 lks. N. of Cor. No. 2 of F.W.T.R., and reestablished
 $\frac{1}{4}$ sec. cor. of secs. 27 and 34, which is an iron post,
 1 in. in diam., projecting 10 ins. above ground, firmly
 set, marked on brass cap as per record, and witnessed
 by two properly marked bearing trees, one each NE.
 and SW. of cor.
 True course and dist. of E. $\frac{1}{4}$ of line bet. secs. 27 and
 34 are therefore, N. 89° 33' W., 39.71 chs.

Retracement of
Part of the Subdivision Lines of T. 13 N., R. 2 W.

chains

Thence
N.88°33'W., (1918 resurvey record) on random line, bet.
secs. 27 and 34 (W. $\frac{1}{2}$)
Over rolling land, thru dense timber and undergrowth.
40.00 Fall 50 lks. N. of the reestablished cor. of secs. 27,
28, 33 and 34, hereinbefore described.
True course and dist. of W. $\frac{1}{2}$ of line bet. secs. 27 and
34 are therefore, N.89°16'W., 40.00 chs.

Land, rolling.
Soil, sandy and rocky, 3rd and 4th rate.
Timber, oak and pine.
Undergrowth, scrub oak and cacti.

Resurvey of Part of the Subd. Lines of T.13 N., R.2 W.

chains The subdivision lines of T.13 N., R.2 W. were surveyed in 1871 by O.H. Case, U.S.D.S. The N. $\frac{1}{2}$ of line bet. secs. 26 and 27 was retraced in 1911 by J.W. Waara, U.S.M.S. in connection with H.E.S. No. 69. The line bet. secs. 27 and 28, the W. $\frac{1}{2}$ of line bet. secs. 26 and 35, and subdivision lines bounding secs. 33 and 34, were resurveyed in 1918 by D.W. Eaton, U.S.T. No other retracement or resurvey of the subdivision lines of this Tp. is of record. The following notes describe a resurvey of all of the subdivision lines of T.13 N., R.2 W. except those retraced as hereinbefore described.

 From reconstructed original std. cor. of secs. 35 and 36, T.13 N., R.2 W., on 3rd Std. Par. N., hereinbefore described,

- N. 1°30'E., on true line, bet. secs. 35 and 36. Over mountainous land, thru dense timber and undergrowth. Asc. gradually over SW. slope.
- 1.00 Spur, brs. W. Desc. 40 ft. over N. slope.
- 2.20 Wash, 10 lks. wide, course W. Asc. 136 ft. over S. slope.
- 4.50 Wire fence, brs. NW.-E.
- 9.60 Spur, brs. SW. Desc. 187 ft. over NW. slope to creek.
- 19.00 Spur, brs. NW.
- 27.10 Creek, with stream of water, 10 lks. wide, 5 ins. deep, course W. Asc. 137 ft. over S. slope.
- 27.90 Road, brs. NE.-SW.
- 37.10 Spur, brs. SW. Asc. 33 ft. over W. slope to
- 44.04 (Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished $\frac{1}{4}$ sec. cor. of secs. 35 and 36, with brass cap marked.



from which
 an oak, 20 ins. diam., brs. N. 20° E., 4 lks. dist., marked $\frac{1}{4}$ S36 BT
 a yellow pine, 20 ins. diam., brs. N. 15° W., 31 lks. dist., marked $\frac{1}{4}$ S35 BT

- Desc. gradually over NW. slope.
- 48.20 Desc. 83 ft. over N. slope.
- 51.30 Wash, 10 lks. wide, course W. Asc. 15 ft. over S. slope.
- 53.50 Spur, brs. SW. Asc. 120 ft. over SW. slope.
- 62.65 Old road, brs. E.-W.
- 67.10 Ridge, brs. N. 70° W. - S. 70° E.
- 73.70 Head of wash, course NE. Asc. gradually over SE. slope.
- 76.40 Spur, brs. NE. Desc. 168 ft. over NW. slope.
- 83.40 Wash, 10 lks. wide, course NE. Asc. 13 ft. over SE. slope to sec. cor.
- 84.69 Intersect S. end line (3-4-5) of "Illinois" patented lode mining claim, Min. Surv. No. 671, at a point 3.97 chs. N. 75 $\frac{1}{2}$ ° E. from Cor. No. 5 thereof. Thence across said claim.
- 88.08 Intersect the original cor. of secs. 25, 26, 35 and 36, which is an oak tree, 10 ins. in diam., scribed TXIIIN SXXXV on SW. face, illegibly marked on other faces and witnessed by an oak, 30 ins. in diam., S. 48° W., 24 lks. dist., marked TXIIIN and illegible marks.

Reconstruct this cor. monument as follows:

chains

alongside original tree cor., set an iron post, 3 ft. long, 2 ins. in diam., 18 ins. in the ground to bedrock, and raise a mound of stone around post, for cor. of secs. 25, 26, 35 and 36, with brass cap marked

T13N	R2W
S26	S25
S35	S36

1930

from which
 a yellow pine, 20 ins. in diam., brs. N.29°W., 81 lks. dist., marked T13N R2W S26 BT
 an oak, 10 ins. in diam., brs. S.67 $\frac{3}{4}$ °E., 40 lks. dist., marked T13N R2W S36 BT
 an oak, 14 ins. in diam., brs. N.70°E., 50 lks. dist., marked T13N R2W S25 BT
 renew marking on original bearing tree SW. of cor. to read. TXIIN R2W S35 BT

Land, mountainous.
 Soil, rocky, 4th rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, scrub oak, manzanita and cacti.

From original cor. of secs. 25 and 36, on the E. bdy. of the Tp., hereinbefore described,

S.89°20'W., on true line, bet. secs. 25 and 36.
 Over mountainous land, thru dense timber and undergrowth, across unpatented mineral land, M.S. No. 1549.
 Desc. 20 ft. over W. slope.

- 0.70 Wash, 5 lks. wide, course NW. Asc. 14 ft. over NE. slope.
- 2.00 Spur, brs. NW. Desc. 39 ft. over SW. slope.
- 3.15 Wash, 5 lks. wide, course NE. Asc. 52 ft. over NE. slope.
- 6.40 Wash, course NE. Asc. gradually over NE. slope.
- 9.30 Spur, brs. NW. Desc. 96 ft. over SW. slope.
- 13.49 Intersect E. side line (3-4) of "New Year Test" patented lode mining claim, Min. Surv. No. 1636, at a point 5.99 chs. S.6° 3'W. from Cor. No. 4 thereof.
 Thence across patented mineral land, Mineral Surveys Nos. 1636 and 1569.
- 14.00 Wash, 5 lks. wide, course NW. Asc. 11 ft. over NE. slope.
- 16.00 Spur, brs. NW. Desc. 68 ft. over SW. slope.
- 19.00 Wash, near head, course N. Asc. 39 ft. over E. slope.
- 20.80 Spur, brs. NE. Asc. over N. slope.
- 21.80 Wash, 10 lks. wide, course NE. Asc. 76 ft. over NE. slope.
- 22.00 Trail, brs. NE.-SW.
- 26.40 Ridge, brs. W.-S.80°E. Thence along top of same.
- 28.20 Leave top of ridge, brs. NW.-E. Desc. 194 ft. over SW. slope to

38.52 (Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for reestablished $\frac{1}{4}$ sec. cor. of secs. 25 and 36, with brass cap marked

S 25
$\frac{1}{4}$
S 36

1930


from which
 a yellow pine, 10 ins. diam., brs. N.71 $\frac{1}{2}$ °E., 32 lks. dist., marked $\frac{1}{4}$ S25 BT
 a yellow pine, 24 ins. diam., brs. S.4°E., 33 lks. dist., marked $\frac{1}{4}$ S36 BT
 a large prospect hole brs. E. 20 lks. dist.

Resurvey of Part of the Subd. Lines of T.13 N., R.2 W.

chains
 46.30 Continue across patented mineral land.
 Desc. 181 ft. over SW. slope.
 50.58 Iron shack and tunnel, brs. S. 2 chs. dist.
 Intersect W. side line (2-3) of "Douglas No. 2" patented
 lode mining claim, M.S. No. 1569 at a point 21 lks.
 N. 7° 19' E. from Cor. No. 2 thereof. Leave patented
 mineral land.
 51.60 Thence across "Empire" unpatented mining claim, M.S. 1471.
 Fork of Groom Creek, 20 lks. wide, course NW., containing
 a small stream of running water.
 Asc. 111 ft. over NE. slope.
 57.62 Intersect E. side line (3-4) of "King Kelly" patented
 lode mining claim, M.S. No. 1465 Amended, at a point
 5.30 chs. S. 9° 30' E. from Cor. No. 4 and 15.31 chs. N. 9° 30'
 W. from Cor. No. 3. Thence across pat. mineral land.
 60.00 Ridge, brs. NW.-SE. Desc. 253 ft. over SW. slope.
 70.00 Intersect W. side line (1-2) of "New Haven" patented lode
 mining claim, M.S. No. 2980, at a point 8.72 chs.
 S. 11° 24' W. from Cor. No. 1 thereof. Leave patented
 mineral land.
 72.20 Road, brs. NW.-SE.
 72.40 Fork of Groom Creek, 10 lks. wide, course NW.
 Asc. 83 ft. over NE. slope to sec. cor.
 72.52 Intersect E. side line (2-3) of "Illinois" patented lode
 mining claim, M.S. No. 671, at a point 2.19 chs. N. 9° 2' W.
 from Cor. No. 3 thereof. Thence across pat. mineral land.
 72.90 Mouth of small wash, from SW.
 75.60 Trail, brs. NE.-SW.
 77.04 Intersect original cor. of secs. 25, 26, 35 and 36.

Land, mountainous. Soil, rocky, 4th rate.
 Timber, yellow pine, spruce, oak and juniper.
 Undergrowth, scrub oak and mahzanita.

N. 0° 25' E., on true line, bet. secs. 25 and 26.
 Over mountainous land, thru dense timber and undergrowth,
 across patented mineral land.
 Desc. 141 ft. over NE. slope.
 6.60 Wash, 10 lks. wide, course NE. Asc. 10 ft. over SE. slope.
 7.60 Spur, brs. NE. Desc. 28 ft. over NW. slope.
 9.70 Fork of Groom Creek, 20 lks. wide, course NW.
 Asc. 55 ft. over SW. slope.
 10.80 Road, brs. NW.-SE.
 15.00 Narrow guage R.R. track, brs. E.-W. to mine 5 chs. E.
 16.30 Spur, brs. W. Desc. 13 ft. over W. slope.
 17.90 Wash, at head, course SW. Asc. 51 ft. over SE. slope.
 21.00 Spur, brs. SW. Desc. 29 ft. over NW. slope.
 23.75 Head of wash, course SW. Asc. 52 ft. over SE. slope.
 24.73 Intersect E. side line (2-3) of "Chicago" patented lode
 mining claim, M.S. No. 609, at a point 6.69 chs.
 N. 12° 25' W. from Cor. No. 2 thereof. Leave patented
 mineral land.
 26.00 Spur, brs. SW. Desc. 152 ft. over NW. slope.
 31.90 Groom Creek, 20 lks. wide, course SW. Asc. 182 ft. over
 steep SE. slope.
 32.60 Road, brs. E.-W.
 39.42 (Midpoint) Set an iron post, 3 ft. long, 1 in. in diam.,
 15 ins. in the ground to bedrock, and raise a mound of
 stone around post, for reestablished $\frac{1}{4}$ sec. cor. of
 secs. 25 and 26, with brass cap marked.



from which
 an oak, 16 ins. diam., brs. N. 62° E., 32 lks.
 dist., marked $\frac{1}{4}$ S25 BT

chains

- an oak, 8 ins. diam., brs. N.15°W., 8 lks.
dist., marked $\frac{1}{4}$ S26 BT
Spruce Mt. Lookout Tower bears S.57°E.
Asc. 49 ft. over S. slope.
- 42.10 Ridge, brs. E.-W. Desc. 235 ft. over N. slope.
48.55 Wash, 15 lks. wide, course W. Asc. 61 ft. over S. slope.
53.50 Spur, brs. W. Desc. 11 ft. over NW. slope.
55.00 Wash, near head, course SW. Asc. 150 ft. over S. slope.
64.40 Ridge, brs. E.-W. Desc. 69 ft. over N. slope.
67.60 Wash, 10 lks. wide, course SW. Asc. 53 ft. over SE. slope.
72.40 Change to W. slope and asc. gradually to sec. cor.
78.84 Intersect accepted original cor. of secs. 23, 24, 25 and
26, which is an oak stump, 30 ins. diam., 2 ft. high,
unmarked.
The record of this cor. monument describes same as a
pin oak, 24 ins. diam.,
The position of the stump found, agrees with sec. cor.
point determined by proportionate measurement, and
its acceptance as remains of original cor. mon. is
verified by old line blazes on each of the subd.
lines radiating therefrom.
Reconstruct this cor. monument as follows:
alongside the stump, set an iron post, 2 ins. in diam.,
20 ins. in the ground to bedrock, and raise a mound of
stone around post, for cor. of secs. 23, 24, 25 and 26,
with brass cap marked

T13N	R2W
S23	S24
S26	S25

1930

- from which
a yellow pine, 20 ins. diam., brs. N.61°E., 68 lks.
dist., marked T13N R2W S24 BT
an oak, 6 ins. diam., brs. S.46 $\frac{1}{2}$ °E., 78 lks.
dist., marked T13N R2W S25 BT
an oak, 14 ins. diam., brs. N.68°W., 8 lks.
dist., marked T13N R2W S23 BT
a yellow pine, 26 ins. diam., brs. S.31°W., 22 lks.
dist., marked T13N R2W S26 BT.

Land, mountainous.
Soil, rocky, 4th rate.
Timber, yellow pine, oak and juniper.
Undergrowth, scrub oak, catclaw and cacti.

- From reconstructed original cor. of secs. 24 and 25, on
the E. bdy. of the Tp. hereinbefore described,
N.87°40'W., on true line, bet. secs. 24 and 25 (E. $\frac{1}{2}$)
Over mountainous land, thru dense timber and undergrowth,
across patented mineral land.
Desc. 166 ft. over W. slope.
0.87 Intersect NW. end line (2-3) of "Cornucopia" patented
lode mining claim, M.S. No. 1572 at a point 1.68 chs.
S.74°38'W. from Cor. No. 3 thereof.
Leave patented mineral land.
5.00 Wash, 10 lks. wide, course N. Asc. 63 ft. over E. slope.
7.60 Spur, brs. N. Desc. 47 ft. over NW. slope.
9.50 Wash, 10 lks. wide, course NE.
Asc. 55 ft. over SE. slope.
14.00 Wire fence, brs. NW.-SE.

Re-Survey of Part of the Subd. Lines of T.13 N. R.2 W. 43

Chains	
15.20	Spur, brs. NE. Desc. slight NW slope.
15.61	Intersect the East end line (2-3) of the "Prince Albert No. 4" patented lode mining claim, Min. Sur. No. 3746, at 2.28 chs. N.4°28'W. of Cor. No. 3 thereof. Across patented mineral land.
16.20	Wash, near head, course NE. Asc. 141 ft. over SE slope.
16.80	Power line, brs. NW-SE.
18.75	Trail, brs. N-S.
21.40	Old road, brs. NE-SW.
22.40	Ridge, brs. NE-SW. Desc. 165 ft. over NW slope.
23.98	Intersect the NW side line (1-2) of the "Prince Albert No. 4" patented lode mining claim, Min. Sur. No. 3746, at 11.95 chs. N.46°02'E. of Cor. No. 1 thereof. Leave patented mineral land.
31.40	Wash, 5 lks. wide, course NW. Asc. 58 ft. over NE slope.
33.28	Intersect the east side line (2-3) of the "Prince Albert No. 1" patented lode mining claim, Min. Sur. No. 3746, at 3.90 chs. S.4°28'E. of Cor. No. 2 thereof. Across patented mineral land.
34.20	Spur, brs. NW. Desc. 69 ft. over SW slope.
38.63	Intersect the original $\frac{1}{4}$ sec. cor. of secs. 24 and 25, which is a stone 4 x 8 x 14 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face, from which, a yellow pine, 20 ins. in diam., brs. N.24 $\frac{1}{2}$ °E., 38 lks. dist., marked $\frac{1}{4}$ SBT a yellow pine, 18 ins. in diam., brs. S.10°E., 50 lks. dist., marked $\frac{1}{4}$ SBT
	Reconstruct this cor. monument as follows:
	Alongside the original stone cor., set an iron post 3 ft. long, 1 in. in diam., 12 ins. in the ground to bed-rock, raise a mound of stone about post, for the $\frac{1}{4}$ secs. cor. of secs. 24 and 25, with brass cap marked
	$\frac{1}{4} \begin{array}{l} S 24 \\ S 25 \end{array}$
	1930 from which, a yellow pine, 18 ins. in diam., brs. N.28°E., 55 lks. dist., marked $\frac{1}{4}$ S24 BT a yellow pine, 20 ins. in diam., brs. S.30°E., 54 lks. dist., marked $\frac{1}{4}$ S25 BT
	Thence, S.89°57'W., on true line, bet. secs. 24 and 25, (W $\frac{1}{2}$) Desc. 106 ft. over NW slope.
0.30	Telephone line, brs. NW-SE.
5.55	Wash, 10 lks. wide, course N. Asc. gradual NE slope.
8.30	Spur, brs. N. Desc. 61 ft. over W. slope.
10.81	Intersect the West side line (3-4) of the "Prince Albert No. 2" patented lode mining claim, Min. Sur. No. 3746, at 1.84 chs. S.4°28'E., of Cor. No. 4 thereof. Leave patented mineral land.
11.00	Trail, brs. NW-SE.
14.40	Wash, 5 lks. wide, course NW. Asc. 15 ft. over NE slope.
15.00	Spur, brs. NW. Desc. 21 ft. over SW slope.
17.50	Wash, 10 lks. wide, course NW. Asc. 12 ft. over NE slope.
18.20	Spur, brs. NW. Desc. 99 ft. over SW slope.
25.25	Wash, 20 lks. wide, course NW. Old road in same, brs. NW-SE.
26.40	Spur, brs. N. Desc. 21 ft. over W. slope.
27.90	Wash, 10 lks. wide, course N. Asc. 35 ft. over E. slope.

44

ReSurvey of Part of the Subd. Lines of T. 13 N., R. 2 W.

Chains

29.60 Spur, brs. N. Desc. 21 ft. over W. slope.
 31.40 Wash, 5 lks. wide, course NE. Asc. 113 ft. over E. slope.
 37.00 Spur, brs. NW. Across level top.
 37.40 Road, brs. NW-SE. Desc. 13 ft. over SW slope.
 38.75 Intersect the reconstructed cor. of secs. 23, 24, 25 & 26.
 Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita, cacti.

N.3°00'W., on true line, bet. secs. 23 and 24, (S $\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth.
 Along level W. slope.
 1.30 Ridge, brs. NW-SE. Road, on same, brs. NW-SE.
 Desc. 101 ft. over NE slope.
 6.30 Head of wash, course NE. Asc. 28 ft. over SE slope.
 8.50 Spur, brs. NE. Desc. 146 ft. over rolling NW slope.
 15.30 Bannon Creek, stream of water 6 lks. wide 3 ins. deep
 course SW. Asc. 128 ft. over SW slope.
 16.00 Old road, brs. SW and SE.
 22.00 Spur, brs. West. Desc. 18 ft. over NW slope.
 25.90 Wash, 5 lks. wide, course SW. Asc. 21 ft. over SE slope.
 27.10 Spur, brs. West. Desc. 147 ft. over N. slope.
 33.00 Wash, 10 lks. wide, course W. Asc. 100 ft. over S. slope.
 42.80 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 23 and 24,
 which is a stone 18 x 12 x 8 ins. faintly marked $\frac{1}{4}$
 on W. face, in mound of stone. No bearing trees.
 Alongside the old cor. stone, set an iron post 3 ft.
 long, 1 in. in diam., 20 ins. in the ground to bed-
 rock, raise a mound of stone about post, for the
 $\frac{1}{4}$ sec. cor. of secs. 23 and 24, with
 brass cap marked

 $\frac{1}{4}$

S23 | S24

1930

from which,

an oak, 7 ins. in diam., brs. N.76°W., 69 lks. dist.,
 marked $\frac{1}{4}$ S23 BT
 a yellow pine, 14 ins. in diam., brs. S.52 $\frac{1}{2}$ °E., 132
 lks. dist., marked $\frac{1}{4}$ S24 BT
 Spruce Mtn. Lookout Tower, brs. S.35°42'E.

Thence,
 N.0°34'W., on true line, bet. secs. 23 and 24, (N $\frac{1}{2}$)
 Asc. 41 ft. over SW slope.
 3.00 Spur, brs. SE. Along level E. slope.
 6.50 Same spur, brs. SW. Desc. 26 ft. over NW slope.
 13.25 Wash, 5 lks. wide, course SW. Asc. 51 ft. over SE slope.
 16.00 Spur, brs. SW. Asc. 179 ft. over SW slope.
 33.00 Ridge, brs. E-W. Desc. 41 ft. over N. slope.
 34.90 Enter wash, near head, course N. from SE.
 Desc. 86 ft. down same.
 39.00 Leave wash to NW. Fence, brs. NW-SE. Asc. 17 ft. over SW slope to
 40.08 intersect the proportionate point for the cor. of secs.
 13, 14, 23 and 24; set an iron post 3 ft. long, 2 ins.
 in diam., for the reestablished cor. of secs. 13, 14,
 23 and 24, with brass cap marked

Re-Survey of Part of the Subd. Lines of T.13 N..R.2 W. 45

Chains

T13N	R2W
S14	S13
S23	S24

1930 from which,
 a yellow pine, 8 ins. in diam., brs. N.51 $\frac{1}{4}$ °W., 100 lks.
 dist., marked T13N R2W S14 BT
 a yellow pine, 30 ins. in diam., brs. N.1°E., 18 lks.
 dist., marked T13N R2W S13 BT
 a yellow pine, 14 ins. in diam., brs. S.67 $\frac{1}{2}$ °E., 50 lks.
 dist., marked T13N R2W S24 BT
 an oak, 14 ins. in diam., brs. S.72°W., 21 lks.
 dist., marked T13N R2W S23 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita, cacti and catclaw.

From the reestablished cor. of secs. 13 and 24, on E. Bdy.
 of Tp., hereinbefore described.

S.89°41'W., on true line, bet. secs. 13 and 24.
 Over mountainous land, thru thick timber & undergrowth.
 Desc. 32 ft. over NW slope.

- 1.30 Wash, 5 lks. wide, course NE. Asc. 142 ft. over SE slope.
- 8.40 Spur, brs. NE. Desc. 116 ft. over NW slope.
- 15.50 Wash, 10 lks. wide; course N. Asc. 9 ft. over SE slope.
- 16.75 Spur, near end, brs. N: Desc. gradual NW slope about
1 chs. S. of main wash, with blazed trail in same.
- 20.10 Same main wash, course N.85°E., 20 lks. wide, trail brs.
same. Asc. gradually up same.
- 22.90 Leave wash, from SW. at mouth of wash from NW. Trail
brs. NW up same.
Asc. 38 ft. over E. slope.
- 25.30 Tip of spur, brs. S. Desc. 7 ft. over SW slope.
- 27.40 Same wash, and trail, course SE. Asc. 15 ft. up same.
- 29.80 Leave wash, from NW. Asc. 62 ft. over NE slope.
- 32.00 Spur, brs. N. Along level N. slope.
- 33.25 Side wash, 10 lks. wide, course NE. Asc. 136 ft. over
E. slope.
- 38.22 (Proportionate point) set an iron post 3 ft. long, 1 in.
in diam., 16 ins. in the ground to bedrock, raise a
mound of stone about post, for the reestablished $\frac{1}{4}$
sec. cor. of secs. 13 and 24, with brass cap marked

$\frac{1}{4}$	S 13
	S 24


1930 from which,
 a yellow pine, 12 ins. in diam., brs. N.70°E., 57 lks.
 dist., marked $\frac{1}{4}$ S13 BT
 an oak, 10 ins. in diam., brs. S.32°E., 41 lks.
 dist., marked $\frac{1}{4}$ S24 BT

- Desc. 54 ft. over NW slope.
- 43.10 Wash, 10 lks. wide, course NE. Asc. 69 ft. over SE slope.
- 47.50 Spur, brs. NE. Asc. 30 ft. over NW slope.
- 51.40 Wash, 10 lks. wide, course NE. Asc. 198 ft. over steep
SE slope.
- 58.30 Branch spur, brs. NE. from W., up top of spur on slight
ascent.

Chains	
62.50	Ridge, brs. NW-SE. Trail, same bearing. Desc. 189 ft. over top of spur, which brs. West.
68.25	Power line, brs. N.10°E.-S.10°W.
73.53	Telephone line, brs. N.10°W.-S.10°E. At trail which brs. same.
76.44	Intersect the reestablished cor. of secs. 13, 14, 23 & 24.
	Land, mountainous. Soil, rocky 4th. rate. Timber, yellow pine, oak and juniper. Undergrowth, oakbrush, manzanita, cacti and catclaw.
	N.4°40'W., on true line, bet. secs. 13 and 14. Over mountainous land, thru thick timber & undergrowth. Desc. slight NE slope.
.35	Shallow wash, course NW. Asc. 30 ft. over SW slope.
4.50	Spur, brs. NW. Desc. 50 ft. over NE slope.
7.20	Wash, 10 lks. wide, course W. Asc. gradual S. slope.
10.25	Blazed trail, brs. E-W., on spur, brs. W. Desc. 22 ft. over N. slope.
12.85	Junction of washes from NE-SE. Asc. 45 ft. over S. slope.
16.05	Telephone line, brs. N.14°W.-S.14°E.
18.50	Spur, brs. SW. Desc. 54 ft. over NW slope.
21.65	Wash, 10 lks. wide, course SW. Asc. gradual SE slope.
22.65	Main trail, brs. NE-SW.
25.65	Wash, 10 lks. wide, course SW. Asc. 39 ft. over SE slope.
29.30	Ridge, brs. E-W. Desc. 109 ft. over N. slope.
34.90	Wash, near head, course NE. Desc. 35 ft. over E. slope.
40.35	(Proportionate point) set an iron post 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs. 13 and 14, with brass cap marked
	$\frac{1}{4}$
	S14 S13
	1930 from which, an oak, 9 ins. in diam., brs. S.22 $\frac{1}{2}$ °W., 33 lks. dist., marked $\frac{1}{4}$ S14 BT a yellow pine, 20 ins. in diam., brs. S.89 $\frac{1}{2}$ °E., 82 lks. dist. marked $\frac{1}{4}$ S13 BT
	Desc. 7 ft. over N. slope.
40.59	Wash, 5 lks. wide, course E. Asc. 14 ft. over S. slope.
41.60	Along level E. slope.
48.60	Power line, brs. NW-SE. Desc. 189 ft. over NE slope.
54.60	Wash, 20 lks. wide, course NW. Asc. 49 ft. over SW slope.
59.00	Spur, brs. West. Desc. 18 ft. over NW slope.
61.45	Wash, 10 lks. wide, course SW. Asc. 213 ft. over SE slope.
71.00	Ridge, brs. NW-SE. Desc. 274 ft. over steep N. slope.
80.70	Proportionate point for cor. Set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished cor. of secs. 11, 12, 13 and 14, with brass cap marked

Re-Survey of Part of the Subd. Lines of T. 13 N., R. 2 W.


Chains



1930 from which,
 an oak, 4 ins. in diam., brs. N.19½°E., 11 lks. dist.,
 marked T13N R2W S12 BT
 a yellow pine, 12 ins. in diam., brs. S.36°E., 129 lks.
 dist., marked T13N R2W S13 BT
 an oak, 8 ins. in diam., brs. S.21½°W., 46 lks. dist.,
 marked T13N R2W S14 BT
 an oak, 9 ins. in diam., brs. N.64½°W., 42 lks. dist.,
 marked T13N R2W S11 BT
 Land, mountainous. Soil, rocky 4th. rate., Timber, yellow
 pine, oak and juniper; Undergrowth, oak, manzanita & cacti.

From the reestablished cor. of secs. 12 & 13, on E.bdy. of
 Tp., hereinbefore described., Thence, S.86°30'W., on
 true line, bet. secs. 12 and 13. Over mountainous
 land, thru thick timber and undergrowth.

Desc. 16 ft. over SW slope.
 6.00 Wash, 10 lks. wide, course S. Asc. 92 ft. over E. slope.
 13.40 Spur, brs. SE. Desc. 77 ft. over SW slope.
 17.40 Wash, 10 lks. wide, course SE. Asc. 151 ft. over NE slope.
 28.40 Spur, brs. SE. Desc. gradual SW slope.
 30.20 Wash, 10 lks. wide, course SE. Asc. 131 ft. over SE slope.
 38.40 Ridge, brs. NE-SW. Desc. slight SW slope.
 39.68 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 26 ins. in the ground for the reestablished ¼ sec. cor.
 of secs. 12 & 13, with brass cap marked



1930 from which,
 a juniper, 30 ins. in diam., brs. N.75°E., 88 lks. dist.,
 marked ¼ S12 BT
 a yellow pine, 14 ins. in diam., brs. S.69°W., 130 lks.
 dist., marked ¼ S13 BT
 Asc. slight SE slope.

40.50 Same ridge, brs. NE-SW. Desc. 96 ft. over NW slope.
 46.75 Wash, 10 lks. wide, course N. Asc. 123 ft. over SE slope.
 53.85 Spur, brs. NE. Desc. 25 ft. over NW slope.
 57.75 Wash, 10 lks. wide, course NE. Asc. 172 ft. over NE slope.
 66.36 Ridge, brs. NW-SE. Desc. 330 ft. over rolling SW slope to
 78.50 Wash, 20 lks. wide, course NW. Asc. 25 ft. over NE slope.
 79.36 Intersect the cor. of secs. 11, 12, 13 & 14.
 Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak & juniper.
 Undergrowth, oak, manzanita, and cacti.


N.11°40'W., on true line, bet. secs. 11 & 12.
 Over mountainous land, thru thick timber & undergrowth.
 Desc. 25 ft. over NE slope.

0.40 Wash, 20 lks. wide, course NW. Asc. 22 ft. over SW slope.
 3.00 Spur, brs. W. Desc. 16 ft. over NW slope.
 5.85 Wash, near head, course SW. Asc. 93 ft. over SE slope.
 9.50 Spur, brs. SW. Asc. 41 ft. over spur top.
 13.05 Head of wash, course SW. Asc. 89 ft. over SE slope.
 16.30 Ridge, brs. E-W. Desc. 372 ft. over steep NE slope.
 20.15 Wire fence, brs. N1°E.-S.1°W.
 32.50 Wash, 20 lks. wide, course NW. Asc. 73 ft. over SW slope.
 40.95 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 26 ins. in the ground for the reestablished ¼ sec.

485 Re-Survey of Part of the Subd. Lines of T. 13 N., R. 2 W.


Chains

Cor. of sec 1 and 12, with brass cap marked



1930 No bearing trees available.

- 46.20 Raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.
- 56.75 Asc. 58 ft. over SW slope.
- 58.85 Spur, brs. NW. Desc. 332 ft. over steep NE slope.
- 60.20 Wash, 20 lks. wide, course NW. Asc. 58 ft. over SW slope.
- 62.35 Old road, brs. NW-SE.
- 77.00 Spur, brs. W. Desc. 23 ft. over N. slope.
- 81.90 Wash, 10 lks. wide, course SW. Asc. 343 ft. over SE slope.
- Spur, brs. SW. Desc. 23 ft. over NW slope to
- Intersect the original cor. of secs. 1, 2, 11 & 12, which is a stone 10 x 10 x 8 ins. above ground & mound of stone, marked 5 and 1 grooves on S. and E. faces respectively. No bearing trees. Reconstruct this cor. monument by setting an iron post 3 ft. long, 2 ins. in diam., 18 ins. in the ground to bedrock, alongside old cor. stone, raise a mound of stone about post, for the cor. of secs. 1, 2, 11 and 12, with brass cap marked




1930

Land, mountainous. Soil, rocky 4th. rate. Timber, yellow pine, oak and juniper. Undergrowth, oak, manzanita, cacti.

From the reconstructed cor. of secs. 1 and 12, on E. bdy. of Tp., hereinbefore described. Thence, S. 84° 10' W., on true line, bet. secs. 1 and 12. Over mountainous land, thru scattering timber & dense undergrowth.

- 2.90 Asc. 13 ft. over SE slope.
- 11.10 Spur, brs. NE. Desc. 88 ft. over NW slope.
- 16.40 Wash, 10 lks. wide, course N. 10° E., Asc. 63 ft. over E. slope.
- 27.80 Ridge, brs. N-S. Desc. 120 ft. over W. slope.
- 31.10 Wash, 20 lks. wide, course N. Asc. 20 ft. over E. slope.
- 32.20 Spur, brs. N. Desc. gradual W. slope.
- 37.10 Shallow wash, course N. Asc. 153 ft. over NE slope.
- 42.30 Trail, brs. NE-SW.
- 46.15 Small wash, course NE. Asc. gradual NE slope.
- (Midpoint) set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished 1/4 sec. cor. of secs. 1 and 12, with brass cap marked



1930 from which,

- 62.80 a pinion, 9 ins. in diam., brs. N. 85° W., 71 lks. dist. marked 1/4 S1 BT
- 78.20 a juniper, 24 ins. in diam., brs. S. 35° W., 52 lks. dist., marked 1/4 S12 BT
- 83.60 Asc. 221 ft. over NE slope.
- 88.30 Ridge, brs. NW-SE. Desc. 176 ft. over SW slope.
- 92.30 Wire fence, brs. N-S.
- Head of wash, course S. Asc. 29 ft. over E. slope.
- Spur, brs. SW. Desc. 35 ft. over W. slope to
- The cor. of secs. 1, 2, 11 and 12.
- Land, mountainous.
- Soil, rocky 4th. rate.
- Timber, yellow pine, oak and juniper.
- Undergrowth, oakbrush, manzanita, catclaw and cacti.


Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains

From reconstructed original cor. of secs.1,2,35 and 36, on the N. bdy. of the Tp., hereinbefore described, S.1°24'W., on true line, bet. secs. 1 and 2 (N.½) Over mountainous land, thru scattering timber and undergrowth

- Asc. 56 ft. over NE. slope.
- 1.70 Spur, brs. NW. Desc. 14 ft. over SW. slope.
- 5.60 Head of wash, course NW. Asc. 125 ft. over NE. slope.
- 10.70 Spur, brs. N.70°W. Desc. 81 ft. over SW. slope.
- 18.00 Wash, 10 lks. wide, course NW. Asc. 84 ft. over NE. slope.
- 26.40 Spur, brs. N.80°W. Desc. 143 ft. over S. slope.
- 33.20 Wash, 20 lks. wide, course W., near head. Asc. gradually over NW. slope.
- 36.00 End of spur from E. Desc. slightly over SW. slope.
- 39.00 Wash, 10 lks. wide, course NW. Asc. 47 ft. over N. slope to

39.78 intersect the original ¼ sec. cor. of secs.1 and 2, which is a granite stone 10x10x5 ins. above ground, firmly set, marked ¼ on W. face. NO accessories.
 Reconstruct this cor. monument as follows:
 alongside old cor. stone, set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, and raise a mound of stone around post, for ¼ sec. cor. of secs.1 and 2, with brass cap marked



from which
 a juniper, 16 ins. diam., brs. S.45°W., 6 lks. dist., marked ¼ S2 BT
 an oak, 4 ins. diam., brs. S.51°E., 12 lks. dist., marked ¼ S1 BT

- Thence
 S.15°42'W., on true line, bet. secs.1 and 2 (S.½)
 Over mountainous land, thru scattering timber and undergrowth.
- Asc. 71 ft. over N. slope.
 - 5.80 Ridge, brs. E.-W. Desc. 171 ft. over SW. slope.
 - 12.55 Wash, 20 lks. wide, course NW. Asc. 269 ft. over NE. slope.
 - 22.85 Spur, brs. NW. Desc. 21 ft. over SW. slope.
 - 27.45 Head of wash, course NW. Asc. 86 ft. over NE. slope.
 - 32.65 Spur, brs. N.80°W. Desc. 113 ft. over SW. slope.
 - 38.00 Wash, near head, course NW. Asc. 50 ft. over NW. slope to
 - 43.63 intersect reconstructed original cor. of secs.1,2,11. and 12.

Land, mountainous.
 Soil, rocky, 4th rate.
 Timber, oak and juniper.
 Undergrowth, scrub oak, manzanita, catclaw and cacti.

Chains	From original cor. of secs.25,26,35 and 36, S.83°17'W., on true line, bet. secs.26 and 35 (E.½) Over mountainous land, thru dense timber and undergrowth. Across patented mineral land. Asc. 15 ft. over SE. slope.
1.10	Spur, brs. NE. Desc. 40 ft. over NW. slope.
3.80	Wash, 10 lks. wide, course NE. Asc. 145 ft. over SE. slope.
4.43	Intersect the W. side line (5-6) of the "Illinois" patented lode mining claim of Mineral Survey No.671, at a point 3.89 chs. N.6°50'W. from Cor.No.5 thereof. Leave patented mineral land.
12.20	Branch spur, brs. NE. Continue ascent.
16.50	Ridge, brs. N. and S. Desc. 71 ft. over NW. slope.
24.95	Spur, brs. NW. Desc. 75 ft. over SW. slope.
30.10	Wash, 10 lks. wide, course NW. Asc. gradually over SE. slope.
32.70	Spur, brs. NE. Desc. gradually over NW. slope.
34.10	Old road, brs. N.-S.
37.50	Wash, 10 lks. wide, course N. Asc. gradually over E. slope.
38.40	Road, brs. N.-S.
39.30	Telephone line, brs. NE.-SW.
41.00	Wash, 10 lks. wide, course N. Asc. 44 ft. over NE. slope to
43.80	Intersect the reconstructed original ¼ sec.cor. of secs.26 and 35, hereinbefore described.
	Land, mountainous. Soil, rocky, 4th rate. Timber, yellow pine, oak and juniper. Undergrowth, scrub oak and cacti.

	From the reconstructed original cor. of secs.26,27, 34 and 35, hereinbefore described, N.0°40'E., on true line, bet. secs.26 and 27 (S.½) Over mountainous land, thru dense timber and undergrowth. Desc. gradually over NE. slope.
0.30	Wash, 10 lks. wide, course NW. Asc. gradually over W. slope.
4.25	Old trail, brs. E.-W.
7.25	Spur, brs. NW. Desc. 70 ft. over NE. slope.
15.55	Wash, 5 lks. wide, course NW. Asc. gradually over SW. slope.
16.65	Marquess house brs. E. about 4 chs. dist.
19.95	Flat topped spur, brs. NW.
21.35	Road, brs. E.-W. Desc. gradually over NE. slope.
27.35	Wash, 10 lks. wide, course NW. Asc. gradually over SW. slope.
27.65	Wire fence, brs. NE.-SW.
30.85	Wire fence, brs. NW.-SE.
32.35	Bridgewater's house brs. W. about 3 chs. dist.
33.75	Head of wash, course W.
34.55	Road, brs. NE.SW.
38.15	Road, brs. NW.-SE.
39.00	Moores house brs. E. 5 lks. dist.
39.75	Spring branch, 5 lks. wide, course SW. Asc. 11 ft. over SW. slope to
41.33	Intersect the original ¼ sec.cor. of secs.26 and 27, which is a granite stone 4x6x12 ins. above ground, firmly set, marked ¼ on W. face, and witnessed by, a pine stump, 22 ins. diam., N.75°W., 24 lks. dist., faintly marked. an oak stump, 20 ins. diam., S.61°E., 36 lks. dist., faintly marked Reconstruct this cor. monument as follows:

Chains

alongside old cor. stone, set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, and raise a mound of stone around post, for $\frac{1}{4}$ sec. cor. of secs. 26 and 27, with brass cap marked.

$\frac{1}{4}$
S27 | S26
1930

from which
an oak, 24 ins. diam., brs. N. $78\frac{1}{2}^{\circ}$ E., 27 lks. dist., marked $\frac{1}{4}$ S26 BT
a yellow pine, 14 ins. diam., brs. N. $52\frac{1}{2}^{\circ}$ W., 39 lks. dist., marked $\frac{1}{4}$ S27 BT

Thence
N. $2^{\circ}58'$ E., on true line, bet. secs. 26 and 27 (N. $\frac{1}{2}$)
Over rolling land, thru dense timber and undergrowth.
Asc. slightly over S. slope.

- 0.40 Spur, brs. W. Desc. 13 ft. over N. slope.
- 2.60 Wash, 10 lks. wide, course W. Asc. 24 ft. over S. slope.
- 6.05 Spur, brs. W. Old road, brs. E.-W.
Desc. 16 ft. over N. slope.
- 7.60 Wash, 10 lks. wide, course NW.
- 13.10 Head of wash, course W. Asc. gradually over S. slope.
- 14.80 Spur, brs. W. Desc. gradually over N. slope.
- 16.70 Old road, brs. E.-W. House brs. W. about 5 chs. dist.
- 19.30 Groom Creek, 50 lks. wide, course W., containing a stream of water, 10 lks. wide, 4 ins. deep.
Thence across bottom land.
- 20.11 Wire fence, brs. E.-W. Across Lang's field.
- 20.31 intersect line 5-6 of boundary of patented forest homestead entry Survey No. 69, at a point 14.15 chs. S. $88^{\circ}55'$ E. from Cor. No. 6, and 5 lks. N. $88^{\circ}55'$ W. from point for Cor. No. 5, the monument of which is missing. Cor. point and intersection of sec. line with H.E.S. bdy. determined by retracement of part of the homestead bdy. as follows:
From Cor. No. 2 retrace S. 47° E. 81 lks. and intersect Cor. No. 3, which course & dist. agrees with record.
From Cor. No. 3 retrace S. $11^{\circ}27'$ W. 1.95 chs. and intersect Cor. No. 4, also in agreement with record.
From Cor. No. 4 retrace N. $89^{\circ}00'$ W. 31 lks. to record point for Cor. No. 5, missing. Set temp. cor. No. 5.
Thence retrace N. $88^{\circ}55'$ W. 14.20 chs. and intersect Cor. No. 6, which course and dist. agrees with record.
From 20.31 ch. station on sec. line
a house brs. S. 80° E. about 5 chs. dist., another house brs. N. 70° W. about 3 chs. dist., and a well brs. N. 88° W. about 4 chs. dist.
- Across patented forest homestead, Survey No. 69.
- 22.55 Road, brs. E.-W. Asc. gradually over S. slope.
- 22.80 intersect line 1-2 of bdy. of H.E.S. No. 69 at a point 5 lks. N. 47° W. from Cor. No. 2.
Leave patented forest homestead, Surv. No. 69.
- 22.96 intersect SW. side line (4-5) of "Webfoot" patented lode mining claim of M.S. No. 1862, at a point 4.19 chs. N. $47^{\circ}59'$ W. from Cor. No. 4, and 15.95 chs. S. $47^{\circ}59'$ E. from Cor. No. 5.
Thence across patented mineral land.
- 23.35 Road, brs. NE.-SW.
- 29.65 Spur, brs. SW. Desc. gradually over NW. slope.
- 30.65 Road, brs. NW.-SE.
- 32.05 Small wash, course SW. Asc. gradually over rolling SW. slope to sec. cor.
- 34.75 Small wash, course SW.
- 36.55 Telephone line, brs. NW.-SE.
- 39.35 Prescott municipal water pipe line, brs. NW.-SE.

Chains

40.44

Intersect the original cor. of secs. 22, 23, 26 and 27, which is a mound of stone, 2 ft. base, 1 ft. high. The original oak cor. tree is gone, but bits of the stump of same still remain in the ground within the mound. This point has been accepted as the sec. cor. locally for many years.

reconstruct this cor. monument as follows:

remove the mound of stone and in center of its position set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, and rebuild mound of stone around post, for cor. of secs. 22, 23, 26 and 27, with brass cap marked

T13N	R2W
S22	S23
S27	S26

1930

from which

- a yellow pine, 10 ins. diam., brs. N. 20 $\frac{3}{4}$ ° W., 19 lks. dist., marked T13N R2W S22 BT
- a yellow pine, 16 ins. diam., brs. N. 75° E., 59 lks. dist., marked T13N R2W S23 BT
- a yellow pine, 12 ins. diam., brs. S. 89 $\frac{3}{4}$ ° E., 55 lks. dist., marked T13N R2W S26 BT
- a yellow pine, 10 ins. diam., brs. S. 50 $\frac{1}{2}$ ° W., 30 lks. dist., marked T13N R2W S27 BT

Land, mountainous and rolling.

Soil, rocky, 4th rate.

timber, yellow pine, oak and juniper.

Undergrowth, second growth timber, scrub oak and cacti.

From the reconstructed original cor. of secs. 23, 24, 25 and 26,

S. 88° 37' W., on true line, bet. secs. 23 and 26 (E. $\frac{1}{2}$)

Over mountainous land, thru dense timber and undergrowth.

Desc. 200 ft. over rolling SW. slope.

- 9.90 Wash, 20 lks. wide, course NW. Asc. 49 ft. over NE. slope.
- 14.20 Spur, brs. N. Desc. 139 ft. over NW. slope.
- 26.10 Senator Highway, brs. N.-S.
- 28.30 Wash, 5 lks. wide, course SW. Asc. slight SE. slope.
- 30.30 Spur, brs. SW. Desc. gradually over NW. slope.
- 32.90 Small wash, course SW. Asc. gradually over SE. slope.
- 36.00 Spur, brs. SW. House brs. N. about 50 lks. dist. Desc. 19 ft. over W. slope to

39.89

Intersect the original $\frac{1}{4}$ sec. cor. of secs. 23 and 26, which is a granite stone 10x12x14 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face, and witnessed by a pine stump, 16 ins. diam., S. 63° W., 64 lks. dist., marked $\frac{1}{4}$ S BT.

Hole left by removal of original bearing tree, brs. N. 84° W., 81 lks. dist.

Reconstruct this cor. monument as follows:

alongside old cor. stone, set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 23 and 26, with brass cap marked

$\frac{1}{4}$ S 23
$\frac{1}{4}$ S 26

1930

from which

- a yellow pine, 12 ins. diam., brs. N. 46° E., 15 lks. dist., marked $\frac{1}{4}$ S23 BT
- a yellow pine, 10 ins. diam., brs. S. 39 $\frac{1}{2}$ ° W., 14 lks. dist., marked $\frac{1}{4}$ S26 BT


Re-Survey of Part of The Subd. Lines of T.13 N., R.2 W. 53

Chains

Thence,
 S.89°10'W., on true line, bet. secs. 23 and 26, (W $\frac{1}{2}$)
 Over rolling land.
 4.80 Old road, brs. NE-SW.
 9.70 Shallow wash, course NW.
 12.30 Road, brs. NE-SW.
 12.80 Telephone line, brs. N. and to SE.
 15.50 Same shallow wash, course SW.
 17.50 Old road, brs. N-S. House brs. S. about 10 chs. dist.
 19.30 Spur, brs. SW.
 21.20 Head of wash, course SW.
 24.60 Spur, brs. SW.
 26.30 Head of wash, course SW.
 29.60 Spur, brs. SW. Desc. 25 ft. over NE slope.
 33.20 Wash, 5 lks. wide, course SW. Asc. 9 ft. over SE slope.
 34.70 Spur, brs. SW. Desc. 24 ft. over NW slope.
 38.08 Intersect the NE side line, (1-4) of the patented lode
 mining claim "Miners Dream," Min. Sur. No. 3660, at
 5.82 chs. N.38°56'W. of Cor. No.1.
 Across patented mineral land.
 37.75 Wash, 5 lks. wide, course SW. Asc. gradual SE slope.
 40.30 Intersect the reconstructed cor. of secs. 22, 23, 26
 and 27.

Land, rolling.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush and cacti.

N.0°42'E., on true line, bet. secs. 22 and 23.
 Over rolling land, thru thick timber & undergrowth.
 Across patented mineral land.
 Asc. 49 ft. over S. slope.
 2.74 Intersect the NE side line (1-4) of the "Miners Dream,"
 pat. lode mining claim, Min. Sur. No. 3660, at 13.00
 chs. S.38°56'E. of Cor. No. 4 thereof. Leave patented
 mineral land.
 13.10 Divide, brs. West. Desc. 32 ft. over N. slope.
 30.15 Yellow pine, 24 ins. on line.
 35.60 Spur, brs. NE.
 38.00 Road, brs. E-W.
 39.50 Wash, 10 lks. wide, course N.10°E.
 41.20 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 14 ins. in the ground to bedrock; raise a mound of
 stone about post, for the reestablished $\frac{1}{4}$ sec. cor.
 of secs. 22 and 23, with brass cap marked



1930 from which,
 a yellow pine, 10 ins. in diam., brs. N.22°W., 11 lks.
 dist., marked $\frac{1}{4}$ S22 BT
 a yellow pine, 26 ins. in diam., brs. S.73°E., 23 lks.
 dist., marked $\frac{1}{4}$ S23 BT

Continue over level land, across granite boulders.
 46.15 Spur, brs. NW. from SW. Desc. 68 ft. over NE slope.
 55.40 Bannon Creek, stream of water, 10 lks. wide, 4 ins. deep,
 course NW. Asc. 19 ft. over SW slope.
 59.47 Spur, brs. NW. Desc. 24 ft. over NE slope.
 Intersect the SE side line (2-3) of the "Good Year No.2"
 pat. lode claim, at 8.62 chs. S.14°23'W. of Cor. No.2.

Chains

61.35 Telephone line, brs. NW-SE.
 62.95 Wash, 20 lks. wide, course NW. Asc. gradual SW slope.
 68.34 Intersect the NE end line (1-2) of the "Goodyear No. 2"
 pat., lode mining claim, M.S. No. 3967, at 2.10 chs.
 N. 75° 37' W. of Cor. No. 2. Leave pat. mineral land.
 69.60 Spur, brs. NW. Desc. 26 ft. over N. slope.
 71.15 Wash, 5 lks. wide, course West.
 Asc. 19 ft. over S. slope.
 72.80 Spur, brs. West. Desc. 22 ft. over N. slope.
 73.75 Wash, 10 lks. wide, course W.
 Asc. 22 ft. over SE slope.
 75.80 Spur, brs. SW. Desc. 28 ft. over NW slope.
 80.05 Wash, 10 lks. wide, course SW. Asc. 28 ft. over SE slope.
 82.40 Intersect the original cor. of secs. 14, 15, 22 and 23,
 which is stump of an oak tree, 10 ins. in diam.,
 standing four feet above ground, blazed on four faces
 but scribe marks on same faintly visible. No bearing
 trees. This stump has been recognized locally for
 years past.

Reconstruct this cor. monument as follows:

Alongside the old cor. tree set an iron post 3 ft. long,
 2 ins. in diam.; 20 ins. in the ground to bedrock,
 raise a mound of stone about post, for the cor. of
 secs. 14, 15, 22 and 23, with brass cap marked

T13N	R2W
S15	S14
S22	S23

1930

from which,

- a yellow pine, 8 ins. in diam., brs. N. 26 1/4° E., 15
lks. dist., marked T13N R2W S14 BT
- a yellow pine, 5 ins. in diam., brs. S. 23° E., 5 lks.
dist., marked T13N R2W S23 BT
- a yellow pine, 8 ins. in diam., brs. S. 33° W., 35 lks.
dist., marked T13N R2W S22 BT
- a yellow pine, 10 ins. in diam., brs. N. 40 1/2° W., 16 lks.
dist., marked T13N R2W S15 BT

Land, mountainous.

Soil, rocky 4th. rate.

Timber, yellow pine, oak and juniper:

Undergrowth, oakbrush and cacti.

From the reestablished cor. of secs. 13, 14, 23 and 24.
 S. 86° 14' W., on true line, bet. secs. 14 and 23, (E 1/2)
 Over mountainous land, thru scattering timber and thick
 undergrowth.


Asc. 18 ft. over E. slope.

0.72 Wire fence, brs. N. 80° W. - S. 80° E.
 2.80 Spur, brs. N. Desc. 29 ft. over W. slope.
 4.50 Head of wash, course NW. Asc. 14 ft. along N. slope.
 10.50 Spur, brs. NW. Desc. 313 ft. over SW slope.
 30.10 Wash, 20 lks. wide, course SW. Asc. 99 ft. over SE slope.
 33.00 Old road, brs. NE-SW.
 38.18 Intersect the original 1/4 sec. cor. of secs. 14 and 23,
 which is a stone 10 x 10 x 10, firmly set in a mound
 of stone, faintly marked 1/4 on one face, no bearing
 trees. Reconstruct this cor. monument by setting an
 iron post 3 ft. long, 1 in. in diam., 8 ins. in the
 ground to bedrock, alongside old stone cor., with

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W. 55

Chains

brass cap marked




1930 from which,
 a juniper, 8 ins. in diam., brs. N.58°E., 105 lks.
 dist., marked $\frac{1}{4}$ S14 BT
 no other bearing tree available.

- 18.15 Thence, N.89°27'W., on true line, bet. secs. 14 & 23 (W $\frac{1}{2}$)
- 22.40 Desc. 184 ft. over West slope.
- 28.00 Senator Highway, brs. N-S.
- 35.64 Wash, 10 lks. wide, course SW.
- 38.54 Asc. 39 ft. over SE slope.
- Spur, brs. SW. Desc. 75 ft. over NW slope.
- Asc. 16 ft. over SE slope.
- Intersect the cor. of secs. 14, 15, 22 and 23.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita, cacti and catclaw.

- 3.60 N.0°43'W., on true line, bet. secs. 14 and 15, (S $\frac{1}{2}$)
 - 4.40 Over mountainous land, thru thick timber and undergrowth.
 - 6.15 Asc. gradual SE slope.
 - 14.05 Spur, brs. SW. Desc. gradual N. slope.
 - 15.50 Head of wash, course W.
 - 15.85 Spur, brs. SW. Desc. 14 ft. over NW slope.
 - 19.95 Rocky wash, course SW. Asc. 49 ft. over SE slope.
 - 21.40 Wash, 10 lks. wide, course SW. Asc. gradual S. slope.
 - 23.60 Spur, brs. SW. Desc. 9 ft. over NW slope.
 - 25.60 Wash, 10 lks. wide, course SW. Asc. 24 ft. over SE slope.
 - 29.00 Spur, brs. SW. Desc. 12 ft. over NW slope.
 - 31.50 Head of wash, course SW. Asc. 12 ft. over SE slope.
 - 40.56 Spur, brs. W. Desc. 26 ft. over N. slope.
 - Wash, 10 lks. wide, course W. Asc. 46 ft. over S. slope.
 - Senator Highway, brs. NE-SW. Asc. 29 ft. over SW slope.
 - Intersect the original $\frac{1}{4}$ sec. cor. of secs. 14 and 15,
 which is a granite stone 8 x 10 x 12 ins. above ground,
 firmly set in a mound of stone, marked $\frac{1}{4}$ on W. face.,
 no bearing trees.
- reconstruct this cor. monument as follows:
 alongside old stone cor., set an iron post 3 ft. long,
 1 in. in diam., 26 ins. in the ground for the $\frac{1}{4}$ sec.
 cor. of secs. 14 and 15, with brass cap marked



1930 from which,
 a juniper, 14 ins. in diam., brs. N.22 $\frac{1}{2}$ °E., 34 lks.
 dist., marked $\frac{1}{4}$ S14 BT
 a yellow pine, 8 ins. in diam., brs. West, 48 lks.
 dist., marked $\frac{1}{4}$ S15 BT

56. Re-Survey of Part of the Subd. Lines of T. 13 N., R. 2 W.

Chains

Thence,
 N.12°05'W., on true line, bet. secs. 14 and 15, (N $\frac{1}{2}$)
 Asc. gradual SW slope.
 1.00 Spur, brs. NW. Desc. 37 ft. over NE slope.
 6.30 Wash, 20 lks. wide, course NW. Asc. 22 ft. over SW slope.
 8.20 Spur, brs. NW. Desc. 47 ft. over NE slope.
 11.80 Wash, 10 lks. wide, course NW. Asc. 18 ft. over SW slope.
 13.40 Spur, brs. NW. Desc. 13 ft. over NE slope.
 14.90 Wash, 10 lks. wide, course NW. Asc. 9 ft. over SW slope.
 15.90 Spur, brs. NW. Desc. 52 ft. over NE slope.
 20.30 Wash, 5 lks. wide, course NW. Asc. 21 ft. over SW slope.
 20.90 Spur, brs. N.10°W. Desc. 61 ft. over NW slope.
 29.20 Wash, 10 lks. wide, course NE. Asc. 19 ft. over SE slope.
 29.50 Road, brs. N.20°E.-S.20°W.
 38.60 Spur, brs. E. Desc., 17 ft. over N. slope.
 39.10 Wash, 5 lks. wide, course E. Asc. gradual S. slope.
 40.90 Page wire fence, brs. E-W.
 41.90

intersect the original cor. of secs. 10, 11, 14 and 15,
 which is a mound of stone 4 ft. wide, 1 ft. high
 in center of which find stump of oak tree.
 This mound agrees with the 1871 survey record distance
 to site of old Govt. sawmill in Government Canyon
 about 5 chs. Northeasterly. The site of old mill
 was determined after careful investigation.
 Reconstruct this cor. monument as follows:
 Alongside old stump in mound of stone set an iron post
 3 ft. long, 2 ins. in diam., 24 ins. in the ground
 for the cor. of secs. 10, 11, 14 and 15, with brass
 cap marked

T13N	R2W
S10	S11
S15	S14

1930 from which,
 an oak, 8 ins. in diam., brs. N.55 $\frac{1}{4}$ °W., 53 lks.
 dist., marked T13N R2W S10 BT
 a yellow pine, 12 ins. in diam., brs. N.36°E., 51 lks.
 dist., marked T13N R2W S11 BT
 a yellow pine, 14 ins. in diam., brs. S.42 $\frac{1}{4}$ °E., 45 lks.
 dist., marked T13N R2W S14 BT
 a yellow pine, 9 ins. in diam., brs. S.47 $\frac{1}{2}$ °W., 18 lks.
 dist., marked T13N R2W S15 BT


Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, catclaw and cacti.

From the reestablished cor. of secs. 11, 12, 13 & 14.
 S.89°05'W., on true line, bet. secs. 11 and 14.
 Over mountainous land, thru thick timber & undergrowth.
 Asc. 25 ft. over NE slope.
 4.90 Slope changes to NW. Desc. 247 ft. over same slope.
 27.00 Wash, 10 lks. wide, course NW. Asc. 13 ft. over NE slope.
 27.40 Telephone line, brs. NW-SE. Wire fence, brs. NE-SW.
 28.00 Spur, brs. NW. Desc. 30 ft. over SW slope.
 30.40 Wash, 20 lks. wide, course NW. Asc. 37 ft. over NE slope.
 33.55 Desc. 54 ft. along N. slope.

Re-Survey of Part of the Subd. Lines of T.13 N., R.2W. 57

Chains

39.77 (Midpoint) set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for the reestablished 1/4 sec. cor. of secs. 11 and 14, with brass cap marked



1930 from which, a yellow pine, 6 ins. in diam., brs. N.62 1/2°W., 3 lks. dist., marked 1/4 S11 BT a yellow pine, 8 ins. in diam., brs. S.23°W., 38 lks. dist., marked 1/4 S14 BT

46.00 On spur, brs. NW. Desc. 96 ft. over W. slope. Wash, 10 lks. wide, course N. Asc. 99 ft. over E. slope.

49.65 Spur, brs. NE. Desc. 44 ft. over NW slope. 51.95 Wash, 10 lks. wide, course NE. Asc. 161 ft. over NE slope.

60.00 Spur, brs. NE. Desc. 253 ft. over West slope. 68.55 Wash, 10 lks. wide, course NW. Asc. gradual NE slope.

72.54 Spur, brs. E. Desc. 17 ft. over W. slope. 73.25 Wash, 10 lks. wide, in Govt. Canyon, course North. Asc. gradual E. slope.

74.84 Road, brs. N-S. 79.54 Intersect the cor. of secs. 10, 11, 14 and 15.

Land, mountainous. Soil, rocky 4th. rate. Timber, yellow pine, juniper and oak. Undergrowth, oakbrush, manzanita and cacti.

N.0°16'E., on true line, bet. secs. 10 and 11(S 1/2) Over mountainous land, thru thick timber & undergrowth. Asc. slight SE slope.

2.00 Spur, brs. E. Old timber road, brs. E-W. The site of old Government sawmill, in Government Canyon, brs. E. about 5 chs. dist. There is a small house and spring there now.

Desc. 31 ft. over NE slope. 3.95 Wash, 10 lks. wide, course NE. Asc. 17 ft. over S. slope. 6.30 Spur, brs. E. Desc. 32 ft. along E. slope. 8.30 Wash, 5 lks. wide, course E. Asc. gradual S. slope. 11.80 Spur, brs. E. Desc. 11 ft. over S. slope. 12.00 Wash, 5 lks. wide, course E. Asc. 9 ft. over S. slope. 13.50 Spur, brs. E. Desc. 14 ft. over N. slope. 14.45 Wash, 5 lks. wide, course E. Asc. 18 ft. along E. slope. 16.10 Spur, brs. E. Desc. 46 ft. over NW slope. 19.90 Wash, 10 lks. wide, course NE. Asc. 9 ft. over SE slope. 20.90 Spur, brs. NE. Desc. 18 ft. over NW slope. 22.10 Junction of washes from SW and NW, thence NE. Asc. 9 ft. over SE slope. 23.00 Spur, brs. NE. Desc. 14 ft. over NW slope. 24.80 Head of wash, course NE. Asc. gradual SE slope. 26.90 Spur, brs. NE. Desc. 17 ft. over NW slope. 31.50 Wash, 10 lks. wide, course NE. Asc. 103 ft. over SE slope.

58 Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.


Chains

40.93

Intersect the original 1/4 sec. cor. of secs. 10 and 11, which is a stone 18 x 10 x 10 ins. set in amount of stone; this cor. stone is unmarked, but accept same as the 1/4 sec. cor. in view of old blazes leading to cor. on N-S lines and from which, a yellow pine, 40 ins. in diam., brs. N.19 3/4° W., 36 lks. dist., an old blaze has grown over, but marks on tree have disappeared.

Reconstruct this cor. monument as follows:

Alongside the original cor. stone, set an iron post 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, raise a mound of stone about post for the 1/4 sec. cor. of secs. 10 and 11, with brass cap marked



1930 from which, an oak, 6 ins. in diam., brs. S.55° E., 65 lks. dist. marked 1/4 S11 BT
Remarkd original NW BT 1/4 S 10 BT.


Thence, N.11° 02' W., on true line, bet. secs. 10 and 11, (N 1/2) Asc. 116 ft. over SE slope.

12.00
12.45
21.90
22.60
26.00
26.55
33.15
35.60
40.93

Spur, brs. NE. Desc. 78 ft. over N. slope.
McMurrens house, brs. N.82° E., about 50 chs. dist.
Trail, brs. NW-SE.
Head of wash, course E. Asc. 115 ft. over S, slope.
Old road, brs. NE-SW. On ridge, brs. NE-SW.
Page wire fence, brs. NE-SW.
Goat shed, brs. W. about 5 chs. dist. Ridge, brs. NW-SE.
Old road, brs. NW-SE. Desc. 123 ft. over NE slope.
Intersect the original cor. of secs. 2, 3, 10 and 11, which is a mound of stone 4 ft. wide, 1 ft. high, in center of which is a stone 20 x 10 x 4 ins. marked with 2 notches on one side, no other marks.

Reconstruct this cor. monument as follows:

Alongside the original cor. stone, set an iron post 3 ft. long, 2 ins. in diam., 16 ins. in the ground to bedrock, raise a mound of stone about post, for the cor. of secs. 2, 3, 10 and 11, with brass cap marked



1930 from which,

a juniper, 8 ins. in diam., brs. N.68° W., 22 lks. dist., marked T13N R2W S3 BT
a juniper, 18 ins. in diam., brs. N.67° E., 96 lks. dist., marked T13N R2W S2 BT
a juniper, 8 ins. in diam., brs. S.65 1/4° E., 70 lks. dist., marked T13N R2W S11 BT
a juniper, 10 ins. in diam., brs. S.55° W., 38 lks. dist., marked T13N R2W S10 BT

Re-Survey of Part of the Subd. Lines of T.13 N., R.2W. 159

chains


Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush, manzanita, catclaw and cacti.

From the cor. of secs. 1, 2, 11 and 12.

S.88°35'W., on true line, bet. secs. 2 and 11, (E½)
Over mountainous land, thru scattering timber & thick undergrowth.

- 18.80 Desc. 490 ft. over rolling W. slope.
- 21.70 Deep mine shaft, brs. N. about 150 lks.
- 26.70 Old road, brs. NE-SW.
- 36.70 Same old road, brs. NW-SE.

37.47 intersect the original ¼ sec. cor. of secs. 2 and 11, which is a stone 8 x 8 x 12 ins. lying in mound of stone, faintly marked ¼ on one face. No bearing trees. Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground alongside old cor. stone, with brass cap marked



1930 from which,
a yellow pine, 12 ins. in diam., brs. N.70°W., 23 lks. dist., marked ¼ S2 BT
a juniper, 6 ins. in diam., brs. S.69½°E., 89 lks. dist., marked ¼ S11 BT

Thence,
N.89°15'W., on true line, bet. secs. 2 and 11, (W½)
Desc. 98 ft. over W. slope to wash.

- 2.30 Old road, brs. NW-SE.
- 6.50 Road, brs. N-S.
- 7.10 center of Government Canyon, 100 lks. wide, course N.
- 8.000 Road, brs. N-S., on W. edge of Canyon.
- 9.95 Asc. slight NE slope.
- 9.95 Side wash, 10 lks. wide, course NE.
- 14.40 Asc. 139 ft. over E. slope.
- 14.40 Power line, brs. N.30°W.-S.30°E.
- 18.70 Spur, brs. NE. Desc. 13 ft. over NW slope.
- 21.45 Wash, near head, course NE. Asc. 173 ft. over SE slope.
- 24.40 Telephone line, brs. N.26°W.-S.26°E.
- 27.25 Page wire fence, brs. N.10°E.-S.10°W.
- 28.30 Ridge, brs. N-S. Desc. 49 ft. over West slope.
- 33.07 intersect the cor. of secs. 2, 3, 10 and 11.

Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush, manzanita, catclaw and cacti.

From the reestablished cor. of secs. 2, 3, 34 & 35, on N. bdy. of Tp., hereinbefore described.
S.2°04'W., on true line, bet. secs. 2 and 3, (N½)
Over mountainous land, thru scattering timber & thick undergrowth.


Chains	
	Across bottom of Government canyon.
4.15	Center of wash, 1 ch. wide, course NW.
6.50	Road, brs. N-S.
6.95	Wire fence, brs. N-S.
7.75	Same fence, brs. E-W. Asc. 315 ft. over NE slope.
39.73	Intersect the original $\frac{1}{4}$ sec. cor. of secs. 2 & 3, which is a stone 4 x 8 x 14 ins. above ground and mound of stone, marked $\frac{1}{4}$ on W. face. No bearing trees. Reconstruct this cor. monument as follows: Alongside old stone cor. set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, with brass cap marked.
	$\frac{1}{4}$ S3 S2
	1930 from which,
	a juniper, 5 ins. in diam., brs. N.75°E., 33 lks. dist., marked $\frac{1}{4}$ S2 BT
	a juniper, 12 ins. in diam., brs. N.7°W., 90 lks. dist., marked $\frac{1}{4}$ S3 BT
	Thence, S.3°26'W., on true line, bet. secs. 2 and 3, (S $\frac{1}{2}$) Asc. slight NE slope.
.20	Ridge, brs. NW-SE. Desc. 74 ft. over SW slope.
9.60	Wash, 10 lks. wide, course NW. Asc. 186 ft. over NE slope.
15.40	Power line, brs. N.26°W.-S.26°E.
20.75	Page wire fence, brs. E-W.
21.70	Spur, brs. NW. Desc. 94 ft. over SW slope.
28.65	Wash, at head, course NW. Asc. 88 ft. over NE slope.
32.10	Spur, brs. NW. Telephone line, brs. N.33°W.-S.33°E. Desc. 29 ft. over SW slope.
39.40	Wash, 10 lks. wide, course NW. Asc. 51 ft. up wash.
41.80	Leave wash, to SE. Asc. gradual NE slope.
42.10	Intersect the cor. of secs. 2, 3, 10 and 11.
	Land, mountainous. Soil, rocky 4th. rate. Timber, oak and juniper. Undergrowth, oakbrush, catclaw and cacti.

	The reestablished cor. of secs. 27, 28, 33 and 34 is an iron post 2 ins. in diam., firmly set, projecting 12 ins. above ground and with brass cap properly marked, with four properly marked bearing trees, one each NW, NE, SE and SW of cor. Thence, N.1°14'E., on true line, bet. secs. 27 and 28. Over mountainous land, thru thick timber & undergrowth. Desc. slight NE slope.
6.65	Wash, 10 lks. wide, course NW. Asc. 32 ft. over SW slope.
8.50	Spur, brs. SW. Desc. 43 ft. over NE slope.
14.75	Wash, 10 lks. wide, course NW. Asc. 14 ft. over SW slope.
17.10	Spur, brs. NW. Desc. 20 ft. over NE slope.
18.60	Wash, 10 lks. wide, course W. Asc. 21 ft. over SE slope.
20.60	Spur, brs. SW. Desc. 9 ft. over NW slope.
21.90	Old road, brs. E-W.

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W. 61

Chains


24.60 Wash, 10 lks. wide, course SW. Asc. gradual S. slope.
 25.40 Spur, brs. W. Old sawmill brs. W. about 3 chs. dist.
 Desc. 45 ft. over N. slope.
 28.40 Groom Creek, stream of running water 20 lks. wide, 5 ins.
 deep, course SW. Asc. 36 ft. over gradual S. slope.
 Leave timber, brs. N.70°E.-SW.
 31.50 Road, brs., NE-SW.
 32.00 Enter timber, brs. E-W.
 38.70 Spur, brs. SE. Desc. 6 ft. over gradual NE slope.
 40.51 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 20 ins. in the ground to bedrock, raise a mound of
 stone about post, for the reestablished $\frac{1}{4}$ sec. cor.
 of secs. 27 and 28, with brass cap marked



1930 from which,
 a yellow pine, 20 ins. in diam., brs. S.72 $\frac{1}{2}$ °W., 28 lks.
 dist., marked $\frac{1}{4}$ S28 BT
 a yellow pine, 10 ins. in diam., brs. S.53°E., 36 lks.
 dist., marked $\frac{1}{4}$ S27 BT

Desc. gradual NW slope.
 42.50 Wash, 10 lks. wide, course SE. Asc. 64 ft. over SE slope.
 48.00 Spur, brs. NE. Desc. 17 ft. over NW slope.
 48.50 Wash, 10 lks. wide, course NE. Asc. 77 ft. over SE slope.
 59.60 Spur, brs. SE. Desc., 9 ft. over NE slope.
 61.60 Wash, 10 lks. wide, course SE. Asc. 208 ft. over SW slope.
 77.40 Spur, brs. SE. Desc. 25 ft. over NE slope.
 79.00 Head of wash, course SE. Asc. 23 ft. over SW slope.
 81.02 intersect the cor. of secs. 21, 22, 27 and 28, which is
 a stone 8 x 10 x 14 ins., firmly set, properly marked
 set in a mound of stone, with two properly marked
 bearing trees NW and SE of cor. Reconstruct this cor.
 monument as follows:

Alongside old cor. stone set an iron post 3 ft. long, 2 ins.
 in diam., 24 ins. in the ground for the cor. of secs.
 21, 22, 27 and 28, with brass cap marked.



1930 from which,
 a juniper, 24 ins. in diam., brs. N.87°W., 39 lks. dist.
 marked T13N R2W S21 BT
 a yellow pine, 12 ins. in diam., brs. N.15°E., 200 lks.
 dist., marked T13N R2W S22 BT
 a yellow pine, 12 ins. in diam., brs. S.85 $\frac{1}{2}$ °E., 36 lks.
 dist., marked T13N R2W S27 BT
 a juniper, 18 ins. in diam., brs. S.21 $\frac{1}{2}$ °W., 133 lks.
 dist., marked T13N R2W S28 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, oak, yellow pine and juniper.
 Undergrowth, oakbrush, and cacti.

Chains

From the cor. of secs. 22, 23, 26 and 27.
 N. 89°45'W., on true line bet. secs. 22 and 27.
 Over rolling land, thru thick timber and scattering
 undergrowth. Across patented mineral land.

1.41 Prescott pipe line, brs. NW-SE.
 4.85 House, brs. S. 1½ chs. dist.
 5.15 Road, brs. N-S.
 8.70 Shallow wash, course SW.
 9.75 Low spur, brs. SW.
 11.35 Small wash, course SW.
 18.85 Old mill, brs. N. 200 lks. dist.
 19.75 Old road, brs. NE-SW.
 21.35 Spur, brs. S.
 21.40 Intersect the SW side line (2-3) of the "Blake" patented
 lode mining claim, Min. Sur. No. 3660, at 11.09 chs.
 N. 51°28'W., of Cor. No. 2 thereof.
 Leave patented mineral land.

33.85 Shallow wash, course SW.
 36.07 Pipe line, brs. N-S. (Prescott).
 37.27 Road, brs. NE-SW.
 38.87 Wash, 20 lks. wide, course SW. A spring brs. NE 50 lks.
 dist.

40.27 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 22 ins. in the ground to bedrock, raise a mound of stone
 about post, for the reestablished ¼ sec. cor. of secs.
 22 and 27, with brass cap marked

$\frac{1}{4}$ S 22

 S 27

1930 from which,

an oak, 24 ins. in diam., brs. N. 38°W., 24 lks. dist.
 marked ¼ S22 BT
 a yellow pine, 10 ins. in diam., brs. S. 12°W., 7 lks.
 dist., marked ¼ S27 BT
 A spring of water, brs. N. 80°E., 228 lks. dist.
 " " " " , brs. S. 57½°E., 305 chs. dist.

Leave rolling, enter mountainous land, and thick brush.
 Asc. 96 ft. over NE slope.


51.45 Spur, brs. SE. Desc. 12 ft. over SW slope.
 56.60 Wash, course SE. Asc. 15 ft. over E. slope.
 57.70 Spur, brs. S. Desc. 11 ft. over W. slope.
 58.64 wash, 10 lks. wide, course S. Asc. 56 ft. over NE slope.
 62.35 Spur, brs. SE. Desc. 46 ft. over SW slope.
 66.25 Prescott fence, brs. N-S.
 69.60 Wash, 20 lks. wide, course SE. Asc. 65 ft. over SE slope.
 75.50 Spur, brs. SE. Desc. 12 ft. over SW slope.
 78.10 Wash, 10 lks. wide, course SE. Asc. 56 ft. over SE slope.
 80.54 Intersect the cor. of secs. 21, 22, 27 and 28.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, cacti.

Re-survey of Part of the Subd. Lines of T.13 N., R.2 W. 6163

Chains

N.2°26'W., on true line, bet. secs. 21 and 22.
 Over mountainous land, thru thick timber & undergrowth.
 Asc. 32 ft. over SE slope.
 3.40 Ridge, brs. NE-SW. Desc. 187 ft. over NW slope.
 15.60 Wash, 10 lks. wide, course NW. Asc. 98 ft. over SW slope.
 18.30 Ridge, from SE to N. Desc. 125 ft. down same.
 37.40 Leave ridge to NW. Desc. 119 ft. over NE slope.
 40.81 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 26 ins. in the ground for the reestablished 1/4 sec. cor.
 of secs. 21 and 22, with brass cap marked




1930 from which,

a yellow pine, 10 ins. in diam., brs. S.63 1/2°E., 17 lks. dist., marked 1/4 S22 BT
 a yellow pine, 8 ins. in diam., brs. S.78°W., 32 lks. dist., marked 1/4 S21 BT

Desc. 65 ft. over NE slope.
 44.30 Wash, 20 lks. wide, course NW. Asc. 13 ft. over SW slope.
 45.80 Spur, brs. West. Asc. 19 ft. over rolling SW slope.
 50.70 Spur, brs. West. Desc. 33 ft. over N. slope.
 51.80 Wash, 10 lks. wide, course west.
 Asc. 70 ft. over S. slope.
 57.60 Ridge, brs. NW-SE. Desc. 151 ft. over NE slope.
 63.10 Wash, 10 lks. wide, course NW. Asc. 151 ft. over SW slope.
 70.50 Spur, brs. NW. Road, brs. SE -NW. Desc. 37 ft. over NE slope.
 73.25 Wash, 10 lks. wide, course W. Asc. 17 ft. over S. slope.
 76.00 Spur, brs. West. Desc. 33 ft. over N. slope.
 79.40 Wash, 5 lks. wide, course W. Asc. 37 ft. over SW slope.
 81.62 Intersect the original cor. of secs. 15, 16, 21 and 22, which is a granite stone 12 x 12 x 8 ins. above ground, firmly set, in old mound of stone, marked with 3 and 3 grooves on S. and E. faces, from which, a cedar stump, 3 ft. diam., 2 ft. high, brs. S.75°E., 65 lks. dist., marked SXX11BT

Reconstruct this cor. monument as follows:
 Alongside old stone cor. set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for the cor. of secs. 15, 16, 21 and 22, with brass cap marked



1930 from which,

a yellow pine, 12 ins. in diam., brs. N.60°W., 79 lks. dist., marked T13N R2W S16 BT
 an oak, 6 ins. in diam., brs. N.58°E., 41 lks. dist., marked T13N R2W S15 BT
 an oak, 5 ins. in diam., brs. S.41°E., 79 lks. dist., marked T13N R2W S22 BT
 a yellow pine, 12 ins. in diam., brs. S.40°W., 76 lks. dist., marked T13N R2W S21 BT

Land, mountainous.
 Soil, rocky 4th. rate.

Chains

Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush, manzanita, cacti.

From the cor. of secs. 14, 15, 22 and 23.
N. 89° 55' W.; on true line, bet. secs. 15 and 22, ($E\frac{1}{2}$)
Over mountainous land, thru thick timber & undergrowth.
Desc. 70 ft. over NW slope.

1.10 Old road, brs. NE-SW.
4.00 Same road, brs. NW-SE.
6.90 Wash, 10 lks. wide, course SW. Asc. gradual SE slope.
8.90 Spur, brs. SW. Desc. 19 ft. over NW slope.
13.10 Rocky wash, 20 lks. wide, course SW. Asc. 20 ft. over SE slope.
15.15 Old road, brs. NW-SE.
15.60 Spur, brs. SW. Desc. gradual NW. slope.
18.20 Road, brs. NW-SE. Across rolling land.
19.75 Telephone line, brs. NW-SE.
21.25 New pipe line, brs. NW-SE.
Road, brs. NW-S.
24.40 Enter Bannon Creek, course NW. Small stream of water in same.
26.25 Leave Bannon Creek. Asc. 67 ft. over NE slope, entering mountainous land.
31.50 Desc. 42 ft. over NW slope.
37.20 Wash, course N. Asc. 48 ft. over NE slope.
41.30 Spur, brs. NW. Desc. gradual SW slope to
42.20 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 15 and 22, which is a granite stone 5 x 9 x 15 ins. set firmly in a mound of stone, marked $\frac{1}{4}$ on N. face. from which, a pine stump 2 ft. diam., 2 ft. high, brs. S. 12 lks. dist., scribe marks on same.
Hole at foot of fallen pine snag, brs. N. 77° W., 35 lks. dist., part of same being marked $\frac{1}{4}$ SBT
Reconstruct this cor. monument as follows:
Alongside the old cor. stone set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, with brass cap marked

$\frac{1}{4}$ $\frac{S15}{S22}$

1930 from which,
an oak, 8 ins. in diam., brs. N. 78° W., 20 lks. dist., marked $\frac{1}{4}$ S15 BT
a yellow pine, 8 ins. in diam., brs. S. 89½° E., 37 lks. dist., marked $\frac{1}{4}$ S22 BT


Thence,
S. 89° 40' W., on true line, bet. secs. 15 and 22, ($W\frac{1}{2}$)
Desc. 92 ft. over SW slope.

5.20 City fence, brs. NE-SW. At edge of Lake Goldwater.
at mouth of wash frm S. across lake.
6.00 Leave lake. Asc. 40 ft. over NE slope.
6.30 Fence, brs. NW-SE.
9.00 Spur, brs. NW. Desc. 13 ft. over W. slope.
10.20 Wash, 10 lks. wide, course N. Asc. 61 ft. over E. slope.
12.00 Spur, brs. N. Desc. 58 ft. over W. slope.
14.60 Wash, 10 lks. wide, course N. (50 lks. S. of edge of lake.)

Chains
 17.00 Asc. 51 ft. over E. slope.
 20.00 Spur, brs. N. Thence along level N. slope.
 West end of City dam, brs. N. about 4 chs. dist.
 Asc. 45 ft. over NE slope.
 22.00 Ridge, brs. NW-SE. Desc. 135 ft. over rolling NW slope.
 28.30 Wash, 20 lks. wide, course NW. Asc. 43 ft. over NE slope.
 34.20 City fence, brs. NW-SE.
 35.20 Ridge, brs. NW-SE. Over top, level.
 36.00 Leave top; desc. 21 ft. over W. slope to
 42.54 Intersect the original cor. of secs. 15, 16, 21 and 22.

Land, mountainous and rolling.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush and cacti.

N.4°30'W., on true line, bet. secs. 15, and 16.
 Over mountainous land, thru thick timber and undergrowth.
 Asc. 23 ft. over rolling S. slope.
 5.00 Spur, brs. West. Desc. 60 ft. over NW slope.
 7.70 Head of wash, course NW. Along level W. slope.
 11.00 Desc. 120 ft. over NW slope.
 20.65 Wash, 10 lks. wide, course NE. Asc. gradual SE slope.
 23.60 Citys wire fence, brs. NW-SE.
 28.00 Desc. 15 ft. over N. slope.
 28.40 Wash, 10 lks. wide, course East. Asc. 39 ft. over
 South slope.
 31.50 Citys wire fence, brs. N.10°E.-S.10°W.
 33.60 Spur, brs. E. Desc. 65 ft. over N. slope.
 34.75 road, brs. NE-SW.
 37.50 wire fence, brs. NW-SE.
 39.00 Wash, 10 lks. wide, course E. Asc. 17 ft. over S. slope.
 41.30 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 26 ins. in the ground for the reestablished $\frac{1}{4}$ sec. cor.
 of secs.15 and 16, with brass cap marked



1930 from which,
 a yellow pine, 10 ins. in diam., brs. N.54°W., 15 lks.
 dist., marked $\frac{1}{4}$ S16 BT
 a yellow pine, 10 ins. in diam., brs. S.30°E., 21 lks.
 dist., marked $\frac{1}{4}$ S15 BT

Asc. 31 ft. over SE slope.
 42.80 Wash, course E. Asc. gradual S. slope.
 46.30 Spur, brs. E. Desc. 56 ft. over N. slope.
 49.55 Wash, 10 lks. wide, course NE.
 Asc. 77 ft. over S. slope.
 55.80 Spur, brs. E. Desc. 66 ft. over N. slope. Fence, brs. NE-SW.
 56.30 Fence, brs. NW.
 58.65 Wash, course NE. (at head). Asc. 52 ft. over SE slope.
 62.20 Spur, brs. NE. Desc. 141 ft. over NW slope.
 71.50 Bannan Creek, 100 lks. wide, course NW. (Dry).
 73.50 Road, brs. E-W. Asc. 101 ft. over SW slope to
 82.60 intersect the true point for the cor. of secs. 9, 10, 15
 and 16 determined from original BT.

Chains

From the original B¹, which is a cedar 20 ins. in diam., marked T13N S10 BT, measure 19 lks. S.60 $\frac{1}{2}$ °W., and at this point set an iron post 3 ft. long, 2 ins. in diam., 10 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished cor. of secs. 9, 10, 15 and 16, with brass cap marked

T13N	R2W
S9	S10
S16	S15

1930 from which, an oak, 12 ins. in diam., brs. N.2°W., 56 lks. dist. marked T13N R2W S9 BT
Remark original NE BT, T13N R2W S10 BT
a yellow pine, 5 ins. in diam., brs. S.41 $\frac{1}{2}$ °W., 41 lks. dist., marked T13N R2W S16 BT
No good SE BT available, chisel BOS15 on face of large boulder, above which cut a cross (+) which brs. S.76 $\frac{1}{4}$ °E., 58 lks. dist.

Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush and cacti.

From original cor. secs. 10, 11, 14 and 15. N.89°25'W., on true line, bet. secs. 10 and 15. Over mountainous land, thru thick timber & undergrowth. Asc. 56 ft. over SE slope.

- 4.40 Spur, brs. NE. Desc. 13 ft. over NW slope.
- 5.70 Wash, 10 lks. wide, course NE. Asc. 209 ft. over SE slope.
- 16.00 Ridge, brs. N-SE. Desc. 65 ft. over SW slope.
- 22.05 Head of wash, course S. Asc. 24 ft. over SE slope.
- 25.00 Spur, brs. SW. Desc. 183 ft. over NW slope.
- 30.00 Wash, course West, brs. N. 50 lks. from line.
- 35.50 Side wash, course NW. Desc. 26 ft. over NW slope.
- 36.80 Wire fence, brs. NW-SE.
- 40.83 (Midpoint) set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs. 10 and 15, with brass cap marked

$\frac{1}{4}$	S 10
	S 15

1930 from which, a juniper, 5 ins. in diam., brs. S.1 $\frac{1}{4}$ °E., 14 lks. dist., marked $\frac{1}{4}$ S15 BT
a juniper, 10 ins. in diam., brs. N.53°W., 141 lks. dist., marked $\frac{1}{4}$ S10 BT

- 43.50 Desc. 43 ft. over SW slope.
- 43.50 Senator highway, brs. NE-SE (at bend).
- 45.90 Wash, 10 lks. wide, course NW. Asc. 40 ft. over NE slope.
- 48.80 Spur, brs. N. Along level N. slope.
- 53.30 Spur, from SE to West. Desc. 185 ft. down same.
- 73.20 Pipe line, brs. N-S.
- 80.35 Pipe line, brs. N-S.

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W. 67

Chains	
80.50	Telephone line, brs. N.-S.
81.66	Intersect the cor. of secs. 9, 10, 15 and 16.
	Land, mountainous. Soil, rocky 4th. rate. Timber, yellow pine. oak and juniper. Undergrowth, oakbrush, catclaw and cacti.

	N.0°56'W., on true line, bet. secs. 9 and 10. Over mountainous land, thru thick timber & undergrowth.
0.05	Wire fence, brs. E-W. Continue along Page wire fence, to east of line. Along spur top, on slight descent.
3.00	Leave spur, to NW. Desc. 61 ft. over NE slope.
8.45	Wash, 20 lks. wide, course S.30°E. to West. Asc. 23 ft. over S. slope.
12.00	Spur, brs. West. Desc. 37 ft. over N. slope.
12.80	Pipe line, brs. N.5°W.-S.5°E.
15.50	Wash, 10 lks. wide, course West. Asc. 37 ft. over S. slope.
20.50	Spur, brs. West. Desc. 11 ft. over N. slope.
22.40	Shallow wash, course West. Asc. 23 ft. over S. slope.
25.00	Slope changes to west.
29.00	Desc. 35 ft. over N. slope.
32.20	Head of wash, course West. Asc. gradual S. slope.
33.30	Tip of spur, brs. west. Desc. 9 ft. over N. slope.
33.70	Shallow wash, course W. Asc. 20 ft. over S. slope.
36.00	Spur, brs. West. Desc. 47 ft. over N. slope.
38.10	Wash, 20 lks. wide, course West. Asc. 15 ft. over S. slope.
39.33	(Midpoint) set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs. 9 and 10, with brass cap marked
	$\frac{1}{4}$ S9 S10
	1930 from which, an oak, 8 ins. in diam., brs. N.38°E., 24 lks. dist., marked $\frac{1}{4}$ S10 BT a juniper, 14 ins. in diam., brs. N.88°W., 60 lks. dist., marked $\frac{1}{4}$ S9 BT Indian ruins on hill about 20 chs. dist., brs. S.80°W.
	Asc. 15 ft. over N. slope.
39.90	Spur, brs. West. Desc. 30 ft. over NW slope.
41.60	Wash, 20 lks. wide, course W. Asc. 70 ft. over S. slope.
52.60	Trail, brs. E-W.
53.50	Ridge, brs. E-W. Desc. 133 ft. over N. slope.
53.60	Same ruins as noted from $\frac{1}{4}$ cor., brs. S.52°W.
55.40	City pipe line, brs. NE-SW.
66.35	Wash, 10 lks. wide, course W. Asc. 80 ft. over S. slope.
72.70	Ridge, brs. E-W. Desc. 139 ft. over N. slope.
78.50	Shallow wash, course NW.
78.66	Intersect the original cor. of secs. 3, 4, 9 and 10, which is a stone 8 x 8 x 5 ins. above ground, firmly set, marked with 5 and 3 grooves on S. and E. faces, respect- ively. and set in small mound of stone. No bearing trees.

Chains

Reconstruct this cor., by setting an iron post 3 ft. long, 2 ins. in diam., 16 ins. in the ground along-side old stone cor., to bedrock, raise a mound of stone about post, for the cor. secs. 3, 4, 9 & 10 with brass cap mkd.

T13N R2W
 $\frac{S4}{S9} \mid \frac{S3}{S10}$

1930 from which,
 an oak, 8 ins. in diam., brs. N.53½°E., 100 lks. dist., marked T13N R2W S3 BT
 an oak, 6 ins. in diam., brs. S.39°E., 11 lks. dist., marked T13N R2W S10 BT
 an oak, 9 ins. in diam., brs. S.59½°W., 162 lks. dist., marked T13N R2W S9 BT
 No NW bearing tree available.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, oak, juniper and yellow pine.
 Undergrowth, oakbrush and cacti.

From the cor. of secs. 2, 3, 10 and 11, S.88°46'W., on true line, bet. secs. 3 and 10.
 Over mountainous land, thru scattering timber & thick undergrowth.

Asc. 33 ft. over SE slope.
 5.00 Spur, brs. NW. Desc. 6 ft. over W. slope.
 7.70 Head of wash, course NW. Asc. 56 ft. over NE slope.
 15.00 Spur, brs. NW. Desc. 304 ft. over SW slope.
 15.70 Old road, brs. NW-SE.
 27.40 Same old road, brs. NE-SW.
 30.50 Same old road, brs. NW-SE.
 32.10 Wash, 20 lks. wide, course NW. Asc. 78 ft. over NE slope to
 37.64 (Midpoint) set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished ¼ sec. cor. of secs. 3 and 10, with brass cap marked

$\frac{1}{4} \frac{S3}{S10}$

1930 from which,
 a juniper, 10 ins. in diam., brs. N.82½°W., 126 lks. dist., marked ¼ S3 BT
 a juniper, 10 ins. in diam., brs. S.18°E., 51 lks. dist., marked ¼ S10 BT
 House, brs. N.4°W., about 20 chs. dist.
 Norris Hill, brs. N. 12½°W., about 50 chs. dist.

Asc. 15 ft. over NE slope.
 41.00 Spur, brs. NW. Desc. 70 ft. over SW slope.
 47.00 Wash, 10 lks. wide, course N. Asc. 86 ft. over E. slope.
 53.90 Old road, brs. NW-SE.
 54.00 Page wire fence, brs. N-S.
 56.00 Ridge, brs. NW-SE. Desc. 211 ft. over SW slope.
 59.80 Senator Highway, brs. NW-SE.
 71.65 Wash, 10 lks. wide, course NW.
 Asc. gradual NE slope.
 72.50 City pipe line, brs. NW-SE.
 73.90 Wire fence, brs. N-S. Telephone line, same bearing.
 75.28 Intersect the cor. of secs. 3, 4, 9 and 10.

Re-Survey of Part of the Subd.Lines of T.13 N., R.2 W.


Chains

Land, mountainous.
Soil, rocky 4th rate.
Timber, oak and juniper.
Undergrowth, scrub oak and cacti.

From reestablished cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described,

S. 0° 3' E., on true line bet. secs. 3 and 4.
Over open rolling land, thru City of Prescott, Ariz., along W. side of Pleasant St., (paved).

- 5.23 Center of Union St., 100 ft. wide; extends W.
- 10.45 Center of Goodwin St., 100 ft. wide, brs. E. and W.
- 20.62 End of pavement in Pleasant St. Enter Carleton St.
- 21.00 Center of Carleton St., brs. E. and W., 100 ft. wide to the W., and 70 ft. wide to the E.
- 26.75 Wash, 10 lks. wide, course NW. Asc. 46 ft. over NE. slope.
- 27.35 Enter road, brs. NW. and S. Thence along road.
- 30.85 Road, brs. NE. and SW. Leave road.
Desc. gradually over SW. slope.
- 32.54 Wire fence, brs. E. and W. Leave open land and enter scattering timber and dense undergrowth.
- 34.00 Wash, 20 lks. wide, course NW. Leave rolling and enter mountainous land. Asc. 141 ft. over NE. slope to
- 41.32 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished 1/4 sec. cor. of secs. 3 and 4, with brass cap marked



from which

A juniper, 12 ins. diam., brs. N. 82° E., 278 lks. dist., marked 1/4 S3 BT

A juniper, 10 ins. diam., brs. N. 49° W., 93 lks. dist. marked 1/4 S4 BT.

Prescott City Reservoir brs. NE. about 5 chs. dist.

- Asc. 67 ft. over N. slope.
- 44.30 Top of knoll, about 1.50 chs. in diam.
Desc. 92 ft. over S. slope, along W. side of road.
- 58.44 Wire fence, brs. E. - W. Southern limit of the City of Prescott, according to 1930 City Map, brs. E. and W. Fence cor. brs. E. about 1.25 chs. dist., from which fences extend W., S., and N.
Leave City of Prescott.
- 60.34 Wash, 10 lks. wide; course NW. Asc. 42 ft. over N. slope.
- 63.55 Spur, brs. NW. Desc. 21 ft. over SW. slope.
- 68.65 Head of wash, course NW. Asc. 18 ft. over NE. slope.
- 70.35 Spur, brs. W. Desc. 81 ft. over S. slope.
- 74.90 Telephone line; brs. NW. - SE.
- 77.80 Wire fence, brs. E. - W. Fence cor. brs. E. about 1.35 chs. dist.; from which fences extend W., S., and N.
- 79.75 Wash; 20 lks. wide, course W. Asc. 24 ft. over N. slope.
- 81.55 Spur, brs. W. Desc. slightly over SW. slope to
- 82.74 Intersect original cor. of secs. 3, 4, 9, and 10.

Land, rolling and mountainous.
Soil, rocky, 4th rate.
Timber, oak and juniper.
Undergrowth, scrub oak and cacti.

Re-Survey of Part of the Subd. Lines of T.13 N., R. 2 W.


Chains

From the std. cor. of secs. 32 and 33, on S. Bdy. of Tp. hereinbefore described.
 N. 0° 52' E., on true line, bet. secs. 32 and 33, ($S\frac{1}{2}$).
 Over mountainous land, thru dense timber & undergrowth.
 Desc. gradual N. slope.

2.35 Wash, 10 lks. wide, course NW. Asc. 14 ft. over SW. slope.
 6.00 Spur, brs. West. Desc. 72 ft. over NE slope.
 6.15 Old road, brs. E - W. Roads, fork to NE-SE about 1 ch. E.
 10.70 Wash, 5 lks. wide, course NW. Asc. slight SW slope.
 11.35 Spur, brs. NW. Desc. slight NE slope.
 12.35 Wash, 10 lks. wide, course NW. Asc. slight SW slope.
 13.75 Spur, brs. West. Desc. 92 ft. over NW slope.
 18.35 Hassayampa Creek, 50 lks. wide, course W. Asc. 112 ft. over SE. slope.

19.00 Lane's house on line.
 29.60 Highway, brs. NE-SW.
 33.00 Spur, brs. SW. Desc. 89 ft. over NW slope.
 39.00 Behd in Groom Creek, from NW-SW. Asc. 13 ft. over SW slope to

42.34 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 32 & 33, which is a granite stone 8 x 18 x 12 ins. loosely set in ground, mkd. $\frac{1}{4}$ on one face, from which,
 A pine stump 3 ft. high, 30 ins. in diam., brs. N. 39° E., 54 lks. dist. (Old BT).
 Oak stump, 16 ins. diam. brs. N. 37° W., 37 lks. dist. (old BT).
 Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground alongside old stone cor., for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, with brass cap marked



from which

A yellow pine, 28 ins. in diam., brs. N. 22 $\frac{1}{2}$ ° W., 246 lks. dist., marked $\frac{1}{4}$ S32 BT.
 A yellow pine, 16 ins. in diam., brs. S. 40° E., 97 lks. dist., marked $\frac{1}{4}$ S33 BT.
 Fail to find $\frac{1}{4}$ sec. cor. of secs. 32 and 33, set by D. W. Eaton.
 A small shack, brs. S. 51° E., 1 ch. dist.

Thence,
 N. 1° 45' E., on true line, bet. secs. 32 and 33, ($N\frac{1}{2}$).
 Over mountainous land, thru dense timber and undergrowth.
 Asc. 71 ft. over SW. slope.

8.00 Spur, brs. NW. Desc. 15 ft. over NE. slope.
 9.60 Small wash, course W. Asc. 25 ft. over S. slope.
 11.55 Spur, brs. West. Desc. 36 ft. over N. slope.
 13.70 Groom Creek, 50 lks. wide, course W. Asc. 18 ft. over S. slope.

25.50 Spur, brs. S. Asc. 18 ft. over same.
 33.40 Leave spur, which turns W. from E. Desc. 78 ft. over NW. slope.

35.80 Wash, 10 lks. wide, course SW. Asc. 39 ft. over SE slope.
 40.60 Spur, brs. SW. Desc. 18 ft. over NW. slope.
 41.30 Small wash, course NE. Asc. slight S. slope.
 42.73 Spur, brs. S. and from NW, intersect the original cor. of secs. 28, 29, 32 and 33, which is a pine tree 24 ins. in diam., in good condition, blazed on four faces, NW, NE, SE and SW. Open the NE face and read TXIIIN SXXVIII. No bearing trees.
 Reconstruct this cor. monument by setting an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W. 71

Chains

on N. edge of original tree cor., for the cor. of secs. 28, 29, 32 and 33, with brass cap marked

T13N	R2W
S29	S28
S32	S33

1930 from which,
 an oak, 6 ins. in diam., brs. N.37 $\frac{1}{4}$ °W., 48 lks. dist., marked T13N R2W S29 BT
 an oak, 16 ins. in diam., brs. N.43°E., 43 lks. dist., marked T13N R2W S28 BT
 an oak, 6 ins. in diam., brs. S.40°E., 36 lks. dist., marked T13N R2W S33 BT
 a yellow pine, 24 ins. in diam., brs. S.38°W., 81 lks. dist., marked T13N R2W S32 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, catclaw and cacti.

From the reestablished cor. of secs. 27, 28, 33 & 34. S.89°56'W., on true line, bet. secs. 28 & 33, (E $\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth. Topography omitted because of close agreement with Eaton Record.

39.70 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 28 and 33, which is a stone 10 x 10 x 12 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face, and witnessed by bearing trees properly marked one each SE and NW of cor. Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground alongside old stone cor., with brass cap marked

$\frac{1}{4}$ S 28
S 33

1930

Thence,
 S.83°56'W., on true line, bet. secs. 28 and 33, (W $\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth. Desc. 35 ft. over NW slope.
 1.60 Groom Ck., 20 lks. wide, course SW. Asc. 25 ft. over E. slope.
 5.60 Spur, brs. SE. Desc. 12 ft. over SW slope.
 7.65 Wash, 5 lks. wide, course SE.
 Asc. 131 ft. over gradual E. slope. Shafts, br. S. 3 chs.
 10.65 Old shaft, 20 lks. S. of line.
 18.60 Spur, brs. S. Desc. 27 ft. over West slope.
 23.20 Wash, 10 lks. wide, course S. Asc. 31 ft. over E. slope.
 25.10 Spur, brs. S. Desc. 51 ft. over W. slope.
 26.45 Old road, brs. N-S.
 32.40 Wash, 10 lks. wide, course SE. Asc. 51 ft. over SE slope.
 37.55 Spur, brs. SW. Desc. 90 ft. over NW slope.

720 Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains

42.05 Wash, 10 lks. wide, course SW. Asc. 26 ft. over SE slope.
 43.90 Spur, brs. S. Desc. 26 ft. over SW slope.
 45.90 Wash, 5 lks. wide, course SE. Asc. 14 ft. over SE slope.
 46.90 Intersect the original cor. of secs. 28, 29, 32 and 33.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, catclaw and cacti.

N.2°00'W., on true line, bet. secs. 28 and 29.
 Over mountainous land, thru thick timber & undergrowth.
 Asc. 69 ft. along SE slope.
 2.60 Thence along E. slope, on slight descent.
 11.60 Wash, 10 lks. wide, course SE. Asc. slight SE slope.
 12.30 Spur, slopes SW. Desc. gradual NW slope.
 13.40 Same wash, course SW. Asc. 137 ft. over NE slope.
 22.00 Spur, brs. SW. Desc. 113 ft. over NW slope.
 27.20 Branch spur, brs. NW. Desc. NE slope.
 31.40 Wash, 10 lks. wide, course NW. Asc. 19 ft. over SW slope.
 32.80 Spur, brs. NW. Desc. 32 ft. over NE slope.
 34.00 Wash, 10 lks. wide, course W. Asc. 29 ft. over SW slope.
 35.20 Spur, brs. SW. Desc. 9 ft. over NW slope.
 36.40 Wash, 10 lks. wide, course SW. Asc. 60 ft. over SE slope.
 41.12 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 20 ins. in the ground to bedrock, raise a mound of stone
 about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs.
 28 and 29, with brass cap marked

S29

S28

1930


from which,

a yellow pine, 10 ins. in diam., brs. S. 42°E., 55 lks.
 dist., marked $\frac{1}{4}$ S28 BT
 an oak, 8 ins. in diam., brs. S. 34 $\frac{1}{2}$ °W., 22 lks. dist.,
 marked $\frac{1}{4}$ S29 BT

Asc. 16 ft. over SE slope.
 44.45 Slope changes to SW.
 45.60 Spur, brs. SW. Asc. SE slope 47 ft.
 49.00 Spur, brs. SW. Desc. 31 ft. over NW slope.
 51.85 Wash, 10 lks. wide, course SW. Asc. 30 ft. over SE slope.
 54.00 Spur, brs. SW. Desc. 9 ft. over NW slope.
 56.60 Shallow wash, course SW. Asc. gradual SE slope.
 58.30 Spur, brs. SW. Desc. gradual NW slope.
 59.10 Wash, 5 lks. wide, course SW. Asc. 39 ft. over S. slope.
 60.50 Old road, brs. NW-SE.
 67.30 Spur, brs. West. Desc. 34 ft. over N. slope.
 70.30 Wash, 5 lks. wide, course W. Asc. 32 ft. over S. slope.
 75.30 Spur, brs. West. Desc. 16 ft. over N. slope.
 80.60 Wash, 10 lks. wide, course SW. Asc. 6 ft. over SE slope.
 82.24 Intersect the original cor. of secs. 20, 21, 28 and 29,
 which is a granite stone 14 x 14 x 18 ins. above
 ground, firmly set, marked with two and four notches
 on S. and E. edges respectively, from which,
 an oak, 10 ins. in diam., brs. S. 22 $\frac{3}{4}$ °E., 46 lks. dist.,
 marked TX111NR11WSXXV111BT

Chains

No other tree remains.
Reconstruct this cor. monument by setting an iron post 3 ft. long, 2 ins. in diam., 22 ins. in the ground to bedrock, alongside old stone cor., for the cor. of secs. 20, 21, 28 and 29, with brass cap marked




1930 from which,
an oak, 6 ins. in diam., brs. N.51°W., 10 lks. dist., marked T13N R2W S20 BT
an oak, 4 ins. in diam., brs. N.37°E., 15 lks. dist., marked T13N R2W S21 BT
an oak, 12 ins. in diam., brs. S.55°E., 48 lks. dist., marked T13N R2W S28 BT
a yellow pine, 9 ins. in diam., brs. S.30½°W., 43 lks. dist., marked T13N R2W S29 BT

Land, mountainous.
Soil, rocky 4th. rate.
Timber, oak, juniper, and yellow pine.
Undergrowth, oakbrush, catclaw, manzanita and cacti.

From the cor. of secs. 21, 22, 27 and 28.
S.87°45'W., on true line, bet. secs. 21 and 28.
Over mountainous land, thru thick timber & undergrowth.
Asc. 61 ft. over SE slope.

3.50	Spur, brs. S. Desc. 16 ft. over W. slope.
5.00	Wash, at head, course S. Asc. 147 ft. over E. slope.
11.50	Spur, brs. S. Desc. 48 ft. over W. slope.
19.00	Ridge, brs. NE-SW. Desc. 189 ft. over NW slope.
31.50	Saddle, in ridge, brs. E-W. Head of wash, course SW. Asc. 49 ft. over SE slope.
42.00	Hill, about 3 chs. in diam., on divide, which brs. SE-SW. Desc. 71 ft. over NW slope.
45.54	(Midpoint) set an iron post 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished ¼ sec. cor. of secs, 21 and 28, with brass cap marked



1930 from which,
a yellow pine, 10 ins. in diam., brs. N.36½°W., 38 lks. dist., marked ¼ S21 BT
a yellow pine, 10 ins. in diam., brs. S.28°W., 20 lks. dist., marked ¼ S28 BT

50.20	Desc. 70 ft. over W. slope.
57.60	Road, brs. N-S. Wash, near head, course SW. Asc. 11 ft. over gradual SE slope.
59.30	Spur, brs. SW. Desc. 38 ft. over NW slope.
60.40	Shallow wash, course S.

74- Re-survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains-

Asc. gradual SE slope.
 64.50 Spur, from NE-W. Desc. 52 ft. over spur.
 71.30 Wash, 20 lks. wide, course NW. Asc. slight NE slope.
 72.20 Rocky spur, brs. NW. Desc. 18 ft. over W. slope.
 73.80 Same wash, course West. Desc. 29 ft. down same.
 77.70 Leave wash, turns SW.
 80.80 Same wash, course NW. Asc. 9 ft. over slight NE slope.
 83.70 Spur, brs. NW. Desc. 11 ft. over slight SW slope.
 84.30 Same wash, course SW. Thence over level land.
 91.08 Intersect the cor. of secs. 20, 21, 28 and 29.

Land, mountainous and level.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, catclaw and cacti.

N.0°48'E., on true line, bet. secs. 20 and 21, ($S\frac{1}{2}$)
 Over mountainous land, thru thick timber and undergrowth.
 Asc. 32 ft. up spur top.
 3.10 Head of wash, course SW.
 8.00 Spur, brs. SW. Desc. gradually along W. slope.
 10.00 Road, brs. NW-SE.
 14.80 Wash, 10 lks. wide, course W. for 50 lks. thence S.
 Asc. gradual S. slope, 23 ft.
 21.00 Road, brs. E-W.
 21.40 Divide, brs. E-W. Desc. 108 ft. over N. slope.
 30.25 Road, brs. NW-SE.
 34.75 Wash, from SE thence N. Continue down same.
 36.50 Same wash, course NW. Asc. gradual SW slope.
 40.80 Spur, brs. NW. Desc. gradual N. slope.
 42.33 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 20 and 21,
 which is a granite stone 9 x 14 x 20 ins. above ground
 and mound of stone, firmly set, marked $\frac{1}{4}$ on W. face.,
 no bearing trees now remain.
 Reconstruct this cor. monument by setting an iron post
 3 ft. long, 1 in. in diam., 20 ins. in the ground to
 bedrock, raise a mound of stone about post, for the
 reconstructed $\frac{1}{4}$ sec. cor. of secs. 20 and 21, with
 brass cap marked

$\frac{1}{4}$
 S20 | S21

1930

from which,
 a yellow pine, 30 ins. in diam., brs. S.79°E., 41 lks.
 dist., marked $\frac{1}{4}$ S21 BT
 a yellow pine, 10 ins. in diam., brs. N.79°W., 40 lks.
 dist., marked $\frac{1}{4}$ S20 BT

Thence, N.0°20'E., on true line, bet. secs. 20 and 21, ($N\frac{1}{2}$)
 Desc. 21 ft. over N. slope.
 1.00 Wash, 10 lks. wide, course NW. Asc. 19 ft. over SW slope.
 3.10 Spur, brs. NW. Desc. 59 ft. over NE slope.
 6.25 Wash, 10 lks. wide, course NW. Asc. 11 ft. over SW slope.
 7.50 Spur, brs. NW. Desc. 58 ft. over NE slope.
 8.50 Wash, 10 lks. wide, course W. Asc. 92 ft. over SE slope.
 14.50 Spur, brs. W. Desc. 53 ft. over N. slope.
 16.80 Wash, at head, course NW. Asc. slight SW slope.
 17.70 Spur, brs. NW. Desc. 70 ft. over NE slope.

Re-Survey of Part of the Subd. Lines of T.13 N., -R.2 W. 75

Chains

- 18.40 Wash, 10 lks. wide, course W. Asc. 51 ft. over S. slope.
- 22.70 Spur, brs. W. Desc. 7 ft. over N. slope.
- 23.65 Small wash, course W. Asc. 16 ft. over S. slope.
- 25.25 Spur, brs. W. Desc. 102 ft. over steep N. slope.
- 29.25 Wash, 10 lks. wide, course West. Asc. 20 ft. along W. slope.
- 35.40 Spur, brs. West. Desc. 61 ft. over N. slope.
- 37.85 Wash, 10 lks. wide, course NW. Asc. 14 ft. over SW slope.
- 38.60 Spur, brs. NW. Desc. 160 ft. over N. slope.
- 43.83 Intersect the original cor. of secs. 16, 17, 20 and 21, which is a rock 3 ft. x 3 ft. x 4 ft. high, dimly marked 3 and 3 grooves on S. and E. faces, respectively from which,
 - a pine stump, 20 ins. in diam., 2 ft. high, brs. S.41°E. 60 lks. dist., scribed parts of this tree found alongside same.
 - a pine stump, 20 ins. in diam., brs. S.72°E., 81 lks. dist. scribed parts of this tree found alongside.

Reconstruct this cor. monument by setting a bronze tablet 5 ins. in diam., on top of the original cor. rock; marked

T13N R2W	
S17	S16
S20	S21

- 1930 from which,
 - a yellow pine, 12 ins. in diam., brs. N.3°W., 33 lks. dist., marked T13N R2W S17 BT
 - a yellow pine, 14 ins. in diam., brs. N.53½°E., 28 lks. dist., marked T13N R2W S16 BT
 - a yellow pine, 10 ins. in diam., brs. S.28°E., 15 lks. dist., marked T13N R2W S21 BT
 - a yellow pine, 14 ins. in diam., brs. S.38°W., 53 lks. dist., marked T13N R2W S20 BT

Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush, catclaw and cacti.

From the cor. of secs. 15, 16, 21 and 22, N.89°25'W., on true line, bet. secs. 16 and 21. Over mountainous land, thru thick timber & undergrowth. Desc. 57 ft. over SW slope.

- 3.40 Wash, 5 lks. wide, course SW. Asc. 10 ft. over SE slope.
- 4.00 Tip of spur, brs. S. Desc. gradual W. slope.
- 4.40 Wash, 5 lks. wide, course S. Asc. 40 ft. over E. slope.
- 8.50 Spur, brs. SW. Desc. 85 ft. over NW slope.
- 13.00 Wash, 10 lks. wide, course SW. Asc. 21 ft. over SE slope.
- 16.70 Spur, brs. S. Desc. 82 ft. over SW slope.
- 22.10 Wash, 20 lks. wide, course NW. Desc. 57 ft. over NE slope.
- 22.85 Road, brs. NW-SE.
- 27.50 Wash, 10 lks. wide, course N. Asc. 56 ft. over E. slope.
- 32.20 Spur, brs. N. Desc. 53 ft. over W. slope.
- 34.60 Wash, 10 lks. wide, course N. Asc. 27 ft. over E. slope.
- 37.20 Spur, brs. N. Desc. 46 ft. over W. slope.
- 39.80 Wash, 10 lks. wide, course N. Asc. 24 ft. over SE slope.
- 42.00 Spur, brs. NE. Desc. gradual NW slope to
- 43.15 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,

76 Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains

26 ins. in the ground for the reestablished $\frac{1}{4}$ sec. cor. of secs. 16 and 21, with brass cap marked

$\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$

1930 from which,

a yellow pine, 16 ins. in diam., brs. N.15°W., 14 lks. dist., marked $\frac{1}{4}$ S16 BT

a yellow pine, 12 ins. in diam., brs. S.63 $\frac{1}{4}$ °W., 50 lks. dist., marked $\frac{1}{4}$ S21 BT

43.95 Desc. 10 ft. over NW slope.
 47.00 Wash, 5 lks. wide, course NE. Asc. 59 ft. over SE slope.
 48.50 Spur, brs. NE.
 Ridge, brs. NW-SE. Old road on same.
 63.40 Desc. 133 ft. over SW slope.
 68.30 Wash, 20 lks. wide, course NW. Asc. 57 ft. over NE slope.
 70.45 Spur, brs. NW-SE. Desc. 43 ft. over SW slope.
 75.30 Wash, 10 lks. wide, course NW. Asc. 56 ft. over NE slope.
 77.50 Wash, 5 lks. wide, course NE. Asc. gradual SE slope.
 80.65 Spur, brs. N-S. Desc. 60 ft. over rolling SW slope.
 83.40 Wash, 5 lks. wide, course SW. Asc. 55 ft. over SE slope.
 86.30 Spur, brs. SW. Desc. 40 ft. over W. slope.
 Intersect the cor. of secs. 16, 17, 20 and 21.

Land, mountainous.

Soil, rocky 4th. rate.

Timber; yellow pine, oak and juniper.


Undergrowth, oakbrush, manzanita, cacti and catclaw.

N.1°30'E., on true line, bet. secs. 16 and 17, (S $\frac{1}{2}$)
 Over mountainous land, thru thick timber and undergrowth.
 Asc. gradual S. slope.
 2.00 Spur, brs. W. Desc. gradual NW slope.
 3.50 Road, brs. NE-SW.
 4.30 Granite Creek, (Dry,) 50 lks. wide, course NE. Asc. slight S.
 9.20 White Spar Highway, brs. NE-SW. (slope.
 11.00 Mouth of wash, from W. Asc. gradual S. slope.
 13.60 Spur, brs. E. Desc. gradual N. slope.
 18.80 Wash, 10 lks. wide, course NE. Asc. gradual SE slope.
 20.90 Spur, brs. NE. Desc. gradual NW slope.
 22.30 Wash, 10 lks. wide, course E. Asc. gradual S. slope.
 23.60 Spur, brs. E. Desc. gradual N. slope.
 24.50 Wash, 5 lks. wide, course E. Asc. gradual S. slope.
 31.40 Spur, brs. E. Desc. 24 ft. over N. slope.
 32.40 Wash, 10 lks. wide, course E. Asc. rolling S. slope.
 39.40 Old blazed tree, Y.P. 30 ins. in diam.,
 40.00 Spur, brs. E. Desc. gradual NE slope.
 40.80 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 16 and 17,
 which is a granite stone 8 x 8 x 20 ins. above ground
 and mound of stone, marked $\frac{1}{4}$ on W. face, from which
 a burned pine stump, brs. N.77°W., 25 lks. dist.
 marks have been destroyed by fire.

Reconstruct this cor. monument by setting an iron post,
 3 ft. long, 1 in. in diam., 20 ins. in the ground to
 bedrock, alongside the old stone cor., for the $\frac{1}{4}$ sec.
 cor. of secs. 16 and 17, with brass cap marked

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W. 77


Chains



1930 from which,
 - a yellow pine, 14 ins. in diam.; brs. S.24°W., 18 lks. dist., marked $\frac{1}{4}$ S17 BT
 an oak, 5 ins. in diam., brs. N.58°E., 15 lks. dist., marked $\frac{1}{4}$ S16 BT

Thence,
 N.3°25'W., on true line, bet. secs. 16 and 17, (N $\frac{1}{2}$)
 Over level E. slope.

2.00 Desc. 77 ft. over NE slope.
 7.40 Wash, 20 lks. wide, course E. Asc: 51 ft. over S. slope.
 11.00 Spur, brs. East. Desc. 51 ft. over N. slope.
 13.40 Wash, 20 lks. wide, course E. Asc. 12 ft. over S. slope.
 17.60 Ridge, brs. NE-SW. Over rolling E. slope.
 20.60 Small cabin, brs. 20 lks. E. of line.
 25.00 Desc. 35 ft. over NE slope.
 29.60 Wash, 20 lks. wide, course NE. Asc. 24 ft. over SE slope.
 31.30 Spur, brs. NE. Desc. 27 ft. over N. slope.
 33.80 Wash, 10 lks. wide, course E. Asc. 23 ft. over S. slope.
 36.90 Spur, brs. E. Desc. gradually over E. slope to
 41.70 (Proportionate point), set an iron post 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished cor. of secs. 8, 9, 16 and 17, with brass cap marked



1930 from which,
 a yellow pine, 18 ins. in diam., brs. N.79°W., 56 lks. dist., marked T13N R2W S8 BT
 a yellow pine, 9 ins. in diam., brs. N.74°E., 52 lks. dist., marked T13N R2W S9 BT
 an oak, 6 ins. in diam., brs. S.44 $\frac{1}{4}$ °E., 32 lks. dist., marked T13N R2W S16 BT
 a yellow pine, 12 ins. in diam., brs. S.0°30'W., 43 lks. dist., marked T13N R2W S17 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, cacti and catclaw.

From cor. of secs. 9, 10, 15 and 16.
 N.89°18'W., on true line, bet. secs. 9 and 16, (E $\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth.
 Desc. 30 ft. over W. slope. Along N. side wire fence.
 5.05 Road, brs. NW-SE. House brs. S. about 3 chs. dist.
 6.50 Wire fence, brs. N. and S. 20 lks. to cor.
 6.70 **Bannon Creek**, 20 lks. wide, course NW. (Dry.)
 Asc. 30 ft. over E. slope.
 9.00 Spur, brs. NE. Desc. 12 ft. over NW slope.
 11.15 Wash, 5 lks. wide, course NE.

Chains


	Asc. 24 ft. over SE slope.
16.30	Spur, brs. NE. Desc. gradually over NW slope.
20.00	Ridge, brs. N. and S. Desc. 14 ft. over W. slope.
21.70	Wash, 10 lks. wide, course N. Asc. rolling SE slope.
25.00	Spur, brs. NE. Desc. 22 ft. over NW slope.
28.00	Wash, 10 lks. wide, course N. Asc. 22 ft. over E. slope.
31.00	Spur, brs. N. Along level N. slope.
35.00	Desc. 43 ft. over W. slope.
40.80	Intersect the original $\frac{1}{4}$ sec. cor. of secs. 9 and 16, which is a granite stone 8 x 10 x 18 ins. above ground firmly set, marked $\frac{1}{4}$ on N. face, from which, a pine stump, 18 ins. in diam., brs. N. 8° E., 24 lks. dist. (Agrees with record.) a pine stump, 20 ins. in diam., brs. S. 58° E., 27 lks. dist., (Record, S. 67° E., 27 lks.) Fence cor., from which wire fences extend N.-E. and W., brs. 5 lks. NE. Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, raise a mound of stone about post, for the reconstructed $\frac{1}{4}$ sec. cor. of secs. 9 and 16, with brass cap marked
	$\frac{1}{4} \frac{S9}{S16}$
	1930 from which,
	a yellow pine, 14 ins. in diam., brs. N. 67 $\frac{1}{2}$ ° W., 39 lks. dist., marked $\frac{1}{4}$ S9 BT
	a yellow pine, 10 ins. in diam., brs. S. 20° W., 40 lks. dist., marked $\frac{1}{4}$ S16 BT
	Thence,
	N. 89° 24' W., on true line, bet. secs. 9 and 16, (W $\frac{1}{2}$)
	Desc. 47 ft. over rocky W. slope.
2.00	Intersect Cor. No. 1 of the "Stay Cowboy" mining claim, Min. Sur. No. 4113.
6.60	Wash, 10 lks. wide, course NW. Asc. 15 ft. over E. slope.
6.80	Tip of spur, brs. NW. Desc. gradual NW slope.
7.55	Wash, 10 lks. wide, course N. Asc. 15 ft. over E. slope.
8.80	Spur, brs. N. Desc. 50 ft. over W. slope to Creek.
13.26	Cor. of fences from N. and E., on line.
13.70	Road, brs. N-S.
15.10	Center of Granite Creek, 50 lks. wide, course N. Asc.
16.90	White Spar Highway, brs. N.-S. (gradual E. slope.
19.70	Road, brs. NE-SW.
19.97	Cor. of Perkins fence, brs. 6 lks. N. (Fence extends N. and W. House brs. NW about 2 chs. dist.)
22.60	Wash, 10 lks. wide, course NE. Asc. 10 ft. over E. slope.
23.20	Same road, brs. NW-SE.
23.70	Fence brs. N-S. (Perkins).
26.50	Spur, brs. NE. Desc. slight NW-slope.
28.80	Enter wash, course NE. At mouth of washes from SW and NW. Continue up wash.
29.05	A new well, brs. N. about 25 lks. dist. An older well, brs. S. about 5 lks. dist.
34.00	Leave wash, which turns to NW. Asc. 11 ft. over NE slope.
36.00	Short spur, brs. N. Desc. 17 ft. over NW slope.
37.70	Wash, 10 lks. wide, course NE. Asc. 41 ft. over E. slope.
40.50	Intersect the cor. of secs. 8, 9, 16 and 17.

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W., 79

Chains

Land, mountainous and rolling.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush and cacti.

N.3°20'E., on true line, bet. secs. 8 and 9, (S $\frac{1}{2}$)
Over mountainous land, thru thick timber & undergrowth.
Desc. 39 ft. over N. slope.
1.40 Wash, 20 lks. wide, course E. Asc. 79 ft. over S. slope.
4.70 Spur, brs. SE. Desc. gradual NE slope.
7.70 Wash, 10 lks. wide, course SE. Asc. 221 ft. over S. slope.
23.70 Ridge, brs. E-W. A high knoll, about 4 chs. long and
1 ch. wide, brs. E., about 3 chs. dist.
Desc. 352 ft. over NW slope.
26.80 Wire fence, brs. NW and SE.
41.70 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 8 and 9,
which is a mound of stone 3 ft. base, 1 ft. high in
center of which find broken pieces of stone with
chisel marks upon the various pieces. Accept this
evidence as the $\frac{1}{4}$ sec. cor. and reconstruct same by
setting an iron post 3 ft. long, 1 in. in diam.,
18 ins. in the ground to bedrock, alongside the
old cor. pieces, raise a mound of stone about post,
for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, with brass cap
marked



1930 from which,
a yellow pine, 30 ins. in diam., brs. N.40 $\frac{1}{2}$ °W., 57
lks. dist., marked $\frac{1}{4}$ S8 BT
a yellow pine, 14 ins. in diam., brs. S.76 $\frac{3}{4}$ °E., 21
lks. dist., marked $\frac{1}{4}$ S9 BT

Thence,
N.2°20'W., on true line, bet. secs. 8 and 9, (N $\frac{1}{2}$)
Asc. 10 ft. over S. slope.
11.20 Wire fence, brs. NW and SE.
1.40 Spur, brs. NE. Desc. 89 ft. over NW slope.
4.90 Wash, 10 lks. wide, course NE. Asc. 44 ft. over SE slope.
10.00 Spur, brs. NE. Desc. 23 ft. over N. slope.
12.30 Wash, 5 lks. wide, course E. Asc. 88 ft. over S. slope.
12.90 Road, brs. E-W.
17.20 Road, brs. E-W.
20.85 Road, brs. E-W.
21.00 Water tank on knoll, about 1 ch. in diam., on spur,
bearing E-W., on line. Same road brs. W. This is a
supply tank for the Hassayampa Mtn. Club colony.
Desc. 154 ft. over N. slope.
23.30 Same road, brs. E-W.
23.50 Telephone line, brs. E-W.
27.60 Road, brs. E-W.
29.50 Power line, brs. E-W.
30.90 Road, brs. E-W.
31.50 Wash, 20 lks. wide, course E. Over level bottom.
34.70 Road, brs. E-W. Asc. 82 ft. over S. slope.
39.72 Intersect the true point for the cor. of secs. 4, 5, 8
and 9, as pointed out to me by John C. Stevens who
states that he has lived in this vicinity for sixty-
five years and that his father owned the S $\frac{1}{2}$ SE $\frac{1}{4}$ of
Sec. 5.

Chains

At this point set a wooden stake 4 ins. sq. and 2 1/2 ft. long, on bedrock, raise a mound of stone about same to mark the true point for cor. of secs. 4, 5, 8 and 9. From which, a 2 in. cross cut on boulder 3 x 3 x 3 ft., brs. S.1°W., 2.17 chs. dist. In accordance with Special Instructions do not monument this cor. point.

Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush and cacti.

From the original cor. of secs. 3, 4, 9 and 10. N.83°00'W., on true line, bet. secs. 4 and 9, (E 1/2) Over mountainous land, thru scattering timber & undergrowth.

- 5.15 Desc. 10 ft. over NW slope. Rocky wash, 10 lks. wide, course SW. Desc. 41 ft. over SW slope.
- 13.40 Rocky wash, 10 lks. wide, course NW. Asc. 10 ft. over E. slope.
- 15.00 Spur., brs. NW. Desc. 13 ft. over SW slope.
- 22.20 Wash, 20 lks. wide, course NW. Asc. 104 ft. over NE slope.
- 35.50 Spur, brs. NW. Desc. 13 ft. over gradual SW slope.
- 38.83 Intersect the original 1/4 sec. cor. of secs. 4 and 9, which is a granite stone 15 x 8 x 8 ins. unmarked, set in a mound of stone at cor. of fences from N.-S.-E., from which the original SE.BT, a yellow pine, 20 ins. in diam., brs. S.47 1/2°E., 43 lks. dist. (Record), marked 1/4 SBT an oak, 8 ins. in diam., brs. N.60 1/2°E., 76 lks. dist. (Record) marked 1/4 SBT Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, alongside old stone cor., for the 1/4 sec. cor. of secs. 4 and 9, with brass cap marked

1/4 S4

1/4 S9

1930 from which,
an oak, 9 ins. in diam., brs. N.45°W., 29 lks. dist., marked 1/4 S4 BT
an oak, 12 ins. in diam., brs. S.22 1/2°W., 92 lks. dist., marked 1/4 S9 BT

- Thence, S.88°22'W., on true line, bet. secs. 4 and 9, (W 1/2) Desc. 30 ft. over W. slope.
- 2.25 Wash, 10 lks. wide, course N. Asc, 21 ft. over E. slope.
- 6.00 Spur, brs. N. Desc. 57 ft. over W. slope.
- 7.60 Telephone line, brs. N.60°E.-S.60°W.
- 8.85 Granite Creek, 20 lks. wide, course N. Asc, 88 ft. over E. slope. Across slightly rolling land.
- 9.65 Wire fence, brs. N-S.
- 15.95 Wire fence, brs. N-S.
- 16.65 Wire fence, brs. N-S.
- 19.00 House brs. N., 100 lks. dist.
- 19.10 Power line, brs. N. and SW.

Chains	
24.00	Allen Dairy barn, brs. N. about 1.50 chs. dist.
26.30	Wire fence, brs. NE.-SW.
26.80	White Spar Highway, in bend, from NE. to SE.
27.20	Wire fence, brs. NE.-SW.
29.05	Pipe line, brs. NE.-SW. Hassayampa Auto Camp brs. N. 3 chs. dist.
30.50	Road, brs. NE.-SW.
33.20	Road, brs. NW.-SE.
40.00	Spur, brs. SW. Desc. slightly over SW. slope to
40.86	Intersect true point for cor. of secs. 4, 5, 8 and 9.
	Land, mountainous and rolling. Soil, rocky, 4th rate. Timber, yellow pine, oak and juniper. Undergrowth, scrub oak and cacti.

	From reestablished cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described, S.0°36'E., on true line, bet. secs. 4 and 5 (N. 1/2)
	Over rolling land, along wire fence on E. side of County road, and on the western limit of the City of Prescott according to the 1930 City Map.
	Asc. 29 ft. over N. slope.
0.43	fence cor., from which fences extend N. and S. 65° E.
0.84	Center of Juniper St., 50 ft. wide, extends S. 65° E.
1.26	fence cor., from which fences extend S. and S. 65° E.
9.50	Spur, brs. E. City Limit brs. westerly around Pinecrest subdivision. Enter City of Prescott. Thence along E. side of First St., descending slightly over S. slope.
13.10	Center of Gurley Ave., 60 ft. wide, extends N. 65° E.
14.50	Wash, 10 lks. wide, course E. Asc. 100 ft. over N. slope.
17.80	Center of Glendale Ave., 50 ft. wide, extends N. 85 1/2° E. Thence across Buena Vista Heights subdivision.
20.00	Enter scattering timber and undergrowth.
23.60	Spur, brs. W. Desc. 89 ft. over S. slope. Leave timber
26.63	N. side of Vista Drive, brs. N. 55 1/2° W. - S. 55 1/2° E. City Limit brs. N. 55 1/2° W. and S. Leave Buena Vista Heights. Thence along City Limit, across Vista Drive.
27.77	S. side of Vista Drive, brs. N. 55 1/2° W. - E. Continue along City Limit, on W. side of Ridgewood Heights subdivision.
30.06	City Limit brs. E. and N. Leave same. (Continue along W. side of Ridgewood Heights subdivision.)
34.10	Center of Fairview Ave., 50 ft. wide, extends S. 81° E. Thence along old wire fence, on W. side of Ridgewood Heights subdivision.
35.00	Wash, 10 lks. wide, course E. Asc. gradually over N. slope.
39.80	Intersect accepted 1/4 sec. cor. of secs. 4 and 5, which is a fence cor. post, 8 ins. diam., projecting 5 ft. above the ground, from which fences extend W., S., and N. John C. Stephens, pioneer citizen of Prescott stated that this fence cor. occupies the original position of the 1/4 sec. cor. In accordance with instructions no recon- struction of this cor. monument is made.
	Thence S.0°38'E., on true line, bet. secs. 4 and 5 (S. 1/2)
	Over rolling land, on the outskirts of Prescott, along wire fence across W. end of Bertrand Ave. which extends N. 88° E.
0.75	fence cor. from which fences extend N. 88° E., S. and N. Thence along fence bet. St. Luke's Homes tract on the E. and Brightwood Subdivision on the W. Desc. gradually over S. slope.
3.05	fence cor. from which fences extend S. 60° E., S. and N. Cont. along fence on E. side of Brightwood Subdivision.
5.85	Creek, containing small stream of water, in bend, from SW. to course SE. Continue along fence on E. side of Brightwood Subd., on W. side of cultivated land. Ascend gradually over N. slope.

Chains	
10.00	Group of houses brs. E. about 60 lks. dist.
13.80	Fence cor. from which fences extend N. 85° W. and N. This fence cor. is at SE. cor. of Brightwood Subd. and on N. side of Copper Basin Road.
14.00	Center of Copper Basin Road brs. N. 85° W. - S. 85° E.
14.45	Electric power transmission line, parallel to road.
14.50	Fence cor. from which fences extend S. 85° E. & S. Thence along fence.
14.90	Fence cor. from which fences extend S., N. 85° W. and N.
33.00	Electric power transmission line, brs. N. 60° E. and SW. along road, same bearing. Leave N.-S. fence.
37.70	intersect true point for cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Soil, rocky, 4th rate. Timber, yellow pine, oak and juniper. undergrowth, scrub oak and cacti.

	From true point for std. cor. of secs. 31 & 32, on the S. bdy. of the Tp., hereinbefore described, N. 11° 00' W., on true line, bet. secs. 31 and 32. Over mountainous land, thru dense timber and undergrowth, across bottom of Hassayampa Creek, course S.
0.50	Stream of water, 10 lks. wide, 3 ins. deep, course S.
1.50	Leave bottom. Asc. 423 ft. over steep, brushy SE. slope.
6.20	Road, brs. NE.-SW.
16.00	Spur, brs. SE. Desc. 19 ft. over N. slope.
21.30	Head of wash, course SE. Asc. 103 ft. over SW. slope.
25.00	Spur, brs. E. Desc. 119 ft. over NW. slope.
29.90	Wash, 10 lks. wide, course E. Asc. 24 ft. over S. slope.
32.00	Short spur, brs. E. Desc. 15 ft. over N. slope.
32.70	Wash, 5 lks. wide, course SE. Asc. 33 ft. over S. slope to
37.05	Midpoint, set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, and raise a mound of stone around post, for reestablished $\frac{1}{4}$ sec. cor. of secs. 31 and 32, with brass cap marked.
	$\frac{1}{4}$ S31 S32
	1930
	from which a juniper, 5 ins. diam., brs. S. 40° E., 85 lks. dist., marked $\frac{1}{4}$ S32 BT a yellow pine, 8 ins. diam., brs. S. 76 $\frac{1}{2}$ ° W., 82 lks. dist., marked $\frac{1}{4}$ S31 BT Spruce Mt. lookout tower bears N. 88° 4' E., +3° 47' V.A. Mt. Union lookout tower bears S. 59° 52' E., +3° 50' V.A.
	Asc. 47 ft. over S. slope.
38.50	Spur, brs. E. Desc. 115 ft. over N. slope.
42.50	Wash, 5 lks. wide, course E. Asc. 27 ft. over S. slope.
46.00	Spur, brs. E. Desc. 27 ft. over N. slope.
46.75	Wash, 10 lks. wide, course E. Asc. 44 ft. over S. slope.
50.20	Spur, brs. E. Desc. 80 ft. over N. slope.
53.80	Head of wash, course E. Asc. 13 ft. over S. slope.
55.10	Spur, brs. E. Desc. 47 ft. over N. slope.
57.10	Wash, 10 lks. wide, course E. Asc. 81 ft. over S. slope.
59.80	Spur, brs. E. Desc. 45 ft. over N. slope.
62.70	Wash, 10 lks. wide, course E. Asc. 64 ft. over S. slope.
65.00	Old road, brs. E.-W.
68.75	Ridge, brs. NE.-SW. Desc. 138 ft. over N. slope to
74.10	Intersect remains of original cor. of secs. 31, 32, 29 and 30, which is an oak stump, 20 ins. diam., 2 ft. high, scribed XXXI. Other markings visible but illegible. Reconstruct this cor. monument as follows: alongside old stump, set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in ground to bedrock, and raise a mound of stone around post, for cor. of secs. 31, 32, 29 and 30, with brass cap marked

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains

T13N	R2W
S30	S29
S31	S32

1930

from which

- a yellow pine, 10 ins.diam., brs. N.49½°W., 23 lks. dist., marked T13N R2W S30 BT
- a yellow pine, 12 ins.diam., brs. N.68°E., 85 lks. dist., marked T13N R2W S29 BT
- a yellow pine, 14 ins.diam., brs. S.36°E., 22 lks. dist., marked T13N R2W S32 BT
- an oak, 9 ins.diam., brs. S.77°W., 35 lks. dist., marked T13N R2W S31 BT

Land, mountainous. Soil, rocky, 4th rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, scrub oak, catclaw and cacti.

From original cor.of secs.28,29,32 and 33,
 S.89°40'W., on true line, bet. secs.29 and 32.
 Over mountainous land, thru dense timber and undergrowth.
 Asc. 24 ft. over E. slope.

- 2.30 Spur, brs. S. Desc. 17 ft. over W. slope.
- 3.45 Wash, 10 lks.wide, course S. Asc. 4 ft. over E. slope.
- 4.50 Low spur, brs. S. Desc. 6 ft. over SW. slope.
- 5.40 Shallow wash, course SE. Asc. 70 ft. over NE. slope.
- 9.50 Spur, brs. SE. Desc. 13 ft. over SW. slope.
- 11.20 Wash, near head, course S. Asc. 8 ft. over E. slope.
- 14.20 Spur, brs. S. Desc. 81 ft. over W. slope.
- 18.90 Wash, 10 lks.wide, course SW. Asc. 11 ft. over SE. slope.
- 20.30 Spur, brs. SW. Thence along S. slope.
- 23.17 From this point, Cor.No.2 of "Baby McKee" unpatented lode mining claim, M.S.No.1264, brs.S.25°E., 44 lks.dist., which is a granite stone 18x10x12 ins., firmly set in a mound of stone, and marked B McK 2-1264. From this claim cor. retrace S.19°23'E. (record course) on NE. side line (1-2) of "Baby McKee" claim, and at 8.55 chs. intersect Cor.No.1 thereof, identical with Cor.No.1 of "Ruth" patented lode claim of same M.S., which is a granite stone 6x12x20 ins. above ground, firmly set and marked B McK 1-1264 on N. face, and R 1-1264 on S. face, and witnessed by a mound of stone N. of cor. Computed direct tie to this claim cor. from 23.17 ch. station on sec. line is S.19°39½'E., 8.99 chs.
- 25.00 Desc. 144 ft. over NW. slope.
- 29.70 Old road, brs. NW.-SE.
- 34.80 Wash, 20 lks.wide, course NW. Old road, brs. NW.-SE. Asc. 21 ft. over NE. slope.
- 37.00 Spur, brs. NW. Old mill on line. Group of small mining houses brs. N. 3 chs. dist. Desc. 52 ft. over W. slope.
- 39.80 Highway, brs. N.-S.
- 41.20 Indian Creek, 20 lks.wide, course S. Asc. slightly over E. slope to
- 43.30 (Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in ground, for reestablished ¼ sec. cor. of secs. 29 and 32, with brass cap marked

S 29
¼
S 32

1930

from which

- an oak, 16 ins.diam., brs. N.53½°E., 103 lks. dist., marked ¼ S29 BT
- a yellow pine, 14 ins.diam., brs. S.76¼°W., 40 lks. dist., marked ¼ S32 BT
- House brs. S.8°E. 4 chs. House brs. N.28°E. 5 chs.

Chains
 48.50 Asc. 219 ft. over NE. slope.
 Wash, 10 lks. wide, course SE.
 62.20 Ridge, brs. NW.-SE. Desc. 212 ft. over SW. slope.
 75.10 Wash, 50 lks. wide, course SE. Asc. 21 ft. over NE. slope.
 76.20 Old road, brs. NW.-SE.
 80.30 Point of spur, brs. N. Desc. gradually over NW. slope.
 81.80 Bend in wash, course NE. from NW. Asc. 41 ft. over E. slope.
 86.60 Intersect original cor. of secs. 29, 30, 31 and 32.
 Land, mountainous. Soil, rocky, 4th rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, scrub oak, catclaw and cacti.

From reestablished cor. of secs. 30 and 31, on the W. bdy. of the Tp., hereinbefore described, S. 81° 50' E., on true line, bet. secs. 30 and 31. Over mountainous land, thru scattering timber and dense undergrowth. Desc. 389 ft. over E. slope to wash.

4.90 White Spar Highway, brs. N.-S.
 11.05 Wash, 20 lks. wide, course S. Asc. 425 ft. over W. slope.
 24.20 Ridge, brs. N.-S. Desc. 142 ft. over SE. slope.
 33.75 Wash, 10 lks. wide, course NE. Asc. 8 ft. over NW. slope to
 34.60 (Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in ground to bedrock, and raise a mound of stone around post, for reestablished $\frac{1}{4}$ sec. cor. of secs. 30 and 31, with brass cap marked

S 30

$\frac{1}{4}$ S31

1930

from which

a juniper, 9 ins. diam., brs. N. 85 $\frac{1}{2}$ ° E., 51 lks. dist., marked $\frac{1}{4}$ S30 BT
 an oak, 6 ins. diam., brs. S. 46° W., 75 lks. dist., marked $\frac{1}{4}$ S31 BT

Asc. gradually over NW. slope.
 39.70 Spur, brs. NE. Desc. 34 ft. over SE. slope.
 40.30 Wash, 5 lks. wide, course NE. Asc. 17 ft. over NW. slope.
 43.20 Spur, brs. NE. Desc. 162 ft. over SE. slope.
 49.10 Wash, 10 lks. wide, course NE. Asc. 9 ft. over NW. slope.
 50.00 Desc. 31 ft. over NE. slope.
 51.40 Wash, 20 lks. wide, course SE. Asc. 57 ft. over SW. slope.
 62.70 Spur, brs. S. Desc. 74 ft. over SE. slope.
 67.00 Wash, 20 lks. wide, course NE. Road, brs. NE.-SW.
 Asc. gradually over NW. slope.
 68.00 Spur, brs. N. Desc. slightly over NE. slope to
 69.20 Intersect original cor. of secs. 29, 30, 31 and 32.
 Land, mountainous. Soil, rocky, 4th rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, scrub oak, manzanita and cacti.


N. 0° 53' E., on true line, bet. secs. 29 and 30 (S. $\frac{1}{2}$)
 Over mountainous land, thru dense timber and undergrowth.
 Desc. 6 ft. over N. slope.

0.50 Wash, 10 lks. wide, course E. Asc. 57 ft. over SE. slope.
 1.10 Road, brs. NE.-SW.
 5.00 Spur, brs. E. Desc. 37 ft. over N. slope.
 6.65 Wash, 5 lks. wide, course E. Asc. 32 ft. over S. slope.
 10.00 Spur, brs. SE. Desc. 46 ft. over N. slope.
 12.50 Wash, 10 lks. wide, course SE. Road, brs. NW.-SE.
 House brs. W. 50 lks. Asc. 7 ft. over SE. slope.
 13.60 Spur, brs. W. Desc. 9 ft. over N. slope.
 14.90 Wash, 10 lks. wide, course SW. Asc. 135 ft. over SE. slope.
 15.80 Road, brs. NE.-SW.
 25.50 Spur, brs. E. Desc. 27 ft. over NE. slope.
 29.00 Wash, at bend, 50 lks. wide, course SE. from NE.

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains

Asc. 65 ft. over SW slope.
 35.40 Slope changes to West. Along level land.
 39.90 Road, brs. E-W.
 42.30 Small wash, course SW. Asc. 23 ft. over SE slope.
 43.41 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 29 & 30, which is a juniper tree 24 ins. in diam., marked $\frac{1}{4}$ S on S. face. No bearing trees.
 Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, raise a mound of stone about post, for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, with brass cap marked




1930 from which,
 an oak, 6 ins. in diam., brs. N.44°W., 29 lks. dist., marked $\frac{1}{4}$ S30 BT
 an oak, 8 ins. in diam., brs. S.79°E., 19 lks. dist., marked $\frac{1}{4}$ S29 BT

Thence,
 N.1°14'W., on true line, bet. secs. 29 and 30, (N $\frac{1}{2}$)
 Asc. 122 ft. over SE slope.

1.40 Highway, brs. NW-SE.
 7.90 Ridge, brs. NW-SE. Desc. 28 ft. over NE slope.
 11.00 Wash, near head, course NE. Asc. 42 ft. over SE slope.
 14.60 Branch spur, brs. NE. Desc. 97 ft. over NW slope to wash.
 18.00 Spur, brs. East.
 22.20 Wash, 5 lks. wide, course E. Asc. 37 ft. over SE slope.
 28.00 Ridge, brs. NE-SW. Desc. 52 ft. over NW slope.
 32.90 Wash, 10 lks. wide, course NE. Asc. 9 ft. over SE slope.
 34.40 Spur, brs. NE.. Desc. 18 ft. over N. slope..
 37.20 Road, brs. NW-SE.
 38.40 Wash, 20 lks. wide, course SE. Asc. 18 ft. over SW slope.
 42.98 Intersect the original cor. of secs. 19, 20, 29 and 30

which is a stone 10 x 14 x 18 ins., marked with two and five grooves on S. and E. faces respectively.

from which,
 a pine stump. 24 ins. in diam., 2 ft. above ground, brs. N.4°W., 83 lks. dist., scribe marks visible but illegible. No other bearing tree remains.
 Reconstruct this cor. monument by setting an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, alongside the old stone cor., with brass cap marked



1930 from which,
 a yellow pine, 14 ins. in diam., brs. N.70°W., 25 lks. dist., marked T13N R2W S19 BT
 an oak, 10 ins. in diam., brs. N.15°E., 15 lks. dist., marked T13N R2W S20 BT
 an oak, 18 ins. in diam., brs. S.53°E., 63 lks. dist., marked T13N R2W S29 BT
 an oak, 18 ins. in diam., brs. S.61°W., 80 lks. dist., marked T13N R2W S30 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, cacti and catclaw.

Chains

From the cor. of secs. 20, 21, 28 and 29.
 N.87°20'W., on true line, bet. secs. 20 and 29.
 Over mountainous land, thru thick timber & undergrowth.
 Desc. 17 ft. over W. slope.
 4.80 Wash, 10 lks. wide, course SW. Asc. 20 ft. over SE slope.
 7.25 Spur, brs. S. Desc. 17 ft. over SW slope.
 13.80 Wash, 10 lks. wide, course S. Asc. 41 ft. over SE slope.
 16.45 Spur, brs. SW. Desc. 78 ft. over NW slope.
 24.75 Wash, 10 lks. wide, course SW. Asc. 15 ft. over SE slope.
 27.54 Spur, brs. S. Desc. 30 ft. over W. slope.
 31.35 Wash, 20 lks. wide, course S. Asc. 60 ft. over E. slope.
 35.30 Spur, brs. S. Desc. 38 ft. over W. slope.
 39.25 Wash, 10 lks. wide, course S. Asc. gradual SE slope.
 41.94 Old road, brs. N-S.
 42.12 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
 18 ins. in the ground to bedrock, raise a mound of stone
 about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs.
 20 and 29, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 20 \\ S 29 \end{array}$$

1930 from which,
 a yellow pine, 6 ins. in diam., brs. N.12°W., 4 lks.
 dist., marked $\frac{1}{4}$ S20 BT
 a yellow pine, 8 ins. in diam., brs. S.26 $\frac{1}{4}$ °W., 23 lks.,
 dist., marked $\frac{1}{4}$ S29 BT
 Asc. 26 ft. over E. slope.
 45.60 Old road, on ridge, brs. NE-SW. Desc. 161 ft. over W.
 slope.
 61.55 Wash, 10 lks. wide, course S.25°W. Asc. 53 ft. over
 E. slope.
 64.80 Spur, brs. S. Desc. 50 ft. over W. slope.
 72.00 Wash, 10 lks. wide, course SW. Asc. 34 ft. over E. slope.
 84.24 Intersect the cor. of secs. 19, 20, 29 and 30.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita and cacti.

From the reestablished cor. of secs. 19 and 30, on W.
 bdy. of Tp., hereinbefore described.
 S.85°10'E., on true line, bet. secs. 19 and 30, ($W\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth.
 Desc. 102 ft. over NE slope.
 2.00 Wash, 20 lks. wide, from NW to East. Thence down same.
 5.70 Leave wash, turns NE. Asc. gradual NW slope.
 7.70 Spur, brs. NE. Desc. 223 ft. over rolling E. slope.
 23.45 Wash, 20 lks. wide, course NE. Asc. 106 ft. over NW slope.
 27.65 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 19 and 30,
 recovered from original SW bearing tree, which brs.
 S.40°W., 50 lks. dist., marked $\frac{1}{4}$ SBT, and which is a stump
 5 ft. above ground, 2 ft. in diam.
 Reconstruct this cor. monument by setting an iron post
 3 ft. long, 1 in. in diam., 26 ins. in the ground
 for the reconstructed $\frac{1}{4}$ sec. cor. of secs. 19 & 30,
 with brass cap marked

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W. 387

Chains

$\frac{1}{4}$ S19
S30

1930 from which,
an oak, 5 ins. in diam., brs. N.55°E., 24 lks. dist.,
marked $\frac{1}{4}$ S19 BT
a yellow pine, 20 ins. in diam., brs. S.30°W., 62 lks.
dist., marked $\frac{1}{4}$ S30 BT

- 6.00 Thence, S.88°50'E., on true line, bet.secs. 19 and 30,(E $\frac{1}{2}$)
- 6.50 Asc. 37 ft. over NW slope.
- 18.65 Spur, brs. NE. Desc. 248 ft. over SE slope.
- 18.90 Wire fence, brs. N.30°E-S.30°W.
- 23.00 Wash, 20 lks. wide, course NE. Asc. 14 ft. over NW slope.
- 26.00 Old road, brs. NE-SW.
- 27.50 Spur, brs. NE. Desc. 49 ft. over SE slope.
- 29.70 Wash, 10 lks. wide, course NE. Asc. slight NW slope.
- 38.76 Spur, brs. N. Desc. 100 ft. over NE slope to wash.
- 39.20 White Spar Highway, brs. N. and SE.
- 43.62 Road, brs. NW-SE,
Indian Creek, 20 lks. wide, course SE.(Dry.)
Asc. 9 ft. over SW slope.
Intersect the cor. of secs. 19, 20, 29 and 30.

Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush, manzanita and cacti.

- 3.00 N.2°40'E., on true line, bet. secs. 19 and 20.
- 10.00 Over mountainous land, thru thick timber & undergrowth.
- 15.00 Asc. 37 ft. over gradual S. slope.
- 16.10 Old road, brs. NE-SW.
- 17.30 Spur, brs. SW. Desc. gradual NW slope.
- 20.00 Wash, 10 lks. wide, course SW: Asc. slight SE slope.
- 21.15 Pumphouse, brs. E. 20 lks. dist.
- 23.55 Same wash, course SE.Asc. 40 ft. over SE slope.
- 27.10 Spur, brs. SW. Desc. gradual NW slope.
- 28.70 Same wash, course SW. Continue up same.
- 32.10 Leave wash, turns to NW.
- 34.00 Same wash, course SW. Continue up same.
- 34.95 Leave wash, turns to NW. Asc. 29 ft. over SW slope.
- 35.20 Wire fence, brs. NW-SE. Asc. 42 ft. over S. slope.
- 36.50 Spur, brs. SE. Desc. 14 ft. over SE slope.
- 41.50 Wash, 10 lks. wide, course SE.
- 41.62 Asc. 25 ft. over S. slope.
Pipeline, brs. NW-SE.
Top of The Pines Camp, cluster of cabins E.-W. of line.
Across camp yard, on divide, bearing E-W.
Wire fence, brs. E-W. Leave camp yard.
(Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
20 ins. in the ground to bedrock, raise a mound of
stone about post, for the reestablished $\frac{1}{4}$ sec. cor.
of secs. 19 and 20, with brass cap marked

$\frac{1}{4}$
S19 | S20

1930

88 Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains

- 53.64 Desc. 67 ft. over NE slope. Granite Creek, near head, course NE. Asc. 19 ft. over SE slope.
- 57.14 White Spar Highway, brs. NE-S.10°W.
- 60.25 Spur, brs. E. Desc. 41 ft. over N. slope.
- 62.64 Wash, 20 lks. wide, course E. Asc. 206 ft. over S. slope.
- 78.24 Spur, brs. E. Desc. 37 ft. over N. slope.
- 80.74 Wash, 10 lks. wide, course E. Asc. 40 ft. over S. slope.
- 83.24 Intersect the original cor. of secs. 17, 18, 19 and 20, which is a stone 16 x 16 x 8 ins., marked 3 grooves on S. and 5 grooves on E. faces, firmly set in a mound of stone.
Reconstruct this cor. monument by setting an iron post 3 ft. long, 2 ins. in diam., 16 ins. in the ground to bedrock, alongside old stone cor., raise a mound of stone about post, for the cor. of secs. 17, 18, 19 and 20, with brass cap marked

T13N	R2W
S18	S17
S19	S20

1930

from which

- A yellow pine 8 ins. diam. brs. N. 54° W., 58 lks. dist., mkd. T13N R2W S18 BT.
- A yellow pine 10 ins. diam. brs. N. 18° E., 51 lks. dist., mkd. T13N R2W S17 BT.
- No other bearing trees available.

-
- 0.80 From cor. of secs. 16, 17, 20 and 21. N.87°12'W., on true line, bet. secs. 17 and 20, (E½) Over mountainous land, thru thick timber & undergrowth. Desc. slight SW slope.
 - 2.10 Wash, 10 lks. wide, course NW. Continue on desc. of 24 ft. over NW slope.
 - 3.80 Old road, brs. N-S. Center of Granite Creek, 30 lks. wide, course N. Asc. 41 ft. over E. slope.
 - 5.60 White Spar Hgy., brs. NE-SW.
 - 6.70 Spur, brs. S. Desc. 8 ft. over SW slope.
 - 8.65 Wash, 10 lks. wide, course SE. Asc. 183 ft. over SE slope.
 - 32.70 Spur, brs. S. Desc. 29 ft. over SW slope.
 - 36.80 Wash, 10 lks. wide, course S. Asc. 29 ft. over E. slope.
 - 38.50 Spur, brs. S. Desc. 10 ft. over W. slope.
 - 40.21 Intersect the original ¼ sec. cor. of secs. 17 & 20, which is a granite stone 10 x 12 x 24 ins., firmly set, marked ¼, from which, a pine stump, 3 ft. high, 20 ins. in diam., brs. S.9°W. 29 lks. dist. (Record), markings have gone. Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground alongside the old stone cor., raise a mound of stone about post, for the ¼ sec. cor. of secs. 17 and 20, with brass cap marked

Re-Survey of Part of the Subd. Lines of T.13 N., R.2 W.

Chains

1/4 S 17
S 20

1930 from which,
 a yellow pine, 12 ins. in diam., brs. N.20°E., 20 lks. dist., marked 1/4 S17 BT
 a yellow pine, 14 ins. in diam., brs. S.46°E., 26 lks. dist., marked 1/4 S20 BT
 Thence, S, 89°W., on true line, bet. secs. 17 & 20, (W 1/2)
 Desc. 10 ft. over W. slope.
 1.40 Wash, 10 lks. wide, course S. Asc. 34 ft. over E. slope.
 6.45 Rocky spur, brs. S. Desc. 24 ft. over W. slope.
 11.20 Wash, 5 lks. wide, course S. Asc. 20 ft. over E. slope.
 12.30 Spur, brs. S. Desc. 10 ft. over W. slope.
 14.45 Wash, 10 lks. wide, course SE. Asc. 119 ft. over NE slope.
 28.95 Spur, brs. SE. Asc. 69 ft. over SE slope to
 40.96 Intersect the cor. of secs. 17, 18, 19 and 20.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, catclaw and cacti.

From the reestablished cor. of secs. 18 and 19, on W. bdy. of Tp., hereinbefore described.
 N. 89°47'E., on true line, bet. secs. 18 and 19.
 Over mountainous land, thru thick timber & undergrowth.
 Asc. 23 ft. over W. slope.
 3.00 Spur, brs. S. Desc. 43 ft. over E. slope.
 5.70 Wash, 10 lks. wide, course S. Asc. 48 ft. over W. slope.
 10.00 Spur, brs. S. Desc. 42 ft. over E. slope.
 13.70 Wash, 5 lks. wide, course SE. Asc. 11 ft. over SW slope.
 16.00 Spur, brs. SE. Desc. 96 ft. over NE slope.
 22.15 Wash, 10 lks. wide, course SE. Desc. 56 ft. down same.
 24.80 Leave wash, to SE. Over spur, tip, from N.
 26.30 Same wash, course East. Desc. gradually down same.
 28.50 Leave wash, from N-NE. Asc. 9 ft. over NW slope.
 30.00 Spur, brs. NE. Desc. 52 ft. over SE slope.
 32.70 Wash, 10 lks. wide, course SE. Asc. 93 ft. over SW slope.
 37.80 Spur, brs. SE. Desc. gradual NE slope to
 38.99 (Proportionate point) set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished 1/4 sec. cor. of secs. 18 and 19, with brass cap marked


1/4 S 18
S 19

1930 from which,
 a yellow pine, 10 ins. in diam., brs. N.62°E., 41 lks. dist., marked 1/4 S18 BT
 a yellow pine, 14 ins. in diam., brs. S.71°W., 24 lks. dist., marked 1/4 S19 BT
 Desc. 74 ft. over NE slope.
 44.10 Wash, 10 lks. wide, course SE. Asc. 97 ft. over SW slope.
 47.00 Spur, brs. SE. Asc. 17 ft. along SW slope.
 59.00 Spur, brs. SE. Desc. 130 ft. over NE slope.

Chains	
69.40	Wash, 10 lks. wide, course S. Asc. 60 ft. over W. slope.
73.60	Spur, brs. SE. Desc. 23 ft. over NE slope.
75.50	Wash, 10 lks. wide, course SE. Asc. 19 ft. over SW slope.
78.16	Intersect the cor. of secs. 17, 18, 19 and 20.
	<p>Land, mountainous. Soil, rocky 4th. rate. Timber, yellow pine, oak and juniper. Undergrowth, oakbrush, manzanita, cacti and catclaw.</p>
	<p>N.1°13'W., on true line, bet. secs. 17 and 18. Over mountainous land, thru thick timber & undergrowth. Asc. 31 ft. over S. slope.</p>
3.00	Spur, brs. E. Desc. 139 ft. over steep N. slope.
8.40	Wash, 20 lks. wide; course E. Asc. 384 ft. over brushy S. slope.
13.24	<p>Intersect the SE side line, (3-4) of the "Comet" pat. lode mining claim, Min. Sur. No.2677, at 2.46 chs. N.21°18'E., of Cor. No.3 thereof.</p>
	Across patented mineral land.
21.30	<p>Quartz Peak; about 50 lks. in diam., on ridge, brs. E-W. Desc. 257 ft. over steep N. slope.</p>
25.50	Old road, brs. E-W.
29.20	Shallow wash, course NE. Along SE slope.
30.19	<p>Intersect the NE end line (1-4) of the "Comet" pat. claim., at 84 lks. S.80°50'E. of Cor. No.1 thereof. Leave patented mineral land.</p>
37.00	Spur, brs. NE. Desc. 106 ft. over NW slope.
39.80	Wash, 10 lks. wide, course NE. Asc. slight SE slope.
40.53	<p>(Midpoint) set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs. 17 and 18, with brass cap marked</p>
	<p style="text-align: center;"> $\frac{1}{4}$ S18 S17 1930 </p>
	<p style="text-align: center;">from which,</p> <p>a yellow pine, 20 ins. in diam., brs. N.30°E., 77 lks. dist., marked $\frac{1}{4}$ S17 BT a yellow pine, 16 ins. in diam., brs. S.4$\frac{1}{2}$°W., 32 lks. dist., marked $\frac{1}{4}$ S18 BT</p>
	Desc. 128 ft. along NE slope.
58.00	Spur, brs. NE. Asc. 10 ft. along top of spur.
61.50	Leave spur, desc. 71 ft. over NW slope.
67.15	Wash, 10 lks. wide, course NE. Asc. slight SE slope.
71.60	Spur, brs. East, Desc. slight N. slope.
71.90	Wash, 10 lks. wide, course E. Asc. 13 ft. over S. slope.
76.00	Spur, brs. E. Desc. 46 ft. over N. slope.
81.06	<p>Intersect the original cor. of secs. 7, 8, 17 and 18, which is a granite stone 18 x 12 x 5 ins. firmly set in mound of stone, marked 4 and 5 notches on S. and E. faces respectively. From which, pine stump, 20 ins. in diam., barely projecting above ground, brs. N.19°W., 25 lks. dist., (Record.) pine stump, (remains) brs. N.83°W., 19 lks. dist. (Record.)</p> <p>Reconstruct this cor. monument by setting an iron post 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, alongside old cor. stone, raise a mound of stone about post, for the cor. of secs. 7, 8, 17 & 18, with brass cap marked</p>

Re-Survey of Part of the Subd. Lines of T. 13 N., R. 2 W.

Chains




1930 from which,
 a yellow pine, 24 ins. in diam., brs. N. 38 $\frac{1}{4}$ °W., 129 lks. dist., marked T13N R2W S7 BT
 a yellow pine, 20 ins. in diam., brs. N. 27 $\frac{3}{4}$ °E., 76 lks. dist., marked T13N R2W S8 BT
 a yellow pine, 12 ins. in diam., brs. S. 73 $\frac{1}{4}$ °E., 41 lks. dist., marked T13N R2W S17 BT
 an oak, 8 ins. in diam., brs. S. 51 $\frac{1}{4}$ °W., 36 lks. dist., marked T13N R2W S18 BT

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita, catclaw and cacti.

5.00
 9.50
 11.30
 20.00
 21.40
 36.00
 40.50

From the reestablished cor. of secs. 8, 9, 16 & 17. S. 89° 38' W., on true line, bet. secs. 8 and 17. Over mountainous land, thru thick timber & undergrowth. Asc. 56 ft. over NE slope.
 Spur, brs. N. Thence along NW slope on slight descent.
 Wash, 10 lks. wide, course NE. Asc. up same, gradually.
 Leave wash, from NW. Asc. 43 ft. over E. slope.
 Spur, brs. N. Desc. 9 ft. over NW slope.
 Same wash, course NE. Asc. 100 ft. over SE slope.
 Ridge, brs. NE-W., along level top.
 (Midpoint) set an iron post 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs. 8 and 17, with brass cap marked



1930 from which,
 a yellow pine, 14 ins. in diam., brs. N. 23°E., 88 lks. dist., marked $\frac{1}{4}$ S8 BT
 a juniper, 12 ins. in diam., brs. S. 73°W., 83 lks. dist., marked $\frac{1}{4}$ S17 BT

45.00
 50.70
 57.20
 68.50
 74.60
 75.00
 81.00

Asc. 26 ft. over ridge top.
 Leave ridge from SW., desc. 171 ft. over rolling NW slope.
 Spur, brs. NW.
 Wash, 20 lks. wide, course NW. Asc. 163 ft. over rolling NE slope.
 Spur, brs. N. Desc. 68 ft. over W. slope.
 Road, brs. NW-SE.
 Wash, 20 lks. wide, course N. Asc. 22 ft. over NE slope.
 Intersect the cor. of secs. 7, 8, 17 & 18.
 Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita and cacti.

Chains

From the reestablished cor. of secs. 7 and 18, on W. bdy. of Tp., hereinbefore described.

Then,

S. 87° 55' E., on true line, bet. secs. 7 and 18.

Over mountainous land, thru thick timber & undergrowth.

Desc. 206 ft. over E. slope.

7.70

Power line, brs. NE-SW.

9.90

Wash, 10 lks. wide, course N. Asc. 25 ft. over NW slope.

12.20

Spur, brs. N. Desc. 164 ft. over SE slope.

21.90

Wash, 10 lks. wide, course NE. Asc. 6 ft. over NW slope.

22.80

Spur, brs. NE. Desc. 45 ft. over S^W slope.

28.95

Wash, 10 lks. wide, course N. Asc. 12 ft. over W. slope.

30.10

Spur, brs. N. Desc. 18 ft. over E. slope.

32.70

Wash, 10 lks. wide, course N. Asc. 12 ft. over W. slope.

34.80

Spur, brs. NE. Old road, brs. NE-SW.

Desc. gradual E. slope.

35.40

Wash, 10 lks. wide, course NE. Asc. gradual W. slope.

37.40

Spur, brs. N. Desc. 16 ft. over E. slope to

39.00

(Proportionate point) set an iron post 3 ft. long, 1 in. in diam., on bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs. 7 and 18, with brass cap marked

$\frac{1}{4}$ $\frac{S 7}{S 18}$

1930

from which,

a yellow pine, 10 ins. in diam., brs. N. 27° E., 16 lks. dist., marked $\frac{1}{4}$ S7 BT

a yellow pine, 18 ins. in diam., brs. S. 63° E., 79 lks. dist., marked $\frac{1}{4}$ S18 BT

Asc. slight W. slope.

39.35

Telephone line, brs. N. 60° E. - S. 60° W.

42.40

Spur, brs. NE. Desc. 23 ft. over SE slope.

44.20

Wash, 10 lks. wide, from SW to E. Desc. 23 ft. down same.

47.20

Leave wash, to NE. Asc. 12 ft. over NW slope.

49.80

Spur, brs. NE. Desc. 24 ft. over SE slope.

51.20

Wash, 10 lks. wide, course NE. Asc. 6 ft. over NW slope.

51.90

Spur, brs. NE. Desc. 9 ft. over E. slope.

54.00

Wash, 5 lks. wide, course NE. Asc. 21 ft. over NW slope.

59.40

Spur, brs. NE. Desc. 39 ft. over SE slope.

63.35

Wash, 10 lks. wide, course NE. Asc. 49 ft. over NW slope.

68.40

Spur, brs. NE. Desc. 46 ft. over SE slope.

75.80

Wash, near head, course NE. Asc. 26 ft. over NW slope.

77.00

Spur, brs. NE. Desc. 26 ft. over SE slope to

78.40

Intersect the cor. of secs. 7, 8, 17 and 18.

Land, mountainous.

Soil, rocky 4th rate.

Timber, yellow pine, oak and juniper.

Undergrowth, oakbrush, manzanita, catclaw and cacti.

N. 2° 23' W., on true line, bet. secs. 7 and 8, ($S\frac{1}{2}$)

Over mountainous land, thru thick timber & undergrowth.

Desc. 21 ft. over NE slope.

3.80

Shallow wash, course E. Along rolling E. slope.

10.50

Wash, 10 lks. wide, course NE. Asc. 15 ft. over SE slope.

13.00

Spur, brs. NE. Desc. 9 ft. over NW slope.

19.35

Shallow wash, 10 lks. wide, course NE. Asc. 7 ft. over SE slope.


20.60

Spur, brs. NE. Desc. 53 ft. over rolling NW slope.

Resurvey of Part of the Subd. Lines of T. 13 N., R. 2 W. 93


Chains

22.00 Telephone line, brs. NE-SW.
 31.00 Wash, 20 lks. wide, course NE. Asc. 14 ft. over SE slope.
 32.00 Spur, brs. NE. Desc. 17 ft. over NW slope.
 35.80 Wash, 30 lks. wide, course NE. Asc. 40 ft. over SE slope.
 39.70 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 7 and 8,
 which is a stone 14 x 14 x 16 ins. lying on ground in
 partly buried mound of stone, faintly marked $\frac{1}{4}$ on one
 face. From which,
 stump of oak, brs. N.15 $\frac{1}{2}$ °W., 18 lks. dist. (Record).
 stump of oak, brs. S.53°W., 31 lks. dist.
 Reconstruct this cor. monument by setting an iron post
 3 ft. long, 1 in. in diam., 16 ins. in the ground
 to bedrock, alongside old stone cor., raise a mound
 of stone about post, for the $\frac{1}{4}$ sec. cor. of secs.
 7 and 8, with brass cap marked



1930 from which,
 an oak, 6 ins. in diam., brs. N.80°W., 24 lks. dist.,
 marked $\frac{1}{4}$ S7 BT
 an oak, 6 ins. in diam., brs. S.65 $\frac{1}{2}$ °E., 18 lks. dist.,
 marked $\frac{1}{4}$ S8 BT

Thence,
 N.3°00'E., on true line, bet. secs. 7 and 8, N $\frac{1}{2}$.
 Asc. 21 ft. over SE slope.
 2.00 Wash, 20 lks. wide, course SE. Asc. 103 ft. over SW slope.
 5.00 Spur, brs. SE. Asc. gradually over same.
 12.00 Power line, brs. NE-SW.
 14.20 Copper Basin Road, brs. NE-SW.
 16.70 Spur, brs. SE. Desc. 18 ft. over NE slope.
 19.00 Wash, 10 lks. wide, course E. Over rolling E. slope
 on gradual descent of 41 ft.
 29.50 Spur, brs. NE. Desc. 50 ft. over NW slope.
 35.00 Wash, 30 lks. wide, course E. Asc. 56 ft. over S. slope to
 38.22 Intersect the original cor. of secs. 5, 6, 7 and 8,
 which is a stone 24 x 20 x 20 ins. above ground, firmly
 set in a mound of stone, marked with 5 and 5 grooves
 on S. and E. edges, from which,
 a juniper 30 ins. in diam., brs. N.56°W., 17 lks. dist.
 marked T13N R2W S6 BT
 an oak, 10 ins. in diam., brs. N.43 $\frac{1}{2}$ °E., 17 lks. dist.
 has been blazed and marked, but same markings have gone.
 Reconstruct this cor. monument by setting an iron post
 3 ft. long, 2 ins. in diam., 20 ins. in the ground to
 bedrock, alongside the old stone cor., for the cor.
 of secs. 5, 6, 7 and 8, with brass cap marked



1930 from which,
 an oak, 4 ins. in diam., brs. N.44°E., 19 lks. dist.,
 marked BT
 an oak, 4 ins. in diam., brs. S.8°E., — lks. dist.,
 marked BT
 an oak, 9 ins. in diam., brs. S.31°W., — lks. dist.,
 marked T13N R2W S7 BT

94 Resurvey of Part of the Subd. Lines of T. 13 N., R. 2 W.

Chains

Land, mountainous.
Soil, rocky 4th. rate.
Timber, yellow pine, pinion, juniper and oak.
Undergrowth, oakbrush, manzanita, catclaw and cacti.

From the cor. of secs. 4, 5, 8 and 9.
S. 87° 15' W., on true line, bet. secs. 5 and 8.
Over mountainous land, thru thick timber & undergrowth.
Desc. 9 ft. over W. slope.

0.10 Wire fence, brs. N-S.
2.60 Wash, 10 lks. wide, course S. Asc. 18 ft. over E. slope.
2.90 Power line, brs. NE-SW.
3.10 Road, brs. NE-SW.
6.00 Rocky spur, brs. S. Desc. 52 ft. over W. slope.
10.85 Road, bends from SE-SW.
12.00 Wash, 5 lks. wide, course S. Asc. 76 ft. over SE slope.
16.80 Spur, brs. SW. Desc. 86 ft. over NW slope.
20.80 Wash, 10 lks. wide, course S. Asc. 41 ft. over E. slope.
24.00 Spur, brs. S. Desc. 17 ft. over rolling W. slope.
27.10 Shallow wash, course SW.
30.10 Wash, 10 lks. wide, course SE. Asc. 27 ft. over SE slope.
34.60 Spur, brs. S. Over level land.
39.00 Road, brs. N-S.
40.85 (Midpoint) set an iron post 3 ft. long, 1 in. in diam.,
16 ins. in the ground to bedrock, raise a mound of
stone about post, for the reestablished $\frac{1}{4}$ sec. cor.
of secs. 5 and 8, with brass cap marked

$$\frac{S\ 5}{S\ 8}$$

1930

from which,
an oak, 14 ins. in diam., brs. N. 62 $\frac{1}{2}$ ° W., 12 lks.
dist., marked $\frac{1}{4}$ S5 BT
a yellow pine, 16 ins. in diam., brs. S. 59° W., 17 lks.
dist., marked $\frac{1}{4}$ S8 BT

41.00 Road, brs. NW-SE.
42.15 Road, brs. N-S.
42.45 Wire fence, brs. N-S.
46.00 Leave level, enter rolling land. Asc. 66 ft. over E. slope.
55.00 Spur, brs. NE. Desc. gradual NW slope.
57.70 Wire fence, brs. NE-SW. in draw, course NE.
58.35 Copper Basin Road, brs. NE-SW.
60.00 Spur, brs. NE. Desc. gradual NW slope.
62.10 Wash, 10 lks. wide, course NE. Asc. 18 ft. over SE slope.
65.90 Spur, brs. NE.
69.70 Shallow wash, course NE. Asc. 16 ft. over E. slope.
71.90 Fence cor., fences br. S. and W. Along fence.
72.00 Spur, brs. N. Desc. 28 ft. over W. slope.
75.45 Fence turns to SW.
75.80 Wash, 20 lks. wide, course NE. Asc. 85 ft. over SE slope.
81.70 Intersect the cor. of secs. 5, 6, 7 and 8.

Land, mountainous and rolling.
Soil, rocky 4th. rate.
Timber, yellow pine, oak and juniper.
Undergrowth, oakbrush, catclaw and cacti.

Re-Survey of Part of the Subd. Lines of T. 15 N., R. 2 W.

Chains

From the reestablished cor. of secs. 6 and 7 on W. bdy. of Tp., hereinbefore described.

Thence,
 S.89°E., on true line, bet. secs. 6 and 7, ($W\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth.
 Desc. 134 ft. overrolling SE slope.
 17.10 Wash, 20 lks. wide, course SE.
 19.15 Wash, 20 lks. wide, course NE. Asc. 14 ft. over NW slope.
 21.90 Wire fence, on Spur, brs. N. Desc. 164 ft. over rolling SE slope to $\frac{1}{4}$ sec. cor.
 29.50 Wash, 20 lks. wide, course SE.
 39.60 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 6 & 7 which is a granite stone 10 x 10 x 14 ins. above ground, firmly set and marked $\frac{1}{4}$ on N. face, from which, a pine 16 ins. in diam., brs. S.63°E., 24 lks. dist., marked $\frac{1}{4}$ S7 BT
 Reconstruct this cor. monument by setting an iron post 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, alongside old stone cor., for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, with brass cap marked

$$\frac{1}{4} \frac{S6}{S7}$$

1930 from which,
 a yellow pine, 8 ins. in diam., brs. N.19°W., 21 lks. dist., marked $\frac{1}{4}$ S6 BT
 Remark original BT, $\frac{1}{4}$ S7 BT

Thence,
 S.87°46'E., on true line, bet. secs. 6 and 7, ($E\frac{1}{2}$)
 Desc. 59 ft. over SE slope.
 3.20 Wire fence, brs. N-S.
 4.60 S. edge of small reservoir. Across orchard.
 7.83 Creek. 20 lks. wide, 6 ins. deep, course NE.
 The Paradise Valley Guest Ranch, brs. NE about 10 chs. dist.
 9.00 Asc. 104 ft. over NW slope.
 12.43 Wire fence, brs. NE-SW.
 17.00 Spur, brs. N. Desc. gradual E. slope.
 22.00 Wash, 10 lks. wide, course NE. Asc. 9 ft. over NW slope.
 25.00 Spur, brs. NE. Desc. 31 ft. over E. slope.
 26.30 Wire fence, brs. NE-SW.
 27.68 Same fence, brs. N.-S.
 28.83 Same fence, brs. NE-SW.
 37.00 Spur, brs. NE. Desc. 33 ft. over SE slope.
 37.68 Same fence, brs. NW-SE.
 38.58 Same fence, brs. NE-SW.
 39.98 Intersect the cor. of secs. 5, 6, 7 and 8.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, manzanita, catclaw and cacti.

From the cor. of secs. 5, 6, 31 and 32, on N. bdy. of Tp., hereinbefore described.
 S.0°47'W., on true line, bet. secs. 5 and 6, ($N\frac{1}{2}$)
 Over rolling land, thru thick timber & undergrowth.
 0.50 Power line, brs. NW-SE.
 1.40 Wash, 10 lks. wide, course SE.
 2.20 Road, brs. NW-SE.
 3.80 Road, brs. E-W. Enters yard 10 lks. West.

96 Re-Survey of Part of the Subd. Lines of T. 13 N., R. 2 W.

Chains

7.60 Wire fence, brs. E-W. Alongside of N-S. fence, about 20 ft. E.
 12.30 Wash, 20 lks. wide, course E.
 20.00 Fence, jogs West from N-S. fence, thence S.
 22.80 Shallow wash, course NE.
 33.70 Cross wire fence, brs. E-W. Asc. gradual N. slope.
 40.00 Intersect the true point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6 determined from the remains of two original bearing trees, which are the stumps of juniper trees protruding about 12 ins. above ground and about 20 ins. in diam., unearth old scribe marks upon pieces of these trees below ground at face of stumps.
 Determine true point for cor. by measuring record distances of 21 and 61 lks. SE and SW from center of old stumps and at intersection of these two measurements set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, raise a mound of stone about post, for the reestablished $\frac{1}{4}$ sec. cor. of secs. 5 & 6, with brass cap marked

$\frac{1}{4}$
 S6 | S5

1930 from which,
 old original tree brs. N.40°W., 21 lks. dist.
 old original tree brs. N.52°E., 61 lks. dist.
 (New trees,)
 a yellow pine, 28 ins. in diam., brs. N.42°W., 94 lks. dist., marked $\frac{1}{4}$ S6 BT
 an oak, 14 ins. in diam., brs. S.24°E., 40 lks. dist., marked $\frac{1}{4}$ S5 BT
 A cor. of wire and rock fence, which brs. N. and about East, brs. S. 13 lks. dist.
 The $\frac{1}{4}$ sec. cor. set under N-S. fence.

Thence,
 S.0°58'W., on true line, bet. secs. 5 and 6, (S $\frac{1}{2}$)
 Over mountainous land, thru thick timber & undergrowth.
 Asc. gradual S. slope.
 1.00 Spur, brs. E. Desc. 50 ft. over S. slope.
 12.00 Creek, 20 lks. wide, 5 ins. deep, course E.
 Asc. 28 ft. over N. slope.
 12.20 Spur, end from W. Desc. slight SE slope.
 14.10 Side wash, 10 lks. wide, course NE. Asc. 100 ft. over N. slope.
 24.20 Road, to Paradise Ranch, brs. E-W.
 30.22 Spur, brs. E. Desc. gradual S. slope. Along fence from NW-S.
 33.50 Wash, 10 lks. wide, course E. Asc. 27 ft. over N. slope.
 35.50 Spur, brs. E. Desc. gradual S. slope.
 37.00 Swale drains E. Asc. gradual N. slope.
 40.22 Spur, brs. E. Intersect the cor. of secs. 5, 6, 7 & 8.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, yellow pine, oak and juniper.
 Undergrowth, oakbrush, catclaw and saati.

Retracement of "CORNUCOPIA" patented lode mining claim; Min. Surv. No. 1572

Chains Cor. No. 1 of "Cornucopia" patented lode mining claim of Mineral Survey No. 1572, in the NE. 1/4 of Sec. 25, T. 13 N., R. 2 W., is a porphyry stone 10x12x14 ins. above ground, firmly set, marked C No. 1 1572 on E. face, and witnessed by a mound of stone N. and two oak bearing trees NE., each marked BT C No. 1 1572.

Thence
N. 8° 13' W., on random line, on SW. side line (1-2) of "Cornucopia" lode claim.

20.20 Fall 31 lks. N. 81° 47' E. from Cor. No. 2 of said claim, which is a granite stone 8x12x10 ins. above ground, firmly set, marked C No. 2 1572 on E. face, and witnessed by a mound of stone NW, 5 lks. dist. True course and dist. of SW. side line (1-2) of claim are therefore, N. 9° 6' W., 20.20 chs.

Thence
N. 75° 15' E., on random line, on NW. end line (2-3) of claim.

4.54 No trace of N. center end cor.
8.97 Fall 10 lks. S. 14° 45' E. from Cor. No. 3 of said claim, which is a porphyry stone 8x12x6 ins. above ground, firmly set, marked C No. 3 1572 on S. face, and witnessed by two oak bearing trees, one each SE. and SW. of cor., each marked BT C No. 3 1572. True course and dist. of NW. end line (2-3) of claim are therefore, N. 74° 38' E., 8.97 chs.

Thence
S. 8° 13' E., on random line, on NE. side line (3-4) of claim.

20.68 (Record dist.) Diligent search in this vicinity fails to reveal any trace of Cor. No. 4 of claim.

The NE. side line and the SE. end line of the claim are therefore assumed to be parallel and of same length as the SW. side line and NW. end line, respectively.

Retracement of
"Gold Trail" patented lode mining claim, Min. Surv. No. 1752.

Chains	<p>Cor. No. 1 of "Gold Trail" patented lode mining claim of Mineral Survey No. 1752, in SE. $\frac{1}{4}$ of Sec. 25, T. 13 N., R. 2 W., identical with Cor. No. 2 of "Contest" unpatented lode mining claim of Mineral Survey No. 1549, is a stone 4x4x10 ins. above ground, firmly set, marked GT No. 1 1752 on N. face, and C No. 2 1549 on S. face, and witnessed by a mound of stone W. of cor.</p>
22.16	<p>Thence N. $18^{\circ}10'$ E., on random line, on W. side line (5-1) of "Gold Trail" patented lode claim, Min. Surv. No. 1752. Fall 40 lks. S. $71^{\circ}50'$ E. from Cor. No. 5 of said claim, which is a granite stone 6x8x10 ins. above ground, firmly set, marked GT No. 5 1752 on S. face, and witnessed by a mound of stone W. of cor. True course and dist. of W. side line (5-1) of claim are therefore, S. $17^{\circ}8'$ W., 22.16 chs.</p>
4.54 8.55	<p>Thence N. $78^{\circ}45'$ E., on random line, on N. end line (4-5) of claim. No trace of N. end center cor. Intersect Cor. No. 4 of claim, which is a stone 7x9x12 ins. above ground, firmly set, marked GT No. 4 1752 on W. face, and witnessed by a mound of stone W. of cor. True course and dist. of N. end line (4-5) of claim are therefore, S. $78^{\circ}45'$ W., 8.55 chs.</p>

Chains

U.S.B.M. 1649, in Sec. 22.

From the cor. of secs. 22, 23, 26 and 27.

Thence, N.88°24'W., on traverse line.

6.98 Thence, N.2°E.,

3.71 Thence, N.47°W.,

4.13 Thence, N.19°W.,

1.33 Thence, N.4°20'W.,

6.68 Thence, N.9½°W.,

7.87 Thence, N.2°W.,

1.49 To USBM 1649 which is an iron post 4 ins. in diam., projecting 20 ins. above ground, with brass cap marked "U.S. Geological Survey" around rim and

Elevation	
Above	Sea
6149	Feet
Datum	Prescott

B.M.

U.S.B.M. 5548 in sec. 9.

From Cor. No.4 of the "Fraction" patented lode mining claim in sec. 9, thence, traverse to BM as follows:

N.7½°E., 7.20 chs.

N.16½°E., 5.07 "

N.3¼°W., 3.72 " to an iron post 4 ins. in diam., projecting 24 ins. above ground, with brass cap marked with "U.S. Geological Survey" around rim and

Elevation	
Above	Sea
5548	Feet
Datum	Prescott

B.M.

GENERAL DESCRIPTION.

Lands: The lands within this Tp. are mountainous in character, the main divide of the Bradshaw Mountains enters in sec. 25 and traversing the South central parts leaves thru sec. 19 on the West Bdy. To the North of this divide, the drainage via Bannon, and Granite Creeks principally, is towards the Agua Fria River, to the NE of this Tp. South of the divide, the drainage, principally via Groom, Wolf and Indian Creeks is into the Hassayampa Creek which has a brief course along the South Bdy. The elevation ranges from 5200 ft. about secs. 3 & 4, to 7600 ft., in the extreme Southeasterly part.

Soil: The prevailing soil is a stony 4th. rate, on the slopes and hill tops, while along the larger creeks, especially Bannon & Groom, there is to be found in places good loam 2nd. rate soil.

Timber: Yellow pine, oak, juniper and a few spruce are the predominating species. This growth of timber is prevalent throughout the entire township with the exception of secs. 2 and 3 which has a thinly scattered timber covering. Spruce is found only in the highest parts.

Undergrowth: Oakbrush covers, thickly, the Northeast corner of the Tp. and also the SW parts, and is the predominating brush growing over all parts. Manzanita is also growing thickly in the same SW. and NE. cors. and is especially thick along the N. half of the E. Bdy.

Mineral: Evidence of the existence of mineral is plentiful throughout the Tp., many cuts, winzes, shafts, tunnels and other mining improvements, most of which are in a present state of dilapidation, are found all thru the area surveyed. At present no mining on a large scale is being done, that industry being limited to a small amount of exploration and assessment work.

Water: Groom, Wolf and a creek in secs. 6 & 7 carry the only permanent water except the Hassayampa Creek. Bannon Creek has water for a ways then empties into the Prescott Reservoir and is dry the remainder of its length.

Settlement: City of Prescott lies partly in secs. 3, 4, and 5. Many summer cottages are built along Groom Creek, and Service stations and tourist camps and frequently found in the Tp. especially along the White Spar Hgy. The Mormon Church maintains a summer camp in sec. 26 and the Campfire Girls of Phoenix, Ariz. have a large camp in sec. 35. The Tp. as a whole is well populated, the tops of the highest peaks remaining untenanted.

Roads: The White Spar Highway, crosses the Tp. thru the western part; the Senator Highway, from Prescott to large mines in T. 12 N., R. 1 & 2 W. crosses thru the central part; there is a good cutoff road from the White Spar road to the Senator road crossing thru the southern part of the Tp.; The Copper Basin road cuts across the NW cor. of Tp. Numerous other roads render most of the Tp. accessible to auto travel. Many old roads lead from the higher regions towards Prescott, most of these being used in early days to haul logs from sawmills on Bannon & Groom Creeks to Ft. Whipple and Prescott town.

GENERAL DESCRIPTION (Cont.)

Trails: The principal trails in this Tp. consist of one along the main divide thru secs. 24 and 25, and then Northerly along a high ridge to sec. 1, thence out by the NE Tp. cor., and branch trail to Lynx Creek in T. 13 N., R. 1 W., in sec. 13.

Industry: The lands are fit chiefly for grazing and mining, and for recreational purposes.

FINAL FIELD TEST
of
Buff Transit No. 18,000
and
Young & Sons Transit No. 8540.

August 25, 1930; at station in sec. 9, T13N R2W Ariz., latitude 34° 31' N., longitude 112° 28½' W., examine the adjustments of the instrument and find no errors, then to test the solar apparatus proceed as follows:

At 9h. 26m., p.m., l.m.t., using Buff transit No. 18,000 observe Polaris at Eastern elongation, making four observations, two each with the telescope in direct and reversed positions and mark the mean point in the line thus determined by a tack set in top of a peg driven firmly in the ground about 5 chs. N.
Azimuth of Polaris at elongation = 1° 18' 5"

August 26: Lay off the azimuth of Polaris 1° 18' to the West, and mark the true meridian by a tack set in top of peg driven firmly in the ground about 5 chs. N.

At 9h. 00m., A.M., app.t., set off 34° 31' N., on lat. arcs, 10° 31½' N. on decl. arcs, and determine a meridian with each solar, both of which agree with the true meridian.

At 12h. 00m., app. noon, with lat. arcs unchanged observe the sun on the meridian; the resultant reading of the decl. arcs is 10° 29' N., which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app. t., with lat. arcs unchanged, set off 10° 26½' N. on the decl. arcs and determine a meridian with each solar, both of which I find agree with the true meridian.

As all of the observations taken during the usual hours of solar work agree within 1' of the true meridian, conclude that the adjustments of the instruments have been maintained during the surveys described in the foregoing notes.

September 29, 1930, at Phoenix, Arizona, during a.m. and p.m. hours, I make proper setting on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments, when compared with the meridian have a maximum error of less than 1' 30".

CERTIFICATE OF UNITED STATES SURVEYOR

I, Benjamin J. Kinsey, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 16th day of April, 1930, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instruc-

tions, and the laws of the United States, RETRACED all those parts or portions of the 3rd Std. Par. North in Range 2 West; Bdy. of Ft. Whipple Timber Reserve; Bdrs. of patented lode mining claims "Cornucopia" M.S.1572, and "Gold Trail" M.S.1752; Bdy. of Forest Homestead Entry Survey No.69; and Subdivision Lines of Township 13 North, Range 2 West;

and RESURVEYED all those parts or portions of 3rd Standard Parallel North in Range 2 West; East, West, and North Boundaries, and Subdivision Lines of Township 13 North, Range 2 West of the Gila and Salt

River Base and Meridian, in the State of Arizona, which are represented in and by diagram on page 2 hereof the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said retracement and survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such retracement and resurvey.

Place: Phoenix, Arizona. Date: July 27, 1932.

Benjamin J. Kinsey, U. S. Surveyor

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colo., NOV 18 1932, 193

The foregoing field notes of the RETRACEMENT of 3rd Std. Par. N. thru part of Range 2 West; Part of the Bdy. of Ft. Whipple Timber Reserve; Parts of the bdrs. of patented lode mining claims "Cornucopia" M.S.1572 and "Gold Trail" M.S.1752; part of the Bdy. of Forest Homestead Entry Survey No.69; and Part of the Subdivision Lines of T.13 N., R.2 W.; and of the RESURVEY of 3rd Standard Parallel North thru part of R.2 W.; the East, West and North Boundaries and Part of the Subdivision Lines of Township 13 North, Range 2 West, of the Gila and Salt River Base and Meridian, in the State of Arizona

executed by Benjamin J. Kinsey, U.S. Surveyor under his special instructions dated April 16, 1930 for Group 157 Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the retracements and resurveys they describe, are hereby approved.

U. S. Supervisor of Surveys

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys