

BOOK 3977

FIELD NOTES

OF THE

Retracement of part of the South Boundaries

of T. 10 N., Rs. 3 and 4 W., the survey of

subdivisional lines of T. 9 N., R. 3 W., and

retracement of mining claim boundaries in said

township of the

Of the Gila and Salt River Base and Meridian,

In the State of ARIZONA

EXECUTED BY

Dupree R. Averill

In the capacity of U. S. Surveyor, under Special Instructions dated October 6,

1931, issued by the District Cadastral Engineer to govern surveys included in Group

No. 171, which were approved by the Commissioner of the General Land

Office, Dec. 1, 1931, and Assignment Instructions dated Nov. 18, 1931

Survey commenced January 4, 1932

Survey completed February 10, 1932.

3977

3977

The subdivisional survey of township 9 north, range 3 west, was executed with a light mountain transit made by Buff and Buff, Serial No. 17992, constructed in accordance with the standard specifications of the General Land Office. The horizontal circle has a diameter of 4½ ins., with two double opposite verniers reading to single minutes; the vertical circle has a diameter of 4 ins., with one double vernier reading to single minutes. The instrument is equipped with the improved Smith solar attachment; radius of latitude arc 2½ ins., and of the declination arc 3½ ins., each with verniers reading to single minutes. The instrument was in good condition, and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, was approved by the district cadastral engineer on Nov., 28, 1931. I examine all instrumental adjustments before making the field tests hereinafter recorded.

The directions of all lines were determined by the solar transit method, supplemented by direct observations upon the sun for azimuth. The measurements were made with a Lallie steel tape, 5 chs. in length, graduated every link for the first 100 lks., and the balance at intervals of 10 lks. The tape was tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by two clinometers in good adjustment; the horizontal equivalents are entered in the field note record.

The data furnished with the special instructions gives the geographic position for the SE. cor., of T.9 N., R.3 W., as follows: latitude 34°04'04"N., and longitude 112°31'02"W.

January 3, 1932, at camp near the center of the NE ¼ of NW ¼ of SE ¼ of sec. 21, T.9 N., R.3 W., at 5h.35m.30s. p.m., by my watch which reads correct standard 105th. meridian time, I make an observation on Polaris, four sights each with the telescope in direct and reversed positions, reading vertical angles, and the horizontal deflection angle to a sharply defined point upon the apex of Wades Butte, to the west, about 3½ miles distant.

Mean horizontal angle. Polaris to mark	11° 57' 45"
Mean observed vertical angle	35° 00' 30"
Azimuth of Polaris	0° 33' 36"
True bearing to mark	N. 11° 24' 10" W
Reduced latitude	34° 06' 12" N

Every hour from 8 to 11 a.m. and from 1 to 4 p.m., I make proper settings on the arcs of the solar attachment and ascertain that the resulting orientation of the instrument, when compared with the meridian established by Polaris observation, has a maximum error of less than 1' 30".

I repeat the tests of the arcs daily by noon observation, and verify the meridional indications at frequent intervals throughout the survey.

chains

The second standard parallel north was resurveyed by Kinsey in 1930. who also surveyed the west boundary in 1929. The south boundary of T.10 N., R.3 W. was surveyed by Sawyer and Cook in 1925. The east boundary was surveyed by Davis in 1919.

I commence the subdivisional survey at the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., 30 ins. above ground, supported in a mound of stone to top, properly mkd. on brass cap.

N.0°01'W. bet. secs. 35 and 36.

Over rolling mountainous land, through moderate undergrowth.

Desc. 90 ft. over NW. slope.

- 7.40 Draw, course N.30°E.; asc. 85 ft. over SE. slope.
- 12.70 Spur, slopes N.80°E.; desc. 145 ft. over broken NE. slope.
- 16.00 Gulch, course N.60°E.
- 28.10 Small draw, course E.; asc. SE. slope 115 ft.
- 35.50 Along E. slope, desc. 70 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- S 35 | S 36
1932
- of stone 3 ft. base, 2 ft. high, W. of cor. raise a mound
- 44.00 Spur, slopes NE.; desc. NW. slope 130 ft.
- 49.00 Hawk Spring Gulch, wash 40 lks. wide, course S.70°W.
Asc. 125 ft. over SE. slope.
- 53.00 High point of spur, from saddle to the E., slopes steeply SW and W.
Desc. 200 ft. over N. slope.
- 59.10 Draw, course N.60°W. flowing a small stream of water.
Asc. 55 ft.
- 61.50 Point of spur, slopes W.; desc. 50 ft. over NW. slope.
- 62.70 Draw, course W., flowing a small stream of water.
Asc. rolling SE. slope 150 ft.
- 72.90 Gully, course SE.
- 77.80 Along E. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam. 28 ins. in the ground, for the cor. of secs. 25, 26, 35 and 36, with

chains

brass cap mkd.

T9N R3W	
S 26	S 25
S 35	S 36

1932

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, rolling and broken mountains. Soil, rocky, 3rd. rate. No timber; undergrowth, oak, mahogany, catclaw, grease-wood, mesquite and cacti.

East on a random line bet. secs. 25 and 36.

- 40.00 Set temp. 1/4 sec. cor.
- 79.96 Intersect E. bdy. of Tp. 16 lks. S. of the cor. of secs. 25, 30, 31 and 36, an iron post 2 ins. diam. supported in a mound of stone to top, properly mkd. on brass cap.
- Thence
- S. 89° 53' W. on true line bet. secs. 25 and 36.
- Over mountainous land, through scattered undergrowth.
- Desc. 20 ft. over W. slope.
- 1.75 Small draw, course N.; asc. 140 ft. over E. slope.
- 4.35 Gully, course N. 50° E.
- 14.00 Ridge, bears N. and S.; desc. 280 ft. over SW. slope.
- 33.15 Draw, course N. 70° W.; asc. 110 ft. over NE. slope.
- 39.98 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 25
S 36

1932

- 40.80 Spur, slopes N. 70° W.; desc. 250 ft. over SW. slope.
- 56.30 Draw, course N. 70° W.; along brushy N. slope.
- 60.00 Point of spur, slopes NW.; desc. 45 ft.
- 62.15 Gully, course N.; asc. 55 ft.
- 66.00 Small spur, slopes N. 20° E.
- Small wire corral bears S. about 2.50 chs. dist.
- Desc. 25 ft.
- 68.25 Gully, course N.; asc. 45 ft.
- 73.30 Low ridge, bears N. and S.; desc. SW. slope 65 ft.
- 78.55 Gully, course S. 10° E.; asc. 30 ft. over E. slope.

SUBDIVISION OF T.9 N., R.3 W.

chains

79.96 The cor. of secs. 25,26,35 and 36.

Land, rolling mountains.
Soil, rocky, 3rd. rate.
No timber; undergrowth, scattered oak, mahogany, catclaw
greasewood and cacti.

N.0°01'W. bet.secs. 25 and 26.

Over rolling mountains, through scattered undergrowth.

0.50 Gully, course SE.; asc. 140 ft. over S. slope.

7.20 Low ridge, bears N.30°E. and S.30°W.; along W. slope.

9.30 Gully, course W.


16.40 Ridge, bears NW. and SE.; desc. 140 ft. over NE. slope.

25.80 Gulch, course N.60°E.;

34.80 Draw, course N.75°E.; asc. 100 ft. over SE. slope.

39.40 Spur, slopes E.

40.00 Set an iron post, 3 ft. long, 1 in. diam. .28 ins. in the
ground, for 1/4 sec. cor. with brass cap mkd.



raise a mound
of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

Desc. 160 ft. over NE. slope.

50.50 Draw, course N.60°E.; asc. 100 ft. over SE. slope.

57.00 Spur, slopes N.30°E.; desc. NW. slope 100 ft.


62.70 Draw, course NE. ;asc. 30 ft.

67.20 Small spur, slopes N.60°E.; desc. 70 ft. over NE. slope.

74.60 Small draw, course NW.

79.80 Gully, course N.80°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam. .26 ins. in the
ground, for the cor. of secs. 23,24,25 and 26, with
brass cap mkd.



raise a mound
of stone 4 ft. base, 2 ft. high, W. of cor.

Land, rolling mountains.
Soil, rocky, 3rd. and 2nd. rate.
No timber; undergrowth, greasewood, oak, catclaw and
cacti.

SUBDIVISION OF T.9 N., R.3 W.

chains

N.89°53'E. on a random line bet.secs. 24 and 25.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 Intersect E. bdy. of Tp. 12 lks. S. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, 2 ins. diam., 18 ins. above ground, properly mkd. on brass cap.

Raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, about post.

U.S.L.M. No.1259, which is a granite stone 18 x 10 x 10 ins., mkd. with a cross (X) on top, USLM No1259 BRMD on the N. face, and set in the apex of a cairn of stone 4 ft. base, 3 ft. high, bears S.14°30'W..5.52 chs. dist.

Thence from cor.

S.89°48'W. on true line bet.secs. 24 and 25.

Over mountainous land, through scattered undergrowth.

Along N. slope.

1.25 Intersect north side line of Silver King mining claim. Survey No.1259. N.57°10'W. 5.45 chs. dist., from cor. No.4. Enter patented land.

5.00 Change of slope to NW.; desc. 35 ft.

9.00 Sharp rocky spur, slopes N.60°W.; desc. 170 ft. over SW. slope.

15.30 Draw, Crown Point Gulch, dry wash 30 lks. wide, course N.40°W.; asc. broken NE. slope 300 ft.

17.43 Intersect south side line of Silver King mining claim. Survey No.1259. S.57°57'E. 1.70 chs. dist., from cor. No.2. Leave patented land.

20.40 Gulch, course N.50°E.

32.50 Ridge spur, slopes N.10°W.; desc. 180 ft. over W. slope.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$

1932

raise a mound

of stone 3 ft. base, 2 ft. high, N. of cor.

Continue descent 440 ft.

43.50 Gulch, from S.70°E., course W.

51.30 Leave gulch, course S.70°W.

56.30 Same gulch, course NW.

63.20 Same gulch, course SW.

65.20 Draw, from S., at mouth of gulch, course N.60°W.

69.90 Wash, 40 lks. wide, course N.10°W.; asc. rolling E. slope 50 ft.

72.00 Cabin, bears N.10°E. about 6 chs. dist.

SUBDIVISION OF T.9 N., R.3 W.

chains

75.05 Wash, 20 lks. wide, course N.30°E.

79.40 Gully, course N.70°E.

79.98 The cor. of secs. 23,24,25 and 26.

Land, mountainous.
Soil, rocky, 3rd. rate.
No timber; undergrowth, scattered oak, greasewood, cacti and catclaw.

N.0°01'W. bet.secs. 23 and 24.

Over mountainous land, through scattered undergrowth.

Asc. 30 ft.


4.30 Small spur, slopes E.; desc. 60 ft. over NE. slope.

8.40 Draw, course E.; asc. 60 ft. over SE. slope.

12.50 Change of slope to E.

18.50 Change of slope to NE., desc. 260 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.



raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

41.90 Draw, wash 60 lks. wide, water in pools, course N.70°W.
Asc. bluff bank 30 ft.

43.00 Over rolling land, asc. 150 ft.


50.50 Gulch, 30 ft. deep, course W.

62.50 Small spur, slopes W.; desc. along NW. slope 130 ft.

68.40 Gully, course N.80°W.

79.30 Wash. 20 lks. wide, course SW.; asc. 20 ft.

80.00 Set an iron post, 3 ft. long; 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 13,14,23 and 24, with brass cap mkd.



raise a mound of stone 3 ft. base, 1 1/2 ft. high, W. of cor.


Land, rolling mountains.
Soil, rocky, 3rd. rate.
No timber; undergrowth, greasewood, catclaw, cacti and scrub oak.

chains	N.89°48'E on a random line bet.secs. 13 and 24.
40.00	Set temp. 1/4 sec. cor.
79.98	Intersect E. bdy. of Tp. 20 lks. S. of the cor. of secs. 13,18,19 and 24, which is an iron post, 2 ins. diam. 20 ins. above ground, supported in a mound of stone to top, properly mkd. on brass cap.
	Thence
	S.89°39'W. on true line bet.secs. 13 and 24.
	Over mountainous land, through scattered undergrowth.
	Desc. 30 ft. over W. slope.
1.30	Head of draw, course SW.; asc. 20 ft.
12.40	Small spur, slopes S.30°W.; desc. 140 ft. over W. slope.
17.00	Gully, course SW.; along S. slope.
25.60	Spur, slopes S.30°W.; desc. 230 ft. over W. slope.
28.20	Gulch, course SW.; change of slope to SW.
36.60	Small spur; slopes SW.
39.99	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S-13}{S-24}$
	1932
	raise a mound
	of stone 3 ft. base, 2 ft. high, N. of cor.
	Desc. 30 ft.
41.90	Gulch. course SW.; desc. 30 ft. along S. slope.
48.00	Spur, slopes S.60°W.; desc. 100 ft. over W. slope.
53.00	Gulch, course NW.; along N. slope, through dense brush.
57.00	Desc. 160 ft. over NW. slope.
69.30	Wash, 40 lks. wide, course S.60°W.; asc. bluff bank 20 ft.
73.00	Desc. gradual SW. slope, through scattered undergrowth, 60 ft.
79.98	The cor. of secs. 13,14,23 and 24.
	Land, rolling mountains. Soil, rocky, 3rd. rate. No timber; undergrowth, greasewood, scrub oak, catclaw and cacti.

	N.0°01'W. bet.secs. 13 and 14.
	Over rolling mountainous land, through scattered timber and undergrowth.
	Asc. 210 ft. over S. slope.


chains

- 7.70 E. slope of flat elongated lava butte, extending N.70°W. low connecting spur bears E.
Desc. 180 ft. over NE. slope.
- 16.60 Wash, 25 lks. wide, course W.; asc. 200 ft. over broken SW. slope.
- 30.80 Wash, 20 lks. wide, course S.70°W.
- 35.20 Gully, course SW.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

- 41.70 Low divide, extends W. from point of spur, NE.; desc. 170 ft. over NW. slope.
- 49.60 Draw, course W.; asc. 450 ft. over S. slope.
- 66.80 Shoulder of spur, slopes steeply SW.; along NW. slope, desc. 180 ft.
- 77.40 Small spur, slopes N.80°W., continue descent.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 11, 12, 13 and 14, with brass cap mkd.



Land, rolling mountains.
 Soil, rocky, 3rd. rate.
 Timber, scattered paloverde; undergrowth, greasewood, cacti, catclaw, scrub oak and mahogany.

N.89°39'E on a random line bet. secs. 12 and 13.

- 40.00 Set temp. 1/4 sec. cor.
- 79.96 Intersect E. bdy. of Tp. 27 lks. N. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, 2 ins. diam., 20 ins. above ground, and in a mound of stone, properly mkd on brass cap.

Thence

S.89°51'W. on true line bet. secs. 12 and 13.

Over rough mountainous land, through moderate undergrowth.

Desc. 940 ft. over W. slope, along crest of small spur.

chains

- 26.50 Draw, course N.60°W.; continue descent along NW. slope.
- 36.25 Gully, course N.; asc. 80 ft. over NE. slope.
- 39.98 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 12 \\ S 13 \end{array}$$

1932

Asc. 80 ft.

- 43.20 Sharp spur, slopes NW.; desc. 370 ft. over W. slope.
- 49.50 Draw, course N.70°W., change of slope to NW.
- 52.30 Draw, course N.40°W.; asc. 130 ft. over NE. slope.
- 58.50 Spur, slopes NW.; desc. 260 ft. over W. slope.
- 66.15 Draw, course NW.; asc. 200 ft. over NE. slope.
- 78.75 Spur, slopes N.; desc. 20 ft.
- 79.96 The cor. of secs. 11, 12, 13 and 14.

Land, broken mountains.
 Soil, rocky, 3rd. and 4th. rate.
 No timber; undergrowth; mahogany, oak, catclaw and cacti.

N.0°01'W. bet. secs. 11 and 12.

Over mountainous land, through scattered undergrowth.
 Desc. 480 ft. over NW. slope.

- 9.00 Change of slope to N., small spur, slopes N.
- 18.10 Draw, near mouth, course NW.; asc. 65 ft.
- 23.00 Bluff point of spur, from E.; desc. 100 ft.
- 26.50 Mouth of draw, from E., enter river bottom in rocky canyon.
- 27.30 Enter Hassayampa River, 50 lks. wide, 8 ins. deep, course SW.
- 40.00 True point for 1/4 sec. cor. falls in river.
- 41.30 Leave river, at foot of rocky bluffs; asc. 45 ft. over SW. slope.
- 43.00 Set an iron post, 3 ft. long, 1 in. diam., on point of broken bluff bank of river, 18 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone to top, for witness 1/4 sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 11 \\ | \\ S 12 \end{array}$$

WC
1932

SUBDIVISION OF T.9 N., R.3 W.

chains

- Asc. rolling and broken SW. slope 210 ft.
- 43.30 Gulch, course W.
- 62.20 Spur, slopes W.; desc. NW. slope 225 ft.
- 71.40 Enter Hassayampa River, course W. for about 4 chs., thence S.
- 73.00 Leave river; asc. S. slope 90 ft.
- 73.70 Sharp spur extends E. about 10 chs.; desc. N. slope 80 ft.
- 75.00 Enter river bed.
- 78.90 Leave river, 50 lks. wide, 8 ins. deep, course E.; asc. S. slope 45 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., over **CROSS** (X) on shelf of surface rock, supported in a mound of stone 6 ft. base, 3 ft. high, for the cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

T9N R3W

S 2	S 1
S 11	S 12

 1932

Land, mountainous.
 Soil, rocky, 3rd. and 4th. rate.
 No timber; undergrowth, greasewood, mahogany, catclaw, cacti, lilac, laurel.

 N.89°51'E. on a random line bet.secs. 1 and 12.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.94 Intersect E. bdy. of Tp. 12 lks. S. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, 2 ins. diam., supported in a stone chinked crevice in granite boulders, properly mkd. on brass cap.

Thence

S.89°46'W. on true line bet.secs. 1 and 12.

Over broken mountainous land, through scattered undergrowth.

Desc. 340 ft. over SW. slope.

- 19.50 Draw, course NW.; asc. 40 ft.
- 24.00 Flat spur, slopes N.; desc. 100 ft. over NW. slope.
- 29.80 Draw, course N.; asc. gradually, 60 ft.
- 35.60 Gully, course N.
- 39.97 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 1	S 12
-----	------

 1932.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

40.25 Small spur, slopes NE.

43.60 Shoulder of spur, slopes steeply to NW.; desc. 790 ft. over precipitous SW. slope.

72.40 Enter Hassayampa river at foot of bluff slope, course SE., along N. margin of river, at foot of low bluffs.

75.75 Leave river; asc. 45 ft.

79.94 The cor. of secs. 1, 2, 11 and 12.

Land, mountainous.
Soil, rocky, 3rd. and 4th. rate.
No timber; undergrowth, greasewood, oak, mahogany, cacti and catclaw.

N.0°01'W. on true line bet. secs. 1 and 2.

Over broken land, through scattered undergrowth.

Asc. 150 ft. over S. slope.

12.75 Small sharp spur, slopes SW.; desc. 160 ft. over NW. slope.

17.80 Enter Hassayampa River. course S.20°W.

22.90 Leave river; asc. 150 ft. over SE. slope.

37.00 Spur, slopes E.; desc. 40 ft. over N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam. .28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S \ 2 \ | \ S \ 1 \\ | \\ 1932 \end{array}$$

raise a mound

of stone 3 ft. base, 2 ft. high, W. of cor.

Desc. 65 ft.

46.90 Enter Hassayampa River, course S.70°E.

49.20 Leave river.; asc. 155 ft. over S. slope.

53.90 Sharp rocky spur, slopes W., sharp conical peak bears W. about 3 chs. dist.

Desc. NW. slope 145 ft.

56.80 Enter Hassayampa River, course SW.

59.70 Leave river; asc. 100 ft. over SE. slope.

71.10 Point of spur, slopes E.; along E. slope.

73.10 Desc. over vertical bluff 80 ft. high, to canyon bed.

78.83 Set an iron post, 3 ft. long, 2 ins. diam. in ledge of river boulders, against cross (X) on rock; and in a mound of stone to top, for witness cor. to true point for closing cor. of secs. 1 and 2, with brass cap mkd.

SUBDIVISION OF T.9 N., R.3 W.

chains

T10N R3W
 S 36
 S 2 | S 1
 T9N R3W
 WO
 CC
 1932

80.23 Intersect N. bdy. of Tp.; true point for closing cor. of secs. 1 and 2.

From point of intersection the witness cor. established 16 lks. E. of true point for cor of secs. 35 and 36, T.10N., R.3 W., bears W. 7.42 chs. dist.; an iron post, 2 ins. diam., 12 ins. above ground, mkd. and witnessed as described in the official record.

Land, broken mountainous.
 Soil, rocky, 3rd. and 4th. rate.
 No timber; undergrowth, scrub oak, catclaw, cacti, mesquite and greasewood.

 From the standard cor. of secs. 34 and 35, on S. bdy. of Tp. which is an iron post, 2 ins. diam., 14 ins. above ground, mkd. and witnessed as described in the official record.

N.0°01'W. bet. secs. 34 and 35.

Over rolling mountainous land, through scattered undergrowth.

Desc. NE. slope 80 ft.

2.00 End of old road, from Constellation, bears S.20°E.

3.70 Intersect line 5-6, Survey No.1553, Bellairs lode, S.25°57'E., 1.66 chs. dist. from cor. No.5. Enter patented land.

4.60 Draw, 30 lks. wide, from SE., course NE.; asc. SE. slope 95 ft.

5.615 Intersect line 4-5, Survey No.1553 Bellairs lode. N.60°00'E. 0.84 chs. dist., from cor. No.5. Leave patented land.

9.25 Spur, slopes E.; desc. N. slope 70 ft.

10.95 Intersect line 1-2, Survey No.1531, Curley lode. S.51°50'E. 13.87 chs. dist., from cor. No.2. Enter patented land.

11.80 Draw, course N.50°E.; asc. 25 ft.

15.00 Spur, slopes N.75°E.; desc. NE. slope 75 ft.

17.65 Draw, course E.; asc. 65 ft. over S. slope.

19.50 Spur, slopes E.; desc. 85 ft. over NE. slope.

20.525 Intersect line 4-5, Survey No.1531, Curley lode, N.43°55'W. 2.04 chs. dist., from cor. No.5. Leave patented land.

23.345 Intersect line 1-2, Survey No. 1531, Keystone lode. S.19°08'E. 0.475 chs. dist. from cor. No.2. Enter patented land.

23.40 Draw, course S.80°E.; asc. 175 ft. over S. slope.

23.84 Intersect line 2-3, Survey No.1531, Keystone lode. N.60°00'E. 0.165 chs. dist. from cor. No.2. Leave patented land.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

30.60 Spur, slopes E.; desc. along NE. slope 110 ft.

33.50 Head of gully, course E.

35.50 Spur, extends NE.; change of slope to W. and NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 34\ | \ S\ 35 \\ | \\ 1932 \end{array}$$

raise a mound
of stone 3 ft. base, 2 ft. high, W. of cor.

Desc. 125 ft. over NW. slope.

46.25 Draw, course N.30°E.; along E. slope.

48.60 Point of rocky spur, slopes E.; desc. N. slope 100 ft.

50.85 Draw, course E.; asc. S. slope 100 ft.

53.40 Spur, slopes N.80°E.; desc. 85 ft. over N. slope.

56.80 Draw, course N.50°E.; along SE. slope, asc. 20 ft.

60;25 Spur, slopes N.50°E.; desc. 100 ft. over NE. slope.

64.00 Drain, course NE.; along E. slope.

68.00 Spur, slopes N.30°E.; desc. 70 ft. over NW. slope.

74.00 Small draw, course N.20°E.; change of slope to NE, desc. 110 ft.

79.85 Drain, course E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

$$\begin{array}{c} T9N\ R3W \\ S\ 27\ | \ S\ 26 \\ S\ 34\ | \ S\ 35 \\ | \\ 1932 \end{array}$$

Land, rolling mountains.
Soil, rocky, 3rd. rate.
No timber; undergrowth, scrub oak, mahogany, catclaw, cacti and greasewood.

East on a random line bet. secs. 26 and 35.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.10 Intersect the cor. of secs. 25, 26, 35 and 36.

Thence

West on true line bet. secs. 26 and 35.

Over mountainous land, through scattered undergrowth.

SUBDIVISION OF T.9 N., R.3 W.

chains

- Asc. 95 ft. over E. slope.
- 5.00 Change of slope to S.
- 11.00 Low ridge, bears NE. and SW.; desc. 70 ft. over NW. slope.
- 17.25 Head of draw, course N.; asc. 50 ft. over NE. slope.
- 20.80 Shoulder of ridge, spur slopes NW.; desc. SW. slope 350 ft.
- 31.20 Enter Hawk Spring Gulch, wash 50 lks. wide, flowing a small stream of water, course W. from SE.
- 36.25 Leave canyon, course NW.; asc. 90 ft. over NE. slope.
- 39.50 Small spur, slopes N.; desc. 70 ft.
- 40.05 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\begin{array}{r} \frac{1}{4} S 26 \\ \frac{1}{4} S 35 \end{array}$$
 1932
- raise a mound
- of stone 3 ft. base, 2 ft. high, N. of cor.
- 40.40 Small draw, course N.; asc. 140 ft. over broken NE. slope.
- 52.50 Change of slope to N.
- 59.20 Spur, slopes NW.; desc. 270 ft. over SW. slope.
- 71.75 Wash, 50 lks. wide, course NW.; asc. 50 ft.
- 76.00 Point of low spur, slopes N.30°E.; desc. 30 ft.
- 78.90 Small draw, course N.30°E.; asc. 30 ft.
- 80.10 The cor. of secs. 26, 27, 34 and 35.
- Land, mountainous.
Soil, rocky, 3rd. rate.
Timber, cottonwood and willow along watercourse; undergrowth, greasewood, oak, mahogany, catclaw and cacti.
-
- N.0°01'W. bet. secs. 26 and 27.
- Over rolling mountains, through scattered undergrowth.
Asc. 35 ft. over SE. slope.
- 2.70 Flat spur, slopes N.70°E.; desc. 100 ft. over NE. slope.
- 12.40 Small draw, course N.80°E.; asc. 40 ft.
- 15.30 Point of spur, slopes E.; desc. 110 ft. over NE. slope.
- 22.40 Amazon Gulch, wash 60 lks. wide, course W.; asc. 90 ft. over SW. slope.
- 31.00 Point of spur, sloping W.; desc. 130 ft. over NW. slope.
- 34.80 Enter Amazon Gulch, 60 lks. wide, course N.25°E.
- 37.90 Leave wash, course N.60°W.; asc. 20 ft.
- 39.30 Mouth of draw, from E., 10 lks. wide, 8 ft. deep.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

- chains
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$

S 27	S 26
1932	
- Asc. 215 ft. over S. slope.
 - 48.50 Spur, slopes S.40°W.; asc. 80 ft. over SW. slope.
 - 57.20 Spur, slopes W.; desc. 110 ft. over N. slope.
 - 62.20 Draw, course S.70°W.; asc. 240 ft. over SW. slope.
 - 70.60 Spur, slopes W.; desc. 140 ft. over NW. slope.
 - 77.90 Draw, course S.70°W.; asc. S. slope 70 ft.
 - 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, for the cor. of secs. 22, 23, 26 and 27, with brass cap mkd.
- | | |
|---------|------|
| T9N R3W | |
| S 22 | S 23 |
| S 27 | S 26 |
| 1932 | |
- raise a mound
 - of stone 3 ft. base, 2 ft. high W. of cor.
- Land, rolling mountains.
 Soil, rocky, 3rd. rate.
 Timber; cottonwood in canyon bottom, scattered paloverde along the hillsides; undergrowth, greasewood, catclaw, mahogany and paloverde.
-
- East on a random line bet. secs. 23 and 26.
 - 40.00 Set temp. $\frac{1}{4}$ sec. cor.,
 - 80.06 Intersect the cor. of secs. 23, 24, 25 and 26.
 - Thence
 - West on true line bet. secs. 23 and 26.
 - Over mountainous land, through scattered undergrowth.
 - Asc. 190 ft. over E. slope.
 - 3.35 Drain, course SE.
 - 10.30 Spur, slopes N.60°E.; along NE. slope.
 - 13.50 Same spur, slopes SE.; desc. SW. slope 50 ft.
 - 18.15 Small draw, course SE.; asc. E. slope 110 ft.
 - 22.75 Low spur, slopes NE.; continue ascent.
 - 27.35 Old road, abandoned, bears N.20°W. and S.20°E.
 - 29.25 Same old road, bears N.70°W. and NE.

SUBDIVISION OF T.9 N., R.3 W.

chains

35.50 Low ridge, bears N.20°W. and S.20°E.; desc. gradual SW. slope 90 ft.

38.00 Drain, course S.30°W.

40.03 Set an iron post, 3 ft. long, 1 in. diam. .16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 23 / S 26

1932

42.85 Small draw, course SE.; asc. 90 ft. over E. slope.

50.00 Low divide, bears N.20°W. and S.; desc. 20 ft.

54.35 Drain, course N.30°W.; asc. over increasing E. slope. 160 ft.

64.00 Short ridge, bears N. and S.; desc. over SW. slope 285 ft.

74.50 Draw, course S.60°W.; along S. slope.

80.06 The cor. of secs. 22, 23, 26 and 27.

Land, rolling mountains.
Soil, rocky, 3rd. rate.
No timber; undergrowth, greasewood, scrub oak, catclaw and cacti.

N.0°01'W. bet. secs. 22 and 23.

Over mountainous land, through scattered undergrowth.
Asc. 85 ft. over S. slope.

3.40 Spur, slopes S.70°W.; desc. 45 ft.

5.40 Draw, course S.70°W.; asc. 100 ft. over SW. slope.

14.00 Short spur, slopes W.; desc. 250 ft. over NW. slope.

19.20 Abandoned road, bears E. and W.; change of slope to N.

25.90 Draw, course SW.; asc. 330 ft. over S. slope.

35.00 Change of slope to SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam. .6 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4

S 22 | S 23

1932

42.60 Small draw, course S.20°E.; change of slope to SW.

52.25 Ridge, bears N.60°W. and SE.; desc. 40 ft. over NE. slope.

59.20 Flat spur, slopes NE.; desc. N. slope 260 ft.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

- 68.60 Draw, course N.50°E.; asc. 50 ft. over SE. slope.
- 73.60 Spur, slopes E.; desc. 215 ft. over NW. slope.
- 79.90 Gulch, course N.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., over cross (X) on surface rock, supported in a mound of stone 6 ft. base. 3 ft. high, for the cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

T9N R3W	
S 15	S 14
S 22	S 23

1932

Land, mountainous.
 Soil, rocky, 3rd. rate.
 Timber, scattered paloverde; undergrowth, greasewood, catclaw, cacti and mahogany.

East on a random line bet. secs. 14 and 23.

- 40.00 Set temp. 1/4 sec. cor.
- 80.08 Intersect N. and S. line 5 lks. N. of the cor. of secs. 13, 14, 23 and 24.

Thence

N.89°58'W. on true line bet. secs. 14 and 23.

Over broken and mountainous land. through scattered undergrowth.

Asc. 75 ft. over SE. slope.

- 6.75 Short spur, slopes S.; desc. 235 ft. over SW. slope.
- 23.00 Wash, 80 lks. wide, in box canyon 50 ft. deep, course N.20°W.; asc. 275 ft. over NE. slope.
- 37.70 Sharp lava spur, extends NW.; desc. 80 ft.
- 40.04 Set an iron post, 3 ft. long, 1 in. diam. 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 14
1/4 S 23

1932

Desc. 200 ft. over SW. slope.

- 44.50 Draw, wash 50 lks. wide, course N.20°W.; asc. 200 ft. over NE. slope.
- 58.00 Spur, slopes N.; desc. NW. slope 90 ft.
- 61.40 Small draw, course N.10°E.; asc. 60 ft.
- 64.00 Spur, slopes N.20°E.; desc. 25 ft.
- 65.40 Draw, course NE.; asc. 130 ft. over E. slope.

SUBDIVISION OF T.9 N., R.3 W.

chains


- 70.20 Spur, slopes N.; desc. 90 ft. over NW. slope.
- 73.00 Draw, course N.20°W.; asc. 50 ft.
- 77.50 Spur, slopes NE.; desc. 45 ft. over NW. slope.
- 80.00 Gulch, course N.
- 80.08 The cor. of secs. 14, 15, 22 and 23.
- Land mountainous.
Soil, rocky, 3rd. rate.
No timber; undergrowth, greasewood, cacti and catclaw.
-
- N.0°01'W. bet. secs. 14 and 15.
- Over mountainous land, through scattered undergrowth.
Desc. 60 ft. along gulch, course N.
- 2.80 Draw, course N.60°W.; asc. 50 ft. over SW. slope.
- 5.00 Short spur, slopes NW.; desc. 120 ft.
- 8.70 Small draw, course N.60°W.; asc. 10 ft.
- 12.10 Point of spur, slopes NW.; desc. N. slope 200 ft.
- 21.60 Enter Hassayampa River, at foot of sloping bluff, stream
50 lks. wide, 6 ins. deep, course W.
- 24.50 Leave river bed; asc. bluff bank 90 ft.
- 26.80 Bluff point of flat spur, from NW.; desc. 60 ft.
- 32.50 Wash, 35 lks. wide, course S.30°E.; asc. 55 ft.
- 35.00 Flat spur, sloping SW.; desc. 45 ft.
- 37.60 Same wash, course SW.; asc. 45 ft.
- 39.70 Small gravel spur, slopes E. desc. 10 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
ground, to rock, with marked (X) stone deposited
alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec.
cor., with brass cap mkd.
- $\frac{1}{4}$
 S 15 S 14
 1932
- Desc. 15 ft.
- 40.50 Same wash, 30 lks. wide, course SE.; asc. 485 ft. over
broken S. slope.
- 55.80 Gully, course S.70°W.
- 57.40 Gully, course S.10°W.
- 66.40 Spur, slopes S.70°W.; desc. 70 ft. over NW. slope.
- 69.10 Head of draw, course S.70°W.; asc. 260 ft. over SW.
slope.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

- 76.50 Gully, course S.30°W.; change of slope to S.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam.. 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 10, 11, 14 and 15, with brass cap mkd.



Land, mountainous.
 Soil, rocky, 3rd. rate.
 No timber; undergrowth, greasewood, cacti, catclaw and paloverde.

 S.89°58'E. on a random line bet. secs. 11 and 14.


- 40.00 Set temp. 1/4 sec. cor.
- 80.14 Intersect N. and S. line 10 lks. S. of the cor. of secs. 11, 12, 13 and 14.

Thence

S.89°58'W. on true line bet. secs. 11 and 14.

Over rough mountains, through scattered undergrowth.
 Desc. 160 ft. over NW. slope.

- 9.50 Flat spur, slopes steeply NW.; desc. W. slope 350 ft.
- 21.40 Enter Hassayampa River at foot of precipitous bluff, stream 40 lks. wide, 5 ins. deep, course S.20°W.
- 24.30 Leave river bed; asc. 500 ft. over E. slope.
- 38.65 Sharp rocky spur, slopes SE.; desc. 10 ft.
- 40.07 True point for 1/4 sec. cor. falls upon sloping granite ledge.
- 40.17 Set an iron post, 3 ft. long, 1 in. diam.. 6 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone to top, for witness 1/4 sec. cor., with brass cap mkd.



Desc., over rocky SW. slope. 130 ft.

- 52.50 Draw, course SE.; asc. E. slope 620 ft.
- 63.60 Spur, slopes SE.; change of slope to SE., continue ascent.
- 66.50 Spur, slopes S.
- 69.20 Spur, slopes S.10°W.; desc. 250 ft. over W. slope.
- 78.45 Gully, course S.30°W.; along S. slope.

SUBDIVISION OF T.9 N., R.3 W.

chains

80.14

The cor. of secs. 10, 11, 14 and 15.

Land, rough mountains.
Soil, rocky, 3rd. and 4th. rate.
No timber; undergrowth, greasewood, scruboak and cacti.

N.0°01'W. bet. secs. 10 and 11.

Over mountainous land, through scattered undergrowth.

Asc. S. slope 110 ft.

1.60 Small sharp rock peak, on spur, sloping SW.; asc. 390 ft. over SW. slope.

18.20 Shallow draw, course S.20°W.; change of slope to SE.


29.70 Ridge, sloping S.60°E., bears N.60°W. to peak about 7 chs. dist.

Desc. broken NE. slope 120 ft.

34.00 Head of gulch, course E.

37.00 Spur, slopes N.75°E.; desc. 95 ft. over brushy NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam. .30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.,

Desc. 250 ft.


46.40 Draw, course E.; asc. 150 ft. over SE. slope through very scattered undergrowth.

55.00 Point of rocky spur, slopes E.; desc. 100 ft. over NE. slope.

64.60 Draw, course SE.; asc. 530 ft. over S. slope.

77.50 Short steep spur, slopes SE.; along E. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam. .16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 2, 3, 10 and 11, with brass cap mkd.



Land, mountainous.
Soil, rocky, 3rd. and 4th. rate.
No timber; undergrowth, greasewood, oak, mahogany, cacti and catclaw.

SUBDIVISION OF T.9 N., R.3 W.

chains

N.89°58'E. on a random line bet.secs. 2 and 11.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.06 Intersect N. and S. line 12 lks. S. of the cor. of secs. 1,2,11 and 12.

Thence

S.89°53'W. on true line bet.secs. 2 and 11.

Over rough mountainous land, through scattered undergrowth.

Desc. 40 ft.

1.85 Enter Hassayampa River. 40 lks. wide, 6 ins. deep, course SE.

4.25 Leave river bed; asc. 500 ft. over precipitous NE.slope.

16.30 Spur, slopes S.30°E.; desc. 200 ft. over SW. slope.

28.70 Draw, course S.40°E.; asc. 365 ft. over E. slope.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4} \frac{S \ 2}{S \ 11}$

1932.

Asc. precipitous NE. slope 850 ft.

56.80 Spur, slopes S.60°E.; continue ascent.along SE.slope.

66.25 Change of slope to SW.; desc. 315 ft.

77.10 Draw, course S.25°E.; asc. 100 ft. over E. slope.

80.06 The cor.of secs.2,3,10 and 11.
Land, rough mountains.
Soil, rocky, 3rd. and 4th. rate.
No timber; undergrowth, greasewood, mahogany, catalaw. oak and cacti.

N.0°01'W. on true line bet.secs. 2 and 3.

Over mountainous land, through scattered undergrowth.

Along E. slope.

3.40 Draw, course SE.; asc. 150 ft. over S. slope.

11.80 Ridge, bears N.70°W. and S.70°E.; desc. 140 ft. over NE. slope.


19.60 Head of draw, course N.75°E.; asc. 150 ft. over S.slope.

27.00 Spur, extends N.60°E.; desc. 315 ft. over brushy NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

SUBDIVISION OF T.9 N., R.3 W.

chains



Continue descent 220 ft.

46.30 Draw, course N.30°E.; desc. along NE. slope 20 ft.


49.70 Draw, course E.; asc. 140 ft. over SE. slope.

55.00 Rocky spur, slopes S.75°E.; desc. 120 ft. over NE. slope.

60.00 Draw, course SE.; asc. 735 ft. over SW. slope.

80.29 Intersect N. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap mkd.



1932

raise a mound of stone 3 ft. base, 2 ft. high, S. of cor.

From point of intersection the cor. of secs. 34 and 35. T.10 N., R.3 W.; bears W. 7.45 chs. dist.; an iron post, 2 ins. diam., 12 ins. above ground, mkd. and witnessed as described in the official record.

From the same point the $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 35, T.10 N., R.3 W. bears E.; a 1 in. iron post, mkd. and witnessed as described in the official record.

Land, rolling and rough mountains. Soil, rocky, 3rd. and 4th. rate. No timber; undergrowth, greasewood, catclaw, mahogany, laurel. cacti.

From the standard cor. of secs. 33 and 34, on S. bdy. of Tp, which is an iron post, 2 ins. diam., 18 ins. above ground, marked and witnessed as described in the official record.

N.0°02'W. bet. secs. 33 and 34.

Over rolling mountainous land, through scattered undergrowth.

Asc. 45 ft. over SW. slope.

2.10 Spur, slopes SW.; desc. 90 ft.

6.15 Telephone line bears N.20°E. and S.20°W.

7.70 Small draw, course SW.; asc. 315 ft. over S. slope.

20.90 Gully, course S.30°E.

27.50 Ridge, bears E. and W.; desc. 145 ft. over NE. slope.


34.70 Draw, course N.60°E.; asc.

36.30 Draw, course E.; asc. S. slope 90 ft.

39.50 Spur, slopes N.80°E.;

chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



Desc. 110 ft. over N. slope.

42.70 Draw, course N.60°E.; asc. 30 ft.

45.00 Spur, slopes N.60°E.; desc. 140 ft. over NW. slope.

50.54 Intersect line 2-3. Survey No. 4060A. Robert lode. N.64°00'W. 0.84 chs. dist., from cor. No. 2.

51.70 Draw, course NE.; asc. 95 ft.

57.10 Spur, slopes N.60°E.; desc. 205 ft. over NW. slope.

67.20 Draw, course N.80°E.; asc. 75 ft. over SE. slope.

69.80 Road, along spur, sloping NE., bears N.60°E. to Hassayampa River, and S.60°W. to Wickenburg.

Desc. 155 ft. over N. slope.


71.60 Road, in disuse, bears W. to Gold Bar Mine.

74.30 Draw, course NE. asc. 30 ft.

78.50 Gully, course E.

79.40 Small spur, slopes E.; desc. 15 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 27, 28, 33 and 34. with brass cap mkd.



1932

of stone 2 ft. base, $1\frac{1}{2}$ ft. high. W. of cor. raise a mound

Land, rolling mountains.
Soil, rocky, 3rd. rate.
No timber; undergrowth, greasewood, catclaw and cacti; chaparral on the N. slopes.

East on a random line bet. secs. 27 and 34.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect N. and S. line 7 lks. S. of the cor. of secs. 26, 27, 34 and 35.

Thence

S.89°57'W. on true line bet. secs. 27 and 34.

SUBDIVISION OF T.9 N., R.3 W.

chains

Over rolling mountainous land, through scattered undergrowth.

Asc. 220 ft. over SE. slope.

1.00 Drain, course S.80°E.

7.94 Cor. No.4. Survey No.1384. Texas Chief lode. bears S.11°E. 3.34 chs. dist..

8.20 Spur, slopes NE.; along broken N. slope.

16.98 Intersect line 1-2, Survey No.1384, Texas Chief lode. N.11°43'W. 5.18 chs. dist. from cor. No. 1. Leave patented land.

20.00 Draw, course N.70°E.; asc. 190 ft. over E. slope.

25.65 Ridge, bears N.10°W. and S.10°E.

U.S. L. M. No.1384 bears S.25°07'E. 16.34 chs. dist.; a granite gock, in place. 30 x 14 x 8 ins. above ground, marked USLM 1384 on the E. face, witnessed by a cairn of stone 5 ft. base, 5 ft. high, NW. 3 ft. dist.

Desc. 315 ft. over W. slope.

35.50 Small draw, course S.60°W.; asc. 50 ft. over SE. slope.

39.70 Small spur, slopes S.60°W.; desc. slightly.

39.95 Set an iron post, 3 ft. long, 1 in. diam. 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S \ 27 \\ S \ 34 \end{array}$$

1932

raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.

Desc. 200 ft. over W. slope.

41.92 Intersect line 1-4, Survey No.4060A, The Home lode. S.20°36'W. 3.85 chs. dist., from cor No. 4.

46.60 O'Brien Gulch, dry wash. 40 lks. wide. course N.20°W.

Asc. 140 ft. over E. slope.

50.23 Intersect line 1-2, Survey No.4060A, The Home lode. N.53°00'W. 8.10 chs. dist. from cor. No.1.

51.60 Spur, slopes N.; desc. 125 ft. over NW. slope.

58.00 Draw, course NE.; asc. 150 ft. over SE. slope.

58.74 Intersect line 1-4, Survey No.4060A, Buttons lode. S.52°58'E. 3.09 chs. dist., from cor. No.4.

62.65 Buildings on The Home lode, bear N.66°E. about 10 chs. dist.

63.70 Spur, slopes N.30°E.; desc. 65 ft. over NW. slope.

68.20 Small draw, course N.30°E.; asc. 60 ft.

68.70 Road, bears N.10°E. to Hassayampa River and S.10°W. to Wickenburg.

70.60 Spur, slopes NE.; desc. 90 ft. over NW. slope.

COPPER
DRINK


SUBDIVISIONS OF T.9 N., R.3 W.

BOOK 3977

chains

- 77.10 Draw, course N.60°E.; asc. 50 ft. over NE. slope.
- 79.90 The cor. of secs. 27, 28, 33 and 34.
Land, broken mountains.
Soil, rocky, 3rd. and 4th. rate.
Timber; hackberry and cottonwood along canyon bottom;
undergrowth, chaparral, oak, greasewood, catclaw. and
cacti.

- N.0°02'W. bet. secs. 27 and 28.
Over rolling mountains, through scattered undergrowth.
Desc. 10 ft.
- 0.35 Gully, course E.; asc. 80 ft. over SE. slope.
- 1.30 Small building on line.
- 1.50 NW. cor. of mine building bears E. about 30 lks. dist.
- 1.96 Mine shaft, and hoist, bears E. about 2.25 chs. dist.
- 2.00 Old roadway, bears N.80°E. and S.80°W.
- 7.10 Gully, course SE.
- 8.10 Old roadway, bears N.80°W. and S.80°E.
- 8.70 Small spur, slopes E.; desc. 110 ft. over N. slope.
- 8.75 Mill building bears S.80°E. about 10 chs. dist.
- 12.24 Intersect line 2-3, Survey 4060A, Charm lode, N.19°45'E.
1.14 chs. dist. from cor. No. 2.
- 13.60 Small draw, course NE.; asc. 60 ft.
- 18.40 Spur, slopes NE.; desc. 120 ft.
- 22.04 Intersect line 1-5, Survey No. 4060A, White Blaze lode.
S.11°55'W. 2.65 chs. dist. from cor. No. 5.
- 22.60 Draw, course NE.; asc. 50 ft.
- 25.06½ Intersect line 4-5, Survey 4060A, White Blaze lode,
N.51°35'W. 0.70 chs. dist. from cor. No. 5.
- 27.60 Spur, slopes N.30°E.; desc. 130 ft. over NW. slope.
- 33.10 Draw, course NE.; asc. 15 ft.
- 36.75 Pipe line, 4" diam., bears N.20°W. and S.20°E.
- 37.20 Small spur, slopes NE.; desc. 40 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for ¼ sec. cor., with brass cap mkd.



1932

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

chains

Desc. 25 ft.

40.70 Gully, course N.60°E.; asc. 110 ft. over S. slope.

44.80 Flat spur, extends N.30°E.; desc. 120 ft. along NW. slope.

50.40 Head of draw, course N.60°W.; asc. 80 ft. over SW. slope.

60.60 Short spur, slopes NW.; desc. 250 ft. over N. slope.

68.80 Pipe line, bears N.10°W. and S.10°W.

73.90 Draw, course N.60°W.; asc. 50 ft.

77.20 Small spur, slopes N.80°W.; desc. 40 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T9N	R3W
S 21	S 22
S 28	S 27

1932

raise a mound
of stone 3 ft. base, 2 ft. high. W. of cor.

Land, rolling mountains.

Soil, rocky, 3rd. rate.

No timber; undergrowth, greasewood, catclaw, oak, mahogany, cacti and paloverde.

N.89°57'E. on a random line bet. secs. 22 and 27.40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.76 Intersect N. and S. line 10 lks. N. of the cor. of secs. 22, 23, 26, and 27.

Thence

N.89°59' W. bet. secs. 22 and 27.

Over rountainous land, through scattered timber and undergrowth.

Along S. slope.

5.30 Spur, slopes S.80°W.; desc. 270 ft. over W. slope.

9.70 Wire fencing bears N.30°E. and S.30°W.

27.60 Small spur, slopes N.60°W.; desc. 50 ft. over SW. slope.

27.65 Old barn, bears S.70°W. about 15 chs. dist.

32.50 Old roadway, bears N.70°E. and S.70°W.

35.20 Same roadway, bears N.70°W. and S.70°E.

39.88 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 22	
S 27	

1932

chains

Old building bears N.60°W. about 3. chs. dist..

Desc. 20 ft.

43.10 Draw, course S.20°W.; asc. 50 ft.

45.45 Wire fence, bears N. and S.

50.00 Small flat spur, slopes S.; desc. 65 ft.

54.00 Enter Amazon Gulch, dry wash, course NW.

57.30 Confluence of O'Brien Gulch, dry wash, 1 ch. wide, from the S.; road to Hassayampa river descends wash.

58.50 Leave draw, course NW.; asc. 190 ft. over NE. slope.

74.50 Short spur, slopes N.; desc. 140 ft. over W. slope.

79.10 Gully, course NW.; along N.slope.

79.76 The cor. of secs..21,22,27 and 28.

Land, rolling mountains.
Soil, rocky, 3rd. rate.
Timber, scattered paloverde; undergrowth, greasewood, catclaw, chaparral and cacti.

N.0°02'W. bet.secs. 21 and 22.

Over mountainous land, through scattered undergrowth.

Desc. 35 ft. over NW. slope.

0.35 Gully, course N.70°W.; asc. 55 ft.

2.80 Drain, course N.80°W.

6.60 Short spur, slopes NW.; desc. 140 ft. over N. slope.

15.20 Amazon Gulch, dry wash 1.00 ch. wide, course N.70°W.
Road to Hassayampa River follows along wash.

Asc. 300 ft. over S. slope.

23.60 E. slope of small lava butte, on spur extending NW.
Desc. 140 ft. over NE. slope.


32.50 Small draw, course N.60°W.; asc. 80 ft. over SW. slope.

35.78 Cor. No.2, Survey No.4060A, Brunton Mill Site, bears S.79°04'W. 14.56 chs. dist.; a granite stone 14 x 12 x 8 ins above ground, firmly set, mkd. with a cross (X) on top, 2BMS 4060A on N. face.

Residence of Mr. Goodwin bears S.73°W. about 25 chs.dist.

Spur, slopes NW.; desc. 120 ft. over N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam. on bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



SUBDIVISION OF T.9 N., R.3 W.

chains

Desc. 100 ft.

43.20 Enter Hassayampa river, stream 50 lks. wide, 6 ins. deep, course S.75°W.

47.00 Leave river bottom; asc. 210 ft. over S. slope.

49.00 Small spur, slopes SE.

56.00 Short spur, slopes E.; desc. 195 ft. over N. slope.

68.00 Over bottom land.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

T9N R3W	
S 16	S 15
S 21	S 22

1932

raise a mound

of stone 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous and broken.

Soil, rocky, 3rd. and 4th. rate.

Timber, mesquite along river bottom; undergrowth, greasewood, catclaw, cacti and paloverde.

S.89°59'E. on a random line bet. secs. 15 and 22.40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.82 Intersect N. and S. line 5 lks. S. of the cor. of secs. 14, 15, 22 and 23.

Thence

S.89°59'W. on true line bet. secs. 15 and 22.

Over mountainous land, through scattered undergrowth.

Asc. 165 ft. over NE. slope.

2.90 Gully, course NE.

7.70 Spur, slopes N.10°E.; desc. 150 ft. over NW. slope.

12.90 Short draw, course N.10°E.; asc. 100 ft.

16.00 Spur, slopes N.; desc. 85 ft.

19.80 Short draw, course N.20°E.; asc. 210 ft. over NE. slope.

26.40 Spur, slopes N.60°W.; desc. 220 ft. over SW. slope.

37.00 Small spur, slopes SW.

39.91 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 15
S 22

1932

raise a mound

of stone 3 ft. base, 2 ft. high, N. of cor.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

Desc. W. slope 95 ft.

44.00 Small draw, course SW.; asc. 40 ft. over S. slope.

51.80 Spur, slopes SW.; desc. 285 ft. over W. slope.

69.90 Enter Hassayampa River at foot of rubble bluff, stream 50 lks. wide, 6 ins. deep, course S.30°W.

72.00 Leave river bed; over bottom land.

79.82 The cor. of secs. 15, 16, 21 and 22.

Land, mountainous.
 Soil, rocky, and sandy, 3rd. and 2nd. rate.
 Timber; mesquite along river; undergrowth, greasewood, cacti, catclaw, mahogany and paloverde.

N.0°02'W. bet. secs. 15 and 16.

Over mountainous land, through scattered timber and undergrowth.

Asc. 175 ft. over SE. slope.

14.00 Change of slope to NE; desc. 100 ft.

18.20 Draw, course E.; asc. 250 ft.

24.10 Draw, course S.20°E.


25.90 Same draw, course S.20°W.

28.00 Same draw, course SE.

36.70 Spur, slopes W.; desc. 90 ft. over NW. slope.

39.30 Draw, course W.; asc. 30 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., .8 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



Asc. 80 ft. over S. slope.

43.00 Small spur, slopes SW.; along W. slope.

48.00 Draw, course S.30°W.; asc. 410 ft. over SE. slope.

55.90 Same draw, course SE.; change of slope to S.

71.30 Low ridge, bears N.30°E. and S.30°W.; asc. 30 ft. along W. slope.

76.00 Spur, slopes N.70°W.; desc. 95 ft. over N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., .18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

SUBDIVISION OF T.9 N..R.3 W.

chains

T9N R3W	
S 9	S 10
S 16	S 15
1932	

Land, mountainous.
Soil, rocky, 3rd. rate.
Timber; scattered paloverde and mesquite; undergrowth,
greasewood, catclaw and cacti.

N.89°59'E. on a random line bet.secs. 10 and 15.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect N. and S. line 12 lks. S. of the cor. of secs.
10,11,14 and 15.

Thence

S.89°54'W. on true line bet.secs. 10 and 15.

Over mountainous land, through scattered undergrowth.

0.50 Small spur, slopes SW.; desc. 340 ft. over SW. slope.

20.70 Draw, course S.10°E.; asc. 340 ft. over E. slope.

29.50 Shoulder of flat spur, from NW., slopes steeply SE.

Along broken S. slope.

36.50 Gully, course S.

39.95 Set an iron post, 3 ft. long, 1 in. diam..16 ins. in the
ground, to bedrock, with marked (X) stone deposited
alongside, and in a mound of stone to top. for $\frac{1}{4}$ sec.
cor., with brass cap mkd.

$\frac{1}{4}$	S 10
-----	S 15

1932

42.00 Small spur, slopes S.; desc. 85 ft. over SW. slope.

45.00 Head of draw, course S.; asc. 230 ft.

50.10 Draw, course S.60°E.; change of slope to E.

54.00 Ridge, bears N.20°W. and S.50°E.; desc. 330 ft. over SW.
slope.

60.20 Gully, head of draw, course SW.

70.40 Draw, same, course N.60°W.; along N. slope.

79.90 The cor..of secs. 9,10,15 and 16.

Land, mountainous.
Soil, rocky, 3rd. rate.
No timber; undergrowth, greasewood, catclaw, cacti. oak
and paloverde.

SUBDIVISION OF T.9 N., R.3 W.

chains

N.0°02'W. bet.secs 9 and 10.
 Over mountainous land, through scattered undergrowth.
 Desc. 125 ft. over N. slope.

5.80 Draw, course N.70°W.; asc. 140 ft. over SW. slope.

14.80 Spur, slopes W.; desc. 145 ft. over NW. slope.

17.50 Head of draw, course W.


17.50 Small spur, slopes NW.; change of slope to NE.

26.90 Draw, course N.70°W.; asc. 45 ft.

29.30 Spur, slopes W. desc. 40 ft. over NW. slope.

31.20 Draw, course SW.; asc. 200 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



1932

42.60 Raise a mound of stone 3ft. base, 2ft. high west of cor. Small spur, extends S.30°W.; desc. 80 ft. over NW. slope.

45.10 Gulch, course W.

54.90 Draw, course S.30°W.; asc. 525 ft. over SE. slope.


60.00 Change of slope to S.

63.00 Change of slope to SW.; steep spur slopes SW.

73:00 Change of slope to NW.; short spur, slopes W.; desc. 45 ft.

78.30 Gully, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, and against cross (X) on granite boulder 6 ft. x 3 ft. x 3 ft. above ground, for the cor. of secs. 3,4,9 and 10. with brass cap mkd.



1932

raise a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous.
 Soil, rocky, 3rd. rate.
 No timber; undergrowth, greasewood, cacti, catclaw and mahogany.

N.89°54'E. on a random line bet.secs. 3 and 10.

40.00 Set temp. 1/4 sec. cor.

79.96 Intersect N. and S. line 7 lks. N. of the cor. of secs. 2,3,10 and 11.

chains

Thence

S.89°57'W. on true line bet.secs. 3 and 10.

Asc. E. slope 110 ft.

4.50 Spur, slopes SE.; desc. 300 ft. over SW. slope.

15.25 Draw, course SE.; asc. 375 ft. over E. slope.

27.25 Ridge, bears N. and S.; desc. 340 ft. over W. slope.

36.00 Drain, course S.80°W.

39.75 Draw, course S.70°W.

39.98 Set an iron post, 3 ft. long, 1 in. diam., over cross (X) on surface rock, supported in a mound of stone 5 ft. base, 3 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 3
S 10

1932

Asc. 60 ft. over SE. slope.

45.00 Drain, course S.

47.50 Change of slope to S.

63.60 Small spur, slopes S.; desc. 60 ft. over SW. slope.

72.60 Spur, slopes SW.; desc. 130 ft. over W. slope.

79.96 The cor. of secs. 3, 4, 9 and 10.

Land, mountainous.

Soil, rocky, 3rd. rate.

No timber; undergrowth, cacti, catclaw and scrub oak.

N.0°02'W. on true line bet.secs. 3 and 4.

Over broken mountains, through scattered undergrowth.

Along W. slope.

6.80 Change of slope to NW.; desc. 200 ft.

17.50 Draw, course S.70°W.

20.40 Draw, course S.60°E.; confluence of gully from N.10°W.

Asc. broken S. slope 300 ft.

30.60 Small concrete water trough bears W. about 4. chs. dist.

35.60 Gully, course S.20°W.

38.80 Drain, course S.10°E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$
S 4 | S 3
1932

chains

Continue ascent 175 ft.

49.00 Sharp spur, slopes SW.; desc. 130 ft. over brushy NW. slope.

56.10 Draw, course S.60°W.; asc. 145 ft. over S. slope.

61.50 Change of slope to W.

67.80 Gully, course SW.; asc. 390 ft. over S. slope.

76.50 Shoulder of small spur, sloping SE.; along E. slope, ascend gradually.

80.41 Intersect N. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd.

T10N R3W
S 34
S 4 | S 3
T9N R3W
CC
1932

raise a mound of stone 3 ft. base, 2 ft. high, S. of cor.

From point of intersection the cor. of secs. 33 and 34, T.10 N., R.3 W., bears West 7.86 chs. dist.; an iron post 2 ins. diam., 18 ins. above ground, mkd and witnessed as described in the official record.

From the same point the 1/4 sec. cor. on the S. bdy. of sec. 34, T.10 N., R.3 W., bears East.; an iron post, 1 in. diam., 10 ins. above ground, mkd and witnessed as described in the official record.

Land, rolling and broken mountains.
Soil, rocky, 3rd. rate.
No timber; undergrowth, greasewood, cacti, catclaw and mahogany.

From the standard cor. of secs. 32 and 33, on S. bdy. of Tp., which is an iron post, 2 ins. diam., 18 ins. above ground, supported in a mound of stone to top, properly mkd on brass cap.

N.0°02'W. bet. secs. 32 and 33.

Over mountainous land, through scattered timber and undergrowth.

Desc. 20 ft. over NE. slope.

1.20 Change of slope to NW.; desc. 160 ft.

8.30 Slim Jim Wash, 50 lks. wide, course S.60°W., from SE.; asc. 100 ft. over S. slope.

13.50 Spur, slopes S.70°W.; desc. 55 ft.

17.20 Small draw, course S.30°W.; asc. SE. slope 380 ft.

23.18 Intersect line 1-2, Survey No. 1974, Gold Bug No. 2 Lode. S.58°12'E. 5.765 chs. dist. from cor. No. 2.

Enter patented land.


SUBDIVISION OF T.9 N., R.3 W.

chains

33.83 Intersect line 3-4, Survey No.1974, Gold Bug No.2.Lode
S.58°12'E. 0.12 chs. dist. from cor. No.3.
Leave patented land.

38.80 Small draw, course SE.; asc. over S. slope.

40.00 Set an iron post,3 ft. long, 1 in. diam.,30 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



of stone 3 ft. base, 2 ft. high, W. of cor. raise a mound

Asc. 120 ft. over S. slope.

43.50 Spur, slopes S.60°W.; desc. 160 ft. over NW. slope.

49.00 Small draw, course N.60°W.; asc. 70 ft.


52.90 Spur, slopes N.80°W.; desc. 150 ft. over NW. slope.

59.20 Draw, course W.; asc. 265 ft. over SW. slope.

64.80 Draw, course SW.; change of slope to S.; continue ascent.

78.50 Gully, course S.20°E.

80.00 Set an iron post,3 ft. long, 2 ins. diam., 30 ins. in
the ground. for the cor. of secs. 28,29,32 and 33, with
brass cap mkd.



of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. raise a mound

Land, rolling mountains.

Soil, rocky, 3rd. rate.

Timber, scattered paloverde; undergrowth, greasewood,
cacti, catclaw and scrub oak.

East on a random line bet.secs 28 and 33.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect N. and S. line 10 lks. S. of the cor. of secs.
27,28,33 and 34.

Thence

S.89°56'W. on true line bet.secs. 28 and 33.

Over mountainous land, through scattered undergrowth.

Along N. slope.

0.80 Gully, course N.70°E.; asc. 440 ft. over increasing NE.
slope.

2.60 Same gully, course S.70°E.

4.80 Shaft and group of buildings of Gold Bar Mine bear South

SUBDIVISION OF T.9 N..R.3 W.

BOOK 3977

chains

from 2 to 4 chs. dist..

5.50 Old roadway, bears N. and S.

21.10 Ridge, bears N.10°E. and S.10°W.; desc. 210 ft. over NW. slope.

29.00 Change of slope to W.

29.74 Intersect line 2-3. Survey 4060A, Bennet lode, S.51°35'E. 2.29 chs. dist. from cor.No.3.

32.60 Draw, course N.; asc. 125 ft. over E. slope.

37.00 Spur, slopes N.20°W.; desc. 95 ft. over NW. slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 28 / S 33

1932

of stone 3 ft. base, 2 ft. high. N. of cor. raise a mound

Desc. 75 ft.

43.30 Draw, course N.; asc. 125 ft. over E. slope.

48.30 Spur, slopes N.20°E.; desc. 60 ft. over NW. slope.

51.20 Gully, course N.; asc. 175 ft. over NE. slope.

60.50 Drain, course N.20°E.

63.00 Ridge, bears N.20°W. and S.20°E.; desc..190 ft. over SW. slope.

71.40 Draw, course S.10°W.; asc. 140 ft. over E. slope.

77.70 Small spur, slopes S.20°E.; along S. slope.

80.02 The cor. of secs., 28, 29, 32 and 33.

Land, rolling mountains.
Soil, rocky, 3rd. rate.
Timber; scattered paloverde; undergrowth, greasewood, chaparral, cacti, scrub oak, and catclaw.

N.0°02'W. bet.secs. 28 and 29.

Over mountainous land, through scattered undergrowth.

Asc. 25 ft. over S. slope.

1.20 Ridge, bears NE. and S.70°W.; desc..170 ft. over NW. slope.

5.10 Gully, course W.

16.30 Draw, course SW.; asc. 260 ft. over SE. slope.

39.70 Gully, course SE.; change of slope to S.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

SUBDIVISIONS OF T.9 N., R.3 W.

chains

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 29 \mid \text{S } 28 \\ | \\ 1932 \end{array}$$

raise a mound
of stone 3 ft. base, 2 ft. high. W. of cor.

Asc. 45 ft.

42.50 Small saddle in short ridge, bearing W. to peak, and E.
to N. and S. divide.

Desc. 270 ft. over NE. slope.

46.80 Head of draw, course NE.

59.40 Same draw, course NW.; asc. 235 ft. over SW. slope.

72.00 Ridge, bears NW. and S.30°E.; continue ascent over SE.
slope.

77.00 Steep, rocky spur, slopes E.; desc. 55 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., over cross
(X) on surface rock, supported in a mound of stone 6 ft.
base, 3 ft. high, for the cor. of secs. 20, 21, 28 and 29,
with brass cap mkd.

$$\begin{array}{c} \text{T9N R3W} \\ \text{S } 20 \mid \text{S } 21 \\ \text{S } 29 \mid \text{S } 28 \\ | \\ 1932 \end{array}$$

Land, rolling mountains.

Soil, rocky. 3rd. rate.

No timber; undergrowth, cacti, greasewood, oak, and
catclaw.

N.89°56'E on a random line bet. secs. 21 and 28.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect N. and S. line 3 lks. S. of the cor. of secs.
21, 22, 27 and 28.

Thence

S.89°55'W. on true line bet. secs. 21 and 28.

Over mountainous land, through scattered undergrowth.

Desc. 60 ft. over NW. slope.

0.50 Pipe line, 4 ins. diam. bears N. and S.

2.60 Draw, wash 50 lks. wide, course N.; asc. 345 ft. over
broken E. slope.

15.00 Spur, slopes N.30°E.; change of slope to NE.


21.00 Spur, slopes N.; desc. 100 ft. over NW. slope.

26.70 Gully, course N.; asc. 135 ft.

30.20 Spur, slopes N.45°E.; along N. slope.

chains

- 39.60 Draw , course N.60°E.; asc. E. slope.20 ft.
- 40.04 Set an iron post,3 ft. long,1 in. diam..6 ins. in the ground, to rock, with marked (X) stone deposited along-side, and in a mound of stone to top. for 1/4 sec. cor. with brass cap mkd.



1932

Asc. 350 ft.

- 46.00 Change of slope to SE.
- 52.00 Spur, slopes N.50°E.; desc. 130 ft. over NW. slope.
- 64.20 Draw, course NE.; asc. 440 ft. over E. slope.
- 68.40 Gulch, course N.80°E.
- 80.08 The cor. of secs. 20,21,28 and 29.


Land, rough mountains.
 Soil, rocky, 3rd. rate.
 No timber; undergrowth. greasewood, catclaw, cacti and mahogany.

N.0°02'W. bet.secs. 20 and 21.

Over mountainous land, through scattered undergrowth.

Along E. slope.

- 1.40 Small spur, slopes E.; desc. 90 ft.
- 4.20 Head of draw, course E.; asc. 230 ft. over SE. slope.
- 17.50 Spur, slopes E.; desc. 60 ft.
- 20.50 Spur, slopes N.30°E.; desc. NW. slope 450 ft.
- 30.60 Gully, course N.20°W.
- 34.50 Gulch, course N.80°W.; asc. 60 ft. over SW.slope.
- 37.40 Short spur, slopes W.; desc. 100 ft.
- 38.80 Drain, course N.70°W.
- 40.00 Set an iron post,3 ft. long, 1 in. diam.,16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor.. with brass cap mkd.



1932

Desc. 650 ft. over NW. slope.

- 60.00 Change of slope to N.
- 70.80 Enter Hassayampa River, at foot of slope, stream 50 lks. wide. 5 ins. deep, course N.70°W.

SUBDIVISION OF T.9 N., R.3 W.

chains

- 72.20 Ascend over gravel embankment.
- 74.50 Mine building, mill and power house, on line; allied buildings bear west 2 to 5 chs. dist.
Asc. 130 ft. over S. slope.
- 79.40 Two galvanized iron water tanks bear East about 50 lks. dist.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

T9N R3W	
S 17	S 16
S 20	S 21

1932

Land, rough mountains.
Soil, rocky, 3rd. and 4th. rate.
Timber, scattered paloverde, some willow and mesquite along river bottom; undergrowth, greasewood and cacti.

N.89°55'E. on a random line bet. secs. 16 and 21.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.10 Intersect N. and S. line 18 lks. S. of the cor. of secs. 15, 16, 21 and 22.
Thence
S.89°47'W. on true line bet. secs. 16 and 21.
Over rolling and broken land, through scattered timber and undergrowth.
Asc. 40 ft. over E. slope.
- 8.70 Low divide, bears N.20°E. and S.20°W.; along gentle N. slope.
- 17.00 Desc. 60 ft. over NW. slope.
- 20.40 Draw. 50 lks. wide, course SW.; asc. 95 ft. over SE. slope.
- 23.80 Gulch, course S.
- 40.05 Set an iron post, 3 ft. long, ; in. diam., 12 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 16
S 21

1932.

Asc. 50 ft.

- 45.30 Small spur, slopes S.20°E.; desc. 160 ft. over W. slope.
- 51.00 Desc. steeply over bluff slope of canyon.
- 57.80 Enter river bed, course NW.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

60.00 Leave Hassayampa River, stream 60 lks. wide, 4 ins. deep, course NW.
Asc. 55 ft. over NE. slope.

64.25 Spur, slopes N.; desc. 60 ft. over NW. slope.

67.10 Enter Hassayampa River, stream 50 lks. wide, 5 ins. deep, course SW.

71.50 Leave river bottom; asc. SE. slope 135 ft.

76.50 Small spur, slopes SE.; desc. gradually over S. slope.

80.10 The cor. of secs. 16, 17, 20 and 21.
Land, broken and mountainous.
Soil, rocky, 3rd. and 4th. rate.
Timber; scattered paloverde, mesquite and willow along river bottom; undergrowth, greasewood, cacti, catclaw and oak.

N.0°02'W. bet. secs. 16 and 17.

Over mountainous land, through scattered timber and undergrowth.

Asc. 190 ft. over S. slope.


5.60 Sharp spur, slopes S.60°E.; desc. 130 ft. over NE. slope.

12.20 Draw, course S.70°E.; asc. 185 ft. over SE. slope.

17.40 Spur, slopes SE.; desc. 55 ft.

21.20 Draw, course SE.; asc. 500 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



Asc. 140 ft. over S. and SW. slopes.

44.90 Ridge, bears N.20°W. and S.20°E.; along E. slope.

54.80 Ridge, bears N.20°E. and S.20°W.; desc. 210 ft. over NW. slope.

57.20 Head of draw, course N.60°W.

65.30 Gulch, course N.80°W.

71.40 Head of draw, course S.80°W.; asc. 75 ft. over S. slope.

76.80 Saddle in short spur, extending W. and NW.; desc. 40 ft. over N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 8, 9, 16 and 17. with brass cap mkd.

SUBDIVISION OF T.9 N., R.3 W.

chains

T9N R3W	
S 8	S 9
S 17	S 16
1932	

Land rough mountains.
Soil, rocky, 3rd. and 4th. rate.
Timber, scattered paloverde; undergrowth, greasewood,
catclaw and cacti.

N.89°47'E. on a random line bet.secs. 9 and 16.

- 40.00 Set temp. 1/4 sec. cor.
- 80.00 Intersect N. and S. line 14 lks. N. of the cor. of secs. 9,10,15 and 16.
- Thence
- S.89°53'W. on true line bet.secs. 9 and 16.
- Over rolling mountainous land, through scattered undergrowth.
- Asc. 45 ft. over NE. slope.
- 1.00 Drain, course N.
- 5.10 Short spur, slopes N.30°W.; desc. 380 ft. over decreasing W. slope.
- 16.70 Small draw, course SW.
- 19.70 same draw, course N.80°W.
- 23.00 Draw, course S.10°W., asc. 20 ft.
- 26.80 Narrow point of low spur, slopes S.10°W.; desc. 45 ft.
- 29.30 Draw, course S.10°W.; asc. 30 ft.
- 30.40 Narrow point of spur, slopes S. desc. 45 ft.
- 32.30 Draw, small flow of water, course S.; asc. 195 ft. over E. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam. 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 9
S 16
1932

Asc. 10 ft.

- 40.30 Small spur, slopes S.; desc. 175 ft. over SW. slope.
- 45.60 Draw, course SE.; asc. 470 ft. over increasing E. slope.
- 74.40 Sharp rocky spur, projects N. about 5 chs., then slopes steeply N.
- Desc. 120 ft. over W. slope.
- 78.80 Drain, course N.20°W.; along N. slope.
- 80.00 The cor. of secs. 8,9,16 and 17.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

Land, rolling mountains.
Soil, rocky, 3rd. rate.
No timber; undergrowth, chaparral, cacti, catalaw and
greasewood.

N.0°02'W. bet.secs. 8 and 9.

Over rolling mountains, through scattered undergrowth.

Desc. 300 ft. over N. slope.

4.70 Drain, from SE. course N.10°E.


11.30 Gully, same drain, course N.20°W.

18.30 Small draw, course W.; asc. 210 ft. over rolling SW.
slope.

32.90 Small spur, slopes SW.; along W. slope.

39.70 Drain, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
ground, with marked (X) stone deposited alongside, and
in a mound of stone to top, for 1/4 sec. cor., with brass
cap mkd.



Continue along W. slope.


52.80 Shallow draw, course SW.; asc. 380 ft. over gradual SW.
slope.

58.70 Wash, course S.20°W.; change of slope to S.

76.00 Flat spur, slopes SW.

79.50 Along steep left bank of gulch.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the
ground, for the cor. of secs. 4, 5, 8 and 9, with brass
cap mkd.



raise a mound
of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous, broken and rolling.
Soil, rocky, 3rd. rate.
No timber; undergrowth, greasewood, cacti, and catalaw.

N.89°53'E. on a random line bet.secs. 4 and 9.

40.00 Set temp. 1/4 sec. cor.

80.02 Intersect N. and S. line 7 lks. N. of the cor. of secs.
3, 4, 9 and 10.

SUBDIVISION OF T.9 N., R.3 W.

chains

Thence

S.89°56'W. on true line bet.secs. 4 and 9.

Over mountainous land, through scattered undergrowth.

Desc. 350 ft. over increasing W. slope.

13.90 Draw, course S.20°W.; asc. 490 ft. over SE. slope.

28.30 Spur, slopes SW.; desc. 345 ft. over W. slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{l} S 4 \\ S 9 \end{array}$$

1932

raise a mound

of stone 3 ft. base, 2 ft. high. N. of cor.

Desc. 90 ft.

43.75 Draw, course S.40°W.; asc. 350 ft. over SE. slope.

46.00 Gully, course S.

64.25 Steep flat spur, slopes S.; desc. 320 ft. over decreasing SW. slope.

71.75 Gully, course SW.

74.00 Flat spur, slopes SW.

79.50 Desc. abruptly over bank of gully.

80.02 The cor. of secs. 4, 5, 8 and 9.

Land, mountainous.

Soil, rocky, 3rd. rate.

No timber; undergrowth, greasewood, catclaw, and cacti.

N.0°02'W. on true line bet.secs. 4 and 5.

Over mountainous land, through scattered undergrowth.

Desc. 15 ft.

0.70 Gulch, course SW.; asc. 340 ft. over S. slope.

9.60 Spur, slopes W.; desc. 165 ft. over NW. slope.

14.60 Draw, course W.

15.50 Draw, course SW.; asc. 640 ft. over S. slope.

30.80 Spur, slopes S.60°W.; desc. 250 ft. over NW. slope.

39.10 Draw, course S.70°W.; asc. 45 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{l} S 5 \\ S 4 \end{array}$$

1932

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Asc. 420 ft. over S. slope.

54.30 Spur, slopes W.; desc. 175 ft. over brushy NW. slope.


63.80 Draw, course W.; asc. 100 ft. over SW. slope.

69.50 Spur, slopes W.; desc. 120 ft. over NW. slope.

75.25 Draw, course S.70°W.; asc. 190 ft. over S. slope.

80.54 Intersect N. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for closing cor. of secs. 4 and 5, with brass cap mkd.



From point of intersection the cor. of secs. 32 and 33, T.10 N., R.3 W. bears West 7.97 chs. dist.; an iron post, 2 ins. diam., 10 ins. above ground, mkd. and witnessed as described in the official record.

From the same point the 1/4 sec. cor. on the S. bdy. of sec. 33, T.10 N., R.3 W. bears East. an iron post, 1 in. diam., 10 ins above ground, mkd. and witnessed as described in the official record.

Land, rough mountains.
Soil, rocky, 3rd. rate.

No timber; undergrowth, chaparral and oak on the N. slope
catclaw, greasewood and cacti.

From the standard cor. of secs. 31 and 32, on S. bdy. of Tp.; which is an iron post, 2 ins. diam., 16 ins. above ground, supported in a mound of stone to top, properly mkd. on brass cap.

N.0°03'W. bet. secs. 31 and 32.

Over mountainous land, through scattered undergrowth.

Desc. 35 ft. over NW. slope.

2.80 Gully, course S.60°W.; asc. 260 ft. over S. slope.

12.00 Change of slope to SW.

15.20 W. slope of small peak on ridge, bearing NW. and SE.

Desc. 440 ft. over N. slope.

31.10 Slim Jim wash, 60 lks. wide, course W.; asc. 285 ft. over S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

SUBDIVISION OF T.9 N., R.3 W.

chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 31 \mid \text{S } 32 \\ \hline 1932 \end{array}$$

Asc. 100 ft.

45.00 Change of slope to SW.

48.50 Drain, course SW.

52.50 Spur, extends W.; desc. 140 ft. over NW. slope.

62.78 Cor. No.2, Survey No.2000, Abe Lincoln lode, bears West 5.94 chs. dist.; a sawed pine post, 5 ins. square, 20 ins. above ground, firmly set, mkd. 2 AL 2000 on the SW face.

64.40 Small draw, course N.70°W.; asc. 150 ft. over SW.slope.

68.70 Spur, slopes W.; desc. 85 ft.

77.60 Draw, course S.50°W.; asc. 100 ft. over S. slope.

79.60 Point of narrow spur, sloping SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

$$\begin{array}{c} \text{T9N R3W} \\ \text{S } 30 \mid \text{S } 29 \\ \hline \text{S } 31 \mid \text{S } 32 \\ \hline 1932 \end{array}$$

raise a mound
of stone 3 ft. base, 2 ft. high, W. of cor.

Land, rolling mountains.

Soil, rocky, 3rd. rate.

Timber, scattered paloverde and mesquite; undergrowth, greasewood, cacti, catclaw and mahogany.

East on a random line bet.secs. 29 and 32.40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect the cor. of secs. 28, 29, 32 and 33.

Thence

West on true line bet.secs. 29 and 32.

Over mountainous land, through scattered undergrowth.

Asc. 30 ft. over SE. slope.

1.30 Flat ridge, extends S.70°W., bears NE.

Desc. 370 ft. over NW. slope.

13.20 Small spur, slopes NW.; change of slope to W.

18.00 Small draw, course N.80°W.

20.10 Same draw, course SW.

22.70 Same draw, course N.60°W.

SUBDIVISION OF T.9 N.,R.3 W.

BOOK 3977

chains

- 30.50 Gully, course NW.
- 33.50 Small draw, course N.; asc. 85 ft. over NE. slope.
- 38.25 Change of slope to N.
- 40.01 Set an iron post, 3 ft. long, 1 in. diam. .20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S \ 29}{S \ 32}$$

1932

Along gradual N. slope.

- 53.00 Shoulder of flat spur, from SE.; desc. 440 ft. over decreasing W. slope.
- 70.80 Wash, 40 lks. wide, course S.60°W.; asc. 40 ft.
- 79.60 Small flat spur, extends SW.
- 80.02 The cor. of secs. 29,30,31 and 32.

Land, rolling mountains.
 Soil, rocky, 3rd. rate.
 Timber, scattered paloverde and mesquite; undergrowth,
 greasewood, catclaw, scruboak, and cacti.

 West on a random line bet. secs. 30 and 31.

- 40.00 Set temp. 1/4 sec. cor.
- 79.82 Intersect W. bdy. of Tp. 14 lks. S. of the cor. of secs. 25,30,31 and 36; an iron post, 2 ins. diam. .20 ins. above ground, and in a mound of stone to top, mkd. and witnessed as described in the official record.

Thence

S.89°54'E. on true line bet. secs. 30 and 31.

Over broken and mountainous land, through scattered timber and undergrowth.

Desc. 10 ft.

- 3.40 Enter Hassayampa River, stream 50 lks. wide, 6 ins. deep, course N.70°W.
- 6.10 Leave river.; asc. 300 ft. over SW. slope.
- 15.30 Spur, slopes S.; desc. 265 ft. over E. slope.
- 23.90 Enter Hassayampa River at foot of slope, stream 50 lks. wide, 6 ins. deep. course S.10°E.
- 26.10 Leave river bed, asc. bluff bank 50 ft.
- 27.25 Over broken W. slope, asc. 170 ft.
- 36.40 Wash, 40 lks. wide, course NW.
- 39.82 Set an iron post, 3 ft. long, 1 in. diam. .30 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.

SUBDIVISION OF T.9 N., R.3 W.

chains

$$\frac{1}{4} \begin{array}{l} S 30 \\ S 31 \end{array}$$

1932

raise a mound
of stone 3 ft. base, 2 ft. high, W. of cor.

Asc. 175 ft. over W. slope.

48.30 Slope changes to SW.

53.00 Short spur, slopes S.; desc. 140 ft. over SE. slope.

61.40 Small draw, course S.; asc. 120 ft.

72.40 Spur, slopes S.; desc. 115 ft.

77.90 Draw, wash 40 lks. wide, course S.30°W.; asc. 85 ft. over W. slope.

79.82 The cor. of secs. 29, 30, 31 and 32.

Land, broken and rolling mountains.

Soil, rocky, 3rd. and 4th. rate.

Timber, scattered paloverde and mesquite, some willow along the river; undergrowth, greasewood, catclaw and cacti.

N.0°03'W. bet. secs. 29 and 30.

Over rolling mountains, through scattered paloverde and undergrowth.

Desc. 60 ft. along W. slope.

3.10 Draw, course S.30°W.; asc. 350 ft. over SE. slope.

30.90 Ridge, bears NE. and SW.; along W. slope.

34.10 Spur, slopes N.60°W.; desc. 170 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam. 16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone 3 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{l} S 30 \\ S 29 \end{array}$$

1932

Desc. 140 ft. over N. slope.

43.80 Draw, course N.40°W.; along W. slope.

49.30 Spur, slopes N.60°W.; desc. 210 ft. over N. slope.

52.00 Draw, course N.30°W.;

54.30 Same draw, course N.10°E.

55.50 Draw, course N.70°W.; asc. 120 ft. over SW. slope.


66.20 Gully, course S.80°W.

73.20 Spur, slopes NW.; desc. 175 ft. over NE. slope.

78.60 Draw, course NW.; asc. 20 ft.

chains

80.00 Set an iron post, 3 ft. long, 2 ins. diam. .18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 19, 20, 29 and 30, with brass cap mkd.



1932

Land, rolling and broken mountains.
Soil, rocky. 3rd. rate.
Timber, scattered paloverde; undergrowth, greasewood, chaparral, catclaw and cacti.

East on a random line bet. secs. 20 and 29.

40.00 Set temp. 1/4 sec. cor.

80.02 Intersect N. and S. line 7 lks. N. of the cor. of secs. 20, 21, 28 and 29.

Thence

N. 89° 57' W. on true line bet. secs. 20 and 29.

Over mountainous land, through scattered undergrowth.

Asc. 305 ft. over E. slope.

6.85 Southerly one of two rocky peaks on apex of ridge. bearing N. and sloping steeply SE.

6.94 A bench mark of the U.S. Geological Survey, published elevation 4109 ft. above mean sea level, bears N. 1° 08' E. 8.96 chs. dist.; a brass tablet seated in a granite ledge, conforming to the record; situated upon the north peak of ridge.

Desc. 920 ft. over decreasing W. slope.


18.80 Gully, course S. 80° W.

24.50 Same gully, course N. 80° W.

35.00 Same gully, course S. 70° W.

39.40 Small spur, slopes S. 70° W.

40.01 Set an iron post, 3 ft. long, 1 in. diam. .20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



1932

Desc. 180 ft.

44.80 Draw, course N. 10° W.; asc. 220 ft. over NE. slope.

61.00 Spur, slopes N. 70° W. to conical peak about 7 chs. dist.

Desc. 40 ft. over S. slope.

SUBDIVISION OF T.9 N., R.3 W.

chains	
69.00	Change of slope to SW., desc. 360 ft.
79.30	Gully, course SW.
80.02	The cor. of secs. 19, 20, 29 and 30. Land, broken and rough mountains. Soil, rocky, 3rd. and 4th. rate. No timber; scattered greasewood, cacti, catclaw and chaparral.

	N.89°54'W. on a random line bet. secs 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.80	Intersect W. bdy. of Tp. 10 lks. N. of the cor. of secs. 19, 24, 25 and 30.; an iron post, 2 ins. diam., 20 ins. above ground, and in a mound of stone to top, properly mkd. on brass cap.
	Thence
	S.89°58'E. on true line bet. secs. 19 and 30. Over rolling mountains, through scattered undergrowth. Desc. 165 ft. over E. slope.
5.00	Draw, course N.20°E.; asc. 235 ft. over NW. slope.
13.90	Spur, slopes N.20°E.; desc. 220 ft. over E. slope.
21.30	Draw, course N.20°E.; asc. 40 ft.
24.40	Small spur, slopes N.10°E.; desc. 155 ft. over gradual NE. slope.
34.40	Gully, course NE.
39.60	Gully, course N.30°E.
39.80	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ $\frac{S}{S}$ $\frac{19}{30}$
	1932
	raise a mound
	of stone 3 ft. base, 2 ft. high, N. of cor.
	Desc. gradual NE. slope 280 ft.
53.00	Small wire corral bears S. about 2.50 chs. dist.
58.25	Desc. abrupt NE. slope.
59.80	Foot of slope, across river bottom.
60.50	Enter Hassayampa river, course S.
62.60	Leave river.; asc. increasing W. slope 70 ft.
70.00	Asc. 120 ft. over NW. slope.
75.30	Point of spur, sloping N.; desc. NE. slope 55 ft.

SUBDIVISION OF T.9 N., R.3 W.

BOOK 3977

chains

77.70 Draw, course NW.; asc. 45 ft. over SW. slope.

79.80 The cor. of secs. 19, 20, 29 and 30.

Land, broken and rolling mountains.
Soil, rocky, 3rd. rate.
Timber, scattered paloverde, cottonwood and willow along the river bottom; undergrowth, greasewood, catclaw and cacti.

N.0°03'W. bet. secs. 19 and 20.

Over mountainous land, through scattered timber and undergrowth.

Asc. 145 ft. over SW. slope.

7.40 Spur, slopes W.; desc. 195 ft. over NW. slope.

15.60 Wash, 30 lks. wide, course N.80°W.; asc. 85 ft.


23.80 Spur, slopes W.; desc. 80 ft.

28.00 Wash, 25 lks. wide, course S.70°W.; asc. 90 ft.

33.50 Spur, slopes W. desc. 140 ft. over NW. and N. slope.

39.00 Change of slope to NE.; desc. bluff of river canyon.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



Desc. 30 ft.

40.70 Enter river bed, course N.80°W.


44.00 Leave Hassayampa River, stream 60 lks. wide, 4 ins. deep, at foot of S. slope.; Asc. 300 ft.

58.10 Spur, slopes S.30°E.; desc. 50 ft. over NE. slope.

71.40 Small draw, course S.70°E.; asc. 120 ft. over S. slope.

76.00 Spur, slopes E.; desc. 30 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 17, 18, 19 and 20. with brass cap mkd.



raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, rolling mountains.
Soil, rocky, 3rd. rate.
Timber, scattered paloverde and mesquite; undergrowth, greasewood, catclaw and cacti.

SUBDIVISION OF T.9 N., R.3 W.

chains

S.89°57'E. on a random line bet.secs. 17 and 20.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. and S. line 27 lks. S. of the cor. of secs. 16,17,20 and 21.

Thence

S.89°51'W. on true line bet.secs. 17 and 20.

Over broken and mountainous land, through scattered timber and undergrowth.

Desc. 140 ft. over S. and SW. slopes.

8.00 Enter river bottom, course NW.

10.20 Enter Hassayampa River, stream 60 lks. wide, 4 ins. deep, course NW.

17.60 Enter River, stream 50 lks. wide, 5 ins. deep, course S.30°W.

20.10 Leave river bottom.; asc. 210 ft. over E. slope.

25.00 Wash, 20 lks. wide, 5 ft. deep, course S.30°E.; change of slope to NE.

33.00 Spur, slopes SE.; desc. 125 ft. over S. and SW. slopes.

39.40 Gully, course S.

40.00 Set an iron post, 3 ft. long, 1 in. diam. 10 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ $\frac{S\ 17}{S\ 20}$

1932

Desc. 115 ft.

47.80 Enter Hassayampa River, stream 50 lks. wide, 5 ins. deep, at foot of slope, course N.80°W.

55.00 Leave river.

59.40 Enter river, 50 lks. wide, 5 ins. deep, course S.

63.00 Leave river bottom; asc. 290 ft. over broken E. slope.

74.10 Small spur, slopes NE.

77.00 Gully, course NE.

80.00 The cor. of secs. 17,18,19 and 20.

Land, broken and mountainous.

Soil, rocky, 3rd. and 4th. rate.

Timber, scattered paloverde, willow along river bottom; undergrowth, greasewood, catclaw and cacti.

SUBDIVISION OF T.9 N.,R.3 W.

BOOK 3977

chains

N.89°58'W. on a random line bet.secs. 18 and 19.

40.00 Set temp. 1/4 sec. cor.

79.82 Intersect W. bdy. of Tp. 2 lks. S. of the cor. of secs. 13,18,19 and 24; an iron post,2 ins. diam..16 ins. above ground, and in mound of stone to top, properly mkd on brass cap.

Thence

S.89°57'E. on true line bet. secs. 18 and 19.

Over mountainous land, through scattered timber and undergrowth.

Desc. 20 ft.

2.00 Gully, course S.30°W.; asc. 260 ft. over SW. slope.

13.80 Apex of lava capped spur, extending SE.; desc. 490 ft. over NE. and E. slopes.

28.80 Draw, from N. course S.60°E.; asc. 130 ft. over SW. slope

36.50 Sharp spur, slopes S.; desc. 50 ft.

38.75 Gulch, course S.10°W.

39.82 Set an iron post,3 ft. long, 1 in. diam. 6 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 18
S 19

1932

Asc. 300 ft. over broken SW. slope.

44.30 Gulch, course S.20°W.

48.90 Ridge, bears N.30°W. and S.30°E.; desc. 250 ft. over NE. slope.

64.00 Gully, course NE.; asc. 110 ft. over NW. slope.

73.10 Small spur, slopes N.; desc. 125 ft. over NE. slope.

76.00 Small spur, slopes NE.

79.82 The cor. of secs.,17,18,19 and 20.

Land, broken mountains.

Soil, rocky, 3rd. and 4th. rate.

Timber; scattered paloverde; undergrowth, greasewood. catclaw and cacti.

N.0°03'W. bet.secs. 17 and 18.

Over rolling mountainous land, through scattered timber and undergrowth.

Desc. 20 ft.

0.60 Gully, course N.80°E.; asc. 40 ft.

2.30 Small spur, slopes N.70°E.;desc. 150 ft. over NE. slope.

SUBDIVISION OF T.9 N., R.3 W.

chains

- 9.40 Draw, course S.70°E.; asc. 210 ft. over S. slope.
- 16.80 Spur, slopes S.60°E.; desc. 190 ft. over N. slope.
- 28.00 Draw, small flow of water, course S.60°E.; asc. 150 ft. over broken S., and SW.slope.
- 31.70 Draw, course S.10°E.
- 39.90 Drain, course W.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 18 \text{ | S } 17 \\ \hline 1932 \end{array}$$

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Asc. 30 ft. over gradual SW. slope.

- 48.00 Change of slope to SE; asc. gradually 330 ft. over increasing slope.
- 53.30 Wash, course SE.
- 62.10 Low flat spur, slopes SE.; along E. slope.
- 65.60 Rocky wash, 30 lks. wide, course S.70°E.; asc. 470 ft. over S. slope.
- 76.00 Along crest of sharp spur, from N.,
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

$$\begin{array}{c} \text{T9N R3W} \\ \text{S } 7 \text{ | S } 8 \\ \hline \text{S } 18 \text{ | S } 17 \\ \hline 1932 \end{array}$$

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, rolling mountains.

Soil, rocky, 3rd. rate.

Timber, scattered paloverde and mesquite; undergrowth, greasewood, catclaw and cacti.

N.89°51'W. on a random line bet.secs. 8 and 17.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.16 Intersect N. and S. line 7 lks. N. of the cor. of secs. 8, 9, 16 and 17.
- Thence
- S.89°54'W. on true line bet.secs. 8 and 17.
- Over mountainous land, through scattered undergrowth.
- Asc. 95 ft. over NE. slope.
- 5.35 Short rocky spur, projects N.; desc. precipitous W.slope 480 ft.

chains	
17.25	Gully, course N.50°W.; along NW. slope.
22.90	Gully, course N.; asc. 75 ft. over NE. slope.
28.25	Shoulder of spur, from S.70°E.; desc. 200 ft. over increasing NW. and W. slopes.
38.50	Draw, small flow of water, course S.25°W.; asc. E. slope 110 ft.
40.08	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.
	$\frac{1}{4} \frac{S 8}{S 17}$ 1932
	raise a mound of stone 3 ft. base, 2 ft. high, N. of cor. Corner falls upon point of small spur, sloping SE. Along S. slope.
41.25	Gulch, course SE.; asc. 305 ft. over E. slope.
48.60	Spur, slopes S.20°E.; desc. 80 ft. over SW. slope.
52.00	Gully, course S.; asc. 45 ft.
55.75	Spur, projects S.; desc. 120 ft.
58.50	Draw, course S.; asc. 240 ft. over E. slope.
67.00	Spur, projects S.; desc. 45 ft.
68.70	Gully, course S.10°W.; asc. 175 ft. over E. slope.
74.60	Spur, slopes S.; desc. 35 ft.
78.00	Gully, course S.20°E.; asc. 95 ft. over SE. slope.
80.16	The cor. of secs. 7, 8, 17 and 18.
	Land, broken and mountainous. Soil, rocky, 3rd. and 4th. rate. No timber; undergrowth, greasewood, cacti and catclaw.

	N.89°57'W. on a random line bet. secs. 7 and 18.
40.00	Set temp. 1/4 sec. cor.
79.70	Intersect W. bdy. of Tp. 2 lks. N. of the cor. of secs. 7, 12, 13 and 18; an iron post, 2 ins. diam., 30 ins. above ground, in a mound of stone to top, properly mkd. on brass cap.
	Thence
	S.89°58'E. on true line bet. secs. 7 and 18.
	Over mountainous land, through scattered undergrowth.
	Along S. slope.
0.50	Head of drain, course S.20°E.
2.60	Small spur, slopes S.10°E.; desc. SE. slope 430 ft.

SUBDIVISION OF T.9 N., R.3 W.

chains

- 5.50 Head of gully. course S.
- 9.80 Small spur, slopes S.
- 25.50 Draw, course S.; asc. 90 ft.
- 27.50 Spur, slopes S.; desc. 50 ft.
- 30.10 Draw, course S.30°W.; asc. 155 ft. over increasing W. slope.
- 39.70 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S 7}{S 18}$

1932

Asc. 285 ft.

- 48.20 Spur-ridge, slopes S.40°W.; asc. 40 ft. over SW. slope.
- 55.00 Sharp steep spur, slopes SE.; desc. 370 ft. over E. slope.
- 62.10 Gulch, course S.30°E.; asc. 140 ft. over SW. slope.
- 65.00 Gully, course S.20°W.
- 79.70 The cor. of secs. 7, 8, 17 and 18.

Land, mountainous.
Soil, rocky, 3rd. and 4th. rate.
No timber; undergrowth, greasewood, cacti and catclaw.

N.0°03'W. bet. secs. 7 and 8.

Over mountainous land, through scattered undergrowth.

Asc. 135 ft. along crest of small spur, sloping S.

- 4.40 Shoulder of spur, from NW.. sloping SE. ; desc. 170 ft. over NE. slope.
- 24.60 Draw, course SE.; asc. 65 ft.
- 27.30 Point of spur, slopes SE.; desc. 25 ft.
- 32.50 Draw, course SE.; asc. 195 ft. over SE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground. for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 7 | S 8

1932

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Asc. 80 ft.

- 45.90 Flat spur, slopes E.; desc. 325 ft. over NE. slope.
- 64.80 Draw, small-flow of water. course S.80°E.; asc. 60 ft.

chains

- 67.00 Point of spur, from small conical peak, slopes S.60°E. Along E. slope.
- 70.80 Draw, course S.30°E.; asc. 195 ft. over SW. and S.slopes.
- 79.50 Flat spur, slopes SE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 5, 6, 7 and 8, with brass cap mkd.

T9N	R3W.
S 6	S 5
S 7	S 8

1932

Land, rolling mountains.
 Soil, rocky, 3rd. rate.
 No timber; undergrowth, greasewood, catclaw, chaparral and cacti.

 N.89°54'E. on a random line bet. secs. 5 and 8.

- 40.00 Set temp. 1/4 sec. cor.
- 80.18 Intersect N. and S. line 10 lks. S. of the cor. of secs. 4, 5, 8 and 9.

Thence

S.89°50'W. on true line bet. secs. 5 and 8.

Over broken mountainous land, through scattered undergrowth.

Desc. 250 ft. over broken SW. slope.

- 3.50 Gulch, course S.70°W.
- 11.20 Flat spur, slopes SW., change of slope to W.
- 18.60 Draw, course S.; asc. 380 ft. over E. slope.
- 30.70 Spur, extends S.; desc. 235 ft. over SW. slope.
- 37.20 Small draw, course S.; asc. 25 ft.
- 38.25 Point of small spur, slopes S.; desc. 40 ft. over SW. slope.
- 40.09 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4	S 5
S 8	

1932

raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.

Desc. 35 ft.

- 41.35 Draw, course S.10°E.; asc. 120 ft. over SE. slope.
- 45.40 Spur, slopes S.10°E.; desc. 55 ft. over SW. slope.

SUBDIVISION OF T.9 N., R.3 W.

chains

- 47.60 Draw, course S.; asc. 200 ft. over E. slope.
- 54.00 Spur, slopes S.; desc. 230 ft. over SW. slope.
- 59.70 Draw, course S.; asc. 240 ft. over E. slope.
- 74.50 Flat spur, slopes S.; desc. 35 ft. over SW. slope.
- 77.50 Drain, course S.; asc. 50 ft. over E. slope.
- 80.18 The cor. of secs. 5,6,7 and 8.
- Land, broken mountains.
Soil, rocky, 3rd. and 4th. rate.
No timber; undergrowth, greasewood, catclaw, cacti and paloverde.
-
- N.89°58'W. on a random line bet. secs. 6 and 7.
- 40.00 Set temp $\frac{1}{4}$ sec. cor.
- 79.62 Intersect the W. bdy. of Tp. 14 lks. S. of the cor. of secs. 1,6,7 and 12; an iron post, 2 ins. diam., 14 ins. above ground, mkd. and witnessed as described in the official record.
- Thence
- S.89°52'E. on true line bet. secs. 6 and 7.
- Over rolling and mountainous land, through scattered undergrowth.
- 2.70 Wash, 30 lks. wide, course S.60°W.; asc. gradually 80 ft. over SW. slope.
- 11.90 Small draw, course S.30°W.
- 17.20 Small spur, slopes S.; desc. 50 ft.
- 21.40 Draw, course S.30°E.
- 25.70 Wash, 40 lks. wide, course SW.; asc. 175 ft. over NW. slope.
- 36.00 Spur, slopes S.20°W.; desc. 25 ft.
- 38.90 Drain, course S.; asc. 10 ft.
- 39.62 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4} \frac{S 6}{S 7}$
- 1932
- raise a mound
- of stone 3 ft. base, 2 ft. high, N. of cor.
- Asc. 100 ft. over W. slope.
- 46.10 Ridge, bears N. and S.; low saddle bears N. about 5 chs. dist.,
- Desc. 240 ft. over NE. slope:
- 60.75 Draw, course S.60°E.; asc. 55 ft. over SW. slope.

SUBDIVISION OF T.9 N.,R.3 W.

BOOK 3977

- chains
- 67.60 Short spur, slopes S.; desc. 95 ft.
- 71.30 Gulch, course S.; asc. 110 ft. over W. slope.
- 75.00 Change of slope to SW.; asc. gradually.
- 79.00 Low spur, slopes SE.
- 79.62 The cor. of secs. 5,6,7 and 8.

Land, rolling and broken mountains.
 Soil, gravelly and rocky, 3rd. rate.
 No timber; undergrowth, catclaw, greasewood and cacti.

 N.0°03'W. on true line bet.secs. 5 and 6.

Over mountainous land, through scattered undergrowth.
 Asc. 135 ft. over gradual SE. slope.

- 11.70 Small spur, slopes SE.; desc. 70 ft.
- 22.40 Small draw, course S.50°E.; asc. 260 ft. over S. slope.
- 28.50 Rocky dyke, 20 ft. high, upon apex of small spur, sloping S.60°E.; desc. 50 ft.
- 30.00 Head of draw, course E.; along E. slope.
- 37.20 Gulch, course S.60°E.; asc. 75 ft. over SE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4
 S 6 | S 5
 1932

Asc. 120 ft.

- 45.00 Spur, slopes S.70°E.; desc. 90 ft. over NE. slope.
- 54.80 Head of draw, course SE.; asc. 90 ft. over S. slope.
- 59.00 Divide, bears NE. and SW.; desc. 185 ft. over N. slope.
- 73.90 S. Fork of Spring Creek, dry wash 20 lks. wide, course N.80°E.
- Along gradual E. slope; asc. slightly.
- 78.80 Gully, course N.80°E.
- 80.61 Intersect N. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.

T10N R3W
 S 32
 S 6 | S 5
 T9N R3W
 CC
 1932

SUBDIVISION OF T.9 N.,R.3 W.

chains

raise a mound of

stone, 3 ft. base, 2 ft. high, S. of cor.

From point of intersection the cor. of secs. 31 and 32, T.10 N.,R.3 W., bears West 7.84 chs. dist.; an iron post, 2 ins. diam., 36 ins. above ground, supported in a mound of stone to top, properly marked on brass cap.

From the same point the 1/4 sec. cor. on the S. bdy. of sec. 32, T.10 N.,R.3 W., bears East; an iron post, 1 in. diam., 10 ins. above ground, mkd. and witnessed as described in the official record.

Land, rolling and rough mountains.

Soil, rocky. 3rd. and 4th. rate.

No timber; undergrowth, greasewood, cacti, catclaw and chaparral.

RETRACEMENT OF THE S. BDY. OF SEC. 31, T.10 N.R.3 W.

From the cor. of secs. 31 and 32, T.10 N.,R.3 W. and true

West on a random line on the S. bdy. of sec. 31.

39.96 Intersect 1/4 sec. cor.; an iron post, 1 in. diam., 22 ins. above ground, mkd. and witnessed as described in the official record.

Continuing line and measurement:

60.40 Intersect the cor. of Ts.10 N.,Rs. 3 and 4 W.; an iron post, 3 ins. diam., 10 ins. above ground, mkd. and witnessed as described in the official record.

RETRACEMENT OF A PORTION OF THE S. BDY. OF SEC. 36, T.10 N.,R.4 W.

From the cor. of Ts. 10 N., Rs. 3 and 4 W.

and true

West on a random line on the S. bdy. of sec. 36, T.10 N., R.4 W.

11.26 Intersect the closing cor. of Ts.9 N.,Rs. 3 and 4 W.; an iron post, 3 ins. diam., 22 ins. above ground, mkd. and witnessed as described in the official record.

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED MINERAL CLAIMS IN T.9 N.,R.3 W.

Survey No.1259, Silver King Lode.

Cor. No.1 of the Silver King lode, identical with cor. No.1 of the Yankee Boy lode, Survey No.1259, is a granite stone 8 x 6 x 6 ins. above ground, firmly set, marked SK 1 1259 on NW. face, YB 1 on SE. face.

Thence

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N.,R.3 W.

chains	Survey No. 1259, Silver King Lode. Patented N.57°57'W.
20.14	Intersect line bet. secs. 24 and 25, T.9 N., R.3 W.. S.89°48'W. 17.43 chs. dist. from the cor. of secs. 19, 24, 25 and 30.
21.84	Intersect cor. No. 2 of the Silver King, identical with cor. No. 1 of the Crown Point lode, Survey No. 1259; a granite stone 10 x 8 x 6 ins. above ground, firmly set mkd. SK 2 on SE. face, CP 1 1259 on the NE. face. Thence N.25°33'E.
8.92	Intersect cor. No. 3 of the Silver King, identical with cor. No. 4 of the Crown Point lode; a granite stone 10 x 10 x 6 ins. above ground, firmly set, mkd. SK No 3 1259 on SE. face, CP No 4 1259 on the NW. face. Thence S.57°10'E.
16.36	Intersect line bet. secs. 24 and 25, S.89°48'W 1.25 chs. dist. from the cor. of secs. 19, 24, 25 and 30.
17.85	Intersect E. bdy. of Tp. South 0.81 chs. dist. from the cor. of secs. 19, 24, 25 and 30.
21.81	Intersect cor. No. 4, Silver King, identical with cor. No. 4, Yankee Boy lode; a cross (X) on granite ledge 2 ft. high, 6 ft. long, additionally mkd. YB No. 4 1259 on SE. and SK 4 NW. of cross.

	Survey No. 1384, Texas Chief Lode. Patented
	Cor. No. 1 of the Texas Chief, identical with cor. No. 1 of the Copper Prince lode, Survey No. 1384, is a quartz stone 12 x 10 x 8 ins. above ground, firmly set, mkd. 1 1384 TC on the NW. face, 1 CP on the SE. face. U.S.L.M. No. 1384, hereinbefore described, bears S.16°00'W. 10.13 chs. dist., Thence N.78°15'E.
8.82	Intersect cor. No. 4 of the Texas Chief, identical with cor. No. 4, of the Copper Prince lode; a granite stone 12 x 12 x 8 ins. above ground, mkd. 4 1384 CP on SE. face, 4 TC on N. face. Thence N.11°00'W.
3.34	Intersect line bet. secs. 27 and 34, S.89°57'W. 7.94 chs. dist. from the cor. of secs. 26, 27, 34 and 35.
10.98	Fail to find center cor.
21.96	Fail to find cor. No. 3; set. temp. cor. Thence S.79°00'W.

COPPER PRINCE

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N., R.3 W.

chains

9.09 To a point from which cor. No. 2, Texas Chief lode, bears S.12°00'E. 1.52 chs. dist.; a granite boulder, 4 x 2½ x 1½ ft., mkd. 2 1384 TC on the top (no exact point defined, measurement taken to center of lettering).

Thence from Cor.No.2

S.11°43'E.

15.38 Intersect line bet.secs. 27 and 34, S.89°57'W. 16.98 chs. dist. from the cor. of secs. 26, 27, 34 and 35.

20.56 Intersect cor. No.1 and place of beginning.

Survey No.1553, Bellairs Lode.
Patented.

Cor.No.6, Bellairs lode, is a granite stone 12 x 12 x 8 ins above ground, firmly set, mkd. with cross (X) on top, B No 6 1553 on the N. face.

Thence

N.25°57'W.

5.36 Intersect line bet.secs. 2 and 3, T.8 N., R.3 W., S.0°01'E. 1.87 chs. dist. from the closing cor. of secs. 2 and 3.

7.44½ Intersect first stan. par. north, East 1.795 chs. dist. from the standard cor. of secs. 34 and 35, T.9 N., R.3 W.

11.56 Intersect line bet.secs. 34 and 35, T.9 N., R.3 W. N.0°01'W. 3.70 chs. dist. from the standard cor. of secs. 34 and 35. on S. bdy. of Tp.

13.22 Intersect cor. No.5, Bellairs lode; a quartz stone 14 x 10 x 6 ins. above ground, firmly set, mkd. B No 5 1553 on E. face.

Thence

N.60°00'E.

0.84 Intersect line bet.secs. 34 and 35, N.0°01'W. 5.61½ chs. dist. from the standard cor. of secs. 34 and 35.

4.93 Intersect line 1-2. Survey No.1531, Curley lode, N.50°37'W. 3.99 chs. dist. from point for cor. No.1.

5.36 Intersect cor. No.4. Bellairs lode; a granite stone 10 x 8 x 6 ins. above ground, mkd. B No 4 1553 on S. face.

Survey No.1531, Curley Lode.
Patented.

Cor. No.1 of Curley lode being lost, the point therefor is recovered from the record bearing objects:

A granite rock in place; 3 x 3 x 1 ft. above ground, mkd. B X R on top, C No 1 1531 on NW. face, bears S.9°W. 20 lks. dist.

A granite rock in place. 2 x 1½ x 1 ft. above ground, mkd. B X R on top, C No 1 1531 on NW. face, bears S.66½°W. 39 lks. dist.

Thence

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N., R.3 W.

BOOK 3977

chains

N.50°37'W. on a random line

3.99 Intersect line 4-5, Survey No.1553. Bellairs Lode. ✓
S.60°00'W. 0.43 chs. dist. from cor. No.4.

8.58 Intersect line bet.secs. 34 and 35. N.0°01'W. 10.57 chs.
dist., from the standard cor. of secs. 34 and 35.

18.70 Intersect cor. No.2, Curley Lode; a granite stone 14 x
12 x 9 ins. above ground, firmly set, mkd. C No 2 1531
on NE. face, and witnessed as described in the official
record.

Thence

N.19°40'W.

9.02 Intersect cor. No.3, Curley Lode; a granite stone 14 x
12 x 8 ins. above ground, firmly set, mkd. WCE C No 3
1531 on SE. face.

Thence

N.34°05'E.

4.48 Intersect cor. No.4, Curley Lode; a granite stone 14 x
10 x 6 ins. above ground, firmly set, mkd. C No 4 1531
on SW. face.

Thence

S.43°55'E.

12.08 Intersect line bet.secs. 34 and 35, N.0°01'W. 20.525 chs.
dist. from the standard cor. of secs. 34 and 35.

14.12 Intersect cor. No. 5, Curley Lode; a quartz stone 10 x
8 x 8 ins. above ground, firmly set, mkd. C No 5 1531
on NW. face, and witnessed as described in the official
record.

Survey No. 1531, Keystone Lode.
Patented.

Cor. No.1 of the Keystone lode, identical with Cor.No.2
of Bellairs lode and Cor. No.3 of Homestake lode. is a
granite stone 14 x 12 x 8 ins. above ground, firmly set
mkd. with a cross (X) on top, H No 3 1553 on E.face.
B No 2 1553 on SW face and K No 1 1531 on NE.face.

Thence

N.20°05'W. on a random line

2.45 Point for cor. No.1, Curley Lode, identical with cor.No.
3, Bellairs Lode, bears N.50°37'W. 0.05 chs. dist.

16.985 Cor. No.5, Curley Lode, bears N.43°55'W. 0.39 chs. dist..

21.90 Intersect line bet.secs. 34 and 35, N.0°01'W. 23.375 chs.
dist. from the standard cor. of secs. 34 and 35.

22.31 Intersect cor. No.2, Keystone lode; a granite stone,
16 x 14 x 3 ins. above ground, firmly set, mkd.K No.2
1531 on NE. face, witnessed by a mound of stone W.

Thence

N.60°00'E.

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N., R.3 W.

chains

0.165 Intersect line bet. secs. 34 and 35. N.0°01'W. 23.84 chs. dist. from the standard cor. of secs. 34 and 35.

9.01 Intersect cor. No.3, Keystone Lode, identical with cor. No.2, Survey 1531, Little Dandy Lode; a granite stone 10 x 8 x 6 ins. above ground, firmly set, mkd. with cross (X) on top, K No 3 1531 on SW. face. LD No 2 1531 on NE. face.

SURVEY No. 4060 A & B

Robert Lode

Cor. No.2, Survey No.4060 A, Robert lode, is an igneous stone, 12 x 8 x 6 ins. above ground, firmly set, mkd. with a cross (X) on top, 2 R 4060A on N. face.

Thence

N.64°00'W.

0.84 Intersect line bet. secs. 33 and 34, N.0°02'W. 50.54 chs. dist. from the standard cor. of secs. 33 and 34, on S. bdy. of Tp.

15.04 Intersect cor. No.3, Little Jim lode; a quartz stone 12 x 10 x 5 ins. above ground, firmly set, mkd. with cross (X) on top, LJ on SW. face.

20.52 Intersect cor. No.3, Robert lode; a granite stone 14 x 12 x 6 ins. above ground, mkd. 3R 4060A on NE. face.

Thence

N.26°00'E.

9.15 Intersect cor. No.4, Robert lode, identical with cor. No.3, Cable lode, and cor. No.2, Bennett lode; a quartz stone 10 x 8 x 6 ins. above ground, firmly set, mkd. with a cross (X) on top, 4R 4060A on SW. face. B2 on N. face.

Bennett Lode.

Thence from the last named corner,

N.51°35'W.

20.41 Intersect line bet. secs. 28 and 33, S.89°56'W. 29.74 chs. dist. from the cor. of secs. 27, 28, 33 and 34.

22.70 Intersect cor. No. 3, Bennett lode; a granite stone 12 x 10 x 8 ins. above ground, firmly set, mkd. 3B 4060A on SE. face.

Cable Lode.

From cor. No.3, Cable lode, hereinbefore described.

N.26°00'E.

9.09 Intersect cor. No. 4, Cable lode, identical with cor. No. 1, Bennett lode, cor. No.2, Gilbreth lode and cor. No.3, Black Bear lode; a quartz stone 12 x 10 x 8 ins. above ground, firmly set, mkd. with a cross (X) on top, 3BB 4060A on E. face, 4C on S, 1B on W. and 2G on N. faces.

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N., R.3 W.

chains	SURVEY No. 4060 A & B. Black Bear Lode.
	Thence N. 26° 00' E.
5.02	Intersect line bet. secs. 28 and 33, S. 89° 56' W. 7.53 chs. dist. from the cor. of secs. 27, 28, 33 and 34.
9.11	Intersect cor. No. 4, Black Bear lode, identical with cor. No. 1, Gilbreth lode, cor. No. 2, White Blaze lode and cor. No. 3, Homestake lode; a granite stone 16 x 12 x 12 ins. above ground, firmly set, mkd. 4BB on SE, G1 4060A on SW, WB2 on NW, and 3H on NE. faces.
	Homestake Lode.
	Thence N. 26° 00' E.
7.52	Intersect cor. No. 1, White Blaze lode; a granite stone 12 x 8 x 6 ins. above ground, firmly set, mkd. 1WB 4060A on W. face.
9.14	Intersect cor. No. 4, Homestake lode; a granite stone 10 x 8 x 8 ins. above ground, firmly set, mkd. with cross (X) on top, 4H 4060A on SE. face.
	Thence S. 64° 00' E.
1.505	Intersect cor. No. 2, Charm lode; a granite stone 12 x 10 x 8 ins. above ground, mkd. with cross (X) on top. 2C 4060A on N. face.
1.945	Intersect line bet. secs. 27 and 28, N. 0° 02' W. 10.97 chs. dist. from the cor. of secs. 27, 28, 33 and 34.
10.595	Intersect cor. No. 1, Charm lode, identical with cor. No. 2 Fob lode; a granite stone 10 x 10 x 8 ins. above ground, firmly set, mkd. with cross (X) on top. C1 on W., and 2F 4060A on E. faces.
19.685	Intersect cor. No. 1, Fob lode; a quartz stone 10 x 10 x 8 ins. above ground, firmly set, mkd. with cross (X) on top. F1 4060A on E. face.
22.715	Intersect cor. No. 1, Homestake lode, identical with cor. No. 4, Buttons lode; a granite stone 10 x 9 x 6 ins. above ground, firmly set, mkd. with cross (X) on top, 1H on W. and 4B 4060A on E. faces.
	Buttons Lode.
	Thence from the last named cor. S. 52° 58' E.
3.09	Intersect line bet. secs. 27 and 34, N. 89° 57' E. 21.16 chs. dist. from the cor. of secs. 27, 28, 33 and 34.
22.73	Intersect cor. No. 1, Buttons lode; a granite stone 14 x 12 x 6 ins. above ground, firmly set, mkd. with cross (X) on top. 1B 4060A on SW. face.
	The Home Lode.
	Cor. No. 4, The Home lode is a quartz stone 12 x 8 x 6 ins. above ground, firmly set, mkd. with cross (X) on top; TH4 4060A on NW. face.

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N., R.3 W.

chains	
	SURVEY No.4060 A & B. The Home Lode.
	Thence
	S.20°36'W.
3.85	Intersect line bet.secs. 27 and 34, S.89°57'W. 1.97 chs. dist. from the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
9.05	True point for cor. No.1, The Home lode.
	Thence
	N.53°00'W.
0.165	Intersect witness cor. to true point for cor. No.1, The Home lode; a granite stone 10 x 8 x 6 ins. above ground, firmly set, mkd. with cross (X) on top, WC No.1TH 4060A on NW. face.
8.10	Intersect line bet.secs. 27 and 34, S.89°57'W. 10.28 chs. dist. from the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
22.72	Intersect cor. No.2, The Home lode; a granite stone 12 x 10 x 5 ins. above ground, firmly set, mkd. 2TH 4060A on SE. face.
	Fob Lode.
	Thence from the last named cor.
	S.19°45'W. on E. side line of Fob lode.
5.99	Intersect cor. No.1, Fob lode, hereinbefore described.
	Charm Lode.
	From cor. No.2, Charm lode, hereinbefore described.
	N.19°45'E.
1.14	Intersect line bet.secs. 27 and 28, N.0°02'W. 12.24 chs. dist. from the cor. of secs. 27, 28, 33 and 34.
22.75	Intersect cor. No.3, Charm lode; a granite stone 12 x 10 x 8 ins. above ground, mkd. with cross (X) on top. 3C 4060A on S. face.
	White Blaze Lode.
	From cor. No.1, White Blaze lode, hereinbefore described.
	N.11°55'E.
11.93	Intersect line bet.secs. 27 and 28, N.0°02'W. 22.04 chs. dist. from the cor. of secs. 27, 28, 33 and 34.
14.58	Intersect cor. No.5, White Blaze; a quartz stone 10 x 8 x 6 ins. above ground, firmly set, mkd. with cross (X) on top, 5WB 4060A on SW. face.
	Thence
	N.51°35'W.
0.70	Intersect line bet.secs. 27 and 28, N.0°02'W. 25.065 chs. dist. from the cor. of secs. 27, 28, 33 and 34.
10.15	Intersect cor. No.4, White Blaze lode; a granite stone

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N.,R.3 W.

BOOK 3971

chains

SURVEY No.4060 A & B.

White Blaze Lode.

8 x 8 x 6 ins. above ground, mkd. 4WB 4060A on SE.face.

Survey No.1623, Rosalind Lode.
Patented.

Cor. No.1, Rosalind lode, is a pine post, 4 ins. square.
3 ft. above ground, and in a mound of stone, mkd.
1 1623 on NW. face.

Thence

N.59°45'W.

0.83 Intersect 2nd. standard parallel north. East 25.93 chs.
dist. from the stan. cor. of secs. 32 and 33, and West
14.15 chs. dist. from the stan. $\frac{1}{4}$ sec. cor. on S. bdy.
of sec. 33, T.9 N.,R.3 W.

U.S.L.M. No. 1623 bears N.23°45'W. 1.36 chs. dist.; an
iron post, 3 ins. diam., 3 ft. above ground, supported
in a mound of stone 5 ft. base, 3 ft. high. mkd. on
brass cap

USLM
No
1623

1929

6.23 Intersect cor. No.1. Survey No.1974, Cacti lode; a pine
post, 4 ins. square, 3 ft. above ground, mkd. C No 1
1974 on NW. face.

22.63 Intersect cor. No.2 Rosalind lode; a pine post, 4 ins.
square, 2 $\frac{1}{2}$ ft above ground, mkd. 2 1623 on SE. face.

Thence

S.30°05'W.

8.99 Intersect cor. No.3, Rosalind lode; a pine post, 4 ins.
square, 2 $\frac{1}{2}$ ft. above ground, in a mound of stone, mkd.
3 1623 on NE. face.

Thence

S.59°45'E.

6.30 Intersect 2nd. standard parallel north, East 8.06 chs.
dist. from the stan. cor. of secs. 32 and 33, T.9 N.
R.3 W.

22.65 Intersect cor. No.4, Rosalind lode; a pine post, 4 ins.
square, 3 ft. above ground, in a mound of stone, mkd.
4 1623 on N. face.

Survey No.1974, Cacti Lode.
Patented.

From cor. No.2, Rosalind lode, hereinbefore described.

N.59°45'W.

2.06 Intersect cor. No.6, Cacti lode; a rotted pine stake in
a mound of stone.

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N., R.3 W.

chains

Survey No.1974, Cacti Lode.

Thence

N.25°15'E.

1.40 Intersect cor. No.5, Cacti lode; a pine post, 4 ins. square, 2½ ft. above ground, in a mound of stone, mkd. C5 1974 on SE. face.

Thence

N.64°15'W.

4.045 Intersect cor. No.4, Cacti lode; a pine post, 4 ins. square, 3 ft. above ground, in a mound of stone. mkd. C4 1974 on NE. face.

Thence

N.31°50'E.

5.75 Intersect cor. No.3, Cacti lode; a pine post, 4 ins. square, 3½ ft. above ground, in a mound of stone, mkd. C3 1974 on SW. face.

From cor. No.1, Cacti lode, hereinbefore described.

N.31°50'E.

6.21 Intersect cor. No.2, Cacti lode; a dilapidated mound of stone, from which
A granite ledge, 4 ft. high, mkd. X BR 1974 C2 bears S.57½°W. 54 lks. dist.,
A granite boulder, 6 x 6 x 5 ft. mkd. with cross (X) bears S.11°E. 78 lks. dist.

Survey No.1974, Gold Bug No.2, Lode.
Patented.

Cor. No.1. Gold Bug No.2 lode, identical with cor. No.1. Survey No.1624, Olympia lode, is a pine post, 4 ins. square, 3½ ft. above ground, in a mound of stone, with markings illegible.

Thence

N.58°12'W.

10.62 Intersect cor. No.3, Survey No.1974, Cacti lode, hereinbefore described.

16.835 Intersect line bet. secs. 32 and 33, N.0°02'W. 23.18 chs. dist. from the standard cor. of secs. 32 and 33, on S. bdy. of Tp.

22.60 Intersect cor. No.2, Gold Bug No.2 lode; a partially rotted pine post, 4 ins. square, 3½ ft. long, in a dilapidated mound of stone.

Thence

N.32°00'E.

9.03 Intersect cor. No.3, Gold Bug No.2 lode; a pine post, 4 ins. square, 3 ft. above ground, in a mound of stone, mkd. 3 1974 GB No2 on SW. face.

Cor. No.4, Gold Bug No.2, lode, bears S.58°12'E.; a pine post, 4 ins. square, 3 ft. above ground, in a mound of stone.

RETRACEMENT OF A PORTION OF THE LINES OF SURVEYED

MINERAL CLAIMS IN T.9 N.,R.3 W.

chains

Survey No.1974, Gold Bug No.2 Lode.

S.58°12'E.

0.12 Intersect line bet.secs. 32 and 33, N.0°02'W. 33.83 chs. dist. from the standard cor. of secs. 32 and 33. on S. bdy. of Tp.

Measurement of line 3-4, Gold Bug No.2 lode, was not extended beyond this point.

Survey No.1624, Olympia Lode.
Patented.

From cor. No.1, Survey No.1624, Olympia lode, identical with cor. No.1, Survey No.1974, Gold Bug No.2 lode, hereinbefore described.

S.58°12'E.

11.97 Intersect cor. No.2, Survey No.1974, Cacti lode, hereinbefore described.

22.54 True point for cor No.2, Olympia lode, identical with cor. No.4, Survey No.1973, Olympia Extension. Witness cor. bears N.31°30'E. 0.61 chs. dist.; a partially rotted stake, 4 ins. square, supported in a mound of stone.

Survey No.1973, Olympia Extension.
Patented.

From true point for cor No.4, Olympia Extension, above described.

S.58°12'E.

4.64 Intersect 2nd. stan. par. north. West 2.62 chs. dist. from the stan. 1/4 sec. cor. on S. bdy. of sec. 33. T.9 N. R.3 W.

5.72 Intersect cor. No.1, Olympia Extension; a pine post. 4 ins. square, 3 ft. above ground, in a mound of stone mkd. 1 1973

Thence

N.31°30'E.

0.67 Intersect 2nd. standard parallel north. West 1.35 chs. dist. from the stan. 1/4 sec. cor. on S. bdy. of sec.33. T.9 N.,R.3 W.

Measurement of line 1-2, Olympia Extension, was not extended beyond this point.

FINAL TEST OF SOLAR ATTACHMENT.

Feb. 7,1932. At camp in sec.21,T.9 N.,R.3 W. at 8h.0m. a.m., appt. t., I set off 34°06 1/4'N. on the lat.,arc; 15°30'S. on the decl. arc, and orient the instrument with the solar; the line of sight agrees with the meridian established by Polaris observation.

At 4h.0m.p.m.,appt.t.,with the lat. arc unchanged, I set off 15°23'S. on the decl. arc, and repeat the test of the solar; the line of sight agrees with the true meridian.

GENERAL DESCRIPTION.

The land in T.9 N., R.3 W. varies from a rolling to a broken mountainous formation, lying in elevation from 2500 ft. to slightly over 5000 ft. above sea level. The soil is a rocky formation of poor quality and shallow depth. There is a scattered growth of desert verdure, paloverde, mesquite, greasewood, cacti and catclaw, some willow and cottonwood timber borders the Hassayampa River, which flows through the township in a southwesterly direction, and along some of the north slopes of the hills and ridges dense patches of scruboak, mahogany and chaparral predominate.

The land is utilized entirely for grazing, goat culture being the principal activity at the present time. A small ranch, occupied by Mr. Goodwin, is situated at the end of the road in section 21, adjacent to the river. Due to the rough character of the country no agricultural development is possible, or has ever been attempted.

There is little live water within the township, Iron Springs, in section 36, drains a small flow of water into Hawk Springs Gulch, a small spring has been developed near the quarter section corner on the south boundary of section twenty one furnishing water for the Goodwin ranch needs, a well and pump in O'Brien Gulch furnishes water for the current needs of those resident there on The Home Claim, a well and pumping station on the Brunton Mill Site, adjacent to the river, furnished the water supply of the Gold Bar Mines during those periods of active operation.

Mining activity lies dormant; the largest development, that of the Gold Bar, formerly known as the O'Brien, mine situated in secs. 27, 28, 33 and 34, has been extensive in outlay but restricted in production. Patented areas lie in sections 20, 32, 33, 34 and 35, all idle and the improvements thereon fallen into a condition of disuse and dilapidation. Some isolated and sporadic prospecting is under way along the river bottom, where marginal sands are being washed in search of color.

4-680
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Howard Beard	1st. chairman.
Sam Palmer	2nd. chairman.
Kenneth Linscott	2nd. chairman.
A. F. Gray	Cornerman.
J. D. Harris	Axman.
J. D. Waring	Flagman.
Kenneth Linscott	Flagman.

CERTIFICATE OF UNITED STATES SURVEYOR

I, Dupree R. Averill, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona, bearing date of the 6th day of October, 1931, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, retraced ~~all those parts or portions of~~ part of the south boundaries of T.10 N., Rs. 3 and 4 W.; surveyed the subdivisional lines of T.9 N., R. 3 W.; and retraced mining claim boundaries in said township of the Gila and Salt River Base & Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of and retracement said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey and retracement.

May 4, 1932. San Francisco, California.

Dupree R. Averill U. S. Surveyor.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, MAR 20 1933, 19

The foregoing field notes of the ~~survey of~~ retracement of part of the south boundaries of T.10 N., Rs. 3 and 4 W.; the survey of the subdivisional lines of T.9 N., R. 3 W.; and the retracement of mining claim boundaries in said township of the Gila and Salt River Meridian, in the State of Arizona,

executed by Dupree R. Averill, U. S. Surveyor,

under his special instructions dated October 6, 1931, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the survey and retracements they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.