

Book F.

BOOK 3992

FIELD NOTES

OF THE SURVEY OF THE

subdivisional lines

of

township 34 North, Range 16 West,

3992

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

William E. Hiester, U.S. Surveyor

3992

In the capacity of U. S. Surveyor, under Special Instructions dated December 21, 1932, issued by the District Cadastral Engineer to govern surveys included in Group No. 169, which were approved by the Commissioner of the General Land Office, March 7, 1932, and Assignment Instructions dated Jan. 27, 1933.

Survey commenced February 2, 1933.

Survey completed February 27, 1933.

INDEX DIAGRAM.

Township _____, Range _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
29	28	26	27	26	25
31	32	33	34	35	36

Chains.

The survey was executed by William E. Hiester U. S. Surveyor, with a light mountain transit made by Buff and Buff, Serial No. 19423, constructed in accordance with the standard specifications of the General Land Office. For description and tests of instrumental equipment and for preliminary observations, see field notes of the resurvey of a portion of the Arizona and Nevada State Boundary, resurveyed under this group.

I commence the subdivisional survey at the cor. of secs. 1, 2, 35, and 36 on the S. bdy. of the Tp.

N.0°01'W., bet. secs. 35 and 36.

Over rolling land, through scattered desert growth.

Along top of spur, slopes NW.

- 4.00 Leave spur.; desc. 63 ft. over NE. slope.
- 9.41 Wash, 20 lks. wide, course NW.; asc. 52 ft. over SW. slope.
- 16.00 Spur, slopes NW.; desc. 50 ft. over NE. slope.
- 20.57 Wash, 10 lks. wide, course W.; asc. 34 ft. over S. slope.
- 25.00 Spur, slopes W.; desc. 105 ft. over NW. slope.
- 32.65 Wash, 10 lks. wide, course W.; asc. 20 ft. over S. slope.
- 36.80 Spur, slopes W.; desc. 20 ft. over NW. slope.
- 40.00 True point for $\frac{1}{4}$ sec. cor. falls in wash. 50 lks. wide. course W.
- 41.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a limestone, 6 x 6 x 8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S35 | S36
 W C
 1933

Ascend 8 ft.

- 42.00 Spur, slopes W.; desc. 20 ft. over NW. slope.
- 45.65 Seven Springs Wash, 100 lks. wide, course SW.; asc. 72 ft. over SE. slope.
- 59.00 Spur, slopes W.; continue along W. slope.
- 66.00 Wash, 3 lks. wide, course W.; asc. 29 ft. over S. slope.
- 73.00 Spur, slopes W.
- 77.50 Wash, 5 lks. wide, course W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with a limestone, 12x10x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 25, 26, 35, and 36, with brass cap mkd.

Chains

T34N R16W	
S 26	S 25
S 35	S 36
1933	

Land, rolling.
Soil, gravelly; 3rd rate.
Timber, none; undergrowth, cactus, joshua, catclaw and greasewood.

East on a random line bet. secs. 25 and 36.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.08 Intersect E. bdy. of Tp. 3 lks. S. of the cor. of secs. 25, 30, 31, and 36,
- Thence
- S. 89° 59' W., on a true line bet. secs. 25 and 36.
- Over rolling land, through scattered desert growth.
- 5.68 Wash, 10 lks. wide, course NW.; asc. 24 ft.
- 10.08 Spur, slopes N.; desc. 18 ft. over NW. slope.
- 17.28 Same wash, 10 lks. wide, course SW.; asc. 67 ft. over SE. slope.
- 38.08 Spur, slopes SE.; continue along same.
- 40.04 Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the ground to bedrock, with a limestone 15x12x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 25
S 36
1933

- 42.10 Leave spur, slopes SW.; desc. 23 ft. over NW. slope.
- 49.78 Wash, 10 lks. wide, course SW.; asc. 24 ft. over SE. slope.
- 80.08 The cor. of secs. 25, 26, 35, and 36.
- Land, rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, catclaw, cactus, joshua and greasewood.

N. 0° 01' W., bet. secs. 25 and 26.

- Over rolling land, through scattered desert growth.
- 3.30 Head of wash, course SW.
- 9.90 Wash near head, course SW.; asc. 10 ft.
- 11.70 Low spur, slopes SW.; desc. 17 ft.
- 14.78 Wash, 10 lks. wide, course SW.; asc. 46 ft. over SE. slope.

Chains

- 19.00 Continue over bench land.
 - 40.00 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a limestone, 10x10x12 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- $\frac{1}{4}$
 S26 | S25
 1933
- 45.00 Leave bench land, bears E. and W.; desc. 102 ft. over NW. slope.
 - 50.33 Old road, bears E. and W.
 - 51.62 Wash, 50 lks. wide, course W.; asc. 22 ft. over S. slope.
 - 56.00 Spur, slopes W.
 - 57.84 Wash, 20 lks. wide, course SW.; asc. 128 ft. over SE. slope.
 - 65.00 Spur, slopes W.; desc. 132 ft. over E. slope.
 - 72.32 Wash, 5 lks. wide, course NW.; asc. 80 ft. over SW. slope.
 - 76.90 Spur, slopes W.; desc. 41 ft. over NW. slope.
 - 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 10x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 23, 24, 25, and 26, with brass cap mkd.

T34N R16W
 S 23 | S 24
 S 26 | S 25
 1933

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, joshua, cactus, catclaw and greasewood.

- N. 89° 59' E., on a random line, bet. secs. 24 and 25.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.14 Intersect E. bdy. of Tp., 7 lks. S. of the cor. of secs. 19, 24, 25, and 30.
- Thence
- S. 89° 56' W., on a true line bet. secs. 24 and 25.
- Over rolling land, through scattered desert growth.
- Ascend 23 ft. over NE. slope.
- 2.00 Low spur, slopes N.; desc. 57 ft. over NW. slope.

SUBDIVISION OF T. 34 N., R. 16 W.

Chains.
 16.10 Wash, 30 lks. wide, course W.; continue along same.
 18.10 Leave wash, course NW.; asc. 13 ft.
 19.80 Top of ascent; desc. 30 ft. over NW. slope.
 24.00 Same wash, course SW.; asc. 38 ft. over SE. slope.
 40.07 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor. with brass cap, mkd.

$\frac{1}{4}$ S 24
 S 25
 1933

raise a mound
 of stone, 3 ft. base, 2 ft. high, N. of cor.
 Ascend 54 ft. over SE. slope.

47.80 Spur, slopes SW.; continue along N. slope.
 62.80 Descend 153 ft. over NW. slope.
 72.28 Wash, 10 lks. wide, course W.; continue along same.
 75.80 Leave wash, course NW.; asc. 17 ft.
 76.50 Spur, slopes N. desc. 21 ft. over NW. slope.
 80.14 The cor. of secs. 23, 24, 25, and 26.

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, joshua, cactus and grease-
 wood.

N.0°01'W., bet. secs. 23 and 24.

Over rolling and mountainous land, through scattered
 desert growth.

2.20 Wash, 10 lks. wide, course SW.; asc. 103 ft. over SE.
 slope.
 12.50 Spur, slopes SW.; desc. 33 ft. over NW. slope.
 16.00 Wash near head, course SW.; asc. 6 ft.
 19.00 Wash, 5 lks. wide, course SW.; continue along same.
 24.30 Leave wash, from NE.; asc. 77 ft. over SE. slope.
 32.00 Spur, slopes SW.; desc. 23 ft. over NW. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S23 | S24

1933

raise a mound of
 stone, 3 ft. base, 2 ft. high, W. of cor.

- Chains. Descend 14 ft. over NW. slope.
- 41.70 Wash, 3 lks. wide, course W.
- 49.00 Low spur, slopes W; desc. 164 ft. over N. slope.
- 62.00 Wash, 10 lks. wide, course W.; from this point a spring 12 ins. wide, bears S.75°E. 300 lks. dist.
- 62.50 Trail, bears E. and W.
- 66.00 Point of spur, slopes W.; desc. 29 ft. over NW. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 13,14,23, and 24, with brass cap mkd.

T34N R16W
S 14 | S 13
 S 23 | S 24
 1933

Land, rolling and mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, cactus, black brush, catclaw and joshua.

- N.89°56'E., on a random line bet. secs. 13 and 24.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.20 Intersect E. bdy. of Tp., 5 lks. N. of the cor. of secs. 13,18,19, and 24.
- Thence
- S.89°58'W., on a true line bet. secs. 13 and 24.
- Over rolling land, through scattered desert growth.
- Descend 76 ft. over broken SW. slope.
- 8.56 Wash, 20 lks. wide, course NW.; asc. 131 ft. over broken NE. slope.
- 28.20 Spur, slopes NW; continue along rimrocks, and top of spur.
- 38.20 Leave spur, slopes NW.
- 40.10 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a limestone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 13
 S 24
 1933

- 42.43 Head of wash, course NW.
- 45.20 Spur, slopes NE.; continue along same.
- 57.20 Leave spur, slopes N.; desc. 67 ft. over SW. slope.
- 66.73 Wash, 10 lks. wide, course NW.; asc. 27 ft. over NE. slope.
- 68.20 Spur, slopes N.; desc. 84 ft. over NW. slope.

Chains.
 72.20 Enter wash, *from* NE.
 76.00 Leave wash, course NW.
 79.70 Low spur, slopes NE.
 80.20 The cor. of secs. 13,14,23, and 24.
 Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth black greasewood, cactus and joshua.

N.0°01'W., bet. secs. 13 and 14.

Over rolling land, through scattered desert growth.

1.50 Enter Grand Wash, course SW; continue along same.
 18.10 Leave same; asc. 52 ft. over SE. slope.
 20.10 Ledge, 8 ft. high.
 22.50 Road, bears E. and W.; continue over bench land.
 31.00 Leave bench, bears NE. and SW.; desc. 32 ft.
 35.20 Wash, 20 lks. wide, course SW; asc. 32 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
 †
 S14 | S13
 1933
 raise a mound of stone, 3 ft. base, 2 ft. high. W. of cor.
 Ascend 34 ft. over SE. slope.
 45.00 Spur, slopes E.
 50.00 Wash, 15 lks. wide, course SE.; asc. 61 ft. over SW. slope.
 57.30 Spur, slopes SW.; desc. 26 ft.
 62.60 Same wash, course SW.; asc. 174 ft. over SE. slope.
 71.80 Top of rimrocks, 15 ft. high, bears NE. and SW.; continue over level land.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground to bedrock, with a limestone, 8x4x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 11,12,13, and 14, with brass cap mkd.

T34N R16W
 S 11 | S 12
 S 14 | S 13
 1933

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, joshua, catclaw and cactus.

Chains. N.89°58'E., on a random line bet. secs. 12 and 13.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.22 Intersect E. bdy. of Tp., 4 lks. S. of the cor. of secs. 7,12,13, and 18.

Thence

S.89°56'W., on a true line bet. secs. 12 and 13.

Over level bench land.

26.22 Leave bench land, bears NE and SW; desc. 168 ft. over NW. slope.

26.72 Top of white ledge, 20 ft. high, bears NE and SW.

28.22 Top of rimrocks, 30 ft. high, bears NE, and SW,

31.22 Wash, 20 lks. wide, course SW.

38.42 Wash, 5 lks. wide, course SE.; asc. 13 ft.

40.11 Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground to bedrock, with a lava stone, 16x12x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 12.
S 13
1933

Ascend 112 ft. over NE. slope.

44.12 Ledge, 10 ft. high.

51.22 Top of white ledge, 20 ft. high. bears SE. and NV.; continue over level land.

73.72 Same ledge, bears NW. and SE.; desc. 92 ft. over SW. slope.

77.58 Head of wash, course SE.; asc. 92 ft. over SE. slope.

79.02 Top of same ledge, bears NE. and SW.; continue over level land.

80.22 The cor. of secs. 11,12,13, and 14.

Land, level and rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, cactus. catclaw and joshua.

N.0°01'W., bet. secs. 11 and 12.

Over level land, through scattered desert growth.

4.00 Head of wash, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Chains.

S11 | S12

1933

45.00 Top of rimrocks, bears NE. and SW.; desc. 189 ft. over broken NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd.

T34N R16W

S 2 | S 1

S 11 | S 12

1933

Land level and rolling.

Soil, sandy; 3rd rate.

Timber, none; undergrowth, sage, cactus, catclaw and joshua.

N. 89° 56' E., on a random line bet. secs. 1 and 12.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.24 Intersect E. bdy. of Tp., 9 lks. S. of the cor. of secs. 1, 6, 7, and 12.

Thence

S. 89° 52' W., on a true line bet. secs. 1 and 12.

Over rolling land, through scattered desert growth.

Descend 102 ft. over broken NW. slope.

5.99 Wash; 15 lks. wide. course SW.; asc. 225 ft. over broken SE. slope.

30.54 Top of ascent; continue over bench land.

40.12 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a lava stone, 10x10x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

+ S 1

S 12

1933

64.24 Leave bench land, bears N. and S.; desc. 279 ft. over W. slope.

66.94 Top of rimrocks, 20 ft. high, bears N. and S.

80.24 The cor. of secs. 1, 2, 11, and 12.

Land, rolling and level.

Soil, sandy; 3rd rate.

Timber, none; undergrowth, joshua, cactus and catclaw.

Chains. N.0°01'W., on a random line bet. secs. 1 and 2.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.17 Intersect N. bdy. of Tp. 37 lks. W. of the cor. of secs. 1, 2, 35 and 36.

Thence

S.0°15'W., on a true line bet. secs. 1 and 2.

Over rolling land, through scattered desert growth.

7.57 Wash, 200 lks. wide, course SW.; asc. 14 ft.

26.71 Road, bears NE. and SW.

40.17 Set an iron post, 3 ft. long, 1 min. diam., 13 ins. in the ground to bedrock, with a lava stone, 10x12x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 2 | S 1
 1933

42.77 Road, bears NE. and SW.

46.17 Continue along W. slope of spur.

49.67 Wash, 3 lks. wide, course SW.; asc. 23 ft. over NW. slope.

57.60 Spur, slopes W.; desc. 18 ft.

63.11 Wash, 5 lks. wide, course SW.; asc. 18 ft.

65.17 Top of ascent; desc. 46 ft. over SW. slope.

74.00 Continue along W. slope.

80.17 The cor. of secs. 1, 2, 11, and 12.

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, joshua and catclaw.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.

N.0°01'W., bet. secs. 34 and 35.

Over rolling land, through scattered desert growth.

.10 Trail, bears E. and W.; desc. 81 ft. over broken NW. slope.

7.40 Wash, 20 lks. wide, course SW.; small spring bears E. 20 lks. dist.

8.80 Ed Yates barn, bears W. 15 lks. dist.

8.90 Corral, bears E. 100 lks. dist.

9.00 Road, bears E. and W.

9.10 Fence, bears E. and W.

9.60 Ed Yates, house, bears E. 400 lks. dist.

Chains	
11.38	Seven Springs, bears S.61 $\frac{1}{2}$ °E., 7.00 chs. dist.
11.40	Small spring bears E. 30 lks. dist.; asc. 22 ft. along broken W. slope.
12.40	Trail, bears E. and W.
21.80	Same trail, bears NE. and SW.
27.00	Descend 45 ft. over NW. slope.
29.30	Wash, 20 lks. wide, course SW.; asc. 62 ft. over SE. slope.
34.00	Continue along W. slope.
34.13	Spring, bears S.50°E., 15.00 chs. dist.; desc. 13 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 12x12x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 34 S 35 1933
41.00	Small clearing bears E. 5.00 chs. dist.; desc. 21 ft.
42.00	Wash, 100 lks. wide, course W.
44.90	Fence, bears NE. and SW.
46.00	A lava rock, on line, 6x6x4 ft. above ground, mkd. with Indian Hieroglyphics on E. and W. faces.
54.00	Enter Grand Wash, 400 lks. wide, course SW.; continue along bottom of same.
80.00	True point for cor. of secs. 26, 27, 34 and 35, falls in channel of Grand Wash.
	At a point N.89°56'W., 70 lks. dist., from true point for cor. of secs. 26, 27, 34, and 35.
	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for witness cor. of secs. 26, 27, 34, and 35, with brass cap mkd.
	T34N R16W S 27 S 26 WC S 34 S 35 1933
	raise a mound of
	stone, 3 ft. base, 2 ft. high W. of cor.
	Land, rolling.
	Soil, sandy; 3rd rate.
	Timber, none; undergrowth catclaw, cactus and joshua.

Chains. From true point for cor. of secs. 26, 27, 34, and 35.
East on a random line bet. secs. 26 and 35.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.82 Intersect N. and S. line 7 lks. S. of the cor. of secs. 25, 26, 35, and 36.

Thence

S. 89° 57' W., on a true line bet. secs. 26 and 35.

Over rolling land, through scattered desert growth, along top of spur,

4.50 Leave spur, slopes SW.; desc. 14 ft. over NW. slope.

12.80 Wash, 5 lks. wide, course SW.; asc. 14 ft. over SE. slope.

21.00 Spur, slopes SW.; desc. 30 ft. over NW. slope.

26.25 Wash, 5 lks. wide, course SW.; asc. 7 ft.

39.91 Set an iron post, 3 ft. long, 1 in. diam., on bedrock with a limestone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 26
S 35
1933

54.00 Top of rimrocks, 20 ft. high, bears NE. and SW.; desc. 354 ft. over rocky W. slope.

71.82 Enter Grand Wash, course S.

79.82 The true point for cor. of secs. 26, 27, 34, and 35.

Land, rolling and mountainous.
Soil, sandy and rocky; 3rd and 4th rates.
Timber, none; undergrowth, joshua, cactus and catclaw.

N. 0° 01' W., bet. secs. 26 and 27.

Over rolling land, through scattered desert growth.

1.00 Leave Grand Wash, course SW.

7.50 Center of Black Wash, 200 lks. wide, course SE.

37.00 Ascend 46 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a limestone, 6x8x5 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 27 | S 26
1933

Continue over rolling bench land.

42.20 Head of wash, course SW.

SUBDIVISION OF T. 34 N., R. 16 W.

Chains.	
57.50	Road, bears NE. and SW.
62.60	Descend 33 ft. over SW. slope.
63.80	Road, in Cottonwood Wash, 300 lks. wide, course SW.; continue along bottom of wash.
74.70	Leave wash, course SW. ; asc. 24 ft. over SE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 8x10x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 22, 23, 26, and 27. with brass cap mkd. Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, cactus, and greasewood.
	T34N R16W S22 S23 S27 S26 1933
	N. 89° 57' E., on a random line bet. secs. 23 and 26.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 23, 24, 25, and 26.
	Thence
	S. 89° 58' W., on a true line bet. secs. 23 and 26.
	Over rolling land, through scattered desert growth.
	Descend 8 ft.
.90	Wash, 10 lks. wide, course W.; continue along bottom of same.
3.50	Leave wash, course SW.; asc. 37 ft. over SE. slope.
7.10	Point of rocky spur, slopes S; desc. 81 ft. over rocky SW. slope.
13.28	Wash, 12 lks. wide, course S.; asc. 61 ft. over SE. slope.
15.00	Spur, slopes S.; desc. 106 ft. over SW. slope.
19.25	Grapevine, Spring, bears S. 30 lks. dist.; continue along wash 30 lks. wide.
20.22	Creek, 18 ins. wide, course NW.
31.20	Lone cottonwood tree, bears N. 1.50 lks. dist.
36.20	Same wash, course SW.
39.97	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 23 S 26 1933
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Chains.

- 51.50 Enter Grand Wash, course S.
- 53.00 Leave same.; asc. 57 ft. over SE. slope.
- 55.00 Top of ascent; continue over rolling land.
- 55.94 Road, bears N. and S.; desc. 38 ft. over SW. slope.
- 69.93 Cottonwood Wash, 200 lks. wide, course S.; asc. 34 ft. over SE. slope.
- 79.94 The cor. of secs. 22, 23, 26, and 27.


Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, catclaw and joshua.

N.0°01'W., bet. secs. 22 and 23.

Over rolling land, through scattered desert growth.

- 39.95 Wash, 3 lks. wide, course SE.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.



raise a mound


of stone, 3 ft. base, 2 ft. high, W. of cor.

- 42.00 Same wash, course SW.; asc. 68 ft. over SE. slope.

- 69.00 Spur, slopes E.; desc. 40 ft. over NE. slope.

- 78.30 Same wash, 5 lks. wide, course SE.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.



raise a mound

of stone, 3 ft. base, 2 ft. high W. of cor.

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth black sage, cactus and cat-claw.

Chains N.89°58'E., on a random line bet. secs. 14 and 23.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.84 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 13, 14, 23 and 24.
 Thence
 N.89°56'W., on a true line bet. secs. 14 and 23.
 Over rolling land, through scattered desert growth.
 11.40 Grand Wash, 300 lks. wide, course SW.; asc. 47 ft. over SE. slope.
 16.14 Road, bears NE. and SW.
 18.84 Top of ascent; continue over bench land.
 20.74 Road, bears NE. and SW.
 34.84 Road, bears N. and S.
 39.92 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 14
 S 23
 1933

41.44 Leave bench land,; desc. 28 ft. over rolling land.
 42.34 Cottonwood Wash, 300 lks. wide, course SW.
 79.84 The cor. of secs. 14, 15, 22, and 23.
 Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth. black sage, cactus and cat-claw.

N.0°01'W., bet. secs. 14 and 15:

Over rolling land, through scattered desert growth.
 12.00 Wash, 10 lks. wide, course SW.; continue along wash.
 18.00 Leave wash, course SW.; asc. 97 ft. over S. slope.
 28.00 Top of ascent.; continue over level land.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a limestone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S15 | S14

1933

Chains.

49.60

Road, bears E. and W.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with a limestone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 10, 11, 14, and 15, with brass cap mkd.

T34N R16W
S 10 | S 11
S 15 | S 14
1933

Land, rolling and level.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, black sage and cactus.

S. 89°56'E., on a random line, bet. secs. 11 and 14.

40.00

Set temp. 1/4 sec. cor.

79.88

Intersect N. and S. line, 2 lks. N. of the cor. of secs. 11, 12, 13, and 14.

Thence

N. 89°57'W., on a true line bet. secs. 11 and 14.

Over rolling land, through scattered desert growth.

21.38

Top of rimrocks, bears NE. and SW.; desc. 222 ft. over broken NW. slope.

34.88

Old road, bears N. and S.

39.94

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.

S 11
S 14
1933

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

43.58

Cottonwood Wash, 200 lks. wide, course SW.; asc. 81 ft. over SE. slope.

68.48

Top of ascent; continue over level land.

79.88

The cor. of secs. 10, 11, 14, and 15.

Land, rolling and mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw, cactus, joshua and black sage.

N. 0°01'W., bet. secs. 10 and 11.

Over level land, through scattered desert growth.

10.00

Road, bears NE. and SW.

Chains.
40.00

Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the ground to bedrock, with a limestone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\frac{1}{4}$$

S10	S11
1933	

66.00

Continue over rolling land.

68.50

Wash, 20 lks. wide, course SW.; continue along wash.

71.00

Leave wash, from NW.; asc. 46 ft. over SE. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 2, 3, 10, and 11, with brass cap mkd.

T34N R16W	
S 3	S 2
S 10	S 11
1933	

Land, level and rolling.

Soil, sandy and rocky; 4th rate.

Timber, none; undergrowth, black sage and cactus.

S. 89°57'E., on a random line bet. secs. 2 and 11.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

79.86

Intersect the cor. of secs. 1, 2, 11, and 12.

Thence

N. 89°57'W., on a true line bet. secs. 2 and 11.

Over rolling land, through scattered desert growth.

9.66

Road, bears N. and S.

15.74

Cottonwood Wash, 200 lks. wide, course SW.; asc. 105 ft. over SE. slope.

29.86

Top of ascent; continue over bench land.

37.16

New road, bears NE. and SW.

37.76

Old road, bears NE. and SW.

39.93

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 6x4x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\frac{1}{4}$$

S 2	
S 11	
1933	

49.86

Leave bench land, bears NE. and SW.; Asc. 51 ft. over SE. slope.

Chains.

65.71 Spur, slopes SW.
72.86 Wash, 15 lks. wide, course SE.; asc. 29 ft. over SE. slope.

79.86 The cor. of secs. 2,3,10 and 11.

Land, level and rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, black sage and cactus.

N.0°15'E., on a random line bet. secs. 2 and 3.

40.00 Set temp. 1/4 sec. cor.

80.07 Intersect N. bdy. of Tp., 16 lks. E. of the cor. of secs. 2,3,34 and 35.

Thence

S.0°08'W., on a true line bet. secs. 2 and 3.

Over mountainous land, through scattered desert growth.

Descend 35 ft. over NE. slope.

5.17 Wash near head, course NE.; asc. 52 ft. over NW. slope.

7.57 Spur, slopes E.; desc. 220 ft. over broken SE. slope.

28.67 Wash, 5 lks. wide, course E.; asc. 32 ft. over NE. slope.

32.07 Spur, slopes E.; desc. 59 ft. over SE. slope.

37.29 Head of wash, course NE.; asc. 22 ft. over NE. slope.

40.07 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

S 3 | S 2

1933

Ascend 75 ft. over NE. slope.

45.77 Spur, slopes E.; desc. 198 ft. over broken SE. slope.

58.81 Wash, 10 lks. wide, course E.; asc. 76 ft. over NE. slope.

78.57 Spur, slopes E.; desc. 130 ft. over SE. slope.

80.07 The cor. of secs. 2,3, 10 and 11.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw and greasewood.

Chains.	From the cor. of secs. 3,4,33 and 34, on the S. bdy. of the Tp. N.0°02'W., bet. secs. 33 and 34. Over rolling land, through scattered desert growth. .90 Wash, 5 lks. wide, course E. 18.00 Low spur, slopes SE.; desc. 26 ft. over NE. slope. 20.63 Wash, 5 lks. wide, course SE.; asc. 23 ft. over SW. slope. 25.00 Spur, slopes SE.; desc. 34 ft. over NE. slope. 30.00 Wash, 10 lks. wide, course SE. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a lava stone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ S33 S34 1933 50.00 Wash, 5 lks. wide, course SE. 54.00 Wash, 10 lks. wide, course SE.; asc. 44 ft. over SW. slope. 68.00 Spur, slopes SE.; desc. 23 ft. over NE. slope. 77.95 Wash, 15 lks. wide, course SE.; asc. 14 ft. over SW. slope. 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 27,28,33, and 34, with brass cap mkd. T34N R16W S 28 S 27 S 33 S 34 1933 Land rolling. Soil, sandy and rocky; 4th rate. Timber, none; undergrowth, cactus. joshua and catclaw.
40.00	East on a random line bet. secs. 27 and 34. Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect N. and S. line, 9 lks. N. of the true point for cor. of secs. 26,27,34 and 35. Thence N.89°56'W., on a true line bet. secs. 27 and 34. Over rolling land, through scattered desert growth. .20 Right bank of Grand Wash channel, course S. .70 The witness cor. of secs. 26,27,34 and 35, hereinbefore described.

SUBDIVISION OF T. 34 N., R. 16 W.

BOOK 3002

Chains. *west channel of*
 5.05 Center of Black Wash, 150 lks. wide, course SE.; continue along draw.
 12.00 Leave draw.; asc. 57 ft. over SE. slope.
 40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 27
 S 34
 1933

raise a mound of
 stone, 3 ft. base, 2 ft. high, N. of cor.

Ascend 29 ft. over SE. slope.
 45.00 Spur, slopes S.; desc. 10 ft.
 49.35 Wash, 10 lks. wide, course S.; asc. 19 ft. over E. slope.
 54.00 Low spur, slopes SW.; desc. 17 ft.
 58.05 Wash, 12 lks. wide, course SE.; asc. 27 ft. over NE. slope.
 61.50 Spur, slopes SE.
 76.00 Wash, 5 lks. wide, course SE.; asc. 20 ft.
 80.02 The cor. of secs. 27, 28, 33 and 34.

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth catclaw, cactus and black sage.

N.0°02'W., bet. secs. 27 and 28.
 Over rolling land, through scattered desert growth.
 Ascend 28 ft. over SW. slope.

18.00 Low spur, slopes SE.; desc. 16 ft.
 22.47 Wash, 5 lks. wide, course SE.; asc. 16 ft.
 39.30 Wash, near head, course SE.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a lava stone, 14x4x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S28 | S27
 1933

48.90 Wash, 5 lks. wide, course SE.
 57.09 Wash, 10 lks. wide, course SE.; asc. 14 ft. over SW. slope.
 62.00 Low spur, slopes E.; desc. 12 ft. over N. slope.

Chains. 64.77	Wash, 20 lks. wide, course E.; asc. 68 ft. over broken SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 21, 22, 27, and 28, with brass cap mkd.
	T34N R16W S 21 S 22 S 28 S 27 1933
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, black sage and cactus.
	S. 89° 56' E., on a random line bet. secs. 22 and 27.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect N. and S. line, 12 lks. S. of the cor. of secs. 22, 23, 26 and 27.
	Thence
	S. 89° 59' W., on a true line bet. secs. 22 and 27.
	Over rolling land, through scattered desert growth.
	Descend 23 ft. over SW. slope.
21.64	Wash, 30 lks. wide, course SE.; asc. 76 ft. over NE. slope.
26.53	Road, bears NW. and SE.
28.00	Spur, slopes SE.; desc. 86 ft. over SW. slope.
32.08	Enter draw, course East.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 22 S 27 1933
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
44.43	Center of Black Wash, 150 lks. wide, course SE.; asc. 23 ft. over SE. slope.
52.00	Spur, slopes S.; desc. 23 ft. over SW. slope.
54.54	Wash, 20 lks. wide, course SE.; asc. 81 ft. over NE. slope.
72.00	Spur, slopes SE.; desc. 9 ft.
79.50	Wash, 5 lks. wide, course SE.; asc. 9 ft.
80.08	The cor. of secs. 21, 22, 27 and 28.

Chains. Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, black sage, cactus and joshua.

N. 0° 02' W., bet. secs. 21 and 22.

Over rolling land, through scattered desert growth.

- 1.20 Wash, 5 lks. wide, course SE.; asc. 35 ft. over SW. slope.
- 5.00 Spur, slopes SE.; desc. 57 ft. over NE. slope.
- 12.00 Wash, 10 lks. wide, course SE.; asc. 37 ft. over SW. slope.
- 17.50 Spur, slopes SE.; desc. 48 ft. over NE. slope.
- 24.35 Wash, 5 lks. wide, course SE.; asc. 27 ft. over SW. slope.
- 28.85 Wash, 5 lks. wide, course SE.; asc. 49 ft. over broken S. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 21 | S 22
 1933

raise a mound of
 stone, 3 ft. base, 2 ft. high, W. of cor.

Ascend 31 ft. over S. slope.

- 42.80 Spur, slopes E.; desc. 22 ft. over broken NE. slope.
- 65.25 Wash, 10 lks. wide, course SE.; asc. 85 ft. over SW. slope.
- 77.00 Spur, slopes SE.; desc. 39 ft. over NE. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15, 16, 21, and 22, with brass cap mkd.

T34N R16W
 S 16 | S 15
 S 21 | S 22
 1933


raise a mound of
 stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, cactus, joshua and catclaw.

Chains.	N.89°59'E., on a random line bet. secs. 15 and 22.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.16	Intersect the cor. of secs. 14,15,22 and 23.
	Thence
	S.89°59'W., on a true line bet. secs. 15 and 22.
	Over rolling land, through scattered desert growth.
1.16	Wash, 5 lks. wide, course SE.; asc. 85 ft. over SW. slope.
11.00	Spur, slopes S.; desc. 94 ft. over SW. slope.
27.42	Wash, 20 lks. wide; course S.; asc. 76 ft. over SE. slope.
40.08	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a lava stone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 15</u> S 22 1933
40.70	Spur, slopes SE.; desc. 27 ft. SW. slope.
43.12	Wash, near head, course SE.
52.04	Road, bears NW. and SE.
61.41	Center of Black Wash, 150 lks. wide, course S.; asc. 40 ft. over NE. slope.
70.00	Spur, slopes SE.; desc. 30 ft. over SW. slope.
75.66	Wash, 10 lks. wide, course SE.; asc. 40 ft. over NE. slope.
80.16	The cor. of secs. 15,16,21, and 22.
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, black sage and cactus.
	N.0°02'W., bet. secs. 15 and 16.
	Over rolling land, through scattered desert growth.
	Descend 14 ft. over NE. slope.
7.60	Wash, 5 lks. wide, course SE.; asc. 14 ft. over SW. slope.
9.00	Low spur, slopes SE.; desc. 29 ft. over NE. slope.
19.70	Center of Black Wash, 150 lks. wide, course SE.; asc. 115 ft. over SW. slope.
31.30	Old road, bears NW. and SE.
36.00	Continue over level land.

Chains.
40.00

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a lava stone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



44.07

Road, bears NW. and SE.

52.00

Road, bears NW. and SE.

62.00

Leave level land, bears SE. and NW.; desc. 34 ft. over N. slope.

64.35

Wash, 5 lks. wide, course E.; asc. 40 ft. over S. slope.

67.40


Spur, slopes E.; desc. 30 ft. over NE. slope.

72.12

Wash, 5 lks. wide, course SE.; asc. 54 ft. over SE. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 9, 10, 15, and 16, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, level and rolling.
Soil, sandy and rocky; 4th rates.
Timber, none; undergrowth black sage.

N. 89° 59' E., on a random line bet. secs. 10 and 15.

40.00

Set temp. 1/4 sec. cor.

80.14

Intersect N. and S. line, 7 lks. N. of the cor. of secs. 10, 11, 14 and 15.

Thence

N. 89° 58' W., on a true line, bet. secs. 10 and 15.

Over rolling land, through scattered desert growth.

7.54

Road, bears NE. and SW.

10.14

Road, bears N. and S.

13.34


Wash, 20 lks. wide, course SW.

36.14

Wash, 10 lks. wide, course SW.

40.07

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.



- Chains. Descend 34 ft. over SW. slope.
- 45.43 Wash, 10 lks. wide, course SE.; asc. 64 ft. over NE. slope.
- 68.20 Spur, slopes SE.; desc. 50 ft. over SW. slope.
- 74.80 Head of wash, course S.; asc. 48 ft. over broken SE. slope.
- 80.14 The cor. of secs. 9,10,15 and 16.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw, cactus and black sage.

N.0°02'W., bet. secs. 9 and 10.

Over mountainous land, through scattered desert growth.
Ascend 113 ft. over broken SE. slope.

- 5.50 Spur, slopes E.; desc. 64 ft. over NE. slope.
- 15.86 Wash, 5 lks. wide, course E.; asc. 70 ft. over SE. slope.
- 21.00 Spur, slopes E.; desc. 38 ft. over NE. slope.
- 23.77 Wash near head, course E.; asc. 140 ft. over SE. slope.
- 30.50 Spur, slopes E.; desc. 40 ft. over NE. slope.
- 32.44 Wash, 3 lks. wide, course E.; asc. 105 ft. over SE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a lava stone, 14x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S9 | S10

1933

Ascend 231 ft. over broken SE. slope.

- 71.20 Top of rimrocks, bears NE. and SW.; continue over rolling bench land.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a lava stone, 12x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 3,4,9, and 10, with brass cap mkd.

T34N R16W
S 4 | S 3
S 9 | S 10
1933

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth greasewood.

SUBDIVISION OF T.34 N., R. 16 W.

Chains. S.89°58'E., on a random line bet. secs. 3 and 10.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.10 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 2,3,10, and 11.

Thence

S.89°58'W., on a true line bet. secs. 3 and 10.

Over rolling land, through scattered desert growth.

Ascend 134 ft. over broken SE. slope.

40.05 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a lava stone, 12x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 3
S 10
1933

Ascend 149 ft. over SE. slope.

68.80 Top of rimrocks, 10 ft. high, bears NE. and SW.; continue over level bench land.

80.10 The cor. of secs. 3,4,9, and 10.

Land, level and mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth greasewood.

N.0°08'E., on a random line bet. secs. 3 and 4.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.15 Intersect N. bdy. of Tp., 9 lks. W. of the true point for cor. of secs. 3,4,33, and 34.

Thence

S.0°12'W., on a true line bet. secs. 3 and 4.

Over rolling bench land, through scattered desert growth.

Ascend 17 ft. over NW. slope.

2.00 Low spur, slopes W.; desc. 95 ft. over S. slope.

13.18 Wash, 5 lks. wide, course W; asc. 32 ft. over N. slope.

17.70 Top of ascent; continue over level land.

40.15 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a lava stone, 12x8x2 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S4 | S3
1933

SUBDIVISION OF T.34 N., R. 16 W.

Chains.
 55.13 Wash, 5 lks. wide, course SW;; asc. 41 ft. over NW. slope.
 68.20 Low spur, slopes SW.; desc. 29 ft. over gradual SE. slope.
 80.15 The cor. of secs. 3,4,9, and 10.
 Land, rolling.
 Soil, sandy and rocky; 4th rate.
 Timber, none; undergrowth; catclaw, cactus and joshua.

From the cor. of secs. 4,5,32 and 33, on the S. bdy. of the Tp.

N.0°03'W., bet. secs. 32 and 33.

Over rolling land, through scattered desert growth.

Descend 23 ft.

15.00 Head of wash, course NE.; asc. 92 ft. over SE. slope.


22.00 Spur, slopes E.; desc. 51 ft. over NE. slope.

25.74 Wash, 5 lks. wide, course SE.; asc. 43 ft. over SW. slope.

28.50 Spur, slopes SE.; desc. 52 ft. over NE. slope.

33.33 Bend in wash, 10 lks. wide, from SW. course SE.; asc. 40 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a lava stone, 6x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.




Ascend 41 ft. along E. slope.

42.00 Head of wash, course SE.

73.70 Wash, 20 lks. wide, course SE.; asc. 40 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with a lava stone, 8x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 28,29,32, and 33, with brass cap mkd.



Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth: catclaw, joshua, cactus and greasewood.

Chains. East, on a random line bet. secs. 28 and 33.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.98 Intersect the cor. of secs. 27, 28, 33, and 34.
 Thence
 West on a true line bet. secs. 28 and 33.
 Over rolling land, through scattered desert growth.
 Descend 12 ft. over SW. slope.
 2.50 Wash, 15 lks. wide, course SE.; asc. 70 ft. over NE. slope.
 13.70 Spur, slopes SE.; desc. 20 ft. over SW. slope.
 18.63 Wash, 5 lks. wide, course SE.; asc. 67 ft.
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a limestone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 28
 S 33
 1933

45.00 Low spur, slopes N.
 50.00 Wash, 5 lks. wide, course NE.; continue along bottom of wash.
 56.00 Leave wash, from NW.; asc. 81 ft. over NE. slope.
 79.98 The cor. of secs. 28, 29, 32, and 33.

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, catclaw, cactus and joshua.

N.0°03'W., bet. secs. 28 and 29.

Over rolling land, through scattered desert growth.
 Along E. slope.

5.00 Spur, slopes E.; desc. 81 ft. over NW. slope.
 7.75 Wash near head, course NE.; asc. 81 ft. over SE. slope.
 13.00 Spur, slopes E.; desc. 58 ft. over NE. slope.
 17.33 Wash, 10 lks. wide, course NE.; continue along broken E. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a lava stone, 14x12x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S29 | S28
 1933

Chains.	
41.50	Descend 57 ft. over NE. slope.
46.82	Head of wash, course NE.; continue along broken E. slope.
55.38	Wash, 5 lks. wide, course E.; asc. 197 ft. over broken SE. slope.
72.50	Spur, slopes E.; desc. 45 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 20, 21, 28, and 29, with brass cap mkd.
	T34N R16W S 20 S 21 S 29 S 28 1933
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, cactus, joshua and catclaw.
	East on a random line bet. secs. 21 and 28.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 21, 22, 27, and 28,
	Thence
	N. 89° 58' W., on a true line bet. secs. 21 and 28.
	Over rolling land, through scattered desert growth.
34.64	Wash, 20 lks. wide, course SE.
40.02	True point for $\frac{1}{4}$ sec. cor. falls in wash, 30 lks. wide, course SE.
41.04	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for witness $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 21 WC S 28 1933
	Ascend 46 ft. over NE. slope.
58.00	Spur, slopes SE.; desc. 45 ft. over SW. slope.
71.46	Wash, near head, course SE.; asc. 123 ft. over NE. slope.
80.04	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, cactus, joshua and catclaw.

SUBDIVISION OF T.34 N., R. 16 W.

Chains. N.0°03'W., bet. secs. 20 and 21.
 Over rolling land, through scattered desert growth.
 Descend 86 ft. over NE. slope.

12.31 Wash, 5 lks. wide, course SE.

20.88 Road, bears NW. and SE.

31.50 Wash, 150 lks. wide, course E.; asc. 52 ft. over steep S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S20 | S21
 1933

raise a mound
 of stone, 3 ft. base, 2 ft. high, W. of cor.

Ascend 248 ft. over steep rocky S. slope.

45.15 Top of rimrocks 20 ft. high, bears E. and W.; continue ascending.

56.00 Rocky spur, slopes E.

58.35 Top of rimrocks, 10 ft. high, bears NW. and SE.; desc. 119 ft. over NE. slope.

64.30 Head of wash, course SE.; asc. 73 ft. over SE. slope.

70.00 Spur, slopes E.; desc. 101 ft. over NE. slope.

73.78 Wash, 5 lks. wide, course E.; asc. 117 ft. over SE. slope.

78.30 Top of rimrocks, 10 ft. high, bears NE. and SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a lava stone, 12x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 16, 17, 20, and 21, with brass cap mkd.

T34N R16W
 S 17 | S 16
 S 20 | S 21
 1933

Land, rolling and mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth greasewood.

S.89°58'E., on a random line bet. secs. 16 and 21.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 15, 16, 21 and 22.

Thence

SUBDIVISION OF T.34 N., R. 16 W.

Chains. N.89°54'W., on a true line bet. secs. 16 and 21.
 Over rolling land, through scattered desert growth.
 Ascend 54 ft. over NE. slope.

3.50 Spur, slopes SE.; desc. 103 ft. over SW. slope.

26.04 Wash, 10 lks. wide, course SE.; continue over level land.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 12x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 16
 S 21
 1933

54.81 Wash, 10 lks. wide, course NE.; asc. 371 ft. over steep rocky SE. slope.

72.19 Top of rimrocks, 20 ft. high, bears N. and SW.; continue over bench land.

80.04 The cor. of secs. 16, 17, 20, and 21.

Land, rolling and mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, joshua, cactus and catclaw.

N.0°03'W., bet. secs. 16 and 17.

Over rolling bench land.

Ascend 29 ft. over gradual SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a lava stone, 16x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S17 | S16
 1933

65.20 Top of rimrocks, 40 ft. high, bears NW. and SE.; desc. 333 ft. over rocky NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 8, 9, 16, and 17, with brass cap mkd.

T34N R16W
 S 8 | S 9
 S 17 | S 16
 1933

raise a mound of
 stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling and mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, black sage, cactus and catclaw.

SUBDIVISION OF T. 34 N., R. 16 W.

Chains. S. 89°54'E., on a random line bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.12 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 9, 10, 15 and 16.

Thence

N. 89°58'W., on a true line bet. secs. 9 and 16.

Over rolling land, through scattered desert growth.

Ascend 144 ft. over broken SE. slope.

12.00 Top of ascent; desc. 70 ft. over broken S. slope.

32.10 Descend 72 ft. over SW. slope.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a lava stone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ $\frac{S 9}{S 16}$
1933

Descend 70 ft. over SW. slope.

53.42 Center of Black Wash, 200 lks. wide, course SE.; asc. 165 ft. over NE. slope.

80.12 The cor. of secs. 8, 9, 16, and 17.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none.; undergrowth. catclaw, cactus, joshua and greasewood.

N. 0°03'W., bet. secs. 8 and 9.

Over rolling land, through scattered desert growth.

Descend 134 ft. over NE. slope.

35.50 Center of Black Wash, 100 lks. wide, course SE.; asc. 23 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
s8 | s9
1933

raise a mound of
stone, 3 ft. base, 2 ft. high, W. of cor.

51.00 Spur, slopes W.; desc. 23 ft. over NW. slope.

56.30 Center of Black Wash, 100 lks. wide, course SW.; asc. 23 ft. over SE. slope.

70.50 Low spur, slopes E.; desc. 20 ft.

SUBDIVISION OF T.34 N., R. 16 W.

Chains.

73.23

Center of Black Wash, 100 lks. wide, course SE.; continue along E. bank of same.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 4, 5, 8, and 9, with brass cap mkd.

T34N R16W
S 5 | S 4
S 8 | S 9
1933

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, rocky; 4th rate.

Timber, none; undergrowth, catclaw and cactus.

S.89°58'E., on a random line, bet. secs. 4 and 9.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

80.16

Intersect N. and S. line, 5 lks. S. of the cor. of secs. 3, 4, 9, and 10.

Thence

West, on a true line bet. secs. 4 and 9.

Over rolling bench land, through scattered desert growth.

4.20

Low spur, slopes S.; desc. 99 ft. over W. slope.

18.00

Wash, 10 lks. wide, course S.; asc. 74 ft. over E. slope.

22.00

Top of ascent; desc. 37 ft. over SW. slope.

40.08

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a lava stone, 14x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 4
S 9
1933

Descend 154 ft. over SW. slope.

47.31

Ravine, course SW.; asc. 64 ft. over SE. slope.

53.00

Top of ascent; desc. 358 ft. over broken SW. slope.

80.16

The cor. of secs. 4, 5, 8, and 9.

Land, rolling and level.

Soil, rocky; 4th rate.

Timber, none; undergrowth greasewood.

SUBDIVISION OF T. 34 N., R. 16 W.

BOOK 3992

Chains N.0°12'E., on a random line bet. secs. 4 and 5.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.11 Intersect N. bdy. of Tp., 7 lks. E. of the cor. of secs. 4, 5, 32 and 33.
 Thence
 S.0°09'W., on a true line bet. secs. 4 and 5.
 Over rolling land, through scattered desert growth.
 12.99 Wash, 20 lks. wide, course SW.; asc. 82 ft. over NW. slope.
 30.10 Spur, slopes SW.; desc. 93 ft. over SE. slope.
 37.61 Enter draw, course SW.
 40.11 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 5 | S 4
 1933

raise a mound of
 stone, 3 ft. base, 2 ft. high, W. of cor.

55.11 Enter Black Wash, 200 lks. wide, course S.; continue along same. from NE.
 75.11 Black wash, channel 30 lks. wide, course SW.
 80.11 The cor. of secs. 4, 5, 8, and 9.
 Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, joshua and catclaw.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.
 N.0°03'W., bet. secs. 31 and 32.
 Over mountainous land, through scattered desert growth.
 Ascend 300 ft. over broken SW. slope.
 21.00 Spur, slopes SE.; desc. 22 ft. over N. slope.
 23.48 Head of wash, course E.; asc. 111 ft. over SE. slope.
 38.00 Spur, slopes E.; desc. 12 ft. over NE. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 31 | S 32
 1933

raise a mound of
 stone, 3 ft. base, 2 ft. high, W. of cor.

Chains	Descend 45 ft. over NE. slope.
44.00	Wash, 5 lks. wide, course SE.; asc. 45 ft. over SW. slope.
47.00	Spur, slopes SE.; desc. 38 ft. over NE. slope.
50.00	Wash, 5 lks. wide, course SE.; asc. 38 ft. over SW. slope.
53.30	Spur, slopes SE.; desc. 20 ft. over NE. slope.
57.70	Wash, 5 lks. wide, course SE.; asc. 104 ft. over broken SW. slope.
78.00	Spur, slopes SE.; desc. 13 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, with a lava stone, 12x12x4 ins. mkd. X, deposited alongside, and in a mound of stone to top, for cor. of secs. 29, 30, 31, and 32, with brass cap mkd.
	T34N R16W S 30 S 29 S 31 S 32 1933

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, catclaw, joshua and cactus.

	East on a random line bet. secs. 29 and 32.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect N. and S. line, 5 lks. S. of the cor. of secs. 28, 29, 32 and 33.
	Thence
	S. 89° 58' W., on a true line bet. secs. 29 and 32.
	Over mountainous land, through scattered desert growth.
	Ascend 29 ft. over NE. slope.
2.60	Spur, slopes SE.; desc. 29 ft. over SW. slope.
9.00	Enter sand wash, 30 lks. wide, course SE.; continue in wash,
25.20	Leave wash.; asc. 132 ft. over NE. slope.
39.97	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a lava stone, 10x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 29 S 30 1933
	Ascend 285 ft. over NE. slope.
44.70	Top of rimrocks, 20 ft. high, bears SE. and NW.; continue ascending over bench land.

SUBDIVISION OF T. 34-N., R. 16 W.

BOOK 3992

Chains.
64.00

Spur, slopes N.; desc. 23 ft. over NW. slope.

69.00

Head in wash, 30 lks. wide, course NE. from SE.; asc. 126 ft. over NE. slope.

79.94

The cor. of secs. 29, 30, 31, and 32.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, cactus and catclaw.

West bet. secs. 30 and 31.

Over rolling bench land, through scattered desert growth.

Ascend 20 ft. over NE. slope.

2.50

Low spur, slopes SE.; desc. 13 ft. along E. slope.


12.50

Head of draw, course SE.

28.66

Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a lava stone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of frac. secs. 30 and 31, with brass cap mkd.



1933

From this point the 348 Mi. Cor., heretofore described bears N.4°00'E., 29.77 chs. dist.

Land, rolling.
Soil, sandy loam; 2nd rate.
Timber, none; undergrowth, joshua and cactus.

From the cor. of secs. 29, 30, 31, and 32.

N.0°03'W., bet. secs. 29 and 30.

Over rolling bench land, through scattered desert growth.

Descend 48 ft. over NE. slope.

4.14

Head of draw, course SE.; asc. 91 ft. over SW. slope.

9.50

Spur, slopes SE.; desc. 421 ft. over rocky NW. slope.

28.36

Wash, 5 lks. wide, course SE.; asc. 17 ft. over SW. slope.

30.00

Low spur, slopes E.; desc. 22 ft. over NE. slope.

33.05

Wash, 15 lks. wide, course SE.; asc. 56 ft. over SE. slope.

37.00

Spur, slopes SE.; desc. 18 ft. over SE. slope.

Chains.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 30 | S. 29
1933

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

42.20

Wash, 30 lks. wide, course SE.; asc. 373 ft. over broken SE. slope.

70.50

Spur, slopes E.; desc. 81 ft. over NE. slope.

76.33

Wash near head, course SE.; asc. 45 ft. over SW. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., on solid rock, with a cross X, mkd. at the base, and in a mound of stone to top, for cor. of secs. 19, 20, 29, and 30, with brass cap mkd.

T34N R16W
S 19 | S 20
S 30 | S 29
1933

Land, rolling and mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, catclaw and cactus.

N. 89° 58' E., on a random line bet. secs. 20 and 29.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

80.00

Intersect N. and S. line, 3 lks. S. of the cor. of secs. 20, 21, 28, and 29.

Thence

S. 89° 57' W., on a true line bet. secs. 20 and 29.

Over rolling land, through scattered desert growth.

Ascend 189 ft. over NE. slope.

8.00

Top of ascent; continue along top of spur.

20.00

Leave spur, slopes N.; desc. 29 ft. over NW. slope.

26.70

Wash, 5 lks. wide, course NE.; continue over rolling land.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a lava stone, 12x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 20
S 29
1933

Ascend 195 ft. over NE. slope.

78.10

Spur, slopes SE.; continue along S. slope.


Chains.
80.00

The cor. of secs. 19, 20, 29 and 30.
Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, catclaw and cactus.

West bet. secs. 19 and 30.
Over rolling land, through scattered desert growth.

19.00
20.30
29.02

Low spur, slopes SE.
Ledge, 10 ft. high, bears SE. and NW.
Intersect the Arizona and Nevada State Boundary.
Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a lava stone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of frac. secs. 19 and 30, with brass cap mkd.



1933

From this point the 347⁴³ Mi. Cor., heretofore described bears N. 2° 53' W., 26.51 chs. dist.

Land, rolling.
Soil, sandy and rocky; 4th rate.
Timber, none; undergrowth, joshua, cactus and catclaw.


From the cor. of secs. 19, 20, 29, and 30.
N. 0° 03' W., bet. secs. 19 and 20.
Over mountainous land, through scattered desert growth.

1.50
28.83
30.20

Spur, slopes E.; desc. 217 ft. over broken NE. slope.
Road, bears E. and W.
Wash, 15 lks. wide, course SE.; asc. 136 ft. over SW. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground to bedrock, with a lava stone, 12x10x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for sec. cor. with brass cap mkd.



1933

Ascend 298 ft. over broken SW. slope.

64.00

Top of ascent; continue over level land.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a lava stone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 17, 18, 19, and 20, with brass cap mkd.

SUBDIVISION OF T. 34 N., R. 16 W.

Chains

T34N R16W
 S 18 | S 17
 S 19 | S 20
 1933

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, catclaw and greasewood.

- N. 89° 57' E., on a random line bet. secs. 17 and 20.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.92 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 16, 17, 20 and 21.
- Thence
- S. 89° 54' W., on a true line bet. secs. 17 and 20.
- Over mountainous land, through scattered desert growth.
- 2.42 Low spur, slopes S.; desc. 42 ft. over SW. slope.
- 8.79 Wash, 5 lks. wide, course SE.; asc. 53 ft. over NE. slope.
- 13.42 Spur, slopes SE.; desc. 86 ft. over SW. slope.
- 29.92 Wash, 10 lks. wide, course SE.; asc. 16 ft. over NE. slope.
- 31.92 Spur, slopes SE.; desc. 21 ft. over SW. slope.
- 37.32 Wash, 10 lks. wide, course SE.
- 39.96 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a lava stone, 8x6x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 17
 S 20
 1933

- Ascend 485 ft. over SE. slope.
- 67.92 Top of rimrocks, 10 ft. high; bears N. and S.
- 79.92 The cor. of secs. 17, 18, 19 and 20.
- Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, catclaw, cactus and greasewood.

- West bet. secs. 18 and 19.
- Over rolling land, through scattered desert growth.
- 6.00 Low spur, slopes S.; desc. 318 ft. over W. slope.
- 10.00 Top of rimrocks, 20 ft. high, bears N. and S.
- 21.99 Wash, 30 lks. wide, course S.; asc. 26 ft. over E. slope.

Chains.
29.96

Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 8x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of frac. secs. 18 and 19, with brass cap mkd.

	T34N	
NEV	S 18	C
	S 19	C
	R16W	

1933

From this point the 346 Mi. Cor., heretofore described bears N. 0° 21' E., 37.71 chs. dist.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, cactus and catclaw.

From the cor. of secs. 17, 18, 19, and 20.

N. 0° 03' W., bet. secs. 17 and 18.

Over rolling land, through scattered desert growth.

5.00 Continue over level land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground to bedrock, with a lava stone, 10x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

S18	S17
-----	-----

1933

57.00 Top of rimrocks, 6 ft. high, bears SE. and NW.; desc. 125 ft. over rocky NE. slope.

69.40 Wash, 3 lks. wide, course E.; asc. 84 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a lava stone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 7, 8, 17, and 18, with brass cap mkd.

T34N	R16W
S 7	S 8
S 18	S 17

1933

Land, rolling and mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth catclaw, joshua and cactus.

Chains.	N.89°54'E., on a random line bet. secs. 8 and 17.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 8,9,16, and 17.
	Thence
	S.89°53'W., on a true line bet. secs. 8 and 17.
	Over mountainous land, through scattered desert growth.
	Ascend 389 ft. over NE. slope.
22.90	Top of rimrocks, 30 ft. high, bears NW. and SE.
26.40	Spur, slopes SE.; desc. 42 ft. over SW. slope.
33.67	Wash, 3 lks. wide, course SE.; asc. 63 ft. over NE. slope.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a lava stone. 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4} \frac{S 8}{S 17}$ 1933
	Ascend 20 ft. over NE. slope.
43.90	Spur, slopes SE.; desc. 65 ft. over SW. slope.
52.35	Wash, 10 lks. wide, course SE.; asc. 225 ft. over NE. slope.
64.90	Spur, slopes SE.; desc. 97 ft. over SW. slope.
74.04	Wash, 4 lks. wide, course S.; asc. 124 ft. over SE. slope.
79.90	The cor. of secs. 7,8,17, and 18.
	Land, mountainous.
	Soil, rocky; 4th rate.
	Timber, none; undergrowth, joshua, catclaw and cactus.
	West bet. secs. 7 and 18.
	Over rolling land, through scattered desert growth.
	Ascend 86 ft. over SE. slope.
11.00	Continue over bench land.
28.11	Intersect the Arizona and Nevada State Boundary.
	Set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground to bedrock, with a lava stone 12x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of frac. secs. 7 and 18, with brass cap mkd.

Chains.

T34N
 NEV | S 7 C
 | S 18 C
 R16W

From this cor., the 345 N. Cor., hereto-

1933 fore described, bears N.2°08'E., 30.49 chs. dist.

Land, level and rolling.

Soil, rocky; 4th rate.

Timber, none; undergrowth, joshua and cactus.

From the cor. of secs. 7, 8, 17, and 18.

N.0°03'W., bet. secs. 7 and 8.

Over rolling land, through scattered desert growth.

Descend 300 ft. over broken NE. slope.

3.00 Low spur, slopes E.

10.00 Drain, course E.

14.00 Low spur, slopes E.

19.00 Top of rimrocks, 20 ft. high, bears E. and W.; continue descending.

28.15 Drain, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

S 7 | S 8

1933

Descend 42 ft. over NE. slope.

52.00 Drain, course SE.; asc. 86 ft. over SW. slope.

61.00 Spur, slopes E.; desc. 159 ft. over broken NE. slope.

79.85 Top of volcanic knoll.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 5, 6, 7, and 8, with brass cap mkd.

T34N R16W.

S 6 | S 5

S 7 | S 8

1933

Land, rolling and mountainous.

Soil, rocky; 4th rate.

Timber, none; undergrowth, catclaw, cactus and joshua.

N.89°53'E., on a random line bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.94 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 4, 5, 8 and 9.

Thence

S.89°54'W., on a true line bet. secs. 5 and 8.

Chains. Over rolling land, through scattered desert growth.

2.50 Wash, 30 lks. wide, course SE.; continue along wash.

2.80 Leave wash, course SE.; asc. 29 ft. over NE. slope.

4.40 Road, bears NW. and SE.

10.00 Spur, slopes SE.; desc. 45 ft. over SW. slope.

20.11 Wash, 3 lks. wide, course SE.; asc. 29 ft. over NE. slope.

23.40 Spur, slopes SE.; continue along S. slope.

23.47 Mound of stone, 3 ft. base, 2 ft. high, posted Location No. 3 Inspiration Placer Claim, bears N.13°21'E., 6.23 chs. dist.

25.43 Wash, 5 lks. wide, course SE.; asc. 104 ft. over NE. slope.

32.50 Spur, slopes SE.; desc. 40 ft. over broken NE. slope.

39.97 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 5
S 8
1933

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Ascend 214 ft. over broken NE. slope.

79.94 The cor. of secs. 5, 6, 7, and 8.

Land, rolling and mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw, cactus and joshua.

West bet. secs. 6 and 7.

Over mountainous land, through scattered desert growth.

Descend 29 ft. over NW. slope.

6.21 Drain, course N.; asc. 23 ft. along broken N. slope.

23.01 Wash, 5 lks. wide, course N.

25.21 Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground to bedrock, with a lava stone, 12x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of frac. secs. 6 and 7, with brass cap mkd.

NEV T34N
S 6 C
S 7 C
R16W

1933 From this cor., the 344 M. Cor., heretofore described, bears N.1°59'E., 27.70 chs.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw.

SUBDIVISION OF T. 34 N., R. 16 W.

43

BOOK 3992

Chains	From the cor. of secs. 5, 6, 7, and 8. N. 0° 09' E., on a random line bet. secs. 5 and 6.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.19	Intersect N. bdy. of Tp., 12 lks. E. of the cor. of secs. 5, 6, 31, and 32.
	Thence
	S. 0° 04' W., on a true line bet. secs. 5 and 6.
	Over rolling land, through scattered desert growth.
	Ascend 20 ft. over NW. slope.
18.19	Low spur, slopes E.; desc. 20 ft. over SE. slope.
26.69	Road, bears NE. and SW.
27.83	Wash, 10 lks. wide, course NE.; asc. 34 ft. over NW. slope.
30.60	Spur, slopes NE.; desc. 40 ft. over SE. slope.
33.47	Wash, 3 lks. wide, course NE.; asc. 34 ft. over NW. slope.
36.39	Road, bears NE. and SW. on low spur, slopes NE.; desc. 32 ft. over SW. slope.
40.19	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a limestone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. S6 S5 1933
42.20	Low spur, slopes E.; desc. 71 ft. over SE. slope.
48.89	Drain, course SE.
50.19	Old road, bears E. and W.
63.65	Wash, 20 lks. wide; course E.; asc. 139 ft. over NW. slope.
71.03	On E. slope of volcanic knoll near top; desc. 60 ft. over SE. slope.
75.48	Wash, 3 lks. wide, course NE.; asc. 129 ft. over NE. slope.
80.19	The cor. of secs. 5, 6, 7, and 8.
	Land, rolling and mountainous. Soil, sandy and rocky; 3rd and 4th rates. Timber, none; undergrowth, catclaw, joshua and cactus.

SUBDIVISION OF T. 34 N., R. 16 W.

Chains. At a point N. 4° 00' E., 9.70 chs. dist. from the 349 mi. cor. on the Arizona and Nevada State boundary, heretofore described, midway in latitude bet. the SW. and NW. cors. of sec. 31.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap mkd.

NEV $\frac{1}{4}$ S 31
1933

stone, 3 ft. base, 2 ft. high, E. of cor. raise a mound of

At a point N. 2° 53' W., 11.14 chs. dist. from the 348 mi. cor. on the Arizona and Nevada State boundary, heretofore described, and N. 2° 53' W., 88 lks. dist. from the true point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness $\frac{1}{4}$ sec. cor. of sec. 30, with brass cap marked

NEV $\frac{1}{4}$ S 30
WC
1933

True point for $\frac{1}{4}$ sec. cor., midway in latitude bet. the SW. and NW. cors. of sec. 30, falls in wash, 50 lks. wide, course E.

At a point N. 0° 21' E., 13.51 chs. dist. from the 347 mi. cor. on the Arizona and Nevada State boundary, heretofore described, midway in latitude bet. the SW. and NW. cors. of sec. 19.

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a lava stone 14x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 19, with brass cap mkd.

NEV $\frac{1}{4}$ S 19
1933

At a point N. 2° 08' W., 2.31 chs. dist. from the 346 mi. cor. on the Arizona and Nevada State boundary, heretofore described, midway in latitude bet. the SW. and NW. cors. of sec. 18,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a lava stone 10x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 18, with brass cap mkd.

NEV $\frac{1}{4}$ S 18
1933

Chains.

At a point N.1°59'E., 9.54 chs. dist., from the 345 Mi. Cor. on the Arizona and Nevada State Boundary heretofore described, midway in latitude bet. the SW. and NW. cors. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., on solid rock, with a cross X, mkd. at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 7, with brass cap mkd.

NEV | $\frac{1}{4}$ S 7
1933

At a point N.1°25'E., 12.32 chs. dist., from the 344 Mi. Cor. on the Arizona and Nevada State Boundary heretofore described, 40.00 chs. in latitude from the SW. cor. of sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap mkd.

NEV | $\frac{1}{4}$ S 6
1933

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

FINAL TEST OF INSTRUMENT.

For final test of instrument No. 19423, see field notes of the resurvey of a portion of the Arizona and Nevada State Boundary, resurveyed under this group.

GENERAL DESCRIPTION.

The land in T. 34 N., R. 16 W., is rolling and mountainous. The general elevation of the township is about 2,500 ft. above sea level. The east and west portions of the township are rough and stony bench land. The central portion of the township is rolling and level valley land. The soil throughout the township is sandy and rocky; 3rd and 4th rates. Several large washes traverse through the township: Black and Cottonwood washes empty into Grand Wash, in the SE. portion of the township. Grand Wash leaves the township near the $\frac{1}{4}$ sec. cor. of sec. 34 on the S. bdy. of the township.

Several springs (known as Seven Springs) are located in the east portions of secs. 23, 26, and 35.

There is no timber within the township. The undergrowth is cactus, joshua, black sage, catclaw and greasewood.

There is one settler in the SW. $\frac{1}{4}$ of sec. 35 with small fields of land under cultivation. The predominating interest is stock grazing.

CERTIFICATE OF UNITED STATES SURVEYOR

I, William E. Hiester, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 21st. day of December, 1932, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed ~~all these parts of~~ the subdivisional lines, completing the survey of Township 34 North, Range 16 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

William E. Hiester
U. S. Surveyor.
Glendale, California,
August 26, 1933.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,
Denver, Colorado, April 28, 1934.

The foregoing field notes of the survey of the subdivisional lines, completing the survey of Township 34 North, Range 16 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by William E. Hiester, U. S. Surveyor, under his special instructions dated December 21, 1932, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.