

Original.

4-679
(April 1933)

Book A.

FIELD NOTES

BOOK 4028

of the

Dependent Resurvey of the 3rd Standard Parallel North, along the
North Boundary of T. 12 N., through part of Ranges 2 and 3 East;

and the

Dependent Resurvey of the West Bdy., part of the South Bdy., and
a portion of the Subdivision lines; and Survey of the East Bdy.
and a portion of the subdivisional lines, completing the
subdivision of Township 12 North, Range 3 East.

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Theodore Vander Meer, U. S. Transitman

and

Benj. J. Mollette, U. S. Transitman

Under special instructions dated March 9, 1934, which provided
for the surveys included under Group No. 184, bearing the approval of the
Commissioner of the General Land Office under date of March 19, 1934
and assignment instructions dated April 12, 1934

Survey commenced April 27, 1934

Survey completed May 12, 1934

4028

4028

BOOK 4028

INDEX DIAGRAM.

		Township		12 North		Range		3 East				
4	36	3	31	3	32	2	33	2	34	2	35	
9	6	59	5	47	4	40	3	33	2	22	1	16
	58		57		47		39		33		26	
8	7	57	8	46	9	39	10	32	11	21	12	15
	56		55		45		38		31		25	
7	18	54	17	45	16	38	15	31	14	20	13	15
	53		53		44		37		30		24	
6	19	52	20	43	21	37	22	30	23	19	24	14
	51		50		43		36		29		23	
5	30	50	29	42	28	35	27	28	26	18	25	13
	49		49		41		35		28		22	
5	31	48	32	41	33	34	34	27	35	17	36	12
	10		11		12							

Resurvey of 3rd Standard Parallel North, South Boundary

15

of T. 13 N., R. 2 E.

The surveys and resurveys of township 12 north, range 3 east, was executed with light mountain solar transits, made by Buff and Buff Co., Serial Nos. 9977 and 9223, used respectively by Theodore Vander Meer and Benjamin J. Mollette, U. S. Transitmen, both instruments being property of the General Land Office. The horizontal circles have diameters of $4\frac{1}{2}$ ins., with two double verniers placed opposite each other reading to single minutes; the vertical circles have diameters of 4 ins., with one double vernier reading to single minutes; the telescopes have fixed stadia wires, ratio 1-132, with a focal constant of 1.2 lks. The instruments are equipped with Smith solar attachments; radius of latitude arcs $3\frac{1}{2}$ ins., and of declination arcs 3 ins., each with verniers reading to single minutes. The instruments were in good condition, and having been placed in satisfactory adjustment prior to beginning the survey, were approved by the district cadastral engineer on April 12, 1934. All the instrument adjustments were examined before making the field tests hereinafter recorded.

The directions of the lines were determined by solar transit method, checked by occasional direct solars which are not recorded. The measurements were made with Lallie steel tapes, 5 chs. in length, graduated every link for the first 100 lks. and the remainder at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The data furnished with the special instructions gives the geographic position for the SE.cor. of Tp. 12 N., R. 3 E., as follows: latitude $34^{\circ}22'06''$ N., and longitude $111^{\circ}58'53''$ W.

April 26, 1934, in camp in the SW $\frac{1}{4}$ of sec. 26, T.12 N., R. 3 E., latitude $34^{\circ}23'03''$ N., longitude $112^{\circ}00'40''$ W., using instrument No. 9977, we observe Polaris at eastern elongation at 5h 25m a.m., l.m.t., making two observations each with the telescope in direct and reversed positions, and mark the mean point with a tack in a stake, about 6 chs. N. We read the angle to a sky-line point about 2 miles north-easterly, which by reduced repetition is $18^{\circ}14'50''$. Adding the azimuth of Polaris $1^{\circ}16'12''$ the true bearing of the point is N. $19^{\circ}31'02''$ E.

At intervals of 30 minutes from 7.30 to 10.30 a.m., and from 1.30 to 4.30 p.m., we make proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments, when compared with the meridian established by Polaris observation, have a maximum error of less than $1'30''$.

We verify the meridional indications at frequent intervals during the period of the survey, and make daily tests of the vernier positions.

Mean magnetic declination is $14^{\circ} 52' E.$

The 3rd Standard Parallel North, through Rs. 2 and 3 E., was surveyed in 1873 by C. B. Foster, U.S. Deputy Surveyor. That part of it which constitutes the N. bdy. of T. 12 N., R. 3 E., was resurveyed in 1928 by B. J. Kinsey, U. S. Surveyor., and L. R. Hanson, U. S. Transitman, who found no evidence of the original closing cors. of T. 12 N., R. 3 E., and did not reestablish them. No other resurveys or retracements are of record.

The west 5 tiers of sections of T.12 N., R. 3 W., were also surveyed in 1873 by C. B. Foster, who established all the subdivisional and west bdy. closing cors. on said standard.

Resurvey of 3rd Standard Parallel North, South Boundary
of T. 13 N., R. 2 E.

Chains. The following notes describe the reestablishment of the closing corners after a search at each point revealed no evidence of the Foster closing corners.
The topography of the following resurvey is as of record.

Beginning at the standard cor. of secs. 34 and 35, T. 13 N., R. 3 E., which is an iron post, 2 ins. diam., 6 ins. above a mound of stone, firmly set, mkd. on brass cap and witnessed as described in the official record.

N.88°30'W., on a random and true line on S. bdy. of sec. 34.

5.84 Proportional distance,

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 1 and 2, of T. 12 N., with brass cap mkd.

T 13 N R 3 E
S 34

S 2 S 1
C C
T 12 N R 3 E
1934

41.13 The standard $\frac{1}{2}$ sec. cor. of sec. 34, an iron post, 1 in. diam., firmly set, and mkd. on brass cap, and witnessed as described in the official record.

Beginning at the standard cor. of secs. 33 and 34, T. 13 N., R. 3 E., an iron post, 2 ins. diam., 4 ins. above a small mound of stone, firmly set, mkd. on brass cap and witnessed as described in the official record.

S.89°48'W., on a random and true line on S. bdy. of sec. 33.

5.81 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 2 and 3, of T. 12 N., with brass cap mkd.

T 13 N R 3 E
S 33

S 3 S 2
C C
T 12 N R 3 E
1934

of stone, 3 ft. base, 2 ft. high, S. of cor. raise a mound

40.80 The standard $\frac{1}{2}$ sec. cor. of sec. 33, an iron post, 1 in. diam., firmly set, mkd. on brass cap and witnessed as described in the official record.

Beginning at the standard cor. of secs. 32 and 33, T. 13 N., R. 3 E., an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

N.88°36'W., on random and true line on S. bdy. of sec. 32.

Resurvey of 3rd Standard Parallel North, South Boundary 3

of T. 13 N., R. 2 E.

Chains. 5.71	<p>Proportional distance,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 3 and 4 of T. 12 N., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 13 N R 3 E</p> <p style="margin-left: 40px;">S 32</p> <hr style="width: 20%; margin: 0 auto;"/> <p style="margin-left: 20px;">S 4 S 3</p> <p style="margin-left: 20px;">C C</p> <p>T 12 N R 3 E</p> <p style="margin-left: 40px;">1934</p> </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, S. of cor.</p>
40.82	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 32, an iron post, 1 in. diam., firmly set, mkd. on brass cap and witnessed as described in the official record.</p>
<p>Beginning at the standard cor. of secs. 31 and 32, T. 13 N., R. 3 E., an iron post, 2 ins. diam., 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.</p>	
<p>N.88°59'W., on random and true line on S. bdy. of sec. 31.</p>	
5.82	<p>Proportional distance,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for closing cor. of secs. 4 and 5, of T. 12 N., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 13 N R 3 E</p> <p style="margin-left: 40px;">S 31</p> <hr style="width: 20%; margin: 0 auto;"/> <p style="margin-left: 20px;">S 5 S 4</p> <p style="margin-left: 20px;">C C</p> <p>T 12 N R 3 E</p> <p style="margin-left: 40px;">1934</p> </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, S. of cor.</p>
41.22	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 31, an iron post, 1 in. diam., firmly set, mkd. on brass cap and witnessed as described in the official record.</p>
<p>Resurvey of Part of 3rd Standard Parallel North, along South Boundary of T. 13 N., R. 2 E.</p>	
<p>Beginning at the standard cor. of Tps. 13 N., Rs. 2 and 3 E., an iron post, 3 ins. diam., 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.</p>	
<p>N.88°59'W., on random and true line on S. bdy. of sec. 36.</p>	
5.79	<p>Proportional distance,</p> <p>Set an iron post; 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, with a stone mkd. X deposited at the base, and in a mound of stone; 6 ft. base, to top, for closing cor. of secs. 5 and 6, of T. 12 N., R. 3 E., with brass cap mkd.</p>

Resurvey of Part of 3rd Standard Parallel North,
along South Boundary of T. 13 N., R. 3 E.

Chains

T 13 N R 2 E
S 36
S 6 | S 5
T 12 N R 3 E
C C
1934

41.22 The standard $\frac{1}{2}$ sec. cor. of sec. 36, an iron post, 1 in. diam., firmly set, mkd. on brass cap and witnessed as described in the official record.

Beginning at the standard cor. of secs. 35 and 36, T. 13 N., R. 2 E., an iron post, 2 ins. diam., 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

N.88°59'W., on random and true line on S. bdy. of sec. 35.

4.04 Proportional distance,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for closing cor. of Tps. 12 S., Rs. 2 and 3 E., with brass cap mkd.

T 13 N R 2 E
S 35
S 1 | S 6
C C
R 2 E R 3 E
1934

raise a mound
of stone, 3 ft. base, 2 ft. high, S. of cor.

41.22 The standard $\frac{1}{2}$ sec. cor. of sec. 35, an iron post, 1 in. diam., firmly set, mkd. on brass cap and witnessed as described in the official record.

Resurvey of West Boundary of T. 12 N., R. 3 E.

The west boundary of T. 12 N., R. 3 E., was surveyed in 1873 by C. B. Foster, U. S. Deputy Surveyor. No resurveys are of record.

The following notes describe a complete dependent resurvey.

Beginning at the closing cor. of Tps. 12 N., Rs. 2 and 3 E.

South, on random line bet. secs. 1 and 6.

40.00 Fail to find $\frac{1}{2}$ sec. cor. Set temp. $\frac{1}{2}$ sec. cor.

80.77 A point 3.43 chs. E. of the cor. of secs. 1, 6, 7 and 12.

Thence from cor.

South, on a random line, searching for and failing to find corners and setting temp. $\frac{1}{2}$ sec. cor. and sec. cors. at intervals of 40.00 and 80.00 chs.

403.35 A point 6.45 chs. E. of the cor. of Tps. 11 and 12 N., Rs. 2 and 3 E., which is an iron post, 3 ins. diam., 2 ins. above a mound of stone, firmly set, mkd. on brass

Chains cap and witnessed as described in the official record.

Thence from cor.,

N.0°55'E., on true line bet. secs. 31 and 36.


Over rolling land, through scattering undergrowth along W. side of wire fence, bears N. and S.

Ascend 83 ft. over S. and SE. slopes.

4.70 Wire fence, bears N.2°W. and S.2°E.

26.30 Short spur, slopes E.; desc. 65 ft. over NE. slope.

40.34 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.




raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Corner stands in W. end of small dry lake, drains SE.

Over flat.

80.68 Proportional distance,

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.



18x18x12 ins., one in each sec., 3 ft. dist. dig pits,

Land, flat and rolling.

Soil, adobe; 1st and 3rd rate.

Undergrowth, scrub oak, quinine, cactus and cats claw.


N.0°55'E., on true line bet. secs. 25 and 30.

Over gently rolling land, through scattering undergrowth.

4.40 An unused road, bears SW. to Cordes and NE.

15.40 Wash, 30 lks. wide, 1 ft. deep, course SE.; a dyke across same about 8 chs. SE.; asc. 24 ft. over SW. slope.

40.34 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



raise a mound

Resurvey of West Boundary of T. 12 N., R. 3 E.

Chains.	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Ascend 84 ft. over gradual SW. slope.
59.90	Short spur, slopes W.; desc. slightly.
65.00	Spur, slopes SE.; over E. slope.
80.68	Proportional distance, Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.
	T 12 N R 2 E R 3 E S 24 S 19 S 25 S 30 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, gently rolling. Soil, adobe; 1st and 2nd rate. Undergrowth, scrub oak, cats claw, cactus and quinine.

	N.0°55'E., on true line bet. secs. 19 and 24. Over rolling land, through scattering undergrowth; over E. slope.
27.00	Road, bears SW. to Mayer and NE. to Sycamore.
31.50	Low spur, slopes SE.; desc. 25 ft. over NE. slope.
39.20	Wash, 20 lks. wide, 3 ft. deep, course E.
40.34	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 24 S 19 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Ascend 32 ft. over S. slope.
49.82	Telephone line, parallels power line.
51.55	Steel tower power line, bears S.70 $\frac{1}{2}$ °E. and N.70 $\frac{1}{2}$ °W.
52.20	Wire fence, bears E. and W.; low spur, slopes E.; desc. 36 ft.
64.00	Swale, drains E.; asc. 48 ft. over S. slope.
79.90	Low hill, bears SE. and NW.
80.68	Proportional distance, Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

Resurvey of West Boundary of T. 12 N., R. 3 E.

7

Chains.

T 12 N
R 2 E R 3 E
S 13 | S 18
S 24 | S 19
1934

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, adobe and gravel; 2nd rate.

Timber, none; undergrowth, scrub oak, quinine, cats claw and cactus.

N.0°55'E., on true line bet. secs. 13 and 18.

Over rolling land, through scattering undergrowth.

Descend 40 ft. over rolling E. slope.

12.20 Wash, 15 lks. wide, 2 ft. deep, course SE.; asc. 50 ft.

25.10 Spur, slopes SE.; desc. 52 ft. over NE. slope.

32.00 Wash, 10 lks. wide, 6 ft. deep, course SE.; asc. 18 ft.

40.34 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 13 | S 18
1934

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

Ascend 47 ft. over gradual S. slope.

58.80 Spur, slopes E.; desc. 64 ft.

62.60 Drain, course E.; asc. 30 ft.

63.80 Short spur, slopes E.; desc. 24 ft.

66.80 Small drain, course SE.; asc. 57 ft.

72.40 Spur, slopes SE.; desc. 40 ft. over NE. slope.

76.70 Small drain, course S.70°E.; asc. 25 ft.

80.50 Low spur, slopes SE.

80.68 Proportional distance,

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.

T 12 N
R 2 E R 3 E
S 12 | S 7
S 13 | S 18
1934

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

Chains. Land, rolling.
Soil, gravel and adobe; 2nd rate.
Timber none; undergrowth, cats claw, oak brush, cactus
and quinine.

N.0°55'E., on true line bet. secs. 7 and 12.
Over rolling land, through scattering undergrowth.
Descend 20 ft. over NE. slope.

2.70 Wash, 10 lks. wide, course SE.; asc. 85 ft.
15.40 Spur, slopes E.; desc. 45 ft.
19.20 Head of ravine, course E.; asc. 44 ft.
23.50 Spur, slopes E.; desc. 46 ft.
27.50 Drain, 5 lks. wide, course E.; asc. 36 ft.
31.10 Spur; slopes E.; desc. 50 ft. over NE. slope.
35.00 Wash, 10 lks. wide, course SE.; asc. 51 ft. over S. slope.
39.50 Spur; slopes SE.; desc. slightly.
40.34 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the
ground, for $\frac{1}{2}$ sec. cor.; with brass cap mkd.

$\frac{1}{2}$
 S 12 | S 7
 1934

raise a mound

of stone, 3 ft. base, 2 ft. high, W. of cor.

Descend 30 ft. over NE. slope.

45.80 Drain, course SE.; asc. 107 ft. over SW. slope.
66.70 Spur, slopes E.; desc. 81 ft. over NE. slope.
72.60 Head of ravine, course E.; asc. 40 ft. over SE. slope.
76.60 Spur, slopes E.; desc. 45 ft. over NE. slope.
80.68 The cor. of secs. 1, 6, 7 and 12; a weathered stake, $1\frac{1}{2}$ ins.
square by 14 ins. long, marks partly legible.

In place of and with original stake alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 1, 6, 7 and 12, with brass
cap mkd.

T 12 N
 R 2 E R 3 E
 S 1 | S 6
 S 12 | S 7
 1934

raise a mound

of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Resurvey of West Boundary of T. 12 N., R. 3 E.

9

1022

Chains	Soil, adobe and gravel; 2nd rate. Timber, none; undergrowth, scrub oak, cats claw and quinine.

	N.2°26'E., on true line bet. secs. 1 and 6. Over rolling land, through scattering undergrowth. Descend 44 ft. over N. slope.
2.60	Short ravine, course NE.; asc. 15 ft.
5.20	Short spur, slopes E.; desc. 32 ft.
11.00	Wash, 25 lks. wide, 2 ft. deep, course SE.; asc. 112 ft. over SW. slope.
21.40	Short spur, slopes SW.; desc. 24 ft.
23.20	Short ravine, course SW.; asc. 23 ft.
26.40	Short spur, slopes SW.; desc. 38 ft.
30.40	Ravine, course SW.; asc. 84 ft. over SW. slope.
37.00	Spur, slopes SW.; desc. 22 ft. over NW. slope.
40.42	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 1 S 6 1934
	Descend 42 ft. over NW. slope.
43.00	Short ravine, course W.; asc. 187 ft. over general S. slope.
63.50	Short spur, slopes W.; desc. 35 ft.
66.90	Short ravine, course W.; asc. 47 ft.
75.00	Slope changes; along W. slope.
80.84	The closing cor. of Tps. 12 N., Rs. 2 and 3 E., hereinbefore described.
	Land, rolling. Soil, gravel and adobe; 2nd rate. Timber, none; undergrowth, scrub oak, cats claw, cactus and quinine.

Resurvey of Part of South Boundary of T. 12 N., R. 3 E.

The west 5 miles of the south boundary of T. 12 N., R. 3 E., was surveyed in 1873 by C. B. Foster, U. S. Deputy Surveyor, and the E. mile, south boundary of sec. 36, by T. F. White, in 1881.

The only retracement or resurvey of record is the resurvey of the E. 3 miles by G. F. Rigby, U. S. Surveyor, in 1918. The following notes describe a

Chains	resurvey of the W. 3 miles.
	Beginning at the cor. of secs. 3,4,33 and 34, on the S. bdy. of T. 12 N., R. 3 E.
	S.88°21'W., on random line bet. secs. 4 and 33.
40.00	Fail to find $\frac{1}{4}$ sec. cor. Set temp. cor.
77.49	A point 9 lks. S. of the cor. of secs. 4,5,32 and 33.
	Thence from cor.,
	N.89°30'W., on random line bet. secs. 5 and 32.
40.00	Fail to find $\frac{1}{4}$ sec. cor. Set temp. cor.
80.56	A point 2 lks. S. of the cor. of secs. 5,6,31 and 32.
	Thence from cor.,
	N.86°44'W., on random line bet. secs. 6 and 31.
40.00	Fail to find $\frac{1}{4}$ sec. cor. Set temp. cor.
81.53	A point 9 lks. S. of the cor. of Tps. 11 and 12 N., Rs. 2 and 3 E., hereinbefore described.
	Thence from Tp. cor.,
	S.86°40'E., on true line bet. secs. 6 and 31.
	Over rolling land, through scattering undergrowth.
.27	Corner of ^{wire} fences bearing N. E. and W.; desc. 46 ft. over gentle E. slope.
23.90	Small drain, course S.; asc. 50 ft. over gentle W. slope.
40.00	Proportional distance,
	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 31}{S\ 6}$ 1934
	Over flat.
59.00	Fence, bears N. and S.; desc. 123 ft. over E. slope.
70.10	Enter Ash Creek wash, water 80 lks. wide, 1 in deep, course S.
72.80	Leave same; bank 27 ft. high.; asc. 102 ft. over SW. slope.
81.53	The cor. of secs. 5,6,31 and 32, a stake, 2 ins. square by 18 ins. long, badly decayed, marks partly legible, in a mound of stone.
	At point for cor., with old stake alongside,
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 5,6,31 and 32, with brass cap mkd.

Resurvey of Part of South Boundary of T. 12 N., R. 3 E. 11

ECCO 4021

Chains

T 12 N R 3 E
 S 31 | S 32
 S 6 | S 5
 T 11 N
 1934

raise a mound
 of stone, 3 ft. base, 2 ft. high, W. of cor.

A corner of wire fence, bearing N. and E. bears 20 lks. N.

Land, rolling.

Soil, adobe and gravel; 2nd rate.

Timber none; undergrowth, scrub oak, quinine and cats-claw.

S.89°29'E., on true line bet. secs. 5 and 32.

Ascend 112 ft. over W. slope, through scattering undergrowth.

21.00 Descend 35 ft. over flat top spur, slopes S.

40.28 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 32
 S 5
 1934

raise a mound
 of stone, 3 ft. base, 2 ft. high, N. of cor.

An E. and W. wire fence, bears 1.36 chs. S.

Over flat.

50.00 Slope changes; desc. 113 ft. over E. slope.

56.60 Rocky wash, 50 lks. wide, traces of water, course S.; asc. 115 ft. over W. slope.

64.00 Over flat, bears E. and W.

80.56 The cor. of secs. 4, 5, 32 and 33, a decayed stake of indeterminate size with dim marks, in a mound of stone.

At point for cor., in the mound of stone,

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with the original stake alongside, and in a mound of stone to top, for cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

T 12 N R 3 E
 S 32 | S 33
 S 5 | S 4
 T 11 N
 1934

Wire fences, bear irregularly E. W. and S.

Land, rolling and flat.

Soil, adobe, 1st rate; and rocky, 3rd rate.

No timber; undergrowth, scrub oak, cats claw and cactus.

12 Resurvey of Part of South Boundary of T. 12 N., R. 3 E.

Chains	N.88°25'E., on true line bet. secs. 4 and 33. Over rolling land, through scattering undergrowth.
.30	Road, bears N. and S.; asc. 38 ft. over gentle W. slope.
23.30	Flat spur, slopes S.; desc. 132 ft. over E. slope.
30.10	Rock fence, bears NW. and SE.
36.10	Ditch, 2 lks. wide at bottom, bears NW. and SE.
38.00	Enter rocky bottom of Spring Creek, traces of water, course S.
38.74	True point for $\frac{1}{2}$ sec. cor. falls in wash, an unsuitable place for a permanent corner.
39.50	Leave wash; asc. 15 ft. over W. slope.
39.94	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X deposited at the base, and in a mound of stone to top, for witness $\frac{1}{2}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \text{WC } \frac{1}{4} \text{ S } 33 \\ \hline \text{S } 4 \\ 1934 \end{array}$
	Ascend 173 ft. over W. slope.
45.50	Top of cliff; faces W.; asc. 130 ft. over gentle W. and SW. slopes.
77.49	The cor. of secs. 3, 4, 33 and 34; a stone, 16x16x14 ins. above ground, firmly set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, adobe, 2nd rate; and rocky, 4th rate No timber; undergrowth, scrub oak, cats claw, cactus and quinine.
----- East Boundary of T. 12 N., R. 3 E. -----	
	Beginning at the cor. of Tps. 11 and 12 N., Rs. 3 and 4 E., an iron post, 3 ins. diam., 2 ins. above a large mound of stone, firmly set, mkd. on brass cap and witnessed as described in the official record.
	North, on E. bdy. of sec. 36.
	Over rolling land, through scattering undergrowth.
	Descend 20 ft. over NW. slope.
.70	Wire fence, bears NNE. and SSW.
2.50	Wire fence, bears irregularly E. and W.
3.60	Road, bears E. to Sycamore, and W. to Mayer; desc. 50 ft. over gentle NE. slope.
15.35	Telephone line, parallels power line.
19.60	Power Line, bears NW. and SE.

Chains 40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 36 1934</p> <p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Descend 25 ft. over N. slope.</p>
42.60	Rocky wash, 60 lks. wide, course W.; asc. 210 ft. over S. slope.
52.20	Drain, course SW.
59.70	Over flat spur, slopes W.
69.80	Leave same; desc. 125 ft. over N. slope.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25 and 36 only, with brass cap mkd.</p> <p style="text-align: center;">T 12 N R 3 E S 25 S 36 1934</p> <p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, scrub oak and cats claw.</p>

	<p>North, on E. bdy. of sec. 25.</p> <p>Descend 50 ft. over N. slope, through scattering undergrowth.</p>
19.50	Draw, course N.70°W.; desc. 20 ft. over NW. slope.
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 25 only, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 25 1934</p> <p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
44.70	Wash, 30 lks. wide, course N.70°W.
47.80	Wash, 15 lks. wide, course SW.
64.40	Shallow wash, 25 lks. wide, course SW.; asc. 100 ft. over S. slope.

Chains											
79.90	Spur., slopes SW.										
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 24 and 25 only, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 12 N</td><td></td></tr> <tr><td>R 3 E</td><td></td></tr> <tr><td>S 24</td><td> </td></tr> <tr><td>S 25</td><td> </td></tr> <tr><td></td><td>1934</td></tr> </table>	T 12 N		R 3 E		S 24		S 25			1934
T 12 N											
R 3 E											
S 24											
S 25											
	1934										
	Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, scrub oak, cats claw and quinine.										
	North, on E. bdy. of sec. 24.										
	Over rolling land, through scattering undergrowth.										
7.00	Small drain, course SW.										
12.10	Slope changes; desc. 80 ft. over NW. slope.										
17.10	Fence, bears E. and W.										
19.50	Wash, 30 lks. wide, course SW.										
24.70	Drain, 10 lks. wide, course SW.; asc. 40 ft. over SE. slope.										
26.30	Over flat spur, slopes SW.										
31.30	Leave same; desc. 24 ft. over NW. slope.										
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 24 only, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>$\frac{1}{4}$</td><td></td></tr> <tr><td>S 24</td><td> </td></tr> <tr><td></td><td>1934</td></tr> </table>	$\frac{1}{4}$		S 24			1934				
$\frac{1}{4}$											
S 24											
	1934										
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.										
	Over flat.										
61.00	Descend 66 ft. over gradual N. slope.										
72.20	Draw, 30 lks. wide, course W.; a box ravine, 30 ft. deep, bears 2 chs. E.; asc. 138 ft. over S. slope.										
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 13 and 24 only, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 12 N</td><td></td></tr> <tr><td>R 3 E</td><td></td></tr> <tr><td>S 13</td><td> </td></tr> <tr><td>S 24</td><td> </td></tr> <tr><td></td><td>1934</td></tr> </table>	T 12 N		R 3 E		S 13		S 24			1934
T 12 N											
R 3 E											
S 13											
S 24											
	1934										
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.										

East Boundary of T. 12 N., R. 3 E.

15

1934

Chains. Land, rolling.
Soil, adobe and rocky; 2nd rate.
No timber; undergrowth, scrub oak, cats claw and quinine.

North, on E. bdy. of sec. 13.

Over rolling land, through scattering undergrowth.

2.20 Spur, slopes SE.; desc. 57 ft. over NE. slope.

12.20 Head of ravine, course SE.; asc. 75 ft. over SE. slope.

27.10 Spur, slopes SE.; desc. 44 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 13 only, with brass cap mkd.

$\frac{1}{4}$
S 13 |
1934

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

41.00 Drain, course SE.; asc. 340 ft. over S. slope.

76.30 Over flat spur, slopes SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 12 and 13 only, with brass cap mkd.

T 12 N
R 3 E
S 12 |
S 13 |
1934

Land, rolling.
Soil, adobe and rocky; 2nd rate.
No timber; undergrowth, scrub oak, cats claw and quinine.

North, on E. bdy. of sec. 12.

Over rolling land, through scattering undergrowth.

Descend 35 ft. over gentle NW. slope.

19.20 Fence, bears NE. and SW.

20.80 Leave flat topped spur, slopes SW.; desc. 70 ft. over NW. slope.

24.70 Ravine, course SW.; asc. 74 ft. over SW. slope.

39.00 Over rolling top of spur, slopes W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd.

Chains	
	$\frac{1}{4}$ S 12 1934
47.70	Leave spur; desc. 136 ft. over NW. slope.
57.50	Draw, course SW.; asc. 231 ft. over rocky SW. slope.
71.50	Saddle in spur, slopes S. 75° W.; desc. 150 ft. over N. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 1 and 12 only, with brass cap mkd.
	T 12 N R 3 E S 1 S 12 1934
	Land, rolling. Soil, adobe, 2nd rate; and rocky, 3rd rate. No timber; undergrowth, scrub oak, quinine and cats claw.

	North, on E. bdy. of sec. 1.
	Over rolling land, through scattering undergrowth.
	Descend 30 ft. over N. slope.
5.60	Drain, course SE.; asc. 33 ft.
13.00	Slope changes; desc. 16 ft.
20.60	Small ravine, course SE.; asc. 120 ft. over SE. slope.
34.80	Long spur, slopes SW.; asc. 50 ft. over S. slope.
40.76	At this point which is 40.20 chs. dist. from the closing cor. of T. 12 N., Rs. 3 and 4 E., such distance being equal to the original distance of the $N\frac{1}{2}$ of the W. bdy. of sec. 1,
	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor. of sec. 1 only, with brass cap mkd.
	$\frac{1}{4}$ S 1 1934
	Ascend 448 ft. over SW. slope.
67.00	Spur, slopes NW.; desc. 168 ft. over N. slope.
80.96	Intersect the 3rd Standard Parallel North,
	Set an iron post, 3 ft. long, 3 ins. diam., 16 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of Tps. 12 N., Rs. 3 and 4 E., with brass cap mkd.

Chains

T 13 N R 3 E
 S 35
 S 1 | S 6
 C | C
 R 3 E | R 4 E
 T 12 N
 1934

From point of intersection the standard cor. of secs. 35 and 36, bears S.89°30'E., 13.22 chs. dist.; an iron post, 2 ins. diam., 4 ins. above a mound of stone, firmly set, mkd. on brass cap and witnessed as described in the official record.

From the same point the standard $\frac{1}{2}$ sec. cor. of sec. 35, bears N.89°30'W., 28.19 chs. dist.

Land, rolling and mountainous.
 Soil, adobe, 2nd rate; and rocky, 3rd rate.-
 No timber; undergrowth, scrub oak, scrub cedar, cats claw and quinine.

 Dependent Resurvey of the Subdivisions
 of T. 12 N., R. 3 E.

The west 5 tiers of sections of Township 12 North, Range 3 East, were surveyed in 1873 by C.B. Foster, U. S. Deputy Surveyor, with no official retracements or resurveys of record.

The following notes describe the complete resurvey of the west 5 tiers of sections and the survey of the east tier of sections.

Preliminary to the resurvey, a retracement of all of the 1873 subdivisional lines was made, resulting in the positive identification of only the $\frac{1}{2}$ sec. cor. of secs. 17 and 18, and the cor. of secs. 26, 27, 34 and 35.

Under the dependent method of resurvey, the NE. cors. of secs. 31, 32 and 33 were reestablished at points proportionate in latitude and longitude between existing or reestablished sec. cors. in four directions; the remaining sec. cors. were reestablished at points proportionate in latitude and at the 1873 record in departure from the nearest section corner in the same row of sections to the west.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

N.1°24'W., on true line on E. bdy. of sec. 35.

Descend 46 ft. over rolling N. slope, through scattering undergrowth; along a wire fence approximately on line.

- 7.60 Enter square wire fence corral.
 9.80 Leave same.
 10.00 Slope changes; asc. 20 ft. over E. slope.
 21.90 Wire fence, bears NE. and 1 ch. SW. to fence corner.
 22.00 Slope changes; desc. 109 ft. over NE. slope.
 39.90 Mid point between the NW. cor. of sec. 36, hereinafter described and the SW. cor. of sec. 36.

Chains.	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd. $\frac{1}{4}$ s 36 1934
40.16	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 35 only, with brass cap mkd. $\frac{1}{4}$ s 35 1934 Descend 187 ft. over N. slope.
50.50	A dry creek bed, 50 lks. wide, course W.; asc. 183 ft. over S. and SW. slopes.
51.90	Telephone Line, parallels power line.
53.95	Road, bears NW. to Mayer, and SE. to Sycamore.
59.75	Power Line, bears E. and W.
69.00	Short spur, slopes W.; desc. 105 ft. over NW. slope.
80.32	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 26 and 35 only, with brass cap mkd. T 12 N R 3 E S 26 s 35 1934 raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, rolling. Soil, adobe, 2nd rate; and rocky, 3rd rate. No timber; undergrowth, scrub oak, cats claw, mesquite and cactus.

	N.7°25'W., on true line on E. bdy. of sec. 26. Over rolling land, through scattering undergrowth.
.25	Wash, 10 lks. wide, course SW.; asc. 104 ft. over SW. slope.
23.50	Spur, slopes W.; desc. 146 ft. over N. slope.
30.50	Wash, 25 lks. wide, course SW.
33.10	End of spur, slopes W.
35.80	Wash, 30 lks. wide, course SW.; asc. 40 ft. over SE. slope.
39.82	Mid point between the NW. and SW. cors. of sec. 25,

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

Chains. hereinafter described.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 25 only, with brass cap mkd.

$\frac{1}{4}$
| S 25
1934

40.49 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 26 only, with brass cap mkd.

$\frac{1}{4}$
S 26 |
1934

Ascend 310 ft. over general S. slope.

73.60 Fence, bears NE. and SW.

80.98 Set an iron post, 3 ft. long, 2 ins. diam., 17 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 23 and 26 only, with brass cap mkd.

T 12 N R 3 E
S 23 |
S 26 |
1934

Land, rolling.
Soil, rocky and adobe; 2nd rate.
No timber; undergrowth, scrub oak, cats claw, quinine and cactus.

N.0°30'E., on true line on E. bdy. of sec. 23.

Over rolling land, through scattering undergrowth.

4.90 Spur, slopes NW.; desc. 109 ft. over NE. slope.

24.00 Drain, course SE.; asc. 70 ft. over SW. slope.

38.70 Spur, slopes SE.; over E. slope.

39.20 Mid point between the NW. and SW. cors. of sec. 24, hereinafter described.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 24 only, with brass cap mkd.

$\frac{1}{4}$
| S 24
1934

of stone, 3 ft. base, 2 ft. high, E. of cor. raise a mound

Chains.	
40.15	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 23 only, with brass cap mkd.
	$\frac{1}{4}$ S 23 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
45.10	Ridge, bears NE. and SW.; desc. 58 ft. over N. slope.
55.10	Head of ravine, course NW.; asc. 362 ft. over SW. slope.
80.29	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 14 and 23 only, with brass cap mkd.
	T 12 N R 3 E S 14 S 23 1934
	Land, rolling. Soil, rocky and adobe; 2nd rate. No timber; undergrowth, scrub oak, cats claw, cactus and quinine.

	N.1°30'E., on true line on E. bdy. of sec. 14. Over rolling land, through scattering undergrowth.
1.00	Low rocky spur, slopes SE.; desc. 347 ft. over NE. slope.
28.50	Over flat, bears E. and W.
38.95	Mid point between the NW. and SE. cors. of sec. 13, hereinafter described, Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 13 only, with brass cap mkd.
	$\frac{1}{4}$ S 13 1934
40.16	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 14 only, with brass cap mkd.
	$\frac{1}{4}$ S 14 1934
	Ascend 45 ft. over gentle SW. slope.
65.20	Slope changes; desc. 74 ft. over gentle NW. slope.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

L. 4028

Chains.
80.32

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 11 and 14 only, with brass cap mkd.

T 12 N R 3 E
 S 11 |
 S 14 |
 1934

Land, rolling.

Soil, adobe and rocky; 2nd rate.

No timber; undergrowth, oak brush, cats claw, cactus and quinine.

N.0°54'E., on true line on E. bdy. of sec. 11.

Over rolling land, through scattering undergrowth.

Descend 38 ft. over N. slope.

9.30 Rocky wash, 30 lks. wide, course SW.; asc. 361 ft. over SE. slope.

38.00 Spur, slopes W.; desc. 10 ft. over NW. slope.

38.60 Mid point between the NW. and SW. cors. of sec. 12, hereinafter described,

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd.

$\frac{1}{4}$
 | S 12
 1934

40.15 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 11 only, with brass cap mkd.

$\frac{1}{4}$
 | S 11 |
 1934

Descend 345 ft. over NW. slope.

70.90 Wash, 20 lks. wide, course SW.; asc. 100 ft. over S. slope.

80.30 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 2 and 11 only, with brass cap mkd.

T 12 N R 3 E
 S 2 |
 S 11 |
 1934

Land, rolling.

Chains.	Soil, adobe, 2nd rate; and rocky, 3rd rate. No timber; undergrowth, oak brush, cats claw, quinine and cactus.

	N.9°38'E., on true line on E. bdy. of sec. 2. Over rolling land, through scattering undergrowth. Ascend 181 ft. over SE. slope.
8.90	Spur, slopes SW.; desc. 215 ft. over broken N. slope.
33.60	Small ravine, course SW.; asc. 34 ft. over SE. slope.
40.72	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone, 4x4x2 ins.; mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 2 S 1 1934
	Ascend 262 ft. over SE. slope.
73.00	Spur, slopes SE.; a branch spur, slopes N.70°E.; desc. 127 ft. over NE. slope.
81.64	The closing cor. of secs. 1 and 2, hereinbefore described. Land, rolling. Soil, adobe, and rocky; 3rd rate. No timber; undergrowth, scrub cedar, scrub oak, cats-claw, cactus and quinine.

Subdivision of T. 12 N., R. 3 E.	

	Beginning at the cor. of secs. 25 and 36, on the E. bdy. of the Tp. N.89°42'W., on true line bet. secs. 25 and 36; parallel to the mean bearing of S. bdy. of sec. 36. Over rolling land, through scattering undergrowth. Ascend 70 ft. over gentle NE. slope.
38.00	Slope changes; desc. 10 ft. over NW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 25 S 36 1934
	raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
	Over N. slope.

Chains.	
73.00	Low spur, slopes NW.; desc. 93 ft. over W. slope.
82.20	Intersect the E. bdy. of sec. 35. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 25 and 36, with brass cap mkd.
	<pre> T 12 N R 3 E S 35 S 25 CC S 36 1934 </pre>
	raise a mound of stone, 3 ft. base, 3 ft. high, E. of cor.
	From point of intersection the cor. of secs. 26 and 35 only, bears N.1°24'W., 52 lks. dist.
	Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	From the cor. of secs. 24 and 25, on the E. bdy. of the Tp. N.89°42'W., on true line bet. secs. 24 and 25. Over rolling land, through scattering undergrowth.
1.00	Leave top of spur, slopes SW.; desc. 55 ft. over rolling W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<pre> $\frac{1}{4}$ S 24 S 25 1934 </pre>
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
50.80	A dry creek bed, 50 lks. wide, course S.; asc. 162 ft. over SE. slope.
58.40	Rocky spur, slopes S.; desc. 74 ft. over W. slope.
65.00	Ravine, course SW., soon S.; asc. 235 ft. over SE. slope.
78.40	Over flat top of spur, slopes SE.
78.45	Fence, bears N.70°E. and S.70°W.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, and in a mound of stone, 3 ft. base to top, for cor. of lots 7 and 8 of sec. 24, and of lots 1 and 2 of sec. 25, with brass cap mkd.
	<pre> S 24 7 + 8 + 1 2 + 1 S 25 1934 </pre>

Chains.
92.61

Intersect the E. bdy. of sec. 26.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 24 and 25, with brass cap mkd.

	T 12 N	
	R 3 E	
s 26	S 24	cc
	S 25	
	1934	

From point of intersection the cor. of secs. 23 and 26 only, bears N.7°25'W., 81 lks. dist.

Land, rolling.

Soil, adobe and rocky; 3rd rate.

No timber; undergrowth, oak brush, cats claw, quinine and cactus.

From the cor. of secs. 13 and 24, on the E. bdy. of the Tp.

N.89°42'W., on true line bet. secs. 13 and 24.

Over rolling land, through scattering undergrowth.

Descend 75 ft. over W. slope.

18.00 Slope changes; asc. slightly.

31.10 Drain, course S.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 13	
	S 24	
	1934	

41.60 Draw, 12 ft. deep, course SE.; asc. 448 ft. over general E. slope.

73.95 Fence, bears S. and N.

80.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. of lots 7 and 8 of sec. 13, and of lots 1 and 2 of sec. 24, with brass cap mkd.


	S 13	
	7 8	
	2 1	
	S 24	
	1934	

90.60 Rocky spur, slopes SE.; over SW. slope.

92.08 Intersect the E. bdy. of sec. 23.

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 13 and 24, with brass cap mkd.

Chains



From point of intersection the cor. of secs. 14 and 23 only, bears N.0°30'E., 1.10 chs. dist.

Land, rolling.
Soil, adobe, 2nd. rate; and rocky, 3rd rate.
No timber; undergrowth, scrub oak, cats claw, cactus and quinine.


From the cor. of secs. 12 and 13, on the E. bdy. of the Tp.

N.89°42'W., on true line bet. secs. 12 and 13.

Descend 260 ft. over rolling W. slope, through scattering undergrowth.

29.00 Foot of slope; over level land.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



of stone, 3 ft. base, 2 ft. high, N. of cor. raise a mound

60.00 Ascend about 50 ft. over gentle NE. slope.


80.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. of lots 7 and 8 of sec. 12, and for cor. of lots 1 and 2 of sec. 13, with brass cap mkd.



Descend about 40 ft. over gentle NW. slope.

90.08 Intersect the E. bdy. of sec. 14,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for closing cor. of secs. 12 and 13, with brass cap mkd.



of stone, 3 ft. base, 2 ft. high, E. of cor. raise a mound

From point of intersection the cor. of secs. 11 and 14 only, bears N.1°30'E., 1.31 chs. dist.

Land, rolling.
Soil, adobe and rocky; 2nd rate.
No timber; undergrowth, scrub oak, cats claw, cactus and

Chains. quinine.

From the cor. of secs. 1 and 12, on the E. bdy. of the Tp. N.89°42'W., on true line bet. secs. 1 and 12.

Over rolling land, through scattering undergrowth.

1.70 Drain, course NE.; asc. 98 ft. over NW. slope.

9.00 Spur, slopes SE.; desc. 111 ft. over SW. slope.

17.50 Head of ravine, course S.; asc. 100 ft. over SE. slope.

35.00 Over top of flat spur, slopes S.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a stone mkd. x, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. of sec. 12 only, with brass cap mkd.

1/4 S 12

1934

48.72 At a point 40.00 chs. E. of the SW. cor. of sec. 1,

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. of sec. 1 only, with brass cap mkd.

1/4 S 1

1934

53.40 Leave top of spur; desc. 220 ft. over W. slope.

71.97 Wash, 40 lks. wide, course SW.; asc. 53 ft.

80.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of lots 1 and 2 of sec. 12, with brass cap mkd.

2 | 1

S 12

1934

88.72 Intersect the E. bdy. of sec. 11.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a stone, 6x2x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 1 and 12, with brass cap mkd.

T 12 N R 3 E

S 11 | S 1 CC

S 12

1934

From point of intersection the cor. of secs. 2 and 11 only, hereinbefore described, bears N.0°53'E., 1.80 chs. dist.

Chains.	<p>Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, cats claw, scrub oak, quinine and cactus.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.</p> <hr/> <p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., an iron post, 2 ins. diam., 8 ins. above ground, firmly set, properly mkd. on brass cap, and witnessed as described in the official record.</p> <p>N. 2° 03' E., on true line bet. secs. 34 and 35.</p> <p>Over rolling land, through scattering undergrowth.</p> <p>Ascend 83 ft. over gentle S. slope.</p> <p>29.00 Ridge, bears NE. and S. 70° W.; desc. 92 ft. over NE. slope.</p> <p>41.21 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 34 S 35 1934 </div> <p>Descend 194 ft. over NE. slope.</p> <p>66.80 Fence, bears E. and W.; corner of fence to S. bears about 45 lks. W.</p> <p>76.20 Ravine, course NW.; asc. 50 ft. over SW. slope.</p> <p>80.05 Spur, slopes NW.; desc. 10 ft. over N. slope.</p> <p>82.42 The cor. of secs. 26, 27, 34 and 35, which is the rotted remains of identifiable old stake in a mound of stone.</p> <p>In the mound, with the fragments of old stake placed alongside,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.</p> <div style="text-align: center;"> T 12 N R 3 E S 27 S 26 S 34 S 35 1934 </div> <p style="text-align: right;">raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p> <p>Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, scrub oak, cats claw, cactus and quinine.</p> <hr/>
---------	--

Chains.	From the cor. of secs. 26 and 35.
	N.88°12'W., on true line bet. sees. 26 and 35.
	Over rolling land, through scattering undergrowth.
5.50	Small drain, course S.; asc. 110 ft. over SE. slope.
19.50	Spur, slopes S.25°E.; desc. 150 ft. over SW. slope.
37.90	Power line, bears N.62½°W. and S.62½°E.
40.07	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 26}{S \ 35}$ 1934
	Descend 55 ft. over SW. slope.
43.00	Road, bears NW. to Mayer, and SE. to Sycamore.
44.60	Over bottom land, bears N. and S.
52.00	Spring Creek, 8 lks. wide, 3 ins. deep in channel, 80 lks. wide, 6 ft. deep, course NW.
54.00	Fence, bears NW. and SE.
59.00	Leave bottom land, bears NW. and SE.; asc. 130 ft. over NE. slope.
59.40	Telephone Line, parallels power line.
64.50	Over top of spur, slopes NW.
70.00	Leave same; desc. 90 ft. over NW. slope.
80.14	The cor. of secs. 26, 27, 34 and 35.

Land, rolling.
Soil, adobe, 1st rate; and rocky, 2nd rate.
Timber, ash in creek bottom and few scrub cedars.
Undergrowth, oak brush, mesquite, cats claw, cactus,
alder, willow and quinine.

	N.7°27'W., on true line bet. secs. 26 and 27.
	Over rolling land, through scattering undergrowth.
	Descend 75 ft. over NW. slope.
5.60	South bank of Spring Creek, 3 ft. high, bears SW. and NE. Over bottom land, partly washed.
10.50	Telephone line, bears N.70°W. and S.70°E.
12.80	Spring Creek, 8 lks. wide, course SW.
13.30	Leave creek bottom, bears SW. and NE.; asc. 75 ft. over SE. slope.
19.70	Power line, bears S.75°E. and N.75°W.; hill, bears 3 chs. W.; desc. 23 ft. over NE. slope.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

4028

Chains. 27.80	Road, bears W. to Mayer, and E. to Sycamore; over E. slope.
39.20	Drain, 8 ft. wide, 3 ft. deep, course SE.
40.38	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 27 S 26 1934
41.80	Drain, 10 lks. wide, 3 ft. deep, course SE.; asc. 140 ft. over W. slope to cor.
63.30	Small drain, 4 ft. deep, course W.
66.40	Wash, 10 lks. wide, course SW.; ascend over S. slope.
80.76	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd. T 12 N R 3 E S 22 S 23 S 27 S 26 1934 Land, rolling. Soil, adobe; 2nd rate. No timber; undergrowth, scrub oak, scrub cedar, mesquite, cats claw, quinine and cactus.

	From the cor. of secs. 23 and 26. N.88°18'W., on true line bet. secs. 23 and 26. Over rolling land, through scattering undergrowth. Descend 77 ft. over gentle SW. slope.
7.50	Drain, course SE.; asc. 170 ft. over NE. slope.
26.00	Ridge, bears N. and S.; desc. 120 ft. over SW. slope.
40.14	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 23 S 26 1934
	Descend 300 ft. over SW. slope.
46.00	Fence, bears N. and S.
63.20	Wash, 30 lks. wide, course SW.; asc. 60 ft. over SE. slope.
78.30	Low spur, slopes S.; desc. 12 ft. over SW. slope.

Chains.
80.29

The cor. of secs. 22, 23, 26 and 27.


Land, rolling.
Soil, adobe; 2nd rate.
No timber; undergrowth, oak brush, mesquite, cats claw
and cactus.

N.0°28'E., on true line bet. secs. 22 and 23.

Over gentle SW. slope, through scattering undergrowth.

29.00 Slope changes; over gentle NW. slope.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.




raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

Descend 48 ft. over NW. slope.

54.40 Wash, 25 lks. wide, course W.; asc. 115 ft. over S. slope.

80.08 Set an iron post, 3 ft. long, 2 ins. diam., on cross(X)
on exposed bedrock, and in a mound of stone to top, for
cor. of secs. 14, 15, 22 and 23, with brass cap mkd.



Land, gently rolling.
Soil, adobe and rocky; 2nd rate.
No timber; undergrowth, scrub oak, cats claw, cactus and
quinine.

From the cor. of secs. 14 and 23.

N.88°26'W., on true line bet. secs. 14 and 23.


Over rolling land, through scattering undergrowth.

Descend 266 ft. over SW. slope.

28.00 Slope changes; asc. 136 ft. over SE. slope.

38.50 Spur, slopes SW.; desc. 58 ft. over NW. slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the
ground to bedrock, with a stone mkd. X, deposited at the
base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor.,
with brass cap mkd.



Descend 308 ft. over gradual NW. slope.

Chains.	
49.50	Fence, bears N. and S.
80.02	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, scrub oak, cats claw, cactus and quinine.

	N.1°30'E., on true line bet. secs. 14 and 15. Over rolling land, through scattering undergrowth. Descend 50 ft. over NW. slope.
5.00	Drain, course SW.; asc. 178 ft. over SW. slope.
9.00	Fence, bears E. and W.
35.00	Spur, slopes W.; desc. 65 ft. over NW. slope.
40.05	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 15 \mid S\ 14 \\ 1934 \end{array}$
	Descend 77 ft. over NW. slope.
47.40	Small drain, course W.; asc. 20 ft.
50.00	Short spur, slopes W.; asc. 53 ft. over rolling SW. slope.
80.10	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd. $\begin{array}{c} T\ 12\ N\ R\ 3\ E \\ S\ 10 \mid S\ 11 \\ S\ 15 \mid S\ 14 \\ 1934 \end{array}$
	Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, scrub oak, quinine, cats claw and cactus.

	From the cor. of secs. 11 and 14. N.88°30'W., on true line bet. secs. 11 and 14. Descend 70 ft. over gradual NW. slope, through scattering undergrowth.
17.50	Draw, course SW.; asc. 68 ft. over SE. slope.
26.80	Spur, slopes SW.; desc. 35 ft. over NW. slope.
38.20	Spur, slopes NW.; over S. slope.

Chains.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 11
S 14
1934

Descend 95 ft. over SW. slope.

48.80 Fence, bears N. and S.

60.90 Along S. bank of wash.

62.90 Wash, 30 lks. wide, course NE., soon NW.

78.00 Over top of flat spur, slopes NW.

80.02 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.

Soil, adobe and rocky; 2nd rate.

No timber; undergrowth, scrub oak, cats claw, cactus and quinine.

N.0°47'E., on true line bet. secs. 10 and 11.

Descend 116 ft. over NE. slope, through scattering brush.

16.50 Wash, 50 lks. wide, course NW.; asc. 40 ft. over SW. slope.

30.50 Low spur, slopes NW.; desc. 40 ft. over N. slope.

34.70 Drain, course NW.; asc. 11 ft. over gentle SW. slope.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 10 | S 11
1934

Ascend 35 ft. over gentle SW. slope.

49.80 Short spur, slopes W.; desc. 38 ft. over N. slope.

57.00 Over flat, bears E. and W.

80.09 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

T 12 N R 3 E
S 3 | S 2
S 10 | S 11
1934

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.

Soil, adobe and rocky; 2nd rate.

Dependent Resurvey of the Subdivisions of T.12 N., R. 3 E.

33

Chains.	No timber; undergrowth, scrub oak, cats claw, cactus and quinine.

	From the cor. of secs. 2 and 11. N.88°56'W., on true line bet. secs. 2 and 11. Over rolling land, through scattering undergrowth. Descend 157 ft. over SW. slope.
20.60	Wash, 30 lks. wide, course SW.; asc. 95 ft. over NE. slope.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 2}{S\ 11}$ 1934
	Descend 120 ft. over gradual SW. slope.
48.40	Fence, bears N. and S.
80.02	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak, cats claw, cactus and quinine.

	N.8°08'E., on true line bet. secs. 2 and 3. Over rolling land, through scattering undergrowth.
1.80	Wash, 20 lks. wide, course SW.
3.50	Enter same wash, course S.
5.40	Leave wash from NE.; asc. 50 ft. over SE. slope.
17.50	Spur, slopes SE.; desc. 30 ft. over gentle NE. slope.
36.00	Wash, 15 lks. wide, course SE.; asc. gently.
40.44	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 3 S 2 1934
	raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	Ascend 58 ft. over SW. slope.
48.50	Spur, slopes NW.; desc. 14 ft.

Chains.	
51.50	Wash, 15 lks. wide, course SW.; asc. 30 ft.
58.50	Slope changes; desc. 15 ft.
63.40	Slope changes; asc. 220 ft. over SW. slope to cor.
71.20	Gully, course SW.
81.04	The closing cor. of secs. 2 and 3, hereinbefore described. Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, scrub oak, scrub cedar, cats claw, quinine and cactus.

	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp. N.6°38'E., on true line bet. secs. 33 and 34. Descend 53 ft. over gentle NW. slope, through scattering undergrowth.
15.20	Swale, drains W.; asc. 18 ft.
28.00	Low hill, bears 4 chs. W.; desc. 108 ft. over N. slope.
38.20	Short ravine, course W.; asc. 60 ft. over S. slope.
40.56	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 33 S 34 1934
	Ascend 25 ft. over S. slope.
43.00	Flat topped spur, slopes W.; desc. 222 ft. over NW. slope.
46.60	Cliff, 30 ft. high, faces NW.
56.50	Slope changes; along W. slope.
74.00	Pool of water, 30 lks. wide, 1 ft. deep, in Spring Creek, course W.; asc. 146 ft. over SE. slope.
81.12	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd. T 12 N R 3 E S 28 + S 27 S 33 + S 34 1934 raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, adobe and rocky; 3rd rate. No timber; undergrowth, oak brush, cats claw, cactus, quinine and willow.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

Chains.	From the cor. of secs. 26, 27, 34 and 35. S. 89° 22' W., on true line bet. secs. 27 and 34. Over rolling land, through scattering undergrowth.
5.40	Ravine, course NW.
7.00	Enter marsh in creek bottom, bears NE. and SW.
12.00	Leave marsh, bears NE. and SW.; over bottom land.
22.00	Leave creek bottom, bears N. 75° E. and S. 75° W.; asc. bank 12 ft. high; over S. slope.
25.40	Drain, 3 ft. wide, 6 ft. deep, course S.
41.43	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 27</u> S 34 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Ascend 68 ft. over SE. slope.
49.00	Spur from NE., slopes W.; desc. 50 ft. over top of same.
64.00	Leave spur, slopes SW.; desc. 22 ft. over W. slope.
66.60	Ravine, course SW.; asc. 101 ft. over SE. slope.
79.00	Slope changes; over gentle S. slope.
82.86	The cor. of secs. 27, 28, 33 and 34. Land, rolling. Soil, adobe and rocky; 3rd rate. No timber; undergrowth, cats claw, oak brush, willow and cactus.
	N. 5° 17' W., on true line bet. secs. 27 and 28. Over rolling land, through scattering undergrowth. Ascend gradually.
1.70	Wire fence, bears NW. and SE.
22.60	Road, bears E. to Sycamore and W. to Mayer; asc. 33 ft.
34.00	Top of rise, bears NE. and SW.; desc. 10 ft. over NW. slope.
40.46	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 28 S 27 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Chains. Descend 126 ft. over NW. slope.

47.00 Telephone line, parallels power line.

50.50 Power line, bears N.70 $\frac{1}{4}$ °W. and S.70 $\frac{1}{4}$ °E.

55.10 Wash, 50 lks. wide, 2 ft. deep, course SW.; asc. 98 ft. over SE. slope.

66.30 Spur, slopes E. from SW.; desc. 41 ft. over N. slope.

76.00 Slope changes; asc. 35 ft. over SE. slope.

80.92 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T 12 N. R 3 E
S 21 + S 22
S 28 + S 27
1934

Land, rolling.
Soil, adobe and rocky; 3rd rate.
No timber; undergrowth, scrub oak, quinine, catsclaw and cactus.

From the cor. of secs. 22, 23, 26 and 27.

S.89°40'W., on true line bet. secs. 22 and 27.

Descend 40 ft. over gentle SW. slope, through scattering undergrowth.

30.00 Slope changes; asc. 25 ft. over gentle NE. slope.

39.90 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone mkd. x, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 22
S 27
1934

Ascend 23 ft. over gentle NE. slope.

45.00 Over top of spur, slopes NW.

50.00 Leave spur; desc. 145 ft. over W. slope.

71.10 Rocky wash, 20 lks. wide; traces of water, course SW.; asc. 98 ft. over SE. slope.

79.80 The cor. of secs. 21, 22, 27 and 28.

Land, rolling.
Soil, adobe and rocky; 2nd rate.
No timber; undergrowth, scrub oak, catsclaw, cactus and quinine.

Dependent Resurvey of the Subdivisions of T.12 N., R. 3 E.

Chains.	N.0°50'E., on true line bet. secs. 21 and 22. Over rolling land, through scattering undergrowth. Ascend 20 ft. over SE. slope.
1.60	Short spur, slopes E.; desc. 46 ft. over NE. slope.
12.80	Dim road, bears NE. and SW.; over rolling E. slope.
21.30	Low spur, slopes E.
36.70	Low spur, slopes E.
40.29	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 21 S 22 1934
	of stone, 3 ft. base, 2 ft. high, W. of of cor. raise a mound Over gentle E. slope.
65.30	Small wash, course E.
80.59	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15,16,21 and 22, with brass cap mkd. T 12 N R 3 E S 16 S 15 S 21 S 22 1934
	of stone, 3 ft. base, 2 ft. high, W. of cor. raise a mound Land, rolling and flat. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	From the cor. of secs. 14,15,22 and 23. S.89°47'W., on true line bet. secs. 15 and 22. Over rolling land, through scattering undergrowth. Descend 54 ft. over NW. slope.
9.40	Drain, course SW.; asc. 38 ft. over SE. slope.
24.80	Spur, slopes SW.; desc. 97 ft. over NW. slope.
39.70	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 15 S 22 1934
	of stone, 3 ft. base, 2 ft. high, N. of cor. raise a mound

Chains.	Ascend 72 ft. over NW. slope.
53.20	Drain, 15 lks. wide, course SW.; over flat.
76.00	Wash, 20 lks. wide, 1 ft. deep, course S.
79.40	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling and flat. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.
	N.1°03'E., on true line bet. secs. 15 and 16. Over gentle SE. slope, through scattering undergrowth.
6.35	Wire fence, bears E. and W.
40.29	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 16 S 15 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Ascend 100 ft. over gentle SE. slope.
54.70	Dim road, bears E. and W.
80.59	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.
	T 12 N R 3 E S 9 S 10 S 16 S 15 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, gently rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, scrub oak, cats claw, cactus and quinine.
	From the cor. of secs. 10, 11, 14 and 15. West, on true line bet. secs. 10 and 15. Descend 113 ft. over gentle W. slope, through scattering undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 10 S 15 1934

Dependent Resurvey of the Subdivisions of T, 12 N., R. 3 E.

Chains.	Descend 63 ft. over W. slope.
50.30	Rocky wash, 30 lks. wide, course SW.; asc. 75 ft. over E. slope.
65.90	Spur, slopes S.; over S. slope.
76.00	Wire fence, bears N. and S.
80.00	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, quinine, cats claw and cactus.

	N.0°47'E., on true line bet. secs. 9 and 10.
	Over rolling land, through scattering undergrowth.
	Ascend 74 ft. over S. slope.
6.15	Wire fence, bears E. and W.
19.50	Over top of flat spur, bears NE. and SW.
30.00	Descend gradually over NW. slope.
40.29	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone, 4x4x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 9 S 10 1934
	Descend 25 ft. over gradual NW. slope.
53.70	Dim road, bears NE. and SW.; desc. 60 ft. over gradual NE. slope.
80.59	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone, 5x4x3 ins., mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.
	T 12 N R 3 E S 4 S 3 S 9 S 10 1934
	Land, gently rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, cats claw and cactus.

	From the cor. of secs. 2, 3, 10 and 11.
	N.89°51'W., on true line bet. secs. 3 and 10.
	Over rolling land, through scattering undergrowth.
	Descend 8 ft.
4.00	Wash, 20 lks. wide, course SW.; asc. 53 ft. over SE. slope.

40 Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

Chains.	
15.00	Low spur, slopes S.; desc. 58 ft. over SW. slope.
30.00	Head of drain, course S.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 3</u> S 10 1934
	of stone, 3 ft. base, 2 ft. high, N. of cor. raise a mound
	Ascend 25 ft. over gentle E. slope.
45.00	Over flat top of spur, slopes S.
56.00	Leave spur; desc. 15 ft.
58.30	Drain, course SE.; asc. 70 ft. over gradual E. slope.
80.00	The cor. of secs. 3, 4, 9 and 10.
	Land, gently rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, cats claw, cactus, oak and quinine.

	N. 7° 11' E., on true line bet. secs. 3 and 4.
	Over rolling land, through scattering undergrowth.
	Ascend 40 ft. over SE. slope.
6.50	Short spur, slopes E.; desc. 98 ft. over NE. slope.
20.90	Rocky wash, 30 lks. wide, course irregularly SW.; asc. 240 ft. over S. slope.
40.61	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone, 5x5x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 4 S 3 1934
	Ascend 51 ft. over SE. slope.
52.30	Spur, slopes SW.; desc. 102 ft. over NW. slope.
79.50	Over W. slope.
81.22	The closing cor. of secs. 3 and 4, hereinbefore described.
	Land, rolling. Soil, adobe and rocky; 3rd rate. No timber; undergrowth, scrub oak, cats claw, quinine, scrub cedar and cactus.

Dependent Resurvey of the Subdivisions of T.12 N., R. 3 E.

Chains.	From the cor. of secs. 4,5,32 and 33, on the S. bdy. of the Tp.
	N.2°44'E., on true line bet. secs. 32 and 33.
	Over flat, through scattering undergrowth.
3.80	Road, bears N.25°W. and S.; over gradual SW. slope.
17.00	Same road, bears SW. and N.20°E.
30.00	Top of rise, bears E. and W.; over gradual NW. slope.
40.63	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 32 S 33 1934
	raise a mound
	of stone, 3 ft. base, 2 ft. high, W. of cor.
	Descend 30 ft. over N. slope.
46.50	Same road, bears NW. and SE.
47.50	Short ravine, course N.70°W.; asc. 37 ft.
51.00	Short spur, slopes W.; desc. 86 ft. over NW. slope.
59.00	Same road, bears E. and SW.
59.70	Creek bed, 40 lks. wide, water in pools, course SW.; asc. 78 ft. over SE. slope.
70.00	Over flat top of spur, slopes E.
72.50	Fence, bears S.63°W. and N. 63°E.
77.00	Leave spur; desc. 24 ft. over N. slope.
81.27	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 28,29,32 and 33, with brass cap mkd.
	T 12 N R 3 E S 29 S 28 S 32 S 33 1934
	raise a mound
	of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling.
	Soil, adobe and rocky; 2nd rate.
	No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	From the cor. of secs. 27,28,33 and 34.
	S.89°13'W., on true line bet. secs. 28 and 33.
	Over gentle SE. slope, through scattering undergrowth.
8.50	Spur, slopes SW.; over flat.

Chains	
12.00	Fence, bears SW. and NE.
30.00	Leave flat; desc. 126 ft. over NW. slope.
41.43	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 28 \\ \hline S 33 \\ 1934 \end{array}$
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
	Descend 65 ft. over W. slope.
46.00	Creek bottom, 30 lks. wide, water 4 lks. wide, course SW. asc. 65 ft. over rolling SE. slope.
63.50	Low spur, slopes SW.; desc. 40 ft. over rolling NW. slope.
70.80	Fence, bears N. and S.
79.50	Road, bears SE. and NW.
82.86	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling. Soil, adobe and rocky; 3rd rate. No timber; undergrowth, oak brush, quinine, cats claw and cactus.

	N.3°06'W., on true line bet. secs. 28 and 29.
	Descend 35 ft. over gradual NW. slope, through scattering undergrowth.
5.50	Road, bears NW. and SE.
15.80	A spring and water hole, surrounded by trees, bears 5 chs. W.
40.65	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 29 S 28 \\ \hline 1934 \end{array}$
	raise a mound
	of stone, 3 ft. base, 2 ft. high, W. of cor.
45.50	Drain, 15 lks. wide, 3 ft. deep, course SW.
50.20	Fence, bears NW. and SE.
58.60	Road, bears NW. to Mayer, and SE. to Sycamore; -asc. 45 ft. over S. slope.
69.00	Slope changes; along W. slope.
71.20	Small ravine, course SW.; asc. 50 ft. over SE. slope.
78.10	Telephone line, bears S.70°E. and N.70°W.
81.30	Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

E.C. ...

Chains	<p>ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.</p> <p style="text-align: center;"> T 12 N R 3 E S 20 S 21 S 29 S 28 1934 </p> <p>SE. Cor. of Arizona Power Co., steel tower No. 215, bears N.67°45'W., 1.01 chs. dist.</p> <p>Land, flat and rolling. Soil, adobe; 2nd rate. No timber; undergrowth, oak brush, quinine, cats claw and cactus.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S.89°40'W., on true line bet. secs. 21 and 28.</p> <p>Over rolling land, through scattering undergrowth.</p> <p>Ascend 85 ft. over SE. slope.</p> <p>8.00 Hill, bears NE. and SW.; desc. gently.</p> <p>15.00 Dim road, bears N. and S.; asc. 25 ft. over E. slope.</p> <p>20.30 Top of rise, bears N. and S.; desc. 37 ft.</p> <p>28.00 Over S. slope.</p> <p>38.00 Top of rise, bears N. and S.; desc. 8 ft.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ <u>S 21</u> S 28 1934 </p> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Descend 133 ft. over gentle W. slope.</p> <p>79.60 Power line, bears S.70$\frac{1}{4}$°E. and N.70$\frac{1}{2}$°W.</p> <p>80.00 The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, flat and rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.</p> <hr/> <p>N.0°51'E., on true line bet. secs. 20 and 21.</p> <p>Over W. slope, through scattering undergrowth.</p> <p>12.00 Drain in channel, 15 ft. deep, course W.; asc. 120 ft. over gradual W. slope.</p> <p>31.10 Low spur, slopes W.; desc. 22 ft. over NW. slope.</p> <p>40.59 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the</p>
--------	--

Chains	ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 20 S 21 1934
	Descend 54 ft. along W. slope.
55.00	Slope changes; asc. 30 ft. along W. slope.
68.00	Slope changes; desc. 20 ft. over NW. slope.
73.30	Drain, 25 lks. wide, 6 ft. deep, course W.; desc. 20 ft. over NW. slope.
81.19	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.
	T 12 N R 3 E S 17 S 16 S 20 S 21 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling. Soil, adobe and rocky; 3rd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	From the cor. of secs. 15, 16, 21 and 22. N. 89° 52' W., on true line bet. secs. 16 and 21. Over gradual E. slope.
10.00	South end of hill, 70 ft. high, bears N. and S.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 16 S 21 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Ascend 93 ft. over E. slope.
65.00	Ridge, bears N. and S. 30° W.; desc. 210 ft. over W. slope.
80.00	The cor. of secs. 16, 17, 20 and 21. Land, flat and rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, cats claw, oak brush, quinine and cactus.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

BOOK 407

Chains.	N.1°06'E., on true line bet. secs. 16 and 17.
	Descend 10 ft. over NW. slope, through scattering undergrowth.
2.00	Drain, 5 lks. wide, 2 ft. deep, course W.; asc. 31 ft. over rocky SW. slope.
7.80	Wire fence, bears E. and W.
10.00	Low spur, slopes W.; over rolling W. slope.
37.00	Low spur, slopes W.; desc. 33 ft. over N. slope.
40.59	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 17 S 16 1934
	Descend 83 ft. over N. slope.
47.00	Wash, 15 lks. wide, 2 ft. deep, course W.; asc. 38 ft. over SW. slope.
53.40	Low spur, slopes W.; desc. 30 ft. along W. slope.
67.00	Dim road, bears E. and W.
68.20	Drain, 15 lks. wide, 3 ft. deep, course W.
81.19	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.
	T 12 N R 3 E S 8 + S 9 S 17 S 16 1934
	raise a mound
	of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling.
	Soil, adobe, 2nd rate; and rocky, 3rd rate.
	No timber; undergrowth, scrub oak, cats claw, cactus and quinine.
	From the cor. of secs. 9, 10, 15 and 16.
	N.89°25'W., on true line bet. secs. 9 and 16.
	Ascend 24 ft. over gentle SE. slope, through scattering undergrowth.
16.50	Flat topped ridge, bears N. and S.; desc. 80 ft. over SW. slope.
36.80	Drain, 20 lks. wide, 4 ft. deep, course SE.; asc. 18 ft. over E. slope.
37.50	Dim road, bears NW. and SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the

Chains.	ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S 9}{S 16}$ 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Ascend 158 ft. over E. slope.
51.80	Spur, slopes S.; desc. 248 ft. over broken NW. slope.
80.00	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling. Soil, adobe, 2nd rate; and rocky, 3rd rate. No timber; undergrowth, scrub oak, cats claw, cactus and quinine.

	N.0°58'E., on true line bet. secs. 8 and 9.
	Over gentle W. slope, through scattering undergrowth.
8.30	Wire fence, bears E. and W.
20.00	Slope changes; asc. 30 ft. over S. slope.
23.00	Low spur, slopes W.; over W. slope.
35.00	Slope changes; asc. 71 ft. over S. slope.
40.59	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 8 S 9 1934
	Ascend 40 ft. over S. slope.
43.10	Point of hill, slopes W.; desc. 103 ft. along rocky W. slope.
62.90	Wash, 50 lks. wide, course SW.; asc. 42 ft.
67.30	Small knoll, bears 2 chs. W.; enter scattering scrub cedars; Over flat.
71.00	Slope changes; asc. 76 ft. over SW. slope.
81.19	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.
	T 12 N R 3 E S 5 S 4 S 8 S 9 1934

Dependent Resurvey of the Subdivisions of T.12 N., R. 3 E.

Chains.	<p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, adobe and rocky; 3rd rate. Timber, scrub cedar; undergrowth, scrub oak, cats claw, cactus and quinine.</p> <hr/> <p>From the cor. of secs. 3,4,9 and 10. N.89°07'W., on true line bet. secs. 4 and 9. Ascend 36 ft. over gradual E. slope, through scattering undergrowth.</p> <p>13.00 Top of rise, bears NW. and SE.; desc. 142 ft. over W. slope.</p> <p>33.00 Wash, 30 lks. wide, course SW.; asc. 30 ft. over SE. slope.</p> <p>39.90 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone, 4x4x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ <u>S 4</u> S 9 1934</p> <p>Ascend 90 ft. over SE. slope.</p> <p>53.00 Spur, slopes SW.; desc. 67 ft. over N. slope.</p> <p>63.50 Head of ravine, course SW.; asc. 46 ft. over SE. slope.</p> <p>74.50 Spur, slopes SW.; desc. 65 ft. over W. slope.</p> <p>79.80 The cor. of secs. 4,5,8 and 9.</p> <p>Land, rolling. Soil, adobe; 3rd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.</p> <hr/> <p>N.5°28'E., on true line bet. secs. 4 and 5. Descend 83 ft. over NW. slope, through scattering under- growth.</p> <p>12.30 Wash, 30 lks. wide, 6 ft. deep, course W.; asc. 200 ft. over S. slope.</p> <p>18.40 Top of malpais cliff, 25 ft. high, faces S.; over top of small mesa.</p> <p>29.00 Rim of mesa, bears NE. and SW.; desc. 115 ft. over NW. slope.</p> <p>36.00 Short ravine, course SW.; asc. 120 ft. over SW. slope.</p> <p>40.78 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone, 7 ft. base to top, for $\frac{1}{2}$ sec. cor., with brass cap mkd.</p>
---------	--

Chains.

 $\frac{1}{4}$

S 5 | S 4

1934

Ascend 65 ft. over SW. slope.

46.30 West edge of small malpais mesa; desc. 170 ft. over NW. slope.

76.40 Drain, 20 lks. wide, 5 ft. deep, course W.

81.56 Intersect the closing cor. of secs. 4 and 5, hereinbefore described.

Land, rolling and mountainous.

Soil, adobe and rocky; 3rd rate.

Timber, scrub cedar; undergrowth, scrub oak, cats claw, cactus and quinine.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.

N.0°57'E., on true line bet. secs. 31 and 32.

Ascend 40 ft. over SW. slope, through scattering undergrowth, along wire fence, irregularly on line.

8.00 Slope changes; desc. 108 ft. over rolling NW. slope.

30.60 Drain, 15 lks. wide, course NW.; over bottom land.

37.00 Ash Creek, 20 lks. wide, 2 ins. deep, course W.; asc. 40 ft.

41.59 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$

S 31 | S 32

1934

Corner stands 8 lks. E. of N. and S. wire fence.

Ascend 80 ft. over SE. slope.

67.50 Wire fence, bears E. and $1\frac{1}{2}$ chs. W.

78.00 Slope changes; desc. 10 ft. along E. slope.

83.19 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T 12 N R 3 E

S 30 | S 29

S 31 | S 32

1934

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, adobe and rocky; 3rd rate.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

Chains.	Timber, ash in creek bottom; undergrowth, oak brush, cats claw, cactus and quinine.

	From the cor. of secs. 28, 29, 32 and 33.
	N.88°00'W., on true line bet. secs. 29 and 32.
	Descend 50 ft. over rolling N. slope, through scattering undergrowth.
41.45	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 29</u> S 32 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Descend gently.
52.00	Wash, 20 lks. wide, 3 ft. deep, course SW.; asc. slightly.
63.20	Spur, slopes S.; desc. 78 ft. over NW. slope.
64.10	Fence, bears N. and S.
71.90	Left bank of Ash Creek, bears N. and S., 10 ft. high.
75.00	Creek, 10 lks. wide, course SE.
75.50	Right bank of same, 5 ft. high, bears N. and S.; asc. 130 ft.
	Land, rolling. Soil, adobe; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	From the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.
	S.88°25'E., on true line bet. secs. 30 and 31.
	Descend 46 ft. over gradual E. slope, through scattering undergrowth.
31.50	Wash, 10 lks. wide, course SE.
33.50	Shallow wash, 60 lks. wide, course SE.; asc. 23 ft. over gentle W. slope.
39.88	Proportional distance,
	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 30</u> S 31 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Ascend 50 ft. over gentle W. slope.

Chains 65.00	Over flat, drains S.
81.32	The cor. of secs. 29, 30, 31 and 32. Land, gently rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	N.1°01'W., on true line bet. secs. 29 and 30. Over E. slope, through scattering undergrowth.
20.00	Flat spur, slopes E.; desc. 98 ft. over NE. slope.
41.59	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S } 30 \text{ S } 29 \\ 1934 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Taylor's house, bears S.73°E.; barn, bears S.78°E. Descend 13 ft. over N. slope.
49.30	Swale, drains E.; asc. 20 ft. over gentle E. slope.
73.00	Change to NE. slope; desc. 22 ft.
77.00	Drain, 5 lks. wide, course E.; asc. 22 ft. over SE. slope.
83.19	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd. $\begin{array}{c} \text{T } 12 \text{ N } \text{R } 3 \text{ E} \\ \text{S } 19 \text{ S } 20 \\ \text{S } 30 \text{ + S } 29 \\ 1934 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Chimney of Taylor's house, bears S.24°E.; barn, bears S.26 $\frac{1}{2}$ °E. Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	From the cor. of secs. 20, 21, 28 and 29. N.86°23'W., on true line bet. secs. 20 and 29. Descend 62 ft. over gentle W. slope, through scattering undergrowth.
12.00	Telephone line, bears N.70°W. and S.70°E.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

51

Chains.	
18.30	Wash, 10 lks. wide, course S.; over flat.
27.00	Road, bears NW. to Mayer, and SE. to Sycamore.
38.00	Low spur, slopes N.; desc. 6 ft. over W. slope.
40.08	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 20</u> S 29 1934
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
	Descend 25 ft. over gradual W. slope.
63.30	Road, bears S. to Taylor's, and connects N.
68.70	Enter Ash Creek wash, seep of water, course S.
71.50	Leave same; asc. 35 ft. over SE. slope.
80.16	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling. Soil, adobe and rocky; 2nd rate. No timber; undergrowth, cats claw, oak brush, cactus and quinine.

	From the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	S. 89° 56' E., on true line bet. secs. 19 and 30.
	Descend 25 ft. over gentle E. slope, through scattering undergrowth.
14.00	Change to SW. slope; asc. 30 ft.
32.00	Change to SE. slope; desc. 30 ft.
38.50	Record distance,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 19</u> S 30 1934
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
41.00	Change to SW. slope; asc. 40 ft.
48.50	Spur, slopes SW.; desc. 96 ft. over general E. slope.
65.50	Unused road, bears SW. and NE.
78.50	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling. Soil, adobe and rocky; 3 rd rate. No timber; undergrowth, cats claw, oak brush, quinine and cactus.

Chains.	N.0°54'E., on true line bet. secs. 19 and 20. Over flat, through scattering undergrowth.
3.00	Unused road, bears NE. and SW.
15.00	Change to N. slope; desc. 25 ft.
20.00	Over bottom land, bears E. and W.; drains E.; through dense mesquite.
21.30	Telephone line, parallels power line.
23.70	Power line, bears N.70 $\frac{1}{4}$ °W. and S.70 $\frac{1}{4}$ °E.; steel tower No. 225 of same, on line.
31.00	Leave bottom land and mesquite thicket, bears E. and W.; asc. 27 ft. over S. slope.
38.30	Road, bears W. to Mayer, and E. to Sycamore.
39.00	Road, bears NW. to Cherry and Camp Verde, and SE. to Sycamore.
39.50	Low spur, slopes E.; desc. 5 ft.
41.59	Set an iron post, 3 ft. long, 1 in. diam., 29 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 19 S 20 1934
	raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
	Over gentle NE. slope.
43.50	Sheet iron shed, bears 4 chs. E.
45.00	Side road, bears NE.
47.70	Wire fence, bears E. and W.
60.00	Road, bears S.15°W. to Sycamore, and N.15°E. to Cherry; asc. 10 ft. over SE. slope.
64.00	Low short spur, slopes E.; desc. 10 ft. over NE. slope.
67.00	Road, bears NW. to Cherry, and SE. to Sycamore.
70.00	Shallow wash, 30 lks. wide, course SE.; over bottom land.
76.00	End of spur from NW.
83.19	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.
	T 12 N R 3 E S 18 S 17 S 19 S 20 1934
	raise a mound of stone, 3 ft. base, 2 ft. high; W. of cor.
	Land, rolling. Soil, adobe and gravel; 2nd rate.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

Chains.	No timber; undergrowth, mesquite, cats claw, cactus, arrow-weed and oak brush.

	From the cor. of secs. 16,17,20 and 21.
	N.85°03'W., on true line bet. secs. 17 and 20.
	Descend 24 ft. over gradual NW. slope, through scattering undergrowth.
5.20	Drain, 20 lks. wide, 3 ft. deep, course SW.
10.20	Drain, 10 lks. wide, 4 ft. deep, course NW.; asc. 24 ft. along N. slope.
20.00	Change to NW. slope; desc. 70 ft.
35.00	Wash, 20 lks. wide, course S.65°W.; over gentle S. slope.
40.15	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, supported in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 17</u> S 20 1934
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
58.00	Left bank of Ash Creek, 8 ft. high, bears N. and S.
59.00	Dry creek bed of same, 1 ch. wide, course S.; over bottom land, through dense undergrowth.
63.40	Fence, bears N. and S.
70.20	Irrigation ditch, 4 lks. wide, course S.
70.80	Fence, bears N. and S.; enter scattering undergrowth; asc. 18 ft. over E. slope.
72.80	Short spur, slopes S.25°E.; desc. 16 ft. over SW. slope.
77.00	Over bottom land, bears NW. and SE.
80.30	The cor. of secs. 17,18,19 and 20.
	Land, rolling and bottom. Soil, adobe and gravel; 3rd rate. No timber; undergrowth, mesquite, arrow-weed, cats claw, buck thorn, oak brush, quinine and cactus.

	From the cor. of secs. 13,18,19 and 24, on the W. bdy. of the Tp.
	N.88°18'E., on true line bet. secs. 18 and 19.
	Descend 60 ft. over gentle NE. slope, through scattering undergrowth.
15.00	Over flat, drains NE.
38.42	Record distance in departure,
	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to bedrock, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains.	$\frac{1}{4}$ <u>S 18</u> S 19 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
43.00	Leave flat, bears NW. and SE.; desc. 50 ft. over NE. slope.
63.00	Wash, 30 lks. wide, course SE.; over S. slope.
68.00	Road, bears NW. to Cherry, and SE. to Sycamore.
71.00	Spur, slopes SE.; desc. 20 ft. over NE. slope.
77.00	Over N. edge of bottom land, bears E. and S.
78.44	The cor. of secs. 17, 18, 19 and 20. Land, rolling and flat. Soil, adobe and gravel; 2nd rate. No timber; undergrowth, oak brush, cats claw, mesquite and cactus.

	N.2°10'E., on true line bet. secs. 17 and 18. Ascend 34 ft. over SW. slope.
5.30	Spur, slopes SE.; desc. 25 ft. over N. slope.
10.00	Foot of slope; over bottom land, through dense undergrowth.
29.00	Leave bottom land and dense undergrowth; asc. 74 ft. over S. slope.
34.70	Short spur, slopes SE.; desc. 28 ft.
38.90	Short ravine, course SE.; asc. 42 ft. over S. slope.
41.62	The $\frac{1}{4}$ sec. cor., a decayed stake, 2 ins. square by 18 ins. long, in a mound of stone. This does not agree with description in the official record, but is undoubtedly the corner of the original survey. At point for cor., with original stake alongside, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 18 S 17 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Corner stands on top of sharp volcanic hill, bears E. and W.
	Thence
	N.0°11'W., on true line bet. secs. 17 and 18.
.70	Enter dense undergrowth, bears E. and W.; desc. 73 ft. over N. slope.
4.40	Wash, 60 lks. wide, 1 ft. deep, course SE.; over bottom land.

Dependent Resurvey of the Subdivisions of T.12 N., R. 3 E.

Doc. 402

Chains.	
21.90	Leave bottom land; enter scattering undergrowth; asc. 37 ft. over S. slope.
25.40	Spur, slopes E.; desc. 35 ft. over gradual NE. slope.
39.32	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.
	<p>T 12 N R 3 E S 7 S 8 S 18 S 17 1934</p>
	raise a mound
	of stone, 4 ft. base, 2 ft. high, W. of cor.
	C.H.Orme's house, $\frac{1}{4}$ circle V Bar Dude Ranch, bears N. $60\frac{1}{2}^{\circ}$ E.; large barn, bears N. 72° E.; two story tenant house, bears N. 76° E.
	Land, flat and rolling. Soil, adobe, silt and gravel; 2nd rate. No timber; undergrowth, mesquite, buck thorn, cats claw, oak brush, cactus and arrow weed.

	From the cor. of secs. 8, 9, 16 and 17.
	N. $85^{\circ} 11'$ W., on true line bet. secs. 8 and 17.
	Descend 6 ft. over gentle W. slope, through scattering undergrowth.
8.00	Wash, 30 lks. wide, course S.; asc. 31 ft. over E. slope.
8.60	Wire fence, bears N. and S.
20.00	Flat top of spur, slopes S.
20.50	Road, bears NW. and SE.
26.50	Leave top of spur; desc. 50 ft. over SW. slope.
36.34	Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<p>WC $\frac{1}{4}$ S 8 S 17 1934</p>
	from which
	A cottonwood, 15 ins. diam., bears S. 86° E., 9 lks. dist., mkd. $\frac{1}{4}$ S 8 W C B T.
	A cottonwood, 15 ins. diam., bears S. $12\frac{1}{2}^{\circ}$ W., 87 lks. dist., mkd. $\frac{1}{4}$ S 17 W C B T.
36.40	East edge of reservoir, bears N. and S.
40.14	True point for $\frac{1}{4}$ sec. cor., falls in reservoir.
44.00	West edge of reservoir dyke, 15 ft. high, bears NE. and SW.; desc. 25 ft.
50.00	Fence, bears N. and S.; over cultivated field.

Chains.	
63.10	Ditch, water, 3 ft. wide, course S.; leave field.
67.30	Enter Ash Creek wash, dry, course S.
69.30	Leave same; over flat slopes E.
80.28	The cor. of secs. 7, 8, 17 and 18.
	Land, rolling. Soil, adobe and gravel; 2nd rate. Timber, cottonwood and ash; along creek and reservoir; undergrowth, mesquite, arrow weed, cats claw, cactus and oak brush.

	From the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	N. 88° 05' E., on true line bet. secs. 7 and 18.
	Over rolling land, through scattering undergrowth.
	Descend. 21 ft. over NE. slope.
3.20	Wash, 10 lks. wide, course S. 20° E.; asc. 34 ft. over SW. slope.
10.50	Spur, slopes S.; desc. 92 ft. over NE. slope.
26.50	Wash, 10 lks. wide, from SW., course SE.; asc. 34 ft. over SW. slope.
33.00	Spur, slopes SE.; desc. 45 ft. over E. slope.
38.44	Record distance in departure.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 7 \\ S 18 \\ 1934 \end{array}$
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
39.00	Drain, 15 lks. wide, 2 ft. deep, course SE.; asc. 33 ft. over W. slope.
45.10	Spur, slopes S.; desc. 72 ft. over SE. slope.
53.50	Wash, 20 lks. wide, course S.
55.30	Another channel of same, 20 lks. wide.
56.30	Another channel of same, 15 lks. wide; asc. 31 ft. over W. slope.
61.00	Spur, slopes S.; road, bears N. to Cherry, and S. to Sycamore; desc. 58 ft. over NE. slope.
73.00	Road, bears NE. to Orme's ranch, and SW. to Mayer.
78.46	The cor. of secs. 7, 8, 17 and 18.
	Land, rolling. Soil, adobe and gravel; 2nd rate. No timber; undergrowth, oak brush, cactus, cats claw and quinine.

Dependent Resurvey of the Subdivisions of T. 12 N., R. 3 E.

57

BOOK 4028

Chains. N.0°58'E., on true line bet. secs. 7 and 8.
 Over gently rolling land, through scattering undergrowth.
 5.50 Road, bears NE. to Orme's, and SW. to Mayer.
 8.30 Corral, bears 2 chs. E.; asc. 33 ft. over SW. slope.
 19.99 U.S.G.S. bench mark, elevation 3849, bears S.70°45'E.,
 24.57 chs. dist.
 20.00 Spur, slopes SE.; desc. 20 ft. over NE. slope.
 36.10 Drain, 20 lks. wide, 8 ft. deep, course E.
 39.32 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 7 | S 8
 1934

of stone, 3 ft. base, 2 ft. high, W. of cor. raise a mound

Ascend 65 ft. over gradual S. slope.

77.70 Old road, bears NW. and SE.; low spur, slopes SE.

78.65 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
 the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap
 mkd.

T 12 N R 3 E
 S 6 + S 5
 S 7 + S 8
 1934

of stone, 3 ft. base, 2 ft. high, W. of cor. raise a mound

Land, rolling.

Soil, gravel and adobe; 2nd rate.

No timber; undergrowth, oak brush, mesquite, cats claw
 and cactus.

From the cor. of secs. 4, 5, 8 and 9.

N.87°02'W., on true line bet. secs. 5 and 8.

Over rolling land, through scattering scrub cedar and
 scattering undergrowth.

Descend 130 ft. over W. slope.

3.00 Wire fence, bears N. and S.

12.00 Over bottom land, bears E. and W.

14.30 Ditch, water, 4 lks. wide, 1 ft. deep, course S.

15.20 A secondary road, bears N. and S.

17.00 Dry creek bed of Ash Creek, 1 ch. wide, course S.; asc.
 36 ft.

22.30 Spur, slopes S.; hill, bears 2 chs. S.; desc. 12 ft. over
 NW. slope.

Chains.	
38.50	Change to sharper W. slope; desc. 30 ft.
40.05	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 5 \\ S 8 \\ 1934 \end{array}$
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
	Descend 15 ft. over W. slope.
41.80	Wash, 100 lks. wide, course S.
45.20	Wire fence, bears N. and S.
47.40	Same wash, course N. 60° E.
52.00	Same wash, course S.
54.50	Drain, 50 lks. wide, 6 ft. deep, course SE.
56.60	Drain, 25 lks. wide, 6 ft. deep, course S.; asc. 37 ft. over NE. slope.
64.30	Spur, slopes SE.; desc. 15 ft.
68.00	Drain, 10 lks. wide, 4 ft. deep, course SE.; asc. 37 ft. over gradual E. slope.
80.10	The cor. of secs. 5, 6, 7 and 8.
	Land, bottom and rolling. Soil, loam gravel and adobe; 2nd rate. Timber, ash, cottonwood and willow in bottom; undergrowth oak brush, mesquite, cats claw and cactus.

	From the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	N. 89° 38' E., on true line bet. secs. 6 and 7.
	Over rolling land, through scattering undergrowth.
	Descend 90 ft. over NE. slope.
9.30	Wash, 50 lks. wide, 1 ft. deep, course SE.; asc. 62 ft. over SW. slope.
17.10	Short spur, slopes S.; desc. 26 ft. over SE. slope.
19.90	Short ravine, course S.; desc. 58 ft. over NW. slope.
25.90	Spur, slopes S.; desc. 120 ft. over E. slope.
36.10	Wash, 20 lks. wide, 1 ft. deep, course S.; asc. 94 ft. over W. slope.
38.38	Record distance,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 6 \\ S 7 \\ 1934 \end{array}$

Dependent Resurvey of the Subdivision of T.12 N., R. 3 E.

BOOK 4028

Chains.	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Ascend 50 ft. over W. slope.
43.30	Spur, slopes S.; desc. 41 ft. over E. slope.
47.00	Ravine near head, course S.; asc. 11 ft. over W. slope.
54.10	Road, bears N. to Cherry, and S. to Sycamore; spur slopes S.; desc. 90 ft. over E. slope.
78.38	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, gravel; 2nd rate. No timber; undergrowth, oak brush, cats claw, cactus and quinine.

	N.4°03'E., on true line bet. secs. 5 and 6. Over rolling E. slope, through scattering undergrowth.
8.60	Drain, course SE.
21.40	Dim road, bears NE. and SW.
39.42	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 6 S 5 1934
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
45.40	Drain, 5 lks. wide, course E.
45.70	Drain, 5 lks. wide, course E.
62.10	Dim road, bears SE. and N.15°W.; asc. 33 ft. over SW. slope.
78.00	Volcanic ledge, bears E. and W.
78.84	The closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, loam, gravel and adobe; 2nd rate. No timber; undergrowth, mesquite, cats claw, oak brush and cactus.

FINAL TEST OF SOLAR ATTACHMENTS

May 12, 1934, on the meridian previously established, at 7h 30m a.m., app.t., set off 34°23'N., on the lat. arcs; and 18°05'N., of the the decl. arcs; and orient the instruments with the solar attachments; the resulting line agrees within 1' with the meridian established by Polaris observation.

At 4h 30m., ^{P.M.} app.t., with the same lat. setting, set off 18°10 $\frac{1}{2}$ 'N., on the decl. arcs; and orient the instruments with the solar attachments; the resulting line agrees

within 1' with the meridian established by Polaris observation.

GENERAL DESCRIPTION.

The township lies about 10 miles NE. of the town of Mayer, Arizona, from which it is reached by a moderately good road, from which other roads reach all except the NE. cor. of the Tp.

Land is rolling plains of volcanic formation, characterized by flat valleys among flat hills. The township lies on the W. edge of this formation and part of the W. range of sections is alluvial soil of other origin.

The township drains south-westerly into the Agua Fria River. Ash Creek, which runs southerly through the W. part of the township, drains a considerable area above the township and has a stream on the surface of its rather wide wash on most of its course. The stream in the SE. cor. known as Spring Creek, has a smaller channel and a surface stream on all of its course within the township. A third water channel, between the two, has little water.

The township is in a Forest Reserve and is used for stock raising. There is no mineral.

There are residents, each with a good set of buildings in secs. 32 and 8, the latter being stock ranch, farm and "dude ranch", with a school in connection and an average population of about 20.

A steel tower power line, and telephone line across the S. end of the Tp., connect Child's power house on the Verde River with Prescott, Arizona.

4-680
(August, 1926)

BOOK 4028

FIELD ASSISTANTS.
to

Theodore Vander Meer, U.S. Transitman

NAMES.	CAPACITY.
Raymond S. Davis	1st Chairman
Claude A. Mulkey	2nd Chairman
Walter Harbold	Flagman
David C. Bryant	Axman
Gilden Redewill	Axman
Robert R. Riesgo	Moundsman

Field Assistants to

Benjamin J. Mollette, U. S. Transitman.

Stanley S. Palmer	1st Chairman
Clifton A. Lewis	2nd Chairman
Claude Burk	Flagman
Glen Greenaw	Axeman
Thomas O'Brein	Axeman
Orland Parks	Moundsman

CERTIFICATE OF UNITED STATES SURVEYOR

We Theodore Vander Meer and Benjamin J. Mollette

U. S. Transitmen, U. S. Surveyor, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 9th day of March, 1934, we have well, faithfully, and truly

our in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all these parts or portions of North along the N. bdy. of T. 12 N., through part of Ranges 2 and 3 east; and dependently resurveyed the W. bdy. part of the S. bdy. and a portion of the subdivisional lines; and surveyed the east boundary and a portion of the subdivisional lines completing the subdivision of Township 12 North Range 3 East.

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us and under our direction; and that all the corners of said survey and resurvey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey and resurvey.

Benjamin J. Mollette
U. S. Transitman
Phoenix, Arizona.
March 14, 1935

Theodore Vander Meer
U.S. Transitman
Glendale, California
July 14, 1934

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colo., March 25, 1935

The foregoing field notes of the dependent resurvey of the 3rd Standard Parallel North along the north boundary of T. 12 N., through part of ranges 2 and 3 east, and the dependent resurvey of the west boundary, part of the south boundary, and a portion of the subdivisional lines; and survey of the east boundary and a portion of the subdivisional lines, completing the subdivision of Township 12 North Range 3 East.

executed by Benjamin J. Mollette and Theodore Vander Meer, U.S. Transitmen. under his special instructions dated March 9th, 1934, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys and resurveys they describe, are hereby approved.

Quentin Johnson
U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.