

Book "C"

4-879

BOOK 4052

FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION LINES of

Township 7 South, Range 5 West

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Robt. H. Williams

and Dexter S. King

Temporary Transistmen

In the capacity of U. S. Surveyors, under Special Instructions dated December 12, 1933, issued by the District Cadastral Engineer to govern surveys included in Group No. 199, Arizona, which were approved by the Commissioner of the General Land Office, February 17, 1934, and Assignment Instructions dated December 15, 1933.

Survey commenced January 20, 1934

Survey completed February 7, 1934

4052

4052

INDEX DIAGRAM.

Township , *Range*

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

• INDEX • DIAGRAM •

T.6S.-R.5W.

		32		33		34		35		36	
	6 34	5 23	4 17	3 11	2 7	1					
	33 34	33 24	23	16	11	6					
	7 32	8 22	9 15	10 10	11 6	12					
	32	31	22 21	15	10 5	5					
	18 31	17 21	16 14	15 10	14 5	13					
	30 30	29	T.7S. - R.5W.		14	4					
	19 29	20 20	21 14	22 9	23 4	24					
	28 28	27 19	19 13	13	8	3					
	30 27	29 18	28 13	27 8	26 3	25					
	25 26	25	18	12	8 7	2					
	21 24	22 17	23 12	24 7	25 2	26					


———— Accepted surveys.

———— Surveyed under Group No. 198.

~~———— Surveyed under Group No. 198.~~

———— Surveyed under this group. (Exterior Field Notes in Book "B")

----- Resurveyed under this group (Exterior Field Notes in Book "B")

 Areas surveyed as per accepted plats on file.

The survey of the subdivisional lines of T. 7 S., R. 5 W. was executed with Young and Sons transits Nos. 8493 and 8584. These instruments conform in every respect, to the specifications of General Land Office and were approved by the district cadastral engineer on December 15, 1933. Previous to the inception of the survey each instrument was placed in proper adjustment, such adjustment being maintained throughout the survey.

The lines to be established run over desert or rolling mountainous country, with sparse undergrowth and scattering timber. The courses of all lines were determined by deflection from meridians established by Polaris observation or direct observation of the sun. The deflection angles were checked by repetition of the angles. All lines were projected by the back and fore sight method. Offsets from the tangent to the parallel were made on the latitude lines.

Measurements were made with Lallie steel tapes, 5 chains in length, graduated every link for the first 100 links, the balance at intervals of ten links. The tapes were tested by comparison with a Lufkin Standard, and found to be correct. The measurements were made on the slope, the angles of which were read with clinometers in good adjustment. The horizontal equivalents appear in the field note record.

Subdivision of T. 7 S., R. 5 W.

chains

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., described in the field notes of the N. bdy. of T. 8 S., R. 5 W., surveyed under this group.

N.0°01'W., bet. secs. 35 and 36.

Over rolling land through scattering timber and dense undergrowth.

14.10 Wash, 10 lks. wide, course NW.

40.00 Set a malpais stone, 6x14x22 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

48.30 Wash, 3 lks. wide, course NW.

71.00 Wash, 30 lks. wide, course NW.

77.50 Wash, 6 lks. wide, course NW.

80.00 Set a malpais stone, 10x12x20 ins., 15 ins. in the ground for cor. of secs. 25, 26, 35 and 36, marked with 1 notch on the S. and 1 notch on the E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, cats claw and cacti.

N.89°54'E., on random line, bet. secs. 25 and 36.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.96 Intersect the E. bdy. of Tp. 5 lks. N. of the cor. of secs. 25, 30, 31 and 36; which is a malpais stone, 12x10x4 ins. above ground, firmly set, marked and witnessed as described in field notes of Tp. exterior of current Group, 198.

Thence,

S.89°56'W., on true line bet, secs. 25 and 36.

Over rolling land through scattering timber and dense undergrowth.

17.85 Wash, 50 lks. wide, course N.20°W.

39.98 Set a malpais stone, 6x9x22 ins., 16 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

49.90 Wash, 20 lks. wide, course N.50°W.

72.85 Wash, 10 lks. wide, course NW.

79.96 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde

Undergrowth, greasewood, cats claw and cacti.

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains	N.0°01'W., bet. secs. 25 and 26
	Over rolling land through scattering timber and thick undergrowth.
3.50	Wash, 20 lks. wide, course NE.
10.50	Wash, 20 lks. wide, course NW.
28.50	Wash, 20 lks. wide, course N.20°W.
34.20	Wash, 8 lks. wide, course W.
40.00	Set a malpais stone, 6x9x20 ins., 15 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
67.80	Wash, 40 lks. wide, course W.
75.00	Wash, 10 lks. wide, course NW.
80.00	Set a granite stone, 6x9x18 ins., 13 ins. in the ground for cor. of secs. 23, 24, 25 and 26, marked with 2 notches on S. and 1 notch on E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
	Land, rolling. Soil, sandy and gravelly loam; 1st and 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N.89°56'E., on a random line bet. secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect E. bdy. of Tp., 2 lks. N. of the cor. of secs. 19, 24, 25 and 30, which is a malpais stone 13x6x8 ins. above ground, firmly set, marked and witnessed as described in field notes of Tp. Exteriors of current group 198.
	Thence,
	S.89°57'W., on true line bet. secs. 24 and 25.
	Over rolling land through scattering timber and dense undergrowth.
2.80	Wash, 5 lks. wide, course N.30°W.
22.90	Wash, 15 lks. wide, course NW.
40.01	Set a malpais stone, 6x9x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
43.40	Wash, 20 lks. wide, course NW.
51.00	Wash, 4 lks. wide, course N.
55.40	Wash, 10 lks. wide, course N.
74.90	Wash, 20 lks. wide, course NW.
80.02	The cor. of secs. 23, 24, 25 and 26.

Subdivision of T. 7 S., R. 5 W.

chains	<p>Land, rolling. Soil, Sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.</p>
	<p>N.0°01' W., bet. secs. 23 and 24+</p> <p>Over rolling land through scattering timber and dense undergrowth.</p> <p>4.20 Wash, 20 lks. wide, course NW.</p> <p>8.70 Wash, 10 lks. wide, course W.</p> <p>40.00 Set a malpais stone, 6x9x20 ins., 15 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.</p> <p>63.70 Wash, 20 lks. wide, course NW.</p> <p>80.00 Set a granite stone 6x9x20 ins., 15 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked with 3 notches on S, and 1 notch on E. face; and raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy and gravelly loam; 1st and 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, cats claw and cacti</p>
	<p>N.89°57'E., on a random line, bet secs. 13 and 24.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.04 Intersect E. bdy. of Tp., at the cor. of secs. 13, 18, 19 and 24, which is a malpais stone 9x9x9 ins. above ground, firmly set, marked and witnessed as described in field notes of Tp. Exteriors of current group, 199.</p> <p>Thence,</p> <p>S.89°57'W., on true line bet. secs. 13 and 24.</p> <p>20.80 Wash, 20 lks. wide, course N.</p> <p>27.60 Wash, 80 lks. wide; course N:10°W.</p> <p>40.02 Set a malpais stone 7x8x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and dig pits, 18x18x12 ins., E. and W. of cor. 3 ft. dist.</p> <p>57.60 Wash; 15 lks. wide, course N:30°W.</p> <p>69.40 Wash, 10 lks. wide, course N:30°W:</p> <p>80.04 The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, sandy and gravelly loam; 1st and 2nd rate. Timber, scattering ironwood; mesquite and palo verdá. Undergrowth, greasewood, scattering cats claw and cacti.</p>

Subdivision of T. 7 S., R. 5 W.

BOOK 4082

chains

N.0°01'W., bet. secs. 13 and 14.

Over rolling land through scattering timber and dense undergrowth.

18.20 Wash, 4 lks. wide, course N.10°W.

30.00 Wash, 4 lks. wide, course NE.

40.00 Set a malpais stone 8x8x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

40.10 Wash, 8 lks. wide, course N.10°W.

67.30 Wash, 30 lks. wide, course N.10°W.

80.00 Set a granite stone, 8x10x24 ins., 18 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked with 4 notches on S. and 1 notch on E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.89°57'E., on a random line bet. secs. 12 and 13.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs. 7, 12, 13 and 24, which is a malpais stone 9x6x8 ins. above ground, firmly set, marked and witnessed as described in field notes of Tps. Exteriors of current Group, 198.

Thence,

S.89°55'W., on true line bet. secs. 12 and 13.

Over rolling land through scattering timber and dense undergrowth.

40.04 Set a malpais stone 6x9x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

45.00 Wash, 10 lks. wide, course N.10°W.

53.10 Wash, 35 lks. wide, course NW.

64.00 Wash, 5 lks. wide, course N.10°W.

80.08 The cor. of secs. 11, 12, 13 and 14.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.0°01'W., bet. secs. 11 and 12

Over rolling land, through scattering timber and dense undergrowth.

Subdivision of T. 7 S., R. 5 W.

chains	
37.00	Wash, 45 lks. wide, course N.20°W.
40.00	Set a malpais stone, 6x9x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high W. of cor.
67.80	Wash, 15 lks. wide, course N.10°W.
80.00	Set a malpais stone, 8x14x22 ins., 17 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, marked with 5 notches on S. and 1 notch on E. faces; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N.89°55'E., on a random line bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect E. bdy. of Tp., 12 lks. E. of cor. of secs. 1, 6, 7 and 12, which is a granite stone, 8x8x8 ins. above ground, firmly set, marked and witnessed as described in field notes of township exteriors of current group 198. Thence,
	S.89°50'W., on true line bet. secs. 1 and 12.
	Over rolling land through scattering timber and dense undergrowth.
21.80	Wash, 5 lks. wide, course N.10°W.
27.20	Wash, 5 lks. wide, course NW.
40.05	Set a malpais stone, 6x12x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
46.80	Wash, 8 lks. wide, course N.20°W.
62.90	Wash, 5 lks. wide, course N.20°W.
72.50	Wash, 10 lks. wide, course NW.
80.10	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	North, on a random line bet. secs. 1 and 2
40.00	Set temp. $\frac{1}{4}$ sec. cor.
76.82	Intersect N. bdy. of Tp., 2 lks. W. of the cor. of secs. 1 and 2, T. 7 S., R. 5 W., described in the field notes of the E. bdy. of T. 6 S., R. 5 W., resurveyed under this group.

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

Thence,

S.0°01'W., on true line bet. secs. 1 and 2.

Over rolling land through scattering timber and dense undergrowth.

23.40 Wash, 3 lks. wide, course N.20°W.

36.82 Set a malpais stone, 8x14x22 ins., 17 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

45.90 Wash, 40 lks. wide, course N.10°W.

76.82 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, cats claw and cacti.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., described in the field notes of the N. bdy. of T. 8 S., R. 5 W., surveyed under this group.

N.0°01'W., bet. secs. 34 and 35.

Over rolling land through scattering timber and dense undergrowth.

40.00 Set a malpais stone, 7x8x20 ins., 15 ins. in the ground, for cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

44.30 Wash, 4 lks. wide, course NW.

51.50 Wash, 10 lks. wide, course N.80°W.

80.00 Set a malpais stone, 7x8x22 ins., 16 ins. in the ground for cor. of secs. 26, 27, 34 and 35, marked with 1 notch on S. and 2 notches on the E. faces; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.89°54'E., on a random line bet. secs. 26 and 35.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect N. and S. line, at the cor. of secs. 25, 26, 35 and 36.

Thence;

S.89°54'W., on true line, bet. secs. 26 and 35.

Over rolling land through scattering timber and dense undergrowth.

1.00 Wash, 10 lks. wide, course N.

Subdivision of T. 7 S., R. 5 W.

chains	
40.01	Set a malpais stone, 6x9x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
80.02	The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N.0°01'W., bet. secs. 26 and 27. Over rolling land through scattering timber and dense undergrowth.
24.90	Wash, 3 lks. wide, course NW.
40.00	Set a malpais stone, 8x10x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
47.40	Wash, 5 lks. wide, course W.
80.00	Set a malpais stone, 8x8x20 ins., 15 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked with 2 notches on S. and 2 notches on E. faces; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde Undergrowth, greasewood, scattering cats claw and cacti.
	N.89°54'E., on a random line bet. secs. 23 and 26.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	Intersect N. and S. line, at the cor. of secs. 23, 24, 25 and 26. Thence, S.89°54'W., on true line bet. secs. 23 and 26. Over rolling land through scattering timber and dense undergrowth.
2.70	Wash, 15 lks. wide, course N.
14.00	Wash, 15 lks. wide, course N.10°W.
20.00	Wash, 3 lks. wide, course N.10°W.
38.10	Wash, 10 lks. wide, course N.10°W.
39.99	Set a malpais stone 7x8x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
79.98	The cor. of secs. 22, 23, 26 and 27.

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

Land, rolling.
Soil, sandy and gravelly loam; stony, 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.0°01'W., bet. secs. 22 and 23.

Over rolling land through scattering timber and dense undergrowth.

40.00 Set a malpais stone, 8x8x22 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

80.00 Set a malpais stone 7x10x22 ins., 17 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, marked with 3 notches on S. and 2 notches on E. faces; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly loam; 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.89°54'E., on a random line bet. secs. 14 and 23.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect the N. and S. line, at the cor. of secs. 13, 14, 23 and 24.

Thence,

S.89°54'W., on true line bet. secs. 14 and 23.

Over rolling land through scattering timber and dense undergrowth.

15.50 Wash, 10 lks. wide, course N.20°W.

30.20 Wash, 15 lks. wide, course N.20°W.

39.70 Wash, 15 lks. wide, course N.10°W.

39.95 Set a malpais stone, 6x9x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

41.80 Wash, 5 lks. wide, course N.10°W.

54.80 Wash, 30 lks. wide, course N.

61.10 Wash, 10 lks. wide, course N.

79.90 The cor. of secs. 14, 15, 22 and 23.

Land, rolling.
Soil, sandy and gravelly loam; 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

Subdivision of T. 7 S., R. 5 W.

chains	N. 0°01'W. bet. secs. 14 and 15. Over rolling land through scattering timber and dense undergrowth.
40.00	Set a malpais stone, 8x8x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00	Set a malpais stone, 10x10x20 ins., 15 ins. in the ground for cor. of secs. 10, 11, 14 and 15, marked with 4 notches on S. and 2 notches on E. faces; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, sandy and gravelly loam, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N. 89°54'E.; on a random line bet. secs. 11 and 14.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.88	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 11, 12, 13 and 14. Thence, S. 89°56'W., on true line bet. secs. 11 and 14. Over rolling land through scattering timber and dense undergrowth.
3.70	Wash, 20 lks. wide, course N. 10°W.
27.70	Wash, 10 lks. wide, course NW.
29.80	Wash, 4 lks. wide, course N.
39.94	Set a malpais stone, 10x12x20 ins., 15 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
66.70	Wash, 20 lks. wide, course N.
68.70	Wash, 10 lks. wide, course N.
79.88	The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, sandy and gravelly loam; 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N. 0°01'W., bet. secs. 10 and 11. Over rolling land through scattering timber and dense undergrowth.
40.00	Set a malpais stone, 8x9x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00	Set a malpais stone, 8x10x22 ins., 15 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, marked with 5 notches on S. and 2 notches on E. faces; and raise a

Subdivision of T 7 S., R. 5 W.

BOOK 4062

chains

mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N. $89^{\circ}56'E.$, on a random line bet. secs. 2 and 11.40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.88 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 1, 2, 11 and 12.

Thence,

S. $89^{\circ}57'W.$, on true line bet. secs. 2 and 11.

Over rolling land through scattering timber and dense undergrowth.

19.60 Wash, 27 lks. wide, course NW.

22.20 Wash, 80 lks. wide, course N.

35.65 Wash, 15 lks. wide, course N.

39.94 Set a malpais stone, 6x9x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

50.90 Wash, 30 lks. wide, course N.

76.30 Wash, 50 lks. wide, course N. $10^{\circ}W.$

79.188 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N. $0^{\circ}01'E.$, on a random line bet. secs. 2 and 3.40.00 Set temp. $\frac{1}{4}$ sec. cor.

76.36 Intersect N. bdy. of Tp., 20 lks. E. of the cor. of secs. 2 and 3, T. 7 S., R. 5 W., described in the field notes of the S. bdy. of T. 6 S., R. 5 W., resurveyed under this group.

Thence,

S. $0^{\circ}08'E.$, on true line bet. secs. 2 and 3.

Over rolling land through scattering timber and dense undergrowth.

36.36 Set a malpais stone, 8x8x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.60.50 Wash, 50 lks. wide, course N. $20^{\circ}W.$

Subdivision of T. 7 S., R. 5 W.

chains	
76.36	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., described in the field notes of the N. bdy. of T. 8 S., R. 5 W., surveyed under this group.</p> <p>N.0°02'W., bet. secs. 33 and 34.</p> <p>Over rolling land through scattering timber and dense undergrowth.</p>
3.60	Wash, 30 lks. wide, course HW.
6.60	Wash, 40 lks. wide, course W.
40.00	Set a malpais stone, 7x8x20 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
79.75	Wash, 50 lks. wide, course NW.
80.00	<p>True point for cor. of secs. 27, 28, 33 and 34, falls in wash, 50 lks. wide, course NW.</p> <p>Land, rolling. Soil, sandy and gravelly loam; 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.</p>
40.00	N.89°54'E., on a random line bet. secs. 27 and 34. Set temp. $\frac{1}{4}$ sec. cor.
79.96	<p>Intersect N. and S. line, 2 lks. N. of the cor. of secs. 26, 27, 34 and 35.</p> <p>Thence S.89°55'W., on true line bet. secs. 27 and 34.</p> <p>Over rolling land through scattering timber and dense undergrowth.</p>
25.00	Wash, 30 lks. wide, course N.
39.98	Set a malpais stone, 7x8x24 ins., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
77.00	Wash, 40 lks. wide, course NW.
79.96	<p>True point for cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling. Soil, sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Under growth, greasewood, scattering cats claw and cacti.</p>

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

N.0°02'W., bet. secs. 27 and 28.

Over rolling land through scattering timber and dense undergrowth.

0.60 Set a malpais stone, 6x8x28 ins., 21 ins. in the ground, for witness to cor. of secs. 27, 28, 33 and 34, marked with 1 notch and WC on S., and 3 notches on E. faces; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

5.00 Wash, 30 lks. wide, course NW.

40.00 Set a malpais stone, 6x8x20 ins., 15 ins. in the ground, for ¼ sec. cor., marked with ¼ on W. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

80.00 Set a malpais stone, 6x10x24 ins., 15 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked with 2 notches on S., and 3 notches on E. faces; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.89°55'E., on a random line bet. secs. 22 and 27.

40.00 Set temp. ¼ sec. cor.

80.00 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 22, 23, 26 and 27.

Thence

S.89°57'W., on true line bet. secs. 22 and 27

Over rolling land through scattering timber and dense undergrowth.

28.30 Wash, 20 lks. wide, course N.

40.00 Set a malpais stone, 8x8x24 ins., 18 ins. in the ground, for ¼ sec. cor., marked ¼ on N. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

51.20 Wash, 20 lks. wide, course N.

80.00 The cor. of secs. 21, 22, 27 and 28.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.0°02'W., bet. secs. 21 and 22.

Over rolling land through scattering timber and dense undergrowth.

40.00 Set a malpais stone, 8x8x20 ins., 15 ins. in the ground, for ¼ sec. cor., marked ¼ on W. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Subdivision of T. 7 S., R. 5 W.

chains

66.10 Wash, 30 lks. wide, course NW.

80.00 Set a malpais stone, 8x8x24 ins., 18 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked with 3 notches on S. and 3 notches on E. faces; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde,

Undergrowth, greasewood, scattering cats claw and cacti.

N.89°57'E., on a random line bet. secs. 15 and 22.

40.00 Set temp. ¼ sec. cor.

80.00 Intersect N. and S. line, at the cor. of secs. 14, 15, 22 and 23.

Thence,

S.89°57'W., on true line bet. secs. 15 and 22.

Over rolling land through scattering timber and dense undergrowth.

40.00 Set a malpais stone, 6x12x20 ins., 15 ins. in the ground, for ¼ sec. cor., marked ¼ on N. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

80.00 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.0°02'W., bet. secs. 15 and 16.

Over rolling land, through scattering timber and dense undergrowth.

40.00 Set a malpais stone, 7x8x20 ins., 15 ins. in the ground, for ¼ sec. cor., marked ¼ on W. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

77.80 Wash, 20 lks. wide, course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for the cor. of secs. 9, 10, 15 and 16, with brass cap marked

T7S R5W

S9 | S10

S16 | S15

1934

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

Land, rolling.
Soil, sandy and gravelly loam; stony, 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.89°57'E., on a random line bet. secs. 10 and 15.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.96 Intersect N. and S. line, at the cor. of secs. 10, 11, 14 and 15.

Thence,

S.89°57'W., on true line bet. secs. 10 and 15.

Over rolling land through scattering timber and dense undergrowth.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{r} S 10 \\ \frac{1}{4} \text{---} \\ S 15 \end{array}$$

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

68.50 Wash, 10 lks. wide, course N.

79.96 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.
Soil, sandy and gravelly loam; stony, 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.0°02'W., bet. secs. 9 and 10.

Over rolling land through scattering timber and dense Undergrowth

37.80 Wash, 10 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ | \\ S9 \quad | \quad S10 \end{array}$$

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 3, 4, 9 and 10, with brass cap marked

Subdivision of T. 7 S., R. 5 W.

chains

T7S	R5W
S4	S3
S9	S10

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N. $89^{\circ}57'E.$, on a random line bet. secs. 3 and 10.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.92 Intersect N. and S. line, at the cor. of secs. 2, 3, 10 and 11.

Thence,

S. $89^{\circ}57'W.$, on true line bet. secs. 3 and 10.

Over rolling land through scattering timber and dense undergrowth.

16.00 Wash, 20 lks. wide, course N.

39.86 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap marked

WC $\frac{1}{4}$	S 3
	S10

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

39.96 True point for $\frac{1}{4}$ sec. cor. falls in edge of wash.

40.60 Center of wash, 50 lks. wide, course NW.

79.92 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N. $0^{\circ}08'W.$, on a random line bet. secs. 3 and 4.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

75.96 Intersect N. bdy. of Tp., 13 lks. E. of the cor. of secs. 3 and 4, T. 7 S., R. 5 W., described in the field notes of the S. bdy. of T. 6 S., R. 5 W., resurveyed under this group.

Thence,

Subdivision of T. 7 S., R. 5 W

BOOK 4052

chains

S.0°14'E., on true line bet. secs. 3 and 4.

Over rolling land through scattering timber and dense undergrowth.

- 7.15 Highway, bears NE. to Gila Bend, and SW. to Ajo.
- 11.90 Telegraph line, bears NE. and SW.
(Tucson, Cornelia & Gila Bend R.R.)
- 12.05 Railroad, bears NE. to Gila Bend and SW. to Ajo.
- 35.96 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4}$$

S4	S3
----	----

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 75.96 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., described in the field notes of the N bdy. of T. 8 S., R. 5 W. surveyed under this group.

N.0°02'W., bet. secs. 32 and 33.

Over rolling land through scattering timber and dense undergrowth.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4}$$

S32	S33
-----	-----

1934

Dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

- 65.20 Wash, 50 lks. wide, course N.80°W.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs, 28, 29, 32 and 33, with brass cap marked

T7S	R5W
S29	S28
S32	S33

1934

Dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

chains	<p>Land, rolling. Soil, sandy and gravelly loam; 1st and 2nd rate. Timber, scattering ironwood, mesquite and palo verde Undergrowth, greasewood, scattering cats claw and cacti.</p>
	<p>N. 89° 54' E., on a random line bet. secs. 28 and 33.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect N. and S. line, 5 lks. S. of the true point for cor. of secs. 27, 28, 33 and 34.
	Thence,
	S. 89° 52' W., on true line bet. secs. 28 and 33.
	Over rolling land through scattering timber and dense undergrowth, across wash.
0.20	Leave wash, course N. 20° W.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S28 \\ \frac{1}{4} \\ \hline S33 \\ 1934 \end{array}$
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft high, W. of cor.
80.04	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling. Soil, sandy and gravelly loam; stony, 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N. 0° 02' W., bet. secs. 28 and 29.
	Over rolling land through scattering timber and dense undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ S29 \quad \quad S28 \\ 1934 \end{array}$
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
75.00	Wash, 100 lks. wide, course NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass cap marked

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

T7S	R5W
S20	S21
S29	S28

1934

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly loam; stony, 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.89°52'E., on a random line bet. secs. 21 and 28.

40.00 Set temp. ¼ sec. cor.

80.06 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 21, 22, 27 and 28.

Thence,

S.89°53'W., on true line bet. secs. 21 and 28.

Over rolling land through scattering timber and dense undergrowth.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap marked

¼	S21
	S28

1934.

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

55.90 Wash, 30 lks. wide, course NW.

66.90 Wash, 15 lks. wide, course N.80°W.

73.20 Wash, 35 lks. wide, course NW.

80.06 The cor. of secs. 20, 21, 28 and 29.

Land, rolling.
Soil, sandy and gravelly loam; stony, 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.0°02'W., bet. secs. 20 and 21.

Over rolling land through scattering timber and dense undergrowth.

9.10 Wash, 20 lks. wide, course NW.

17.00 Wash, 4 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the

Subdivision of T. 7 S., R. 5 W.

chains

ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\frac{1}{4}$$

S20	S21
-----	-----

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 2 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap marked.

T7S S17	R5W S16
S20	S21

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; 1st. rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N. $89^{\circ}53'E.$, on a random line bet. secs. 16 and 21.40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 15, 16, 21 and 22.

Thence,

S. $89^{\circ}49'W.$, on true line bet. secs. 16 and 21.

Over rolling land through scattering timber and dense undergrowth.

16.30 Wash, 25 lks. wide, course NW.

20.00 Wash, 4 lks. wide, course N.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\frac{1}{4}$$

S16
S21

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

80.02 The cor. of secs. 16, 17, 20 and 21.

Land, rolling.

Soil, sandy and gravelly loam; stony, 2nd rate.

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.0°02'W., bet. secs. 16 and 17.

Over rolling land through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$\frac{1}{4}$
S17 | S16

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

54.60 Tucson, Cornelia and Gila Bend Railroad, bears N.25 $\frac{1}{4}$ °E. to Gila Bend and S.25 $\frac{1}{4}$ °W., to Ajo.

57.85 Telegraph line, bears N.25 $\frac{1}{4}$ °E. and S. 25 $\frac{1}{4}$ °W.

59.85 Highway, bears N.25 $\frac{1}{4}$ °E. to Gila Bend and S.25 $\frac{1}{4}$ °W. to Ajo.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap marked

T7S | R5W
S8 | S9
S17 | S16

1934

Dig pits, 18x18x12 ins. in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy and gravelly loam; 1st rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.89°49'E., on a random line bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 9, 10, 15 and 16.

Thence,

S.89°48'W., on true line bet. secs. 9 and 16.

Over rolling land through scattering timber and dense undergrowth.

1.90 Wash, 4 lks. wide, course NW.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the

Subdivision of T. 7 S., R. 5 W.

chains

ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S 9

S16

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

50.00 Wash, 3 lks. wide, course N.

68.05 Tucson Cornelia and Gila Bend Railroad, bears N. $25\frac{1}{4}^{\circ}$ E., to Gila Bend, and S. $25\frac{1}{4}^{\circ}$ W. to Ajo.

69.65 Telegraph line, bears N. $25\frac{1}{4}^{\circ}$ E., and S. $25\frac{1}{4}^{\circ}$ W.

70.40 Highway, bears N. $25\frac{1}{4}^{\circ}$ E. to Gila Bend and S. $25\frac{1}{4}^{\circ}$ W. to Ajo.

80.04 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.

Soil, sandy and gravelly loam, stony, 2nd rate.

Timber, scattering ironwood, mesquite and cacti.

Undergrowth, greasewood, scattering cats claw and cacti.

N. $0^{\circ}02'$ W., bet. secs. 8 and 9.

Over rolling land through scattering timber and dense undergrowth.

22.00 Telephone line, bears N. 25° E. and S. 25° W.

31.60 Wash, 5 lks. wide, course N. 20° W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$

S8	S9
----	----

1934

Dig pits, 18x18x12 ins. N. and S. of cor., 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap marked

T7S	R5W
S5	S4
S8	S9

1934

Dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy and gravelly loam, 1st rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

Subdivision of T. 7 S., R. 5 W.

ECCO 4062

chains

N. $89^{\circ}48'E.$, on a random line bet. secs. 4 and 9.40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.06 Intersect N. and S. line, 12 lks. N. of the cor. of secs. 3, 4, 9 and 10.

Thence,

S. $89^{\circ}53'W.$, on true line bet. secs. 4 and 9.

Over rolling land through scattering timber and dense undergrowth.

30.15 Tucson, Cornelia and Gila Bend Railroad, bears N. $25\frac{1}{4}^{\circ}E.$ to Gila Bend and S. $25\frac{1}{4}^{\circ}W.$ to Ajo.32.30 Telegraph line, bears N. $25\frac{1}{4}^{\circ}E.$ and S. $25\frac{1}{4}^{\circ}W.$ 35.60 Highway, bears N. $25\frac{1}{4}^{\circ}E.$ to Gila Bend and S. $25\frac{1}{4}^{\circ}W.$ to Ajo.40.03 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S \ 4}{S \ 9}$$

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

43.00 Wash, 5 lks. wide, course N.

46.80 Wash, 3 lks. wide, course N. $10^{\circ}W.$

52.00 Wash, 2 lks. wide, course NE.

52.20 Telephone line, bears N. $25^{\circ}E.$ and S. $25^{\circ}W.$

80.06 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.

Soil, sandy and gravelly loam, 1st. rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N. $0^{\circ}14'W.$, on a random line bet. secs. 4 and 5.40.00 Set temp. $\frac{1}{4}$ sec. cor.

75.93 Intersect N. bdy. of Tp., 2 lks. W. of the cor. of secs. 4 and 5, T. 7 S., R. 5 W., described in the field notes of the S. bdy. of T. 6 S., R. 5 W., resurveyed under this group.

Thence,

S. $0^{\circ}13'E.$, on true line bet. secs. 4 and 5.

Over rolling land through scattering timber and dense undergrowth.

33.20 Wash, 10 lks. wide, course N. $80^{\circ}W.$

Subdivision of T. 7 S., R. 5 W.

chains

35.93 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S5 | S4
1934

Dig pits, 18x18x12 ins., N. and S. of cor. 3 ft. dist.

43.70 Wash, 4 lks. wide, course N.20°W.

75.93 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.

Soil, sandy and gravelly loam, 1st rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., described in the field notes of the N. bdy. of T. 8 S., R 5 W., surveyed under this group.

N.0°03'W., bet. secs. 31 and 32.

Over rolling land through scattering timber and dense undergrowth.

35.00 Wash, 10 lks. wide, course NW.

40.00 True point for $\frac{1}{4}$ sec. cor. falls in wash, 10 lks. wide, course NW.

40.50 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S31 | S32
WC
1934

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

42.60 Wash, 20 lks. wide, course NW.

78.20 Wash, 20 lks. wide, course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap marked

T7S R5W
S30 | S29
S31 | S32
1934

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly loam; 1st rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N. $89^{\circ}54'E.$, on a random line bet. secs. 29 and 32.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 28, 29, 32 and 33.

Thence,

West, on true line bet. secs. 29 and 32.

Over rolling land, through scattering timber and dense undergrowth.

23.00 Wash, 30 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

59.10 Wash, 30 lks. wide, course NW.

80.00 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.
Soil, sandy and gravelly loam, stony; 1st and 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

S. $89^{\circ}54'W.$, on a random line bet. secs. 30 and 31.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

78.69 Intersect W. bdy. of Tp., 12 lks. N. of cor. of secs. 25, 30, 31 and 36, described in the field notes of said Township boundary as surveyed under this Group.

Thence,

N. $89^{\circ}49'E.$, on true line bet. secs. 30 and 31.

Descend 34 ft. over SE. slope, through scattering undergrowth.

5.70 Small wash, course NE.; ascend 40 ft. over NW. slope.

Subdivision of T. 7 S., R. 5 W.

chains	
10.70	Point of spur, slopes NE.; desc. 40 ft. over NE. slope.
13.70	Foot of hill, bears NW. and S.; thence over rolling land, through scattering timber and dense undergrowth.
24.00	Wash, 20 lks. wide, course N.
38.69	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S\ 30 \\ \frac{1}{4} \\ \hline S\ 31 \end{array}$
	1934
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
39.00	Telephone line, bears N.25°E. and S. 25°W.
42.30	Wash, 20 lks. wide, course N.
54.70	Highway, bears N.25°E. to Gila Bend and S. 25°W. to Ajo.
56.00	Telegraph line, bears N.25 $\frac{1}{4}$ °E. and S.25 $\frac{1}{4}$ °W.
57.50	Tucson, Cornelia and Gila Bend Railroad, bears N.25 $\frac{1}{4}$ °E. to Gila Bend and S.25 $\frac{1}{4}$ °W. to Ajo.
76.60	Wash, 20 lks. wide, course NW.
78.69	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling. Soil, sandy and gravelly loam, stony; 1st and 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N.0°03'W., bet. secs. 29 and 30.
	Over rolling land, through scattering timber and dense undergrowth.
36.50	Wash, 30 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ S30 \quad \quad S29 \end{array}$
	1934
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
45.00	Tucson, Cornelia and Gila Bend Railroad, bears N.25 $\frac{1}{4}$ °E. to Gila Bend and S.25 $\frac{1}{4}$ °W. to Ajo.
46.50	Telegraph line, bears N.25 $\frac{1}{4}$ °E. and S.25 $\frac{1}{4}$ °W.

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

55.00 Highway, bears N.25°E. to Gila Bend and S.25°W. to Ajo.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap marked

T7S	R5W
S19	S20
S30	S29

1934

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam, stony; 1st and 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

East, on a random line bet. secs. 20 and 29.

40.00 Set temp. ¼ sec. cor.

79.98 Intersect N. and S. line, at the cor. of secs. 20, 21, 28 and 29.

Thence,

West, on true line bet. secs. 20 and 29.

Over rolling land, through scattering timber and dense undergrowth.

5.70 Wash, 10 lks. wide, course NW.

11.90 Wash, 20 lks. wide, course NW.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap marked

¼	S 20
	S 29

1934

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

63.50 Tucson, Cornelia and Gila Bend Railroad, bears N.25¼°E. to Gila Bend and S.25¼°W. to Ajo.

65.00 Telegraph line, bears N.25¼°E. and S.25¼°W.

66.50 Highway, bears N.25°E. to Gila Bend and S.25°W. to Ajo.

79.98 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, sandy and gravelly loam, stony; 1st and 2nd rate.

Subdivision of T. 7 S., R. 5 W.

chains

Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

S.89°49'W., on a random line bet. secs. 19 and 30.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

78.64 Intersect the W. bdy. of Tp., 9 lks. N. of the cor. of
secs. 19, 24, 25 and 30, described in the field notes
of said Township boundary, as surveyed under this group.

Thence,

N.89°45'E., on true line bet. secs. 19 and 30.

Over rolling land, through scattering timber and dense
undergrowth.

11.60 Wash, 10 lks. wide, course NE.

31.20 Wash, 50 lks. wide, course N.

38.64 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S 19}{S 30}$

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of
cor.

54.20 Wash, 30 lks. wide, course N.

75.65 Telephone line, bears N.25°E. and S.25°W.

78.64 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, sandy and gravelly loam, stony; 1st and 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

N.0°03'W., bet. secs. 19 and 20.

Over rolling land, through scattering timber and dense
undergrowth.

6.00 Telephone line, bears N.25°E. and S.25°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S19 | S20

1934


Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap marked



1934

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly loam, stony; 1st and 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

East, on a random line bet. secs. 17 and 20.

40.00 Set temp. 1/4 sec. cor.

79.98 Intersect N. and S. line, 12 lks. N. of the cor. of secs. 16, 17, 20 and 21.

Thence,

N. 89° 55' W., on true line bet. secs. 17 and 20.


Over rolling land, through scattering timber and dense undergrowth.

25.70 Tucson, Cornelia and Gila Bend Railroad, bears N. 25 1/4° E. to Gila Bend and S. 25 1/4° W. to Ajo.

27.00 Telegraph line, bears N. 25 1/4° E. and S. 25 1/4° W.

28.00 Highway, bears N. 25° E. to Gila Bend and S. 25° W. to Ajo.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked



1934

46.98 Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

48.00 Telephone line, bears N. 25° E. and S. 25° W.

61.80 Wash, 50 lks. wide, course NW.

67.60 Wash, 20 lks. wide, course NW.

79.98 The cor. of secs. 17, 18, 19 and 20.

Subdivision of T. 7 S., R. 5 W.

chains

Land, rolling.
Soil, sandy and gravelly loam, stony; 1st and 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

S.89°45'W., on a random line bet. secs. 18 and 19.

40.00 Set temp. 1/4 sec. cor.

78.50 Intersect W. bdy. of Tp., at the cor. of secs. 13, 18, 19 and 24, described in the field notes of said Township. Boundary as surveyed under this Group.


Thence,

N.89°45'E., on true line bet. secs. 18 and 19

Over rolling land, through scattering timber and dense undergrowth.

31.20 Wash, 60 lks. wide, course NE.

38.50 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked



Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

78.50 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.
Soil, sandy and gravelly loam, stony; 1st and 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.


N.0°03'W., bet. secs. 17 and 18.

Over rolling land, through scattering timber and dense undergrowth.

14.80 Wash, 20 lks. wide, course E.

17.30 Wash, 50 lks. wide, course E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked



Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap marked.

T7S	R5W
S7	S8
S18	S17

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam, stony; 1st and 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

S. $89^{\circ}55'E.$, on a random line bet. secs. 8 and 17.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. and S. line, 7 lks. S. of cor. of secs. 8, 9, 16 and 17.

Thence,

N. $89^{\circ}58'W.$, on true line bet. secs. 8 and 17.

Over rolling land, through scattering timber and dense undergrowth.

11.00 Telephone line, bears N. $25^{\circ}E.$ and S. $25^{\circ}W.$

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	S 8
	S 17

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

80.00 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, sandy and gravelly loam, stony; 1st and 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

S. $89^{\circ}45'W.$, on a random line bet. secs. 7 and 18.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

Subdivision of T. 7 S., R. 5 W.

chains

- 78.46 Intersect W. bdy. of Tp., 12 lks. S. of the cor. of secs. 7, 12, 13 and 18, described in the field notes of said Township Boundary as surveyed under this Group. Thence,
N.89°50'E., on true line bet. secs. 7 and 18.
Over rolling land, through scattering timber and dense undergrowth.
- 13.00 Leave rolling land, bears NW. and SE.; asc. 133 ft. over SW. slope.
- 22.00 Spur, slopes SE.; desc. 146 ft. over NE. slope.
- 33.50 Base of hill, bears N. and S., thence over rolling land.
- 34.30 Wash, 60 lks. wide, course N.
- 38.46 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} S 7 \\ \frac{1}{4} \\ \hline S 18 \end{array}$$

1934

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 78.46 The cor. of secs. 7, 8, 17 and 18.
Land, rolling.
Soil, sandy and gravelly loam, stony; 1st and 2nd rate.
Timber, scattering ironwood, mesquite and palo verde.
Undergrowth, greasewood, scattering cats claw and cacti.

N.0°03'W., bet. secs. 7 and 8.

Over rolling land, through scattering timber and dense undergrowth.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S7 \quad | \quad S8 \end{array}$$

1934

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap marked

Subdivision of T. 7 S., R. 5 W.

BOOK 4052

chains

T7S	R5W
S6	S5
S7	S8

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly loam; stony; 1st and 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

S. $89^{\circ}58'E.$, on a random line bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect N. and S. line, at the cor. of secs. 4, 5, 8 and 9.

Thence,

N. $89^{\circ}58'W.$, on true line bet. secs. 5 and 8.

Over rolling land, through scattering timber and dense undergrowth.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	S 5
	S 8

1934

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

80.04 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.

Soil, sandy and gravelly loam, stony; 1st and 2nd rate.

Timber, scattering ironwood, mesquite and palo verde.

Undergrowth, greasewood, scattering cats claw and cacti.

S. $89^{\circ}50'W.$, on a random line bet. secs. 6 and 7.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

78.30 Intersect W. bdy. of Tp., 5 lks. N. of the cor. of secs. 1, 6, 7 and 12, described in the field notes of said Township Boundary as surveyed under this Group.

Thence,

N. $89^{\circ}48'E.$, on true line bet. secs. 6 and 7.

Subdivision of T. 7 S., R. 5 W.

chains	Over rolling land, through scattering timber and dense undergrowth.
9.00	Base of hill, bears NE. and SW.; asc. 29 ft. over NW. slope.
14.00	Spur, slopes NE.; desc. 24 ft. over SE. slope.
22.00	Draw, course NE.; asc. 8 ft. over N. slope.
23.40	Low spur, slopes NE.; desc. 52 ft. over N. slope.
28.30	Base of hill, bears N. and S.; thence over rolling land.
38.30	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S\ 6 \\ \frac{1}{4} \\ \hline S\ 7 \\ 1934 \end{array}$
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
78.30	The cor. of secs. 5, 6, 7 and 8. Land, rolling and hilly. Soil, sandy and gravelly loam, stony; 1st and 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.
	N.0°18'W., on a random line bet. secs. 5 and 6.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
75.45	Intersect N. bdy. of Tp., 9 lks. W. of the cor. of secs. 5 and 6, T. 7 S., R. 5 W., described in the field notes of S. bdy. of T. 6 S., R. 5 W., resurveyed under this group.
	Thence, S.0°14'E., on true line bet. secs. 5 and 6.
	Over rolling land, through scattering timber and dense undergrowth.
35.45	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ S6 \quad \quad S5 \\ 1934 \end{array}$
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
75.45	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, sandy and gravelly loam, stony; 1st and 2nd rate. Timber, scattering ironwood, mesquite and palo verde. Undergrowth, greasewood, scattering cats claw and cacti.

T. 7 S., R. 5 W.

BOOK 4052

GENERAL DESCRIPTION

The general elevation of this township is about 1000 feet above sea level. The surface of the entire township is very gently rolling, except a few scattering hills. It is drained by large washes which flow in a northwesterly direction.

The soil, is of gravelly and sandy loam, with scattering patches of rocks, classed generally as 2nd rate.

A heavy growth of ironwood, mesquite and palo verde is found along the washes, and more or less scattering over the township. The undergrowth is greasewood, scattering cats claw, ocotillo and various kinds of cacti.

The Tucson, Cornelia and Gila Bend railroad, ^{a telegraph line,} an improved highway and a telephone line extend in a northeasterly and southwesterly direction through the township. There are no other improvements in the township. No indication of mineral or evidence of water was found.

4-679 b

~~INDEX~~ DIAGRAM.

Township 7 South, Range 5 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

6-4817

_____ Surveyed by Dexter S. King, Temporary Transitman.
 _____ Surveyed by Robt. H. Williams, Temporary Transitman.

FIELD ASSISTANTS.
to
Robt. H. Williams, Temporary Transitman

NAMES.	CAPACITY.
G. C. Capes	1st Chainman
Odis Kent	2nd Chainman
Harmon Yoakum	Flagman
A. L. Hart	Cornerman
LeRoy De Brown	Cornerman
R. P. Childers	Axman
Albert Scott	Axman

38

44

BOOK 4052

CERTIFICATE OF UNITED STATES SURVEYOR

I, Robt. H. Williams Temporary Transitman, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of

Township 7 South, Range 5 West

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Robt. H. Williams Temporary Transitman

APPROVAL

Office of U. S. Supervisor of Surveys

19

The foregoing field notes of the survey of

executed by under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys

I certify that the foregoing transcript of the field notes of the above described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys

4-680
(August, 1926)

FIELD ASSISTANTS.

to
Dexter S. King, Temporary Transitman

NAMES.	CAPACITY.
C. R. Tonneman	1st Chainman
R. D. Lewis	2nd Chainman
George H. Lindberg	2nd Chainman
Lloyd Harroll	Flagman
Chas. L. Turner	Flagman
Frank P. Hebert	Cornerman
G. C. Cole	Cornerman
Earl Cline	Axman
John Horcy	Axman

BOOK 4052

CERTIFICATE OF UNITED STATES SURVEYOR

I, Dexter S. King *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of _____ the SUBDIVISION LINES of _____ Township 7 South, Range 5 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey,

Dexter S. King
Temporary Transitman

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,
 Denver, Colorado, May 16, 1935

The foregoing field notes of the survey of _____ the SUBDIVISION LINES of _____ Township 7 South, Range 5 West of the Gila and Salt River Base and Meridian, in the State of Arizona executed by Robt. H. Williams and Dexter S. King *Temporary Transitman* under special instructions dated December 12, 1933- Group 199, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Monte H. Hanson
 U. S. Supervisor of Surveys.

~~I certify that the foregoing transcript of the field notes of the above described surveys in _____, has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~