

FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISIONS of

Township 8 South, Range 6 West

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Ben D. Procter, Frank C. Mulford, Robt. H. Williams,

R.E. McMahan and K.K. Bowsher, Temporary Transmitters

In the capacity of U. S. Surveyors, under Special Instructions dated Dec. 12, 1933, issued by the District Cadastral Engineer to govern surveys included in Group No. 199, Arizona, which were approved by the Commissioner of the General Land Office, February 17, 1934, and Assignment Instructions dated Dec. 15, 1933.

Survey commenced January 12, 1934.

Survey completed January 17, 1934.

4055

4055

INDEX DIAGRAM.

Township _____, Range _____

6	5	4	3	2	1
7	8	9	10	11	12
13	17	16	15	14	13
19	20	21	22	23	24
29	29	28	27	26	25
31	32	33	34	35	36

INDEX DIAGRAM.

BOOK 4055

	6 31	5 24	4 19	3 14	2 8	1		
	31	30	24	19	13	8 7		
	7 30	8 24	9 18	10 13	11 7	12		
	29 30	29 23	23	18	12	7 6		
	18 29	17 23	¹⁶ 17	¹⁵ 12	14 6	13		
	28	28 22	T. S. - R. G. W.		11	6 5		
	19 28	20 22	21 16	22 11	23 5	24		
	27 27	27 21	21	16	10 4	4		
	30 26	29 21	28 15	27 10	26 3	25		
	26	25 20	20	15	9	3 2		
	31 25	32 20	33 14	34 9	35 2	36		
		19		8	1			

———— Surveyed under this group.

———— Resurveyed under this group.



Areas surveyed as per accepted plats on file.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

The subdivisional survey of T.8 S., R.6 W., was executed with Young & Sons light-mountain transits Nos. 8477, 8584, 8588 and 8592, and W. & L.E. Gurley Transit No. 20117, by Ben D. Procter, K.K. Bowsher, Frank C. Mulford, R.E. McMahan and Robt. H. Williams, Temporary Transitmen. The instruments are constructed in accordance with the standard specifications of the General Land Office, with full vertical circles reading to single minutes, which is also the least count of the two verniers of the horizontal circles of each instrument. The transits were in good condition, and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, were approved by the district cadastral engineer on Dec. 15, 1933.

The types of land, timber and undergrowth in T.8 S., R.6 W., offer few objections to projection of lines by back and foresight method; that method is selected in view of the unfamiliarity of the instrumentmen with the solar attachments with which the instruments are equipped.

Lines are initiated from the south boundary of the Tp., carefully surveyed at this time with instruments tested as described in notes of that line. The true bearings of all lines are checked by repetition of angles, double back and foresights and occasional direct altitude observations on the sun for azimuth, and where feasible, by check of the azimuths initiated at different points on the S. bdy. against each other.

The measurements were made with Lallie and Lufkin steel tapes, 5 chs. in length, graduated every link for the first 100 lks. and the balance at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements are made on the slope; the vertical angle of each interval is ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

SURVEY

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., established under this Group, described in notes of that line,

N.0°01'W., bet. secs. 35 and 36.

Over gently rolling land; through scattering timber and dense undergrowth.

- 0.60 Wash, 10 lks. wide, course N.75°W., soon N.30°W.
 11.00 Wash, 10 lks. wide, course N.70°W.
 17.00 Wash, 12 lks. wide, course W.
 35.00 Wash, 20 lks. wide, course N.70°W.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for sec. cor., with brass cap mkd.

↑
 S35 | S36
 1934

and raise a mound

SUBDIVISIONS OF T.8 S., R.6 W.


Chains

of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

43.30 Wash, 30 lks. wide, course N.60°W.

53.30 Wash, 10 lks. wide, course N.70°W.

79.90 (10 lks. S.0°01'E. of true point) Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. to cor. of secs. 25, 26, 35 and 36, with brass cap mkd.



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

80.00 True point for cor. of secs. 25, 26, 35 and 36 falls in wash, 20 lks. wide, course NW.

Land: gently rolling.
Soil: sandy and gravelly loam, stony, 2nd rate.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, ocotillo, catclaw and cactus.

S.89°58'E., on random line, bet. secs. 25 and 36.

40.00 Set temp. 1/4 sec. cor.

80.10 Intersect the E. bdy. of the Tp. at a point 2 lks. S. of the cor. of secs. 25, 30, 31 and 36, established under this Group, described in notes of that line.

Thence

N.89°59'W., on true line, bet. secs. 25 and 36.

Asc. 23 ft. over E. slope; through scattering timber and dense undergrowth.

3.20 Spur, slopes N.; desc. 44 ft. over W. slope.

7.80 Small wash, 5 lks. wide, course NW.; asc. 23 ft. over NE. slope.

12.90 Rocky spur, slopes NW.; desc. 44 ft. over SW. slope.

17.10 Small wash, 8 lks. wide, course NW.; over rolling land.


21.50 Wash, 30 lks. wide, course NW.

26.90 Begin ascent of 29 ft. over E. slope.

35.10 Spur, slopes N.; desc. 46 ft. over NW. slope.

40.00 Foot of descent, bears N. and S.; over gently rolling land.

40.05 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 4055

Chains	
	and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
60.00	Begin ascent of 93 ft. over NE. slope.
64.50	Spur, slopes NW.; desc. 102 ft. over W. slope.
74.10	Foot of slope; over gently rolling land.
77.95	Wash, 15 lks. wide, course NW.
79.70	Small wash, 20 lks. wide, course N.70°W.
80.10	The true point for cor. of secs. 25,26,35 and 36.
	Land: rolling and gently rolling. Soil: sandy and gravelly loam, rocky, 2nd and 3rd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw, ocotillo and cactus.

	N.0°01'W., bet. secs. 25 and 26.
	Over gently rolling land; through scattering timber and dense undergrowth.
0.70	Wash, 30 lks. wide, course NW.
9.70	Railroad, bears NE. to Gila Bend and SW. to Ajo.
12.00	Telegraph line, parallels railroad.
14.80	Highway, bears NE. to Gila Bend and SW. to Ajo.
22.00	Wash, 12 lks. wide, course NW.
31.20	Wash, 8 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ S26 \quad \quad S25 \\ \\ 1934 \end{array}$
	and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
55.00	Wash, 30 lks. wide, course W.
73.00	Wash, 30 lks. wide, course S.80°W.
78.00	Wash, 30 lks. wide, course S.80°W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 23,24,25 and 26, with brass cap mkd.
	$\begin{array}{c} T8S \quad R6W \\ S23 \quad \quad S24 \\ \hline S26 \quad \quad S25 \\ \\ 1934 \end{array}$
	and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, ocotillo and cactus.

S.89°59'E., on random line, bet. secs. 24 and 25.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.22 Intersect the E. bdy. of the Tp. at a point 14 lks. N. of the cor. of secs. 19, 24, 25 and 30, established under this Group, described in notes of that line.

Thence

N.89°53'W., on true line, bet. secs. 24 and 25.

Over gently rolling land; through scattering timber and dense undergrowth.

5.00 Wash, 15 lks. wide, course SW.

10.00 Wash, 15 lks. wide, course NW.

12.00 Same wash, course SW.

15.70 Same wash, course NW.

40.11 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S24
 $\frac{1}{4}$ S25

1934

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

53.70 Wash, 30 lks. wide, course NW.

56.70 Wash, 30 lks. wide, course NW.

59.15 Railroad, bears N.11°E. to Gila Bend and S.11°W. to Ajo.

60.20 Telegraph line, parallels railroad.

67.20 Highway, bears N.20°E. to Gila Bend and S.20°W. to Ajo.

80.22 The cor. of secs. 23, 24, 25 and 26.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°01'W., bet. secs. 23 and 24.

Over gently rolling land; through scattering timber and dense undergrowth.

15.50 Wash, 15 lks. wide, course W.

22.00 Wash, 12 lks. wide, course W.

36.00 Wash, 12 lks. wide, course NW.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 407

Chains 40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S23 S24 1934 </p> <p style="text-align: right;">and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.</p>
46.00	Wash, 10 lks. wide, course NW.
60.00	Wash, 10 lks. wide, course W.
66.00	Telephone line, bears NE. and SW.
76.00	Wash, 30 lks. wide, course W.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.</p> <p style="text-align: center;"> T8S R6W S14 S13 S23 S24 1934 </p> <p style="text-align: right;">and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.</p> <p>Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw, ocotillo and cactus.</p> <hr style="border-top: 1px dashed black;"/> <p>S.89°53'E., on random line, bet. secs. 13 and 24.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.32	<p>Intersect the E. bdy. of the Tp. at a point 5 lks. S. of the cor. of secs. 13, 18, 19 and 24, established under this Group, described in notes of that line.</p> <p>Thence</p> <p>N.89°55'W., on true line, bet. secs. 13 and 24.</p> <p>Over gently rolling land; through scattering timber and dense undergrowth.</p>
19.00	Wash, 30 lks. wide, course SW.
40.16	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S13 $\frac{1}{4}$ S24 1934 </p> <p style="text-align: right;">and raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p>
44.30	Railroad, bears N.11°E. and S.11°W.
45.70	Telegraph line, parallels railroad.
46.70	Highway, bears N.11°E. to Gila Bend and S.11°W. to Ajo.

SUBDIVISIONS OF T. 6 S., R. 6 W.

Chains

66.30 Wash, 45 lks. wide, course SE.

74.50 Telephone line, bears N.20°E. and S.20°W.

80.32 The cor. of secs. 13,14,23 and 24.

Land: gently rolling.

Soil: sandy and gravelly loam, stony, 2nd rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°01'W., bet. secs. 13 and 14.

Over gently rolling land; through scattering timber and dense undergrowth.

15.50 Wash, 30 lks. wide, course N.80°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S14 | S13
 1934

and dig pits, 18 x
18 x 12 ins., N. and S. of post, 3 ft. dist.

58.00 Wash, 10 lks. wide, course W.

80.00 Set a lava stone, 20 x 8 x 6 ins., 15 ins. in the ground, for cor. of secs. 11,12,13 and 14, mkd. with 4 grooves on S. and 1 groove on E. faces, and

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land: gently rolling.

Soil: sandy and gravelly loam, stony, 2nd rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

S.89°55'E., on random line, bet. secs. 12 and 13.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.24 Intersect the E. bdy. of the Tp. at a point 12 lks. S. of the cor. of secs. 7,12,13 and 18, established under this Group, described in notes of that line.

Thence

West, on true line, bet. secs. 12 and 13.

Over gently rolling land; through scattering timber and dense undergrowth.

34.15 Railroad, bears N.20°E. to Gila Bend and S.20°W. to Ajo.

35.80 Telegraph line, parallels railroad.

36.65 Highway, bears N.15°E. to Gila Bend and S.15°W. to Ajo.

40.12 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 100

Chains	
	$\begin{array}{r} \frac{1}{4}S12 \\ \frac{1}{4}S13 \\ \hline 1934 \end{array}$ <p style="text-align: right;">and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.</p>
46.20	Telephone line, bears NE. and SW.
80.24	The cor. of secs. 11,12,13 and 14.
	<p>Land: gently rolling. Soil: sandy and gravelly loam, stony, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw, ocotillo and cactus.</p>

	N.0°01'W., bet. secs. 11 and 12.
	Over gently rolling land; through scattering timber and dense undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S11 S12 \\ 1934 \end{array}$ <p style="text-align: right;">and raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p>
80.00	Set a lava stone, 20 x 8 x 8 ins., 15 ins. in the ground, for cor. of secs. 1,2,11 and 12, mkd. with 5 grooves on S. and 1 groove on E. faces, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	<p>Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw, ocotillo and cactus.</p>

	East, on random line, bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.24	Intersect the cor. of secs. 1,6,7 and 12, on the E. bdy. of the Tp., established under this Group, described in notes of that line.
	Thence
	West, on true line, bet. secs. 1 and 12.
	Desc. 149 ft. over NW. slope; through scattering timber and undergrowth.
11.00	Foot of slope, bears NE. and SW.; over gently rolling land.
17.60	Railroad, bears N.25°E. to Gila Bend and S.25°W. to Ajo.
19.10	Telegraph line, parallels railroad.
20.20	Highway, bears N.20°E. to Gila Bend and S.20°W. to Ajo.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

- 24.10 Telephone line, bears N.20°E. and S.20°W.
- 40.12 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- S1
—
S12
1934
- and dig pits, 18 x 18
x 12 ins., E. and W. of post, 3 ft. dist.
- 74.20 Wash, 15 lks. wide, course NW.
- 80.24 The cor. of secs. 1,2,11 and 12.
- Land: rolling.
Soil: sandy and gravelly loam, stony, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.
-
- N.0°01'W., on random line, bet. secs. 1 and 2.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.81 Intersect the N. bdy. of the Tp. at a point 25 lks. W. of the cor. of secs. 1,2,35 and 36, established under this Group, described in notes of that line.
- Thence
- S.0°10'W., on true line, bet. secs. 1 and 2.
- Asc. 54 ft. over NW. slope; through scattering timber and undergrowth.
- 4.40 Spur, slopes W.; desc. 59 ft. over SW. slope.
- 9.80 Foot of descent, bears NW. and SE.; over gently rolling land.
- 39.81 Set a lava stone, 22 x 6 x 6 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{2}$ on W. face, and
- dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.
- 43.80 Wash, 150 lks. wide, course NW.
- 64.80 Flat wash, 30 lks. wide, course NW.
- 79.81 The cor. of secs. 1,2,11 and 12.
- Land: rolling.
Soil: sandy and gravelly, 2nd rate.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw, ocotillo and cactus.
-
- From the cor. of secs. 2,3,34 and 35, on the S. bdy. of the Tp., established under this Group, described in notes of that line,
- N.0°01'W., bet. secs. 34 and 35.
- Over gently rolling land; through scattering timber and dense undergrowth.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 401

Chains	
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \uparrow \\ S34 S35 \\ \hline 1934 \end{array}$ </div> and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.
49.00	Wash, 200 lks. wide, course W.
58.75	Wash, 40 lks. wide, course W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{cc} T8S & R6W \\ \hline S27 & & S26 \\ \hline S34 & & S35 \\ \hline 1934 \end{array}$ </div> and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw and cactus.

	S. $89^{\circ}58'E.$, on random line, bet. secs. 26 and 35.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	A point 5 lks. S. of the true point for cor. of secs. 25, 26, 35 and 36, hereinbefore described.
	Thence West, on true line, bet. secs. 26 and 35. Over gently rolling land; through scattering timber and undergrowth.
4.80	Railroad, bears N. $27^{\circ}E.$ to Gila Bend and S. $27^{\circ}W.$ to Ajo.
6.50	Telegraph line, parallels railroad.
7.70	Highway, bears NE. to Gila Bend and SW. to Ajo.
26.10	Wash, 14 lks. wide, course NW.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} S26 \\ \hline S35 \\ \hline 1934 \end{array}$ </div> and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.
44.40	Telephone line, bears N. $10^{\circ}E.$ and S. $10^{\circ}W.$
80.02	The cor. of secs. 26, 27, 34 and 35. Land: gently rolling.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, ocotillo and catclaw and cactus.

N.0°01'W., bet. secs. 26 and 27.

Over gently rolling land; through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S27 | S26
 1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

55.00 Wash, 200 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

T8S R6W
 S22 | S23
 S27 | S26
 1934

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land: gently rolling.

Soil: sandy and gravelly loam, stony, 2nd rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

East, on random line, bet. secs. 23 and 26.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 A point 2 lks. N. of the cor. of secs. 23, 24, 25 and 26.

Thence

N.89°59'W., on true line, bet. secs. 23 and 26.

Over gently rolling land; through scattering timber and dense undergrowth.

19.15 Telephone line, bears N.10°E. and S.10°W.

39.95 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S23
 S26
 1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

79.90 The cor. of secs. 22, 23, 26 and 27.

SUBDIVISIONS OF T.8 S., R.6 W.

11

BOOK 401

Chains

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

 N.0°01'W., bet. secs. 22 and 23.

Over gently rolling land; through scattering timber and dense undergrowth.

10.00 Wash, 15 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S22 | S23
 1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

T8S R6W
 S15 | S14
 S22 | S23
 1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

 S.89°59'E., on random line, bet. secs. 14 and 23.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.06 Intersect the cor. of secs. 13, 14, 23 and 24.

Thence

N.89°59'W., on true line, bet. secs. 14 and 23.

Over gently rolling land; through scattering timber and dense undergrowth.

40.03 True point for $\frac{1}{4}$ sec. cor. falls in wash, 15 lks. wide, course N.65°W.

40.18 (15 lks. N.89°59'W. of true point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S14 WC
 S23
 1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

80.06 The cor. of secs. 14, 15, 22 and 23.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

 N.0°01'W., bet. secs. 14 and 15.

Over gently rolling land; through scattering timber and dense undergrowth.

38.90 Wash, 15 lks. wide, course N.60°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 |
 S15 | S14
 |
 1934

and raise a mound of
 stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 10,11,14 and 15, with brass cap mkd.

T8S R6W
 S10 | S11
 S15 | S14
 1934

and raise a mound of
 stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

 S.89°59'E., on random line, bet. secs. 11 and 14.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.18 A point 2 lks. N. of the cor. of secs. 11,12,13 and 14.

Thence

N.89°58'W., on true line, bet. secs. 11 and 14.

Over gently rolling land; through scattering timber and dense undergrowth.

40.09 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S11
 |
 S14
 1934

and raise a mound of
 stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

80.18 The cor. of secs. 10,11,14 and 15.

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 4088

Chains

Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°01'W., bet. secs. 10 and 11.

Over gently rolling land; through scattering timber and dense undergrowth.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S10 | S11
 1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

- 80.00 Set a lava stone, 20 x 8 x 8 ins., 15 ins. in the ground, for cor. of secs. 2,3,10 and 11, mkd. with 5 grooves on S. and 2 grooves on E. faces, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

S.89°58'E., on random line, bet. secs. 2 and 11.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.

- 80.20 A point 2 lks. S. of the cor. of secs. 1,2,11 and 12.

Thence

N.89°59'W., on true line, bet. secs. 2 and 11.

- 40.10 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S2
 S11
 1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

- 80.20 The cor. of secs. 2,3,10 and 11.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°10'E., on random line, bet. secs. 2 and 3.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.

- 79.90 Intersect the N. bdy. of the Tp. at a point 3 lks. E. of the cor. of secs. 2,3,34 and 35, established under this Group, described in notes of that line.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

Thence

S.0°09'W., on true line, bet. secs. 2 and 3.

Over gently rolling land; through scattering timber and dense undergrowth.

34.40 Wash, 60 lks. wide, course NW.

39.90 Set a lava stone, 20 x 6 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and

dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

79.90 The cor. of secs. 2,3,10 and 11.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

From the cor. of secs. 3,4,33 and 34, on the S. bdy. of the Tp., established under this Group, described in notes of that line,

N.0°02'W., bet. secs. 33 and 34.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S33} \mid \text{S34} \\ 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

71.00 Wash, 25 lks. wide, course N.80°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 27,28,33 and 34, with brass cap mkd.

$$\begin{array}{c} \text{T8S R6W} \\ \text{S28} \mid \text{S27} \\ \text{S33} \mid \text{S34} \\ 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

S.89°58'E., on random line, bet. secs. 27 and 34.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 A point 2 lks. N. of the cor. of secs. 26,27,34 and 35.

Thence

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 15 4085

Chains	
	N.89°57'W., on true line, bet. secs. 27 and 34. Over gently rolling land; through scattering timber and dense undergrowth.
14.65	Wash, 40 lks. wide, course NW.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \underline{327} \\ 334 \\ 1934 \end{array}$
	and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.
73.65	Wash, 40 lks. wide, course NW.
79.96	The cor. of secs. 27, 28, 33 and 34. Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw and cactus.

	N.0°02'W., bet. secs. 27 and 28. Over gently rolling land; through scattering timber and dense undergrowth.
34.30	Wash, 40 lks. wide, course N.25°W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ \underline{328} \quad \underline{327} \\ 1934 \end{array}$
	and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.
48.00	Wash, 100 lks. wide, course W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.
	$\begin{array}{r} T8S \quad R6W \\ \underline{321} \quad \underline{322} \\ \underline{328} \quad \underline{327} \\ 1934 \end{array}$
	and dig pits, 18' x 18 x 12 ins., one in each sec., 3 ft. dist.
	Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw and cactus.

	S.89°57'E., on random line, bet. secs. 22 and 27.
40.00	Set temp. $\frac{1}{4}$ sec. cor.

Chains

79.92 A point 7 lks. S. of the cor. of secs. 22, 23, 26 and 27.

Thence

West, on true line, bet. secs. 22 and 27.

Over gently rolling land; through scattering timber and dense undergrowth.

39.96 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \text{S22} \\ \hline \frac{1}{4} \text{S27} \end{array}$$

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

47.30 Wash, 25 lks. wide, course N.10°W.

79.92 The cor. of secs. 21, 22, 27 and 28.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°02'W., bet. secs. 21 and 22.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \downarrow \\ \text{S21} \mid \text{S22} \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

79.80 (20 lks. S.0°02'E. of true point) Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. to cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

$$\begin{array}{c} \text{T8S R6W} \\ \text{W C} \\ \hline \text{S16} \mid \text{S15} \\ \hline \text{S21} \mid \text{S22} \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., one each NE., SE., SW. and NW., 3 ft. dist.

80.00 True point for cor. of secs. 15, 16, 21 and 22 falls in wash, 30 lks. wide, course NW.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 405E

Chains

East, on random line, bet. secs. 15 and 22.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 A point 5 lks. N. of the cor. of secs. 14,15,22 and 23.

Thence

N.89°58'W., on true line, bet. secs. 15 and 22.

Over gently rolling land; through scattering timber and dense undergrowth.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} S15 \\ \hline \frac{1}{4} S22 \end{array}$$

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

79.98 The true point for cor. of secs. 15,16,21 and 22.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°02'W., bet. secs. 15 and 16.

Over gently rolling land; through scattering timber and dense undergrowth.

32.90 Wash, 15 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} S16 \quad \frac{1}{4} S15 \\ \hline \end{array}$$

1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 9,10,15 and 16, with brass cap mkd.

$$\begin{array}{r} T8S R6W \\ \hline S9 \quad S10 \\ \hline S16 \quad S15 \end{array}$$

1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

SUBDIVISIONS OF T.8 S., R.6 W.

- Chains 3.89°58'E., on random line, bet. secs. 10 and 15.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.98 A point 5 lks. S. of the cor. of secs. 10,11,14 and 15.
- Thence
West, on true line, bet. secs. 10 and 15.
- Over gently rolling land; through scattering timber and dense undergrowth.
- 39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\begin{array}{r} \frac{1}{4}S10 \\ \frac{1}{4}S15 \\ 1934 \end{array}$$
- and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.
- 55.00 Wash, 15 lks. wide, course NW.
- 79.98 The cor. of secs. 9,10,15 and 16.
- Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.
-
- N.0°02'W., bet. secs. 9 and 10.
- Over gently rolling land; through scattering timber and dense undergrowth.
- 34.20 Shallow wash, 15 lks. wide, course NW.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\begin{array}{r} \frac{1}{4} \\ S9 \quad S10 \\ 1934 \end{array}$$
- and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.
- 80.00 Set a lava stone, 28 x 6 x 6 ins., 20 ins. in the ground, for cor. of secs. 3,4,9 and 10, mkd. with 5 grooves on S. and 3 grooves on E. faces, and
- dig pits, 18x18x12 ins., one in each sec., 3 ft. dist.
- Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.
-
- East, on random line, bet. secs. 3 and 10.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.18 A point 5 lks. N. of the cor. of secs. 2,3,10 and 11.

Chains

Thence

N.89°58'W., on true line, bet. secs. 3 and 10.

Over gently rolling land; through scattering timber and dense undergrowth.

14.35 Wash, 15 lks. wide, course NW.

35.20 Wash, 40 lks. wide, course N.10°W.

40.09 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{2}$ sec. cor., with brass cap mkd. $\frac{3}{4}$ S10

1934

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

80.18 The cor. of secs. 3,4,9 and 10.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°09'E., on random line, bet. secs. 3 and 4.

40.00 Set temp. $\frac{1}{2}$ sec. cor.

79.99 Intersect the N. bdy. of the Tp. at a point 23 lks. W. of the cor. of secs. 3,4,33 and 34, established under this Group, described in notes of that line.

Thence

S.0°19'W., on true line, bet. secs. 3 and 4.

Over gently rolling land; through scattering timber and dense undergrowth.

2.80 Wash, 15 lks. wide, course NW.

39.99 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and

dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

79.99 The cor. of secs. 3,4,9 and 10.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

From the cor. of secs. 4,5,32 and 33, on the S. bdy. of the Tp., established under this Group, described in notes of that line,

N.0°02'W., bet. secs. 32 and 33.

Over gently rolling land; through scattering timber and dense undergrowth.

SUBDIVISIONS OF T.8 S., R.6 W.


Chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.

S.89°58'E., on random line, bet. secs. 28 and 33.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 A point 2 lks. N. of the cor. of secs. 27, 28, 33 and 34.

Thence


N.89°57'W., on true line, bet. secs. 28 and 33.

Over gently rolling land; through scattering timber and dense undergrowth.

4.10 Wash, 15 lks. wide, course NW.

35.00 Wash, 5 lks. wide, course NW.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

79.98 The cor. of secs. 28, 29, 32 and 33.

Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.

N.0°02'W., bet. secs. 28 and 29.

Over gently rolling land; through scattering timber and dense undergrowth.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 4055

Chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{2}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{2} \\ \text{S29} \mid \text{S28} \\ 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

63.10 Wash, 10 lks. wide, course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

$$\begin{array}{c} \text{T8S, R6W} \\ \text{S20} \mid \text{S21} \\ \hline \text{S29} \mid \text{S28} \\ 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

S.89°57'E., on random line, bet. secs. 21 and 28.

40.00 Set temp. $\frac{1}{2}$ sec. cor.

79.98 Intersect the cor. of secs. 21, 22, 27 and 28.

Thence

N.89°57'W., on true line, bet. secs. 21 and 28.

Over gently rolling land; through scattering timber and dense undergrowth.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \text{S21} \\ \hline \frac{1}{4} \text{S28} \\ 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

79.98 The cor. of secs. 20, 21, 28 and 29.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°02'W., bet. secs. 20 and 21.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

$$\begin{array}{c} \frac{1}{2} \\ \hline S20 | S21 \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

$$\begin{array}{c} T8S R6W \\ \hline S17 | S16 \\ \hline S20 | S21 \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

S.89°57'E., on random line, bet. secs. 16 and 21.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.92 Intersect the true point for cor. of secs. 15, 16, 21 and 22, hereinbefore described.

Thence

N.89°57'W., on true line, bet. secs. 16 and 21.

Over gently rolling land; through scattering timber and dense undergrowth.

39.96 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} S16 \\ \hline S21 \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

79.92 The cor. of secs. 16, 17, 20 and 21.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°02'W., bet. secs. 16 and 17.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{2} \\ \hline S17 | S16 \\ \hline 1934 \end{array}$$

and dig pits, 18 x

Chains

18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 8,9,16 and 17, with brass cap mkd.

T8S R6W
 38 | 39
 317 | 316
 1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

S.89°57'E., on random line, bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{2}$ sec. cor.

79.88 Intersect the cor. of secs. 9,10,15 and 16.

Thence

N.89°57'W., on true line, bet. secs. 9 and 16.

Over gently rolling land; through scattering timber and dense undergrowth.

29.65 Wash, 12 lks. wide, course N.70°W.

37.40 Wash, 12 lks. wide, course NW.

39.94 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

39
 316
 1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

79.88 The cor. of secs. 8,9,16 and 17.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°02'W., bet. secs. 8 and 9.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

38 | 39
 1934

and dig pits, 18 x

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for cor. of secs. 4,5,8 and 9, mkd. with 5 grooves on S. and 4 grooves on E. faces, and

dig pits, 18x18x12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

S.89°57'E., on random line, bet. secs. 4 and 9.

40.00 Set temp. $\frac{1}{2}$ sec. cor.

80.02 A point 7 lks. N. of the cor. of secs. 3,4,9 and 10.

Thence

N.89°54'W., on true line, bet. secs. 4 and 9.

Over gently rolling land; through scattering timber and dense undergrowth.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{34}{439}$$

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

65.00 Wash, 40 lks. wide, course NW.

80.02 The cor. of secs. 4,5,8 and 9.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°19'E., on random line, bet. secs. 4 and 5.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.86 Intersect the N. bdy. of the Tp. at a point 7 lks. E. of the cor. of secs. 4,5,32 and 33, established under this group, described in notes of that line.

Thence

S.0°16'W., on true line, bet. secs. 4 and 5.

Over gently rolling land; through scattering timber and dense undergrowth.

39.86 Set a lava stone, 20 x 8 x 8 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and

dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

79.86 The cor. of secs. 4,5,8 and 9.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 4088

Chains

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw and cactus.

 From the cor. of secs. 5,6,31 and 32, on the S. bdy. of the
 Tp., established under this Group, described in notes of
 that line,

N.0°03'W., bet. secs. 31 and 32.

Over gently rolling land; through scattering timber and
 dense undergrowth.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 |
 S31 | S32
 |
 1934

and dig pits, 18 x
 18 x 12 ins., N. and S. of post, 3 ft. dist.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
 ground, for cor. of secs. 29,30,31 and 32, with brass cap
 mkd.

T8S R6W
 S30 | S29

 S31 | S32
 1934

and dig pits, 18 x
 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw and cactus.

 S.89°58'E., on random line, bet. secs. 29 and 32.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.

- 79.94 A point 5 lks. S. of the cor. of secs. 28,29,32 and 33.

Thence

West, on true line, bet. secs. 29 and 32.

Over gently rolling land; through scattering timber and
 dense undergrowth.

- 39.97 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S29
 |
 S32
 |
 1934

and dig pits, 18 x
 18 x 12 ins., E. and W. of post, 3 ft. dist.

- 79.94 The cor. of secs. 29,30,31 and 32.

Chains

Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.

N.89°58'W., on random line, bet. secs. 30 and 31.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.05 Intersect the W. bdy. of the Tp. at a point 7 lks. S. of the cor. of secs. 25,30,31 and 36, established under this Group, described in notes of that line.

Thence

S.89°55'E., on true line, bet. secs. 30 and 31.

Over gently rolling land; through scattering timber and dense undergrowth.

39.05 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S30
S31

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

79.05 The cor. of secs. 29,30,31 and 32.

Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.

N.0°03'W., bet. secs. 29 and 30.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S30 | S29
1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19,20,29 and 30, with brass cap mkd.

T8S | R6W
S19 | S20
S30 | S29
1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.

SUBDIVISIONS OF T.8 S., R.6 W.

227
BOOK 4065

Chains

Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.

East, on random line, bet. secs. 20 and 29.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.92 A point 9 lks. N. of the cor. of secs. 20, 21, 28 and 29.

Thence

N.89°56'W., on true line, bet. secs. 20 and 29.

Over gently rolling land; through scattering timber and dense undergrowth.

23.10 Wash, 100 lks. wide, course NW.

39.96 Set a lava stone, 24 x 12 x 10 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

79.92 The cor. of secs. 19, 20, 29 and 30.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.89°55'W., on random line, bet. secs. 19 and 30.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

78.95 Intersect the W. bdy. of the Tp. at a point 7 lks. S. of the cor. of secs. 19, 24, 25 and 30, established under this Group, described in notes of that line.

Thence

S.89°52'E., on true line, bet. secs. 19 and 30.

Over gently rolling land; through scattering timber and dense undergrowth.

38.95 Set a lava stone, 24 x 10 x 8 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

78.95 The cor. of secs. 19, 20, 29 and 30.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°03'W., bet. secs. 19 and 20.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set a lava stone, 30 x 9 x 6 ins., 20 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 17,18,19 and 20, with brass cap mkd.

T8S	R6W
S18	S17
S19	S20
1934	

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

S.89°56'E., on random line, bet. secs. 17 and 20.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 A point 2 lks. N. of the cor. of secs. 16,17,20 and 21.

Thence

N.89°55'W., on true line, bet. secs. 17 and 20.

Over gently rolling land; through scattering timber and dense undergrowth.

39.95 Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for $\frac{1}{2}$ sec. cor., mkd. $\frac{1}{2}$ on N. face, and

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

79.90 The cor. of secs. 17,18,19 and 20.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.89°52'W., on random line, bet. secs. 18 and 19.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

78.85 Intersect the W. bdy. of the Tp. at a point 9 lks. N. of the cor. of secs. 13,18,19 and 20, established under this Group, described in notes of that line.

Thence

S.89°56'E., on true line, bet. secs. 18 and 19.

Over gently rolling land; through scattering timber and dense undergrowth.

38.85 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for $\frac{1}{2}$ sec. cor., mkd. $\frac{1}{2}$ on N. face, and

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

78.85 The cor. of secs. 17,18,19 and 20.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 4085

Chains

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw and cactus.

 N.0°03'W., bet. secs. 17 and 18.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set a lava stone, 24 x 10 x 8 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and

dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

80.00 Set a lava stone, 30 x 10 x 8 ins., 20 ins. in the ground, for cor. of secs. 7,8,17 and 18, mkd. with 4 grooves on S. and 5 grooves on E. faces, and

dig pits, 18x18x12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw and cactus.

 S.89°55'E., on random line, bet. secs. 8 and 17.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.94 A point 9 lks. N. of the cor. of secs. 8,9,16 and 17.

Thence

N.89°51'W., on true line, bet. secs. 8 and 17.

Over gently rolling land; through scattering timber and dense undergrowth.

39.97 Set a lava stone, 20 x 12 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

79.94 The cor. of secs. 7,8,17 and 18.

Land: gently rolling.
 Soil: sandy and gravelly loam, 1st and 2nd rates.
 Timber: scattering ironwood, mesquite and palo verde.
 Undergrowth: greasewood, catclaw and cactus.

 N.89°56'W., on random line, bet. secs. 7 and 18.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

78.70 Intersect the W. bdy. of the Tp. at a point 5 lks. S. of the cor. of secs. 7,12,13 and 18, established under this Group, described in notes of that line.

Thence

S.89°54'E., on true line, bet. secs. 7 and 18.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

Over gently rolling land; through scattering timber and dense undergrowth.

38.70 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

78.70 The cor. of secs. 7, 8, 17 and 18.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

N.0°03'W., bet. secs. 7 and 8.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set a lava stone, 24 x 12 x 10 ins., 16 ins. in the ground, for $\frac{1}{2}$ sec. cor., mkd. $\frac{1}{2}$ on W. face, and dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

80.00 Set a lava stone, 24 x 12 x 10 ins., 16 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, mkd. with 5 grooves on S. and 5 grooves on E. faces, and

dig pits, 18x18x12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

S.89°51'E., on random line, bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{2}$ sec. cor.

80.02 A point 2 lks. S. of the cor. of secs. 4, 5, 8 and 9.

Thence

N.89°52'W., on true line, bet. secs. 5 and 8.

Over gently rolling land; through scattering timber and dense undergrowth.

30.50 Wash, 10 lks. wide, course NW.

40.01 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for $\frac{1}{2}$ sec. cor., mkd. $\frac{1}{2}$ on N. face, and dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

80.02 The cor. of secs. 5, 6, 7 and 8.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw and cactus.

SUBDIVISIONS OF T.8 S., R.6 W.

BOOK 4000

Chains

- N.89°54'W., on random line, bet. secs. 6 and 7.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 78.61 Intersect the W. bdy. of the Tp. at a point 9 lks. N. of the cor. of secs. 1,6,7 and 12, established under this Group, described in notes of that line.
- Thence
- S.89°58'E., on true line, bet. secs. 6 and 7.
- Over gently rolling land; through scattering timber and dense undergrowth.
- 38.61 Set a lava stone, 20 x 12 x 12 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and
- dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.
- 78.61 The cor. of secs. 5,6,7 and 8.
- Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.

- N.0°16'E., on random line, bet. secs. 5 and 6.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.70 Intersect the N. bdy. of the Tp. at a point 7 lks. E. of the cor. of secs. 5,6,31 and 32, established under this Group, described in notes of that line.
- Thence
- S.0°13'W., on true line, bet. secs. 5 and 6.
- Over gently rolling land; through scattering timber and dense undergrowth.
- 39.70 Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and
- dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.
- 79.70 The cor. of secs. 5,6,7 and 8.
- Land: gently rolling.
Soil: sandy and gravelly loam, 1st and 2nd rates.
Timber: scattering ironwood, mesquite and palo verde.
Undergrowth: greasewood, catclaw and cactus.

GENERAL DESCRIPTION

Township 8 south, range 6 west, is situated about 16 miles south-westerly from the town of Gila Bend, Ariz., from which a graded highway runs southerly through the east part of the township. The highway continues south-westerly to the town of Ajo, about 35 miles distant. There are no other roads except a few old wagon trails, which are dim and little-used.

Surface of the township is flat and gently rolling with the exception of a few lava hills in the NE. and SE. corners.

SUBDIVISIONS OF T.8 S., R.6 W.

Chains

Drainage of the township is north-westerly. There are many small washes coming into or heading in the east portion of the township which, uniting, form larger washes. The washes become wider and shallower and are finally lost. There are no washes of note crossing the N. or W. boundaries of the township.

Soil in the east portion is a gravelly loam, that in the west a silty loam, nearly all of good depth and quality and suitable for agriculture with irrigation. There is some evidence of a nearly frost-free thermal zone adapted to semi-tropical crops.

There are the usual varieties of desert growth, considerable of the larger varieties along the washes with greasewood and cacti predominating elsewhere. The presence of ironwood, saguaro and ocotillo is notable.

A railroad, telegraph line, telephone line and highway cross the township from sec. 1 to sec. 35. There are no other improvements.

There is no water and no evidence of mineral. There are no residents.

BOOK 468

4-679 b

~~XXXXXXXXXX~~ DIAGRAM.

Township 8 South, Range 6 West.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

6-1817

- Surveyed by R. E. McMahan, Temporary Transitman.
- - - - - Surveyed by Frank C. Mulford, Temporary Transitman.
- Surveyed by Robt. H. Williams, Temporary Transitman.
- - - - - Surveyed by Ben D. Proctor, Temporary Transitman.
- Surveyed by K. K. Bowsher, Temporary Transitman.

185
33A

BOOK 4055

4-680
(August, 1926)

FIELD ASSISTANTS.
to

Ben D. Procter, Temporary Transitman

NAMES.	CAPACITY.
Haskell Welch	1st Chairman
D.B. Carver	2nd Chairman
Thomas L. Bond	Flagman
William Norris	Axman
J.P. Edgar	Axman
Samuel Bunger	Cornerman
Harry Yeager	Cornerman

34

186

BOOK 4055

CERTIFICATE OF UNITED STATES SURVEYOR

I, Ben D. Procter Temporary Transitman, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of

Township 8 South, Range 6 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Ben D. Procter
Temporary Transitman.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

, 19

The foregoing field notes of the survey of

executed by under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

BOOK 4055

4-680
(August, 1926)

FIELD ASSISTANTS.
to

Frank C. Mulford, Temporary Transitman

NAMES.	CAPACITY.
J.H.McVey	1st Chainman
Roy A. Drake	2nd Chainman
G.B.Ruiz	Flagman
J.C.Bigger	Flagman
George W. Bellas	Cornerman
A.C.Bucher	Cornerman
E.M.Heathington	Axman
Ed. Storey	Axman

36

CERTIFICATE OF UNITED STATES SURVEYOR

I, Frank C. Mulford Temporary Transitman, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of Township 8 South, Range 6 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Frank C. Mulford Temporary Transitman.

APPROVAL

Office of U. S. Supervisor of Surveys,

19

The foregoing field notes of the survey of

executed by

under his special instructions dated, 10, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in

, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

189
37

4-680
(August, 1926)

FIELD ASSISTANTS.
to

Robt. H. Williams, Temporary Transitman

NAMES.	CAPACITY.
G.C.Capes	1st Chainman
Odis Kent	2nd Chainman
Harrion Yoakum	Flagman
A.L.Hart	Cornerman
LeRoy De Brown	Cornerman
R.P.Childers	Axman
Albert Scott	Axman

38 190
BOOK 4055

CERTIFICATE OF UNITED STATES SURVEYOR

I, Robt. H. Williams *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of
Township 8 South, Range 6 West
of the Gila and Salt
River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Robt. H. Williams
Temporary Transitman.

~~APPROVAL~~

~~OFFICE OF U. S. SUPERVISOR OF SURVEYS,~~

~~19~~

~~The foregoing field notes of the survey of~~

~~executed by~~
~~under his special instructions dated~~ 19 ~~having been~~
~~critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys~~
~~they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~
~~has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~

40 192
BOOK 4055

CERTIFICATE OF UNITED STATES SURVEYOR

I, R. E. McMahan *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1923, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of
Township 8 South, Range 6 West
of the Gila and Salt
River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

R. E. McMahan
Temporary Transitman.

~~APPROVAL.~~

~~OFFICE OF U. S. SUPERVISOR OF SURVEYS,~~

~~19~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under his special instructions dated~~ 10 ~~having been~~
~~critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys~~
~~they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~

~~, has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~

194
42

BOOK 4055

CERTIFICATE OF UNITED STATES SURVEYOR

I, K.K. Bowsher *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of Township 8 South, Range 6 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

K. K. Bowsher
Temporary Transitman.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,
Denver, Colorado, May 16, 1935

The foregoing field notes of the survey of the SUBDIVISION LINES of Township 8 South, Range 6 West of the Gila and Salt River Base and Meridian, in the State of Arizona executed by Ben D. Procter, Frank C. Mulford, Robt. H. Williams and R.E. McMahan, and K.K. Bowsher, Temporary Transitmen under special instructions dated December 12, 1933- Group 199, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Wm. H. Johnson
U. S. Supervisor of Surveys.

~~I certify that the foregoing transcript of the field notes of the above-described surveys in~~
~~has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~