

# FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION LINES of

Township 9 South, Range 6 West

Of the Gila and Salt River Base & Meridian,

In the State of Arizona

### EXECUTED BY:

Ben D. Procter, K.K. Bowers, Robert H. Williams and

Dexter S. King, Temporary Transmitters

In the capacity of U. S. Surveyors, under Special Instructions dated Dec. 12, 1933, issued by the District Cadastral Engineer to govern surveys included in Group No. 199 Arizona, which were approved by the Commissioner of the General Land Office, Feb. 17, 1934, and Assignment Instructions dated December 15, 1933.

Survey commenced January 8, 1934.

Survey completed January 17, 1934.

4058

4058

# INDEX DIAGRAM.

Township ..... , Range .....

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

INDEX-DIAGRAM.

BOOK 4058

	6 35	5 26	4 21	3 15	2 8	1				
	34	34	26	20	14	7				
	7 33	8 25	9 20	10 13	11 6	12				
	33	33 32	25 19	19	13	6				
	18 32	17 24	16 19	15 12	14 5	13				
	31 32	31	T.9S. 18 24	R.6W. 18	12 11	5 4				
	19 30	20 23	21 18	22 11	23 4	24				
	30	29	23 17	17	10	3				
	29	29 22	28 16	27 10	26 3	25				
	30	28 27	22	16 9	9 2	2				
	28	28 27	22	16	9	2				
	31 27	32 21	33 15	34 8	35 1	36				

2nd Standard Parallel South

————— Surveyed under this group.

----- Resurveyed under this group.

## Chains

The subdivisional survey of T. 9 S., R. 6 W., was executed with Young & Sons transits Nos. 8477, 8592, 8584 and 8493, by Ben D. Procter, K.K. Bowsher, Robt. H. Williams and Dexter S. King, Temporary Transitmen. The instruments are constructed in accordance with the standard specifications of the General Land Office, with full vertical circles with verniers reading to single minutes, which is also the least count of the two verniers of the horizontal circles of each instrument. The instruments were in good condition, and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, were approved by the district cadastral engineer on Dec. 15, 1933.

The types of land, timber and undergrowth in T. 9 S., R. 6 W., offer few objections to projection of lines by back and foresight method; that method is selected in view of the unfamiliarity of the instrumentmen with the solar attachments with which the instruments are equipped.

Lines are initiated from the standard parallel on the S. bdy. of the Tp., which is independently resurveyed at this time as described in the notes of the first Book of this Group. The true bearings of all lines are checked by repetition of angles, double back and foresights, and occasional direct altitude observations on the sun for azimuth, and where feasible, by check of the azimuths initiated at different points on the standard parallel against each other.

The measurements are made with Lallie and Lufkin steel tapes, 5 chs. in length, graduated every link for the first 100 lks. and the balance at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements are made on the slope; the vertical angle of each interval is ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

From the standard cor. of secs. 35 and 36, on the S. bdy. of T. 9 S., R. 6 W., as relocated by independent resurvey under this Group, described in notes of resurvey of 2nd Parallel, S.,

N. 0° 01' W., bet. secs. 35 and 36.

Over gently rolling land; through scattering timber and dense undergrowth.

- 2.50 Wash, 10 lks. wide, course W.  
4.50 Wash, 10 lks. wide, course W.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S35 | S36  
1934

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

- 44.80 Wash, 30 lks. wide, course W.  
47.30 Wash, 30 lks. wide, course W.

Chains

54.10 Wash, 40 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T9S	R6W
S26	S25
S35	S36
1934	

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land: gently rolling.  
Soil: sandy and gravelly loam, 2nd rate.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo, catclaw and cactus.

-----  
East, on random line, bet. secs. 25 and 36.

40.00 Set temp. ¼ sec. cor.

79.86 Intersect the E. bdy. of the Tp. at a point 7 lks. N. of the cor. of secs. 25, 30, 31 and 36, as described, in the book of exteriors of this Group.

Thence

N. 89° 57' W., on true line, bet. secs. 25 and 36.

Over gently rolling land; through scattering timber and dense undergrowth.

31.86 Old road, bears N. and S.

39.93 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

S25
S36
1934

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

79.86 The cor. of secs. 25, 26, 35 and 36.

Land: gently rolling.  
Soil: sandy and gravelly loam, 2nd and 3rd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo, catclaw and cactus.

-----  
N. 0° 01' W., bet. secs. 25 and 26.

Over gently rolling land; through scattering timber and dense undergrowth.

17.60 Wash, 20 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

SUBDIVISIONS OF T.9 S., R.6 W.

BOOK

Chains

$$\begin{array}{c} \frac{1}{4} \\ \hline S26 | S25 \\ \hline 1934 \end{array}$$

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

50.50 Wash, 10 lks. wide, course W.

66.20 Wash, 20 lks. wide, course W.

70.00 Wash, 20 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

$$\begin{array}{c} T9S | R6W \\ S23 | S24 \\ \hline S26 | S25 \\ \hline 1934 \end{array}$$

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land: gently rolling.

Soil: sandy loam, 2nd rate; gravelly and rocky, 3rd rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

S. 89° 57' E., on random line, bet. secs. 24 and 25.

40.00 Set temp. 1/2 sec. cor.

79.82 Intersect the E. bdy. of Tp. at a point 7 lks. S. of the cor. of secs. 19, 24, 25 and 30, described in the book of, exterior to this Group.

Thence

West, on true line, bet. secs. 24 and 25.

Over gently rolling land; through scattering timber and dense undergrowth.

36.02 Old road, bears N. and S.

39.91 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} S24 \\ \hline \frac{1}{4} S25 \\ \hline 1934 \end{array}$$

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

55.80 Wash, 20 lks. wide, course SW.

79.82 The cor. of secs. 23, 24, 25 and 26.

Land: gently rolling.

Soil: sandy loam, gravelly, rocky, 3rd rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

## SUBDIVISIONS OF T.9 S., R.6 W.

Chains	N.0°01'W., bet. secs. 23 and 24.
	Over gently rolling land; through scattering timber and dense undergrowth.
6.50	Wash, 30 lks. wide, course W.
12.00	Wash, 70 lks. wide, course W.
21.80	Wash, 40 lks. wide, course W.
26.00	Wash, 30 lks. wide, course W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \hline S23   S24 \\ \hline 1934 \end{array}$
	and raise a mound of
	stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
45.10	Wash, 10 lks. wide, course W.
52.80	Old road, bears E. and W.
73.30	Wash, 20 lks. wide, course W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.
	$\begin{array}{c} T9S R5W \\ \hline S14   S13 \\ \hline S23   S24 \\ \hline 1934 \end{array}$
	and raise a mound of
	stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land: gently rolling.
	Soil: <b>gravelly</b> and sandy loam, 2nd rate.
	Timber: scattering ironwood, mesquite and palo verde.
	Undergrowth: <b>greasewood</b> , catclaw, ocotillo and cactus.
	-----
	East, on random line, bet. secs. 13 and 24.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., described in the book of exteriors of this Group.
	Thence
	West, on true line, bet. secs. 13 and 24.
	Over gently rolling land; through scattering timber and dense undergrowth.
2.10	Wash, 40 lks. wide, course N.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

SUBDIVISIONS OF T.9 S., R.6 W.

Chains

S13  
S24  
1934

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

47.50 Old road, bears N. and S.

79.90 The cor. of secs. 13, 14, 23 and 24.

Land: gently rolling.  
Soil: sandy loam, stony, 2nd and 3rd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo, catclaw and cactus.

N.0°01'W., bet. secs. 13 and 14.

Over gently rolling land; through scattering timber and dense undergrowth.

6.00 Wash, 20 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S14 | S13  
1934

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

42.30 Wash, 20 lks. wide, course W.

54.00 Wash, 20 lks. wide, course W.

69.50 Wash, 20 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.

T9S R6W  
S11 | S12  
S14 | S13  
1934

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land: gently rolling.  
Soil: sandy loam, 2nd rate.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.

East, on random line, bet. secs. 12 and 13.

40.00 Set temp. 1/4 sec. cor.

79.88 Intersect the E. bdy. of the Tp. at a point 14 lks. N. of the cor. of secs. 7, 12, 13 and 18, described in the book of exteriors of this Group.



## SUBDIVISIONS OF T.9 S., R.6 W.

Chains	Thence
	N.89°54'W., on true line, bet. secs. 12 and 13. Over gently rolling land; through very scattering timber and dense undergrowth.
19.90	Wash, 30 lks. wide, course N.
36.50	Old road, bears N. and S.
39.94	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} S12 \\ \hline \frac{1}{4} S13 \\ 1934 \end{array}$
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
54.10	Wash, 120 lks. wide, course NW.
79.88	The cor. of secs. 11,12,13 and 14.  Land: gently rolling. Soil: sandy loam, 2nd rate. Timber: very scattering ironwood and palo verde. Undergrowth: greasewood, ocotillo and cactus.
-----	
	N.0°01'W., bet. secs. 11 and 12. Over gently rolling land; through very scattering timber and dense undergrowth.
22.70	Wash, 30 lks. wide, course W.
27.60	Wash, 30 lks. wide, course W.
35.00	Begin ascent of 40 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ S11   S12 \\ \hline 1934 \end{array}$
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Asc. 21 ft. over SE. slope.
53.60	Spur, slopes E.; desc. 85 ft. over N. slope.
68.60	Wash, 20 lks. wide, course W.; over gently rolling land.
73.10	Wash, 30 lks. wide, course W.
74.50	Wash, 20 lks. wide, course W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1,2,11 and 12, with brass cap mkd.

## SUBDIVISIONS OF T.9 S., R.6 W.

7  
BOOK 4018

Chains

T9S R6W	
S2	S1
S11	S12
1934	

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land: gently rolling and hilly.  
Soil: sandy loam, stony, 2nd rate.  
Timber: very scattering ironwood and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.

S.89°54'E., on random line, bet. secs. 1 and 12.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 Intersect the E. bdy. of the Tp. at a point 2 lks. N. of the cor. of secs. 1,6,7 and 12, described in the book of exteriors of this Group.

Thence

N.89°53'W., on true line, bet. secs. 1 and 12.

Desc. 336 ft. over broken, rocky SW. slope; through scattering undergrowth.

39.00 Foot of slope; over gently rolling land; through dense undergrowth.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S1
$\frac{1}{4}$ S12
1934

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

41.25 Wash, 30 lks. wide, course SW.

69.95 Old road, bears N. and S.

79.96 The cor. of secs. 1,2,11 and 12.

Land: gently rolling and mountainous.  
Soil: sandy loam, rocky in places, 2nd and 3rd rates.  
No timber. Undergrowth: greasewood, ocotillo and cactus.

N.0°01'W., on random line, bet. secs. 1 and 2.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.82 Intersect the N. bdy. of the Tp. at a point 25 lks. E. of the cor. of secs. 1,2,35 and 36, described in the book of exteriors of this Group.

Thence

## SUBDIVISIONS OF T.9 S., R.6 W.

Chains	
	S.0°12'E., on true line, bet. secs. 1 and 2.
	Over flat; through scattering timber and dense undergrowth.
8.00	Wash, 10 lks. wide, course W.
15.60	Begin ascent of 116 ft. over NE. slope.
28.80	Top of hill, bears E. and W.; desc. 72 ft. over SE. slope.
34.80	Foot of slope; over gently rolling land.
39.82	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\uparrow$ S2   S1 1934
	and raise a mound of
	stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
48.10	Old road, bears NW. and SE.
50.40	Wash, 15 lks. wide, course W.
79.82	The cor. of secs. 1, 2, 11 and 12.
	Land: gently rolling and hilly.
	Soil: sandy loam, stony, 2nd and 3rd rates.
	Timber: very scattering ironwood and palo verde.
	Undergrowth: greasewood, catclaw, ocotillo and cactus.
-----	
	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., described in the notes of the resurvey of the Second Standard Parallel South of this Group.
	N.0°01'W., bet. secs. 34 and 35.
	Over gently rolling land; through scattering timber and dense undergrowth.
21.04	Wash, 15 lks. wide, course W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\uparrow$ S34   S35 1934
	and dig pits, 18 x 18
	x 12 ins., N. and S. of post, 3 ft. dist.
41.00	Wash, 12 lks. wide, course W.
56.30	Wash, 15 lks. wide, course W.
64.70	Wash, 30 lks. wide, course NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

## SUBDIVISIONS OF T.9 S., R.6 W.

1934

Chains

T9S	R6W
S27	S26
S34	S35
1934	

and dig pits, 18 x 18  
x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.

East, on random line, bet. secs. 26 and 35.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 Intersect the cor. of secs. 25, 26, 35 and 36.

Thence

West, on true line, bet. secs. 26 and 35.

Over flat, drains W.; through scattering timber and dense undergrowth.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S26
$\frac{1}{4}$ S35
1934

and raise a mound of  
stone, 2-ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

40.10 Enter wash, 25 lks. wide, from NE., course W.

55.00 Leave same, course NW.

65.00 Wash, 30 lks. wide, course N.

Tucson, Cornelia and Gila Bend

66.05 Railroad, bears N.  $2\frac{1}{2}^{\circ}$  W. to Gila Bend and S.  $2\frac{1}{2}^{\circ}$  E. to Ajo.

67.30 Telegraph line, parallels railroad.

69.10 Highway, bears N. to Gila Bend and S. to Ajo.

75.10 Wash, 10 lks. wide, course NW.

80.02 The cor. of secs. 26, 27, 34 and 35.

Land: flat.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood and cactus.

N.  $0^{\circ}01'$  W., bet. secs. 26 and 27.

Over gently rolling land; through scattering timber and dense undergrowth.

3.20 Wash, 30 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

$$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ \text{S27} | \text{S26} \\ \downarrow \\ 1934 \end{array}$$

and dig pits, 18 x 18  
x 12 ins., N. and S. of post, 3 ft. dist.

47.40 Wash, 25 lks. wide, course W.

67.85 Wash, 20 lks. wide, course N.60°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

$$\begin{array}{c} \text{T9S R6W} \\ \text{S22} | \text{S23} \\ \hline \text{S27} | \text{S26} \\ \hline 1934 \end{array}$$

and raise a mound  
of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, ocotillo and cactus.

East, on random line, bet. secs. 23 and 26.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 A point 12 lks. S. of the cor. of secs. 23, 24, 25 and 26.

Thence

S.89°55'W., on true line, bet. secs. 23 and 26.

Over gently rolling land; through scattering timber and dense undergrowth.

17.30 Wash, 70 lks. wide, course NW,

23.95 Wash, 10 lks. wide, course N.25°W.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{S23} \\ \hline \frac{1}{4} \text{S26} \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18  
x 12 ins., E. and W. of post, 3 ft. dist.  
Tucson, Cornelia and Gila Bend

69.55 Railroad, bears N.2½°W. to Gila Bend and S.2½°E. to Ajo.

70.80 Telegraph line, parallels railroad.

72.60 Highway, bears N. to Gila Bend and S. to Ajo.

79.98 The cor. of secs. 22, 23, 26 and 27.

Land: gently rolling.

Soil: gravelly and sandy loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

N.0°01'W., bet. secs. 22 and 23.

Over gently rolling land; through scattering timber and dense undergrowth.

- 11.00 Road, bears NW. and SE.  
 15.10 Wash, 30 lks. wide, course W.  
 21.40 Wash, 30 lks. wide, course N.75°W.  
 24.00 Wash, 30 lks. wide, course NW.  
 30.50 (9.50 chs. S.0°01'E. of true point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to  $\frac{1}{4}$  sec. cor., with brass cap mkd.

W | C  
 S22 | S23  
 1934

and dig pits, 18 x 18  
 x 12 ins., N. and S. of post, 3 ft. dist.

- 30.90 Highway, bears N. to Gila Bend and SE. to Ajo.  
 40.00 True point for  $\frac{1}{4}$  sec. cor. falls in highway; set a washed boulder, 6 x 6 x 4 ins., mkd. X, 12 ins. in the ground at true point.  
 58.80 Highway, bears N.20°E. to Gila Bend and S. to Ajo; wash, 30 lks. wide, course W.  
 59.70 Road, bears NW. and SE.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

T9S R6W  
 S15 | S14  
 S22 | S23  
 1934

and dig pits, 18 x 18  
 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.  
 Soil: sandy and gravelly loam, 1st and 2nd rates.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, ocotillo and cactus.

N.89°55'E., on random line, bet. secs. 14 and 23.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.90 A point 5 lks. N. of the cor. of secs. 13, 14, 23 and 24.  
 Thence  
 S.89°57'W., on true line, bet. secs. 14 and 23.  
 Over gently rolling land; through scattering timber and dense undergrowth.  
 17.15 Wash, 60 lks. wide, course NW.  
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## SUBDIVISIONS OF T.9 S., R.6 W.

Chains

$$\frac{S14}{\frac{1}{4}S23}$$

1934

and raise a mound of  
stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

- 67.80 Old road, bears N. and S.  
Tucson, Cornelia and Gila Bend  
72.90 Railroad, bears N.  $2\frac{1}{2}^{\circ}$  W. to Gila Bend and S.  $2\frac{1}{2}^{\circ}$  E. to Ajo.  
74.40 Telegraph line, parallels railroad.  
75.60 Highway, bears N. to Gila Bend and S. to Ajo.  
79.90 The cor. of secs. 14, 15, 22 and 23.

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.

N.  $0^{\circ}01'$  W., bet. secs. 14 and 15.

Over gently rolling land; through scattering timber and  
dense undergrowth.

- 18.65 Wash, 15 lks. wide, course W.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{\frac{1}{4}}{S15 \quad S14}$$

1934

and dig pits, 18 x  
18 x 12 ins., N. and S. of post, 3 ft. dist.

- 78.60 Wash, 100 lks. wide, course NW.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
ground, for cor. of secs. 10, 11, 14 and 15, with brass cap  
mkd.

$$\frac{T9S \quad R6W}{S10 \quad S11}$$

$$\frac{S15 \quad S14}{1934}$$

and raise a mound of  
stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land: gently rolling.  
Soil: sandy and gravelly, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.

N.  $89^{\circ}57'$  E., on random line, bet. secs. 11 and 14.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
79.86 A point 5 lks. S. of the cor. of secs. 11, 12, 13 and 14.  
Thence

## SUBDIVISIONS OF T.9 S., R.6 W.

4058

## Chains

- S.89°55'W., on true line, bet. secs. 11 and 14.  
Over gently rolling land; through scattering timber and dense undergrowth.
- 29.35 Wash, 30 lks. wide, course N. 80°W.
- 35.85 Wash, 30 lks. wide, course N.75°W.
- 39.93 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$  S11  
 $\frac{1}{4}$  S14  
 1934
- and raise a mound of  
stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.
- 49.10 Old road, bears N.15°E. and S.15°W.
- 72.10 Wash, 10 lks. wide, course NW.
- 75.40 Railroad, bears N.2 $\frac{1}{2}$ °W. to Gila Bend and S.2 $\frac{1}{2}$ °E. to Ajo.
- 76.90 Telegraph line, parallels railroad.
- 78.75 Highway, bears N. to Gila Bend and S. to Ajo.
- 79.86 The cor. of secs. 10,11,14 and 15.
- Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rate.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N.0°01'W., bet. secs. 10 and 11.  
Over gently rolling land; through scattering timber and dense undergrowth.
- 28.00 Highway, bears S.5°E. to Ajo and Northerly to Gila Bend.
- 40.00 True point for  $\frac{1}{4}$  sec. cor. falls in highway; set a washed boulder, 6 x 4 x 4 ins., mkd. X, 12 ins. below surface, at true point.
- 40.90 Highway, bears N.10°E. to Gila Bend and S.3°E. to Ajo.
- 42.22 (2.22 chs. N.0°01'W. of true point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$   
 S10 | S11  
 W | C  
 1934
- and raise a mound of  
stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- 44.50 Wash, 60 lks. wide, course W.
- 69.25 Telephone line, bears N.10°E. and S.10°W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 2,3,10 and 11, with brass cap mkd.



## SUBDIVISIONS OF T.9 S., R.6 W.

Chains

T9S	R6W
S3	S2
S10	S11
1934	

and raise a mound of  
stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, ocotillo and cactus.

-----  
N.89°55'E., on random line, bet. secs. 2 and 11.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.88 A point 5 lks. N. of the cor. of secs. 1,2,11 and 12.

Thence

✓ S.89°57'W., on true line, bet. secs. 2 and 11.

Over gently rolling land; through scattering timber and dense undergrowth.

10.10 Wash, 30 lks. wide, course N.80°W.

39.94 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S2	
$\frac{1}{4}$ S11	
1934	

and dig pits, 18 x 18  
x 12 ins., E. and W. of post, 3 ft. dist.

41.00 Old road, bears N. and S.

43.70 Wash, 12 lks. wide, course N.70°W.

60.40 Wash, 200 lks. wide, course NW.

Tucson, Cornelia and Gila Bend

72.05 Railroad, curving, bears N. to Gila Bend and S. to Ajo.

73.50 Telegraph line, parallels railroad.

74.50 Highway, bears N. to Gila Bend and S. to Ajo.

77.90 Telephone line, bears N.10°E. and S.10°W.

79.88 The cor. of secs. 2,3,10 and 11.

Land: gently rolling.

Soil: sandy and gravelly loam, stony, 2nd rate.

Timber: very scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, ocotillo and cactus.

-----  
N.0°12'W., on random line, bet. secs. 2 and 3.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.73 Intersect the N. bdy. of the Tp. at a point 7 lks. E. of the cor. of secs. 2,3,34 and 35, described in the book

## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

of exteriors of this Group.

Thence

S.0°15'E., on true line, bet. secs. 2 and 3.

Over gently rolling land; through scattering timber and dense undergrowth.

23.20 Wash, 100 lks. wide, course NW.

28.20 Wash, 10 lks. wide, course NW.

39.73 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S3 | S2  
 1934

and dig pits, 18 x 18  
x 12 ins., N. and S. of post, 3 ft. dist.

54.57 Wash, 10 lks. wide, course N.30°W.

74.50 Wash, 10 lks. wide, course N.75°W.

79.73 The cor. of secs. 2, 3, 10 and 11.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, ocotillo and cactus.

From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., described in notes of resurvey of Second Standard Parallel South, under this Group.

N.0°02'W., bet. secs. 33 and 34.

Over flat; through scattering timber and dense undergrowth.

30.00 Old road, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S33 | S34  
 1934

and dig pits, 18 x  
18 x 12 ins., N. and S. of post, 3 ft. dist.

43.00 Wash, 20 lks. wide, course N.80°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

T9S R6W  
 S28 | S27  
 S33 | S34  
 1934

and dig pits, 18 x  
18 x 12 ins., one in each sec., 3 ft. dist.

## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

Land: flat.  
 Soil: sandy and gravelly loam, 2nd rate.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, ocotillo and cactus.

-----  
 East, on random line, bet. secs. 27 and 34.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.94 A point 5 lks. N. of the cor. of secs. 26, 27, 34 and 35.

Thence

N.89°58'W., on true line, bet. secs. 27 and 34.

Over gently rolling land; through scattering timber and dense undergrowth.

11.75 Wash, 15 lks. wide, course N.60°W.

24.95 Old road, bears N. and S.

39.97 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   $\frac{S27}{S34}$   
 1934

and dig pits, 18 x 18  
 x 12 ins., E. and W. of post, 3 ft. dist.

55.95 Telephone line, bears N.20°E. and S.20°W.

79.94 The cor. of secs. 27, 28, 33 and 34.

Land: gently rolling.  
 Soil: sandy and gravelly loam, 1st and 2nd rates.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, ocotillo and cactus.

-----  
 N.0°02'W., bet. secs. 27 and 28.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S28 | S27  
 1934

and dig pits, 18 x  
 18 x 12 ins., N. and S. of post, 3 ft. dist.

53.00 Wash, 30 lks. wide, course N.70°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

SUBDIVISIONS OF T.9 S., R.6 W.

Chains

T9S	R6W
S21	S22
S28	S27

1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

S.89°58'E., on random line, bet. secs. 22 and 27.

40.00 Set temp. 1/4 sec. cor.

79.94 A point 2 lks. N. of the cor. of secs. 22,23,26 and 27.

Thence

N.89°57'W., on true line, bet. secs. 22 and 27.

Over gently rolling land; through scattering timber and dense undergrowth.

12.00 Old road, bears NE. and SW.

39.97 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S22
1/4 S27

1934

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

40.95 Telephone line, bears N.20°E. and S.20°W.

53.85 Wash, 15 lks. wide, course N.70°W.

79.94 The cor. of secs. 21,22,27 and 28.

Land: gently rolling.  
Soil: sandy and gravelly loam, 2nd rate.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°02'W., bet. secs. 21 and 22.

Over gently rolling land; through scattering timber and dense undergrowth.

13.70 Wash, 30 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S21	S22
-----	-----

1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

51.00 Wash, 30 lks. wide, course N.60°W.

72.00 Road, bears NW. and SE.

72.10 Wash, 30 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15,16,21 and 22, with brass cap mkd.

T9S	R6W
S16	S15
S21	S22
1934	

and dig pits, 18 x  
18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, ocotillo, catclaw and cactus.

-----  
S.89°57'E., on random line, bet. secs. 15 and 22.40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.90 Intersect the cor. of secs. 14,15,22 and 23.

Thence

N.89°57'W., on true line, bet. secs. 15 and 22.

Over gently rolling land; through scattering timber and dense undergrowth.

26.70 Telephone line, bears N.20°E. and S.20°W.

39.95 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S15	
$\frac{1}{4}$ S22	
1934	

and dig pits, 18 x  
18 x 12 ins., E. and W. of post, 3 ft. dist.

79.90 The cor. of secs. 15,16,21 and 22.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
N.0°02'W., bet. secs. 15 and 16.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S16	$\frac{1}{4}$ S15
1934	

## SUBDIVISIONS OF T.9 S., R.6 W.

BOOK 4033

## Chains

and dig pits, 18 x  
18 x 12 ins., N. and S. of post, 3 ft. dist.

65.00 Wash, 6 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
ground, for cor. of secs. 9,10,15 and 16, with brass cap  
mkd.

T9S	R6W
S9	S10
S16	S15

1934

and dig pits, 18 x  
18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 2nd rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

S.89°57'E., on random line, bet. secs. 10 and 15.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.90 A point 2 lks. S. of the cor. of secs. 10,11,14 and 15.

Thence

N.89°58'W., on true line, bet. secs. 10 and 15.

Over gently rolling land; through scattering timber and  
dense undergrowth.

3.90 Wash, 6 lks. wide, course NW.

12.50 Telephone line, bears N.20°E. and S.20°W.

26.80 Wash, 20 lks. wide, course NW.

39.95 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S10
S15

1934

and dig pits, 18 x  
18 x 12 ins., E. and W. of post, 3 ft. dist.

51.20 Wash, 30 lks. wide, course NW.

79.90 The cor. of secs. 9,10,15 and 16.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°02'W., bet. secs. 9 and 10.

Over gently rolling land; through scattering timber and  
dense undergrowth.

## SUBDIVISIONS OF T.9 S., R.6 W.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S9 | S10  
 1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

T9S R6W  
 S4 | S3  
 S9 | S10  
 1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

S.89°58'E., on random line, bet. secs. 3 and 10.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 A point 7 lks. N. of the cor. of secs. 2, 3, 10 and 11.

Thence

N.89°55'W., on true line, bet. secs. 3 and 10.

Over gently rolling land; through scattering timber and dense undergrowth.

38.95 Wash, 15 lks. wide, course NW.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S3  
 S10  
 1934

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

79.96 The cor. of secs. 3, 4, 9 and 10.

Land: gently rolling.

Soil: sand and gravelly loam, 2nd rate.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°15'W., on random line, bet. secs. 3 and 4.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.77 Intersect the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., described in the book of exteriors of this Group.


SUBDIVISIONS OF T.9 S., R.6 W.

Chains

Thence

S.0°15'E., on true line, bet. secs. 3 and 4, over rolling land through scattering timber and dense undergrowth.

39.77 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

41.40 Wash, 12 lks. wide, course N.60°W.

42.60 Wash, 30 lks. wide, course N.60°W.

79.77 The cor. of secs. 3,4,9 and 10.

Land: gently rolling.  
Soil: sandy and gravelly loam, stony, 2nd rate.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., described in notes of resurvey of Second Standard Parallel South, under this Group.


N.0°02'W., bet. secs. 32 and 33.

Over gently rolling land; through scattering timber and dense undergrowth.

16.00 Old road, bears NW. and SE.

22.00 Wash, 20 lks. wide, course NW.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

64.00 Wash, 20 lks. wide, course N.60°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 28,29,32 and 33, with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.



## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
East, on random line, bet. secs. 28 and 33.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the cor. of secs. 27, 28, 33 and 34.

Thence

West, on true line, bet. secs. 28 and 33.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S28  
-----  
S33

1934

and dig pits, 18 x 18  
x 12 ins., E. and W. of post, 3 ft. dist.

80.00 The cor. of secs. 28, 29, 32 and 33.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
N.0°02'W., bet. secs. 28 and 29.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S29 | S28

1934

and dig pits, 18 x  
18 x 12 ins., N. and S. of post, 3 ft. dist.

67.40 Wash, 20 lks. wide, course N.70°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

T9S R6W  
S20 | S21  
-----  
S29 | S28

1934

and dig pits, 18 x  
18 x 12 ins., one in each sec, 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

SUBDIVISIONS OF T.9 S., R.6 W.

Chains

East, on random line, bet. secs. 21 and 28.

40.00 Set temp. 1/4 sec. cor.


80.04 A point 7 lks. S. of the cor. of secs. 21,22,27 and 28.

Thence

S.89°57'W., on true line, bet. secs. 21 and 28.

Over gently rolling land; through scattering timber and dense undergrowth.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

80.04 The cor. of secs. 20,21,28 and 29.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.


Undergrowth: greasewood, ocotillo, catclaw and cactus.

N.0°02'W., bet. secs. 20 and 21.

Over gently rolling land; through scattering timber and dense undergrowth.


31.00 Wash, 200 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16,17,20 and 21, with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

SUBDIVISIONS OF T.9 S., R.6 W.

Chains

N.89°57'E., on random line, bet. secs. 16 and 21.

40.00 Set temp. 1/4 sec. cor.

80.06 A point 2 lks. S. of the cor. of secs. 15,16,21 and 22.

Thence

S.89°56'W., on true line, bet. secs. 16 and 21.

Over gently rolling land; through scattering timber and dense undergrowth.

14.05 Road, bears NW. and SE.

23.06 Wash, 20 lks. wide, course NW.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S16  
S21  
1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

46.05 Wash, 12 lks. wide, course NW.

57.05 Wash, 10 lks. wide, course N.70°W.

80.06 The cor. of secs. 16,17,20 and 21.

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°02'W., bet. secs. 16 and 17.

Over gently rolling land; through scattering timber and dense undergrowth.

11.00 Wash, 10 lks. wide, course N.70°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4  
S17 S16  
1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

68.10 Road, bears E.60°N. and S.60°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 8,9,16 and 17, with brass cap mkd.

T9S R6W  
S8 | S9  
S17 | S16  
1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

SUBDIVISIONS OF T.9 S., R.6 W.

Chains

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.89°56'E., on random line, bet. secs. 9 and 16.

40.00 Set temp. 1/4 sec. cor.

80.08 A point 2 lks. N. of the cor. of secs. 9,10,15 and 16.

Thence

S.89°57'W., on true line, bet. secs. 9 and 16.

Over gently rolling land; through scattering timber and dense undergrowth.

19.90 Wash, 20 lks. wide, course N.70°W.

25.00 Wash, 10 lks. wide, course N.70°W.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S9  
S16

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

80.08 The cor. of secs. 8,9,16 and 17.

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°02'W., bet. secs. 8 and 9.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S8 S9  
1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4,5,8 and 9, with brass cap mkd.

T9S R6W  
S5 S4  
S8 S9  
1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

## SUBDIVISIONS OF T.9 S., R.6 W.

Chains

Land: gently rolling.  
 Soil: sandy and gravelly loam, 1st and 2nd rates.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.89°57'E., on random line, bet. secs. 4 and 9.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.10 A point 5 lks. N. of the cor. of secs. 3,4,9 and 10.

Thence

S.89°59'W., on true line, bet. secs. 4 and 9.

Over gently rolling land; through scattering timber and dense undergrowth.

40.05 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S4  
 $\frac{1}{4}$ S9

1934

and dig pits, 18 x 18  
 x 12 ins., E. and W. of post, 3 ft. dist.

80.10 The cor. of secs. 4,5,8 and 9.

Land: gently rolling.  
 Soil: sandy and gravelly loam, 1st and 2nd rates.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°15'W., on random line, bet. secs. 4 and 5.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.84 Intersect the cor. of secs. 4,5,32 and 33, on the N. bdy. of the Tp., described in the book of exteriors of this Group.

Thence

S.0°15'E., on true line, bet. secs. 4 and 5.

Over gently rolling land; through scattering timber and undergrowth.

7.35 Wash, 10 lks. wide, course N.60°W.

39.84 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S5 | S4

1934

and dig pits, 18 x 18  
 x 12 ins., N. and S. of post, 3 ft. dist.

79.84 The cor. of secs. 4,5,8 and 9.

Land: gently rolling.

SUBDIVISIONS OF T.9 S., R.6 W.


Chains

Soil: sandy and gravelly loam, 1st and 2nd rate.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.,


N.0°03'W., bet. secs. 31 and 32.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.  
Soil: sandy and gravelly loam, 1st and 2nd rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

East, on random line, bet. secs. 29 and 32.

40.00 Set temp. 1/4 sec. cor.

80.08 A point 12 lks. N. of the cor. of secs. 28, 29, 32 and 33.

Thence

N.89°55'W., on true line, bet. secs. 29 and 32.


Over gently rolling land; through scattering timber and dense undergrowth.

30.00 Old road, bears NW. and SE.

40.00 Wash, 40 lks. wide, course N.60°W.

40.04 True point for 1/4 sec. cor. falls in wash.

40.74 (70 lks. N.89°55'W. of true point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to 1/4 sec. cor., with brass cap mkd.



## SUBDIVISIONS OF T.9 S., R.6 W.

Chains

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

47.30 Wash, 20 lks. wide, course NW.

59.20 Wash, 40 lks. wide, course NW.

80.08 The cor. of secs. 29,30,31 and 32.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----

West, on random line, bet. secs. 30 and 31.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.80 Intersect the W. bdy. of the Tp. at a point 5 lks. S. of the cor. of secs. 25,30,31 and 36, described in the book of exteriors of this Group.

Thence

S.89°58'E., on true line, bet. secs. 30 and 31.

Over gently rolling land; through scattering timber and dense undergrowth.

36.10 Wash, 30 lks. wide, course N.

39.80 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4}S30 \\ \frac{1}{4}S31 \end{array}$$

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

46.20 Wash, 20 lks. wide, course NW.

79.80 The cor. of secs. 29,30,31 and 32.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----

N.0°03'W., bet. secs. 29 and 30.

Over gently rolling land; through scattering timber and dense undergrowth.

14.80 Wash, 40 lks. wide, course NW.

31.10 Wash, 30 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## SUBDIVISIONS OF T.9 S., R.6 W.

Chains

$$\begin{array}{c} \frac{1}{4} \\ \hline S30 | S29 \\ \hline 1934 \end{array}$$

and raise a mound of  
stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

47.00 Wash, 100 lks. wide, course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

$$\begin{array}{c} T9S, R6W \\ \hline S19 | S20 \\ \hline S30 | S29 \\ \hline 1934 \end{array}$$

and dig pits, 18 x  
18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
S.89°55'E., on random line, bet. secs. 20 and 29.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.10 Intersect the cor. of secs. 20, 21, 28 and 29.

Thence

N.89°55'W., on true line, bet. secs. 20 and 29.

Over gently rolling land; through scattering timber and dense undergrowth.

40.05 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} S20 \\ \hline \frac{1}{4} S29 \\ \hline 1934 \end{array}$$

and dig pits, 18 x  
18 x 12 ins., E. and W. of cor., 3 ft. dist.

80.10 The cor. of secs. 19, 20, 29 and 30.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
N.89°58'W., on random line, bet. secs. 19 and 30.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.68 Intersect the W. bdy. of the Tp. at a point 7 lks. S. of the cor. of secs. 19, 24, 25 and 30, described in the book of exteriors of this Group.



SUBDIVISIONS OF T.9 S., R.6 W.

Chains

Thence

S.89°55'E., on true line, bet. secs. 19 and 30.

Over gently rolling land; through scattering timber and dense undergrowth.

18.70 Wash, 100 lks. wide, course N.

20.10 Wash, 30 lks. wide, course N.

28.20 Wash, 30 lks. wide, course NW.

39.68 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S19  
S30

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

41.00 Wash, 10 lks. wide, course NW.

46.60 Wash, 10 lks. wide, course NW.

50.20 Wash, 70 lks. wide, course NW.

79.68 The cor. of secs. 19, 20, 29 and 30.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.0°03'W., bet. secs. 19 and 20.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4  
S19 S20

1934

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

44.40 Wash, 10 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

T9S R6W  
S18 S17  
S19 S20

1934

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

SUBDIVISIONS OF T.9 S., R.6 W.

Chains

Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

S.89°55'E., on random line, bet. secs. 17 and 20.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 A point 5 lks. S. of the cor. of secs. 16,17,20 and 21.

Thence

N.89°57'W., on true line, bet. secs. 17 and 20.

Over gently rolling land; through scattering timber and dense undergrowth.

17.40 Wash, 10 lks. wide, course NW.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S17  
 $\frac{1}{4}$ S20

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

80.02 The cor. of secs. 17,18,19 and 20.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

N.89°55'W., on random line, bet. secs. 18 and 19.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.65 Intersect the W. bdy. of the Tp. at a point 2 lks. N. of the cor. of secs. 13,18,19 and 24, described in the book of exteriors of this Group.

Thence

S.89°56'E., on true line, bet. secs. 18 and 19.

Over gently rolling land; through scattering timber and dense undergrowth.

39.55 (10 lks. N.89°56'W. of true point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S18 WC  
 $\frac{1}{4}$ S19

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

39.65 True point for  $\frac{1}{4}$  sec. cor. falls in wash, 10 lks. wide, course N.

## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

79.65 The cor. of secs. 17, 18, 19 and 20.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
N.0°03'W., bet. secs. 17 and 18.

Over gently rolling land; through scattering timber and dense undergrowth.

11.50 Wash, 10 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \hline S18 | S17 \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

46.40 Wash, 40 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

$$\begin{array}{c} T9S R6W \\ \hline S7 | S8 \\ \hline S18 | S17 \\ \hline 1934 \end{array}$$

and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
S.89°57'E., on random line, bet. secs. 8 and 17.40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.04 A point 7 lks. S. of the cor. of secs. 8, 9, 16 and 17.

Thence

West, on true line, bet. secs. 8 and 17.

Over gently rolling land; through scattering timber and dense undergrowth.

13.00 Road, bears NW. and SE.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} S8 \\ \hline S17 \\ \hline 1934 \end{array}$$

and dig pits, 18 x

## SUBDIVISIONS OF T.9 S., R.6 W.

BOOK 408

Chains	
	18 x 12 ins., E. and W. of post, 3 ft. dist.
80.04	The cor. of secs. 7,8,17 and 18.
	Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw, ocotillo and cactus.
	-----
	N.89°56'W., on random line, bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.60	Intersect W. bdy. of Tp. at a point 19 lks. N. of the cor. of secs. 7,12,13 and 18, described in the book of exteriors of this Group.
	Thence
	N.89°56'E., on true line, bet. secs. 7 and 18.
	Over gently rolling land; through scattering timber and dense undergrowth.
3.90	Wash, 10 lks. wide, course NW.
12.50	Wash, 30 lks. wide, course NW.
39.60	Set a lava stone, 20 x 12 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face,
	and dig pits, 18 x 18 x 12 ins., N. and S. of cor., 3 ft. dist.
	18 x 12 ins., E. and W. of cor., 3 ft. dist.
79.60	The cor. of secs. 7,8,17 and 18.
	Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw, ocotillo and cactus.
	-----
	N.0°03'W., bet. secs. 7 and 8.
	Over gently rolling land; through scattering timber and dense undergrowth.
40.00	Set a lava stone, 30 x 12 x 6 ins., 22 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and dig pits, 18 x 18 x 12 ins., N. and S. of cor., 3 ft. dist.
40.80	Road, bears NW. and SE.
80.00	Set a lava stone, 20 x 8 x 6 ins., 15 ins. in the ground, for cor. of secs. 5,6,7 and 8, mkd. with 5 notches on S. and 5 notches on E. edges, and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.
	Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates.

## SUBDIVISIONS OF T.9 S., R.6 W.

## Chains

Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
East, on random line, bet. secs. 5 and 8.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 A point 7 lks. N. of the cor. of secs. 4, 5, 8 and 9.

Thence

N.89°57'W., on true line, bet. secs. 5 and 8.

Over gently rolling land; through scattering timber and dense undergrowth.

40.00 Set a lava stone, 20 x 8 x 6 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and

dig pits, 18 x 18 x 12 ins., E. and W. of cor., 3 ft. dist.

80.00 The cor. of secs. 5, 6, 7 and 8.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
S.89°56'W., on random line, bet. secs. 6 and 7.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.52 Intersect the W. bdy. of the Tp. at a point 5 lks. N. of the cor. of secs. 1, 6, 7 and 12, described in the book, of exteriors of this Group.

Thence

N.89°54'E., on true line, bet. secs. 6 and 7.

Over gently rolling land; through scattering timber and dense undergrowth.

14.50 Road, bears NW. and SE.

39.52 Set a lava stone, 20 x 8 x 6 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and

dig pits, 18 x 18 x 12 ins., E. and W. of cor., 3 ft. dist.

79.52 The cor. of secs. 5, 6, 7 and 8.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

-----  
N.0°15'W., on random line, bet. secs. 5 and 6.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.92 Intersect N. bdy. of Tp. at a point 16 lks. W. of the cor.

## Chains

of secs. 5, 6, 31 and 32, described in the book of exteriors of this Group.

## Thence

S.0°08'E., on true line, bet. secs. 5 and 6.

Over gently rolling land; through scattering timber and dense undergrowth.

- 39.92 Set a lava stone, 20 x 8 x 6 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, and dig pits, 18 x 18 x 12 ins., N. and S. of cor., 3 ft. dist.
- 79.92 The cor. of secs. 5, 6, 7 and 8.

Land: gently rolling.

Soil: sandy and gravelly loam, 1st and 2nd rates.

Timber: scattering ironwood, mesquite and palo verde.

Undergrowth: greasewood, catclaw, ocotillo and cactus.

## GENERAL DESCRIPTION

T.9 S., R.6 W., lies about 20 miles southerly from the town of Gila Bend, Ariz. A highway from Gila Bend to Ajo and points south crosses the east part of the township. Branch roads reach other parts of the township.

Land is gently rolling, draining west and north-west, with the exception of the north-west corner, which is nearly level, and the north-east corner, which has a few isolated hills and the foothills of the Saucedá Mts. Elevation is about 1,400 ft. above sea-level.

Soil in the east two tiers of sections is a sandy and gravelly loam, frequently rocky, though of good depth, mostly of volcanic origin. In the remainder of the township it is of the same type, almost free of rocks, very friable and excellent for agriculture if the water for the necessary irrigation could be had.

A heavy growth of ironwood, mesquite and palo verde timber, suitable only for fuel and fence posts, is found along the washes, with a scattering of the same elsewhere. There is a heavy growth of greasewood with less amounts of catclaw and several varieties of cacti.

The Tucson, Cornelia and Gila Bend R.R., together with a paralleling telegraph line, runs southerly through the east part of the township. A station on the railroad, named Midway, located in sec. 23, consists only of a platform used in maintenance. A telephone line runs south-westerly through the east half of the township. There are no residents or other improvements.

There is no water.

There is no evidence of mineral.

4-679 b

~~INDEX~~ DIAGRAM.

Township *9 South*, Range *6 West*

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

6-1817

—————Surveyed by Ben D. Proctor, Temporary Transitman.

-----Surveyed by K. K. Bowsher, Temporary Transitman.

—————Surveyed by Robert H. Williams, Temporary Transitman.

-----Surveyed by Dexter S. King, Temporary Transitman.





38  
BOOK 4058

CERTIFICATE OF UNITED STATES SURVEYOR

I, K. K. Bowsher *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for ARIZONA bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of  
Township 9 South, Range 6 West  
of the Gila and Salt  
River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for ARIZONA and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*K. K. Bowsher*  
*Temporary Transitman.*

~~APPROVAL~~

~~OFFICE OF U. S. SUPERVISOR OF SURVEYS,~~

~~....., 19~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under his special instructions dated ....., 19....., having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~

~~....., has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~

4-680  
(August, 1926)

**FIELD ASSISTANTS.**  
to

**Robt. H. Williams, Temporary Transitman**

NAMES.	CAPACITY.
G. C. Capes	1st Chainman
Odis Kent	2nd Chainman
Harmon Yoakum	Flagman
A.L.Hart	Cornerman
LeRoy De Brown	Cornerman
R.P.Childers	Axman
Albert Scott	Axman

CERTIFICATE OF UNITED STATES SURVEYOR

I, Robt. H. Williams *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of \_\_\_\_\_ the SUBDIVISION LINES of \_\_\_\_\_ Township 9 South, Range 6 West \_\_\_\_\_ of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*Robt. H. Williams*  
*Temporary Transitman.*

~~APPROVAL~~

~~OFFICE OF U. S. SUPERVISOR OF SURVEYS,~~

~~10~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under his special instructions dated \_\_\_\_\_, 10, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~

4088

4-680  
(August, 1926)

**FIELD ASSISTANTS.**  
to

Dexter S. King, Temporary Transitman

NAMES.	CAPACITY.
C.R. Tonneman	1st Chainman
R.D. Lewis	2nd Chainman
George H. Lindberg	2nd Chainman
Lloyd Harroll	Flagman
Chas. L. Turner	Flagman
Frank P. Hebert	Cornerman
G.C. Coles	Cornerman
Earl Cline	Axman
John Horey	Axman

160  
42  
BOOK 4058

CERTIFICATE OF UNITED STATES SURVEYOR

I, Dexter S. King *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of Township 9 South, Range 6 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*Dexter S. King*  
*Temporary Transitman.*

~~APPROVAL~~

~~OFFICE OF U. S. SUPERVISOR OF SURVEYS,~~

~~, 19~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under his special instructions dated, 10, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~

~~, has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~

161  
43

5009 4058

4-680  
(August, 1926)

**FIELD ASSISTANTS.**  
to

Ben D. Procter, Temporary Transitman

NAMES.	CAPACITY.
Haskell Welch	1st Chairman
D.B.Carver	2nd Chairman
Thomas L. Bond	Flagman
William Norris	Axman
J.P.Edgar	Axman
Samuel Bunger	Cornerman
Harry Yeager	Cornerman

162  
44  
BOOK 4058

CERTIFICATE OF UNITED STATES SURVEYOR

I, Ben D. Procter *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of  
Township 9 South, Range 6 West  
of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*Ben D. Procter*  
*Temporary Transitman*

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,  
Denver, Colorado, May 16, 1935

The foregoing field notes of the survey of the SUBDIVISION LINES of  
Township 9 South, Range 6 West  
of the Gila and Salt River Base and Meridian, in the State of Arizona

executed by K.K. Bowsher Robert H. Williams Dexter S. King  
and Ben D. Procter, Temporary Transitsmen

under special instructions dated December 12, 1933 - Group 199, Arizona having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

*Wm. H. Johnson*  
U. S. Supervisor of Surveys.

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~  
~~has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~