

Book D.

BOOK 4063

# FIELD NOTES

OF THE SURVEY OF THE

Subdivisional Lines of Township 9 South, Range 4 West.

Of the Gila & Salt River Meridian,

In the State of Arizona

### EXECUTED BY

David, D. Baker, Daniel M. Wier, George W. Danehy and Herman J. Shafer,

U.S. Transitmen,

Under special instructions dated December 12., 1933, which provided for the surveys included under Group No. 198, bearing the approval of the Commissioner of the General Land Office under date of March 26, 1934. and assignment instructions dated December 15., 1933

Survey commenced January 8., 1934

Survey completed January 20., 1934

4063

4063

BOOK 4063

# INDEX DIAGRAM.

Township 9 S., Range 4 W.

6	42 5	32 4	24 3	16 2	9 1
42	41	31	23	16	8
7	41 8	30 9	22 10	15 11	7 12
40	40	30	22	14	6
18	39 17	29 16	21 15	13 14	6 18
38	37	28	20	13	5
19	37 20	27 21	19 22	12 23	4 24
36	35	27	19	11	4
30	35 29	26 28	18 27	11 26	3 25
34	33	25	17	10	2
31	33 32	24 33	17 34	9 35	1 36

The subdivisional survey of township 9 south, range 4 west was executed with Young & Sons transits Nos. 8585, and 8487, Buff and Buff transit No. 9208, and W. & L.E. Gurley transit No. 20116, property of the General Land Office, each with full vertical circles reading to single minutes. The instruments were in good condition and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, were approved by the district cadastral engineer on Dec. 15, 1933.

As the lines to be established run over desert and rolling mountainous country with sparse timber and undergrowth, the direction of the lines were determined and verified by horizontal deflection angles from meridians determined by Polaris and direct altitude observations of the sun for azimuth; described in the field notes of the 2nd standard parallel south, through Rs. 3 and 4 W., resurveyed under this group.

The bearings were deflected from meridians by repetition of angles, taking the mean of direct and reversed sights at each instrument station. The back and foresight method was selected, making proper offsets on the latitudinal lines as required, and checked against each other frequently, and on meridians determined by direct altitude observations of the sun for azimuth throughout the survey.

The measurements were made with Lallie steel tapes 5 chs. in length, graduated every link for the first 100 lks. and the balance at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by clinometers in good adjustment; the horizontal equivalents are entered in the field note record.

Beginning at the standard cor. of secs. 35 and 36 on the S. bdy. of the Tp.; described in the field notes of the 2nd standard parallel south, through R. 4 W., resurveyed under this group.

N.0°01'W., bet. secs. 35 and 36.

Over rolling desert land, through scattering timber and undergrowth.

- 5.25 Wash, 10 lks. wide, course NE.  
 15.20 Wash, 30 lks. wide, course E.  
 22.50 Wash, 10 lks. wide, course E.  
 24.80 Wash, 80 lks. wide, course E.; asc. 50 ft. over S. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 35 | S 36

1934

raise a mound  
 of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Ascend 50 ft. over S. slope.

Chains  
 43.10 Ridge, bears E. and W.; desc. 225 ft. over NW. slope.  
 61.60 Wash, 30 lks. wide, course NW.; asc. 135 ft. over SW, slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T 9 S R 4 W  
 S 26 | S 25  
 S 35 | S 36  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and mountainous.  
 Soil, gravelly, 3rd rate; and rocky, 4th rate.  
 Timber, scattering palo verde, ironwood and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

-----  
 East, on a random line bet. secs. 25 and 36.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.

79.96 Intersect E. bdy. of Tp., 19 lks. N. of the cor. of secs. 25, 30, 31 and 36; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.

Thence

N.  $89^{\circ}52'W.$ , on a true line bet. secs. 25 and 36.

Over rolling and mountainous land, through scattered timber and undergrowth.

Descend 25 ft. over SW. slope.

7.55 Wash, 10 lks. wide, course S.; asc. 155 ft. over gradual SE. slope.

35.10 Spur, slopes S.; thence along broken S. slope.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 25  
 S 36  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

50.10 Wash, 20 lks. wide, course S.

55.00 Wash, 10 lks wide, course S.; asc. 175 ft. over E. slope.

69.25 Ridge, bears N. and S.; desc. 245 ft. over W. slope.

79.96 The cor. of secs. 25, 26, 35 and 36.

-----  
 Land, rolling and mountainous.  
 Soil, gravelly, 3rd rate; and rocky, 4th rate.  
 Timber, scatterinh palo verde, ironwood, and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

Chains	N.0°01'W., bet. secs. 25 and 26.
	Over rolling and mountainous land, through scattering timber and undergrowth.
	Descend 65 ft. over NW. slope.
6.15	Wash, 40 lks. wide, course W.; asc. 140 ft. over SW. slope.
11.90	Spur, slopes W.; desc. 30 ft. over NW. slope.
14.00	Base of slope, bears E. and W.; asc. 30 ft. over SW. slope.
20.80	Spur, slopes W.; desc. 50 ft. over NW. slope.
25.00	Base of slope, bears E. and W.; asc. 65 ft. over SW. slope.
29.60	Spur, slopes W.; desc. 65 ft. over NW. slope.
35.90	Base of slope, bears E. and W.; asc. 20 ft. over SW. slope.
38.80	Spur, slopes NW.; desc. 80 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 26 \mid \text{S } 25 \\ 1934 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Descend 25 ft. over N. slope.
43.00	Wash, 20 lks. wide, course W.; asc. 60 ft. over SW. slope.
52.30	Spur, slopes W.; desc. 30 ft. over NW. slope.
56.10	Wash, 50 lks. wide, course W.; asc. 415 ft. over SW. slope.
72.20	Ridge, bears E. and W.; desc. 175 ft. over NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.
	$\begin{array}{c} \text{T } 9 \text{ S } R \text{ 4 } W \\ \text{S } 23 \mid \text{S } 24 \\ \text{S } 26 \mid \text{S } 25 \\ 1934 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling and mountainous.
	Soil, sandy, 2nd rate; and rocky, 4th rate.
	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and ocotillo.

Chains.	S.89°52'E., on a random line bet. secs: 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect E. bdy. of Tp., 26 lks. S. of the cor. of secs. 19,24,25 and 30; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	S.89°57'W., on a true line bet, secs. 24 and 25.
	Over mountainous land, through scattering timber and undergrowth.
	Ascend 195 ft. over E. slope.
7.15	Ridge, bears N. and S.; desc. 120 ft. over SW. slope.
14.90	Ravine, course SE.; asc. 155 ft. over SE. slope.
17.85	Ridge, bears NE. and SW.; desc. 145 ft. over NW. slope.
39.97	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 24</u> S 25 1934
	raise a mound
	of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	Descend 140 ft. over W. slope.
44.85	Ravine, course NW.; asc. 75 ft. over NE. slope.
52.64	Small spur, slopes N.; desc. 62 ft. over NW. slope.
57.00	Ravine, course NW.; asc. 100 ft. over NE. slope.
61.75	Small spur, slopes N.; desc. 75 ft. over NW. slope.
70.10	Ravine, course NW.; asc. 10 ft. over NE. slope.
71.55	Small spur, slopes N.; desc. 75 ft. over NW. slope.
79.94	The cor. of secs. 23,24,25 and 26.
	Land, mountainous.
	Soil, rocky; 4th rate.
	Timber, scattering palo verde; undergrowth, greasewood, sage brush, cactus and ocotillo.
-----	
	N.0°01'W., bet. secs. 23 and 24.
	Over mountainous land, through scattering timber and undergrowth,
	Descend 240 ft. over NW. slope.
18.40	Gulch, course NW.; asc. 130 ft. over SW. slope.
27.60	Spur, slopes W.; desc. 170 ft. over NW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains.	
	$\frac{1}{4}$ S 23   S 24 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue descending 180 ft. over NW. slope.
48.55	Wash, 15 lks. wide, course NW.; asc. 75 ft. over S. slope.
63.40	Spur, slopes W.; desc. 90 ft. over NW. slope.
70.15	Gulch, course NW.; asc. 45 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.
	T 9 S R 4 W S 14   S 13 S 23   S 24 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, mountainous. Soil, sandy; 2nd rate; and rocky, 4th rate. Timber, very scattering palo verde; undergrowth, greasewood, sage brush, cactus and ocotillo.
-----	
	N. 89° 57' E., on a random line bet. secs. 13 and 24.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect E. bdy. of Tp., 16 lks. N. of the cor. of secs. 13, 18, 19 and 24; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	N. 89° 56' W., on a true line bet. secs. 13 and 24.
	Over mountainous land, through scattering timber and undergrowth.
	Ascend 135 ft. over NE. slope.
9.85	High point on ridge, bears N. and S.; desc. 600 ft. over SW. slope.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 13 S 24 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
40.20	Wash, 30 lks. wide, course NW.; asc. 35 ft. over NE. slope.
43.00	Small rocky spur, slopes N.; desc. 110 ft. over NW. slope.
79.96	The cor. of secs. 13, 14, 23 and 24.

Chains	Land, mountainous. Soil, sandy, 2nd rate; and rocky, 4th rate. Timber, scattering palo verde; undergrowth, greasewood, cactus and ocotillo.
	-----
	N.0°01'W., bet. secs. 13 and 14.
	Over rolling land, through scattering timber and under- growth.
	Descend 45 ft. over N. slope.
7.50	Base, of slope, bears E. and W.; continue over rolling desert land.
29.65	Wash, 75 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor., with brass cap mkd.
	$\frac{1}{2}$ S 14   S 13 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
46.65	Wash, 70 lks. wide, course NW.
75.00	Ascend 130 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.
	T 9 S R 4 W S 11   S 12 S 14   S 13 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, sandy, 2nd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	S.89°56'E., on a random line bet. secs. 12 and 13.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect E. bdy. of Tp., 21 lks. S. of the cor. of secs. 7, 12, 13 and 18; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	S.89°55'W., on a true line bet. secs. 12 and 13.
	Over rolling desert land, through scattering timber and undergrowth.
4.15	Wash, 70 lks. wide, course NW.



Chains.	
9.85	Wash, 15 lks. wide, course NW.
17.40	Ascend 235 ft. over NE. slope.
33.50	Spur, slopes N.; desc. 60 ft. over NW. slope.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 12}{S\ 13}$ 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
40.90	Ravine, course NE.; asc. 30 ft. over NE. slope.
45.85	Spur, slopes N.; desc. 210 ft. over NW. slope.
72.50	Wash, 15 lks. wide, course NE.; asc. 145 ft. over SE. slope.
79.90	The cor. of secs, 11,12,13 and 14.
	Land, rolling. Soil, sandy, 2nd rate; and rocky, 4th rate. Timber, very scattering palo verde; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°01'W., bet. secs. 11 and 12.
	Over rolling desert land, through scattering timber and undergrowth.
	Ascend 15 ft. over S. slope.
1.40	Ridge, bears E. and W.; desc. 100 ft. over N. slope.
16.90	Ravine, course W.; asc. 40 ft. over S. slope.
20.50	Ridge, bears E. and W.; desc. 145 ft. over NW. slope.
28.45	Base of slope, bears E. and W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{3}{4}$ S 11   S 12 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
54.45	Wash, 40 lks. wide, course NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1,2,11 and 12, with brass cap mkd.

Chains.

T	9	S	R	4	W
S	2	S	1		
S	11	S	12		
1934					

from which

A mesquite, 12 ins. diam., bears N.12 $\frac{1}{2}$ °W., 83 lks. dist., mkd. T 9 S R 4 W S 2 B T.

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.

Soil, sandy, 2nd rate; and rocky, 4th rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.

N.89°55'E., on a random line bet. secs. 1 and 12.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.92 Intersect E. bdy. of Tp., 14 lks. N. of the cor. of secs. 1, 6, 7 and 12; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.

Thence

N.89°59'W., on a true line bet. secs. 1 and 12.

Over level desert land, through scattering timber and undergrowth.

16.90 Wash, 20 lks. wide, course NW.

29.30 Wash, 60 lks. wide, course NW.

34.40 Wash, 50 lks. wide, course NW.

39.96 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$	S	1
	S	12
1934		

of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor. raise a mound

50.60 Wash, 50 lks. wide, course NE.

65.00 Wash, 100 lks. wide, course NW.

79.50 Wash, 10 lks. wide, course N.

79.92 The cor. of secs. 1, 2, 11 and 12.

Land, level.

Soil, sandy; 2nd rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.

North, on a random line bet. secs. 1 and 2.

40.00 Set temp,  $\frac{1}{4}$  sec. cor.

80.18 Intersect N. bdy. of Tp., 9 lks. W. of the cor. of secs.

Chains.	1,2,35 and 36; described in the field notes of the N. bdy. of T. 9 S., R. 4 W., surveyed under this group.
	Thence
	S.0°04'W., on a true line bet. secs. 1 and 2.
	Over level desert land, through scattering timber and undergrowth.
6.70	Wash, 250 lks. wide, course NW.
30.80	Wash, 30 lks. wide, course NW.
37.60	Wash, 40 lks. wide, course NW.
40.18	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 2   S 1 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
58.40	Wash, 20 lks. wide, course W.
61.30	Wash, 10 lks. wide, course NW.
80.18	The cor. of secs. 1,2,11 and 12.
	Land, level.
	Soil, sandy; 2nd rate.
	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp.; described in the field notes of the 2nd standard parallel south, through Rs. 3 and 4 W., resurveyed under this group.
	N.0°01'W., bet. secs. 34 and 35.
	Over rolling desert land, through scattering timber and undergrowth.
	Descend 95 ft. over gradual NW. slope.
1.00	Ravine, course W.; asc. 40 ft. over SW. slope.
3.70	Small spur, slopes NW.; desc. 40 ft. over NE. slope.
13.10	Wash, 40 lks. wide, course NW.
20.00	Wash, 10 lks. wide, course W.
32.50	Wash, 20 lks. wide, course NW.; asc. 100 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains

$$\frac{1}{4}$$

$$S 34 \mid S 35$$

1934

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Continue ascending over SW. slope.

45.00 Ridge, bears NW. and E.; desc. 110 ft. over N. slope.

56.00 Wash, 20 lks. wide, course NW.

63.00 Wash, 10 lks. wide, course W.; asc. 220 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock; and in a mound of stone to top, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

$$\begin{array}{c} T 9 S R 4 W \\ S 27 \mid S 26 \\ \hline S 34 \mid S 35 \\ 1934 \end{array}$$

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.

Soil, sandy, 3rd rate; and rocky, 4th rate.

Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.

East, on a random line bet. secs. 26 and 35.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.84 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 25, 26, 35 and 36.

Thence

S.  $89^{\circ}58'$  W., on a true line bet. secs. 26 and 35.

Over rolling desert land, through scattering timber and undergrowth.

Descend 130 ft. over W. slope.

13.85 Wash, 10 lks. wide, course NW.

29.90 Wash, 10 lks. wide, course NW.

39.92 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 26}{S 35}$$

1934

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

51.35 Wash, 10 lks. wide, course NE.; asc. 285 ft. over broken SE. slope.

79.84 The cor. of secs. 26, 27, 34 and 35.

Chains.	<p>Land, rolling. Soil, sandy, 2nd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/> <p>N.0°01'W., bet. secs. 26 and 27.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p> <p>Ascend 75 ft. over S. slope.</p> <p>5.99 Top of peak on ridge, bears NW. and SE.; desc. 380 ft. over NE. slope.</p> <p>33.50 Wash, 10 lks. wide, course NW.</p> <p>39.75 Wash, 10 lks. wide, course NW.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 27   S 26 1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Ascend 155 ft. over SW. slope.</p> <p>51.00 Ravine, 200 lks. wide, course W.; continue ascending over SW. slope.</p> <p>68.00 Spur, slopes NW.; desc. 155 ft. over N. slope.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 4 W S 22   S 23 + S 27   S 26 1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, mountainous. Soil, rocky and gravelly; 4th rate. Timber, scattering palo verde, and mesquite; undergrowth, scattering greasewood, cactus and sage brush.</p> <hr/> <p>N.89°58'E., on a random line bet. secs. 23 and 26.</p> <p>40.00 Set temp. <math>\frac{1}{4}</math> sec. cor.</p> <p>79.94 Intersect N. and S. line, at the cor. of secs. 23, 24, 25 and 26.</p> <p>Thence</p> <p>S.89°58'W., on a true line bet. secs. 23 and 26.</p> <p>Over mountainous land, through scattering timber and</p>
---------	---

Chains undergrowth.  
 Descend 335 ft. over NW. slope.  
 22.95 Wash, 15 lks. wide, course NW.  
 29.95 Wash, 30 lks. wide, course NW.  
 39.97 Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 23  
 S 26  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

49.34 Wash, 30 lks. wide, course NW.  
 54.95 Ravine, 20 lks. wide, course NE.; asc. 97 ft. over E. slope.  
 62.55 Spur, slopes NW.; desc. 115 ft. over NW. slope.  
 79.94 The cor. of secs. 22, 23, 26 and 27.

Land, mountainous and rolling.  
 Soil, gravelly, 3rd rate; and rocky, 4th rate.  
 Timber, scattering palo verde, mesquite and ironwood;  
 undergrowth, greasewood, sage brush and cactus.

N.0°01'W., bet. secs. 22 and 23.

Over rolling land, through scattering timber and undergrowth.

2.50 Wash, 6 lks. wide, course NW.; asc. 70 ft. over S. slope.  
 13.75 Top of W. slope of hill; desc. 55 ft. over NE. slope.  
 30.00 Base of slope, bears NW. and SE.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 22 | S 23  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

58.50 Wash, 30 lks. wide, course N.; asc. 55 ft. over S. slope.  
 61.20 Rocky round hill; desc. 35 ft. over NW. slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.


T 9 S R 4 W  
 S 15 | S 14  
 S 22 | S 23  
 1934

Chains.	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high; W. of cor.</p> <p>Land, rolling. Soil, gravelly, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr style="border-top: 1px dashed black;"/> <p>N.89°58'E., on a random line bet. secs. 14 and 23.</p> <p>40.00 Set temp. <math>\frac{1}{4}</math> sec. cor.</p> <p>79.60 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 13, 14, 23 and 24.</p> <p>Thence</p> <p>S.89°59'W., on a true line bet. secs. 14 and 23.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p> <p>Descend 20 ft. over NW. slope.</p> <p>14.60 Wash, 50 lks. wide, course NW.</p> <p>20.60 Base of hill, bears NW. and SE.; asc. 120 ft. over broken NE. slope.</p> <p>39.80 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\frac{1}{4} \begin{array}{r} \text{S 14} \\ \text{S 23} \\ 1934 \end{array}</math> </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, N. of cor.</p> <p>The <math>\frac{1}{4}</math> sec. cor. is located on spur, slopes N.</p> <p>Descend 145 ft. over broken NW. slope.</p> <p>58.60 Ravine, 20 lks. wide, course NW.</p> <p>63.60 Ravine, 20 lks. wide, course NW.</p> <p>69.60 Base, of slope, bears NW. and SE.; continue over rolling land.</p> <p>79.60 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, mountainous and rolling. Soil, gravelly, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr style="border-top: 1px dashed black;"/> <p>N.0°01'W., bet. secs. 14 and 15.</p> <p>Over level desert land, through scattering timber and undergrowth.</p> <p>25.00 Wash, 40 lks. wide, course NE.</p> <p>29.00 Wash, 20 lks. wide, course NE.</p>
---------	--

Chains.

39.50 Wash, 10 lks. wide, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.




raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

54.00 Wash, 20 lks. wide, course NE.; enter rolling land.; asc. 115 ft. over S. slope.

70.00 Top of knoll; desc. 90 ft. over N. slope.

75.00 Ravine, 20 lks. wide, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, level and rolling.  
Soil, gravelly, 3 rd rate; and rocky, 4th rate.  
Timber, scattering palo verde, ironwood and mesquite;  
undergrowth, greasewood, sage brush and cactus.

N.89°59'E., on a random line bet. secs. 11 and 14.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.72 Intersect N. and S. line, 7 lks. N. of the cor. of secs. 11, 12, 13 and 14.

Thence

N.89°58'W., on a true line bet. secs. 11 and 14.


Over rolling desert hills, through scattering timber and undergrowth.

Descend 160 ft. over gradual W. slope.

35.70 Wash, 20 lks. wide, course N.

38.70 Wash, 30 lks. wide, course NW.

39.86 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high. N. of cor.



<p>Chains. 40.20 49.70 58.70 75.70 79.72</p>	<p>Wash, 10 lks. wide, course NW.; asc. 45 ft. over E. slope.</p> <p>Top of round hill; desc. 30 ft. over N. slope.</p> <p>Wash, 10 lks. wide, course N.; continue along rolling N. slope.</p> <p>Ravine, 20 lks. wide, course NE.; asc. 25 ft. over E. slope.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling hills. Soil, gravelly, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/> <p>N.0°01'W., bet. secs. 10 and 11.</p> <p>Over rolling desert land, through scattering timber and undergrowth.</p> <p>Descend 20 ft. along E. slope.</p> <p>7.00 Top of ascent; desc. 35 ft. over NE. slope.</p> <p>11.00 Base of slope, bears NW. and SE.; asc. 15 ft. over S. slope.</p> <p>18.50 Top of knoll; desc. 100 ft. over N. slope.</p> <p>39.70 Base of knoll, bears E. and W.; continue over level desert land.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>              S 10   S 11              1934         </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <p>56.00 Wash, 8 lks. wide, course NW.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.</p> <div style="text-align: center;">             T 9 S R 4 W              S 3   S 2              S 10   S 11              1934         </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, rolling and level. Soil, gravelly 3rd rate; and rocky, 4th rate. Timber, scattering ironwood, palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/>
--	--

Chains.	S, 89°58'E., on a random line bet. secs. 2 and 11.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.74	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 1, 2, 11 and 12.
	Thence
	N. 89°56'W., on a true line bet. secs. 2 and 11.
	Over level desert land, through scattering timber and undergrowth.
39.87	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} S 2 \\ S 11 \\ 1934 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
44.75	Wash, 100 lks. wide, course NW.
75.75	Wash, 30 lks. wide, course NW.
79.74	The cor. of secs. 2, 3, 10 and 11.
	Land, level.
	Soil, sandy, 2nd rate; and gravelly, 3rd rate.
	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N. 0°04'E., on a random line bet. secs. 2 and 3.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.31	Intersect N. bdy. of Tp., 33 lks. E. of the cor. of secs. 2, 3, 34 and 35; described in the field notes of the N. bdy. of T. 9 S., R. 4 W., surveyed under this group.
	Thence
	S. 0°10'E., on a true line bet. secs. 2 and 3.
	Over level desert land, through scattering timber and undergrowth.
21.30	Wash, 8 lks. wide, course NW.
40.31	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} S 3   S 2 \\ 1934 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
66.30	Wash, 40 lks. wide, course NW.
70.30	Wash, 10 lks. wide, course NW.
80.31	The cor. of secs. 2, 3, 10 and 11.

Chains. Land, level.  
 Soil, sandy, 2nd rate; and rocky, 4th rate.  
 Timber, scattering palo verde, ironwood and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

---

From the standard cor. of secs. 33 and 34 on the S. bdy.  
 of the Tp.; described in the field notes of the 2nd  
 parallel south, through Rs. 3 and 4 W., resurveyed under  
 this group.

N.0°02'W., bet. secs. 33 and 34.

Over mountainous land, through scattering timber and  
 undergrowth.

Descend 620 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the  
 ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$   
 sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 33 | S 34  
 1934

raise a mound  
 of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

45.00 Wash, 20 lks. wide, course NW.; continue over rolling  
 land.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
 the ground, for cor. of secs. 27, 28, 33 and 34, with brass  
 cap mkd.

T 9 S R 4 W  
 S 28 | S 27  
 S 33 | S 34  
 1934

raise a mound  
 of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, mountainous and rolling.  
 Soil, sandy, 2nd rate; and rocky 4th rate.  
 Timber, scattering palo verde; undergrowth, greasewood,  
 cactus, catclaw, sage brush and ocotillo.

---

East, on a random line bet. secs. 27 and 34.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect N. and S. line, 5 lks. S. of the cor. of secs.  
 26, 27, 34 and 35.

Thence

S.89°58'W., on a true line bet. secs. 27 and 34.

Over mountainous land, through scattering timber and  
 undergrowth.

Descend 260 ft. over NW. slope.

19.00 Wash, 10 lks. wide, course NE.

Chains	
25.00	Wash, 20 lks. wide, course NW.; continue over rolling land.
29.00	Wash, 10 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 27 S 34 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Ascend 50 ft. over NE. slope.
47.50	Ridge, bears NW. and SE.; desc. 80 ft. over SW. slope.
59.50	Wash, 10 lks. wide, course NW.; asc. 20 ft. over E. slope.
63.50	Ridge, bears NW. and SE.; desc. 40 ft. over SW. slope.
80.00	The cor. of secs. 27, 28, 33 and 34.
	Land, mountainous and rolling. Soil, sandy, 2nd rate; and rocky, 4th rate. Timber, scattering palo verde; undergrowth, greasewood, catclaw, cactus and ocotillo.
-----	
	N.0°02'W., bet. secs. 27 and 28.
	Over rolling desert land, through scattering timber and undergrowth.
7.00	Wash, 30 lks. wide, course NW.; asc. 115 ft. over SW. slope.
28.00	Spur, slopes NW.; desc. 145 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 28   S 27 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue over level land.
50.50	Wash, 10 lks. wide, course NW.; asc. 25 ft. over SW. slope.
65.00	Low flat hill, bears NW. and SE.; desc. 45 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

Chains.

T 9 S R 4 W  
 S 21 | S 22  
 S 28 | S 27  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and level.  
 Soil, sandy, 2nd rate; and rocky, 4th rate.  
 Timber, scattering palo verde, ironwood and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

N.89°58'E., on a random line bet. secs. 22 and 27.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.

79.92 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 22, 23, 26 and 27.

Thence

N.89°56'W., on a true line bet. secs. 22 and 27.

Over rolling desert hicks, through scattering timber and undergrowth.

Ascend 90 ft. over NE. slope.

6.92 Spur, slopes NW.; desc. 100 ft. over NW. slope.

29.92 Wash, 20 lks. wide, course NE.; asc. 35 ft. over NE. slope.

39.96 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 22  
 S 27  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

49.92 Spur, slopes NW.; desc. 100 ft. over SW. slope.

55.92 Wash, 10 lks. wide, course NW.; asc. 45 ft. over NE. slope.

62.60 Spur, slopes NW.; desc. 30 ft. over SW. slope.

64.92 Ravine, course NW.; asc. 45 ft. over NE. slope.

69.90 Spur, slopes NW.; desc. 50 ft. over W. slope.


79.92 The cor. of secs. 21, 22, 27 and 28.

Land, rolling hills.  
 Soil, gravelly, 3rd rate; and rocky, 4th rate.  
 Timber, scattering palo verde; undergrowth, greasewood,  
 cactus and sage brush.

N.0°02'W., bet. secs. 21 and 22.


Over rolling desert hills, through scattering timber and undergrowth.

Chains. Descend 20 ft. over NE. slope.  
 15.00 Base of slope.  
 23.50 Wash, 10 lks. wide, course NE.  
 30.50 Wash, 10 lks. wide, course NE.  
 33.00 Wash, 30 lks. wide, course NE.; asc. 15 ft. over SE. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Continue ascending 20 ft. over SE. slope.

42.70 Spur, slopes NE.; desc. 30 ft. over NW. slope.  
 66.80 Base of slope; continue over level land.  
 70.50 Wash, 10 lks. wide, course E.  
 78.00 Wash, 10 lks. wide, course E.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Land, rolling and level.  
 Soil, sandy, 2 nd rate; and rocky, 4th rate.  
 Timber, scattering palo verde and mesquite; undergrowth, greasewood, catclaw and cactus.

S.89°56'E., on a random line bet. secs. 15 and 22.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.00 Intersect N. and S. line, at the cor. of secs. 14, 15, 22 and 23.  
 Thence  
 N.89°56'W., on a true line bet. secs. 15 and 22.  
 Over level desert land, through scattering timber and undergrowth.  
 14.50 Wash, 20 lks. wide, course NE.  
 32.50 Wash, 50 lks. wide, course NE.; asc. 75 ft. over rolling SE. slope.

Chains  
40.00

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 15  
S 22  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Continue ascending 45 ft. over SE. slope.

49.00 Ridge, bears SE. and NW.; desc. 105 ft. over SW. slope.

57.00 Wash, 30 lks. wide, course SE.; asc. 10 ft. over gradual SE. slope.

80.00 The cor. of secs. 15, 16, 21 and 22.

Land, level and rolling.  
Soil, sandy, 2nd rate; and rocky, 4th rate.  
Timber, scattering palo verde, mesquite and ironwood;  
undergrowth, greasewood, sage brush and cactus.

N.0°02'W., bet. secs. 15 and 16.

Over rolling desert land, through scattering timber and undergrowth.

12.50 Wash, 30 lks. wide, course SE.; asc. 90 ft. over S. slope.

30.00 Spur, slopes E.; desc. 60 ft. over NE. slope.

35.50 Head of ravine, course SE.; asc. 60 ft. over S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 16 | S 15  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

The  $\frac{1}{4}$  sec. cor. is located in saddle on ridge, bears E. and W.

Descend 175 ft. over N. slope.

58.54 Wash, 20 lks. wide, course SE.; asc. 200 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

T 9 S R 4 W  
S 9 | S 10  
S 16 | S 15  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Chains.	The cor. of secs. 9,10,15 and 16 is located on spur, slopes E.  Land, rolling and mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	S.89°56'E., on a random line bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 10,11, 14 and 15.  Thence  N.89°57'W.; on a true line bet. secs. 10 and 15.  Over mountainous land; through scattering timber and undergrowth.  Ascend 160 ft. over NE. slope.
10.64	Spur, slopes NW.; desc. 190 ft. over W. slope.
19.21	Ravine, course N.; asc. 70 ft. over NE. slope.
25.86	Ridge, bears N. and S.; desc. 28 ft. over SW. slope.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4}$ S 10 S 15 1934
	raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.  Continue descending 65 ft. over SW. slope.
62.91	Wash, 10 lks. wide, course SE.; asc. 221 ft. over SE. slope.
75.86	Spur, slopes S.; desc. 25 ft. over SW. slope.
80.06	The cor. of secs. 9,10,15 and 16.  Land, mountainous and rolling. Soil, gravelly, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde; undergrowth, greasewood, sage brush and cactus.
	-----
	N.0°02'W., bet. secs. 9 and 10.  Over rolling desert land, through scattering timber and undergrowth.  Descend 175 ft. over NE. slope.
20.30	Wash, 20 lks. wide, course SE.; asc. 65 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



Chains.	$\frac{1}{4}$ S 9   S 10 1934	
	<p>raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p>	
	<p>The <math>\frac{1}{4}</math> sec. cor. is located on ridge, bears NE. and SW.</p>	
	<p>Descend 205 ft. over NW. slope.</p>	
62.70	<p>Wash, 10 lks. wide, course E.; asc. 55 ft. over SW. slope.</p>	
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bedrock, and in a mound of stone to top, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.</p>	
	$\begin{array}{cccc} T & 9 & S & R & 4 & W \\ S & 4 &   & S & 3 \\ S & 9 &   & S & 10 \\ & & & & 1934 \end{array}$	
	<p>raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p>	
	<p>The cor. of secs. 3, 4, 9 and 10 is located on ridge, bears NE. and SW.</p>	
	<p>Land, rolling.  Soil, rocky; 4th rate.  Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, cactus and sage.</p>	
	-----	
	<p>S. 89° 57' E., on a random line bet. secs. 3 and 10.</p>	
40.00	<p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>	
79.88	<p>Intersect N. and S. line, 12 lks. S. of the cor. of secs. 2, 3, 10 and 11.</p>	
	<p>Thence</p>	
	<p>S. 89° 58' W., on a true line bet. secs. 3 and 10.</p>	
	<p>Over rolling desert land, through scattering timber and undergrowth.</p>	
23.88	<p>Wash, 10 lks. wide, course NW.</p>	
39.94	<p>Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p>	
	$\begin{array}{c} \frac{1}{4} \text{ S } 3 \\ \text{S } 10 \\ 1934 \end{array}$	
	<p>raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, N. of cor.</p>	
61.38	<p>Wash, 10 lks. wide, course NE.; asc. 105 ft. over gradual NE. slope.</p>	
79.88	<p>The cor. of secs. 3, 4, 9 and 10.</p>	
	<p>Land, rolling.</p>	

Chains.	Soil, sandy, 2 <sup>nd</sup> rate; and gravelly, 3 <sup>rd</sup> rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N.0°10'W., on a random line bet. secs. 3 and 4.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.23	Intersect N. bdy. of Tp., 23 lks. E. of the cor. of secs. 3, 4, 33 and 34; described in the field notes of the N. bdy. of T. 9 S., R. 4 W., surveyed under this group.
	Thence
	S.0°20'E., on a true line bet. secs. 3 and 4.
	Over rolling desert hills, through scattering timber and undergrowth.
	Ascend 120 ft. over NE. slope.
15.23	Ridge, bears E. and W.; desc. 75 ft. over SW. slope.
30.33	Wash, 10 lks. wide, course NW.; asc. 70 ft. over NE. slope.
40.23	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 4   S 3 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	The $\frac{1}{4}$ sec. cor. is located on E. slope of ridge.
	Continue descending 55 ft. along E. slope.
56.23	Wash, 10 lks. wide, course E.; asc. 15 ft. over N. slope.
61.23	Spur, slopes NE.; desc. 30 ft. over SE. slope.
67.73	Wash, 10 lks. wide, course E.; asc. 50 ft. over NW. slope.
80.23	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling. Soil, sandy, 3 <sup>rd</sup> rate; and rocky, 4 <sup>th</sup> rate. Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	From the standard cor. of secs. 32 and 33 on the S. bdy. of the Tp.; described in the field notes of the 2 <sup>nd</sup> standard parallel south, through Rs. 3 and 4 W., resurveyed under this group.
	N.0°02'W., bet. secs. 32 and 33.
	Over mountainous land, through scattering timber and undergrowth.
	Ascend 645 ft. over steep SW. slope.

Chains.	
20.00	Ridge, bears N.20°W. and S.20°E.; desc. 190 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math>  S 32   S 33  1934 </div>
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue descending 30 ft. over NE. slope.
46.18	Base of slope, bears NE. and SW.; asc. 25 ft. over SE. slope.
48.50	Spur, slopes NE.; desc. 45 ft. over NW. slope.
51.49	Ravine, course W.; asc. 80 ft. over SW. slope.
62.33	Point of ridge, slopes NW.; desc. 465 ft. over N. slope.
76.53	Ravine, 20 lks. wide, course NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.  <div style="text-align: center;"> T 9 S R 4 W  S 29   S 28  S 32   S 33  1934 </div>
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, mountainous. Soil, gravelly, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, cactus and ocotillo.
	-----
	East, on a random line bet. secs. 28 and 33.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect N. and S. line, 7 lks. S. of the cor. of secs. 27, 28, 33 and 34.
	Thence
	S.89°57'W., on a true line bet. secs. 28 and 33.
	Over level desert land, through scattering timber and undergrowth.
15.06	Wash, 10 lks. wide, course NE.
29.05	Wash, 20 lks. wide, course NE.
36.05	Wash, 10 lks. wide, course NE.; leave level land. asc. 30 ft. over mountainous land.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in

Chains	the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 28</u> S 33 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	The $\frac{1}{4}$ sec. cor. is located on ridge, bears NE. and SW.
	Descend 40 ft. over SW. slope.
47.56	Head of ravine, course NW.
58.50	Head of ravine, course NW.; asc. 170 ft. over E. slope.
66.06	Spur, slopes N.; desc. 50 ft. over NW. slope.
72.36	Ravine, course N.; asc. 25 ft. over NE. slope.
77.26	Spur, slopes N.; desc. 40 ft. over NW. slope.
80.06	The cor. of secs. 28, 29, 32 and 33.
	Land, level and mountainous. Soil, sandy, 2nd rate; and rocky, 4th rate. Timber, scattering palo verde; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°02'W., bet. secs. 28 and 29.
	Over rolling desert land, through scattering timber and undergrowth.
	Descend 175 ft. over gradual broken NE. slope.
5.70	Wash, 20 lks. wide, course NE.
8.95	Wash, 75 lks. wide, course NE.
21.60	Wash, 30 lks. wide, course NE.
31.70	Wash, 10 lks. wide, course NE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 29   S 28 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
40.30	Wash, 30 lks. wide, course NE.
48.30	Wash, 40 lks. wide, course NE.; asc. 35 ft. over SE. slope.
57.10	Spur, slopes E.; desc. 100 ft. over NE. slope.
67.55	Wash, 30 lks. wide, course NE.
73.95	Wash, 30 lks. wide, course NE.

Chains. 80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, with a stone, 8x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 4 W S 20   S 21 S 29   S 28 1934</p> <p>Land, rolling. Soil, gravelly, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/> <p>N. 89° 57' E., on a random line bet. secs. 21 and 28.</p> <p>40.00 Set temp. <math>\frac{1}{4}</math> sec. cor.</p> <p>80.00 Intersect N. and S. line, 37 lks. N. of the cor. of secs. 21, 22, 27 and 28.</p> <p>Thence</p> <p>N. 89° 47' W., on a true line bet. secs. 21 and 28.</p> <p>Over level desert land, through scattering timber and undergrowth.</p> <p>11.30 Wash, 100 lks. wide, course NE.</p> <p>15.00 Wash, 10 lks. wide, course NE.</p> <p>19.50 Wash, 50 lks. wide, course NE.</p> <p>27.00 Wash, 20 lks. wide, course NE.</p> <p>30.90 Wash, 30 lks. wide, course NE.; continue over rolling land.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 21 S 28 1934</p> <p style="text-align: right;">raise a mound of stone, 2 ft. base, 1<math>\frac{1}{2}</math> ft. high, N. of cor.</p> <p>62.00 Wash, 30 lks. wide, course SE.</p> <p>68.80 Wash, 30 lks. wide, course SE.; asc. 25 ft. over gradual E. slope.</p> <p>80.00 The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, level and rolling. Soil, sandy, 2nd rate; and rocky; 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/> <p>N. 0° 02' W., bet. secs. 20 and 21.</p> <p>Over rolling desert hills, through scattering timber and undergrowth.</p>
------------------	--

Chains.	
2.00	Wash, 20 lks. wide, course NE.
25.75	Wash, 30 lks. wide, course SE.; asc. 55 ft. over gradual S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 20   S 21 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Ascend 145 ft. over SW. slope.
49.15	W. end of ridge, slopes SW.; desc. 100 ft. over NW. slope.
53.85	Ravine, course NW.; asc. 105 ft. over SW. slope.
59.15	Spur, slopes W.; desc. 200 ft. over steep NW. slope.
79.95	Ravine, course NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.
	T 9 S R 4 W S 17   S 16 S 20   S 21 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling desert hills.
	Soil, sandy, 2nd rate; and gravelly, 3rd rate.
	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	S. $89^{\circ}47'E.$ , on a random line bet. secs. 16 and 21.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect N. and S. line, 16 lks. S. of the cor. of secs. 15, 16, 21 and 22.
	Thence
	N. $89^{\circ}54'W.$ , on a true line bet. secs. 16 and 21.
	Over rolling desert land, through scattering timber and undergrowth.
39.85	Wash, 20 lks. wide, course NE.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 16 S 21 1934

Chains.	
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
45.05	Wash, 10 lks. wide, course NE.; asc. 65 ft. over NE. slope.
55.00	Spur, slopes N.; desc. 14 ft. over NW. slope.
57.95	Ravine, course N.; asc. 110 ft. over NE. slope.
69.35	Spur, slopes N.; desc. 55 ft. over NW. slope
80.06	The cor. of secs. 16,17,20 and 21.

Land, rolling.

Soil, sandy, 2nd rate; and gravelly, 3rd rate.

Timber, scattering palo verde, ironwood and mesquite;  
undergrowth, greasewood, sage brush and cactus.

N.0°02'W., bet. secs. 16 and 17.

Over rolling desert land, through scattering timber and undergrowth.

4.95	Descend 90 ft. over gradual N. slope.
20.10	Wash, 10 lks. wide, course NE.
24.10	Wash, 150 lks. wide, course NE.; asc. 65 ft. over S. slope.
28.25	Spur, slopes E.; desc. 70 ft. over N. slope.
33.30	Wash, 30 lks. wide, course NE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 17 | S 16

1934

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

47.25	Wash, 75 lks. wide, course NE.
79.50	Wash, 50 lks. wide, course SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 8,9,16 and 17, with brass cap mkd.

T 9 S R 4 W

S 8 | S 9

S 17 | S 16

1934

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.

Soil, sandy, 2nd rate; and gravelly, 3rd rate.

Timber, scattering palo verde, ironwood and mesquite;  
undergrowth, greasewood, sage brush and cactus.

Chains.	S.89°54'E., on a random line bet. secs. 9 and 16.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.48	Intersect N. and S. line, 12 lks. N. of the cor. of secs. 9,10,15 and 16.
	Thence
	N.89°49'W., on a true line bet. secs. 9 and 16.
	Over rolling desert hills, through scattering timber and undergrowth.
	Descend 100 ft. over gradual SW. slope.
14.10	Wash, 30 lks. wide, course SE.
22.10	Wash, 20 lks. wide, course SE.; asc. 60 ft. over NE. slope.
28.75	Spur, slopes SE.; desc. 25 ft. over SW. slope.
36.85	Wash, 40 lks. wide, course SE.; asc. 45 ft. over NE. slope.
40.24	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 9 S 16 1934
	raise a mound
	of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	Continue ascending over NE. slope.
47.00	Ridge, bears SE. and NW.; desc. 110 ft. over SW. slope.
56.40	Ravine, course SW.; asc. 75 ft. over SE. slope.
62.35	Spur, slopes S.; desc. 70 ft. over SW. slope.
68.00	Wash, 75 lks. wide, course SE.; asc. 25 ft. over NE. slope.
80.48	The cor. of secs. 8,9,16 and 17.
	Land, rolling desert hills.
	Soil, gravelly, 3rd rate; and rocky, 4th rate.
	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°02'W., bet. secs. 8 and 9.
	Over rolling desert hills, through scattering timber and undergrowth.
16.00	Wash, 20 lks. wide, course NE.
18.60	Wash, 30 lks. wide, course NE.
38.55	Wash, 20 lks. wide, course SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



Chains.

$$\frac{1}{4}$$

S 8	S 9
-----	-----

1934

raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Leave rolling land, and enter mountainous land, bears SE. and NW.; asc. 330 ft. over broken S. slope.

64.85 Ridge, bears NW. and SE.; desc. 405 ft. over rocky N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam.; 27 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T 9	S R 4	W
S 5	S 4	
S 8	S 9	

1934

raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and rough mountains.

Soil, rocky; 4th rate.

Timber, scattering palo verde, catclaw and mesquite; undergrowth, greasewood and cactus.

S.  $89^{\circ}49'E.$ , on a random line bet. secs. 4 and 9.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.46 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 3, 4, 9 and 10.

Thence

N.  $89^{\circ}53'W.$ , on a true line bet. secs. 4 and 9.

Over rolling desert hills, through scattering timber and undergrowth.

Descend 35 ft. over gradual NW. slope.

20.00 Wash, 20 lks. wide, course NE.

40.23 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 4
	S 9

1934

raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

42.67 Wash, 15 lks. wide, course N.

50.95 Wash, 100 lks. wide, course NE.; asc. 295 ft. over E. slope.

69.85 Spur, slopes NE.; desc. 50 ft. over W. slope.

72.85 Wash, 30 lks. wide, course N.; asc. 35 ft. over E. slope.

Chains	
74.60	Spur, slopes NW.; desc. 105 ft. over W. slope.
79.00	Wash, 40 lks. wide, course N.; asc. 15 ft. over NE. slope.
80.46	The cor. of secs. 4,5,8 and 9. Land, rolling desert hills. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, catclaw and cactus.
	-----
	N.0°20'W., on a random line bet. secs. 4 and 5.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.30	Intersect N. bdy. of Tp., 42 lks. W. of the cor. of secs. 4,5,32 and 33; described in the field notes of the N. bdy. of T. 9 S., R. 4 W., surveyed under this group. Thence S.0°02'E., on a true line bet. secs. 4 and 5. Over rolling desert land, through scattering timber and undergrowth.
11.70	Spur, slopes SW.; desc. 130 ft. over SE. slope.
16.80	Wash, 40 lks. wide, course NE.
31.80	Wash, 25 lks. wide, course NE.
40.10	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 5   S 4 W   C 1934 raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
40.30	True point for $\frac{1}{4}$ sec. cor. falls in wash 100 lks. wide, course NW.
53.25	Wash, 75 lks. wide, course NE..
55.95	Wash, 75 lks. wide, course NE.; asc. 175 ft. over N. slope.
80.30	The cor. of secs. 4,5,8 and 9. Land, rolling. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----

Chains	From the standard cor. of secs. 31 and 32 on the S. bdy. of the Tp.; described in the field notes of the 2nd. standard parallel south, through Rs. 3 and 4 W., resurveyed under this group.  N.0°03'W., bet. secs. 31 and 32.  Over mountainous land, through scattering timber and undergrowth.  Ascend 445 ft. over SW. slope.
17.30	Spur, slopes N.70°W.; desc. 80 ft. over NE. slope.
20.00	Ravine, course N.70°W.; asc. 140 ft. over SW. slope.
29.65	Spur, slopes N.60°W.; desc. 340 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \\ \text{S } 31 \text{   S } 32 \\ 1934 \end{array}$
	Descend 165 ft. over N. slope.
50.60	Wash, 14 lks. wide, course N.60°W.
51.40	Wash, 10 lks. wide, course N.65°W.; asc. 105 ft. over SW. slope.
79.90	Spur, slopes W.
80.00	Set a tufa stone, 20x8x6 ins., 12 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, mkd. with 1 groove on S. and 5 grooves on E. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.  The cor. of secs. 29, 30, 31 and 32 is located on spur, slopes NW.  Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush, saguaro and ocitillo.
	-----
	East, on a random line bet. secs. 29 and 32.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.18	Intersect N. and S. line, 26 lks. S. of the cor. of secs. 28, 29, 32 and 33.  Thence  S.89°49'W., on a true line bet. secs. 29 and 32.  Over mountainous land, through scattering timber and undergrowth.  Ascend 195 ft. over NE. slope.
18.90	Ridge, bears N.15°W. and S.10°E.; desc. 235 ft. over NW. slope.

Chains	
22.20	Head of ravine, course S.60°W.; continue descending 200 ft. over broken SW. slope.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone, 14x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 29</u> S 32 1934
	Continue descending 70 ft. over SW. slope.
43.28	Rocky ravine, course N.65°W.
69.50	Ascend 85 ft. over NE. slope.
80.18	The cor. of secs. 29, 30, 31 and 32.
	Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	West, on a random line bet. secs. 30 and 31.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect W. bdy. of Tp., at the cor. of secs. 25, 30, 31 and 36; described in the field notes of the W. bdy. of T. 9 S., R. 4 W., surveyed under this group.
	Thence
	East, on a true line bet. secs. 30 and 31.
	Over mountainous land, through scattering timber and undergrowth.
	Descend 155 ft. over NE. slope.
9.60	Foot of hill, bears SE. and NW.
11.10	Wash, 25 lks. wide, course S.10°E.
32.30	Ascend 310 ft. over broken SW. slope.
37.10	Spur, slopes S. 30°W.; desc. 10 ft. over E. slope.
40.08	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone, 8x7x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 30</u> S 31 1934
	Continue descending 270 ft. over steep E. slope.
43.65	Foot of hill, bears N. and S.
47.20	Wash, 20 lks. wide, course S. 15° E.
58.10	Wash, 100 lks. wide, course S.10°W.; asc. 195 ft. over SW. slope.

Chains. 80.08	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rough mountains. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush, cat-claw, saguaro and ocotillo.</p> <p>-----</p> <p>N.0°03'W., bet. secs. 29 and 30.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p> <p>Descend 120 ft. over NE. slope.</p>
10.65	Ravine, course S.50°W.; asc. 290 ft. over SW. slope.
29.05	Spur, slopes N.30°W.; desc. 45 ft. over NE. slope.
35.95	Head of ravine, course NW.; asc. 20 ft. over SW. slope.
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a stone, 6x5x3 ins. mkd. X; deposited at the base, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor.; with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 30   S 29</p> <p style="text-align: center;">1934</p> <p>Continue ascending 105 ft. over broken SW. slope.</p>
53.35	Spur, slopes N.40°W.; desc. 330 ft. over N. slope.
64.50	Wash, 30 lks. wide, course N.70°W.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 4 W</p> <p style="text-align: center;">S 19   S 20</p> <p style="text-align: center;">S 30   S 29</p> <p style="text-align: center;">1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, cat-claw, saguaro and ocotillo.</p> <p>-----</p>
40.00	<p>N.89°49'E., on a random line bet. secs. 20 and 29.</p> <p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>
80.04	<p>Intersect N. and S. line, 19 lks. S. of the cor. of secs. 20, 21, 28 and 29.</p> <p>Thence</p> <p>S.89°41'W., on a true line bet. secs. 20 and 29.</p>

Chains.	Over rolling desert land, through scattering timber and undergrowth.
12.75	Ascend 55 ft. over NE. slope.
22.90	Descend 40 ft. over SW. slope.
27.90	Wash, 30 lks. wide, course SW.; asc. 110 ft. over NE. slope.
35.90	Spur, slopes SE.; desc. 30 ft. over SW. slope.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \text{ S } 20 \\ \hline \text{S } 29 \\ 1934 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
42.50	Wash, 40 lks. wide, course SW.
63.40	Wash, 50 lks. wide, course SW.
71.90	Wash, 50 lks. wide, course SW.
78.20	Wash, 30 lks. wide, course SW.
80.04	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling. Soil, rocky; 4th rate. Timber, scattering palo verde, catclaw, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	West, on a random line bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.18	Intersect W. bdy. of Tp., 19 lks. S. of the cor. of secs. 19, 24, 25 and 30; described in the field notes of the W. bdy. of T. 9 S., R. 4 W., surveyed under this group.
	Thence
	S. 89° 52' E., on a true line bet. secs. 19 and 30.
	Over mountainous land, through scattering timber and undergrowth.
	Descend 95 ft. over SE. slope.
6.90	Wash, 40 lks. wide, course SE.; asc. 160 ft. over SW. slope.
18.75	Spur, slopes SE.; desc. 185 ft. over E. slope.
25.80	Wash, 50 lks. wide, course S.
30.30	Wash, 30 lks. wide, course SW.; asc. 105 ft. over W. slope.
40.18	Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a stone, 8x5x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \text{ S } 18 \\ \hline \text{S } 30 \\ 1934 \end{array}$

Chains.	
44.15	Gulch, course SW.; asc. 95 ft. over SW. slope.
47.65	Spur, slopes SE.; desc. 175 ft. over E. slope.
65.30	Wash, 30 lks. wide, course SW.; asc. 55 ft. over W. slope.
70.70	Spur, slopes SW.; desc. 60 ft. over SE. slope.
80.18	The cor. of secs. 19, 20, 29 and 30.
	Land, rough mountains. Soil, gravelly, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N.0°03'W., bet. secs. 19 and 20.
	Over mountainous land, through scattering timber and undergrowth.
	Ascend 40 ft. over gradual SW. slope.
10.80	Wash, 20 lks. wide, course S.60°E.; continue ascending over SW. slope.
34.85	Base of ridge, bears NW. and SE.; asc. 135 ft. over SW. slope.
40.00	Set a malpais stone, 18x10x5 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{2}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Ascend 205 ft. over S. slope.
50.40	Spur, slopes N.60°W.; desc. 130 ft. over steep NW. slope.
53.50	Ravine, course N.70°W.; asc. 255 ft. over SW. slope.
66.65	Ridge, bears N.30°W. and S.30°E.; desc. 125 ft. over broken NE. slope.
80.00	True point for cor. of secs. 17, 18, 19 and 20, falls on steep rocky NE. slope; mark a cross X, at true point for cor. on surface rock.
	Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N.89°41'E., on a random line bet. secs. 17 and 20.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.24	Intersect N. and S. line, 9 lks. N. of the cor. of secs. 16, 17, 20 and 21.
	Thence
	S.89°45'W., on a true line bet. secs. 17 and 20.
	Over rolling mountainous land, through scattering timber and undergrowth.
.10	Ravine, course NW.; asc. 40 ft. over NE. slope.

Chains.	
3.00	Small spur, slopes NE.; desc. 95 ft. over NW. slope.
13.25	Wash, 15 lks. wide, course NE.
23.05	Wash, 75 lks. wide, course NE.; asc. 195 ft. over E. slope.
40.12	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 17</u> S 20 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Ascend 50 ft. over E. slope.
45.35	Spur, slopes SW.; desc. 160 ft. over SW. slope.
63.60	Wash, 50 lks. wide, course SE.; asc. 320 ft. over SE. slope.
78.85	Deep gulch, course SE.
80.24	The true point for cor. of secs. 17, 18, 19 and 20.
	Land, rolling mountains. Soil, rocky and gravelly; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N.89°52'W., on a random line bet. secs. 18 and 19.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.30	Intersect W. bdy. of Tp., 19 lks. S. of the cor. of secs. 13, 18, 19 and 24; described in the field notes of the W. bdy. of T. 9 S., R. 4 W., surveyed under this group.
	Thence
	S.89°44'E., on a true line bet. secs. 18 and 19.
	Over rolling mountains, through scattering timber and undergrowth.
1.10	Ravine, course SE.
3.00	Spur, slopes SE.; desc. 105 ft. over SE. slope.
11.50	Wash, 100 lks. wide, course SE.
20.40	Wash, 70 lks. wide, course SE.
28.15	Wash, 50 lks. wide, course SE.; asc. 205 ft. over NW. slope.
40.30	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 18</u> S 19 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.



Chains:	Ascend 85 ft. over NW. slope.
49.60	Spur, slopes SE.; desc. 180 ft. over SE. slope.
56.50	Wash, 50 lks. wide, course SE.; asc. 330 ft. over SW. slope.
72.20	Ridge, bears SE. and NW.; desc. 250 ft. over SE. slope.
80.30	The true point for cor. of secs. 17,18,19 and 20.
	Land, rolling mountains. Soil, rocky; 4th rate. Timber, scattering palo verde, catclaw and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°03'W., bet. secs. 17 and 18.
	Over mountainous land, through scattering timber and undergrowth.
	Descend 160 ft. over broken NE. slope.
1.60	Set a malpais stone, 20x6x6 ins., 14 ins. in the ground, for witness cor. of secs. 17,18,19 and 20, mkd. with 3 notches on S. and 5 notches on E. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
13.50	Ravine, course SE.; asc. 75 ft. over broken SE. slope.
27.45	Small saddle bears E. and W.; desc. 40 ft. over broken NW. slope.
30.00	Head of ravine, course NW.; asc. 20 ft. over broken SW. slope.
40.00	True point for ¼ sec. cor. falls on steep rocky NW. slope.
40.15	Set a malpais stone, 20x8x6 ins. 4 ins. in the ground to bedrock, and in a mound of stone to top, for witness ¼ sec. cor., mkd. WC on S. and ¼ on W. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Descend 65 ft. over NW. slope.
50.20	Head of ravine, course NW.; asc. 125 ft. over SW. slope.
54.95	Spur, slopes N.45°W.; desc. 400 ft. over NE. slope.
80.00	Set a malpais stone, 24x9x5 ins., 10 ins. in the ground, for cor. of secs. 7,8,17 and 18, mkd. with 4 grooves on S. and 5 grooves on E. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, catclaw and mesquite.
-----	
	N.89°45'E., on a random line bet. secs. 8 and 17.
40.00	Set temp. ¼ sec. cor.
79.96	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 8,9,16 and 17.
	Thence

Chains.	S.89°47'W., on a true line bet. secs. 8 and 17.
	Over rolling mountains, through scattering timber and undergrowth.
3.10	Wash, 40 lks. wide, course SE.; asc. 70 ft. over NE. slope.
23.05	Spur, slopes SE.; desc. 50 ft. over SW. slope.
28.00	Wash, 20 lks. wide, course SE.; asc. 15 ft. over NE. slope.
39.98	Set a malpais stone, 24x10x8 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Ascend 40 ft. over SE. slope.
43.60	Spur, slopes SE.; desc. 35 ft. over SW. slope.
53.30	Wash, 20 lks. wide, course SE.
59.55	Saddle in ridge, bears NW. and SE.; desc. 115 ft. over NW. slope.
77.50	Wash, 50 lks. wide, course NW.
79.96	The cor. of secs. 7, 8, 17 and 18.
	Land, rolling mountains. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush, ocotillo and cactus.
-----	
	N.89°44'W., on a random line bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{2}$ sec. cor.
79.81	Intersect W. bdy. of Tp., 7 lks. S. of the cor. of secs. 7, 12, 13 and 18; described in the field notes of the W. bdy. of T. 9 S., R. 4 W., surveyed under this group.
	Thence
	S.89°41'E., on a true line bet. secs. 7 and 18.
	Over mountainous land, through scattering timber and undergrowth.
	Ascend 120 ft. over NW. slope.
4.25	Ridge, bears SW. and NE.; desc. 595 ft. over NE. slope.
32.70	Wash, 100 lks. wide, course NE.; continue over rolling desert land.
39.81	Set a malpais stone, 24x8x6 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
62.10	Wash, 200 lks. wide, course NE.
70.20	Wash, 150 lks. wide, course NE.
79.81	The cor. of secs. 7, 8, 17 and 18.
	Land, mountainous and rolling, Soil, gravelly, 3rd rate; and rocky, 4th rate.

BOOK 4063

Chains.	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°03'W., bet. secs. 7 and 8.
	Over rolling desert land, through scattering timber and undergrowth.
9.50	Wash, 80 lks. wide, course N.20°E.
36.00	Wash, 16 lks. wide, course SE.
40.00	Set a malpais stone, 17x10x8 ins., 4 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
50.00	Ascend 30 ft. over SE. slope.
58.00	Spur, slopes E.; desc. 70 ft. over NE. slope.
80.00	Set a malpais stone, 18x6x6 ins., 12 ins. in the ground, for cor. of secs. 5,6,7 and 8, mkd. with 5 grooves on S. and 5 grooves on E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, sandy, 2nd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush, cactus and catclaw.
-----	
	N.89°47'E., on a random line bet. secs. 5 and 8.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.16	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 4,5,8 and 9.
	Thence
	S.89°49'W., on a true line bet. secs. 5 and 8.
	Over mountainous land, through scattering timber and undergrowth.
	Ascend 325 ft. over NE. slope.
11.15	Spur, slopes N.; desc. 25 ft. over NW. slope.
12.15	Head of ravine, course N.; asc. 25 ft. over NE. slope.
16.55	Spur, slopes N.; desc. 430 ft. over W. slope.
31.35	Ravine, course N.10°W.; asc. 140 ft. over NE. slope.
38.80	Ridge, bears N.15°W. and S.10°E.; desc. 40 ft. over NW. slope.
40.08	Set a malpais stone, 22x8x8 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Descend 105 ft. over NW. slope.
48.85	Ravine, course N.45°W.; asc. 65 ft. over NE. slope.
67.40	Spur, slopes N.10°E.; desc. 95 ft. over NW. slope.

Chains.	
71.85	Wash, 60 lks. wide, course N.15°W.
80.16	The cor. of secs. 5,6,7 and 8. Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N.89°41'W., on a random line bet. secs. 6 and 7.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.54	Intersect W. bdy. of Tp., 12 lks. N. of the cor. of secs. 1,6,7 and 12; described in the field notes of the W. bdy. of T. 9 S., R. 4 W., surveyed under this group. Thence S.89°46'E., on a true line bet. secs. 6 and 7. Over mountainous land, through scattering timber and undergrowth. Ascend 170 ft. over W. slope.
8.15	Spur, slopes N.; desc. 305 ft. over SE. slope.
16.25	Ravine, course N.45°E.; asc. 100 ft. over NW. slope.
28.90	Top of rocky knoll, on spur, slopes NE.; desc. 175 ft. over SE. slope.
39.54	Set a malpais stone, 18x12x4 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
47.75	Wash, 25 lks. wide, course N.; asc. 35 ft. over NW. slope.
55.20	Spur, slopes N.; desc. 30 ft. over NE. slope.
59.05	Ravine, course NW.; asc. 80 ft. over SW. slope.
68.60	Saddle, bears N. and S.; desc. 75 ft. over SE. slope.
79.54	The cor. of secs. 5,6,7 and 8. Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N.0°02'W., on a random line bet. secs. 5 and 6.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.30	Intersect N. bdy. of Tp., 2 lks. E. of the cor. of secs. 5,6,31 and 32; described in the field notes of the N. bdy. of T. 9 S., R. 4 W., surveyed under this group. Thence S.0°03'E., on a true line bet. secs. 5 and 6. Over mountainous land, through scattering timber and undergrowth.

- Chains Ascend 40 ft. over NW. slope.
- 11.70 Ravine, course N.10°W.; asc. 30 ft. over NE. slope.
- 29.00 Ravine, course N.10°W.; continue ascending 50 ft. over NW. slope.
- 35.30 Low saddle, bears N.30°E. and S.50°W.; desc. 50 ft. over SE. slope.
- 38.50 Ravine, course N.30°E.; asc. 5 ft. over NW. slope.
- 40.30 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
s 6 | s 5  
1934

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Ascend 180 ft. over NW. slope.

- 46.75 Spur, slopes N.25°E.; desc. 175 ft. over SE. slope.
- 55.20 Ravine, course N.80°E.; asc. 85 ft. over NE. slope.
- 63.30 Spur, slopes N.45°E.; desc. 80 ft. over SE. slope.
- 80.30 The cor. of secs. 5, 6, 7 and 8.

Land, mountainous.

Soil, sandy, 2nd rate; and rocky, 4th rate.

Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, ocotillo, catclaw and cactus.

#### GENERAL DESCRIPTION.

The land embraced within T. 9 S., R. 4 W., is desert and mountainous. The general elevation of the desert region varies from 800 to 1000 ft. above sea level. The mountain area is medium rough with some peaks rising as much as 1000 ft. above the natural level of the desert. The water course consists mostly of deep canyons and ravines, the general drainage of the township is northerly, except the SW. portion which is southwesterly. The surface is very rocky in the mountain region which consists of decomposed granite and lava, 4th rate. The soil in the desert is sandy 2nd rate; and gravelly, 3rd rate. The surface of the desert is covered with loose volcanic rocks, which have been thrown from volcanic peaks. The timber is very scattering palo verde, ironwood, mesquite and catclaw. The undergrowth, is scattering greasewood, sage and several varieties of cactus. The area is arid, no source of water supply being noted.

No mineral deposits were found.

The average magnetic declination of the township is 14° E.

4-680  
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
William Steinhilber	1st Chainman
Dee W. May	1st Chainman
Frank J. Clancy	2nd Chainman
Marion E. Baker	2nd Chainman.
N. E. Herron	2nd Chainman
Ivan L. Dial	2nd Chainman
Charles A. Mayes	Flagman
Mathias Pacheco	Cornerman
W. C. Clark	Axeman
Alva Mills	Axeman
Charles Grinstaff	Axeman
John Maddux	Moundsman
L. B. Roberts	Moundsman

45 184 BOOK 4063

CERTIFICATE OF UNITED STATES SURVEYOR

We, David D. Baker, Daniel M. Wier, George W. Danehy and Herman J. Shafer, U.S. Transitmen,

hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 12th day of December, 1933. We have well, faithfully, and truly

in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed the subdivisional lines of Township 9 South, Range 4 West.

of the Gila and Salt River Meridian, in the State of Arizona,

which are represented in the foregoing field notes as having been executed by us, and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

For signature of Daniel M. Wier, George W. Danehy and Herman J. Shafer, see attached certificates.

David D. Baker U.S. Transitman

Gila Bend, Arizona, January 20, 1934.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

19

The foregoing field notes of the survey of

executed by

under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

BOOK 4068

4-680  
(August, 1926)

**FIELD ASSISTANTS.**

NAMES.	CAPACITY.
Niel Greehaw	1st Chainman
John H. Robinson	2nd Chainman
Daniel B. Elkins	Flagman
Earnest Cooley	Axeman
M.E. Hydock	Cornerman
Dawson Cooley	Moundsman
L.V. Trosper	Moundsman



47 186  
BOOK 4068

CERTIFICATE OF UNITED STATES SURVEYOR

We, David D. Baker, Daniel M. Wier,  
George W. Danehy and  
Herman J. Shafer, U.S. Transitmen, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 12th day of December, 1933, we have well, faithfully, and truly

in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed the subdivisional lines of Township 9 South, Range 4 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us, and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*Daniel M. Wier*

U. S. Transitman

Gila Bend, Arizona,  
January 20, 1934.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

19

The foregoing field notes of the survey of

executed by

under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

ED 0114 4003

4-680  
(August, 1926)

**FIELD ASSISTANTS.**

NAMES.	CAPACITY.
Rowland Norris	1st Chainman
H.B. Burt	2nd Chainman
Ernest L. Shockley	Flagman
Phil C. Ensign	Cornerman
Merritt Preston	Moundsman
Aubrey Washburn	Moundsman
Robert Wallis	Axeman

188  
49 BOOK 4063

### CERTIFICATE OF UNITED STATES SURVEYOR

We, David D. Baker, Daniel M. Wier,  
George W. Danehy and  
Herman J. Shafer, U.S. Transitmen

, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 12th day of December, 1933, we have well, faithfully, and truly

in ~~my~~ <sup>our</sup> own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instruc-  
tions, and the laws of the United States, surveyed the subdivisional lines of Township  
9 South, Range 4 West,

of the Gila and Salt  
River Meridian, in the State of Arizona,

which are represented in the foregoing field notes as having been executed by <sup>us</sup> ~~me~~, and under <sup>our</sup> ~~my~~ direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-  
tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*George Welsh Danehy*  
U.S. Transitman.

APPROVAL Gila Bend, Arizona,  
January 20, 1934.

Office of U. S. Supervisor of Surveys,

19

The foregoing field notes of the survey of

executed by

under his special instructions dated \_\_\_\_\_, 19\_\_\_\_, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680  
(August, 1926)

1926 4063

**FIELD ASSISTANTS.**

NAMES.	CAPACITY.
William M.Heina	1st Chainman
A.W.Porter	2nd Chainman
George R.Hegi	2nd Chainman
Joseph W.Coulter	Flagman
Angus Pryor	Cornerman
Henry Hayes	Cornerman
H.F.Reeves	Axeman
P.L.Lowry	Axeman
Al Blake	Axeman
J.Wilson Cobb	Moundsman
Tom Flynn	Moundsman

CERTIFICATE OF UNITED STATES SURVEYOR

We, David D. Baker, Daniel M. Wier,  
George W. Danehy and  
Herman J. Shafer, U.S. Transitmen, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 12th day of December, 1933, we have well, faithfully, and truly

in ~~our~~ <sup>OUR</sup> own proper person, and in strict conformity with said instructions, the Manual of Surveying Instruc-

tions, and the laws of the United States, surveyed the subdivisonal lines of Township

9 South, Range 4 West,

River of the Gila and Salt  
Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us, and under our direction; and that all the corners of  
said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-  
tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of  
such survey.

*Herman J. Shafer*  
U.S. Transitman

APPROVAL Gila Bend, Arizona,  
January 20, 1934.

OFFICE OF U. S. SUPERVISOR OF SURVEYS,  
Denver, Colorado, May 11, 1935.

The foregoing field notes of the survey of the subdivisonal lines of Township  
9 South, Range 4 West, of the Gila and Salt River Meridian, in the  
State of Arizona,

executed by David D. Baker, Daniel M. Wier, George W. Danehy  
and Herman J. Shafer, U.S. Transitmen,  
~~their~~ <sup>their</sup> special instructions dated December 12, 1933, having been  
critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys  
they describe, are hereby approved.

*Wm. D. Johnson*  
U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in  
, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.