

4-679
(April 1933)

Book C

BOOK 4080

FIELD NOTES

OF THE

Dependent Resurvey of the Subdivisional Lines

of

Township 5 South, Range 9 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

William Merry Heina, U. S. Transitman, and

Daniel M. Wier, U. S. Transitman, and

Jess R. Horak, U. S. Transitman

Under special instructions dated February 15, 1934, which provided for the surveys included under Group No. 201, bearing the approval of the Commissioner of the General Land Office under date of April 13, 1934, and assignment instructions dated January 15, 26 and 28, 1934.

Survey commenced January 30, 1934.

Survey completed March 20, 1934.

4080

4080

1A 152
BOOK 4030

INDEX DIAGRAM.

Township 5 South, Range 9 West

6 35	35 5 35	26 4 25	19 8 19	13 2 12	7 1 7
7 33	34 8 33	25 9 24	18 10 18	12 11 11	6 12 5
18 31	32 17 31	24 16 23	17 15 16	11 14 10	5 18 4
19 30	30 20 29	22 21 22	15 22 15	10 23 9	3 24 3
30 28	28 29 27	21 28 21	14 27 14	9 26 8	3 25 2
31	27 32	20 33	13 34	7 35	1 36

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

The subdivisional resurvey of township 5 south, range 9 west, was executed with the following transit instruments, property of the General Land Office: Young and Sons transits, Serial Nos. 8487 and 8585; Gurley transits Serial Nos. 20116 and 20117; and Buff and Buff transit, Serial No. 9305. The instruments have full vertical circles with one double vernier reading to single minutes. The horizontal circles have two double opposite verniers.

The instruments were in good condition, and having been placed in satisfactory adjustment prior to beginning the survey and tested and found free from appreciable error, were approved by the district cadastral engineer on Jan. 20, 1934.

The measurements were made with Lallie steel tapes five chains in length, graduated every link for the first one hundred links and the balance at intervals of 10 links. The measurements were made on the slope; the vertical angles determined with clinometers in good adjustment and the horizontal equivalents then entered in the field note record.

As the lines to be reestablished extend over a comparative level country with practically no timber and little undergrowth, the back and fore sight method of carrying the alinement was selected, making due allowance in the final bearings of the true lines for all accumulated differences in bearing through a divergence of the latitudinal random lines from true latitude curves.

The direction of the lines were determined by turning deflection angles from true lines along the township boundaries; the true lines being deflected from true meridians determined by observations on Polaris and by direct observations on the sun, as described in the field notes of the boundaries of T. 5 S., R. 9 W., resurveyed under this group.

In 1877, T.F. White, U.S. Deputy surveyor, made a survey of the subdivisional lines of T. 5 S., R. 9 W.

In 1926, Sidney E. Blout, U. S. Cadastral Engineer, resurveyed the boundaries of section 11; the S. $\frac{1}{2}$ of the line between 1 and 2, and retraced the line between 1 and 12. No other survey or resurvey in this township is of record.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search made for all corners. The retracement data is thoroughly verified and to gain simplification, the true line field notes only, are recorded herein.

In the dependent resurvey of the subdivisional lines hereinafter described, the lost section corners were reestablished by double proportion between the known and identified subdivisional corners and reestablished corners on the east and west boundaries; or between identified subdivisional corners as appropriate, all being based on the original record. Missing $\frac{1}{4}$ section corners were reestablished midway between original or reestablished section corners, except on the north tier and west range of sections where they were reestablished by single proportion based upon the original record.

From the standard cor. of secs. 35 and 36 on the south bdy. of Tp., described in the field notes of the 1st. Standard Parallel S., through R. 9 W., resurveyed under this group.

N.0°22'E. on a true line bet. secs. 35 and 36.

Over rolling ground, through scattered undergrowth.

41.64

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

$$\begin{array}{c} \frac{1}{4} \\ \sqrt{s35 | s36} \\ 1934 \end{array}$$

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

83.28

The cor. of secs. 25, 26, 35 and 36, which is a partially decayed mesquite post lying in center of an old mound of stone

In center of old mound with old mesquite post alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a stone, 6x5x3 ins., mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

$$\begin{array}{c} T5S, R9W \\ \sqrt{s26 | s25} \\ s35 | s36 \\ 1934 \end{array}$$

raise a mound
of stone, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy loam; 2nd rate.

Timber, scattering palo verde, mesquite and ironwood; undergrowth, sage, cactus and greasewood.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 5 S., R. 9 W., resurveyed under this group.

N.88°57'W., on a true line bet. secs. 25 and 36.

Over rolling ground, through scattering undergrowth.

39.75

The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, which is a palo verde post, 3 ft. long, 2 ins. in diam., partially decayed, lying along side of a mound of stone.

In center of old mound and with old post set along side;

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\begin{array}{c} s 25 \\ \frac{1}{4} \\ \sqrt{s 36} \\ 1934 \end{array}$$

raise a mound

of stone, 4 ft. base, 3 ft. high, N. of cor.

Thence

N.88°59'W., on a true line bet. secs. 26 and 35.

39.65

The cor. of secs. 25, 26, 35 and 36, hereinbefore described.

Land, rolling.

Soil, sandy loam,; 2nd rate.

Timber, scattering palo verde, mesquite and ironwood; undergrowth, sage, cactus and greasewood.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

chains	Thence
40.31-	<p>N.0°07'W., on a true line bet. secs. 25 and 26.</p> <p>Over rolling ground, through scattering undergrowth.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$ S26 S25 1934</p>
80.62	<p>The corner of secs. 23, 24, 25 and 26, which is a partially decayed post, 3 ins. in diam., 36 ins. long with all scribe mks. weathered away, set in center of an old mound of stone.</p> <p>In the center of the old mound and with the old corner post set along side;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone to top, for cor. of secs. 23, 24, 25 and 26, with brass cap marked</p> <p style="text-align: center;">T5S R9W S23 S24 S26 S25 1934</p> <p style="text-align: right;">from which</p> <p>An original bearing tree;</p> <p>A palo verde, bears N.86°00'W., 63 lks. dist., mkd. T V S R IX W S XXIII.</p> <p>Land, rolling. Soil, sandy loam; 2nd rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, sage, cactus and greasewood.</p>
39.75	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T.5 S., R.9 W., resurveyed under this group.</p> <p>N.89°32'W., on a true line bet. secs. 24 and 25.</p> <p>Over rolling ground, through scattering brush.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone 5x5x3 ins. mkd. with a (X) cross deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 24 S 25</p>
79.49	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, sandy loam; 2nd rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, greasewood, sage and cactus.</p> <p>Thence</p> <p>N.0°26'W., on a true line bet. secs. 23 and 24.</p>

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	Over rolling ground, through scattering brush.
43.02	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, which is the remaining end of a partially decayed post in the center of an old mound of stone,</p> <p>In center of old mound and in place of old cor. post which is set alongside;</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S23 S24 1934 </div> <p>Thence</p> <p>N.0°52'E., on a true line bet. secs. 23 and 24.</p>
35.20	Wash, 10 lks. wide, course NE.
39.12	<p>The cor. of secs. 13, 14, 23 and 24, which is a palo verde post, 4 ins. diam., 24 ins. above ground, set in an old mound of stone, The old post being badly weathered no scribe marks were discernible.</p> <p>In center of old mound, in place of the old post which is set alongside;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.</p> <div style="text-align: center;"> T5S R9W S14 S13 S23 S24 1934 : </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy loam; 2nd rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, sage, cactus and greasewood.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 5 S., R. 9 W., resurveyed under this group.</p> <p>N.89°06'W., on a true line bet. secs. 13 and 24.</p> <p>Over rolling ground, through scattering brush.</p>
24.60	Descend 90 ft. over W. slope.
34.00	Bottom of gulch, 30 lks. wide, course N.; asc. 40 ft.
39.46	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, which is a partially decayed palo verde post, 12 ins. long, 4 ins. diam., set in the center of an old mound of stone, No scribe marks were discernible on the old post.</p> <p>In center of old mound, in place of the old post which is set alongside;</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, over a cross (X), chiseled on surface of rock ledge,</p>

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 13 \\ S 24 \\ 1934 \end{array}$$

from which

An original bearing tree:

A palo verde tree, 8 ins. diam., bears S.68°E., 140 lks. dist., mkd. XIII.

Thence

N.89°16'W., on a true line, bet. secs. 13 and 24.

Ascend 40 ft. over E. slope.

2.20 Top of ascent; thence over rolling ground.

12.20 Head of wash, course NW.

34.90 Wash, 15 lks. wide, course N.

39.70 The cor. of secs. 13, 14, 23 and 24.

Land, rolling.

Soil, sandy and rocky; 3rd rate.

Timber, scattering palo verde, mesquite and ironwood; undergrowth, cactus and greasewood.

Thence

N.0°34'W., on a true line bet. secs. 13 and 14.

Over rolling land, through scattering undergrowth.

4.80 Road, bears NE. and SW.; desc. 23 ft.

15.00 Thence along broken E. slope.

40.29 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S14 | S13 \\ 1934 \end{array}$$

raise a mound

of stone, 4 ft. base, 3 ft. high, W. of cor.

65.00 Wash, 10 lks. wide, course NE.

80.58 The cor. of secs. 11, 12, 13 and 14, which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, sandy loam; 2nd rate.

Timber, scattering pale verde, mesquite and ironwood; undergrowth, cactus, sage and greasewood.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 5 S., R. 9 W., resurveyed under this group.

N.87°12'W., on a true line bet. secs. 12 and 13.

Dependent Resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	Over level river bottom, through dense mesquite trees.
20.00	Desc, 105 ft. over rocky W. slope.
39.92	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, which is the decayed remains of an old post, 2 ins. in diam., 4 ins. long set alongside of a stone, 24x10x10 ins. above ground. In place of the decayed end of post and old stone, both of which were set alongside; Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S } 12 \\ \text{S } 13 \\ 1934 \end{array}$ raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor. Thence S.89°11'W., on a true line bet, secs. 12 and 13.
3.75	Fence, bears N. and S.
14.90	Road, bears N.15°E. and S.15°W.
35.00	Wash, 20 lks. wide, course N.
39.96	The cor. of secs. 11,12,13 and 14. Land, level. Soil, sandy; 3rd rate. Timber, mesquite; undergrowth, cactus and sage.

	Thence North, on a true line bet. secs. 11 and 12. Over level ground, through mesquite timber.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, which is an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record. Thence N.0°11'E., on a true line bet. secs. 11 and 12.
20.00	Thence over sandy river bed.
28.00	Water hole in main channel of Gila River, 1 ch. wide, course W.
34.00	Leave sandy bed of river; continue over bottom land.
40.05	At this point determined by double proportion; Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a deposit of glass at base, for cor. of secs. 1,2,11 and 12, with brass cap mkd. $\begin{array}{r} \text{S5S R9W} \\ \text{S2} \text{S1} \\ \text{S11} \text{S12} \\ 1934 \end{array}$ No suitable accessory.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

4080

chains	Land, level. Soil, sandy; 2nd rate. Timber, mesquite; undergrowth, sage and arrow weed.
39.74	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 5 S., R. 9 W., resurveyed under this group. N. 89° 01' W., on a true line bet. secs. 1 and 12. Over level river bottom, through dense brush. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a deposit of broken glass at base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S1}{S12}$ 1934 No suitable accessory.
79.48	The cor. of secs. 1, 2, 11 and 12. Land, level. Soil, sandy; 2nd rate. Timber, mesquite; undergrowth arrow weed and sage.
37.50	Thence N. 0° 40' W., on a true line bet. secs. 1 and 2. Over level river bottom, through dense brush.
40.05	Leave river bottom; thence over rolling ground. The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, which is an iron post, 1 in. in diam., set, mkd. and witnessed as described in the official record. Thence N. 0° 05' W., on a true line bet. secs. 1 and 2.
14.25	Ravine, course SE.
27.25	Wash, 30 lks. wide, course SE.
40.26	The cor. of secs. 1, 2, 35 and 36, Tps. 4 and 5 S., R. 9 W., which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record. Land, level and rolling. Soil, sandy; 2nd rate. Timber, mesquite and ironwood; undergrowth, arrow weed, sage and cactus.
41.52	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., described in the field notes of the 1st. Stan. Par. through R. 9 W., resurveyed under this group. N. 0° 20' E., on a true line bet. secs. 34 and 35. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

$$\begin{array}{c} \frac{1}{4} \\ \hline S34 | S35 \\ \hline 1934 \end{array}$$

from which

A palo verde, 8 ins. diam., bears S.13°E., 164 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

A palo verde, 8 ins. diam., bears N.26°W., 193 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

83.04

The cor. of secs. 26, 27, 34 and 35, which is a partially decayed palo verde post, $\frac{3}{8}$ ins. diam., 12 ins. long, set in an old mound of stone. No marks were discernible on the decayed end of old post.

In the center of the old mound and in place of old post which is set alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone to top, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

$$\begin{array}{c} T5S R9W \\ \hline S27 | S26 \\ \hline S34 | S35 \\ \hline 1934 \end{array}$$

from which

An original bearing tree:

A palo verde, 12 ins. diam., bears S.29 $\frac{1}{2}$ °E., 253 lks. dist., with discernible but illegible markings. I remark this tree as follows: T 5 S R 9 W S 35 B T.

And a new bearing tree:

A palo verde, 8 ins. diam., bears N.50°E., 184 lks. dist., mkd. T 5 S R 9 W S 26 B T.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, scattering palo verde and mesquite; undergrowth, sage, cactus and greasewood.

From the cor. of secs. 25, 26, 35 and 36, hereinbefore described.

N.88°47'W., on a true line bet. secs. 26 and 35.

Over rolling ground, through scattering brush.

40.20

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} S26 \\ \hline \frac{1}{4} \\ \hline S35 \\ \hline 1934 \end{array}$$

raise a mound

of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

80.39

The cor. of secs. 26, 27, 34 and 35.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

chains	<p>Land, rolling. Soil, sandy; 2nd rate. Timber, scattering mesquite and palo verde; undergrowth, sage, greasewood and cactus.</p>
40.21	<p>Thence N.0°13'W., on a true line bet. secs. 26 and 27. Over rolling ground, through scattered brush. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \hline S27 S26 \\ 1934 \end{array}$ </div>
43.70	<p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, W. of cor. Road, bears NE. and SW.</p>
80.42	<p>The cor. of secs. 22, 23, 26 and 27, which is the remaining end of a partially decayed post in center of old mound of stone. In the center of old mound, with decayed end of old post set alongside; Set an iron post, $\frac{1}{2}$ ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross (X), de- posited at base, in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T5S R9W \\ \hline S22 S23 \\ \hline S27 S26 \\ 1934 \end{array}$ </div>
2.00	<p>Land, rolling. Soil, sandy; 2nd rate. Timber, none; undergrowth, greasewood and cactus.</p>
40.26	<p>From the cor. of secs. 23, 24, 25 and 26, hereinbefore describ- ed. N. 89°03'W., on a true line bet. secs. 23 and 26. Over rolling ground, through scattered brush. Wash, 10 lks. wide, course NE. The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, which is an old mound of stone with traces of decayed wooden post in center. In the center of old mound; Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} S 23 \\ \hline S 26 \\ 1934 \end{array}$ </div>
	<p style="text-align: right;">from which</p> <p>An original bearing tree: A palo verde, 6 ins. diam., bears N.40°E., 63 lks. dist., mks. illegible.</p>

Dependent resurvey of the subdivisions of

T. 5 S., R. 9 W.,

chains	<p>And new bearing trees:</p> <p>A palo verde, 8 ins. diam., bears N.52°E., 64 lks. dist. mkd. $\frac{1}{4}$ S 23 B T.</p> <p>A palo verde, 8 ins. diam., bears S.30°W., 153 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.</p> <p>Thence</p> <p>N.89°00'W., on a true line bet. secs. 23 and 26.</p> <p>26.00 Old road, bears NE. and SW.</p> <p>40.25 The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sandy loam.; 2nd rate. Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.</p> <hr/> <p>Thence</p> <p>N.0°14'E., on a true line bet. secs. 22 and 23.</p> <p>Over rolling ground, through scattered brush.</p> <p>40.93 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S22 S23 1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, W. of cor.</p> <p>81.86 The cor. of secs. 14, 15, 22 and 23, which is a palo verde post, 4 ins. diam., 3 ft. above ground, set in an old mound of stone,</p> <p>In the center of the old mound and in place of the old post which is set alongside;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone to top, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W S15 S14 S22 S23 1934</p> <p style="text-align: right;">from which</p> <p>The original bearing trees:</p> <p>A palo verde tree, 6 ins. diam., bears N.62°W., 70 lks. dist., with illegible markings. I remark this tree as follows: T 5 S R 9 W S 15 B T.</p> <p>A dead palo verde tree, 6 ins. diam., bears S.23°E., 187 lks. dist., with illegible markings.</p> <p>Land, rolling. Soil, sandy; 2nd rate. Timber, scattering palo verde; undergrowth, sage, greasewood and cactus.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24, hereinbefore described.</p> <p>N.88°05'W., on a true line bet. secs. 14 and 23.</p>
--------	---

Dependent resurvey of subdivisions of

T. 5 S., R 9 W.

chains	Over rolling ground through scattering brush.
13.40	Road, bears NE. and SW.
37.90	Old road, bears N. and S.
40.03	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, which is the partially decayed end of a palo verde post, 4 ins. in diam., 5 ins. above ground, set in the center of an old mound of stone. In the center of the old mound, in place of decayed end of old post, which is set alongside; Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 14 S 23 1934 raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor. Thence S.89°42'W., on a true line bet. secs. 14 and 23.
40.45	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sandy; 2nd rate. Timber, none; undergrowth, sage, cactus and greasewood.
	Thence N.0°09'W., on a true line bet. secs. 14 and 15. Over rolling ground, through scattered undergrowth.
35.10	Road, bears E. and W.
40.18	Set an iron post, 3 ft. long, 1 in. diam., over a cross (X) chiseled on the surface of a rock ledge, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S15 S14 1934
44.00	Wash, 110 lks. wide, course NW.
65.00	Enter same wash, course N. from S.10°W.
68.00	Leave wash, course N.10°W.
80.36	The cor. of secs. 10, 11, 14 and 15, which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record. Land, rolling. Soil, sandy; 2nd rate. Timber, scattering mesquite, palo verde, and ironwood; undergrowth, sage, cactus and greasewood.
	From the cor. of secs. 11, 12, 13 and 14, hereinbefore described. N.89°16'W., on a true line bet. secs. 11 and 14. Over rolling ground, through scattering undergrowth.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	
5.00	Ascend 86 ft. over rocky E. slope.
22.50	Thence over W.slope, desc. 74 ft.
28.80	Wash, 40 lks. wide, course N.; ascend 68 ft. over E. slope.
39.84	The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, which is an iron post, 1 in. diam., set mkd. and witnessed as described in the official record.
	Thence
	N.89°19'W., on a true line bet. secs. 11 and 14.
2.50	Ravine, course N.
6.00	Oatman Monument road, bears NE. and SW.
39.85	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling. Soil, sandy; 2nd rate. Timber, scattering mesquite, palo verde and ironwood; undergrowth, sage, cactus and greasewood.
	Thence
	N.0°03'W., on a true line bet. secs. 10 and 11.
	Over rolling ground, through scattering undergrowth.
3.50	Desc. 60 ft. over NW. slope.
8.50	Thence along sandy river bar.
40.18	The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, which is an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.
	Thence
	N.0°12'W., on a true line bet. secs. 10 and 11.
.50	Ascend 30 ft.
2.50	Descend 30 ft. over NE. slope.
4.00	Thence over sandy river bed.
6.00	Enter Gila River channel, 150 lks. wide, course W.
27.00	Leave river bottom; ascend 83 ft. over SE. slope.
37.30	Ravine, 100 lks. wide, course SE.
40.45	The cor. of secs. 2, 3, 10 and 11, which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, sandy; 2nd rate. Timber, scattering palo verde; undergrowth, sage, cactus and mesquite.
	From the cor. of secs. 1, 2, 11 and 12, hereinbefore described.
	N.89°05'W., on a true line bet. secs. 2 and 11.
	Over level river bottom, through undergrowth.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

chains	
16.00	Leave river bottom land; ascend 118 ft. over SE. slope.
20.50	Thence over rolling ground.
39.94	The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, which is an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.
	Thence
	N.89°04'W., on a true line bet. secs. 2 and 11.
16.00	Wash, 50 lks. wide, course SW.
33.00	Wash, 20 lks. wide, course S.
36.10	Wash, 30 lks. wide, course S.
40.03	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling. Soil, sandy; 2nd rate. Timber, mesquite, iron wood and palo verde; undergrowth, sage, greasewood and arrowweed.

	Thence
	N.0°10'W., on a true line bet. secs. 2 and 3.
	Over rolling ground through scattering undergrowth.
40.26	The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, which is a partially decayed wooden post, 4 ins. diam., 16 ins. long, with all mks. weathered away, and set in an old mound of stone.
	In the center of the old mound, in place of the decayed post which is set alongside;
	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S3 S2 1934
	Thence
	N.0°05'W., on a true line, bet. secs. 2 and 3.
18.40	Old road, bears E. and W.
39.93	The cor. of secs. 2 and 3, which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, sandy; 2nd rate. Timber, scattering palo verde; undergrowth, sage, greasewood and cactus.

	From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., described in the field notes of the 1st. Stan. Par. S., through R. 9 W., resurveyed under this group.
	N.0°04'E., on a true line bet. secs. 33 and 34.
	Over rolling ground, through scattering undergrowth.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains
40.58

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a deposit of glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4}$$

S33	S34
1934	

81.15

The cor. of secs. 27, 28, 33 and 34, which is a mound of stone.

In the center of the old mound of stone;

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

T5S	R9W
S28	S27

S33	S34
1934	

from which

An original bearing tree:

A palo verde, 10 ins. diam., bears S.26°E., 232 lks. dist., mkd. T V S R IX W SXXXIV B T.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.

From the cor. of secs. 26, 27, 34 and 35, hereinbefore described.

S.89°26'W., on a true line bet. secs. 27 and 34.

Over rolling ground, through scattering undergrowth.

18.90

Road, bears N. and S.

25.30

Wash, 20 lks. wide, course N. 15°W.

40.22

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4}$$

S	27
S	34
1934	

from which

A palo verde, 14 ins. diam., bears S.63°E., 149 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

A palo verde, 8 ins. diam., bears N.11°E., 254 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.

80.44

The cor. of secs. 27, 28, 33 and 34.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.

Thence

N.0°26'E., on a true line bet. secs. 27 and 28.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

Over rolling ground, through scattering undergrowth.

42.00

The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, which is a partially decayed palo verde post, 3 ins. diam., 24 ins. long, with all scribe mks. weathered away, set in an old mound of stone.

In the center of the old mound of stone, in place of the old post which is set along side;

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a deposit of glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S28} \mid \text{S27} \\ \hline 1934 \end{array}$$

Thence

N.0°12'W., on a true line bet. secs. 27 and 28.

40.79

The cor. of secs. 21, 22, 27 and 28, which is the remaining end of a partially decayed palo verde post, 3 ins. diam., 12 ins. above ground, set in an old mound of stone.

In the center of the old mound, with the decayed end of old post set alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

$$\begin{array}{c} \text{T5S R9W} \\ \hline \text{S21} \mid \text{S22} \\ \hline \text{S28} \mid \text{S27} \\ \hline 1934 \end{array}$$

of stone, 3 ft. base, 2 ft. high, W. of cor. raise a mound

Land, rolling.

Soil, sandy; 2nd rate.

Timber scattering palo verde; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 22, 23, 26 and 27, hereinbefore described.

N.88°54'W., on a true line bet. secs. 22 and 27.

Over rolling ground, through scattering undergrowth.

40.01

Set an iron post 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, over a cross (X), chiseled on rock surface, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S } 22 \\ \hline \text{S } 27 \\ \hline 1934 \end{array}$$

80.02

The cor. of secs. 21, 22, 27 and 28.

Land rolling.

Soil, sandy; 2nd rate.

Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.

North, on a true line bet. secs. 21 and 22.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

Over rolling ground, through scattering undergrowth.

41.16

The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, which is a decayed portion of a palo verde post, in the center of an old mound stone. Two dead and fallen trees, while without discernible markings were recognized as old bearing trees.

In the center of the old mound of stone, in place of the decayed portion of the palo verde post which is set along side;

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a deposit of glass at base, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor., with brass cap mkd.

| $\frac{1}{4}$
S21 | S22
1934

Thence

N.0°04'W., on a true line bet. secs. 21 and 22.

40.35

The cor. of secs. 15, 16, 21 and 22, which is an old mound of stone, with decayed pieces of the old palo verde post in the center,

In the center of this old mound of stone;

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with a stone mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

| T5S R9W
S16 | S15
S21 | S22
1934

from which

An original bearing tree:

A dead and fallen palo verde, 8 ins. diam., bears N.18° E., 164 lks. dist. No scribe marks are legible on this old bearing tree.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.

From the cor. of secs. 14, 15, 22 and 23, hereinbefore described.

N.89°12'W., on a true line bet. secs. 15 and 22.

Over rolling ground, through scattering undergrowth.

40.22

The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, which is an old mound of stone with traces of the decayed post in the center,

In the center of the old mound of stone;

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, over a cross (X), chiseled on rock surface, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

| S 15
 $\frac{1}{4}$ S 22
1934

from which

Dependent resurvey of subdivisions of

T. 5 S., R 9 W.

BOOK 4000

chains

An original bearing tree:

A dead palo verde 6 ins.diam., bears S.44°E., 239 lks. dist., marks illegible.

Thence

N.89°15'W., on a true line bet. secs. 15 and 22.

40.22 The cor. of secs. 15,16,21 and 22.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.

Thence

N.0°05'W., on a true line bet. secs. 15 and 16.

Over rolling ground, through scattering undergrowth.

40.22 The 1/4 sec. cor. of secs. 15 and 16, which is the decayed remains of a palo verde post, in an old mound of stone.

In the center of the old mound, in place of the decayed portion of old post which is set alongside;

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4
S15 | S16
1934

from which

An original bearing tree:

A palo verde, 8 ins. diam., bears N.48°W., 130 lks. dist. The markings on tree are illegible. I remark this tree as follows: 1/4 S 15 B T.

Thence

N.0°05'W., on a true line bet. secs. 15 and 16.

40.18 The cor. of secs. 9,10,15 and 16, which is the decayed remains of a palo verde post, 3 ins. diam., 12 ins. above ground, in an old mound of stone.

In the center of the old mound, and in place of the decayed portion of the old post;

Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 9,10,15 and 16, with brass cap mkd.

T5S R9W
S9 | S10
S16 | S15
1934

from which

An original bearing tree:

A palo verde, 10 ins. in diam., bears south, 130 lks. dist., mkd. S. XV.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	Land rolling. Soil, rocky; 3rd rate. Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.

	From the cor. of secs. 10, 11, 14 and 15, hereinbefore described.
	N. 89° 12' W., on a true line bet. secs. 10 and 15.
	Over rolling ground, through scattering timber.
1.00	Descend 92 ft. over NW. slope through scattering undergrowth.
5.00	Thence over sandy river bed.
21.00	Enter Gila River channel, course NW.
30.00	Leave river channel, course NW.; asc. 132 ft. over NE. slope.
40.00	Thence over rolling ground.
40.23	Proportionate dist.; point for $\frac{1}{4}$ sec. cor.
42.34	The witness $\frac{1}{4}$ sec. cor. of secs. 10 and 15, which is the decayed remains of a palo verde post, 3 ins. diam., 12 ins. long in a mound of stone.
	In the center of the old mound of stone, in place of the decayed portion of post which is set alongside;
	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \\ \text{WC } \frac{1}{4} \text{ S } 10 \\ \quad \quad \quad \text{S } 15 \\ \quad \quad \quad 1934 \end{array}$
	Thence
	N. 89° 00' W., on a true line, bet. secs. 10 and 15.
18.00	Road, bears NW. and SE.
37.96	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, sandy; 2nd rate. Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.

	Thence
	N. 0° 12' W., on a true line bet. secs. 9 and 10.
	Over rolling ground, through scattering undergrowth.
8.40	Road, bears NE. and SW.
20.00	Descend 74 ft. over NW. slope.
28.80	Enter bottom land.
40.15	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a deposit of broken glass at base, and with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ \text{S9} \text{S10} \\ 1934 \end{array}$
	from which

Dependent resurvey of subdivisions of

19

T. 5 S., R. 9 W.

BOOK 4080

chains	A palo verde, 6 ins. diam., bears west, 134 lks. dist. mkd. $\frac{1}{4}$ S 10 B T.
45.00	Cross sandy river bar.
54.00	Main channel of the Gila River, 150 lks. wide, course W.
58.70	Leave river bottom; ascend 60 ft. over S. slope.
60.00	Thence over rolling ground.
80.30	The cor. of secs. 3, 4, 9 and 10, which is a partially decayed palo verde post, 3 ins. diam., 12 ins. long, in an old mound of stone. In the center of the old mound of stone, in place of the decayed portion of the old post which is set alongside; Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a deposit of glass at base, and in a mound of stone to top, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd. <div style="text-align: center;"> T5S R9W S4 S3 S9 S10 1934 </div>
	from which
	An original bearing tree: A dead palo verde tree, 6 ins. diam., bears N.75°W., 127 lks. dist. All marks are weathered away. Land, rolling. Soil, sandy; 2nd rate. Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.
	----- From the cor. of secs. 2, 3, 10 and 11, hereinbefore described, N.89°18'W., on a true line, bet. secs. 3 and 10. Over level ground, through scattering undergrowth.
1.00	Ravine, course SE.
16.00	Ravine, course S.
40.23	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross(X), deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> $\frac{1}{4}$ $\frac{S}{S}$ $\frac{3}{10}$ 1934 </div>
80.47	The cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, sandy; 3rd rate. Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.
	----- Thence N.0°01'W., on a true line bet. secs. 3 and 4.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

- | | |
|--------|---|
| chains | Over rolling ground, through scattering undergrowth. |
| 40.17 | <p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, which is a mound of stone.</p> <p>In the center of the old mound of stone;</p> <p>Set an iron post, 3 ft. long, 1 in. diam., over a cross (X) chiseled on the surface of a rock ledge, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$
S4 S3
1934</p> <p style="text-align: right;">from which</p> <p>The original bearing trees:</p> <p>A palo verde, 10 ins. diam., bears N.30°E., 145 lks. dist., mkd. $\frac{1}{4}$ S III B T.</p> <p>A dead palo verde, bears N.40°W., 277 lks. dist., mks. illegible.</p> <p>Thence</p> <p>N.0°06'W., on a true line bet. secs. 3 and 4.</p> |
| 20.00 | Road, bears E. and W. |
| 40.20 | <p>The cor. of secs. 3, 4, 33 and 34, Tps. 5 and 6 S., R. 9 W., which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>Land, rolling.</p> <p>Soil, sandy and rocky; 3rd rate.</p> <p>Timber, scattering palo verde.</p> <p>Undergrowth sage, cactus and greasewood.</p> |
| 40.88 | <p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., described in the field notes of the 1st. Stan. Par. S., through R. 9 W., resurveyed under this group.</p> <p>N.0°21'W., on a true line bet. secs. 32 and 33.</p> <p>Over rolling ground, through scattering undergrowth.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$
S32 S33
1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, W. of cor.</p> |
| 81.76 | <p>The cor. of secs. 28, 29, 32 and 33, which is a palo verde post, 3 ins. diam., 30 ins. above ground, badly weathered, with no legible scribe mks., set in an old mound of stone.</p> <p>In the center of old mound of stone, in place of the old post, which is set alongside;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.</p> |

Dependent resurvey of subdivisions of

BOOK 4080

T. 5 S., R. 9 W.

chains	T5S R9W S29 S28 S32 S33 1934
	<p>Land, rolling. Soil, sandy and rocky, 3rd rate. Timber, scattering mesquite and palo verde; undergrowth, sage and greasewood.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, hereinbefore described, N.88°06'W., on a true line bet. secs. 28 and 33. Over rolling ground, through scattering undergrowth.</p>
36.60	Old road, bears NE. and SW.
40.51	<p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, which is a palo verde post, 3 ins. diam., 24 ins. above ground, with no legible scribe marks, set in an old mound of stone.</p> <p>In the center of the old mound of stone, in place of the old post which is set alongside; Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bedrock, over a cross (X), chiseled on rock surface, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 28 S 33 1934</p> <p style="text-align: right;">from which</p> <p>The original bearing trees:</p> <p>A dead and fallen palo verde, 8 ins. diam., bears S.27° E., 232 lks. dist., mkd. $\frac{1}{4}$ S X.</p> <p>A mesquite stump, 6 ins. diam., bears N.15°E., 284 lks. dist., No marks are on this stump.</p> <p>And new bearing tree.</p> <p>A palo verde, 6 ins. diam., bears N.6°W., 145 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.</p> <p>Thence</p> <p>N.89°12'W., on a true line, bet. secs. 28 and 33.</p>
21.60	Old road, bears NE. and SW.
40.22	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, rocky and gravelly; 3rd rate. Timber, palo verde and mesquite; undergrowth, greasewood, sage and cactus.</p> <hr/> <p>Thence</p> <p>N.0°09'W., on a true line bet. secs. 28 and 29. Over rolling ground, through scattering undergrowth.</p>
40.77	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S29} | \text{S28} \\ \hline 1934 \end{array}$$

from which

A palo verde, 8 ins. diam., bears S. 5°E., 396 lks. dist., mkd. $\frac{1}{4}$ S 28 B.T.

Dig pits, 18x18x12, N. and S. of cor., 3 ft. dist.

81.54

The cor. of secs. 20, 21, 28 and 29, which is a palo verde post, 3 ins. diam., 24 ins. long, with all markings weathered away, and set in an old mound of stone.

In the center of the old mound of stone, in place of the old post, which is set alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

$$\begin{array}{c} \text{T5S R9W} \\ \hline \text{S20} | \text{S21} \\ \hline \text{S29} | \text{S28} \\ \hline 1934 \end{array}$$

Land, rolling.

Soil, rocky; 3rd rate.

Timber, palo verde and mesquite; undergrowth, sage, cactus and greasewood.

From the cor. of secs. 21, 22, 27 and 28, hereinbefore described,

N. 89° 35' W., on a true line, bet. secs. 21 and 28.

Over rolling ground, through scattering undergrowth.

22.80

Road, bears NW. and SE.

40.60

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a deposit of glass at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S } 21 \\ \hline \text{S } 28 \\ \hline 1934 \end{array}$$

dig pits

18x18x12 ins., N. and S. of cor., 3 ft. dist.

81.20

The cor. of secs. 20, 21, 28 and 29.

Land, rolling and broken.

Soil, rocky and gravelly; 3rd rate.

Timber, scattering mesquite and palo verde; undergrowth, greasewood, sage and cactus.

Thence

N. 0° 03' E., on a true line bet. secs. 20 and 21.

Over rolling ground, through scattering undergrowth.

40.73

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 400

chains	$\frac{1}{4}$ $\begin{array}{c c} \text{S20} & \text{S21} \\ \hline \end{array}$
	<p style="text-align: center;">1934</p> <p style="text-align: right;">from which</p>
	<p>A mesquite, 6 ins. diam., bears S.78°W., 77½ lks. dist., mkd. $\frac{1}{4}$ S 20 B T.</p>
	<p>A mesquite, 6 ins. diam., bears N.18°E., 22 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.</p>
43.80	Road, bears NW. and SE.
81.45	<p>A point determined by double proportion;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.</p>
	$\begin{array}{c c} \text{T5S R9W} & \\ \hline \text{S17} & \text{S16} \\ \hline \text{S20} & \text{S21} \\ \hline \end{array}$ <p style="text-align: center;">1934</p>
	<p>Land, rolling. Soil, sandy; 3rd rate. Timber, scattering palo verde and mesquite; undergrowth, sage, cactus and greasewood.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22, hereinbefore described,</p>
	<p>N.89°07'W., on a true line, bet. secs. 16 and 21.</p>
	<p>Over rolling ground, through scattering undergrowth.</p>
40.23	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, which is an old mound of stone with pieces of old decayed post in center.</p>
	<p>In the center of this old mound;</p>
	<p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross (X), deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	$\frac{1}{4} \begin{array}{c} \text{S 16} \\ \hline \text{S 21} \\ \hline \end{array}$ <p style="text-align: center;">1934</p>
	<p style="text-align: right;">from which</p>
	<p>The original bearing trees:</p>
	<p>A palo verde, 12 ins. indiam., bears N.58°W., 288 lks. dist., with illegible markings.</p>
	<p>A palo verde, 6 ins. diam., bears S.6°E., 215 lks. dist. with old blaze decayed away.</p>
	<p>Thence</p>
	<p>N.89°54'W., on a true line, bet. secs. 16 and 21.</p>
3.00	Old road, bears N. and S.
40.76	The cor. of secs. 16, 17, 20 and 21.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

Land rolling.
Soil, rocky; 3rd rate.
Timber, scattering mesquite and palo verde; undergrowth,
sage, greasewood, and cactus.

Thence

N.0°35'E., on a true line, bet. secs. 16 and 17.


Over rolling ground, through scattering undergrowth.

40.72

The 1/4 sec. cor. of secs. 16 and 17, which is a point determined by measuring the record courses and distances from the old bearing trees.

At this point;

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



from which

The original bearing trees:

A palo verde tree, 8 ins. diam., bears W. 296 lks. dist., with marks which are illegible. I remark this tree as follows: 1/4 S 17 B T.

A dead and fallen palo verde tree, bears N.38°W., 120 lks. dist., with illegible markings,

Dig pits, 18x18x12, N. and S. of cor., 3 ft. dist.

Thence


N.0°12'W., on a true line bet. secs. 16 and 17.

40.28

The cor. of secs. 8,9,16 and 17, which is a palo verde post, 3 ins. diam., 24 ins. long, with illegible markings and set in an old mound of stone.

In the center of the old mound, with the old post set alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 8,9,16 and 17, with brass cap mkd.



Land, rolling.
Soil, rocky; 3rd rate.
Timber, scattering palo verde; undergrowth, sage, cactus and greasewood.

From the cor. of secs. 9,10,15 and 16, hereinbefore described,

N.89°04'W., on a true line, bet. secs. 9 and 16.

Over rolling ground, through scattering undergrowth.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

c hains	
28.00	Old road, bears NE. and SW.
40.32	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \text{ S } 9 \\ \hline \text{S } 16 \\ 1934 \end{array}$
80.63	The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, sandy; 2nd rate. Timber, scattering mesquite and palo verde; undergrowth, sage, cactus and greasewood.

	Thence N.0°07'W., on a true line bet. secs. 8 and 9. Over rolling ground, through scattering undergrowth.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, which is a rock in place, 12x12x12 ins. above ground, mkd. with a cross on top and with a $\frac{1}{4}$ on W. face. Alongside of the old stone in place; Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S } 8 \text{ } \text{S } 9 \\ \hline 1934 \end{array}$

	Thence N.0°02'W., on a true line bet. secs. 8 and 9.
37.00	Enter Gila River channel, 2.50 chs. wide, course W.
40.22	At this point, determined by double proportion; Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a deposit of broken glass at base, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd. $\begin{array}{c} \text{T5S R9W} \\ \text{S5 S4} \\ \hline \text{S8 S9} \\ 1934 \end{array}$
	No suitable corner accessory. Land, rolling. Soil, sandy; 2nd rate. Timber, scattering mesquite, cottonwood and palo verde; undergrowth, greasewood and sage.

	From the cor. of secs. 3, 4, 9 and 10, hereinbefore described. N.89°04'W., on a true line bet. secs. 4 and 9. Over rolling ground, through brush.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	
17.00	Ravine, course S.10°E.
34.70	Desc. 37 ft. over SW. slope.
40.22	The true point for the $\frac{1}{4}$ sec. cor., on Gila River bank, where a corner would be insecure. At a point 50 lks. N.; Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a deposit of broken glass at base, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd. $W C \frac{1}{4} \frac{S 4}{S 9}$ 1934 from which A mesquite, 6 ins. diam., bears N.70°E., 26 lks. dist. mkd. $W C \frac{1}{4} S 4 B T$ A cross (X), followed by letters B O, chiseled on a rock, 20x15x10 ft., bears S., 30 lks. dist. Thence from true point for cor., ^{desc.} 50 ft. over SW. slope.
50.00	Thence across river bed in bend from NW. to SW.
75.00	Leave river bed; thence over bottom land.
80.44	The cor. of secs. 4, 5, 8 and 9. Land, rolling and level. Soil, sandy and rocky; 3rd rate. Timber, mesquite and palo verde. Undergrowth, greasewood, sage and cactus.
	Thence N.0°02'E., on a true line bet. secs. 4 and 5. Over rolling ground, through brush.
5.00	Leave river bottom; ascend 75 ft. over S. slope.
9.90	Thence over rolling rocky ground.
40.22	The $\frac{1}{2}$ sec. cor. of secs. 4 and 5, which is a blazed palo verde post, with illegible markings, 4 ins. diam., 24 ins. long, in an old mound of stone, In the center of the old mound, in place of the old post which is set alongside; Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a deposit of broken glass at base and in a mound of stone to top, for $\frac{1}{2}$ sec. cor., with brass cap mkd. $\frac{1}{2}$ S 5 S 4 1934
	Thence N.0°03'W., on a true line, bet. secs. 4 and 5.
25.00	Wash 200 lks. wide, course W.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

chains
40.20

The cor. of secs. 4, 5, 32 and 33, which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.
Soil, rocky and gravelly; 3rd rate.
Timber, palo verde and mesquite; undergrowth, greasewood and sage.

From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., described in the field notes of the 1st. Stan. Par. S., through R. 9 W., resurveyed under this group.

N.0°30'W., on a true line bet. secs. 31 and 32.

Over rolling ground, through scattering undergrowth.

40.90

Set an iron post, 3 ft. long, 1 in. diam.; 24 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 31 | S 32

1934

from which

A palo verde, 14 ins. diam., bears N.77°E., 75 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.

A palo verde, 12 ins. diam.; bears S.55°E., 18 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.

81.80

The cor. of secs. 29, 30, 31 and 32, which is a partially decayed palo verde post, 3 ins. diam., 18 ins. long, in an old mound of stone.

In the center of this old mound, in place of the old post which is set alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 3 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T5S R9W
S30 | S29
S31 | S32
1934

Land, rolling.
Soil, sandy and rocky; 3rd rate.
Timber, palo verde and mesquite; undergrowth, greasewood sage and cactus.

From the cor. of secs. 28, 29, 32 and 33, hereinbefore described;

N.89°06'W., on a true line bet. secs. 29 and 32.

Over rolling ground, through scattering undergrowth.

40.24

The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, which is a weathered blazed palo verde post, with illegible markings, set in an old mound of stone.

In the center of this old mound of stone, and with the old post set alongside;

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 29 S 32 1934 </p> <p style="text-align: right;">from which</p> <p>An original bearing tree;</p> <p>A dead palo verde, 8 ins. diam., ; bears S.70°E., 111 lks. dist. The scribe marks are not legible.</p> <p>Thence</p> <p>N.89°08'W., on a true line, bet. secs. 29 and 32.</p>
22.80	Wash, 30 lks. wide, course NW.
26.20	Wash, 20 lks. wide, course NW.
40.13	The cor. of secs. 29, 30, 31 and 32.
	<p>Land, rolling. Soil, sandy and rocky; 3rd rate. Timber, palo verde; undergrowth, greasewood, sage and cactus.</p> <hr/> <p>Thence</p> <p>N.88°34'W., on a true line bet. secs. 30 and 31.</p> <p>Over rolling ground, through scattering undergrowth.</p>
40.03	<p>Proportional distance;</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{2}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{2}$ S30 S31 1934 </p> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
79.88	<p>The cor. of secs. 25, 30, 31 and 36, described in the field notes of the dependent resurvey of the W. bdy. of T. 5 S. R. 9 W., resurveyed under this group.</p> <p>Land, rolling. Soil, rocky and gravelly; 3rd rate. Timber, palo verde and mesquite; undergrowth, greasewood and sage and cactus.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, hereinbefore described;</p> <p>N.0°17'W., on a true line bet. secs. 29 and 30.</p> <p>Over rolling ground, through scattering undergrowth.</p>
40.69	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, which is the decayed particles of an old post, in an old mound of stone.</p> <p>In the center of this old mound of stone;</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor., with brass</p>

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

chains

cap mkd.

$\frac{1}{4}$
 S30 | S29
 1934

from which

An original bearing tree: -----

A palo verde, dead, fallen and loose from ground, bears N.9°W., 230 lks. dist. The old blaze is discernible, but the markings have weathered away.

Thence

N.0°09'W., on a true line, bet. secs. 29 and 30.

40.72

The cor. of secs. 19, 20, 29 and 30, which is a palo verde post, 4 ins. diam., 28 ins. long, in an old mound of stone.

In the center of the old mound, in place of the old post which is set alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T5S R9W
 S19 | S20
 S30 | S29
 1934

An original bearing tree; -----

from which

A dead palo verde, 8 ins. diam., bears N.86°W., 197 lks. dist., mkd., T V S R IX W S XXX B T.

Land, rolling.

Soil, gravelly and rocky; 3rd rate.

Timber, palo verde; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 20, 21, 28 and 29, hereinbefore described;

N.89°16'W., on a true line, bet. secs. 20 and 29.

Over rolling ground, through scattering undergrowth.

40.25

The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, which is an old mound of stone with traces of the decayed old corner post in the center.

In the center of this old mound;

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S20
 S29
 1934

Thence

N.89°05'W., on a true line, bet. secs. 20 and 29.

24.00

Wash, 50 lks. wide, course NW.

31.80

Wash, 30 lks. wide, course NW.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	
40.18	The cor. of secs. 19, 20, 29 and 30. Land, rolling. Soil, gravelly and rocky; 3rd rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, greasewood, sage, cactus and ocotillo.

	Thence N. 88° 35' W., on a true line bet. secs. 19 and 30. Over rolling ground, through scattering undergrowth.
19.00	Wash, 30 lks. wide, course NW.
35.50	Descend 63 ft.
39.97	Proportional distance; Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ s } 19 \\ \hline \text{ s } 30 \\ 1934 \end{array}$
41.00	Wash, 50 lks. wide, course NW.; asc. 70 ft.
55.70	Wash, course NW.
63.50	Descend 52 ft. over gradual NW. slope.
73.40	Wash, 30 lks. wide, course NW.; asc. 40 ft.
75.60	Descend 34 ft.
78.80	Wash, 40 lks. wide, course NW., asc. 48 ft.
79.74	The cor. of secs. 19, 24, 25 and 30, Tp. 5 S., Rs. 9 and 10 W., which is an iron post, 2 ins. diam., described in the field notes of the W. bdy. of T. 5 S., R. 9 W., resurveyed under this group. Land, rolling. Soil, gravelly and rocky; 3rd rate. Timber, palo verde, mesquite and ironwood; undergrowth, cactus, greasewood and sage.

	From the cor. of secs. 19, 20, 29 and 30, hereinbefore described; N. 0° 27' E., on a true line bet. secs. 19 and 20. Over rolling ground, through scattering undergrowth.
41.05	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \\ 319 \text{ s } 20 \\ 1934 \end{array}$ raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
82.10	The cor. of secs. 17, 18, 19 and 20, which is the remaining end of a decayed post, in the center of an old mound of stone.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

chains

In the center of this old mound of stone, with end of old post set alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

T5S R9W

S18 | S17

S19 | S20

1934

from which

An original bearing tree;

A dead palo verde, 6 ins. diam., bears west, 65 lks. dist., with discernible, but illegible markings.

Land, rolling.

Soil, gravelly and rocky; 3rd rate.

Timber, palo verde and mesquite; undergrowth, greasewood sage and cactus.

From the cor. of secs. 16, 17, 20 and 21, hereinbefore described;

S.88°44'W., on a true line bet. secs. 17 and 20.

Over rolling ground, through scattering undergrowth.

15.50 Old road, bears NW. and SE.

27.40 Old road, bears N. and S.

40.82 The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, which is an old mound of stone, with traces of decayed post in the center.

In the center of this old mound;

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross (X), deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 17

S 20

1934

Thence

N.86°12'W., on a true line bet. secs. 17 and 20.

38.99 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood, cactus and sage.

Thence

N.89°11'W., on a true line bet. secs. 18 and 19.

Over rolling ground, through scattering undergrowth.

40.28 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, which is a weathered palo verde post, 4 ins. diam., 24 ins. above ground, bearing traces of old scribe marks.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains

In place of the old post which is set alongside;

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 18 \\ \hline \text{S } 19 \\ 1934 \end{array}$$

from which

An original bearing tree:

A palo verde, 6 ins. diam., bears S.37°E., 237 lks. dist., mkd. $\frac{1}{4}$ S.

Thence

N.89°08'W., on a true line bet. secs. 18 and 19.

Descend 60 ft. over NW.slope.

7.00 Thence over bottom land.

40.07 The cor. of secs. 13,18,19 and 24, which is an iron post, 2 ins. diam., described in the field notes of the W. bdy. of T. 5 S., R. 9 W., resurveyed under this group.

Land, rolling.

Soil, sandy; 2nd rate.

Timber, scattering mesquite and palo verde; undergrowth, greasewood, cactus and sage.

From the cor. of secs. 17,18,19 and 20, hereinbefore described.

N.0°10'W., on a true line bet. secs. 17 and 18.

Over rolling ground, through scattering undergrowth.

19.00 Desc. 34 ft. over SW. slope.

21.50 Wash, 30 lks. wide, course NE.

36.00 Desc. 56 ft. over NW. slope.

37.50 Wash, 40 lks. wide, course NE.

40.01 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, which is an old mound of stone, with decayed pieces of the old corner post in the center.

In the center of this old mound of stone;

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \hline \text{S } 18 \text{ | } \text{S } 17 \\ 1934 \end{array}$$

from which

An original bearing tree;

A dead palo verde tree, 8 ins. diam., bears S.63°E., 64 lks. dist. The weathered blaze on this tree shows illegible scribe marks.

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

BOOK 4080

chains	Thence						
	N.0°39'W., on a true line bet. secs. 17 and 18.						
11.20	Wash, 50 lks. wide, course NE.; asc. 88 ft. over NE. slope.						
21.20	Descend 96 ft. over SW. slope.						
23.60	Old irrigation canal, 20 lks. wide, course S.70°W.						
31.00	Enter bottom land.						
✓ 40.26	A point determined by double proportion; Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a deposit of broken glass at base, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>T5S</td><td>R9W</td></tr> <tr><td>S7</td><td>S8</td></tr> <tr><td>S18</td><td>S17</td></tr> </table> <p>1934</p> </div> <div style="text-align: right;">from which</div> A cottonwood, 16 ins. diam., bears N.74°E., 257 lks. dist., mkd. T 5 S R 9 W S 8 B T. Land, rolling. Soil, rocky and gravelly; 3rd rate. Timber, scattering palo verde, mesquite and cottonwood; undergrowth, greasewood, sage and cactus.	T5S	R9W	S7	S8	S18	S17
T5S	R9W						
S7	S8						
S18	S17						

	From the cor. of secs. 8, 9, 16 and 17, hereinbefore described; N.89°14'W., on a true line bet. secs. 8 and 17. Over rolling ground, through scattering undergrowth.						
✓ 40.25	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with a deposit of broken glass at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>$\frac{1}{4}$</td><td>S8</td></tr> <tr><td></td><td>S17</td></tr> </table> <p>1934</p> </div>	$\frac{1}{4}$	S8		S17		
$\frac{1}{4}$	S8						
	S17						
44.00	Wash, 30 lks. wide, course NW.						
61.50	Descend 110 ft. over NW. slope.						
67.00	Old irrigation canal, 20 lks. wide, course SW.						
67.50	Foot of slope; thence over bottom land.						
80.49	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, rocky and sandy; 2nd and 3rd rate. Timber, palo verde, mesquite and cottonwood; undergrowth, greasewood, arrow weed, sage and cactus.						

	Thence						
	N.88°56'W., on a true line bet. secs. 7 and 18. Over level, sandy bottom ground, through dense brush						
✓ 40.17	Proportional distance;						

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a deposit of broken glass at base, for $\frac{1}{4}$ sec. cor. of secs. 7 and 18, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \text{ S } 7 \\ \hline \text{S } 18 \\ 1934 \end{array}$ </p>
64.00	Main channel of the Gila River, 200 lks. wide, course SW.
65.00	At a point approximately 12 ins. south, and along north wall of cliff are numerous excellent Indian inscriptions and pictures.
80.23	<p>The cor. of secs. 7, 12, 13 and 18, which is an iron post, 2 ins. diam., described in the field notes of the W. bdy. of T. 5 S., R. 9 W., resurveyed under this group.</p> <p>Land, rolling and level. Soil, sandy; 2nd rate. Timber, cottonwood and mesquite; undergrowth, arrow weed and willow.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 7, 8, 17 and 18, hereinbefore described;</p> <p>N.0°09'W., on a true line bet. secs. 7 and 8.</p> <p>Over level ground, through dense undergrowth.</p>
40.27	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a deposit of broken glass at base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \\ \text{S } 7 \text{ } \text{S } 8 \\ \hline 1934 \end{array}$ </p>
58.00	Thence over sandy river bed.
62.00	Main channel of the Gila River, 3 chs. wide, course W.
75.00	Right bank of Gila River, bears E. and W.
80.53	<p>The cor. of secs. 5, 6, 7 and 8, which is the remaining end of a decayed post in an old mound of stone.</p> <p>In the center of this old mound of stone;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a deposit of broken glass at base, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} \text{T5S R9W} \\ \hline \text{S6 S5} \\ \hline \text{S7 S8} \\ 1934 \end{array}$ </p> <p style="text-align: right;">from which</p> <p>An original bearing tree:</p> <p style="padding-left: 40px;">A dead mesquite, 6 ins. diam., blazed but without discernible markings, bears north, 79 lks. dist.,</p> <p>Land, rolling. Soil, sandy and rocky; 2nd and 3rd rate. Timber, cottonwood, mesquite and palo verde; undergrowth, greasewood, sage and arrow weed.</p>

Dependent resurvey of subdivisions of BOOK 4080

T. 5 S., R. 9 W.

chains From the cor. of secs. 4, 5, 8 and 9, hereinbefore described,
N.89°01'W., on a true line bet. secs. 5 and 8.
Over level river bottom, through dense brush.
3.50 Enter Gila River channel, course NW., small stream of water.
4.50 Left bank of channel; thence over dry sandy river bed.
15.00 Enter Gila River channel, course SW.
16.70 Right bank of river channel; thence along sandy river bar.
40.29 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with a deposit of broken glass at base, for $\frac{1}{4}$ sec.
cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 5 \\ \hline \text{S } 8 \\ 1934 \end{array}$$

No suitable corner accessory.

56.00 Leave river bottom; ascend 23 ft. over SE. slope.

80.58 The cor. of secs. 5, 6, 7 and 8.

Land, rolling and level.

Soil, sandy and rocky; 2nd and 3rd rate.

Timber, mesquite, cottonwood and palo verde; undergrowth,
greasewood, sage, arrow weed and cactus.

Thence

N.88°42'W., on a true line bet. secs. 6 and 7.

Over rolling ground, through scattering undergrowth.

40.68 Proportional dist;

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with a deposit of broken glass at base, for $\frac{1}{4}$ sec.
cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \text{ S } 6 \\ \hline \text{S } 7 \\ 1934 \end{array}$$
81.03 The cor. of secs. 1, 6, 7 and 12, which is an iron post,
2 ins. diam., described in the field notes of the W. bdy.
of T. 5 S., R. 9 W., resurveyed under this group.

Land, rolling.

Soil, sandy and rocky; 2nd rate.

Timber, scattering mesquite and palo verde; undergrowth,
sage, catclaw and cactus.

From the cor. of secs. 5, 6, 7 and 8, hereinbefore described,

North, on a true line bet. secs. 5 and 6.

Over rolling ground, through scattering undergrowth.

40.22 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, which is the remaining
end of a decayed palo verde post, 3 ins. diam., set in an
old mound of stone.

In the center of this old mound of stone, in place of the

Dependent resurvey of subdivisions of

T. 5 S., R. 9 W.

chains	<p>decayed end of old post, which is set alongside;</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a deposit of broken glass at base, for $\frac{1}{4}$ sec. cor. of secs. 5 and 6, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S6 S5 1934</p> <p style="text-align: right;">from which</p> <p>An original bearing tree:</p> <p style="padding-left: 40px;">An iron wood, 14 ins. diam., bears S.32°E., 180 lks. dist., mkd. $\frac{1}{4}$ S 5. I add to these marks the letters BT.</p> <p>Thence</p> <p>N.0°03'W., on a true line bet. secs. 5 and 6.</p> <p>20.50 Wash, 30 lks. wide, course N.70°W.</p> <p>31.90 Wash, 200 lks. wide, course SW.</p> <p>40.19 The cor. of secs. 5 and 6, Tp. 5 S., R.9 W., which is an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>Land, rolling. Soil, sandy and rocky; 3rd rate. Timber, mesquite, palo verde and ironwood; undergrowth, greasewood, sage and cactus.</p> <hr/> <p>None of the corners purported to have been established at the intersection with the Gila River was found. As the river was not meandered at the time of the original survey, and is not a meanderable stream, no attempt was made to re-establish these corners.</p> <hr/> <p style="text-align: center;">General Description</p> <p>The center of this township is situated about nine miles northeast of the town of Sentinel, Arizona. The general elevation is about 550 ft. above sea level, excepting along the Gila River bottom, where it is about 100 ft. lower. The land surface is fairly level, except where it breaks from the upland to the river bottoms. The soil of the upland is sandy and gravelly with frequent outcroppings of lava rock. The bottom land is generally sandy.</p> <p>The Gila River enters the township near the northeast cor. of sec. 12, flows in a general westerly direction, and leaves, near the northwest cor. of sec. 18, The river channel is seldom more than three chains wide, At times of high water, much of the bottom land is overflowed and the river frequently changes its channel. The river bottoms vary in width from twenty to eighty chains.</p> <p>The vegetation consists of scattered growths of palo verde, ironwood, mesquite and cottonwood trees; sage, greasewood, catsclaw and arrow weed; saguaro cactus and numerous other species of small cactus. The cottonwood trees and arrow weeds are found only along the river bottom.</p> <p>One settler lives near the northeast corner of the township in section 1. His improvements consists of a small house, some fencing and a well, about 30 ft. deep. This well furnishes fair drinking water.</p> <p>A dirt road from Agua Caliente to Phoenix, runs in an east and west direction through the northern portion of the township. Another old road leading to Sentinel, crosses the township in a northeast and southwest direction.</p>
--------	---

Dependent resurvey of subdivisions of

BOOK 4080

T. 5 S., R. 9 W.

Along the cliff walls on the south side of the Gila River, about 25 chains west and 10 chains south of the $\frac{1}{4}$ section corner of sections 7 and 18, extending for a distance of a quarter of a mile, are numerous well preserved Indian hieroglyphics. The profile of thunder birds, deer, ducks, lizards, suns, moons, comets and other prehistoric Indian pictures may be clearly seen on the smooth face of rocks. The rocks bearing these pictures vary in size from 2 by 2 ft. to 7 by 10 ft.

No mineral deposits were observed in the township.

39
192
BOOK 4080

CERTIFICATE OF UNITED STATES SURVEYOR

We, William Merry Heina,
Daniel M. Wier, and
Jess R. Horak, U. S. Transitmen

hereby certify upon honor that, in pursuance
of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934, we

in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, ~~surveyed all these parts or portions of~~

lines of township 5 South, Range 9 West

of the Gila and Salt
River Meridian, in the State of Arizona

which are represented in
the foregoing field notes as having been executed by us, and under our direction; and that all the corners of
said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-
tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of
such survey.

Sentinel, Arizona,
March 23, 1934.

William Merry Heina
U. S. Transitman

APPROVAL

For signatures of
Daniel M. Wier, and
Jess R. Horak, see the
attached certificates.

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

19

The foregoing field notes of the survey of

executed by
under his special instructions dated, 19, having been
critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys
they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in
, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680
(August, 1920)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Niel Greenhaw	Principal assistant
John H. Bronson	Chainman
Daniel B. Elkins	Field Assistant
Earnest Cooley	Field Assistant
M. E. Hydock	Field Assistant
Dawson Cooley	Field Assistant
L. V. Trosper	Field Assistant

41
194
BOOK 4080

CERTIFICATE OF UNITED STATES SURVEYOR

We, William Merry Heina,
Daniel M. Wier, and
Jess R. Horak, U. S. Transitman, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934, we have well, faithfully, and truly

in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, dependently resurveyed the subdivisonal
lines of Township 5 South, Range 9 West

of the Gila and Salt
River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us and under our direction; and that all the corners of
said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-
tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of
such survey.

Sentinel, Arizona,
March 23, 1934.

For signatures of
William Merry Heina
and Jess R. Horak, see
attached certificates.

Daniel M. Wier
U.S. *Jess R. Horak*

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

19

The foregoing field notes of the survey of

executed by

under his special instructions dated, 19, having been
critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys
they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in
, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

195
42

4-680
(August, 1926)

SOON 4080

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Rowland Norris	Principal Assistant
Earnest L. Shockler	Chairman
H. W. Burt,	Field Assistant
Phil C. Ensign	Field Assistant
Merritt Preston	Field Assistant
Aubrey Washburn	Field Assistant

43 196
CERTIFICATE OF UNITED STATES SURVEYOR

We, William Merry Heina,
Daniel M. Wier, and
Jess R. Horak, U. S. Transitmen

_____ hereby certify upon honor that, in pursuance
of special instructions received from the District Cadastral Engineer for Arizona

we
bearing date of the 15th day of February, 1934,

we have well, faithfully, and truly
in ~~my~~ ^{our} own proper ~~person~~ ^{persons}, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tion, and the laws of the United States, ~~surveyed all these parts or portions of~~

lines of Township 5 South, Range 9 West

_____ of the Gila and Salt

River Meridian, in the State of Arizona, which are represented in

us our
the foregoing field notes as having been executed by ~~me~~ and under ~~my~~ direction; and that all the corners of
re
said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-

tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of
re
such survey.

Sentinel, Arizona,
March 23, 1934.

Jess R. Horak
U. S. Transitman

For signatures of
William Merry Heina
and Daniel M. Weir,
see attached cer-
tificate.

APPROVAL

Sentinel, Arizona,
March 23, 1934.

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, June 11, 1935.

The foregoing field notes of the dependent resurvey of the subdivisio-
nal
lines of Township 5 South, Range 9 West, of the Gila and Salt River
Meridian, in the State of Arizona.

Transitmen,
executed by William Merry Heina, Daniel M. Wier, and Jess R. Horak, U. S.
their
under ~~his~~ special instructions dated February 15, 1934, having been
critically examined, and the necessary corrections and explanations made, the said field notes, and the ~~re~~ surveys
they describe, are hereby approved.

William M. Johnson
U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in

has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.