

Original

4-679
(April 1933)

Book G.

BOOK 4084

FIELD NOTES

of the

dependent resurvey of the subdivisional lines

of

Township 6 South, Range 10 West,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Cyril Gilliam, Charles E. Bronson and Herman J. Shafer, U.S. Transitmen,

Under special instructions dated February 15, 1934, which provided for the surveys included under Group No. 201, bearing the approval of the Commissioner of the General Land Office under date of April 13, 1934, and assignment instructions dated January 15, 1934.

Survey commenced January 22, 1934.

Survey completed March 26, 1934.

4084

4084

1A

BOOK 4094

INDEX DIAGRAM.

Township 6 South, Range 10 West

42	41	31	24	16	8
6	40 5	31 4	23 3	15 2	8 1
40	39	30	22	15	7
7	38 8	29 9	22 10	14 11	6 12
37	37	29	21	13	6
18	36 17	28 16	20 15	12 14	5 13
36	35	27	20	12	5
19	35 20	27 21	19 22	11 23	4 24
34	34	26	18	10	3
30	33 29	25 28	18 27	10 26	3 25
33	32	25	17	9	2
31	32 32	24 33	16 34	9 35	2 36

Resurvey of the Subdivisions of T.6 S., R.10 W.

The subdivisional survey of T.6 S., R.10 W., was executed with W. & L. E. Gurly transit No. 20116, and Young & Sons transits Nos. 8527 and 8567, all property of the General Land Office, and constructed in accordance with its standard specifications. The instruments were in good condition, and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, were approved by the district cadastral engineer conditional upon satisfactory field tests.

Since the solar attachments were not used for the determination of azimuth, the field tests of the solar apparatus were omitted.

As the land in this township is mostly free from heavy timber and dense undergrowth, the lines were run as transit lines, using fore and back sights. The directions of the meridional lines were determined by deflection from the south bdy. of the township, the direction of which was determined as described in the field notes of the resurvey thereof under this group. The directions of the latitudinal lines were determined by deflection from the meridional lines, the angles being checked at all intersections.

The measurements were made with steel tapes 5 chs. in length, graduated every link for the first 100 lks., and thereafter at intervals at 10 lks. The tapes were tested by comparison with a standard tape and found correct. The measurements were made on the slope; and the vertical angle of each interval was ascertained by a clinometer in adjustment; the horizontal equivalents are entered in the field notes.

Preliminary to the resurvey, the lines of the original survey were retraced and diligent search was made for all original corners. Missing section corners were reestablished by double proportion between the nearest known end identified subdivisional corners and original or reestablished corners on the township boundaries; or between identified subdivisional corners as appropriate, all lines being based on the original record. Missing closing corners on the north bdy. were reestablished by single proportion on the first standard parallel south.

Missing $\frac{1}{2}$ sec. cors. were reestablished midway between original or reestablished subdivisional corners, except for the N. tier and W. range of sections, where they were reestablished by single proportion, based upon the original record.

In order to simplify the record, only the true lines are given in the field notes.

The mean magnetic declination is N. $14^{\circ}30'$ E.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

From the cor. of secs. 35 and 36 on S. bdy. of Tp., which is an iron post firmly set, marked and witnessed as described in the official record.

N. 1°09' W., on true line bet. secs. 35 and 36.

Over rocky land thru scattering undergrowth.

5.00 Paved highway, bears N. 80° E. to Phoenix, and S. 70° W. to Yuma.

5.50 4 wire telegraph line, parallel highway.

39.51 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36

1934

from which

A palo verde, 8 ins. diam., bears N. 23° E., 247 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.

An ironwood, 8 ins. diam., bears S. 4 $\frac{3}{4}$ ° W., 356 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

79.02 The cor. of secs. 25, 26, 35 and 36, which is a badly weathered palo verde post 3 ins. diam., in a mound of stone, no marks visible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground over a cross x marked on bedrock, and in a mound of stone, 3 ft. base to top, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T 6 S R 10 W

S 26 | S 25

S 35 | S 36

1934

Land, rolling rocky.

Soil, rocky, 4th rate.

Timber, very scattering palo verde and mesquite; undergrowth, greasewood and cactus.

From the cor. of secs. 25, 30, 31 and 36 on E. bdy. of Tp., described in the field notes of the resurvey thereof under this group.

S. 89°48' W., on true line bet. secs. 25 and 36.

Over rolling desert land thru scattering timber and undergrowth.

40.71 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock, with a stone 6x5x2 ins. marked with cross x, deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

 $\frac{1}{4}$ S 25

S 36

from which

A palo verde, 8 ins. diam., bears S. 36° E., 307 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.

81.42 The cor. of secs. 25, 26, 35 and 36.

Land, rolling rocky.

Soil, rocky, 4th rate.

Timber, very scattering palo verde and mesquite, undergrowth, greasewood and cactus.

N. 0°05' W., on true line bet. secs. 25 and 26.

Over rolling desert land thru scattering timber and undergrowth.

40.21 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 26 | S 25

1934

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

80.43 The cor. of secs. 23, 24, 25 and 26, which is a rotted palo verde post 2 ins. diam., 12 ins. above ground, with no marks visible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd:

T 6 S R 10 W

S 23 | S 24

S 26 | S 25

1934

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, rolling desert.

Soil, rocky, 4th rate.

Timber, very scattering palo verde and mesquite, undergrowth, greasewood.

From the cor. of secs. 19, 24, 25 and 30 on E. bdy. of Tp., described in the field notes of the resurvey thereof under this group.

S. 89°55' W., on true line bet. secs. 24 and 25.

Over level desert land thru scattering undergrowth.

40.73 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with broken glass deposited at base of

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 24

S 25

1934

81.47 The cor. of secs. 23, 24, 25 and 26.

Land, level desert.

Soil, rocky loam, 3rd rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage and cactus.

N. $0^{\circ}08'$ W., on true line bet. secs. 23 and 24.

Over slightly rolling desert thru scattering timber and undergrowth.

40.29 Set an iron post, 3 ft. long, 1 in. diam., over a cross x marked on solid rock, also with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 23 | S 24

1934

from which

A palo verde, 8 ins. diam., bears S. $34\frac{3}{4}^{\circ}$ E., 338 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.

A palo verde, 8 ins. diam., bears S. $73\frac{3}{4}^{\circ}$ W., 25 lks. dist., mkd. S 23 B T.

80.58 The cor. of secs. 13, 14, 23 and 24, which is a badly weathered mesquite post squared at upper end, set in a mound of stone. Marks visible but illegible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a stone 4x3x1 ins. marked with a cross x deposited at base of post, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

T 6 S R 10 W

S 14 | S 13

S 23 | S 24

1934

from which

The original bearing tree:

A palo verde, 14 ins. diam., bears S. 19° E., 75 lks. dist., mkd. T VI S R X W XIV. I remark T 6 S R 10 W S 24 B T.

Land, rolling desert.

Soil, rocky and sandy, 3rd and 4th rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood and cactus.

Chains

From the cor. of secs. 13, 18, 19 and 24 on E. bdy. of Tp., described in the field notes of the resurvey thereof under this group.

N. 89°55' W., on true line bet. secs. 13 and 24.

Over rolling desert land thru scattering timber and undergrowth.

40.80 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a stone 6x4x3^{inches} ^{marked with a cross (x)} at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 13

S 24

1934

from which

A palo verde, 6 ins. diam., bears S. 56 $\frac{1}{2}$ ° E., 93 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

73.75 Wash, 15 lks. wide, course N. 10° W.

75.10 3 wire telephone line, bears N. 32° W. and S. 32° E.

75.75 Desert road, parallels telephone line.

81.61 The cor. secs. ~~13, 18, 23~~ and 24.

Land, slightly rolling desert.

Soil, sandy and rocky, 4th rate.

Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, ocotillo, cactus and sahuaro.

N. 0°12' W., on true line bet. secs. 13 and 14.

Over slightly rolling land thru very scattering timber and undergrowth.

9.50 Graded road, bears S. 31° E. to Sentinel, and N. 31° W. to Agua Caliente.

10.50 3 wire telephone line, parallels road.

14.30 Wash, 15 lks. wide, course N. 30° W.

40.18 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a broken crock deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 14 | S 13

1934

from which

A mesquite, 5 ins. diam., bears S. 15° W., 29 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.

Dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

80.37

The cor. of secs. 11, 12, 13 and 14, which is the rotted remains of old post in center of a mound of stone.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.

T 6 S R 10 W

S 11 | S 12

S 14 | S 13

1934

from which

The original bearing tree

A palo verde, 16 ins. diam., bears S. 11° E., 230 lks. dist., mkd. T VI S R X W S XIII. I remark T 6 S R 10 W S 13 B T.

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, scattering mesquite and palo verde; undergrowth, greasewood and cactus.

From the cor. of secs. 7, 12, 13 and 18 on E. bdy. of Tp., described in the field notes of the resurvey thereof under this group.

N. 89°54' W., on true line bet. secs. 12 and 13.

Over slightly rolling desert land thru scattering timber and undergrowth.

40.79

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 12

S 13

1934

raise a mound

of stone, 4 ft. base, 3 ft. high, N. of cor.

81.58

The cor. of secs. 11, 12, 13 and 14.

Land, rolling rocky desert.

Soil, rocky loam, 4th rate.

Timber, very scattering palo verde; undergrowth, greasewood and sage.

N. 0°15' E., on true line bet. secs. 11 and 12.

Over slightly rolling desert land thru scattering timber and undergrowth.

40.12

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

$$\frac{1}{4}$$

S 11	S 12
------	------

1934

18x18x12 ins., N. and S. of cor., 3 ft. dist.

dig pits,

80.24 At this point determined by the method of double proportion.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at base of post, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

T 6 S R 10 W

S 2	S 1
-----	-----

S 11	S 12
------	------

1934

18x18x12 ins., in each sec., 3 ft. dist.

dig pits,

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood and cactus.

From the cor. of secs. 1, 2, and 12 on E. bdy. of Tp., described in the field notes of the resurvey thereof under this group.

N. 89°09' W., on true line bet. secs. 1 and 12.

Over level desert land thru scattering timber and undergrowth.

40.67 The $\frac{1}{4}$ sec. cor., which is a badly weathered ironwood post 2 ins. diam., 16 ins. above ground. No marks visible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 1
---------------	-----

S 12

1934

from which

A mesquite, 4 ins. diam., bears S. 39°30' W., 103 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.

Thence

S. 88°53' W., on true line bet. secs. 1 and 12.

40.29 The cor. of secs. 1, 2, 11 and 12.

Land, level desert land.

Soil, sandy loam, 2d rate.

Timber, scattering palo verde and mesquite; undergrowth, scattering sage and greasewood.

Resurvey of the Subdivisions of T.6 S., R.10 W.


Chains

N. 0°32' W., on true line bet. secs. 1 and 2.

Over level desert land thru scattering timber and undergrowth.

40.12 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for 1/4 sec. cor., with brass cap mkd.



1934

18x18x12 ins., N. and S. of cor., 3 ft. dist.


dig pits,

80.05 Intersect the 1st Stan. Par. S., at a point determined by single proportion bet. the standard cor. of secs. 35 and 36, and the standard 1/4 sec. cor. of sec. 36 of T.5 S., R. 10 W.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.

T 5 S R 10 W

S 36



T 6 S R 10 W

C C

1934

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From point of intersection the standard 1/4 sec. cor. of sec. 36, T.5 S., R.10 W., bears S. 89°11' E., 18.15 chs. dist.; described in the field notes of the 1st Stan. Par. S., thru R.10 W., resurveyed under this group.


Land, level desert.

Soil, sandy loam, 2d rate.

Timber, scattering mesquite and palo verde; undergrowth and greasewood.

At the midpoint of N. bdy. of sec. 1,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brown glass bottle deposited at base, for 1/4 sec. cor. of sec. 1 only, with brass cap mkd.



1934

18x18x12 ins., on line E. and W. of cor., 3 ft. dist.

dig pits,

From this cor., the standard cor. of T.5 S., Rs.9 and 10 W., bears S. 88°46' E., 17.66 chs. dist.; described in the field notes of the 1st Stan. Par. S., resurveyed under this group.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

From the cor. of secs. 34 and 35 on S. bdy. of Tp., which is an iron post, marked and witnessed as described in the official record.

N. $1^{\circ}30'$ W., on true line bet. secs. 34 and 35.

Over level desert thru scattering timber and undergrowth.

39.43 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$.

S 34 | S 35

1934

from which

An ironwood tree, 6 ins. diam., bears S. 25° E., 179 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

59.00 Wash, 30 lks. wide, course W.

78.87 The cor. of secs. 26, 27, 34 and 35, which is a rotted mesquite post 2 ins. diam., 36 ins. long, standing in mound of stone. Marks visible but illegible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

T 6 S R 10 W

S 27 | S 26

S 34 | S 35

1934

from which

A palo verde, 6 ins. diam., bears S. 5° W., 122 lks. dist., mkd. T 6 S R 10 W S 34 B T.

Land, level desert.

Soil, rocky loam, 4th rate.

Timber, none; undergrowth, scant sage, cacti and greasewood.

From the cor. of secs. 25, 26, 35 and 36.

N. $89^{\circ}10'$ W., on true line bet. secs. 26 and 35.

Over level desert land thru scattering timber and undergrowth.

40.13 The $\frac{1}{4}$ sec. cor., which is a small mound of stone with a rotted portion of old post in center.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

$$\frac{1}{4} \text{ S } 26$$

S 35

1934

Continue on same line bet. secs. 26 and 35.

80.36 The cor. of secs. 26, 27, 34 and 35.

Land, slightly rolling.

Soil, sandy and rocky loam, 2d and 4th rate.

Timber, scattering mesquite and palo verde; undergrowth, greasewood and sage.

N. 0°06' W., on true line bet. secs. 26 and 27.

Over slightly rolling desert land thru scant timber and undergrowth.

40.30 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$

S 27 | S 26

1934

80.60 The cor. of secs. 22, 23, 26 and 27, which is a rotted palo verde post 4 ins. diam., 3 ft. long, set in mound of stone, no marks visible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

T 6 S R 10 W

S 22 | S 23

S 27 | S 26

1934

Land, slightly rolling desert.

Soil, rocky, 4th rate.

Timber, none; undergrowth, scant sage, cacti and greasewood.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°05' W., on true line bet. secs. 23 and 26.

Over level desert land thru scant timber and undergrowth.

40.25 The $\frac{1}{4}$ sec. cor., which is a badly rotted post set in a mound of stone.

In place of old post, and with the old post alongside,

Resurvey of the Subdivisions of T.6 S., R.10 W. BOOK 4084

Chains

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 23

S 26

1934

from which

An original bearing tree

A palo verde, 6 ins. diam., bears N. $19^{\circ}30'$ E., 169 lks. dist. Scribe marks illegible. I remark $\frac{1}{4}$ S 23 B T.

Find no trace of the other old bearing tree.

Continue on same line bet. secs. 23 and 26.

80.42. The cor. of secs. 22, 23, 26 and 27.

Land, slightly rolling.
Soil, rocky, 4th rate.
Timber, none; undergrowth, scant greasewood, sage and cacti.

N. $0^{\circ}08'$ W., on true line bet. secs. 22 and 23.

Over slightly rolling desert thru scattering timber and undergrowth.

40.27 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 22 | S 23

1934

from which

A palo verde, 4 ins. diam., bears N. 86° E., 208 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.

80.54 At this point determined by the method of double proportion.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at base of post, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

T 6 S R 10 W

S 15 | S 14

S 22 | S 23

1934

from which

A palo verde, 6 ins. diam., bears N. 29° E., 61 lks. dist., mkd. T 6 S R 10 W S 14 B T.

A palo verde, 8 ins. diam., bears N. 6° W., 70 lks. dist., mkd. T 6 S R 10 W S 15 B T.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

Raise a mound of stone, 4 ft. base, 4 ft. high, W. of cor.

Land, slightly rolling.

Soil, rocky, 4th rate.

Timber, scattering palo verde and mesquite; undergrowth, sage and cacti.

From the cor. of secs. 13, 14, 23 and 24.

N. 89°02' W., on true line bet. secs. 14 and 23.

Over rolling rocky land thru scattering undergrowth.

40.18 The $\frac{1}{4}$ sec. cor., which is a small mound of stone with badly rotted fragment of post in center. No marks visible.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 14

S 23

1934

Thence

N. 89°23' W., on true line bet. secs. 14 and 23.

40.10 The cor. of secs. 14, 15, 22 and 23.

Land, rolling desert.

Soil, sandy gravel and rocky, 4th rate.

Timber, scattering palo verde, ironwood and mesquite; undergrowth, sage, greasewood, ocotillo, cactus and sahuaro.

N. 0°22' W., on true line bet. secs. 14 and 15.

Over level desert land thru scattering timber and undergrowth.

40.26 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 15 | S 14

1934

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

80.53 The cor. of secs. 10, 11, 14 and 15, which is a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high.

At point for cor.,


Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock, with broken glass deposited at base of post, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

T 6 S R 10 W



1934

from which

The original bearing tree

A palo verde, 10 ins. diam., bears S. 22°30' E.; 237 lks. dist. Scribe marks illegible. I remark T 6 S R 10 W S 14 B T.

And new bearing tree

A palo verde, 8 ins. diam., bears S. 89° W., 377 lks. dist., mkd. T 6 S R 10 W S 15 B T.

Land, level desert.

Soil, rocky, 4th rate.

Timber, scant palo verde and mesquite; undergrowth, sage and greasewood.

From the cor. of secs. 11, 12, 13 and 14.


N. 89°09' W., on true line bet. secs. 11 and 14.

Over rough and rocky land thru scattering timber and undergrowth.

40.13 The 1/4 sec. cor., which is a rotted post set in center of small mound of stone. Marks illegible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with broken glass deposited at base of post, for 1/4 sec. cor., with brass cap mkd.



S 14

1934

from which

The original bearing tree

A palo verde, 6 ins. diam., bears S. 37° W., 230 lks. dist. Scribe marks illegible.

No other bearing trees available.

Thence

N. 89°05' W., on true line bet. secs. 11 and 14.

17.00 3 wire telephone line, bears NE. and SW.

23.20 Graded road, bears SE. to Sentinel and NW. to Agua Caliente.

24.20 Wash, 20 lks. wide, course NW.

40.31 The cor. of secs. 10, 11, 14 and 15.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

Land, rough and rocky.
Soil, rocky, 4th rate.
Timber, scattering palo verde; undergrowth and greasewood.

N. 0°04' E., on true line bet. secs. 10 and 11.

Over slightly rolling desert land thru scattering timber and undergrowth.

17.00 Wash, 20 lks. wide, course NW.

22.70 Graded road, bears NW. to Agua Caliente and SE. to Sentinel.

36.50 3 wire telephone line, bears NW. and SE.

40.20 The $\frac{1}{4}$ sec. cor., which is a rotted mesquite post 4 ins. diam., 24 ins. long, faced on two sides and set in a mound of stone. No marks visible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 10 | S 11

1934

from which

A palo verde, 6 ins. diam., bears S. 10°30' E., 301 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.

Thence

N. 1°17' E., on true line bet. secs. 10 and 11.

42.06 The cor. of secs. 2, 3, 10 and 11, which is a badly weathered mesquite post 4 ins. diam., 18 ins. long, markings not visible lying on ground over stub that is in place.

At point for cor., and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

T 6 S R 10 W

S 3 | S 2

S 10 | S 11

1934

from which

A palo verde, 6 ins. diam., bears N. 89° W., 108 lks. dist., mkd. T 6 S R 10 W S 3 B T.

A palo verde, 6 ins. diam., bears N. 20° W., 130 lks. dist., mkd. T 6 S R 10 W S 3 B T.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

Land, level desert.
Soil, rocky, 4th rate.
Timber, scattering palo verde; undergrowth, greasewood,
sage and cactus.

From the cor. of secs. 1, 2, 11 and 12.

N. 87°45' W., on true line bet. secs. 2 and 11.

Over level desert land thru scattering timber and under-
growth.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with broken glass deposited at base of post, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 2

S 11

1934

from which

The new bearing trees

A palo verde, 10 ins. diam., bears N. 8° E., 29 lks.
dist., mkd. $\frac{1}{4}$ S 2 B T.

A palo verde, 5 ins. diam., bears S. 3° E., 141 lks.
dist., mkd. $\frac{1}{4}$ S 11 B T.

Find no trace of original bearing trees.

79.97 The cor. of secs. 2, 3, 10 and 11.

Land, level desert.
Soil, sandy loam, 2d rate.
Timber, very scattering palo verde, undergrowth, sage,
greasewood and cactus.

N. 0°32' W., on true line bet. secs. 2 and 3.

Over level desert land thru scattering timber and under-
growth.

39.25 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with broken glass deposited at base of post, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 3 | S 2

1934

18x18x12 ins., N. and S. of post, 3 ft. dist.

dig pits,

78.17 Intersect the 1st Stan. Par. S., at a point determined by
single proportion bet. the standard cor. of secs. 34 and
35, and the standard $\frac{1}{4}$ sec. cor. of sec. 35, of T.5 S.,
R.10 W.

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the
ground to bedrock, and in a mound of stone to top, for

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

closing cor. of secs. 2 and 3, with brass cap mkd.

T 5 S R 10 W

S 35

S 3 | S 2

C C

T 6 S R 10 W.

1934

from which

A palo verde, 8 ins. diam., bears S. $54\frac{1}{2}^{\circ}$ E., 71 lks. dist., mkd. T 6 S R 10 W S 2 C C B T.

A palo verde, 9 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ W., 231 lks. dist., mkd. T 6 S R 10 W S 3 C C B T.

From point of intersection the standard $\frac{1}{4}$ sec. cor. of sec. 35, T.5 S., R.10 W., bears S. $89^{\circ}11'$ E., 17.80 chs. dist.; described in the field notes of the 1st Stan. Par. S., thru R.10 W., resurveyed under this group.

Land, rocky rolling desert.

Soil, rocky loam and sand, 4th rate.

Timber, scattering palo verde and mesquite; undergrowth, scattering sage and cactus.

At the midpoint of the N. bdy. of sec. 2,

Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, with broken glass deposited at base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap mkd.

$\frac{1}{4}$ S 2

1934

From this cor., the standard cor. of secs. 35 and 36, T. 5 S., R.10 W., bears S. $89^{\circ}11'$ E., 17.98 chs. dist.; described in the field notes of the 1st Stan. Par. S., thru R.10 W., resurveyed under this group.

From the cor. of secs. 33 and 34 on S. bdy. of Tp., which is an iron post, marked and witnessed as described in the official record.

N. $1^{\circ}11'$ W., on true line bet. secs. 33 and 34.

Over rolling desert land thru scattering timber and undergrowth.

39.44 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd:

S 33 | S 34

1934

Chains

from which

A palo verde, 6 ins. diam., bears S. 61°30' E., 133 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

78.88

The cor. of secs. 27, 28, 33 and 34, which is a badly rotted palo verde post 2 ins. sq. at upper end, 30 ins. long, 5 ins. diam. at lower end, standing in small mound of stone. No marks visible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

T 6 S R 10 W

S 28 | S 27

S 33 | S 34

1934

from which

The original bearing tree

An ironwood, 6 ins. diam., bears N. 7° W., 365 lks. dist. Old scribe marks visible. I remark T 6 S R 10 $\frac{1}{4}$ S 28 B T.

And new bearing tree

A ironwood, 5 ins. diam., bears N. 38° E., 328 lks. dist., mkd. T 6 S R 10 W S 27 B T.

Land, slightly rolling desert.
Soil, sandy gravel and broken lava, 4th rate.
Timber, very scattering palo verde and ironwood; undergrowth, sage, greasewood and cactus.

From the cor. of secs. 26, 27, 34 and 35.

N. 89°12' W., on true line bet. secs. 27 and 34.

Over level desert thru scattering undergrowth.

39.69

The $\frac{1}{4}$ sec. cor., which is badly rotted remains of old post in a mound of stone.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 27

S 34

1934

Thence

N. 89°02' W., on true line bet. secs. 27 and 34.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

39.69 The cor. of secs. 27, 28, 33 and 34.

Land, slightly rolling desert.
Soil, sandy gravel and lava, 4th rate.
Timber, very scattering palo verde and mesquite; undergrowth, greasewood and sage.

N. 0°50' W., on true line bet. secs. 27 and 28.

Over rolling rocky desert land thru very scattering timber and undergrowth.

40.34 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 28 | S 27

1934

from which

An ironwood, 6 ins. diam., bears S. 81° E., 331 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.

80.68 The cor. of secs. 21, 22, 27 and 28, which is the badly decayed stub of old post 4 ins. diam.; flush with surface of old mound of earth; bottom of post is 12 ins. below surface and shows cross x marks.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at base of post, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T 6 S R 10 W

S 21 | S 22

S 28 | S 27

1934

from which

A palo verde, 8 ins. diam., bears S. 85°30' E., 403 lks. dist., mkd. T 6 S R 10 W S 27 B T.

Land, rocky rolling and slightly rolling desert.
Soil, Rocky loam and sandy gravel, 4th rate.
Timber, very scattering palo verde and mesquite; undergrowth, greasewood and cactus.

From the cor. of secs. 22, 23, 26 and 27.

N. 89°01' W., on true line bet. secs. 22 and 27.

Over slightly rolling desert thru scattering timber and undergrowth.

40.20 The $\frac{1}{4}$ sec. cor., which is the badly decayed fragments of wood in center of old mound of stone.

At point for cor.,

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \text{ S } 22$$

$$\text{S } 27$$

1934

Continue on same line bet. secs. 22 and 27.

80.41 The cor. of secs. 21, 22, 27 and 28.

Land, slightly rolling desert.
Soil, sandy loam and rocky loam, 2d and 4th rate.
Timber, very scattering palo verde and mesquite; undergrowth, greasewood and sage.

N. $0^{\circ}03'$ W., on true line bet. secs. 21 and 22.

Over rocky and rolling desert land thru scattering timber and undergrowth.

40.20 The $\frac{1}{4}$ sec. cor., which is a slightly weathered ironwood post 3 ins. diam. faced on two sides, marked $\frac{1}{4}$ S. set firmly 18 ins. in the ground and projecting 16 ins. above ground.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \text{ S } 21 \text{ | } \text{S } 22$$

1934

from which

The original bearing trees

A dead ironwood, 5 ins. diam., bears N. 55° E., 149 lks. dist. No scribe marks visible.

An ironwood, 5 ins. diam., bears S. $66^{\circ}15'$ W., 250 lks. dist., mkd. $\frac{1}{4}$ S. I remark $\frac{1}{4}$ S 21 B T.

And new bearing tree

An ironwood, 16 ins. diam., bears N. $20^{\circ}45'$ E., 188 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.

Thence

N. $0^{\circ}06'$ W., on true line bet. secs. 21 and 22.

40.21 The cor. of secs. 15, 16, 21 and 22, which is the badly decayed stub of old post set firmly in mound of earth and flush with the surface, witnessed by old pits SE., NE., SW. and NW.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

ground, with broken glass deposited at base of post, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

T 6 S R. 10 W

S 16 | S 15

S 21 | S 22

1934

from which

A palo verde, 10 ins. diam., bears N. $20\frac{1}{2}^{\circ}$ W., 257 lks. dist., mkd. T 6 S. R 10 W S 16 B. T.

Dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling desert and malpais formation.

Soil, sandy gravel and malapai, 2d and 4th rate.

Timber, very scattering palo verde and ironwood; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 14, 15, 22 and 23.

N. $89^{\circ}00'$ W., on true line bet. secs. 15 and 22.

Over rolling desert land thru scattering timber and undergrowth.

40.20 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 15

S 22

1934

18x18x12 ins., E. and W. of cor., 3 ft. dist.

dig pits,

80.41 The cor. of secs. 15, 16, 21 and 22.

Land, rolling rocky.

Soil, sandy gravel and rocky, 4th rate.

Timber, very scattering palo verde, ironwood and mesquite; undergrowth, sage, greasewood and cactus.

N. $0^{\circ}22'$ W., on true line bet. secs. 15 and 16.

Over rolling desert land thru scattering timber and undergrowth.

40.48 The true point for $\frac{1}{4}$ sec. cor. determined from the original bearing tree.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 16 | S 15

1934

from which

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

The original bearing tree

An ironwood, 4 ins. diam., bears N. 65° E., 279 lks. dist. Scribe marks illegible. I remark $\frac{1}{4}$ S 15 B T.

Thence

N. 0°01' W., on true line bet. secs. 15 and 16.

39.94 The cor. of secs. 9, 10, 15 and 16, which is a badly weathered palo verde post 2 ins. diam., 30 ins. long standing in small mound of stone. No marks visible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

$$\begin{array}{c} \cdot \text{ T 6 S R 10 W} \\ \text{S 9 | S 10} \\ \hline \text{S 16 | S 15} \end{array}$$

1934

from which

The original bearing trees

An ironwood, 4 ins. diam., bears N. 52°15' E., 154 lks. dist., mkd. T VI S R X W S X. I remark T 6 S R 10 W S 10 B T.

An ironwood, 8 ins. diam., bears S. 54°30' W., 128 lks. dist. Old scribe marks illegible. I remark T 6 S R 10 W S 16 B T.

Land, rocky rolling desert.

Soil, sandy gravel and rocky, 4th rate.

Timber, very scattering ironwood and palo verde; undergrowth, sage, greasewood and cactus.

From the cor. of secs. 10, 11, 14 and 15.

N. 89°01' W., on true line bet. secs. 10 and 15.

Over rough rolling desert land thru scattering timber and undergrowth.

40.13 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \text{S 10} \\ \hline \text{S 15} \end{array}$$

1934

18x18x12 ins., E. and W. of post, 3 ft. dist.

dig pits,

80.27 The cor. of secs. 9, 10, 15 and 16.

Land, rough rolling desert.

Soil, rocky, 4th rate.

Timber, very scattering palo verde; undergrowth, greasewood and sage.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains	<p>N. 0°46' E., on true line bet. secs. 9 and 10.</p> <p>Over rolling desert thru scattering timber and undergrowth.</p> <p>17.65 Wash, 10 lks. wide, course S. 70° W.</p> <p>40.74 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">S 9 S 10 1934</p> <p style="text-align: right;">from which</p> <p>An ironwood, 8 ins. diam., bears S. 85°30' E., 200 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.</p> <p>57.85 Graded road, bears S. 75° E. to Sentinel and NW. to Agua Caliente.</p> <p>81.48 The cor. of secs. 3, 4, 9 and 10, which is a small mound of stone with rotten remains of old post in center. No marks visible.</p> <p>At point for cor.,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 10 W S 4 S 3 ----- S 9 S 10 1934</p> <p style="text-align: right;">from which</p> <p>A palo verde, 8 ins. diam., bears E., 80 lks. dist., mkd. T VI S R X W S 10. I remark T 6 S R 10 W S 10 B T.</p> <p>Land, rolling desert. Soil, rocky and sandy gravel, 4th rate. Timber, very scattering palo verde and ironwood; undergrowth, sage, greasewood and cactus.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°42' W., on true line bet. secs. 3 and 10.</p> <p>Over slightly rolling desert thru scattering timber and undergrowth.</p> <p>38.60 3 wire telephone line, bears NW. and SE.</p> <p>40.03 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
--------	---

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains	
	$\frac{1}{4}$ S 3 S 10 1934
58.00	Dim desert road, bears NW. and SE.
79.00	Wash, 15 lks. wide, course NW.
80.07	The cor. of secs. 3, 4, 9 and 10. Land, mostly level, and slightly rolling. Soil, rocky, 4th rate. Timber, scattering palo verde; undergrowth, sage and greasewood.

	N. 0°06' W., on true line bet. secs. 3 and 4. Over broken malpais formation thru scattering timber and undergrowth.
1.00	Wash, 20 lks. wide, 25 ft. deep, course N. 60° W.
8.00	South edge of mesa, bears E. and W., descend 75 ft. over N. slope.
18.40	Foot of descent.
38.45	3 wire telephone line, bears N. 56° W. and S. 56° E.
39.95	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{2}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 4 S 3 1934
	from which
	A palo verde, 8 ins. diam., bears S. 40° E., 135 lks. dist., mkd. $\frac{1}{4}$ S. 3 B T.
	A palo verde, 5 ins. diam., bears N. 33° W., 50 lks. dist., mkd. $\frac{1}{4}$ S. 4 B T.
46.30	Asc. 90 ft. over SW. slope.
50.00	Point of mesa. Desc. 90 ft. over NW. slope.
60.00	Foot of descent, bears NE. and SW.
78.90	Intersect the 1st Stan. Par. S. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for closing cor. of secs. 3 and 4., with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

T 5 S R 10 W

S 34

S 4 | S 3

C | C

T 6 S R 10 W

1934

18x18x12 ins., on lines S., E. and W. of cor., 3 ft. dist. dig pits,

From point of intersection the standard 1/4 sec. cor. of sec. 34, T.5 S., R.10 W., bears S. 89°12' E., 17.22 chs. dist.; described in the field notes of the 1st Stan. Par. S. thru R.10 W., resurveyed under this group.

Continue N. 0°06' W. on blank line.

79.27 The original closing cor. of secs. 3 and 4, which is the old stake in a mound of earth.

Land, rough malpais.
Soil, rocky and sandy gravel, 4th rate.
Timber, scattering mesquite, palo verde and ironwood; undergrowth, sage and greasewood.

At the midpoint of N. bdy. of sec. 3.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, with bottle deposited at base and in a mound of stone, for 1/4 sec. cor. of sec. 3 only, with brass cap mkd.

1/4 S 3

1934

of stone, 2 ft. base, 1 1/2 ft. high, S. of cor. raise a mound

From this cor., the standard cor. of secs. 34 and 35, bears S. 89°12' E., 17.41 chs. dist.; described in the field notes of the 1st Stan. Par. S. thru R.10 W., resurveyed under this group.

From the cor. of secs. 32 and 33 on S. bdy. of Tp., which is an iron post, 2 ins. diam., marked and witnessed as described in the official record.

N. 0°10' W., on true line bet. secs. 32 and 33.

Over slightly rolling desert thru scattering timber and undergrowth.

40.15 The 1/4 sec. cor., which is the remains of badly decomposed post in center of small mound of stone.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with broken crockery deposited at base of post, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084
BOOK 4084

Chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 32 \mid \text{S } 33 \\ 1934 \end{array}$$

Thence

N. 2°19' W., on true line bet. secs. 32 and 33.

40.20 At this point determined by the method of double proportion.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken crockery deposited at base of post, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

$$\begin{array}{c} \text{T } 6 \text{ S } \text{R } 10 \text{ W} \\ \text{S } 29 \mid \text{S } 28 \\ \text{S } 32 \mid \text{S } 33 \\ 1934 \end{array}$$

18x18x12 ins., in each sec., 3 ft. dist.

dig pits,

Land, slightly rolling.

Soil, sandy loam, 2d rate.

Timber, scattering palo verde; undergrowth, greasewood and sage.

From the cor. of secs. 27, 28, 33 and 34.

N. 88°09' W., on true line bet. secs. 28 and 33.

Over level desert land thru scattering timber and undergrowth.

40.07 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \text{ S } 28 \\ \text{S } 33 \\ 1934 \end{array}$$

80.15 The cor. of secs. 28, 29, 32 and 33.

Land, level desert.

Soil, sandy loam, 1st rate.

Timber, very scattering palo verde and mesquite; undergrowth, greasewood and sage.

N. 2°15' E., on true line bet. secs. 28 and 29.

Over level desert thru scattering timber and undergrowth.

40.20 The $\frac{1}{4}$ sec. cor., which is the rotted remains of post in center of small mound of stone.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

ground to solid rock, with broken crockery deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \mid \text{S } 28 \\ 1934 \end{array}$$

Thence

N. $0^{\circ}12'$ W., on true line bet. secs. 28 and 29.

40.22 The cor. of secs. 20, 21, 28 and 29, which is the stub of old post.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of earth to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

$$\begin{array}{c} \text{T } 6 \text{ S } \text{R } 10 \text{ W} \\ \text{S } 20 \mid \text{S } 21 \\ \hline \text{S } 29 \mid \text{S } 28 \\ 1934 \end{array}$$

from which

The original bearing trees

An ironwood, 10 ins. diam., bears N., 50 lks. dist. Old scribe marks illegible. Remark T 6 S R 10 W S 21 B T.

An ironwood, 12 ins. diam., bears S. 15° E., 71 lks. dist. Old scribe marks illegible. Remark T 6 S R 10 W S 28 B T.

Dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, very scattering ironwood and palo verde; undergrowth, greasewood and sage.

From the cor. of secs. 21, 22, 27 and 28.

N. $88^{\circ}12'$ W., on true line bet. secs. 21 and 28.

Over level desert thru scattering timber and undergrowth.

38.79 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S } 21 \\ \text{S } 28 \\ 1934 \end{array}$$

from which

An ironwood, 5 ins. diam., bears S. 30° W., 111 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

Dig pits, 18x18x12 ins., on line E. and W. of post,
3 ft. dist.

77.58 The cor. of secs. 20, 21, 28 and 29.

Land, level desert.
Soil, sandy loam, 2d rate.
Timber, very scattering ironwood and palo verde; under-
growth, greasewood and sage.

N. 0°07' W., on true line bet. secs. 20 and 21.

Over level desert thru scattering timber and undergrowth.

40.19 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with broken glass deposited at base of post, for
sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 20 | S 21
 1934

18x18x12 ins., on line N. and S. of cor., 3 ft. dist. dig pits,

80.38 The cor. of secs. 16, 17, 20 and 21, which is the stub of
old post.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the
ground, with broken glass deposited at base of post, for
cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

T 6 S R 10 W
 S 17 | S 16

 S 20 | S 21
 1934

from which

The original bearing tree

An ironwood, 10 ins. diam., bears S. 15° E., 26 lks.
dist. Old scribe marks illegible, Remark T 6 S R 10
W S 21 B T.

Land, level desert.
Soil, sandy loam, 2d rate.
Timber, very scattering ironwood and palo verde; under-
growth, greasewood and sage.

From the cor. of secs. 15, 16, 21 and 22.

N. 88°13' W., on true line bet. secs. 16 and 21.

Over level desert land thru scattering timber and under-
growth.

38.80 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with broken glass deposited at base of post, for
sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

S 16

S 21

1934

from which

An ironwood, 6 ins. diam., bears N. 72° E., 262 lks.
dist., mkd. $\frac{1}{4}$ S 16 B T.

77.60 The cor. of secs. 16, 17, 20 and 21.

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, scattering ironwood and palo verde; undergrowth,
greasewood and sage.

N. 1°11' W., on true line bet. secs. 16 and 17.

Over level desert land thru scattering timber and under-
growth.39.44 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with broken glass deposited at base of post, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 17 | S 16

1934

from which

An ironwood, 5 ins. diam., bears N. 60°30' E., 111 lks.
dist., mkd. $\frac{1}{4}$ S 16 B T.

78.89 The cor. of secs. 8, 9, 16 and 17, which is the rotted
remains of old post in center of small stone mound.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the
ground to solid rock, with broken glass deposited at base
of post, and in a mound of stone to top, for cor. of secs.
8, 9, 16 and 17, with brass cap mkd.

T 6 S R 10 W

S 8 | S 9

S 17 | S 16

1934

from which

A palo verde, 4 ins. diam., bears S. 38° E., 123 lks.
dist., mkd. T 6 S R 10 W S 16 B T.

A palo verde, 5 ins. diam., bears S. 80° W., 76 lks.
dist., mkd. T 6 S R 10 W S 17 B T.

Find no trace of old bearing trees.

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, very scattering palo verde and ironwood; under-
growth, greasewood and sage.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

From the cor. of secs. 9, 10, 15 and 16.

N. 89°56' W., on true line bet. secs. 9 and 16.

Over level desert land thru scattering timber and undergrowth.

15.30 Ravine, 20 lks. wide, course N.

39.09 The 1/4 sec. cor., which is a small mound of stone.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 9
S 16

1934

from which

A palo verde, 6 ins. diam., bears S. 65°30' W., 102 lks. dist., mkd. 1/4 S 16 B T.

Thence

N. 88°39' W., on true line bet. secs. 9 and 16.

39.91 The cor. of secs. 8, 9, 16 and 17.

Land, rolling desert.

Soil, rocky loam, 4th rate.

Timber, very scattering palo verde and ironwood; undergrowth, greasewood and sage.

N. 0°08' W., on true line bet. secs. 8 and 9.

Over rolling desert land thru scattering timber and undergrowth.

11.00 Wash, 20 lks. wide, course NW.

38.30 Leave level desert; descend 30 ft. over NE. slope.

40.20 The 1/4 sec. cor., which is the rotted remains of old post in center of small mound of stone.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 8 | S 9

1934

Continue descent 50 ft. over NE. slope.

48.20 Wash in bottom of ravine, 20 lks. wide, course NW.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

Thence over level land.

66.20 Ascend from bottom of ravine to mesa about 80 ft. high.

71.20 Top of ascent, thence over level land.

80.33 The cor. of secs. 4, 5, 8 and 9, which is a badly weathered piece of old post in center of small stone mound.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T 6 S R 10 W

S 5 | S 4

S 8 | S 9

1934

Land, broken desert.

Soil, rocky, 4th rate.

Timber, very scattering palo verde and ironwood; undergrowth, greasewood and sage.

From the cor. of secs. 3, 4, 9 and 10.

S. 89°52' W., on true line bet. secs. 4 and 9.

Over rolling desert thru scattering timber and undergrowth.

34.25 Graded road, bears NW. to Agua Caliente and SW. to Sentinel.

39.85 The $\frac{1}{4}$ sec. cor., which is a mound of stone with pieces of rotted post in center.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with pieces of broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$ S 4

S 9

1934

from which

A palo verde, 6 ins. diam., bears N. 76° E., 270 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.

Thence

S. 89°47' W., on true line bet. secs. 4 and 9.

40.52 The cor. of secs. 4, 5, 8 and 9.

Land, rolling desert.

Soil, rocky, 4th rate.

Timber, very scattering palo verde and ironwood; undergrowth, sage and greasewood.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

N. 0°25' W., on true line bet. secs. 4 and 5.

Over broken desert land thru scattering timber and undergrowth.

31.85 Dim desert road, bears NW. and SE.

38.20 Desc. 30 ft. over N. slope to

40.36 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.




Continue descent 35 ft.

45.00 Foot of descent, thence over level land.

80.13 Intersect the 1st Stan. Par. S., at a point determined by single proportion bet. the standard cor. of secs. 32 and 33, and the standard 1/4 sec. cor. of sec. 33.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with glass jar deposited at base, for closing cor. of secs. 4 and 5, with brass cap mkd.



18x18x12 ins., on lines E., W. and S. of post, 3 ft. dist. dig pits,

From point of intersection the standard 1/4 sec. cor. of sec. 33, T.5 S., R.10 W., bears S. 89°43' E., 18.12 chs. dist.; described in the field notes of the 1st Stan. Par. S., thru R.10 W., resurveyed under this group.

Land, broken desert.

Soil, rocky and sandy loam, 4th and 2d rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood and sage.

At the midpoint of the N. bdy. of sec. 4.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for 1/4 sec. cor. of sec. 4 only, with brass cap mkd.



Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

from which

A mesquite, 6 ins. diam., bears S. $69\frac{1}{2}^{\circ}$ E., 46 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.

No other suitable tree available.

From this cor., the standard cor. of secs. 33 and 34, T. 5 S., R.10 W., bears S. $89^{\circ}12'$ E., 17.67 chs. dist.; described in the field notes of the 1st Stan. Par. S., resurveyed under this group.

From the cor. of secs. 31 and 32 on S. bdy. of Tp., which is an iron post, 2 ins. diam., marked and witnessed as described in the official record.

N. $1^{\circ}18'$ W., on true line bet. secs. 31 and 32.

Over level desert land thru scattering timber and undergrowth.

39.44 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 31 | S 32

1934

18x18x12 ins., N. and S. of cor., 3 ft. dist.

dig pits,

78.88 The cor. of secs. 29, 30, 31 and 32, which is a weathered ironwood post 4 ins. sq., 18 ins. above ground in small mound of stone. Scribe marks illegible.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at base of post, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T 6 S R 10 W

S 30 | S 29

S 31 | S 32

1934

18x18x12 ins., in each sec., 3 ft. dist.

dig pits,

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, very scattering mesquite and palo verde; undergrowth, sage, greasewood and cactus.

From the cor. of secs. 28, 29, 32 and 33.

S. $88^{\circ}46'$ W., on true line bet. secs. 29 and 32.

Over level desert land thru scattering timber and undergrowth.

40.18 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 29

S 32

1934

dig pits,

18x18x12 ins., E. and W. of cor., 3 ft. dist.

80.36

The cor. of secs. 29, 30, 31 and 32.

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, very scattering palo verde and mesquite; undergrowth, greasewood and sage.

N. 89°09' W., on true line bet. secs. 30 and 31.

Over level desert land thru scattering timber and undergrowth.

39.24

Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 30

S 31

1934

76.75

The cor. of secs. 25, 30, 31 and 36, on W. bdy. of Tp.; described in the field notes of the resurvey thereof under this group.

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, very scattering palo verde and mesquite; undergrowth, sage and greasewood.

From the cor. of secs. 29, 30, 31 and 32.

N. 1°12' E., on true line bet. secs. 29 and 30.

Over level desert land thru scattering timber and undergrowth.

40.23

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 30 | S 29

1934

dig pits,

18x18x12 ins., N. and S. of post, 3 ft. dist.

56.00

Small frame house, bears W., about 3 chs. dist.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

80.46

At this point determined by the method of double proportion.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at base, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T 6 S R 10 W

S 19 | S 20

S 30 | S 29

1934

18x18x12 ins., in each sec., 3 ft. dist.

dig pits,

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, none; undergrowth, sage, greasewood and cactus.

From the cor. of secs. 20, 21, 28 and 29.

S. 88°53' W., on true line bet. secs. 20 and 29.

Over level desert land thru scattering timber and undergrowth.

40.05

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for 1/4 sec. cor., with brass cap mkd.

1/4 S 20

S 29

1934

18x18x12 ins., on line E. and W. of post, 3 ft. dist.

dig pits,

80.11

The cor. of secs. 19, 20, 29 and 30.

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, none; undergrowth, sage and greasewood.

N. 89°10' W., on true line bet. secs. 19 and 30.

Over level desert land thru scattering timber and undergrowth.

15.40

House, bears S. 23° E., about 4 chs. dist.

40.13

Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at base of post, for 1/4 sec. cor., with brass cap mkd.

1/4 S 19

S 30

1934

18x18x12 ins., on line E. and W. of post, 3 ft. dist.

dig pits,

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

78.57

The cor. of secs. 19, 24, 25 and 30 on W. bdy. of Tp.; described in the field notes of the resurvey thereof under this group.

Land, level desert.
Soil, sandy loam, 2d rate.
Timber, none; undergrowth, sage, greasewood and cactus.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°03' W., on true line bet. secs. 19 and 20.

Over level desert land thru scattering timber and undergrowth.

40.22

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, with broken glass deposited at base of post, and in a mound of earth to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 19 | S 20
1934

18x18x12 ins., on line N. and S. of post, 3 ft. dist. dig pits,

80.44

At this point determined by the method of double proportion.

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with broken glass deposited at base of post, and in a mound of stone to top, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

T 6 S R 10 W
S 18 | S 17

S 19 | S 20
1934

from which

A palo verde, 5 ins. diam., bears N. 20° W., 30 lks. dist., mkd. T 6 S R 10 W S 18 B T.

A palo verde, 8 ins. diam., bears N. 33° E., 73 lks. dist., mkd. T 6 S R 10 W S 17 B T.

A palo verde, 6 ins. diam., bears S. 23° W., 68 lks. dist., mkd. T 6 S R 10 W S 19 B T.

Land, slightly rolling.
Soil, sandy loam, 2d rate.
Timber, scattering palo verde and mesquite; undergrowth, greasewood and sage.

From the cor. of secs. 16, 17, 20 and 21.

S. 88°54' W., on true line bet. secs. 17 and 20.

Over slightly rolling desert land thru scattering timber and undergrowth.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

40.07 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 17

S 20

1934

18x18x12 ins., on line E. and W. of cor., 3 ft.

dig pits,
dist.

80.14 The cor. of secs. 17, 18, 19 and 20.

Land, slightly rolling desert.

Soil, sandy loam, 2d rate.

Timber, very scattering palo verde and mesquite; undergrowth, greasewood, sage and cactus.

N. 89°16' W., on true line bet. 18 and 19.

Over rolling desert land thru scattering timber and undergrowth.

40.12 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with glass deposited at base of post, and in a mound of earth and gravel to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 18

S 19

1934

18x18x12 ins., E. and W. of post, 3 ft. dist.

dig pits,

78.57 The cor. of secs. 13, 18, 19 and 24 on W. bdy. of Tp., described in the field notes of the resurvey thereof under this group.

Land, slightly rolling desert.

Soil, sandy and gravelly loam, 3rd rate.

Timber, very scattering palo verde and ironwood; undergrowth, sage, greasewood and cactus.

From the cor. of secs. 17, 18, 19 and 20.

N. 0°43' W., on true line bet. secs. 17 and 18.

Over slightly rolling desert land thru scattering timber and undergrowth.

40.22 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

$$\begin{array}{c} \frac{1}{4} \\ \hline S 18 | S 17 \end{array}$$

1934

18x18x12 ins., on line N. and S. of post, 3 ft. dist. dig pits,

80.44 At this point determined by the method of double proportion.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at base of post, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

T 6 S R 10 W

$$\begin{array}{c} S 7 | S 8 \\ \hline S 18 | S 17 \end{array}$$

1934

18x18x12 ins., in each sec., 3 ft. dist. dig pits,

Land, level desert.

Soil, sandy loam, 2d rate.

Timber, very scattering palo verde; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 8, 9, 16 and 17.

S. 89°57' W., on true line bet. secs. 8 and 17.

Over level desert land thru scattering timber and undergrowth.

39.68 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} S 8 \\ \hline \frac{1}{4} \end{array}$$

S 17

1934

from which

A palo verde, 4 ins. diam., bears S. 25° W., 219 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.An ironwood, 7 ins. diam., bears N. 6° E., 199 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.

79.37 The cor. of secs. 7, 8, 17 and 18.

Land, slightly rolling desert.

Soil, sandy and rocky loam, 4th rate.

Timber, scattering palo verde and ironwood; undergrowth, greasewood and sage.

N. 89°22' W., on true line bet. secs. 7 and 18.

Over slightly rolling desert land thru scattering timber and undergrowth.

39.76 Proportional distance.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 7
S 18
1934

from which

A palo verde, 8 ins. diam., bears S. 83° E., 162 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

Dig pits, 18x18x12 ins., on line E. and W. of post, 3 ft. dist.

77.80 The cor. of secs. 7, 12, 13 and 18 on W. bdy. of Tp.; described in the field notes of the resurvey thereof under this group.

Land, slightly rolling desert.
Soil, rocky loam, 4th rate.
Timber, very scattering palo verde; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 7, 8, 17 and 18.

N. 0°06' W., on true line bet. secs. 7 and 8.

Over level desert land thru scattering timber and undergrowth.

40.22 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with glass deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 7 | S 8

1934

62.70 Edge of mesa, bears E. and W. Desc. 50 ft. over N. slope.

72.00 Foot of descent, thence over level land.

80.44 The cor. of secs. 5, 6, 7 and 8, which is a badly weathered mesquite post 4 ins. sq., 30 ins. long, with some scribe marks visible broken off, but with lower portion in ground.

In place of old post, and with the old post alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with glass deposited at base of post, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.

T 6 S R 10 W

S 6 | S 5

S 7 | S 8

1934

from which

Resurvey of the Subdivisions of T.6 S., R.10 W.

BOOK 4084

Chains

The original bearing tree

A fallen palo verde, bears S. 76° E., 204 lks. dist.,
mkd. T VI S R X W VIII.

And new bearing tree

A palo verde, 6 ins. diam., bears S. 86° E., 177 lks.
dist., mkd. T 6 S R 10 W S 8 B T.

Land, level desert.

Soil, rocky loam, 4th rate.

Timber, very scattering palo verde; undergrowth, grease-
wood and sage.-----
From the cor. of secs. 4, 5, 8 and 9.

S. 89°20' W., on true line bet. secs. 5 and 8.

Over broken desert land thru scattering timber and under-
growth.

9.00 Wash, 20 lks. wide, course N.

15.00 Bluff, facing W., bears N. and S. Desc. 60 ft.

21.50 Foot of descent, thence over flat washed land.

34.80 Wash, 20 lks. wide, course NW.

38.00 Asc. 70 ft. over E. slope.

41.18 The $\frac{1}{4}$ sec. cor., which is a badly weathered mesquite
stake in center of small mound of stone. No marks visible.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the
ground to solid rock, with glass deposited at base of
post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor.,
with brass cap mkd. $\frac{1}{4}$ S 5

S 8

1934

Thence

N. 89°10' W., on true line bet. secs. 5 and 8.

Over nearly level mesa.

28.80 Bluff, facing W., bears N. and S. Desc. 46 ft.

34.75 Wash, 20 lks. wide, course N.

38.23 The cor. of secs. 5, 6, 7 and 8.

Land, mostly broken and rolling.

Soil, rocky, 4th rate.

Timber, scattering palo verde and ironwood, undergrowth,
greasewood and sage.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

N. 89°37' W., on true line bet. secs. 6 and 7.

Over rolling desert along S. edge of broken mesa thru scattering timber and undergrowth.

13.35 Wash, 20 lks. wide, course N.

22.40 Wash, 15 lks. wide, course N.

39.79 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at base of post, for 1/4 sec. cor., with brass cap mkd.

1/4 S 6

S 7

1934

from which

An ironwood, 24 ins. diam., bears N. 15° E., 141 lks. dist., mkd. 1/4 S 6 B T.

77.83 The cor. of secs. 1, 6, 7 and 12 on W. bdy. of Tp.; described in the field notes of the resurvey thereof under this group.

Land, rough rolling desert.
Soil, sandy gravel and rocky loam, .4th rate.
Timber, scattering palo verde and ironwood; undergrowth, greasewood and sage.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°19' W., on true line bet. secs. 5 and 6.

Over slightly rolling desert land thru scattering timber and undergrowth.

36.00 Wash, 60 lks. wide, course NW.

40.22 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at base of post, for 1/4 sec. cor., with brass cap mkd.

1/4 S 6 | S 5

1934

from which

A palo verde, 10 ins. diam., bears N. 22° E., 91 lks. dist., mkd. 1/4 S 5 B T.

A palo verde, 16 ins. diam., bears S. 52° W., 108 lks. dist., mkd. 1/4 S 6 B T.

40.93 Wash, 10 lks. wide, course NW.

53.30 Dim road, bears E. and W.

57.90 Old irrigation canal, bears S. 66°30' W., and N. 66°30' E.

Resurvey of the Subdivisions of T.6 S., R.10 W. BOOK 4084

Chains

- 58.05 Old barb wire fence, bears S. $66^{\circ}30'$ W. and N. $66^{\circ}30'$ E.
 65.90 Old irrigation canal, bears S. $66^{\circ}30'$ W. and N. $66^{\circ}30'$ E.
 66.40 Old barbed wire fence, bears S. $66^{\circ}30'$ W. and N. $66^{\circ}30'$ E.
 80.34 Intersect the 1st Stan. Par. S., at a point determined by single proportion bet. the standard cor. of secs. 31 and 32, and the standard $\frac{1}{4}$ sec. cor. of sec. 32.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.

T 5 S R 10 W

S 32

S 6 | S 5

C | C

T 6 S R 10 W

1934

from which

A mesquite, 16 ins. diam., bears S. 45° E., 265 lks. dist., mkd. T 6 S R 10 W S 5 C C B T.

A mesquite, 12 ins. diam., bears S. $39\frac{1}{2}^{\circ}$ W., 45 lks. dist., mkd. T 6 S R 10 W S 6 C C B T.

From point of intersection, the standard $\frac{1}{4}$ sec. cor. of sec. 32, T.5 S., R.10 W., bears S. $89^{\circ}43'$ E., 18.69 chs. dist.; described in the field notes of the 1st Stan. Par. S. thru R.10 W., resurveyed under this group.

Land, slightly rolling first $\frac{1}{4}$ sec., level desert 2d $\frac{1}{4}$. Soil, sandy loam and silt, 1st and 2d rate. Timber, heavy mesquite and palo verde; undergrowth, sage and mesquite brush.

At the midpoint of N. bdy. of sec. 5.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 5

1934

from which

A mesquite, 10 ins. diam., bears S. 72° E., 70 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.

A mesquite, 12 ins. diam., bears S. $61\frac{3}{4}^{\circ}$ W., 167 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.

From this cor., the standard cor. of secs. 32 and 33, T. 5 S., R.10 W., bears S. $89^{\circ}43'$ E., 17.91 chs. dist.; described in the field notes of the 1st Stan. Par. S., resurveyed under this group.

Resurvey of the Subdivisions of T.6 S., R.10 W.

Chains

At a point on the N. bdy. of sec. 6, determined by single proportion bet. the NE. and NW. corners of said sec.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$ S 6

1934

from which

A mesquite, 8 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ E., 271 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

A mesquite, 6 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ W., 117 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

From this cor., the standard cor. of secs. 31 and 32, T. 5 S., R.10 W., bears S. $89^{\circ}54'$ E., 19.13 chs. dist.; described in the field notes of the 1st Stan. Par. S., resurveyed under this group.

GENERAL DESCRIPTION

The elevation of this township will range from about 430 feet in the NW. corner of section 6 to about 700 feet in section 35.

The major portion is of rolling mesa land, covered with a soil of gravel, sand and lava rock, gradually draining to the NW. into the Gila River.

Very little timber except along the N. boundary in sections 3, 4, 5 and 6, in the bottom lands, where the mesquite is very dense and thick. On the higher portions in the central and southern portions are some scattering Palo Verde and Ironwood trees.

The undergrowth is mostly soap weed and cactus. The land, where it breaks off into the river bottom, is of lava rock formation.

The soil is of 3rd and 4th rate, not suitable for pasturage or agricultural purposes.

The drainage is to the N. and W.

A fair graded dirt road runs through sections 4, 5, 9, 10, 11, 14 and 24, in a SE. direction from Agua Caliente Springs to Sentinel, Arizona.

There are no settlers located in this township that I know of.

The nearest P. O. and shipping point is Sentinel, Arizona, located on U. S. Highway #80, and the Southern Pacific Railway about 1 mile E. of the SE. township corner.

No mineral deposits were noted.

4-680
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Jess R. Horak	Principal Assistant
Thomas T. Cage	Chainman
Foster W. Kelly	Field Assistant
Omer S. Boswell	Field Assistant
Carroll White	Field Assistant
Otis L. Mosely	Field Assistant
Donovan D. Boyer	Field Assistant

44

BOOK 4084

CERTIFICATE OF UNITED STATES SURVEYOR

We, Cyril Gilliam, Charles E. Bronson, and Herman J. Shafer, U.S. Transitman,

hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934, we have well, faithfully, and truly in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, independently resurveyed the subdivisional lines of Township 6 South, Range 10 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

For signature of Charles E. Bronson and Herman J. Shafer, see the attached certificates,

Cyril Gilliam U.S. Transitman Sentinel, Arizona.

APPROVAL February 17, 1934.

Office of U. S. Supervisor of Surveys,

19

The foregoing field notes of the survey of

executed by

under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in

, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

205
45

continued

BOOK 4084

4-680
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Sloan A. Amos	Principal Assistant
E. W. Fields	Chairman
Rody G. Capron	Field Assistant
J. N. Peterson	Field Assistant
F. O. Colson	Field Assistant
M. L. Patrick	Field Assistant
Erwin W. Peterson	Field Assistant
Elbert T. Mosley	Field Assistant

CERTIFICATE OF UNITED STATES SURVEYOR

We, Cyril Gilliam, Charles E. Bronson, and Herman J. Shafer, U.S. Transitmen, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934, have well, faithfully, and truly

our in my own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, ~~separately~~ resurveyed the subdivisional lines of Township 6 South, Range 10 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us, and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

For signature of Cyril Gilliam and Herman J. Shafer, see the attached certificates.

Chas. E. Bronson

U.S. Transitman

APPROVAL Sentinel, Arizona. February 10, 1934

Office of U. S. Supervisor of Surveys,

19

The foregoing field notes of the survey of

executed by under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680
(August, 1926)

BOOK 4084

FIELD ASSISTANTS.

NAMES.	CAPACITY.
William M. Heina	Principal Assistant
A. W. Porter	Principal Assistant and Chairman
George R. Hegi	Chairman and Field Assistant
Joseph W. Coulter	Field Assistant
Angus Pryor	Field Assistant
Harry Hayes	Field Assistant
H. F. Reeves	Field Assistant
P. L. Lowry	Field Assistant
AL Blake	Field Assistant
J. William Cobb	Field Assistant
Tom Flynn	Field Assistant

CERTIFICATE OF UNITED STATES SURVEYOR

We, Cyril Gilliam, Charles E. Bronson, and Herman J. Shafer, U.S. Transitmen, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934, we have well, faithfully, and truly

in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, dependently resurveyed the subdivisional lines of Township 6 South, Range 10 West,

of the Gila and Salt

River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us, and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

For signature of Cyril Gilliam and Charles E. Bronson, see the attached certificates.

Herman J. Shafer

U.S. Transitman
Sentinel, Arizona.

APPROVAL Feb. 24, 1934.

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, June 11, 1935

The foregoing field notes of the dependent resurvey of the subdivisional lines of Township 6 South, Range 10 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Cyril Gilliam, Charles E. Bronson and Herman J. Shafer,

executed by U.S. Transitmen

under their special instructions dated February 15, 1934, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in

has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.