

4085

Original

4-679
(April 1933)

Book H.

BOOK 4085

FIELD NOTES

of the

dependent resurvey of the subdivisional lines

of

Township 6 South, Range 11 West,

4085

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Anthony C. Kimmell, U.S. Surveyor, and Herman J. Shafer, Jess R. Horak and

William M. Heina, U.S. Transitmen,

4085

Under special instructions dated February 15, 1934, which provided for the surveys included under Group No. 201, bearing the approval of the Commissioner of the General Land Office under date of April 13, 1934, and assignment instructions dated January 15, 26 and 28, 1934.

Survey commenced February 14, 1934.

Survey completed March 24, 1934.

2
14
BOOK 4085

INDEX DIAGRAM.

Township 6 South, Range 11 West

36	36	27	21	15	8
6	35 5	26 4	20 3	14 2	7 1
35	34	26	20	13	6
7	34 8	26 9	19 10	12 11	5 12
33	33	25	19	12	5
18	32 17	24 16	18 15	11 14	4 13
32	31	24	17	11	4
19	30 20	23 21	17 22	10 23	4 24
30	29	23	17	10	3
30	29 29	22 28	16 27	9 26	2 25
28	28	22	16	9	2
31	28 32	21 33	15 34	8 35	2 36

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

1. B

chains

The subdivisionsl survey of T. 6 S., R. 11 W. was executed with W. & L.E. Gurley transit No. 20116, Young and Sons. transit No. 8493 and Buff transits Nos. 9987 and 9305, all property of the General Land Office and constructed in accordance with its standard specifications. The instruments were in good condition, and having been placed in satisfactory adjustment prior to beginning the survey and tested and found free from appreciable error, were approved by the district cadastral engineer, conditional upon satisfactory field tests. Since the solar attachments were not used for the determination of azimuth, the field tests of the solar apparatus were omitted.

As the land in this township is mostly free from heavy timber and dense undergrowth, the lines were run as transit lines, using fore and back sights. The directions of the meridional lines were determined by deflection from the south bdy. of the township, the direction of which was determined as described in the field notes of the resurvey thereof under this group. The directions of the latitudinal lines were determined by deflection from the meridional lines, the angles being checked at all intersections.

The measurements were made with steel tapes, 5 chs. in length, graduated every link for the first 100 lks. and thereafter at intervals of 10 lks. The tapes were tested by comparison with a standard and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by a clinometer in good adjustment, the horizontal equivalents are entered in the field notes.

Preliminary to the resurvey, the lines of the original survey were retraced and diligent search was made for all original corners, missing section corners were reestablished by double proportion between the nearest known and identified subdivisional corners and original or reestablished corners on the township boundaries; or between identified subdivisional corners as appropriate, all lines being base on the original record. Missing closing corners on the North bdy. were reestablished by single proportion on the first standard parallel south. Missing $\frac{1}{4}$ sec. cors. were reestablished midway between original or reestablished subdivisional corners, except for the N. tier and W. range of sections where they were reestablished by single proportion, based upon the original record.

In order to simplify the record, only the true lines are given in the field notes.

The mean magnetic declination is N. 14° 30' E.

Reestablishment of surveys executed by T. F. White in 1877.

ECCN 4085

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	Beginning at the cor. of secs. 1, 2, 35 and 36 on S. bdy. of Tp. described in the field notes of the resurvey thereof under this group.								
	N.0°51'W., on true line bet. secs. 35 and 36.								
	Over level desert land, through scattering undergrowth.								
39.48	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.								
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1934</td> </tr> </table>	S35	S36	1934					
S35	S36								
1934									
	dig pits,								
	18x18x12 ins. on line N. and S. of cor. 3 ft. dist.								
78.96	The cor. of secs. 25, 26, 35 and 36, which is a badly weathered mesquite stake, 4 ins. diam., 12 ins. above ground with scribe marks not legible.								
	In place of and with the old stake alongside;								
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit glass at base of post, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T6S</td> <td style="padding: 0 5px;">R11W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S26</td> <td style="padding: 0 5px;">S25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1934</td> </tr> </table>	T6S	R11W	S26	S25	S35	S36	1934	
T6S	R11W								
S26	S25								
S35	S36								
1934									
	dig pits,								
	18x18x12 ins. in each sec. 3 ft. dist.								
	Land, rolling and level.								
	Soil, sandy, 2nd rate.								
	Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.								

	From the cor. of secs. 25, 30, 31 and 36 on E. bdy. of Tp. described in the field notes of the resurvey thereof under this group.								
	S.88°48'W., on true line bet. secs. 25 and 36.								
	Over level desert land, through scattering undergrowth.								
40.68	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">$\frac{1}{4}$ S</td> <td style="padding: 0 5px;">25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">$\frac{1}{4}$ S</td> <td style="padding: 0 5px;">36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1934</td> </tr> </table>	$\frac{1}{4}$ S	25	$\frac{1}{4}$ S	36	1934			
$\frac{1}{4}$ S	25								
$\frac{1}{4}$ S	36								
1934									
	dig pits,								
	18x18x12 ins. on line E. and W. of cor. 3 ft. dist.								
81.36	The cor. of secs. 25, 26, 35 and 36.								
	Land, level.								
	Soil, sandy, 2nd rate.								
	Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.								

	N.0°05'W., on true line bet. secs. 25 and 26.								

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	Over rolling land, through scattering undergrowth.
40.11	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> $\begin{array}{r} \frac{1}{4} \\ S26 S25 \\ 1934 \end{array}$ <p style="text-align: right;">Dig pits,</p> <p>18x18x12 ins. on line N. and S. of cor. 3 ft. dist.</p>
80.22	<p>The cor. of secs. 23, 24, 25 and 26, which is the rotted remains of old palo verde post in mound of stone.</p> <p>In place of and with the old post alongside;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to solid rock with broken glass deposited at base, and in a mound of stone to top for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.</p> $\begin{array}{r} T6S R11W \\ S23 S24 \\ \hline S26 S25 \\ 1934 \end{array}$ <p style="text-align: right;">from which</p> <p>The original bearing tree:</p> <p>An ironwood 9 ins. diam., bears N.48°E., 252 lks. dist. mkd. T 6 S R 11 W S XXIV, I add the marks B T.</p> <p>Dig pits, 18x18x12 ins. in each sec. 3 ft. dist.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering palo verde and ironwood; undergrowth, greasewood, sage and cactus.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 19, 24, 25 and 30 on E. bdy. of Tp. described in the field notes of the resurvey thereof under this group.</p> <p>S.88°42'W., on true line bet. secs. 24 and 25.</p> <p>Over rolling land, through scattering undergrowth.</p>
40.65	<p>An iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> $\begin{array}{r} S24 \\ \frac{1}{4} \\ S25 \\ 1934 \end{array}$ <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line E. and W. of cor. 3 ft. dist.</p>
81.30	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering palo verde and ironwood; undergrowth, greasewood, sage and cactus.</p>

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

- chains N.0°11'W., on true line bet. secs. 23 and 24.
Over rolling land, through scattering undergrowth.
- 40.01 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- $\frac{1}{4}$
S23 | S24
1934
- dig pits,
- 18x18x12 ins. on line N. and S. of cor. 3 ft. dist.
- 80.02 The cor. of secs. 13, 14, 23 and 24, which is a badly weathered mesquite post, 4 ins. diam., 18 ins. long, with scribe marks not legible, stub of post in ground.
- At point for cor.,
- Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 13, 14, 23 and 24 with brass cap mkd.
- T6S R11W
S14 | S13
S23 | S24
1934
- dig pits,
- 18x18x12 ins. in each sec. 3 ft. dist.
- Land, level.
Soil, sandy loam, 1st. rate.
Timber, scattering mesquite, palo verde and ironwood; undergrowth, greasewood and catsclaw.
-
- From the cor. of secs. 13, 18, 19 and 24, on E. bdy. of Tp. described in the field notes of the resurvey thereof under this group.
- S.88°31'W., on true line bet. secs. 13 and 24.
Over rolling land, through scattering undergrowth.
- 40.72 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$ S 13
S 24
1934
- dig pits,
- 18x18x12 ins. on line E. and W. of cor. 3 ft. dist.
- 81.44 The cor. of secs. 13, 14, 23 and 24.
- Land, level.
Soil, sandy, loam, 1st. rate.
Timber, scattering mesquite, palo verde and ironwood; undergrowth, sage, greasewood and catsclaw.
-
- N.0°33'E., on true line bet. secs. 13 and 14.

Resurvey of the subdivisions of T. 6 S., R. 11 W.

chains	Over level desert land, through scattering undergrowth.
40.68	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S14} \text{S13} \\ 1934 \end{array}$ <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line N. and S. of cor. 3 ft. dist.</p>
81.36	At this point determined by double proportion. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 11, 12, 13 and 14 with brass cap mkd. $\begin{array}{c} \text{T6S R11W} \\ \text{S11} \text{S12} \\ \hline \text{S14} \text{S13} \\ 1934 \end{array}$ <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. in each section 3 ft. dist.</p> <p>Land, level. Soil, sandy, 2nd rate. Timber scattering palo verde, mesquite and ironwood; undergrowth, sage, greasewood and cactus.</p> <p>-----</p> <p>From the cor. of secs. 7, 12, 13 and 18, on E. bdy. of Tp. described in the field notes of the resurvey thereof under this group.</p> <p>S.89°19'W., on true line bet. secs. 12 and 13.</p> <p>Over level land, through scattering undergrowth.</p>
40.29	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{c} \frac{1}{4} \text{ S 12} \\ \hline \text{S 13} \\ 1934 \end{array}$ <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line E. and W. of cor., 3 ft. dist.</p>
80.57	The cor. of secs. 11, 12, 13 and 14. Land, level. Soil, sandy, 2nd rate. Timber, scattering mesquite, palo verde and ironwood; undergrowth, greasewood, sage and cactus. <p>-----</p> <p>N.0°31'E., on true line bet. secs. 11 and 12.</p> <p>Over rolling land, through scattering undergrowth.</p>
35.20	Wash, 30 lks. wide, course W.
40.68	The $\frac{1}{4}$ sec. cor., which is the remains of a palo verde post, 3 ins. diam., 2 ins. above ground, with scribe marks rotted

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

off, set in an old mound of stone.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{2}$ sec. cor. with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline S11 | S12 \\ 1934 \end{array}$$

dig pits,

18x18x12 ins. on line N. and S. of cor. 3 ft. dist.

Thence,

N.0°17'W., on true line bet. secs. 11 and 12.

32.00 Descend 45 ft.

37.00 Enter bottom land, bears E. and W.

40.00 The cor. of secs. 1, 2, 11 and 12, which a mesquite stake, 4 ins. diam., 30 ins. long, with scribe marks visible set in a mound of earth.

In place of and with the old stake alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

$$\begin{array}{c} T6S R11W \\ \hline S 2 | S 1 \\ \hline S11 | S12 \\ 1934 \end{array}$$

from which

The original bearing trees:

A dead mesquite, 8 ins. diam., bears W., 19 lks. dist., mkd. T6S R11W 11.

A dead mesquite, 8 ins. diam., bears S.41°W., 44 lks. dist., marks not legible.

Land, level and rolling.

Soil, sandy, 2nd rate.

Timber, scattering mesquite and palo verde; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 1, 6, 7, 12 on E. bdy. of Tp. described in the field notes of the resurvey thereof under this group.

S.89°43'W., on true line bet. secs. 1 and 12.

Over rolling land, through scattering undergrowth.

Desc. 90 ft. to

40.17 Point for $\frac{1}{2}$ sec. cor. as determined by the original bearing trees.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{2}$ sec. cor. with brass cap mkd.

$$\begin{array}{c} S 1 \\ \hline S12 \\ 1934 \end{array}$$

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	from which
	The original bearing trees: A dead ironwood bears S.23 $\frac{1}{2}$ °W., 169 lks. dist., marks illegible. A dead palo verde bears N.87°W., 207 lks. dist., marks illegible. Dig pits, 18x18x12 ins. on line E. and W. of post 3 ft. dist.
46.85	Wash, 100 lks. wide, course NW.
80.34	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, sandy, 2nd rate. Timber scattering palo verde, mesquite and ironwood; undergrowth, greasewood, sage and cactus.

	N.0°20'W., on true line bet. secs. 1 and 2. Over level land, through dense brush.
9.00	Well and cistern, bears W. 3.60 chs. dist.
9.40	Road, bears E. and W.
11.25	Canal, 12 lks. wide, course W.
11.75	Fence, bears E. and W., enter field.
27.50	Same canal, course SE.
28.30	Fence, bears NW. and N. leave field.
40.07	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S2 S1 1934
	from which
	Cor. of fence, extending N., S., and W., bears S.35°W. 7 lks. dist. A mesquite 16 ins. diam., bears N.18°E., 225 lks. dist., marked $\frac{1}{4}$ S 1 B T. A mesquite 10 ins. diam., bears N.76°W., 175 lks. dist., marked $\frac{1}{4}$ S 2 B T.
55.00	Road, bears E. and W.
74.05	Cor. of fence, extending S. and W.
80.53	Intersect the first standard parallel south at a point determined by single proportion bet. the standard cor. of secs. 35 and 36, and the standard $\frac{1}{4}$ sec. cor. of sec. 36, Tp. 5 S., R. 11 W. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground with glass bottle deposited at base, for closing cor. of secs. 1 and 2, with brass cap mkd.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

T5S R11W
S36

S2 | S1
C | C
T6S R11W
1934

from which

A cottonwood, 9 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ E., 184 lks. dist., mkd. T 6 S R 11 W S 1 C C B T.

A cottonwood, 14 ins. diam., bears S. 85° W. 100 lks. dist., mkd. T 6 S R 11 W S 2 C C B T.

From point of intersection the standard $\frac{1}{4}$ sec. cor. of sec. 36, bears S. $89^{\circ}54'$ E., 17.23 chs. dist., described in the field notes of the first standard parallel south through R. 11 W. resurveyed under this group.

Land, level.

Soil, sandy, 2nd rate.

Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.

At the midpoint of N. bdy. of sec. 1,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a one qt. fruit jar deposited at the base for $\frac{1}{4}$ sec. cor. of sec. 1 and with brass cap mkd.

 $\frac{1}{4}$ S 1
1934

from which

A mesquite, 12 ins. diam., bears S. 13° E., 129 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.

A mesquite, 8 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ W. 292 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.

From this cor., the standard cor. of Tps. 5 S., R. 10 and 11 W. bears S. $89^{\circ}54'$ E., 17.11 chs. dist. described in the field notes of the 1st. Stan. Par. S. resurveyed under this group.

From the cor. of secs. 2, 3, 34 and 35, on S. bdy. of Tp. described in the field notes of the resurvey thereof under this group.

N. $0^{\circ}51'$ W., on true line bet. secs. 34 and 35.

Over rolling land, through scattering undergrowth.

39.74

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S34 | S35

1934

dig pits,

18x18x12 ins. on line N. and S. of cor. 3 ft. dist.

79.48

At this point determined by double proportion,

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit glass at base of post, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

T6S R11W	
S27	S26
S34	S35
1934	

dig pits,

18x18x12 ins. in each sec. 3 ft. dist.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 25, 26, 35 and 36.

N.89°47'W., on true line bet. secs. 26 and 35.

Over rolling land, through scattering undergrowth.

40.05

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{2}$ sec. cor. with brass cap mkd.

$\frac{1}{2}$	S 26

	S 35
1934	

dig pits,

18x18x12 ins. on line E. and W., of cor. 3 ft. dist.

80.09

The cor. of secs. 26, 27, 34 and 35.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.

N.0°17'W., on true line bet. secs. 26 and 27.

Over rolling land, through scattering undergrowth.

39.74

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{2}$ sec. cor. with brass cap mkd.

$\frac{1}{2}$	S27	S26

	S27	S26
1934		

79.48

The point for cor. of secs. 22, 23, 26 and 27, which is determined from the original bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 22, 23, 26 and 27 with brass cap mkd.

T6S R11W	
S22	S23
S27	S26
1934	

from which

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	<p>A mesquite, 8 ins. diam., bears S.80°W. 245 lks. dist.</p> <p>A mesquite, 14 ins. diam., bears N.10°E., 219 lks. dist. mkd. TVL RXLW XX111.</p> <p>Dig pits, 18x18x12 ins. in each sec. 3 ft. dist.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage and cactus.</p>
40.19	<p>From the cor. of sec. 23, 24, 25 and 26.</p> <p>S.89°39'W., on true line bet. secs, 23 and 26.</p> <p>Over rolling land, through scattering undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor., which is the rotted remains of a palo verde, stake, with scribe marks rotted off set in a mound of stone.</p> <p>At point for cor.,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 23 <hr style="width: 50px; margin: 0 auto;"/> S 26 1934 </p>
40.13	<p>Thence,</p> <p>S.89°42'W., on a true bet. secs. 23 and 26.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering mesquite and palo verde; undergrowth, greasewood, cactus and sage.</p>
40.12	<p>N.0°15'W., on true line bet. secs. 22 and 23.</p> <p>Over rolling land, through scattering undergrowth.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S22 S23 1934 </p>
80.24	<p>dig pits,</p> <p>18x18x12 ins. on line N. and S. of cor. 3 ft. dist.</p> <p>The cor. of secs. 14, 15, 22 and 23, which is mesquite post, 4 ins. diam., 24 ins. above ground, with scribe marks not legible, set in a mound of stone.</p> <p>In place of and with the old stake alongside;</p> <p>Set an iron post, $\frac{1}{2}$ ft. long, 2 ins. diam. 28 ins, in the ground, to solid rock with broken glass deposited at base and in a mound of stone to top, for cor. of secs. 14, 15, 22 and 23 with brass cap mkd.</p>

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

DOCK 60

chains	<p style="text-align: center;">T6S R11W S15 S14 S22 S23 1934</p>
	<p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering palo verde and mesquite; undergrowth, greasewood sage and cactus.</p>
40.17	<p>From the cor. of secs. 13, 14, 23 and 24. S. 89°55'W., on true line bet. secs. 14 and 23. Over rolling land, through scattering undergrowth. The $\frac{1}{2}$ sec. cor., which is a mesquite post, 4 ins. diam., 10 ins. above ground, with scribe marks not legible. In place of old stake, with old stake alongside; Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{2}$ S 14 S 23 1934</p> <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line E. and W. of cor. 3 ft. dist. Thence, S. 89°48'W., on a true line bet. secs. 14 and 23.</p>
40.17	<p>The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sandy, 2nd rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, sage, greasewood and cactus.</p>
40.50	<p>N. 0°21'E., on true line bet. secs. 14 and 15. Over rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S15 S14 1934</p> <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line N. and S. of cor. 3 ft. dist.</p>
74.90	<p>Road, bears E. and W.</p>
81.00	<p>The cor. of secs. 10, 11, 14 and 15, which is the stub of rotted post in mound of earth. In place of old stub,</p>

Resurvey of the subdivisions of T.6 S., R. 11 W.

chains

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to solid rock with broken glass deposited at base and in a mound of stone to top for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

T6S R11W
 S10 | S11
 S15 | S14

1934

from which

The original bearing trees:

A dead mesquite, 6 ins. diam., bears S.70 $\frac{1}{2}$ °E., 138 lks. dist., scribe marks not legible.

A dead mesquite, 6 ins. diam., bears S.15 $\frac{1}{2}$ °W., 200 lks. dist., scribe marks not legible.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage and cactus.

 From the cor. of secs. 11, 12, 13 and 14.

S.89°38'W., on true line bet. secs. 11 and 14.

Over rolling land, through scattering undergrowth.

40.29

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 11
 S 14

1934

from which

A mesquite, 8 ins. diam., bears N.34°E., 70 lks. dist. mkd. $\frac{1}{4}$ S 11 B T.

A mesquite, 16 ins. diam., bears S.13°E., 150 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.

62.60

Wash, 4 chs. wide, course N.5°W.

65.60

Road bears NE. and SW.

80.58

The cor. of secs. 10, 11, 14 and 15.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattering palo verde, mesquite and ironwood; undergrowth, sage, greasewood and cactus.

 N.0°19'E., on true line bet. secs. 10 and 11.

Over rolling land, through scattering undergrowth.

27.00

Wash, 30 lks. wide, course N.5°E., from S.5°E. thence along wash.

40.65

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	
	$\frac{1}{4}$ S10 S11 1934 from which
	A mesquite, 8 ins. diam., bears S.47°E., 106 lks.dist., mkd. $\frac{1}{4}$ S 11 B T. A mesquite 6 ins. diam., bears N.62°E., 96 lks.dist., mkd. $\frac{1}{4}$ S 11 B T.
81.30	The cor. of secs. 2, 3, 10 and 11, which is a mesquite post 4 ins. diam., 18 ins. above ground, with scribe marks not legible. In place of and with the old stake alongside; Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.
	T6S R11W S 3 S 2 S10 S11 1934 from which
	The original bearing trees: A mesquite, 8 ins. diam., bears S.79°E., 42 lks. mkd. TV1S RX1W SX1. I add the marks B T. A mesquite, 14 ins. diam., bears S. 51 lks. dist.mkd. TV1S RX1W SX1. I add the marks B T. A mesquite, 12 ins. diam., bears W. 33 lks. dist., mkd. TV1S RX1W., I add the marks S 3 B T.
	Land, rolling. Soil, sandy, 2nd rate. Timber, scattering mesquite and palo verde; undergrowth, greasewood, sage and cactus.
	From the cor. of secs. 1, 2, 11 and 12. N.89°53'W., on true line bet. secs. 2 and 11. Over rolling land, through dense brush.
20.00	Road, bears NE. and SW.
22.70	Canal, 15 lks. wide, course S.85°W.
25.00	Fence bears NE. and W.
40.20	The $\frac{1}{4}$ sec. cor., which is mesquite post, 4 ins. diam., 18 ins. above ground marked S11 on N., and SX1 on S. sides. In place of and with the old post alongside; Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor, with brass cap mkd.
	$\frac{1}{4}$ S 2 S 11 1934 from which

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

The original bearing trees:

A mesquite 12 ins. diam, bears S.30°E.; 168 lks. dist.
mkd. $\frac{1}{4}$ S 11 B T.

The original position of a dead mesquite, 10 ins.diam.,
lying on ground, bears West, 100 lks.dist. no marks
legible.

Thence,

S.89°55'W., on a true line bet. secs. 2 and 11.

.30 Fence, bears N. and S.

18.70 Road, bears N. and S.

20.10 Fence, bears N. and S.

23.10 Road, bears NE. and SW.

40.10 The cor. of secs. 2,3,10 and 11.

Land, rolling,

Soil, sandy, 2nd rate.

Timber, scattering, ironwood and palo verde; undergrowth,
arrowweed, catsclaw and greasewood.

N.0°30'W., on true line bet. secs. 2 and 3.

Over rolling land, through dense brush.

5.55 Old canal, 15 lks. wide, course NW.

40.07 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor.
with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S3 \mid S2 \\ 1934 \end{array}$$

from which

A mesquite, 20 ins. diam., bears N.34°E., 70 lks.dist.
mkd. $\frac{1}{2}$ S 2 B T.

A mesquite 16 ins. diam., bears S.64°W., 85 lks.dist.,
mkd. $\frac{1}{4}$ S 3 B T.

80.62 Intersect the first standard parallel south at a point
determined by single proportion bet. the standard cor. of
secs. 34 and 35. and the standard $\frac{1}{4}$ sec. cor. of sec. 35.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, with a glass jar deposited at the base for
closing cor. of secs. 2 and 3, with brass cap mkd.

T5S R11W

S35

S3 | S2

C | C

T6S R11W

1934

from which

A mesquite, 8 ins. diam., bears S.21°E., 57 lks.dist.
mkd. T 6 S R 11 W S 2 C C B T.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

A mesquite, 9 ins. diam., bears S.19°W., 157 lks. dist., mkd. T 6 S R 11 W S 3 C C BT.

From point of intersection, the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 5 S., R. 11 W., bears S.89°54'E., 17.60 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

Land, level.

Soil, sandy, 2nd rate.

Timber, mesquite, and ironwood; undergrowth, arrowweed, greaseweed and sage.

At the midpoint of north bdy. of sec. 2.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground with a glass bottle deposited at the base, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap mkd.

S 2
1934

from which

A mesquite 14 ins. diam., bears S.83 $\frac{1}{2}$ °E., 60 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.

A mesquite, 7 ins. diam., bears S.76 $\frac{1}{2}$ °W., 20 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.

From this cor. the standard cor. of secs. 35 and 36, T. 5 S., bears S.89°54'E., 17.41 chs. dist.; described in the field notes of the first standard parallel south through R. 11 W., resurveyed under this group.

From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp. described in the field notes of the resurvey thereof under this group.

N.0°56'W., on true line bet. secs. 33 and 34.

Over rolling land, through scattering undergrowth.

39.67 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S33 | S34
1934

dig pits,

18x18x12 ins. on line N. and S. of cor. 3 ft. dist.

79.34 The cor. of secs. 27, 28, 33 and 34, which is an ironwood stake, 4 ins. diam., 24 ins. above ground, marked XXVIII on one side, other sides not legible.

In place of and with the old stake, alongside;

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

T6S R11W
S28 | S27
S33 | S34
1934

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	<p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. in each sec. 3 ft. dist.</p> <p>Land, rolling, Soil, sandy, 2nd rate. Timber, none; undergrowth, greasewood, sage and cactus.</p>
40.17	<p>-----</p> <p>From the cor. of 26,27,34 and 35. S.89°37'W., on true line bet. secs. 27 and 34. Over rolling land, through scattering undergrowth.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for 1/4 sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S 27 \\ S 34 \\ 1934 \end{array}$ </p>
80.34	<p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line E. and W. of cor. 3 ft. dist.</p> <p>The cor. of secs. 27,28,33 and 34.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, none; undergrowth, greasewood, sage and cactus.</p>
40.20	<p>-----</p> <p>N.0°03'E., on true line bet. secs. 27 and 28. Over rolling land, through scattering undergrowth.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post for 1/4 sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S28 S27 \\ 1934 \end{array}$ </p>
80.40	<p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line, N. and S. of cor. 3 ft. dist.</p> <p>At this point determined by double proportion.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 21,22,27 and 28.</p> <p style="text-align: center;"> $\begin{array}{l} T6S R11W \\ S21 S22 \\ S28 S27 \\ 1934 \end{array}$ </p> <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. in each sec. 3 ft. dist.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, none; undergrowth, greasewood, cactus and sage.</p>

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

From the cor. of secs. 22, 23, 26 and 27.

N.89°46'W., on true line bet. secs. 22 and 27.

Over rolling land, through scattering undergrowth.

39.86

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{l} S 22 \\ S 27 \\ 1934 \end{array}$$

79.72

The cor. of secs. 21, 22, 27 and 28.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, none; undergrowth, greasewood, sage and cactus.

N.0°07'W., on true line bet. secs. 21 and 22.

Over rolling land, through scattering undergrowth,

40.20

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{l} S 21 | S 22 \\ 1934 \end{array}$$

dig pits,

18x18x12 ins. on line N. and S. of cor. 3 ft. dist.

80.40

The cor. of secs. 15, 16, 21 and 22, which is the rotted remains of old post set in a mound of stone and 4 original pits.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 17 ins. in the ground, to solid rock with a stone 8x4x3 ins. mkd. X, and broken glass deposited at the base, and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

$$\begin{array}{l} T6S R11W \\ S16 | S15 \\ S21 | S22 \\ 1934 \end{array}$$

from which

The original bearing tree:

A dead mesquite, 8 ins. diam., bears East, 241 lks. dist., scribe marks not legible.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, none; undergrowth greasewood, sage and cactus.

From the cor. of secs. 14, 15, 22 and 23,

N.89°39'W., on true line bet. secs. 15 and 22.

Over rolling land, through scattering undergrowth.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains
39.80

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S. 15} \\ \hline \text{S. 22} \\ 1934 \end{array}$$

dig pits

18x18x12 ins. on line E. and W. of cor., 3 ft. dist.

79.60

The cor. of secs. 15, 16, 21 and 22.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, none; undergrowth greasewood, sage and cactus.

N.0°07'W., on true line bet. secs. 15 and 16.

Over rolling land, through scattering undergrowth.

3.35

Desert road, bears NE. and SW.

40.27

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \text{S16 | S15} \\ 1934 \end{array}$$

dig pits,

18x18x12 ins. on line N. and S. of cor., 3 ft. dist.

80.54

The cor. of secs. 9, 10, 15 and 16, which is the rotted remains of old stake in a mound of rock.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, to solid rock with glass and a stone 8x6x3 ins. mkd. with a cross (X), deposited at base of post, and in a mound of stone to top for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

$$\begin{array}{r} \text{T6S R11W.} \\ \text{S 9 | S10} \\ \hline \text{S16 | S15} \\ 1934 \end{array}$$

from which

The original bearing trees:

A dead palo verde, 10 ins. diam., bears N.35°W., 228 lks. with scribe marks not legible.

A dead palo verde, stump, bears S.86 $\frac{1}{2}$ °E., 205 lks. with old marks not legible.

A dead palo verde, 12 ins. bears N.83°W., 225 lks. with old scribe marks not legible.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

1934

chains	From the cor. of secs. 10,11,14 and 15, S.89°51'W., on true line bet. secs. 10 and 15. Over rolling land, through scattering undergrowth.
40.15	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{2}$ sec. cor. with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S } 10 \\ \hline \text{S } 15 \\ 1934 \end{array}$ <p style="text-align: right;">dig pits,</p> <p>18x18x12 ins. on line E. and W. of post, 3 ft. dist.</p>
74.75	Desert road, bears NW. and SE.
80.30	The cor. of secs. 9,10,15 and 16. Land, rolling. Soil, sandy, rocky, 2nd rate. Timber, scattering palo verde; undergrowth, greasewood, sage, and cactus.

	N.0°24'E., on true line bet. secs. 9 and 10. Over rolling land, through scattering undergrowth.
4.35	Desert road, bears NW. and SE.
40.53	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to solid rock, with broken glass deposited at base and in a mound of stone to top, for $\frac{1}{2}$ sec. cor. with brass cap mkd. $\begin{array}{r} \frac{1}{4} \\ \text{S } 9 \text{ } \text{S } 10 \\ 1934 \end{array}$
59.55	Wash, 10 lks. wide, course W.
68.30	Wash, 30 lks. wide, course W.
77.35	Wash, 15 lks. wide, course S.50°W.
81.05	The cor. of secs. 3,4,9 and 10, which is a badly weathered mesquite stake, 4 ins. diam., 22 ins. above ground with scribe marks not legible, set in a mound of stone. In place of old stake, with old stake alongside; Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to solid rock with broken glass and a stone 4x3x3 ins. mkd. with a cross (X), deposited at base and in a mound of stone to top, for cor. of secs. 3,4,9 and 10, with brass cap mkd. $\begin{array}{r} \text{T6S R11W} \\ \text{S } 4 \text{ } \text{S } 3 \\ \hline \text{S } 9 \text{ } \text{S } 10 \\ 1934 \end{array}$ <p style="text-align: right;">from which</p> <p>The original bearing trees;</p> <p>A dead palo verde, 8 ins. diam., bears N.57°E., 204 lks. dist., with scribe marks illegible.</p>

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	<p>The buttend of an uprooted palo verde, bears N.19°E. 188 lks. dist., scribe marks illegible.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering palo verde; undergrowth, greasewood, sage and cactus.</p>

	<p>From the cor. of secs. 2, 3, 10 and 11. S.89°44'W., on true line bet. secs. 3 and 10. Over rolling land, through scattering undergrowth. Along broken rim of the Gila River bottom. Asc. 50 ft.</p>
5.30	Top of ascent, desc. 60 ft.
9.60	Wash, 100 lks. wide, course NW.; asc. 50 ft.
27.00	Desc. 90 ft.
35.35	Wash, 200 lks. wide, course N.; asc. 34 ft. to
40.35	<p>The $\frac{1}{4}$ sec. cor., which is a mesquite stake, 3 ins. diam., 32 ins. long, marked $\frac{1}{4}$ S and set in a mound of stone.</p> <p>In place of and with the old stake alongside;</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to solid rock with glass deposited at the base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p>
	$\begin{array}{r} \frac{1}{4} \text{ S } 3 \\ \hline \text{S } 10 \\ 1934 \end{array}$
	from which
	The original bearing tree:
	<p>A palo verde 8 ins. diam., bears N.40°E. 36 lks. dist., mkd. $\frac{1}{4}$ S. I remark $\frac{1}{4}$ S 3 B T.</p>
	Thence,
	S.89°52'W., on a true line bet. secs. 3 and 10.
10.50	Desc. 90 ft. to
24.90	Wash, 100 lks. wide, course NE.; asc. gradually.
39.91	The cor. of secs. 3, 4, 9, and 10.
	<p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering palo verde; undergrowth, greasewood sage and cactus.</p>

	N.0°31'W., on true line bet. secs. 3 and 4.
	Over rolling land, through scattering undergrowth. Desc. 50 ft. to
8.60	Enter Gila River bottom land and dense arrowweed, bears E. and W.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chsins
35.25

S. bank of Gila River bed, 5 ft. high bears N.30°E. and S.30°W.

37.00

Main channel of the Gila River, 300 lks. wide, ^{dry,} course SW.

40.35

Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for 1/4 sec. cor. with brass cap mkd.

1/4
S 4 | S 3
1934

dig pits

18x18x12 ins. on line N. and S. of cor. 3 ft. dist.

Continue over washed land in river bottom.

81.03

Intersect the first standard parallel south at a point determined by single proportion bet. the standard cor. of secs. 33 and 34 and the standard 1/2 sec. cor. of sec. 34.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground with a pint bottle deposited at the base for closing cor. of secs. 3 and 4, with brass cap mkd.

T5S R11W
S34

S 4 | S 3
C | C
T6S R11W
1934

No other accessory available.

From point of intersection, the standard 1/2 sec. cor. of 34, T. 5 S. bears S.89°54'E., 17.70 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

Land, rolling and level.

Soil, sandy, 2nd rate.

Timber, palo verde and mesquite; undergrowth arrowweed, squa brush, greasewood and sage.

At the midpoint of the north bdy. of sec. 3.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground with a glass bottle deposited at the base for 1/4 sec. cor. of sec. 3 only with brass cap mkd.

1/4 S 3
1934

No other accessory available.

From this cor. the standard cor. of secs. 34 and 35, T. 5 S., bears S.89°54'E., 17.65 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp. described in the field notes of the resurvey thereof under this group.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	N.0°45'W., on true line bet. secs. 32 and 33.
	Over rolling land, through scattering undergrowth.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit porcelain at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S32 S33 1932
	dig pits
	18x18x12 ins. on line N. and S. of cor. 3 ft. dist.
80.18	At this point determined by double proportion.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.
	T6S R11W S29 S28 ----- S32 S33 1934
	dig pits
	18x18x12 ins. in each sec. 3 ft. dist.
	Land, rolling. Soil, sandy, 2nd rate. Timber, scattering mesquite; undergrowth, greasewood, sage and cactus.
	From the cor. of secs. 27, 28, 33 and 34,
	N.89°41'W., on true line bet. secs. 28 and 33.
	Over rolling land, through scattering undergrowth.
39.87	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 28 ----- S 33 1934
	dig pits
	18x18x12 ins. on line E. and W. of cor. 3 ft. dist.
79.74	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling. Soil, sandy, 2nd rate. Timber, none; undergrowth, greasewood, sage and cactus.
	N.0°04'E., on true line bet. secs. 28 and 29.
	Over rolling land, through scattering undergrowth.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Resurvey of the Subdivisions of T. 6 S., R.11 W.

chains	$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \mid \text{S } 28 \\ 1934 \end{array}$
	dig pits
	18x18x12 ins. on line N. and S. of cor. 3 ft. dist.
77.80	Road, bears NE. and SW.
80.18	At this point determined by double proportion;
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.
	$\begin{array}{c} \text{T6S } \mid \text{R11W} \\ \text{S20} \mid \text{S21} \\ \hline \text{S29} \mid \text{S28} \\ 1934 \end{array}$
	dig pits
	18x18x12 ins. in each sec. 3 ft. dist.
	Land, rolling.
	Soil, sandy, 1st. and 2nd. rate.
	Timber, none; undergrowth, greasewood, sage and cactus.

	From the cor. of secs. 21, 22, 27 and 28.
	N.89°50'W., on true line bet. secs. 21 and 28.
	Over rolling land, through scattering undergrowth.
39.89	set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \text{ S } 21 \\ \hline \text{S } 28 \\ 1934 \end{array}$
	dig pits
	18x18x12 ins. on line E. and W. of cor. 3 ft. dist.
77.45	Road, bears NE. and SW.
79.77	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling.
	Soil, sandy, 2nd rate.
	Timber, none; undergrowth, greasewood, sage and cactus.

	N.0°32'W., on true line bet. secs. 20 and 21.
	Over rolling land, through scattering undergrowth.
25.00	House bears W. about 10 chs. dist.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S20} \mid \text{S21} \\ 1934 \end{array}$
	dig pits

Resurvey of Subdivisions of T. 6 S., R. 11 W.

chains	18x18x12 ins. on line N. and S. of cor. 3 ft. dist.						
80.18	<p>The cor. of secs. 16, 17, 20, and 21, which is a badly rotted palo verde stake, 3 ins. diam., 14 ins. above ground with scribe marks illegible, set in a mound of earth.</p> <p>In place of and with the old stake alongside;</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 16, 17, 20 and 21 with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T6S. R11W</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td>S20</td><td>S21</td></tr> </table> <p>1934</p> </div> <p style="text-align: right;">dig pits</p> <p>18x18x12 ins. in each sec. 3 ft. dist.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering mesquite; undergrowth, greasewood, sage and cactus.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89° 58' W., on true line bet. secs. 16 and 21.</p> <p>Over rolling land, through scattering undergrowth.</p>	T6S. R11W		S17	S16	S20	S21
T6S. R11W							
S17	S16						
S20	S21						
3.25	Desert road, bears NE. and SW.						
40.12	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">$\frac{1}{4}$ S 16</td></tr> <tr><td colspan="2">S 21</td></tr> </table> <p>1934</p> </div> <p style="text-align: right;">dig pits</p> <p>18x18x12 ins. on line E. and W. of cor. 3 ft. dist.</p>	$\frac{1}{4}$ S 16		S 21			
$\frac{1}{4}$ S 16							
S 21							
80.24	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy, 2nd rate. Timber, scattering mesquite; undergrowth, greasewood, sage and cactus.</p> <hr style="border-top: 1px dashed black;"/> <p>N. 0° 02' W., on true line bet. secs. 16 and 17.</p> <p>Over rolling land, through scattering undergrowth.</p>						
12.90	Desert road, bears NE. and SW.						
40.37	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">$\frac{1}{4}$</td></tr> <tr><td>S17</td><td>S16</td></tr> </table> <p>1934</p> </div> <p style="text-align: right;">dig pits</p> <p>18x18x12 ins. on line N. and S. of cor. 3 ft. dist.</p>	$\frac{1}{4}$		S17	S16		
$\frac{1}{4}$							
S17	S16						

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	bottom										
62.00	S. bank of the Gila River, bears NE. and SW.										
67.10	Old canal, 40 lks. wide, course SW.										
80.74	At this point determined by double proportion. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T6S</td><td>R11W</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td colspan="2" style="text-align: center;">1934</td></tr> </table>	T6S	R11W	S 8	S 9			S17	S16	1934	
T6S	R11W										
S 8	S 9										
S17	S16										
1934											
	from which										
	A mesquite, 10 ins. diam., bears N.5°E., 82 lks. dist. mkd. T 6 S R 11 W S 9 B T.										
	A mesquite, 6 ins. diam., bears S.45°E., 206 lks. dist. mkd. T 6 S R 11 W S 16 B T.										
	Land, rolling. Soil, sandy, 2nd rate. Timber, scattering mesquite; undergrowth, greasewood, sage and cactus.										

	From the cor. of secs. 9, 10, 15 and 16. S.89°54'W., on true line bet. secs. 9 and 16. Over rolling land, through scattering undergrowth.										
40.11	The $\frac{1}{4}$ sec. cor., which is a mesquite stake, 3 ins. diam., 40 ins. long with scribe marks not legible, lying on mound of stone. At point for cor. with old stake alongside; Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock with broken glass at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.										
	<table> <tr><td>$\frac{1}{4}$</td><td>S 9</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td></td><td>S 16</td></tr> <tr><td colspan="2" style="text-align: center;">1934</td></tr> </table>	$\frac{1}{4}$	S 9				S 16	1934			
$\frac{1}{4}$	S 9										
	S 16										
1934											
	Thence, N.89°25'W., on a true line bet. secs. 9 and 16.										
2.65	Wash, 100 lks. wide, course NW.										
11.00	Wash, 80 lks. wide, course NE.										
17.76	Desert road, bears N.25°W., and S.25°E.										
30.40	S. bank of the Gila River, bears NE. and SW.										
35.20	Old canal, 20 lks. wide, course SW.										
40.05	The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, sandy, rocky, 3rd rate. Timber, palo verde and mesquite; undergrowth, greasewood, and sage.										

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	N.0°04'W., on true line bet. secs. 8 and 9. Over broken bottom land, through dense arrowweed and mesquite.
32.00	Main channel of the Gila River, 200 lks. wide, ^{dry,} course SW.
40.37	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit a clear glass beer bottle at base of post for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{c} \frac{1}{2} \\ s\ 8 s\ 9 \\ 1934 \end{array}$
	No other accessory available.
80.74	At this point determined by double proportion. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit brown glass beer bottle at base of post, for the cor. of secs. 4, 5, 8 and 9, with brass cap mkd. $\begin{array}{c} T6S\ R11W \\ s\ 5 s\ 4 \\ \hline s\ 8 s\ 9 \\ 1934 \end{array}$
	dig pits 18x18x12 ins. in each sec. 3 ft. dist. Land, rolling. Soil, sandy, 1st rate. Timber, cottonwood and mesquite; undergrowth, arrow weed and salt cedar.

	From the cor. of secs. 3, 4, 9 and 10. West, on true line bet. secs. 4 and 9. Over rolling land, through scattering undergrowth.
5.50	S. bank of the Gila River bottom bears NE. and S., Desc. 80 ft. over NW. slope.
7.00	Foot of descent, Enter dense brush.
37.00	Main channel of the Gila River, 200 lks. wide, ^{dry,} course SW.
40.37	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit a brown beer bottle at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{c} s\ 4 \\ \hline s\ 9 \\ 1934 \end{array}$
80.74	The cor. of secs. 4, 5, 8 and 9. Land, rolling and level. Soil, sandy, and rocky, 1st and 2nd rate. Timber, cottonwood and mesquite; undergrowth, arrowweed and salt cedar.

	N.0°07'W., on true line bet. secs. 4 and 5.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

Over rolling land, through dense brush.

40.37

Proportional distance.

Set an iron post, 5 ft. long, 1 in. diam., 27 ins. in the ground, deposit a brown beer bottle at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 5 | S 4
1934

from which

A mesquite 6 ins. diam., bears N. 46° E., 256 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.

81.05

Intersect the first standard parallel south at a point determined by single proportion bet. the standard cor. of secs. 32 and 33, and the Stand. $\frac{1}{4}$ sec. cor. on S. bdy. of sec. 33 T. 5 S.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for closing cor. of secs. 4 and 5, with brass cap mkd.

T5S R11W
S33

S 5 | S 4
C | C
T6S R11W
1934

from which

A mesquite 4 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ E. 71 lks. dist., mkd. B T.

A mesquite 6 ins. diam., bears S. 22° W. 129 lks. dist., mkd. T 6 S R 11 W S 5 C C B T.

From point of intersection the standard $\frac{1}{4}$ sec. cor. on south bdy. of sec. 33, T. 5 S. bears S. $89^{\circ}54'E.$, 17.95 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, cottonwood and mesquite; undergrowth, arrowweed, and salt cedar.

At the mid point of the south bdy. of sec. 4.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground with a glass beer bottle deposited at the base for $\frac{1}{4}$ sec. cor. of sec. 4 only, with brass cap mkd.

$\frac{1}{4}$ S 4
1934

from which

A cottonwood, 12 ins. diam., bears S. $19\frac{1}{2}^{\circ}$ E. 110 lks. dist., mkd $\frac{1}{4}$ S 4 B T.

A mesquite, 6 ins. diam., bears S. 15° W., 32 lks. dist., mkd $\frac{1}{4}$ S 4 B T.

From this cor. the standard cor. of secs. 33 and 34, T. 5 S., bears S. $89^{\circ}54'E.$ 17.83 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	<p>From the cor. of secs. 5,6,31 and 32, on S. bdy, of Tp., described in the field notes of the resurvey thereof under this group.</p> <p>N.0°28'W., on true line bet. secs. 31 and 32.</p> <p>Over rolling land, through scattering undergrowth.</p>
40.17	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S31 S32 1934 </p> <p style="text-align: right;">dig pits</p> <p>18x18x12 ins. on line N. and S. of cor. 3 ft. dist.</p>
57.40	Desert road, bears NE. and SW.
80.34	<p>At this point determined by double proportion,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 29,30,31 and 32, with brass cap mkd.</p> <p style="text-align: center;"> T6S R11W S30 S29 S31 S32 1934 </p> <p style="text-align: right;">dig pits</p> <p>18x18x12 ins. in each sec. 3 ft. dist.</p> <p>Land, rolling. Soil, sandy, 1st. rate. Timber, scattering mesquite; undergrowth, greasewood, sage and cactus.</p>
40.02	<p>From the cor. of secs. 28,29,32 and 33,</p> <p>S.89°48'W., on true line bet. secs. 29 and 32.</p> <p>Over rolling land, through scattering undergrowth.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 29 S 32 1934 </p> <p style="text-align: right;">dig pits</p> <p>18x18x12 ins. on line E. and W. of cor. 3 ft. dist.</p>
63.00	Desert road, bears NE. and SW.
80.04	<p>The cor. of secs. 29,30,31 and 32.</p> <p>Land, rolling. Soil, sandy, 1st. rate. Timber, scattering mesquite; undergrowth, sage and cactus.</p>
	<p>S.89°56'W., on true line bet. secs. 30 and 31.</p>

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

DON 408

chains	Over rolling land, through scattering undergrowth.
6.90	Desert road, bears NE. and SW.
39.95	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock with glass and a stone 6x3x2 ins. mkd. with a cross (X), at base of post, and in a mound of stone to top for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} S 30 \\ \hline S 31 \\ 1934 \end{array}$
78.11	The cor. of secs. 25, 30, 31 and 36 on W. bdy. of Tp, described in the field notes of the resurvey thereof under this group. Land, rolling. Soil, sandy, 2nd rate. Timber, scattering mesquite; undergrowth, greasewood, sage and cactus.

	From the cor. of secs. 29, 30, 31 and 32. N.0°09'E., on true line bet. secs. 29 and 30.
6.20	Road, bears NE. and SW.
40.17	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$S30 \begin{array}{c} \frac{1}{4} \\ \\ S29 \\ 1934 \end{array}$
	dig pits
	18x18x12 ins. on line N. and S. of cor. 3 ft. dist.
80.34	The cor. of secs. 19, 20, 29 and 30, which is a badly rotted mesquite post, 3 ins. diam., 40 ins. long, set in a mound of stone. No marks legible. At point for cor. and with the old stake alongside; Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock with glass and a stone 8x6x2 ins. mkd. with a cross (X), at base of post, and in a mound of stone to top for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.
	$\begin{array}{c} T6S R11W \\ S19 S20 \\ \hline S30 S29 \\ 1934 \end{array}$
	Land, rolling. Soil, sandy, rocky, 2nd rate. Timber, scattering mesquite and palo verde; undergrowth, greasewood, sage and cactus.

	From the cor. of secs. 20, 21, 28 and 29, S.89°56'W., on true line bet. secs. 20 and 29. Over rolling land, through scattering undergrowth.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	
15.00	Desert road, bears NW. and SE.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit glass at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S } 20 \\ \hline \frac{1}{4} \text{ S } 29 \\ 1934 \end{array}$ <p style="text-align: right;">dig pits</p> 18x18x12 ins. on line E. and W. of cor. 3 ft. dist.
45.00	Desert road, bears NE. and SW.
79.96	The cor. of secs. 19, 20, 29 and 30. Land, rolling. Soil, sandy, rocky, 3rd rate. Timber, scattering mesquite and ironwood; undergrowth, greasewood and sage.

	S. 89° 52' W., on true line bet. secs. 19 and 30. Over rolling land, through scattering undergrowth.
40.38	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S } 19 \\ \hline \frac{1}{4} \text{ S } 30 \\ 1934 \end{array}$ <p style="text-align: right;">from which</p> A palo verde, 10 ins. diam., bears S. 85° W., 11 lks. dist., mkd. $\frac{1}{4}$ S 30 B T. Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist.
78.89	The cor. of secs. 19, 24, 25 and 30, on W. bdy. of Tp. described in the field notes of the resurvey thereof under this group. Land, rolling. Soil, sandy, rocky, 3rd rate. Timber, scattering mesquite and ironwood; undergrowth, greasewood, sage and cactus.

	From the cor. of secs. 19, 20, 29 and 30, N. 1° 28' W., on true line bet. secs. 19 and 20. Over rolling land, through scattering undergrowth.
40.06	The $\frac{1}{4}$ sec. cor., which is a badly weathered mesquite stake, 4 ins. diam., 20 ins. above ground, with no scribe mark legible. In place of and with the old stake, alongside; Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

$$\begin{array}{c} \frac{1}{4} \\ S19 \quad S20 \\ 1934 \end{array}$$

from which

The original bearing trees:

A mesquite, 6 ins. diam., bears N. 8°E., 127 lks. dist., no marks legible.

A mesquite, 9 ins. diam., bears N. 80°W., 114 lks. dist., marks not legible, I add the marks $\frac{1}{2}$ S 19 B T.

New bearing tree:

A palo verde, 12 ins. diam., bears S. 81 $\frac{1}{2}$ °E., 89 lks. dist., mkd. $\frac{1}{2}$ S 20 B T.

Thence

N. 0°07'E., on a true line bet. secs. 19 and 20.

1.85 Wash, 50 lks. wide, course NW.

8.00 Enter old river bottom and dense brush, bears NE. and SW.

13.30 Old canal, course S. 60°W.

40.31 At this point determined by double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit broken glass at base of post, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

$$\begin{array}{c} T6S \quad R11W \\ S18 \quad S17 \\ \hline S19 \quad S20 \end{array}$$

1934

from which

A cottonwood, 11 ins. in diam., bears S. 15 $\frac{1}{2}$ °E., 124 lks. dist., mkd. T 6 S R 11 W S 20 B T.

Land, rolling.

Soil, sandy, rocky; 2nd rate.

Timber, mesquite, ironwood and cottonwood; undergrowth, arrowweed, greasewood and sage.

From the cor. of secs. 16, 17, 20 and 21,

S. 89°51'W., on true line bet. secs. 17 and 20.

Over rolling land, through scattering undergrowth.

4.00 Road bears NE. and SW.

40.06 The $\frac{1}{4}$ sec. cor., which is a badly weathered mesquite stake, 3 ins. diam., 24 ins. above ground, with scribe marks not legible.

In place of and with the old stake alongside;

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \quad S \quad 17 \\ \hline S \quad 20 \end{array}$$

1934

dig pits

18x18x12 ins. on line E. and W. of cor. 3 ft. dist.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	Thence,
	N.89°44'W., on a true line bet. secs. 17 and 20.
15.80	S. bank of the Gila River, bottom, bears NE. and SW.,
17.80	Enter dense arrowweed.
26.50	Leave arrowweed, thence over sandy overflow land.
39.99	The cor. of secs. 17,18,19 and 20.
	Land, slightly rolling. Soil, sandy loam, 1st. rate. Timber, cottonwood and mesquite; undergrowth, arrowweed, salt cedar and greasewood.

	S.89°49'W., on true line bet. secs. 18 and 19.
	Over sandy river bottom, through dense brush.
40.09	Proportional distance,
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit broken glass at base of post, for $\frac{1}{2}$ sec. cor. with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 18 \\ \hline S 19 \\ 1934 \end{array}$
	No other accessory.
57.00	Fence, bears N. and S.
60.60	Leave river bottom, bears NW. and SE.
	Thence, over mesa land, through heavy mesquite.
78.23	The cor. of secs. 13,18,19 and 24, on W. bdy. of Tp. des- cribed in the field notes of the resurvey thereof under this group.
	Land, rolling. Soil, sandy, silt loam, 1st. rate. Timber, cottonwood, and mesquite; undergrowth, arrowweed, salt cedar and sage.

	From the cor. of secs. 17,18,19 and 20.
	N.0°12'W., on true line bet. secs. 17 and 18.
	Over rolling river bottom, through dense brush.
40.31	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit a beer bottle at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S18 S17 \\ \hline 1934 \end{array}$
	No other accessory.
80.62	At this point determined by double proportion,

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit dark green glass alongside of post, for cor. of secs. 7, 8, 17 and 18 with brass cap mkd.

T6S R11W	
S 7	S 8
S 18	S 17

1934

dig pits

18x18x12 ins. in each sec. 3 ft. dist.

Land, rolling.

Soil, sandy, 1st. rate.

Timber cottonwood and mesquite; undergrowth, arrowweed, and salt cedar.

From the cor. of secs. 8, 9, 16 and 17,

West, on true line bet. secs. 8 and 17.

Over rolling bottom land, through mesquite, greasewood and sage.

40.17

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit green beer bottle at base of post, for $\frac{1}{2}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$	S 8
$\frac{1}{4}$	S 17

1934

from which

A mesquite, 4 ins. diam., bears N.22°E., 75 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.

A mesquite, 7 ins. diam., bears S.27 $\frac{1}{2}$ °W., 207 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

80.33

The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, sandy, 1st rate.

Timber, mesquite; undergrowth, arrowweed, sage, greasewood and cactus.

S.89°38'W., on true line bet. secs. 7 and 18.

Over rolling bottom land, through dense brush.

40.01

Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit a clear glass 6 oz. bottle mkd. Thomas A. Edison special battery oil, at base of post; for $\frac{1}{2}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 7
$\frac{1}{4}$	S 18

1934

from which

A cottonwood, 12 ins. diam., bears N.67°E., 44 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	
47.00	Main channel of the Gila River, 200 lks. wide, course SW.
78.23	The cor. of secs. 7, 12, 13 and 18, on W. bdy. of Tp, described in the field notes of the resurvey thereof under this group. Land, rolling. Soil, sandy, 1st. rate. Timber, cottonwood and mesquite; undergrowth, arrowweed and salt cedar.

	From the cor. of secs. 7, 8, 17 and 18. N.0°03'W., on true line bet. secs. 7 and 8. Over rolling river bottom, through dense brush.
18.00	Main channel of the Gila River, 200 lks. wide, course SW.
40.31	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit a green glass beer bottle at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 7\ \ S\ 8 \\ 1934 \end{array}$ No other accessory.
80.62	At this point determined by double proportion, Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, deposit a brown glass beer bottle at base of post, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd. $\begin{array}{c} T6S\ R11W \\ S\ 6\ \ S\ 5 \\ S\ 7\ \ S\ 8 \\ 1934 \end{array}$ from which A willow, 18 ins. in diam., bears N.74°E., 153 lks. dist., mkd. T. 6 S R 11 W S 5 B T. A cottonwood, 16 ins. diam., bears S.57°E., 148 lks. dist., mkd. T 6 S R 11 W S 8 B T. No other trees available. Land, rolling. Soil, sandy, 1st rate. Timber, cottonwood and mesquite; undergrowth, arrowweed and salt cedar.

	From the cor. of secs. 4, 5, 8 and 9. S.89°56'W., on true line bet. secs. 5 and 8. Over rolling river bottom, through dense brush.
40.12	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit a dark brown beer bottle at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{c} \frac{1}{4} \ S\ 5 \\ S\ 8 \\ 1934 \end{array}$ raise a mound

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains	of stone, 3 ft. base 2 ft. high N. of cor.
80.24	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, sandy, 1st. rate. Timber, mesquite and cottonwood; undergrowth, arrowweed, sage and greasewood.
40.21	----- S. 89°44'W., on true line bet. secs. 6 and 7. Over rolling bottom land, through dense brush. Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit a brown beer bottle at base of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{r} \frac{1}{2} \text{ S } 6 \\ \hline \frac{1}{2} \text{ S } 7 \\ 1934 \end{array}$ from which A mesquite, 14 ins. diam., bears N. 80 $\frac{1}{2}$ °E., 102 lks. dist., mkd. $\frac{1}{4}$ S 6 B T. A mesquite, 6 ins. diam., bears S. 2°E., 50 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.
73.00	Fence, bears N, and S.
78.51	The cor. of secs. 1, 6, 7 and 12, on W. bdy. of Tp. described in the field notes of the resurvey thereof under this group. Land, rolling. Soil, sandy, 1st rate. Timber, scattering cottonwood and mesquite; undergrowth, arrowweed and salt cedar.
32.24	----- From the cor. of secs. 5, 6, 7 and 8. N. 0°16'W., on true line bet. secs. 5 and 6. Over rolling land, through dense brush.
36.78	Fence, bears E. and W.
38.38	Fence, bears E. and W.
40.31	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, deposit brown beer bottle at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{2} \\ \text{S } 6 \text{ } \text{S } 5 \\ 1934 \end{array}$ from which A mesquite, 5 ins. diam., bears N. 62 $\frac{1}{2}$ °E., 135 lks. dist., mkd. $\frac{1}{4}$ S 5 B T. A mesquite, 5 ins. diam., bears N. 30°W., 121 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

chains

46.16

Fence, bears E. and W.

58.00

Fence, bears E. and W.

81.10

Intersect the first standard parallel south.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a $\frac{1}{2}$ pint bottle deposited at the base for closing cor. of secs. 5 and 6, with brass cap mkd.

T5S R11W

S32

S 6 | S 5

C | C

T6S R11W

1934

from which

A mesquite, 6 ins. diam., bears S.47°E., 48 lks. dist. mkd. T. 6 S R 11 W S 5 C C B T.

No other tree available in sec. 6.

From point of intersection the standard $\frac{1}{2}$ sec. cor. of sec. 5, T. 5 S., bears S.89°54'E., 18.46 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

Continue N.0°16'W., on blank line.

81.24

The old closing cor. of secs. 5 and 6, which is an old stake, 4 ins. sq. 8 ins. above ground, firmly set in a mound of earth, some scribe marks visible.

A mesquite stump with old blaze showing bears N.34°50'E., 85 lks. dist.

A mesquite stump bears N.87°08'E., 70 lks. dist. some scribe marks visible.

Land, rolling.

Soil, sandy silt, 1st rate.

Timber, mesquite, undergrowth, arrowweed and sage.

At the mid-point of the N. bdy. of sec. 5.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a brown glass beer bottle deposited at the base for $\frac{1}{2}$ sec. cor. of sec. 5 only with brass cap mkd.

 $\frac{1}{2}$ S 5

1934

dig pits

18x18x12 ins. on line E. and W. of cor. 3 ft. dist.

From this cor. the standard cor. of secs. 32 and 33, T.5 S., bears S.89°54'E., 18.21 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

At a point on the N. bdy. of sec. 6, determined by single proportion bet. the NE. and NW. corners of sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with green ale bottle deposited at base for $\frac{1}{4}$ sec. cor. of sec. 6 only with brass cap mkd.

Resurvey of the Subdivisions of T. 6 S., R. 11 W.

37

chains

 $\frac{1}{2}$ S 6
1934

dig pits

18x18x12 ins. on line E. and W. of cor. 3 ft. dist.

From this cor., the standard cor. of secs. 31 and 32, T. 5 S., bears S.89°54'E., 18.41 chs. dist., described in the field notes of the first standard parallel south resurveyed under this group.

GENERAL DESCRIPTION

The elevation of this township ranges from about 530 feet along the East boundary, to about 420 feet in the northwest portion. The drainage is to the North and Northwest. The Southeast portion of the township is a rolling mesa. The soil is mostly sand and gravel, with some lava rock.

The Gila River runs through the northwest quarter of the township in a southwesterly direction. The higher portions are covered with a very scattered growth of Palo Verde and Ironwood. The river bottom is covered with a dense growth of Mesquite and scattered cottonwood trees.

Several old houses were located in the bottom lands, but no one has lived in them for a number of years.

Several old roads traverse the township, but they are not used much and are in very poor condition.

The nearest post office and shipping point is located about three miles to the southwest on the Southern Pacific Rail Road and U.S. Highway No. 80.

No mineral deposits were noted.

FIELD ASSISTANTS.

NAMES.	CAPACITY.
J.M.Champie	First Assistant.
A.R.Zent	Chainman.
Frank Burt	Field Assistant.
Paul Wolf	Field Assistant.
Gordon Bates	Field Assistant.
Murray Sloan	Field Assistant.
Harvey L. Samuel	Field Assistant.

42
39

BOOK 4085

CERTIFICATE OF UNITED STATES SURVEYOR

We, Anthony C. Kimmell, U.S. Surveyor, and
Herman J. Shafer, Jess R. Horak and
William M. Heina, U.S. Transitmen, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934, we have well, faithfully, and truly

in ~~my~~ ^{our} own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, dependently resurveyed the subdivisional
lines of Township 6 South, Range 11 West,

of the Gila and Salt
River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by ~~me~~ ^{us}, and under ~~my~~ ^{our} direction; and that all the corners of
re said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-
tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of
re such survey.

For signature of Herman J. Shafer,
Jess R. Horak and William M. Heina,
see the attached certificates.

Anthony C. Kimmell
U. S. Surveyor.
Sentinel, Arizona,
March 26, 1934

APPROVAL

Office of U. S. Supervisor of Surveys,

19

The foregoing field notes of the survey of

executed by

under his special instructions dated _____, 19____, having been
critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys
they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in _____
_____, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
William M. Heina	Principal Assistant.
A. W. Porter	Principal Assistant.
George R. Hegi	Chainman.
Joseph W. Coulter	Field Assistant.
Angus Pryor	Field Assistant.
Harry Hayes	Field Assistant.
H. F. Reeves	Field Assistant.
P. L. Lowry	Field Assistant.
Al Blake	Field Assistant.
J. Wilson Cobb	Field Assistant.
Tom Flynn	Field Assistant.

44
41

BOOK 4085

CERTIFICATE OF UNITED STATES SURVEYOR

We, Anthony C. Kimmell, U.S. Surveyor, and
Herman J. Shafer, Jess R. Horak and
William M. Heina, U.S. Transitmen

, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15 th day of February, 1934, I have well, faithfully, and truly

in ~~my~~ ^{our} own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, dependently resurveyed the subdivisonal
lines of Township 6 South, Range 11 West,

of the Gila and Salt
River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by ~~me~~ ^{us}, and under ~~my~~ ^{our} direction; and that all the corners of
~~the~~ ^{re} said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of
such ~~the~~ ^{re} survey.

For signature of Jess R. Horak,
William M. Heina and Anthony C.
Kimmell, see the attached certificates.

Herman J. Shafer
U.S. Transitman

APPROVAL

Sentinel, Arizona.
February 23, 1934.

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

19

The foregoing field notes of the survey of

executed by
under his special instructions dated , 19 , having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in
, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Rowland Norris	Principal Assistant.
Ernest R. Shockley	Chainman.
H.B.Burt	Field Assistant.
Phil C. Ensign	Field Assistant.
Merritt Preston	Field Assistant.
Aubrey Washburn	Field Assistant.

46
43

BOOK 488

CERTIFICATE OF UNITED STATES SURVEYOR

We, Anthony C. Kimmell, U.S. Surveyor, and
Herman J. Shafer, Jess R. Horak and
William M. Heina, U.S. Transitmen,....., hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934, we have well, faithfully, and truly

^{our} in ~~my~~ own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, dependently resurveyed the subdivisonal
lines of Township 6 South, Range 11 West,

..... of the Gila and Salt
River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by ^{us} ~~me~~, and under ^{our} ~~my~~ direction; and that all the corners of
said ^{re} survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-
tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of
^{re} such survey.

For signature of Anthony C. Kimmell,
Herman J. Shafer and William M Heina,
see the attached certificates.

Jess R. Horak
U.S. Transitman

Sentinel, Arizona.
March 26, 1934.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

....., 19.....

The foregoing field notes of the survey of

executed by

under his special instructions dated, 19....., having been
critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys
they describe, are hereby approved.

.....
U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in,
....., has been correctly copied from the original notes on file in this office.

.....
U. S. Supervisor of Surveys.

BOOK 403

4-680
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Dee W. May	First Assistant.
John Maddux	Chainman.
W.C.Clark	Field Assistant.
Chas. A. Mayes	Field Assistant.
Alva Mills	Field Assistant.
Chas. Grinstaff	Field Assistant.

48
45
BOOK 4085

CERTIFICATE OF UNITED STATES SURVEYOR

We, Anthony C. Kimmell, U.S. Surveyor, and
Herman J. Shafer, Jess R. Horak and
William M. Heina, U.S. Transitmen,

hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 15th day of February, 1934 have well, faithfully, and truly

in ^{our} ~~my~~ own proper person, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, dependently resurveyed the subdivisional
lines of Township 6 South, Range 11 West,

of the Gila and Salt

River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by ^{us} ~~me~~, and under ^{our} ~~my~~ direction; and that all the corners of
^{re} said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-
tions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of
^{re} such survey.

For signature of Anthony C. Kimmell,
Herman J. Shafer and Jess R. Horak,
see the attached certificates.

William M. Heina
U.S. Transitman.

APPROVAL

Sentinel, Arizona,
March 26, 1934.

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, June 11, 1935.

The foregoing field notes of the dependent resurvey of the subdivisional lines
of Township 6 South, Range 11 West, of the Gila and Salt River Meridian,
in the State of Arizona,

executed by Anthony C. Kimmell, U.S. Surveyor, and Herman J. Shafer, Jess R.
Horak and William M. Heina, U.S. Transitmen,

under ^{their} ~~his~~ special instructions dated February 15, 1934, having been
critically examined, and the necessary corrections and explanations made, the said field notes, and the ^{re} ~~surveys~~
they describe, are hereby approved.

Charles D. Simon
U. S. Supervisor of Surveys.

~~I certify that the foregoing transcript of the field notes of the above-described surveys in
has been correctly copied from the original notes on file in~~

~~U. S. Supervisor of Surveys.~~