

Book "E"

4119

4-878
(April 1933)

(1)

BOOK 4119

FIELD NOTES

OF THE RESURVEY OF

SOUTH BOUNDARY

WEST BOUNDARY

NORTH BOUNDARY

AND

SUBDIVISION LINES

TOWNSHIP 6 NORTH, RANGE 29 EAST

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Roger F. Wilson - U. S. Surveyor

Carroll I. Parkman - U.S. Transitman

supplemental
Under special instructions dated January 31, 1936, which provided for the surveys included under Group No. 192 Arizona, bearing the approval of the Commissioner of the General Land Office under date of April 2, 1936 and assignment instructions dated July 31 and Oct. 5, 1936

ReSurvey commenced September 5, 1936

ReSurvey completed November 6, 1936

4119

4119

INDEX DIAGRAM.

Township _____, *Range* _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

INDEX-DIAGRAM

BOOK 4119

	31	32	33	34	35	36	
	25 26	27	28 29	30	31	32 33	
1 22	6 94	5 79	4 67	3 55	2 44	1	6
	93 94	93 92	79 68	67 66	55 54	45	44
21		78		54			
12	7 91	8	9 65	10	11 43	12	7
20	90	90 89	77 76	65 64	53		42
		77		53			
20		76		52		41	
13	18	17	16	15	14	13	18
19	87 87	87 86	75 74	T.6N62 R.29E.51 62 62	51	40	40
24 18	19 86	20 74	21 61	22 50	23 39	24	19
	84 85	84 73	72 60	60 59	49 38		38
25 17	30 83	29 71	28 59	27 48	26 37	25	30
	82 83	82 81	70 58	58 57	48 47	36	36 35
16	control cor. 31 81	32 69	33 56	34 46	35 35	36	31
4	15 80	control cor. 11 10	10 9	8 45	7 34	6	5
4	13 12						
5	5 6	5	4	3	2	1	
5	1/4 Sec. Cor. reconstructed for Tp. Cor. Control						

Accepted surveys.

Resurveyed under this group.

Retraced under this group (For Tp. Cor. reestablishment)

The resurveys herein described were executed by Roger F. Wilson, U. S. Surveyor, using a Buff and Buff solar transit No. 10125, Sept. to Oct. 13, 1936, and a Buff and Buff solar transit No. 23829, Oct. 14 to Nov. 6, 1936; and by Carroll I. Parkman, U.S. Transitman, using a Young and Sons solar transit No. 8477 from Oct. 14, 1936 throughout the entire period of work. These instruments are each equipped with improved Smith solar attachment and otherwise conform to the standard specifications of the General Land Office. The instruments were examined and tested by the District Cadastral Engineer just prior to their assignment to these resurveys and were approved at that time conditional upon satisfactory results of field tests.

PRELIMINARY TESTS OF INSTRUMENTS

Preliminary test of Buff and Buff transit No. 10125, on Sept. 4, 1936, by Roger F. Wilson, U.S. Surveyor, is described in the notes of resurvey of T. 7 N., R. 29 E. and the final test is herein described.

Oct. 14, 1936, at camp in N. center of sec. 34, T. 6 N., R. 29 E., G. & S.R. Base and Meridian, Arizona, in latitude $33^{\circ} 51\frac{1}{2}'$ N., and longitude $109^{\circ} 19'$ W., determined from data accompanying the instructions for Group No. 192. We examine the instruments and find no appreciable errors, then test the indications of the solar apparatus by comparison with a meridian established this day by Polaris observation by Roger F. Wilson, U.S. Surveyor, using Buff and Buff transit No. 23829 as follows:

Watch checked in Springerville, Arizona, at 2 p.m. on Oct. 14, 1936. Make an hour angle observation on Polaris E. of the meridian turning left from a prominent dead topped tree about 3 miles dist., accumulating the angle of 6 readings, 3 direct and 3 reverse.

Mean watch time p.m.	6 ^h 6.5 ^m
Watch fast of L.M.T.	17.2 ^m
Accumulated angle reference point to Polaris	97° 10'
Mean Angle	16° 11' 42"
Azimuth of Polaris	<u>1° 14' 48"</u>
Bearing of reference point	17° 26' 30"
Mean observed altitude	33° 47' 42"
Reduced latitude	33° 51' 36" N.

Then turn 17° 26' 30" left from reference point and establish a point in the meridian about 10.00 chs. N. by driving a tack in a stake firmly set in the ground.

Test of Buff and Buff transit No. 23829 by Roger F. Wilson, U. S. Surveyor.

Oct. 15, 1936, at 8h 00m, a.m. app.t., set off $33^{\circ} 51\frac{1}{2}'$

2.

N. on the latitude arc; $8^{\circ} 34\frac{1}{2}'$ S. on the declination arc; and determine a meridian with the solar, which agrees within 1' with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian and obtain a reading of $8^{\circ} 39'$ S., on the declination arc; which agrees with the computed declination of the sun.

At 4h 00m p.m. app.t., with the latitude arc unchanged, set off $8^{\circ} 42'$ S. on the declination arc and determine a meridian with the solar, which agrees with the true meridian.

Test of Young and Sons transit No. 8477 by Carroll I. Parkman, U.S. Transitman.
(Same transit used Sept. 4 to Oct. 14 by Robt. H. Fischer, U.S. Transitman in resurvey T. 7 N., R. 29 E.)

Oct. 15, 1936, at 8h 00m, a.m. app.t., set off $33^{\circ} 51\frac{1}{2}'$ N. on the latitude arc; $8^{\circ} 34\frac{1}{2}'$ S. on the declination arc and determine a meridian with the solar which agrees within 1' 30" with the true meridian.

At app. noon with the latitude arc unchanged; observe the sun on the meridian and obtain a reading of $8^{\circ} 39'$ S., on the declination arc, which agrees with the computed declination of the sun.

At 4h 00m p.m. app.t., with the latitude arc unchanged set off $8^{\circ} 42'$ S. on the declination arc; and determine a meridian with the solar, which agrees within 1' with the true meridian.

All of the solar observations made with these transits during the usual hours of solar work coming within 1' 30" of the true meridian, demonstrates that they are in satisfactory adjustment on this date.

All measurements are made with Lallie and Lufkin steel tapes, 5 chs. long, graduated every link for the first 100 lks. and the balance at intervals of 10 lks. The tapes were tested with a Lufkin Standard, by comparison and found correct. The measurements are made on the slope; the vertical angle of each interval is determined with a clinometer in good adjustment and the horizontal equivalents are entered in the field note record.

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

3.

Chains

The South bdy. of T. 6 N., R. 29 E., was surveyed in 1883 by W. R. Fitzgerald, U.S.D.S., establishing $\frac{1}{4}$ sec. and sec. cors., alternately, at 40.00 ch. intervals, counting from the east, with common reference to areas both sides of the line. No retracement or resurvey of any part of this line is of record. The following notes describe a dependent resurvey of the entire line, reconstructing all existing corners, retaining their original references, reestablishing all missing corners by proportional measurement, and monumenting all corners with regulation brass-capped iron posts.

RETRACEMENT FOR RESURVEY

From the cor. of Tps. 5 and 6 N., Rs. 29 and 30 E., S. $89^{\circ} 52'$ W., on random line, bet. secs. 1 and 36.

40.00 No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.

80.24 A point 28 lks. S. of original cor. of secs. 1, 2, 35 and 36. True course and dist. of the line bet. secs. 1 and 36 are therefore, N. $89^{\circ} 56'$ W., 80.24 chs.

S. $89^{\circ} 52'$ W., on random line, bet. secs. 2 and 35.

40.00 No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.

78.91 A point 87 lks. N. of the original cor. of secs. 2, 3, 34 and 35. True course and dist. of line bet. secs. 2 and 35 are therefore S. $89^{\circ} 14'$ W., 78.92 chs.

S. $89^{\circ} 52'$ W., on random line, bet. secs. 3 and 34.

40.00 No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.

81.62 A point 2.16 chs. S. of the original cor. of secs. 3, 4, 33 and 34. True course and dist. of line bet. secs. 3 and 34 are therefore, N. $88^{\circ} 37'$ W., 81.64 chs.

S. $89^{\circ} 52'$ W., on random line, bet. secs. 4 and 33.

40.00 No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.

81.13 A point 1.96 chs. N. of the original cor. of secs. 4, 5, 32 and 33. True course and dist. of line bet. secs. 4 and 33 are therefore, S. $88^{\circ} 29'$ W., 81.16 chs.

S. $89^{\circ} 52'$ W., on random line, bet. secs. 5 and 32 ($E\frac{1}{2}$).

39.16 A point 90 lks. S. of the original $\frac{1}{4}$ sec. cor. True course and dist. of $E\frac{1}{2}$ of line bet. secs. 5 and 32 are therefore, N. $88^{\circ} 49'$ W., 39.17 chs.

Thence,

S. $89^{\circ} 52'$ W., on random line, bet. secs. 5 and 32 ($W\frac{1}{2}$).

39.85 A point 10 lks. S. of the original cor. of secs. 5, 6, 31 and 32. True course and dist. of $W\frac{1}{2}$ of line bet. secs. 5 and 32 are therefore, N. $89^{\circ} 59'$ W., 39.85 chs.

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

4.

Chains	S. 89° 52' W., on random line, bet. secs. 6 and 31.												
40.00	No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.												
80.40	(Record dist.) No trace of the original cor. of Tps. 5 and 6 N., Rs. 28 and 29 E. Set temp. cor.												
	Thence,												
	N. 89° 55' W., (record course) bet. secs. 1 and 36. continuing measurement.												
120.40	No trace of original $\frac{1}{4}$ sec. cor.												
164.81	A point 6.98 chs. N. of the original cor. of secs. 1, 2, 35 and 36, which is an aspen tree, 12 ins. diam., faintly mkd. on bark. Remark on bark T6N R28E on N. face, S36 on NE. face, S1 on SE. face; T5N R28E on S. face, S2 on SW. face, and S35 on NW. face and witnessed by the record bearing tree: A yellow pine, 16 ins. diam., S. 16 $\frac{1}{2}$ ° W., 14 lks. dist. faintly mkd. on bark. Remark on bark, T6N R28E S2 BT. At a point 10 lks. East of true cor. point, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground for witness cor. to cor. of secs. 1, 2, 35 and 36, with brass cap mkd.,												
	<table style="margin: auto;"> <tr><td></td><td>T6N R28E</td><td></td></tr> <tr><td>WC</td><td>S35 S36</td><td></td></tr> <tr><td></td><td>S 2 S 1</td><td></td></tr> <tr><td></td><td>T5N</td><td></td></tr> </table>		T6N R28E		WC	S35 S36			S 2 S 1			T5N	
	T6N R28E												
WC	S35 S36												
	S 2 S 1												
	T5N												
	1936												
	and establish additional bearing trees to true cor. point:												
	A yellow pine, 9 ins. diam., brs. N. 52 $\frac{1}{2}$ ° E., 28 lks. dist. mkd. T6N R28E S36 BT.												
	A spruce, 12 ins. diam., brs. S. 8° E., 74 lks. dist., mkd. T5N R28E S1 BT.												
	A yellow pine, 8 ins. diam., brs. N. 50° W., 37 lks. dist., mkd. T6N R28E S35 BT.												
	True course and dist. of direct line back to cor. of secs. 5, 6, 31 and 32 are therefore N. 87° 33' E., 164.96 chs.												
	Thence,												
	N. 87° 33' E., on trial latitudinal Tp. bdy. bet. secs. 1 and 36.												
82.27	(Proportional dist.) Set temp. Tp. cor. "A" and remove the temp. cor. previously set.												
	From the $\frac{1}{4}$ sec. cor. of secs. 36 and 31, Ts. 6 N., Rs. 28 and 29 E.												
	South, on random line, bet. secs. 31 and 36 (S $\frac{1}{2}$).												
40.00	No trace of original Tp. cor. Continue measurement.												
	South, on random line, bet. secs. 1 and 6 (N. $\frac{1}{2}$)												
79.19	A point 1.20 chs. W. of the original $\frac{1}{4}$ sec. cor. of secs. 1 and 6, Ts. 5 N., Rs. 28 and 29 E. which is an unmarked lava stone, 14x8x4 ins. above ground, firmly set and												

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

5.

Chains

witnessed by the record bearing tree:

A yellow pine, 14 ins. diam., N. 15° W., 17 lks. dist. Overgrowth removed shows marking $\frac{1}{4}$ S. Reconstruct this cor. monument as follows: remove old stone and in same place set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock with the old stone, mkd. with a cross (X) reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 1 $\frac{1}{4}$ S 6
|
1936

and establish additional bearing trees:

A yellow pine, 14 ins. diam., brs. S. 41° E., 72 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

A spruce, 14 ins. diam., brs. S. 51 $\frac{1}{2}$ ° W., 46 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

The true course and dist., of a direct line back to the $\frac{1}{4}$ sec. cor. of secs. 31 and 36 are therefore, N. 0° 52' W., 79.20 chs.

Thence,

N. 0° 52' W., on true meridional range line, bet. secs. 1 and 6 (N $\frac{1}{2}$).

39.60

(Proportional dist.) Set temp. Tp. cor. "B". From which temp. Tp. cor. "A" brs. 3.75 chs. W., and 1.05 chs. S. The point for reestablishment of the missing cor. of Tps. 5 and 6 N., Rs. 28 and 29 E., is therefore, 1.05 chs. N. from temp. cor. "A" and 3.75 chs. W., from temp. cor. "B". The true courses and distances of the portions of the Tp. bdys. controlled by this reestablished Tp. cor. are therefore:

Line bet. secs. 1 and 36; S. 86° 49' W., 82.32 chs.
S $\frac{1}{2}$ of line bet. secs. 31 and 36; N. 4° 33' E., 39.73 chs.
Line bet. secs. 6 and 31; S. 88° 17' W., 82.65 chs.
N. $\frac{1}{2}$ of line bet. secs. 1 and 6; N. 6° 16' W., 39.84 chs..

RESURVEY

From the cor. of Tps. 5 and 6 N., Rs. 29 and 30 E., which is an iron post, 3 ins. diam., projecting 10 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

Thence,

N. 89° 56' W., on true line, bet. secs. 1 and 36.

Over level open land.

0.44 Fence (5 strand barbed wire) brs., S. 86° W., and N. 86° E.

5.24 Draw, in swampy bottom land, course NW.

36.44 Stream of water, 2 lks. wide, 4 ins. deep, course NE.

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

6.

- Chains Thence over grassy meadow.
- 40.12 (Mid. point). Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- $\frac{1}{4}$ S 36
S 1
- 1936
- from which
- A spruce, 10 ins. diam., brs. N. 86° 53' W., 10.75 chs. dist., mkd. $\frac{1}{4}$ S36 BT.
- A spruce, 10 ins. diam., brs. S. 87° 35' W., 10.32 chs. dist., mkd. $\frac{1}{4}$ S1 BT.
- Continue over grassy meadow.
- 50.12 Fence (5 strand barbed wire) brs. N. 55° W., and S. 55° E. Leave grassy meadow, enter timber, brs. NW. and SE.
- 51.24 Old graded highway brs. NW. and SE. Thence over rolling land. Asc. 160 ft., over NE. slope to
- 66.14 Thence over N. slope to
- 80.24 Intersect the original cor. of secs. 1, 2, 35 and 36, which is an unmarked sandstone, 16x14x8 ins. firmly set in a mound of stone and witnessed by the three record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground with the original cor. stone reset alongside, for cor. of secs. 1, 2, 35 and 36, with brass cap mkd:
- | | |
|-----|------|
| T6N | R29E |
| S35 | S36 |
| S 2 | S 1 |
| T5N | |
- 1936
- from which
- the original bearing trees:
- A sugar pine, 10 ins. diam., brs. N. 58° E., 18 lks. dist., mkd. T6N R29E S36 BT.
- A fir stump, 10 ins. diam., brs. S. 39 $\frac{1}{2}$ ° W., 26 lks. dist., mkg. overgrown.
- A yellow pine, 14 ins. diam., brs. N. 82 $\frac{1}{2}$ ° W., 26 lks. dist., mkd. T6N R29E S35 BT.
- and establish additional bearing trees:
- A sugar pine, 12 ins. diam., brs. S. 57 $\frac{1}{2}$ ° E., 61 lks. dist., mkd. T5N R29E S1 BT.
- A sugar pine, 12 ins. diam., brs. S. 8° W., 100 lks. dist., mkd. T5N R29E S2 BT.
- Land, level and rolling.
Soil, volcanic loam, gravelly and rocky, 1st and 4th rates.
Timber, yellow pine, spruce, aspen fir and sugar pine.
Undergrowth, scrub timber and bunch grass.

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

DOK 4112

Chains	<p>S. 89° 14' W., on true line, bet. secs. 2 and 35.</p> <p>Over mountainous land, thru medium timber and undergrowth. Desc. over N. slope to</p> <p>0.44 Spur, slopes N. 60° W. Desc. 46 ft. over SW. slope.</p> <p>6.22 Draw, course N. 20° W., asc. 80 ft. over NE. slope.</p> <p>6.62 Graded road, brs. N. 20° W., about 20 chs. to highway and S. 30° E.</p> <p>12.92 Spur, slopes NE.; desc. 35 ft. over NW. slope.</p> <p>17.02 Draw, course N. 20° E.; asc. 285 ft. over SE. slope.</p> <p>34.42 Ridge, brs. SW. and N. 25° E.; desc. 15 ft. over NW. slope to</p> <p>39.46 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4} \frac{S \ 35}{S \ 2}$ <p>1936</p> <p>from which</p> <p>A yellow pine, 20 ins. diam., brs. S. 2° W., 80 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p>A yellow pine, 16 ins. diam., brs. N. 21$\frac{1}{2}$° W., 84 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p> <p>Desc. 10 ft. over NW. slope.</p> <p>42.42 Draw, near head, course N. 15° W., asc. 50 ft. over NE. slope.</p> <p>50.82 Ridge, brs. N. 30° W. and S. 30° E., desc. 200 ft. over SW. slope.</p> <p>66.52 Draw, course NW. Leave mountainous and enter rolling land. Asc: 10 ft. over NE. slope.</p> <p>68.62 Low spur, slopes N. 75° W., desc. 57 ft. over SW. slope.</p> <p>74.52 Draw, course N. 75° W.; asc. 12 ft. over NE. slope to</p> <p>78.92 Intersect the original cor. of secs. 2, 3, 34 and 35, which is an unmarked lava stone, 16x8x8 ins., firmly set in a mound of stone and witnessed by two of the three record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and in same place set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock, with original cor. stone reset alongside and in a mound of stone to top, for cor. of secs. 2, 3, 34 and 35, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T6N</td> <td>R29E</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> </table> <p>T5N</p> <p>1936</p> <p>from which</p> <p>the original bearing trees:</p> </div> </div>	T6N	R29E	S34	S35	S 3	S 2
T6N	R29E						
S34	S35						
S 3	S 2						

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

8.

Chains

A yellow pine, 14 ins. diam., brs. S. 77° W., 22 lks. dist. Remark alongside of open old blaze, T5N R29E S3 BT.

A fir, (dead) 10 ins. diam., brs. N. 16½° W., 26 lks. dist. mkd. T6N R29E S34 BT.

and establish additional bearing trees:

A spruce, 8 ins. diam., brs. N. 20° E., 52 lks. dist. mkd. T6N R29E S35 BT.

A sugar pine, 8 ins. diam., brs. S. 65° E., 33 lks. dist., mkd. T5N R29E S2 BT.

A yellow pine, 24 ins. diam., brs. N. 30° W., 17 lks. dist., mkd. T6N R29E S34 BT.

Land, mountainous and rolling.

Soil, volcanic loam, 2nd and 3rd rates.

Timber, yellow pine in W. ½, yellow pine, spruce, aspen and fir in E. ½.

Undergrowth, scrub timber and bunch grass.

N. 88° 37' W., on true line, bet. secs. 3 and 34.

Over rolling land, thru scattering timber and undergrowth.

Asc. slightly over NE. slope.

3.44 Spur, slopes N. 75° W. Leave rolling and enter mountainous land. Desc. 265 ft. over SW. slope.

12.34 Leave timber, brs. N. and S.

16.47 Leave mountainous and enter gently rolling land. Desc. 35 ft. over W. slope.

26.89 Draw, course N., asc. 26 ft. to ¼ sec. cor. over nearly level meadow land.

33.34 Highway, brs. N. 37½° E., to Alpine and S. 37½° W., to cattle guard, thence SW.

40.65 Fence (4 strand barbed wire) brs. N. 1° E., and S. 1° W.

40.82 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a stone, 10x8x8 ins. mkd. with a cross (X) deposited alongside, for ¼ sec. cor., with brass cap mkd.

¼ S 34
S 3

1936

No bearing trees available.

Continue over nearly level meadow land.

44.54 Wash, 9 lks. wide, 3 ft. deep, course NE., from S. 30° W. Asc. 38 ft. over E. slope to

52.30 Leave nearly level and enter mountainous land. Asc. 247 ft. over E. slope.

55.79 Enter timber, brs. N. and S.

RESURVEY: SOUTH BOUNDARY of T. 6 N., R. 29 E.


BOOK 411

Chains

75.24 Spur, slopes S. 30° E. Leave mountainous and enter rolling land. Desc. 33 ft. over SW. slope to

81.64 Intersect the original cor. of secs. 3, 4, 33 and 34, which is an unmarked lava stone, 18x16x10 ins., above ground, firmly set, witnessed by a mound of stone, 3 ft. base, 2 ft. high N. of cor. and the three record bearing trees. Reconstruct this cor. monument as follows:

Remove the original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock with the old stone reset alongside, and in a mound of stone to top, for cor. of secs. 3, 4, 33 and 34, with brass cap mkd.



1936

from which

the original bearing trees:

- A yellow pine, (dead and fallen) 16 ins. diam., brs. N. 52° E., 56 lks. dist., markings partly visible.
- A yellow pine, 24 ins. diam., brs. S. 38° E., 54 lks. dist., mkd. T5N R29E S3 BT.
- A yellow pine, 12 ins. diam., brs. N. 53° W., 47 lks. dist., mkd. T6N R29E S33. Add BT above old blaze.

and establish additional bearing trees:

- A yellow pine, 24 ins. diam., brs. N. 46° E., 165 lks. dist., mkd. T6N R29E S34 BT.
- A yellow pine, 12 ins. diam., brs. S. 32½° W., 120 lks. dist., mkd. T5N R29E S4 BT.

Land, rolling, nearly level and mountainous.
Soil, volcanic loam, 2nd and 3rd rates.
Timber, spruce, aspen, fir and yellow pine.
Undergrowth, scrub timber and bunch grass.

S. 88° 29' W., on true line, bet. secs. 4 and 33.

Over rolling land, thru scattering timber and undergrowth. Desc. slightly over SW. slope to


0.36 Shallow draw, course S., asc. 52 ft. over E. slope.

9.15 Spur, slopes SE., desc. 158 ft. over SW. slope.

31.15 Leave timber, brs. NW. and SE.

34.16 Draw, course NW., asc. 10 ft. over NE. slope to

40.58 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.



1936

from which

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

10

Chains

A yellow pine, 10 ins. diam., brs. N. $73\frac{1}{2}^{\circ}$ W., 285 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

A spruce, 9 ins. diam., brs. S. $36\frac{1}{4}^{\circ}$ E., 272 lks. dist. mkd. $\frac{1}{4}$ S4 BT.

Asc. 93 ft. over NE. slope.

42.16 Enter timber, brs. NW. and SE.

55.49 Spur, slopes N. 60° W. Leave rolling and enter mountainous land. Desc. 170 ft. over NW. slope.

75.96 South bank of wash, course NW. from NE., brs. about 30 lks. N. Leave mountainous and enter rolling land. Asc. 34 ft. over NE. slope.

79.96 Short spur, slopes N. 60° W., desc. 13 ft. over NW. slope to

81.16 Intersect the original cor. of secs. 4, 5, 32 and 33, which is an unmarked lava stone, 15x11x5 ins. firmly set in a mound of stone and witnessed by the two record bearing trees.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

T6N	R29E
S32	S33
S 5	S 4
T5N	

1936

from which

the original bearing trees:

A spruce, 16 ins. diam., brs. S. 33° E., 20 lks. dist. Remark on overgrowth, T5N R29E S4 BT.

A spruce (dead and fallen) 16 ins. diam., brs. N. 41° W., 21 lks. dist., mkd. T6N R29E S32 BT.

and establish additional bearing trees:

A yellow pine fork, 14 ins. diam., brs. N. $72\frac{1}{2}^{\circ}$ E., 114 lks. dist., mkd. T6N R29E S32 BT.

A spruce, 20 ins. diam., brs. S. $50\frac{1}{2}^{\circ}$ W., 133 lks. dist., mkd. T5N R29E S5 BT.

A yellow pine, 16 ins. diam., brs. N. 87° W., 114 lks. dist., mkd. T6N R29E S32 BT.

Land, rolling and mountainous.
Soil, volcanic loam, 2nd and 3rd rates.
Timber, yellow pine, spruce, aspen and fir.
Undergrowth, scrub timber and bunch grass.

N. $88^{\circ} 49'$ W., on true line, bet. secs. 5 and 32 ($E\frac{1}{2}$)

Over rolling land, thru medium timber and undergrowth.

Desc. 35 ft. over NW. slope.

Chains	
3.37	Open draw, about 5 chs. wide, course N. 15° W. Asc. 50 ft. over NE. slope to
11.40	Leave rolling and enter mountainous land. Asc. 55 ft. over NE. slope.
14.50	Short rocky spur, slopes N. 15° W., desc. 182 ft., over W. slope.
22.50	Creek, with a stream of running water, 12 lks. wide, 10 ins. deep, course SW., asc. 248 ft. over E. slope to
39.17	<p>Intersect the original $\frac{1}{4}$ sec. cor. which is an unmarked lava stone, 14x11x9 ins. firmly set in a mound of stone, and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with the original cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S 32 \\ S 5 \end{array}$ <p>1936</p> </div> <p style="text-align: right;">from which</p> <p>the original bearing trees:</p> <p>A yellow pine, 12 ins. diam., brs. N. 56° W., 7 lks. dist., mkd. $\frac{1}{4}$ S BT.</p> <p>A yellow pine, 14 ins. diam., brs. S. 81$\frac{1}{2}$° E., 33 lks. dist. Remark on overgrowth $\frac{1}{4}$ S5 BT.</p> <p>and establish an additional bearing tree:</p> <p>A yellow pine, 10 ins. diam., brs. N. 14° E., 63 lks. dist., mkd. $\frac{1}{4}$ S32 BT.</p> <p>This cor. is on top of a spur, sloping S. 30° E.</p> <p>Thence,</p> <p>N. 89° 59' W., on true line, bet. secs. 5 and 32. (W$\frac{1}{2}$)</p> <p>Over rolling land, thru dense timber and scattering undergrowth.</p> <p>Desc. 37 ft. over SW. slope.</p>
7.35	Fence (3 strand barbed wire) brs. N. and S.
17.00	Ascend 20 ft. over SE. slope.
27.00	Desc. 57 ft. over W. slope.
36.25	Draw, course S. 10° E. Leave rolling and enter mountainous land. Asc. 50 ft. over NE. slope to
39.85	<p>Intersect the original cor. of secs. 5, 6, 31 and 32, which is a mound of stone, 2 ft. base, 1 ft. high, witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.</p>

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

12.

Chains

T6N	R29E
S31	S32
S 6	S 5
T5N	

1936

from which

the original bearing trees:

A yellow pine, (dead and fallen) 30 ins. diam., brs. S. $35\frac{1}{2}^{\circ}$ E., 22 lks. dist., mkd. T5N R29E S5 BT.

A yellow pine, 14 ins. diam., brs. N. 44° W., 38 lks. dist., mkd. T6N R29E S31 BT.

and establish additional bearing trees:

A yellow pine, 10 ins. diam., brs. N. $62\frac{1}{2}^{\circ}$ E., 71 lks. dist., mkd. T6N R29E S32 BT.

A yellow pine, 12 ins. diam., brs. S. $46\frac{1}{2}^{\circ}$ E., 16 lks. dist., mkd. T5N R29E S5 BT.

A yellow pine, 20 ins. diam., brs. S. $39\frac{1}{2}^{\circ}$ W., 103 lks. dist., mkd. T5N R29E S5 BT.

A yellow pine, 14 ins. diam., brs. N. $56\frac{1}{2}^{\circ}$ W., 54 lks. dist., mkd. T6N R29E S31 BT.

Land, rolling and mountainous.

Soil, volcanic loam, rocky, 3rd and 4th rates.

Timber, yellow pine, aspen and fir.

Undergrowth, scrub timber and bunch grass.

S. $88^{\circ} 17'$ W., on true line, bet. secs. 6 and 31.

Over mountainous land, thru medium timber and undergrowth. Asc. 10 ft. over NE. slope.

2.00 Long spur, slopes S. 20° E., desc. 210 ft. over SW. slope to Black River.

18.90 Top of red sandstone bluff, 40 ft. high, brs. NW. and SE. facing SW.

23.65 Black River, with stream of running water, 25 lks. wide, 2 ft. deep, course S. 30° E., from N. 60° W., asc. 120 ft. over NE. slope to

31.65 Desc. 60 ft. over NW. slope to

41.12 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$	S 31
$\frac{1}{4}$	S 6

1936

from which

A fir, 18 ins. diam., brs. N. $48\frac{3}{4}^{\circ}$ W., 121 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

A fir, 14 ins. diam., brs. S. $9\frac{1}{2}^{\circ}$ W., 73 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

RESURVEY: SOUTH BOUNDARY OF T. 6 N., R. 29 E.

LOCAL COR

13

Chains	Desc.										
	Desc. 15 ft. over NW. slope.										
46.55	Short draw, course N., asc. 255 ft. over NE. slope.										
57.65	Flat topped ridge, brs. N. 70° W., and SE., thence, along S. slope of ridge.										
64.55	Leave timber, brs. S. and NW.										
82.65	Point for reestablishment of the Tp. cor. determined by double proportion bet. control cors., 1/2 mile N., 1 mile E., 1/2 mile S. and 1 mile W. as hereinbefore described. Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with a stone 8x6x6 ins. mkd. with a cross (X) deposited at base, and in a mound of stone to top, for cor. of Ts. 5 and 6 N., Rs. 28 and 29 E., with brass cap mkd.										
	<table border="1"> <tr><td colspan="2">T6N</td></tr> <tr><td>R28E</td><td>R29E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td>S1</td><td>S6</td></tr> <tr><td colspan="2">T5N</td></tr> </table>	T6N		R28E	R29E	S36	S31	S1	S6	T5N	
T6N											
R28E	R29E										
S36	S31										
S1	S6										
T5N											
	1936										
	No bearing trees available..										
	Land, mountainous. Soil, volcanic loam and rocky, 1st and 4th rates. Timber, yellow pine, fir, spruce and aspen. Undergrowth, scrub timber and bunch grass.										

RESURVEY: WEST BOUNDARY, T. 6 N., R. 29 E.

14

Chains

The West bdy. of T. 6 N., R. 29 E., was surveyed in 1883, by W. R. Fitzgerald, U.S.D.S., establishing $\frac{1}{4}$ sec. and sec. cors., alternately, at 40.00 ch. intervals counting from the N. with common reference to areas both sides of the line. No retracement or resurvey of any part of this line is of record. The following notes describe a dependent resurvey of the entire line, reconstructing all existing cors., retaining their original references, and reestablishing all missing cors. by proportional measurement, and monumenting all cors. with regulation brass-capped iron posts.

RETRACEMENT FOR RESURVEY

The S. $\frac{1}{2}$ of line bet. secs. 31 and 36 was retraced in connection with the reestablishment of the cor. of Ts. 5 and 6 N., Rs. 28 and 29 E., as hereinbefore described in notes of resurvey of S. bdy. of T. 6 N., R. 29 E., therefore begin retracement for resurvey of West bdy. at the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.

Thence,

North, on random line, bet. secs. 31 and 36 ($N\frac{1}{2}$).

39.79 A point 2.64 chs. E. of original cor. of secs. 25, 30, 31 and 36.

True course and dist. of N. $\frac{1}{2}$ of line bet. secs. 31 and 36 are therefore, N. $3^{\circ} 48'$ W., 39.88 chs.

North, on random line, bet. secs. 25 and 30 ($S\frac{1}{2}$).

39.82 A point 1.16 chs. E. of original $\frac{1}{4}$ sec. cor.
True course and dist. of S. $\frac{1}{2}$ of line bet. secs. 25 and 30 are therefore, N. $1^{\circ} 40'$ W., 39.84 chs.

Thence,

North, on random line, bet. secs. 25 and 30 ($N\frac{1}{2}$).

40.00 No trace of original cor. of secs. 19, 24, 25 and 30.
Set temp. cor. Continue measurement North, on random line, bet. secs. 19 and 24 ($S\frac{1}{2}$).

78.99 A point 2.02 chs. E., of original $\frac{1}{4}$ sec. cor. of secs. 19 and 24. True course and dist., of Tp. bdy. from $\frac{1}{4}$ sec. cor. of secs. 25 and 30, to this $\frac{1}{4}$ sec. cor. are therefore N. $1^{\circ} 28'$ W., 79.02 chs., which to maintain original proportion bet. cor. intervals, gives two intervals of 39.51 chs. each, for the reestablishment of the missing sec. cor.

North, on random line, bet. secs. 19 and 24 ($N\frac{1}{2}$).

39.48 A point 17 lks. E., of original cor. of secs. 13, 18, 19 and 24. True course and dist. of N. $\frac{1}{2}$ of line bet. secs. 19 and 24 are therefore, N. $0^{\circ} 15'$ W., 39.48 chs.

North, on random line, bet. secs. 13 and 18 ($S\frac{1}{2}$).

39.95 A point 17 lks. E., of original $\frac{1}{4}$ sec. cor. True course and dist. of S. $\frac{1}{2}$ of line bet. secs. 13 and 18 are therefore, N. $0^{\circ} 15'$ W., 39.95 chs.

Thence,

RESURVEY: WEST BOUNDARY, T. 6 N., R. 29 E.

DOOM 4118

15

Chains	North, on random line, bet. secs. 13 and 18 ($N\frac{1}{2}$).
39.92	A point 23 lks. E. of original cor. of secs. 7, 12, 13 and 18. True course and dist., of $N\frac{1}{2}$ of line bet. secs. 13 and 18 are therefore, N. $0^{\circ} 20' W.$, 39.92 chs.
40.08	North, on random line, bet. secs. 7 and 12 ($S\frac{1}{2}$). A point 14 lks. E. of original $\frac{1}{4}$ sec. cor. True course and dist. of $S\frac{1}{2}$ of line bet. secs. 7 and 12 are therefore, N. $0^{\circ} 12' W.$, 40.08 chs. Thence,
40.02	North, on random line, bet. secs. 7 and 12 ($N\frac{1}{2}$). A point 83 lks. E. of original cor. of secs. 1, 6, 7 and 12. True course and dist. of $N\frac{1}{2}$ of line bet. secs. 7 and 12 are therefore, N. $1^{\circ} 11' W.$, 40.03 chs.
40.10	North, on random line, bet. secs. 1 and 6 ($S\frac{1}{2}$). A point 70 lks. W. of original $\frac{1}{4}$ sec. cor. True course and dist. of $S\frac{1}{2}$ of line bet. secs. 1 and 6 are therefore, N. $1^{\circ} 00' E.$, 40.11 chs. Thence,
40.60	North, on random line, bet. secs. 1 and 6 ($N\frac{1}{2}$). A point 1.21 chs. W., of original cor. of Ts. 6 and 7 N., Rs. 28 and 29 E. True course and dist. of $N\frac{1}{2}$ of line bet. secs. 1 and 6 are therefore, N. $1^{\circ} 42' E.$, 40.62 chs.
RESURVEY	
11.38	From the reestablished cor. of Ts. 5 and 6 N., Rs. 28 and 29 E., hereinbefore described. N. $4^{\circ} 33' E.$, on true line, bet. secs. 31 and 36 ($S\frac{1}{2}$) Over open mountainous land. Asc. 24 ft. over S. slope.
14.40	Enter scattering timber and undergrowth, brs. E. and W. S. edge of flat top of ridge, brs. E. and W., thence across same.
28.85	Leave top of ridge, brs. E. and W., desc. 224 ft., over N. slope to Black River.
30.25	Top, of high bluff, brs. S. $70^{\circ} E.$ and N. $70^{\circ} W.$, facing N.
35.03	Black River with a stream of running water, 20 lks. wide, 2 ft. deep, course S. $80^{\circ} E.$, from N. $10^{\circ} W.$ Asc. 40 ft. over SW. slope to
39.73	Intersect the original point of location of the $\frac{1}{4}$ sec. cor. determined from the record bearing tree SE. At this point, set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

RESURVEY: WEST BOUNDARY, T. 6 N., R. 29 E.

16.

Chains

S36		S31
1936		

from which

the original bearing tree:

A spruce, 14 ins. diam., brs. S. $39\frac{1}{4}^{\circ}$ E., 61 lks. dist.
Overgrowth removed shows mkg. $\frac{1}{4}$ S.

and establish additional bearing trees:

A spruce, 16 ins. diam., brs. N. 89° E., 61 lks. dist.,
mkd. $\frac{1}{4}$ S31 BT.

A spruce, 12 ins. diam., brs. S. $36\frac{1}{2}^{\circ}$ W., 51 lks. dist.,
mkd. $\frac{1}{4}$ S36 BT.

N. $3^{\circ} 48'$ W., on true line, bet. secs. 31 and 36 ($N\frac{1}{2}$).

Over mountainous land, thru medium timber and scattering
undergrowth. Asc. 260 ft. over SW. slope to

16.60 Leave mountainous and enter rolling land. Asc. 117 ft.
over S. slope to

39.88 Intersect original cor. of secs. 25, 30, 31 and 36, which
is a lava stone, 16x10x10 ins., firmly set in a mound of
stone mkd. with one notch on S. face and witnessed by
two of the three record bearing trees. Reconstruct this
cor. monument as follows: remove the mound of stone,
and original cor. stone and in same place, set an iron
post, 3 ft. long, 2 ins. diam., 26 ins. in the ground,
with the original cor. stone reset alongside, for cor.
of secs. 25, 30, 31 and 36, with brass cap mkd.

T6N	
R28E	R29E
S25	S30
S36	S31

1936

from which

the original bearing trees:

A yellow pine, 12 ins. diam., brs. S. 61° E., 23 lks.
dist. Old blaze visible, marking overgrown.

A yellow pine, 12 ins. diam., brs. S. 40° W., 16 lks.
dist. Old blaze visible, marking overgrown.

and establish additional bearing trees:

A yellow pine, 10 ins. diam., brs. N. 66° E., 12 lks.
dist., mkd. T6N R29E S30 BT.

A yellow pine, 12 ins. diam., brs. S. $51\frac{1}{2}^{\circ}$ E., 35 lks.
dist., mkd. T6N R29E S31 BT.

A yellow pine, 10 ins. diam., brs. S. 13° W., 25 lks.
dist., mkd. T6N R28E S36 BT.

A yellow pine, 10 ins. diam., brs. N. 85° W., 59 lks.
dist., mkd. T6N R28E S25 BT.

Land, mountainous and rolling.

Soil, volcanic loam, rocky, 1st and 4th rates.

RESURVEY: WEST BOUNDARY, T. 6 N., R. 29 E.

BOOK 412

17

Chains	
	Timber, yellow pine, aspen, spruce and fir. Undergrowth, scrub timber.
	N. 1° 40' W., on true line, bet. secs. 25 and 30 (S $\frac{1}{2}$) Over rolling land, thru medium timber and undergrowth. Asc. 50 ft. over S. slope.
22.09	S. edge of top of ridge, brs. E. and W., thence across nearly level top of ridge. Desc. 12 ft. to
27.14	N. edge of top of ridge brs. N. 70° E. and S. 70° W. Leave top of ridge. Enter mountainous land. Desc. 336 ft. over steep N. slope.
36.84	Black River with stream of running water, 20 lks. wide, 1 ft. deep, course N. 75° W., asc. 38 ft. over SW. slope to
39.84	Intersect the original point of location of the $\frac{1}{4}$ sec. cor. of secs. 25 and 30 determined from the one record bearing tree SE. At this point, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	from which
	the original bearing tree:
	A spruce, 24 ins. diam., brs. S. 60° E., 29 lks. dist. remove part of overgrowth to show $\frac{1}{4}$.
	and establish additional bearing trees:
	A spruce, 14 ins. diam., brs. S. 87° E., 34 lks. dist. mkd. $\frac{1}{4}$ S30 BT.
	A spruce, 20 ins. diam., brs. N. 77° W., 12 lks. dist. mkd. $\frac{1}{4}$ S25 BT.
	N. 1° 28' W., on true line, bet. secs. 25 and 30 (N $\frac{1}{2}$). Over mountainous land, thru dense timber and scattering undergrowth. Asc. 230 ft. over SW. slope.
7.07	Fence (4 strand barbed wire) brs. N. 80° W., and S. 80° E.
10.56	S. edge of top of ridge brs. N. 80° W. and S. 80° E. Leave timber. Asc. 15 ft. across top of ridge.
15.56	Enter dense timber, brs. N. 80° W. and S. 80° E.
16.57	N. edge of top of ridge, brs. N. 80° W. and S. 80° E. Leave top of ridge. Desc. 217 ft. over NE. slope to Black River.
20.48	Leave dense timber, brs. E. and W., and enter scattering undergrowth.
29.97	Black River with stream of running water 20 lks. wide, 1 ft. deep, course S. 80° E., from N. 40° W. Asc. 15 ft. over grassy W. slope to

RESURVEY: WEST BOUNDARY, T. 6 N., R. 29 E.

18

Chains

39.51 (Proportional dist.) Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bed rock and in a mound of stone to top, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.

T6N	
R28E	R29E
S24	S19
S25	S30

1936

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling and mountainous.
Soil, volcanic loam and rocky, 1st and 4th rates.
Timber, spruce, fir and aspen.
Undergrowth, scrub timber and bunch grass.

N. 1° 28' W., on true line, bet. secs. 19 and 24 (S $\frac{1}{2}$).

Over mountainous land, devoid of timber and undergrowth.

Asc. 120 ft. over grassy W. slope.

37.71 Point of broad spur, slopes N. 30° W., desc. 54 ft. over NW. slope to

39.51 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 19 and 24, which is a lava stone, 11x8x8 ins. firmly set in a mound of stone and mkd. $\frac{1}{4}$ on W. face. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with the original cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S24 S19

1936

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 15' W., on true line, bet. secs. 19 and 24 (N $\frac{1}{2}$)

Over mountainous land, devoid of timber and undergrowth.

Desc. 37 ft. over NW. slope.

4:43. Black River, with a stream of running water 20 lks. wide, 1 ft. deep, course S. 80° W., asc. 230 ft. over SW. slope.

25.13 S. edge of top of ridge, brs. N. 50° W. and S. 70° E. Thence across nearly level top of ridge.

28.10 N. edge of top of ridge brs. N. 50° W. and S. 70° E. Leave top of ridge. Enter rolling land. Desc. 47 ft. over NE. slope to

37.08 Top of bluff, brs. NW. and SE. facing NE. Desc. 48 ft. to

39.48 Intersect original cor. of secs. 13, 18, 19 and 24, which

RESURVEY; WEST BOUNDARY, T. 6 N., R. 29 E.

E0000 0110

19

Chains

is a sandstone, 16x16x12 ins. firmly set; in a mound of stone and mkd. with 3 grooves on each of N. and S. faces. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, with the original cor. stone reset alongside; for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

T6N
R28E | R29E
S13 | S18
S24 | S19

1936

and raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.

Land, mountainous and rolling.

Soil, volcanic loam and rocky, 1st and 4th rates.

Timber, none.

Undergrowth, none.

Fair growth of grass.

N. 0° 15' W., on true line, bet. secs. 13 and 18 (S $\frac{1}{2}$).

Over rolling grassy land, devoid of timber and undergrowth.

Desc. 25 ft. over NE. slope.

3.03 Black River, with a stream of running water, 20 lks. wide, 1 ft. deep, course S. 65° E.; asc. 35 ft. over SW. slope.

10.00 Spur, slopes N. 75° W., desc. 15 ft. over N. slope.

14.95 Wash, 15 lks. wide, 2 ft. deep, with water in pools, course N. 75° W.; asc. 60 ft. over SW. slope.

15.50 Old road, brs. N. 75° W., and S. 75° E.

25.00 Top of spur, slopes SE. from N. Asc. 55 ft. along top of spur to

39.90 Leave top of spur, sloping S. from NE.

39.95 Intersect original $\frac{1}{4}$ sec. cor. of secs. 13 and 18, which is a mound of stone, 4 ft. base, 1 ft. high. Reconstruct this cor. monument as follows: remove the mound of stone, and in center of its position, set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bed rock, with a stone, 12x10x6 ins. mkd. with a cross (X) deposited alongside and raise a mound of stone around post to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S13 | S18
1936

From this cor., center of highway bridge over Black River, brs. S. 70° 52' W.

Thence,

N. 0° 20' W., on true line, bet. secs. 13 and 18 (N $\frac{1}{2}$).

Over rolling grassy land, devoid of timber and undergrowth.

.RESURVEY;. WEST. BOUNDARY, T. 6 N., R. 29 E.

20

Chains

Desc. 23 ft. over NW. slope.

4.42 Creek, with stream of running water, 5 lks. wide, 3 ins. deep, course SW. Asc. 75 ft. over gradual SE. slope to sec. cor.

39.77 Fence (4 strand barbed wire) brs. S. $87\frac{1}{2}^{\circ}$ E., and N. $87\frac{1}{2}^{\circ}$ W.

39.92 Intersect the orig. cor. of secs. 7, 12, 13 and 18, which is a mound of stone, 3 ft. base, 1 ft. high. Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.

T6N	
R28E	R29E
S12	S 7
S13	S18

1936

from which,

A yellow pine, 24 ins. diam., brs. S. $87^{\circ} 51' W.$, 646 lks. dist., mkd. T6N R28E S13 BT.A yellow pine, 28 ins. diam., brs. N. $89^{\circ} W.$, 608 lks. dist., mkd. T6N R28E S12 BT.

No other bearing trees within limits.

Land, rolling.

Soil, volcanic loam and rocky, 4th rate.

Timber, none.

Undergrowth, none.

Fair growth of grass.

N. $0^{\circ} 12' W.$, on true line, bet. secs. 7 and 12 (S $\frac{1}{2}$).

Over rolling, grassy land, devoid of timber and undergrowth.

4.28 Swampy draw, course SE. Asc. 230 ft. over SW. slope.

13.08 Road, brs. E. and W.

14.73 Enter dense timber and scattering undergrowth, brs. E. and W.

35.58 Ridge, brs. N. $60^{\circ} W.$ and S. $60^{\circ} E.$; dest. 31 ft. over NE. slope to40.08 Intersect point of original location of the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, determined from the record bearing tree NW. At this point, set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

S12		S. 7
1936		

1936

from which

the original bearing tree:

RESURVEY: WEST BOUNDARY, T, 6 N., R. 29 E.

DCC

21

Chains

A yellow pine, (dead) 30 ins. diam., brs. N. 75° W.,
43 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

and establish additional bearing trees:

A spruce, 6 ins. diam., brs. N. 68 $\frac{1}{2}$ ° E., 10 lks. dist.,
mkd. $\frac{1}{4}$ S7 BT.

A spruce, 7 ins. diam., brs. N. 35 $\frac{1}{2}$ ° W., 24 lks. dist.,
mkd. $\frac{1}{4}$ S12 BT.

N. 1° 11' W., on true line, bet. secs. 7 and 12 (N $\frac{1}{2}$).

Over rolling land, thru dense timber and scattering under-
growth.

Desc. 10 ft. over NE. slope.

2.00 Road, brs. N. 70° W. and S. 70° E.

2.80 Draw, course S. 70° E., asc. 85 ft. over S. slope.

10.70 Asc. 15 ft. over SE. slope.

14.10 Low spur, slopes S. 60° W., desc. 10 ft. over NW. slope.

22.35 Draw, course S. 70° W., asc. 130 ft. over SE. slope.

23.97 Same road, brs. NE. and SW.

38.50 S. edge of top of ridge, brs., N. 30° E. and S. 30° W.
Thence over flat top of ridge.

40.03 Intersect original cor. of secs. 1, 6, 7 and 12, which is
a mound of stone, 3 ft. base, 1 ft. high, witnessed by
the two record bearing trees. Reconstruct this cor.
monument as follows: remove the mound of stone, and in
the center of its position, set an iron post, 3 ft.
long, 2 ins. diam., 26 ins. in the ground, and in a
mound of stone to top, for cor. of secs. 1, 6, 7 and 12,
with brass cap mkd.

	T6N	
R28E		R29E
S 1		S 6
S12		S 7

1936

from which

the original bearing trees:

A yellow pine, (dead) 12 ins. diam., brs. S. 21 $\frac{1}{2}$ ° E.,
55 lks. dist., mkd. T6N R29E S7 BT.

A yellow pine stump, 24 ins. diam., brs. S. 41 $\frac{1}{4}$ ° W.,
64 lks. dist., mkd. T6N R28 E S12 BT.

and establish additional bearing trees:

A yellow pine, 6 ins. diam., brs. N. 59 $\frac{1}{2}$ ° E., 26 lks.
dist., mkd. T6N R29E S5 BT.

A yellow pine, 12 ins. diam., brs. S. 70° E., 51 lks.
dist., mkd. T6N R29E S7 BT.

A yellow pine, 12 ins. diam., brs. S. 79 $\frac{1}{2}$ ° W., 64 lks.
dist., mkd. T6N R28E S12 BT.

A fir, 26 ins. diam., brs. N. 51 $\frac{1}{2}$ ° W., 75 lks. dist.,
mkd. T6N R28E S1 BT.

RESURVEY: WEST BOUNDARY, T. 6 N., R. 29 E.

22

Chains.

Land, rolling.
Soil, volcanic loam, 2nd rate.
Timber, yellow pine, fir, aspen and spruce.
Undergrowth, scrub timber and bunch grass.

N. 1° 00' E. on true line, bet. secs. 1 and 6 (S $\frac{1}{2}$).

Over flat top of ridge, thru dense timber and scattering undergrowth.

- 7.80 N. edge of top of ridge, bears S. 30° W. and S. 70° E. at junction of ridges bearing N. 30° W., S. 30° W. and S. 70° E. Leave top of ridge and enter rolling land. Desc. 135 ft. over NE. slope.
- 19.00 Leave dense timber, brs. S. 60° E., and N. 60° W. Enter open grassy land.
- 28.00 Creek, near head, with a small stream of water, course S. 60° E., asc. 85 ft. over S. slope to $\frac{1}{4}$ sec. cor.
- 31.70 Enter scattering timber, brs. S. 60° E. and N. 60° W. and continue over grassy land.
- 40.11 Intersect original $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is an unmarked sandstone, 16x12x4 ins. firmly set in a mound of stone and witnessed by the record bearing tree. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock with the original cor. stone reset alongside, and raise a mound of stone around post to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- S 1 $\frac{1}{4}$ S 6

1936
- from which the
- original bearing tree:
- A yellow pine, (half dead) brs. N. 81 $\frac{1}{2}$ ° W., 89 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
- and establish additional bearing trees:
- A yellow pine, 12 ins. diam., brs. S. 55° E., 54 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
- A yellow pine, 24 ins. diam., brs. S. 80 $\frac{1}{2}$ ° W., 100 lks. dist. mkd. $\frac{1}{4}$ S1 BT.
- Thence,
- N. 1° 42' E., on true line, bet. secs. 1 and 6 (N $\frac{1}{2}$).
- Over gently rolling grassy land, devoid of timber and undergrowth. Asc. 50 ft. over S. slope.
- 12.62 NE. point of timbered area, brs. W. and SW.
- 15.75 Asc. 35 ft. over SE. slope.
- 39.50 Low flat-topped ridge, brs. N. and S. 30° W. Asc. slightly along top of ridge to
- 40.62 Intersect original cor. of Tps. 6 and 7 N., Rs. 28 and 29

RESURVEY: WEST BOUNDARY, T. 6 N., R. 29 E.

23

Chains

E., which is an unmarked lava stone, 10x10x10 ins., firmly set in a mound of stone and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground to bedrock, with original cor. stone reset alongside, and raise a mound of stone around post to top, for cor. of Ts. 6 and 7 N., Rs. 28 and 29 E., with brass cap mkd.

	T7N	
R28E		R29E
S36		S31
S 1		S 6
	T6N	

1936

from which

the original bearing trees:

An aspen, 8 ins. diam., brs. N. 20° W., 216 lks. dist., faintly mkd. on bark.

An aspen stump, 14 ins. diam., brs. N. 21 $\frac{3}{4}$ ° E., 197 lks. dist., no visible marks.

and establish additional bearing trees:

An aspen, 12 ins. diam., brs. N. 14° E., 234 lks. dist., mkd. T7N R29E S31 BT.

An aspen, 12 ins. diam., brs. N. 19° W., 222 lks. dist., mkd. T6N R29E S6 BT.

No other bearing trees available.

Salt House Lake, about 15 acres in area, brs. SW. about 25 chs. dist.

Land, rolling and gently rolling.

Soil, volcanic loam, 1st and 2nd rates.

Timber, yellow pine and aspen.

Undergrowth, scrub timber and bunch grass.

RESURVEY: NORTH BOUNDARY, T. 6 N., R. 29 E.

24

Chains	The North bdy. of T. 6 N., R. 29 E. was surveyed in 1883 by W. R. Fitzgerald, U.S.D.S., establishing $\frac{1}{4}$ sec. and sec. cors. alternately at 40.00 ch. intervals counting from the east, with common reference to areas both sides of the line. No retracement or resurvey of any part of this line is of record. The following notes describe a dependent resurvey of the entire line, reconstructing all existing cors, retaining their original references, reestablishing all missing cors. by proportional measurement, and monumenting all cors. with regulation brass-capped iron posts.
RETRACEMENT FOR RESURVEY	
	From the cor. of Ts. 6 and 7 N., Rs. 28 and 29 E., S. $89^{\circ} 56'$ E., on random line, bet. secs. 6 and 31 ($W\frac{1}{2}$).
38.63	A point 63 lks. N. of original $\frac{1}{4}$ sec. cor. True course and dist. of $W\frac{1}{2}$ of line bet. secs. 6 and 31 are therefore, S. $89^{\circ} 00'$ E., 38.64 chs. Thence, S. $89^{\circ} 56'$ E., on random line, bet. secs. 6 and 31 ($E\frac{1}{2}$).
39.77	A point 31 lks. S. of original cor. of secs. 5, 6, 31 and 32. True course and dist. of $E\frac{1}{2}$ of line bet. secs. 6 and 31 are therefore, N. $89^{\circ} 37'$ E., 39.77 chs. S. $89^{\circ} 56'$ E., on random line, bet. secs. 5 and 32 ($W\frac{1}{2}$).
40.04	A point 8 lks. S. of original $\frac{1}{4}$ sec. cor. True course and dist. of $W\frac{1}{2}$ of line bet. secs. 5 and 32, are therefore, N. $89^{\circ} 57'$ E., 40.04 chs. Thence, S. $89^{\circ} 56'$ E., on random line, bet. secs. 5 and 32 ($E\frac{1}{2}$).
40.19	A point 24 lks. N. of original cor. of secs. 4, 5, 32 and 33. True course and dist. of $E\frac{1}{2}$ of line bet. secs. 5 and 32, are therefore, S. $89^{\circ} 35'$ E., 40.19 chs. S. $89^{\circ} 56'$ E., on random line, bet. secs. 4 and 33 ($W\frac{1}{2}$).
40.14	A point 9 lks. S. of original $\frac{1}{4}$ sec. cor. True course and dist. of $W\frac{1}{2}$ of line bet. secs. 4 and 33 are therefore, N. $89^{\circ} 56'$ E., 40.14 chs. Thence, S. $89^{\circ} 56'$ E., on random line, bet. secs. 4 and 33 ($E\frac{1}{2}$).
40.11	A point 50 lks. S. of original cor. of secs. 3, 4, 33 and 34. True course and dist. of $E\frac{1}{2}$ of line bet. secs. 4 and 33 are therefore, N. $89^{\circ} 21'$ E., 40.11 chs. S. $89^{\circ} 56'$ E., on random line, bet. secs. 3 and 34.
40.00	No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.
77.84	A point 32 lks. S. of original cor. of secs. 2, 3, 34 and 35.

Chains

True course and dist. of line bet. secs. 3 and 34 are therefore, N. 89° 50' E., 77.84 chs.

S. 89° 56' E., on random line, bet. secs. 2 and 35 ($W\frac{1}{2}$).

43.61 A point 1.45 chs. N. of original $\frac{1}{4}$ sec. cor.
True course and dist. of $W\frac{1}{2}$ of line bet. secs. 2 and 35 are therefore, S. 88° 02' E., 43.63 chs.

Thence,

S. 89° 56' E., on true line bet. secs. 2 and 35 ($E\frac{1}{2}$).

39.18 A point 26 lks. S. of locally accepted original point of location of cor. of secs. 1, 2, 35 and 36.
True course and dist. of $E\frac{1}{2}$ of line bet. secs. 2 and 35 are therefore, N. 89° 41' E., 39.18 chs.

S. 89° 56' E., on random line, bet. secs. 1 and 36 ($W\frac{1}{2}$).

40.16 A point 13 lks. S. of original $\frac{1}{4}$ sec. cor.
True course and dist. of $W\frac{1}{2}$ of line bet. secs. 1 and 36 are therefore, N. 89° 53' E., 40.16 chs.

Thence,

S. 89° 56' E., on random line, bet. secs. 1 and 36 ($E\frac{1}{2}$).

40.13 A point 1.18 chs. N. of cor. of Ts. 6 and 7 N., Rs. 29 and 30 E.
True course and dist. of $E\frac{1}{2}$ of the line bet. secs. 1 and 36 are therefore, S. 88° 15' E., 40.15 chs.

RESURVEY

From the cor. of Ts. 6 and 7 N., Rs. 28 and 29 E., hereinafter described.

S. 89° 00' E., on true line, bet. secs. 6 and 31 ($W\frac{1}{2}$)

Over gently rolling grassy land, thru very scattering undergrowth. Desc. 40 ft. over E. and SE. slopes.

35.00 Head of draw, course S. Asc. 6 ft. over SW. slope to

38.64 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 6 and 31, which is a mound of stone, 3 ft. base, 1 ft. high, witnessed by the record bearing tree NE. Reconstruct this cor. monument as follows, remove the mound of stone and in center of its position, set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S \ 31}{S \ 6}$$

1936

from which

the original bearing tree:

A pine stump, 24 ins. diam., brs. N. 80° E., 281 lks. dist., mkd. $\frac{1}{4}$ S BT.

and establish additional bearing trees:

RESURVEY: NORTH BOUNDARY, T. 6 N., R. 29 E.

26

Chains

A yellow pine, 12 ins. diam., brs. N. $68\frac{1}{2}^{\circ}$ E., 408 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

A yellow pine, 12 ins. diam., brs. E., 283 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Thence,

N. $89^{\circ} 37'$ E., on true line, bet. secs. 6 and 31 ($E\frac{1}{2}$).

Over gently rolling grassy land, devoid of timber and undergrowth. Asc. 10 ft. over W. slope.

3.00 Enter scattering timber and undergrowth, brs. N. 30° W. and S.

8.20 Low spur, slopes S. 30° W.; desc. 76 ft. over SE. slope.

13.20 Road, brs. N. and S.

18.80 Creek with stream of running water, 5 lks. wide, 2 ins. deep, course S., asc. 70 ft. over W. slope.

20.90 Leave timber, brs. NW. and SE. Continue thru scattering undergrowth.

33.00 Ridge, brs. N. 20° E. and S. 20° W., desc. 25 ft. over SE. slope to sec. cor.

35.00 Enter scattering timber, brs. NW. and SE.

39.77 Intersect original cor. of secs. 5, 6, 31 and 32, which is an aspen tree, 12 ins. diam., mkd. T7N R29E S32 on NE. face, and S31 on NW. face and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: at a point 4 lks. S. $89^{\circ} 37'$ W., of true point for cor., set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. to cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T7N	R29E	
S31	S32	WC
S 6	S 5	
T6N		

1936

the original bearing trees: from true point for cor.

A yellow pine, 12 ins. diam., brs. S. $43\frac{1}{2}^{\circ}$ E., 47 lks. dist. Marking overgrown. Remark on bark T6N R29E S5 BT.

An aspen, 16 ins. diam., brs. N. 66° W., 79 lks. dist., mkd. T7N R29E S31 BT.

and establish additional bearing trees:

An aspen, 10 ins. diam., brs. N. 55° E., 31 lks. dist., mkd. on bark, T7N R29E S32 BT.

A yellow pine, 20 ins. diam., brs. S. $58\frac{1}{2}^{\circ}$ W., 109 lks. dist., mkd. T6N R29E S6 BT.

Land, gently rolling.

Soil, volcanic loam, 1st and 3rd rates.

Timber, yellow pine and aspen.

Undergrowth, scrub timber and bunch grass.

Chains	
	N. 89° 57' E. on true line, bet. secs. 5 and 32 ($W\frac{1}{2}$). Over gently rolling land, thru scattering timber and undergrowth. Desc. 60 ft. over SE. slope.
17.30	Leave timber and undergrowth, brs. N. 50° E. and S., thence over grassy land.
23.60	Head of draw, course S. 10° E. Old road brs. N. 15° W. and S. 10° E. Enter scattering timber and undergrowth, brs. N. 15° W. and S. 5° E., asc. 12 ft. over SW. slope.
30.41	Fence, (4 strand barbed wire) brs. N. and S.
35.00	Low ridge, brs. NW. and SE.; desc. 12 ft. over NE. slope to
40.04	Intersect original $\frac{1}{4}$ sec. cor. of secs. 5 and 32, which is an unmarked lava stone, 10x10x10 ins. firmly set in a mound of stone and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock with the original cor. stone reset alongside, for $\frac{1}{4}$ sec. cor, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$
	1936
	from which
	the original bearing trees:
	A yellow pine, 18 ins. diam., brs. N. 32 $\frac{1}{2}$ ° W., 29 lks. dist. Marking overgrown. Remark $\frac{1}{4}$ S32 BT.
	A yellow pine, 18 ins. diam., brs. S. 36 $\frac{1}{2}$ ° E., 23 lks. dist. Marking overgrown. Remark $\frac{1}{4}$ S5 BT.
	and establish additional bearing tree:
	A yellow pine, 16 ins. diam., brs. N. 50 $\frac{1}{2}$ ° E., 41 lks. dist., mkd. $\frac{1}{4}$ S32 BT.
	Thence,
	S. 89° 35' E., on true line, bet. secs. 5 and 32 ($E\frac{1}{2}$). Over gently rolling land, thru dense timber and scattering undergrowth. Desc. 72 ft. over NE. slope.
23.68	Leave timber and undergrowth, brs. N. 60° E. and S. 60° W. and enter grassy land.
26.50	Creek, with stream of running water, 3 lks. wide, 3 ins. deep, course N. 60° E.; asc. 25 ft. over NW. slope to sec. cor.
30.90	Enter dense timber and scattering undergrowth, brs. N. 60° E. and S. 60° W.
40.19	Intersect original cor. of secs. 4, 5, 32 and 33, which is a lava stone, 10x9x6 ins. mkd. with two grooves on W. face, and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the

RESURVEY: NORTH BOUNDARY, T. 6 N., R. 29 E.

28

Chains

mound of stone; and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

T7N	R29E
S32	S33
S 5	S 4
T6N	

1936

the original bearing trees: from which

An aspen, 12 ins. diam., brs. S. $50\frac{1}{2}^{\circ}$ E., 41 lks. dist., mkd. T6N R29E S4 BT.

A fir, 50 ins. diam., brs. N. 18° W., 42 lks. dist., mkd. T7N R29E S32 BT.

and establish additional bearing trees:

A spruce, 12 ins. diam., brs. N. $58\frac{1}{2}^{\circ}$ E., 31 lks. dist., mkd. T7N R29E S33 BT.

A fir, 8 ins. diam., brs. S. 70° E., 125 lks. dist., mkd. T6N R29E S4 BT.

A yellow pine, 10 ins. diam., brs. S. 33° W., 70 lks. dist., mkd. T6N R29E S5 BT.

Land, gently rolling.

Soil, volcanic loam, 1st and 3rd rates.

Timber, yellow pine, aspen, fir and spruce.

Undergrowth, scrub timber.

Fair grass.

N. $89^{\circ} 56'$ E., on true line, bet. secs. 4 and 33 ($W\frac{1}{2}$).

Over gently rolling land, thru dense timber and scattering undergrowth. Asc. slightly over NW. slope.

1.00 Low spur, slopes N. 30° E.; desc. 10 ft. over E. slope.

2.00 Leave timber and undergrowth, brs. N. and S., and enter grassy land.

4.70 Draw, course N. 4,00 chs., thence N. 60° E., asc. 60 ft. over NW. slope.

9.50 Enter dense timber and scattering undergrowth, brs. N. 45° W. and S. 20° W.

28.90 W. edge of top of ridge, brs. N. 60° E. and S. 60° W. Thence across nearly level top of ridge brs. NE. and SW.

40.14 Intersect original $\frac{1}{4}$ sec. cor. of secs. 4 and 33, which is an unmarked lava stone, $8 \times 8 \times 6$ ins. firmly set in a mound of stone, and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$.	S 33
	S 4

1936

Chains

from which
the original bearing trees:

A yellow pine, 18 ins. diam., brs. N. 52° E., 13 lks. dist., mkg. obliterated. Remark $\frac{1}{4}$ S BT.

A yellow pine (dead) 18 ins. diam., brs. S. 60° E., 34 lks. dist., mkd. $\frac{1}{4}$ S BT.

and establish additional bearing trees:

A yellow pine, 16 ins. diam., brs. N. 7° E., 48 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

A yellow pine, 14 ins. diam., brs. S. 10° W., 38 lks. dist., mkd. $\frac{1}{4}$ S4 BT.

Thence,

N. 89° 21' E., on true line, bet. secs. 4 and 33 ($E\frac{1}{2}$).

Over nearly level top of ridge, bearing NE. and SW., thru dense timber and scattering undergrowth.

8.00 E. edge of top of ridge, brs. NE. and SW. Leave top of ridge. Enter gently rolling land. Desc. 20 ft. over SE. slope to

21.50 Enter mountainous land. Desc. 200 ft. over SE. slope to

40.11 Intersect the original cor. of secs. 3, 4, 33 and 34, which is an unmarked lava stone, 11x8x4 ins., firmly set in a small mound of stone and witnessed by the three record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

T7N	R29E
S33	S34
S 4	S 3
T6N	

1936

from which

the original bearing trees:

A yellow pine, (dead) 12 ins. diam., brs. N. 39 $\frac{1}{2}$ ° E., 68 lks. dist., mkd. T7N R29E S34 BT.

A yellow pine, 12 ins. diam., brs. S. 83 $\frac{1}{2}$ ° E., 59 lks. dist., mkg. overgrown. Remark T6N R29E S3 BT.

A yellow pine, (half dead) 10 ins. diam., brs. N. 59 $\frac{1}{4}$ ° W., 49 lks. dist., mkg. overgrown.

and establish additional bearing trees:

A yellow pine, 10 ins. diam., brs. N. 71 $\frac{1}{2}$ ° E., 61 lks. dist., mkd. T7N R29E S34 BT.

A yellow pine, 12 ins. diam., brs. S. 85 $\frac{1}{4}$ ° W., 122 lks. dist., mkd. T6N R29E S4 BT.

A yellow pine, 12 ins. diam., brs. N. 55 $\frac{1}{2}$ ° W., 51 lks. dist., mkd. T7N R29E S33 BT.

RESURVEY: NORTH BOUNDARY, T. 6 N., R. 29 E.

30

Chains

Land, gently rolling, nearly level and mountainous.
Soil, volcanic loam, 1st and 3rd rates.
Timber, yellow pine, fir, aspen and spruce.
Undergrowth, scrub timber and bunch grass.

N. 89° 50' E., on true line, bet. secs. 3 and 34.

Over mountainous land, thru dense timber and scattering undergrowth.

Desc. 472 ft. over steep SE. slope.

21.50 Creek, with stream of running water 10 lks. wide, 4 ins. deep, course N. 15° E., asc. 384 ft. over steep NW. slope.

37.20 Spur, slopes N. 30° E., desc. 14 ft. over E. slope to

38.92 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 34 \\ S 3 \end{array}$$

1936

from which

A yellow pine, 12 ins. diam., brs. N. 79° W., 104 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

A yellow pine, 14 ins. diam., brs. S. 70 $\frac{1}{2}$ ° E., 107 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

A yellow pine, 12 ins. diam., brs. S. 34° W., 9 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

Desc. 509 ft. over E. slope.

56.00 Trail brs. N. 20° E. to Nutrioso and S. 20° W.

56.40 Colter Creek, with a stream of running water 6 lks. wide, 4 ins. deep, course N. 20° E.; asc. 334 ft. over NW. slope to

77.84 Intersect original cor. of secs. 2, 3, 34 and 35, which is a pine tree (dead) 16 ins. diam., mkd. T7N S35 on NE. face, R29E S2 on SE. face, T6N S3 on SW. face, and S34 on NW. face, and witnessed by two of the three record bearing trees. Reconstruct this cor. monument as follows: at a point 10 lks. S. 89° 50' W. from the true cor. point, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for witness cor. to cor. of secs. 2, 3, 34 and 35, with brass cap mkd.

$$\begin{array}{c} T7N \quad R29E \\ S34 \quad S35 \quad WC \\ S 3 \quad S 2 \\ T6N \end{array}$$

1936

from true cor. point

the original bearing trees:

A yellow pine, 16 ins. diam., brs. S. 39 $\frac{1}{2}$ ° W., 23 lks. dist., mkd. T6N R29E S3 BT.

A yellow pine, 12 ins. diam., brs. N. 74° W., 52 lks. dist., mkd. T7N R29E S34 BT.

RESURVEY: NORTH BOUNDARY, T. 6 N., R. 29 E.

BOOK 4119

31

Chains

and establish additional bearing trees:

A yellow pine, 8 ins. diam., brs. N. $61\frac{1}{2}^{\circ}$ E., 106 lks. dist., mkd. T7N R29E S35 BT.

A yellow pine, 8 ins. diam., brs. S. 21° E., 48 lks. dist., mkd. T6N R29E S2 BT.

A yellow pine, 10 ins. diam., brs. S. 67° W., 82 lks. dist., mkd. T6N R29E S3 BT.

Land, mountainous.

Soil, volcanic loam, rocky, 3rd and 4th rates.

Timber, yellow pine, fir, aspen and spruce:

Undergrowth, scrub timber.

S. $88^{\circ} 02'$ E., on true line, bet. secs. 2 and 35 ($W\frac{1}{2}$).

Over mountainous land, thru dense timber and scattering undergrowth. Asc. 122 ft. over W. slope.

7.20 Ridge, brs. N. 20° E. and S. 20° W.; desc. 740 ft. over SE. slope to $\frac{1}{4}$ sec. cor.

31.60 Graded wood road, brs. NE. and SW.

43.63 Intersect original $\frac{1}{4}$ sec. cor. of secs. 2 and 35, which is an unmarked lava stone, 12x8x6 ins., firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground with original cor. stone reset alongside for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ $\frac{S\ 35}{S\ 2}$

1936

from which

A juniper, 10 ins. diam., brs. N. 14° E., 10 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A juniper, 20 ins. diam., brs. S. 59° W., 86 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

A tree fence cor. brs. N. $87\frac{1}{2}^{\circ}$ E., 36 lks. dist., from which fences extend N. 12° W. and N. $87\frac{1}{2}^{\circ}$ E.

Thence, N. $89^{\circ} 41'$ E.; on true line, bet. secs. 2 and 35 ($E\frac{1}{2}$).

Over mountainous land, thru dense timber and scattering undergrowth. Desc. 190 ft. over SE. slope to

21.90 Corral, at foot of steep slope, brs. NE. and SW. Leave dense and enter scattering timber. Fence cor. brs. N. 25 lks. dist., from which fences extend E. and NW. Leave mountainous and enter gently rolling land in valley. Desc. 60 ft. over SE. slope to sec. cor.

26.60 Fence cor. brs. N. 15 lks. dist. From which fences extend W. and S. 20° E.26.70 Fence cor. brs. S. 15 lks. dist., from which fences extend N. 20° W. and N. 85° E.

RESURVEY: NORTH BOUNDARY, T. 6 N., R. 29 E.

32

Chains

33.25 A yellow pine, 24 ins. diam., on line, mkd. with 2 notches on each of E. and W. faces. This tree is a fence cor. from which fence extends E. and S. 85° W. Leave timber and undergrowth and enter grassy land.

38.20 Leave gently rolling and enter nearly level land.

39.18 Intersect the locally accepted point of original location of the cor. of secs. 1, 2, 35 and 36, at fence corner from which fences extend N., S., and W. Alongside this fence cor. set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, with brass cap mkd.

T7N	R29E
S35	S36
S 2	S 1
T6N	

1936

from which

A yellow pine, 24 ins. diam., brs. S. $80\frac{1}{2}^{\circ}$ W., 556 lks. dist., mkd. T6N R29E S2 BT.

A yellow pine, 24 ins. diam., brs. N. $86\frac{3}{4}^{\circ}$ W., 594 lks. dist., mkd. T7N R29E S35 BT.

SE. cor. of a log cabin brs. N. $75^{\circ} 20'$ E.

A stone chimney on Lloyd Wilkin's house brs. N. $30^{\circ} 50'$ E.

A summer cabin brs. N. $25\frac{1}{2}^{\circ}$ E., about 25 chs. dist.

Land, mountainous, gently rolling and nearly level.

Soil, volcanic loam, 1st and 3rd rates.

Timber, yellow pine, oak and juniper.

Undergrowth, scrub timber and bunch grass.

N. $89^{\circ} 53'$ E., on true line, bet. secs. 1 and 36 ($W\frac{1}{2}$).

Over nearly level open cultivated land in valley. Desc. 35 ft. over SE. slope to wash.

20.05 Fence cor. brs. N. 1 lk. dist., from which fences extend N., S. and E. Leave cultivated land.

25.00 Log cabin brs. N. 7.00 chs. dist. Old log barn and deserted cabin, brs. S. 50 lks. dist.

27.00 Stream of running water, 2 lks. wide, 2 ins. deep, course S. 20° E.

32.00 Wash, 25 lks. wide, 15 ft. deep, course S. 70° E.

35.50 Road, brs. N. 70° W., and S. 70° E. Leave nearly level open land, and enter gently rolling land, and scattering timber and undergrowth. Asc. 12 ft. over SW. slope to

40.16 Intersect original $\frac{1}{4}$ sec. cor. of secs. 1 and 36, which is a mound of stone with fragment of a wood post in center. No trace of record bearing tree SE. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 25 ins. in the ground, to bedrock and raise mound of stone around post to top for $\frac{1}{4}$ sec. cor. with brass cap mkd.

RESURVEY: NORTH BOUNDARY, T. 6 N., R. 29 E.

BOOK 415

33

Chains

 $\frac{1}{4} \frac{S 36}{S 1}$

1936

from which

A juniper, 4 ins. diam., brs. N. $14\frac{1}{2}^{\circ}$ E., 23 lks. dist., mkd. BT only.

An oak, 6 ins. diam., brs. S. $30\frac{1}{2}^{\circ}$ W., 12 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Fence cor. brs. S. 3° W., 235 lks. dist. from which fences extend E. and S. $0\frac{1}{2}^{\circ}$ W.

A sheet iron barn (about 75 ft. square) at Lockhart Ranch, brs. S. $51\frac{1}{2}^{\circ}$ E.

Brick chimney on a frame house painted cream and green, brs. S. $33\frac{1}{2}^{\circ}$ E.

Thence,

S. $88^{\circ} 15'$ E., on true line, bet. secs. 1 and 36 ($E\frac{1}{2}$).

Over gently rolling land, thru scattering timber and undergrowth.

Asc. 45 ft. over SW. slope.

11.00 Desc. 100 ft. over SE. slope to Tp. cor.

26.20 Fence (4 strand barbed wire) brs. N. and S. At a point 150 lks. S. is a gate in fence for road bearing E. and W., at fence cor. from which fences extend E., W. and N. on S. side of road, and fence extends E. on N. side of road.

35.60 Fence, brs. N. 80° E. and S. 80° W.

38.25 Road, brs. E. and W.

40.15 Intersect the cor. of Tps. 6 and 7 N., Rs. 29 and 30 E., which is an iron post, 3 ins. diam., projecting 9 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record. This cor. is located at intersection of roads bearing N. $67\frac{1}{2}^{\circ}$ E., S. $1\frac{1}{2}^{\circ}$ W. and S. 81° W.

From this Tp. cor.

Sheet iron barn at Lockhart Ranch, brs. S. 35° W.

Brick chimney on cream and green painted frame house brs. S. $50\frac{1}{2}^{\circ}$ W.

A house about 5.00 chs. N. of the sheet iron barn at Lockhart Ranch brs. S. $43\frac{1}{2}^{\circ}$ W.

Land, nearly level and gently rolling.

Soil, W. $\frac{1}{2}$ dark loam, 1st rate. E. $\frac{1}{2}$ volcanic loam, 2nd and 3rd rates.

Timber, yellow pine, oak and juniper.

Undergrowth, scrub timber and bunch grass.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

34

Chains

Township 6 North, Range 29 East, was completely subdivided in 1883 by W. R. Fitzgerald, U. S. Deputy Surveyor, and no retracement or resurvey of any part of the subdivision lines of this township is of record.

The following notes describe a dependent resurvey of all of the subdivision lines, reconstructing all existing corner monuments, reestablishing all missing corners by proportional measurement between existing corners, and monumenting all corners with regulation brass-capped iron posts.

Commence dependent resurvey of the subdivision lines of T. 6 N., R. 29 E., at the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp. hereinbefore described.

Thence,

N. $0^{\circ} 57'$ W., on true line, bet. secs. 35 and 36 ($S\frac{1}{2}$).

Over rolling land, thru medium timber and scattering undergrowth. Desc. 135 ft. over N. slope to

10.23 U. S. Forest Service telephone line, brs. E. and W. Leave rolling land, timber and undergrowth and enter nearly level grassy land. Desc. 10 ft. over N. slope to draw.

11.10 Old highway, brs. N. 68° W., and S. 68° E.

13.18 Draw, course N. 80° E. Desc. gradually over E. slope.

16.33 Fence (5 strand barbed wire) brs. N. 16° W. and S. 16° E. Turns to S. 68° E. at 5.70 chs. SE. of this point and turns to N. 65° W. at 1.42 chs. NW.

18.58 Highway, brs. N. $42\frac{1}{2}^{\circ}$ E. and S. $42\frac{1}{2}^{\circ}$ W.

30.78 Leave nearly level land, brs. N. 60° W. and S. 60° E. and enter gently rolling land. Asc. 10 ft. over SW. slope to

39.82 Intersect original $\frac{1}{4}$ sec. cor. of secs. 35 and 36, which is an unmarked lava stone, $12 \times 10 \times 8$ ins., firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone reset alongside; for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S35 | S36
1936

raise a mound of stone
3 ft. base, 2 ft. high W. of cor.

Thence,

N. $2^{\circ} 02'$ E., on true line, bet. secs. 35 and 36 ($N\frac{1}{2}$)

Over gently rolling grassy land, devoid of timber and undergrowth, asc. slightly over SW. slope.

1.50 Low ridge, brs. S. 60° E. and N. 60° W. At about 2 chs. NW. a short spur slopes S. 30° W., desc. 29 ft. over NE. slope.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

35

Chains

- 2.00 Trail, brs. NE. and SW.
- 11.20 Enter timber, brs. N. 50° E. and N. 45° W.
- 14.45 Leave timber, brs. N. 60° W. and S. 60° E.
- 15.47 Creek, with a stream of water, 3 lks. wide, 2 ins. deep, course N. 60° W. Leave gently rolling and enter mountainous land. Asc. 245 ft. over SW. slope to sec. cor.
- 16.48 Enter dense timber, brs. N. 60° W. and S. 60° E.
- 39.97 Intersect original cor. of secs. 25, 26, 35 and 36, which is a lava stone, 16x14x8 ins. above ground, firmly set, mkd. with one notch on S. face, and witnessed by two of the three record bearing trees. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground, to bed rock and in a mound of stone to top, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T6N	R29E
S26	S25
S35	S36

1936

from which

the original bearing trees:

A yellow pine, 16 ins. diam., brs. N. 57° E., 20 lks. dist., mks. overgrown. Remark on overgrowth, T6N R29E S25 BT.

A yellow pine (fallen) 16 ins. diam., brs. N. 5° W., 33 lks. dist., mkd. T6N R29E S26 BT.

and establish additional bearing trees:

A yellow pine, 14 ins. diam., brs. S. 73½° E., 66 lks. dist., mkd. T6N R29E S36 BT.

A yellow pine, 8 ins. diam., brs. S. 56½° W., 51 lks. dist., mkd. T6N R29E S35 BT.

A yellow pine, 12 ins. diam., brs. N. 18½° W., 62 lks. dist., mkd. T6N R29E S26 BT.

Land, rolling, nearly level, gently rolling and mountainous.

Soil, volcanic loam, 1st rate in valley, rocky 4th rate elsewhere.

Timber, fir, yellow pine, spruce and aspen.

Undergrowth, scrub timber.

Fair grass.

From cor. of secs. 25, 30, 31 and 36, on E. bdy. of the Tp. which is an iron post, 2 ins. diam., projecting 14 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

Thence,

S. 89° 55' W., on true line, bet. secs. 25 and 36 (E½).

Over mountainous land, thru dense timber and scattering

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

36

Chains	undergrowth. Desc. 200 ft. over SW. slope to
15.61	Draw, course S. 35° W. Asc. 15 ft. over SE. slope.
22.56	Desc. 37 ft. over S. and SW. slopes to
40.05	Intersect original $\frac{1}{4}$ sec. cor. of secs. 25 and 36, which is an unmarked lava stone, 20x14x6 ins., above ground, firmly set and witnessed by the record bearing tree SE. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top; for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$
	1936
	from which
	the original bearing trees:
	A yellow pine, 20 ins. diam., brs. S. 55° E., 34 lks. dist., old blaze visible but mks. are overgrown. Remark on overgrowth $\frac{1}{4}$ S36 BT.
	and establish additional bearing tree:
	A yellow pine, 18 ins. diam., brs. N. 51 $\frac{1}{2}$ ° W., 68 lks. dist., mkd. $\frac{1}{4}$ S25 BT.
	This cor. is located on top of a spur, sloping S. 30° W.
	Thence,
	N. 89° 48' W., on true line, bet. secs. 25 and 36. (W $\frac{1}{2}$)
	Over mountainous land; thru dense timber and scattering undergrowth.
	Desc. 162 ft. over SW. slope.
10.78	Draw, course S. 10° E., asc. 133 ft. over SE. slope.
18.28	Spur, slopes S. 20° E. from N. 30° W. Desc. 52 ft. over SW. slope.
29.25	Asc. 57 ft. over SE. slope.
34.20	Desc. 12 ft. over SW. slope to
39.67	The cor. of secs. 25, 26, 35 and 36.
	Land, mountainous. Soil, lava rock, over dark loam, 1st and 4th rates. Timber, yellow pine, aspen, fir and oak. Undergrowth, scrub timber and bunch grass.
	N. 4° 55' W., on true line, bet. secs. 25 and 26 (S $\frac{1}{2}$).
	Over mountainous land, thru dense timber and scattering undergrowth. Asc. 30 ft. over SW. slope.
3.18	Fence (4 strand barbed wire) brs. E. and W.
4.00	Spur, slopes W., desc. 95 ft. over NW. slope.
24.00	Head of draw, course SW.; asc. 232 ft. over SW. slope to

Chains

38.25

(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S26 \quad | \quad S25 \end{array}$$

1936

from which

A yellow pine, 10 ins. diam., brs. N. $33\frac{1}{2}^{\circ}$ E., 50 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

A yellow pine, 14 ins. diam., brs. S. 38° W., 29 lks. dist., mkd. $\frac{1}{4}$ S26 BT.

Asc. 33 ft. over SW. slope.

42.75

Ridge bears N. 80° E. and S. 80° W. A spur slopes N. from ridge at this point. Desc. 84 ft. along top of spur to

57.00

Leave top of spur, slopes N. 60° W. from S., desc. 180 ft. over N. slope.

65.70

Draw, course W.; asc. 160 ft. over SW. slope to

76.50

Intersect original cor. of secs. 23, 24, 25 and 26, which is an unmarked lava stone, 20x10x10 ins. firmly set in a mound of stone and witnessed by two of the three record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 23, 24, 25 and 26; with brass cap mkd.

$$\begin{array}{c} T6N \quad R29E \\ S23 \quad | \quad S24 \\ \hline S26 \quad | \quad S25 \end{array}$$

1936

from which

the original bearing trees:

A yellow pine, 16 ins. diam., brs. S. $55\frac{1}{4}^{\circ}$ E., 29 lks. dist. Old blaze visible, mkg. overgrown. Remark on overgrowth T6N R29E S25 BT.

A white pine, 18 ins. diam.; brs. S. 37° W., 36 lks. dist. Old blaze visible, mkg. overgrown.

and establish additional bearing trees:

A yellow pine, 8 ins. diam., brs. N. 21° E., 43 lks. dist., mkd. T6N R29E S24 BT.

A yellow pine, 14 ins. diam., brs. S. $81\frac{1}{2}^{\circ}$ W., 74 lks. dist., mkd. T6N R29E S26 BT.

A yellow pine, 14 ins. diam., brs. N. $28\frac{1}{2}^{\circ}$ W., 58 lks. dist., mkd. T6N R29E S23 BT.

Land, mountainous.

Soil, volcanic loam, rocky, 1st and 3rd rates.

Timber, yellow pine, aspen, spruce and sugar pine.

Undergrowth, scrub timber and bunch grass.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

38

Chains	
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. which is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.
	Thence,
	S. 89° 53' W., on true line, bet. secs. 24 and 25 (E½).
	Over mountainous land, thru dense timber and scattering undergrowth. Desc. 250 ft. over W. slope.
29.32	Draw, course S., asc. 80 ft. over E. slope to
34.57	Leave mountainous and enter rolling land. Asc. 15 ft. over SE. slope to
39.57	Intersect original ¼ sec. cor. which is a lava stone, mkd. ¼ on top, 16x8x8 ins. firmly set in a mound of stone and witnessed by charred stump of original bearing tree SW. which has been burned. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original cor. stone reset alongside and in mound of stone to top for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 24}{S \ 25}$
	1936
	from which,
	A yellow pine, 14 ins. diam., brs. N. 30° E., 55 lks. dist., mkd. ¼ S24 BT.
	A yellow pine, 4 ins. diam., brs. S. 25° E., 15 lks. dist., mkd. ¼ S25 BT.
	Thence,
	S. 89° 55' W., on true line, bet. secs. 24 and 25 (W½).
	Over rolling land, thru dense timber and scattering undergrowth. Asc. slightly over SE. slope.
0.96	Ridge, brs. S. 35° W., and N. 35° E., desc. 122 ft. over SW. slope.
12.11	Draw, 2.00 chs. wide, course S. 30° W., asc. 134 ft. over SE. slope.
28.96	Spur, slopes S. 10° E., desc. 103 ft. over SW. slope to
39.96	The cor. of secs. 23, 24, 25 and 26.
	Land, mountainous and rolling. Soil, dark rocky loam, 1st and 3rd rates. Timber, yellow pine, aspen, fir and sugar pine. Undergrowth, scrub timber and bunch grass.
	N. 0° 04' E. on true line, bet. secs. 23 and 24.
	Over rolling land, thru dense timber and scattering undergrowth. Asc. 40 ft. over SW. slope.
9.98	Spur, slopes W., desc. 31 ft. over NW. slope.
12.94	Draw, course W., asc. 68 ft. over SW. slope.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

39

Chains

24.93 Spur, slopes N. 75° W.; desc. 58 ft. over NW. slope to

38.90. Leave rolling and enter mountainous land. Desc. 30 ft. over steep NW. slope to

39.85 (Mid point). Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd..

S23 | S24

1936

from which

A fir, 14 ins. diam., brs. S. 84 $\frac{1}{2}$ ° E., 35 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

A spruce, 8 ins. diam., brs. S. 55° W., 16 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

Desc. 59 ft. over steep NW. slope.

42.77 Draw, course S. 70° W., asc. 235 ft. over SE. slope.

65.00 Long spur, slopes S. 70° W.; asc. 63 ft. over SW. slope.

77.00 Divide bet. Salt River and Colorado River, brs. NW. and SE., desc. 13 ft. over N. slope to sec. cor.

79.30 Trail bears NW. and SE.

79.70 Intersect the original cor. of secs. 13, 14, 23 and 24, which is a triple-trunk white pine bearing tree, with one overgrown blaze on NE. fork, 12 ins. diam., one on SE. fork 10 ins. diam., and one on SW. fork 10 ins. diam. Remark this tree for same reference as follows: T6N R29E S13 on NE. face, S24 on SE. face, S23 on SW. face, and S14 on NW. face. This tree is alive and healthy and offers reasonable permanency for the cor. monument, therefore do not set regulation brass-capped iron post.

From which one of the two original bearing trees:

A yellow pine, 16 ins. diam., brs. S. 37° W., 19 lks. dist. Old blaze visible but mks. overgrown. Remark above and below old blaze, T6N R29E S23 BT.

and establish additional bearing trees:

A yellow pine, 14 ins. diam., brs. N. 22° E., 10 lks. dist., mkd. T6N R29E S13 BT.

A yellow pine, 12 ins. diam., brs. S. 15 $\frac{1}{2}$ ° E., 33 lks. dist., mkd. T6N R29E S24 BT.

A fir, 30 ins. diam., brs. N. 15 $\frac{1}{2}$ ° W., 16 lks. dist., mkd. on bark T6N R29E S14 BT.

Land, rolling and mountainous.
Soil, lava rock over dark loam, 1st and 4th rates.
Timber, yellow pine, fir, spruce, aspen and oak.
Undergrowth, scrub timber.

From the cor. of secs. 13, 18, 19 and 24, on E. bdy. of Tp. which is an iron post, 2 ins. diam., projecting 20 ins. above ground, firmly set in ground and mound of

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

40

Chains	stone, mkd. on brass cap and witnessed as described in the official record, thence,
	N. 89° 23' W., on true line, bet. secs. 13 and 24.
	Over mountainous land, thru dense timber and scattering undergrowth. Asc. 51 ft. over NE. slope to
13.28	Ravine, course NE. Asc. 506 ft. over NE. slope to
39.72	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ $\frac{S13}{S24}$
	1936
	from which
	A fir, 8 ins. diam., brs. N. 81° E., 40 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
	A fir, 12 ins. diam., brs. S. 77° W., 44 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	Asc. 30 ft. over NE. slope.
43.44	Ridge, brs. N. 70° W. and S. 70° E.; desc. 20 ft. over S. slope to
51.44	Same ridge, brs. S. 85° W., and N. 70° E., desc. 40 ft. over NW. slope.
60.50	Head of draw, course N., asc. 51 ft. over NE. slope.
67.50	Bend in same ridge from S. 60° E. to S. 85° W. Desc. 24 ft. over N. slope.
75.15	Asc. 10 ft. over NE. slope to
79.44	The cor. of secs. 13, 14, 23 and 24.
	Land, mountainous.
	Soil, rocky, over dark loam, 3rd and 4th rates.
	Timber, yellow pine, fir, spruce, and aspen.
	Undergrowth, scrub timber.
	N. 0° 20' E., on true line, bet. secs. 13 and 14 ($S\frac{1}{2}$).
	Over mountainous land, thru dense timber and scattering undergrowth. Desc. 530 ft. over NE. slope to $\frac{1}{4}$ sec. cor.
8.70	Blazed trail, brs. NE. and SW.
39.60	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S14 S13
	1936
	from which
	A fir, 10 ins. diam., brs. East, 12 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
	A white pine, 14 ins. diam., brs. S. 83° W., 14 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Chains

Desc. 330 ft. over NE. and E. slopes to

79.20

Intersect original cor. of secs. 11, 12, 13 and 14, which is a sandstone, 18x12x8 ins., mkd. with a cross (X) on top, firmly set in a mound of stone and witnessed by charred stump of record bearing tree NE.; destroyed by fire. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone reset alongside, and in a mound of stone to top, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.

T6N	R29E
S11	S12
S14	S13

1936

from which

A yellow pine, 12 ins. diam., brs. N. 77° E., 62 lks. dist., mkd. T6N R29E S12 BT.

A yellow pine, 10 ins. diam., brs. S. 29° E., 45 lks. dist., mkd. T6N R29E S13 BT.

A yellow pine, 16 ins. diam., brs. S. 5° W., 30 lks. dist., mkd. T6N R29E S14 BT.

A yellow pine, 16 ins. diam., brs. N. 71° W., 40 lks. dist., mkd. T6N R29E S11 BT.

From this cor. Mary's Nipple on SW. point of Gobbler Mountain brs. N. 38° E., vertical angle + 9 $\frac{3}{4}$ °.

Land, mountainous.

Soil, dark loam, rocky, 1st and 4th rates.

Timber, yellow pine, fir, spruce, aspen, oak and sugar pine. Undergrowth, scrub timber.

The brass-capped iron post described in the record of the resurvey in 1925 of West bdy. of T. 6 N., R. 30 E. as having been set at original point of location of the cor. of secs. 7, 12, 13 and 18 has been removed and no trace of same can be found, therefore recover the corner point by record tie from the original bearing tree, which is a pine stump, 60 ins. diam., 3 ft. high, mkd. T6N R29E S12 BT., bearing N. 12 $\frac{1}{2}$ ° W., 114 lks. dist. At true point for cor., set a sandstone, 8x6x4 ins., 10 ins. below surface of the ground, mkd. with cross (X) on top, from which

the bearing trees established in the 1925 resurvey:

A yellow pine, 16 ins. diam., brs. N. 24 $\frac{1}{2}$ ° E., 245 lks. dist., mkd. T6N R30E S7 BT.

A yellow pine, 36 ins. diam., brs. S. 30 $\frac{1}{2}$ ° W., 694 lks. dist., mkd. T6N R29E S13 BT.

A yellow pine, 14 ins. diam., brs. N. 7 $\frac{1}{2}$ ° W., 218 lks. dist., mkd. T6N R29E S12 BT.

No trace of the record SE. bearing tree, therefore establish new bearing tree:

A yellow pine, 18 ins. diam., brs. S. 23° E., 650 lks. dist., mkd. T6N R29E S18 BT.

Chains	Description										
	The original corner point is now in a cultivated field where corner monument is again liable to destruction, therefore at a point N. 0° 51' E., 2.00 chs. dist., set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for witness cor. to cor. of secs. 7, 12, 13 and 18, with brass cap mkd.										
	<table border="1"> <tr><td colspan="2">T6N</td></tr> <tr><td>R29E</td><td>R30E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">W C</td></tr> </table> <p>1936</p>	T6N		R29E	R30E	S12	S 7	S13	S18	W C	
T6N											
R29E	R30E										
S12	S 7										
S13	S18										
W C											
	From true point for cor.										
	S. 89° 52' W., on true line, bet. secs. 12 and 13.										
	Over nearly level, open, cultivated land.										
3.65	Leave nearly level cultivated land, brs. N. 70° E. and S. 70° W., and enter rolling land, scattering timber and undergrowth. Asc. 45 ft. over SE. slope to draw.										
3.85	Road, brs. N. and S.										
9.05	Fence (5 strand barbed wire) brs. N. 85° E., and S. 85° W.										
10.45	Draw, near head, course S. 70° E., from N. 20° W. Ascend 120 ft. over SE. and S. slopes to										
36.00	Desc. 16 ft. over S. slope to $\frac{1}{4}$ sec. cor.										
38.75	Fence, brs. N. 60° W. and S. 60° E.										
39.35	Intersect line 3-4 of boundary of Forest Homestead Entry Survey No. 240 (patented), at a point 3.51 chs. N. 60° 16' W., from cor. No. 3 thereof. Thence across said patented homestead.										
39.70	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.										
	<table border="1"> <tr><td>$\frac{1}{4}$</td><td>S 12</td></tr> <tr><td></td><td>S 13</td></tr> </table> <p>1936</p>	$\frac{1}{4}$	S 12		S 13						
$\frac{1}{4}$	S 12										
	S 13										
	from which,										
	A yellow pine, 24 ins. diam., brs. N. 75½° E., 71 lks. dist., mkd. $\frac{1}{4}$ S12 BT.										
	A yellow pine, 40 ins. diam., brs. N. 52° W., 131 lks. dist., mkd. $\frac{1}{4}$ S13 BT.										
	Desc. 12 ft. over SW. slope.										
42.12	Creek, with stream of water, 2 lks. wide, 3 ins. deep course S. 60° E. Asc. 125 ft. over NE. slope.										
43.40	Intersect line 7-8 of boundary of Forest Homestead Entry Survey No. 240, at a point, 23 lks. S. 54° 51' E., from cor. No. 7 thereof. Leave said patented homestead.										
45.34	Fence (4 strand barbed wire) brs. N. 60° W. and S. 60° E.										
45.54	Old road, brs. NW. and SE.										

RESURVEY; SUBDIVISION LINES, T. 6 N., R. 29 E.

43

Chains							
59.45	Enter mountainous land. Asc. 223 ft. over E. slope to						
79.40	The cor. of secs. 11, 12, 13 and 14.						
	Land, nearly level, rolling and mountainous. Soil, dark loam, rocky, 1st and 4th rates. Timber, yellow pine, fir, oak, spruce and aspen. Undergrowth, scrub timber and bunch grass.						
	N. 0° 29' W., on true line, bet. secs. 11 and 12.						
	Over mountainous land, thru dense timber and scattering undergrowth. Desc. 90 ft. over E. and NE. slopes.						
15.50	Draw, course S. 70° E.; asc. 370 ft. over broken SE. slope to						
40.50	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S11</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S12</td> </tr> <tr> <td></td> <td style="text-align: center;">1936</td> <td></td> </tr> </table> <p style="text-align: right;">from which</p>	S11		S12		1936	
S11		S12					
	1936						
	A juniper, 5 ins. diam., brs. N. 57° E., 44 lks. dist. mkd. $\frac{1}{4}$ S12 BT.						
	A juniper fork, 12 ins. diam., brs. S. 55½° W., 57 lks. dist., mkd. $\frac{1}{4}$ S11 BT.						
	Mary's Nipple on SW. point of Gobbler Mountain, brs. S. 75½° E. Asc. 60 ft. over SE. slope.						
43.25	Saddle brs. E. and W., desc. 473 ft., over broken NE. slope to						
81.00	Intersect original cor. of secs. 1, 2, 11 and 12, which is a mound of stone, 2 ft. base, 1 ft. high, witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to bedrock and in a mound of stone to top, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T6N</td> <td style="text-align: center;">R29E</td> </tr> <tr> <td style="text-align: center;">S2</td> <td style="text-align: center;">S1</td> </tr> <tr> <td style="text-align: center;">S11</td> <td style="text-align: center;">S12</td> </tr> </table> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p>	T6N	R29E	S2	S1	S11	S12
T6N	R29E						
S2	S1						
S11	S12						
	the original bearing trees:						
	A yellow pine, 24 ins. diam., brs. S. 40° E., 54 lks. dist. Old blaze visible, mks. overgrown. Remark on overgrowth, T6N R29E S12 BT.						
	A yellow pine, 16 ins. diam., brs. S. 72° W., 62 lks. dist., mkd. T6N R29E S11 BT.						
	and establish additional bearing trees:						
	A yellow pine, 24 ins. diam., brs. N. 26° E., 147 lks. dist., mkd. T6N R29E S1 BT.						

RESURVEY: SUBDIVISION LINES, T. 6 N.; R. 29 E.

44

Chains	
	<p>A yellow pine, 20 ins. diam., brs. N. 76° W., 143 lks. dist., mkd. T6N R29E S2 BT.</p> <p>Land, mountainous. Soil, dark loam, rocky, 1st and 4th rates. Timber, yellow pine, oak, fir, spruce and juniper. Undergrowth, scrub timber.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. which is an iron post, 2 ins. diam., projecting 16 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.</p> <p>Thence,</p> <p>N. 88° 26' W., on true line, bet. secs. 1 and 12.</p> <p>Over gently rolling land, thru dense timber and scattering undergrowth. Asc. 40 ft. over E. slope to</p> <p>6.20 Enter mountainous land. Asc. 130 ft. over SE. slope.</p> <p>16.47 Spur, slopes NE. Descend slightly over N. slope.</p> <p>19.97 Draw, course N. 60° E.; asc. 158 ft. over E. slope.</p> <p>30.57 Spur, slopes NE.; desc. 61 ft. over NW. slope to</p> <p>40.41 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 1}{S 12}$</p> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p> <p>A fir, 6 ins. diam., brs. S. 37$\frac{1}{2}$° W., 18 lks. dist., mkd. $\frac{1}{4}$ S12 BT.</p> <p>A yellow pine, 30 ins. diam., brs. N. 63° W., 55 lks. dist.; mkd. $\frac{1}{4}$ S1 BT.</p> <p>Desc. 213 ft. over NW. slope.</p> <p>60.42 Stream of running water, 2 lks. wide, 1 in. deep, course N. 15° E.; asc. 240 ft. over broken NE. slope to</p> <p>80.82 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, gently rolling and mountainous. Soil, dark loam, rocky, 1st and 4th rates. Timber, yellow pine, aspen, spruce, fir and oak. Undergrowth, scrub timber.</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp. hereinbefore described.</p> <p>S. 0° 42' W., on true line, bet. secs. 1 and 2 (N$\frac{1}{2}$).</p> <p>Over nearly level grassy land, devoid of timber and undergrowth, along W. side of fence bearing N. and S. Desc. 6 ft. over SE. slope to</p> <p>5.00 Draw, course N. 70° E.; asc. slightly over N. slope.</p>

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

45

Chains	
7.00	Fence (4 strand barbed wire) brs. N. and S. 3° W. Leave nearly level open land, and enter rolling land and dense timber and scattering undergrowth. Asc. 50 ft. over N. slope.
11.94	Low spur, slopes N. 80° E., desc. 12 ft. over S. slope.
16.64	Same fence, brs. N. 20° W., and S. 20° E.
21.13	Fence (6 strand barbed wire) brs. N. 30° E., and S. 30° W.
21.90	Asc. 49 ft. over NE. slope to
38.96	Intersect the point of original location of the $\frac{1}{4}$ sec. cor. determined by record tie from the original bearing tree NW, at which point, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$S \ 2 \frac{1}{4} \ S \ 1$ 1936
	from which
	the original bearing tree:
	A white oak, 30 ins. diam.; brs. N. 31 $\frac{1}{2}$ ° W., 38 lks. dist., mkd. $\frac{1}{4}$ S2 BT.
	and establish additional bearing trees:
	A yellow pine, 16 ins. diam., brs. N. 71 $\frac{1}{2}$ ° E., 65 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
	A yellow pine, 24 ins. diam., brs. N. 86° W., 52 lks. dist., mkd. $\frac{1}{4}$ S2 BT.
	Thence,
	S. 0° 30' W., on true line, bet. secs. 1 and 2 (S $\frac{1}{2}$):
	Over rolling land, thru dense timber and scattering undergrowth. Asc. 140 ft. over NE. slope to
25.80	Enter mountainous land. Asc. 125 ft. over NE. slope to
39.86	The cor. of secs. 1, 2, 11 and 12.
	Land, nearly level, rolling and mountainous. Soil, volcanic loam and rocky, 1st and 3rd rates. Timber, yellow pine, oak, juniper, aspen and fir. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 10' W., on true line, bet. secs. 34 and 35 (S $\frac{1}{2}$).
	Over mountainous land, thru medium timber and scattering undergrowth. Desc. 73 ft. over NE. slope.
3.80	Draw, course NW., asc. 10 ft. over SW. slope.
5.80	Spur, slopes NW. Desc. 66 ft. over N. slope.
10.10	Ravine, course NW., asc. 154 ft. over SW. slope.
10.70	Trail, brs. NW. and SE.


RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

46

Chains

30.00 Ascend gradually over W. slope to

41.22 Intersect original $\frac{1}{4}$ sec. cor. of secs. 34 and 35, which is a small mound of stone witnessed by the record bearing tree. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

the original bearing tree:

A pine, 30 ins. diam., brs. S. $45\frac{3}{4}^{\circ}$ W., 10 lks. dist., mkd. $\frac{1}{4}$ S.

and establish additional bearing trees:

A yellow pine, 18 ins. diam., brs. S. 68° E., 15 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A yellow pine, 18 ins. diam., brs. S. $74\frac{1}{2}^{\circ}$ W., 25 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

Thence,

N. $0^{\circ} 12'$ E., on true line, bet. secs. 34 and 35 ($N\frac{1}{2}$).

Over mountainous land; thru medium timber and scattering undergrowth.

Desc. 155 ft. over NW. slope.

15.60 Highway, brs. E. and SW.

16.80 Draw, course NE. Leave mountainous and enter rolling land. Ascend gradually over E. slope.


24.80 Desc. 75 ft. over NE. slope to sec. cor.

38.40 Leave timber and undergrowth, brs. NW. and SE., enter open grassy land.

39.10 Road, brs. NW. and SE.

39.30 Fence (4 strand barbed wire) brs. N. 60° W. and S. 60° E.

39.73 Intersect the original cor. of secs. 26, 27, 34 and 35, which is a small mound of stone around decayed remains of a wood post. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, and raise mound of stone around post to top, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.



from which

A yellow pine, 30 ins. diam., brs. S. $43\frac{1}{2}^{\circ}$ E., 206 lks. dist., mkd. T6N R29E S35 BT.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

47

Chains

A yellow pine, 36 ins. diam., brs. S. 21° W., 366
lks. dist., mkd. T6N R29E S34 BT.

No other bearing trees within limits.

Land, mountainous and rolling.

Soil, volcanic loam, rocky, 1st and 4th rates.

Timber, yellow and black pine, fir and spruce.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 25, 26, 35 and 36.

N. 89° 48' W., on true line, bet. secs. 26 and 35. (E½).

Over rolling land, thru dense timber and scattering under-
growth. Desc. 63 ft. over S. slope.

4.98 Fence (4 strand barbed wire) brs. N. and S. At a point 3
chs. north this fence turns to E.

9.95 Spur, slopes S. 70° W., desc. 81 ft. over NW. and N. slopes
to

21.38 Same spur, slopes N. 65° W., desc. 148 ft., over SW. slope.

29.67 Leave timber, brs. N. 60° W. and S. 50° E.

33.97 Open draw, 4.00 chs. wide, course N. Enter gently rolling
land, asc. 17 ft. over NE. slope.

37.00 Enter scattering timber, brs. NW. and SE.

37.16 Low ridge, brs. N. 20° W. and S. 50° E., desc. 7 ft. over
SW. slope to

39.92 Intersect original ¼ sec. cor. of secs. 26 and 35, which
is an unmarked lava stone, 16x12x6 ins., firmly set in
a mound of stone and witnessed by the one record bearing
tree NW. Reconstruct this cor. monument as follows:
remove the mound of stone and the original cor. stone,
and in same place, set an iron post, 3 ft. long, 1 in.
diam., 12 ins. in the ground to bedrock with the origi-
nal cor. stone reset alongside, and in a mound of stone
to top, for ¼ sec. cor., with brass cap mkd.

¼ $\frac{S26}{S35}$

1936

from which

the original bearing tree:

A yellow pine, 20 ins. diam., brs. N. 73½° W., 29 lks.
dist., mks. overgrown. Remark ¼ S26 BT.

and establish additional bearing tree:

A yellow pine, 16 ins. diam., brs. S. 43½° W., 75 lks.
dist., mkd. ¼ S35 BT.

Thence,

S. 89° 45' W., on true line, bet. secs. 26 and 35 (W½).

Over nearly level land, thru scattering timber and under-
growth.

Desc. 85 ft. over W. slope.

. RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

Chains


- 1.00 Leave timber and undergrowth, hrs. N. and S. 60° E. and enter open grassy land.
- 23.40 Wash, course NW. Ascend gradually over NE. slope to
- 36.60 Old road, hrs. NW, and SE. Leave nearly level and enter gently rolling land. Asc. 17 ft. over NE. slope to
- 39.70 The cor. of secs. 26, 27, 34 and 35.

Land, rolling, gently rolling and nearly level.
 Soil, dark loam, rocky, 1st and 4th rates.
 Timber, yellow pine, fir, spruce and aspen.
 Undergrowth, scrub timber.
 Fair grass.

N. 0° .20' W., on true line, bet. secs. 26 and 27.

Over gently rolling, open grassy land, desc. 34 ft. over N. slope.

- 2.30 Old road, hrs. SE. and W.
- 9.80 Wash, 8 lks. wide, 2 ft. deep, course W., asc. 35 ft. over S. slope.
- 21.50 Low ridge, hrs. E. and W.; desc. slightly over N. slope.
- 25.00 Wash, 4 lks. wide, 1 ft. deep, course W., asc. 56 ft. over S. slope to
- 40.36 (Mid point) Set an iron post, .3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.




Thence,

N. 0° 20' W., on true line, bet. secs. 26 and 27 (N $\frac{1}{2}$).

Over gently rolling, open, grassy land. Asc. 60 ft. over SW. slope.

- 70.30 Desc. 25 ft. over NW. slope.
- 77.40 Ravine, with a stream of running water, 3 lks. wide, 1 in. deep, course SW., asc. 15 ft. over S. slope to
- 80.73 Intersect original cor. of secs. 22, 23, 26 and 27, which is a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with a lava stone, 12x9x7 ins., mkd. with a cross (X) deposited at base, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.



1936

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

49

Chains	<p>Land, gently rolling. Soil, volcanic loam, 2nd and 3rd rates. Timber, none. Undergrowth, none. Fair grass.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26. N. 82° 13' W., on true line, bet. secs. 23 and 26 ($E\frac{1}{2}$). Over mountainous land, thru dense timber and scattering undergrowth. Desc. 290 ft. over SW. slope to $\frac{1}{4}$ sec. cor.</p>
14.69	Enter aspen thicket, brs. N. and S.
16.19	Leave aspen thicket, brs. N. and S. Thence thru scattering timber and undergrowth.
24.49	Trail, brs. NE. and SW.
33.69	<p>Intersect original $\frac{1}{4}$ sec. cor. of secs. 23 and 26, which is a small mound of stone. Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 25 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S}{S}$ $\frac{23}{26}$ </p> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p> <p>A yellow pine, 8 ins. diam., brs. N. 52$\frac{1}{2}$° E., 41 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p>A yellow pine, 12 ins. diam., brs. S. 72$\frac{1}{2}$° W., 40 lks. dist., mkd. $\frac{1}{4}$ S26 BT.</p> <p>Thence,</p> <p>S. 89° 58' W., on true line, bet. secs. 23 and 26 ($W\frac{1}{2}$). Over gently rolling land, thru scattering timber and undergrowth. Desc. 65 ft. over SW. slope to sec. cor.</p>
1.26	Trail, brs. NW. and SE.
11.16	Leave timber and undergrowth, brs. S. and NW. and enter open grassy land.
24.56	Ravine, with stream of running water, 5 lks. wide, 1 in. deep, course SW.
40.16	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling. Soil, volcanic loam, 2nd and 3rd rates. Timber, yellow pine, fir, aspen and spruce. Undergrowth, scrub timber. Fair grass.</p>
	<p>N. 0° 53' W., on true line, bet. secs. 22 and 23. Over gently rolling, open grassy land. Asc. gradually over SW. slope to</p>
5.30	Wash, 5 lks. wide, 1 ft. deep, course SW. Asc. gradually over SW. slope to

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

50

Chains									
16.50	Leave gently rolling, open grassy land, brs. NW. and SE. and enter rolling land, scattering timber and undergrowth. Asc. 153 ft. over SW. slope to								
40.26	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 25 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>S22</td> <td> </td> <td>S23</td> </tr> <tr> <td colspan="3" style="text-align: center;">1936</td> </tr> </table> </div> <p style="text-align: right;">from which</p> <p>A black pine, 8 ins. diam., brs. N. 35° E., 44 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p>A yellow pine, 24 ins. diam., brs. N. 15° W., 15 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>Asc. 166 ft. over SW. and S. slopes.</p>	S22		S23	1936				
S22		S23							
1936									
63.40	Spur, slopes W., Desc. 50 ft. over N. slope.								
68.80	Leave timber and undergrowth, brs. E. and W. and enter open grassy land.								
69.90	Draw, course W., asc. 62 ft., over SW. slope.								
71.60	Leave open grassy land and enter medium timber and scattering undergrowth, brs. E. and W.								
80.30	Spur, slopes W. Thence across top of spur to								
80.51	Intersect original cor. of secs. 14, 15, 22 and 23, which is a mound of stone witnessed by the one original bearing tree. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T6N</td> <td>R29E</td> </tr> <tr> <td>S15</td> <td> </td> <td>S14</td> </tr> <tr> <td>S22</td> <td> </td> <td>S23</td> </tr> </table> </div> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p> <p>the original bearing tree:</p> <p>A black pine, 30 ins. diam., brs. S. 66° W., 13 lks. dist., mkd. T6N R29E S22 BT.</p> <p>and establish additional bearing trees:</p> <p>A black pine, 12 ins. diam., brs. N. 73$\frac{1}{2}$° E., 94 lks. dist., mkd. T6N R29E S14 BT.</p> <p>A black pine, 10 ins. diam., brs. S. 10$\frac{1}{2}$° E., 104 lks. dist., mkd. T6N R29E S23 BT.</p> <p>A black pine, 24 ins. diam., brs. S. 57° W., 165 lks. dist., mkd. T6N R29E S22 BT.</p> <p>A spruce, 6 ins. diam., brs. N. 45° W., 55 lks. dist., mkd. T6N R29E S15 BT.</p>	T6N	R29E	S15		S14	S22		S23
T6N	R29E								
S15		S14							
S22		S23							

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

51

Chains	
	Land, gently rolling and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, fir, spruce, pine, aspen and box cedar. Undergrowth, scrub timber. Fair grass.
	From the cor. of secs. 13, 14, 23 and 24. N. 85° 56' W., on true line, bet. secs. 14 and 23, Over rolling land, thru dense timber and scattering undergrowth.
3.00	Divide bet. Salt River and Colorado River, brs. NW. and SE. Desc. 171 ft. over SW. and S. slopes to $\frac{1}{4}$ sec. cor.
14.96	Trail brs. N. 80° E., and S. 60° W.
37.48	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 14}{S. 23}$
	1936
	from which,
	A fir, 8 ins. diam., brs. S. 75° W., 11 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	A fir, 6 ins. diam., brs. N. 50° W., 7 lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	Desc. 42 ft. over S. slope to
56.00	Spur, slopes W. from NE. Desc. 120 ft. along top of spur to
74.96	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, fir, spruce, aspen and pine. Undergrowth, scrub timber.
	N. 0° 58' E., on true line, bet. secs. 14 and 15 ($S\frac{1}{2}$). Over mountainous land, thru dense timber and scattering undergrowth. Desc. 92 ft. over N. slope.
6.40	Creek, with stream of water, 5 lks. wide, 1 in. deep, course W.; asc. 125 ft. over S. slope to
16.10	Leave mountainous and enter rolling land. Asc. 125 ft. over SW. slope to.
39.74	Intersect original $\frac{1}{4}$ sec. cor. of secs. 14 and 15, which is a mound of stone witnessed by the one record bearing tree. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., on bed rock, supported in a mound of stone, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

52

Chains

S15		S14
-----	--	-----

.1936

from which

the original bearing tree:

A black pine (dead) 8 ins. diam., brs. N. 32° E., 12 lks. dist., mkd. $\frac{1}{4}$ S BT.

and establish additional bearing trees:

A yellow pine, 24 ins. diam., brs. S. 60 $\frac{1}{2}$ ° E., 25 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

A yellow pine, 16 ins. diam., brs. S. 85 $\frac{1}{2}$ ° W., 10 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

Thence,

N. 0° 29' E., on true line, bet. secs. 14 and 15 (N $\frac{1}{2}$).

Over rolling land, thru dense timber and scattering undergrowth. Asc. 30 ft. over SW. slope.

9.00 Divide bet. Salt River and Colorado River, brs. N. 70° W., and S. 70° E. Leave rolling and enter mountainous land. Desc. 111 ft. over N. slope.

21.80 Draw, course NW., asc. 25 ft. over SW. slope.

28.30 Spur, slopes W.; desc. 71 ft. over N. slope.

33.60 Head of draw, course W. Asc. 12 ft. over SW. slope.

35.00 Desc. 40 ft. over W. slope to

39.76 Intersect original cor. of secs. 10, 11, 14 and 15, which is a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 10, 11, 14 and 15; with brass cap, mkd.

T6N		T29E
S10		S11
S15		S14

.1936

from which

A spruce, 10 ins. diam., brs. N. 19° E., 89 lks. dist., mkd. T6N R29E S11 BT.

A fir, 8 ins. diam., brs. S. 46 $\frac{1}{2}$ ° E., 107 lks. dist., mkd. T6N R29E S14 BT.

A spruce, 12 ins. diam., brs. S. 31° W., 84 lks. dist., mkd. T6N R29E S15 BT.

A yellow pine, 8 ins. diam., brs. N. 56° W., 289 lks. dist., mkd. T6N R29E S10 BT.

Land, mountainous and rolling.

Soil, rocky and gravelly, 3rd and 4th rates.

Timber, pine, fir, spruce and aspen.

Undergrowth, scrub timber.

RESURVEY; SUBDIVISION LINES, T. 6 N., R. 29 E.

53

Chains	From the cor. of secs. 11, 12, 13 and 14.
	N. 85° 32' W., on true line, bet. secs. 11 and 14.
	Over mountainous land, thru dense timber and scattering undergrowth.
	Asc. 730 ft. over steep NE. slope.
31.47	Ridge, brs: NW. and SE.; desc. 30 ft. over SW. slope to
37.09	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S 11}{S 14}$
	1936
	from which,
	A yellow pine, 8 ins. diam., brs. N. 80° E., 26 lks. dist., mkd. $\frac{1}{4}$ S11 BT.
	A yellow pine, 12 ins. diam., brs. S. 46° E., 22 lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	Desc. 191 ft., over SW. slope.
54.39	Draw, course NW., asc. 35 ft. over NE. slope.
67.29	Spur, slopes NW., desc. 91 ft. over W. slope to
74.19	The cor. of secs. 10, 11, 14, and 15.
	Land, mountainous.
	Soil, black loam, rocky, 3rd and 4th rates.
	Timber, yellow pine, fir, spruce and aspen.
	Undergrowth, scrub timber.
	N. 0° 29' W., on true line, bet. secs. 10 and 11.
	Over rolling land, thru timber and undergrowth. Desc. 15 ft. over NW. slope.
3.20	Creek, with stream of running water, 4 lks. wide, 6 ins. deep, course NE. Thence along E. slope, descending 20 ft. to
25.00	Desc. 28 ft. over NE. slope.
28.60	Trail, brs. NW. and SE.
30.70	Same creek, course NW., asc. 45 ft. over SW. slope to
40.03	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	S10 S11
	1936
	from which
	A fir, 36 ins. diam., brs. S. 79 $\frac{1}{2}$ ° E., 110 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

RESURVEY: SUBDIVISION LINES, T. 6 N.; R. 29 E.

54

Chains

A fir, 6 ins. diam., brs. S. 61½° W., 78 lks. dist.,
mkd. ¼ S10 BT.

Asc. slightly over SW. slope.

41.00 Spur, slopes W., desc. 116 ft. over NW. slope.

64.40 Bend in same creek, from SW. to NW., about 1 ch. W. of
this point., asc. 35 ft., over SW. slope.

69.60 Point of spur, slopes W., desc. 10 ft. over NW. slope.

71.20 Draw, course SW. Leave rolling and enter mountainous land.
Asc. 114 ft. over SW. slope to

80.07 Intersect the cor. of secs. 2, 3, 10 and 11, which is a
mound of stone. No accessories. Reconstruct this cor.
monument as follows: remove the mound of stone and in
the center of its position, set an iron post, 3 ft.
long, 2 ins. diam., 23 ins. in the ground to bed rock
and in a mound of stone to top, for cor. of secs. 2, 3,
10 and 11, with brass cap mkd.

T6N	R29E
S3	S2
S10	S11

1936

from which

A yellow pine, 24 ins. diam., brs. N. 54½° E., 100
lks. dist.; mkd. T6N R29E S11 BT.

A yellow pine, 24 ins., diam., brs: S. 74° E., 98 lks.
dist., mkd. T6N R29E S11 BT.

A yellow pine, 6 ins. diam., brs. S. 25° W., 53 lks.
dist., mkd. T6N R29E S10 BT.

A yellow pine, 30 ins. diam., brs. N. 37° W., 89 lks.
dist., mkd. T6N R29E S3 BT.

Land, rolling and mountainous.
Soil, gravelly and rocky, 3rd and 4th rates.
Timber, fir, spruce, yellow pine, aspen and oak.
Undergrowth, timber and bunch grass.
scrub

From the cor. of secs. 1, 2, 11 and 12.

N. 86° 31' W., on true line, bet. secs. 2 and 11.

Over mountainous land, thru dense timber and scattering
undergrowth. Asc. 46 ft. over NE. slope.

4.50 Spur, slopes N., desc. 26 ft. over NW. slope.

6.70 Draw, course N., asc. 739 ft. over steep broken NE. slope
to

36.86 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 12
ins. in the ground to bed rock, and in a mound of stone
to top, for ¼ sec. cor., with brass cap mkd.

¼	S 2
	S 11

1936

from which

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

Chains	
	<p>A fir, 8 ins. diam., brs. S. 49° E., 15 lks. dist., mkd. $\frac{1}{4}$ S11 BT.</p> <p>A fir, 12 ins. diam., brs. N. 57° E., 45 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p>Ascend 20 ft. over NE. slope.</p>
38.50	Spur, slopes SE. Leave mountainous and enter rolling land,; desc. 17 ft. over SW. slope.
45.00	Desc. 87 ft. over S. slope.
62.40	Desc. 118 ft. over SW. slope to
73.72	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, yellow pine, spruce, aspen and oak. Undergrowth, scrub timber.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on N. bdy. of the Tp., hereinbefore described.</p> <p>S. 6° 35' E., on true line, bet. secs. 2 and 3.</p> <p>Over mountainous land, thru dense timber and scattering undergrowth. Asc. 204 ft., over NW. slope.</p>
29.06	Spur, slopes W. Leave mountainous and enter rolling land, desc. 10 ft. over S. slope.
30.46	Head of swale, course W., asc. 55 ft. over NW. slope to
37.88	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 23 ins. in the ground to bed rock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S3 \quad \quad S2 \\ 1936 \end{array}$
	from which
	<p>A yellow pine, 30 ins. diam., brs. S. 58$\frac{1}{2}$° E., 28 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p>A yellow pine, 30 ins. diam., brs. S. 39$\frac{1}{2}$° W., 19 lks. dist., mkd. $\frac{1}{4}$ S3 BT.</p> <p>Asc. 35 ft. over NW. slope.</p>
43.74	Spur, slopes W.; desc. 29 ft. over SW. slope.
53.84	Draw, course SW. Asc. 32 ft. over NW. slope.
56.60	Asc. 50 ft. over W. slope.
68.45	Desc. 90 ft. over SW. slope to
75.86	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, yellow pine, aspen, fir, pinyon and oak. Undergrowth, scrub timber and bunch grass.</p>

RESURVEY: Subdivision Lines, T. 6 N., R. 29 E.


56

Chains	
	From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of the Tp., hereinbefore described.
	N. 0° 04' E., on true line bet, secs. 33 and 34 ($S\frac{1}{2}$).
	Over rolling land, thru scattering timber and undergrowth. Asc. 34 ft. over SW. slope.
12.55	Saddle in ridge bearing E. and W., desc. 35 ft. over N. slope to
18.45	Desc. 98 ft. over NW. slope to
37.25	Asc. 10 ft. over SW. slope to
39.99	Intersect the original $\frac{1}{4}$ sec. cor. of secs. 33 and 34, which is an unmarked sandstone, 14x10x5 ins., firmly set in a mound of stone and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and original cor. stone and in same place, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, to bed rock, with original cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.,
	<div style="text-align: center;"> $\frac{1}{4}$ S33 S34 1936 </div>
	<div style="text-align: right;">from which</div> the original bearing trees:
	A yellow pine, 16 ins. diam., brs. N. 53 $\frac{1}{2}$ ° E., 41 lks. dist. mks. overgrown. Remark $\frac{1}{4}$ S34 BT.
	A spruce, 12 ins. diam., brs. N. 34 $\frac{1}{2}$ ° W., 29 lks. dist., mkd. $\frac{1}{4}$ S BT.
	and establish additional bearing tree:
	A spruce, 12 ins. diam., brs. N. 65 $\frac{1}{2}$ ° W., 48 lks. dist., mkd. $\frac{1}{4}$ S33 BT.
	This $\frac{1}{4}$ sec. cor. is on a low spur sloping N. 40° W.
	Thence,
	N. 1° 13' W., on true line, bet. secs. 33 and 34 ($N\frac{1}{2}$).
	Over rolling land, thru dense timber and scattering undergrowth. Desc. 100 ft. over NE. slope.
15.20	Head of draw, course NE., asc. 20 ft. over SE. slope,
19.15	Fence cor. from which fences extend N. 4° E., and N. 85 $\frac{1}{2}$ ° E.
19.20	Spur, slopes N. 20° E., desc. 20 ft. over NW. slope.
32.40	Leave timber, bears E. and W. Desc. 85 ft. over N. slope.
38.15	Creek with stream of running water, 10 lks. wide, 10 ins. deep, course S. 60° W.; asc. 9 ft. over SE. slope to
40.18	Intersect original cor. of secs. 27, 28, 33 and 34, which is an unmarked sandstone, 24x12x4 ins. firmly set in a mound of stone. No accessories. Reconstruct this cor.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

Chains

monument as follows: remove the mound of stone and original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground with original cor. stone reset alongside, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.



1936

from which

A spruce, 30 ins. diam., brs. S. 27° W., 616 lks. dist., mkd. T6N R29E S33 BT.

No other bearing trees available.

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly and rocky, 2nd and 3rd rates.

Timber, yellow pine, spruce, aspen and fir.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 26, 27, 34 and 35.

N. 85° 15' W., on true line, bet. secs. 27 and 34 (E $\frac{1}{2}$).

Over gently rolling open grassy land. Ascend gradually over N. slope.

0.70 Fence (4 strand barbed wire) brs. N. 60° W. and S. 60° E.

1.00 Road, brs. NW. and SE.


6.60 Enter medium timber and scattering undergrowth, brs. NW. and SE. Ascend 102 ft. over NE. slope.

22.90 Ridge, brs. NW. and SE. Leave gently rolling and enter mountainous land. Desc. 30 ft. over S. slope.

31.40 N. end of reservoir, 15.00 chs. long, 10.00 chs. wide, brs. South about 12.00 chs. dist.

35.20 Descend 93 ft. over SW. slope to

40.05 Intersect original $\frac{1}{4}$ sec. cor. of secs. 27 and 34, which is a wood post, 2 ins. square, mkd. $\frac{1}{4}$ S., firmly set and surrounded by a mound of stone, under fence bearing N. and S. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone, and alongside the old wood post, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



1936

from which

A spruce, 14 ins. diam., brs. S. 61° W., 20 lks. dist. mkd. $\frac{1}{4}$ S34 BT.

A spruce, 30 ins. diam., brs. N. 12° W., 118 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

58

Chains	Cabin No. 1 of Kenwood Lodge, brs. S. 1° 46' W., 809 lks. dist.
	Cabin No. 2, brs. S. 8° 55' W., 714 lks. dist.
	Cabin No. 3, brs. S. 15° W., 684 lks. dist.
	Cabin No. 4, brs. S. 19½° W., 600 lks. dist.
	Thence, from ¼ sec. cor.
	S. 87° 36' W., on true line, bet. secs. 27 and 34 (W½).
	Over rolling land, thru scattering timber and undergrowth; desc. 77 ft. over W. slope.
5.00	Road brs. N. and S. At 2.00 chs. N., the road forks to NE. and NW.
6.90	Leave timber and enter marshy land, brs. N. and S.
40.56	Creek, with stream of water, 2 lks. wide, 12 ins. deep, course S. 10° W., from N. 80° E.
41.00	Leave marshy land, brs. N. and S. and enter gently rolling grassy land. Asc. gradually over SE. slope to sec. cor.
41.90	Fence, brs. N. 4° E. and S. 4° W.
42.50	The cor. of secs. 27, 28, 33 and 34.
	Land, rolling and mountainous.
	Soil, black loam, rocky, 1st and 4th rates.
	Timber, black pine, yellow pine and fir.
	Undergrowth, scrub timber.
	Fair grass.
	N. 1° 16' E., on true line, bet. secs. 27 and 28.
	Over rolling, open, grassy land, asc. 190 ft. over SE. slope.
1.00	Trail, brs. NE. and SW.
10.00	Enter scattering timber and undergrowth, brs. NE. and SW.
18.70	Spur, slopes N. 75° E., desc. 162 ft. over NE. slope.
33.55	Leave timber, brs. NW. and SE.
35.40	Old road, brs. NW. and SE.
35.50	Wash, 15 lks. wide, 1 ft. deep, course S. 55° E., from N. 10° W.; asc. 10 ft. over SW. slope to
39.90	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S28} \quad \quad \text{S27} \\ \hline 1936 \end{array}$
	from which
	A spruce, 16 ins. diam., brs. N. 71° E., 152 lks. dist., mkd. ¼ S27 BT.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

Chains	<p>A spruce, 30 ins. diam., brs. N. $35\frac{1}{2}^{\circ}$ W., 335 lks. dist., mkd. $\frac{1}{4}$ S28 BT.</p> <p>Asc. 22 ft. over SW. slope to wash, thru very scattering timber.</p> <p>45.00 Fence (4 strand barbed wire) brs. NW. and SE.</p> <p>51.00 Rocky wash, 15 lks. wide, 1 ft. deep, course SW.; asc. 57 ft., over S. slope to</p> <p>55.30 Rock rim, brs. NE. and SW. Ascend gradually over E. slope to</p> <p>79.80 Intersect original cor. of secs. 21, 22, 27 and 28, which is a sandstone, $14 \times 12 \times 8$ ins., firmly set in a mound of stone, mkd. with two grooves on S. face. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bed rock with original cor. stone reset alongside and in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T6N</td> <td>R29E</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> </table> <p>1936</p> </div> <p style="text-align: right;">from which.</p> <p>A yellow pine, 8 ins. diam., brs. N. $3\frac{1}{2}^{\circ}$ E., 430 lks. dist., mkd. T6N R29E S22 BT.</p> <p>A yellow pine, 14 ins. diam., brs. N. 52° W., 281 lks. dist., mkd. T6N R29E S21 BT.</p> <p>Land, rolling. Soil, rocky and gravelly, over dark loam, 2nd and 3rd rates. Timber, yellow pine, spruce, aspen and fir. Undergrowth, scrub timber. Fair grass.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27. N. $89^{\circ} 45'$ W., on true line, bet. secs. 22 and 27 ($E\frac{1}{2}$). Over gently rolling, open, grassy land. Desc. slightly over SW. slope.</p> <p>1.50 Draw, course SW., ascend 50 ft. over SE. slope.</p> <p>7.10 Leave open, grassy land and enter scattering timber and undergrowth, brs. NE. and W.</p> <p>16.50 Thence along S. slope, ascending gradually.</p> <p>21.00 Descend gradually over SW. slope.</p> <p>29.90 Road, brs. NW. and SE.</p> <p>30.50 Creek, with stream of running water, 5 lks. wide, 4 ins. deep, course SE. Ascend 50 ft. over NE. slope to $\frac{1}{4}$ sec. cor.</p> <p>32.60 Same creek, course N. 80° E. from NW.;</p>	T6N	R29E	S21	S22	S28	S27
T6N	R29E						
S21	S22						
S28	S27						

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

60

Chains

40.11 Intersect original $\frac{1}{4}$ sec. cor. of secs. 22 and 27, which is a mound of stone. Find no trace of the marked stone or the record bearing tree SE. Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., .27 ins. in the ground and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 22 \\ S 27 \end{array}$$

1936

from which

A fir, 24 ins. diam., brs. N. 76° E., 17 lks. dist.
mkd. $\frac{1}{4}$ S22 BT.

A spruce, 18 ins. diam., brs. S. 35° W., 35 lks. dist.
mkd. $\frac{1}{4}$ S27 BT.

Thence,

N. 89° 49' W., on true line, bet. secs. 22 and 27 ($W\frac{1}{2}$).

Over gently rolling land, thru medium timber and scattering undergrowth. Asc. 21 ft. over NE. slope.

3.00 Ridge, brs. NW. and SE. Descend gradually over S. slope.

11.70 Trail, brs. N. and S.

16.00 Enter aspen thicket, brs. N. and S.

18.00 Leave thicket and asc. 16 ft. over E. slope.

20.80 Spur, slopes S.; desc. 52 ft. over W. slope.

28.60 Leave timber and enter open, grassy land.

39.00 Wash, 5 lks. wide, 1 ft. deep, course SW.; asc. slightly over SE. slope to

40.19 The cor. of secs. 21, 22, 27 and 28.

Land, gently rolling.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, black pine, yellow pine, aspen and fir.

Undergrowth, scrub timber.

Fair grass.

N. 0° 09' E., on true line, bet. secs. 21 and 22 ($S\frac{1}{2}$).

Over gently rolling, open, grassy land.

Asc. 21 ft. over SE. slope.

5.00 Leave open, grassy land and enter dense timber and scattering undergrowth, brs. NW. and NE.

10.60 SE. end of long spur, from NW., desc. 17 ft. over NE. slope.


14.80 Open draw, course SE.; asc. 35 ft. over SW. slope.

16.60 Trail, brs. N. 30° W. and SE.

29.00 Desc. 11 ft. over NW. slope.

Chains

- 31.50 Same trail, brs. NE. and SW.
- 32.70 Same draw, with stream of running water 3 lks. wide, 3 ins. deep, course SW., asc. 20 ft. over SE. slope to
- 40.20 Intersect original $\frac{1}{4}$ sec. cor. of secs. 21 and 22, which is a sandstone, 10x9x6 ins. above ground, firmly set, mkd. $\frac{1}{4}$ on top and witnessed by the one record bearing tree NW. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

the original bearing tree:

A yellow pine, 12 ins. diam., brs. N. 77° W., 12 lks. dist. mks. overgrown. Remark $\frac{1}{4}$ S21 BT.

and establish additional bearing tree:

A yellow pine, 12 ins. diam., brs. S. 59° E., 39 lks. dist. mkd. $\frac{1}{4}$ S22 BT.

Thence,


N. 0° 42' E., on true line, bet. secs: 21 and 22 (N $\frac{1}{2}$)

Over gently rolling land, thru dense timber and scattering undergrowth.

Asc. 83 ft. over SE. slope.

- 25.20 Trail, brs. E. and W. on broad top of ridge, brs. NE. and SW. Asc. 30 ft. over W. and SW. slopes to

- 40.27 Intersect original cor. of secs. 15, 16, 21 and 22, which is an unmarked lava stone, 16x12x6 ins. firmly set in a mound of stone and witnessed by two of the three record bearing trees: Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, with the original cor. stone reset alongside and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.



1936

from which,

the original bearing trees:

A yellow pine, 26 ins. diam., brs. S. 80° E., 47 lks. dist., mks. overgrown. Remark T6N R29E S22 BT.

A yellow pine, 26 ins. diam., brs. S. 53° W., 38 lks. dist., mks. overgrown. Remark T6N R29E S21 BT.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

62

Chains	
	<p>and establish additional bearing trees:</p> <p>A yellow pine, 8 ins. diam., brs. N. $21\frac{3}{4}^{\circ}$ E., 94 lks. dist., mkd. T6N R29E S15 BT.</p> <p>A yellow pine, 24 ins. diam., brs. N. $66\frac{1}{2}^{\circ}$ W., 147 lks. dist., mkd. T6N R29E S16 BT.</p> <p>Land, gently rolling. Soil, dark loam, rocky, 1st and 3rd rates. Timber, yellow pine, aspen and sugar pine. Undergrowth, scrub timber. Fair grass.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. $89^{\circ} 56'$ W., on true line, bet. secs. 15 and 22 ($E\frac{1}{2}$).</p> <p>Over mountainous land, thru dense timber and scattering undergrowth, along top of spur, sloping W. Desc. 34 ft. to</p>
6.78	Point of spur; Leave top of spur and descend 105 ft. over steep W. slope.
12.80	Creek, with stream of running water, 3 lks. wide, 3 ins. deep, course S.; asc. 65 ft. over E. slope.
19.40	Ridge, brs. N. and S.; desc. 55 ft. over SW. slope.
26.40	Leave mountainous and enter rolling land. Desc. 25 ft. over S. slope to $\frac{1}{4}$ sec. cor.
35.10	Trail, brs. NE. and SW.
39.17	(Mid point) Set an iron post; 3 ft. long, 1 in. diam., 27 ins. in the ground, and in mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4} \frac{S 15}{S 22}$
	1936
	from which
	<p>A yellow pine, 16 ins. diam., brs. S. 39° W., 54 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>A yellow pine, 24 ins. diam., brs. N. $28\frac{1}{2}^{\circ}$ W., 31 lks. dist., mkd. $\frac{1}{4}$ S15 BT.</p> <p>Continue over rolling S. slope.</p>
59.00	Ascend 45 ft. over NE. slope.
64.17	Ridge, brs. NW. and SE.; desc. 69 ft. over SW. slope to
78.35	The cor. of secs. 15, 16, 21 and 22.
	<p>Land, mountainous and rolling. Soil, gravelly, rocky, 3rd and 4th rates. Timber, yellow pine, fir and oak. Undergrowth, scrub timber and bunch grass.</p>
	<p>N. $0^{\circ} 10'$ E., on true line, bet. secs. 15 and 16 ($S\frac{1}{2}$).</p> <p>Over rolling land, thru dense timber and scattering undergrowth.</p>

Chains

Asc. 50 ft. over SW. slope.

10.00 Spur, slopes N. 40° W.; desc. 24 ft. over N. slope.

15.50 Head of draw, course NW.; asc. 24 ft. over SW. slope.

28.50 Low spur, slopes N. 60° W.; desc. 36 ft. over NW. slope to

40.19 Intersect original $\frac{1}{4}$ sec. cor. of secs. 15 and 16, which is an unmarked sandstone, .18x7x7 ins. firmly set in a mound of stone and witnessed by the one record bearing tree NE. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S16 | S15
 1936

from which

the original bearing tree:

A yellow pine, (dead) 16 ins. diam., brs. S. 15 $\frac{1}{2}$ ° E., 21 lks. dist., mkd. $\frac{1}{4}$ S BT.

and establish additional bearing trees:

A yellow pine, 30 ins. diam., brs. N. 45 $\frac{1}{4}$ ° E., 78 lks. dist. mkd. $\frac{1}{4}$ S15 BT.

A yellow pine, 16 ins. diam., brs. N. 87 $\frac{1}{2}$ ° W., 95 lks. dist. mkd. $\frac{1}{4}$ S16 BT.

Thence,

N. 0° 04' W., on true line, bet. secs. 15 and 16 (N $\frac{1}{2}$).

Over rolling land, thru dense timber and scattering undergrowth.

Asc. 6 ft. over SW. slope.

5.00 Divide bet. Salt River and Colorado River, brs. N. 60° W., and S. 60° E., desc. 120 ft. over NE. slope.

22.90 Leave timber, brs. N. 55° E. and S. 55° W. and enter open grassy land.

27.85 Creek, with stream of running water, 9 lks. wide, 6 ins. deep, course NE.; asc. 21 ft. over SE. slope to sec. cor.

34.90 Enter dense timber and scattering undergrowth, brs. N. 55° E. and S. 55° W.

40.07 Intersect original cor. of secs. 9, 10, 15 and 16, which is a lava stone, .16x16x10 ins. mkd. with 3 notches on E. face, firmly set in a mound of stone, and witnessed by the one record bearing tree SE. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone reset along side, and in a mound of stone to top, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

.RESURVEY; .SUBDIVISION LINES, T. 6 N.; R. 29 E.

64

Chains

T6N	R29E
S9	S10
.316	S15

1936

from which

the original bearing tree:

A yellow pine, (dead) 36 ins. diam., brs. S. 30° E., 22 lks. dist., mkd. T6N R29E S15 BT.

and establish additional bearing trees:

A yellow pine, 8 ins. diam., brs. N. 31½° E., 17 lks. dist. mkd. T6N R29E S10 BT.

A spruce, 8 ins. diam., brs. S. 66½° E., 133 lks. dist. mkd. T6N R29E S15 BT.

A yellow pine, 8 ins. diam., brs. S. 77° W., 14 lks. dist., mkd. T6N R29E S16 BT.

A yellow pine, 14 ins. diam., brs. N. 71° W., 58 lks. dist., mkd. T6N R29E S9 BT.

Land, rolling.

Soil, dark loam, rocky, 1st and 3rd rates.

Timber, yellow pine, aspen, spruce, fir and sugar pine.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 10, 11, 14 and 15.

Thence,

N. 89° 15' W. on true line, bet. secs. 10 and 15.

Over mountainous land, thru dense timber and scattering undergrowth. Desc. 6 ft. over NW. slope.

1.20 Creek, with stream of running water, 5 lks. wide, 6 ins. deep, course NE.; asc. 114 ft. over E. slope.

15.70 Ridge, brs. N. and S.; desc. 160 ft. over W. slope to

39.74 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.

¼	S 10
	S 15

1936

from which

A spruce, 8 ins. diam., brs. N. 26½° E., 78 lks. dist. mkd. ¼ S10 BT.

A spruce, 14 ins. diam., brs. S. 65½° W., 25 lks. dist. mkd. ¼ S15 BT.

Thence over rolling land; desc. 29 ft. over W. slope.

41.30 Leave timber and undergrowth, brs. N. and S. and enter open grassy land.

44.40 Draw, course N., asc. 29 ft. over E. slope.

RESURVEY; SUBDIVISION LINES, T. 6 N., R. 29 E.

LOCAL 972

65

Chains	
46.40	Enter dense timber and scattering undergrowth, brs. N. and S.
51.10	Ridge, brs. NE. and SW., desc. 79 ft. over W. slope.
59.40	Leave timber and undergrowth, brs. N. and S. and enter open grassy land.
72.00	Draw, course NE. Enter dense timber and scattering undergrowth, brs. NE. and SW., asc. 28 ft. over SE. slope to
79.49	The cor. of secs. 9, 10, 15 and 16.
	Land, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, fir, spruce, yellow pine, aspen and oak. Undergrowth, scrub timber. Fair grass.
	N. 0° 11' E., on true line, bet. secs. 9 and 10.
	Over rolling land, thru dense timber and scattering undergrowth..
	Asc. 116 ft. over SE. slope.
18.91	Spur, slopes N. 50° E. Leave rolling and enter mountainous land; desc. 209 ft. over NE. slope.
33.65	Leave dense timber and scattering undergrowth, brs. E. and W. and enter open grassy land.
37.30	Colter Creek, with stream of running water, 2 lks. wide, 2 ins. deep, course N. 65° E., asc. 15 ft. over SW. slope to $\frac{1}{4}$ sec. cor.
38.70	Old line of fence posts, brs. E. and W.
38.80	Trail, brs. N. 65° E. and S. 65° W.
39.52	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bed rock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd..
	$ \begin{array}{c} \frac{1}{4} \\ \text{S } 9 \quad \quad \text{S } 10 \\ 1936 \end{array} $
	from which
	A yellow pine, 12 ins. diam., brs. N. 51 $\frac{1}{2}$ ° E., 219 lks. dist., mkd. $\frac{1}{4}$ S10 BT.
	A yellow pine, 12 ins. diam., brs. N. 73 $\frac{1}{2}$ ° W., 189 lks. dist., mkd. $\frac{1}{4}$ S9 BT.
	Asc. 377 ft. over SW. slope.
41.40	Leave open grassy land and enter dense timber and scattering undergrowth, brs. S. 75° W. and N. 75° E.
61.77	Spur, slopes S. 50° E. Leave mountainous and enter rolling land. Desc. 47 ft. over NE. slope.
68.32	Asc. 72 ft. over SE. slope.
75.68	Point of spur sloping E.; desc. 40 ft. over NE. slope to

.RESURVEY: SUBDIVISION LINES, T. 6 N.; R. 29 E.

66

Chains

79.04 Intersect original cor. of secs. 3, 4, 9 and 10, which is a lava stone, 16x8x6 ins. mkd. with 5 grooves on S. face, and 3 grooves on E. face, firmly set in a mound of stone and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset alongside and in a mound of stone to top, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

T6N	R29E
S4	S3
S9	S10

1936

from which

the original bearing trees:

A yellow pine, 20 ins. diam., brs. N. 79° E., 36 lks. dist., mks. overgrown. Remark T6N R29E S3 BT.

A yellow pine, 24 ins. diam., brs. N. 21° W., 39 lks. dist., mks. overgrown. Remark T6N R29E S4 BT.

and establish additional bearing trees:

A yellow pine, 10 ins. diam., brs. S. 14½° E., 129 lks. dist., mkd. T6N R29E S10 BT.

A fir, 10 ins. diam., brs. S. 14½° W., 69 lks. dist., mkd. T6N R29E S9 BT.

Land, rolling and mountainous.
Soil, dark loam, rocky, 1st and 4th rates.
Timber, pine, fir and spruce.
Undergrowth, scrub timber.
Fair grass.

From the cor. of secs. 2, 3, 10 and 11.

N. 89° 56' W., on true line, bet. secs. 3 and 10 (E½).

Over mountainous land, thru dense timber and scattering undergrowth.

Desc. 176 ft. over SW. slope.

7.30 Leave timber, brs. NW. and SE., and continue thru scattering undergrowth.

10.40 Draw, course NW., asc. 126 ft., over NE. slope.

12.70 Enter aspen thicket, brs. NW. and SE.

16.50 Leave aspen thicket, and enter medium timber.

21.00 Spur, slopes N., desc. 177 ft. over NW. slope.

34.30 Leave timber, brs. N. and S. and continue thru scattering undergrowth.

38.20 Wash, 9 lks. wide, 1 ft. deep, course NW., asc. 20 ft. over E. slope to ¼ sec. cor.

38.40 Enter dense timber, brs. N. and S.

Chains	
39.00	<p>Intersect original $\frac{1}{4}$ sec. cor. of secs. 3 and 10, which is a mound of stone, witnessed by the one record bearing tree SW. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 23 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S}{S}$ $\frac{3}{10}$</p> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p> <p>the original bearing tree:</p> <p>A yellow pine, 40 ins. diam., brs. S. $27\frac{1}{2}^{\circ}$ W., 26 lks. dist. mkd. $\frac{1}{4}$ S BT.</p> <p>and establish additional bearing trees:</p> <p>A yellow pine, 30 ins. diam., brs. N. $11\frac{1}{2}^{\circ}$ W., 132 lks. dist., mkd. $\frac{1}{4}$ S3 BT.</p> <p>A pinyon, 14 ins. diam., brs. S. 12° E., 60 lks. dist., mkd. $\frac{1}{4}$ S10 BT.</p> <p>S. end of reservoir, extending about 12.00 chs. N. to earth dam, brs. N. about 12.00 chs. dist.</p> <p>Thence, S. $89^{\circ} 59'$ W., on true line, bet. secs. 3 and 10 ($W\frac{1}{2}$).</p> <p>Over mountainous land, thru dense timber and scattering undergrowth. Asc. 107 ft. over E. slope.</p> <p>6.50 Spur, slopes N.; desc. 20 ft. over NW. slope.</p> <p>10.60 Line tree, a fir, 16 ins. diam., mkd. with 2 notches on each of E. and W. faces.</p> <p>10.80 Colter Creek, with stream of running water, 5 lks. wide, 6 ins. deep, course NE., asc. 144 ft. over NE. slope.</p> <p>16.30 Enter aspen thicket, brs. NE. and SW.</p> <p>19.80 Leave aspen thicket, brs. NE. and SW., continue thru dense timber.</p> <p>23.80 Line tree, a fir, 48 ins. diam., mkd. with 2 notches on each of E. and W. faces.</p> <p>30.60 Head of draw, course NE.; asc. 206 ft. over steep E. slope to</p> <p>39.60 The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, mountainous. Soil, gravelly and rocky, 3rd and 4th rates. Timber, fir, spruce, aspen, yellow pine and oak. Undergrowth, scrub timber and bunch grass.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on N. bdy. of the Tp. hereinbefore described</p> <p>S. $5^{\circ} 58'$ E., on true line, bet. secs. 3 and 4.</p> <p>Over mountainous land, thru dense timber and scattering undergrowth.</p>

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

68

Chains	
	Desc. 376 ft. over SE. slope.
13.10	Creek, with stream of water, 9 lks. wide, 6 ins. deep, course E.; asc. 601 ft. over N. and NW. slopes to
37.68	(Proportional dist) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S4 \quad \quad S3 \\ 1936 \end{array}$
	from which
	A sugar pine, 10 ins. diam., brs. N. $19\frac{1}{2}^{\circ}$ E., 70 lks. dist., mkd. $\frac{1}{4}$ S3 BT.
	A yellow pine, 16 ins. diam., brs. N. $35\frac{1}{2}^{\circ}$ W., 143 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	Asc. 20 ft. over NW. slope.
45.68	Long spur, slopes N. 20° E., desc. 161 ft. over SE. and E. slopes to sec. cor.
48.75	Fence (4 strand barbed wire) brs. N. 13° E., and S. 22° W.
75.70	The cor. of secs. 3, 4, 9 and 10.
	Land, mountainous. Soil, gravelly and rocky, 3rd and 4th rates. Timber, yellow pine, aspen, fir, spruce and oak. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of the Tp., hereinbefore described.
	N. $6^{\circ} 19'$ W., on true line, bet. secs. 32 and 33.
	Over rolling land, thru medium timber and undergrowth.
	Desc. 75 ft., over NW. slope.
2.80	Leave timber and undergrowth, brs. NE. and SW. and enter open grassy land.
4.20	Trail, brs. E. and W.
5.60	Wash, 12 lks. wide, 3 ft. deep, course W., asc. 20 ft. over SW. slope.
7.30	Spur, slopes SW.; desc. 30 ft. over NW. slope.
10.10	Trail, brs. NE. and SW.
10.30	Creek, with stream of running water, 15 lks. wide, 12 ins. deep, course SW. Asc. gradually over E. slope to
14.80	Same creek, course SE.; asc. gradually over SW. slope to
18.70	Same creek, course SW.; asc. 27 ft. over SE. slope.
19.50	Trail, brs. NE. and SW.
32.60	Asc. gradually over E. slope.
37.60	Desc. 23 ft. over NE. slope to

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

69

Chains

38.29

(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.

.S32		S33
------	--	-----

1936

from which

A pinyon, 12 ins. diam., brs. S. 27° E., 183 lks. dist. mkd. $\frac{1}{4}$ S33 BT.

A pinyon, 12 ins. diam., brs. S. 11 $\frac{1}{2}$ ° W., 86 lks. dist. mkd. $\frac{1}{4}$ S32 BT..

Continue over open grassy land. Desc. 18 ft. over NE. slope.

45.50

Leave open grassy land and enter dense timber and scattering undergrowth, brs. NE. and SW.

58.70

Draw, course SE.; asc. 163 ft. over SE. slope.

61.10

Fence (5 strand barbed wire), brs. N. 55° W. and S. 55° E.

72.50

Point of spur, slopes NE.; desc. 22 ft. over NE. slope to

76.57

Intersect original cor. of secs. 28, 29, 32 and 33, which is a sandstone, 16x16x16 ins. mkd. with 4 grooves on E. face, firmly set in a mound of stone, and witnessed by two of the three record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone reset alongside and in a mound of stone to top for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T6N	R29E
S29	S28
S32	S33

1936

from which

the original bearing trees:

A spruce, 10 ins. diam., brs. N. 49° E., 15 lks. dist., mks. overgrown. Remark T6N R29E S28 BT.

An aspen, 5 ins. diam., brs. S. 30° E., 5 lks. dist., mks. overgrown. Remark T6N R29E S33 BT.

and establish additional bearing trees:

A spruce, 7 ins. diam., brs. S. 68 $\frac{1}{2}$ ° E., 58 lks. dist., mkd. T6N R29E S33 BT.

A spruce, 14 ins. diam., brs. S. 53° W., 68 lks. dist., mkd. T6N R29E S32 BT.

A spruce, 10 ins. diam., brs. N. 46° W., 58 lks. dist., mkd. T6N R29E S29 BT.

Land, rolling.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, black and yellow pine, spruce and aspen.

Undergrowth, scrub timber.

Fair grass.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

70


Chains	
	From the cor. of secs. 27, 28, 33 and 34.
	S. 86° 10' W., on true line, bet. secs. 28 and 33.
	Over rolling open grassy land.
	Asc. 75 ft. over SE. slope.
1.00	Trail, brs. N. 50° E., and S. 60° W.
10.83	Spur, slopes S., desc. 35 ft. over SW. slope.
19.41	Draw, course S. Asc. 81 ft. over SE. slope.
25.35	Leave open grassy land, and enter dense timber and scattering undergrowth, brs. NE. and SW.
28.34	Leave rolling and enter mountainous land. Asc. 130 ft. over SE. slope to
37.67	Leave mountainous and enter rolling land. Asc. 30 ft. over SE. slope to
44.29	(Mid point) Set an iron post, 3 ft. long, 1/2 in. diam., 24 ins. in the ground to bed rock and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 28 \\ S 33 \end{array}$
	1936
	from which
	A yellow pine, 16 ins. diam., brs. S. 12° W., 61 lks. dist., mkd. 1/4 S33 BT.
	A yellow pine, 24 ins. diam., brs. N. 19° E., 19 lks. dist., mkd. 1/4 S28 BT.
	Continue over rolling land, asc. gradually over S. slope to
59.20	Desc. 65 ft. over SW. slope to
70.66	Leave rolling and enter mountainous land. Desc. 137 ft. over steep SW. slope.
80.90	Rocky wash, course S. 15° E., asc. 108 ft. over steep NE. slope to
85.00	Leave mountainous and enter rolling land. Asc. 16 ft. over NE. slope to
88.58	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling and mountainous.
	Soil, gravelly, dark loam, 1st and 4th rates.
	Timber, yellow pine, spruce and aspen.
	Undergrowth, scrub timber.
	N. 0° 05' E., on true line, bet. secs. 28 and 29 (S 1/2).
	Over rolling land, thru dense timber and scattering undergrowth.
	Desc. 45 ft. over NE. slope.
7.67	Spring branch with stream of running water, 3 ins. wide, 2 ins. deep, course E. Ascend 30 ft. over S. and SW. slopes.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

BOOK 175

Chains

- 17.25 Leave timber and undergrowth, brs. NW. and SE. and enter open grassy land.
- 20.77 Leave open grassy land and enter dense timber and scattering undergrowth, brs. E. and W.
- 23.80 Wash, course SW., asc. 57 ft. over SE. slope.
- 36.57 Spur, slopes SE., desc. 44 ft. over NE. slope.
- 37.35 Draw, course SE. Asc. 17 ft. over SW. slope to
- 39.97 Intersect original $\frac{1}{4}$ sec. cor. of secs. 28 and 29, which is a mound of stone and witnessed by the one record bearing tree. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bed rock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

the original bearing tree:

A black pine, 12 ins. diam., brs. N. $57\frac{1}{2}^\circ$ E., 33 lks. dist., mkd. $\frac{1}{4}$ S BT.

and establish additional bearing trees:

A black pine, 10 ins. diam., brs. S. 66° E., 59 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

A black pine, 10 ins. diam., brs. N. 54° W., 49 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

Thence,


N. $0^\circ 43'$ W. on true line, bet. secs. 28 and 29 ($N\frac{1}{2}$).

Over rolling land, thru dense timber and scattering undergrowth.

Asc. 77 ft. over SW. slope.

30.08 Ridge, brs. NW. and SE.; desc. 80 ft. over NE. slope to

40.08 Intersect original cor. of secs. 20, 21, 28 and 29, which is a mound of stone and witnessed by the one record bearing tree NW. Reconstruct this cor. monument as follows: remove the mound of stone; and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.



1936

from which

the original bearing tree:

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

72

Chains

An aspen, 20 ins. diam., brs. N. $70\frac{1}{2}^{\circ}$ W., 17 lks. dist., mkd. T6N R29E S20 BT.

and establish additional bearing trees:

A fir, 6 ins. diam., brs. N. $59\frac{1}{2}^{\circ}$ E., 21 lks. dist., mkd. T6N R29E S21 BT.

A fir, 8 ins. diam., brs. S. $10\frac{1}{2}^{\circ}$ E., 24 lks. dist., mkd. T6N R29E S28 BT.

A fir, 6 ins. diam., brs. W., 23 lks. dist., mkd. T6N R29E S29 BT.

A fir, 12 ins. diam., brs. N. 30° W., 66 lks. dist., mkd. T6N R29E S20 BT.

Land, rolling.

Soil, black loam and rocky, 1st and 4th rates.

Timber, black and yellow pine, aspen and spruce.

Undergrowth, scrub timber.

Fair grass.

From the cor. of secs. 21, 22, 27 and 28.

S. $86^{\circ} 15'$ W., on true line, bet. secs. 21 and 28.

Over gently rolling, open, grassy land. Asc. 15 ft. over SE. slope to

2.50 E. edge of nearly level top of spur, sloping S., thence across top of spur, desc. 21 ft. over W. slope to

20.00 W. edge of top of spur. Leave top of spur. Desc. 90 ft. over W. slope.

28.42 Fence (4 strand barbed wire) brs. N. 26° W. and S. 26° E.

28.60 Road, brs. N. 26° W. and S. 26° E.

32.35 Creek, with stream of running water 12 lks. wide, 6 ins. deep, course, S. 30° E., asc. 20 ft. over NE. slope to

45.53 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ $\frac{S 21}{S 28}$

1936

from which

A yellow pine, 30 ins. diam., brs. S. $85^{\circ} 25'$ W., 10.21 chs. dist., mkd. $\frac{1}{4}$ S28 BT. No other bearing tree available,

raise a mound of stone, 2 ft. base; $1\frac{1}{2}$ ft. high, N. of cor.

Continue over open, rolling, grassy land.

Asc. 32 ft. over NE. slope to

55.70 Leave rolling, and enter mountainous land, dense timber and scattering undergrowth. Asc. 162 ft. over E. slope.

68.30 Spur, slopes N. 10° E., from S. Leave mountainous and enter rolling land. Desc. 64 ft. over NW. slope.

84.00 Asc. 20 ft. over NE. slope to

RESURVEY: SUBDIVISION LINES, T. 6 N.. R. 29 E.

FROM

73

Chains	
91.06	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, gently rolling, rolling and mountainous. Soil, dark loam, rocky, 1st and 3rd rates. Timber, yellow pine, aspen, spruce and fir. Undergrowth, scrub timber. Fair grass.</p>
	<p>N. 0° 53' W., on true line, bet. secs. 20 and 21 (S$\frac{1}{2}$).</p> <p>Over rolling land, thru dense timber and scattering undergrowth.</p> <p>Desc. 86 ft. over NE. slope.</p>
7.00	<p>Leave timber and undergrowth, brs. E. and W., and enter open, grassy land.</p>
9.90	<p>Draw, course E., asc. 150 ft. over S. slope.</p>
11.80	<p>Leave open, grassy land and enter dense timber and scattering undergrowth, brs. E, and W.</p>
37.80	<p>Ridge, brs. NE. and SW. Leave rolling and enter mountainous land. Desc. 20 ft. over NW. slope to</p>
39.90	<p>Intersect original $\frac{1}{4}$ sec. cor. of secs. 20 and 21, which is a mound of stone, witnessed by the one record bearing tree SW. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	<p style="text-align: center;"> $\frac{1}{4}$ S20 S21 1936 from which </p>
	<p>the original bearing tree:</p>
	<p>A pinyon, 16 ins. diam., brs. S. 17$\frac{1}{2}$° W., 21 lks. dist., mkd. $\frac{1}{4}$ S BT.</p>
	<p>and establish additional bearing trees:</p>
	<p>A black pine, 10 ins. diam., brs. N. 82$\frac{1}{4}$° E., 36 lks. dist., mkd. $\frac{1}{4}$ S21 BT.</p>
	<p>A black pine, 16 ins. diam., brs. N. 71° W., 45 lks. dist., mkd. $\frac{1}{4}$ S20 BT.</p>
	<p>Thence,</p>
	<p>N. 0° 13' W., on true line, bet. secs. 20 and 21 (N$\frac{1}{2}$).</p>
	<p>Over mountainous land, thru dense timber and scattering undergrowth.</p>
	<p>Desc. 152 ft. over NW. slope.</p>
11.40	<p>Leave timber and undergrowth, brs. E. and W. and enter open, grassy land.</p>
13.80	<p>Road, brs. SE. and NW.</p>

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

74

Chains							
15.80	Swale, course NE. Leave mountainous and enter rolling land, asc. 75 ft. over SE. slope.						
25.80	Leave open grassy land and enter dense timber and scattering undergrowth, brs. E. and W.						
33.10	Enter aspen thicket, brs. NE. and SW.						
37.30	Leave aspen thicket, brs. NE. and SW. Continue thru dense timber and scattering undergrowth.						
40.00	Spur, slopes E.						
40.03	Intersect original cor. of secs. 16, 17, 20 and 21, which is a mound of stone, witnessed by one of the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., on exposed bedrock, supported in a mound of stone to top, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.						
	<table border="1" style="margin: auto;"> <tr> <td>T6N</td> <td>R29E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> </table>	T6N	R29E	S17	S16	S20	S21
T6N	R29E						
S17	S16						
S20	S21						
	1936						
	from which.						
	the original bearing tree:						
	A yellow pine, 30 ins. diam., brs. N. $17\frac{1}{2}^{\circ}$ E., 18 lks. dist. mkd. T6N R29E S16 BT.						
	and establish additional bearing trees:						
	A black pine, 12 ins. diam., brs. N. $59\frac{1}{2}^{\circ}$ E., 125 lks. dist. mkd. T6N R29E S16 BT.						
	A black pine, 16 ins. diam., brs. S. $63\frac{1}{2}^{\circ}$ E., 52 lks. dist., mkd. T6N R29E S21 BT.						
	A black pine, 8 ins. diam., brs. S. 53° W., 52 lks. dist., mkd. T6N R29E S20 BT.						
	A yellow pine, 36 ins. diam., brs. N. 64° W., 27 lks. dist., mkd. T6N R29E S17 BT.						
	Land, rolling and mountainous. Soil, gravelly and rocky, 3rd and 4th rates. Timber, black and yellow pine, fir and aspen. Undergrowth, scrub timber. Fair grass.						
	From the cor. of secs. 15, 16, 21 and 22. S. $86^{\circ} 01'$ W., on true line, bet. secs. 16 and 21. Over rolling land, thru dense timber and scattering undergrowth. Desc. 60 ft. over SW. slope.						
10.66	Head of open draw, course S. 10° W., asc. 16 ft. over SE. slope.						
17.36	Low ridge, brs. NE. and SW., desc. 110 ft. over NW. slope to						

RESURVEY.: SUBDIVISION LINES, T. 6 N., R. 29 E.


75

Chains	
34.38	Open draw, course SW. Desc. slightly over SW. slope to
36.38	Open draw, course S. Asc. 44 ft. over SE. slope to
46.25	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4} \frac{S 16}{S 21}$ 1936 from which A yellow pine, 16 ins. diam., brs. N. 28° E., 38 lks. dist. mkd. $\frac{1}{4}$ S16 BT. A yellow pine, 14 ins. diam., brs. S. 52 $\frac{1}{2}$ ° E., 58 lks. dist. mkd. $\frac{1}{4}$ S21 BT, Asc. 6 ft. over SE. slope.
51.30	E. edge of nearly level top of spur, brs. N. and S. Thence across nearly level top of spur sloping S.
55.70	W. edge of top of spur. Leave top of spur.. Desc. 105 ft. over SW. slope.
77.90	Open draw, course S. 40° E., asc. 16 ft. over NE. slope.
80.60	Fence (4 strand barbed wire). brs. N. 38° W. and S.. 38° E.
80.90	Old road, brs. N. 38° W. and S. 38° E. Leave rolling and enter mountainous land. Asc. 140 ft. over NE. slope.
91.00	Spur, slopes S. 60° E. from W. Thence along top of spur. Asc. 7 ft. to
92.50	The cor. of secs. 16, 17, 20 and 21. Land, rolling and mountainous. Soil, dark loam, rocky, 2nd and 3rd rates. Timber, yellow pine, aspen, spruce, sugar pine and fir. Undergrowth, scrub timber and bunch grass.
	N. 0° 15' W. on true line bet. secs. 16 and 17. Over mountainous land, thru dense timber and scattering undergrowth. Desc. 130 ft. over NE. slope.
10.20	Leave timber and undergrowth, brs. SE. and NW. and enter open grassy land.
11.70	Old road, brs. NW. and SE.
13.70	Draw, course NE., asc. 200 ft. over SE. slope.
15.70	Fence (4 strand barbed wire) brs. NE. and SW.
16.90	Fence cor. brs. E., 50 lks. dist., from which fences extend NW. and SW. Leave open grassy land, and enter dense timber and scattering undergrowth.
17.80	Same fence, brs. NW. and SE.
28.90	Asc. 120 ft. over SW. slope to

. RESURVEY.: SUBDIVISION LINES, T. 6 N., R. 29 E.

Chains

39.86 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A black pine, 24 ins. diam., brs. N. $71\frac{1}{2}^{\circ}$ E., 5 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

A black pine, 16 ins. diam., brs. N. 82° W., 81 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

Asc. 167 ft. over SW. slope.

48.76 Enter aspen thicket, brs. NE. and SW.


52.66 Leave aspen, brs. NE. and SW. and continue thru dense timber.

53.66 Divide bet. Salt River and Colorado River, bears E. and W. and from this point spur ridges extend NE. and SW. Desc. 90 ft. over NW. slope to

64.00 Leave mountainous and enter rolling land. Desc. 51 ft. over NW. slope to reservoir.

75.36 Leave timber, brs. NE. and SW. Continue thru scattering undergrowth.

77.80 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bed rock, and in a mound of stone to top, for witness cor. to cor. of secs. 8, 9, 16 and 17, with brass cap mkd.



1936

from which

A black pine, 16 ins. diam., brs. S. 68° E., 169 lks. dist., mkd. T6N R29E S16 WC BT. No other bearing trees available.

79.36 S. edge of reservoir, brs. NE. about 12.00 chs. dist., and SW. about 15.00 chs. dist. Thence across water surface about 1 ft. deep.

79.72 Intersect original cor. of secs. 8, 9, 16 and 17, which is a mound of stone, no accessories. As this cor. point falls in reservoir, establish witness cor. 1.92 chs. S. $0^{\circ} 15'$ E., of true point for cor. as hereinbefore described.

Land, mountainous and rolling.
Soil, gravelly, rocky, 3rd and 4th rates.
Timber, fir, black pine, aspen and yellow pine.
Undergrowth, scrub timber.
Fair grass.

From the cor. of secs. 9, 10, 15 and 16.

S. $85^{\circ} 38'$ W., on true line, bet. secs. 9 and 16.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

77

Chains	
	Over rolling land, thru dense timber and scattering undergrowth. Asc. 40 ft. over SE. slope.
4.96	Leave rolling and enter mountainous land. Ascend 134 ft. over SE. slope.
14.75	Leave mountainous and enter rolling land. Asc. 47 ft. over E. slope.
21.70	Top of hill, brs. N. and S., desc. 27 ft. over NW. slope to
25.18	Enter mountainous land. Desc. 121 ft. over NW. slope.
34.00	Head of draw, course N. 10° W. Enter rolling land. Asc. 40 ft. over NE. slope.
39.46	Top of hill, brs. S. 60° E. and N. 60° W., desc. 30 ft. over NW. slope to
46.57	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S 9}{S 16}$ 1936 from which A fir, 24 ins. diam., brs. N. 40 $\frac{1}{2}$ ° W., 49 lks. dist., mkd. $\frac{1}{4}$ S9 BT. A spruce, 8 ins. diam., brs. S. 40 $\frac{1}{2}$ ° E., 8 lks. dist., mkd. $\frac{1}{4}$ S16 BT. Desc. 4 ft. over NW. slope.
47.90	Draw, course N. 70° E.; asc. 70 ft. over SE. slope.
72.90	Top of hill, brs. N. and S.; desc. 80 ft. over NW. slope.
90.95	Leave timber and undergrowth, brs. NE. and SW. and enter open land.
92.50	Edge of reservoir, brs. NE. and SW. Thence across water surface of reservoir, water about 1 ft. deep.
93.14	The true point for cor. of secs. 8, 9, 16 and 17. Land, rolling and mountainous. Soil, dark loam, rocky, 1st and 3rd rates. Timber, yellow pine, aspen, spruce and fir. Undergrowth, scrub timber and bunch grass.
	From true point for cor. of secs. 8, 9, 16 and 17. North, on true line, bet. secs. 8 and 9 (S $\frac{1}{2}$). Over water surface of reservoir, about 1 ft. deep.
4.78	N. edge of reservoir, brs. NE. and SW. Earth dam, brs. E.; about 3.00 chs. dist. Leave reservoir and enter rolling land, dense timber and scattering undergrowth. Ascend 55 ft. over SW. slope.
10.48	Ridge, brs. NW. and SE., desc. 16 ft. over NE. slope.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

78


Chains

13.28 Draw, course E.; asc. 171 ft. over SW. slope.

29.88 Fence (4 strand barbed wire) brs. W. and NE.

35.00 Thence along W. slope.

39.98 Intersect original 1/4 sec. cor. of secs. 8 and 9, which is a mound of stone, witnessed by the one record bearing tree SW. Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bed rock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



from which

the original bearing tree:

A yellow pine, 36 ins. diam., brs. S. 86 1/2° W., 10 lks. dist., mkd. 1/4 S8 BT.

and establish additional bearing tree:

A spruce, 10 ins. diam., brs. N. 30° E., 49 lks. dist., mkd. 1/4 S9 BT.

Thence,

N. 5° 21' E., on true line, bet. secs. 8 and 9 (N 1/2).


Over rolling and mountainous land, thru dense timber and scattering undergrowth.

Desc. 209 ft. over NW. slope.

14.63 Draw, course NE.; asc. 160 ft. over SE. slope.

34.63 Ridge, brs. NE. and W.; desc. 68 ft. over N. slope to

40.03 Intersect original cor. of secs. 4, 5, 8 and 9, which is an unmarked lava stone 12x8x4 ins., firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground with the original cor. stone reset alongside and in a mound of stone to top, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.



1936

from which

A spruce, 12 ins. diam., brs. N. 11 1/2° E., 22 lks. dist., mkd. T6N R29E S4 BT.

A spruce, 8 ins. diam., brs. S. 28° E., 5 lks. dist., mkd. T6N R29E S9 BT.

A spruce, 10 ins. diam., brs. S. 27° W., 27 lks. dist., mkd. T6N R29E S8 BT.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

79

Chains	<p>A spruce, 10 ins. diam., brs. N. $74\frac{1}{2}^{\circ}$ W., 24 lks. dist., mkd. T6N R29E S5 BT.</p> <p>Land, rolling and mountainous. Soil, dark loam and rocky, 1st and 4th rates. Timber, aspen, spruce, yellow pine and fir. Undergrowth, scrub timber and bunch grass.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10. S. $85^{\circ} 56'$ W., on true line, bet. secs. 4 and 9. Over mountainous land; thru dense timber and scattering undergrowth.</p>
	<p>Asc. 133 ft., over NE. slope.</p>
8.85	<p>Fence (4 strand barbed wire) brs. NE. and SW.</p>
10.30	<p>Thence along N. slope, asc. slightly to</p>
13.80	<p>Desc. 23 ft. over N. slope.</p>
18.75	<p>Asc. 49 ft. over N. slope to</p>
31.15	<p>Ridge, brs. E. and W.; desc. 40 ft. over S. slope to</p>
44.82	<p>(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	<p style="text-align: center;">$\frac{1}{4} \frac{S 4}{S 9}$</p> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p>
	<p>A sugar pine, 12 ins. diam., brs. North, 47 lks. dist. mkd. $\frac{1}{4}$ S4 BT.</p>
	<p>A yellow pine, 12 ins. diam., brs. S. 47° E., 38 lks. dist., mkd. $\frac{1}{4}$ S9 BT.</p>
	<p>Desc. 95 ft. over S. slope of ridge.</p>
78.00	<p>Same ridge, brs. N. 80° E.; and S. 75° W., desc. 25 ft. over N. slope to</p>
89.64	<p>The cor. of secs. 4, 5, 8 and 9.</p>
	<p>Land, mountainous. Soil, rocky; over dark loam, 1st and 4th rates. Timber, yellow pine, fir, spruce, aspen and sugar pine. Undergrowth, scrub timber and bunch grass.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33, on N. bdy. of the Tp., hereinbefore described.</p>
	<p>S. $0^{\circ} 54'$ W., on true line, bet. secs. 4 and 5.</p>
	<p>Over gently rolling land thru dense timber and scattering undergrowth.</p>
	<p>Asc. 28 ft. over NW. slope.</p>
8.08	<p>Ridge, brs. N. 70° E. and S. 40° W., desc. 46 ft. over SE. slope to</p>

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

80

Chains	
23.90	Spur slopes SE.; desc. 80 ft. over SW. slope to
40.56	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S5 S4 1936 </div> <p style="text-align: right;">from which</p>
	A yellow pine, 16 ins. diam., brs. East, 94 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	A yellow pine, 16 ins. diam., brs. N. 28° W., 74 lks. dist., mkd. $\frac{1}{4}$ S5 BT.
	Desc. 60 ft. over SW. slope to
49.00	Enter mountainous land. Asc. 14 ft. over NW. slope.
52.90	Desc. 58 ft. over W. slope to
58.00	Point of spur, slopes SW. Desc. 150 ft. over S. slope.
64.90	Creek, with stream of running water $\frac{1}{2}$ lks. wide, 10 ins. deep, course S. 75° E.; asc. 290 ft. over N. slope to
81.18	The cor. of secs. 4, 5, 8 and 9.
	Land, gently rolling, rolling and mountainous. Soil, dark loam and rocky, 1st and 4th rates. Timber, aspen, fir, and pine. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 5, 6, 31 and 32, on S. bay. of the Tp., hereinbefore described.
	N. 6° 20' W., on true line, bet. secs. 31 and 32.
	Over mountainous land, thru dense timber and scattering undergrowth.
	Desc. 10 ft. over NE. slope.
5.00	Asc. 155 ft. over E. and SE. slopes to
35.00	Long spur, slopes S. 30° W. Asc. 18 ft. over W. slope to
38.60	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S31 S32 1936 </div> <p style="text-align: right;">from which</p>
	A yellow pine, 14 ins. diam., brs. N. 68 $\frac{1}{2}$ ° E., 28 lks. dist., mkd. $\frac{1}{4}$ S32 BT.
	A yellow pine, 14 ins. diam., brs. N. 67 $\frac{1}{2}$ ° W., 17 lks. dist., mkd. $\frac{1}{4}$ S31 BT.
	Thence over rolling land, asc. 130 ft. over SW. and S. slopes to

Chains

77.20

Intersect original cor. of secs. 29, 30, 31 and 32, which is a sandstone, 16x12x8 ins. mkd. with 5 grooves on E. face and 1 groove on S. face, firmly set in a mound of stone and witnessed by one of the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bed rock with the original cor. stone reset alongside, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T6N	R29E
S30	S29
S31	S32

1936

from which

the original bearing tree:

A yellow pine, (dead and fallen) 14 ins. diam., brs. S. 55° E., 37 lks. dist., mkd. T6N R29E S32 BT.

and establish additional bearing trees:

A yellow pine, 16 ins. diam., brs. N. 34° E., 52 lks. dist., mkd. T6N R29E S29 BT.

A yellow pine, 16 ins. diam., brs. S. 41½° E., 90 lks. dist., mkd. T6N R29E S32 BT.

A yellow pine, 16 ins. diam., brs. S. 76° W., 62 lks. dist., mkd. T6N R29E S31 BT.

A yellow pine, 14 ins. diam., brs. N. 24½° W., 23 lks. dist., mkd. T6N R29E S30 BT.

Land, mountainous and rolling.

Soil, dark loam, and rocky, 1st and 3rd rates.

Timber, yellow pine, aspen, fir and spruce.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 28, 29, 32 and 33.

N. 88° 36' W., on true line, bet. secs. 29 and 32 (E½).

Over rolling land, thru dense timber and scattering undergrowth. Asc. 36 ft. over NE. slope to

3.46

Leave rolling and enter mountainous land. Asc. 250 ft. over steep NE. slope to

13.40

Top of bluff, 30 ft. high, brs. N. and S. facing E. Asc. 126 ft. over E. slope to

25.20

Top of knoll; desc. 145 ft. over W. slope to

38.32

Foot of steep descent, brs. N. and S. Leave mountainous and enter rolling land. Desc. slightly over W. slope to

39.53

Intersect original ¼ sec. cor. of secs. 29 and 32, which is a black pine tree, 14 ins. diam., mks. overgrown, witnessed by the record bearing tree SW. This tree corner monument being alive and in perfect condition, conclude that its permanency is assured, therefore do not set a regulation brass-capped iron post at this cor., instead remark this tree, ¼ S29 on N. face, and

RESURVEY; SUBDIVISION LINES, T. 6 N.; R. 29 E.

82

Chains	
	<p>$\frac{1}{4}$ S32 on S. face, from which the original bearing tree:</p> <p>A black pine, 24 ins. diam., brs. S. 35° W., 31 lks. dist., mkd. $\frac{1}{4}$ S.BT.</p> <p>and establish additional bearing trees:</p> <p>A black pine, 12 ins. diam., brs. N. 20$\frac{1}{2}$° E., 26 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>A black pine, 36 ins. diam., brs. S. 9$\frac{1}{2}$° E., 74 lks. dist., mkd. $\frac{1}{4}$ S32 BT.</p> <p>Thence,</p> <p>N. 88° 40' W., on true line, bet. secs. 29 and 32. (W$\frac{1}{2}$).</p> <p>Over rolling land, thru dense timber and scattering undergrowth. Desc. 29 ft. over W. slope.</p>
5.20	Fence (4 strand barbed wire) brs. N. and S.
7.45	Asc. gradually over NW. and N. slopes to
20.00	Low ridge, brs. N. 86° W. and S. 86° E. Desc. gradually over S. slope to sec. cor.
21.80	Enter aspen thicket, brs. N. and SE.
25.00	Leave aspen thicket, brs. N. and SE. Continue thru dense timber.
39.98	The cor. of secs. 29, 30, 31 and 32.
	<p>Land, rolling and mountainous.</p> <p>Soil, rocky, over dark loam, 1st and 3rd rates.</p> <p>Timber, yellow pine, aspen, fir and spruce.</p> <p>Undergrowth, scrub timber.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on W. bdy. of the Tp. hereinbefore described.</p> <p>S. 89° 43' E., on true line, bet. secs. 30 and 31.</p> <p>Over rolling land, thru dense timber and scattering undergrowth, along S. slope of ridge. Asc. slightly to</p>
5.10	Desc. 34 ft.
18.00	Asc. 75 ft. to
36.87	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bed rock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 30}{S \ 31}$ <p>. 1936</p> <p style="text-align: right;">from which</p>
	<p>A yellow pine, 24 ins. diam., brs. N. 5° E., 21 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>A yellow pine, 16 ins. diam., brs. S. 5$\frac{1}{2}$° E., 46 lks. dist., mkd. $\frac{1}{4}$ S31 BT.</p> <p>Continue along S. slope of ridge.</p>

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

Chains

73.62	<p>Asc. 75 ft. to The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling. Soil, dark loam and rocky, 1st and 3rd rates. Timber, yellow pine and aspen. Undergrowth, scrub timber and bunch grass.</p>						
3.50	<p>N. 0° 31' E., on true line, bet. secs. 29 and 30.</p> <p>Over rolling land, thru dense timber and scattering undergrowth.</p> <p>Asc. 29 ft. over S. slope.</p> <p>Ridge, brs. E. and W. Enter mountainous land. Desc. 271 ft. over N. slope.</p>						
18.20	<p>Leave dense timber, brs. S. 75° E. and N. 75° W. and enter very scattering timber and undergrowth.</p>						
25.76	<p>Draw, course N. 75° W. Enter rolling land, asc. 68 ft. over SW. slope.</p>						
33.24	<p>Fence (4 strand barbed wire) brs. E. and W.</p>						
38.00	<p>Road, brs. E. and W., on top of spur, sloping W. Desc. slightly over N. slope to</p>						
39.79	<p>(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bed rock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td style="padding-right: 10px;">.S30</td> <td style="text-align: center; padding-right: 10px;"> </td> <td style="padding-left: 10px;">S29.</td> </tr> <tr> <td></td> <td style="text-align: center;">1936</td> <td></td> </tr> </table> <p style="text-align: right; margin-right: 50px;">and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> </div> <p>Desc. 20 ft. over N. slope.</p>	.S30		S29.		1936	
.S30		S29.					
	1936						
46.90.	<p>Ravine, course W.; asc. 70 ft. over SW, slope.</p>						
50.00	<p>Enter dense timber and scattering undergrowth, brs. E. and W.</p>						
64.00	<p>Long spur, slopes N. 60° W., desc. 115 ft., over N. and NW. slopes to sec. cor.</p>						
72.60	<p>Leave dense timber and scattering undergrowth, brs. E. and W. and enter open grassy land.</p>						
79.58	<p>Intersect original cor. of secs. 19, 20, 29 and 30, which is an unmarked sandstone, 18x14x10 ins., firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T6N R29E</td> </tr> <tr> <td style="padding-right: 10px;">S19</td> <td style="padding-left: 10px;">S20</td> </tr> <tr> <td style="border-top: 1px solid black; padding-top: 5px;">S30</td> <td style="border-top: 1px solid black; padding-top: 5px;">S29</td> </tr> </table> <p>1936.</p> </div>	T6N R29E		S19	S20	S30	S29
T6N R29E							
S19	S20						
S30	S29						

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

84

Chains	and raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, rolling and mountainous. Soil, black loam, rocky, 1st and 4th rates. Timber, fir, black pine, spruce and aspen. Undergrowth, scrub timber. Fair grass.
	From the cor. of secs. 20, 21, 28 and 29. N. $88^{\circ} 51'$ W., on true line, bet. secs. 20 and 29. Over gently rolling land, thru dense timber and scattering undergrowth. Ascend gradually over N. and NE. slopes.
29.58	Fence (4 strand barbed wire) brs. N. and S.
38.50	Low ridge, brs. N. and S. Leave dense and enter scattering timber.. Desc. 23 ft. over W. slope to
39.04	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, and in a small mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S 20}{S 29}$ 1936 from which A black pine, 12 ins. diam., brs. N. $42^{\circ} E.$, 88 lks. dist., mkd. $\frac{1}{4} S20 BT.$ A black pine, 30 ins. diam., brs. S. $29\frac{1}{2}^{\circ} W.$, 102 lks. dist., mkd. $\frac{1}{4} S29 BT.$ Desc. 57 ft. over W. slope.
41.70	Leave timber and undergrowth and enter open grassy land.
63.08	Swale, course NW. Asc. slightly over NE. slope.
68.10	Low spur, slopes NW., desc. 30 ft. over N. and NW. slopes to
78.08	The cor. of secs. 19, 20, 29 and 30. Land, gently rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, black and yellow pine, fir and aspen. Undergrowth, scrub timber. Fair grass..
	From the cor. of secs. 19, 24, 25 and 30, on W. bdy. of the Tp., hereinbefore described. S. $89^{\circ} 59'$ E., on true line, bet. secs. 19 and 30. Over mountainous land devoid of timber and undergrowth. Asc. 118 ft. over grassy W. and SW. slopes to
16.36	Ridge, brs. N. $75^{\circ} W.$ and S. $85^{\circ} E.$ Asc. 78 ft. over N. slope of ridge to
38.16	(Proportional dist.) Set an iron post, 3 ft. long, 1 in.

RESURVEY; SUBDIVISION LINES, T. 6 N., R. 29 E.

85

Chains	<p>diam., 16 ins. in the ground to bed rock, with a lava stone, 6x4x4 ins. mkd. with a cross (X) deposited at base of post, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 19}{S 30}$</p> <p style="text-align: center;">1936</p> <p>Asc. 6 ft. over NW. slope to</p> <p>41.56 Thence across top of ridge, brs. NE. and SW.</p> <p>46.44 Leave top of ridge, brs. NE. and SW.; desc. 73 ft. over SE. slope.</p> <p>51.81 Fence (4 strand barbed wire) brs. N. 43° E. and S. 43° W. At a point 3.00 chs. NE. this fence turns to N.</p> <p>57.01 Draw, course S. Leave mountainous and enter gently rolling land. Asc. 30 ft. over SW. slope to</p> <p>72.76 Creek with water in pools, course S. 65° W., asc. 19 ft. over open grassy NW. slope to</p> <p>76.46 The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, mountainous and gently rolling. Soil, rocky, over dark loam, 1st and 4th rates. Timber, none. Undergrowth, none. Fair grass.</p>
	<p>N. 0° 12' W., on true line, bet. secs. 19 and 20 ($S\frac{1}{2}$).</p> <p>Over gently rolling, open, grassy land. Desc. 13 ft. over NW. slope to</p> <p>1.90 Creek, with water in pools, course S. 75° W. Enter rolling land. Asc. 102 ft. over SW. slope.</p> <p>25.00 Flat-topped ridge, brs. N. 75° W. and S. 60° E., desc. 108 ft., over NE. slope to</p> <p>39.97 Intersect original $\frac{1}{4}$ sec. cor. of secs. 19 and 20, which is a sandstone, 30x24x6 ins. mkd. $\frac{1}{4}$ on W. face and firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$S19 \quad \frac{1}{4} \quad S20$</p> <p style="text-align: center;">1936</p> <p style="text-align: right;">and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Thence, N. 0° 27' E., on true line, bet. secs. 19 and 20. ($N\frac{1}{2}$).</p> <p>Over rolling land, thru scattering undergrowth.</p> <p>Desc. 11 ft. over NW. slope.</p>

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

86

Chains							
4.00	Creek, with stream of running water, 2 lks. wide, 2 ins. deep, course S. 75° W., about 15.00 chs. to Black River, asc. 120 ft. over S. slope to						
32.50	Thence across nearly level top of ridge brs. N. 85° W. and S. 85° E.						
38.90	Leave top of ridge, brs. E. and W. Thence over open, grassy land. Desc. 9 ft. over N. slope to						
40.10	Intersect original cor. of secs. 17, 18, 19 and 20, which is a sandstone, 24x16x3 ins. above ground, mkd. with 3 grooves on S. face, firmly set. No accessories. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.						
	<table border="1"> <tr> <td>T6N</td> <td>R29E</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> </table>	T6N	R29E	S18	S17	S19	S20
T6N	R29E						
S18	S17						
S19	S20						
	1936						
	from which						
	Center of highway bridge over Black River, brs. N. 80° 15' W.						
	Land, gently rolling and rolling. Soil, rocky, over dark loam, 1st and 4th rates. Timber, none. Undergrowth, scrub timber. Fair grass.						
	From the cor. of secs. 16, 17, 20 and 21. N. 88° 54' W., on true line, bet. secs. 17 and 20. Over gently rolling land, thru dense timber and scattering undergrowth. Ascend 30 ft. along top of spur, sloping E.						
7.20	Fence (4 strand barbed wire) brs. N. 50° E. and S. 50° W.						
18.00	Leave top of spur and descend gradually over N. slope of same near top.						
33.00	Leave timber and undergrowth, brs. N. and S. and enter open grassy land.						
38.55	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bed rock, deposit a stone, 10 x9x8 ins. mkd. with a cross (X) and a horse shoe, at base of post, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.						
	<table border="1"> <tr> <td>1/4</td> <td>S 17</td> </tr> <tr> <td></td> <td>S 20</td> </tr> </table>	1/4	S 17		S 20		
1/4	S 17						
	S 20						
	1936						
	Descend 20 ft. over NW. slope.						
44.30	Wash, 10 lks. wide, 2 ft. deep, course N., near head. Ascend gradually over N. slope.						

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.


87

Chains	
49.00	Road, brs. NW. and SE.
52.80	Ascend 40 ft. over NE. slope.
57.20	Enter dense timber and scattering undergrowth, brs. NW. and SE.
62.30	Low ridge, brs. SE. and W. Thence along N. slope of ridge near top. Descend 25 ft. to sec. cor.
67.80	Leave timber and undergrowth, brs. N. and S. and enter open grassy land.
77.10	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, black and yellow pine. Undergrowth, scrub timber. Fair grass.
	From the cor. of secs. 13, 18, 19 and 24, on W. bdy. of the Tp. hereinbefore described. N. 89° 08' E., on true line, bet. secs. 18 and 19. Over gently rolling, open, grassy land. Desc. 29 ft. over NE. slope.
5.75	Black River, with stream of running water, 12 lks. wide, 10 ins. deep, course S. 60° E., asc. 77 ft. over SW. slope.
34.95	Spur, slopes N. 80° W., from E.; thence along top of spur ascending slightly to
38.65	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4} \frac{S 18}{S 19}$ 1936 and raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor. Asc. 49 ft. along top of spur sloping W.
56.35	Fence (4-strand barbed wire) brs. N. 3° E. and S. 3° W., leave top of spur, slopes W. from SE. Asc. gradually over N. slope to
77.78	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling. Soil, lava and sandstone, over dark loam, 1st and 4th rates. Timber, none. Undergrowth, none. Grass fair.
	N. 0° 20' W., on true line, bet. secs. 17 and 18 ($S\frac{1}{2}$). Over rolling, open, grassy land. Desc. 32 ft. over N. slope.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

Chains

- 5.50 Dim road, brs. E. and W.
- 7.10 Shallow draw, course W.; asc. 111 ft. over S. and SE. slopes.
- 33.15 Enter dense timber and scattering undergrowth, brs. N. 30° E. and S. 30° W.
- 37.00 Low ridge, brs. NE. and SW. Desc. 12 ft. over NW. slope to
- 40.79 Intersect point of original location of the 1/4 sec. cor. of secs. 17 and 18, determined from record tie to the original bearing tree SW. Reconstruct the cor. monument at this point as follows: set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.



1936

from which

the original bearing tree:

A yellow pine, 30 ins. diam., brs. S. 45° W., 169 lks. dist., mks. overgrown. Remark 1/4 S18 BT.

and establish additional bearing tree:

A yellow pine, 10 ins. diam., brs. S. 57° E., 224 lks. dist., mkd. 1/4 S17 BT.

This 1/4 sec. cor. is in the head of a draw, course NW. This draw turns to SW. at a point about 10 chs. NW. from the 1/4 sec. cor.

Thence,

N. 1° 03' E. on true line, bet. secs. 17 and 18 (N 1/2).

Over rolling land, thru dense timber and scattering undergrowth.

Asc. 46 ft. over SW. slope.


12.00 Spur, slopes S. 75° W., desc. 22 ft. over NW. slope.

28.70 Draw, course S. 60° W.; asc. 21 ft. over S. slope.

36.45 Low ridge, brs. E. and W.; desc. 5 ft. over N. slope to sec. cor.

36.90 Fence cor. brs. E. 10 lks. dist. from which fences extend N. 30° E., S. 30° W. and S. 80° E.

39.63 Intersect original cor. of secs. 7, 8, 17 and 18, which is an unmarked lava stone, 24x16x8 ins. above ground, firmly set, and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: along side the original cor. stone, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.



1936

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

BOOK

89

Chains

the original bearing trees: from which

. An aspen, 10 ins. diam., brs. N. $51\frac{1}{2}^{\circ}$ E., 19 lks.
dist., mkd. T6N R29E S8 BT.

. An aspen, 16 ins. diam., brs. N. $4\frac{1}{2}^{\circ}$ W., 23 lks.
dist., mkd. T6N R29E S7 BT.

and establish additional bearing trees:

. A yellow pine, 12 ins. diam., brs. N. 49° E., 46 lks.
dist. mkd. T6N R29E S8 BT.

. A yellow pine, 20 ins. diam., brs. S. $54\frac{1}{2}^{\circ}$ E., 91 lks.
dist., mkd. T6N R29E S17 BT.

. A yellow pine, 20 ins. diam., brs. S. $37\frac{1}{2}^{\circ}$ W., 100 lks.
dist., mkd. T6N R29E S18 BT.

. A spruce, 12 ins. diam., brs. N. $35\frac{1}{2}^{\circ}$ W., 114 lks.
dist., mkd. T6N R29E S7 BT.

Land, rolling.

Soil, lava and sandstone over dark loam, 1st and 3rd rates.

Timber, yellow pine, aspen, spruce, and fir.

Undergrowth, scrub timber.

Fair grass.

From the true point for cor. of secs. 8, 9, 16 and 17.

N. $88^{\circ} 33'$ W., on true line, bet. secs. 8 and 17.

Over water surface of reservoir, about 1 ft. deep.

12.40 N. edge of reservoir, brs. NE. and SW. Leave reservoir
and enter rolling, open grassy land. Asc. 150 ft. over
SE. slope.

15.20 Fence (4 strand barbed wire) brs. N. 70° E., and S. 70° W.

19.10 Leave open grassy land and enter dense timber and scatter-
ing undergrowth, brs. N. and SE.

34.90 Ridge, brs. N. and S.; desc. 15 ft. over W. slope to

38.00 (Mid point). Set an iron post, 3 ft. long, 1 in. diam.,
16 ins. in the ground, to bed rock, and in a mound of
stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ $\frac{S 8}{S 17}$.

1936

from which

. A black pine, 20 ins. diam., brs. N. $31\frac{1}{2}^{\circ}$ E., 7 lks.
dist., mkd. $\frac{1}{4}$ S8 BT.

. A black pine, 8 ins. diam., brs. S. $37\frac{1}{2}^{\circ}$ W., 30 lks.
dist., mkd. $\frac{1}{4}$ S17 BT.

Fence, (4 strand barbed wire) brs. S. 40 lks. dist., ex-
tending E. and W.

Desc. 98 ft. over NW. slope to

50.50 Same fence, brs. N. 15° W. and S. 15° E. Thence along
N. slope; desc. 42 ft. to sec. cor.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

90

Chains	
56.00	Same fence, brs. E. and W.
64.20	Fence (4 strand barbed wire) brs. N. 25° E. and S. 25° W.
74.60	Fence (5 strand barbed wire) brs. NE. and SW.
76.00	The cor. of secs. 7, 8, 17 and 18...
	Land, rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, black and yellow pine and aspen. Undergrowth, scrub timber. Fair grass.
	From the cor. of secs. 7, 12, 13 and 18, on W. bdy. of the Tp., hereinbefore described. N. 88° 50' E., on true line, bet. secs. 7 and 18. Over gently rolling open, grassy land. Desc. slightly over E. slope.
2.42	Swampy draw, course S. 15° E., asc. 25 ft. over SW. slope.
3.12	Fence (6 strand barbed wire) brs. N. and S. Fence cor. brs. S. 20 lks. dist. From which fences extend E, N. and W. Leave open grassy land, and enter dense timber and scattering undergrowth, brs. N. and S.
19.22	Low ridge, brs. NW. and SE. Leave timber and undergrowth, brs. NW. and E.; desc. 40 ft. over NE. slope to
34.22	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S 7}{S 18}$ W C
	1936
	from which
	Exposed rock outcrop, 3x2x1 ft. brs. S. 34° E., 78 lks. dist., mkd. X B0.
	Exposed rock outcrop, 3x1x4 ft., brs. S. 25 $\frac{1}{4}$ ° W., 74 lks. dist., mkd. X B0.
34.52	Enter nearly level marshy lake bed, brs. NW. and S. 75° E.
39.22	(Proportional dist.) Point for reestablishment of the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, falls in marshy land, where it is impractical to monument the cor., therefore, at a point, 5.00 chs. S. 88° 50' W., from true cor. point, establish witness cor. as hereinbefore described. Continue over marshy lake bed.
40.72	Leave marshy land; brs. NW. and SE., thence over dry lake bed.
47.52	Draw, course S. 50° W., continue over lake bed.
58.72	Leave nearly level dry lake bed, brs. NE. and SW. Enter gently rolling land. Asc. 56 ft. over NW. and N. slopes to sec. cor.
61.72	Enter dense timber and scattering undergrowth, brs. S. and NE.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

91

Chains

- 78.72 The cor. of secs. 7, 8, 17 and 18.
Land, gently rolling and nearly level.
Soil, lava and sandstone, over dark loam, 1st and 3rd rates.
Timber, yellow pine, aspen, fir and spruce.
Undergrowth, scrub timber.
Fair grass.
-
- N. 0° 16' E., on true line, bet. secs. 7 and 8 (S $\frac{1}{2}$).
Over gently rolling land, thru dense timber and scattering undergrowth.
Desc. 30 ft. over N. slope.
- 11.00 Draw; course W., leave gently rolling and enter mountainous land, asc. 330 ft. over SW. slope to $\frac{1}{4}$ sec. cor.
- 16.05 Fence (6 strand barbed wire) brs. E. and W.. At a point about 5 chs. E. this fence turns to S. 20° W.
- 39.79 Intersect original $\frac{1}{4}$ sec. cor. of secs. 7 and 8, which is an unmarked sandstone, 16x14x6 ins. firmly set in a mound of stone and witnessed by the record bearing tree SE. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original cor. stone reset alongside, and in a mound of stone to top for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- S 7 | S 8
1936
- from which
- the original bearing tree:
- An aspen, 12 ins. diam., brs. S. 64 $\frac{1}{4}$ ° E., 21 lks. dist., mks. overgrown. Remark $\frac{1}{4}$ S8 BT. and
- establish additional bearing trees:
- A sugar pine, 14 ins. diam., brs. S. 15 $\frac{1}{2}$ ° E., 86 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
- A sugar pine, 6 ins. diam., brs. S. 80 $\frac{1}{2}$ ° W., 29 lks. dist., mkd. $\frac{1}{4}$ S7 BT.
- Thence,
- N. 0° 30' E., on true line, bet. secs. 7 and 8 (N $\frac{1}{2}$).
Over mountainous land, thru dense timber and scattering undergrowth.
Asc. 90 ft. over SW. slope.
- 15.40 Divide bet. Salt River and Colorado River, brs. E. and W.
Desc. 110 ft. over N. slope to
- 40.06 Intersect the original cor. of secs. 5, 6, 7 and 8, which is an unmarked sandstone, 14x11x9 ins., firmly set in a mound of stone, and witnessed by the two record bearing trees: Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor.

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

92

Chains

stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original corner stone reset alongside, and in mound of stone to top for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.

T6N	R29E
S6	S5
S7	S8

1936

from which

the original bearing trees:

An aspen, 10 ins. diam., brs. S. $33\frac{1}{2}^{\circ}$ E., 22 lks. dist., mks. overgrown. Remark T6N R29E S8 BT.

A fir, (dead and fallen) 12 ins. diam., brs. N. $45\frac{1}{2}^{\circ}$ W., 47 lks. dist., mkd. T6N R29E S6 BT.

and establish additional bearing trees:

A sugar pine, 14 ins. diam., brs. N. 65° E., 68 lks. dist., mkd. T6N R29E S5 BT.

A spruce, 14 ins. diam., brs. S. 60° E., 62 lks. dist., mkd. T6N R29E S8 BT.

A spruce, 12 ins. diam., brs. S. $46\frac{1}{2}^{\circ}$ W., 21 lks. dist., mkd. T6N R29E S7 BT.

A spruce, 14 ins. diam., brs. N. 59° W., 37 lks. dist., mkd. T6N R29E S6 BT.

Land, gently rolling and mountainous.
Soil, rocky, dark loam, 1st and 3rd rates.
Timber, yellow pine, aspen, fir and sugar pine.
Undergrowth, scrub timber.

From the cor. of secs. 4, 5, 8 and 9.

N: $88^{\circ} 21' W.$; on true line, bet. secs. 5 and 8.

Over mountainous land, thru dense timber and undergrowth.

Asc. 113 ft. over N. slope.

20.42 Desc. 172 ft. over NW. slope.

33.66 Fence (4 strand barbed wire) brs. N. and S. at E. edge of open draw, course N. Thence across draw.

36.06 Old road, brs. N. and S.

37.66 W. edge of draw, brs. N. and S. Leave open draw and enter dense timber and scattering undergrowth. Asc. 12 ft. over NE. slope to

39.58 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground and in mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.,

$\frac{1}{4}$	S 5	S 8
---------------	-----	-----

1936

from which

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

BOOK 416

93

Chains

A yellow pine, 20 ins. diam., brs. N. $32\frac{3}{4}^{\circ}$ E., 126 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

A sugar pine, 6 ins. diam., brs. S. $53\frac{1}{4}^{\circ}$ W., 37 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Asc. 23 ft. over NE. slope.

46.35 Spur, slopes N.; desc. 83 ft. over NW. slope.

55.84 Open draw, 3.00 chs. wide, course N. 15° E., asc. 203 ft. over NE. slope.

70.90 Spur, slopes NE., desc. 60 ft. over NW. slope.

78.80 Thence over N. slope.

79.17 The cor. of secs. 5, 6, 7 and 8.

Land, mountainous.

Soil, rocky, over dark loam, 1st and 4th rates.

Timber, aspen, fir, spruce and yellow pine.

Undergrowth, scrub timber.

Fair grass.

From the cor. of secs. 1, 6, 7 and 12, on W. bdy. of the Tp. hereinbefore described.

N. $89^{\circ} 04'$ E., on true line, bet. secs. 6 and 7.

Over rolling land, thru dense timber and scattering undergrowth.

Desc. 47 ft. over SE. slope.

2.90 Desc. 6 ft. over S. slope to

8.27 Divide bet. Salt River and Colorado River, brs. N. 70° W. and S. 60° E. Desc. 12 ft. over NE. slope.

11.58 Old road, brs. N. 15° W. and S. 15° E., and head of draw, course N. Asc. 17 ft. over NW. slope.

18.28 Low spur, slopes N. Desc. 15 ft. over NE. slope.

18.67 Leave timber, brs. N. 80° W. and S. 60° E. Continue thru scattering undergrowth.

24.75 Thence along N. slope. Ascend 16 ft. to

39.79 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a lava stone, $8 \times 6 \times 2$ ins. mkd. with a cross (X) deposited at base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4} \frac{S 6}{S 7}$

1936

from which

A yellow pine, 30 ins. diam., brs. N. 19° E., 390 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

No other bearing tree available.

Asc. 29 ft. over N. slope to

49.74 Draw, course NW. Leave rolling and enter mountainous

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

94

Chains	land, dense timber and scattering undergrowth. Ascend 86 ft. over NW. slope.
63.18	Spur, slopes N., desc. 27 ft. over NE. slope.
71.20	Desc. 40 ft. over N. slope to
80.18	The cor. of secs. 5, 6, 7 and 8. Land, rolling and mountainous. Soil, rocky, over dark loam, 1st and 4th rates. Timber, yellow pine, aspen, fir and spruce. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 5, 6, 31 and 32, on N. bdy. of the Tp., hereinbefore described. S. 0° 01' E. on true line bet. secs. 5 and 6 ($N\frac{1}{2}$). Over gently rolling land, thru scattering timber and undergrowth. Desc. 64 ft. over SE. slope to
14.90	Leave gently rolling and enter mountainous land. Desc. 123 ft. over SE. slope.
25.78	Creek, with stream of running water, 5 lks. wide, 4 ins. deep, course N. 70° E., asc. 100 ft. over N. slope.
32.25	Ridge, brs. E. and W. Leave scattering and enter dense timber; desc. 33 ft. over S. slope to
39.71	Intersect original $\frac{1}{4}$ sec. cor. of secs. 5 and 6, which is a lava stone, 14x8x4 ins. mkd. $\frac{1}{4}$ on top, firmly set in a mound of stone, and witnessed by the two record bear- ing trees. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bed rock with the orig- inal cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{ccc} & \frac{1}{4} & \\ & & \\ S6 & & S5 \\ & 1936 & \end{array}$
	from which
	the original bearing trees:
	A pine, 16 ins. diam., brs. S. 50° E., 72 lks. dist., mks. overgrown. Remark $\frac{1}{4}$ S5 BT.
	A pine, 16 ins. diam., brs. N. 10° W., 21 lks. dist., mks. overgrown. Remark $\frac{1}{4}$ S6 BT.
	and establish additional bearing trees:
	A pine, 16 ins. diam., brs. S. 21 $\frac{1}{2}$ ° E., 104 lks. dist., mkd. $\frac{1}{4}$ S5 BT.
	A pine, 12 ins. diam., brs. N. 20° W., 48 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
	Thence, S. 0° 18' W., on true line, bet. secs. 5 and 6 ($S\frac{1}{2}$).

RESURVEY: SUBDIVISION LINES, T. 6 N., R. 29 E.

95

Chains

Over mountainous land, thru dense timber and scattering undergrowth.

Desc. 174 ft. over S. slope.

10.63 Wash, 2.00 chs. wide, 2 ft. deep, course S. 80° E., asc. 122 ft. over N. slope.

18.20 Spur, slopes NE., desc. 25 ft. over SE. slope.

21.80 Draw, course NE., asc. 74 ft. over N. slope to

39.28 The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling and mountainous.

Soil, lava and sandstone, over dark loam, 1st and 3rd rates.

Timber, pine, aspen, fir, and spruce.

Undergrowth, scrub timber and bunch grass.

Final test of Buff and Buff solar transit No. 10125 by
Roger F. Wilson, U.S. Surveyor.

96

Oct. 15, 1936, at 8h 00m, a.m. app.t. on the meridian established by Polaris observation in N. center of sec. 34, T. 6 N., R. 29 E., set off $33^{\circ} 51\frac{1}{2}'$ N. on the latitude arc; $8^{\circ} 34\frac{1}{2}'$ S. on the declination arc; and determine a meridian with the solar, which agrees within 1' with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian, and obtain a reading of $8^{\circ} 39'$ S. on the declination arc, which agrees with the computed declination of the sun.

At 4h 00m, p.m. app.t., with the latitude arc unchanged, set off $8^{\circ} 42'$ W. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

Final test of Buff and Buff solar transit No. 9984 by
Benjamin J. Mollette, U. S. Transitman.

Oct. 15, 1936, at 8h 00m, a.m. app.t., on the meridian established by Polaris observation in N. center of sec. 34, T. 6 N., R. 29 E., set off $33^{\circ} 51\frac{1}{2}'$ N. on the latitude arc; $8^{\circ} 34\frac{1}{2}'$ S. on the declination arc; and determine a meridian with the solar, which agrees within 1' 30" with the true meridian.

At app. noon with the latitude arc unchanged; observe the sun on the meridian, and obtain a reading of $8^{\circ} 38\frac{1}{2}'$ S. on the declination arc, which agrees within $\frac{1}{2}'$ with the computed declination of the sun.

At 4h 00m, p.m. app.t., with the latitude arc unchanged; set off $16^{\circ} 07'$ S. on the declination arc; and determine a meridian with the solar, which agrees within 1' with the true meridian.

Final test of Buff and Buff solar transit No. 23829 by
Roger F. Wilson, U.S. Surveyor.

Nov. 6, 1936, at 8h 00m, a.m. app.t. on the meridian established by Polaris observation in N. center of sec. 34, T. 6 N., R. 29 E., set off $33^{\circ} 51\frac{1}{2}'$ N. on the latitude arc; $16^{\circ} 01'$ S. on the declination arc; and determine a meridian with the solar, which agrees within $\frac{1}{2}'$ with the true meridian.

At app. noon, with the latitude arc unchanged; observe the sun on the meridian, and obtain a reading of $16^{\circ} 05\frac{1}{2}'$ S. on the declination arc, which agrees with the computed declination of the sun.

At 4h 00m, p.m. app.t., with the latitude arc unchanged; set off $16^{\circ} 07'$ S. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

Final test of Young and Son's solar transit No. 8477 by
Carroll I. Parkman, U. S. Transitman.

(Same transit was used in resurveys in T. 7 N., R. 29 E. By Robt. H. Fischer, U.S. Transitman, Sept. 4 to Oct. 14, 1936.)

Chains

Nov. 6, 1936 at 8h 00m, A.m., app.t., on the meridian established by Polaris observation in North center of sec. 34, T. 6 N., R. 29 E.; set off $33^{\circ} 51\frac{1}{2}'$ N. on the latitude arc; $16^{\circ} 01'$ S. on the declination arc; and determine a meridian with the solar which agrees within $1' 30''$ with the true meridian.

At app. noon, with the latitude arc unchanged; observe the sun on the meridian, and obtain a reading of $16^{\circ} 05\frac{1}{2}'$ S. on the declination arc, which agrees with the computed declination of the sun.

At 4h 00m, p. m., with the latitude arc unchanged; set off $16^{\circ} 07'$ S. on the declination arc; and determine a meridian with the solar, which agrees within $1'$ with the true meridian.

As all of the solar observations made with the four transits tested as described above, during the usual hours of solar work, come within $1' 30''$ of the true meridian, it is evident that they have been in satisfactory adjustment throughout the periods that they were used on the resurveys in Ts. 6 and 7 N., R. 29 E.

GENERAL DESCRIPTION

The surface of this township is mainly mountainous and rolling, with scattered small areas of gently rolling and nearly level land in the valleys and elsewhere. There is some level land in secs. 1 and 36.

The divide between the drainage basins of the Salt River and Colorado River bearing northwesterly and southwesterly extends thru the Tp. from the E. bdy. of sec. 24 to the SW. corner of sec. 6. Slightly less than $\frac{2}{3}$ of the total area lies to the south of said divide, and the remainder lies to the north. Gobbler Peak or Mountain with a smaller attached peak on its SW. side known as Mary's Nipple, is located in section 12.

The elevations above sea level range from 7700 to 9300 ft. The larger part of the total area has a dense growth of heavy timber, and scattering undergrowth, though there are some scattered areas that are devoid of timber and undergrowth. The timber consists of several varieties, such as yellow pine, spruce, black pine, white pine, sugar pine, aspen, fir, juniper; the predominating kind being yellow pine. The undergrowth consists of scrub or second growth of the kinds of timber mentioned, and bunch grass. Where the land is clear of timber there is a fair growth of grass.

The soil of the mountainous and rolling areas is gravelly and rocky, 3rd and 4th rates, and elsewhere is a dark loam, 1st and 2nd rates.

The east fork of Black River drains the portion of the township south of the divide, and Colter Creek drains the portion to the north. Both of these water courses, and several of their tributary creeks carry a permanent flow of water in normal years. There are reservoirs for water storage in secs. 3, 18 and 34, and at the cor. of secs. 8, 9, 16 and 17.

There are about 8 settlers in the township, located in secs. 1, 12 and 13, with improvement consisting of houses, sheds, barns, corrals and fences, also in sec.

34 is a summer resort known as Kenwood Lodge, with a house and several cabins. Other improvements in the township consist of U.S. Forest Service telephone line in the southeastern part and range fences extending thru most of the sections.

There are no mining claims or any evidence of valuable mineral deposits in the township.

There is a graded highway extending easterly thru secs. 34, 35 & 36 to U.S. Highway No. 260 in the adjoining township to the east, which junction is about 2 miles NW. from the town of Alpine. This U.S. Highway extends northerly from Alpine to Springerville. There are no other improved roads in T. 6 N., R. 29 E., the few other roads being passable but rough, and trails lead from the secondary roads into the more inaccessible regions.

The principal value of the land in this township is for the timber, next in rank is the grazing value of a large part, and next the agricultural value by cultivation of a small part of the township. Some land is now, or has been, in cultivation in secs. 1, 12 and 13. Owing to the extremely high elevation, the dense timber, and flowing water in the creeks, this township has a high value as a recreational area during the summer season, especially considering its close proximity to U.S. Highway No. 260.

The nearest towns are Nutrioso, about 1 mile east from the NE. cor. of township, and Alpine, about 5 miles south-easterly from the SE. cor. Both of these towns are post offices; are not railroad stations, but being on the U.S. Highway have stage service.

The entire township is withⁱⁿ the Apache National Forest, which lies both in Arizona and New Mexico.

BOOK 310

4-680
(August, 1926)

FIELD ASSISTANTS.

Carroll I. Parkman

To

U.S. Transitman

NAMES.	CAPACITY.
H.R. Ruddell	Principal Assistant
Buel Samuel	Chainman
Harold E. Grimes	Axman
Fred Wright	Axman
Robert G. Burns	Axman
Earl Fulton	Axman
William W. Jahnke	Axman
John Crofford, Jr.	Flagman
G.B. Ruiz	Flagman
Dave Navarro	Cornerman

100

BOOK 4119

CERTIFICATE OF UNITED STATES SURVEYOR

I, Carroll I. Parkman, U.S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 31st day of January, 1936, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, resurveyed all those parts or portions of

the Subdivision Lines of

Township 6 North, Range 29 East of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said resurvey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the supplemental special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such resurvey.

Phoenix, Arizona
May 17, 1937

Carroll I. Parkman
U.S. Transitman

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

....., 19.....

The foregoing field notes of the survey of

executed by
under his special instructions dated
critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in
has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

106
102

BOOK 4119

CERTIFICATE OF UNITED STATES SURVEYOR

I, Roger F. Wilson, U. S. Surveyor, hereby certify upon honor that, in pursuance ^{supplemental} of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 31st day of January, 19 36, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, ~~resurveyed~~ all those parts or portions of


the South boundary, West Boundary, North Boundary and
the Subdivision Lines of

Township 6 North, Range 29 East of the Gila and Salt

River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of ~~said resurvey~~ have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-

tions, and the ^{supplemental} special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such ~~resurvey~~.

Phoenix, Arizona
April 29, 1937


U. S. Surveyor.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colo., October 2, 1937

The foregoing field notes of the ~~resurvey~~ of

South Boundary, West Boundary, North Boundary


and

Subdivision Lines

Township 6 North, Range 29 East

of the Gila and Salt River Base and Meridian, in the State of Arizona.

executed by Roger F. Wilson, U.S. Surveyor and Carroll I. Parkman, U.S. Transitman. under ^{supplemental} special instructions dated January 31, 1936 for Gp. 192, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the ~~resurveys~~ they describe, are hereby approved.


U. S. Supervisor of Surveys.

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~
~~has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~