

Original

4-679
(April 1933)

Book B.

BOOK 4212

FIELD NOTES

Of

The Resurvey of the East Bdy. of Township 10 South, Range 12 West,

and

The Survey of the East and South Boundaries and Subdivisional
Lines of Township 10 South, Range 11 West,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Horace M. Muscott, Public Land Surveyor,

Thornton Fitzhugh, Transitman, and
Carroll I. Parkman, Transitman,

General Land Office,

Under special instructions dated November 20, 1936, which provided
for the surveys included under Group No. 218, bearing the approval of the
Commissioner of the General Land Office under date of December 18, 1936
and assignment instructions dated February 23, 1937.

Survey commenced February 25, 1937

Survey completed March 6, 1937.

4212

4212

(1A)

BOOK 4212

INDEX DIAGRAM.

Township 10 South, Range 11 West

45	46	37	31	26	20	13
6	5	4	3	2	1	
2	45	44	36	31	25	19
3	45					12
	7	8	9	10	11	12
	43	42	35	30	24	18
3	43					12
	18	17	16	15	14	13
	41	41	34	29	23	17
2	42					11
	19	20	21	22	23	24
	40	39	33	28	22	16
5						10
	30	29	28	27	26	25
	38	38	32	27	21	15
6						10
	31	32	32	27	24	21
	37	32	32	27	24	21
	6	7	7	8	9	9

Resurvey of the East boundary of T.10 S., R.12 W.

4212

Chains

The survey was executed with a Buff & Buff solar transit No. 16723 and Young & Sons solar transits Nos. 8385 and 8491. The instruments are equipped with full vertical circles and the Smith solar attachments and were approved by the District Cadastral Engineer at Glendale, California, on February 23, 1937, conditional upon satisfactory field tests. We examine all the instrumental adjustments before making the field tests hereinafter described.

The direction of the lines were determined by the solar transit method and by deflection angles from the meridian determined by the solar transit method. The measurements were made with Lallie steel tapes, 5 chains in length, graduated every link for the first 100 lks., and thereafter at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard and found to be correct. The measurements were made on the slope and the vertical angle at each interval was ascertained by clinometers in good adjustment. The horizontal equivalents are entered in the field note record.

The geographical position of the SE. cor. of the Township, as furnished with the special instructions, is as follows: latitude $32^{\circ} 30' 35''$ N., and longitude $113^{\circ} 20' 52''$ W.

February 24, 1937, with Buff & Buff solar transit No. 16723, every 30 mins. from 8:00 a. m. to 10:30 a. m., and from 1:30 p. m. to 4:00 p. m., the proper settings are made on the latitude and declination arcs; the resulting orientation of the instrument, when compared with the meridian established by Roger F. Wilson, on November 24, 1936, in camp at Sentinel, Arizona, and recorded in the field notes of T.9 S., R.11 W., Group 200, Arizona, has a maximum error of less than $1' 30''$.

February 24, 1937, with Young & Sons solar transit No. 8385, every 30 mins. from 8:00 a. m. to 10:30 a. m., and from 1:30 p. m. to 4:00 p. m., the proper settings are made on the latitude and declination arcs; the resulting orientation of the instrument, when compared with the meridian established by Roger F. Wilson, on November 24, 1936, in camp at Sentinel Arizona, and recorded in the field notes of T.9 S., R.11 W., Group 200, Arizona, has a maximum error of less than $1' 30''$.

February 24, 1938, with Young & Sons solar transit No. 8491, every 30 mins. from 8:00 a. m. to 10:30 a. m., and from 1:30 p. m. to 4:00 p. m., the proper settings are made on the latitude and declination arcs; the resulting orientation of the instrument, when compared with the meridian established by Roger F. Wilson, on November 24, 1936, in camp at Sentinel, Arizona, and recorded in the field notes of T.9 S., R.11 W., Group 200, Arizona, has a maximum error of less than $1' 30''$.

From the $\frac{1}{4}$ sec. cor. on the East bdy. of sec. 1, T.10 S., R. 12 W.,

South, on a random line, along the East bdy. of the Township.


40.00 Find no evidence of the position of the cor. of secs. 1, 6, 7 and 12. Set temp. cor.

BOOK 4212


Resurvey of the East boundary of T.10 S., R.12 W.

Chains	
80.00	Find no evidence of the position of the $\frac{1}{4}$ sec. cor. Set temp. $\frac{1}{4}$ sec. cor.
120.00	Find no evidence of the position of the cor. of secs. 7,12,13 and 18. Set temp. cor.
160.00	Find no evidence of the position of the $\frac{1}{4}$ sec. cor. Set temp. $\frac{1}{4}$ sec. cor.
200.00	Find no evidence of the position of the cor. of sec. 13,18,19 and 24. Set temp. cor.
240.00	Find no evidence of the position of the $\frac{1}{4}$ sec. cor. Set temp. $\frac{1}{4}$ sec. cor.
280.89	A point 51 lks. E. of the cor. of secs. 19,24,25 and 30.
320.89	Find no evidence of the position of the $\frac{1}{4}$ sec. cor. Set temp. $\frac{1}{4}$ sec. cor.
361.13	A point 70 lks. E. of the cor. of secs. 25,30,31 and 36.
401.25	A point 91 lks. E. of the $\frac{1}{4}$ sec. cor.
441.36	A point 93 lks. E. of the cor. of T.10 S., Rs.11 and 12 W.

I return to the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the E. bdy. of T.10 S., R.12 W., which is an iron post, 1 in. diam., 8 ins. above ground, firmly set with an old redwood stake, 2x3 ins. alongside, and pits visible N. and S., 3 ft. dist., with brass cap mkd.



As this cor. now refers to sec. 1 only, I make alterations and additions on the brass cap, to read as follows:



Thence,


S.0°06'W., on a true line, along the E. bdy. of sec. 1.

Over nearly level land, thru very scattered timber and undergrowth.

40.12 Proportional distance. From this point for. cor., the original redwood stake, 4 ins. square, 4 ft. long, properly mkd. for the cor. of secs. 1,6,7 and 12, and lying loosely on the ground, bears N.38°E., 11 lks. dist.

As this cor. will no longer serve for secs. 6 and 7, R.11 W., at point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken crockery deposited at the base and with the original redwood stake alongside, for cor. of secs. 1 and 12 only of R.12 W., with brass cap mkd.



Resurvey of the East boundary of T.10 S., R.12 W.

Chains

A bench mark of the U.S. Geological Survey, bears S.43°E., 82 lks. dist.; a redwood post, 3x4 ins., 8 ins. above ground, firmly set, mkd. 488 on N. face.

Land, nearly level desert.
Soil, sandy loam; 2nd rate.
Timber, very scattered mesquite; undergrowth, greasewood, and sage.

S.0°06'W., along the E. bdy. of sec. 12.

Over nearly level desert land, thru very scattered timber and undergrowth.

40.12 Proportional distance. From this point for cor. a redwood stake, 1x1½ ins., 1½ ft. long, lying loosely on the ground, bears N.45°E., 4 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, and the redwood stake alongside, for ¼ sec. cor. of sec. 12 only, R.12 W., with brass cap mkd.

¼ S 12
1937

No suitable accessory.

80.25 Proportional distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, and a malpais rock, 10x8x6 ins. alongside, for cor. of secs. 12 and 13 only, R.12 W., with brass cap mkd.

T 10 S | T 10 S
S 12 | S 7
S 13
R 12 W | R 11 W

1937

A bench mark of the U.S. Geological Survey, bears S.7°E., 45 lks. dist.; a redwood post, 3x3 ins., 12 ins. above ground, firmly set, mkd. B M on W. face and 498 on E. face.

Land, nearly level desert.
Soil, sandy loam; 2nd rate.
Timber, very scattered mesquite; undergrowth, greasewood and sage.

S.0°06'W., along the E. bdy. of sec. 13.

Over nearly level desert land, thru very scattered timber and undergrowth.

40.13 Proportional distance. From this point for ¼ sec. cor., the original redwood post, 3 ins. square, 3 ft. long, properly mkd. for ¼ sec. cor., and lying loosely on the ground, bears East, 4 lks. dist.

As this cor. now refers to sec. 13 only, R.12 W., at point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in

Resurvey of the East boundary of T.10 S., R.12 W.

Chains

the ground, with a quantity of broken glass deposited at the base and with the original redwood post alongside, for $\frac{1}{4}$ sec. cor. of sec. 13 only, R.12 W., with brass cap mkd.

$\frac{1}{4}$ S 13
 1937

No suitable accessory.

80.26 Proportional distance. From this point for cor., the original redwood stake, 4 ins. square, 4 ft. long, properly mkd. for the cor. of secs. 13, 18, 19 and 24, lying loosely on the ground, bears N.10°E., 38 lks. dist.

As this cor. will no longer serve for secs. 18 and 19, R.11 W., at point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base and with the original redwood stake alongside, for cor. of secs. 13 and 24 only of R.12 W., with brass cap mkd.

T 10 S | T 10 S
 S 13 | S 18
 S 24 |
 R 12 W | R 11 W

1937

A bench mark of the U.S. Geological Survey bears S.44 $\frac{3}{4}$ °E., 64 lks. dist., a circular concrete post, 6x8 ins., 8 ins. above ground, firmly set, mkd. 9 M 1927 Elevation Above Sea Level.

Land, nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, very scattered mesquite; undergrowth, greasewood and sage.

S.0°06'W., along the E. bdy. of secs. 24.

Over nearly level desert land, thru very scattered timber and undergrowth.

40.13 Proportional distance. From this point for cor. the original redwood stake, 3x3 ins., 3 ft. long, lying loosely on the ground, bears N.28°E., 48 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, and with original redwood stake alongside, for $\frac{1}{4}$ sec. cor. of sec. 24 only, R.12 W., with brass cap mkd.

$\frac{1}{4}$ S 24
 1937

No suitable accessory.

80.26 The cor. of secs. 19, 24, 25 and 30, which is a redwood post 4x4 ins., 3 ft. above ground, firmly set, mkd. and witnessed as described in the official record.

At point for cor.,

Resurvey of the East boundary of T.10 S., R.12 W.

4212

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, and with the redwood post alongside, for cor. of secs. 19,24,25 and 30, with brass cap mkd.

T 10 S

R 12 W	R 11 W
S 24	S 19
S 25	S 30

1937

A bench mark of the U.S. Geological Survey, bears S.44³°E. 66 lks. dist., a redwood post, 3x3 ins., 10 ins. above ground, firmly set, mkd. 513 on W. face.

Land, nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, very scattered mesquite; undergrowth, greasewood, and sage.

S.0°08'W., on a true line, bet. secs. 25 and 30.

Over nearly level desert land, thru very scattered timber and undergrowth.

40.12 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 25	S 30
------	------

1937

No suitable accessory.

80.24 The cor. of secs. 25,30,31 and 36, which is a redwood post, 4 ins. square, 3 ft. above ground, firmly set, mkd. and witnessed as described in the official record.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, and with the redwood stake alongside, for cor. of secs. 25,30,31 and 36, with brass cap mkd.

T 10 S

R 12 W	R 11 W
S 25	S 30
S 36	S 31

1937

A bench mark of the U.S. Geological Survey, bears S.45°E., 69 lks dist., a redwood post, 4x4 ins., 8 ins. above ground, firmly set, mkd. 531 on W. face.

Land, nearly level desert.

Soil, sandy loam; 2nd rate.

Timber, very scattered mesquite; undergrowth, greasewood and sage.

Resurvey of the East boundary of T.10 S., R.12 W.

Chains

S.0°18'W., on a true line, bet. secs. 31 and 36.

Over nearly level desert land, thru very scattered timber and undergrowth.

40.12 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, which is a mesquite post, 3x3 ins., 2 ft. above ground, firmly set, mkd. witnessed as described in the official record.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, and with the old mesquite post alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 36 \text{ | S } 31 \\ | \\ 1937 \end{array}$$

No suitable accessory.

Thence,

S.0°02'W., on a true line bet. secs. 31 and 36.

40.11 The cor. of T.10 S., Rs. 11 and 12 W., which is a redwood post, 4x4 ins., 3 ft. above ground, firmly set, mkd. and witnessed as described in the official record.

At point for cor.,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, and with old redwood post alongside, for cor. of T.10 S., Rs. 11 and 12 S., with brass cap mkd.

$$\begin{array}{c} \text{T } 10 \text{ S} \\ | \\ \text{R } 12 \text{ W | R } 11 \text{ W} \\ | \\ \text{S } 36 \text{ | S } 31 \end{array}$$

1937

A bench mark of the U.S. Geological Survey, bears S.42° 10'W., 65 lks. dist., a circular concrete post, 6x10 ins. 8 ins. above ground, firmly set, mkd. 8 M 1927 Elevation Above Sea Level Feet.

Land, Nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, very scattered mesquite; undergrowth, greasewood and sage.

Survey of the South boundary of T.10 S., R.11 W.

From the cor. of T.10 S., Rs. 11 and 12 W., hereinbefore described;

East, along the South bdy. of sec. 31, on a transit line describing the tangent, which bears S.89°35'41"W.

37.70 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., of sec. 31 only, with brass cap. mkd.

Survey of the South boundary of T.10 S., R.11 W. 4212

Chains

1/4 S 31

1937

No suitable accessory.

77.70 N. 1 lk. from the tangent,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 31 and 32 only, with brass cap mkd.

T 10 S R 11 W
S 31 | S 32

1937

No suitable accessory.

Land, nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, very scattered mesquite; undergrowth, greasewood and sage.

East, along the S. bdy. of sec. 32, on a transit line, describing the tangent, which bears S.89°59.4'E.

Over nearly level desert land, thru very scattered timber and undergrowth.

40.00 N. 1 lk. from the tangent,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken crockery deposited at the base, for 1/4 sec. cor. for sec. 32 only, with brass cap mkd.

1/4 S 32

1937

No suitable accessory.

80.00 N. 3 lks. from the tangent,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 32 and 33 only, with brass cap mkd.

T 10 S R 11 W
S 32 | S 33

1937

No suitable accessory.

Land, nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, very scattered mesquite; undergrowth, greasewood and sage.

East, along the S. bdy. of sec. 33, on a transit line describing the tangent, which bears S.89°58.9'E.

Over nearly level land, thru very scattered timber and undergrowth.

Survey of the South boundary of T.10 S., R.11 W.

Chains 40.00	<p>N. 4 lks. from the tangent,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., of sec. 33 only, with brass cap mkd.</p> <p style="text-align: center;"><u>$\frac{1}{4}$S 33</u></p> <p style="text-align: center;">1937</p> <p>No suitable accessory.</p>
80.00	<p>N., 6 lks. from the tangent,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass and crockery deposited at the base, for cor. of secs. 33 and 34 only, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 11 W <u>S 33 S 34</u></p> <p style="text-align: center;">1937</p> <p>No suitable accessory.</p> <p>Land, nearly level, NW. drainage. Soil, sandy loam; 2nd rate. Timber, scattered mesquite and ironwood; undergrowth, greasewood and sage.</p> <hr/> <p>East, along the S. bdy. of sec. 34, on a transit line, describing the tangent, which bears S.89°58.3'E.</p> <p>Over nearly level desert land, thru scattered timber and undergrowth.</p>
40.00	<p>N., 8 lks. from the tangent,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., of sec. 34 only, with brass cap mkd.</p> <p style="text-align: center;"><u>$\frac{1}{4}$S 34</u></p> <p style="text-align: center;">1937</p> <p>No suitable accessory.</p>
75.00	<p>Drain, 12 lks. wide, course N.20°W.</p>
80.00	<p>N., 10 lks. from the tangent,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 34 and 35 only, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 11 W <u>S 34 S 35</u></p> <p style="text-align: center;">1937</p> <p>No suitable accessory.</p> <p>Land, nearly level, NW. drainage. Soil, sandy loam; 2nd rate. Timber, scattered mesquite and ironwood; undergrowth, greasewood and sage.</p>

Survey of the South boundary of T.10 S., R.11 W.

4212

Chains

East, along the South bdy. of sec. 35, on a transit line describing the tangent, which bears S.89°57.7'E.

Over nearly level desert land, thru scattered timber and undergrowth.

25.00 Drain, 7 lks. wide, course N.10°W.

40.00 N., 13 lks. from the tangent,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., of sec. 35 only, with brass cap mkd.

$\frac{1}{4}$ S 35

1937

No suitable accessory.

80.00 N., 16 lks. from the tangent,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 35 and 36 only, with brass cap mkd.

T 10 S R 11 W
S 35 | S 36

1937

No suitable accessory.

Land, nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, scattered ironwood; undergrowth, greasewood and sage.

East, along the South bdy. of sec. 36, on a transit line describing the tangent, which bears S.89°57.2'E.

Over nearly level desert land, thru scattered timber and undergrowth.

6.00 Drain, 6 lks. wide, course N.10°W.

25.00 Drain, 11 lks. wide, course N.

40.00 N., 19 lks. from the tangent,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., for sec. 36 only, with brass cap mkd.

$\frac{1}{4}$ S 36

1937

No suitable accessory.

55.00 Drain, 6 lks. wide, course N:

60.00 Drain, 20 lks. wide, course N.

80.00 N., 24 lks. from the tangent,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for SE. cor. of T, 10 S., R. 11 W., with brass cap mkd.

Survey of the South boundary of T.10 S., R.11 W.

Chains

T 10 S
R 11 W
S 36

1937

No suitable accessory.

Land, nearly level, NW. drainage.
Soil, sandy loam; 2nd rate.
Timber, scattered ironwood; undergrowth, greasewood and mesquite.

Survey of the East boundary of T.10 S., R.11 W.

From the cor. of T. 10 S., R.11 W.,

North, along the E. bdy. of sec. 36.

Over nearly level land, thru scattered timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd.

$\frac{1}{4}$ S 36

1937

No suitable accessory.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 25 and 36 only, with brass cap mkd.

T 10 S
S 25
S 36

R 11 W

1937

from which

A mesquite, 8 ins. diam., bears N.58 $\frac{1}{2}$ °W., 279 lks. dist., mkd. T 10 S R 11 W S 25 B T.

Land, nearly level, NW. drainage.
Soil, sandy loam; 2nd rate.
Timber, scattered mesquite and ironwood; undergrowth, greasewood and sage.

North, along the E. bdy. of sec. 25.

Over nearly level land, thru scattered timber and undergrowth.

8.20 Unimproved desert road, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor. of sec. 25 only, with brass cap mkd.

Survey of the East boundary of T.10 S., R.11 W.

4212

Chains

 $\frac{1}{4}$ S 25

1937

No. suitable accessory.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 24 and 25 only, with brass cap mkd.

T 10 S

S 24

S 25

R 11 W

1937

No suitable accessory.

Land, nearly level desert, NW. drainage.
Soil, sandy loam; 2nd rate.
Timber, scattered paloverde and ironwood; undergrowth, greasewood and sage.

North, along the E. bdy. of sec. 24.

Over nearly level desert land, thru scattered timber and undergrowth.

0.80 Unimproved road, bears N.64°W. and S.64°E.

30.00 Dim road, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor. of sec. 24 only, with brass cap mkd.

 $\frac{1}{4}$ S 24

1937

raise a mound

of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high W. of cor.

44.50 Wash, 20 lks. wide, course W.

50.70 Leave nearly level land, enter low rolling hills; asc. 40 ft. to spur.

55.70 Spur, slopes SW.; desc. 42 ft. over NW. slope.

62.60 Draw, 20 lks. wide, course NW.; asc., 21 ft. over W. slope.

67.20 Desc. 46 ft. over N. slope.

72.10 Leave rolling hills, enter nearly level land.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13 and 24 only, with brass cap mkd.

T 10 S

S 13

S 24

R 11 W

1937

Survey of the East boundary of T.10 S., R.11 W.

Chains

from which

A paloverde, 6 ins. diam., bears S.16 $\frac{1}{2}$ °W., 404 lks. dist., mkd. T 10 S R 11 W S 24 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.

Land, nearly level desert and low rolling hills.
Soil, sandy loam and rocky; 2nd and 4th rate.
Timber, scattered ironwood, paloverde and mesquite; undergrowth, greasewood and sage.

North, along the E. bdy. of sec. 13.

Over nearly level desert land, thru scattered timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 13 only, with brass cap mkd.

$\frac{1}{4}$ S 13

1937

raise a mound

of stone, 3 ft. base, 2 ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 12 and 13 only, with brass cap mkd.

T 10 S

S 12

S 13

R 11 W

1937

from which

An ironwood, 5 ins. diam., bears S.36°W., 424 lks. dist., mkd. T 10 S R 11 W S 13 B T.

A sahuara Cactus, bears N.14°W., 26 lks. dist., mkd. T 10 S R 11 W S 12 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level, W. drainage.
Soil, sandy loam; 2nd rate.
Timber, scattered ironwood and paloverde; undergrowth, greasewood and sage.

North, along the E. bdy. of sec. 12.

Over nearly level desert land, thru scattered timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd.

$\frac{1}{4}$ S 12

1937

from which

Survey of the East boundary of T.10 S., R.11 W.

4212

Chains

A paloverde, 8 ins. diam., bears N.82 $\frac{1}{2}$ °W., 136 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{3}{4}$ ft. high, W. of cor.

65.00 Wash, 40 lks. wide, course SE.; thence over a series of small washes draining W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1 and 12 only, with brass cap mkd.

T 10 S	
S 1	
S 12	
R 11 W	

1937

from which

An ironwood, 4 ins. diam., bears S.81°W., 226 lks. dist., mkd. T 10 S R 11 W S 12 B T.

A sahuara cactus, bears N.9 $\frac{1}{2}$ °W., 112 lks. dist., mkd. T 10 S R 11 W S 1 B T.

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, nearly level, SE. drainage.

Soil, sandy loam; 2nd rate.

Timber, scattered paloverde; undergrowth, greasewood and sage.

North, along the E. bdy. of sec. 1.

Over rolling hills, thru scattered timber and undergrowth.

3.50 Asc. 58 ft. over SE. slope.

7.60 Spur, slopes SE.; desc. 40 ft. over NE. slope.

12.60 Canyon, course, SE.; asc. 81 ft. over S. slope.

19.00 Saddle on spur sloping E.; desc. 101 ft. over N. slope.

26.00 Leave rolling hills, enter nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap mkd.

$\frac{1}{4}$ S 1	
-------------------	--

1937

from which

A paloverde, 6 ins. diam., bears S.27 $\frac{1}{4}$ °W., 134 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.

A sahuara cactus, bears N.18 $\frac{1}{2}$ °W., 302 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high,

Survey of the East boundary of T.10 S., R.11 W.

Chains

W. of cor.

47.20 Unimproved desert road, bears E. to Eagle Tanks and W. to Aztec.

70.57 Intersect the 2nd Stan. Par., South.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for closing cor. of T.10 S., Rs. 10 and 11 W., with brass cap mkd.

T 9 S R 11 W

S 36
S 1

T 10 S
R 11 W

C C
1937

raise a mound

of stone, 2½ ft. base, 1¾ ft. high, SW. of cor.

From the point of intersection, the standard cor. of secs. 35 and 36, bears West, 19.24 chs. dist., an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

Land, nearly level and rolling hills.
Soil, sandy loam and rocky; 2nd and 4th rate.
Timber, scattered ironwood and paloverde; undergrowth, greasewood and sage.

Subdivision of T.10 S., R.11 W.

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described,

N.0°01'W., bet. secs. 35 and 36.

Over nearly level land, thru very scattered timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken crockery deposited at the base, for ¼ sec. cor., with brass cap mkd.

¼
S 35 | S 36
1937

No suitable accessory.

71.30 Old dim road, bears N.60°E. and SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken crockery deposited at the base, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T 10 S R 11 W

S 26 | S 25
S 35 | S 36

1937

Subdivision of T.10 S., R.11 W.

BOOK 4212


Chains	<p>No suitable accessory.</p> <p>Land, nearly level. Soil, sandy loam; 2nd rate. Timber, very scattered mesquite; undergrowth, greasewood and scrub mesquite.</p>
40.00	<p>East, on a random line, bet. secs. 25 and 36.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>
79.96	<p>A point 3 lks. S. of the cor. of secs. 25 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>Thence,</p> <p>S.89°59'W., on a true line, bet. secs. 25 and 36.</p> <p>Over nearly level land, thru very scattered timber and undergrowth.</p>
5.00	<p>Enter fairly dense timber and undergrowth.</p>
39.98	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	$\frac{1}{4} \begin{array}{l} S 25 \\ S 36 \end{array}$
	<p>1937 from which</p>
	<p>A mesquite, 10 ins. diam., bears N.64$\frac{1}{4}$°E., 375 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.</p>
	<p>A mesquite, 6 ins. diam., bears S.11$\frac{1}{2}$°W., 105 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.</p>
45.00	<p>Leave fairly dense timber; enter scattered timber and undergrowth.</p>
68.10	<p>Old dim road, bears NE. and S.60°W.</p>
79.96	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, nearly level. Soil, sandy loam; 2nd rate. Timber, mesquite; undergrowth, greasewood.</p>
	<p>N.0°01'W., bet. secs. 25 and 26.</p> <p>Over nearly level land, thru scattered timber and undergrowth.</p>
18.60	<p>Wash, 10 lks. wide, course NW.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	$\frac{1}{4} \begin{array}{c} \\ S 26 S 25 \\ \\ 1937 \end{array}$
	<p>No suitable accessory.</p>
41.30	<p>Wash, 8 lks. wide, course NW.</p>

Subdivision of T.10 S., R.11 W.

Chains
80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

T 10 S R 11 W



1937

No suitable accessory.

Land, nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, scattered mesquite; undergrowth, greasewood.

N.89°59'E., on a random line, bet. secs. 24 and 25.

40.00 Set temp. 1/4 sec. cor.

79.94 A point 3 lks. S. of the cor. of secs. 24 and 25, on the E. bdy. of the Tp., described hereinbefore.

Thence,


S.89°58'W., on a true line, bet. secs. 24 and 25.

Over nearly level land, thru no timber and scattered undergrowth.

0.80 Wash, 7 lks. wide, course SW.

6.80 Wash, 6 lks. wide, course SW.

39.97 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



1937

No suitable accessory.

79.94 The cor. of secs. 23, 24, 25 and 26.

Land, nearly level desert, SW. drainage.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth; greasewood.

N.0°01'W., bet. secs. 23 and 24.

Over nearly level land, no timber and scattered undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.




1937

No suitable accessory.

Subdivision of T.10 S., R.11 W.

4212

Chains
 54.00 Old road, bears NW. and SE.
 75.00 Drain, 8 lks. wide, course N.60°W.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a ½ pint glass jar deposited at the base, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.




No suitable accessory.
 Land, nearly level.
 Soil, sandy loam; 2nd rate.
 Timber, none; undergrowth, greasewood and scrub mesquite.

N.89°58'E., on a random line, bet. secs. 13 and 24.

40.00 Set temp. ¼ sec. cor.
 79.86 A point 4 lks. N. of the cor. of secs. 13 and 24, on the E. bdy. of the Tp., hereinbefore described.

Thence,
 West, on a true line, bet. secs. 13 and 24.
 Over nearly level land, no timber and scattered undergrowth.


19.90 Draw, 8 lks. wide, course SW.
 34.00 Wash, 10 lks. wide, course S.25°W.
 39.93 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken crockery deposited at the base, for ¼ sec. cor., with brass cap mkd.



No suitable accessory.
 79.86 The cor. of secs. 13, 14, 23 and 24.
 Land, nearly level.
 Soil, sandy loam; 2nd rate.
 Timber, none; undergrowth, greasewood and scrub mesquite.

N.0°01'W.; bet. secs. 13 and 14.

Over nearly level land, thru scattered timber and undergrowth.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for ¼ sec. cor., with brass cap mkd.



Subdivision of T.10 S., R.11 W.

Chains	No suitable accessory.
60.00	Wash, 15 lks. wide, course SW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.
	T 10 S R 11 W S 11 S 12 S 14 S 13 1937
	No suitable accessory.
	Land, nearly level. Soil, sandy loam; 2nd rate. Timber, scattered ironwood and paloverde; undergrowth, greasewood and sage.
	East, on a random line, bet. secs. 12 and 13.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.86	A point 8 lks. N. of the cor. of secs. 12 and 13, on the E. bdy. of the Tp., hereinbefore described.
	Thence, N.89°57'W., on a true line, bet. secs. 12 and 13. Over nearly level land, thru scattered timber and undergrowth.
14.10	Leave nearly level land, enter rolling land.
28.60	Wash, 20 lks. wide, course SE.
38.30	Wash, 30 lks. wide, course SE.
39.93	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a rock mkd. with a cross (+) deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 12 $\frac{1}{4}$ S 13 1937
	No suitable accessory.
43.00	Wash, 20 lks. wide, course SE.; asc. 57 ft. over NE. slope.
66.20	Top of spur, slopes SE.; desc. 51 ft. over SW. slope.
75.00	Bottom of descent.
79.86	The cor. of secs. 11, 12, 13 and 14.
	Land, nearly level and rolling. Soil, sandy loam, gravelly and rocky; 2nd, 3rd and 4th rate. Timber, scattered ironwood and paloverde; undergrowth, greasewood and sage.
	N.0°01'W., bet. secs. 11 and 12.

Subdivision of T.10 S., R.11 W.


BOOK 4212

Chains	
	Over rolling and mountainous land, thru scattered timber and undergrowth; asc. over gentle S.slope.
15.00	Wash, 20 lks. wide, course W.; asc. 99 ft. over SE. slope.
23.00	Top of ridge, bears NW.; desc. 147 ft. over NE. slope.
34.60	Wash, 5 lks. wide, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ S\ 11\ \ S\ 12 \\ \\ 1937 \end{array}$
	from which
	A paloverde, 6 ins. diam., bears N.14 $\frac{1}{2}$ °E., 27 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.
	A paloverde, 7 ins. diam., bears N.77 $\frac{1}{4}$ °W., 160 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
50.00	Wash, 30 lks. wide, course SW.
65.00	Enter mountains; asc. 126 ft. over E. slope.
79.30	Spur, slopes SE.
79.35	Draw, course SE.; over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., on bedrock and in a mound of stone, 5 ft. base to top, for cor. of secs. 1,2,11 and 12, with brass cap mkd.
	$\begin{array}{c} T\ 10\ S\ R\ 11\ W \\ \\ S\ 2\ \ S\ 1 \\ \\ S\ 11\ \ S\ 12 \\ \\ 1937 \end{array}$
	No suitable accessory.
	Land, rolling and mountainous. Soil, rocky; 3rd and 4th rate. Timber, scattered ironwood and paloverde; undergrowth, greasewood.
	S.89°57'E., on a random line, bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	A point 28 lks. S. of the cor. of secs. 1 and 12, on the E. bdy. of the Tp., hereinbefore described.
	Thence,
	S.89°51'W., on a true line, bet. secs. 1 and 12.
	Over mountainous land, thru scattered timber and undergrowth.
10.00	Wash, 10 lks. wide, course SE.; asc. 74 ft. over E.slope.
19.20	Top of spur, slopes SE.; desc. 46 ft. over SW. slope.
24.90	Draw, 1 lks. wide, course S.; asc. 189 ft. over NE.slope.

Subdivision of T.10 S., R.11 W.

Chains

- 34.45 Top of ridge, bears NW. and SE.
- 39.50 Draw, course SW.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



1937

No suitable accessory.


- 41.85 Top of spur, slopes SW.; desc. 121 ft. over SW. slope.
- 54.30 Wash, 50 lks. wide, course NW.;
- 63.70 Wash, 50 lks. wide, course W.
- 68.30 Same wash, 50 lks. wide, course W.
- 72.50 Wash, 5 lks. wide, course SW.; asc. 99 ft. over SE. slope.
- 80.00 The cor. of secs. 1, 2, 11 and 12.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, scattered ironwood and paloverde; undergrowth, greasewood.

N.0°01'W., bet. secs. 1 and 2.

Over rough mountainous land, thru scattered timber and undergrowth; asc. 440 ft. over broken SE. slope.

- 29.00 Top of ridge, bears E. and SW.; desc. 577 ft. over broken N. slope.
- 39.83 Set an iron post, 3 ft. long, 1 in. diam., on bedrock, and in a mound of stone, 4 ft. base to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.




1937

No suitable accessory.

- 40.00 True point for $\frac{1}{4}$ sec. cor. falls on face of cliff.
- 49.60 Bottom of descent.
- 54.60 Asc. 96 ft. over SW. slope.
- 65.20 Spur, slopes W.; desc. 98 ft. to sec. cor.
- 70.79 Intersect the 2nd Stan. Par. South.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.



1937

Subdivision of T.10 S., R.11 W.

4212

Chains

No suitable accessory.

From the point of intersection, the standard cor. of secs. 34 and 35, T.9 N., R.11 W., bears West, 19.52 chs. dist., an iron post, 2 ins. diam., 10 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

Land, mountainous.

Soil, rocky; 4th rate.

Timber, scattered mesquite; undergrowth, greasewood.

From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described,

N.0°01'W., bet. secs. 34 and 35.

Over nearly level land, thru scattered underbrush; no timber.

14.70 Dim road, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 34\ | \ S\ 35 \\ | \\ 1937 \end{array}$$

No suitable accessory.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

T 10 S R 11 W

$$\begin{array}{c} S\ 27\ | \ S\ 26 \\ \hline S\ 34\ | \ S\ 35 \\ | \\ 1937 \end{array}$$

No suitable accessory.

Land, nearly level, NW. drainage.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood.

East, on a random line, bet. secs. 26 and 35.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 A point 5 lks. S. of the cor. of secs. 25, 26, 35 and 36.

Thence,

S.89°58'W., on a true line, bet. secs. 26 and 35.

Over nearly level land, thru scattered undergrowth.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Subdivision of T.10 S., R.11 W.

Chains

$$\frac{1}{4} \begin{array}{c} S 26 \\ S 35 \end{array}$$

1937

No suitable accessory.

80.02 The cor. of secs. 26, 27, 34 and 35.

Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, none; undergrowth, greasewood.

N.0°01'W., bet. secs. 26 and 27.

Over nearly level land, thru very scattered timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken crockery deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{c} | \\ S. 27 | S. 26 \\ | \\ 1937 \end{array}$$

No suitable accessory.

48.70 Wash, 10 lks. wide., course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

T 10 S R 11 W

$$\begin{array}{c} S 22 | S 23 \\ S 27 | S 26 \\ | \\ 1937 \end{array}$$

1937

from which

A mesquite, 5 ins. diam., bears S.29 $\frac{1}{2}$ °E., 88 lks. dist., mkd. T 10 S R 11 W S 26 B T.

Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, scattered mesquite; undergrowth, greasewood and scrub mesquite.

N.89°58'E., on a random line, bet. secs. 23 and 26.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 A point 2 lks. N. of the cor. of secs. 23, 24, 25 and 26.

Thence,

S.89°59'W., on a true line, bet. secs. 23 and 26.

Over nearly level land, thru very scattered timber and undergrowth.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Subdivision of T.10 S., R.11 W.

4212

Chains

$$\frac{1}{4} \begin{array}{c} S 23 \\ S 26 \end{array}$$

1937

No suitable accessory.

80.02 The cor. of secs. 22,23,26 and 27.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, scattered scrub mesquite; undergrowth, greasewood, scrub mesquite.

N.0°01'W., bet. secs. 22 and 23.

Over nearly level land, thru scattered undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{c} S 22 | S 23 \\ 1937 \end{array}$$

No suitable accessory.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 14,15,22 and 23, with brass cap mkd.

T 10 S R 11 W

$$\frac{1}{4} \begin{array}{c} S 15 | S 14 \\ S 22 | S 23 \end{array}$$

1937

No suitable accessory.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood.

N.89°59'E., on a random line, bet. secs. 14 and 23..

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 The cor. of secs. 13,14,23 and 24.

Thence,

S.89°59'W., on a true line, bet. secs. 14 and 23.

Over nearly level land, thru scattered undergrowth.

29.00 Dim road, bears NW. to Aztec and SE. to Ajo.

40.01 Set an iron post, 3 ft. long, 1 in., diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{c} S 14 \\ S 23 \end{array}$$

1937

Chains	No suitable accessory.
80.02	The cor. of secs. 14,15 22 and 23. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, scattered greasewood.
24.80	N.0°01'W., bet. secs. 14 and 15. Over nearly level land, thru scattered undergrowth. Drain, 15 lks. wide, course N.70°W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \\ S\ 15\ \ S\ 14 \\ \\ 1937 \end{array}$
48.70	No suitable accessory. Old road, bears NW. and SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for cor. of secs. 10,11,14 and 15, with brass cap mkd. $\begin{array}{c} T.10\ S\ R\ 11\ W \\ \\ S\ 10\ \ S\ 11 \\ \\ S\ 15\ \ S\ 14 \\ \\ 1937 \end{array}$
40.00	No suitable accessory. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite
40.00	N.89°59'E., on a random line, bet. secs. 11 and 14. Set temp. $\frac{1}{4}$ sec. cor.
80.00	The cor. of secs. 11,12,13 and 14. Thence, S.89°59'W., on a true line, bet. secs. 11 and 14. Over nearly level land, thru scattered undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \\ S. 11 \\ \\ S 14 \\ \\ 1937 \end{array}$
	No suitable accessory.

Subdivision of T.10 S., R.11 W.

BOOK 4212

Chains
80.00


The cor. of secs. 10,11,14 and 15.
Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, none; undergrowth, greasewood and scrub mesquite.

N.0°01'W., bet. secs. 10 and 11.

Over nearly level land, thru scattered timber and undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



No suitable accessory.

47.20

Wash, 20 lks. wide, course SW.


50.50

Enter series of washes, courses SW.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 2,3,10 and 11, with brass cap mkd.

T 10 S R 11 W



from which

An ironwood, 6 ins. diam., bears S.19 $\frac{1}{2}$ °W., 90 lks. dist., mkd. T 10 S R 11 W S 10 B T.

Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, scattered ironwood; undergrowth, greasewood and sage.

N.89°59'E., on a random line, bet. secs. 2 and 11.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

80.12

A point 2 lks. N. of the cor. of secs. 1,2,11 and 12.

Thence,

West, on a true line, bet. secs. 2 and 11.

Over mountainous land, thru scattered timber and undergrowth; asc. 43 ft. over E slope.

2.70

Draw, course SE.; asc. 189 ft. over E. slope.

6.80

Top of ridge, bears NE. curving to W.; desc. 431 ft. over NW. slope.

12.20

Draw, course N., slope changes to N.

12.70

Top of spur, slopes N.

Subdivision of T.10 S., R.11 W.

Chains	
17.00	Draw, course N.
17.30	Top of spur, slopes N., over NW. slope.
20.10	Slope changes to W.
22.75	Top of spur, slopes NW.
35.10	Leave mountainous land, enter nearly level land.
40.06	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, and in a mound of stone, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} S 2 \\ S 11 \end{array}$ 1937
	No suitable accessory.
45.10	Enter series of washes, courses SW.
70.10	Leave series of washes, courses SW.
80.12	The cor. of secs. 2, 3, 10 and 11.
	Land, mountainous and nearly level. Soil, rocky; 3rd and 4th rate. Timber, scattered ironwood; undergrowth, greasewood and sage.
	N.0°01'W., bet. secs. 2 and 3.
	Over nearly level land, thru scattered timber and undergrowth. Over a series of washes, courses SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} S 3 \\ S 2 \end{array}$ 1937
	No suitable accessory.
70.52	Intersect the 2nd Stan. Par. South.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for closing cor. of secs. 2 and 3, with brass cap mkd.
	T 9 S R 11 W $\frac{S 34}{S 3 S 2}$ T 10 S R 11 W C C. 1937
	No suitable accessory.
	From the point of intersection, the standard cor. of secs. 33 and 34, on the S. bdy. of T.9 S., R.11 W., bears

Subdivision of T.10 S., R.11 W.

BOOK 4212

Chains

West, 19.60 chs. dist., an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the official record.


Land, nearly level.
Soil, sandy loam and gravel; 2nd and 3rd rate.
Timber, scattered ironwood; undergrowth, greasewood and sage.

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described,

N.0°02'W., bet. secs. 33 and 34.


Over nearly level land, thru scattered undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



No suitable accessory.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 3 pieces of broken glass deposited at the base, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.



No suitable accessory.

Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, none; undergrowth, greasewood and scrub mesquite.

East, on a random line, bet. secs. 27 and 34.

40.00 Set temp. 1/4 sec. cor.


80.06 A point 3 lks. N. of the cor. of secs. 26, 27, 34 and 35.

Thence;

N.89°59'W., on a true line, bet. secs. 27 and 34.

Over nearly level land, thru scattered undergrowth.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



No suitable accessory.

Subdivision of T.10 S., R.11 W.

Chains 80.06	The cor. of secs. 27, 28, 33 and 34. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.
40.00	N.0°02'W., bet. secs. 27 and 28. Over nearly level land, thru scattered undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S } 28 \text{ } \text{S } 27 \\ \hline 1937 \end{array}$ No suitable accessory.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd. $\begin{array}{c} \text{T } 10 \text{ S } \text{R } 11 \text{ W} \\ \hline \text{S } 21 \text{ } \text{S } 22 \\ \hline \text{S } 28 \text{ } \text{S } 27 \\ \hline 1937 \end{array}$ No suitable accessory. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.
40.00	S.89°59'E., on a random line, bet. secs. 22 and 27. Set temp. $\frac{1}{4}$ sec. cor.
80.17	A point 5 lks. N. of the cor. of secs. 22, 23, 26 and 27. Thence, N.89°57'W., on a true line, bet. secs. 22 and 27.
21.17	Over nearly level land, thru scattered undergrowth. Wash, 15 lks. wide, course NW.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \text{ S } 22 \\ \hline \text{S } 27 \end{array}$ 1937 No suitable accessory.
80.17	The cor. of secs. 21, 22, 27 and 28. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, scattered greasewood.

Subdivision of T.10 S., R.11 W.

4212


Chains

N.0°02'W., bet. secs. 21 and 22.

Over nearly level land, thru scattered undergrowth..

13.50 Wash, 10 lks. wide, course NW.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



No suitable accessory.

47.00 Wash, 5 lks. wide, course N.50°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for cor. of secs. 15,16,21 and 22, with brass cap mkd.



No suitable accessory.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

S.89°57'E., on a random line, bet. secs. 15 and 22.

40.00 Set temp. 1/4 sec. cor.


80.20 A point 5 lks. S. of the cor. of secs. 14,15,22 and 23.

Thence,

N.89°59'W., on a true line, bet. secs. 15 and 22.

Over nearly level land, thru scattered undergrowth.

40.10 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



1937

No suitable accessory.

80.20 The cor. of secs. 15,16,21 and 22.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

N.0°02'W., bet. secs. 15 and 16.

Subdivision of T.10 S., R.11 W.


Chains	Over nearly level land, thru scattered undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ S\ 16\ \ S\ 15 \\ \\ 1937 \end{array}$
	No suitable accessory.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for cor. of secs. 9,10,15 and 16, with brass cap mkd.
	$\begin{array}{c} T\ 10\ S\ R\ 11\ W \\ \\ S\ 9\ \ S\ 10 \\ \hline S\ 16\ \ S\ 15 \\ \\ 1937 \end{array}$
	No suitable accessory.
	Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood.
	S.89°59'E., on a random line, bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.22	The cor. of secs. 10,11,14 and 15.
	Thence,
	N.89°59'W., on a true line, bet. secs. 10 and 15.
	Over nearly level land, thru scattered undergrowth.
36.00	Old road, bears NW. and SE.
40.11	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 4 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \ S\ 10 \\ \hline S\ 15 \\ \\ 1937 \end{array}$
	No suitable accessory.
80.22	The cor. of secs. 9,10,15 and 16.
	Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth greasewood.
	N.0°02'W., bet. secs. 9 and 10.
	Over nearly level land, thru scattered undergrowth.
33.65	Dim road, bears NW. and SE.

Subdivision of T.10 S., R.11 W.

4212

Chains
40.00


Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



No suitable accessory.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 3,4,9 and 10, with brass cap mkd.



No suitable accessory.

Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, none; undergrowth, greasewood and sage.

S.89°59'E., on a random line, bet. secs. 3 and 10.

40.00

Set temp. 1/4 sec. cor.

80.26


The cor. of secs. 2,3,10 and 11.

Thence,

N.89°59'W., on a true line, bet. secs. 3 and 10.

40.13

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



No suitable accessory.

80.26

The cor. of secs. 3,4,9 and 10.


Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, none; undergrowth; greasewood and sage.

N.0°02'W., bet. secs. 3 and 4.

Over nearly level land, thru scattered undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



Subdivision of T.10 S., R.11 W.

Chains

No suitable accessory.

70.40

Intersect the 2nd Stan. Par. South.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a beer bottle deposited at the base, for closing cor. of secs. 3 and 4, with brass cap mkd.

T 9 S R 11 W

S 33
S 4 | S 3

T 10 S R 11 W

C. C

1937

No suitable accessory.

From the point of intersection, the standard cor. of secs. 32 and 33 on the S. bdy. of T.9 S., R.11 W., bears West, 19.27 chs. dist., an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

From the cor. of secs. 32 and 33, on the South bdy. of the Tp., hereinbefore described,

N.0°02'W., bet. secs. 32 and 33.

Over nearly level land, thru scattered undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 32 | S 33

1937

No suitable accessory.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a pint glass jar deposited at the base, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T 10 S R 11 W

S 29 | S 28
S 32 | S 33

1937

No suitable accessory.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

East on a random line, bet. secs. 28 and 33.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

Subdivision of T.10 S., R.11 W.

4212

Chains

79.94

A point 5 lks. N. of the cor. of secs. 27,28,33 and 34.

Thence,

N.89°58'W., on a true line, bet. secs. 28 and 33.

Over nearly level land, thru scattered undergrowth.

39.97

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{c} S 28 \\ S 33 \end{array}$$

1937

No suitable accessory.

79.94

The cor. of secs. 28,29,32 and 33.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood.

N.0°02'W., bet. secs. 28 and 29.

Over nearly level land, thru scattered undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 3 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{c} S 29 | S 28 \\ 1937 \end{array}$$

No suitable accessory.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken crockery deposited at the base, for cor. of secs. 20,21,28 and 29, with brass cap mkd.

T 10 S R 11 W

$$\begin{array}{c} S 20 | S 21 \\ S 29 | S 28 \\ 1937 \end{array}$$

1937

No suitable accessory.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

S.89°58'E., on a random line, bet. secs. 21 and 28..

40.00

Set temp. $\frac{1}{4}$ sec. cor.

79.92

A point 2 lks. S. of the cor. of secs. 21,22,27 and 28.

Thence,

N.89°59'W., on a true line, bet. secs. 21 and 28.

Subdivision of T.10 S., R.11 W.

Chains	Over nearly level land, thru scattered undergrowth.
39.96	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \text{ S } 21 \\ \hline \frac{1}{4} \text{ S } 28 \\ 1937 \end{array}$
	No suitable accessory.
79.92	The cor. of secs. 20,21,28 and 29. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.
	N.0°02'W., bet. secs. 20 and 21. Over nearly level land, thru scattered undergrowth.
20.50	Drain, 10 lks. wide, course W.
29.20	Drain, 8 lks. wide, course W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \hline \text{S } 20 \mid \text{S } 21 \\ 1937 \end{array}$
	No suitable accessory.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for cor. of secs. 16,17,20 and 21, with brass cap mkd. $\begin{array}{c} \text{T } 10 \text{ S } \text{R } 11 \text{ W} \\ \hline \text{S } 17 \mid \text{S } 16 \\ \hline \text{S } 20 \mid \text{S } 21 \\ 1937 \end{array}$
	No suitable accessory.
	Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.
	S.89°59'E., on a random line, bet. secs. 16 and 21.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.93	The cor. of secs. 15,16,21 and 22. Thence, N.89°59'W., on a true line, bet. secs. 16 and 21. Over nearly level land, thru scattered undergrowth.

Subdivision of T.10 S., R.11 W.

4212

Chains 39.96	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 16 \\ S 21 \end{array}$ <p>1937</p>
	No suitable accessory.
79.93	The cor. of secs. 16,17,20 and 21. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.
	N.0°02'W., bet. secs. 16 and 17.
	Over nearly level land, thru scattered undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 17 S 16 \end{array}$ <p>1937</p>
	No suitable accessory.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 8,9,16 and 17, with brass cap mkd.
	<p>T 10 S R 11 W</p> $\frac{1}{4} \begin{array}{l} S 8 S 9 \\ S 17 S 16 \end{array}$ <p>1937</p>
	No suitable accessory.
	Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood.
	S.89°59'E., on a random line, bet. secs. 9 and 16.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	The cor. of secs. 9,10,15 and 16.
	Thence,
	N.89°59'W., on a true line, bet. secs. 9 and 16.
	Over nearly level land, thru scattered undergrowth.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 9 \\ S 16 \end{array}$ <p>1937</p>

Subdivision of T.10 S., R.11 W.

Chains	No suitable accessory.
79.96	The cor. of secs. 8,9,16 and 17. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood.
40.00	N.0°02'W., bet. secs. 8 and 9. Over nearly level land, thru scattered undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 8\ \ S\ 9 \\ 1937 \end{array}$
80.00	No suitable accessory. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 4,5,8 and 9, with brass cap mkd. $\begin{array}{c} T\ 10\ S\ R\ 11\ W \\ S\ 5\ \ S\ 4 \\ S\ 8\ \ S\ 9 \\ 1937 \end{array}$
40.00	No suitable accessory. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.
80.00	S.89°59'E., on a random line, bet. secs. 4 and 9. Set temp. $\frac{1}{4}$ sec. cor. A point 5 lks. S of the cor. of secs. 3,4,9 and 10. Thence, S.89°59'W., on a true line, bet. secs. 4 and 9. Over nearly level land, thru scattered undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \quad S\ 4 \\ \quad \quad S\ 9 \end{array}$ 1937
68.00	No suitable accessory. Old road, bears N.60°W. and S.60°E.
80.00	The cor. of secs. 4,5,8 and 9. Land, nearly level.

Subdivision of T.10 S., R.11 W.

4212

Chains


Soil, sandy loam; 2nd rate.
Timber, none; undergrowth, greasewood and scrub mesquite.

N.0°02'W., bet. secs. 4 and 5.

Over nearly level land, thru scattered undergrowth.

6.60 Old road, bears NW. and SE.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



No suitable accessory.

70.40 Intersect the 2nd Stan. Par. South.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with an empty beer bottle deposited at the base, for closing cor. of secs. 4 and 5, with brass cap mkd.



No suitable accessory.

From the point of intersection, the standard cor. of secs. 31 and 32, on the S. bdy. of T.9 S., R.11 W., bears West, 19.22 chs. dist., an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the official record.


Land, nearly level.
Soil, sandy loam; 2nd rate.
Timber, none; undergrowth, greasewood and scrub mesquite.

From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described,

N.0°03'W., bet. secs. 31 and 32.

Over nearly level land, thru scattered timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



No suitable accessory.

63.80 Wash, 10 lks. wide., course NW.

BOOK 4212

Subdivision of T.10 S., R.11 W.

Chains 80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 11 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>S 30</td> <td> </td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td> </td> <td>S 32</td> </tr> </table> <p style="text-align: center;">1937</p> <p>No suitable accessory.</p> <p>Land, nearly level. Soil, sandy loam; 2nd rate. Timber, scattered mesquite; undergrowth, greasewood.</p>	S 30		S 29	S 31		S 32
S 30		S 29					
S 31		S 32					
40.00	<p>East, on a random line, bet. secs. 29 and 32.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>						
80.04	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Thence,</p> <p>West, on a true line, bet. secs. 29 and 32.</p> <p>Over nearly level land, thru scattered undergrowth.</p>						
30.00	<p>Low sand hill, 2 chs. wide, 5 chs. long, bears NE. and SW.</p>						
40.02	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken crockery deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>$\frac{1}{4}$</td> <td>S 29</td> </tr> <tr> <td>$\frac{1}{4}$</td> <td>S 32</td> </tr> </table> <p style="text-align: center;">1937</p> <p>No suitable accessory.</p> <p>Over low sand hills.</p>	$\frac{1}{4}$	S 29	$\frac{1}{4}$	S 32		
$\frac{1}{4}$	S 29						
$\frac{1}{4}$	S 32						
80.04	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, nearly level and low hills. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.</p>						
40.00	<p>West, on a random line, bet. secs. 30 and 31.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>						
77.44	<p>A point 26 lks. S. of the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Thence,</p> <p>S. 89° 49' E., on a true line, bet. secs. 30 and 31.</p> <p>Over nearly level land, thru scattered timber and undergrowth.</p>						
37.44	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>$\frac{1}{4}$</td> <td>S 30</td> </tr> <tr> <td>$\frac{1}{4}$</td> <td>S 31</td> </tr> </table> <p style="text-align: center;">1937</p>	$\frac{1}{4}$	S 30	$\frac{1}{4}$	S 31		
$\frac{1}{4}$	S 30						
$\frac{1}{4}$	S 31						

Subdivision of T.10 S., R.11 W.

4212

Chains	No suitable accessory.
53.20	Enter series of washes, courses NW.
58.80	Leave series of washes.
77.44	The cor. of secs. 29,30,31 and 32. Land, nearly level. NW. drainage. Soil, sandy loam; 2nd rate. Timber, scattered mesquite; undergrowth, greasewood.
	N.0°03'W., bet. secs. 29 and 30. Over nearly level land, thru scattered timber and undergrowth.
10.80	Wash, 10 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 30\ \ S\ 29 \\ 1937 \end{array}$
	No suitable accessory.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 19,20,29 and 30, with brass cap mkd. $\begin{array}{c} T\ 10\ S\ R\ 11\ W \\ S\ 19\ \ S\ 20 \\ S\ 30\ \ S\ 29 \\ 1937 \end{array}$
	No suitable accessory. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, scattered mesquite; undergrowth, greasewood.
	East, on a random line, bet. secs. 20 and 29.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.97	A point 2 lks. S. of the cor. of secs. 20,21,28 and 29. Thence, S.89°59'W., on a true line, bet. secs. 20 and 29. Over nearly level land, thru scattered undergrowth.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} S\ 20 \\ \frac{1}{4} \text{---} S\ 29 \\ 1937 \end{array}$

BOOK 4212

Subdivision of T.10 S., R.11 W.

Chains	
	No suitable accessory.
79.97	The cor. of secs. 19,20,29 and 30.
	Land, nearly level.
	Soil, sandy loam; 2nd rate.
	Timber, none; undergrowth; greasewood and scrub mesquite.
	West, on a random line, bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
77.20	A point 45 lks. S. of the cor. of 19,24,25 and 30, on the W. bdy. of the Tp., hereinbefore described.
	Thence,
	S.89°40'E., on a true line, bet. secs. 19 and 30.
	Over nearly level land, thru scattered timber and undergrowth.
15.80	Wash, 6 lks. wide, course NW.
25.20	Wash, 7 lks. wide, course NW.
37.20	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \text{ S } 19 \\ \frac{1}{4} \text{ S } 30 \end{array}$
	1937
	No suitable accessory.
77.20	The cor. of secs. 19,20,29 and 30.
	Land, nearly level. NW. drainage.
	Soil, sandy loam; 2nd rate.
	Timber, scattered mesquite; undergrowth, greasewood.
	N.0°03'W., bet. secs. 19 and 20.
	Over nearly level land, thru scattered undergrowth.
17.30	Wash, 10 lks. wide, course N.60°W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 19 \text{ } \text{S } 20 \\ \frac{1}{4} \end{array}$
	1937
	No suitable accessory.
60.50	Drain, 5 lks. wide, course N.60°W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for cor. of secs. 17,18,19 and 20, with brass cap mkd.

Subdivision of T.10 S., R.11 W.

4212

Chains														
	<p>T 10 S R 11 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S 20</td> </tr> </table> <p>1937</p>	S 18	S 17	S 19	S 20									
S 18	S 17													
S 19	S 20													
	<p>No suitable accessory.</p> <p>Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.</p>													
	<p>N.89°59'E., on a random line, bet. secs. 17 and 20.</p>													
40.00	Set temp. $\frac{1}{4}$ sec. cor.													
79.95	A point 2 lks. N. of the cor. of secs. 16,17,20 and 21. Thence, West, on a true line, bet. secs. 17 and 20. Over nearly level land, thru scattered undergrowth.													
39.97	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.													
	<table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">$\frac{1}{4}$</td> <td style="padding: 0 5px;">S 17</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">$\frac{1}{4}$</td> <td style="padding: 0 5px;">S 20</td> </tr> </table> <p>1937</p>	$\frac{1}{4}$	S 17	$\frac{1}{4}$	S 20									
$\frac{1}{4}$	S 17													
$\frac{1}{4}$	S 20													
	<p>No suitable accessory.</p>													
79.95	The cor. of secs. 17,18,19 and 20. Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.													
	<p>N.89°40'W., bet. secs. 18 and 19.</p> <p>Over nearly level land, thru scattered undergrowth.</p>													
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 3 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.													
	<table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">$\frac{1}{4}$</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">$\frac{1}{4}$</td> <td style="padding: 0 5px;">S 19</td> </tr> </table> <p>1937</p>	$\frac{1}{4}$	S 18	$\frac{1}{4}$	S 19									
$\frac{1}{4}$	S 18													
$\frac{1}{4}$	S 19													
	<p>No suitable accessory.</p>													
77.01	Intersect the W. bdy. of the Tp. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 3 pieces of broken crockery deposited at the base, for closing cor. of secs. 18 and 19, with brass cap mkd.													
	<p>T 10 S</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 10 S</td> <td style="padding: 0 5px;">S 18</td> <td></td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">C</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 12 W</td> <td style="border-right: 1px solid black; padding: 0 5px;">R 11 W</td> <td></td> <td></td> </tr> </table> <p>1937</p>	T 10 S	S 18			S 24	S 19	C	C	R 12 W	R 11 W			
T 10 S	S 18													
S 24	S 19	C	C											
R 12 W	R 11 W													

Chains

No suitable accessory.

From the point of intersection, the cor. of secs. 13 and 24 only, on the E. bdy. of T.10 S., R.12 W., bears N.0°06' E., 24 lks. dist., hereinbefore described.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

At a point S.0°06'W., 12 lks. dist., from the $\frac{1}{4}$ sec. cor. of sec. 24, on the E. bdy. of T.10 S., R.12 W., which point is midway between the NW. closing cor. of sec. 19, and the cor. of secs. 19, 24, 25 and 30, T.10 S., Rs. 11 and 12 W., hereinbefore described,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor. of sec. 19, T.10 S., R.11 W., only, with brass cap mkd.

$\frac{1}{4}$ S 19

1937

No suitable accessory.

From the cor. of secs. 17, 18, 19 and 20. N.0°03'W., bet. secs. 17 and 18.

Over nearly level land, thru scattered undergrowth.

40.00. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$.

S 18 | S 17

1937

No suitable accessory.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

T 10 S R 11 W

S 7 | S 8
S 18 | S 17

1937

No suitable accessory.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

East, on a random line, bet. secs. 8 and 17.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 A point 5 lks. S. of the cor. of secs. 8, 9, 16 and 17.

Thence,

Subdivision of T.10 S., R.11 W.


4212

Chains

S.89°58'W., on a true line, bet. secs. 8 and 17.

Over nearly level land, thru scattered undergrowth.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.



1937

No suitable accessory.

79.98 The cor. of secs. 7, 8, 17 and 18.

Land, nearly level.


Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

N.89°40'W., bet. secs. 7 and 18.

Over nearly level land, thru scattered undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.




1937

No suitable accessory.

76.77 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a 2 ounce glass bottle deposited at the base, for closing cor. of secs. 7 and 18, with brass cap mkd.



1937

No suitable accessory.

From the point of intersection, the cor. of secs. 12 and 13 only, on the E. bdy. of T.10 S., R.12 W., bears N.0°06' E., 50 lks. dist., hereinbefore described.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

At a point S.0°06'W., 37 lks. dist., from the 1/4 sec. cor. pf sec. 13, on the E. bdy. of T.10 S., R.12 W., which point is midway bet. the NW. and SW. closing cors. of sec. 18, R.11 W., hereinbefore described,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with 2 pieces of broken glass deposited at the base, for 1/4 sec. cor. of sec. 18, T.10 S., R.11 W., only,

Subdivision of T.10 S., R.11 W.

Chains	with brass cap mkd.
	$\begin{array}{c} \\ \frac{1}{4} S 18 \\ 1937 \end{array}$
	No suitable accessory.
	From the cor. of secs. 7, 8, 17 and 18, N.0°03'W., bet. secs. 7 and 8.
	Over nearly level land, thru scattered undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S 7 S 8 \\ 1937 \end{array}$
	No suitable accessory.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.
	T 10 S R 11 W $\begin{array}{c} S 6 S 5 \\ S 7 S 8 \\ 1937 \end{array}$
	No suitable accessory.
	Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.
	N.89°58'E., on a random line, bet. secs. 5 and 8.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	A point 2 lks. S. of the cor. of secs. 4, 5, 8 and 9.
	Thence,
	S.89°57'W., on a true line, bet. secs. 5 and 8.
	Over nearly level land, thru scattered undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} S 5 \\ \frac{1}{4} - S 8 \\ 1937 \end{array}$
	No suitable accessory.
80.00	The cor. of secs. 5, 6, 7 and 8.
	Land, nearly level. Soil, sandy loam; 2nd rate. Timber, none; undergrowth, greasewood and scrub mesquite.

Subdivision of T.10 S., R.11 W.

4212

Chains

N.89°40'W., bet. secs. 6 and 7.

Over nearly level land, thru scattered undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 6 \\ S 7 \end{array}$$

1937

No suitable accessory.

76.57 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for closing cor. of secs. 6 and 7, with brass cap mkd.

$$\begin{array}{c} T 10 S \\ T 10 S \\ S 12 \left| \begin{array}{c} S 6 \\ S 7 \end{array} \right. C C \\ R 12 W \left| R 11 W \end{array}$$

1937

No suitable accessory.

From the point of intersection, the cor. of secs. 1 and 12 only, on the E. bdy. of T.10 S., R.12 W., bears N.0°06'E., 75 lks. dist., hereinbefore described.

Land, nearly level.

Soil, sandy loam; 2nd rate.

Timber, none; undergrowth, greasewood and scrub mesquite.

At a point S.0°06'W., 62 lks. dist., from the $\frac{1}{4}$ sec. cor. of sec. 12, on the E. bdy. of T.10 S., R.12 W., which point is midway bet. the NW. and SW. closing cors. of sec. 7, R.11 W., hereinbefore described,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor. of sec. 7, T.10 S., R.11 W., only, with brass cap mkd.

$$\frac{1}{4} S 7$$

1937

No suitable accessory.

At a point S.0°06'W., 87 lks. dist., from the $\frac{1}{4}$ sec. cor. of sec. 1, on the E. bdy. of T.10 S., R.12 W., which point is N.0°06'E., 40 chs. dist. from the SW. closing cor. of sec. 6, R.11 W., hereinbefore described,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor. of sec. 6, T.10 S., R.11 W., only, with brass cap mkd.

$$\frac{1}{4} S 6$$

1937

No suitable accessory.

BOOK 4212

Subdivision of T.10 S., R.11 W.

Chains	<p>from the cor. of secs. 5, 6, 7 and 8, N.0°03'W., bet. secs. 5 and 6.</p>
	<p>Over nearly level land, thru scattered undergrowth.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	$\frac{1}{4}$
	$S 6 S 5$
	1937
	<p>No suitable accessory.</p>
64.70	<p>Old road, bears NW. and SE.</p>
70.47	<p>Intersect the 2nd Stan. Par. South.</p>
	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a quantity of broken glass deposited at the base, for closing cor. of secs. 5 and 6, with brass cap mkd.</p>
	$T 9 S R 11 W$
	$S 31$
	$S 6 S 5$
	$T 10 S R 11 W$
	$C C$
	1937
	<p>No suitable accessory.</p>
	<p>From the point of intersection, the standard cor. of T.9 S., Rs. 11 and 11$\frac{1}{2}$ W., bears West, 19.20 chs. dist., an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the official record.</p>
	<p>Land, nearly level.</p>
	<p>Soil, sandy loam; 2nd rate.</p>
	<p>Timber, none; undergrowth, greasewood and scrub mesquite.</p>
	<p>Final tests of the solar attachments.</p>
	<p>March 7, 1937, with Buff & Buff solar transit No. 16723, every 30 min. from 8:00 a.m. to 10:30 a.m., and from 1:30 p.m. to 4:00 p.m., the proper settings are made on the declination and latitude arcs; the resulting orientation of the instrument, when compared with the meridian established as hereinbefore described, has a maximum error of less than 1'30".</p>
	<p>March 7, 1937, with Young & Sons solar transit No. 8385, every 30 min. from 8:00 a.m. to 10:30 a.m., and from 1:30 p.m. to 4:00 p.m., the proper settings are made on the latitude and declination arcs; the resulting orientation of the instrument, when compared with the meridian established as hereinbefore described, has a maximum error of less than 1'30".</p>
	<p>March 7, 1937, with Young & Sons solar transit No. 8491, every 30 min. from 8:00 a.m. to 10:30 a.m., and from 1:30 p.m. to 4:00 p.m., the proper settings are made on the latitude and declination arcs; the resulting orientation of the instrument, when compared with the meridian establish-</p>

BOOK 4212

Subdivision of T.10 S., R.11 W.

Chains

ed as hereinbefore described, has a maximum error of less than 1'30".

General Description

The topography of Township 10 South, Range 11 West, is nearly level, except in sections 1, 2, and 12 which is partly mountainous.

The soil is generally sandy loam, 2nd rate, covered with a thin layer of drifting sand, except in the mountainous area, where it is of a malpais rock formation. The soil is suitable for agriculture provided water is supplied.

There is very little timber in the Township, and none suitable for commercial purposes. The undergrowth is greasewood and scrub mesquite with a scattering of cactus. There is no grazing land of any importance.

There is no permanent water supply in the Township, and very few washes, indicating an arid region. The area is so nearly level that the drainage varies. In general it is to the West. No indications of mineral deposits were noted. There are no settlers or improvements in the Township.

147
49

4-680
(Revised May 1934)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE**

4212

FIELD ASSISTANTS

NAMES	CAPACITY
I. B. Williams	Principal Assistant
Edmond R. Brenizer	"
H. R. Ruddell	"
John Crofford, Jr.	Chainman
Edmond R. Brenizer	"
Robert O. Jones	"
Fred D. Harris	"
Robert G. Burns	Moundman
Bob R. Alexander	"
James C. Bass	"
Elbert T. Mosley	"
Walter Fields	"
Gilbert M. Allred	Flagman
Robert O. Jones	"
James C. Bass	"
Melwood S. Mitchum	"
Robert G. Burns	Axeman
John Crofford, Jr.	"
Paul R. Ernst	"
Valdoran Burrow	"
Edmond R. Brenizer	"
Robert O. Jones	"
James C. Bass	"
Kenneth Poor	"
Fred D. Harris	"
H. R. Ruddell	"
Walter Fields	"

148
DOOR 4212

CERTIFICATE OF SURVEYOR

We, Horace M. Muscott, Public Land Surveyor, and Thornton Fitzhugh and Carroll I. Parkman, Transitmen, General Land Office, _____, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of November 1936, received from the district cadastral engineer for Arizona, _____, with assignment instructions dated Feb. 23, 1937, we have resurveyed the East boundary of Township 10 South, Range 12 West and surveyed the East and South boundaries and subdivisional lines of Township 10 South, Range 11 West,

_____ of the Gila and Salt River Meridian, in the State of Arizona, _____, which are represented in the foregoing field notes as having been executed by ^{US} me and under ^{OUR} my direction; and that said resurvey and survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Glendale, California, March 21, 1939. *Horace M. Muscott*
Public Land Surveyor
Phoenix, Ariz., April 3, 1939. *Thornton Fitzhugh*
Transitman
Phoenix, Arizona, April 3, 1939. *Carroll I. Parkman*
Transitman
General Land Office

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, AUG 26 1940, 1939.

The foregoing field notes of the ^{re} survey of the East boundary of Township 10 South, Range 12 West, and of the survey of the East, ~~aries~~ and subdivisional lines of Township 10 South, Range 11 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Horace M. Muscott, Public Land Surveyor, and Thornton Fitzhugh and Carroll I. Parkman, Transitmen, General Land Office, under special instructions dated November 20, 1936, and assignment instructions dated February 23, 1937, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the ^{resurvey and} survey therein described, are hereby approved.

William H. Johnson
Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

I ~~certify~~ that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys.