

Original

4-679  
(April 1933)

Doc. 4219

Book I.

# FIELD NOTES

OF THE SURVEY OF THE

South Boundary, West Boundary and Subdivision of

Township 10 South, Range 17 West

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Horace M. Muscott, Public Land Surveyor,

Thornton Fitzhugh, Transitman,

John Boggs, Transitman,

Benjamin J. Mollette, Transitman,

General Land Office.

Under special instructions dated November 20, 1936, which provided

for the surveys included under Group No. 218, bearing the approval of the

Commissioner of the General Land Office under date of December 18, 1936

and assignment instructions dated April 15 and February 23, 1937.

Survey commenced April 15, 1937.

Survey completed April 29, 1937.

4219

4219

160  
1A

BOOK 4219

## INDEX DIAGRAM.

*Township* 10 South, *Range* 17 West, G. & S.R. Mer.

		54	54	45	36	27	19
9		6	53 5	44 4	35 3	26 2	18 1
		53	52	43	34	26	17
9		7	52 8	42 9	33 10	25 11	17 12
		51	51	42	32	24	16
8		18	50 17	41 16	32 15	24 14	15 13
		50	49	40	31	23	14
8		19	48 20	39 21	30 22	22 23	13 24
		48	47	39	30	22	13
7		30	47 29	38 28	29 27	21 26	12 25
		46	46	37	28	20	11
6		31	45 32	36 33	27 34	19 35	10 36
		5	5	4	3	2	1

Beginning on April 15, 1937, the survey of the South and West Boundaries of T.10 S., R.17 W., was executed by Horace M. Muscott, Public Land Surveyor and Chief of Party, using Buff solar transit, No. 16723 of 1924 model. The survey of the subdivisional lines of the township was begun on April 16, 1937, and executed by Transistmen, Mollette, Boggs and Fitzhugh, using Buff transit No. 9984, Lietz transit No. 6166 and Young and Sons transit No. 8385, respectively. All instruments are equipped with solar attachments and were approved by the District Cadastral Engineer, on February 23, 1937, conditional upon satisfactory field tests.

The azimuth at point of beginning the survey, was determined with the solar, and the survey then extended by the transit method using fore and back sights and deflection angles. However the azimuths were checked at frequent intervals with the solar attachments.

The measurements were made with Lallie steel tapes, 5 chs. in length, graduated every link for the first 100 lks. and the balance at intervals of ten lks. The tapes were all tested by comparison with a Lufkin standard and found correct. Measurements were made on the slope and the vertical angle of each interval determined with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The data furnished with the special instructions gives the geographic position of the SE. cor. of the township as follows: latitude 32°30'35"N., and longitude 113°57'40"W.

At camp, near the 1/4 sec. cor. of secs. 24 and 25, T.8 S. R.15 W., which is about 1 1/2 miles south of the town of Mohawk, Arizona, an observation was made on Polaris for determination of a Meridian, on March 9, as described in the field notes of the survey of T.10 S., R.15 W., under this group. An observation was also made on Polaris for verification of latitude.

April 18: Every 30 min. from 7 to 10:30 a.m. and from 1:30 to 5 p.m., we make proper settings on the arcs of the solar attachments, and ascertain that the resulting orientation of the instruments, when compared with the meridian established by Polaris observation, has a maximum error of less than 1'30".

Other tests were made at frequent intervals throughout the survey.

South Boundary of T.10 S., R.17 W.

From the cor. of Ts.10 S., Rs.16 and 17 W., described in the field notes of the survey of the S. bdy. of T.10 S., R.16 W., under this group,

West, along the S. bdy. of sec. 36, on a transit line describing the tangent.

Over nearly level land, through dense palo verde and iron wood.

31.70 Road, bears N.40°E. and S.40°W.

36.30 Wash, 20 lks. wide, 4 ft. deep, course N.40°E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor. of sec. 36 only, with brass cap mkd.

1/4 S 36  
1937

from which

BOOK 4219

## South Boundary of T.10 S., R.17 W.

Chains	<p>A palo verde, 8 ins. diam., bears N.30<math>\frac{1}{2}</math>°E., 188 lks. dist., mkd. <math>\frac{1}{4}</math> S 36 B T</p> <p>A palo verde, 6 ins. diam., bears N.36°W., 57 lks. dist., mkd. <math>\frac{1}{4}</math> S 36 B T</p>
61.30	Leave flat and asc. 464 ft. over broken NE. slope of the Copper Mts.
80.00	<p>N. 1 lk. from the tangent,</p> <p>The true point for cor. of secs. 35 and 36, falls on rocky spur, sloping NE., a place where it is impracticable to establish the cor. monument.</p> <p>Land, E. part, nearly level wash land; W. part, mountainous. Soil, rocky, 4th. rate. Timber, palo verde and ironwood, on the flat. Undergrowth, none.</p>
	<p>West, along the S. bdy. of sec. 35, on a transit line describing the tangent, which bears S.89°59.4'W.</p> <p>Desc. 39 ft. to</p>
.14	<p>N. 1 lk. from the tangent,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., on surface rock supported in a mound of stone, 4 ft. base to top of post, wit. cor. of secs. 35 and 36 only, with brass cap mkd.</p> <p style="text-align: center;">T10S R17W S 35   S 36 WC ----- 1937</p> <p>Cor. stands in draw, course NE.</p> <p>Asc. broken NE. slope.</p>
.54	Spur, slopes NW.; desc. 35 ft. over broken NE. slope.
1.73	Drain, course NE.; asc. 240 ft. over NE. slope.
7.70	Spur, slopes SE.; asc. 225 ft. over NE. slope.
15.62	Spur, slopes NW.; pole on Coyote Peak, bears N.79°36'W. Desc. 150 ft. over broken NW. slope.
23.75	Spur, slopes NW.; desc. 280 ft. over broken NW. slope.
29.20	Canyon, course NW.
34.80	Asc. 30 ft. over NE. slope.
37.40	Trail to mine camp, bears SE. and NW.
38.00	Spur, slopes NW.; desc. 27 ft. over broken NW. slope.
40.00	<p>N. 1 lk. from the tangent,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bed rock, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor. of sec. 35 only, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 35 ----- 1937</p> <p>Cor. stands in draw, course NE.</p>

Chains Asc. 230 ft. over broken NE. slope.

49.43 Rooky spur, trends NE.; desc. 115 ft. over broken NW. slope.

55.35 Asc. 53 ft. over NE. slope.

60.00 Spur, slopes NE.; desc. 95 ft. over NW. slope.

62.00 Draw, course NE.; asc. NE. slope.

65.00 Spur, slopes NE.; old mine buildings, bear N. about 7½ chs. dist. Desc. 200 ft. over NW. slope.

71.40 Mine road, bears NW. 2½ chs. to the Betty Lee Mine, and SE. to the Wellton road.

71.90 Canyon wash, course NE.; asc. 300 ft. over SE. slope.

76.24 The head frame of the Betty Lee Mine, bears S., about 2 chs. dist.

79.12 A boulder, 30 ft. long, 10 ft. high.

80.00 3 lks. N. from the tangent,  
Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bed rock, and in a mound of stone, for cor. of secs. 34 and 35 only, with brass cap mkd.

T10S R17W  
S 34 | S 35

1937

Land, mountainous.  
Soil, rocky, 4th. rate.  
Undergrowth, cactus.  
No timber.

West, along the S. bdy. of sec. 34, on a transit line describing the tangent, which bears S. 89° 58.9' W.

Asc. 120 ft. over cliffs, bearing N. and S.

3.30 Spur, slopes NE.; desc. 75 ft. over NW. slope.

9.00 Canyon wash, 1 ch. wide, 35 ft. deep, course NE.; asc. 240 ft. over broken NE. slope.

17.40 Spur, slopes NE.; desc. 40 ft. over NW. slope.

24.00 Canyon wash, 80 ft. deep, course NE.

25.00 Spur, slopes NE.

28.00 Canyon wash, 100 ft. deep, course NE.; asc. 530 ft. over E. slope.

40.00 North 4 lks. from the tangent,  
Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bed rock, and in a mound of stone, for ¼ sec. cor. with brass cap mkd.

¼ S 34

1937

Asc. 60 ft. over NE. slope.

B000 4219

## South Boundary of T.10 S., R.17 W.

Chains					
41.74	Main ridge, bears SE. and NW.; pole on Coyote Peak bears N.15½°W. Desc. 456 ft. over broken SW. slope.				
50.20	Canyon wash, course SW.; asc. 130 ft. over broken SE. slope				
60.25	Spur, slopes SW. ; desc. 400 ft. over broken SW. slope.				
69.30	Canyon wash, course SW.;				
70.20	Desc. 150 ft. over broken land.				
79.60	Spur, slopes SW.				
80.00	N. 6 lks. from the tangent,				
	Set an iron post, 3 ft. long, 2 ins. diam., on surface rock supported in a mound of stone, for cor. of secs. 33 and 34 only, with brass cap mkd.				
	<table border="1"> <tr> <td>T10S R17W</td> <td></td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table>	T10S R17W		S 33	S 34
T10S R17W					
S 33	S 34				
	1937				
	Land, mountainous. Soil, rocky, 4th. rate. Undergrowth, cactus. No timber.				
	West, along the S. bdy. of sec. 33, on a transit line describing the tangent, which bears S.89°58.3'W.				
	Desc. 715 ft. over broken SW. slope.				
35.00	Foot of mountains, bearing SE. and NW. Thence desc. gradually over wash land.				
40.00	N. 8 lks. from the tangent,				
	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bed rock, and in a mound of stone, for ¼ sec. cor. of sec. 33 only, with brass cap mkd.				
	<table border="1"> <tr> <td>¼ S 33</td> <td></td> </tr> </table>	¼ S 33			
¼ S 33					
	1937				
54.50	Wash, 20 lks. wide, 4 ft. deep, course SW.; asc. gradually.				
61.15	Spur, slopes SW.; desc. 63 ft. over W. slope.				
70.00	Leave wash land and asc. 170 ft. over E. slope.				
76.00	Spur, slopes S.; desc. 50 ft.				
78.00	Draw; course S.; asc. 80 ft.				
80.00	N. 10 lks. from the tangent,				
	Set an iron post, 3 ft. long, 2 ins. diam., on surface rock, supported in a mound of stone, for cor. of secs. 32 and 33 only, with brass cap mkd.				
	<table border="1"> <tr> <td>T10S R17W</td> <td></td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table>	T10S R17W		S 32	S 33
T10S R17W					
S 32	S 33				
	1937				

South Boundary of T.10 S.,R.17 W.

Chains

Land, mountainous.  
Soil, rocky, 4th. rate.  
Timber, none.  
Undergrowth, none.

West, along the S. bdy. of sec. 32, on a transit line describing the tangent, which bears S.89°57.7'W.

Desc. 100 ft. over broken W. slope.

4.75 Spur, slopes S.; desc. 125 ft. over W. slope.

10.00 Wash, course S.; asc. E. slope.

16.00 Spur, slopes SW.; desc. 85 ft. over SW. slope.

20.00 Foot of mountains, bears N. and SE., thence over gentle NW. slope.

25.90 Wash, 10 lks. wide, 3 ft. deep, course NW.

39.80 Road, bears NW. to Wellton, and S.

40.00 N. 13 lks. from the tangent,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 32 only, with brass cap mkd.

$\frac{1}{4}$  S 32

1937

from which

A palo verde, 6 ins. diam., bears N.31°E., 227 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T

A palo verde, 6 ins. diam., bears N.66 $\frac{1}{2}$ °W., 103 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T

80.00 N. 16 lks. from the tangent,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 31 and 32 only, with brass cap mkd.

T10S R17W

S 31 | S 32

1937

from which

An ironwood, 6 ins. diam., bears N.31°E., 170 lks. dist., mkd. T 10 S R 17 W S 32 B T

An ironwood, 6 ins. diam., bears N.66°W., 267 lks. dist., mkd. T 10 S R 17 W S 31 B T

Land, E. 20 chs., mountainous, balance, nearly level.  
Soil, rocky and sandy, 4th. rate and 2nd. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood and sage.

West, along the S. bdy. of sec. 31, on a transit line describing the tangent, which bears S.89°57.2'W.

Over nearly level land, draining NW.

40.00 N. 20 lks. from the tangent,

## South Boundary of T.10 S.,R.17 W.

Chains	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor. with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1937</p> <p style="text-align: right;">from which</p> <p>A palo verde, 6 ins. diam., bears N.71<math>\frac{1}{2}</math>°E., 272 lks. dist., mkd. <math>\frac{1}{4}</math> S 31 B T</p> <p>A palo verde, 6 ins. diam., bears N.36<math>\frac{1}{2}</math>°W., 350 lks. dist., mkd. <math>\frac{1}{4}</math> S 31 B T</p>
77.70	<p>N. 24 lks. from the tangent,</p> <p>Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Ts.10 S.,Rs.17 and 18 W., with brass cap mkd.</p> <p style="text-align: center;">T 10 S R18W R17W S 36   S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1937</p> <p style="text-align: right;">from which</p> <p>A palo verde, 7 ins. diam., bears N.14<math>\frac{3}{4}</math>°E., 369 lks. dist., mkd. T 10 S R 17 W S 31 B T</p> <p>A palo verde, 4 ins. diam., bears N.3<math>\frac{1}{4}</math>°W., 451 lks. dist., mkd. T 10 S R 18 W S 36 B T</p> <p>Land, nearly level. Soil, sandy loam, 2nd. rate. Timber, scattering ironwood and palo verde. Undergrowth, greasewood and sage.</p>
West Boundary of T.10 S.,R.17 W.	
	<p>From the cor. of Ts. 10 S.,Rs.17 and 18 W., described above,</p> <p>North, bet. secs. 31 and 36.</p> <p>Over nearly level desert land, draining NW.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor. with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 36   S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1937</p> <p style="text-align: right;">from which</p> <p>An ironwood, 6 ins. diam., bears N.24°E., 290 lks. dist., mkd. <math>\frac{1}{4}</math> S 31 B T</p> <p>An ironwood, 6 ins. diam., bears N.5<math>\frac{1}{2}</math>°W., 258 lks. dist., mkd. <math>\frac{1}{4}</math> S 36 B T</p>
80.00	<p>Set an iron post; 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R18W R17W S 25   S 30</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 36   S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1937</p>



Chains

from which

An ironwood, 6 ins. diam., bears N.42 $\frac{3}{4}$ °E., 545 lks.  
dist., mkd. T 10 S R 17 W S 30 B T

An ironwood, 6 ins. diam., bears S.18°E., 219 lks.  
dist., mkd. T 10 S R 17 W S 31 B T

An ironwood, 8 ins. diam., bears S.65 $\frac{3}{4}$ °W., 227 lks.  
dist., mkd. T 10 S R 18 W S 36 B T

A palo verde, 6 ins. diam., bears N.19°W., 376 lks.  
dist., mkd. T 10 S R 18 W S 25 B T

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering ironwood and palo verde.  
Undergrowth, greasewood, sage and cacti.

North, bet. secs. 25 and 30.

Over nearly level land, draining NW.

37.00 Wash, 120 lks. wide, 1 $\frac{1}{2}$  ft. deep, course N.20°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
S 25 | S 30  
1937

from which

An ironwood, 10 ins. diam., bears S.15°E., 276 lks.  
dist., mkd.  $\frac{1}{4}$  S 30 B T

An ironwood, 6 ins. diam., bears N.46 $\frac{3}{4}$ °W., 239 lks.  
dist., mkd.  $\frac{1}{4}$  S 25 B T

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the  
ground, for cor. of secs. 19, 24, 25 and 30, with brass  
cap mkd.

T 10 S  
R18W | R17W  
S 24 | S 19  
S 25 | S 30  
1937

from which

An ironwood, 8 ins. diam., bears N.18 $\frac{1}{2}$ °E., 291 lks.  
dist., mkd. T 10 S R 17 W S 19 B T

A palo verde, 7 ins. diam., bears S.31°E., 482 lks.  
dist., mkd. T 10 S R 17 W S 30 B T

A palo verde, 6 ins. diam., bears S.30 $\frac{1}{2}$ °W., 325 lks.  
dist., mkd. T 10 S R 18 W S 25 B T

A palo verde, 6 ins. diam., bears N.77 $\frac{1}{2}$ °W., 174 lks.  
dist., mkd. T 10 S R 18 W S 24 B T

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering ironwood and palo verde.  
Undergrowth, greasewood, sage and cacti.

West Boundary of T.10 S.,R.17 W.

Chains North, bet. secs. 19 and 24.  
 Over nearly level land, draining NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
 S 24 | S 19  
 1937

from which

A palo verde, 6 ins. diam., bears S.  $1\frac{1}{4}^{\circ}$  E., 89 lks. dist., mkd.  $\frac{1}{4}$  S 19 B T

A palo verde, 6 ins. diam., bears N.  $51^{\circ}$  W., 49 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T

41.10 Road, bears NW. to Wellton and southerly.

60.99 A bench mark of the U.S. Geological Survey, bears West, 6.47 chs. dist.; a concrete post, 5 ins. sq., 10 ins. above ground, with brass tablet in top, mkd. 3 M 1925 Elevation above sea level 624 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

T 10 S  
 R18W | R17W  
 S 13 | S 18  
 S 24 | S 19  
 1937

from which

A palo verde, 6 ins. diam., bears N.  $63^{\circ}$  E., 365 lks. dist., mkd. T 10 S R 17 W S 18 B T

A palo verde, 6 ins. diam., bears S.  $29^{\circ}$  E., 540 lks. dist., mkd. T 10 S R 17 W S 19 B T

A palo verde, 6 ins. diam., bears S.  $2\frac{1}{4}^{\circ}$  W., 268 lks. dist., mkd. T 10 S R 18 W S 24 B T

No tree near NW.

Land, nearly level.  
 Soil, sandy loam, 2nd. rate.  
 Timber, scattering palo verde and ironwood.  
 Undergrowth, greasewood, sage and cacti.

North, bet. secs. 13 and 18.  
 Over nearly level land, draining NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 13 | S 18  
 1937

from which

A palo verde, 6 ins. diam., bears N.  $9\frac{1}{2}^{\circ}$  E., 228 lks. dist., mkd.  $\frac{1}{4}$  S 18 B T

West Boundary of T.10 S.,R.17 W.

4219

Chains

A palo verde, 6 ins. diam., bears S.32°W., 307 lks. dist., mkd.  $\frac{1}{4}$  S 13 B T

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at the base, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.

T 10 S	
R18W	R17W
S 12	S 7
S 13	S 18
1937	

No trees or stones near.

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood, sage and cacti.

North, bet. secs. 7 and 12.

Over nearly level land, draining NW.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at the base, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$	
S 12	S 7
1937	

No trees or stones near.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at the base, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T 10 S	
R18W	R17W
S 1	S 6
S 12	S 7
1937	

No trees or stones near.

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, none.  
Undergrowth, greasewood, sage and cacti.

North, bet. secs. 1 and 6.

Over nearly level land, draining NW.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at the base, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$	
S 1	S 6
1937	

No trees or stones near.

BOOK 4219

## West Boundary of T.10 S., R.17 W.

Chains  
55.40

Intersect the 2nd. standard parallel south.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with broken glass deposited at the base, for closing cor. of Ts.10 S., Rs.17 and 18 W., with brass cap mkd.

T9S R18W  
S 36  
-----  
S 1 | S 6  
R18W | R17W  
T10S  
C C  
1937

No trees or stones near.

From this point, the standard  $\frac{1}{4}$  sec. cor. of sec. 36, bears S.  $89^{\circ}54'W.$ , 42 lks. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.18 W., under this group.

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Undergrowth, greasewood, sage and cacti.  
No timber.

## Subdivision of T.10 S., R.17 W.

true point for  
From the cor. of secs. 35 and 36, on S. bdy. of Tp., here-  
inbefore described,

N.  $0^{\circ}01'W.$ , bet. secs. 35 and 36.

Desc. N. slope.

- 3.50 Canyon, course E.; asc. 175 ft. over S. slope.  
9.60 Spur, slopes E.; desc. 380 ft. over N. slope.  
18.25 Draw, course NE.  
22.70 Spur, slopes NE.; desc. 200 ft. over NW. slope.  
27.50 Foot of steep descent, bears E. and W.  
33.52 Road, bears W. to mine, and E.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
S 35 | S 36

1937

from which

A palo verde, 6 ins. diam., bears N.  $11\frac{1}{2}^{\circ}E.$ , 101 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T

An ironwood, 6 ins. diam., bears N.  $31^{\circ}W.$ , 153 lks. dist., mkd.  $\frac{1}{4}$  S 35 B T

- 43.85 Wash, 85 lks. wide, 3 ft. deep, course NE.  
53.10 Wash, 35 lks. wide, 2 ft. deep, course SE.; asc. 85 ft. over SW. slope.  
58.00 Spur, slopes SE.; desc. 60 ft. over NE. slope.

Subdivision of T.10 S., R.17 W.

- Chains
- 60.80 Draw, course SE.; asc. 210 ft. over broken SE. slope.
- 69.00 Spur, slopes N.70°E.; desc. 143 ft. over broken NW. slope.
- 76.10 Draw, 10 lks. wide, 4 ft. deep, course E.; asc. 90 ft. over SE. slope.
- 80.00 Set an iron post, 3 ft. long, .2 ins. diam., on surface rock with broken glass deposited at the base, and supported in a mound of stone, 4 ft. base, to top of post, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T10S R17W

S 26 | S 25

S 35 | S 36

1937

Land, mountainous.  
 Soil, rocky, 4th. rate.  
 Timber, scattering palo verde and ironwood.  
 Undergrowth, greasewood and cacti.

East, on a random line bet. secs. 25 and 36.

- 40.00 Set temp. 1/4 sec. cor.
- 80.06 A point 16 lks. S. of the cor. of secs. 25, 30, 31 and 36, on E. bdy. of Tp., described in the field notes of the W. bdy. of T.10 S., R.16 W., surveyed under this group.

Thence

S.89°53'W., on a true line bet. secs. 25 and 36.

Over wash land.

- 4.20 Leave washes, thence over nearly level land.
- 18.60 Asc. 100 ft. over NE. slope.
- 23.30 Top of ascent.
- 28.15 Asc. along broken N. slope.
- 36.30 Saddle in ridge, bearing NW. and E.
- 37.00 Desc. 80 ft. over SW. slope.
- 40.03 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, with glass deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

S 25

1/4

S 36

1937

Desc. 45 ft. over SW. slope.

- 47.50 Wash, 15 lks. wide, course SE.; asc. 70 ft. over E. slope.
- 50.90 Spur, slopes S.20°E.; desc. 75 ft. over SW. slope.
- 55.45 Wash, 10 lks. wide, course SE.; asc. 80 ft. over E. slope.
- 60.60 Spur, slopes S.; desc. 90 ft. over W. slope.
- 64.80 Wash, 15 lks. wide, 3 ft. deep, course SE.; asc. 90 ft.

BOOK 4219

Subdivision of T.10 S., R.17 W.

Chains	over NE. slope.
68.70	Spur, slopes SE.; desc. 45 ft. over W. slope.
71.00	Asc. 145 ft. over broken SE. slope.
80.06	The cor. of secs. 25, 26, 35 and 36.
	Land, mountainous.
	Soil, rocky, 4th. rate.
	Timber, ironwood and palo verde.
	Undergrowth, greasewood and cacti.
<hr/>	
	N.0°01'W., bet. secs. 25 and 26.
	Asc. 50 ft. over SE. slope.
5.00	Ridge, bears SW. and E. 2 chs. thence NE.; desc. 160 ft. over broken NE. slope.
9.30	Head of draw, course N.10°W.; along W. slope.
21.00	Spur, slopes NW.; desc. 130 ft. over NE. slope.
25.70	Foot of steep descent, thence over rolling land.
31.20	Wash, 50 lks. wide, 10 ft. deep, course NE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bed rock, with glass deposited at the base, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 26   S 25 1937
	raise a mound of
	stone around post.
50.40	Wash, 50 lks. wide, 10 ft. deep, course E., at junction with another wash from SW.
54.50	Asc. 135 ft. over broken S. slope.
62.40	Ridge, bears E. and W.; desc. 115 ft. over broken N. slope.
74.35	Wash, 1 ch. wide, 10 ft. deep, course W.
76.30	Asc. 90 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., on bed rock, with glass deposited at the base, and supported in a mound of stone, 6 ft. base, 2½ ft. high, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.
	T10S R17W S 23   S 24 S 26   S 25 1937
	Land; mountainous:
	Soil, rocky, 4th. rate.
	Timber, ironwood and palo verde.
	Undergrowth, greasewood, cacti and sage.

## Subdivision of T.10 S., R.17 W.

Chains	N.89°53'E., on a random line bet, secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.06	A point 6 lks. N. of the cor. of secs. 19, 24, 25 and 30, on E. bdy. of Tp., described in the field notes of the W. bdy. of T.10 S., R.16 W., surveyed under this group.
	Thence
	S.89°56'W., on a true line bet. secs. 24 and 25.
	Asc. 215 ft. over broken SE. slope.
1.00	Short spur, slopes S.; continue ascent.
8.85	Spur, slopes S.; desc. 130 ft. over SW. slope.
15.75	Gulch, 40 lks. wide, 7 ft. deep, course SE.; asc. 310 ft. over NE. slope.
27.35	Spur, slopes SE.; desc. 47 ft.
29.00	Asc. 34 ft.
33.00	Spur, slopes S.; desc. 144 ft. over broken SW. slope.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	S 24 — S 25 1937
40.25	Gulch, 15 lks. wide, 5 ft. deep, course SE.; asc. 40 ft. over SE. slope.
41.50	Spur, slopes SE.; desc. 85 ft. over SW. slope.
46.75	Gulch, course SE.; asc. 35 ft.
48.00	Spur, slopes SE.; desc. 125 ft. over SW. slope.
57.00	Gulch, 20 lks. wide, 8 ft. deep, course SW.; asc. 55 ft. over SE. slope.
59.40	Spur, slopes SW.; desc. 85 ft. over NW. slope.
63.85	Gulch, 10 lks. wide, course SW.; asc. 66 ft. over SE. slope.
70.00	Along S. slope.
78.80	Desc. 25 ft. to
80.06	The cor. of secs. 23, 24, 25 and 26.
	Land, mountainous. Soil, rocky, 4th. rate. Timber, palo verde and ironwood. Undergrowth, greasewood and cactus.
	N.0°01'W., bet. secs. 23 and 24.
	Asc. 6 ft. over SW. slope.
.25	Spur, slopes N.70°W.; desc. 100 ft. over NE. slope.
6.00	Base of hill, bears SE. and NW.; over rolling land.

Chains	
10.40	Wash, 15 lks. wide, 6 ft. deep, course NW.
19.50	Wash, 160 lks. wide, 10 ft. deep, course NE.
27.50	Asc. 37 ft. over SE. slope.
30.70	Toe of spur, slopes E.; desc. NE. slope.
37.80	Gulch, 5 lks. wide, 3 ft. deep, course SE.; asc. SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., on bed rock, with glass deposited at the base, and supported in a mound of stone, 6 ft. base, 2½ ft. high, for ¼ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 23   S 24 1937
	Asc. 90 ft. over SW. slope.
43.90	Spur, slopes SE.; along broken E. slope.
49.00	Desc. 30 ft. to
51.90	Head of draw, course SE.; asc. 160 ft. over SE. slope.
59.80	Ridge, bears N.70°E. and SW.; desc. 140 ft. over N. slope.
63.30	Head of draw, course NW.; desc. 80 ft. along NW. slope.
74.15	Asc. 45 ft.
75.00	Spur, slopes NW.; desc. 70 ft.
78.00	Gulch, 30 lks. wide, course NW.; along W. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bed rock, with glass deposited at the base, and in a mound of stone, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.
	T10S R17W S 14   S 13 S 23   S 24 1937
	Land, mountainous. Soil, rocky, 4th. rate. Timber, ironwood and palo verde. Undergrowth, greasewood and cacti.
	N.89°56'E., on a random line bet. secs. 13 and 24.
40.00	Set temp. ¼ sec. cor.
80.10	A point 2 lks. N. of the cor. of secs. 13, 18, 19 and 24, on E. bdy. of Tp., described in the field notes of the W. bdy. of T.10 S., R.16 W., surveyed under this group.
	Thence
	S.89°57'W., on a true line bet. secs. 13 and 24.
	Asc. 64 ft. over E. slope.
3.60	Spur, slopes SE.; along S. slope.



Subdivision of T.10 S., R.17 W.

Chains	
6.20	Spur, slopes S.; desc. 180 ft. over W. slope.
11.85	Draw, 10 lks. wide, course S.; asc. 160 ft. over E. slope.
16.00	Spur, slopes S.; desc. 37 ft.
18.50	Along broken S. slope.
24.30	Desc. 105 ft. over SW. slope.
34.05	Gulch, 20 lks. wide, 4 ft. deep, course SE.; asc. 170 ft. over NE. slope.
40.00	Spur, slopes SE.
40.05	Set an iron post, 3 ft. long, 1 in. diam., on bed rock, with glass deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 13 <hr style="width: 50px; margin: auto;"/> S 24 1937
40.80	Desc. 118 ft. over broken SW. slope.
45.60	Gulch, 13 lks. wide, 4 ft. deep, course SE.; asc. 350 ft. over SE. slope.
59.00	Ridge, bears NE. and SW.; desc. 140 ft. over NW. slope.
64.50	Head of draw, course NW.; along N. slope.
67.20	Desc. 118 ft. over NW. slope.
71.80	Gulch, 10 lks. wide, course NW.
76.35	Desc. 86 ft. over NW. slope.
80.10	The cor. of secs. 13, 14, 23 and 24.
	Land, mountainous. Soil, rocky, 4th. rate. Undergrowth, greasewood and cacti. No timber.
	N.0°01'W., bet. secs. 13 and 14.
	Asc. 30 ft. over SW. slope.
2.75	Spur, slopes NW.; desc. 85 ft. over NE. slope.
7.50	Gulch, 15 lks. wide, course NW.
13.10	Head of draw, course W.; asc. 55 ft. over S. slope.
16.50	Top of hill; desc. 97 ft. over N. slope.
26.40	Leave mountains, bearing NE. and SW., thence over gently rolling land, draining N.
39.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for witness $\frac{1}{4}$ sec. cor. with brass cap mkd.
	W C $\frac{1}{4}$ S 14   S 13 1937

BOOK 4219

## Subdivision of T.10 S., R.17 W.

- Chains  
 40.00 The true point for  $\frac{1}{4}$  sec. cor. falls in wash, 15 lks. wide  
 3 ft. deep, course NW.  
 62.60 Wash, 1 ch. wide, 4 ft. deep, course NE.  
 67.75 Same wash, course NW.  
 77.30 Same wash, course NE.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the  
 ground, with glass deposited at the base, for cor. of  
 secs. 11, 12, 13 and 14, with brass cap mkd.

T10S R17W

S 11 | S 12

S 14 | S 13

1937

from which

An ironwood, 8 ins. diam., bears N.  $49\frac{1}{4}^{\circ}$  E., 109 lks.  
 dist., mkd. T 10 S R 17 W S 12 B T

An ironwood, 9 ins. diam., bears S.  $33^{\circ}$  E., 101 lks.  
 dist., mkd. T 10 S R 17 W S 13 B T

An ironwood, 12 ins. diam., bears S.  $25\frac{1}{4}^{\circ}$  W., 265 lks.  
 dist., mkd. T 10 S R 17 W S 14 B T

A palo verde, 8 ins. diam., bears N.  $27\frac{3}{4}^{\circ}$  W., 326 lks.  
 dist., mkd. T 10 S R 17 W S 11 B T

Land, S. half; mountainous; N. half, gently rolling.  
 Soil, rocky, 3rd. and 4th. rate.  
 Timber, scattering ironwood and palo verde.  
 Undergrowth, greasewood and caoti.

N.  $89^{\circ}57'$  E., on a random line bet. secs. 12 and 13.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.

- 80.08 A point 5 lks. N. of the cor. of secs. 7, 12, 13 and 18,  
 on E. bdy. of Tp., described in the field notes of the W.  
 bdy. of T.10 S., R.16 W., surveyed under this group.

Thence

S.  $89^{\circ}59'$  W., on a true line bet. secs. 12 and 13.

Over gently rolling land, crossing a series of washes,  
 course N.

- 8.00 Leave washes.  
 12.50 Leave rolling land and asc. 275 ft. over broken E. slope.  
 25.90 Spur, slopes SE.; desc. 16 ft. to  
 27.70 Ridge, bears N. and S.; desc. 260 ft. over NW. slope.  
 40.04 Set an iron post, 3 ft. long, 1 in. diam., on bed rock,  
 and in a mound of stone, 5 ft. base,  $2\frac{1}{2}$  ft. high, for  $\frac{1}{4}$   
 sec. cor. with brass cap mkd.

S 12

 $\frac{1}{4}$ 

S 13

1937

## Subdivision of T.10 S., R.17 W.

Chains Desc. 34 ft. over NW. slope.  
 45.00 Foot of slope, bears NE. and SW.; thence over gently rolling land.  
 77.10 Wash, 50 lks. wide, 3 ft. deep, course NW.  
 78.90 Wash, 40 lks. wide, 3 ft. deep, course N.  
 80.08 The cor. of secs. 11, 12, 13 and 14.

Land, partly, mountainous; partly gently rolling.  
 Soil, rocky, 2nd. and 3rd. rate.  
 Timber, ironwood and palo verde.  
 Undergrowth, greasewood and cacti.

N.0°01'W., bet. secs. 11 and 12.

Over nearly level land.

19.80 Wash, 60 lks. wide; 4 ft. deep, course NW.

38.00 Wash, 60 lks. wide; 4 ft. deep; course NW.

40.00 Set an iron post, 3 ft. long; 1 in. diam., 14 ins. in the ground to bed rock, and in a mound of stone, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
 S 11 | S 12  
 1937

from which

A palo verde, 5 ins. diam., bears N.66 $\frac{1}{2}$ °E.  
 mkd.  $\frac{1}{4}$  S 12 B T

An ironwood, 7 ins. diam., bears S.72 $\frac{1}{2}$ °W.,  
 mkd.  $\frac{1}{4}$  S 11 B T

60.20 Wash, course NE. (Same wash as at 19.80 chs.)

71.10 Wash, 1 ch. wide, 4 ft. deep, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with glass deposited at the base, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

T10S R17W  
 S 2 | S 1  
 S 11 | S 12  
 1937

from which

A palo verde, 6 ins. diam., bears S.17°E., 222 lks. dist., mkd. T 10 S R 17 W S 12 B T

A palo verde, 8 ins. diam., bears S.83°W., 230 lks. dist., mkd. T 10 S R 17 W S 11 B T

Land, nearly level.  
 Soil, sandy and rocky, 3rd. rate.  
 Timber, scattering palo verde and ironwood.  
 Undergrowth, greasewood and cacti.

N.89°59'E., on a random line bet. secs. 1 and 12.

## Subdivision of T.10 S., R.17 W.

Chains							
40.00	Set temp. $\frac{1}{4}$ sec. cor.						
80.06	A point 4 lks. S. of the cor. of secs. 1, 6, 7 and 12, on E. bdy. of Tp., described in the field notes of the W. bdy. of T.10 S., R.16 W., surveyed under this group.						
	Thence						
	S. $89^{\circ}57'W.$ , on a true line bet. secs. 1 and 12.						
	Over nearly level land.						
8.50	Dim road, bears SE. and NW.						
10.90	Road, bears N. to Wellton and S. to Mine.						
13.50	Wash, 80 lks. wide, 3 ft. deep, course N.; asc. gradually.						
23.00	Asc. 156 ft. over broken E. slope.						
31.60	Ridge, bears N. and S.; desc. 240 ft. over NW. slope.						
40.03	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for $\frac{1}{4}$ sec. cor. with brass cap mkd.						
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 1</td></tr> <tr><td>—</td></tr> <tr><td>S 12</td></tr> <tr><td>1937</td></tr> </table>	S 1	—	S 12	1937		
S 1							
—							
S 12							
1937							
	Foot of hills, bear N. and S.; over rolling land.						
45.00	Head of draw, course N.; asc. 30 ft. over gradual E. slope.						
50.15	Top of ascent; desc. 7 ft. over SW. slope.						
71.15	Wash, 150 lks. wide, 4 ft. deep, course N.						
80.06	The cor. of secs. 1, 2, 11 and 12.						
	Land, rolling and mountainous. Soil, rocky, 3rd. and 4th. rate. Timber, ironwood and palo verde. Undergrowth, greasewood and cacti.						
	N. $0^{\circ}01'W.$ , bet. secs. 1 and 2.						
	Over nearly level land.						
35.20	Wash, 6 lks. wide, 2 ft. deep, course NW.						
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.						
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 2</td><td> </td><td>S 1</td></tr> <tr><td colspan="3">1937</td></tr> </table>	S 2		S 1	1937		
S 2		S 1					
1937							
	from which						
	A palo verde, 12 ins. diam., bears S. $83\frac{1}{4}^{\circ}E.$ , 206 lks. dist., mkd. $\frac{1}{4}$ S 1 B T						
	A palo verde, 8 ins. diam., bears S. $42\frac{1}{2}^{\circ}W.$ , 181 lks. dist., mkd. $\frac{1}{4}$ S 2 B T						
46.00	Wash, 1 ch. wide, 5 ft. deep, course NW.						

## Subdivision of T.10 S., R.17 W.

Chains  
57.40

Intersect the 2nd. standard parallel south.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.

T9S R17W  
S 35S 2 | S 1  
T10S R17W  
C C  
1937

from which

A palo verde, 4 ins. diam., bears S.  $71\frac{1}{4}^{\circ}$  E., 120 lks. dist., mkd. T 10 S R 17 W S 1 C C B TA palo verde, 8 ins. diam., bears S.  $29\frac{1}{4}^{\circ}$  W., 270 lks. dist., mkd. T 10 S R 17 W S 2 C C B TFrom this point, the standard  $\frac{1}{4}$  sec. cor. of sec. 35 bears N.  $89^{\circ}52'$  E., 3.46 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.17 W., under this group.Land, nearly level.  
Soil, sandy, 2nd. rate.  
Timber, scattering palo verde.  
Undergrowth, greasewood.

At the mid point of the N. bdy. of sec. 1,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 1, only, with brass cap mkd. $\frac{1}{4}$  S 1

1937

from which

A palo verde, 6 ins. diam., bears S.  $49\frac{1}{2}^{\circ}$  E., 210 lks. dist., mkd.  $\frac{1}{4}$  S 1 B TAn ironwood, 10 ins. diam., bears S.  $45\frac{1}{2}^{\circ}$  W., 284 lks. dist., mkd.  $\frac{1}{4}$  S 1 B TFrom this point, the standard cor. of secs. 35 and 36, bears N.  $89^{\circ}52'$  E., 3.82 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.17 W., under this group.

From the cor. of secs. 34 and 35, on S. bdy. of Tp., hereinafore described,

N.  $0^{\circ}01'$  W., bet. secs. 34 and 35.

Over mountainous land; asc. steep SE. slope 125 ft.

3.50 Spur, slopes NE.; desc. 500 ft. over NW. slope.

21.90 Canyon wash, 20 lks. wide, course NE.; asc. 280 ft. over SE. slope.

35.75 Spur, slopes E.; desc. 170 ft. over steep N. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

BOOK 4219

Subdivision of T.10 S., R.17 W.

	<p style="text-align: center;"> <math>\frac{1}{4}</math>            S 34   S 35            1937         </p> <p>Continue descent 240 ft. over N. slope.</p>
47.60	Canyon wash, 30 lks. wide, course E.; asc. 550 ft. over S. slope.
64.20	Spur, slopes E.; desc. 490 ft. over N. and NE. slopes.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.
	<p style="text-align: center;">           T10S R17W            S 27   S 26            S 34   S 35            1937         </p> <p>Land, rough mountains.          Soil, rocky, 4th. rate.          Timber, scattering palo verde and ironwood.          Undergrowth, greasewood and cactus.</p>
	<p>East, on a random line bet. secs. 26 and 35.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.88	A point 4 lks. S. of the cor. of secs. 25, 26, 35 and 36.
	<p>Thence</p> <p>S.89°58'W., on a true line bet. secs. 26 and 35.</p> <p>Asc. 85 ft. over SE. slope.</p>
4.00	Ridge, bears NE. and SW.; desc. 136 ft. over SW. slope.
13.00	Canyon wash, 20 lks. wide, course NW.; asc. 265 ft. over NE. slope.
22.15	Same ridge as above, bears SE. and NW.; desc. 230 ft. over SW. slope.
25.50	Wash, 5 lks. wide, course S.; asc. 120 ft. over SE. slope.
29.10	Same ridge, bears NE. and SW.; desc. 120 ft. over SW. slope.
35.40	Drain, 10 lks. wide, course NW.; asc. 58 ft. to
39.94	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bed rock, and in a mound of stone, 4 ft. base to top of post, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	<p style="text-align: center;"> <math>\frac{1}{4}</math>            S 26            S 35            1937         </p> <p>Asc. 110 ft. over NE. slope.</p>
42.50	Spur, slopes N.; desc. 70 ft. over NW. slope.

Subdivision of T.10 S., R.17 W.

Chains	
45.40	Drain, course NE.; asc. 130 ft. over NE. slope.
50.55	Spur, slopes N.; desc. 225 ft. over W. slope.
56.20	Wash, 20 lks. wide, in bottom of canyon, course N.; asc. 160 ft. over steep E. slope.
60.00	Ridge, bears N. and SW.; desc. 290 ft. over NW. and SW. slopes.
66.00	Slope changes from NW. to SW.; continue descent.
70.90	Wash, 20 lks. wide, course NE.; asc. 50 ft. over NE. slope.
79.88	The cor. of secs. 26, 27, 34 and 35. Land, mountainous. Soil, rocky, 4th. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood and cactus.
	N.0°01'W., bet. secs. 26 and 27. Desc. 164 ft. over NE. slope.
9.30	Wash, 50 lks. wide, 10 ft. deep, course NE.; asc. 135 ft. over steep SE. slope.
18.10	Along broken E. slope.
24.00	Desc. 190 ft. over NW. slope.
29.06	Wash, 10 lks. wide, course N.80°E.; asc. 250 ft. over steep SE. slope.
40.00	The true point for $\frac{1}{4}$ sec. cor. falls on face of cliff, where cor. monument can not be established.
40.70	Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone, for witness $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ S 27   S 26 W C 1937 Asc. SE. slope.
41.30	Spur, slopes NE.; desc. 475 ft. over NW. slope.
55.86	Wash, 20 lks. wide, 3 ft. deep, course NE.
59.10	Same wash, course NW.
63.60	Asc. 30 ft. over S. slope.
72.65	Desc. 63 ft. over N. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd. T10S R17W S 22   S 23 S 27   S 26 1937 from which

BOOK 4219

Subdivision of T.10 S., R.17 W.

Chains	<p>A palo verde, 8 ins. diam., bears N.85<math>\frac{3}{4}</math>°E., 215 lks. dist., mkd. T 10 S R 17 W S 23 B T</p> <p>A palo verde, 10 ins. diam., bears S.84°W., 293 lks. dist., mkd. T 10 S R 17 W S 27 B T</p> <p>Land, mountainous, and rolling. Soil, rocky, 3rd. and 4th. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood, sage and cacti.</p>
	<p>N.89°58'E., on a random line bet. secs. 23 and 26.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.84	A point 19 lks. N. of the cor. of secs. 23, 24, 25 and 26.
	Thence
	N.89°54'W., on a true line bet. secs. 23 and 26.
	Desc. 85 ft. over SW. slope.
6.70	Wash, 40 lks. wide, 12 ft. deep, course NE.; asc. 110 ft. over E. slope.
15.80	Spur, slopes NE.; desc. 120 ft. over NW. slope.
22.00	Wash, 5 lks. wide, 8 ft. deep, course NE. ; asc. 90 ft. over NE. slope.
26.80	Spur, slopes NE.; desc. 150 ft. over NW. slope.
35.00	Foot of descent, thence over rolling land.
39.92	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 23</u> S 26 1937
	From this point, the SE. cor. of an old cabin, 10 x 10 ft., bears N.69 $\frac{3}{4}$ °E., 340 lks. dist.
79.84	The cor. of secs. 22, 23, 26 and 27.
	Land, hilly and rolling. Soil, gravelly, 3rd. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood, sage, catclaw and cacti.
	N.0°01'W., bet. secs. 22 and 23.
	Over rolling land.
5.70	Enter wash, 150 lks. wide, 4 ft. deep, course N. from SE.
17.45	Leave same, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 22   S 23 1937



## Subdivision of T.10 S., R.17 W.

Chains	from which						
	A palo verde, 6 ins. diam., bears S. $38\frac{1}{4}^{\circ}$ E., 184 lks. dist., mkd. $\frac{1}{4}$ S 23 B T						
	A palo verde, 6 ins. diam., bears S. $34\frac{1}{4}^{\circ}$ W., 17 lks. dist., mkd. $\frac{1}{4}$ S 22 B T						
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.						
	Asc. 60 ft. over rolling land.						
46.60	Top of ascent; desc. 70 ft.						
51.50	Foot of descent.						
54.50	Asc. gradually.						
58.60	Desc. 57 ft. over N. slope.						
63.50	Foot of descent.						
73.50	Wash, 20 lks. wide, 12 ft. deep, course NE.						
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.						
	<table border="1"> <tr> <td colspan="2">T10S R17W</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> </table>	T10S R17W		S 15	S 14	S 22	S 23
T10S R17W							
S 15	S 14						
S 22	S 23						
	1937						
	from which						
	A palo verde, 8 ins. diam., bears N. $17\frac{1}{2}^{\circ}$ E., 41 lks. dist., mkd. T 10 S R 17 W S 14 B T						
	A palo verde, 8 ins. diam., bears S. $39\frac{3}{4}^{\circ}$ W., 208 lks. dist., mkd. T 10 S R 17 W S 22 B T						
	No other trees near.						
	Land, rolling.						
	Soil, rocky, 3rd. rate.						
	Timber, scattering palo verde and ironwood.						
	Undergrowth, sage, greasewood and cacti.						
	S. $89^{\circ}54'E.$ , on a random line bet. secs. 14 and 23.						
40.00	Set temp. $\frac{1}{4}$ sec. cor.						
79.72	A point 12 lks. S. of the cor. of secs: 13, 14, 23 and 24.						
	Thence						
	N. $89^{\circ}59'W.$ , on a true line bet. secs. 14 and 23.						
	Desc. 85 ft. over W. slope.						
10.00	Foot of hills, bears NE. and SW., thence over rolling land.						
33.20	Wash; 50 lks. wide, 12 ft. deep, course N. $20^{\circ}E.$						
34.60	Dim road, bears N. and S.						
39.86	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.						

Chains	<p style="text-align: right;">S 14  <math>\frac{1}{4}</math>  S 23  1937</p> <p>73.95 Wash, 20 lks. wide, 12 ft. deep, course NE.</p> <p>79.72 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling.  Soil, rocky, 3rd. rate.  Undergrowth, greasewood, sage, catclaw and cacti.  Timber, scattering palo verde and ironwood.</p> <hr/> <p>N.0°01'W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: right;"><math>\frac{1}{4}</math>  S 15   S 14  1937  from which</p> <p>A palo verde, 6 ins. diam., bears S.73<math>\frac{1}{2}</math>°E., 62 lks.  dist., mkd. <math>\frac{1}{4}</math> S 14 B T</p> <p>A palo verde, 8 ins. diam., bears N.24<math>\frac{3}{4}</math>°W., 207 lks.  dist., mkd. <math>\frac{1}{4}</math> S 15 B T</p> <p>62.50 Gulch, course NE.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.</p> <p style="text-align: right;">T10S R17W  S 10   S 11  S 15   S 14  1937  from which</p> <p>A palo verde, 8 ins. diam., bears N.59<math>\frac{1}{4}</math>°E., 267 lks.  dist., mkd. T 10 S R 17 W S 11 B T</p> <p>A palo verde, 8 ins. diam., bears S.29<math>\frac{3}{4}</math>°E., 312 lks.  dist., mkd. T 10 S R 17 W S 14 B T</p> <p>An ironwood, 12 ins. diam., bears S.39<math>\frac{1}{2}</math>°W., 336 lks.  dist., mkd. T 10 S R 17 W S 15 B T</p> <p>A palo verde, 6 ins. diam., bears N.29°W., 321 lks.  dist., mkd. T 10 S R 17 W S 10 B T</p> <p>Land, rolling.  Soil, rocky, 3rd. rate.  Timber, scattering palo verde and ironwood.  Undergrowth, greasewood, sage and cacti.</p> <hr/> <p>S.89°59'E., on a random line bet. secs. 11 and 14.</p> <p>40.00 Set temp. <math>\frac{1}{4}</math> sec. cor.</p> <p>79.78 A point 2 lks. S. of the cor. of secs. 11, 12, 13 and 14.</p>
--------	---

Subdivision of T.10 S.,R.17 W.

219

Chains

Thence  
West, on a true line bet. secs. 11 and 14.  
Over rolling land.

5.90 Dim road, bears N.20°E. and S.20°W.

39.89 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.

S 11

S 14

1937

from which

A palo verde, 6 ins. diam., bears N.17 3/4°E., 165 lks. dist., mkd. 1/4 S 11 B T

An ironwood, 10 ins. diam., bears S.1°E., 219 lks. dist., mkd. 1/4 S 14 B T

54.70 Wash, 50 lks. wide, 12 ft. deep, course NW.

60.30 Wash, 50 lks. wide, 12 ft. deep, course NE.

79.78 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.  
Soil, rocky, 3rd. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood, sage, catclaw and cacti.

N.0°01'W., bet. secs. 10 and 11.

Over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bed rock, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

1/4

S 10 | S 11

1937

from which

A palo verde, 8 ins. diam., bears S.23 3/4°E., 278 lks. dist. mkd. 1/4 S 11 B T

A palo verde, 6 ins. diam., bears S.11 1/4°W., 198 lks. dist. mkd. 1/4 S 10 B T

Enter rolling hills; asc. 95 ft.

45.40 Desc. 90 ft. over NE. slope.

50.00 Continue over rolling hills.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., on surface rock, supported in a mound of stone, 5 ft. base, to top of post, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

T10S R17W

S 3 | S 2

S 10 | S 11

1937

from which

Subdivision of T.10 S., R.17 W.

Chains  
 A palo verde, 6 ins. diam., bears N.32 $\frac{1}{2}$ °E., 238 lks.  
 dist., mkd. T 10 S R 17 W S 2 B T  
 A palo verde, 6 ins. diam., bears S.47°E., 114 lks.  
 dist., mkd. T 10 S R 17 W S 11 B T  
 A palo verde, 6 ins. diam., bears S.51 $\frac{3}{4}$ °W., 103 lks.  
 dist., mkd. T 10 S R 17 W S 10 B T  
 A palo verde, 10 ins. diam., bears N.4 $\frac{3}{4}$ °W., 342 lks.  
 dist., mkd. T 10 S R 17 W S 3 B T

Land, rolling and hilly.  
 Soil, rocky, 3rd. rate.  
 Timber, scattering palo verde and ironwood.  
 Undergrowth, greasewood, sage and cacti.

East, on a random line bet. secs. 2 and 11.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.84 A point 10 lks. N. of the cor. of secs. 1, 2, 11 and 12.

Thence

N.89°56'W., on a true line bet. secs. 2 and 11.

Over rolling land.

12.00 Dim road, bears SE. and NW.

39.92 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bed rock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

S 2  
 $\frac{1}{4}$  ———  
 S 11  
 1937

from which

A palo verde, 6 ins. diam., bears N.47 $\frac{3}{4}$ °E., 229 lks.  
 dist., mkd.  $\frac{1}{4}$  S 2 B T

An ironwood, 10 ins. diam., bears S.87 $\frac{1}{4}$ °E., 320 lks.  
 dist., mkd.  $\frac{1}{4}$  S 11 B T

79.84 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.  
 Soil, rocky, 3rd. rate.  
 Timber, scattering palo verde and ironwood.  
 Undergrowth, greasewood, sage, catclaw and cacti.

N.0°01'W., bet. secs. 2 and 3.

Over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
 S 3 | S 2  
 1937

from which

## Subdivision of T.10 S., R.17 W.

## Chains

An ironwood, 10 ins. diam., bears S.  $80\frac{1}{2}^{\circ}$  E., 156 lks.  
dist., mkd.  $\frac{1}{4}$  S 2 B T

A palo verde, 10 ins. diam., bears S.  $42\frac{1}{2}^{\circ}$  W., 180 lks.  
dist., mkd.  $\frac{1}{4}$  S 3 B T

57.35 Intersect the 2nd. standard parallel south.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bed rock, and in a mound of stone to top, for closing cor. of secs. 2 and 3, with brass cap mkd.

T9S R17W

S 34

S 3 | S 2

T10S R17W

C C

1937

from which

A palo verde, 8 ins. diam., bears S.  $7\frac{3}{4}^{\circ}$  E., 92 lks.  
dist., mkd. T 10 S R 17 W S 2 C C B T

A palo verde, 6 ins. diam., bears S.  $69\frac{3}{4}^{\circ}$  W., 70 lks.  
dist., mkd T 10 S R 17 W S 3 C C B T

From this point, the standard  $\frac{1}{4}$  sec. cor. of sec. 34, bears N.  $89^{\circ}52'$  E., 2.46 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.17 W., under this group.

Land, rolling.

Soil, rocky, 3rd. rate.

Timber, scattering palo verde and ironwood.

Undergrowth, greasewood, sage and cacti.

At the midpoint of the N. bdy. of sec. 2,

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bed rock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. of sec. 2 only, with brass cap mkd.

$\frac{1}{4}$  S 2

1937

from which

A palo verde, 8 ins. diam., bears S.  $60\frac{3}{4}^{\circ}$  E., 194 lks.  
dist., mkd.  $\frac{1}{4}$  S 2 B T

A palo verde, 6 ins. diam., bears S.  $\frac{3}{4}^{\circ}$  E., 132 lks.  
dist., mkd.  $\frac{1}{4}$  S 2 B T

From this point, the standard cor. of secs. 34 and 35, bears N.  $89^{\circ}52'$  E., 2.96 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.17 W., under this group.

From the cor. of secs. 33 and 34, on S. bdy. of Tp. here-  
inbefore described,

N.  $0^{\circ}02'$  W., bet. secs. 33 and 34.

Asc. 695 ft. over broken SW. slope.

21.00. Top of ascent.

Subdivision of T.10 S., R.17 W.

Chains	
25.75	Ridge, bears SE. and NW., cross same in saddle. Desc. 75 ft. over NE. slope.
35.50	Foot of descent; asc. 20 ft. to . . . . .
40.00	The true point for $\frac{1}{4}$ sec. cor. falls in unsuitable place to establish monument.
	5 lks. E. of true point,
	Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone, 4 ft. base, to top of post, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{WC} \\ \text{S } 33 \mid \text{S } 34 \\ 1937 \end{array}$
	Asc. 14 ft. over face of boulder.
41.65	Spur, slopes NE.; desc. 730 ft. over steep N. slope.
61.96	Ravine, course W. Tank of water, 3 x 6 ft., 1 ft. deep, bears E., 50 lks. dist. Another tank, 8 ft. diam., 5 ft. deep, bears W., 20 lks. dist. Asc. 195 ft. over broken SW. slope.
77.80	Spur, slopes W.; desc. 45 ft. over steep NW. slope.
79.90	Head of small ravine, course SW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., on surface rock, supported in a mound of stone, 4 ft. base, to top of post, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.
	$\begin{array}{c} \text{T10S R17W} \\ \text{S } 28 \mid \text{S } 27 \\ \text{S } 33 \mid \text{S } 34 \\ 1937 \end{array}$
	Land, mountainous. Soil, rocky, 4th. rate. Timber, scattering palo verde. Undergrowth, greasewood, ocotillo and cacti.
	East, on a random line bet. secs. 27 and 34.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	A point 3 lks. S. of the cor. of secs. 26, 27, 34 and 35.
	Thence
	S. 89° 59' W., on a true line bet. secs. 27 and 34.
	Asc. 120 ft. over NE. slope.
9.60	Spur, slopes N.; desc. 115 ft. over NW. slope.
15.00	Wash, 20 lks. wide, course NE.; asc. 535 ft. over steep SE. slope.
31.40	Spur, slopes NE.; desc. 220 ft. over NW. slope.
39.70	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the

Subdivision of T.10 S.,R.17 W.

Chains ground to bed rock, and in a mound of stone to top, for witness 1/4 sec. cor., with brass cap mkd.

WC 1/4 S 27  
S 34  
1937

39.95 The true point for 1/4 sec. cor., falls on face of cliff, where monument can not be established.

Desc. 180 ft. over NW. slope.

53.10 Wash, 20 lks. wide, course NE.; asc. 340 ft. over SE. slope.

61.60 Spur, slopes NE.; desc. 124 ft. over NW. slope.

70.30 Ravine, course N.; asc. 140 ft. over NE. slope.

76.10 Spur, slopes NW.; desc. 210 ft. over W. slope.

79.90 The cor. of secs. 27, 28; 33 and 34.

Land, mountainous.  
Soil, rocky, 4th. rate.  
Timber, scattering palo verde.  
Undergrowth, greasewood, ocotillo and cacti.

N.0°02'W., bet. secs. 27 and 28.

Asc. 185 ft. over steep SW. slope.

5.30 Spur, slopes NW.; desc. 250 ft. over NE. slope.

11.50 Ravine, course NE.; asc. 125 ft. over SE. slope.

22.20 Ridge; bears E., 1 ch., thence N.; along W. side of ridge.

30.80 Spur, slopes W.; desc. 270 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone, 4 ft. base, to top of post for 1/4 sec. cor., with brass cap mkd.

1/4  
S 28 | S 27  
1937

Desc. 150 ft. over NW. slope.

45.80 Swale; drains NW., 5 chs. to junction with wash, course N. Asc. 14 ft. over SW. slope.

47.60 Along W. slope.

54.50 Spur, slopes NW.; desc. 225 ft. over NE. slope, to cor.

60.00 Leave rough mountains and enter rolling hills.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T10S R17W  
S 21 | S 22  
S 28 | S 27  
1937

Chains	Land, mountainous. Soil, rocky, 4th. rate. Timber, scattering palo verde. Undergrowth, greasewood, sage, ocotillo and cacti.
	N.89°59'E., on a random line bet. secs. 22 and 27.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	A point 12 lks. N. of the cor. of secs. 22, 23, 26 and 27. Thence N.89°56'W., on a true line bet. secs. 22 and 27. Desc. 20 ft. over NW. slope.
8.35	Wash, 40 lks. wide, 10 ft. deep, course NE.; thence over rolling land.
39.97	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ \hline S\ 22 \\ S\ 27 \\ 1937 \end{array}$
	from which
	A palo verde, 10 ins. diam., bears S.31 $\frac{1}{2}$ °E., 217 lks. dist., mkd. $\frac{1}{4}$ S 27 B T
	An ironwood, 16 ins. diam., bears N.34 $\frac{1}{2}$ °W., 234 lks. dist., mkd. $\frac{1}{4}$ S 22 B T
40.45	Wash, 15 lks. wide, 4 ft. deep, course NW.
79.94	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, rocky, 4th. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood, sage, ocotillo and cacti.
	N.0°02'W., bet. secs. 21 and 22. Over rolling land.
14.00	Wash, 50 lks. wide, 15 ft. deep, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ \hline S\ 21\   \ S\ 22 \\ 1937 \end{array}$
	from which
	A palo verde, 8 ins. diam., bears S.73 $\frac{3}{4}$ °E., 194 lks. dist., mkd. $\frac{1}{4}$ S 22 B T
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Asc. 12 ft. over S. slope.



Subdivision of T.10 S., R.17 W.

BOOK 4219

Chains

42.00

Top of low hill; desc. 40 ft. over N. slope.

54.75

Wash, 30 lks. wide, 10 ft. deep, course N.70°W.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with glass deposited at the base, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

T10S R17W

S 16 | S 15

S 21 | S 22

1937

from which

An ironwood, 10 ins. diam., bears N.38°E., 244 lks. dist., mkd. T.10 S R 17 W S 15 B T

A palo verde, 6 ins. diam., bears N.19½°W., 561 lks. dist., mkd. T 10 S R 17 W S 16 B T

Land, rolling.  
Soil, rocky, 4th. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood, sage, ocotillo and cacti.

S.89°56'E., on a random line bet. secs. 15 and 22.

40.00

Set temp. ¼ sec. cor.

79.94

A point 7 lks. N. of the cor. of secs. 14, 15, 22 and 23.

Thence

N.89°53'W., on a true line bet. secs. 15 and 22.

Over rolling land.

15.00

Top of low hill; desc. 18 ft.

19.00

Drain, 5 lks. wide, course SW.; asc. 70 ft. over E. slope.

32.30

Top of low hill; desc. 60 ft. over W. slope.

39.97

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with glass deposited at the base, for ¼ sec. cor. with brass cap mkd.

¼ S 15

S 22

1937

from which

A palo verde, 6 ins. diam., bears S.16°E., 164 lks. dist., mkd. ¼ S 22 B T

62.75

Enter wash, 50 lks. wide, 4 ft. deep, course W. from SE.

67.50

Leave wash, course S.85°W.

73.00

Same wash, course N.70°W.

79.94

The cor. of secs. 15, 16, 21 and 22.

Land, rolling. Soil, rocky, 4th. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood, sage, ocotillo and cacti.

Chains	N.0°02'W., bet. secs. 15 and 16. Over rolling land.
5.90	Wash, 50 lks. wide, 4 ft. deep, course N.70°W.; asc. 65 ft. over rolling S. slope.
19.74	Spur, slopes W.; desc. 66 ft. over N. slope.
25.65	Drain, course W.; asc. 50 ft. over S. slope.
32.75	Spur, slopes W.; desc. 60 ft. over N. slope.
36.25	Wash, 10 lks. wide, course NW.; asc. 24 ft. over SW. slope
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 16   S 15 1937
	from which
	A palo verde, 6 ins. diam., bears N.26 $\frac{1}{2}$ °E., 167 lks. dist., mkd. $\frac{1}{4}$ S 15 B T
	A palo verde, 6 ins. diam., bears N.76 $\frac{3}{4}$ °W., 112 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	Asc. 120 ft. over SW. slope.
53.00	Spur, slopes W.; desc. 75 ft. over N. slope.
57.90	Ravine, course W.; asc. 180 ft. over S. slope.
66.44	Spur, slopes SW.; desc. 74 ft. along W. slope.
76.85	Swale, drains W.; asc. 40 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.
	T10S R17W S 9   S 10 S 16   S 15 1937
	No suitable accessory.
	Land, rolling. Soil, rocky, 4th. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood, sage, ocotillo and cacti.
	S.89°53'E., on a random line bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.80	A point 7 lks. N. of the cor. of secs. 10, 11, 14 and 15. Thence N.89°50'W., on a true line bet. secs. 10 and 15.

Subdivision of T.10 S.,R.17 W.

4215

- Chains Over rolling land.
- 23.35 Wash, 15 lks. wide, 6 ft. deep, course SE.
- 33.80 Asc. 50 ft. over NE. slope.
- 39.90 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$   $\frac{S\ 10}{S\ 15}$   
1937
- No suitable accessory.
- Asc. 140 ft. over NE. slope.
- 48.10 Spurs, slope SE. and SW. from NW.; desc. 160 ft; over W. slope.
- 62.50 Wash, 10 lks. wide, course S.; asc. 100 ft. over E. slope.
- 69.30 Spur, slopes S. 10° E.; desc. 90 ft. over W. slope.
- 79.80 The cor. of secs. 9, 10, 15 and 16.
- Land, rolling.  
Soil, rocky, 4th. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood, sage, ocotillo and cacti.
- 
- N. 0° 02' W., bet. secs. 9 and 10.
- Asc. 85 ft. over SW. slope.
- 6.10 Low ridge, bears NE. and SE.; desc. 165 ft. over NW. slope.
- 16.00 Wash, 10 lks. wide, course W.; asc. 70 ft. over SW. slope.
- 21.70 Spur, slopes NW.; desc. 130 ft. over N. slope.
- 30.00 Wash, 10 lks. wide, course W. about 4 chs., thence N. Asc. 56 ft. over S. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bed rock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$   
S 9 | S 10  
1937
- from which
- A palo verde, 6 ins. diam., bears S. 56 $\frac{3}{4}$ ° E., 117 lks. dist., mkd.  $\frac{1}{4}$  S 10 B T
- A palo verde, 6 ins. diam., bears S. 3 $\frac{3}{4}$ ° W., 134 lks. dist., mkd.  $\frac{1}{4}$  S 9 B T
- Asc. 17 ft. over S. slope.
- 40.65 Spur, slopes W., about 5 chs. to toe; desc. 80 ft. over NW. slope.
- 52.50 Wash, 20 lks. wide, 5 ft. deep, course NE.

Subdivision of T.10 S.,R.17 W.

Chains

- 65.70 Same wash, course NW.
- 71.30 Wash, 30 lks. wide, 15 ft. deep, course W. about 5 chs., thence NW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

T10S R17W  
 S 4 | S 3  
 ---  
 S 9 | S 10  
 1937

from which

A palo verde, 8 ins. diam., bears S.53 $\frac{1}{4}$ °E., 207 lks. dist., mkd. T 10 S R 17, W S 10 B T

No trees near in other secs.

Land, rolling hills.  
 Soil, rocky, 4th. rate.  
 Timber, palo verde and ironwood.  
 Undergrowth, greasewood, sage, ocotillo and cacti.

S.89°50'E., on a random line bet. secs. 3 and 10.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.80 A point 16 lks. S. of the cor. of secs. 2, 3, 10 and 11.  
Thence  
N.89°57'W., on a true line bet. secs. 3 and 10.  
Asc. 100 ft. over NE. slope.
- 4.60 Spur, slopes SE.; desc. 90 ft. over W. slope.
- 17.30 Wash, 10 lks. wide, 10 ft. deep, course NE.; asc. 80 ft. over broken NE. slope.
- 32.70 Spur, slopes SE.; desc. 70 ft. over W. slope.
- 39.90 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bed rock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$  S 3  
 ---  
 S 10  
 1937

from which

A palo verde, 5 ins. diam., bears N.37 $\frac{1}{4}$ °E., 104 lks. dist., mkd.  $\frac{1}{4}$  S 3 B T

A palo verde, 5 ins. diam., bears S.53°W., 46 lks. dist., mkd.  $\frac{1}{4}$  S 10 B T

Asc. slightly.

- 49.00 Spur, slopes SW.; desc. 70 ft. over W. slope.
- 54.85 Wash, 10 lks. wide, course SW.; asc. 30 ft.
- 58.00 Desc. 25 ft. over W. slope.

## Subdivision of T.10 S., R.17 W.

## Chains

62.30 Foot of descent.

79.80 The cor. of secs. 3, 4, 9 and 10.

Land, rolling hills.

Soil, rocky, 4th. rate.

Timber, scattering palo verde and ironwood.

Undergrowth, greasewood, sage, ocotillo and cacti.

N.0°02'W., bet. secs. 3 and 4.

Over rolling land.

23.00 Asc. 56 ft. along SE. slope.

36.50 Top of low hill; desc. 65 ft. over N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone, 4 ft. base, to top of post, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ S\ 4 \mid S\ 3 \\ 1937 \end{array}$$

from which

A palo verde, 10 ins. diam., bears N.50°E., 70 lks. dist., mkd.  $\frac{1}{4}$  S 3 B TAn ironwood, 8 ins. diam., bears N.37 $\frac{1}{2}$ °W., 138 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T

Desc. 23 ft. over N. slope.

40.95 Wash, 15 lks. wide, course W. about 3 chs., thence NW.

48.00 Low ridge, bears S.80°E. and N.80°W.; desc. 30 ft. over N. slope.

56.97 Intersect the 2nd. standard parallel south.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bed rock, and in a mound of stone, 4 ft. base to top of post, for closing cor. of secs. 3 and 4, with brass cap mkd.

$$\begin{array}{c} T9S\ R17W \\ S\ 33 \\ \hline S\ 4 \mid S\ 3 \\ T10S\ R17W \\ C\ C \end{array}$$

No suitable accessory.

From this point, the standard  $\frac{1}{4}$  sec. cor. of sec. 33, bears N.89°40'E., 1.51 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.17 W., under this group.

Land, rolling hills.

Soil, rocky, 4th. rate.

Timber, scattering palo verde and ironwood.

Undergrowth, greasewood, sage, ocotillo and cacti.

## Subdivision of T.10 S., R.17 W.

Chains	
	At the midpoint of the N. bdy. of sec. 3, Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap mkd.
	$\frac{1}{4} S 3$ 1937
	No suitable accessory.
	From this point, the standard cor. of secs. 33 and 34, bears N.89°52'E., 1.98 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.17 W., under this group.
	From the cor. of secs. 32 and 33, on S. bdy. of Tp.; here- inbefore described, N.0°02'W., bet. secs. 32 and 33. Asc. over broken SW. slope.
2.55	Head of draw, course SE.
4.70	Spur, slopes W.; desc. 160 ft. over broken NE. slope.
10.75	Head of draw, course NW.; desc. 75 ft. along broken W. slope.
19.30	Head of draw, course W.; asc. 50 ft. over S. slope.
22.00	Spur, slopes W.; desc. 180 ft. over NE. slope.
31.50	Draw, course NW.; asc. 30 ft. over SW. slope.
36.00	Spur, slopes NW.; desc. 60 ft. over NE. slope.
38.50	Foot of descent; thence over rolling land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone, 5 ft. base, 2 $\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor.; with brass cap mkd.
	$\frac{1}{4}$ S 32   S 33 1937
	from which
	An ironwood, 8 ins. diam., bears S.89°30'E., 44 lks. dist., mkd. $\frac{1}{4}$ S 33 B T
	A palo verde, 10 ins. diam., bears N.70°W., 275 lks. dist., mkd. $\frac{1}{4}$ S 32 B T
42.50	Wash, 60 lks. wide, 2 ft. deep, course W.
52.00	Top of low detached hill, bears E. and SW.
62.50	Wash, 85 lks. wide, 2 ft. deep, course SW.
70.40	Wash, 2 chs. wide, 3 ft. deep, course SW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., on surface rock, supported in a mound of stone 5 ft. base, to top of

Subdivision of T.10 S., R.17 W.

Chains post, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T10S	R17W
S 29	S 28
S 32	S 33
.1937	

from which

An ironwood, 6 ins. diam., bears N.26½°E., 85 lks. dist., mkd. T 10 S R 17 W S 28 B T

A palo verde, 6 ins. diam., bears S.53°E., 210 lks. dist., mkd. T 10 S R 17 W S 33 B T

A palo verde, 5 ins. diam., bears S.86¼°W., 96 lks. dist., mkd. T 10 S R 17 W S 32 B T

A palo verde, 5 ins. diam., bears N.38¼°W., 256 lks. dist., mkd. T 10 S R 17 W S 29 B T

Land, mountainous and rolling.  
Soil, rocky, 4th. rate.  
Timber, ironwood and palo verde.  
Undergrowth, greasewood and sage.

N.89°59'E., on a random line bet. secs. 28 and 33 (flag on objective cor. visible).

- 40.00 Set temp. ¼ sec. cor.
- 80.10 Intersect the cor. of secs. 27, 28, 33 and 34.  
Thence  
S.89°59'W., on a true line bet. secs. 28 and 33.  
Desc. 615 ft. over broken W. slope.
- 27.80 Gulch, course NW.; asc. 90 ft. over E. slope.
- 31.50 Spur, slopes W.; desc. 130 ft. over NW. slope.
- 35.50 Gulch, 30 lks. wide, 3 ft. deep, course SW.; asc. 130 ft. over E. slope.
- 40.05 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for ¼ sec. cor. with brass cap mkd.  

¼	S 28
	S 33
	.1937
- No bearings available.  
Asc. 30 ft. over E. slope.
- 41.10 Short spur, slopes S.; desc. 55 ft. over W. slope.
- 46.00 Head of draw, course SW.; along S. slope.
- 51.00 Spur, slopes SW.; desc. 75 ft. over W. slope.
- 57.00 Leave mountainous land, bears N. and S.
- 78.80 Wash, 10 lks. wide, course NW.
- 80.10 The cor. of secs. 28, 29, 32 and 33.

## Subdivision of T.10 S., R.17 W.

Chains	<p>Land, mountainous and rolling. Soil, rocky, 4th. rate. Timber, scattering ironwood and palo verde. Undergrowth, greasewood and sage.</p> <hr/> <p>N.0°02'W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p> <p>1.20 Wash, 20 lks. wide, course NW.</p> <p>10.00 Toe of spur, from NE.</p> <p>20.15 Wash, 15 lks. wide, course NW.</p> <p>31.90 Wash, 40 lks. wide, 2 ft. deep, course W.</p> <p>37.30 Wash, 15 lks. wide, 2 ft. deep, course W.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bed rock, with glass deposited at the base, and in a mound of stone, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>  S 29   S 28  1937 </div> <p>No bearings available.</p> <p>42.40 Gulch, 15 lks. wide, 3 ft. deep, course NW.</p> <p>46.30 Gulch, 60 lks. wide, 4 ft. deep, course NE.</p> <p>62.00 Enter same gulch; course N.</p> <p>67.00 Leave gulch, course N.3°E.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs.</p> <div style="text-align: center;"> T10S R17W  S 20   S 21  <hr/> S 29   S 28  1937 </div> <p style="text-align: right;">from which</p> <p>A palo verde, 14 ins. diam., bears N.31<math>\frac{1}{2}</math>°E., 30 lks. dist., mkd. T 10 S R 17 W S 21 B T</p> <p>An ironwood, 12 ins. diam., bears S.69<math>\frac{3}{4}</math>°E., 112 lks. dist., mkd. T 10 S R 17 W S 28 B T</p> <p>A palo verde, 7 ins. diam., bears S.10°W., 151 lks. dist., mkd. T 10 S R 17 W S 29 B T</p> <p>A palo verde, 8 ins. diam., bears N.40<math>\frac{1}{4}</math>°W., 129 lks. dist., mkd. T 10 S R 17 W S 20 B T</p> <p>Land, rolling. Soil, sandy and rocky, 3rd. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood and sage.</p>
--------	--



Subdivision of T.10 S.,R.17 W.

4219

Chains N.89°59'E., on a random line bet. secs. 21 and 28.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 A point 14 lks. S. of the cor. of secs. 21, 22, 27 and 28.  
Thence  
S.89°53'W., on a true line bet. secs. 21 and 28.  
Over rolling land.

1.60 Wash, 10 lks. wide, 2 ft. deep, course NW.; asc. 100 ft. over E. slope.

6.25 Spur, slopes NE.; thence along N. slope.

12.65 Desc. 90 ft. over rolling W. slope.

14.10 Short spur, slopes SW.; continue descent.

20.00 Gulch, course NW.; foot of descent.

36.80 Same gulch, course SW.

39.00 Same gulch, 35 lks. wide, 3 ft. deep, course NW.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$       S 21  
                  S 28  
                  1937

from which

A palo verde; 6 ins. diam., bears N.63 $\frac{1}{2}$ °E., 57 lks. dist., mkd.  $\frac{1}{4}$  S 21 B T

A palo verde; 6 ins. diam., bears S.8 $\frac{3}{4}$ °E., 92 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T

Continue over gently rolling NW. slope.

79.00 Wash, 60 lks. wide, 3 ft. deep, course N.

79.98 The cor. of secs. 20, 21, 28 and 29.  
Land, rolling.  
Soil, rocky, 4th. rate.  
Timber, ironwood and palo verde:  
Undergrowth, greasewood and sage.

---

N.0°02'W., bet. secs. 20 and 21.  
Over rolling land, through scattering timber and undergrowth.

15.90 Gulch, 80 lks. wide, 5 ft. deep, course W.

26.80 Asc. 50 ft. over S. slope of low hills.

33.60 Spur, slopes SW.; along W. slope.

37.00 Short spur, slopes NW.; desc. 40 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## Subdivision of T.10 S., R.17 W.

Chains	$\frac{1}{4}$ S 20   S 21 1937 from which A palo verde, 6 ins. diam., bears S. $76\frac{3}{4}^{\circ}$ E., 78 lks. dist., mkd. $\frac{1}{4}$ S 21 B T A palo verde, 5 ins. diam., bears N. $58\frac{1}{2}^{\circ}$ W., 44 lks. dist., mkd. $\frac{1}{4}$ S 20 B T
48.00	Saddle in low ridge, bearing E. and W.; thence along W. slope of long spur.
74.00	Spur curves to NW.; desc. 50 ft. over NE. slope.
79.00	Small wash, course NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.
	T10S R17W S 17   S 16 S 20   S 21 1937 from which A palo verde, 7 ins. diam., bears N. $80\frac{1}{2}^{\circ}$ E., 135 lks. dist., mkd. T 10 S R 17 W S 16 B T A palo verde, 8 ins. diam., bears S. $25^{\circ}$ E., 262 lks. dist., mkd. T 10 S R 17 W S 21 B T An ironwood, 10 ins. diam., bears S. $56\frac{3}{4}^{\circ}$ W., 150 lks. dist., mkd. T 10 S R 17 W S 20 B T A palo verde, 6 ins. diam., bears N. $19\frac{1}{2}^{\circ}$ W., 110 lks. dist., mkd. T 10 S R 17 W S 17 B T Land, rolling. Soil, rocky, 4th. rate. Timber, ironwood and palo verde. Undergrowth, greasewood, sage and cacti.
	N. $89^{\circ}53'$ E., on a random line bet. secs. 16 and 21.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	A point 2 lks. S. of the cor. of secs. 15, 16, 21 and 22. Thence S. $89^{\circ}52'$ W., on a true line bet. secs. 16 and 21. Over rolling land, through scattering timber and undergrowth.
17.55	Wash, 30 lks. wide, 3 ft. deep, course NW.
20.00	Top of hill, 25 ft. high.
25.40	Asc. 55 ft. over E. slope.
30.35	Short spur, slopes S.
35.75	Low broken ridge, bears NE. and SW.; desc. 60 ft. over NW. slope.

## Subdivision of T.10 S., R.17 W.

Chains 40.04	<p>Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math> <math>\frac{S\ 16}{S\ 21}</math>  1937 </p> <p style="text-align: right;">from which</p> <p>A palo verde, 8 ins. diam., bears S.13°E., 265 lks. dist., mkd. <math>\frac{1}{4}</math> S 21 B T</p> <p>A palo verde, 6 ins. diam., bears N.82<math>\frac{3}{4}</math>°W., 26 lks. dist., mkd. <math>\frac{1}{4}</math> S 16 B T</p>
65.10	Gulch, 30 lks. wide, 3 ft. deep; course NW.
80.08	The cor. of secs. 16, 17, 20 and 21.
	<p>Land, rolling.  Soil, rocky, 4th. rate.  Timber, ironwood and palo verde.  Undergrowth, greasewood, sage and cacti.</p>
	<p>N.0°02'W., bet. secs. 16 and 17.</p> <p>Over nearly level land.</p>
21.20	Wash, 50 lks. wide, 10 ft. deep, course NW.
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math>  <math>\frac{S\ 17\   \ S\ 16}{1937}</math> </p> <p style="text-align: right;">from which</p> <p>A palo verde, 8 ins. diam., bears N.78<math>\frac{1}{2}</math>°E., 349 lks. dist., mkd. <math>\frac{1}{4}</math> S 16 B T</p> <p>A palo verde, 6 ins. diam., bears S.75<math>\frac{3}{4}</math>°W., 204 lks. dist., mkd. <math>\frac{1}{4}</math> S 17 B T</p>
55.00	Asc. 25 ft.
57.40	Small spur, slopes W.; desc. 35 ft.
62.35	Foot of descent.
78.15	Wash, 30 lks. wide, 2 ft. deep, course N.70°W.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.</p> <p style="text-align: center;"> T10S R17W  <math>\frac{S\ 8\   \ S\ 9}{S\ 17\   \ S\ 16}</math>  1937 </p> <p style="text-align: right;">from which</p> <p>A palo verde, 10 ins. diam., bears N.35<math>\frac{1}{4}</math>°E., 203 lks. dist., mkd. T 10 S R 17 W S 9 B T</p> <p>A palo verde, 12 ins. diam., bears S.34<math>\frac{1}{2}</math>°E., 167 lks.</p>

## Subdivision of T.10 S., R.17 W.

Chains	<p>dist., mkd. T 10 S R 17 W S 16 B T</p> <p>A palo verde, 10 ins. diam., bears S. <math>76\frac{1}{2}^{\circ}</math>W., 162 lks. dist., mkd. T 10 S R 17 W S 17 B T</p> <p>An ironwood, 10 ins. diam., bears N. <math>30^{\circ}</math>W., 158 lks. dist., mkd. T 10 S R 17 W S 8 B T</p> <p>Land, nearly level. Soil, sandy loam, 2nd. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood; sage and cacti.</p>
	<p>N. <math>89^{\circ}52'E.</math>, on a random line bet. secs. 9 and 16.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.18	A point 9 lks. N. of cor. of secs. 9, 10, 15 and 16.
	Thence
	S. $89^{\circ}56'W.$ , on a true line bet. secs. 9 and 16.
	Desc. 95 ft. over W. slope.
5.50	Asc. 60 ft. over NE. slope.
10.40	Low ridge, bears SE. and NW.
24.80	Desc. 100 ft. over W. slope.
35.00	Asc. 40 ft. over SE. slope.
40.09	Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \quad \frac{S \ 9}{S \ 16} \\ 1937 \end{array}$
	from which
	A palo verde, 6 ins. diam., bears N. $67^{\circ}E.$ , 365 lks. dist., mkd. $\frac{1}{4}$ S 9 B T
	A palo verde, 8 ins. diam., bears S. $60^{\circ}E.$ , 50 lks. dist., mkd. $\frac{1}{4}$ S 16 B T
	Desc. 60 ft. over SW. slope.
51.80	Desc. gently.
65.20	Enter wash, course westerly, from SE.
80.18	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling hills. Soil, rocky, 4th. rate. Timber, scattering palo verde and ironwood. Undergrowth, sage, greasewood and cacti.
	N. $0^{\circ}02'W.$ , bet. secs. 8 and 9.
	Over nearly level land.
7.80	Wash, 30 lks. wide, 2 ft. deep, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the

Subdivision of T.10 S.,R.17 W.

Chains ground to bed rock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4  
S 8 | S 9  
1937

from which

A palo verde, 12 ins. diam., bears N.35 1/2° E., 161 lks. dist., mkd. 1/4 S 9 B T

An ironwood, 10 ins. diam., bears N.80 1/2° W., 454 lks. dist., mkd. 1/4 S 8 B T

44.50 Dim road, bears N.20° E. and S.20° W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T10S R17W  
S 5 | S 4  
S 8 | S 9  
1937

from which

A palo verde, 3 ins. diam., bears N.24 1/2° E., 405 lks. dist., mkd. B T

An ironwood, 10 ins. diam., bears S:84° E., 179 lks. dist., mkd. T 10 S R 17 W S 9 B T

An ironwood, 12 ins. diam., bears N.58 3/4° W., 350 lks. dist., mkd. T 10 S R 17 W S 5 B T

Land, nearly level, drains NW.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood, sage and cacti.

N.89° 56' E., on a random line bet. secs. 4 and 9.

40.00 Set temp. 1/4 sec. cor.

80.18 Intersect the cor. of secs. 3, 4, 9 and 10.

Thence

S.89° 56' W., on a true line bet. secs. 4 and 9.

Over gently rolling land.

5.80 Enter wash, course W., from SE.

20.80 Leave wash, course NW.

40.09 Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone, for 1/4 sec. cor., with brass cap mkd.

1/4 S 4  
S 9  
1937

from which

A palo verde, 8 ins. diam., bears N.69 3/4° E., 253 lks. dist., mkd. 1/4 S 4 B T

## Subdivision of T.10 S., R.17 W.

Chains	A palo verde, 6 ins. diam., bears S.60°W., 415 lks. dist., mkd. $\frac{1}{4}$ S 9 B T
65.00	Land, nearly level.
71.20	Dim road, bears N.20°E. and S.20°W.
80.18	The cor. of secs. 4, 5, 8 and 9. Land, rolling, drains NW. Soil, gravelly and rocky, 3rd. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood, sage and cacti.
	N.0°02'W., bet. secs. 4 and 5. Over nearly level land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 5 \quad   \quad S\ 4 \\ 1937 \end{array}$ from which A palo verde, 6 ins. diam., bears S.81 $\frac{1}{2}$ °E., 111 lks. dist., mkd. $\frac{1}{4}$ S 4 B T A palo verde, 14 ins. diam., bears N.37 $\frac{1}{4}$ °W., 218 lks. dist., mkd. $\frac{1}{4}$ S 5 B T
47.90	Wash, 10 lks. wide, 4 ft. deep, course N.70°W.
56.28	Intersect the 2nd. standard parallel south. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd. $\begin{array}{c} T9S\ R17W \\ S\ 32 \\ \hline S\ 5 \quad   \quad S\ 4 \\ C\ C \\ T10S\ R17W \\ 1937 \end{array}$ from which An ironwood, 8 ins. diam., bears S.5 $\frac{1}{2}$ °E., 240 lks. dist., mkd. T 10 S R 17 W S 4 C C B T A palo verde, 4 ins. diam., bears S.61 $\frac{1}{4}$ °W., 160 lks. dist., mkd. T 10 S R 17 W S 5 C C B T From this point, the standard $\frac{1}{4}$ sec. cor. of sec. 32, bears N.89°36'E., 1.81 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S., R.17 W., under this group. Land, nearly level. Soil, rocky, 3rd. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood, sage and cacti.

Subdivision of T.10 S.,R.17 W.

Chains

At the midpoint of the N. bdy. of sec. 4,  
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
ground to bed rock, and in a mound of stone to top, for  
¼ sec. cor. of sec. 4 only, with brass cap mkd.

¼ S 4

1937

from which

A palo verde, 6 ins. diam., bears S. 15½° W., 78 lks.  
dist., mkd. ¼ S 4 B T

A palo verde, 6 ins. diam., bears S. 79° W., 200 lks.  
dist., mkd. ¼ S 4 B T

From this point, the standard cor. of secs. 32 and 33,  
bears N. 89° 36' E., 1.21 chs. dist.; described in the field  
notes of the resurvey of the S. bdy. of T.9 S., R.17 W.,  
under this group.

From the cor. of secs. 31 and 32, on S. bdy. of Tp., here-  
inbefore described,

N. 0° 03' W., bet. secs. 31 and 32.

Over nearly level land...

29.70 Wash, 12 lks. wide, course NW.

35.00 Wash, 6 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for ¼ sec. cor., with brass cap mkd.

¼

S 31 | S 32

1937

from which

An ironwood, 8 ins. diam., bears S. 59½° E., 307 lks.  
dist., mkd. ¼ S 32 B T

A palo verde, 8 ins. diam., bears N. 82° W., 203 lks.  
dist., mkd. ¼ S 31 B T

43.65 Wash, 15 lks. wide, course NW.

53.50 Road, bears SE. to Papago Springs and NW. to Wellton.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the  
ground, for cor. of secs. 29, 30, 31 and 32, with brass  
cap mkd.

T10S R17 W

S 30 | S 29

S 31 | S 32

1937

from which

An ironwood, 6 ins. diam., bears N. 69½° E., 228 lks.  
dist., mkd. T 10 S R 17 W S 29 B T

An ironwood, 8 ins. diam., bears S. 75½° E., 385 lks.  
dist., mkd. T 10 S R 17 W S 32 B T

## Subdivision of T.10 S., R.17 W.

Chains	<p>An ironwood, 6 ins. diam., bears S.25°W., 221 lks. dist. mkd. T 10 S R 17 W S 31 B T</p> <p>A palo verde, 6 ins. diam., bears N.14<math>\frac{3}{4}</math>°W., 571 lks. dist., mkd. T 10 S R 17 W S 30 B T</p> <p>Land, nearly level. Soil, rocky, 3rd. rate. Timber, scattering ironwood and palo verde. Undergrowth, greasewood, sage and cacti.</p>								
	<p>East, on a random line bet. secs. 29 and 32.</p>								
40.00	Set temp. $\frac{1}{4}$ sec. cor.								
80.02	A point 4 lks. N. of the cor. of secs. 28, 29, 32 and 33.								
	Thence								
	N.89°58'W., on a true line bet. secs. 29 and 32.								
	Over nearly level land.								
9.20	Wash, 10 lks. wide, course NW.								
15.00	Low spur, slopes N.								
40.01	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>S 29</td> </tr> <tr> <td><math>\frac{1}{4}</math></td> <td><u>        </u></td> </tr> <tr> <td></td> <td>S 32</td> </tr> <tr> <td></td> <td>1937</td> </tr> </table>		S 29	$\frac{1}{4}$	<u>        </u>		S 32		1937
	S 29								
$\frac{1}{4}$	<u>        </u>								
	S 32								
	1937								
	from which								
	A palo verde, 6 ins. diam., bears N.75°E., 140 lks. dist., mkd. $\frac{1}{4}$ S 29 B T								
	A palo verde, 8 ins. diam., bears S.84°E., 117 lks. dist., mkd. $\frac{1}{4}$ S 32 B T								
45.00	Over wash land.								
75.00	Main channel, 50 lks. wide, 3 ft. deep, course NW.								
76.50	Leave washes, course N.60°W.								
80.02	The cor. of secs. 29, 30, 31 and 32.								
	Land, nearly level. Soil, rocky, 3rd. rate. Timber, scattering ironwood and palo verde. Undergrowth, greasewood, sage and ocotillo.								
	West, on a random line bet. secs. 30 and 31.								
40.00	Set temp. $\frac{1}{4}$ sec. cor.								
77.67	Intersect the cor. of secs. 25, 30, 31 and 36, on W. bdy. of Tp., hereinbefore described.								
	Thence								
	East, on a true line bet. secs. 30 and 31.								
	Over nearly level land.								



Subdivision of T.10 S., R.17 W.

Chains  
37.67

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 30  
S 31  
1937

from which

A palo verde, 6 ins. diam., bears N.66 $\frac{1}{4}$ °E., 110 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T

An ironwood, 8 ins. diam., bears S.57 $\frac{3}{4}$ °E., 110 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T

58.76 Road, bears SE. to Papago Wells and NW. to Wellton.

77.67 The cor. of secs. 29, 30, 31 and 32.

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering ironwood and palo verde.  
Undergrowth, greasewood, sage and ocotillo.

N.0°03'W., bet. secs. 29 and 30.

Over nearly level land.

10.90 Wash, 90 lks. wide, 2 ft. deep, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 30 | S 29  
1937

from which

A palo verde, 8 ins. diam., bears S.24 $\frac{1}{2}$ °E., 281 lks. dist., mkd.  $\frac{1}{4}$  S 29 B T

A palo verde, 6 ins. diam., bears N.1 $\frac{3}{4}$ °W., 468 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with glass deposited at the base, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T10S R17W  
S 19 | S 20  
S 30 | S 29  
1937

No trees near.

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering ironwood and palo verde.  
Undergrowth, greasewood, sage and ocotillo.

S.89°58'E., on a random line bet. secs. 20 and 29.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the cor. of secs. 20, 21, 28 and 29.

Chains	Thence
	N.89°58'W., on a true line bet. secs. 20 and 29.
	Over rolling land.
10.00	Enter nearly level land, sloping gently to NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 20</u> S 29 1937
	from which
	A palo verde, 10 ins. diam., bears S.5 $\frac{1}{2}$ °W., 310 lks. dist., mkd. $\frac{1}{4}$ S 29 B T
	A palo verde, 8 ins. diam., bears N.3°W., 150 lks. dist., mkd. $\frac{1}{4}$ S 20 B T
80.00	The cor. of secs. 19, 20, 29 and 30.
	Land, nearly level. Soil, sandy loam, 2nd. rate. Timber, ironwood and palo verde. Undergrowth, greasewood, sage and ocotillo.
	West, on a random line bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
77.61	Intersect the cor. of secs. 19, 24, 25 and 30, on W. bdy. of Tp., hereinbefore described.
	Thence
	East, on a true line bet. secs. 19 and 30.
	Over nearly level land.
1.20	Road, bears SE. to Papago Wells and N. to Wellton.
37.61	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 19</u> S 30 1937
	No trees available.
77.61	The cor. of secs. 19, 20, 29 and 30.
	Land, nearly level. Soil, sandy loam, 2nd. rate. Timber, scattering ironwood and palo verde. Undergrowth, greasewood, sage and ocotillo.
	N.0°03'W., bet. secs. 19 and 20.
	Over nearly level land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the

.Subdivision of T.10 S.,R.17 W.

Chains ground, with glass deposited at the base, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

S 19 | S 20

1937

No bearing trees available.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at the base, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

T10S R17W  
S 18 | S 17

S 19 | S 20

1937

No bearing trees available.

Land, nearly level.

Soil, sandy loam, 2nd. rate.

Timber, scattering ironwood and palo verde.

Undergrowth, greasewood, sage and ocotillo.

S.89°58'E., on a random line bet. secs. 17 and 20.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 A point 2 lks. S. of the cor. of secs. 16, 17, 20 and 21.

Thence

N.89°59'W., on a true line bet. secs. 17 and 20.

Over slightly rolling land.

2.65 Wash, course NW.

11.25 Same wash, 25 lks. wide, 4 ft. deep, course SW.

27.40 Same wash, 40 lks. wide, 2 ft. deep, course NW.; thence over nearly level land.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 17

S 20

1937

from which

A. palo verde, 6 ins. diam., bears S.50 $\frac{3}{4}$ °W., 245 lks. dist., mkd.  $\frac{1}{4}$  S 20 B T

A palo verde, 8 ins. diam., bears N.42 $\frac{1}{4}$ °W., 163 lks. dist., mkd.  $\frac{1}{4}$  S 17 B T

43.00 Enter wash land, draining NW.

60.20 Leave wash land.

79.96 The cor. of secs. 17, 18, 19 and 20.

Land, nearly level.

Soil, sandy and rocky, 3rd. rate.

Timber, ironwood & palo verde. Undergrowth, greasewood & sage.

Subdivision of T.10 S., R.17 W.

Chains	West, on a random line bet. secs. 18 and 19.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
77.57	Intersect the cor. of secs. 13, 18, 19 and 24, on W. bdy. of Tp., hereinbefore described.
	Thence
	East, on a true line bet. secs. 18 and 19.
	Over nearly level land.
37.57	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 18 <hr style="width: 50px; margin: 0 auto;"/> S 19 1937
	No bearing trees available.
77.57	The cor. of secs. 17, 18, 19 and 20.
	Land, level.
	Soil, sandy, 2nd. rate.
	Timber, scattering ironwood and palo verde.
	Undergrowth, greasewood and ocotillo.
	N.0°03'W.; bet. secs. 17 and 18.
	Over nearly level land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 18   S 17 <hr style="width: 50px; margin: 0 auto;"/> 1937
	from which
	An ironwood, 4 ins. diam., bears S.46°E., 62 lks. dist., mkd. BT
	A palo verde, 7 ins. diam., bears S.25 $\frac{1}{2}$ °W., 68 lks. dist., mkd. $\frac{1}{4}$ S 18 B T
45.00	Enter wash land, drains NW.
75.00	Leave wash land.
80.00	Set an iron post, .3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.
	T10S R17W S 7   S 8. <hr style="width: 50px; margin: 0 auto;"/> S 18   S 17 1937
	from which
	An ironwood, 8 ins. diam., bears N.34 $\frac{1}{2}$ °E., 210 lks. dist., mkd. T 10 S R 17 W S 8 B T
	An ironwood, 12 ins. diam., bears S.84 $\frac{1}{2}$ °E., 130 lks.

## Subdivision of T.10 S., R.17 W.

Chains	<p>mkd. T 10 S R 17 W S 17 B T</p> <p>A palo verde, 6 ins. diam., bears S. <math>32\frac{1}{4}^{\circ}</math> W., 163 lks. dist., mkd. T 10 S R 17 W S 18 B T</p> <p>A palo verde, 6 ins. diam., bears N. <math>72\frac{1}{2}^{\circ}</math> W., 240 lks. dist., mkd. T 10 S R 17 W S 7 B T</p> <p>Land, nearly level. Soil, sandy loam, 2nd. rate.. Timber, scattering ironwood and palo verde. Undergrowth, greasewood, sage and ocotillo.</p>
40.00	<p>S. <math>89^{\circ}59'E.</math>, on a random line bet. secs. 8 and 17.</p> <p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>
79.94	<p>A point 2 lks. N. of the cor. of secs. 8, 9, 16 and 17.</p> <p>Thence:</p> <p>N. <math>89^{\circ}58'W.</math>, on a true line bet. secs. 8 and 17.</p>
15.00 39.97	<p>Over nearly level land. Drain, 30 lks. wide, course N. <math>70^{\circ}</math> W. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\frac{1}{4} \frac{S \ 8}{S \ 17}</math> <p>1937</p> </div> <p style="text-align: right;">from which</p> <p>A palo verde, 8 ins. diam., bears S. <math>41^{\circ}</math> W., 166 lks. dist., mkd. <math>\frac{1}{4}</math> S 17 B T</p> <p>A palo verde, 10 ins. diam., bears N. <math>52\frac{1}{2}^{\circ}</math> W., 330 lks. dist., mkd. <math>\frac{1}{4}</math> S 8 B T</p>
79.94	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, nearly level. Soil, sandy loam, 2nd. rate. Timber, scattering palo verde and ironwood. Undergrowth, greasewood, sage and cacti.</p>
40.00	<p>West, on a random line bet. secs. 7 and 18.</p> <p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>
77.54	<p>A point 2 lks. S. of the cor. of secs. 7, 12, 13 and 18, on W. bdy. of Tp., hereinbefore described.</p> <p>Thence</p> <p>S. <math>89^{\circ}59'E.</math>, on a true line bet. secs. 7 and 18.</p>
37.54	<p>Over nearly level land.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for <math>\frac{1}{4}</math> sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\frac{1}{4} \frac{S \ 7}{S \ 18}</math> <p>1937</p> </div> <p>No bearing trees available.</p>

Subdivision of T.10 S., R.17 W.

Chains

49.50 Enter wash land, drains NW.

69.75 Main channel, course NW.

72.50 Leave wash land..


77.54 The cor. of secs. 7, 8, 17 and 18.

Land, nearly level..  
Soil, sandy, 2nd. rate.  
Timber, scattering ironwood and palo verde.  
Undergrowth, greasewood, sage and ocotillo.

N.0°03'W., bet. secs. 7 and 8.

Over nearly level land.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for 1/4 sec. cor. with brass cap mkd.



No bearing trees available.

44.50, Gulch, course NW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with glass deposited at the base, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.



No bearing trees available.

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, ironwood and palo verde.  
Undergrowth, greasewood, sage and ocotillo.

S.89°58'E., on a random line bet. secs. 5 and 8.

40.00 Set temp. 1/4 sec. cor.


79.94 A point 5 lks. N. of the cor. of secs. 4, 5, 8 and 9.

Thence

N.89°56'W., on a true line bet. secs. 5 and 8.

Over nearly level land.

39.97 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



from which

Subdivision of T.10 S.,R.17 W.

Chains

A palo verde, 6 ins. diam., bears N.50°E., 197 lks. dist., mkd. 1/4 S 5 B T

A palo verde, 6 ins. diam., bears S.55°E., 232 lks. dist., mkd. 1/4 S 8 B T

79.94 The cor. of secs. 5, 6, 7 and 8

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering palonverde and ironwood.  
Undergrowth, greasewood, sage and cacti.

N.89°59'W., on a random line bet. secs. 6 and 7.

40.00 Set temp. 1/4 sec. cor.

77.48 A point 2 lks. S. of the cor. of secs. 1, 6, 7 and 12, on W. bdy. of Tp., hereinbefore described.

Thence  
S.89°58'E., on a true line bet. secs. 6 and 7.

Over nearly level land.

37.48 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with broken glass deposited at the base, for 1/4 sec. cor., with brass cap mkd.

1/4 S 6  
S 7  
1937

No bearing trees available.

77.48 The cor. of secs. 5, 6, 7 and 8.

Land, nearly level.  
Soil, sandy loam, 2nd. rate.  
Timber, scattering palo verde and ironwood.  
Undergrowth, greasewood, sage and cacti.

N.0°03'W., bet. secs. 5 and 6.

Over nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass deposited at the base, for 1/4 sec. cor. with brass cap mkd.

1/4 S 6 | S 5  
1937

No bearing trees available.

55.82 Intersect the 2nd. standard parallel south.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.

T9S R17W  
S 31  
S 6 | S 5  
T10S R17W  
C C

Subdivision of T.10 S.,R.17 W.

Chains

from which

A palo verde, 6 ins. diam., bears S.  $66\frac{1}{4}^{\circ}$ E., 125 lks.  
dist., mkd. T 10 S R.17 W S 5 C C B T

A palo verde, 4 ins. diam., bears S.  $55\frac{1}{4}^{\circ}$ W., 135 lks.  
dist., mkd. T 10 S R 17 W S 6 C C B T

From this point, the standard  $\frac{1}{4}$  sec. cor. of sec. 31, bears N.  $89^{\circ}40'$ E., 1.95 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S.,R.17 W., under this group.

Land, level.

Soil, sandy loam, 2nd. rate.

Timber, scattering palo verde and ironwood.

Undergrowth, greasewood and sage.

At the midpoint of the N. bdy. of sec. 5.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 5 only, with brass cap mkd.

$\frac{1}{4}$  S 5  
1937

from which

A palo verde, 7 ins. diam., bears S.  $26\frac{1}{2}^{\circ}$ E., 75 lks.  
dist., mkd.  $\frac{1}{4}$  S 5 B T

A palo verde, 5 ins. diam., bears S.  $67^{\circ}$ W., 85 lks.  
dist., mkd.  $\frac{1}{4}$  S 5 B T

From this point, the standard cor. of secs. 31 and 32, bears N.  $89^{\circ}40'$ E., 2.31 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S.,R.17 W., under this group.

At a point on the N. bdy. of sec. 6, 40.00 chs. dist. from the NE. cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at the base, for  $\frac{1}{4}$  sec. cor. of sec. 6 only, with brass cap mkd.

$\frac{1}{4}$  S 6  
1937

No trees or stones near.

From this point, the standard cor. of Ts.9 S.,Rs.17 and 18 W., bears N.  $89^{\circ}54'$ E., 2.05 chs. dist.; described in the field notes of the resurvey of the S. bdy. of T.9 S.,R.17 W., under this group.



Final Test of Solar Attachments.  
-----

For final test of solar attachments, see the final test as outlined in the field notes of the subdivisional lines of Township 10 South, Range 18 East, surveyed under this group.

-----

General Description  
-----

The West onethird of the area of Township 10 South, Range 17 West, is gently sloping land, ranging in elevation from five hundred to eight hundred feet above sea level. The Eastern two thirds of the Township ranges from sloping to mountainous, reaching an elevation of about 2900 feet above sea level in the southeast part of the township.

There are no streams, wells or springs in the township., and no settlers.

The Arizona Consolidated Mining Co., has a mine in Section 35.

Palo Verde and Ironwood trees are found , especially along the washes, but too small for commercial use. The undergrowth consists of scattering greasewood, sage, cat-claw and cactus.

The soil is sandy on the gently rolling land and rocky in the hills.

-----

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

FIELD ASSISTANTS

NAMES	CAPACITY,
I. B. Williams	Principal Assistant
Edmond R. Brenizer	"
Donald Gifford	"
John Crofford, Jr.	Chairman
Edmond R. Brenizer	"
Robert O. Jones	"
Roger T. Voorhees	"
Glenn P. Snyder	"
Robert G. Burns	Moundman
Bob R. Alexander	"
James C. Bass	"
Walter D. Galusha	"
Mark E. Makin	"
Gilbert M. Allred	Flagman
Robert O. Jones	"
James C. Bass	"
Keith Couch	"
Frank G. Brown	"
Robert G. Burns	Axeman
John Crofford	"
Paul R. Ernst	"
Valdoran Burrow	"
Edmond R. Brenizer	"
Robert O. Jones	"
James C. Bass	"
Kenneth Poor	"
Keith Couch	"
Eugene W. Christian	"
Roger T. Voorhees	"
Walter G. Galusha	"
Donald Gifford	"
Glenn P. Snyder	"
Hershel L. Trucks	"

CERTIFICATE OF SURVEYOR

We, Horace M. Muscott, Public Land Surveyor, and Thornton Fitzhugh, John Boggs, and Benjamin J. Mollette, Transitmen, General Land Office

HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of November, 1936, received from the district cadastral engineer for Arizona, with assignment instructions dated February 23 and April 15, 1937, we have surveyed the South and West boundaries and subdivisional lines of Township 10 South, Range 17 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Glendale, California, March 21, 1939. Horace M. Muscott Public Land Surveyor
Phoenix, Ariz., April 3, 1939. Thornton Fitzhugh Transitman
Bowie, Ariz. March 27, 1939. John Boggs Transitman
Phoenix, Ariz., April 3, 1939. Benjamin J. Mollette Transitman
General Land Office.

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS, Denver, Colorado, AUG 26 1940, 19

The foregoing field notes of the survey of the South and West boundaries and subdivisional lines of Township 10 South, Range 17 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Horace M. Muscott, Public Land Surveyor, and Thornton Fitzhugh, John Boggs and Benjamin J. Mollette, Transitmen, General Land Office

under special instructions dated November 20, 1936, and assignment instructions dated February 23 and April 15, 1937, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Signature of Supervisor of Surveys

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes on file in the public survey office.

Signature of Supervisor of Surveys