

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

BOOK 4243

FIELD NOTES

OF THE RESURVEY OF

Subdivision lines bounding Section 22 of

Township 15 South, Range 22 East

and

OF THE SURVEY OF

Central Nos. 1 to 6, incl., Mining Claims

for segregation from Section 22 of

Township 15 South, Range 22 East

Of the Gila and Salt River Meridian,

In the State of ARIZONA

EXECUTED BY

Raymond F. Moss, Assistant Cadastral Engineer

Under special instructions dated September 20, 1940, which provided

for the surveys included under Group No. 231 Arizona, bearing the approval of the

Commissioner of the General Land Office under date of December 2, 1940

and assignment instructions dated November 4, 1940

Resurvey and Survey commenced March 15, 1941

Resurvey and Survey completed March 23, 1941

4243

4243

14

# INDEX DIAGRAM.

Township \_\_\_\_\_, Range \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36



The resurveys and surveys herein described were executed by Raymond F. Moss, Assistant Cadastral Engineer, using Gurley transit No. 371537. This instrument is equipped with an improved Smith solar attachment and otherwise conforms to the standard specifications of the General Land Office. The instrument was examined and tested by the District Cadastral Engineer for California and Arizona prior to the beginning of the surveys of this group, and was approved conditional upon satisfactory results of field tests of same.

The azimuth of all the lines of survey herein described were determined with the solar attachment.

All measurements were made with a Dietzgen steel tape, 5 chs. in length, graduated every link for the first 100 lks., and the remainder at intervals of 10 lks. The tape was tested by comparison with a Lufkin standard tape and found correct. All of the measurements were made on the slope, the vertical angle of each interval determined with a clinometer in good adjustment, and the horizontal equivalents entered in the field notes.

#### PRELIMINARY FIELD TEST OF INSTRUMENT

March 15, 1941; at the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27, T. 15 S., R. 22 E., Gila and Salt River Meridian, Arizona, in latitude  $32^{\circ}06'13''N.$ , and longitude  $110^{\circ}05'23''W.$ , examine the adjustments of Gurley transit No. 371537 and find no errors. Watch reads correct 105th meridian time as checked by comparison with Western Union Telegraph Co. clock. To test workings of the solar apparatus of this instrument, proceed as follows:

At 7h. 32.5m.; a.m.; l.m.t., make an hour angle observation on Polaris east of the meridian, making four observations, two each with the telescope in direct and reversed positions, and reading the deflection angles from a flag set on a low ridge about 25 chs. easterly, west to Polaris;

Mean watch time of observations, a.m.	7h. 52.9m.
Watch fast of l.m.t.	20.4m.
Mean horizontal angle from Polaris W. to reference point	88°49'
Azimuth of Polaris	<u>1°10.5'</u>
True bearing of reference point	N. 89°59.5' E.

March 15, 1941; at same station, at 9h. 00m., a.m., app.t., set off  $32^{\circ}06'N.$  on the latitude arc;  $2^{\circ}05\frac{1}{2}'S.$  on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the latitude arc unchanged; observe the sun on the meridian and obtain a reading of  $2^{\circ}02\frac{1}{2}'S.$  on the declination arc, which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app.t., with the latitude arc unchanged; set off  $1^{\circ}59\frac{1}{2}'S.$  on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within  $1'30''$  of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, on which the surveys herein described are begun.

2.

Chains

The subdivision lines of T. 15 S., R. 22 E. were surveyed by J.B. Wright, U.S.D.S. in 1907, and no retracement or resurvey of any part of same is of official record.

The following notes describe a resurvey of those subdivision lines of said township which bound section 22 thereof, executed in connection with survey of the Central Nos. 1, 2, 3, 4, 5 and 6 lode mining claims for segregation of same from said section, as described in field notes herein which immediately follow the resurvey record.

The cor. of secs. 22, 23, 26 and 27, is a limestone 12x4x6 ins. above ground, firmly set, marked with 2 notches on the S. and E. edges, and witnessed by a mound of stone W.

Reconstruct this cor. monument as follows:

Remove the stone and in same place, set an iron post, 3 ft. long, 2 ins. in diam., 20 ins. in ground, with old stone buried alongside, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap marked

T15S	R22E
S22	S23
S26	S27

1941

No bearing trees available.

Rebuild the mound of stone, 4 ft. base, 2½ ft. high, W. of cor.

Thence

North, on true line bet. secs. 22 and 23 (S.½).

Over rolling and mountainous land, thru scattering timber and medium undergrowth.

Ascend 10 ft. along E. slope.

7:35 Ridge, bears N. 60° E. and S. 60° W.; descend 80 ft. over NW. slope.

16.40 Drain, course NE.

20.00 Road, bears N. 60° E. and SW.

22.00 Wash, 30 lks. wide, course E.; ascend 10 ft.

25:00 Low, flat spur, slopes E.; descend 13 ft. to

40.08 Intersect the ¼ sec. cor. of secs. 22 and 23, which is a limestone, 12x8x5 ins. above ground, firmly set, marked ¼ on W. face, and witnessed by a mound of stone W.

Reconstruct this cor. monument as follows:

Remove the stone and in same place, set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in ground to bedrock over a cross (+) chiseled thereon, with old stone buried alongside, and in a mound of stone to top, for the ¼ sec. cor. of secs. 22 and 23, with brass cap marked

¼

S22	S23
-----	-----

1941

Resurvey: Subdivision lines bounding sec. 22, T. 15 S., R. 22 E.

3.

Chains

No bearing trees available.

Rebuild the mound of stone, 4 ft. base, 3 ft. high,  
W. of cor.

Thence North, on true line bet. secs. 22 and 23 (N.  $\frac{1}{2}$ ).

Over rolling land.

1.12 Draw, course NE.

4.42 Point of spur slopes E.; descend 40 ft.

14.27 Drain, course E.

16.47 Wash, 20 lks. wide, course E.; ascend 20 ft.

38.02 Low spur, slopes N.  $80^{\circ}$  E.; descend 20 ft. over NE. slope  
to

40.22 Intersect the cor. of secs. 14, 15, 22 and 23, which is  
a limestone, 12x9x6 ins. above ground, firmly set,  
marked with 3 notches on S. and 2 notches on E. edges,  
and witnessed by a mound of stone W.

Reconstruct this cor. monument as follows:

Remove the stone and in same place, set an iron post, 3  
ft. long, 2 ins. in diam., 12 ins. in ground to bedrock  
over a cross (+) chiseled thereon, with old stone  
buried alongside, and in a mound of stone to top, for  
cor. of secs. 14, 15, 22 and 23, with brass cap marked

T15S	R22E
S15	S14
S22	S23

1941

No bearing trees available.

From the cor. of secs. 22, 23, 26 and 27.

N.  $89^{\circ} 53'$  W., on true line, bet. secs. 22 and 27 (E.  $\frac{1}{2}$ ).

Over mountainous land, thru scattering timber and medium  
undergrowth.

Ascend 20 ft. over E. slope.

1.25 Spur, slopes S.  $50^{\circ}$  E.; ascend 85 ft. over SE. slope.

8.75 Flat ridge, bears NW. and SE.; thence along S. slope.

14.75 Flat ridge, bears NE. and SW.; thence along N. slope.

21.35 Drain, near head, course NE.; ascend 49 ft. over E. slope  
to ridge.

24.15 Road, 2 chs. from its W. end, bears NE. and S.  $87^{\circ}$  W.

26.75 Low, narrow saddle in ridge, bearing NW. and SE.; descend  
20 ft. over W. slope.

27.70 Wash, in ravine, 30 lks. wide, course SE.; ascend 80 ft.  
over SE. slope.

32.75 Drain, course S.  $60^{\circ}$  E.; ascend 150 ft. over E. slope to

Resurvey; Subdivision lines bounding Sec. 22, T. 15 S., R. 22 E.

BOOK 4248

4.

Chains 39.73	<p>Intersect the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27, which is a granite stone, 10x8x6 ins. above ground, firmly set, marked <math>\frac{1}{4}</math> on N. face, and witnessed by a mound of stone N.</p> <p>Reconstruct this cor. monument as follows:</p> <p>Remove the stone and in same place, set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in ground to bedrock over a cross (+) chiseled thereon, with old stone buried alongside, and in a mound of stone to top, for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27, with brass cap marked</p> <div style="text-align: center;"> <math display="block">\frac{1}{4} \begin{array}{c} S 22 \\ S 27 \end{array}</math> </div> <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A cedar, 8 ins. in diam., bears S. 15°W., 67 lks. dist., marked <math>\frac{1}{4}</math> S27 BT,</p> <p>No other bearing trees available.</p> <p>Thence</p> <p>S. 88°24' W., on true line, bet. secs. 22 and 27 (<math>W.\frac{1}{2}</math>).</p> <p>Over mountainous land.</p> <p>Ascend 212 ft. over E. slope to top of spur.</p>
3.44	<p>Intersect E. side line of the Central No. 3 mining claim.</p> <p>From this point, cor. No. 1, bears N. 29°50'E., 12.91 chs. dist., and cor. No. 2, bears S. 29°50'W., 9.82 chs. dist. These corners are hereinafter described.</p>
10.07	<p>Spur, slopes SE.; descend 20 ft. over SW. slope to draw.</p>
14.09	<p>Intersect the W. side line of the Central No. 3 mining claim, which is common to the E. side line of the Central No. 4 mining claim.</p> <p>From this point, cors. Nos. 4 of the claims, bears N. 29°50'E., 20.25 chs. dist., and cor. No. 3 of the Central No. 3 claim, common to cor. No. 1 of the Central No. 4 claim, bears S. 29°50'W., 2.45 chs. dist. These corners are hereinafter described.</p>
15.02	<p>Draw, course S. 60°E.; ascend 467 ft. over E. slope to top of spur.</p>
17.72	<p>Intersect the S. end line of the Central No. 4 mining claim.</p> <p>From this point, cor. No. 1, bears S. 49°20'E., 3.15 chs. dist., and cor. No. 2, bears N. 49°20'W., 6.11 chs. dist. These corners are hereinafter described.</p>
27.52	<p>Spur, slopes SE.; ascend 136 ft. over SE. slope.</p>
37.77	<p>Spur ridge, slopes S.; enter dense undergrowth and descend 78 ft. over SW. slope to</p>
40.14	<p>Intersect the cor. of secs. 21, 22, 27 and 28, which is a limestone, 12x4x5 ins. above ground, firmly set, marked with 2 notches on S. and 3 notches on E. edges, and witnessed by a mound of stone W. and two pine bearing trees, rather than juniper trees, as of record.</p> <p>Reconstruct this corner monument as follows:</p>

Resurvey: Subdivision lines bounding sec. 22, T. 15 S., R. 22 E.

5.

Chains Remove stone and in same place, set an iron post, 3 ft. long, 2 ins. in diam., 15 ins. in ground to bedrock over a cross (+) chiseled thereon, with old stone buried alongside, and in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28, with brass cap marked

T15S	R22E
S21	S22
S28	S27

1941

. from which

A pine, 8 ins. in diam., bears N.  $79\frac{1}{2}^{\circ}$ E., 19 lks. dist., marked T15S R22E S22 BT. (old tree)

A pine, 8 ins. in diam., bears N.  $32\frac{1}{2}^{\circ}$ W., 95 lks. dist., marked T15S R22E S21 BT. (old tree)

No other bearing trees available.

From the cor. of secs. 21, 22, 27 and 28.

N.  $0^{\circ} 10'$  E., on true line, bet. secs. 21 and 22 (S. $\frac{1}{2}$ ).

Over mountainous land, thru scattering timber and dense undergrowth.

Ascend 14 ft. over SW. slope.

- 3.00 Spur, slopes W.; descend 236 ft. over NW. slope.
- 15.15 Ravine, course W.; ascend 113 ft. over SW. slope.
- 23.80 Saddle in ridge, bearing E. and W.; descend 379 ft. over broken NW. slope.
- 38.00 Spur, slopes N.  $80^{\circ}$ W.; descend 30 ft. over N. slope.
- 41.30 Ravine, course W.; ascend slightly to
- 42.47. Intersect the  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, which is a limestone, 12x10x6 ins. above ground, firmly set, marked  $\frac{1}{4}$  on W. face, and witnessed by a mound of stone W.

Reconstruct this cor. monument as follows:

Remove stone and in same place, set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in ground to bedrock over a cross (+) chiseled thereon, with old stone buried alongside, and in a mound of stone to top, for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, with brass cap marked

S21	S22
-----	-----

1941

No bearing trees available.

Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Thence

N.  $0^{\circ} 04'$  W., on true line, bet. secs. 21 and 22 (N. $\frac{1}{2}$ ).

Over mountainous land.

Along W. slope.



Resurvey: Subdivision lines bounding sec. 22, T. 15 S., R. 22 E.

6.

Chains							
4.03	Drain, course NW.; descend 30 ft.						
5.53	Ravine, course S. 60°W.; ascend 227 ft. over S. slope.						
13.57	Ridge, bears N. 80°W. and S. 80°E. From this point, peak "B" on ridge, bears S. 80½°E. Descend 402 ft. over N. slope.						
24.05	Ravine, course N. 10° W.; descend 215 ft. over NW. slope.						
37.03	Point of spur slopes NW.; descend 10 ft.						
37.33	Same ravine, course N. 30°E.; ascend slightly along E. slope to.						
39.05	Intersect the cor. of secs. 15, 16, 21 and 22, which is a granite stone, 12x12x8 ins. above ground, firmly set, marked 15S on NE. and 22E on SE. faces, and 3 notches on S. and E. edges, and witnessed by a mound of stone W. and one oak bearing tree as of record. Reconstruct this cor. monument as follows: Remove the stone and in same place, set an iron post, 3 ft. long, 2 ins. in diam., 18 ins. in ground to bedrock over a cross (+) chiseled thereon, with old stone buried alongside, and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap marked						
	<table border="1"> <tbody> <tr> <td>T15S</td> <td>R22E</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> </tbody> </table>	T15S	R22E	S16	S15	S21	S22
T15S	R22E						
S16	S15						
S21	S22						
	1941						
	from which						
	An oak, 24 ins. in diam., bears N. 23° W., 20 lks. dist., marked T15S R22E S16 BT. (old tree)						
	No other bearing trees available.						
	Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.						
	From the cor. of secs. 14, 15, 22 and 23. N. 89° 50'W., on true line, bet. secs. 15 and 22 (E.½). Over rolling and mountainous land, thru scattering timber and medium undergrowth. Ascend 57 ft. over NE. slope.						
9.00	Spur, slopes NE.; thence along N. slope.						
9.21	Peak "A", bears S. 63½°W.						
11.10	Wash, 60 lks. wide, 6 ft. deep, course N. 60°E.; ascend 63 ft. over gentle NE. slope to point of spur.						
13.50	Road, bears NE. and SW.						
30.00	Point of spur, slopes NE.; descend slightly.						
31.10	Drain, course NE.; ascend 39 ft. over E. slope.						
35.00	Spur, slopes NE.; descend slightly.						

Resurvey: Subdivision lines bounding sec. 22, T. 15 S., R. 22 E.

Survey: CENTRAL NO. 1 mining claim.

RECORD BOOK

7.

Chains

- 38.00 Drain, course NE.; ascend 60 ft. over E. slope to
- 40.14 Intersect the  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, which is a cross (+), cut in the exposed bedrock, witnessed by a mound of stone N.
- Reconstruct this cor. monument as follows:
- Over the cross (+) set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, with brass cap marked
- $\frac{1}{4}$   $\frac{S\ 15}{S\ 22}$
- 1941
- No bearing trees available.
- Thence
- N.  $89^{\circ} 59'$  W., on true line bet. secs. 15 and 22 ( $W.\frac{1}{2}$ ).
- Over mountainous land.
- Ascend 514 ft. over E. slope.
- 15.66 Ridge, bears N.  $5^{\circ}$  E. and S.  $5^{\circ}$  W.
- From this point, Peak "A", bears S.  $5\frac{1}{2}^{\circ}$  W., Peak "B", on main ridge of Lime Mountain, bears S.  $19\frac{1}{4}^{\circ}$  W.
- Descend 455 ft. over W. slope.
- 34.66 Wash, in ravine, 40 lks. wide, course N.  $30^{\circ}$  W.; thence along N. slope.
- 37.90 Old barbed wire fence, bears NW. and SE.
- 38.40 Drain, course N.; ascend slightly to
- 39.77 Intersect the cor. of secs. 15, 16, 21 and 22.

The following notes describe a metes-and-bounds survey of a tract of land in secs. 22 and 27, T. 15 S., R. 22 E., classified as mineral bearing, but not covered by mineral patent surveys, known as the Central Nos. 1 to 6, incl., mining claims. The claims were located on January 1, 1911, by J.L. Brooks, Peter Dworacyk, J.E. Ball, and L.M. Ball, and were recorded on January 24 of the same year. Mr. Peter Dworacyk, present claimant of the property, was on the ground at the time of the survey and identified the position of the location monuments, which have been obliterated subsequent to their establishment.

The purpose of the survey of these claims is to segregate them from sec. 22 and to provide legal designation and area for the Stockraising Homestead Entry of Fae E. Hurst, Phoenix 075694, which covers the  $W.\frac{1}{2}$  of sec. 22.

#### CENTRAL NO. 1 MINING CLAIM

Begin at the SE. cor. of the location, identical with the NE. cor. of the Central No. 3 claim, which falls in the bottom of a deep ravine course SE. where it is impracticable to monument the cor., therefore establish witness cor., N.  $49^{\circ} 20'$  W., 0.75 chs. dist., as hereinafter described.


Survey: CENTRAL NO. 1 mining claim.

8.

Chains	<p>From the true point for cor., The <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27, bears S. <math>15^{\circ}10'W.</math>, 11.54 chs. dist.</p>
	<p>From point for Cor. No. 1,</p>
	<p>N. <math>49^{\circ}20'W.</math>, on S. end line (1-2).</p>
	<p>Over mountainous land, thru scattering timber and medium undergrowth.</p>
	<p>Ascend 138 ft. over E. slope to top of spur.</p>
0.75	<p>Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in ground to bedrock over a cross (+) chiseled there on, and in a mound of stone to top, for witness cor. to cor. No. 1 of this claim and to cor. No. 1 of the Central No. 3 claim, with brass cap marked</p>
	<p>No bearing trees available.</p>
	<p>From this witness cor.,</p>
	<p>NW. cor. of blacksmith shop, bears S. <math>0^{\circ}11'E.</math>, 1.01 chs. dist.</p>
	<p>Portal of tunnel, approximately 700 ft. long, running N. <math>75^{\circ}W.</math>, bears S. <math>50\frac{1}{2}^{\circ}W.</math>, 1.45 chs. dist.</p>
	<p>Mouth of shaft, approximately 60 ft. deep, bears N. <math>73\frac{3}{4}^{\circ}W.</math>, 3.15 chs. dist..</p>
	<p>Portal of short tunnel, bears N. <math>71\frac{1}{2}^{\circ}W.</math>, 6.39 chs. dist.</p>
	<p>Portal of short tunnel, bears N. <math>77^{\circ}W.</math>, 6.40 chs. dist.</p>
7.50	<p>Short spur, slopes N. <math>80^{\circ}E.</math>; ascend slightly to</p>
9.26	<p>The SW. cor. of this claim, identical with the SE. cor. of the Central No. 2 claim, NW. cor. of the Central No. 3 claim, and NE. cor. of the Central No. 4 claim.</p>
	<p>Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in ground to bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 2 of this claim, cor. No. 1 of the Central No. 2 claim, and cors. Nos. 4 of the Central No. 3 and No. 4 claims, with brass cap marked</p>
	<p>No bearing trees available.</p>
	<p>Thence</p>
	<p>N. <math>29^{\circ}50'E.</math>, on W. side line (2-3).</p>
	<p>Along E. slope.</p>

## Survey: CENTRAL No.1 and CENTRAL No.2, mining claims.

.9.

chains	
1.30	Draw, course N. 80° E., ascend 78 ft. over S. slope..
8.50	Ridge, bears N. 70° W. and S. 70° E.; descend 196 ft. over N. slope.
14.23	Drain, course NE.; descend 32 ft. over NE. slope.
16.00	Point of spur, from W.; descend 58 ft. over N. slope.
18.13	Ravine, course E.; ascend 86 ft. over SE. slope to
22.73	True point for NW. cor. of this claim and NE. cor. of the Central No. 2 claim falls on a steeply sloping rock ledge where it is impracticable to establish cor. monument, therefore cut a cross (+) on the ledge at the true point for cor. and establish witness cor., N. 49°20' W., 0.15 ch. dist., as hereinafter described in the survey of the Central No. 2 claim.
	Thence
	S. 49°20' E., on N. end line (3-4).
	Descend 141 ft. over SE. slope.
5.75	Ravine, course E.; thence, along N. slope to
9.26	The NE. cor. of the location.
	Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in ground to bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for Cor. No. 4, with brass cap marked
	
	No bearing trees available.
	Thence
	S. 29°50' W., on E. side line (4-1).
	Ascend 324 ft. over N. slope.
12.20	Ridge, bears W. and S. 60° E.; descend 205 ft. over S. slope to
22.73	Intersect true point for cor. No. 1, the place of beginning
<u>CENTRAL NO. 2 MINING CLAIM</u>	
	Begin at cor. No. 1, the SE. cor. of the location, identical with cor. No. 2 of the Central No. 1 claim, cor. No. 4 of the Central No. 3 claim, and cor. No. 4 of the Central No. 4 claim, hereinbefore described in the survey of the Central No. 1 claim.
	Thence
	N. 49°20' W., on S. end line (1-2).
	Over mountainous land, thru scattering timber and medium undergrowth.
	Ascend slightly.
1.50	Drain, course N. 80° E.; ascend 247 ft. over SE. slope to


## Survey: CENTRAL No.2 mining claim.

10.

Chains  
9.26

The SW. cor. of this claim, identical with the NW. cor. of the Central No. 4 claim and the NE. cor. of the Central No. 5 claim.

Set an iron post, 3 ft. long, 1 in. in diam., on the exposed bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 2 of this claim, cor. No. 3 of the Central No. 4 claim, and cor. No. 2 of the Central No. 5 claim, with brass cap marked



1941

No bearing trees available.

Thence

N. 29°50' E., on W. side-line (2-3).

Ascend 84 ft. over SE. slope.


6.80 Rocky ridge, bears E. and W.; descend 285 ft. over N. slope.

10.53 Drain, course E.; ascend 57 ft. over S. slope.

19.70 Ridge, bears E. and W.; descend 95 ft. over NW. slope to

22.73 The NW. cor. of the claim.

Set an iron post, 3 ft. long, 1 in. in diam., on exposed bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 3, with brass cap marked



1941

No bearing trees available.


Thence

S. 49°20' E., on N. endline (3-4).

Ascend 76 ft. over NW. slope.

2.75 Ridge, bears E. and W.; descend 235 ft. over SE. slope to true point for cor. No. 4.

9.11 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in ground to bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for witness cor. No. 4 of this claim and witness cor. No. 3 of the Central No. 1 claim, with brass cap marked



1941

Survey: CENTRAL No.2 and CENTRAL No.3, mining claims.

11.

Chains No bearing trees available.

9.26 True point for cor. No. 4.  
Thence  
S. 29°50' W., on E. side line (4-1).  
Descend 86 ft. over SE. slope.

4.60 Ravine, course E.; ascend 58 ft. over N. slope.

6.73 Point of spur, from W.; ascend 32 ft. over NE. slope.

8.50 Drain, course NE.; ascend 196 ft. over N. slope.

14.23 Ridge, bears N. 70° W. and S. 70° E.; descend 78 ft. over S. slope.

21.43 Draw, course N. 80° E.; thence, along E., slope to

22.73 Intersect cor. No. 1, the place of beginning.

CENTRAL NO. 3 MINING CLAIM

Begin at cor. No. 1, the NE. cor. of the location, identical with cor. No. 1 of the Central No. 1 claim, the witness cor. of which is hereinbefore described in the survey of Central No. 1 claim.

Thence

S. 29°50' W., on E. side line (1-2).

Over mountainous land, thru scattering timber and medium undergrowth.

Leaving ravine bottom, ascend 63 ft. along E. slope.

6.20 Drain, course E.; ascend 76 ft. over NE. slope.

12.00 Short spur; slopes E.; thence, along E. slope.

12.91 Intersect line bet. secs. 22 and 27, T. 15 S., R. 22 E. at a point; S. 88°24' W.; 3.44 chs. dist. from the  $\frac{1}{4}$  sec. cor. thereof.

13.30 Spur, slopes E.; descend 50 ft. over S. slope.

20.70 Ravine, course E.; ascend 11 ft. to

22.73 The SE. cor. of the location, identified by Mr. Peter Dworacyk, is a rotted wood post, 4 ins. square, projecting 12 ins. above ground, set in a small mound of stone, and witnessed by two bearing rocks. Remove wood post and in same place, set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in ground, with a stone, ~~6x4x3~~ ins. marked with a cross (+) deposited at base, and in a mound of stone to top, for cor. No. 2, with brass cap marked



1941

from which

A limestone, 24x18x8 ins. above ground, bears N. 67°20' E., 14 lks. dist., marked +. BR. (old bearing rock)

## Survey: CENTRAL NO. 3 mining claim.

12.

Chains	<p>A limestone, 12x12x4 ins. above ground, bears N. 22°53' W., 9 lks. dist., marked + BR. (old bearing rock)</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>From this cor.: The <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27, bears N. 44°01' E., 11.93 chs. dist.</p> <p>Thence</p> <p>N. 49°20' W., on S. end line (2-3).</p> <p>Ascend 164 ft. over E. slope.</p> <p>6.00 Short spur, slopes E.; ascend 79 ft. over NE. slope.</p> <p>9.26 The SW. cor. of this claim, identical with the SE. cor. of the Central No. 4 claim.</p> <p>Set an iron post, 3 ft. long, 1-in. in diam., on exposed bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 3 of this claim and cor. No. 1 of the Central No. 4 claim, with brass cap marked</p> <div style="text-align: center;"> <p>1941</p> </div> <p>No bearing trees available.</p> <p>Thence</p> <p>N. 29°50' E., on W. side line (3-4).</p> <p>Descend 44 ft. over NE. slope.</p> <p>2.42 Ravine, course S. 80° E.; ascend 76 ft. over S. slope to top of spur.</p> <p>2.45 Intersect line bet. secs. 22 and 27, T. 15 S., R. 22 E. at a point, S. 88°24' W.; 14.09 chs. dist. from the <math>\frac{1}{4}</math> sec. cor. thereof.</p> <p>6.20 Short spur; slopes S. 80° E.; descend 75 ft. over NE. slope</p> <p>10.90 Ravine, course E.; thence, ascend 5 ft. over SE. slope.</p> <p>11.85 Point of spur slopes E.; desc. 20 ft. over NE. slope.</p> <p>12.85 Drain, course E.</p> <p>From this point.: portal of a short tunnel, bears W., 50 lks. dist.</p> <p>Descend 122 ft. along E. slope to</p> <p>22.73 Intersect cor. No. 4, the NW. cor. of this claim, cor. No. 2 of the Central No. 1 claim, cor. No. 1 of the Central No. 2 claim, and cor. No. 4 of the Central No. 4 claim, hereinbefore described in the survey of the Central No. 1 claim.</p> <p>Thence</p> <p>S. 49°20' E., on N. end line (4-1).</p> <p>Descend slightly.</p> <p>1.76 Short spur, slopes N. 80° E.; descend 138 ft. over E. slope.</p>
--------	---

Survey: CENTRAL No.3 and CENTRAL No.4, mining claims.

Chains

- 8.51 The witness cor. No. 1 of this claim and of the Central No. 1 claim, hereinbefore described in the survey of Central No. 1 claim.
- 9.26 Intersect true point for cor. No. 1, the place of beginning.

CENTRAL NO. 4 MINING CLAIM

Begin at cor. No. 1, the SE. cor. of the location, identical with cor. No. 3 of the Central No. 3 claim, hereinbefore described in the survey of Central No. 3 claim.

Thence

N. 49°20' W., on S. end line (1-2).


Over mountainous land, thru scattering timber and medium undergrowth.

Ascend 236 ft. over NE. slope to cor. No. 2.

- 3.15 Intersect line bet. secs. 22 and 27, T. 15 S., R. 22 E. at a point, S. 88°24' W., 17.72 chs. dist. from the  $\frac{1}{4}$  sec. cor. thereof.

- 9.26 The SW. cor. of the location.

Set an iron post, 3 ft. long, 1 in. in diam., on exposed bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 2, with brass cap marked



No bearing trees available.

Thence

N. 29°50' E., on W. side line (2-3).

Ascend 32 ft. over SE. slope.

- 2.30 Spur, slopes E.; descend 23 ft. along E. slope.
- 4.21 Intersect cor. No. 3 of the Central No. 6 claim, hereinafter described..
- 13.47 Intersect cor. No. 3 of the Central No. 5 claim and cor. No. 2 of the Central No. 6 claim, hereinafter described.
- 16.03 Ravine, course NE.; ascend slightly.
- 18.03 Drain, course N. 50° E.; ascend 10 ft. over SE. slope to
- 22.73 Intersect cor. No. 3, the NW. cor. of this claim, cor. No. 2 of the Central No. 2 claim, and cor. No. 2 of the Central No. 5 claim, hereinbefore described in the survey of the Central No. 2 claim.

Thence

S. 49°20' E., on N. end line (3-4).

Descend 247 ft. over SE. slope.

- 7.76 Drain, course N. 80° E.; descend slightly.



Survey: CENTRAL No.4 and CENTRAL No.5, mining claims.


14.

Chains 9.26	Intersect cor. No. 4, the NE. cor. of this claim, identical with cor. No. 2 of the Central No. 1 claim, cor. No. 1 of the Central No. 2 claim, and cor. No. 4 of the Central No. 3 claim, hereinbefore described in the survey of Central No. 1 claim.
	Thence S. 29°50' W., on E. side line (4-1). Ascend 122 ft. along E. slope.
9.88	Drain, course E. From this point: portal of a short tunnel, bears W., 50 lks. dist. Ascend 20 ft. over NE. slope.
10.88	Point of spur, slopes E.; descend 5 ft. over SE. slope.
11.83	Ravine, course E.; ascend 75 ft. over NE. slope.
16.53	Short spur, slopes S. 80° E.; descend 76 ft. over S. slope to ravine.
20.28	Intersect line bet. secs. 22 and 27, T. 15. S., R. 22. E. at a point, S. 88°24' W., 14.09 chs. dist. from the $\frac{1}{4}$ sec. cor. thereof.
20.31	Ravine, course S. 80° E.; ascend 44 ft. over NE. slope to
22.73	Intersect cor. No. 1, the place of beginning.

CENTRAL NO. 5 MINING CLAIM

Begin at the NW. cor. of the location at which

Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in ground to bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 1, with brass cap marked.



No bearing trees available..

From this cor.:

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, bears N. 74°18' W., 12.30 chs. dist.

Thence

S. 49°20' E., on N. side line (1-2).

Over mountainous land, thru scattering timber and dense undergrowth.

Ascend 123 ft. over SW. slope.

4.53 Saddle in ridge, bearing N. 10° W. and S. 10° E.; descend 100 ft. over E. slope.


Enter medium undergrowth..

10.03 Drain, course N. 30° E.; ascend 232 ft. over NW. slope.

## Survey: CENTRAL No. 5 mining claim.

15.

- Chains
- 15.23 Spur, slopes N. 15° E.; descend 310 ft. over SE. slope to cor. No. 2.
- 15.67 A flag on top of Lime Mountain, bears S. 51°26' W.
- 22.73 Intersect cor. No. 2, the NE. cor. of this claim, identical with cor. No. 2 of the Central No. 2 claim and cor. No. 3 of the Central No. 4 claim, hereinbefore described in the survey of Central No. 2 claim.
- Thence
- S. 29°50' W., on E. end line (2-3).
- Descend 10 ft. over SE. slope.
- 4.70 Drain, course N. 50° E.; descend slightly.
- 6.70 Ravine, course NE.; ascend 76 ft. over NE. slope to
- 9.26 The SE. cor. of this claim, identical with the NE. cor. of the Central No. 6 claim.
- Set an iron post, 3 ft. long, 1 in. in diam., on the exposed bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 3 of this claim and cor. No. 2 of the Central No. 6 claim, with brass cap marked



No bearing trees available.

Thence

N. 49°20' W., on S. side line (3-4).

Ascend 12 ft. over NE. slope.

0.73 Drain, course N. 30° E.; ascend 50 ft.

2.73 Drain, course NE.; ascend 360 ft.

10.48 Top of limestone rim, 30 ft. high, bears N. and S.; ascend 12 ft.


11.23 Spur, slopes N. 20° E.; thence, along broken N. slope.

15.03 Ridge, bears N. 10° W. and S. 10° E.; descend 288 ft. over broken W. slope to cor.

Enter dense undergrowth.


22.73 The SW. cor. of this claim, identical with the NW. cor. of the Central No. 6 claim.

Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in ground to bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 4 of this claim and cor. No. 1 of the Central No. 6 claim, with brass cap marked



Survey: CENTRAL No.5 and CENTRAL No.6, mining claims.

16.

Chains	<p>No bearing trees available.</p> <p>Thence</p> <p>N. 29°50' E., on W. end line (4-1).</p> <p>Ascend slightly along broken W. slope.</p> <p>0.26 Spur, slopes N. 60° W.; descend 50 ft.</p> <p>4.26 Spur, slopes W.; descend 60 ft.</p> <p>8.26 Drain, course W.; ascend 10 ft. over SW. slope.</p> <p>9.26 Intersect cor. No. 1, the place of beginning.</p>
<p><u>CENTRAL NO. 6 MINING CLAIM</u></p>	
	<p>Begin at cor. No. 1, the NW. cor. of the location, identical with cor. No. 4 of the Central No. 5 claim, hereinbefore described in the survey of Central No. 5 claim.</p> <p>Thence</p> <p>S. 49°20' E., on N. side line (1-2).</p> <p>Over mountainous land, thru scattering timber and dense undergrowth.</p> <p>Ascend 288 ft. over broken W. slope.</p> <p>7.70 Ridge, bears N. 10° W. and S. 10° E.; thence along broken N. slope.</p> <p>Enter medium undergrowth.</p> <p>11.50 Spur, slopes N. 20° E.; descend 12 ft. over E. slope.</p> <p>12.25 Top of limestone rim, 30 ft. high, bears N. and S.; descend 360 ft.</p> <p>20.00 Drain, course NE.; descend 50 ft.</p> <p>22.00 Drain, course N. 30° E.; descend 12 ft. to</p> <p>22.73 Intersect cor. No. 2, the NE. cor. of this claim, identical with cor. No. 3 of the Central No. 5 claim, hereinbefore described in the survey of Central No. 5 claim.</p> <p>Thence</p> <p>S. 29°50' W., on E. end line (2-3):</p> <p>Ascend 143 ft. along broken E. slope.</p> <p>9.26 The SE. cor. of the claim.</p> <p>Set an iron post, 3 ft. long, 1 in. in diam., on exposed bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 3, with brass cap marked</p> <div style="text-align: center;">  <p>c 6 3 1941</p> </div> <p>No bearing trees available.</p>

## Survey: CENTRAL No.6 mining claim.

17.

Chains From this cor.: cor. No. 2 of the Central No. 4 claim, bears S. 29°50' W., 4.21 chs. dist.

Thence

N. 49°20' W., on S. side line (3-4).

Ascend 400 ft. over precipitious E. slope.

9.49 Ridge of Lime Mountain, bears N. 10° W. and S. 10° E.


From this point: a flag on crest of Lime Mountain, bears N. 6°58' W.

Enter dense undergrowth and descend 242 ft. over SW. slope.

22.73 Spur slopes W.

The SW. cor. of the claim.

Set an iron post, 3 ft. long, 1 in. in diam., 4 ins. in ground to bedrock over a cross (+) chiseled thereon, and in a mound of stone to top, for cor. No. 4, with brass cap marked



1941

No bearing trees available.

From this cor.:

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, bears N. 7°01' W., 21.53 chs. dist.

Thence

N. 29°50' E., on W. end line (4-1).

Descend 185 ft. over NW. slope.

7.26 Drain, course N. 50° W.; ascend 20 ft. along W. slope to

9.26 Intersect cor. No. 1, the place of beginning.

FINAL FIELD TEST OF INSTRUMENT

March 23, 1941; at the station of the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27, T. 15 S., R. 22 E., Gila and Salt River Meridian, Arizona, in latitude 32°06'13" N., and longitude 110°05'23" W., examine the adjustments of Gurley transit No. 371537 and find no errors. Then, using the reference point determined at this station by Polaris observation on March 15, 1941, as described at the beginning of these field notes, test the solar apparatus of this instrument as follows:

At 9h. 00m., a.m., app. t., set off 32°06' N. on the latitude arc; 1°04' N. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the latitude arc unchanged; observe the sun on the meridian, and obtain a reading of 1°07' N. on the declination arc, which agrees with the computed declination of the sun.

18.

At 3h. 00m., p.m., app. t., with the latitude arc unchanged; set off  $1^{\circ}10'$  N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within  $1'30''$  of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and has remained in such condition throughout the surveys described in the foregoing field notes.

Dragoon, Arizona  
March 24, 1941

I, Peter Dworacyk, claimant of the Central Mining Locations Nos. 1 to 6, inclusive, in Sections 22 and 27, T. 15 S., R. 22 E., Gila and Salt River Meridian, Arizona, do hereby affirm that the corner monuments of said locations have been obliterated and destroyed subsequent to their establishment, and that I have personally pointed out to Raymond F. Moss, Assistant Cadastral Engineer, the original positions of said corner monuments, and that to the best of my knowledge and belief the segregation survey executed by him is identical to the original positions of the claims described in the recorded location notices upon which the segregation is based.

Peter Dworacyk

Witnesses

George B McDewitt

Roy Mashburn

37  
20

NOTICE OF MINING LOCATION  
LODE CLAIM

---

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the Central No. 1 Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by J. L. Brooks, Peter Dworacyk, J. E. Ball and L.M. Ball Citizens of the U.S. the undersigned, on the First day of January, 1911.

The length of this claim is 1500 feet, and we claim 100 feet, in a northerly direction, and 1400 feet in a southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the Westerly to the Easterly.

The claim is situated and located in the Cochise Mining District, in Cochise County, in the Territory of Arizona, about  $1\frac{1}{2}$  miles in a Westerly direction from Johnson, Ariz.

Note: A relocation of Geo. Washington No. 12 formally owned by the Lime M't. Copper & Smelting Co.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a stone monument at a point in a northerly direction 100 feet from the discovery shaft (at which this notice is posted), being in the center of the north end line of said claim; thence 300 feet to a stone monument, being the North West corner of said claim; thence 1500 feet to a monument, being at the south west corner of said claim; thence 300 feet to a monument at the center of the south end of said claim; thence 300 feet to a monument being at the South East corner of said claim; thence 1500 feet to a monument at the north east corner of said claim; thence 300 feet to the place of beginning.

Dated and posted on the ground this First day of January, 1911.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.

Witness:  
L.W. Brooks.

J. L. Brooks  
Peter Dworacyk  
J.E. Ball  
L.M. Ball

Filed and recorded at request of J.E. Ball, Jan. 24 A.D. 1911  
at 9 A.M. Book 48, Pages 145.

C.A. McDonald  
County Recorder

By Geo. C. Gallen  
Deputy Recorder.

39  
22

4243

NOTICE OF MINING LOCATION  
LODE CLAIM

---

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the Central No. 2 Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by J. L. Brooks, Peter Dworacyk, J. E. Ball and L.M. Ball, Citizens of the U.S. the undersigned, on the First day of January, 1911.

The length of this claim is 1500 feet, and we claim 300 feet, in a northerly direction, and 1200 feet in a Southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the Westerly to the Easterly.

The claim is situated and located in the Cochise Mining District, in Cochise County, in the Territory of Arizona, about  $1\frac{1}{2}$  miles in a Westerly direction from Johnson, Arizona.

Note: A relocation of Geo. Washington No. 11 claim, formally owned by the Lime M't Copper & Smelting Co.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a stone monument at a point in a northerly direction 300 feet from the discovery shaft (at which this notice is posted), being in the center of the north end line of said claim; thence 300 feet to a stone monument, being the North West corner of said claim; thence 1500 feet to a monument, being at the South West corner of said claim; thence 300 feet to a monument at the center of the South end of said claim; thence 300 feet to a monument being at the South East corner of said claim; thence 1500 feet to a Monument at the North East corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona", approved March 16, 1901.

Dated and posted on the ground this First day of January, 1911.

Witness  
L. W. Brooks.

J. L. Brooks  
Peter Dworacyk  
J. E. Ball  
L.M. Ball

Filed and recorded at request of J. E. Ball, Jan. 24 A.D. 1911 at 9 A.M., Book 48 Pages 146.

C. A. McDonald  
County Recorder.

By Geo. C. Gallen  
Deputy Recorder.



41  
24

NOTICE OF MINING LOCATION  
LODE CLAIM

---

BOOK 4243

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the Central No. 3 Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by J. L. Brooks, Peter Dworacyk, J. E. Ball and L. M. Ball Citizens of the U.S. the undersigned, on the First day of January, 1911.

The length of this claim is 1500 feet, and we claim 50 feet, in a northerly direction, and 1450 feet in a Southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the Westerly to the Easterly.

The claim is situated and located in the Cochise Mining District, in Cochise County, in the Territory of Arizona, about  $1\frac{1}{2}$  miles in a Westerly direction from Johnson, Arizona.

Note: a relocation of Geo. Washington No. 10 claim, formally owned by the Lime M't. Copper & Smelting Co.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a stone monument at a point in a northerly direction 50 feet from the discovery shaft (at which this notice is posted), being in the center of the north end line of said claim; thence 300 feet to a stone monument, being the north west corner of said claim; thence 1500 feet to a monument, being at the south west corner of said claim; thence 300 feet to a monument at the center of the South end of said claim; thence 300 feet to a monument being at the South east corner of said claim; thence 1500 feet to a monument at the north east corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona", approved March 16, 1901.

Dated and posted on the ground this First day of January, 1911.

Witness  
L. W. Brooks.

J. L. Brooks,  
Peter Dworacyk  
J.E.Ball  
L.M.Ball

Filed and recorded at request of J. E. Ball, Jan. 24, A.D. 1911, at 9 A.M., Book 48 Pages 147.

C. A. McDonald  
County Recorder.

By Geo. C. Gallen  
Deputy Recorder.

43  
26

ECCOCK 4243

NOTICE OF MINING LOCATION  
LODE CLAIM

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the Central No. 4 Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by J. L. Brooks, Peter Dworacyk, J. E. Ball and L.M. Ball Citizens of the U.S. the undersigned, on the First day of January 1911.

The length of this claim is 1500 feet, and we claim 250 feet, in a Northerly direction, and 1250 feet in a Southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the Westerly to the Easterly.

The claim is situated and located in the Cochise Mining District, in Cochise County, in the Territory of Arizona, about 1½ miles in a Westerly direction from Johnson, Arizona.

Note: a relocation of the Geo. Washington No. 9 claim formally owned by the Lime M't Copper & Smelting Co.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a stone monument at a point in a northerly direction 250 feet from the discovery shaft (at which this notice is posted), being in the center of the north end line of said claim; thence 300 feet to a stone monument, being the North West corner of said claim; thence 1500 feet to a Monument, being at the South West corner of said claim; thence 300 feet to a monument at the center of the South end of said claim; thence 300 feet to a monument being at the South East corner of said claim; thence 1500 feet to a monument at the North East corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.

Dated and posted on the ground this First day of January, 1911.

Witness:  
L. W. Brooks

J. L. Brooks  
Peter Dworacyk  
J.E. Ball  
L.M. Ball

Filed and recorded at request of J.E. Ball Jan. 24, A.D. 1911, at 9 A.M., Book 48 Pages 148.

C. A. McDonald  
County Recorder.

By Geo. C. Gallen  
Deputy Recorder.

45  
20

NOTICE OF MINING LOCATION  
LODE CLAIM

---

BOOK 4248

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the Central No. 5 Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by J. L. Brooks, Peter Dworacyk, J. E. Ball and L. M. Ball Citizens of the U.S. the undersigned, on the First day of January, 1911.

The length of this claim is 1500 feet, and we claim 50 feet, in an Easterly direction, and 1450 feet in a Westerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the Westerly to the Easterly.

The claim is situated and located in the Cochise Mining District, in Cochise County, in the Territory of Arizona, about  $\frac{1}{2}$  miles in a Westerly direction from Johnson, Arizona.

Note: A relocation of the Geo. Washington No. 8 claim, formally owned by the Lime M't Copper & Smelting Co.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a stone monument at a point in an easterly direction 50 feet from the discovery shaft (at which this notice is posted), being in the center of the East end line of said claim; thence 300 feet to a stone monument, being the north East corner of said claim; thence 1500 feet to a monument, being at the North West corner of said claim; thence 300 feet to a monument at the center of the West end of said claim; thence 300 feet to a monument being at the south west corner of said claim; thence 1500 feet to a monument at the South East corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.

Dated and posted on the ground this First day of January, 1911.

Witness:  
L. W. Brooks.

J. L. Brooks,  
Peter Dworacyk  
J.E.Ball  
L.M.Ball

Filed and recorded at request of J.E.Ball Jan. 24, 1911  
at 9 A.M., Book 48 Pages 149.

C. A. McDonald  
County Recorder.

By Geo. C. Gallen  
Deputy Recorder.

47  
20

BOOK 4243

NOTICE OF MINING LOCATION  
LODE CLAIM

---

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the Central No. 6 Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by J. L. Brooks, Peter Dworacyk, J. E. Ball and L. M. Ball Citizens of the U.S. the undersigned, on the First day of January 1911.

The length of this claim is 1500 feet, and we claim 50 feet, in an Easterly direction, and 1450 feet in a Westerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the Westerly to the Easterly.

The claim is situated and located in the Cochise Mining District, in Cochise County, in the Territory of Arizona, about  $1\frac{1}{2}$  miles in a Westerly direction from Johnson, Arizona.

Note: A relocation of Geo. Washington No. 7 claim, formally owned by the Lime M't Copper & Smelting Co.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a stone monument at a point in an Easterly direction 50 feet from the discovery shaft (at which this notice is posted), being in the center of the East end line of said claim; thence 300 feet to a Stone monument, being the North East corner of said claim; thence 1500 feet to a monument, being at the North West corner of said claim; thence 300 feet to a monument at the center of the West end of said claim; thence 300 feet to a monument being at the South West corner of said claim; thence 1500 feet to a monument at the South East corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.

Dated and posted on the ground this First day of January, 1911.

Witness:  
L. W. Brooks.

J. L. Brooks,  
Peter Dworacyk  
J. E. Ball  
L.M.Ball

Filed and recorded at request of J.E.Ball, Jan. 24, A.D. 1911 at 9 A.M., Book 48 Page 150.

C. A. McDonald  
County Recorder.

By Geo. C. Gallen  
Deputy Recorder.

(13)

Kathryn G. Hutchison,  
County Recorder

BOOK 4243

Office of  
THE COUNTY RECORDER  
Cochise County, Arizona

CERTIFICATE 1804

STATE OF ARIZONA )  
                          ) SS.  
COUNTY OF COCHISE )

I, KATHRYN G. HUTCHISON, County Recorder in and for the County of Cochise, State of Arizona, do hereby certify that the annexed and foregoing are full, true and correct copies of Notices of Locations on Central No. 1 to 6 inclusive, located by J. L. Brooks, etal. bearing date of Jan. 1, 1911. as appears of record now in this office in Book 48 Record of Mines at Pages 145 to 150 inclusive.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed by official seal, at my office in Bisbee, this 28 day of March A.D. 1936.

(SEAL)

KATHRYN G. HUTCHISON  
County Recorder

By Frances Lippert  
Deputy



52  
1  
3

BOOK 4248

CERTIFICATE OF SURVEYOR

I, Raymond F. Moss, Assistant Cadastral Engineer HEREBY CERTIFY upon honor that, in  
pursuance of special instructions bearing date of the 20th day of September 1941,  
received from the district cadastral engineer for Arizona, with assignment  
instructions dated November 4, 1941, I have resurveyed the subdivisional lines bounding  
section 22, and surveyed the Central Nos. 1 to 6, incl., mining  
locations in secs. 22 and 27 of  
Township 15 South, Range 22 East  
of the Gila & Salt River Meridian, in the State of Arizona, which are  
represented in the foregoing field notes as having been executed by me and under my direction; and that said  
resurvey and  
survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey  
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.  
Phoenix, Arizona  
July 16, 1941

*Raymond F. Moss*  
Assistant Cadastral Engineer

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,  
Denver, Colorado, April 14, 1942.

The foregoing field notes of the resurvey of the subdivisional lines bounding  
section 22, and of the survey of the Central Nos. 1 to 6, incl.,  
mining locations in secs. 22 and 27, of Township 15 South, Range 22  
East of the Gila and Salt River Meridian, in the State of Arizona.  
executed by Raymond F. Moss, Assistant Cadastral Engineer,  
under special instructions dated Sept. 20, 1940 for Group 231, Arizona, and assignment  
instructions dated November 4, 1940, having been critically examined, and  
the necessary corrections made prior to their certification by the engineer, the said field notes, and the resurvey and  
survey therein described, are hereby approved.

*Frank A. Johnson*  
Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~  
~~is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~