

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

BOOK 4256

FIELD NOTES

OF SURVEY OF

WEST BOUNDARY,

NORTH BOUNDARY

(on the 10th Std. Parallel North)

AND

SUBDIVISIONAL LINES of

TOWNSHIP 40 NORTH, RANGE 9 WEST

Of the Gila and Salt River Meridian,

In the State of ARIZONA

EXECUTED BY

Horace M. Muscott, Surveyor,

Claude F. Warner, Transitman

and Frank Moteh, Public Land Surveyor

supplemental
Under special instructions dated April 30, 1936, which provided
for the surveys included under Group No. 210, Arizona, bearing the approval of the
Commissioner of the General Land Office under date of July 24, 1936
and assignment instructions dated April 11, 1939.

Survey commenced May 10, 1939

Survey completed June 26, 1939

4256

INDEX DIAGRAM.

Township _____, *Range* _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

INDEX-DIAGRAM

LOG. 4256

T.41N.-R.9W.												T.41N. R.8W.	
31		32		33		34		35		36		31	
10th		Standard		Parallel		North							
1	12	11	11	11	10	10	9	9	8				
	7	6	56	5	44	4	36	3	28	2	20	1	6
	6		55		43								
		55	55	54	43	43	36	35	28	27	20	19	
12	6	7	54	8	43	9	35	10	27	11	19	12	7
			53		42				26		18		
		53	53	52	42	42	34		26		18		
13	5	18	52	17	41	16	33	15	25	14	17	13	18
			51			T.40N.-R.9W.							
		51	50		41	40	33		25	24	17	16	
-24	5								24				
		19	49	20	40	21	32	22		23	16	24	19
	4								23				
		48	49	48		39		32	31	23		15	
25	4				39		31				15		
		30	47	29		28		27	22	24		25	30
	3				38		30				14		
		46	46	45	38	38	30	30		22	21	14	
36	3	31	45	32	37	33	29	34	21	35	13	36	31
			44										
1		6		5		4		3		2		1	6

- Lines of accepted surveys (surveyed 1925; accepted 1927)
- ==== Lines surveyed under this group along standard parallel, accomplished by establishment of closing cors. and 1/4 sec. cors. referring to areas S.
- Lines surveyed under this group in 1937.
- Lines surveyed under this group in 1939.
- Lines surveyed under group No. 211 in 1939.
- ==== Lines surveyed under group No. 211 along standard parallel where same was surveyed in 1925 and accepted in 1927.
- Areas surveyed (1925) as per accepted (1927) plats on file.

The surveys herein described were executed by Horace M. Muscott, Surveyor, Claude F. Warner, Transitman, and Frank Motech, Public land Surveyor, using, respectively, Buff and Buff transits Nos. 16723 and 9984, and Young and Sons' transit No. 8526. Each of said instruments is equipped with an improved Smith solar attachment, and otherwise conforms to the standard specifications of the General Land Office.

The azimuths of all of the lines of survey herein described were determined with the solar attachments.

All of the measurements were made with Lufkin and Dietzen steel tapes, 5 chs. in length, graduated every link for the first 100 lks., and the remainder at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard tape and found correct. All of the measurements were made on the slope, the vertical angle of each interval determined with a clinometer in good adjustment, and the horizontal equivalents entered in the field notes.

PRELIMINARY FIELD TESTS OF INSTRUMENTS.

Buff and Buff transit No. 16723
Horace M. Muscott, Surveyor.

May 7, 1939;

At station in camp near center of sec. 22, T.39 N., R.10 W., G. and S.R. meridian, Arizona, latitude $36^{\circ}46'N.$, longitude $113^{\circ}21\frac{1}{2}'W.$, examine the adjustments of Buff and Buff transit No. 16723 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with a true meridian determined at this station, on April 29, 1939, by Polaris observation, as described in field notes of survey of West and North bdrs. and subdivisional lines of T.39 N., R.9 W., executed under this group, proceed as follows:

At 8h. 00m., a.m., app. t., set off $36^{\circ}46'N.$ on the lat. arc; $16^{\circ}41\frac{1}{2}'N.$ on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $16^{\circ}44'N.$ on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app. t., with the lat. arc unchanged; set off $16^{\circ}47'N.$ on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, prior to the beginning of the surveys executed with same which are described in the field notes herein.

Buff and Buff transit No. 9984.
Claude F. Warner, Transitman.

June 18, 1939;

At station in camp near the cor. of secs. 3, 4, 33 and 34, Ts. 38 and 39 N., R.9 W., latitude $36^{\circ}43\frac{1}{2}'N.$, longitude $113^{\circ}15\frac{1}{2}'W.$, examine the adjustments of Buff and Buff transit No. 9984 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with a true meridian established at this station on June 11, 1939,

by Polaris observation, by Horace M. Muscott, Surveyor, as described in field notes of resurvey of West bdy., and survey of North bdy. and Subdivisional lines of T.38 N., R.9 W. executed under this group, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}43\frac{1}{2}'$ N. on the lat. arc; $23^{\circ}24\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $23^{\circ}24\frac{1}{2}'$ N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $23^{\circ}25'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, prior to the beginning of the surveys executed with same which are described herein.

Young and Sons' transit No.8526.
Frank Moteh, Public Land Surveyor.

June 18, 1939;

At same station where the preceding test of instrument was made, examine the adjustments of Young and Sons' transit No.8526 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with the same true meridian, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}43\frac{1}{2}'$ N. on the lat. arc; $23^{\circ}24\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $23^{\circ}24\frac{1}{2}'$ N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $23^{\circ}25'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, prior to the beginning of the surveys executed with same which are described herein.

Survey: West Boundary of T. 40 N., R. 9 W.

BOOK 4256.

Chains

From the cor. of Ts. 39 and 40 N., Rs. 9 and 10 W., which is an iron post, 3 ins. in diam., set, marked, and witnessed as described in the field notes of T. 39 N., R. 9 W., surveyed under this group.

Thence,
North, bet. secs. 31 and 36.
Over rolling land, thru low scattering undergrowth.
Desc. 55 ft. over NE. slope to
17.70 Bottom of draw, course SE. Asc. 76 ft. over SW. slope to
30.35 Top of rocky spur, slopes SE. Desc. 23 ft. over NE. slope to
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S36|S31
1939

raise a mound
of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Continue over NE. slope. Desc. 17 ft. to
50.00 Bottom of draw, course SE., heads approx. 20 chs. NW.
Asc. 86 ft. over SW. slope.

75.00 Top of ridge, brs. N. 10° E. and SW. Along a W. slope to
80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 5 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 25, 30, 31, and 36, with brass cap marked

T40N
R10W R9W
S25|S30
S36|S31
1939

Land, rolling plateau.
Soil, rocky, 3rd and 4th rates.
No timber.
Undergrowth, sage, cliff rose, and Mormon tea. Fair grass.

North, bet. secs. 25 and 30.
Over rolling land, thru low scattering undergrowth.
Asc. 23 ft. along a W. slope to
4.50 Top of ridge, brs. N. 20 W. and S. 20° E. Desc. 183 ft. over E. slope to
39.80 Ungraded road, brs. SE. and NW.
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S25|S30
1939

Survey: West Boundary of T. 40 N., R. 9 W.

4.

Chains	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Continue over NE. slope. Desc. 20 ft.
43.20	Draw, course SE., heads 5.00 chs. NW. Asc. 121 ft. over SW. slope.
53.40	Top of ridge, in saddle, brs. SE. and W. Desc. 160 ft. over steep NE. slope to
60.00	Base of steep descent, brs. SE. and W. Continue over gradual NE. slope. Desc. 73 ft. to
77.10	Draw, course NE. Asc. 10 ft. over gradual SE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 6 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top for the cor. of secs. 19, 24, 25; and 30, with brass cap marked
	T40N R10W R9W S24 S19 S25 S30 1939
	Land, rolling plateau. Soil, rocky clay, 3rd and 4th rates. No timber. Undergrowth, sage, cliff rose, Mormon tea, and cacti. Good grass.
	North, bet. secs. 19 and 24. Over rolling land, thru low scattering undergrowth. Asc. 31 ft. over SE. slope to
4.50	Small knob on top of low spur, slopes NE., approx. 5 chs. to toe. Desc. 55 ft. over N. slope to
8.20	Ravine, 3 lks. wide, course E. Asc. 154 ft. over SE. slope to
24.50	Top of sharp spur, slopes E., approx. 12 chs. to toe. Desc. 60 ft. over N. slope to
30.90	Wash, in bottom of draw, 12 lks. wide, course E. Asc. 90 ft. over S. slope to
38.50	Top of spur, slopes E. Desc. 5 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground, over cross (+) on solid rock, and in a mound of stone to top, for the 2 sec. cor. with brass cap marked
	1/4 S24 S19 1939
	Desc. 33 ft. over N. slope to
43.50	Ravine, course E., heads approx. 5 chs. W. Asc. 30 ft. over S. slope to

Survey: West Boundary of T. 40 N., R. 9 W.

5.

BOOK 4256

Chains	
47.00	Slope changes to rolling E. slope.
60.00	Dim road, brs. NE. and SW.
62.00	Top of spur, slopes E.; descend 105 ft. over steep NW. slope to
70.00	Foot of steep slope, bears NE. and SW.; descend 20 ft. over gradual NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 13, 18, 19, and 24, with brass cap marked
	T40N R10W R9W S13 S18 S24 S19 1939
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling plateau. Soil, sandy to rocky, 3rd and 4th rates. No timber. Undergrowth, sage, cliff rose, Mormon tea, and cacti. Good grass.
	North, bet. secs. 13 and 18. Over rolling land, thru low scattering undergrowth. Desc. gradually over NW. slope to
1.20	Bottom of draw, course northerly, from S. 20° W. Desc. gradually along same draw to
20.60	Leave bottom of draw, course N. 80° E. from S.; ascend 62 ft. over SE. slope.
28.00	Top of spur, slopes NE.; approx. 6 chs. to toe. Desc. 61 ft. over NE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground, over a cross (+) on solid rock, and in a mound of stone to top, for the ¼ sec. cor., with brass cap marked
	¼ S13 S18 1939
	Desc. 16 ft. over gradual NE. slope to
48.40	Wash, 8 lks. wide, in bottom of draw, course N. 80° E. Asc. 61 ft. over SE. slope to
62.00	Top of spur, slopes NE. Desc. 97 ft. over NW. slope to
78.90	Wash, 6 lks. wide, in bottom of draw, course E. Asc. 3 ft. along a gradual E. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 7, 12, 13, and 18, with brass cap marked

Survey: West Boundary of T. 40 N., R. 9 W.


6.

Chains	
	<p style="text-align: center;">T40N R10W R9W S12 S7 S13 S18 1939</p> <p>of stone, 3 ft. base, 2½ ft. high W. of cor. raise a mound</p> <p>Land, rolling plateau. Soil, rocky clay, 3rd rate. No timber. Undergrowth, sage, cliff rose, Mormon tea, and cacti. Good grass.</p>
	<p>North, bet. secs. 7 and 12. Over nearly level land, thru low scattering undergrowth. Desc. slightly over a gradual E. slope.</p> <p>17.60 Drain, course NE. Asc. gradually over SE slope.</p> <p>34.70 Dim road, brs. SE. and NW.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor., with brass cap marked</p> <p style="text-align: center;">¼ S12 S7 1939</p> <p>of stone, 3 ft. base, 2½ ft. high, W. of cor. raise a mound</p> <p>Continue over a gradual SE slope.</p> <p>41.00 Drain, course SE. Asc. 85 ft. over a rolling SW. slope.</p> <p>65.60 Dim road, brs. E. and W. on spur sloping E, desc. 25 ft. over N. slope.</p> <p>73.00 Slope changes to SW. Asc. 10 ft. to</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 1, 6, 7, and 12, with brass cap marked</p>
	<p style="text-align: center;">T40N R10W R9W S1 S6 S12 S7 1939</p> <p>of stone, 4 ft. base, 3 ft. high, W. of cor. raise a mound</p> <p>Land, nearly level to gently rolling. Soil, sandy, 2nd and 3rd rates. No timber. Undergrowth, sage and cacti. Good grass.</p>
	<p>North, bet. secs. 1 and 6. Over gently rolling land, thru dense undergrowth. Asc. 18 ft. over SW. slope to</p> <p>5.00 Top of flat spur, slopes NW. Desc. 64 ft. over rolling NW. slope to</p>

Survey: West Boundary of T. 40 N., R. 9 W.

Chains
40:00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Continue over gently rolling land.


Along general W. slope, with slight change in elevation.

49.70 Dim road, bears NE. and SW.

66.60 Drain, course SW.; ascend slightly over SE. slope to

75.98 Intersect the 10th Standard Parallel North.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, for closing cor. of Ts. 40 N., Rs. 9 and 10 W., with brass cap marked



raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

The standard cor. of Ts. 41 N., Rs. 9 and 10 W. bears West, 24.03 chs. dist., and the standard $\frac{1}{4}$ sec. cor. of sec. 31 bears East, 15.97 chs. dist., both being regulation brass-capped iron posts, set, marked, and witnessed as described in the official record.

Land, gently rolling.

Soil, rocky, 3rd. rate.

Timber, none.

Undergrowth, sagebrush, Mormon tea and cacti.

Good grass.

Survey of North Boundary of T. 40 N., R. 9 W.
(on the 10th Standard Parallel North)

Chains	<p>The following notes describe the survey of the North bdy. of T. 40 N., R. 9 W., along 10th Std. Parallel North, from the closing cor. of Ts. 40 N., Rs. 8 and 9 W. West to the closing cor. of Ts. 40 N., Rs. 9 and 10 W., accomplished by the establishment thereon of subdivisional closing cors. and N. $\frac{1}{4}$ sec. cors. of the north tier of secs. of T. 40 N., R. 9 W. The standard parallel was surveyed thru Rs. 8 and 9 W. by W.E. Hiester, U.S. Surveyor, in December, 1924 and January, 1925, and no retracement or resurvey of the line in any part of these two ranges is of record.</p> <p>No retracement of the parallel in Rs. 8 and 9 W. was made as a preliminary process to this survey, the bearing of same and the measurements of the corner intervals, described in the official record being accepted without change.</p> <p>The lengths of the N. bdrs. of the N. tier of secs. of T. 40 N., R. 9 W., and the points for the N. $\frac{1}{4}$ sec. cors. thereof are computed from the official record, chaining only the connecting distances bet. the closing cors. and the std. cors. on which they close, and the computed offset distances bet. the $\frac{1}{4}$ sec. cors. To present the survey in proper form, the topography and other pertaining data is copied from the official record, computing the stations of the topographical and other features as required to give them the proper relation to the governing cors. of this survey.</p>
	<p>The closing cor. of Ts. 40 N., Rs. 8 and 9 W., established under this group, is an iron post, 3 ins. diam., projecting 8 ins. above ground, firmly set, and described in the field notes of survey of West bdy. of T. 40 N., R. 8 W.</p>
Thence	<p>West, on N. bdy. of sec. 1 (S. of sec. 31, T. 41 N., R. 8 W.)</p>
20.26	<p>Over-rolling land, thru dense undergrowth. Intersect the std. cor. of Ts. 41 N., Rs. 8 and 9 W., a brass-capped iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.</p>
	<p>Continue line and measurement (S. of sec. 36, T. 41 N., R. 9 W.)</p>
25.76	<p>Wash, 50 lks. wide, course N.</p>
28.06	<p>Wash, 20 lks. wide, course NW.</p>
29.76	<p>Wash, 50 lks. wide, course N.</p>
40.07	<p>(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for N. $\frac{1}{4}$ sec. cor. of sec. 1, with brass cap marked</p> <p style="text-align: center;"> $\frac{1}{4}$ S1 1939 </p>
	<p style="text-align: right;">raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of cor.</p>
51.26	<p>Wash, 30 lks. wide, course NE.</p>
60.26	<p>Intersect the std. $\frac{1}{4}$ sec. cor. of sec. 36, a brass-capped iron post, 1 in. in diam., projecting 10 ins. above the ground, firmly set, marked and witnessed as described in the official record.</p>
	<p>Continue line and measurement.</p>

Survey of North Boundary of T. 40 N., R. 9 W.
(on the 10th Std. Parallel North)

BOOK 4258
PAGE 19.

Chains

- 69.26 Wash, 20 lks. wide, course N.
- 80.14 Intersect the subdivisional line bet. secs. 1 and 2, surveyed N. 0° 01' W.
Closing cor. of said secs. established at this point as hereinafter described.

Land, rolling.
Soil, clay loam and rocky, 1st, 2nd, and 4th rates.
Timber, a few cedar.
Undergrowth, oak, sage, yucca, buck brush, and cactus.
- From closing cor. of secs. 1 and 2.
West, on N. bdy. of sec. 2 (S. of sec. 36, T.41N., R.9W.)
Over rolling land, thru dense undergrowth.
- 20.12 Intersect the standard cor. of secs. 35 and 36, which is an iron post, 3 ins. diam., set, marked, and witnessed as described in the official record.
Continue line and measurement (S. of sec. 35, T. 41 N., R. 9 W.)
- 36.12 Wash, 10 lks. wide, course N.
- 39.98 (Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the N. $\frac{1}{4}$ sec. cor. of sec. 2, with brass cap marked

 $\frac{1}{4}$ S2
1939
raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, S. of cor.
- 52.45 Road, bears S. 27° E. and N. 27° W. (Bearing erroneously given as NE. and SW. in official record)
- 60.12 Intersect the standard $\frac{1}{4}$ sec. cor. of sec. 35, which is an iron post, 1 in. in diam., set, marked, and witnessed as described in the official record.
Continue line and measurement.
- 78.32 Drain, course S.
- 79.96 Intersect the subdivisional line bet. secs. 2 and 3, surveyed N. 0° 01' W.
Closing cor. of said secs. established at this point as hereinafter described.

Land, rolling.
Soil, rocky, 4th rate.
No timber.
Undergrowth, sagebrush, buckbrush, oak, and yucca.
- From closing cor. of secs. 2 and 3.
West, on N. bdy. of sec. 3 (S. of sec. 35, T.41N., R.9W.)
Over rolling land, through dense undergrowth.
- 20.16 Intersect the standard cor. of secs. 34 and 35, which is an iron post, 3 ins. in diam., set, marked, and witnessed as described in the official record.

Survey of North Boundary of T. 40 N., R. 9 W.
(on the 10th Std. Parallel North)

10.

Chains	
	Continue line and measurement (S. of sec. 34, T. 41 N., R. 9 W.)
	Desc. 115 ft. over W. slope to
27.56	Antelope Creek Wash, 150 lks. wide, course N. Asc. 115 ft. to
36.36	Top of ascent. Continue over rolling land.
39.96	(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground for the N. $\frac{1}{4}$ sec. cor. of sec. 3, with brass cap marked
	<u>$\frac{1}{4}$ S3</u> 1939
	raise a mound
	of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of cor.
60.16	Intersect the standard $\frac{1}{4}$ sec. cor. of sec. 34, which is an iron post, 1 in. in diam., set, marked, and witnessed as described in the official record.
	Continue line and measurement.
	Desc. 63 ft. to
72.46	Wash, 20 lks. wide, course NE. Asc. gradual E. slope.
79.93	Intersect the subdivisional line bet. secs. 3 and 4, surveyed N. 0° 02' W. Closing cor. of said secs. established at this point as hereinafter described.
	Land, rolling.
	Soil, rocky, 4th rate.
	No timber.
	Undergrowth, sagebrush, buckbrush, and oak.
	From closing cor. of secs. 3 and 4.
	West, on N. bdy. of sec. 4 (S. of sec. 34, T. 41 N., R. 9 W.)
	Over rolling land, through dense undergrowth.
	Asc. gradual E. slope.
10.23	Asc. 70 ft. to
20.23	Intersect the std. cor. of secs. 33 and 34, which is an iron post, 3 ins. in diam., set, marked, and witnessed as described in the official record.
	Continue line and measurement (S. of sec. 33, T. 41 N., R. 9 W.)
39.99	(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the N. $\frac{1}{4}$ sec. cor. of sec. 4, with brass cap marked
	<u>$\frac{1}{4}$ S4</u> 1939
	raise a mound
	of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, S. of cor.

Survey of North Boundary of T. 40 N., R. 9 W.
(on the 10th Std. Parallel North)

BOOK 4256 p. 11.

Chains	
50.23	Draw, course SW.
60.23	Intersect the standard $\frac{1}{4}$ sec. cor. of sec. 33, which is an iron post, 1 in. in diam., set, marked, and witnessed as described in the official record. Continue line and measurement.
79.98	Intersect the subdivisional line bet. secs. 4 and 5, surveyed N. $0^{\circ} 03' W.$ Closing cor. of said secs. established at this point as hereinafter described. Land, rolling. Soil, rocky, 4th rate. No timber. Undergrowth, sagebrush, buckbrush, and oak.
	From closing cor. of secs. 4 and 5. West, on N. bdy. of sec. 5 (S. of sec. 33, T. 41 N., R. 9 W.) Over rolling land, through dense undergrowth.
20.25	Intersect the standard cor. of secs. 32 and 33, which is an iron post, 3 ins. in diam., set, marked, and witnessed as described in the official record. Continue line and measurement (S. of sec. 32, T. 41 N., R. 9 W.)
39.91	(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the N. $\frac{1}{4}$ sec. cor. of sec. 5, with brass cap marked $\frac{1}{4}$ S5 1939
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
60.25	Intersect the standard $\frac{1}{4}$ sec. cor. of sec. 32, which is an iron post, 1 in. in diam., set, marked, and witnessed as described in the official record. Continue line and measurement.
79.82	Intersect the subdivisional line bet. secs. 5 and 6 surveyed N. $0^{\circ} 03' W.$ Closing cor. of said secs. established at this point as hereinafter described. Land, rolling. Soil, rocky, 4th rate. No timber. Undergrowth, sagebrush, buckbrush, oak, and cactus.
	From the closing cor. of secs. 5 and 6. West, on N. bdy. of sec. 6 (S. of sec. 32, T. 41 N., R. 9 W.) Over rolling land, thru dense undergrowth.
18.83	Wash, 10 lks. wide, course NE.
20.43	Intersect the standard cor. of secs. 31 and 32, which is an iron post, 3 ins. in diam., set, marked, and witnessed

Survey of North Boundary of T. 40 N., R. 9 W.
(on the 10th Std. Parallel North)

12.

Chains	
	as described in the official record.
	Continue line and measurement (S. of sec. 31, T. 41 N., R. 9 W.)
	Asc. 26 ft. to
22.93	Limestone ledge, bears NE. and SW.
33.93	Wash, 20 lks. wide, course NE.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., over a cross (+) on limestone bedrock, and in a mound of stone to top, for the N. $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap marked
	<u> </u> $\frac{1}{4}$ S6 1939
47.03	Wash, 10 lks. wide, course SE. Asc. 60 ft. to
60.43	Intersect the standard $\frac{1}{4}$ sec. cor. of sec. 31, which is an iron post, 1 in. in diam., set, marked, and witnessed as described in the official record.
	Continue line and measurement.
72.93	Dim road, bears N. and S.
76.40	Intersect the closing cor. of Ts. 40 N., Rs. 9 and 10 W., which is an iron post, 3 ins. diam., set, marked, and witnessed as hereinbefore described.
	Land, rolling. Soil, rocky, 4th rate. No timber. Undergrowth, sagebrush, oak, and cactus.

Survey: Subdivisional lines: T. 40 N., R. 9 W. BOOK 4256

Chains	Commence the survey of the subdivisional lines of T. 40 N., R. 9 W. at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the field notes of T. 39 N., R. 9 W., surveyed under this group.
	Thence, N. 0° 01' W., bet. secs. 35 and 36.
	Over rolling land, thru low scattering undergrowth.
	Asc. 6 ft. over a gradual SE. slope to
5.00	Flat top spur, slopes NE., from W. Desc. 41 ft. over gradual N. slope to
23.10	Small gulch, course E. Asc. S. slope 30 ft. to
35.00	Top of spur, slopes E. Desc. N. slope 23 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S35 S36 1939
	Desc. slightly over N. slope to.
42.00	Draw, course E. Asc. S. slope 5 ft. to
45.00	Top of low spur, slopes E. Desc. 57 ft. over a gently rolling NE. slope to.
67.90	Bottom of gulch, 20 lks. wide, course E. Along a gradual E. slope, asc. 10 ft. to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 25, 26, 35, and 36, with brass cap marked
	T40N R9W S26 S25 S35 S36 1939
	of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. raise a mound
	Land, gently rolling. Soil, rocky clay, 3rd and 4th rates. No timber. Undergrowth, sage, Mormon tea, and cacti.
	East, on a random line, bet. secs. 25 and 36.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect E. bdy. of Tp. 4 lks. S. of the cor. of secs. 25, 30, 31, and 36, which is an iron post, 2 ins. diam., projecting 8 ins. above ground, marked, and witnessed as described in the field notes of T. 40 N., R. 8 W., surveyed under this group.

BOOK 4256

Survey: Subdivisional lines: T. 40 N., R. 9 W.

14.

Chains	
	From cor., S. 89° 58' W., on true line, bet. secs. 25 and 36. Over rolling land, thru low scattering undergrowth. Asc. 63 ft. over SE. slope to
11.00	Top of spur, slopes NE., from W. Asc. 12 ft. along top of spur.
20.00	Leave top of spur, slopes E., from SW. Desc. 52 ft. over rolling NW. slope to
40.03	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S25 \\ \frac{1}{4} \\ \hline S36 \\ 1939 \end{array}$
	of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N. of cor. raise a mound
	Desc. slightly over NW. slope to
45.80	Cut bank wash, 60 lks. wide, 7 ft. deep, course N. 60° E. Asc. 73 ft. over steep SE. slope to
53.60	Top of steep ascent, brs. N. and SW. Asc. 13 ft. over gradual E. slope to
60.00	Top of flat spur, slopes S. approx. 7 chs. to toe. Desc. 35 ft. over W. slope to
73.10	Swale, drains S. 30° E., from NE. Asc. 23 ft. over a gradual E. slope to
80.06	The cor. of secs. 25, 26, 35, and 36. Land, rolling. Soil, rocky clay, 3rd and 4th rates. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.
	N. 0° 01' W., bet. secs. 25 and 26. Over gently rolling land, thru low scattering undergrowth. Asc. 4 ft. along a gradual E. slope.
1.80	Top of low spur, slopes E. Desc. 12 ft. over N. slope to
8.00	Shallow draw, course NE. Asc. 10 ft. over rolling S. slope to
31.00	Top of low spur, slopes E., from SW. Desc. 50 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ S26 S25 \\ 1939 \end{array}$
	of stone, 3 ft. base, 2 ft. high, W. of cor. raise a mound

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256 15.

Chains	<p>Desc. 65 ft. over slight NE. slope.</p> <p>75.00 Shallow drain, course NE.</p> <p>78.90 Dim road, brs. N. 70° E. and S. 70° W.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 23, 24, 25, and 26, with brass cap marked</p> <div style="text-align: center;"> <p>T40N R9W</p> <table border="1"> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> </table> <p>1939</p> </div> <p style="text-align: right;">raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, gently rolling to nearly level. Soil, rocky to sandy clay, 3rd and 4th rates. No timber. Undergrowth, sage. Fair to good grass.</p>	S23	S24	S26	S25
S23	S24				
S26	S25				
40.00	<p>N. 89° 58' E., on a random line, bet. secs. 24 and 25.</p> <p>Set temp. ¼ sec. cor.</p>				
80.06	<p>Intersect the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., which is an iron post, 2 ins. in diam., projecting 8 ins. above ground, marked, and witnessed as described in the field notes of T. 40 N., R. 8 W., surveyed under this group.</p> <p>From cor.,</p> <p>S. 89° 58' W., on true line, bet. secs. 24 and 25.</p> <p>Over nearly level land, thru low scattering undergrowth.</p> <p>Asc. 29 ft. over slight NE. slope.</p>				
33.60	<p>Shallow draw, course NE.</p>				
40.03	<p>Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked</p> <div style="text-align: center;"> <p>S24</p> <table border="1"> <tr> <td>¼ S25</td> </tr> </table> <p>1939</p> </div> <p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Continue over slight NE. slope. Asc. 12 ft.</p>	¼ S25			
¼ S25					
48.25	<p>Ungraded road, brs. SE. and NW.</p>				
75.00	<p>Shallow draw, course N.</p>				
77.25	<p>Dim road, brs. N. 70° E. and S. 70° W.</p>				
80.06	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, nearly level to slightly rolling. Soil, gravelly to rocky clay, 3rd rate. No timber. Undergrowth, sage. Good grass.</p>				

16. Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains	<p>N. 0° 01' W., bet. secs. 23 and 24.</p> <p>Over nearly level land, thru low scattering undergrowth.</p> <p>Desc. 30 ft. over slight NE. slope to</p> <p>25.00 Shallow draw, course N. 30° W. Desc. 12 ft. over nearly level land to</p> <p>39.95 Ungraded road, brs. SE. and NW.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S23 S24</p> <p style="text-align: center;">1939</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, W. of cor.</p> <p>Leave nearly level land, enter rolling land, brs. E. and NW. Asc. 38 ft. over S. slope to</p> <p>52.50 Top of detached spur, slopes N. Desc. 64 ft. along top of spur to</p> <p>80.00 Point of detached spur, from S.</p> <p>Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 13, 14, 23, and 24, with brass cap marked</p> <p style="text-align: center;">T40N R9W</p> <p style="text-align: center;">S14 S13</p> <p style="text-align: center;">S23 S24</p> <p style="text-align: center;">1939</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, nearly level and rolling.</p> <p>Soil, gravelly to rocky clay, 3rd and 4th rates.</p> <p>No timber.</p> <p>Undergrowth, sage, Mormon tea, algerita, and cacti.</p> <p>Good grass.</p>
40.00	<p>N. 89° 58' E., on a random line, bet. secs. 13 and 24.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>
80.06	<p>Intersect the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., which is an iron post, 2 ins. in diam., projecting 9 ins. above ground, marked, and witnessed as described in the field notes of T. 40 N., R. 8 W., surveyed under this group.</p> <p>From cor.,</p> <p>S. 89° 58' W., on true line, bet. secs. 13 and 24.</p> <p>Over nearly level land, thru low scattering undergrowth.</p>
21.10	<p>Clayhole Wash, 3.50 chs. wide; 25 ft. deep, course N. 31° W.</p>
27.00	<p>Cut bank wash, 80 lks. wide, 15 ft. deep, course N. 30° W.</p>
33.70	<p>Wash, 15 lks. wide, course N. Asc. 12 ft. over NE. slope.</p>

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256

17.

Chains

40.03 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{r} S13 \\ \frac{1}{4} \\ \hline S24 \\ 1939 \end{array}$$

raise a mound
of stone, 3 ft. base, 2 ft. high, N. of cor.

Asc. 23 ft. over NE. slope to

46.10 Top of detached spur, slopes N. 20° W. Desc. 35 ft. over gradual W. slope to

69.10 Wash, 10 lks. wide, course N. Asc. 12 ft. over gradual NE. slope to

80.06 The cor. of secs. 13, 14, 23, and 24.

Land, level to rolling.

Soil, sandy to stoney clay, 3rd and 4th rates.

No timber.

Undergrowth, sage, algerita, and cacti. Good grass.

N. 0° 01' W., bet. secs. 13 and 14.

Over gently rolling land, thru low scattering undergrowth.

Desc. 24 ft. over a gradual N. slope

15.00 Enter level land, brs. E. and NW. Over level land.

31.70 Center of **Clayhole** Wash, 3.00 chs. wide, cut banks 18 ft. high, course S. 85 $\frac{1}{2}$ ° W. Over level land.40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$

S14|S13

1939

raise a mound
of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Leave level land, brs. SE. and NW. Asc. 81 ft. over a gradual S. slope to

77.60 Top of spur, slopes W. approx. 3 chs. to toe. Desc. 12 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 11, 12, 13, and 14, with brass cap marked

T40N R9W

S11|S12

S14|S13

1939

raise a mound
of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, gently rolling and level.

Soil, sandy to gravelly clay, 3rd and 4th rates.

No timber.

Undergrowth, sage, Mormon tea, and cacti. Good grass.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

18.

Chains	
	N. 89° 58' E., on a random line, bet. secs. 12 and 13.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect E. bdy. of Tp. 3 lks. S. of the cor. of secs. 7, 12, 13, and 18, which is an iron post, 2 ins. diam., projecting 8 ins. above ground, marked, and witnessed as described in the field notes of T. 40 N., R. 8 W., surveyed under this group.
	From cor.,
	S. 89° 57' W., on true line, bet. secs. 12 and 13.
	Over gently rolling land, thru low scattering undergrowth.
	Desc. 18 ft. over a slight SW. slope.
15.00	Slope changes to a slight S. slope. Asc. 18 ft. to
40.05	Top of low divide, brs. N. 80° E. and S. 80° W. Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \text{ S12} \\ \hline \frac{1}{4} \text{ S13} \\ 1939 \end{array}$
	raise a mound
	of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
	Desc. slightly along a slight N. slope to
45.00	Asc. 30 ft. over a gradual NE. slope to
60.00	Top of divide, brs. N. and SE. Desc. 29 ft. over W. slope.
65.00	Slope changes to a slight SE. slope. Asc. 12 ft.
76.00	Top of low spur, slopes SW. Desc. NW. slope slightly to
80.10	The cor. of secs. 11, 12, 13, and 14.
	Land, gently rolling. Soil, sandy to gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, Mormon tea, and cacti. Fair to good grass.
	N. 0° 01' W., bet. secs. 11 and 12.
	Over gently rolling land, thru low scattering undergrowth.
	Desc. 7 ft. over NW. slope to
1.00	Draw, near head, course SW. Asc. 28 ft. over SE. slope to
7.00	Top of divide, brs. E. and W. Desc. 73 ft. over slightly broken N. slope.
26.70	Dim road, brs. N. 70° E. and S. 70° W.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ \hline \text{S11 S12} \\ 1939 \end{array}$

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256

Chains

raise a mound
of stone, 2½ ft. base, 2 ft. high, W. of cor.

Over nearly level land. Desc. 25 ft.

78.15 Ungraded road to Pipe Springs, brs. S. 41° E. and N. 41° W.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 1, 2, 11, and 12, with brass cap marked

T40N R9W
S2	S1
S11 | S12
1939

raise a mound
of stone, 3½ ft. base, 2½ ft. high, W. of cor.

Land, gently rolling to nearly level.

Soil, gravelly clay, 3rd rate.

No timber.

Undergrowth, sage, algerita, and cacti. Fair to good grass.

N. 89° 57' E., on a random line, bet. secs. 1 and 12.

40.00 Set temp. ¼ sec. cor.

80.14 Intersect. E. bdy. of Tp. 2 lks. S. of the cor. of secs. 1, 6, 7, and 12, which is an iron post, 2 ins. in diam., projecting 9 ins. above ground, marked, and witnessed as described in the field notes of T. 40 N., R. 8 W., surveyed under this group.

From cor.,

S. 89° 56' W., on true line, bet. secs. 1 and 12.

Over rolling land, thru very scattering timber and undergrowth.

Desc. 24 ft. over NW. slope to

3.15 Draw, course NE. Asc. E. slope 36 ft. to

6.45 Rocky point on spur, slopes N. Desc. steep NW. slope 61 ft. to

8.60 Leave steep NW. slope. Desc. 18 ft. over gradual NW. slope to

38.75 Wash, 40 lks. wide, course N. Over nearly level land.

40.07 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked

S1
¼

S12
1939

from which

A juniper, 8 ins. in diam., brs. N. 83¼° E., 509 lks. dist., marked ¼ S1 BT.

A juniper, 10 ins. diam., brs. S. 36½° E., 330 lks. dist., marked ¼ S12 BT.

raise a mound
of stone, 2½ ft. base, 2 ft. high, N. of cor.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

20.

Chains	
	Continue over nearly level land.
46.25	Wash, 40 lks. wide, course N. Leave scattering timber, brs. NE. and SE.
49.85	Wash, 20 lks. wide, course N. Asc. 12 ft. over slight E. slope to
60.00	Top of low, flat spur, slopes N. Desc. W. slope slightly.
80.14	The cor. of secs. 1, 2, 11, and 12.
	Land, rolling to nearly level. Soil, sandy clay and gypsum, 3rd and 4th rates. Timber, few juniper. Undergrowth, sage. Poor grass.
	N. 0° 01' W., bet. secs. 1 and 2.
	Over gently rolling land, thru low scattering undergrowth.
	Asc. 15 ft. over a slight S. slope to
18.00	Top of low, flat spur, slopes NW. Desc. 31 ft. over slightly broken NE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	S2 S1
	1939
	Desc. 35 ft. over gently rolling N. slope to
75.80	Intersect the Tenth Standard Parallel North.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the closing cor. of secs. 1 and 2, with brass cap marked
	T41N R9W
	S36
	S2 S1
	T40N R9W
	CC
	1939
	raise a mound
	of stone, 3 ft. base, 2 ft. high, S. of cor.
	The standard cor. of secs. 35 and 36, T. 41 N., R. 9 W., brs. West, 20.12 chs. dist., and the standard $\frac{1}{4}$ sec. cor. of sec. 36 brs. East, 19.88 chs. dist., both set, marked , and witnessed as described in the official record.
	Land, gently rolling. Soil, weathered shale and gypsum, 4th rate. No timber. Undergrowth, sage... Poor grass.
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the field notes of T. 39 N., R. 9 W., surveyed under this group.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

21.

BOOK 4256

Chains	
	Thence, N. 0° 01' W., bet. secs. 34 and 35. Over rolling land, thru scattering undergrowth. Desc. 117 ft. over NW. slope.
14.20	Ungraded road, brs. N. 60° E. and S. 60° W.
25.60	Wash, 10 lks. wide, course NE. Asc. 40 ft. over S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 3 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S34 S35 1939
	Continue over S. slope. Asc. 8 ft. to
43.00	Top of spur, slopes E. Desc. 58 ft. over NE. slope to
65.10	Drain, course N. 70° E. Asc. 10 ft. over SE. slope to
68.00	Top of spur, slopes N. 80° E. Desc. 20 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 4 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 26, 27, 34, and 35, with brass cap marked T40N R9W S27 S26 S34 S35 1939
	Land, rolling. Soil, gravelly clay, 3rd. rate: No timber. Undergrowth, sage, algerita, and cacti. Fair grass.
	East, on a random line, bet. secs. 26 and 35.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect the N. and S. line 5 lks. N. of the cor. of secs. 25, 26, 35, and 36.
	Thence, N. 89° 58' W., on true line, bet. secs. 26 and 35. Over rolling land, thru low scattering undergrowth. Asc. 15 ft. over E. slope to
2.70	Top of spur, slopes NE. Desc. NW. slope slightly to
7.60	Slope changes to gradual NE. slope. Asc. 41 ft. to
31.00	Top of spur, slopes N. Desc. 15 ft. over gradual NW. slope.
32.20	Ungraded road to Hurricane, brs. N. 18° E. and S. 18° W.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

22.

Chains	
39.97	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S26 \\ \frac{1}{4} \\ \hline S35 \\ 1939 \end{array}$
	<p style="text-align: right;">raise a mound</p> <p>of stone, 2$\frac{1}{2}$ ft. base, 2$\frac{1}{2}$ ft. high, N. of cor.</p>
	Desc. slightly over NW. slope to
40.50	Draw, course NE. Asc. 30 ft. over E. slope to
46.20	Top of spur, slopes NE. Desc. 25 ft. over NW. slope to
54.10	Draw, course NE. Asc. 30 ft. over E. slope to
64.90	Top of flat spur, slopes NE. Desc. 10 ft. over W. slope.
70.60	Draw, course N. Asc. 35 ft. over slightly broken NE. slope to
79.94	The cor. of secs. 26, 27, 34, and 35.
	<p>Land, rolling. Soil, gravelly clay, 3rd. rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.</p>
	N. 0° 01' W., bet. secs. 26 and 27.
	Over rolling land, thru low scattering undergrowth.
	Desc. 110 ft. over slightly broken NE. slope.
6.70	Head of draw, course NE.
28.00	Draw, course N. 60° E. Along a gradual E. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S27 S26
	1939
	<p style="text-align: right;">raise a mound</p> <p>of stone, 2$\frac{1}{2}$ ft. base, 2$\frac{1}{2}$ ft. high, W. of cor.</p>
	Desc. 18 ft. over gradual NE. slope to
53.20	Wash, 40 lks. wide, course N. 65° E. Over nearly level land.
68.00	Leave level land, brs. N. 70° E. and S. 70° W. Asc. 70 ft. over S. slope to
78.00	Top of spur, slopes N. 70° E. Desc. slightly over NW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 22, 23, 26, and 27, with brass cap marked

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256 23.

Chains

	<p>T40N R9W</p> <table border="1"> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> </table> <p>1939</p> <p>raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor.</p> <p>Land, rolling and nearly level. Soil, sandy and gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.</p>	S22	S23	S27	S26
S22	S23				
S27	S26				
40.00	Set temp. ¼ sec. cor.				
79.96	Intersect the N. and S. line 2 lks. S. of the cor. of secs. 23, 24, 25, and 26.				
	Thence,				
	N. 89° 59' W., on true line, bet. secs. 23 and 26.				
	Over nearly level land, thru low scattering undergrowth.				
23.50	Ungraded road to Hurricane, brs. S. 14° E. and N. 3° W.				
24.00	Wash, course N.				
36.50	Wash, course NE.				
39.98	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked				
	<table border="1"> <tr> <td>S23</td> </tr> <tr> <td>¼ S26</td> </tr> </table> <p>1939</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Continue over nearly level land.</p>	S23	¼ S26		
S23					
¼ S26					
50.70	Wash, 20 lks. wide, course N. 60° E. Asc. 85 ft. over a SE. slope to				
75.20	Top of spur, slopes N. 60° E. Desc. slightly over NW. slope to				
79.96	The cor. of secs. 22, 23, 26, and 27.				
	Land, nearly level and rolling. Soil, sandy and gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.				
	N. 0° 01' W., bet. secs. 22 and 23.				
	Over rolling land, thru low scattering undergrowth.				
	Desc. 60 ft. over NW. slope, to				
4.80	Ungraded road, brs. N. 60° E. and S. 60° W.				
6.20	Gulch, course N. 60° E. Along a rolling E. slope to				
28.00	Slope changes to SE. Asc. 32 ft. to				

Survey:.. Subdivisionallines: T. 40 N., R. 9 W.

24.

Chains	
38.00	Top of flat spur, slopes NE. Desc. slightly over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S22 S23 1939
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
	Desc. 25 ft. over N. slope to
44.50	Drain, course N. 60° E. Asc. 10 ft. over S. slope to
47.60	Small spur, slopes N. 60° E. Desc. 29 ft. over NW. slope.
58.30	Wash, 20 lks. wide, course N. 70° E. Asc. 30 ft. over S. slope to
65.00	Short spur, slopes E. Desc. 23 ft. over NE. slope to
76.00	Draw, course S. 60° E. Asc. 10 ft. over SW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 14, 15, 22, and 23, with brass cap marked
	T40N R9W S15 S14 S22 S23 1939
	raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, gravelly clay, 3rd. rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.
	S. 89° 59' E., on a random line, bet. secs. 14 and 23.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect the N. and S. line 2 lks. S. of the cor. of secs. 13, 14, 23, and 24.
	Thence, West, on true line, bet. secs. 14 and 23. Over slightly rolling land, thru low scattering undergrowth.
	Along a slight N. slope.
12.10	Wash, 20 lks. wide, 4 ft. deep, course N. Asc. slight NE. slope.
29.40	Ungraded road to Hurricane, brs. S. 7 $\frac{1}{2}$ ° E. and N. 7 $\frac{1}{2}$ ° W.
39.97	Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to solid rock, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked

Survey: Subdivisional lines: T. 40 N.; R. 9 W.

BOOK 4256

25.

Chains

$$\frac{S14}{S23}$$
 1939

raise a mound
of stone, 2½ ft. base, 2 ft. high, N. of cor.

Asc. 17 ft. over gently rolling N. slope to

49.20 Draw, course NE. Asc. 95 ft. over an E. slope to

73.40 Top of spur, slopes SE. Desc. 31 ft. over SW. slope to

79.94 The cor. of secs. 14, 15, 22, and 23.

Land, gently rolling and rolling.
Soil, gravelly clay, 3rd rate.
No timber.
Undergrowth, sage, algerita, and cacti. Fair grass.

N. 0° 01' W., bet. secs. 14 and 15.

Over rolling land, thru low scattering undergrowth.

Asc. 25 ft. over SW. slope to

8.00 Top of flat spur, slopes SE. Desc. 40 ft. over N. slope.

12.30 Draw, course NW. Asc. 35 ft. over S. slope to

18.10 Top of short spur, slopes W. Desc. 12 ft. along a W. slope to

24.00 Top of short spur, slopes NW. Desc. 63 ft. over NE. slope.

33.70 Drain, course NW. Asc. 34 ft. over SW. slope to

38.80 Top of spur, slopes NW. Desc. slightly over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked

$$\frac{S15}{S14}$$
 1939

raise a mound
of stone, 3 ft. base, 2½ ft. high, W. of cor.

Desc. 55 ft. over N. slope to

45.70 Canyon wash, 25 lks. wide, course E. Asc. 90 ft. over S slope to

53.60 Top of spur, slopes S. 75° E. Along an E. slope to

60.70 Top of broad spur, slopes N. 30° E. Along a W. slope to

68.50 Top of short spur, slopes W. Desc. 30 ft. over NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 10 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 10, 11, 14, and 15, with brass cap marked

T40N R9W

$$\frac{S10}{S11}$$

$$\frac{S15}{S14}$$
 1939

26. Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains	<p>Land, rolling. Soil, gravelly to rocky clay, 3rd rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.</p>
	<p>East, on a random line, bet. secs. 11 and 14.</p>
40.00	<p>Set temp. $\frac{1}{4}$ sec. cor.</p>
79.96	<p>Intersect N. and S. line 2 lks. S. of the cor. of secs. 11, 12, 13, and 14.</p>
	<p>Thence,</p>
	<p>S. 89° 59' W., on true line, bet. secs. 11 and 14.</p>
	<p>Over rolling land, thru low scattering undergrowth.</p>
	<p>Desc. 10 ft. over NW. slope to</p>
1.90	<p>Draw, course S. 30° W. Asc. 25 ft. over SE. slope to</p>
7.00	<p>Top of short spur, slopes S. Desc. 55 ft. over SW. slope.</p>
29.90	<p>Gulch, course S. Asc. 45 ft. over SE. slope.</p>
30.15	<p>Ungraded road to Hurricane, brs. S. 1° E. and N. 1° W.</p>
39.98	<p>Set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	<p>S11 $\frac{1}{4}$ S14 1939</p>
	<p>Asc. gradually over an E. slope to</p>
41.50	<p>Slope changes to NE. Asc. slightly.</p>
45.50	<p>Top of spur, slopes SE. Desc. 125 ft. over W. slope to</p>
65.30	<p>Clayhole Wash, 150 lks. wide, in canyon, course N. 45° E. Seep spring, in canyon, brs. N. 47° E.; 5.50 chs. dist. Asc. 120 ft. over an E. slope to</p>
72.00	<p>Top of spur, slopes NE. Desc. 10 ft. over NW. slope to</p>
79.96	<p>The cor. of secs. 10, 11, 14, and 15.</p>
	<p>Land, rolling to heavy rolling. Soil, gravelly to rocky clay, 3rd rate. No timber. Undergrowth, sage and algerita. Fair grass.</p>
	<p>N. 0° 01' W., bet. secs. 10 and 11.</p>
	<p>Over rolling and broken land, thru low scattering undergrowth.</p>
	<p>Desc. 85 ft. over NW. slope to</p>
4.20	<p>Short gulch, course N. 10° E. Desc. 10 ft. along E. slope to</p>
10.00	<p>Clay Hole wash, 150 lks. wide, course N. 88° W. Asc. 65 ft. over S. slope to</p>

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256 27.

Chains
 14.70 Top of spur, slopes S. 70° W. Desc. 65 ft. over NW. slope.
 22.10 Clayhole Wash, course N. 47° E. Along bottom.
 22.90 Clayhole Wash, course N. 36° W. Asc. 110 ft. over SW.
 slope to
 38.00 Top of spur, slopes W. Desc. slightly along a W. slope to
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in
 the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

 $\frac{1}{4}$

S10|S11

1939

raise a mound
 of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

Continue along a W. slope. Desc. 29 ft.

45.90 Dim road, brs. SE. and NW.

61.00 Top of short spur, slopes N. 70° W. Desc. 30 ft. over
 N. slope to

64.40 Gulch, course W. Asc. 40 ft. over SW. slope to

71.50 Top of short spur, slopes S. 60° W. Desc. gradually over
 NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 10 ins. in
 the ground, over a cross (+) on bedrock, and in a mound
 of stone to top, for the cor. of secs. 2, 3, 10, and 11,
 with brass cap marked

T40N R9W

S3|S2

S10|S11

1939

Land, rolling and broken.

Soil, rocky and gravelly clay, 3rd and 4th rates.

No timber.

Undergrowth, sage, algerita, and cacti. Fair grass.

N. 89° 59' E., on a random line, bet. secs. 2 and 11.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.96 Intersect N. and S. line 2 lks. N. of the cor. of secs.
 1, 2, 11, and 12.

Thence,

West, on true line, bet. secs. 2 and 11.

Over slightly rolling land, thru low scattering undergrowth.

1.40 Ungraded road to Pipe Springs, brs. S. 38° E. and N. 38° W.

21.20 Ungraded road to Hurricane, brs. N. 7° W. and S. 7° E.

39.90 Drain, course NW.

39.98 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in
 the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

Chains	
	<p style="text-align: center;"> $\frac{1}{4}$ S2 $\frac{1}{4}$ S11 1939 </p> <p>raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p> <p>Continue over slightly rolling land. Along slight N. slope.</p>
70.00	Top of low spur, slopes N. Desc. 10 ft. over NW. slope to
79.96	The cor. of secs. 2, 3, 10, and 11.
	<p>Land, gently rolling.</p> <p>Soil, gravelly clay, 3rd rate.</p> <p>No timber.</p> <p>Undergrowth, sage, algerita, and cacti. Fair grass.</p>
	<p>N. 0° 01' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land, thru low scattering undergrowth.</p> <p>Desc. 12 ft. over NW. slope to</p>
10.00	Slope changes to gradual W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone, to top, for the ¼ sec. cor., with brass cap marked
	<p style="text-align: center;"> $\frac{1}{4}$ S3 S2 1939 </p> <p>Continue along gradual W. slope.</p>
62.50	Top of short spur, slopes W. Desc. 55 ft. over NW. slope.
68.50	Wash, 15 lks. wide, cut banks 8 ft. high, course S. 60° W. Asc. 45 ft. over SE. slope to
75.98	Intersect the Tenth Standard Parallel North.
	<p>Set an iron post, 3 ft. long, 2 ins. in diam., 20 ins. in the ground to solid rock, and in a small mound of stone to top, for the closing cor. of secs. 2 and 3, with brass cap marked</p> <p style="text-align: center;"> T41N R9W S35 $\frac{1}{4}$ S3 S2 T40N R9W CC 1939 </p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>The standard cor. of secs. 34 and 35, T. 41 N., R. 9 W., brs. West, 20.16 chs. dist., and the standard ¼ sec. cor. of sec. 35 brs. East, 19.84 chs. dist., both set, marked, and witnessed as described in the official record.</p> <p>Land, gently rolling and rolling.</p> <p>Soil, gravelly clay, 3rd and 4th rates.</p> <p>No timber. Undergrowth, sage, algerita, and cacti. Fair grass.</p>

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256

29.

Chains

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the field notes of T. 39 N., R. 9 W., surveyed under this group.

Thence,

N. 0° 02' W., bet. secs. 33 and 34.

Over rolling land, thru low scattering undergrowth.

Desc. 48 ft. along a steep E. slope to

8.65 Ravine wash, 15 lks. wide, course N. 60° E. Asc. 47 ft. over S. slope to

19.30 Top of spur, slopes E. Desc. 84 ft. over broken NE. slope.

27.90 Dim road, brs. SE. and NW.

31.20 Draw, course E., approx. 2 chs. to main draw from SE. Along bottom.

35.90 Draw, 3 chs. wide, course N. 30° W. Asc. SW. slope 14 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap marked

1/4

S33|S34

1939

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Continue over SW. slope. Asc. 6 ft.

42.60 Top of spur, slopes W. approx. 3 chs. Desc. NW. slope 52 ft. to

55.20 Draw, 3 chs. wide, course N. 20° E. Asc. SE. slope 59 ft.

70.60 Top of spur, slopes E. approx. 6 chs. Desc. 27 ft. over NE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 27, 28, 33, and 34, with brass cap marked

T40N R9W

S28|S27

S33|S34

1939

Land, rolling.

Soil, sandy clay and limestone, 3rd and 4th rates.

No timber..

Undergrowth, sage. Good grass.

East, on a random line, bet. secs. 27 and 34.

40.00 Set temp. 1/4 sec. cor.

79.94 Intersect N. and S. line 7 lks. S. of the cor. of secs. 26, 27, 34 and 35.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

30.

Chains	
	Thence, S. 89° 57' W., on true line, bet. secs. 27 and 34. Over rolling land, thru low scattering undergrowth. Asc. 18 ft. over a gradual NE. slope to
10.00	Top of spur, slopes N. Desc. 56 ft. over broken NW. slope.
27.80	Ravine, 10 lks. wide, course N. Asc. 24 ft. over NE. slope to
34.90	Top of spur, slopes N. approx. 3 chs. Desc. NW. slope 6 ft. to
39.97	Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S27 \\ \frac{1}{4} \\ \hline S34 \\ 1939 \end{array}$
	Desc. NW. slope 4 ft.
40.15	Ravine, 10 lks. wide, course NE. Asc. NE. slope 46 ft. to
50.60	Top of spur, slopes N. Desc. NW. slope 35 ft. to
56.80	Junction of washes, from N. 60° W. and S. course NE. from N. 60° W. Asc. NE. slope 40 ft. to
65.90	Top of spur, slopes N. approx. 5 chs. Desc. NW. slope 20 ft. to
71.60	Same wash, course NE. Asc. 77 ft. over NE. slope to
79.94	The cor. of secs. 27, 28, 33, and 34. Land, rolling. Soil, sandy clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage and algerita. Fair grass.
	N. 0° 02' W., bet. secs. 27 and 28. Over rolling land, thru low scattering undergrowth. Desc. 17 ft. over NE. slope to
4.50	Low saddle in spur, slopes N. 80° E. Desc. 74 ft. over slightly broken N. slope to
21.55	Wash, 20 lks. wide, in draw, course E. Asc. 90 ft. over S. slope to
30.00	Top of spur, slopes E. Desc. 23 ft. over gradual NE. slope to
39.85	Draw, heads approx. 10 chs. W, course E. Asc. slight S. slope 3 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256 31.

Chains	
	$\frac{1}{4}$ S28 S27 1939 Asc. 13 ft. over S. slope to
45.00	Top of spurs, sloping N. 20° E., N. 60° E. and E., from SW. Desc. 64 ft. over gradual NW. slope to
67.00	Ravine, course NE. Asc. SE. slope 27 ft. to
72.00	Top of spur, slopes E. Desc. 61 ft. over N. slope to
79.50	Shallow draw, course NE. Asc. SE. slope 5 ft. to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 21, 22, 27, and 28, with brass cap marked
	T40N R9W S21 S22 S28 S27 1939 raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
	Land, rolling. Soil, sandy clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage and algerita. Fair grass.
40.00	N. 89° 57' E., on a random line, bet. secs. 22 and 27. Set temp. $\frac{1}{4}$ sec. cor.
79.98	Intersect the cor. of secs. 22, 23, 26, and 27. Thence, S. 89° 57' W., on true line, bet. secs. 22 and 27. Over rolling land, thru low scattering undergrowth. Desc. 32 ft. over NW. slope.
8.80	Dim road, brs. NE. and SW.
9.00	Draw, course NE. Asc. 79 ft. over SE. slope.
38.00	Same road, brs. S. 60° E. and N. 80° W.
39.99	Top of spur, slopes NE. Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S22 S27 1939 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
48.00	Desc. 10 ft. over gradual NW. slope to Draw, course NE. Asc. 58 ft. over slightly broken NE. slope to

Survey: Subdivisional lines: T. 40 N., R. 9 W.

32.

Chains	
62.50	Top of spur, slopes N. 20° E. Desc. 11 ft. over a gradual W. slope to
72.40	Draw, course N. Along a slight N. slope to
79.50	Shallow draw, course NE. Asc. a slight SE. slope to
79.98	The cor. of secs. 21, 22, 27, and 28.
	Land, rolling. Soil, sandy clay, gypsum, and limestone, 3rd and 4th rates. No timber. Undergrowth, sage. Good grass.
	N. 0° 02' W.; bet. secs. 21 and 22. Over rolling land, thru low scattering undergrowth. Asc. 38 ft. over SE. slope.
0.20	Dim road, brs. E. and W.
12.30	Top of spur, slopes NE. Desc. 50 ft. over NW. slope to
20.10	Draw, course N. 80° E. Asc. SE. slope 15 ft. to
35.00	Top of spur, slopes S. 60° E. Desc. N. slope 34 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S21 S22 1939
	Desc. N. slope 15 ft. to
41.10	Rocky wash, 10 lks. wide, course N. 60° E., from N. 60° W. Asc. 20 ft. over a slight S. slope to
57.00	Top of flat spur, slopes N. 60° E. Desc. 35 ft. over gradual N. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 15, 16, 21, and 22, with brass cap marked
	T40N R9W S16 S15 S21 S22 1939
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Land, rolling to gently rolling. Soil, sandy to rocky clay, 3rd and 4th rates. No timber. Undergrowth, sage and algerita. Fair grass.
	N. 89° 57' E., on a random line, bet. secs. 15 and 22.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect the cor. of secs. 14, 15, 22, and 23.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256
p. 33.

Chains	Thence,
	S. 89° 57' W., on true line, bet. secs. 15 and 22. Over rolling land, thru low scattering undergrowth. Desc. SW. slope slightly to
4.00	Head of draw, course SE. Asc. NE. slope 46 ft. to
20.00	Top of spur, slopes NE. Desc. 22 ft. over rolling NW. slope to
27.20	Draw, course N. 30° E. Asc. SE. slope 38 ft. to
31.50	Top of spur, slopes N. 20° E. Desc. NW. slope 34 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S15 \\ \hline S22 \\ 1939 \end{array}$
	raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
	Desc. 25 ft. over NW. slope to
44.10	Wash, 80 lks. wide, course N. 10° E. Asc. 71 ft. over E. slope to
65.00	Top of flat spur, slopes NE. Along a gradual N. slope. Asc. 12 ft.
80.00	The cor. of secs. 15, 16, 21, and 22. Land, rolling. Soil, sandy to rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage and algerita. Fair grass.
	N. 0° 02' W., bet. secs. 15 and 16. Over gently rolling land, thru low scattering undergrowth. Desc. 42 ft. over a gradual N. slope.
37.00	Dim road, brs. NE. and SW.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone, to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ S16 S15 \\ 1939 \end{array}$
	Continue over gradual N. slope. Desc. 41 ft.
57.00	Dim road, brs. NE. and SW.
60.00	Flat draw, course NE. Asc. 12 ft. over SE. slope to
70.00	Slope changes to gradual E. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 18 ins. in

Survey: Subdivisional lines: T. 40 N., R. 9 W.

34.

Chains

the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 9, 10, 15, and 16, with brass cap marked

T40N R9W

S9 | S10

S16 | S15

1939

Land, gently rolling.
Soil, stoney clay and limestone, 3rd and 4th rates.
No timber.
Undergrowth, sage and algerita. Fair grass.

N. 89° 57' E.; on a random line, bet. secs. 10 and 15.

40.00 Set temp. ¼ sec. cor.

79.96 Intersect N. and S. line 4 lks. N. of the cor. of secs. 10, 11, 14, and 15.

Thence,

S. 89° 59' W., on true line, bet. secs. 10 and 15.

Over rolling land, thru low scattering undergrowth.

Desc. 40 ft. over NW. slope to

5.30 Small gulch, course NE. Asc. 58 ft. over E. slope to

13.70 Top of spur, slopes NE. Desc. 15 ft. over gradual NW. slope to

30.50 Drain, course NE. Asc. 25 ft. over NE. slope to

39.98 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked

S10
¼
S15

1939

raise a mound of stone, 2½ ft. base, 2½ ft. high, N. of cor.

Continue over gently rolling general NE. slope.

51.00 Drain, course NE.

61.40 Dim road, brs. NE. and SW.

64.00 Top of flat spur, slopes NE., from S. Desc. 30 ft. over NW. slope to

69.60 Rocky wash, 15 lks. wide, course NE. Asc. 50 ft. over E. slope to

79.96 The cor. of secs. 9, 10, 15, and 16.

Land, rolling.
Soil, gravelly clay, 3rd rate.
No timber.
Undergrowth, sage, algerita, and cliff rose. Fair grass.

N. 02° 00' N., on true line, bet. secs. 10 and 15.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256
35.

Chains	N. 0° 02' W., bet. secs. 9 and 10. Over gently rolling land, thru low scattering undergrowth. Asc. 42 ft. along a gradual E slope to
18.00	Top of ridge, brs. N. 30° E. and S. 30° W. Desc. 35 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S9 S10 1939
	Continue over N. slope. Desc. 73 ft. to
56.70	Sand wash, 30 lks. wide, course E. Forks of wash, from NW. and SW., bear W. approx. 4 chs. dist. Asc. 68 ft. over S. slope to
78.00	Top of detached spur, slopes S. 70° W. and S. 70° W. Desc. 10 ft. over NW. slope to
80.00	Top of low, flat spur, slopes NW. Set an iron post, 3 ft. long, 2 ins. in diam., over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 3, 4, 9, and 10, with brass cap marked
	T40N R9W S4 S3 S9 S10 1939
	Land, gently rolling. Soil, rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage and algerita. Fair grass.
	N. 89° 59' E., on a random line, bet. secs. 3 and 10.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect N. and S. line 5 lks. S. of the cor. of secs. 2, 3, 10, and 11.
	Thence, S. 89° 57' W., on true line, bet. secs. 3 and 10. Over rolling land, thru low scattering undergrowth. Desc. 45 ft. over gradual NW. slope to
18.40	Top of steep descent, brs. NW. and SE. Desc. 35 ft. over steep W. slope to
21.05	Clayhole Wash, 150 lks. wide, in small canyon, course N. 65° W., from S. Asc. 40 ft. over E. slope to
23.70	Top of flat spur, slopes NE. Over top of spur.
29.90	Leave top of spur, slopes NE. Desc. 40 ft. over NW. slope.
39.70	Wash, 10 lks. wide, course NE. Asc. slightly over E. slope to

Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains

39.97

Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the 1/4 sec cor., with brass cap mkd.

S3
1/4
S10
1939

Asc. 150 ft. over E. slope.

59.70

Dim road, brs. N. 30° W. and S. 30° E.

75.80

Top of detached spur, slopes NE. and E. Desc. 18 ft. over NW. slope to

79.94

The cor. of secs. 3, 4, 9, and 10.

Land, rolling.

Soil, gravelly to rocky clay, 3rd rate.

No timber.

Undergrowth, sage, algerita, and cacti. Good grass.

N. 0° 02' W., bet. secs. 3 and 4.

Over rolling land, thru low scattering undergrowth.

Desc. 41 ft. over NE. slope.

13.20

Dim road, brs. SE. and NW. Shallow draw, course S. 60° E. heads approx. 3 chs. W. Asc. 12 ft. over SE. slope to

20.00

Top of spur, slopes E. Desc. 35 ft. over NW. slope to

27.50

Wash, 10 lks. wide, course N. 80° E. Over nearly level land to

30.20

Wash, 10 lks. wide, course S. 30° E. Asc. SW. slope 41 ft.

40.00

Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap marked

1/4

S4|S3

1939

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Asc. 16 ft. over S. slope to

44.50

Top of spur, slopes E. Desc. 17 ft. over NE. slope to

49.80

Small draw, course E. Asc. 15 ft. over SE. slope to

62.50

Top of spur, slopes N. 60° E. Desc. 41 ft. over rolling N. slope to

70.60

Wash, 6 lks. wide, course NE. Asc. 10 ft. along a gradual E. slope to

76.05

Intersect the Tenth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the closing cor. of secs. 3 and 4, with brass cap marked

Survey: Subdivisional lines: T. 40 N., R. 9 W. BOOK 4256 37.

Chains	
	<p style="text-align: center;">T41N R9W S34 S4 S3 T40N R9W CC 1939</p> <p>The standard cor. of secs. 33 and 34, T. 41 N., R. 9 W., brs. West, 20.23 chs. dist., and the standard $\frac{1}{4}$ sec. cor. of sec. 34 brs. East, 19.77 chs. dist.; both set, marked, and witnessed as described in the official record.</p> <p>Land, rolling. Soil, rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage and algerita. Fair grass.</p>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.; which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the field notes of T. 39 N., R. 9 W., surveyed under this group.</p> <p>Thence,</p> <p>N. 0° 03' W., bet. secs. 32 and 33.</p> <p>Over rolling land, thru low scattering undergrowth.</p> <p>Desc. 35 ft. over gradual NE. slope to</p> <p>23.60 Small gulch, course N. 25° W. Along a rolling W. slope. Desc. 40 ft. to</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. in diam., 4 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S32 S33 1939</p> <p>Continue along a rolling W. slope.</p> <p>54.80 Top of short spur, slopes W. Desc. 70 ft. over NW. slope.</p> <p>64.10 Gulch, course NE. Asc. 40 ft. over SE. slope to</p> <p>68.00 Point of spur, slopes E. Desc. slightly over NE. slope to</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 10 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 28, 29, 32; and 33, with brass cap marked</p> <p style="text-align: center;">T40N R9W S29 S28 S32 S33 1939</p> <p>Land, rolling. Soil, gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, cliff rose, and cacti. Fair grass.</p>

Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains	East, on a random line, bet. secs. 28 and 33.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 3 lks. N. of the cor. of secs. 27, 28, 33, and 34.
	Thence,
	N. $89^{\circ} 59'$ W., on true line, bet. secs. 28 and 33.
	Over rolling land, thru low scattering undergrowth.
	Asc. 62 ft. over NE. slope to
10.00	Top of flat spur, slopes N. 30° E. Desc. 40 ft. over W. slope to
18.80	Draw, course N. Along a gradual N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S28}{S33}$ 1939
	raise a mound
	of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
	Continue along a gradual N. slope. Desc. 15 ft. to
47.70	Draw, course N. Continue along a gradual N. slope.
52.90	Dim road, brs. N. and S.
62.60	Gulch, course NE. Asc. 60 ft. over a gradual NE. slope to
80.00	The cor. of secs. 28, 29, 32, and 33.
	Land, rolling.
	Soil, gravelly clay, 3rd rate.
	No timber.
	Undergrowth, sage, algerita, cliff rose, and cacti. Fair grass.
	N. $0^{\circ} 03'$ W., bet. secs. 28 and 29.
	Over rolling land, thru low scattering undergrowth.
	Desc. 10 ft. over gradual NE. slope to
6.00	Gulch, course E. Asc. 50 ft. over SE. slope..
12.70	Dim road, brs. NE. and SW.
26.00	Top of spur, slopes E. Along a gradual E. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $S29 S28$ 1939
	raise a mound
	of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

BOOK 4256

39.

Chains	Continue along gradual E. slope.								
76.50	Drain, course NE.								
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 10 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 20, 21, 28, and 29, with brass cap marked								
	<table border="0"> <tr><td>T40N</td><td>R9W</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td>S29</td><td>S28</td></tr> <tr><td colspan="2">1939</td></tr> </table>	T40N	R9W	S20	S21	S29	S28	1939	
T40N	R9W								
S20	S21								
S29	S28								
1939									
	Land, rolling. Soil, gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, cliff rose, and cacti. Fair grass.								
	S. 89° 59' E., on a random line, bet. secs. 21 and 28.								
40.00	Set temp. 1/4 sec. cor.								
80.02	Intersect N. and S. line 5 lks. S. of the cor. of secs. 21, 22, 27, and 28.								
	Thence, S. 89° 59' W., on true line, bet. secs. 21 and 28. Over rolling land, thru low scattering undergrowth. Asc. 75 ft. over SE. slope.								
4.80	Dim road, brs. NE. and SW.								
16.50	Top of low spur, slopes NE. Desc. slightly over NW. slope.								
23.00	Along a rolling gradual N. slope. Asc. 27 ft. Dim road, brs. SE. and NW.								
36.00	Drain, course NE. Asc. 25 ft. over NE. slope to								
40.01	Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the 1/4 sec. cor., with brass cap mkd.								
	<table border="0"> <tr><td>S21</td></tr> <tr><td>1/4 S28</td></tr> <tr><td>1939</td></tr> </table>	S21	1/4 S28	1939					
S21									
1/4 S28									
1939									
	Asc. 50 ft. over NE. slope.								
45.50	Dim road, brs. NE. and SW.								
56.00	Top of spur, slopes N. 20° E. Desc. 28 ft. over NW. slope.								
68.60	Drain, course NE. Asc. 50 ft. over E. slope to								
80.02	The cor. of secs. 20, 21, 28, and 29.								
	Land, rolling. Soil, gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.								

Survey: Subdivisional lines: T. 40 N., R. 9 W.

40.

Chains	
	N. 0° 03' W., bet. secs. 20 and 21. Over rolling land, thru low scattering undergrowth. Along E. slope to
5.00	Top of flat spur, slopes NE. Desc. 20 ft. over NW. slope.
12.60	Drain, course NE. Along a slightly broken E. slope. Desc. 30 ft.
32.00	Slope changes to SE. Asc. 40 ft.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S20 S21 1939 Asc. slightly over SE. slope to
44.00	Top of low broken ridge, brs. NE. and SW. Desc. 45 ft. over rolling NW. slope to
55.00	Slope changes to NE. Desc. 45 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 16, 17, 20, and 21, with brass cap marked T40N R9W S17 S16 S20 S21 1939 raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.
	N. 89° 59' E., on a random line, bet. secs. 16 and 21.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect the cor. of secs. 15, 16, 21, and 22. Thence, S. 89° 59' W., on true line, bet. secs. 16 and 21. Over rolling land, thru low scattering undergrowth. Along a slight N. slope.
10.10	Dim road, brs. N. and S.
36.20	Wash, 3 lks. wide, course N. Continue along gradual N. slope to
40.01	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

Survey: Subdivisional lines: T. 40 N.; R. 9 W.

BOOK 4256
41.

Chains

S16
S21
1939

Along gradual N. slope. Desc. slightly.

46.60 Drain, course NE. Continue along gradual N. slope. Asc. 30 ft.

66.90 Draw, course NE. Asc. 30 ft. over SE. slope to

73.00 Top of low broken ridge, brs. NE. and SW. Desc. 20 ft. over W. slope to

77.70 Drain course N. Asc. slightly over NE. slope to

80.02 The cor. of secs. 16, 17, 20, and 21.

Land, rolling and gently rolling.

Soil, gravelly clay, 3rd rate.

No timber.

Undergrowth, sage, algerita, cliff rose, and cacti. Fair grass.

N. 0° 03' W., bet. secs. 16 and 17.

Over rolling land, thru low scattering undergrowth.

Desc. 10 ft. over gradual NE. slope to

6.90 Drain, course NW. Along W. slope. Desc. 20 ft.

17.10 Same drain, course N., from SW. Desc. gradually along drain.

27.50 Leave drain, course N. 60° E., from S. Asc. 15 ft. over SE. slope to

35.00 Top of low flat spur, slopes E. Desc. slightly over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap marked

S17|S16

1939

raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Continue slight descent over general NE. slope to

55.00 Slope changes to gradual SE. slope. Asc. gradually.

65.90 Dim road, brs. NE. and SW.

70.00 Top of low spur, slopes NE. Desc. NW. slope 18 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 8, 9, 16, and 17, with brass cap marked

T40N R9W

S8|S9

S17|S16

1939

raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Chains	
	Land, rolling and gently rolling. Soil, gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, cliff rose, and cacti. Fair grass.
	N. 89° 59' E., on a random line, bet. secs. 9 and 16.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 2 lks. S. of the cor. of secs. 9, 10, 15, and 16.
	Thence,
	S. 89° 58' W., on true line, bet. secs. 9 and 16.
	Over rolling land, thru low scattering undergrowth.
	Asc. 12 ft. over gradual E. slope to
10.00	Top of broad ridge, brs. NE. and SW. Desc. 55 ft. over gradual NW. slope to
38.70	Small gulch, course NE. Asc. slightly over SE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., over a cross (+) on limestone outcrop, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S9}{S16}$
	1939
	Asc. 40 ft. over gradual SE. slope to
73.00	Top of low spur, slopes NE. Desc. gradually over NW. slope to
80.00	The cor. of secs. 8, 9, 16, and 17.
	Land, rolling and gently rolling. Soil, gravelly clay, 3rd rate. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.
	N. 0° 03' W., bet. secs. 8 and 9.
	Over rolling land, thru low scattering undergrowth.
	Desc. slightly over NW. slope.
2.40	Wash, 25 lks. wide, course NE. Along a gradual E. slope. Desc. 25 ft.
26.20	Same wash; course NW.; approx. 3 chs. to junction with wash from W., thence NE. Along slight W. slope.
31.00	Same wash; course NE. Asc. 40 ft. over SE. slope to
35.00	Top of spur, slopes N. 60° E. Desc. 22 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S8}{S9}$
	1939

Survey: Subdivisional lines: T40N., R.9 W.

Chains

raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Desc. 65 ft. over a gently rolling NE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 4, 5, 8, and 9, with brass cap marked

T40N R9W

S5 | S4

S8 | S9

1939

raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling and gently rolling.

Soil, gravelly clay, 3rd rate.

No timber.

Undergrowth, sage and cacti. Good grass.

N. 89° 58' E., on a random line, bet. secs. 4 and 9.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line 5 lks. S. of the cor. of secs. 3, 4, 9, and 10.

Thence,

S. 89° 56' W., on true line, bet. secs. 4 and 9.

Over gently rolling land, thru low scattering undergrowth.

Desc. 30 ft. along gradual W. and SW. slopes.

23.00 Draw, course SE. Continue along a gradual S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap marked

S4

1/4 S9

1939

raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N. of cor.

Continue along a gradual S. slope.

63.00 Draw, course SE. Asc. 20 ft. over gradual NE. slope to

80.00 The cor. of secs. 4, 5, 8, and 9.

Land, gently rolling.

Soil, gravelly clay, 3rd rate.

No timber.

Undergrowth, sage, cacti, and algerita. Good grass.

N. 0° 03' W., bet. secs. 4 and 5.

Over gently rolling land, thru low scattering undergrowth.

Desc. slightly over NE. slope.

6.00 Dim road, brs. NE. and SW.

Chains

39.40 Wash, 20 lks. wide, course E. Asc. slightly along a gradual E. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

S5|S4

1939

raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

Continue along a slight E. slope to

58.00 Draw, course SE. Asc. slightly over a SE. slope.

68.30 Dim road, brs. SE. and NW

76.13 Intersect the Tenth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the closing cor. of secs. 4 and 5, with brass cap marked

T41N R9W
S33
S5|S4
T40N R9W
CC
1939

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, S. of cor.

The standard cor. of secs. 32 and 33, T. 41 N., R. 9 W., brs. West, 20.25 chs. dist., and the standard $\frac{1}{4}$ sec. cor. of sec. 33 brs. East, 19.75 chs. dist., both set, marked, and witnessed as described in the official record.

Land, gently rolling.
Soil, gravelly clay, 3rd rate.
No timber.
Undergrowth, sage and cacti. Good grass.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the field notes of T. 39 N., R. 9 W., surveyed under this group.

Thence,

N. 0° 03' W., bet. secs. 31 and 32.

Over rolling land, thru low scattering undergrowth.

Desc. 107 ft. over NW. slope to

17.00 Gulch, course N. 60° E. Asc. 33 ft. over rolling SE. slope to

31.00 Top of spur, slopes E. Desc. N. slope 32 ft. to

34.15 Draw, course E. Asc. S. slope 27 ft. to

39.40 Top of ridge, brs. N. 70° E. and S. 70° W. Desc. 6 ft. over NW. slope to

Chains

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the 1/4 sec. cor., with brass cap mkd.

1/4
S31|S32
1939

Desc. 69 ft. over NW. slope to

47.00 Draw, course N. 80° E. Asc. 60 ft. over broken SE. slope.

47.70 Dim road, brs. E. and W.

63.00 Top of spur, slopes E. Desc. 56 ft. over rolling NE. slope to

72.40 Draw, course SE. Asc. SW. slope 38 ft. to

78.00 Top of flat spur, slopes NE., from NW. Desc. N. slope 5 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 18 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the cor. of secs. 29, 30, 31, and 32, with brass cap marked

T40N R9W
S30|S29
S31|S32
1939

Land, rolling.
Soil, rocky clay and limestone, 3rd and 4th rates.
No timber.
Undergrowth, sage, algerita, and cliff rose. Good grass.

East, on a random line, bet. secs. 29 and 32.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line 5 lks. N. of the cor. of secs. 28, 29, 32, and 33.

Thence,

N. 89° 58' W., on true line, bet. secs. 29 and 32.

Over rolling land, thru low scattering undergrowth.

Asc. 90 ft. over a NE. slope.

11.80 Dim road, brs. NE. and SW.

27.30 Top of ridge, brs. N. and S. Desc. 10 ft. over W. slope to

30.10 Draw, near head, course NW. Asc. NE. slope 25 ft. to

35.00 Point of spur, slopes N. Desc. gradually over W. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the 1/4 sec. cor., with brass cap mkd.

1/4 S29
S32
1939

Survey; Subdivisional lines: T. 40 N., R. 9 W.

46.

Chains

- Desc. 37 ft. over W. slope to
- 46.00 Wash, 10 lks. wide, in wide draw, course N. Asc. 71 ft. over NE. slope.
- 47.10 Dim road, brs. N. and S. 30° W.
- 55.00 Top of spur, slopes SE., from W. Asc. 18 ft. along top of spur.
- 70.00 Short spur, slopes NE. Continue along top of spur. Asc. 12 ft.
- 77.00 Leave top of spur, slopes E., from SW. Along a gradual N. slope to
- 80.00 The cor. of secs. 29, 30, 31, and 32.

Land, rolling.
 Soil, sandy and rocky clay, 3rd rate.
 No timber.
 Undergrowth, sage, algerita, and cacti. Fair grass.

- West, on a random line, bet. secs. 30 and 31.
 - 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 - 76.64 Intersect the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of Tp., hereinbefore described.
 - Thence,
 - East, on true line, bet. secs. 30 and 31.
 - Over rolling land, thru low scattering undergrowth.
 - Asc. 25 ft. over W. slope to
 - 1.15 Top of ridge, brs. N. 10° W. and S. 10° E. Desc. 152 ft. over an E. slope.
 - 14.80 Dim road, brs. N. and S.
 - 16.60 Wide, flat draw, course NW., heads at very low saddle in spur, approx. 5 chs. S. Asc. 80 ft. over W. slope to
 - 24.10 Spur, slopes N. 60° W., from SW. Desc. 71 ft. over SE. slope to
 - 36.64 Set an iron post, 3 ft. long, 1 in. in diam., over cross (+) on limestone bedrock, and in a mound of stone to top for the $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$ S30
 S31
 1939
- Continue over SE. slope. Desc. 54 ft. to
 - 39.70 Rocky gulch, course N. 60° E. Asc. NW. slope 32 ft. to
 - 41.40 Slope changes to broken N. slope. Desc. 5 ft.
 - 53.60 Top of spur, slopes E., from SW. Desc. 24 ft. along flat top of spur.
 - 71.60 Leave top of spur, slopes S. 80° E., from W. Desc. NE. slope 12 ft. to

Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains

76.64

The cor. of secs. 29, 30, 31, and 32.

Land, rolling.

Soil, rocky clay and limestone, 3rd and 4th rates.

No timber.

Undergrowth, sage, algerita, cliff rose, and cacti. Good grass.

N. 0° 03' W., bet. secs. 29 and 30.

Over rolling land, thru low scattering undergrowth.

Desc. 34 ft. over gradual N. slope to

24.00 Desc. 79 ft. over steep N. slope to

28.50 Wash, 15 lks. wide, in wide draw, course NE. approx. 4 chs., thence E. Along gradual E. slope to

30.40 Wash, 10 lks. wide, course E. Asc. 57 ft. over S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$

S30|S29

1939

raise a mound

of stone, 4 ft. base, 2½ ft. high, W. of cor.

Continue over S. slope. Asc. 12 ft.

45.00 Top of spur, slopes E. Desc. NE. slope 80 ft. to

55.50 Swale, drains W. Asc. SW. slope 26 ft. to

63.00 Top of spur, slopes N., from E. Desc. 60 ft. along top of spur to

76.60 Leave top of spur, slopes NW., from S. Desc. 27 ft. over NE. slope to

80.00 Shallow draw, course N., from S. 30° E. Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 19, 20, 29, and 30, with brass cap marked

T40N R9W

S19|S20

S30|S29

1939

raise a mound

of stone, 3½ ft. base, 2½ ft. high, W. of cor.

Land, rolling.

Soil, rocky clay and limestone, 3rd and 4th rate.

No timber.

Undergrowth, sage, algerita, cliff rose, and cacti. Good grass.

S. 89° 58' E., on a random line, bet. secs. 20 and 29.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.96 Intersect N. and S. line 3 lks. N. of the cor. of secs.

BOOK 4256
48.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains	
	20, 21, 28, and 29.
	Thence, N. 89° 57' W., on true line, bet. secs. 20 and 29. Over rolling land, thru low scattering undergrowth.
	Asc. 20 ft. over E. slope to
4.00	Top of flat spur, slopes NE. Asc. 15 ft. along a N. slope.
23.10	Top of ridge, brs. S. 30° E. and N. 30° W. Desc. 60 ft. over W. slope to
27.00	Gulch, course N. 10° W. Asc. 70 ft. over E. slope to
33.00	Top of spur, slopes N. Desc. 48 ft. over W. slope to
39.98	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	S20 $\frac{1}{4}$ S29 1939
	raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
	Continue over W. slope. Desc. 31 ft.
47.10	Wash, 10 lks. wide, in wide draw, course N. Asc. 38 ft. over NE. slope.
48.60	Dim road, brs. N. and S.
53.20	Top of spur, slopes N., approx. 6 chs. Desc. 11 ft. over NW. slope to
60.50	Draw, course NE. Asc. 39 ft. over NE. slope to
66.00	Slope changes to N. slope. Asc. 6 ft. to
75.00	Top of spur, slopes N. 20° W. Desc. W. slope 29 ft. to
79.96	The cor. of secs. 19, 20, 29, and 30. Land, rolling. Soil, rocky clay and sandy clay, 3rd and 4th rates. No timber. Undergrowth, sage, algerita, and cacti. Fair grass.
	West, on a random line, bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
76.57	Intersect the W. bdy. of Tp. 4 lks. S. of the cor. of secs. 19, 24, 25, and 30, hereinbefore described.
	Thence, S. 89° 58' E., on true line, bet. secs. 19 and 30. Over rolling land, thru low scattering undergrowth. Desc. 6 ft. over gradual SE. slope to
0.60	Draw, course N. 30° E. Asc. 46 ft. over SW. slope to

Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains	
10.60	Top of spurs, sloping SE., NE., and N. 30° W., from low saddle in spur from SW. Desc. SE. slope 88 ft. to
31.10	Draw, course NE. Asc. 46 ft. over NW. slope to
36.57	Set an iron post, 3 ft. long, 1 in. in diam., over a cross (+) on bedrock, and in a mound of stone to top, for the 1/4 sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} S19 \\ \hline S30 \\ 1939 \end{array}$
	Continue over NW. slope. Asc. 34 ft.
42.60	Top of spur, slopes NE. Desc. 108 ft. over SE. slope to
58.80	Flat draw, course N. 70° E. Over nearly level bottom. Desc. 6 ft.
71.60	Flat draw, course N. approx. 6 chs. to junction with main draw from SW. Asc. 6 ft. over W. slope to
73.80	Top of low spur, slopes N. Desc. 10 ft. over E. slope to
76.57	The cor. of secs. 19, 20, 29, and 30.
	Land, rolling. Soil, rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage, algerita, and cliff rose. Good grass.
	N. 0° 03' W., bet. secs. 19 and 20.
	Over gently rolling land, thru low scattering undergrowth. Desc. 15 ft. in shallow draw, course N.
9.00	Draw, course E. Asc. 23 ft. over gently rolling SE. slope.
20.00	Top of spur, slopes NE., from W. Desc. N. slope 66 ft. to
39.94	Dim road, brs. W. and E. approx. 2 chs. to main road.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{r} S19 S20 \\ 1939 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Desc. 5 ft. over N. slope to
41.30	Wash, 15 lks. wide, course E. Asc. 11 ft. over gently rolling S. slope.
50.80	Bend in dim road, brs. NE. and S. 10° E.
68.00	Top of low flat spur, slopes E. Desc. N. slope 15 ft. to
74.90	Wash, 15 lks. wide, course S. 80° E. Asc. 20 ft. over SE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 17, 18, 19, and 20,

Chains	
	<p>with brass cap marked</p> <p style="text-align: center;">T40N R9W $\frac{S18}{S19} \frac{S17}{S20}$ 1939</p> <p style="text-align: right;">raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling and gently rolling. Soil, sandy to rocky clay and limestone, 3rd rate. No timber. Undergrowth, sage, algerita, and cliff rose. Good grass.</p>
40.00	<p>S. $89^{\circ} 57'$ E., on a random line, bet. secs. 17 and 20. Set temp. $\frac{1}{4}$ sec. cor.</p>
79.94	<p>Intersect N. and S. line 7 lks. N. of the cor. of secs. 16, 17, 20, and 21.</p> <p>Thence,</p> <p>N. $89^{\circ} 54'$ W., on true line, bet. secs. 17 and 20. Over rolling land, thru low scattering undergrowth. Asc. gradually over NE. slope to</p>
30.00	<p>Top of flat spur, slopes N. Desc. 25 ft. over NW. slope.</p>
36.30	<p>Wash, 25 lks. wide, 2 ft. deep, course NE. Asc. 25 ft. over SE. slope up point of spur, from W.</p>
39.97	<p>Set an iron post, 3 ft. long, 1 in. in diam., over cross (+) on limestone bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{S17}{\frac{1}{4} S20}$ 1939</p>
	<p>Asc. 49 ft. over top of spur.</p>
47.90	<p>Leave top of spur, slopes E., from N. 10° W. Desc. 29 ft. over SW. slope to</p>
54.90	<p>Swale, drains SE. Asc. 74 ft. over SE. slope.</p>
70.15	<p>Dim road, brs. N. and S.</p>
79.94	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, rolling. Soil, sandy to rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage, algerita, and cliff rose. Good grass.</p>
40.00	<p>N. $89^{\circ} 58'$ W., on a random line, bet. secs. 18 and 19. Set temp. $\frac{1}{4}$ sec. cor.</p>
76.54	<p>Intersect the W. bdy. of Tp. 4 lks. S. of the cor. of secs. 13, 18, 19, and 24, hereinbefore described.</p> <p>Thence,</p>

Survey: Subdivisional lines: T. 40 N., R. 9 W.

51.

Chains	
	S. 89° 56' E., on true line, bet. secs. 18 and 19. Over rolling land, thru low scattering undergrowth. Asc. 88 ft. over NW. slope to
5.90	Top of flat spur, slopes N. 30° E. Desc. E. slope 39 ft.
14.30	Ravine, course N., heads approx. 7 chs. S. Asc. NW. slope 12 ft. to
17.90	Dim road, brs. NE. and SW. on spur, slopes NE. Desc. 52 ft. over SE. slope to
29.10	Wash, 20 lks. wide, course N. 70° E. Along slight N. slope to
31.50	Short draw, course N. to wash. Asc. 29 ft. over NW. slope.
36.54	Top of spur, slopes NE., from N. 30° W. Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the ¼ sec. cor., with brass cap mkd.
	S18 S19 1939
	Desc. 35 ft. over E. slope to
43.50	Swale, drains SE. Asc. SW. slope 12 ft. to
46.50	Top of spur, slopes N. 60° E., from NW. Desc. SE. slope 17 ft. to
52.20	Swale, drains S. approx. 5 chs. to wash, whose course is E. Asc. SW. slope 29 ft.
62.00	Top of short spur, slopes S. Desc. 50 ft. over SE. slope.
76.54	The cor. of secs. 17, 18, 19, and 20. Land, rolling. Soil, rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sage, algerita, and cliff rose. Good grass.
	N. 0° 03' W., bet. secs. 17 and 18. Over rolling land, thru low scattering undergrowth. Asc. 7 ft. over SE. slope to
8.20	Top of flat spur, slopes E. Desc. NE. slope 19 ft. to.
12.40	Draw, course E., heads approx. 8 chs. W. Asc. 20 ft. over SE. slope to
17.00	Top of spur, slopes N. 60° E. Desc. 44 ft. over N. slope.
22.60	Draw, course N. 60° E. Along a rolling gradual E. slope. Desc. 7 ft.
33.85	Dim road, brs. S. 30° E. and N. 30° W.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the ¼ sec. cor., with brass cap mkd.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

52.

Chains	
	$\frac{1}{4}$ S18 S17 1939 Continue along gradual E. slope.
48.40	Top of spur, slopes N. 30° E. Desc. 17 ft. over NW. slope.
53.40	Swale, drains W. Asc. SW. slope 15 ft. to
70.00	Top of spur, slopes NW. Desc. NE. slope 47 ft. to
80.00	Shallow draw, course N., from SE. Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 7, 8, 17, and 18, with brass cap marked
	T40N R9W S7 S8 S18 S17 1939 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, rocky clay, 3rd and 4th rate. No timber. Undergrowth, sage, algerita, and cliff rose. Good grass.
	S. 89° 54' E., on a random line, bet. secs. 8 and 17.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect N. and S. line 3 lks. S. of the cor. of secs. 8, 9, 16, and 17.
	Thence, N. 89° 55' W., on true line, bet. secs. 8 and 17. Over rolling land, thru low scattering undergrowth. Desc. slightly over NW. slope to
4.20	Wash, 25 lks. wide, course NE. Asc. 45 ft. over SE. slope.
24.00	Top of spur, slopes NE. Along N. slope. Asc. 15 ft.
32.10	Top of same spur, slopes SE. Along S. slope. Asc. 18 ft.
39.98	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	S8 $\frac{1}{4}$ S17 1939 raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor. Asc. 45 ft. over SE. slope to
48.00	Top of same spur, slopes NE. Desc. 5 ft. over slight NW. slope to
67.30	Draw, course N. Asc. 23 ft. over NE. slope to

Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains 73.00 79.96	<p>Top of spur, slopes N. Desc. 26 ft. over NW. slope to The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling. Soil, sandy to rocky clay, 3rd rate. No timber. Undergrowth, sage, algerita, and cacti. Good grass.</p>
40.00 76.50	<p>N. 89° 56' W., on a random line, bet. secs. 7 and 18.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p> <p>Intersect the W. bdy. of Tp. 4 lks. S. of the cor. of secs. 7, 12, 13, and 18, hereinbefore described.</p> <p>Thence,</p> <p>S. 89° 54' E., on true line, bet. secs. 7 and 18.</p> <p>Over nearly level land, thru low scattering undergrowth. Desc. 30 ft. over slight E. slope to</p>
25.00 36.50	<p>Wash, 20 lks. wide, course N., approx. 7 chs., thence N. 60° E. Over nearly level land.</p> <p>Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked</p>
	<p>S7 $\frac{1}{4}$ S18 1939</p>
	<p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Continue over nearly level land.</p>
39.80 58.50 63.90 71.50 76.50	<p>Dim road, brs. NE. and SW.</p> <p>Shallow draw, course N. Asc. 29 ft. over gradual W. slope.</p> <p>Dim road, brs. N. and S.</p> <p>Top of low spur, slopes N. Desc. slight E. slope 6 ft. to The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, nearly level and gently rolling. Soil, sandy to rocky clay, 3rd. rate. No timber. Undergrowth, sage and cliff rose. Good grass.</p>
18.90 22.30 25.00 40.00	<p>N. 0° 03' W., bet. secs. 7 and 8.</p> <p>Over gently rolling land, thru low scattering undergrowth. Desc. 57 ft. in shallow draw.</p> <p>Dim road, brs. E. and W.</p> <p>Dim road, brs. NE. and SW.</p> <p>Leave draw, course N. 30° W., from S. Along gradual W. slope, desc. 5 ft.</p> <p>Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in</p>

BOOK 4256

54.

Survey: Subdivisional lines: T. 40 N., R. 9 W.

Chains

the ground, over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$

S7|S8

1939

Asc. 15 ft. over gradual SW. slope.

60.00 Top of flat spur, slopes NE., from SE. Desc. 72 ft. over NW. slope to

72.10 Wash, 20 lks. wide, course NE. Asc. SE. slope 18 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 5, 6, 7, and 8, with brass cap marked

T40N R9W

S6|S5

S7|S8

1939

raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high W. of cor.

Land, gently rolling and rolling.

Soil, gravelly and rocky clay, 3rd and 4th rates.

No timber.

Undergrowth, sage, algerita, and cliff rose. Good grass.

S. $89^{\circ} 55'$ E., on a random line, bet. secs. 5 and 8.40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect N. and S. line 4 lks. S. of the cor. of secs. 4, 5, 8, and 9.

Thence,

N. $89^{\circ} 57'$ W., on true line, bet. secs. 5 and 8.

Over gently rolling land, thru low scattering undergrowth.

Asc. 40 ft. over gradual NE. slope.

18.70 Dim road, brs. N. 60° E. and S. 60° W.39.95 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

S5

 $\frac{1}{4}$ S8

1939

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Continue over gradual NE. slope. Asc. 6 ft.

40.50 Dim road, brs. N. 20° E. and S. 20° W.

46.00 Slope changes to gradual W. slope. Desc. 20 ft. to

55.50 Draw, course N. Asc. 20 ft. over E. slope to

59.90 Top of low spur, slopes N. 10° E. Desc. 12 ft. over NW. slope to

Survey: Subdivisional lines: T. 40 N., R. 9 W.

55

Chains	
72.90	Wash, 20 lks. wide, course N.60°E. Asc. 35 ft. over SE. slope to
79.90	The cor. of secs. 5, 6, 7 and 8. Land, gently rolling. Soil, gravelly clay, 3rd rate. No timber. Undergrowth, sagebrush, algerita and cacti. Good grass.
	N. 89° 54' W., on random line, bet. secs. 6 and 7.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
76.47	Intersect the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	Thence
	S. 89° 54' E., on true line, bet. secs. 6 and 7.
	Over rolling land, thru low scattering undergrowth.
	Asc. 23 ft. over SW. slope.
11.50	Long flat spur, slopes N.20°E., and head of a spur, sloping NW.. Desc. 23 ft. over gradual E. slope to $\frac{1}{4}$ sec. cor.
26.50	Dim road, bears NE. and SW.
36.47	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in ground to bedrock, over a cross (X) chiselad thereon, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S6}{\frac{1}{4} \text{ --- } S7}$ 1939
	Desc. 71 ft. over gradual E. slope.
54.00	Ravine, course S. Asc. 39 ft. over W. slope.
57.50	Spur, slopes S. Desc. 74 ft. over NE. slope.
70.40	Ravine, course S. from NW. Asc. 24 ft. over SW. slope.
73.70	Spur, slopes S. about 3 chs. Desc. 36 ft. over SE. slope to
76.47	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sagebrush, algerita and cliff rose. Good grass.
	N. 0° 03' W., bet. secs. 5 and 6.
	Over rolling land, thru low, scattering undergrowth.
	Asc. 53 ft. over SE. slope.
7.00	Spur, slopes NE. from W. Desc. 41 ft. over N. slope.
11.30	Dim road, bears E. and W.

Chains 18.05	Draw, course NE.; heads about 10 chs. SW. Asc. 22 ft. over SE. slope.
24.00	Spur, slopes NE. Desc. 66 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in ground to bedrock, over a cross (X) chiseled thereon, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S6 S5 1939
	Desc. 28 ft. over N. slope.
44.60	Wash, 10 lks. wide, course E., joined at this point by a small wash from SW. Asc. 57 ft. over S. slope.
50.00	Spur, slopes E. Desc. 93 ft. over N. slope.
69.00	Draw, course NE. Asc. 21 ft. over SE. slope.
74.00	Spur, slopes NE. Desc. gradually over N. slope to
76.06	Intersect the 10th Standard Parallel North. Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in ground, for closing cor. of secs. 5 and 6, with brass cap marked
	T41N R9W S32 <hr/> S6 S5 T40N R9W CC 1939
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, S. of cor.
	From point of intersection, the std. cor. of secs. 31 and 32, T.41 N., R.9 W., bears West, 20.43 chs. dist., and the std. $\frac{1}{4}$ sec. cor. of sec. 32 bears East, 19.57 chs. dist., both being regulation brass-capped iron posts, firmly set, marked and witnessed as described in the official record.
	Land, rolling. Soil, rocky clay and limestone, 3rd and 4th rates. No timber. Undergrowth, sagebrush, algerita and cliff rose. Good grass.
	GENERAL DESCRIPTION.
	The surface of T.40 N., R.9 W. is in general, rolling and varying to slightly broken in the southwest portion, and in secs. 3, 10 and 14, where Clayhole Wash forms a small canyon. The general elevation of the land is from 4900 to 5000 feet above sea level. The soil is a sandy to gravelly clay, with limestone and gypsum occurring frequently. A sandy limestone is prevalent over the broken land. There is no permanent water supply of any consequence. A small water seep appears in Clayhole Wash, in SW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 11. Most of the drainage is carried by said wash, which is a cut bank clay wash, varying from 1 to 3 chs.

wide, and about 20 ft. deep, in secs. 13, 14 and 24, forming a small canyon in sec. 14, and draining thru secs. 14, 11, 10 and 3.

There is no timber in the township. The undergrowth, consisting mainly of sagebrush, with some algerita, cliff rose, Mormon tea and cacti, is low and in general scattering. There is an excellent growth of native grass over most of the land, rendering all sections suitable for grazing.

There are no settlers or improvements. No development of mineral, water or land has been made in the township. There is no doubt but what water could be obtained by sinking wells in several parts of the township; but the water, in all probability would be suitable only for stock watering purposes because the gypsum content would be too high for domestic or other uses.

There are no improved roads, but there are several unimproved roads used by stockmen which give travel facilities over most of the area.

The mean magnetic declination is $15^{\circ}50'E$.

FINAL FIELD TESTS OF INSTRUMENTS.

Buff and Buff transit No. 16723.
Horace M. Muscott, Surveyor.

May 13, 1939;

At station in camp near center of sec. 20, T. 40 N., R. 10 W., G. and S. R. meridian, Arizona, latitude $36^{\circ}51'N$, longitude $113^{\circ}23\frac{1}{2}'W$, examine the adjustments of Buff and Buff transit No. 16723 and find no errors. Then, to test the solar apparatus of same by comparing its indications with a true meridian, proceed as follows:

May 14, 1939;

at 4h. 21m., a.m., l.m.t., observe Polaris at eastern elongation, making four observations, two each with the telescope in direct and reversed positions and mark the mean point in the line thus determined by a nail in a stake driven firmly in the ground about 10 chs. N.

Azimuth of Polaris at eastern elongation = $1^{\circ}17'00''$

At 7h. 00m., a.m., lay off the azimuth of Polaris $1^{\circ}17'$ to the west and mark a point in the true meridian thus determined by a nail in a stake driven firmly in the ground about 10 chs. N.

At 8h. 00m., a.m., app.t., set off $36^{\circ}51'N$ on the lat. arc; $18^{\circ}31\frac{1}{2}'N$ on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $18^{\circ}33\frac{1}{2}'N$ on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $18^{\circ}36\frac{1}{2}'N$ on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same which are described in the foregoing field notes.

ECCO 4256

58

Buff and Buff transit No. 9984.
Claude F. Warner, Transitman.

July 2, 1939;

At station in camp near cor. of secs. 3, 4, 33 and 34, Ts. 38 and 39 N., R. 9 W., latitude $36^{\circ}43\frac{1}{2}'$ N., longitude $113^{\circ}15\frac{1}{2}'$ W., examine the adjustments of Buff and Buff transit No. 9984 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with a true meridian established at this station on June 11, 1939, by Polaris observation, as described in field notes of resurvey of West bdy. and survey of North bdy. and subdivisional lines of T. 38 N., R. 9 W., executed under this group, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}43\frac{1}{2}'$ N. on the lat. arc; $23^{\circ}05\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $23^{\circ}04\frac{1}{2}'$ N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $23^{\circ}04'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same which are described in the foregoing field notes.

Young and Sons' transit No. 8526.
Frank Motch, Public Land Surveyor.

July 2, 1939;

At same station where the preceding instrument tests were made, examine the adjustments of Young and Sons' transit No. 8526 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with the same true meridian, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}43\frac{1}{2}'$ N. on the lat. arc; $23^{\circ}05\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $23^{\circ}04\frac{1}{2}'$ N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $23^{\circ}04'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same which are described in the foregoing field notes.

CERTIFICATE OF SURVEYOR

I, Frank Motos, Public Land Surveyor, HEREBY CERTIFY upon honor that, in pursuance of ^{supplemental} special instructions bearing date of the 30th day of April, 1936, received from the district cadastral engineer for Arizona, with assignment instructions dated April 11, 1939, I have surveyed

Part of the North boundary and

Part of the Subdivisional lines of

Township 40 North, Range 9 West

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona Frank Motos

February 1, 1940 Public Land Surveyor.

~~CERTIFICATE OF APPROVAL~~

~~Office of Supervisor of Surveys,~~

~~, 19~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under special instructions dated~~, ~~and assignment~~

~~instructions dated~~, ~~having been critically examined, and~~

~~the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey~~

~~therein described, are hereby approved.~~

~~Supervisor of Surveys.~~

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~

~~is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~

CERTIFICATE OF SURVEYOR

I, Claude F. Warner, Transitman, HEREBY CERTIFY upon honor that, in pursuance of ^{supplemental} special instructions bearing date of the 30th day of April, 1936, received from the district cadastral engineer for Arizona, with assignment instructions dated April 11, 1939, I have surveyed

Part of the North boundary and

Part of the Subdivisional lines of

Township 40 North, Range 9 West

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona

February 1, 1940

Claude F. Warner

Transitman

~~CERTIFICATE OF APPROVAL~~

~~Office of Supervisor of Surveys,~~

~~, 19~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under special instructions dated~~

~~instructions dated~~

~~the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.~~

~~Supervisor of Surveys.~~

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~

~~is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~

216
64 BOOK 4256

BOOK 4256

CERTIFICATE OF SURVEYOR

I, Horace M. Muscott, Surveyor, HEREBY CERTIFY upon honor that, in pursuance of ^{supplemental} special instructions bearing date of the 30th day of April, 1936, received from the district cadastral engineer for Arizona, with assignment instructions dated April 11, 1939, I have surveyed

the West boundary of
Township 40 North, Range 9 West

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
January 23, 1940

Horace M. Muscott
Surveyor

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colo., October 26, 1942.

The foregoing field notes of the survey of the West boundary; North boundary (along 10th Std. Parallel North); and Subdivisional lines of
Township 40 North, Range 9 West

of the Gila and Salt River Meridian, in the State of Arizona
executed by Horace M. Muscott; Surveyor; Claude F. Warner, Transitman;
and Frank Moteh, Public Land Surveyor.

executed by ^{supplemental} special instructions dated April 30, 1936, for Group 210, Arizona, and assignment instructions dated April 11, 1939, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Samuel J. Johnson
Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~