

①

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

BOOK 4260

FIELD NOTES

OF SURVEY OF

NORTH BOUNDARY
(on 9th Std. Parallel North)

and

SUBDIVISIONAL LINES

of

TOWNSHIP 36 NORTH RANGE 9 WEST

Of the Gila and Salt River Meridian,

In the State of ARIZONA

EXECUTED BY

Horace M. Muscott, Surveyor,

Claude F. Warner, Transitman,

and Frank Moteh, Public Land Surveyor

supplemental
Under special instructions dated April 30, 1936, which provided
for the surveys included under Group No. 210 Arizona, bearing the approval of the
Commissioner of the General Land Office under date of July 24 1936
and assignment instructions dated April 11, 1939

Survey commenced July 26, 1939

Survey completed August 7, 1939

4260

INDEX DIAGRAM.

Township _____, Range _____






6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

INDEX-DIAGRAM

BOOK 4260

T.37N-R9W

36	31	32	33	34	35	36	31
	9TH	STANDARD		PARALLEL		NORTH	
	9 8	8 7	7 6	6 5	5 4	4 3	
1	6 67 66	5 52 65	4 41 51 50	3 30 40	2 19 29	1 18	6
12	7 64 63 64	8 49 63 62	9 39 49 48	10 28 38 37	11 17 27	12 16	7
13	18 61 60 61	17 47 60 59	16 37 36 T.36N-R.9W 47 46	15 26 36 35	14 15 25	13 14	18
24	19 59 58 57 58	20 46 45 57 56	21 35 34 45 44	22 24 34 33	23 13 23	24 12 13 12	19
25	30 56 55 54 55	29 44 43 54 53	28 33 32 43 42	27 22 32	26 12 21 11	25 11	30
36	31 53 52	32 42 41	33 31 30	34 20	35 10	36	31
1	6	5	4	3	2	1	6

-  Lines of accepted surveys
-  Lines resurveyed under this group
-  Lines surveyed under this group
-  Survey under this group accomplished by establishment of closing Cors. and single reference 1/4 sec. cors. on accepted surveyed line.
-  Areas surveyed as per accepted plats on file

The surveys herein described were executed by Horace M. Muscott, Surveyor, Claude F. Warner, Transitman, and Frank Moteh, Public Land Surveyor, using, respectively, Buff and Buff transits Nos. 16723 and 9984, and Young and Sons' transit No. 8526. Each of these instruments is equipped with an improved Smith solar attachment, and otherwise conforms to the standard specifications of the General Land Office.

The azimuths of all of the lines of survey herein described were determined with the solar attachments.

All of the measurements were made with Dietzgen steel tapes, 5 chs. in length, graduated every link for the first 100 lks., and the remainder at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard tape and found correct. All of the measurements were made on the slope, the vertical angle of each interval determined with a clinometer in good adjustment, and the horizontal equivalents entered in the field notes.

PRELIMINARY FIELD TESTS OF INSTRUMENTS.

Buff and Buff transit No. 16723.
Horace M. Muscott, Surveyor.

July 23, 1939;

At station in camp near center of sec. 16, T. 36 N., R. 9 W., latitude $36^{\circ}31\frac{1}{2}'N.$, longitude $113^{\circ}16'W.$, examine the adjustments of Buff and Buff transit No. 16723 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with a true meridian determined by Polaris observation at this station on July 11, 1939, as described in field notes of survey of T. 37 N., R. 9 W., executed under this group, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}31\frac{1}{2}'N.$ on the lat. arc; $20^{\circ}11\frac{1}{2}'N.$ on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $20^{\circ}09'N.$ on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $20^{\circ}07\frac{1}{2}'N.$ on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, prior to the beginning of the surveys executed with same which are described herein.

Buff and Buff transit No. 9984.
Claude F. Warner, Transitman.

July 23, 1939:

At same station where the preceding test of instrument was made, examine the adjustments of Buff and Buff transit No. 9984 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with the same true meridian, proceed as follows:

2

At 8h. 00m., a.m., app.t., set off $36^{\circ}31\frac{1}{2}'$ N. on the lat. arc; $20^{\circ}11\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $20^{\circ}09'$ N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $20^{\circ}07\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, prior to the beginning of the surveys executed with same which are described herein.

Young and Sons' transit No. 8526.
Frank Moteh, Public Land Surveyor.

July 23, 1939;

At same station where the two preceding instrument tests were made, examine the adjustments of Young and Sons' transit No. 8526 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with the same true meridian, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}31\frac{1}{2}'$ N. on the lat. arc; $20^{\circ}11\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $20^{\circ}09'$ N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $20^{\circ}07\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, prior to the beginning of the surveys executed with same which are described herein.

Survey of North Boundary of T. 36 N., R. 9 W.
(on the 9th Std. Parallel North)

4200

3

Chains	<p>The following notes describe the survey of the North bdy. of T. 36 N., R. 9 W., along the 9th Std. Parallel North, from the closing cor. of Ts. 36 N., Rs. 8 and 9 W., westerly to the closing cor. of Ts. 36 N., Rs. 9 and 10 W., accomplished by the establishment thereon of subdivisional closing cors. and N. $\frac{1}{4}$ sec. cors. of the north tier of secs. of T. 36 N., R. 9 W. The said $\frac{1}{4}$ sec. cors. are established at midpoints of the N. bdrs. of secs. 1, 2, 3, 4 and 5, and at 40 chs. in W. departure from the closing cor. of secs. 5 and 6, for the N. $\frac{1}{4}$ sec. cor. of sec. 6.</p> <p>The Parallel was surveyed thru Rs. 8, 9, 10 and 11 W. by T. B. Matthews, U.S. Surveyor, in 1915, and no retracement or resurvey of the line in any part of these ranges is of record, however, the S. bdy. of sec. 31, T. 37 N., R. 9 W. was resurveyed under this group as described in the field notes of subdivisional survey of T. 37 N., R. 9 W.</p> <p>Except the retracement of S. bdy. of sec. 31, T. 37 N., R. 9 W. executed under this group, preliminary to the resurvey thereof, no retracement of the Parallel in Rs. 8 and 9 W. was made as a preliminary process to the survey of N. bdy. of T. 36 N., R. 9 W., described herein, the bearing of the line and the measurements of the corner intervals, described in the official record, being accepted without any change.</p> <p>The lengths of the N. bdrs. of secs. 1, 2, 3, 4 and 5, and the points for the N. $\frac{1}{4}$ sec. cors. thereof, are computed from the official record, chaining only the connecting distances bet. the closing cors. and the standard cors. on which they close, and the computed offset distances bet. the $\frac{1}{4}$ sec. cors. The length of the N. bdy. of sec. 6 was completely measured under this group, by survey of the connection bet. the closing cor. of secs. 5 and 6, and the std. cor. of secs. 31 and 32, and by the resurvey of the S. bdy. of sec. 31.</p> <p>With the exception of the N. bdy. of sec. 6, crossing of an ungraded road at 17.80 ch. sta. on N. bdy. of sec. 1, and the crossings of the Hurricane-Mt. Trumbull road on N. bdrs. of secs. 1 and 3, the topographical features, roads and relative data, are copied from the official record, computing the stations as required to give them the proper relation to the governing closing cors. of this survey.</p> <hr/> <p>The closing cor. of Ts. 36 N., Rs. 8 and 9 W. is an iron post, 3 ins. in diam., projecting 12 ins. above ground, firmly set, marked on brass cap and witnessed as described in the official record.</p> <p>Thence</p> <p>West, on N. bdy. of sec. 1 (S. of sec. 31, T. 37 N., R. 8 W.)</p> <p>Over rolling land, thru scattering timber and undergrowth. Descend.</p> <p>1.97 Draw, course SW. Ascend.</p> <p>6.12 Spur, slopes S. Descend.</p> <p>7.12 Ascend 25 ft.</p> <p>12.12 Spur, slopes S. Desc. 30 ft.</p> <p>13.45 Draw, course SE. Ascend.</p> <p>17.12 Intersect the std. cor. of Ts. 37 N., Rs. 8 and 9 W., an iron post, 3 ins. in diam., projecting 12 ins. above</p>
--------	--

Survey of North Boundary of T. 36 N., R. 9 W.
(on the 9th Std. Parallel North)

4

Chains	ground, firmly set, marked on brass cap and witnessed as described in the official record.
	Continue line and measurement, (S. of sec. 36, T. 37 N., R. 9 W.)
	Ascend 80 ft. to top of knoll.
17.80	Ungraded road, brs. S: 1° W. and N: 6° W.
39.96	(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in ground to bedrock, over a cross (X) chiseled thereon, and in a mound of stone to top, for N. $\frac{1}{4}$ sec. cor. of sec. 1, with brass cap marked
	$\frac{1}{4}$ S1.
	1939
	No bearing trees available.
44.12	Top of small knoll. Desc. 30 ft.
49.50	Gulch, 20 lks. wide, course NE. Asc. 30 ft.
52.12	Low ridge, brs. N. and S. Desc. 20 ft.
57.12	Intersect the std. $\frac{1}{4}$ sec. cor. of sec. 36, an iron post, 1 in. in diam., projecting 10 ins. above ground, firmly set, properly marked on brass cap, and witnessed by a mound of stone N. No bearing trees.
59.62	Draw, 25 lks. wide, course N. Asc. 85 ft.
65.07	Sharp spur, slopes N. Desc. 40 ft.
69.84	Canyon, 10 chs. wide, course NE. Asc. 90 ft. to C.C.
75.30	Hurricane-Mt. Trumbull ungraded road, brs. N. 50° E. & S. 50° W.
79.91	Intersect the subdivisional line bet. secs. 1 and 2, surveyed N. 0° 01' W.. Closing cor. of said secs. established at this point as hereinafter described.
	Land, rough and rolling. Soil, thin and rocky, 4th rate. Timber, cedar. Undergrowth, greasewood. Short grass.
	From closing cor. of secs. 1 and 2, West, on N. bdy. of sec. 2. (S. of sec. 36, T. 37 N., R. 9 W.) Over rolling land, thru scattering undergrowth. Asc. 20 ft.
8.81	Spur, slopes N. Descend.
17.21	Intersect the std. cor. of secs. 35 and 36, an iron post, 3 ins. in diam., projecting 26 ins. above ground, firmly set in ground and mound of stone, properly marked on brass cap and witnessed by a mound of stone N.
	Continue line and measurement (S. of sec. 35, T. 37 N., R. 9 W.) Ascend 25 ft.
25.21	Spur, slopes N. Desc. 45 ft.
33.26	Draw, 5 lks. wide, course SE. Asc. 40 ft. to ridge.
39.91	(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in ground, for the N. $\frac{1}{4}$ sec. cor. of sec. 2, with brass cap marked

Survey of North Boundary of T. 36 N., R. 9 W.
(on the 9th Std. Parallel North)

Chains

$\frac{1}{4}$ S2
1939

from which.

A juniper, 12 ins. diam., brs. S. $86\frac{1}{4}^\circ$ W., 464 lks. dist., marked $\frac{1}{4}$ S2 BT.

No other bearing trees available.

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

47.21 Ridge, brs. N. and S. Descend.

52.21 Enter scattering timber, brs. N. and S.

57.21 Intersect the std. $\frac{1}{4}$ sec. cor. of sec. 35, an iron post, 1 in. in diam., projecting 10 ins. above ground, firmly set, marked on brass cap and witnessed as described in the official record.

Ascend 30 ft.

72.21 Low ridge, brs. N. and S. Descend.

79.81 Intersect the subdivisional line bet. secs. 2 and 3, surveyed N. $0^\circ 01'$ W. Closing cor. of said secs. established at this point as hereinafter described.

Land, rolling.
Soil, thin and rocky, 4th rate.
Timber, cedar and pinyon.
Undergrowth, greasewood. Short grass.

From closing cor. of secs. 2 and 3,
West, on N. bdy. of sec. 3 (S. of sec. 35, T. 37 N., R. 9 W.)
Over rolling land, thru scattering timber and undergrowth.
Descend.

4.00 Hurricane Mt. Trumbull ungraded road, brs. N. 81° W. and S. 81° E.

5.30 Same road, brs. N. 80° E. and S. 80° W.

17.40 Intersect the std. cor. of secs. 34 and 35, an iron post, 3 ins. in diam., projecting 12 ins. above ground, firmly set, marked on brass cap and witnessed as described in the official record.

Continue line and measurement (S. of sec. 34, T. 37 N., R. 9 W.)

Ascend.

40.02 (Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in ground to bedrock, and in a mound of stone to top, for N. $\frac{1}{4}$ sec. cor. of sec. 3, with brass cap marked

$\frac{1}{4}$ S3
1939

from which

Survey of North Boundary of T. 36 N., R. 9 W.
(on the 9th Std. Parallel North)

6

Chains	
	A juniper, 8 ins. diam., brs. S. 63° E., 100 lks. dist., marked $\frac{1}{4}$ S3 BT.
	A pinyon, 5 ins. diam., brs. S. 59° W., 24 lks. dist., marked $\frac{1}{4}$ S3 BT.
	Ascend.
42.40	Low ridge, brs. N. and S. Desc.
47.40	Head of gulch, course N.
50.40	Descend 105 ft.
54.05	Canyon, 4 chs. wide, course NE. Asc. 30 ft.
57.40	Intersect the std. $\frac{1}{4}$ sec. cor. of sec. 34, an iron post, 1 in. in diam., projecting 36 ins. above ground, firmly set in a mound of stone, properly marked on brass cap, and witnessed by a mound of stone N. No bearing trees.
	Ascend.
60.40	Descend 15 ft.
63.20	Road, brs. N. and S., in draw, course N. Asc. 110 ft.
75.25	Ridge, brs. N. and S. Desc. 40 ft.
77.40	Enter timber, brs. N. and S.
80.03	Intersect the subdivisinal line bet. secs. 3 and 4, surveyed N. 0° 02' W. Closing cor. of said secs. established at this point as hereinafter described.
	Land, rolling Soil, thin and rocky, 4th rate. Timber juniper and pinyon. Undergrowth, sagebrush and greasewood. Fair grass.
	From closing cor. of secs. 3 and 4, West, on N. bdy. of sec. 4 (S. of sec. 34, T. 37 N., R. 9 W.)
	Over rolling land, thru dense timber and scattering undergrowth.
7.37	Ridge, brs. N. and S. Desc. 40 ft.
11.16	Canyon, 1 ch. wide, course N. Asc. 65 ft.
15.57	Spur, slopes NE. Desc.
17.37	Intersect the std. cor. of secs. 33 and 34, an iron post, 3 ins. in diam., projecting 24 ins. above ground, firmly set in ground and mound of stone, marked on brass cap and witnessed as described in the official record.
	Continue line and measurement (S. of sec. 33, T. 37 N., R. 9 W.)
	Descend.
32.37	Dim road, brs. N. and S. Asc. 20 ft.
34.87	Low ridge, brs. N. and S. Desc. 20 ft.

Survey of North Boundary of T. 36 N., R. 9 W.
(on the 9th Std. Parallel North)

7

Chains 37.37	Thence over rolling prairie.
40.05	(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in ground to bedrock, and in a mound of stone to top, for N. $\frac{1}{4}$ sec. cor. of sec. 4, with brass cap marked
	<u>$\frac{1}{4}$ S4</u> 1939
	from which
	A pinyon, 6 ins. diam., brs. S. $56\frac{3}{4}^{\circ}$ E., 84 lks. dist., marked $\frac{1}{4}$ S4 BT.
	A pinyon, 5 ins. diam., brs. S. 10° W., 96 lks. dist., marked $\frac{1}{4}$ S4 BT.
57.37	Intersect the std. $\frac{1}{4}$ sec. cor. of sec. 33, an iron post, 1 in. in diam., projecting 18 ins. above ground, firmly set in ground and mound of stone, marked on brass cap and witnessed as described in the official record.
	Descend 15 ft.
60.37	Draw, 1 ch. wide, course NE. Asc. 15 ft.
80.10	Intersect the subdivisional line bet. secs. 4 and 5, surveyed N. $0^{\circ} 03' W.$ Closing cor. of said secs. established at this point as hereinafter described.
	Land, rolling. Soil, thin and rocky, 4th rate. Timber, juniper and pinyon. Undergrowth, greasewood and sagebrush. Fair grass.
	From closing cor. of secs. 4 and 5, West, on N. bdy. of sec. 5 (S. of sec. 33, T. 37 N., R. 9 W.) Over rolling land, thru dense timber and scattering undergrowth.
	Ascend.
2.27	Low ridge, brs. N. and S. Desc. 50 ft.
10.27	Draw, 1 ch. wide, course N. Asc. 50 ft.
17.27	Intersect the std. cor. of secs. 32 and 33, an iron post, 3 ins. in diam., projecting 12 ins. above ground, firmly set, marked on brass cap and witnessed as described in the official record.
	Continue line and measurement (S. of sec. 32, T. 37 N., R. 9 W.)
39.83	(Midpoint) Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, over a cross (X) chiseled thereon, and in a mound of stone to top, for N. $\frac{1}{4}$ sec. cor. of sec. 5, with brass cap marked
	<u>$\frac{1}{4}$ S5</u> 1939
	from which

Survey of North Boundary of T. 36 N., R. 9 W.
(on the 9th Std. Parallel North)

8.

Chains

A juniper, 12 ins. diam., brs. S. 26 $\frac{1}{2}$ ° E., 41 lks.
dist., marked $\frac{1}{4}$ S5 BT.

A juniper, 24 ins. diam., brs. S. 36 $\frac{1}{2}$ ° W., 21 lks.
dist., marked $\frac{1}{4}$ S5 BT.

Continue over gently rolling prairie, thru dense timber
and scattering undergrowth.

57.27 Intersect the std. $\frac{1}{4}$ sec. cor. of sec. 32, an iron post,
1 in. in diam., projecting 10 ins. above ground, firmly
set, marked on brass cap and witnessed as described in
the official record.

Ascend gradually.

79.67 Intersect the subdivisional line bet. secs. 5 and 6,
surveyed N. 0° 03' W.
Closing cor. of said secs. established at this point
as hereinafter described.

Land, gently rolling.
Soil, rocky clay, 3rd and 4th rates.
Timber, pinyon and juniper.
Undergrowth, sagebrush and algerita. Poor grass.

From closing cor. of secs. 5 and 6,
West, on N. bdy. of sec. 6 (S. of sec. 32, T. 37 N., R. 9 W.)

Over gently rolling land, thru dense timber and scattering
undergrowth.

Across flat top of spur, sloping N.

0.10 Leave top of spur. Desc. slightly over W. slope

2.60 Descend 80 ft. over SW. slope to

17.60 Intersect the std. cor. of secs. 31 and 32, an iron post,
3 ins. in diam., projecting 18 ins. above ground, firmly
set in ground and mound of stone, marked on brass cap
and witnessed as described in the official record.

Thence

N. 89° 49' W., on true line, continuing measurement of
N. bdy. of sec. 6 (S. of sec. 31, T. 37 N., R. 9 W.)

Over rolling land, thru medium timber and scattering under-
growth.

Descend 23 ft. over SW. slope.

25.25 Draw, course NW. for about 5 chs., thence N. and
Thence over N. slope with slight change in elevation.

29.75 Draw, course N. 10° E. Asc. 42 ft. over E. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in
ground, for N. $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap
marked

$\frac{1}{4}$ S6

1939

from which

Survey of North Boundary of T. 36 N., R. 9 W.
 (on the 9th Std. Parallel North)

Chains	
	A juniper, 14 ins. diam., brs. S. $32\frac{1}{4}^{\circ}$ E., 90 lks. dist., marked $\frac{1}{4}$ S6 BT.
	A juniper, 6 ins. diam., brs. S. $66\frac{3}{4}^{\circ}$ W., 17 lks. dist., marked $\frac{1}{4}$ S6 BT.
	Ascend 25 ft. over E. slope.
43.75	Low spur, slopes NE. Desc. 10 ft. over W. slope.
47.15	Small draw, course NE. Asc. 17 ft. over E. slope.
51.65	Top of Hurricane Ledge, brs. N. and S. Enter mountainous land. Desc. 133 ft. over steep, rocky W. slope to
56.20	Intersect the witness cor. to std. $\frac{1}{4}$ sec. cor. of sec. 31, reestablished under this group, at 1.40 chs. S. $89^{\circ}49'E$. from the true cor. point, and is an iron post, 1 in. in diam., projecting 36 ins. above ground, set in a mound of stone, marked on brass cap and witnessed as described in the field notes of subdivisional survey of T. 37 N., R. 9 W.
	Descend 5 ft. over steep W. slope to
56.52	Top of precipitous W. slope, brs. N. and S. Discontinue chaining at this point. Measurement of the remainder of N. bdy. of sec. 6 by triangulation. Desc. about 830 ft. over precipitous W. slope across slide rock and cliffs.
57.60	True point for std. $\frac{1}{4}$ sec. cor. of sec. 31 is an inaccess- ible location where it cannot be monumented.
72.60	(Approx.) Foot of cliffs, brs. N. and S. Leave mountainous and enter rolling land Desc. about 35 ft. over W. slope to
77.77	Intersect the closing cor. of Ts. 36 N., Rs. 9 and 10 W., an iron post, 3 ins. in diam., projecting 28 ins. above ground, firmly set in ground and mound of stone, and witnessed by a mound of stone S. of cor. No bearing trees.
	Land, rolling, broken and mountainous. Soil, rocky, 4th rate. Timber, juniper and pinyon. Undergrowth, sagebrush. Poor grass.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

10

Chains	<p>Commence the survey of the subdivisional lines of T. 36 N., R. 9 W. at the cor. of secs. 1, 2, 35 and 36; on the S. bdy. of the Tp., an iron post, 2 ins. diam., projecting 12 ins. above ground, firmly set, marked on brass cap and witnessed as described in the official record.</p> <p>Thence</p> <p>N. 0° 01' W., bet. secs. 35 and 36.</p> <p>Over rolling and mountainous land, thru medium timber and undergrowth.</p> <p>Desc. slightly over NE. slope.</p> <p>4.50 Drain, course N. 70° E. Asc. 106 ft. over SE. slope.</p> <p>20.00 Top of ridge, brs. N. 70° E. and S. 70° W. Desc. 185 ft. over NE. slope to</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in ground, for 4 sec. cor., with brass cap marked</p> <p style="text-align: center;">S35 S36</p> <p style="text-align: center;">1939</p> <p style="text-align: right;">from which</p> <p>A juniper, 5 ins. diam., brs. S. 85½° E., 110 lks. dist., marked ¼ S36 BT.</p> <p>A juniper, 10 ins. diam., brs. S. 76½° W., 48 lks. dist., marked ¼ S35 BT.</p> <p>Descend 35 ft. over NE. slope.</p> <p>53.00 Draw, course NE. Asc. 25 ft. over SE. slope.</p> <p>59.00 Top of spur, slopes NE. Dest. 85 ft. over NW. slope.</p> <p>72.90 Gulch, course NE. Asc. 45 ft. over SE. slope to</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked</p> <p style="text-align: center;">T36N R9W</p> <p style="text-align: center;">S26 S25</p> <p style="text-align: center;">S35 S36</p> <p style="text-align: center;">1939</p> <p style="text-align: right;">from which</p> <p>A juniper, 16 ins. diam., brs. N. 85° E., 49 lks. dist., marked T36N R9W S25 BT.</p> <p>A juniper, 12 ins. diam., brs. S. 28½° E., 170 lks. dist., marked T36N R9W S36 BT.</p> <p>A pinyon, 8 ins. diam., brs. S. 29° W., 107 lks. dist., marked T36N R9W S35 BT.</p> <p>A juniper, 3 ins. diam., brs. N. 33° W., 27 lks. dist., marked BT only.</p> <p>Land, rolling and mountainous. Soil, gravelly and rocky clay; 3rd and 4th rates. Timber, juniper and pinyon. Undergrowth, sagebrush, spanish dagger & cacti. Fair grass.</p>
--------	--

Survey: Subdivisional lines: T. 36 N., R. 9 W.

11.

Chains	
	S. 89° 52' E., on a random line, bet. secs. 25 and 36.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect E. bdy. of Tp. 4 lks. N. of the cor. of secs. 25, 30, 31, and 36, which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	From cor.,
	N. 89° 50' W., on true line, bet. secs. 25 and 36.
	Over rolling land, thru moderate timber and undergrowth.
	Asc. gradually over SE. slope.
10.00	Top of low ridge, brs. NE. and SW. Desc. gradually over NW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \text{ S25} \\ \hline \frac{1}{4} \text{ S36} \\ 1939 \end{array}$
	from which
	A juniper, 16 ins. diam., brs. S. 50 $\frac{1}{4}$ ° E., 220 lks. dist., mkd. $\frac{1}{4}$ S36 BT.
	A juniper, 5 ins. diam., brs. N. 30 $\frac{3}{4}$ ° W., 153 lks. dist., mkd. $\frac{1}{4}$ S25 BT.
	Desc. 40 ft. over NW. slope.
68.80	Dim road, brs. N. 20° E. and S. 20° W.
72.90	Gulch, course NE. Asc. 80 ft. over E. slope to
78.10	Slope changes to SE. Asc. slightly.
80.00	The cor. of secs. 25, 26, 35, and 36.
	Land, rolling.
	Soil, gravelly and rocky, 3rd and 4th rates.
	Timber, juniper and pinyon.
	Undergrowth, sage, Spanish dagger, and cacti. Fair grass.
	N. 0° 01' W., bet. secs. 25 and 26.
	Over rolling land, thru moderate timber and dense undergrowth.
	Asc. slightly over SE. slope to
1.00	Top of flat spur, slopes E. Desc. 52 ft. over NE. slope.
10.00	Drain, course E. Asc. 40 ft. over S. slope.
27.00	Top of flat spur, slopes E. Desc. 45 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to solid rock, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked.

Survey: Subdivisional Lines: T. 36 N., R. 9 W.

12.

Chains	
	$\frac{1}{4}$ S26 S25 1939 from which A juniper, 8 ins. diam., brs. N. $38\frac{1}{2}^{\circ}$ E., 37 lks. dist., mkd. $\frac{1}{4}$ S25 BT. A juniper, 14 ins. diam., brs. N. $81\frac{3}{4}^{\circ}$ W., 130 lks. dist., mkd. $\frac{1}{4}$ S26 BT. Continue over N. slope. Desc. 92 ft. 57.80 Wash, 15 lks. wide, 4 ft. deep, course N. 60° W. Asc. 65 ft. over SW. slope. 59.10 Dim road, brs. SE. and NW. 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 23, 24, 25, and 26, with brass cap marked T36N R9W S23 S24 S26 S25 1939 from which A pinyon, 14 ins. diam., brs. N. 83° E., 118 lks. dist., mkd. T36N R9W S24 BT. A pinyon, 12 ins. diam., brs. S. $33\frac{3}{4}^{\circ}$ E., 74 lks. dist., mkd. T36N R9W S25 BT. A pinyon, 10 ins. diam., brs. S. 31° W., 24 lks. dist., mkd. T36N R9W S26 BT. A pinyon, 22 ins. diam., brs. N. 64° W., 308 lks. dist., mkd. T36N R9W S23 BT. Land, rolling. Soil, gravelly and rocky clay, 3rd and 4th rates. Timber, juniper and pinyon. Undergrowth, sage, spanish dagger, and cacti. Fair grass.
40.00	S. $89^{\circ} 50'$ E., on a random line, bet. secs. 24 and 25. Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the official record. From cor., N. $89^{\circ} 50'$ W., on true line, bet. secs. 24 and 25. Over rolling land, thru moderate timber and undergrowth. Desc. slightly over NW. slope.
14.70	Draw, course NE. Asc. 20 ft. over a slight SE. slope.
15.70	Dim road, brs. NE. and SW.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

13.

Chains	
40.03	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S24 \\ \frac{1}{4} \\ \hline S25 \\ 1939 \end{array}$
	from which
	A pinyon, 10 ins. diam., brs. S. 18° W., 129 lks. dist., mkd. $\frac{1}{4}$ S25 BT.
	A juniper, 14 ins. diam., brs. N. 43 $\frac{1}{2}$ ° W., 38 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	Asc. SE. slope slightly to
41.00	Top of ridge, brs. NE. and SE. Beery Knoll, in same ridge, brs. NE., approx. 25 chs. dist. Desc. 10 ft. over gradual SW. slope.
47.30	Drain, course S. Asc. slightly over SE. slope.
61.00	Top of flat spur, slopes S. 20° W. Desc. 40 ft. over W. slope.
70.00	Gulch, course S. 20° W. Asc. 25 ft. over SE. slope.
74.00	Top of spur, slopes S. Desc. 20 ft. over SW. slope to
80.06	The cor. of secs. 23, 24, 25, and 26.
	Land, rolling.
	Soil, rocky, 4th rate.
	Timber, pinyon and juniper.
	Undergrowth, sage, Spanish dagger, and cacti. Fair grass.
	N. 0° 01' W., bet. secs. 23 and 24.
	Over rolling land, thru moderate timber and dense undergrowth.
	Asc. 126 ft. over SW. slope.
37.00	Top of spur, slopes S. 70° W. Along a W. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ S23 S24 \\ 1939 \end{array}$
	from which
	A juniper, 12 ins. diam., brs. N. 26 $\frac{1}{2}$ ° E., 213 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	A pinyon, 12 ins. diam., brs. N. 57 $\frac{1}{2}$ ° W., 68 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	Asc. 10 ft. over a gradual SW. slope.
50.50	Top of spur, slopes W. Desc. 118 ft. over NW. slope.
70.10	Gulch, course W. Asc. 88 ft. over SW. slope to

Survey: Subdivisional lines: T. 36 N., R. 9 W.

14.

Chains 80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, for the cor. of secs. 13, 14, 23, and 24, with brass cap marked</p> <p style="text-align: center;">T36N R9W S14 S13 S23 S24 1939</p> <p style="text-align: right;">from which</p> <p>A pinyon, 10 ins. diam., brs. N. 14° E., 242 lks. dist., mkd. T36N R9W S13 BT.</p> <p>A pinyon, 8 ins. diam., brs. S. 40$\frac{3}{4}$° E., 394 lks. dist., mkd. T36N R9W S24 BT.</p> <p>A juniper, 10 ins. diam., brs. S. 88$\frac{3}{4}$° W., 86 lks. dist., mkd. T36N R9W S23 BT.</p> <p>A juniper, 10 ins. diam., brs. N. 48$\frac{1}{2}$° W., 226 lks. dist., mkd. T36N R9W S14 BT.</p> <p>Land, rolling. Soil, rocky, 4th rate. Timber, pinyon and juniper. Undergrowth, sage, Spanish dagger, and cacti. Fair grass.</p>
40.00	<p>S. 89° 50' E., on a random line, bet. secs. 13 and 24.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>
79.98	<p>Intersect E. bdy. of Tp. 9 lks. S. of the cor. of secs. 13, 18, 19, and 24, which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.</p> <p>From cor.,</p> <p>N. 89° 54' W., on true line, bet. secs. 13 and 24.</p> <p>Over rolling land, thru moderate timber and dense undergrowth.</p> <p>Asc. 93 ft. over broken NE. slope.</p>
32.40	<p>Top of spur, slopes N. 30° E. Desc. 42 ft. over W. slope.</p>
36.00	<p>Draw, course NE. Asc. 40 ft. over SE. slope to</p>
39.99	<p>Set an iron post, 3 ft. long, 1 in. in diam., 25 ins. in the ground, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$ S13 S24 1939</p> <p style="text-align: right;">from which</p> <p>A juniper, 8 ins. diam., brs. S. 13$\frac{1}{4}$° W., 67 lks. dist., mkd. $\frac{1}{4}$ S24 BT.</p> <p>A juniper, 6 ins. diam., brs. N. 85$\frac{1}{2}$° W., 61 lks. dist., mkd. $\frac{1}{4}$ S13 BT.</p> <p>Continue over SE. slope. Asc. 105 ft.</p>

Survey: Subdivisional lines: T. 36 N.; R. 9 W.

BOOK 4260

15.

Chains	
52.00	Top of spur, slopes N. 10° E. Desc. slightly over NW. slope to
54.00	Slope changes to NE. Asc. 46 ft. over NE. slope.
60.80	Top of ridge, brs. N. and S. Desc. 69 ft. over W. slope.
71.50	Draw, near head, course N. 60° W. Asc. 10 ft. over NE. slope.
76.00	Top of spur, slopes N. 60° W. Desc. 15 ft. over SW. slope to
79.98	The cor. of secs. 13, 14, 23, and 24. Land, rolling. Soil, rocky, 4th rate. Timber, pinyon and juniper. Undergrowth, sage, spanish dagger, and cacti. Fair grass.
	N. $0^{\circ} 01'$ W., bet. secs. 13 and 14. Over rolling and heavy rolling land, thru scattering timber and dense undergrowth. Asc. slightly over SW. slope.
1.50	Top of spur, slopes N. 60° W. Desc. 50 ft. over NE. slope.
6.00	Draw, course N. 60° W. Asc. 50 ft. over SW. slope.
10.70	Top of spur, slopes N. 80° W. Desc. 252 ft. over NW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S14 S13 1939 from which A juniper, 20 ins. diam., brs. N. $35\frac{1}{2}^{\circ}$ E., 57 lks. dist., mkd. $\frac{1}{4}$ S13 BT. A juniper, 5 ins. diam., brs. S. $64\frac{1}{2}^{\circ}$ W., 40 lks. dist., mkd. $\frac{1}{4}$ S14 BT. Continue over NW. slope. Desc. 125 ft.
45.70	Gulch, course NW. Asc. 101 ft. over a rocky SW. slope.
58.50	Top of short spur, slopes W. Desc. 132 ft. over NW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, and in a small mound of stone to top, for the cor. of secs. 11, 12, 13, and 14, with brass cap mkd. T36N R9W S11 S12 S14 S13 1939 from which

16. Survey: Subdivisional Lines: T. 36 N., R. 9 W.

Chains	
	<p>A pinyon, 3 ins. diam., brs. N. 38° E., 105 lks. dist., mkd. BT only.</p> <p>A juniper, 12 ins. diam., brs. S. 68$\frac{3}{4}$° E., 19 lks. dist., mkd. T36N R9W S13 BT.</p> <p>A pinyon, 6 ins. diam., brs. S. 36$\frac{1}{2}$° W., 62 lks. dist., mkd. T36N R9W S14 BT.</p> <p>A pinyon, 10 ins. diam., brs. N. 52° W., 230 lks. dist., mkd. T36N R9W S11 BT.</p> <p>Land, rolling and heavy rolling. Soil, rocky, 4th rate. Timber, pinyon and juniper. Undergrowth, sage, Spanish dagger, and cacti. Fair grass.</p>
	<p>S. 89° 54' E., on a random line, bet. secs. 12 and 13.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect the E. bdy. of Tp. 9 lks. N. of the cor. of secs. 7, 12, 13, and 18, which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	From cor.,
	N. 89° 50' W., on true line, bet. secs. 12 and 13.
	Over rolling land, thru scattering timber and undergrowth.
	Asc. 175 ft. over NE. slope.
35.00	Top of flat ridge, brs. N. and S. Desc. 10 ft. over NW. slope to
39.97	Set an iron post, 3 ft. long, 1 in. in diam., 25 ins. in the ground, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S12}{\frac{1}{4} S13}$ 1939
	from which
	A pinyon, 5 ins. diam., brs. S. 1° W., 267 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
	A pinyon, 10 ins. diam., brs. N. 1 $\frac{1}{4}$ ° W., 89 lks. dist., mkd. $\frac{1}{4}$ S12 BT.
	Continue over NW. slope. Desc. 15 ft.
43.70	Head of gulch, course NW. Along a N. slope to
49.10	Top of short spur, slopes NW. Desc. 45 ft. over W. slope.
52.40	Gulch, course N. Asc. 40 ft. over E. slope.
56.40	Top of short spur, slopes N. Desc. 47 ft. over broken NW. slope.
66.60	Top of steep descent, brs. N. and S. Desc. 86 ft. over W. slope.
73.20	Ravine, course NW. Asc. 60 ft. over NE. slope.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

ECCCK 4260

17.

Chains

79.00 Top of short spur, slopes N. 20° W. Desc. 12 ft. over NW. slope to

79.94 The cor. of secs. 11, 12, 13, and 14.

Land, rolling.

Soil, rocky, 4th rate.

Timber, pinyon and juniper.

Undergrowth, sage, Spanish dagger, and cacti. Fair grass.

N. 0° 01' W., bet. secs. 11 and 12.

Over rolling and mountainous land, thru scattering timber and undergrowth.

Desc. 100 ft. over NW. slope.

3.90 Base of steep descent. Enter valley, brs. NE. and SW.

9.70 Lange's Run, wash, 40 lks. wide, 16 ft. deep, course N. 35° E.

10.90 Ungraded road, brs. N. 35° E. and S. 35° W. Leave valley, brs. NE. and SW. Asc. 172 ft. over SE. slope.

30.00 Top of spur, slopes E. Desc. 90 ft. over NE. slope.

31.00 Enter moderate timber, brs. E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap marked

1/4

S11|S12

1939

from which

A juniper, 10 ins. diam., brs. S. 60 3/4° E., 95 lks. dist., mkd. 1/4 S12 BT.

A pinyon, 10 ins. diam., brs. N. 26° W., 106 lks. dist., mkd. 1/4 S11 BT.

Continue over NE. slope. Desc. 25 ft.

46.60 Gulch, course SE. approx. 4 chs., thence E. Asc. 57 ft. over S. slope.

50.50 Top of spur, slopes SE. Along E. slope.

54.20 Top of spur, slopes NE. Desc. 65 ft. over N. slope.

60.50 Gulch, course E. Asc. 64 ft. over SE. slope.

68.00 Short spur, slopes SW. Asc. 23 ft. over SW. slope.

73.70 Top of spur, slopes SE. Desc. 25 ft. over NE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 1, 2, 11, and 12, with brass cap marked

T36N R9W

S2|S1

S11|S12

1939

from which

Survey: Subdivisional Lines: T. 36 N., R. 9 W.

18.

Chains	
	A juniper, 14 ins. diam., brs. N. 13° E., 513 lks. dist., mkd. T36N R9W S1 BT.
	A juniper, 12 ins. diam., brs. S. 41° E., 146 lks. dist., mkd. T36N R9W S12 BT.
	A juniper, 14 ins. diam., brs. S. 48° W., 205 lks. dist., mkd. T36N R9W S11 BT.
	A juniper, 18 ins. diam., brs. N. 89½° W., 284 lks. dist., mkd. T36N R9W S2 BT.
	Land, rolling and mountainous. Soil, gravelly and rocky clay, 3rd and 4th rates. Timber, juniper and pinyon. Undergrowth, sage, Spanish dagger, and cacti. Fair grass.
	S. 89° 50' E., on a random line, bet. secs. 1 and 12.
40.00	Set temp. ¼ sec. cor.
79.88	Intersect the E. bdy. of Tp. 2 lks. S. of the cor. of secs. 1, 6, 7, and 12, which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	From cor.,
	N. 89° 51' W., on true line, bet. secs. 1 and 12.
	Over rolling land, thru moderate timber and dense undergrowth.
	Desc. 10 ft. over SW. slope.
1.30	Ungraded road, brs. S. 10° E. and N. 10° W.
1.60	Gulch, course SE. Asc. 30 ft. over E. slope.
4.10	Earl Pressley's cabin brs. South, 22.10 chs. dist.
8.40	Top of spur, slopes N. Desc. 15 ft. over NW. slope.
12.80	Gulch, course NE. Asc. 82 ft. over SE. slope.
12.90	Dim road, brs. NE. and SW.
18.90	Top of spur, slopes NE. Along a N. slope.
21.90	Top of same spur, slopes SE. Desc. 52 ft. over SW. slope.
28.50	Earl Pressley's proposed dam site on Lange's Run, brs. South, 38.40 chs. dist.
37.40	Bend in ungraded road, brs. S. 70° E. and S. 88° W. Gulch, course SE. Asc. slightly over SE. slope to
39.94	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked
	$\frac{S1}{\frac{1}{4} S12}$ 1939
	from which
	A juniper, 16 ins. diam., brs. N. 52° E., 310 lks. dist., mkd. ¼ S1 BT.

Survey: Subdivisional lines: T. 36 N., R. 9 W. BOOK 4260
19.

Chains

A pinyon, 6 ins. diam., brs. S. $5\frac{1}{2}^{\circ}$ E., 510 lks. dist.,
mkd. $\frac{1}{4}$ S12 BT.

Continue gradual ascent over SE. slope.

45.70 Dim road, brs. NW. and SE. approx. 1 ch. to juncture with
main road from S. to E.

49.90 Gulch, course S. 70° E. Asc. 40 ft. over NE. slope to

79.88 The cor. of secs. 1, 2, 11, and 12.

Land, rolling.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, Spanish dagger, and cacti. Fair grass.

N. $0^{\circ} 01'$ W., bet. secs. 1 and 2.

Over rolling land, thru moderate timber and undergrowth.

Desc. slightly over NE. slope, to

2.20 Gulch, course E. Asc. 45 ft. over S. slope, to

11.00 Top of spur, slopes S. 70° E. Desc. 25 ft. over N. slope.

15.30 Gulch, course S. 70° E. Asc. 30 ft. over S. slope.

25.20 Top of flat spur, slopes E. Desc. slightly over NE. slope.

30.00 Slope changes to SE. Asc. slightly.

34.80 Dim road, brs. S. 70° E. and N. 70° W. Top of spur,
slopes E. Desc. 10 ft. over N. slope, to

38.00 Draw, near head, course N. 70° E. Asc. 10 ft. over S.
slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in
the ground to solid rock, and in a mound of stone to
top, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$

S2|S1

1939

from which

A pinyon, 8 ins. diam., brs. N. $74\frac{1}{4}^{\circ}$ E., 160 lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.

A pinyon, 8 ins. diam., brs. N. $3\frac{3}{4}^{\circ}$ W., 113 lks. dist.,
mkd. $\frac{1}{4}$ S2 BT.

Continue ascent over S. slope. Asc. 14 ft.

44.20 Top of ridge, brs. NE. and SW. Desc. 90 ft. over NW. slope.

66.50 Base of descent. Enter valley and scat. timber, brs. NE. and SW.

76.20 Wide draw, course NE. Asc. slightly over SE. slope.

77.20 Hurricane-Mt. Trumbull ungraded road, brs. N. 70° E. and S. 70° W.

79.85 Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in

BOOK 4200

Survey: Subdivisional lines: T. 36 N., R. 9 W.

20.

Chains

the ground to bedrock, and in a mound of stone to top, for the closing cor. of secs. 1 and 2, with brass cap marked

T37N R9W

S36

S2|S1

CC

T36N R9W

1939

No bearing trees available.

The standard cor. of secs. 35 and 36, T. 37 N., R. 9 W., brs. West, 17.21 chs. dist., and the standard $\frac{1}{4}$ sec. cor. of sec. 36 brs. East, 22.79 chs. dist., both set, marked, and witnessed as described in the official record.

Land, rolling.

Soil, gravelly and rocky clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, spanish dagger, and cacti. Fair grass.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the official record.

Thence,

N. $0^{\circ} 01'$ W., bet. secs. 34 and 35.

Over rolling land, thru moderate timber and scattering undergrowth.

Asc. 5 ft. over SW. slope.

5.00 Top of spur, slopes NW. Desc. 42 ft. over NE. slope.

17.20 Wide, flat draw, course NW. Asc. 32 ft. over SW. slope to

40.00 Top of flat spur, slopes W.
Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked

 $\frac{1}{4}$

S34|S35

1939

from which

A pinyon, 16 ins. diam., brs. N. $11\frac{3}{4}^{\circ}$ E., 126 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A pinyon, 10 ins. diam., brs. N. $18\frac{3}{4}^{\circ}$ W., 183 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

Desc. 50 ft. over N. slope.

57.40 Draw, 1 ch. wide, course N. 60° W. Asc. 73 ft. over rolling SW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, and in a small mound of stone to top, for the cor. of secs. 26, 27, 34, and 35, with brass cap marked

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

T36N R9W	
S27	S26
<hr/>	
S34	S35
1939	

from which

- A pinyon, 12 ins. diam., brs. N. $21\frac{1}{2}^\circ$ E., 174 lks. dist., mkd. T36N R9W S26 BT.
- A pinyon, 12 ins. diam., brs. S. $42\frac{1}{2}^\circ$ E., 107 lks. dist., mkd. T36N R9W S35 BT.
- A pinyon, 12 ins. diam., brs. S. 63° W., 61 lks. dist., mkd. T36N R9W S34 BT.
- A pinyon, 8 ins. diam., brs. N. 37° W., 129 lks. dist., mkd. T36N R9W S27 BT.

Land, rolling.
 Soil, rocky clay, 3rd and 4th rates.
 Timber, pinyon and juniper.
 Undergrowth, sage and cacti. Fair grass.

- 40.00 S. $89^\circ 52'$ E., on a random line, bet. secs. 26 and 35. Set temp. $\frac{1}{4}$ sec. cor.
- 79.84 Intersect N. and S. line 13 lks. S. of the cor. of secs. 25, 26, 35, and 36.
 Thence,
 N. $89^\circ 58'$ W., on true line, bet. secs. 26 and 35.
 Over rolling land, thru moderate timber and scattering undergrowth.
 Asc. 18 ft. over SE. slope.
- 17.30 Top of flat ridge, brs. N. and S. Desc. 87 ft. over SW. slope.
- 37.60 Draw, 1 ch. wide, course NW. Asc. 3 ft. over NE. slope to
- 39.92 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked

S26	
$\frac{1}{4}$	S35
<hr/>	
1939	

from which

- A juniper, 10 ins. diam., brs. N. $43\frac{1}{4}^\circ$ E., 72 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
- A juniper, 36 ins. diam., brs. S. $58\frac{3}{4}^\circ$ W., 77 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

Desc. 16 ft. over NW. slope.

- 44.80 Same draw, course SW. Asc. 6 ft. over SE. slope.
- 49.80 Top of low spur, slopes SW. Desc. 42 ft. over W. slope.
- 63.80 Head of draw, course S. 30° W. Asc. 45 ft. over SE. slope.

22. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
74.30	Top of spur, slopes NW., from N. 70° E. Desc. 37 ft. over SW. slope to
79.84	The cor. of secs. 26, 27, 34, and 35. Land, rolling. Soil, rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.
	N. 0° 01' W.; bet. secs. 26 and 27. Over rolling land, thru moderate timber and scattering undergrowth. Asc. 12 ft. over SW. slope to
2.50	Top of spur, slopes W. Desc. N. slope 5 ft. to
4.00	Head of draw, course NW. Asc. 11 ft. over SW. slope to
10.00	Top of spur, slopes NW. Desc. N. slope 47 ft. to
14.00	Draw, 50 lks. wide, course N. 70° W. Asc. 38 ft. over SW. slope to
21.50	Top of low spur, slopes W. Desc. 44 ft. over NW. slope to
27.00	Draw, 50 lks. wide, heads approx. 15 chs. E., course W. Asc. 22 ft. over SW. slope to
29.70	Top of short spur, slopes W. Desc. 11 ft. over NW. slope.
31.60	Drain, 5 lks. wide, heads approx. 7 chs. N. 60° E., course S. 60° W. Asc. 62 ft. over SW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S27 S26 1939 from which A pinyon, 12 ins. diam., brs. N. 44° E., 69 lks. dist., mkd. $\frac{1}{4}$ S26 BT. A juniper, 14 ins. diam., brs. S. 86 $\frac{1}{2}$ ° W., 98 lks. dist., mkd. $\frac{1}{4}$ S27 BT. Continue over SW. slope. Asc. 5 ft.
40.60	Top of ridge, brs. E. and W. Desc. 73 ft. over NW. slope to
48.80	Head of draw, course NE. Asc. 21 ft. over SE. slope to
55.50	Top of spur, slopes NE. Desc. 120 ft. over rolling NW. slope.
67.00	Leave timber, brs. NE. and W.
80.00	Wide, shallow draw, course N. 30° W., from S. 20° W. Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 22, 23, 26, and 27, with brass cap marked

Survey: Subdivisional lines: T. 36 N., R. 9 W.

23.

Chains

T36N R9W
 S22 | S23
 S27 | S26
 1939

raise a mound
 of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.
 Soil, rocky clay, 3rd and 4th rates.
 Timber, pinyon and juniper.
 Undergrowth, sage and cacti. Fair to good grass.

S. 89° 58' E., on a random line, bet. secs. 23 and 26.

40.00 Set temp. ¼ sec. cor.

79.86 Intersect N. and S. line 2 lks. N. of the cor. of secs. 23, 24, 25, and 26.

Thence,

N. 89° 57' W., on true line, bet. secs. 23 and 26.

Over rolling land, thru moderate timber and scattering undergrowth.

Desc. 146 ft. over SW. slope.

12.60 Dim road, brs. N. and S.

25.00 Leave timber, brs. N. and S. 70° W.

29.90 Draw, 50 lks. wide, course N. 60° W. Asc. 5 ft. over slight NE. slope to

39.93 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked

S23
 ¼ S26
 1939

from which

A juniper, 12 ins. diam., brs. S. 68¼° W., 408 lks. dist., mkd. ¼ S26 BT.

No other tree available.

raise a mound
 of stone, 2 ft. base, 1½ ft. high, N. of cor.

Asc. 22 ft. over NE. slope.

46.30 Top of spur, slopes N. Desc. 44 ft. over W. slope.

55.60 Junction of draws, from S. 20° E. and S. 20° W., course N. Asc. 24 ft. over E. slope.

65.40 Top of spur, slopes N. Desc. W. slope 18 ft.

67.60 Draw, heads approx. 5 chs. S., course N. Asc. 23 ft. over NE. slope.

72.60 Top of spur, slopes N. 30° W. Desc. 37 ft. over W. slope.

79.86 The cor. of secs. 22, 23, 26, and 27.

Land, rolling.

Survey:.. Subdivisional lines: T. 36 N., R. 9 W.

24.

Chains	Soil, rocky clay, 3rd and 4th rates. Timber, pinyon and juniper (E. 25 chs.). Undergrowth, sage and cliff rose. Fair grass.
	N. 0° 01' W., bet. secs. 22 and 23. Over rolling land, thru low scattering undergrowth. Asc. 52 ft. over SW. slope.
10.10	Fern-Esplin earth tank, brs. N. 50° W.
10.50	Top of spur, slopes W., approx. 5 chs. Desc. 77 ft. over NW. slope.
15.40	Dim road, brs. E. and W.
16.00	Draw, 50 lks. wide, course W. Asc. 70 ft. over SW. slope.
23.70	Top of rocky spur, slopes S. 60° W. Desc. 91 ft. over NW. slope.
28.48	Lange's Run, cut bank wash, 40 lks. wide, 6 ft. deep, course N. 51° E. Asc. 112 ft. over SE. slope.
35.00	Enter moderate timber, brs. NE. and SW.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S22 S23 1939 from which A pinyon, 24 ins. diam., brs. S. 47° E., 80 lks. dist., mkd. $\frac{1}{4}$ S23 BT. A pinyon, 8 ins. diam., brs. N. 89 $\frac{1}{2}$ ° W., 49 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	Continue over SE. slope. Asc. 5 ft.
42.40	Top of spur, slopes N. 60° E. Desc. N. slope 115 ft.
51.80	Canyon wash, 10 lks. wide, course E. Asc. SE. slope 102 ft.
58.80	Top of spur, slopes E. Desc. 70 ft. over NE. slope.
62.40	Ravine, course S. 50° E. Asc. 128 ft. over SE. slope.
74.20	Top of spur, slopes N. 60° E. Desc. NE. slope 34 ft.
77.00	Head of ravine, course NE. Asc. 4 ft. along E. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for the cor. of secs. 14, 15, 22, and 23, with brass cap marked T36N R9W S15 S14 S22 S23 1939 from which

Survey: Subdivisional lines: T. 36 N., R. 9 W.

25.

Chains

- A pinyon, 10 ins. diam., brs. N. 19° E., 95 lks.
dist., mkd. T36N R9W S14 BT.
- A pinyon, 16 ins. diam., brs. S. 49° E., 71 lks.
dist., mkd. T36N R9W S23 BT.
- A pinyon, 10 ins. diam., brs. S. 51½° W., 107 lks.
dist., mkd. T36N R9W S22 BT.
- A pinyon, 10 ins. diam., brs. N. 31° W., 165 lks.
dist., mkd. T36N R9W S15 BT.

Land, rolling.

Soil, rocky clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage and cacti. Fair grass.

S. 89° 57' E., on a random line, bet. secs. 14 and 23.

40.00 Set temp. ¼ sec. cor.

79.88 Intersect N. and S. line 7 lks. S. of the cor. of secs.
13, 14, 23, and 24.

Thence,

West, on true line, bet. secs. 14 and 23.

Over rolling and heavy rolling land, thru moderate timber
and scattering undergrowth.

Desc. 234 ft. over SW. slope.

30.40 Draw, 20 lks. wide, course N. 20° W. Asc. 17 ft. over
NE. slope.

36.20 Top of spur, slopes N. Desc. 17 ft. over NW. slope to

39.94 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in
the ground, for the ¼ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S14}{S23} \\ 1939$$

from which

A juniper, 16 ins. diam., brs. N. 87¾° E., 20 lks.
dist., mkd. ¼ S14 BT.A juniper, 16 ins. diam., brs. S. 42½° W., 49 lks.
dist., mkd. ¼ S23 BT.

Continue over NW. slope. Desc. 172 ft.

48.90 Leave timber, brs. NE. and SW.

50.50 Lange's Run, cut bank clay wash, 25 lks. wide, 7 ft. deep,
course N. 38° E. Asc. 186 ft. over SE. slope.

65.90 Enter moderate timber, brs. NE. and SW.

69.20 Top of spur, slopes N. 30° E. Desc. NW. slope 43 ft. to

77.70 Ravine, course NE. Asc. 33 ft. over E. slope to

79.88 The cor. of secs. 14, 15, 22, and 23.

26.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	Land, rolling and heavy rolling. Soil, rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.
	N. 0° 01' W., bet. secs. 14 and 15.
	Over rolling and heavy rolling land, thru moderate timber and scattering undergrowth.
	Desc. 14 ft. along E. slope.
3.00	Top of spur, slopes NE. Desc. 92 ft. over N. slope.
10.70	Canyon wash, 15 lks. wide, course N. 60° E. Asc. 138 ft. over SE. slope.
17.00	Top of spur, slopes N. 70° E. Desc. 43 ft. over N. slope.
19.25	Draw, 15 lks. wide, heads approx. 6 chs. S. 60° W., course N. 60° E. Asc. 28 ft. over SE. slope.
22.50	Top of spur, slopes NE. Desc. 42 ft. over NW. slope.
25.10	Draw, 5 lks. wide, course N. 70° E. Asc. 58 ft. over SE. slope.
32.00	Top of spur, slopes N. 60° E. Desc. 48 ft. over NW. slope.
38.15	Draw, course NE. Asc. 25 ft. over SE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S15 S14
	1939
	from which
	A pinyon, 8 ins. diam., brs. S. 40 $\frac{1}{2}$ ° E., 92 lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	A juniper, 36 ins. diam., brs. N. 30° W., 118 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	Asc. 10 ft. over SE. slope.
44.70	Top of short spur, slopes E., approx. 5 chs. Desc. 37 ft. over NE. slope.
47.15	Draw, 5 lks. wide, course E. Asc. 46 ft. over S. slope.
58.00	Top of spur, slopes E. Desc. NE. slope 160 ft.
70.00	Leave timber, brs. E. and W.
73.55	Ungraded road, brs. S. 70° E. and SW.
75.70	Wide draw, from SW., course S. 70° E. Small draw, from NW. Asc. 20 ft. over gradual S. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 10, 11, 14, and 15, with brass cap marked

Survey: Subdivisional lines: T. 36 N., R. 9 W. BOOK 4280
27.

Chains

T36N R9W

S10 | S11

S15 | S14

1939

raise a mound, of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, rolling and heavy rolling.
Soil, rocky clay and gypsum, 3rd and 4th rates.
Timber, pinyon and juniper.
Undergrowth, sage and cacti. Fair grass.

East, on a random line, bet. secs. 11 and 14.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.86 Intersect N. and S. line 5 lks. S. of the cor. of secs. 11, 12, 13, and 14.

Thence,

S. $89^{\circ} 58'$ W., on true line, bet. secs. 11 and 14.

Over rolling land, thru scattering timber and undergrowth. Desc. 94 ft. over NW. slope.

4.50 Enter bottom land and leave timber, brs. NE. and SW.

13.00 Lange's Run, cut bank wash, 40 lks. wide, 14 ft. deep, course N. 59° E.

14.40 Ungraded road, brs. N. 60° E. and S. 60° W. Leave bottom land, brs. NE. and SW. Asc. 121 ft. over SE. slope.

27.90 Top of spur, slopes S. approx. 5 chs. Desc. 81 ft. over SW. slope.

35.90 Draw, course S. approx. 5 chs. to main draw, course SE. Asc. 5 ft. over SE. slope to

39.93 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

S11

 $\frac{1}{4}$ S14

1939

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Continue over SE. slope. Asc. 10 ft.

44.40 Point of spur, slopes S. Desc. 18 ft. over SW. slope.

47.90 Draw, course S. 20° E. approx. 3 chs. to main draw, from SW. to SE. Asc. 153 ft. over SE. slope.

61.40 Top of spur, slopes S. Desc. 30 ft. over W. slope.

64.30 Ravine, course S. Asc. 35 ft. over SE. slope.

68.40 Top of spur, slopes S. Desc. 113 ft. over SW. slope.

78.00 Slope changes to gradual S. slope.

79.86 The cor. of secs. 10, 11, 14, and 15.

Land, rolling.
Soil, rocky clay and gypsum, 3rd and 4th rates.
No timber. Undergrowth, sage and tumble weed. Fair grass.

28. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
	N. 0° 01' W., bet. secs. 10 and 11. Over mountainous land, thru low scattering undergrowth. Asc. 174 ft. over S. slope.
8.20	Top of rim, brs. SE. and N. 10° W. Over nearly level table land.
8.50	Enter moderate timber, brs. E. and W.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S10 S11 1939 from which A pinyon, 6 ins. diam., brs. N. 75 $\frac{1}{4}$ ° E., 88 lks. dist., mkd. $\frac{1}{4}$ S11 BT. A juniper, 14 ins. diam., brs. S. 52 $\frac{1}{2}$ ° W., 143 lks. dist., mkd. $\frac{1}{4}$ S10 BT. Continue over nearly level land. Asc. 20 ft. over a gradual S. slope.
53.00	Top of low ridge, brs. E. and W. Desc. 41 ft. over N. slope.
76.60	Wash, 5 lks. wide, course E. Asc. 5 ft. over SE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 2, 3, 10, and 11, with brass cap marked T36N R9W S3 S2 S10 S11 1939 from which A juniper, 22 ins. diam., brs. N. 14 $\frac{3}{4}$ ° E., 87 lks. dist., mkd. T36N R9W S2 BT. A pinyon, 16 ins. diam., brs. S. 39° E., 166 lks. dist., mkd. T36N R9W S11 BT. A pinyon, 18 ins. diam., brs. S. 11 $\frac{1}{4}$ ° W., 211 lks. dist., mkd. T36N R9W S10 BT. A pinyon, 8 ins. diam., brs. N. 54 $\frac{1}{2}$ ° W., 21 lks. dist., mkd. T36N R9W S3 BT. Land, mountainous and nearly level. Soil, rocky clay, 3rd and 4th rates. Timber, juniper and pinyon. Undergrowth, sage, algerita, and cliff rose. Fair grass.
40.00	N. 89° 58' E., on a random line, bet. secs. 2 and 11. Set temp. $\frac{1}{4}$ sec. cor.
79.84	Intersect N. and S. line 5 lks. S. of the cor. of secs. 1, 2, 11, and 12.

Survey: Subdivisional lines; T. 36 N., R. 9 W.

29.

Chains

Thence,

S. 89° 56' W., on true line, bet. secs. 2 and 11.

Over rolling land, thru moderate timber and scattering undergrowth.

Asc. 52 ft. over NE. slope.

12.60 Top of low spur, slopes SE. Desc. 58 ft. over SW. slope.

22.70 Slope changes to S. Desc. 29 ft.

29.85 Wash, 6 lks. wide, course S. 75° E. Asc. 34 ft. over NE. slope.

34.80 Slope changes to E. Asc. 12 ft. to

39.92 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S2}{S11}$$

from which

from which

A juniper, 14 ins. diam., brs. N. 78 $\frac{1}{2}$ ° E., 104 lks. dist., mkd. $\frac{1}{4}$ S2 BT.A juniper, 8 ins. diam., brs. S. 55 $\frac{1}{4}$ ° W., 65 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

Continue over E. slope. Asc. 58 ft.

47.80 Top of low, flat ridge, brs. NE. and S. Asc. 5 ft. over nearly level top of ridge.

59.80 Leave top of ridge, brs. NE. and S. Desc. 21 ft. over NW. slope.

63.45 Wash, 10 lks. wide, course NE. Asc. 45 ft. over SE. slope to

79.84 The cor. of secs. 2, 3, 10, and 11.

Land, rolling.

Soil, rocky clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, algerita, and cliff rose. Fair grass.

N. 0° 01' W., bet. secs. 2 and 3.

Over rolling land, thru moderate timber and scattering undergrowth.

Asc. 50 ft. over a gradual SE. slope.

8.50 Top of low spur, slopes E. Desc. 59 ft. over N. slope.

18.80 Wash, 5 lks. wide, course NE. Asc. 6 ft. over SE. slope.

23.80 Point of spur, slopes NE. Desc. 38 ft. over N. slope.

30.10 Wash, 5 lks. wide, course E. Asc. 49 ft. over S. slope.

39.10 Top of spur, slopes E. Desc. 5 ft. over N. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in

BOOK 4260

30. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

the ground to bedrock, and in a mound of stone to top,
for the $\frac{1}{4}$ sec. cor., with brass cap marked

 $\frac{1}{4}$

S3|S2

1939

from which

A juniper, 14 ins. diam., brs. N. $87\frac{1}{4}^{\circ}$ E., 93 lks.
dist., mkd. $\frac{1}{4}$ S2 BT.

A juniper, 16 ins. diam., brs. N. $3\frac{3}{4}^{\circ}$ W., 46 lks.
dist., mkd. $\frac{1}{4}$ S3 BT.

Continue over N. slope. Desc. 82 ft.

50.00 Leave moderate and enter scattering timber, brs. E. and W.

60.10 Wash, 10 lks. wide, course E. Asc. 67 ft. over S. slope.

75.70 Top of ridge, brs. E. and W. Desc. 15 ft. over N. slope.

79.40 Hurricane-Mt. Trumbull ungraded road, brs. S. 66° E. and N. 81° W.

79.95 Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for the closing cor. of secs. 2 and 3, with
brass cap marked.

T37N R9W

S35

S3|S2

T36N R9W

CC

1939

from which

A juniper, 6 ins. diam., brs. S. $32\frac{3}{4}^{\circ}$ E., 349 lks.
dist., mkd. T36N R9W S2 CC BT.

A juniper, 8 ins. diam., brs. S. 17° W., 178 lks.
dist., mkd. T36N R9W S3 CC BT.

The standard cor. of secs. 34 and 35, T. 37 N., R. 9 W.,
brs. West, 17.40 chs. dist., and the standard $\frac{1}{4}$ sec.
cor. of sec. 35 brs. East, 22.60 chs. dist., both set,
marked, and witnessed as described in the official
record.

Land, rolling.

Soil, rocky clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, algerita, and cliff rose. Fair grass.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy.
of the Tp., which is an iron post, 2 ins. in diam., set,
marked, and witnessed as described in the official
record.

Thence,

N. $0^{\circ} 02'$ W., bet. secs. 33 and 34.

Over rolling land, thru dense timber and undergrowth.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

31.

Chains

Desc. slightly along a rolling gradual E. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked

 $\frac{1}{4}$

S33|S34

1939

from which

A juniper, 7 ins. diam., brs. East, 20 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

A juniper, 6 ins. diam., brs. N. $39\frac{1}{4}^{\circ}$ W., 137 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

Continue along gradual E. slope.

40.50 Top of low spur, slopes N. 65° E. Desc. 56 ft. over N. slope.

47.20 Dim road, brs. S. 60° E. and N. 60° W.

52.50 Dry wash, 12 lks. wide, in draw, course E. Asc. 48 ft. over S. slope to

57.00 Top of steep ascent, brs. E. and W. Along a gradual E. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone to top, for the cor. of secs. 27, 28, 33, and 34, with brass cap marked

T36N R9W

S28|S27

S33|S34

1939

from which

A juniper, 5 ins. diam., brs. N. $74\frac{1}{2}^{\circ}$ E., 59 lks. dist., mkd. T36N R9W S27 BT.

A juniper, 5 ins. diam., brs. S. 40° E., 50 lks. dist., mkd. T36N R9W S34 BT.

A juniper, 8 ins. diam., brs. S. 5° W., 107 lks. dist., mkd. T36N R9W S33 BT.

A juniper, 9 ins. diam., brs. N. $73\frac{3}{4}^{\circ}$ W., 213, lks. dist., mkd. T36N R9W S28 BT.

Land, rolling.

Soil, rocky 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, oak brush, and cliff rose. Fair grass.

S. $89^{\circ} 52'$ E., on a random line, bet. secs. 27 and 34.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect N. and S. line 5 lks. N. of the cor. of secs. 26, 27, 34, and 35.

Thence,

32. Survey: Subdivisional Lines: T. 36 N., R. 9 W.

Chains	
	N. 89° 50' W., on true line, bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth. Desc. slightly over gently rolling SW. slope.
10.90	Enter dense timber, brs. N. and S.
22.90	Slope changes to steep W. slope. Desc. 151 ft.
29.90	Leave dense timber, enter scattering timber, brs. N. and S.
36.20	Bottom of Lange's Run, cut bank wash, 60 lks. wide, 10 ft. deep, course N. 21° W. Over nearly level bottom land.
39.95	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S27 \\ \hline \frac{1}{4} \\ S34 \\ 1939 \end{array}$
	raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
	No bearing trees available.
	Continue over nearly level bottom land.
44.10	Hurricane-Mt. Trumbull ungraded road, brs. N. 16° W. and S. 16° E.
44.50	Leave bottom land, brs. N. and SE. Asc. 46 ft. over E. slope to
49.90	Top of ascent. Desc. 15 ft. along rolling S. slope of spur, sloping E., from NW.
60.90	Ravine, course SE. Leave scattering timber, enter dense timber, brs. N. 20° E. and S. Asc. 64 ft. over E. slope to
79.90	The cor. of secs. 27, 28, 33, and 34. Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pinyon and juniper. Undergrowth, sage, algerita, and cacti. Good grass.
	N. 0° 02' W., bet. secs. 27 and 28. Over rolling land, thru dense timber and undergrowth. Asc. slightly along a gradual E. slope. to
5.00	Slope changes to SE. Asc. 17 ft. to
12.00	Top of spur, slopes NE. Desc. 87 ft. over NW. slope. to
23.00	Leave dense and enter scattering timber, brs. E. and NW.
31.55	Draw, course N. 65° E. Asc. 20 ft. over SE. slope.
32.50	Dim road, brs. N. 65° E. and SW.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

Survey: Subdivisional lines: T. 36 N., R. 9 W.

33.

Chains

 $\frac{1}{4}$

S28|S27

1939

from which

A pinyon, 6 ins. diam., brs. N. $52\frac{1}{4}^{\circ}$ E., 120 lks.
dist., mkd. $\frac{1}{4}$ S27 BT.

A pinyon, 12 ins. diam., brs. S. 6° W., 253 lks.
dist., mkd. $\frac{1}{4}$ S28 BT.

Continue over SE. slope. Asc. 60 ft.

48.50 Top of spur, slopes E. Desc. 45 ft. over NE. slope.

59.00 Slope changes to SE. Asc. 30 ft.

63.50 Top of low spur, slopes E. Desc. 40 ft. over N. slope.

79.95 Shallow draw, course NE. Along slight E. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in
the ground to solid rock, and in a mound of stone to
top, for the cor. of secs. 21, 22, 27, and 28, with
brass cap marked

T36N R9W

S21|S22

S28|S27

1939

from which

A juniper, 10 ins. diam., brs. N. $8\frac{1}{4}^{\circ}$ E., 278 lks.
dist., mkd. T36N R9W S22 BT.

A juniper, 10 ins. diam., brs. S. 2° E., 364 lks.
dist., mkd. T36N R9W S27 BT.

A juniper, 12 ins. diam., brs. S. 51° W., 466 lks.
dist., mkd. T36N R9W S28 BT.

A juniper, 14 ins. diam., brs. N. $67\frac{3}{4}^{\circ}$ W., 418 lks.
dist., mkd. T36N R9W S21 BT.

Land, rolling.

Soil, rocky clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, algerita, oak brush, and cacti. Good
grass.S. $89^{\circ} 50'$ E., on a random line, bet. secs. 22 and 27.40.00 Set temp. $\frac{1}{4}$ sec. cor.79.96 Intersect N. and S. line 17 lks. S. of the cor. of secs.
22, 23, 26, and 27.

Thence,

N. $89^{\circ} 57'$ W., on true line, bet. secs. 22 and 27.

Over rolling land, thru scattering undergrowth.

Asc. 60 ft. over E. slope.

BOOK 4260

34. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
8.50	Top of ascent, brs. N. and S. Enter scattering timber, brs. N. and S. Desc. 12 ft. along a N. slope.
13.80	Top of spur, slopes N., approx. 2 chs., thence NE. Desc. 88 ft. over W. slope.
14.68	Fern-Esplin earth tank brs. N. 22° E.
19.00	Enter bottom land, brs. NE. and SW.
23.30	Lange's Run, cut bank wash, 35 lks. wide, 7 ft. deep, course N. 40° E., from S. 50° W. Asc. 66 ft. over SE. slope.
26.10	Dim road, brs. N. 40° E. and S. 40° W.
37.00	Top of spur, slopes S. Desc. 21 ft. over SW. slope to
39.98	Set an iron post, 3 ft. long, 1 in. in diam., over a cross (+) on bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{l} S22 \\ S27 \\ 1939 \end{array}$
	No bearing trees available.
	Continue over SW. slope. Desc. 21 ft.
44.95	Hurricane-Mt. Trumbull ungraded road, brs. N. 22° W. and S. 22° E.
48.00	Draw, course SE., from N. 85° W. Asc. 64 ft. over NE. slope to
70.00	Slope changes to gradual N. slope. Desc. 20 ft. to
79.90	Shallow draw, course N. 20° E., approx. 1.50 chs. to ravine, course E. Asc. slight E. slope to
79.96	The cor. of secs. 21, 22, 27, and 28.
	Land, rolling. Soil, rocky clay, 2nd, 3rd, and 4th rates. Timber, pinyon and juniper. Undergrowth, sage, algerita, cliff rose, and cacti. Good grass.
	N. 0° 02' W., bet. secs. 21 and 22.
	Over rolling land, thru scattering timber and undergrowth.
	Along a gradual E. slope. to
1.60	Ravine, 2 lks. wide, course E., from NW. Asc. 54 ft. over S. slope. to
18.00	Top of spur, slopes E., from NW. Along a gradual E. slope. to
38.00	Top of low ridge, brs. N. 60° E. and W. Desc. slightly over NW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

$\frac{1}{4}$
S21|S22

1939

from which

A juniper, 10 ins. diam., brs. N. 15° E., 84 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

A juniper limb, 10 ins. diam., brs. N. 65½° W., 187 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

Desc. 45 ft. over rolling gradual NW. slope.

52.60 Hurricane-Mt. Trumbull ungraded road, brs. N. 55° W. and S. 55° E.

64.10 Dim road, brs. S. 20° E. and N. 20° W.

69.00 Same dim road, brs. NE. and SW.

70.00 Draw, course NE. Asc. 93 ft. over S. slope.

75.00 Leave scattering and enter dense timber, brs. E. and W.

78.30 Top of spur, slopes NE. Desc. 34 ft. over N. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 15, 16, 21, and 22, with brass cap marked

T36N R9W

S16|S15

S21|S22

1939

from which

A juniper, 10 ins. diam., brs. N. 47½° E., 27 lks. dist., mkd. T36N R9W S15 BT.

A juniper, 12 ins. diam., brs. S. 44° E., 49 lks. dist., mkd. T36N R9W S22 BT.

A juniper, 6 ins. diam., brs. S. 46½° W., 90 lks. dist., mkd. T36N R9W S21 BT.

A juniper, 10 ins. diam., brs. N. 47° W., 24 lks. dist., mkd. T36N R9W S16 BT.

Land, rolling.

Soil, gravelly to rocky clay, 2nd, 3rd, and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, algerita, and cacti. Fair grass.

S. 89° 57' E., on a random line, bet. secs. 15 and 22.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. and S. line 13 lks. N. of the cor. of secs. 14, 15, 22, and 23.

Thence,

N. 89° 51' W., on true line, bet. secs. 15 and 22.

Over rolling land, thru heavy timber and undergrowth.

Asc. 23 ft. over E. slope.

BOOK 4260

36.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
1.70	Top of spur, slopes NE. Asc. 8 ft. along a rolling N. slope.
16.90	Head of ravine, course NE. Asc. 42 ft. over NE. slope.
27.00	Top of spur, slopes SE. Along a gradual S. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S15}{S22}$ 1939
	from which
	A juniper, 10 ins. diam., brs. S. 14° W., 46 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	A juniper, 12 ins. diam., brs. N. 23° W., 67 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	Continue along a gradual S. slope. Asc. 17 ft.
51.00	Top of ridge, brs. N. 70° E. and W. Along top of ridge.
54.00	Leave top of ridge, brs. E. and SW. Top of spur, slopes NW. Desc. 91 ft. over broken W. slope.
70.90	Draw, course NE. Asc. 74 ft. over SE. slope.
71.30	Ungraded road, brs. NE. and SW.
76.20	Top of spur, slopes NE. Desc. slightly along a N. slope to
80.00	The cor. of secs. 15, 16, 21, and 22.
	Land, rolling. Soil, rocky clay and gypsum, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage, algerita, and cacti. Poor grass.
	N. 0° 02' W., bet. secs. 15 and 16.
	Over rolling land, thru dense timber and scattering undergrowth.
	Desc. 5 ft. over N. slope.
0.40	Ravine, course NE, from W. Asc. 29 ft. over S. slope.
6.80	Top of spur, slopes E. Desc. 128 ft. over N. slope.
20.00	Draw, course N. 80° E., approx. 15 chs., thence NE. Asc. 119 ft. over S. slope.
20.30	Dim road, brs. N. 80° E. and S. 80° W.
27.30	Top of spur, slopes E. Desc. 70 ft. over N. slope.
32.50	Ravine, course E. Asc. 44 ft. over SE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S16 S15 1939

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

from which

A juniper, 9 ins. diam., brs. N. 15° E., 60 lks. dist., mkd. 1/4 S15 BT.

A juniper, 10 ins. diam., brs. N. 73° W., 16 lks. dist., mkd. 1/4 S16 BT.

Asc. slightly over S. slope

41.50 Top of spur, slopes E. Desc. 30 ft. over NE. slope

47.00 Slope changes to SE. Asc. 38 ft.

55.00 Top of spur, slopes E. Desc. 45 ft. over N. slope

63.30 Draw, course E. Asc. 78 ft. over S. slope

78.70 Top of spur, slopes SE. Desc. 5 ft. over NE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock, and in a mound of stone to top, for the cor. of secs. 9, 10, 15, and 16, with brass cap marked

T36N R9W
S9|S10
S16|S15
1939

from which

A juniper, 8 ins. diam., brs. N. 81 1/2° E., 41 lks. dist., mkd. T36N R9W S10 BT.

A juniper, 6 ins. diam., brs. S. 28 1/2° E., 68 lks. dist., mkd. T36N R9W S15 BT.

A juniper, 7 ins. diam., brs. S. 83 3/4° W., 52 lks. dist., mkd. T36N R9W S16 BT.

A juniper, 12 ins. diam., brs. N. 59 1/2° W., 74 lks. dist., mkd. T36N R9W S9 BT.

Land, rolling.

Soil, rocky, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage, algerita, cliff rose, and cacti. Fair grass.

S. 89° 51' E., on a random line, bet. secs. 10 and 15.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line 2 lks. N. of the cor. of secs. 10, 11, 14, and 15.

Thence,

N. 89° 50' W., on true line, bet. secs. 10 and 15.

Over rolling and heavy rolling land, thru scattering undergrowth.

Asc. 16 ft. along a gradual S. slope

4.00 Short draw, course SE., from N. Asc. 96 ft. over SE. slope

38. Survey: . Subdivisional lines: T. 36 N., R. 9 W.

Chains	
9.40	Top of steep ascent, brs. N. and SW. Along a steep S. slope. Asc. 29 ft.
10.00	Enter scattering timber, brs. NE. and SW.
14.30	Top of spur, slopes S. Desc. 91 ft. over SW. slope to
19.00	Base of steep descent, brs. SE. and NW. Along a S. slope to
30.30	Ravine, course SE., from N. Asc. 82 ft. over NE. slope to
36.00	Top of spur, slopes SE. Desc. 18 ft. over SW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 23 ins. in the ground, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S10}{\frac{1}{4} S15}$ 1939
	from which
	A juniper, 8 ins. diam., brs. S. 20° W., 164 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	A juniper, 6 ins. diam., brs. N. 44° W., 180 lks. dist., mkd. $\frac{1}{4}$ S10 BT.
	Desc. slightly over SW. slope to
40.70	Ravine, course SE. Asc. 85 ft. over SE. slope.
44.50	Leave scattering and enter dense timber, brs. N. and S.
53.20	Top of spur, slopes S. Desc. 53 ft. over W. slope to
58.65	Ravine, 3 lks. wide, course S. Asc. 47 ft. over E. slope.
60.40	Top of steep ascent, brs. N. and S. Along a gradual S. slope to
67.00	Slope changes to SW. Desc. 25 ft.
69.60	Ravine, 2 lks. wide, course S. Asc. 25 ft. over SE. slope.
70.90	Top of short spur, slopes S. Desc. 28 ft. over SW. slope.
75.10	Ravine, 2 lks. wide, course S. 70° E. Asc. 34 ft. over NE. slope to
80.00	The cor. of secs. 9, 10, 15, and 16.
	Land, rolling and heavy rolling. Soil, rocky and gypsum, 3rd and 4th rates. Timber, pinyon and few juniper. Undergrowth, sage, algerita, cliff rose, oak brush, and cacti. Poor grass.
	N. 0° 02' W., bet. secs. 9 and 10.
	Over rolling land, thru dense timber and scattering undergrowth.
	Desc. 16 ft. over NE. slope to
4.10	Ravine, course S. 60° E. Asc. 62 ft. over gradual SW. slope to

Survey: Subdivisional lines: T. 36 N., R. 9 W.

39.

Chains	
28.00	Top of low ridge, brs. E. and W. Desc. 25 ft. over gradual NW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground to solid rock, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S9 S10
	1939
	from which
	A juniper, 5 ins. diam., brs. N. 59° E., 29 lks. dist., mkd. $\frac{1}{4}$ S10 BT.
	A juniper, 7 ins. diam., brs. N. 48 $\frac{1}{2}$ ° W., 62 lks. dist., mkd. $\frac{1}{4}$ S9 BT.
	Continue over gradual NW. slope. Desc. slightly.
44.00	Shallow draw, course NW., heads approx. 10 chs. E. Asc. 20 ft. over gradual SW. slope
51.00	Top of spur, slopes NW. Leave dense and enter scattering timber, brs. SE. and NW. Desc. 43 ft. over gradual N. slope
60.30	Shallow draw, course NW. Asc. 23 ft. over rolling SW. slope
70.00	Slope changes to slight NW. slope. Desc. 15 ft.
78.40	Shallow draw, course N. 70° W. Asc. slightly over SW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone to top, for the cor. of secs. 3, 4, 9, and 10, with brass cap marked
	T36N R9W
	S4 S3
	S9 S10
	1939
	from which
	A juniper, 6 ins. diam., brs. N. 14° E., 16 lks. dist., mkd. T36N R9W S3 BT.
	A pinyon, 5 ins. diam., brs. S. 51° E., 147 lks. dist., mkd. T36N R9W S10 BT.
	A pinyon, 8 ins. diam., brs. S. 8° W., 274 lks. dist., mkd. T36N R9W S9 BT.
	A juniper, 12 ins. diam., brs. N. 71 $\frac{1}{2}$ ° W., 195 lks. dist., mkd. T36N R9W S4 BT.
	Land, rolling. Soil, rocky clay, 2nd, 3rd, and 4th rates. Timber, pinyon and juniper. Undergrowth, sage, cliff rose, algerita, and cacti. Fair grass.
	S. 89° 50' E., on a random line, bet. secs. 3 and 10.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

40.

Chains	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect N. and S. line 5 lks. N. of the cor. of secs.
	2, 3, 10, and 11.
	Thence,
	N. $89^{\circ} 48'$ W., on true line, bet. secs. 3 and 10.
	Over rolling land, thru scattering timber and undergrowth.
	Asc. 35 ft. over gradual SE. slope
23.40	Top of low spur, slopes N. 60° E. Desc. 15 ft. over
	slight NW. slope
32.30	Shallow draw, course NE. Asc. slightly over rolling
	NE. slope to
40.02	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
	the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S3}{\frac{1}{4} S10}$ 1939
	from which
	A pinyon, 12 ins. diam., brs. N. $26\frac{1}{2}^{\circ}$ E., 51 lks. dist., mkd. $\frac{1}{4}$ S3 BT.
	A double pinyon, 9 ins. diam., brs. S. 28° W., 58 lks. dist., mkd. $\frac{1}{4}$ S10 BT.
	Continue slight ascent over gently rolling NE. slope to
74.00	Top of ridge, brs. S. 10° E. and N. 10° W. Desc. 29 ft.
	over SW. slope to
80.04	The cor. of secs. 3, 4, 9, and 10.
	Land, rolling.
	Soil, sandy clay, 2nd and 3rd rates.
	Timber, pinyon and juniper.
	Undergrowth, sage, algerita, and cacti. Fair grass.
	N. $0^{\circ} 02'$ W., bet. secs. 3 and 4.
	Over rolling land, thru scattering timber and undergrowth.
	Asc. 15 ft. over SW. slope
15.00	Top of spur, slopes W. Desc. 87 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in
	the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S4 S3 1939
	raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
	No bearing trees available.
	Desc. slightly over NW. slope.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

BOOK 420

41.

Chains	
48.00	Hurricane-Mt. Trumbull ungraded road, brs. N. 80° E. & S. 46° W.
48.90	Wash, cut banks 6 ft. high, 8 lks. wide, in long wide draw, course N. 20° E. Asc. 120 ft. over SE. slope
74.00	Top of ascent, brs. NE. and SW. Desc. 15 ft. over NW. slope to
79.59	Intersect the Ninth Standard Parallel North. Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, for the closing cor. of secs. 3 and 4, with brass cap marked
	<p>T37N R9W S34 — S4 S3 T36N R9W CC 1939</p>
	from which
	A pinyon, 8 ins. diam., brs. S. 13½° E., 176 lks. dist., mkd. T36N R9W S3 CC BT.
	A juniper, 6 ins. diam., brs. S. 20° W., 65 lks. dist., mkd. T36N R9W S4 CC BT.
	The standard cor. of secs. 33 and 34, T. 37 N., R. 9 W., brs. West, 17.37 chs. dist., and the standard ¼ sec. cor. of sec. 34 brs. East, 22.63 chs. dist., both set, marked, and witnessed as described in the official record.
	Land, rolling. Soil, rocky, 2nd, 3rd, and 4th rates. Timber, pinyon and juniper. Undergrowth, sage, algerita, cliff rose, and cacti. Fair grass.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., which is an iron post, 2 ins. in diam., set, marked, and witnessed as described in the official record.
	Thence, N. 0° 03' W., bet. secs. 32 and 33. Over rolling land, thru scattering timber and undergrowth. Asc. gradually over SW. slope.
8.50	Earth tank, 1 ch. by 2 chs., brs. S. 79° W., 3.50 chs. dist. Slope changes to S. Asc. 50 ft.
12.00	Leave scattering and enter dense timber, brs. E. and W.
16.20	Top of short spur, slopes SE. Desc. slightly over NE. slope to
18.00	Slope changes to SE. Asc. 15 ft.
23.80	Top of spur, slopes E. Desc. 40 ft. over NE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked

Survey: Subdivisional lines: T. 36 N., R. 9 W.

42.

Chains	
	<p style="text-align: center;">S32 S33</p> <p style="text-align: center;">1939</p> <p style="text-align: right;">from which</p> <p>A pinyon, 8 ins. diam., brs. S. $74\frac{1}{2}^{\circ}$ E., 58 lks. dist., mkd. $\frac{1}{4}$ S33 BT.</p> <p>A pinyon, 5 ins. diam., brs. N. 71° W., 38 lks. dist., mkd. $\frac{1}{4}$ S32 BT.</p> <p>Continue over NE. slope. Desc. slightly.</p>
42.50	Draw, course N. 60° E. Asc. 15 ft. over SE. slope to
47.70	Top of spur, slopes E. Desc. 46 ft. over N. slope to
52.70	Gulch, course E. Asc. 88 ft. over SW. slope.
53.40	Dim road, brs. E. and W.
68.00	Top of spur, slopes SE., from N. Along top of spur.
76.00	Leave top of spur, slopes S., from NW. Desc. gradually over NE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 28, 29, 32, and 33, with brass cap marked
	<p>T36N R9W</p> <p style="border-bottom: 1px solid black;">S29 S28</p> <p style="border-bottom: 1px solid black;">S32 S33</p> <p>1939</p> <p style="text-align: right;">from which</p>
	<p>A pinyon, 6 ins. diam., brs. N. $20\frac{1}{4}^{\circ}$ E., 25 lks. dist., mkd. T36N R9W S28 BT.</p> <p>A pinyon, 12 ins. diam., brs. S. $49\frac{1}{2}^{\circ}$ E., 68 lks. dist., mkd. T36N R9W S33 BT.</p> <p>A pinyon, 8 ins. diam., brs. S. 61° W., 63 lks. dist., mkd. T36N R9W S32 BT.</p> <p>A juniper, 12 ins. diam., brs. N. 65° W., 85 lks. dist., mkd. T36N R9W S29 BT.</p> <p>Land, rolling. Soil, gravelly clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage, oak brush, and cacti. Fair grass.</p>
	S. $89^{\circ} 52'$ E., on a random line, bet. secs. 28 and 33.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect the cor. of secs. 27, 28, 33, and 34.
	Thence,
	N. $89^{\circ} 52'$ W., on true line, bet. secs. 28 and 33.
	Over rolling land, thru dense timber and scattering undergrowth.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

Asc. 20 ft. over E. slope

10.00 Top of low spur, slopes N. 20° E. Desc. 30 ft. over W. slope

23.00 Head of draw, course N. 20° E. Along a N. slope.

28.90 Dim road, brs. N. 20° E. and S. 20° W.

30.00 Low saddle in spur, slopes SE. Desc. 12 ft. over SW. slope

35.00 Wash, 8 lks. wide, in draw, course SE. Asc. 23 ft. over E. slope to

39.98 Set an iron post, 3 ft. long, 1 in. in diam., 22 ins. in the ground to solid rock, and in a small mound of stone to top, for the 1/4 sec. cor., with brass cap marked

1/4 S28
S33
1939

from which

A juniper, 7 ins. diam., brs. N. 76 1/2° E., 194 lks. dist., mkd. 1/4 S28 BT.

A juniper, 6 ins. diam., brs. S. 62° W., 72 lks. dist., mkd. 1/4 S33 BT.

Asc. 21 ft. over NE. slope

61.30 Top of spur, slopes SE. Desc. 15 ft. over SW. slope

66.70 Draw, course SE. Asc. slightly over NE. slope to

79.96 The cor. of secs. 28, 29, 32, and 33.

Land, rolling.
Soil, sandy to gravelly clay, 2nd and 3rd rates.
Timber, pinyon and juniper.
Undergrowth, sage, cliff rose, and cacti. Fair grass.

N. 0° 03' W., bet. secs. 28 and 29.

Over rolling land, thru dense timber and scattering undergrowth.

Desc. 25 ft. over slightly broken NE. slope

24.30 Drain, course S. 70° E. Asc. 18 ft. over S. slope

28.00 Top of low spur, slopes E. Over nearly level top of spur.

34.10 Leave top of low spur, slopes E. Desc. 35 ft. over NE. slope.

38.00 Leave timber and enter valley, brs. E. and W. Over nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap mkd.

1/4
S29|S28
1939

Survey: Subdivisional lines: T. 36 N., R. 9 W.

44.

Chains							
	from which						
	A pinyon, 6 ins. diam., brs. S. $87\frac{1}{2}^{\circ}$ E., 245 lks. dist., mkd. $\frac{1}{4}$ S28 BT.						
	A juniper, 6 ins. diam., brs. S. $59\frac{1}{4}^{\circ}$ W., 135 lks. dist., mkd. $\frac{1}{4}$ S29 BT.						
	Continue over level valley.						
42.00	Drain, course E. Over level valley.						
42.70	Dim road, brs. E. and W.						
44.00	Leave valley and enter dense timber, brs. E. and W. Asc. 45 ft. over S. slope						
53.00	Top of spur, slopes S. 70° E. Desc. 15 ft. over NE. slope						
60.20	Draw, course E. Along E. slope to						
66.10	Draw, course S. 70° E. Asc. 30 ft. over gradual SE. slope.						
73.70	Top of low ridge, brs. E. and W. Desc. 10 ft. over gradual NE. slope to						
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 20, 21, 28, and 29, with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T36N R9W</td> </tr> <tr> <td style="text-align: center;">S20</td> <td style="text-align: center;">S21</td> </tr> <tr> <td style="text-align: center;">S29</td> <td style="text-align: center;">S28</td> </tr> </table>	T36N R9W		S20	S21	S29	S28
T36N R9W							
S20	S21						
S29	S28						
	1939						
	from which						
	A juniper, 10 ins. diam., brs. N. $41\frac{1}{4}^{\circ}$ E., 73 lks. dist., mkd. T36N R9W S21 BT.						
	A juniper, 12 ins. diam., brs. S. $73\frac{1}{2}^{\circ}$ E., 42 lks. dist., mkd. T36N R9W S28 BT.						
	A pinyon, 7 ins. diam., brs. S. 70° W., 43 lks. dist., mkd. T36N R9W S29 BT.						
	A pinyon, 10 ins. diam., brs. N. $65\frac{1}{4}^{\circ}$ W., 74 lks. dist., mkd. T36N R9W S20 BT.						
	Land, rolling. Soil, gravelly clay, 3rd rate. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.						
	S. $89^{\circ} 52'$ E., on a random line, bet. secs. 21 and 28.						
40.00	Set temp. $\frac{1}{4}$ sec. cor.						
79.98	Intersect N. and S. line 5 lks. S. of the cor. of secs. 21, 22, 27, and 28.						
	Thence,						
	N. $89^{\circ} 54'$ W., on true line, bet. secs. 21 and 28.						
	Over rolling land, thru scattering timber and undergrowth.						
	Asc. 23 ft. over E. slope to						
10.00	Slope changes to gradual SW. slope. Desc. slightly.						

Survey: Subdivisional lines: T. 36 N.; R. 9 W.

45.

Chains	
15.00	Shallow draw, course S. 80° E., approx. 3 chs., thence E. Leave scattering and enter dense timber, brs. N. and S. Asc. 52 ft. over gently rolling E. slope to
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to solid rock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S21}{\frac{1}{4} S28}$ 1939
	from which
	A juniper, 16 ins. diam., brs. N. 71° E., 136 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
	A juniper, 5 ins. diam., brs. S. 56 $\frac{3}{4}$ ° W., 33 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
	Continue over gently rolling E. slope. Asc. 20 ft.
60.00	Top of low ridge, brs. NE. and SW. and top of spur, slopes SE. Desc. 22 ft. over W. slope
66.40	Head of draw, course NE. Asc. slightly over NE. slope to
79.98	The cor. of secs. 20, 21, 28, and 29.
	Land, rolling. Soil, sandy to gravelly clay, 2nd and 3rd rates. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.
	N. 0° 03' W., bet. secs. 20 and 21.
	Over rolling land, thru dense timber and scattering undergrowth.
	Desc. slightly over NE. slope to
2.00	Slope changes to NW. Desc. 20 ft.
26.30	Dim road, brs. E. and W.
26.50	Draw, course E., from SW. Asc. 20 ft. over S. slope to
32.00	Top of broad, low spur, slopes E. Desc. 25 ft. over NE. slope
39.80	Wide draw, course S. 70° E. Asc. slightly over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S20 S21}{\frac{1}{4}}$ 1939
	from which
	A juniper, 12 ins. diam., brs. S. 57 $\frac{1}{2}$ ° E., 196 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
	A juniper, 18 ins. diam., brs. N. 65° W., 173 lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	Continue over SE. slope. Asc. 35 ft.

BOOK 4260

Survey: Subdivisional Lines: T. 36 N., R. 9 W.

46.

Chains	
57.00	Top of spur, slopes E. Desc. 50 ft. over NE. slope to
70.30	Draw, course N. 60° E. Asc. 35 ft. over SE. slope to
77.00	Top of spur, slopes E. Desc. 10 ft. over NE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for the cor. of secs. 16, 17, 20, and 21, with brass cap marked
	T36N R9W S17 S16 S20 S21 1939
	from which
	A juniper, 16 ins. diam., brs. N. 50½° E., 305 lks. dist., mkd. T36N R9W S16 BT.
	A pinyon, 6 ins. diam., brs. S. 69° E., 33 lks. dist., mkd. T36N R9W S21 BT.
	A pinyon, 18 ins. diam., brs. S. 69¼° W., 62 lks. dist., mkd. T36N R9W S20 BT.
	A juniper, 12 ins. diam., brs. N. 28¾° W., 31 lks. dist., mkd. T36N R9W S17 BT.
	Land, rolling. Soil, gravelly clay, 3rd rate. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.
	S. 89° 54' E., on a random line, bet. secs. 16 and 21.
40.00	Set temp. ¼ sec. cor.
80.04	Intersect the cor. of secs. 15, 16, 21, and 22.
	Thence,
	N. 89° 54' W., on true line, bet. secs. 16 and 21.
	Over rolling land, thru dense timber and scattering undergrowth.
	Asc. 34 ft. over NE. slope to
3.80	Top of spur, slopes NE. Desc. 98 ft. over W. slope.
19.00	Leave heavy and enter scattering timber, brs. N. and S.
28.60	Hurricane Mt. Trumbull ungraded road, brs. N. 12° W. & S. 30° E.
32.40	Draw, course NE., approx. 5 chs., thence N. 70° E. Asc. 47 ft. over E. slope.
34.00	Dim road, brs. NE. and SW.
38.90	Leave scattering and enter dense timber, brs. S. and NW.
40.02	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor., with brass cap marked
	S16 ¼ ——— S21 1939

Survey: Subdivisional lines: T. 36 N., R. 9 W. BOOK 4260
47.

Chains	
	from which
	A juniper, 8 ins. diam., brs. N. $14\frac{1}{4}^{\circ}$ E., 43 lks. dist., mkd. $\frac{1}{4}$ S16 BT.
	A juniper, 12 ins. diam., brs. S. $57\frac{1}{2}^{\circ}$ W., 17 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
	Asc. 29 ft. over slightly broken E. slope
54.00	Top of spur, slopes N. 20° E. Desc. 23 ft. over W. slope
68.70	Draw, course NE. Asc. 20 ft. over NE. slope to
80.04	The cor. of secs. 16, 17, 20, and 21.
	Land, rolling and slightly broken. Soil, gravelly clay, 2nd and 3rd rates. Timber, pinyon and juniper. Undergrowth, sage, algerita, and cacti. Fair grass.
	N. $0^{\circ} 03'$ W., bet. secs. 16 and 17.
	Over rolling land, thru dense timber and scattering undergrowth.
	Desc. 15 ft. over NE. slope
12.50	Draw, course N. 60° E. Asc. 20 ft. over SE. slope to
16.70	Top of spur, slopes E. Desc. 40 ft. over NE. slope to
23.20	Draw, course S. 70° E. Asc. 46 ft. over S. slope to
29.60	Short spur, slopes SW. Along W. slope to
33.60	Draw, course S. 30° W. Asc. 45 ft. over S. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S17 S16
	1939
	from which
	A pinyon, 8 ins. diam., brs. S. 88° E., 13 lks. dist., mkd. $\frac{1}{4}$ S16 BT.
	A pinyon, 12 ins. diam., brs. N. $66\frac{3}{4}^{\circ}$ W., 5 lks. dist., mkd. $\frac{1}{4}$ S17 BT.
	Continue over S. slope. Asc. 20 ft.
48.50	Top of ridge, brs. E. and N. Along top of ridge.
59.00	Leave top of ridge, brs. S. and NW. Desc. 30 ft. over NE. slope
71.80	Draw, course NW. Asc. gradually over SW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for the cor. of secs. 8, 9, 16 and 17, with brass cap marked

48. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

T36N R9W
 $\frac{S8}{S9}$
 $\frac{S17}{S16}$
 1939

from which

A juniper, 10 ins. diam., brs. N. $26\frac{1}{4}^{\circ}$ E., 61 lks.
 dist., mkd. T36N R9W S9 BT.

A juniper, 16 ins. diam., brs. S. 62° E., 189 lks.
 dist., mkd. T36N R9W S16 BT.

A pinyon, 16 ins. diam., brs. S. $61\frac{1}{2}^{\circ}$ W., 219 lks.
 dist., mkd. T36N R9W S17 BT.

A pinyon, 16 ins. diam., brs. N. $71\frac{1}{4}^{\circ}$ W., 146 lks.
 dist., mkd. T36N R9W S8 BT.

Land, rolling.

Soil, gravelly clay, 3rd rate.

Timber, pinyon and juniper.

Undergrowth, sage and cacti. Fair grass.

S. $89^{\circ} 54'$ E., on a random line, bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect N. and S. line 5 lks. S. of the cor. of secs.
 9, 10, 15, and 16.

Thence,

N. $89^{\circ} 56'$ W., on true line, bet. secs. 9 and 16.

Over rolling land, thru dense timber and scattering under-
 growth.

Asc. slightly over NE. slope to

2.50 Top of spur, slopes SE. Desc. slightly along a S. slope to

7.30 Shallow draw, course SE. Asc. 20 ft. over E. slope to

11.50 Top of spur, slopes SE. Along gently rolling S. slope.
 Asc. 10 ft.

27.00 Shallow draw, course SE. Asc. 43 ft. over NE. slope to

33.00 Top of spur, slopes SE. Desc. slightly over SW. slope to

37.00 Slope changes to SE. Asc. 8 ft.

40.02 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
 the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

S9
 $\frac{1}{4}$
 S16
 1939

from which

A juniper, 12 ins. diam., brs. S. 52° W., 80 lks.
 dist., mkd. $\frac{1}{4}$ S16 BT.

A juniper, 8 ins. diam., brs. N. 12° W., 19 lks.
 dist., mkd. $\frac{1}{4}$ S9 BT.

Continue over SE. slope. Asc. slightly,

Survey: Subdivisional lines: T. 36 N., R. 9 W.

49.

Chains	
44.00	Top of ridge, brs. NE. and SW. Desc. 40 ft. over NW. slope.
50.40	Hurricane Mt. Trumbull ungraded road, brs. N. 8° E. & S. 8° W.
50.90	Draw, course NE., heads approx. 6 chs. S. Asc. 18 ft. over gradual E. slope
67.20	Top of spur, slopes N. 10° E. Desc. 44 ft. over W. slope.
75.00	Slope changes to SW. Desc. slightly.
80.04	The cor. of secs. 8, 9, 16, and 17. Land, rolling. Soil, sandy to gravelly clay and gypsum, 2nd, 3rd, and 4th rates. Timber, pinyon and juniper. Undergrowth, sage, algerita, and cacti. Fair grass.
	N. 0° 03' W., bet. secs. 8 and 9. Over rolling land, thru moderate timber and undergrowth. Asc. 40 ft. over SW. slope
10.50	Top of short spur, slopes W. Desc. 78 ft. over slightly broken NW. slope to
21.50	Enter valley and leave timber, brs. NE. and SW. Desc. slightly across valley.
23.00	Draw, course NE. Continue over nearly level valley.
26.00	Main draw, course N. 70° E. Asc. 17 ft. over S. slope
28.50	Low spur, slopes S. 70° E. Desc. 10 ft. over NE. slope
30.20	Drain, course SE. Dim road, brs. N. 70° E. and S. 70° W.
30.80	Leave valley and enter rolling land, brs. N. 70° E. and S. 70° W. Asc. 51 ft. over SW. slope to $\frac{1}{4}$ sec. cor.
34.50	Enter moderate timber, brs. E. and W.
36.00	Spendlode earth tank, inclosed in barb wire fence, brs. Easterly, approx. 28 chs. dist.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	S. 8 S. 9 1939 from which A pinyon, 8 ins. diam., brs. S. 24 $\frac{3}{4}$ ° E., 58 lks. dist., mkd. $\frac{1}{4}$ S9 BT. A pinyon, 16 ins. diam., brs. S. 36° W., 49 lks. dist., mkd. $\frac{1}{4}$ S8 BT. Continue over SW. slope. Asc. 48 ft.
53.20	Top of spur, slopes SE. Desc. 87 ft. over N. slope
68.00	Wide draw, course N. 75° E. Along a gradual E. slope

Chains

75.00 Draw, course S. 75° E. Asc. 25 ft. over S. slope to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
 the ground, for the cor. of secs. 4, 5, 8, and 9, with
 brass cap marked

T36N R9W

S5|S4

S8|S9

1939

from which

A pinyon, 10 ins. diam., brs. N. 31° E., 50 lks.
 dist., mkd. T36N R9W S4 BT..

A juniper, 10 ins. diam., brs. S. 45° E., 213 lks.
 dist., mkd. T36N R9W S9 BT.

A juniper, 8 ins. diam., brs. S. 11½° W., 64 lks.
 dist., mkd. T36N R9W S8 BT.

A juniper, 4 ins. diam., brs. N. 53½° W., 148 lks.
 dist., mkd. BT only.

Land, rolling.

Soil, gravelly clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage and cacti. Fair grass.

S. 89° 56' E., on a random line, bet. secs. 4 and 9.

40.00 Set temp. ¼ sec. cor.

80.06 Intersect N. and S. line 3 lks. N. of the cor. of secs.
3, 4, 9, and 10.

Thence,

N. 89° 55' W., on true line, bet. secs. 4 and 9.

Over rolling land, thru scattering timber and undergrowth.

Desc. 40 ft. over SW. slope to

18.00 Draw, course NW. Over level land.

20.50 Long draw, course N. 10° E. Asc. 29 ft. over gradual
E. slope to

23.00 Hurricane Mt. Trumbull ungraded road, brs. N. 10° E. & S. 2° W.

27.00 Point of spur, slopes NE. Desc. 8 ft. over NW. slope to

29.40 Ravine, course NE., from S. 70° W. Asc. 35 ft. over SE.
slope to

36.50 Top of ascent, brs. N. and S. Along a gradual S. slope to

40.03 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for the ¼ sec. cor., with brass cap marked

¼ S4

S9

1939

from which

A juniper, 5 ins. diam., brs. N. 18½° E., 60 lks.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

51.

Chains	
	dist., mkd. $\frac{1}{4}$ S4 BT.
	A juniper, 5 ins. diam., brs. S. $38\frac{1}{4}^{\circ}$ W., 303 lks. dist., mkd. $\frac{1}{4}$ S9 BT.
	Asc. 10 ft. along a gradual S. slope.
43.00	Head of same ravine, course S. 65° E. Asc. 33 ft. over SE. slope
51.80	Top of spur, slopes NE. Desc. 39 ft. over NW. slope
68.70	Draw, course N. 20° E. Asc. 54 ft. over SE. slope to
78.00	Slope changes to S.
80.06	The cor. of secs. 4, 5, 8, and 9.
	Land, rolling. Soil, rocky and gypsum, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage, algerita, and cacti. Fair grass.
	N. $0^{\circ} 03'$ W., bet. secs. 4 and 5.
	Over rolling land, thru moderate timber and undergrowth.
	Asc. 23 ft. over S. slope to
5.00	Top of short spur, slopes E. Desc. 25 ft. over N. slope
7.40	Drain, course E. Asc. 15 ft. over S. slope to
9.00	Top of short spur, slopes E. Desc. 20 ft. over N. slope
11.10	Gulch, course E. Asc. 43 ft. over SE. slope to
15.40	Top of short spur, slopes E. Desc. 15 ft. over NE. slope.
17.70	Drain, course E., near head. Asc. 20 ft. over S. slope.
20.00	Top of ridge, brs. NE. and SW. Desc. 30 ft. over N. slope
35.80	Gulch, in wide draw, course E., approx. 2 chs., thence N. 20° E. Asc. 15 ft. over SE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S5 S4
	1939
	from which
	A juniper, 14 ins. diam., brs. N. $26\frac{3}{4}^{\circ}$ E., 130 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	A juniper, 10 ins. diam., brs. N. 40° W., 98 lks. dist., mkd. $\frac{1}{4}$ S5 BT.
	Continue over SE. slope. Asc. 10 ft.
44.00	Top of broad, short spur, slopes E. Desc. 40 ft. over NE. slope
52.60	Draw, course NE. Along slightly broken E. slope.

52.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

61.70 Drain, course E. Continue along a broken E. slope to

79.54 Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone to top, for the closing cor. of secs. 4 and 5, with brass cap marked

T37N R9W

S33

S5|S4

T36N R9W

CC

1939

from which

A juniper, 7 ins. diam., brs. S. 63° E., 49 lks. dist., mkd. T36N R9W S4 CC BT.

A pinyon, 10 ins. diam., brs. S. 43° W., 70 lks. dist., mkd. T36N R9W S5 CC BT.

The standard cor. of secs. 32 and 33, T. 37 N., R. 9 W., brs. West, 17.27 chs. dist., and standard $\frac{1}{4}$ sec. cor. of sec. 33 brs. East, 22.73 chs. dist., both set, marked, and witnessed as described in the official record.

Land, rolling.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage and cacti. Fair grass.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.

Thence, ~~to the cor. of secs. 5, 6, 31, and 32~~

N. 0° 03' W., bet. secs. 31 and 32.

Over rolling land, thru dense timber and scattering undergrowth.

Asc. 14 ft. over SE. slope to

10.00 ~~Low spur, slopes N. 50° E. Desc. 100 ft. over N. slope to~~

13.00 Head of draw, course NE. Asc. 5 ft. over SE. slope to

16.00 Top of spur, slopes NE. Desc. 12 ft. over N. slope to

21.00 Shallow draw, 1 ch. wide, course N. 60° E. Asc. 19 ft. over SE. slope to

25.00 Top of spur, slopes E. Desc. 31 ft. over rolling N. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$

S31|S32

1939

from which

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains

A juniper, 16 ins. diam., brs. N. 36° E., 21 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A juniper, 14 ins. diam., brs. N. 62° W., 70 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Desc. 27 ft. over NW. slope

47.00 Ungraded road, brs. N. 60° E. and S. 60° W. in wide draw, course N. 60° E. Asc. 29 ft. over S. slope

51.80 Top of spur, slopes E. Desc. 16 ft. over NE. slope

59.00 Shallow draw, course N. 60° E. Asc. 35 ft. over SE. slope

70.00 Top of spur, slopes E. Desc. 35 ft. over NE. slope.

78.00 Leave timber, brs. E. and W.

80.00 Shallow draw, 2 chs. wide, course E., from S. 85° W. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 29, 30, 31, and 32, with brass cap marked

T36N R9W

S30 | S29

S31 | S32

1939

from which

A pinyon, 12 ins. diam., brs. N. 9½° E., 149 lks. dist., mkd. T36N R9W S29 BT.

A pinyon, 5 ins. diam., brs. S. 14° E., 278 lks. dist., mkd. BT only.

A pinyon, 16 ins. diam., brs. S. 26¾° W., 292 lks. dist., mkd. T36N R9W S31 BT.

A juniper, 16 ins. diam., brs. N. 22° W., 232 lks. dist., mkd. T36N R9W S30 BT.

Land, rolling.

Soil, rocky clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage. Fair grass.

S. 89° 52' E., on a random line, bet. secs. 29 and 32.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 Intersect N. and S. line 5 lks. N. of the cor. of secs. 28, 29, 32, and 33.

Thence,

N. 89° 50' W., on true line, bet. secs. 29 and 32.

Over rolling land, thru dense timber and scattering undergrowth.

Asc. slightly over NE. slope

1.50 Top of spur, slopes SE. Asc. 28 ft. over a rolling S. slope

12.50 Top of spur, slopes S. Desc. 25 ft. over W. slope

BOOK 4260

Survey: Subdivisional lines: T. 36 N., R. 9 W.

54.

Chains	
21.60	Draw, course S. 30° E. Asc. 45 ft. over SE. slope to
33.70	Top of spur, slopes S. Desc. 25 ft. over W. slope to
39.40	Drain, near head, course S. 20° W. Asc. slightly over SE. slope to
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S29 \\ \hline \frac{1}{4} \\ S32 \\ 1939 \end{array}$
	from which
	A juniper, 6 ins. diam., brs. N. 20° E., 56 lks. dist., mkd. $\frac{1}{4}$ S29 BT.
	A juniper, 8 ins. diam., brs. S. 72 $\frac{1}{2}$ ° W., 80 lks. dist., mkd. $\frac{1}{4}$ S32 BT.
	Continue over SE. slope. Asc. 20 ft.
42.20	Top of short spur, slopes S. Desc. 60 ft. over slightly broken SW. slope.
56.20	Leave timber, brs. NE. and SW.
59.00	Junction of wide draws, from W. and NW. Asc. 30 ft. up wide draw from W.
79.98	The cor. of secs. 29, 30, 31, and 32.
	Land, rolling. Soil, gravelly clay, 3rd rate. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.
	N. 89° 52' W., on a random line, bet. secs. 30 and 31.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.19	Intersect the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	Thence,
	S. 89° 52' E., on true line, bet. secs. 30 and 31.
	Over rolling land, thru dense timber and scattering undergrowth.
	Desc. 92 ft. over NE. slope to
16.70	Wash, 5 lks. wide, course S. 60° E. Asc. 10 ft. over SW. slope to
20.80	Top of spur, slopes SE. Desc. 45 ft. over NE. slope to
27.50	Sandy wash, 6 lks. wide, course S. 70° E. Asc. 20 ft. over SW. slope to
30.20	Short spur, slopes S., approx. 1.50 chs. Desc. 29 ft. over SE. slope to
37.20	Drain, course S. Asc. 11 ft. over SW. slope to

Chains	
38.19	<p>Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground to solid rock, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked</p> $\begin{array}{r} \frac{1}{4} \text{ S30} \\ \hline \text{S31} \\ 1939 \end{array}$ <p style="text-align: right;">from which</p> <p>A pinyon, 14 ins. diam., brs. S. $35\frac{3}{4}^{\circ}$ E., 45 lks. dist., mkd. $\frac{1}{4}$ S31 BT.</p> <p>A juniper, 14 ins. diam., brs. N. $43\frac{1}{2}^{\circ}$ W., 69 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>Continue over SW. slope. Asc. 12 ft.</p>
41.20	Top of short spur, slopes S., approx. 5 chs. Desc. 48 ft. over SE. slope.
48.20	Draw, course S. 85° E., from SW. Leave timber, brs. N. 80° E. and SW. Desc. 45 ft. along a slight S. slope.
78.19	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage. Poor grass.</p>
	<p>N. $0^{\circ} 03'$ W., bet. secs. 29 and 30.</p> <p>Over rolling land, thru scattering undergrowth.</p> <p>Asc. 41 ft. over SE. slope.</p>
1.50	Enter dense timber, brs. E. and W.
10.90	Top of spur, slopes E. Desc. 25 ft. over NE. slope
20.50	Shallow draw, 2.50 chs. wide, course SE. Asc. 48 ft. over SW. slope to
40.00	<p>Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked</p> $\begin{array}{r} \frac{1}{4} \\ \hline \text{S30 S29} \\ 1939 \end{array}$ <p style="text-align: right;">from which</p> <p>A juniper, 12 ins. diam., brs. S. $36\frac{1}{4}^{\circ}$ E., 14 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>A juniper, 12 ins. diam., brs. N. $76\frac{1}{2}^{\circ}$ W., 36 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>Continue over SW. slope. Asc. 15 ft.</p>
47.50	Top of spur, slopes SE. Asc. 10 ft. along a gently rolling gradual E. slope to
57.60	Slope changes to NE. Desc. 28 ft.
59.60	Draw, 1 ch. wide, course SE., approx. 7 chs., thence S. 15° E. Asc. 29 ft. over SW. slope

BOOK 4260

56.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains											
64.80	Top of low spur, slopes SE., approx. 6 chs. Desc. 9 ft. over NE. slope to										
66.40	Draw, course S. 30° E. Asc. 61 ft. over S. slope to										
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the cor. of secs. 19, 20, 29, and 30, with brass cap marked										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T36N R9W</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2">1939</td></tr> </table>	T36N R9W		S19	S20	<hr/>		S30	S29	1939	
T36N R9W											
S19	S20										
<hr/>											
S30	S29										
1939											
	from which										
	A juniper, 10 ins. diam., brs. N. 9° E., 51 lks. dist., mkd. T36N R9W S20 BT.										
	A juniper, 12 ins. diam., brs. S. 13½° E., 89 lks. dist., mkd. T36N R9W S29 BT.										
	A juniper, 24 ins. diam., brs. S. 38½° W., 22 lks. dist., mkd. T36N R9W S30 BT.										
	A juniper, 10 ins. diam., brs. N. 46° W., 84 lks. dist., mkd. T36N R9W S19 BT.										
	Land, rolling and gently rolling. Soil, sandy to rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage and oakbrush. Fair grass.										
	S. 89° 50' E., on a random line, bet. secs. 20 and 29.										
40.00	Set temp. ¼ sec. cor.										
79.96	Intersect N. and S. line 2 lks. S. of the cor. of secs. 20, 21, 28, and 29.										
	Thence,										
	N. 89° 51' W., on true line, bet. secs. 20 and 29.										
	Over rolling land, thru dense timber and scattering undergrowth.										
	Asc. 14 ft. over NE. slope to										
4.00	Top of short, flat spur, slopes N. Desc. 15 ft. over W. slope.										
8.50	Dim road, brs. NE. and SW.										
14.00	Draw, near head, course NE. Asc. 70 ft. over SE. slope to										
23.20	Top of spur, slopes NE. Desc. 30 ft. over gradual NW. slope to										
39.98	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the ¼ sec. cor., with brass cap marked										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">S20</td></tr> <tr><td>¼</td><td>S29</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1939</td></tr> </table>	S20		¼	S29	<hr/>		1939			
S20											
¼	S29										
<hr/>											
1939											
	from which										

58.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
40.20	Top of low ridge, brs. N. and SE. Desc. 60 ft. over NE. slope to
56.20	Draw, course NW., heads approx. 2 chs. SE. Asc. 8 ft. over W. slope to
59.20	Top of low, flat ridge, brs. NE. and SW. Over level top of ridge.
64.70	Leave top of flat ridge, brs. NE. and SW. Desc. 19 ft. over E. slope to
69.40	Drain, 5 lks. wide, course SE. Asc. 18 ft. over W. slope to
78.00	Top of spur, slopes SW. Along a gradual S. slope to
78.16	The cor. of secs. 19, 20, 29, and 30.
	Land, rolling and gently rolling. Soil, rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage. Fair grass.
	N. 0° 03' W., bet. secs. 19 and 20.
	Over gently rolling land, thru heavy timber and scattering undergrowth.
	Asc. 3 ft. over gradual S. slope to
1.50	Top of ridge, brs. N. 70° W. and S. 60° E. Desc. 24 ft. over NE. slope to
6.70	Draw, course N. 80° E. Asc. 20 ft. over SE. slope to
12.80	Top of spur, slopes E. Desc. 26 ft. over NE. slope to
21.00	Slope changes to NW. Desc. 18 ft.
26.50	Draw, course N. 60° E. Asc. 31 ft. over SE. slope to
32.00	Top of spur, slopes N. 70° E. Desc. 22 ft. over N. slope.
38.00	Ravine, course N. 60° E. Asc. 16 ft. over SE. slope to
40.00	Top of spur, slopes N. 70° E. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S19 S20
	1939
	from which
	A juniper, 8 ins. diam., brs. N. 70 $\frac{1}{2}$ ° E., 15 lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	A juniper, 10 ins. diam., brs. N. 84 $\frac{1}{2}$ ° W., 32 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	Desc. 53 ft. over N. slope to
48.20	Ravine, course NE. Asc. 16 ft. over SE. slope to
50.80	Top of short spur, slopes E. approx. 5 chs. Desc. 37 ft. over NE. slope to

Survey: Subdivisional lines: T. 36 N., R. 9 W.

59.

Chains

- 58.00 Draw, 1 ch. wide, course NE. Asc. 36 ft. over SE. slope.
- 60.80 Top of short spur, slopes E. approx. 3 chs. Desc. 19 ft. over NE. slope
- 61.85 Ravine, course E. Asc. 37 ft. over S. slope
- 69.00 Top of spur, slopes E. Desc. 38 ft. over N. slope
- 76.00 Ravine, course NE. Asc. 28 ft. over SE. slope to
- 80.00 Top of spur, slopes N. 60° E., from W.
Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 17, 18, 19, and 20, with brass cap marked

T36N R9W

S18|S17

S19|S20

1939

from which

A juniper, 11 ins. diam., brs. N. $68\frac{1}{4}^\circ$ E., 58 lks. dist., mkd. T36N R9W S17 BT.

A pinyon, 10 ins. diam., brs. S. $63\frac{1}{2}^\circ$ E., 38 lks. dist., mkd. T36N R9W S20 BT.

A juniper, 10 ins. diam., brs. S. $86\frac{1}{2}^\circ$ W., 37 lks. dist., mkd. T36N R9W S19 BT.

A juniper, 14 ins. diam., brs. N. $12\frac{1}{4}^\circ$ W., 63 lks. dist., mkd. T36N R9W S18 BT.

Land, gently rolling and rolling.
Soil, rocky clay, 3rd and 4th rates.
Timber, pinyon and juniper.
Undergrowth, sage and algerita. Fair grass.

- 40.00 S. $89^\circ 51'$ E., on a random line, bet. secs. 17 and 20.
Set temp. $\frac{1}{4}$ sec. cor.
- 79.88 Intersect N. and S. line 5 lks. S. of the cor. of secs. 16, 17, 20, and 21.
Thence,
N. $89^\circ 53'$ W., on true line, bet. secs. 17 and 20.
Over rolling land, thru dense timber and scattering undergrowth.
Asc. 60 ft. over NE. slope
- 17.00 Top of broad, short spur, slopes N. Desc. 11 ft. over NW. slope
- 22.50 Drain, near head, course N. Asc. 33 ft. over NE. slope
- 30.00 Top of short spur, slopes N. Desc. 15 ft. over NW. slope.
- 32.70 Drain, course NE. Asc. 28 ft. over SE. slope to
- 39.94 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked

60. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
	$\frac{1}{4} \frac{S17}{S20}$ 1939 <p style="text-align: right;">from which</p>
	A juniper, 12 ins. diam., brs. S. 79° W., 34 lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	A juniper, 5 ins. diam., brs. N. 66 $\frac{3}{4}$ ° W., 19 lks. dist., mkd. $\frac{1}{4}$ S17 BT.
	Continue over SE. slope. Asc. 25 ft.
44.00	Top of spur, slopes NE. Desc. 40 ft. over NW. slope to
52.30	Draw, course NW. Asc. 34 ft. over E. slope to
66.40	Top of low spur, slopes NE. Desc. gradually over NW. slope to
71.20	Drain, course NE. Asc. 35 ft. over SE. slope to
79.88	The cor. of secs. 17, 18, 19, and 20.
	Land, rolling. Soil, gravelly clay, 3rd rate. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.
40.00	N. 89° 47' W., on a random line, bet. secs. 18 and 19. Set temp. $\frac{1}{4}$ sec. cor.
78.04	Intersect the cor. of secs. 13, 18, 19, and 24 on the W. bdy. of the Tp., which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	Thence,
	S. 89° 47' E., on a random line, bet. secs. 18 and 19.
	Over rolling and gently rolling land, thru heavy timber and scattering undergrowth.
	Asc. 75 ft. over NW. slope to
7.00	Top of spur, slopes N. 70° E. Desc. 140 ft. over SE. slope.
37.00	Leave timber, brs. NE. and SW.
38.04	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S18}{S19}$ 1939 <p style="text-align: right;">from which</p>
	A pinyon, 10 ins. diam., brs. N. 8° E., 77 lks. dist., mkd. $\frac{1}{4}$ S18 BT.
	A juniper, 24 ins. diam., brs. S. 65 $\frac{3}{4}$ ° W., 277 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	Desc. 8 ft. over gradual SE. slope to

Survey: Subdivisional lines: T. 36 N., R. 9 W.

61.

Chains	
42.00	Junction of draws, 2 chs. wide, from S. and SW. course N. 30° E. Asc. 32 ft. over W. slope.
48.00	Enter dense timber, brs. NE. and SW.
56.00	Top of ridge, brs. N. and S. and spur, slopes SE. Desc. 33 ft. over NE. slope
67.00	Head of draw, course NE. Asc. 5 ft. over NW. slope
71.00	Top of same spur, slopes E., from SW. Desc. 3 ft. along top of spur to
78.04	The cor. of secs. 17, 18, 19, and 20. Land, rolling and gently rolling. Soil, rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage and algerita. Fair grass.
	N. 0° 03' W., bet. secs. 17 and 18. Over rolling land, thru dense timber and scattering undergrowth. Desc. 50 ft. over N. slope
5.40	Draw, 30 lks. wide, course N. 60° E. Along a slight E. slope
8.50	Draw, 1 ch. wide, course E. Asc. 56 ft. over S. slope
22.00	Top of spur, slopes E. Desc. 18 ft. over N. slope
24.70	Head of ravine, course S. 60° E. Asc. 12 ft. over SE. slope
27.30	Top of low ridge, brs. E. and W. Desc. 45 ft. over NW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S18 S17 1939 from which A juniper, 40 ins. diam., brs. S. 38 $\frac{1}{4}$ ° E., 24 lks. dist., mkd. $\frac{1}{4}$ S17 BT. A juniper, 24 ins. diam., brs. S. 62 $\frac{1}{2}$ ° W., 17 lks. dist., mkd. $\frac{1}{4}$ S18 BT. Desc. 32 ft. over NW. slope
52.00	Draw, 100 lks. wide, course N. 60° E. Asc. 19 ft. over SE. slope
62.00	Top of spur, slopes NE. Desc. 52 ft. over NW. slope.
72.00	Leave timber, brs. NE. and SW. Over level valley brs. NE. and SW.
74.20	Wash, 20 lks. wide, course NE. Asc. 3 ft. over slight SE. slope.
78.00	Dim road, brs. NE. and SW.

Chains

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 7, 8, 17, and 18, with brass cap marked

T36N R9W

S7|S8

S18|S17

1939

from which

A pinyon, 10 ins. diam., brs. N. $23\frac{1}{4}^\circ$ E., 100 lks. dist., mkd. T36N R9W S8 BT.

A juniper, 12 ins. diam., brs. N. $79\frac{1}{2}^\circ$ W., 200 lks. dist., mkd. T36N R9W S7 BT.

No other trees available.

Land, rolling.

Soil, sandy to rocky clay, 3rd and 4th rates.

Timber, pinyon and juniper.

Undergrowth, sage and algerita. Fair grass.

S. $89^\circ 53'$ E., on a random line, bet. secs. 8 and 17.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

79.82

Intersect N. and S. line 3 lks. N. of the cor. of secs. 8, 9, 16, and 17.

Thence,

N. $89^\circ 52'$ W., on true line, bet. secs. 8 and 17.

Over rolling land, thru scattering timber and dense undergrowth.

Desc. 25 ft. over SW. slope

6.00

Junction of draws, from S. and SW., course N. 20° E. Asc. 55 ft. over E. slope.

12.00

Enter dense timber, brs. SE. and NW.

29.00

Top of spur, slopes N. 20° E. Desc. 20 ft. over W. slope.

34.00

Short draw, course N. 20° W. Asc. 30 ft. over E. slope

39.00

Top of spur, slopes N. 20° W. Desc. 8 ft. over W. slope to

39.91

Set an iron post, 3 ft. long, 1 in. in diam., 23 ins. in the ground to solid rock, and in a small mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked

 $\frac{1}{4}$ S8

S17

1939

from which

A juniper, 15 ins. diam., brs. S. $60\frac{1}{4}^\circ$ W., 160 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

A pinyon, 5 ins. diam., brs. N. 30° W., 88 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Continue over W. slope. Desc. 45 ft.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

63.

Chains	
43.50	Leave timber, brs. N. and S.
47.00	Base of descent and enter valley, brs. N. and S. Over nearly level valley, draining NE.
53.00	Draw, course N. 30° E. Continue over level valley.
67.00	Draw, course N. 75° E. Asc. over a slight SE. slope.
77.00	Dim road, brs. NE. and SW.
79.82	The cor. of secs. 7, 8, 17, and 18. Land, rolling and gently rolling. Soil, gravelly clay, 2nd and 3rd rates. Timber, pinyon and juniper. Undergrowth, sage and cacti. Fair grass.
	N. 89° 47' W., on a random line, bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
77.97	Intersect the W. bdy. of the Tp. 4 lks. S. of the cor. of secs. 7, 12, 13, and 18, which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record. Thence, S. 89° 45' E., on true line, bet. secs. 7 and 18. Over rolling land, thru moderate timber and undergrowth. Asc. 10 ft. over SW. slope
5.00	Top of spur, slopes SE. Desc. 42 ft. over NE. slope
11.00	Draw, course E., from N. 70° W. Desc. 17 ft. along draw.
20.00	Junction of draws, from W. and SW., course N. 85° E. SW., Desc. 35 ft. over rolling NE. slope.
25.00	Same draw bears N., 70 lks. dist., course E.
37.97	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{S7}{\frac{1}{4} S18}$ 1939 from which A pinyon, 7 ins. diam., brs. N. 16 $\frac{3}{4}$ ° E., 74 lks. dist., mkd. $\frac{1}{4}$ S7 BT. A pinyon, 8 ins. diam., brs. S. 33° W., 87 lks. dist., mkd. $\frac{1}{4}$ S18 BT. Continue over NE. slope. Desc. 48 ft.
53.00	Junction of draws, from N. 80° W. and NW., course SE. Asc. 34 ft. over W. slope
58.00	Top of spur, slopes E., from N. Along top of spur.
61.20	Leave top of spur, slopes NE., from W. Desc. 57 ft. over E. slope.

BOOK 4260

64. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
70.00	Leave timber, brs. NE. and SW.
73.00	Draw, 1 ch. wide, course S. 60° E. Desc. 6 ft. over slight SE. slope to
77.97	The cor. of secs. 7, 8, 17, and 18. Land, rolling. Soil, gravelly to rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sage and algerita. Fair grass.
	N. 0° 03' W., bet. secs. 7 and 8. Over rolling land, thru scattering undergrowth. Asc. 81 ft. over SE. slope.
1.00	Enter moderate timber, brs. NE. and W.
15.00	Ridge, brs. W. and N. 5° W., and head of spur, slopes E. and W. Thence along E. slope of ridge.
30.00	Same ridge, bears N. and S. 5° W. Desc. 18 ft. along top of ridge.
40.00	Spur, slopes SE. Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S7 S8 1939 from which
	A pinyon, 10 ins. diam., brs. N. 53 $\frac{3}{4}$ ° E., 84 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
	A juniper, 14 ins. diam., brs. S. 66 $\frac{1}{2}$ ° W., 35 lks. dist., mkd. $\frac{1}{4}$ S7 BT.
	Continue along top of ridge. Desc. 34 ft.
55.00	Leave top of ridge, brs. S. and N. 60° E. Desc. 31 ft. over NW. slope to
63.00	Draw, 2 chs. wide, course N. 60° E. Asc. 15 ft. over SE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for the cor. of secs. 5, 6, 7, and 8, with brass cap marked
	T36N R9W S6 S5 S7 S8 1939 from which
	A juniper, 14 ins. diam., brs. N. 46 $\frac{1}{2}$ ° E., 39 lks. dist., mkd. T36N R9W S5 BT.
	A juniper, 10 ins. diam., brs. S. 23 $\frac{1}{2}$ ° E., 56 lks. dist., mkd. T36N R9W S8 BT.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

65.

Chains

A juniper, 14 ins. diam., brs. S. 73° W., 24 lks. dist., mkd. T36N R9W S7 BT.

A juniper, 24 ins. diam., brs. N. 75½° W., 83 lks. dist., mkd. T36N R9W S6 BT.

Land, rolling.
Soil, gravelly and rocky clay, 3rd and 4th rates.
Timber, pinyon and juniper.
Undergrowth, sage and algerita. Fair grass.

S. 89° 52' E., on a random line, bet. secs. 5 and 8.

40.00 Set temp. ¼ sec. cor.

79.78 Intersect the cor. of secs. 4, 5, 8, and 9.

Thence, N. 89° 52' W., on true line, bet. secs. 5 and 8.

Over rolling land, thru dense timber and scattering undergrowth.

Along gradual S. slope to

2.00 Slope changes to SW. Desc. 14 ft.

5.00 Short draw, course SE. Asc. 86 ft. over slightly broken E. slope

26.40 Top of low ridge, brs. NE. and SW. Desc. 12 ft. over NW. slope to

39.89 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground to solid rock, and in a small mound of stone to top, for the ¼ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S5}{S8} \\ 1939$$

from which

A juniper, 6 ins. diam., brs. N. 18½° E., 34 lks. dist., mkd. ¼ S5 BT.

A pinyon, 9 ins. diam., brs. South, 11 lks. dist., mkd. ¼ S8 BT.

Continue over NW. slope. Desc. 19 ft.

41.80 Draw, course N. 10° E. Asc. 19 ft. over E. slope

44.00 Top of spur, slopes N. 10° E. Desc. 6 ft. over gradual NW. slope

62.80 Shallow draw, 5 chs. wide, course NE. Asc. 37 ft. over a gradual SE. slope to

79.78 The cor. of secs. 5, 6, 7, and 8.

Land, rolling.
Soil, sandy to gravelly clay, 2nd and 3rd rates.
Timber, pinyon and juniper.
Undergrowth, sage and algerita. Fair grass.

N. 89° 45' W., on a random line, bet. secs. 6 and 7.

66. Survey: Subdivisional lines: T. 36 N., R. 9 W.

Chains	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
77.85	Intersect the W. bdy. of Tp. 3 lks. N. of the cor. of secs. 1, 6, 7, and 12, which is an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	Thence,
	S. $89^{\circ} 46'$ E., on true line, bet. secs. 6 and 7.
	Over broken mountainous land, thru very scattering timber and undergrowth.
	Asc. 287 ft. over precipitous NW. slope to
3.85	Top of Hurricane Ledge, which at this point is a cliff, 150 ft. high, bearing N. 30° E. and S. 30° W., facing NW. Continue over mountainous land.
9.20	Asc. 228 ft. over steep W. and NW. slopes to slope to
15.80	Ridge, brs. NE. and SW. Enter rolling land and dense timber. Desc. 80 ft. over E. slope. 80 ft. over W. slope.
32.50	Gulch, course NE. Asc. 35 ft. over NW. slope to
37.30	Top of ridge, brs. NE. and SW. Desc. slightly over SE. slope to
37.85	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \text{ S6} \\ \hline \text{S7} \\ 1939 \end{array}$
	from which
	A pinyon, 6 ins. diam., brs. N. $18\frac{3}{4}^{\circ}$ E., 154 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
	A pinyon, 4 ins. diam., brs. S. $41\frac{1}{2}^{\circ}$ E., 132 lks. dist., mkd. $\frac{1}{4}$ S7 BT.
	Desc. 87 ft. over slightly broken SE. slope to
58.80	Draw, course S. 30° E. Asc. 32 ft. over W. slope to
64.10	Top of spur, slopes SW. Desc. 46 ft. over SE. slope to
77.85	The cor. of secs. 5, 6, 7, and 8.
	Land, broken mountainous to rolling. Soil, rocky to gravelly, 4th and 3rd rates. Timber, pinyon and juniper. Undergrowth, sage and cacti. Poor to fair grass.
	N. $0^{\circ} 03'$ W., bet. secs. 5 and 6.
	Over rolling land, thru dense timber and scattering undergrowth.
	Asc. 26 ft. over SE. slope to
16.60	Top of low ridge, brs. N. 10° E. and SW. Along W. slope of ridge.
21.80	Top of same ridge, brs. S. 30° E. and N. 30° W. Along E. slope of ridge. Desc. 5 ft.

Survey: Subdivisional lines: T. 36 N., R. 9 W.

67

Chains	
26.00	Top of same ridge, brs. N. 60° E. and S. 30° W. Desc. 63 ft. over N. slope.
33.80	Draw, 1 ch. wide, course N. 60° E. Asc. 20 ft. over SE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in ground to bedrock, and in a mound of stone to top, for a sec. cor., with brass cap marked
	$\begin{array}{c} \text{S6} \text{S5} \\ \hline 1939 \end{array}$
	from which
	A juniper, 16 ins. diam., brs. S. 7½° E., 72 lks. dist., marked ¼ S5 BT.
	A juniper, 14 ins. diam., brs. N. 67° W., 26 lks. dist., marked ¼ S6 BT.
	Desc. 8 ft. over NE. slope.
41.40	Head of draw, course S, 80° E. Asc. 19 ft. over SE. slope,
47.00	Top of spur, slopes N. from SW. Desc. 43 ft. along rolling, flat top of this spur to
79.45	Intersect the Ninth Standard Parallel North. Set an iron post, 3 ft. long, 2 ins. in diam., 22 ins. in ground to bedrock, and in a small mound of stone to top, for closing cor. of secs. 5 and 6, with brass cap marked,
	$\begin{array}{c} \text{T37N R9W} \\ \hline \text{S32} \\ \hline \text{S6} \text{S5} \\ \hline \text{T36N R9W} \\ \hline \text{CC} \\ \hline 1939 \end{array}$
	from which
	A leaning pinyon, 14 ins. diam., brs. S. 59° E., 47 lks. dist., marked T36N R9W S5 CC BT.
	A pinyon, 8 ins. diam., brs. S. 7½° W., 96 lks. dist., marked T36N R9W S6 CC BT.
	The standard cor. of secs. 31 and 32, T. 37 N., R. 9 W., bears West, 17.60 chs. dist., and the standard ¼ sec. cor. of sec. 32 bears East, 22.40 chs. dist., both being regu- lation brass-capped iron posts, 3 in. and 1 in. diam., respectively, firmly set, marked and witnessed as descri- bed in the official record.
	Land, rolling. Soil, rocky clay, 3rd and 4th rates. Timber, pinyon and juniper. Undergrowth, sagebrush and algerita. Poor grass.

GENERAL DESCRIPTION.

The land in T. 36 N., R. 9 W. is nearly all a high rolling plateau east of the Hurricane Ledge, which enters the township in the west half of sec. 6 and the northwest cor. of sec. 7. The general elevation in the township is about

5800 to 6000 feet above sea level. The soil is gravelly clay with an occasional occurrence of gypsum. A sandy limestone is prevalent in the broken area in the close vicinity of Hurricane Ledge.

There is no permanent running water in the township. Lange's Run, a wash, 40 to 60 lks. wide, with cut banks, crosses the township with a general northeasterly course, thru secs. 34, 27, 22, 23, 14, 11 and 12, and is the principal drainage feature.

Timber, consisting of pinyon and juniper, moderate to dense growth, is prevalent over the entire area. Undergrowth, mainly sagebrush, with some algerita, cliff rose, Mormon tea, spanish dagger and cacti, is low, and occurs in general in a medium growth. There is a fair growth of native grass in all secs., which renders the land suitable for grazing purposes.

The Fern-Esplin earth tank is located in SE $\frac{1}{4}$ of SE $\frac{1}{4}$ of sec. 22, near Lange's Run. It is dry most of the year as it impounds only a small amount of water during the infrequent rains. The Spendlode tank, in NE $\frac{1}{4}$ of SW $\frac{1}{4}$ of sec. 9, receives a runoff from a larger area, and contains water during most of the year. There is also a small earth tank in the SE $\frac{1}{4}$ of SE $\frac{1}{4}$ of sec. 32, but it is usually dry.

There are no improved roads in the township, but there are several ungraded roads of fair travel facility and used by the stockmen of this region. The principal road is the Hurricane-Mt. Trumbull road, which extends northerly and southerly thru the central part of the Tp. A portion of the old Mt. Trumbull-Antelope wood road crosses secs. 1 and 12, but this is used very little at the present time.

Earl C. Presley has a homestead in the SE $\frac{1}{4}$ of NE $\frac{1}{4}$ of sec. 12, and has improvements consisting of house, small barn, a few outbuildings, and a small plot of cultivated ground. There are no other settlers in this township.

There are no indications of valuable mineral deposits. The mean magnetic declination is 16°E.

FINAL FIELD TESTS OF INSTRUMENTS.

Buff and Buff transit No. 16723
Horace M. Muscott, Surveyor.

Aug. 8, 1939;

At station in camp near center of sec. 16, T. 36 N., R. 9 W., latitude 36°31 $\frac{1}{2}$ ' N., longitude 113°16' W., examine the adjustments of Buff and Buff transit No. 16723 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with a true meridian determined by Polaris observation at this station on July 11, 1939, as described in field notes of survey of T. 37 N., R. 9 W., executed under this group, proceed as follows:

At 8h. 00m., a.m., app.t., set off 36°31 $\frac{1}{2}$ ' N. on the lat. arc; 16°18' N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of 16°14 $\frac{1}{2}$ ' N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off 16°12 $\frac{1}{2}$ ' N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within 1'30" of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such

condition throughout the surveys executed with same, which are described in the foregoing field notes.

Buff and Buff transit No.9984.
Claude F. Warner, Transitman.

Aug. 8, 1939;

At same station where the preceding test of instrument was made, examine the adjustments of Buff and Buff transit No.9984 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with the same true meridian, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}31\frac{1}{2}'$ N. on the lat. arc; $16^{\circ}18'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $16^{\circ}14\frac{1}{2}'$ N. on the decl. arc; which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $16^{\circ}12\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same, which are described in the foregoing field notes.

Young and Sons' transit No.8526.
Frank Motch, Public Land.Surveyor.

Aug. 8, 1939;

At same station where the two preceding instrument tests were made, examine the adjustments of Young and Sons' transit No.8526 and find no errors. Then, to test the solar apparatus of same by comparison of its indications with the same true meridian, proceed as follows:

At 8h. 00m., a.m., app.t., set off $36^{\circ}31\frac{1}{2}'$ N. on the lat. arc; $16^{\circ}18'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the lat. arc unchanged; observe the sun on the meridian and obtain a reading of $16^{\circ}14\frac{1}{2}'$ N. on the decl. arc, which agrees with computed decl. of the sun.

At 4h. 00m., p.m., app.t., with the lat. arc unchanged; set off $16^{\circ}12\frac{1}{2}'$ N. on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1'30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same, which are described in the foregoing field notes.

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FIELD ASSISTANTS
to
Frank Moteh, Public Land Surveyor.

NAMES	CAPACITY
Thorton Fitzhugh	Principal Assistant
Rulon F. Westover	Chainman
Stanley C. Turner	Flagman
Alfred Figueira Jr.	Cornerman
Frank Doner Jr.	Axeman
Winfield S. Wardell 3rd	Axeman

12

BOOK 4260

CERTIFICATE OF SURVEYOR

I, Frank Motch, Public Land Surveyor, HEREBY CERTIFY upon honor that, in pursuance of supplemental special instructions bearing date of the 30th day of April, 1936, received from the district cadastral engineer for Arizona, with assignment instructions dated April 11, 1939, I have surveyed part of the North boundary (on the 9th Std. Parallel N.), and part of the Subdivisional lines of Township 36 North, Range 9 West

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
March 7, 1940

Frank Motch
Public Land Surveyor

CERTIFICATE OF APPROVAL

Office of Supervisor of Surveys

10

The foregoing field notes of the survey of

executed by under special instructions dated and assignment instructions dated having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Supervisor of Surveys

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above described surveys is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys

13

RECORDED

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FIELD ASSISTANTS
to
Claude F. Warner, Transitman

NAMES	CAPACITY
Benjamin J. Mollette	Principal Assistant
Roy M. Clifton	Chainman
Ernest Crofford	Flagman
James Pearce	Cornerman
Dean Peterson	Axeman
Kenneth Carrick	Axeman
Wm. A. Reynolds	Axeman

74

4260

CERTIFICATE OF SURVEYOR

I, Claude F. Warner, Transitman, HEREBY CERTIFY upon honor that, in pursuance of supplemental special instructions bearing date of the 30th day of April, 1936, received from the district cadastral engineer for Arizona, with assignment instructions dated April 11, 1939, I have surveyed part of the North boundary (on the 9th Std. Parallel N.), and part of the Subdivisional lines of Township 36 North, Range 9 West

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona

Claude F. Warner

March 7, 1940

Transitman

CERTIFICATE OF APPROVAL

Office of Supervisor of Surveys

, 19

The foregoing field notes of the survey of

executed by, under special instructions dated, and assignment instructions dated, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Supervisor of Surveys

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above described surveys in

is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys

80
76

CERTIFICATE OF SURVEYOR

BOOK 4260

I, Horace M. Muscott, Surveyor, HEREBY CERTIFY upon honor that, in
pursuance of ^{supplemental} special instructions bearing date of the 30th day of April, 1936,
received from the district cadastral engineer for Arizona, with assignment
instructions dated April 11, 1939, I have surveyed part of the North boundary
(on the 9th Std. Parallel N.), and part of the Subdivisional lines
of Township 36 North, Range 9 West.

of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that said
survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
March 7, 1940

Horace M. Muscott
Surveyor.

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colo., October 26, 1942.

The foregoing field notes of the survey of the North boundary (on the 9th Std. Par-
allel North), and the Subdivisional lines of

Township 36 North, Range 9 West

of the Gila and Salt River Meridian, in the State of Arizona

executed by Horace M. Muscott, Surveyor; Claude F. Warner, Transitman;
and Frank Moteh, Public Land Surveyor.

^{supplemental} under special instructions dated April 30, 1936, for Group 210, Arizona, and assignment
instructions dated April 11, 1939, having been critically examined, and
the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey
therein described, are hereby approved.

Frank Johnson
Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~